

IBM i
7.3

Performance reference information



Note

Before using this information and the product it supports, read the information in [“Notices” on page 401.](#)

This edition applies to IBM i 7.3 (product number 5770-SS1) and to all subsequent releases and modifications until otherwise indicated in new editions. This version does not run on all reduced instruction set computer (RISC) models nor does it run on CISC models.

This document may contain references to Licensed Internal Code. Licensed Internal Code is Machine Code and is licensed to you under the terms of the IBM License Agreement for Machine Code.

© **Copyright International Business Machines Corporation 1998, 2015.**

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Contents

Reference information for Performance.....1

- Collection Services data files..... 1
 - Collection Services data files containing time interval data..... 1
 - Collection Services data files: QAPMAPPN..... 1
 - Collection Services data files: QAPMARMTRT..... 18
 - Collection Services data files: QAPMASYN..... 19
 - Collection Services data files: QAPMBSC.....20
 - Collection Services data files: QAPMBUS..... 23
 - Collection services data files: QAPMBUSINT.....25
 - Collection Services data files: QAPMCIOP..... 27
 - Collection Services data files: QAPMDDI..... 30
 - Collection Services data files: QAPMDIOP.....32
 - Collection Services data files: QAPMDISK..... 35
 - Collection Services data files: QAPMDISKRB..... 53
 - Collection Services data files: QAPMDOMINO..... 54
 - Collection Services data files: QAPMDPS.....58
 - Collection Services data files: QAPMECL..... 62
 - Collection Services data files: QAPMETH.....67
 - Collection Services data files: QAPMETHP..... 72
 - Collection Services data files: QAPMFRLY..... 74
 - Collection Services data files: QAPMHDLC..... 75
 - Collection Services data files: QAPMHTTPB..... 77
 - Collection Services data files: QAPMHTTPD..... 78
 - Collection Services data files: QAPMIDLC..... 80
 - Collection Services data files: QAPMIOPD.....82
 - Collection Services data files: QAPMISUM..... 87
 - Collection Services data files: QAPMJOBMI..... 95
 - Collection Services data files: QAPMJOBOS.....117
 - Collection Services data files: QAPMJOBOS and QAPMJOBL..... 125
 - Collection Services data files: QAPMJOBOSR..... 143
 - Collection Services data files: QAPMJOBWT..... 146
 - Collection Services data files: QAPMJOBWTD..... 147
 - Collection Services data files: QAPMJOBWTG..... 148
 - Collection Services data files: QAPMJSUM.....149
 - Collection Services data files: QAPMJVM..... 154
 - Collection Services data files: QAPMLAPD..... 156
 - Collection Services data files: QAPMLIOP..... 160
 - Collection Services data files: QAPMLPARH..... 161
 - Collection Services data files: QAPMMIOP..... 164
 - Collection Services data files: QAPMPOOL and QAPMPOOLL..... 169
 - Collection Services data files: QAPMPOOLB.....172
 - Collection Services data files: QAPMPOOLT..... 177
 - Collection Services data files: QAPMPPP.....179
 - Collection Services data files: QAPMRESP..... 180
 - Collection Services data files: QAPMSAP.....181
 - Collection Services data files: QAPMSHRMP..... 183
 - Collection Services data files: QAPMSMCMN..... 185
 - Collection Services data files: QAPMSMDSK..... 186
 - Collection Services data files: QAPMSMHTP..... 189
 - Collection Services data files: QAPMSMJMI.....191
 - Collection Services data files: QAPMSMJOS.....193

Collection Services data files: QAPMSMPOL.....	194
Collection Services data files: QAPMSMSYS.....	195
Collection Services data files: QAPMSNA.....	197
Collection Services data files: QAPMSNADS.....	209
Collection Services data files: QAPMSQLPC.....	210
Collection Services data files: QAPMSTND.....	213
Collection Services data files: QAPMSTNE.....	215
Collection Services data files: QAPMSTNL.....	216
Collection Services data files: QAPMSTNY.....	218
Collection Services data files: QAPMSYS and QAPMSYSL.....	220
Collection Services data files: QAPMSYSCPU.....	258
Collection Services data files: QAPMSYSPRC.....	259
Collection Services data files: QAPMSYSTEM.....	261
Collection Services data files: QAPMSYSVP.....	280
Collection Services data files: QAPMSYSWLC.....	282
Collection Services data files: QAPMTAPE.....	284
Collection Services data files: QAPMTCP.....	286
Collection Services data files: QAPMTCPIFC.....	288
Collection Services data files: QAPMUSRTNS.....	291
Collection Services data files: QAPMWASAPP.....	293
Collection Services data files: QAPMWASCFG.....	296
Collection Services data files: QAPMWASEJB.....	297
Collection Services data files: QAPMWASRSC.....	300
Collection Services data files: QAPMWASSVR.....	304
Collection Services data files: QAPMX25.....	307
Collection Services data files: Field data for configuration database files.....	310
Collection Services data files: QAPMCONF.....	310
Collection Services data files: QAPMHDWR.....	318
Collection Services database files: Field data for trace database files.....	324
Collection Services data files: System category and file relationships.....	324
Collection Services data files: Task type extender.....	327
Historical data files.....	330
Historical data configuration database files.....	331
Historical data files: QAPMHCONF.....	331
Historical data files: QAPMHBKTD.....	334
Historical data summary database files.....	335
Historical data files: QAPMHMCMN.....	335
Historical data files: QAPMHMDSK.....	336
Historical data files: QAPMHMISUM.....	338
Historical data files: QAPMHMJMI.....	346
Historical data files: QAPMHMJOS.....	347
Historical data files: QAPMHMPOL.....	349
Historical data files: QAPMHMSQLP.....	350
Historical data files: QAPMHMSYS.....	351
Historical data files: QAPMHMSYST.....	353
Historical data detailed database files.....	361
Historical data files: QAPMHDCOMM.....	361
Historical data files: QAPMHDDISK.....	363
Historical data files: QAPMHDJOBM.....	370
Historical data files: QAPMHDJOBO.....	379
Historical data files: QAPMHDPOL.....	384
Disk Watcher data files.....	385
Disk Watcher data files: QAPYDWINTI.....	385
Disk Watcher data files: QAPYDWOBJR.....	386
Disk Watcher data files: QAPYDWPGMR.....	387
Disk Watcher data files: QAPYDWRUNI.....	387
Disk Watcher data files: QAPYDWSTAT.....	389
Disk Watcher data files: QAPYDWTDER.....	392

Disk Watcher data files: QAPYDWTRC.....	392
Data files: File abbreviations.....	396
CL commands for performance.....	396
Notices.....	401
Programming interface information.....	402
Trademarks.....	402
Terms and conditions.....	403

Reference information for Performance

Additional reference materials related to performance.

Collection Services data files

You can generate database files from the collection objects maintained by Collection Services. Use this topic to find the names, descriptions and attributes of these database files.

Performance data is a set of information about the operation of a system (or network of systems) that can be used to understand response time and throughput. You can use performance data to make adjustments to programs, system attributes, and operations. These adjustments can improve response times and throughputs. Adjustments can also help you to predict the effects of certain changes to the system, operation, or program.

Collection Services collects performance data into a management collection object (*MGTCOL). The Create Performance Data (CRTPFRDTA) command processes data from that collection object and stores the result into performance database files.

Additional field information, such as number of bytes and buffer position, is available by using the Display File Field Description (DSPFFD) command. For example, type the following on any command line:

```
DSPFFD file(QSYS/QAPMCONF)
```

Related concepts

[Collection Services](#) Use Collection Services to collect performance data for later analysis.

Related reference

[Create Performance Data \(CRTPFRDTA\) command](#) See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

[Display File Field Description \(DSPFFD\) command](#) See the Display File Field Description (DSPFFD) command for information on how to display field information.

Collection Services data files containing time interval data

These files contain performance data that is collected each interval.

Collection Services data files: QAPMAPPN

This database file defines the fields in the Advanced Peer-to-Peer Networking (APPN) data file record.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval	PD (7,0)
ANTGU	Total number of transmission group (TG) updates processed	PD(11,0)
ATTGU	Cumulative time (in milliseconds) to process the TG updates	PD(11,0)

Field Name	Description	Attribute
ANTGUM	Number of TG updates that require one or more resources to be added to the topology database update (TDU) buffer	PD(11,0)
ANRATG	Number of resources added to TDU buffers due to TG update processing	PD(11,0)
ANTSTG	Number of TDUs sent as a result of initially creating a TDU buffer on behalf of TG updates	PD(11,0)
ANNTTG	Number of network nodes that had TDUs sent to them due to TDUs being created for TG update processing	PD(11,0)
ANNCTC	Total number of node congestion transition changes processed	PD(11,0)
ATNCTC	Cumulative elapsed time for processing congestion transition changes	PD(11,0)
ATRSNC	Number of times that topology routing services (TRS) entered into non-congested state	PD (11,0)
ATRSC	Number of times that TRS entered into congested state	PD (11,0)
ATNCS	Cumulative elapsed time (in milliseconds) that the system was in non-congested state	PD(11,0)
ATCS	Cumulative elapsed time (in milliseconds) that the system was in congested state	PD (11,0)
ATSCP	Number of TDUs sent as a result of initially creating a TDU buffer on behalf of node congestion processing	PD (11,0)
ANTSCP	Number of network nodes that had TDUs sent to them due to TDUs being created for node congestion processing	PD (11,0)
ANTDUP	Total number of received TDUs processed by this node	PD (11,0)
ATTDUP	Cumulative elapsed time for processing the received TDUs	PD (11,0)
ANNRTD	Number of new resources received in TDUs that cause resources to be added to the TDU buffer	PD (11,0)
ANORTN	Number of old resources received in TDUs that do not require a resource to be added to the TDU buffer	PD (11,0)
ANORTA	Number of old resources received in TDUs that do require resources to be added to the TDU buffer	PD (11,0)
ANTSRT	Number of TDUs sent as a result of initially creating a TDU buffer on behalf of processing a received TDU	PD (11,0)
ANNTST	Number of network nodes that had TDUs sent to them due to TDUs being created for processing received TDUs	PD (11,0)

Field Name	Description	Attribute
ACNTID	Network ID of the node that received the most TDUs within the interval	C (8)
ACCPNM	Control point (CP) name of the node that received the most TDUs within the interval	C (8)
ANTRFN	Number of TDUs received this interval by the node that received the most TDUs in the interval	PD (11,0)
ANITEP	Total number of initial topology exchanges processed by this node	PD (11,0)
ATPIE	Cumulative elapsed time for processing the initial exchange	PD (11,0)
ANTECT	Number of times the initial topology exchange caused the complete network node topology to be sent	PD (11,0)
ANTDE	Total number of entries in the entire topology database (this value is not a delta)	PD (11,0)
ANTERS	Number of resources (nodes and TGs) added to the TDU buffer due to initial topology exchange	PD (11,0)
ANTETS	Number of TDUs sent as a result of initial topology exchange	PD (11,0)
ANGCP	Number of times that obsolete topology entries were removed	PD (11,0)
ATGCP	Cumulative elapsed time for removing the obsolete topology entries	PD (11,0)
ANTEDG	Number of topology entries that were deleted	PD (11,0)
ANTGC	Number of TDUs that were sent when obsolete topology entries were deleted	PD (11,0)
ANNTGC	Number of network nodes that had TDUs sent to them when obsolete topology entries were removed	PD (11,0)
ANRRP	Total number of registration requests processed	PD (11,0)
ANNLRR	Total number of locations processed with the registration requests	PD (11,0)
ATPRR	Cumulative elapsed time to process registration requests	PD (11,0)
ANDRP	Total number of deletion requests processed	PD (11,0)
ANLDDR	Total number of locations deleted with deletion requests	PD (11,0)
ATPDR	Cumulative elapsed time to process deletion requests	PD (11,0)
ANCNAP	Total number of requests to change network attributes processed	PD (11,0)
ATCNA	Cumulative elapsed time to process requests to change network attributes	PD (11,0)

Field Name	Description	Attribute
ANDDRC	Number of times the directory database was deleted and re-created due to processing the requests to change network attributes	PD (11,0)
ANLRSC	Number of location registration requests sent due to processing the requests to change network attributes	PD (11,0)
ANLDSC	Number of location deletion requests sent due to processing the requests to change network attributes	PD (11,0)
ANTDRC	Number of times the topology database was deleted and re-created due to processing the requests to change network attributes	PD (11,0)
ANCART	Number of times the requests to change network attributes caused a node entry resource to be added to the TDU buffer	PD (11,0)
ANTSTC	Number of TDUs sent as a result of initially creating a TDU buffer on behalf of requests to change network attributes	PD (11,0)
ANNTSC	Number of network nodes that had TDUs sent to them due to TDUs being created for processing requests to change network attributes	PD (11,0)
ANDAI	Number of times APPN information was displayed (DSPAPPNINF command)	PD (11,0)
ANLLUP	Total number of local location list updates processed	PD (11,0)
ATLLUP	Cumulative elapsed time to process the local location list updates	PD (11,0)
ANLRSL	Number of location registration requests sent due to local location list updates	PD (11,0)
ANLDLL	Number of location deletion requests sent due to local location list updates	PD (11,0)
ANRLUP	Total number of remote location list updates processed	PD (11,0)
ATRLUP	Cumulative elapsed time to process the remote location list updates	PD (11,0)
ANMDUP	Total number of mode description updates processed by APPN	PD (11,0)
ATMDUP	Cumulative elapsed time to process the mode description updates	PD (11,0)
ANCSUP	Total number of class-of-service updates processed by APPN	PD (11,0)
ATCSUT	Cumulative elapsed time to process the class-of-service (COS) update by TRS	PD (11,0)
ATCSUC	Cumulative elapsed time to process the COS update by the CPMGR task	PD (11,0)

Field Name	Description	Attribute
ANCSSA	Number of contention CP-CP session setups attempted	PD (11,0)
ANCSSS	Number of contention CP-CP session setups successful	PD (11,0)
ANRRS	Total number of registration requests sent	PD (11,0)
ANLRRR	Total number of locations registered with registration requests	PD (11,0)
ATSRR	Cumulative elapsed time to send registration requests	PD (11,0)
ANSTC	Number of single-hop route requests made to TRS for contention CP session setup	PD (11,0)
ANSTCS	Number of single-hop route requests made to topology routing services (TRS) for contention CP session setup that were successful	PD (11,0)
ATSTCS	Cumulative elapsed time for processing single-hop route requests on behalf of contention CP session setups	PD (11,0)
ANARMC	Number of activate-route requests made to MSCP for contention CP session setups	PD (11,0)
ANSARM	Number of successful activate-route requests processed by MSCP for contention CP session setups	PD (11,0)
ATARMC	Cumulative elapsed time for activate-route requests on behalf of contention CP session setups	PD (11,0)
ANTDSC	Number of requests made to the T2 SIOM to perform device selection on behalf of contention CP session setups	PD (11,0)
ATTDSC	Cumulative elapsed time for device selection processing to complete on behalf of contention CP session setups	PD (11,0)
ANDSS	Number of device selection requests that were successful on behalf of contention CP session setups	PD (11,0)
ATCCSA	Cumulative elapsed time for processing contention CP session activation requests	PD (11,0)
ANLSAP	Number of contention CP session activations processed	PD (11,0)
ANCST	Number of contention CP-CP session ends	PD (11,0)
ATCST	Cumulative elapsed time for processing contention CP-CP session ends	PD (11,0)
ANLST	Number of contention CP-CP session ends	PD (11,0)
ATLST	Cumulative elapsed time for processing contention CP-CP session ends	PD (11,0)

Field Name	Description	Attribute
ANCWSA	Number of winning CP-CP sessions currently active (this is not a delta)	PD (11,0)
ANCLSA	Number of losing CP-CP sessions currently active (this is not a delta)	PD (11,0)
ANCDRR	Number of data-received requests processed (CP capabilities)	PD (11,0)
ANCBDR	Number of bytes of data received (CP capabilities)	PD (11,0)
ATCDRR	Cumulative elapsed time for processing the data-received requests (CP capabilities)	PD (11,0)
ANCSDR	Number of send-data requests processed (CP capabilities)	PD (11,0)
ANCBDS	Number of bytes of data sent through the send-data requests (CP capabilities)	PD (11,0)
ATCSDR	Cumulative elapsed time for processing the send-data requests (CP capabilities)	PD (11,0)
ANTDRR	Number of data-received requests processed (topology database update)	PD (11,0)
ANTBDR	Number of bytes of data received (topology database update)	PD (11,0)
ATTDRR	Cumulative elapsed time for processing the data-received requests (topology database update)	PD (11,0)
ANTSDR	Number of send-data requests processed (topology database update)	PD (11,0)
ANTBDS	Number of bytes of data sent through the send-data requests (topology database update)	PD (11,0)
ATTSDR	Cumulative elapsed time for processing the send-data requests (topology database update)	PD (11,0)
ANDDRR	Number of data-received requests processed (directory search)	PD (11,0)
ANDBDR	Number of bytes of data received (directory search)	PD (11,0)
ATDDRR	Cumulative elapsed time for processing the data-received requests (directory search)	PD (11,0)
ANDSDR	Number of send-data requests processed (directory search)	PD (11,0)
ANBDS	Number of bytes of data sent by send-data requests (directory search)	PD (11,0)
ATDSDR	Cumulative elapsed time for processing send-data requests (directory search)	PD (11,0)
ANRDRR	Number of data-received requests processed (registration/deletion)	PD (11,0)
ANRBDR	Number of bytes of data received (registration/deletion)	PD (11,0)

Field Name	Description	Attribute
ATRDRR	Cumulative elapsed time for processing data-received requests (registration/deletion)	PD (11,0)
ANRSDR	Number of send-data requests processed (registration/deletion)	PD (11,0)
ANRBDS	Number of bytes of data sent through send-data requests (registration/deletion)	PD (11,0)
ATRSDR	Cumulative elapsed time for processing send-data requests (registration/deletion)	PD (11,0)
Local system initiated sessions		
ANWAP1	Total number of work activities of this type processed	PD (11,0)
ATWAP1	Cumulative elapsed time to complete work activities of this type	PD (11,0)
ATWAS1	Total number of work activities of this type that yielded a successful result	PD (11,0)
ASSA1	Number of session setup attempts satisfied through an existing APPN session	PD (11,0)
AASNA1	Number of APPC session requests satisfied by using non-APPN device descriptions	PD (11,0)
ASPAC1	Number of session setup requests that require APPN control point services for directory, route selection, and device selection processing	PD (11,0)
ASPSP1	Number of session setup requests that are placed in pending due to another session setup being in progress for the same local location, remote location, and mode	PD (11,0)
ASLNS1	Number of searches that the local end node satisfied locally (that is, without sending a search to its network node (NN) server)	PD (11,0)
AS1HS1	Number of one-hop search requests sent by the end node (EN)	PD (11,0)
A1HSS1	Number of searches satisfied by the end node by sending one-hop search requests	PD (11,0)
ASSBN1	Number of searches satisfied by sending a bind directly to an attached network node server (because the end node has no CP-CP session to a server)	PD (11,0)
ASFNS1	Number of searches that failed because of no network services being available for the local end node	PD (11,0)
ATILP1	Cumulative elapsed time required for the locate phase initiated by the end node to complete	PD (11,0)

Field Name	Description	Attribute
ANSSL1	Number of searches satisfied locally (using the topology database or the directory services (DS) database and finding an entry for an end node that does not support CP sessions)	PD (11,0)
ANIHS1	Number of one-hop search requests sent by the network node	PD (11,0)
ANSS11	Number of searches satisfied by the network node by sending one-hop search requests	PD (11,0)
ANDSS1	Number of directed searches sent	PD (11,0)
ASSDS1	Number of searches that were satisfied by sending directed searches	PD (11,0)
ATDSR1	Cumulative elapsed time for directed search responses to be received	PD (11,0)
ANDBE1	Number of domain broadcasts that have been run	PD (11,0)
ANNDB1	Number of nodes that these domain broadcasts have been sent to	PD (11,0)
ATRDB1	Cumulative elapsed time for the first positive response to be returned on domain broadcasts	PD (11,0)
ATLRD1	Cumulative elapsed time for the last response to be returned on domain broadcasts	PD (11,0)
ASSDB1	Number of searches that were satisfied by sending a domain broadcast	PD (11,0)
ANBSE1	Number of broadcast searches that have been run	PD (11,0)
ANNBS1	Number of adjacent nodes that these broadcast searches have been sent to	PD (11,0)
ATRBS1	Cumulative elapsed time for the first positive response to be returned on broadcast searches	PD (11,0)
ATLRB1	Cumulative elapsed time for the last response to be returned on broadcast searches	PD (11,0)
ANSBS1	Number of searches that were satisfied by sending a broadcast search	PD (11,0)
ATSPR1	Cumulative elapsed time from the start of search processing on the local node until a positive response has been returned to the local user	PD (11,0)
ATSPC1	Cumulative elapsed time from the start of search processing until the local directory services task has completed all processing for the request. This measurement takes into account the time required to process domain broadcast or broadcast search responses even though a positive response has already been sent back to the local user	PD (11,0)
AN1HT1	Number of single-hop route requests made to topology routing services (TRS)	PD (11,0)

Field Name	Description	Attribute
AS1HT1	Number of single-hop route requests made to TRS that were successful	PD (11,0)
AT1HC1	Cumulative elapsed time for processing single-hop route requests	PD (11,0)
ANRRT1	Number of request-route requests made to TRS	PD (11,0)
ASRRT1	Number of request-route requests made to TRS that were successful	PD (11,0)
ATTRT1	Cumulative elapsed time for processing request-route requests	PD (11,0)
AARRM1	Number of activate-route requests made to machine services control point (MSCP)	PD (11,0)
AARCV1	Number of activate-route requests that require a controller description to be automatically created and/or varied on by the system	PD (11,0)
ATRCV1	Cumulative elapsed time for automatic creation and/or vary on of the controller to be processed	PD (11,0)
ASARR1	Number of successful activate-route requests processed by MSCP	PD (11,0)
ATARP1	Cumulative elapsed time for processing activate-route requests by MSCP	PD (11,0)
ARDS1	Number of requests made to the T2 SIOM to perform device selection	PD (11,0)
ATDS1	Cumulative elapsed time for device selection processing to complete	PD (11,0)
ADSS1	Number of device selection requests that were successful	PD (11,0)
Receiver of search requests as an end node		
ANWAP2	Total number of work activities of this type processed	PD (11,0)
ATWAP2	Cumulative elapsed time to complete work activities of this type	PD (11,0)
ATWAS2	Total number of work activities of this type that yielded a successful result	PD (11,0)
Network node performing search requests on behalf of an end node		
ANWAP3	Total number of work activities of this type processed	PD (11,0)
ATWAP3	Cumulative elapsed time to complete work activities of this type	PD (11,0)
ATWAS3	Total number of work activities of this type that yielded a successful result	PD (11,0)

Field Name	Description	Attribute
ANSSL3	Number of searches satisfied locally (by referring to the topology database or by using the directory services database and finding an entry for an end node that does not support control point sessions)	PD (11,0)
ANIHS3	Number of one-hop search requests sent by the network node	PD (11,0)
ANSS13	Number of searches satisfied by the network node by sending one-hop search requests	PD (11,0)
ANDSS3	Number of directed searches sent	PD (11,0)
ASSDS3	Number of searches that were satisfied by sending directed searches	PD (11,0)
ATDSR3	Cumulative elapsed time for directed search responses to be received	PD (11,0)
ANDBE3	Number of domain broadcasts that have been run	PD (11,0)
ANNDB3	Number of nodes that these domain broadcasts have been sent to	PD (11,0)
ATRDB3	Cumulative elapsed time for the first positive response to be returned on domain broadcasts	PD (11,0)
ATLRD3	Cumulative elapsed time for the last response to be returned on domain broadcasts	PD (11,0)
ASSDB3	Number of searches that were satisfied by sending a domain broadcast	PD (11,0)
ANBSE3	Number of broadcast searches that have been run	PD (11,0)
ANNBS3	Number of adjacent nodes that these broadcast searches have been sent to	PD (11,0)
ATRBS3	Cumulative elapsed time for the first positive response to be returned on broadcast searches	PD (11,0)
ATLRB3	Cumulative elapsed time for the last response to be returned on broadcast searches	PD (11,0)
ANSBS3	Number of searches that were satisfied by sending a broadcast search	PD (11,0)
ATSPR3	Cumulative elapsed time from the start of search processing on the local node until a response has been returned to the local user or remote system that initiated the search process on the local system	PD (11,0)
ATSPC3	Cumulative elapsed time from the start of search processing until the local directory services task has completed all processing for the request. This measurement takes into account the time required to process domain broadcast or broadcast search responses even though a positive response has already been sent back to the local user or remote system that initiated a search	PD (11,0)
ANRRT3	Number of request-route requests made to TRS	PD (11,0)

Field Name	Description	Attribute
ASRRT3	Number of request-route requests made to TRS that were successful	PD (11,0)
ATRRT3	Cumulative elapsed time for processing request-route requests	PD (11,0)
Intermediate node on a directed search request		
ANWAP4	Total number of work activities of this type processed	PD (11,0)
ATWAP4	Cumulative elapsed time to complete work activities of this type	PD (11,0)
ATWAS4	Total number of work activities of this type that yielded a successful result	PD (11,0)
Network node that is the destination node of a directed search request		
ANWAP5	Total number of work activities of this type processed	PD (11,0)
ATWAP5	Cumulative elapsed time to complete work activities of this type	PD (11,0)
ATWAS5	Total number of work activities of this type that yielded a successful result	PD (11,0)
ANSSL5	Number of searches satisfied locally (by referring to the topology database or by using the directory services database and finding an entry for an end node that does not support control point sessions)	PD (11,0)
ANIHS5	Number of one-hop search requests sent by the network node	PD (11,0)
ANSS15	Number of searches satisfied by the network node by sending one-hop search requests	PD (11,0)
ANDBE5	Number of domain broadcasts that have been run	PD (11,0)
ANNDB5	Number of nodes that these domain broadcasts have been sent to	PD (11,0)
ATRDB5	Cumulative elapsed time for the first positive response to be returned on domain broadcasts	PD (11,0)
ATLRD5	Cumulative elapsed time for the last response to be returned on domain broadcasts	PD (11,0)
ASSDB5	Number of searches that were satisfied by sending a domain broadcast	PD (11,0)
Network node processing a received-broadcast-search request		
ANWAP6	Total number of work activities of this type processed	PD (11,0)
ATWAP6	Cumulative elapsed time to complete work activities of this type	PD (11,0)
ATWAS6	Total number of work activities of this type that yielded a successful result	PD (11,0)

Field Name	Description	Attribute
ANSSL6	Number of searches satisfied locally (by referring to the topology database or by using the directory services database and finding an entry for an end node that does not support control point sessions)	PD (11,0)
ANIHS6	Number of one-hop search requests sent by the network node	PD (11,0)
ANSS16	Number of searches satisfied by the network node by sending one-hop search requests	PD (11,0)
ANDBE6	Number of domain broadcasts that have been run	PD (11,0)
ANNDB6	Number of nodes that these domain broadcasts have been sent to	PD (11,0)
ATRDB6	Cumulative elapsed time for the first positive response to be returned on domain broadcasts	PD (11,0)
ATLRD6	Cumulative elapsed time for the last response to be returned on domain broadcasts	PD (11,0)
ASSDB6	Number of searches that were satisfied by sending a domain broadcast	PD (11,0)
Network node processing a received-search request from a node in a non-IBM® i network		
ANWAP7	Total number of work activities of this type processed	PD (11,0)
ATWAP7	Cumulative elapsed time to complete work activities of this type	PD (11,0)
ATWAS7	Total number of work activities of this type that yielded a successful result	PD (11,0)
ANSSL7	Number of searches satisfied locally (by referring to the topology database or by using the directory services database and finding an entry for an end node that does not support control point sessions)	PD (11,0)
ANIHS7	Number of one-hop search requests sent by the network node	PD (11,0)
ANSS17	Number of searches satisfied by the network node by sending one-hop search requests	PD (11,0)
ANDSS7	Number of directed searches sent	PD (11,0)
ASSDS7	Number of searches that were satisfied by sending directed searches	PD (11,0)
ATDSR7	Cumulative elapsed time for directed search responses to be used	PD (11,0)
ANDBE7	Number of domain broadcasts that have been run	PD (11,0)
ANNDB7	Number of nodes that these domain broadcasts have been sent to	PD (11,0)
ATRDB7	Cumulative elapsed time for the first positive response to be returned on domain broadcasts	PD (11,0)

Field Name	Description	Attribute
ATLRD7	Cumulative elapsed time for the last response to be returned on domain broadcasts	PD (11,0)
ASSDB7	Number of searches that were satisfied by sending a domain broadcast	PD (11,0)
ANBSE7	Number of broadcast searches that have been run	PD (11,0)
ANNBS7	Number of adjacent nodes that these broadcast searches have been sent to	PD (11,0)
ATRBS7	Cumulative elapsed time for the first positive response to be returned on broadcast searches	PD (11,0)
ATLRB7	Cumulative elapsed time for the last response to be returned on broadcast searches	PD (11,0)
ANSBS7	Number of searches that were satisfied by sending a broadcast search	PD (11,0)
ATSPR7	Cumulative elapsed time from the start of search processing on the local node until a response has been returned to the remote system that initiated the search process on the local system	PD (11,0)
ATSPC7	Cumulative elapsed time from the start of search processing until the local directory services task has completed all processing for the request. This measurement takes into account the time required to process domain broadcast or broadcast search responses even though a positive response has already been sent back to the remote system that initiated a search	PD (11,0)
ANRRT7	Number of request-route requests made to topology routing services (TRS)	PD (11,0)
ASRRT7	Number of request-route requests made to topology routing services (TRS) that were successful	PD (11,0)
ATRRT7	Cumulative elapsed time for processing request-route requests	PD (11,0)
Network node processing a received-bind request from a node in the IBM i network without routing information		
ANWAP8	Total number of work activities of this type processed	PD (11,0)
ATWAP8	Cumulative elapsed time to complete work activities of this type	PD (11,0)
ATWAS8	Total number of work activities of this type that yielded a successful result	PD (11,0)
ASPSP8	Number of session setup requests that are placed in pending status due to another session setup being in progress for the same local location, remote location, and mode	PD (11,0)

Field Name	Description	Attribute
ANSSL8	Number of searches satisfied locally (by referring to the topology database or by using the directory services database and finding an entry for an end node that does not support control point sessions)	PD (11,0)
ANIHS8	Number of one-hop search requests sent by the network node	PD (11,0)
ANSS18	Number of searches satisfied by the network node by sending one-hop search requests	PD (11,0)
ANDSS8	Number of directed searches sent	PD (11,0)
ASSDS8	Number of searches that were satisfied by sending directed searches	PD (11,0)
ATDSR8	Cumulative elapsed time for directed search responses to be used	PD (11,0)
ANDBE8	Number of domain broadcasts that have been run	PD (11,0)
ANNDB8	Number of nodes that these domain broadcasts have been sent to	PD (11,0)
ATRDB8	Cumulative elapsed time for the first positive response to be returned on domain broadcasts	PD (11,0)
ATLRD8	Cumulative elapsed time for the last response to be returned on domain broadcasts	PD (11,0)
ASSDB8	Number of searches that were satisfied by sending a domain broadcast	PD (11,0)
ANBSE8	Number of broadcast searches that have been run	PD (11,0)
ANNBS8	Number of adjacent nodes that these broadcast searches have been sent to	PD (11,0)
ATRBS8	Cumulative elapsed time for the first positive response to be returned on broadcast searches	PD (11,0)
ATLRB8	Cumulative elapsed time for the last response to be returned on broadcast searches	PD (11,0)
ANSBS8	Number of searches that were satisfied by sending a broadcast search	PD (11,0)
ATSPR8	Cumulative elapsed time from the start of search processing on the local node until a response has been returned to the local system to allow the bind processing to continue	PD (11,0)
ATSPC8	Cumulative elapsed time from the start of search processing until the local directory services task has completed all processing for the request. This measurement takes into account the time required to process domain broadcast or broadcast search responses even though a positive response has already been sent back to the local system to allow the bind processing to continue	PD (11,0)
ANRRT8	Number of request-route requests made to topology routing services (TRS)	PD (11,0)

Field Name	Description	Attribute
ASRRT8	Number of request-route requests made to TRS that were successful	PD (11,0)
ATRRT8	Cumulative elapsed time for processing request-route requests	PD (11,0)
AARRM8	Number of activate-route requests made to machine services control point (MSCP)	PD (11,0)
AARCV8	Number of activate-route requests that require a controller description to be automatically created and/or varied on by the system	PD (11,0)
ATRCV8	Cumulative elapsed time for automatic creation and/or vary on of the controller to be processed	PD (11,0)
ASARR8	Number of successful activate-route requests processed by MSCP	PD (11,0)
ATARP8	Cumulative elapsed time for processing activate-route requests by MSCP	PD (11,0)
Network node processing a received-bind request from a node in a non-IBM i network without routing information		
ANWAP9	Total number of work activities of this type processed	PD (11,0)
ATWAP9	Cumulative elapsed time to complete work activities of this type	PD (11,0)
ATWAS9	Total number of work activities of this type that yielded a successful result	PD (11,0)
ASPSP9	Number of session setup requests that are placed in pending status due to another session setup being in progress for the same local location, remote location, and mode	PD (11,0)
ANSSL9	Number of searches satisfied locally (by referring to the topology database or by using the directory services database and finding an entry for an end node that does not support control point sessions)	PD (11,0)
ANIHS9	Number of one-hop search requests sent by the network node	PD (11,0)
ANSS19	Number of searches satisfied by the network node by sending one-hop search requests	PD (11,0)
ANDSS9	Number of directed searches sent	PD (11,0)
ASSDS9	Number of searches that were satisfied by sending directed searches	PD (11,0)
ATDSR9	Cumulative elapsed time for directed search responses to be received	PD (11,0)
ANDBE9	Number of domain broadcasts that have been run	PD (11,0)
ANND9	Number of nodes that these domain broadcasts have been sent to	PD (11,0)

Field Name	Description	Attribute
ATRDB9	Cumulative elapsed time for the first positive response to be returned on domain broadcasts	PD (11,0)
ATLRD9	Cumulative elapsed time for the last response to be returned on domain broadcasts	PD (11,0)
ASSDB9	Number of searches that were satisfied by sending a domain broadcast	PD (11,0)
ANBSE9	Number of broadcast searches that have been run	PD (11,0)
ANNBS9	Number of adjacent nodes that these broadcast searches have been sent to	PD (11,0)
ATRBS9	Cumulative elapsed time for the first positive response to be returned on broadcast searches	PD (11,0)
ATLRB9	Cumulative elapsed time for the last response to be returned on broadcast searches	PD (11,0)
ANSBS9	Number of searches that were satisfied by sending a broadcast search	PD (11,0)
ATSPR9	Cumulative elapsed time from the start of search processing on the local node until a response has been returned to the local system to allow bind processing to continue	PD (11,0)
ATSPC9	Cumulative elapsed time from the start of search processing until the local directory services task has completed all processing for the request. This measurement takes into account the time required to process domain broadcast or broadcast search responses even though a positive response has already been sent back to the local system to allow bind processing to continue	PD (11,0)
ANRRT9	Number of request-route requests made to topology routing services (TRS)	PD (11,0)
ASRRT9	Number of request-route requests made to TRS that were successful	PD (11,0)
ATRRT9	Cumulative elapsed time for processing request-route requests	PD (11,0)
AARRM9	Number of activate-route requests made to machine services control point (MSCP)	PD (11,0)
AARCV9	Number of activate-route requests that require a controller description to be automatically created and/or varied on by the system	PD (11,0)
ATRCV9	Cumulative elapsed time for automatic creation and/or vary on of the controller to be processed	PD (11,0)
ASARR9	Number of successful activate-route requests processed by MSCP	PD (11,0)
ATARP9	Cumulative elapsed time for processing activate-route requests by MSCP	PD (11,0)

Field Name	Description	Attribute
Network node processing a received-bind request from a node in the IBM i network with routing information		
ANWAPA	Total number of work activities of this type processed	PD (11,0)
ATWAPA	Cumulative elapsed time to complete work activities of this type	PD (11,0)
ATWASA	Total number of work activities of this type that yielded a successful result	PD (11,0)
ASPSA	Number of session setup requests that are placed in pending status due to another session setup being in progress for the same local location, remote location, and mode triplet	PD (11,0)
AARRMA	Number of activate-route requests made to machine services control point (MSCP)	PD (11,0)
AARCV A	Number of activate-route requests that require a controller description to be automatically created and/or varied on by the system	PD (11,0)
ATRCVA	Cumulative elapsed time for automatic creation and/or vary on of the controller to be processed	PD (11,0)
ASARRA	Number of successful activate-route requests processed by MSCP	PD (11,0)
ATARPA	Cumulative elapsed time for processing activate-route requests by MSCP	PD (11,0)
Network node processing a received-bind request from a node in a non-IBM i network with routing information		
ANWAPB	Total number of work activities of this type processed	PD (11,0)
ATWAPB	Cumulative elapsed time to complete work activities of this type	PD (11,0)
ATWASB	Total number of work activities of this type that yielded a successful result	PD (11,0)
ASPSB	Number of session setup requests that are placed in pending status due to another session setup being in progress for the same local location, remote location, and mode triplet	PD (11,0)
AARRMB	Number of activate-route requests made to machine services control point (MSCP)	PD (11,0)
AARCVB	Number of activate-route requests that require a controller description to be automatically created and/or varied on by the system	PD (11,0)
ATRCVB	Cumulative elapsed time for automatic creation and/or vary on of the controller to be processed	PD (11,0)
ASARRB	Number of successful activate-route requests processed by MSCP	PD (11,0)

Field Name	Description	Attribute
ATARPB	Cumulative elapsed time for processing activate-route requests by MSCP	PD (11,0)
DATETIME	Interval date and time: The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp

Related reference

[Collection Services data files: System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

[Data files: File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

[Create Performance Data \(CRTPFRDTA\) command](#) See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMARMTRT

This database file contains information about Application Response Measurement (ARM) transaction types that are reported in the QAPMUSRTNS file.

This optional secondary file is created only when the system collects performance data for ARM transactions. The QAPMARMTRT file contains one record for each ARM transaction type that is known to the system.

Applications use ARM APIs to provide information about the progress of application-level transactions. If ARM transactions are enabled on a system, performance data for the ARM transactions from ARM applications and middleware is reported in the QAPMUSRTNS file.

You can identify the ARM transaction type by a combination of the ARM application name and the ARM application group name.

The ARM transaction type name has a prefix of "QARM" followed by a 16-character representation of an 8-byte internal ARM transaction type ID.

Field Name	Description	Attribute
ATTYP	ARM transaction type.	C (20)
ATANAME	ARM application name. Note: This field is in Unicode.	G (127)
ATAGNAME	ARM application group name. Note: This field is in Unicode.	G (255)

Field Name	Description	Attribute
Note:		
<ol style="list-style-type: none"> 1. The QAPMUSRTNS file contains specific data for the first 15 transaction types for each job being reported. The rest of the data is combined in the *OTHER transaction type. However, the QAPMARMTRT file contains records for all ARM transaction types that are known to the system. 2. The ARM APIs are shipped in a disabled state. For information on how to enable ARM APIs on a system, see Enable ARM on IBM-instrumented applications. 3. Different ARM-instrumented applications and middleware products might require specific configuration steps to enable the ARM instrumentation. 4. ARM transaction data is reported only for applications which call the ARM API implementation that is shipped with the operating system. 		

Related reference

Collection Services data files: [QAPMUSRTNS](#)

This database file contains performance data for the user-defined and Application Response Measurement (ARM) transactions.

[Enable ARM on IBM-instrumented applications](#) See the [Enable ARM on IBM-instrumented applications](#) topic for information on how to information on how to enable ARM APIs on a system.

Collection Services data files: [System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: [File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

[Create Performance Data \(CRTPFRDTA\) command](#) See the [Create Performance Data \(CRTPFRDTA\) command](#) for information on how to create performance database files.

Collection Services data files: QAPMASYN

This database file includes asynchronous file entries and lists the fields in the asynchronous file.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
IOPRN	IOP resource name.	C (10)
AIOPID	Reserved	C (1)
ASTYPE	The resource type of the IOP or adapter represented by this record.	C (4)
ASLND	Line description: The name of the description for this line.	C (10)
ASLSP	Line speed: The speed of this line in bits per second (bps.)	PD (11,0)

Field Name	Description	Attribute
ASBTRN	Number of bytes transmitted (data and control characters) including bytes transmitted again because of errors.	PD (11,0)
ASBRCV	Number of bytes received (data and control characters), including characters received in error.	PD (11,0)
ASPRCL	Protocol type: A for asynchronous.	C (1)
ASPDUR	The total number of protocol data units received.	PD (11,0)
ASPDUE	The total number of protocol data units received with parity and stop bit errors.	PD (11,0)
ASPDUT	The total number of protocol data units successfully transmitted and the data-circuit ending equipment (DCE) acknowledged.	PD (11,0)
ASDUP	The duplex state of the line. For some lines, this value might change over time. This field can have the following values: <ul style="list-style-type: none"> • Blank - The duplex state is not known. • F - Full duplex. the line can simultaneously transmit and receive data. • H - Half duplex. The line can either transmit data or receive data, but the line cannot simultaneously transmit and receive data. 	C (1)
ASPORT	Reserved	C (10)
DATETIME	Interval date and time: The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp

Related reference

[Collection Services data files: System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

[Data files: File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

[Create Performance Data \(CRTPFRDTA\) command](#) See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMBSC

This database file includes binary synchronous file entries and lists the fields in the binary synchronous file.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)

Field Name	Description	Attribute
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
IOPRN	IOP resource name.	C(10)
BIOPID	Reserved	C (1)
BSTYPE	The resource type of the IOP or adapter represented by this record.	C (4)
BSLND	Line description: The name of the description for this line.	C (10)
BSLSP	Line speed: The speed of the line in bits per second (bps).	PD (11,0)
BSBTRN	Bytes transmitted: The number of bytes (data and control characters) transmitted, including bytes transmitted again.	PD (11,0)
BSBRCV	Bytes received: The number of bytes (data and control characters) received including bytes received in error.	PD (11,0)
BSPRCL	Protocol type: B for binary synchronous.	C (1)
BSDCRV	Data characters received: The number of data characters received successfully (excluding synchronous characters) while in data mode. For feature types 2507 and 6150, this value is equal to field BSBRCV.	PD (11,0)
BSDCRE	Data characters received in error: The number of data characters received with a block-check character error while in data mode. For feature types 2507 and 6150, this value is equal to field BSCRER.	PD (11,0)
BSDCTR	Data characters transmitted: The number of data characters transmitted successfully while in data mode. For feature types 2507 and 6150, this value is equal to field BSBTRN.	PD (11,0)
BSCRER	Characters received in error: The number of characters received with a block-check character error.	PD (11,0)
BSLNK	Negative acknowledgment character received to text sent (see note). The number of times the remote station or device did not understand the command sent from the host system.	PD (11,0)
BSLWA	Wrong acknowledgment character to text sent (see note). The host system received an acknowledgment from the remote device that was not expected. For example, the system expected an ACK0 and received an ACK1.	PD (11,0)

Field Name	Description	Attribute
BSLQTS	Enqueue to text sent (see note): Text was sent by a station and an ENQ character was returned. The receiving station expected some form of acknowledgment, such as an ACK0, ACK1, or NAK.	PD (11,0)
BSLINV	Invalid (unrecognized format): One of the delimiter characters that encloses the data in brackets being sent/received is not valid (see note).	PD (11,0)
BSLQAK	Enqueue to acknowledged character: The remote station returned an acknowledgment (for example, ACK0) and the host system sent an ENQ character. This indicates that the host station did not recognize the acknowledgment as a valid acknowledgment (see note).	PD (11,0)
BSLTNK	Negative acknowledgment character received to text sent (total): The number of times the remote station did not understand the command sent from the host system (see note).	PD (11,0)
BSLTWA	Wrong acknowledgment character to text sent (total): The host system received an acknowledgment from the remote device that was not expected. For example, the host system expected an ACK0 and received an ACK1 (see note).	PD (11,0)
BSLTQT	Enqueue to text sent (total): Text was sent by a station and an ENQ character was returned. The receiving station expected some form of acknowledgment such as an ACK0, ACK1, or NAK (see note).	PD (11,0)
BSLTIV	Invalid (unrecognized format) (total): One of the delimiter characters that enclose the data in brackets being sent/received is not valid (see note).	PD (11,0)
BSLTQA	Enqueue to acknowledged character (total): The remote station returned an acknowledgment (for example, ACK0) and the host station sent an ENQ character. This indicates that the host station did not recognize the acknowledgment as a valid acknowledgment (see note).	PD (11,0)
BSLDRA	Disconnect received: The remote station issued a disconnect with abnormal end. This could occur when error recovery did not succeed or the binary synchronous job was ended.	PD (11,0)
BSLEAB	End of transmission (EOT) received (abnormal end): Similar to a disconnect.	PD (11,0)
BSLDFA	Disconnect received (forward abnormal end): The host station issued a disconnect with abnormal end. This could occur when the error recovery did not succeed, or the binary synchronous job was ended.	PD (11,0)

Field Name	Description	Attribute
BSLEFA	EOT received (forward abnormal end): Similar to a disconnect.	PD (11,0)
BSLDBT	Number of data blocks transmitted.	PD (11,0)
BSLDBR	Number of data blocks received.	PD (11,0)
BSLBKR	Number of data blocks transmitted again.	PD (11,0)
BSLBKE	Number of data blocks received in error.	PD (11,0)
BSLTRT	Total number of characters transmitted again, including control characters.	PD (11,0)
BSLDRT	Total number of data characters transmitted again.	PD (11,0)
BSPORT	Reserved	C (10)
DATETIME	Interval date and time: The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp

Note: The counters BSLNK through BSLQAK are error recovery counters and are increased the first time the error is detected. The counters BSLTNK and BSLTQA are error recovery counters and are increased every time the error occurs. The same errors are being counted in each set of counters, so the first set indicates how many times an error was detected and the second set indicates how many retries it took to recover from the errors.

Related reference

[Collection Services data files: System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

[Data files: File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

[Create Performance Data \(CRTPFRDTA\) command](#) See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMBUS

This database file contains data for external system buses.

Support for a particular bus as well as what metrics are supported for that bus is dependent on the type of bus, how that bus connects to the system, and if assigned to the partition.

Historically, records were produced for all PCI buses even though data was instrumented only for bus usage within the collecting partition. For that situation now, data is captured only for those buses that have had activity within the collecting partition.

For newer technologies, the hardware may provide additional instrumentation. Hardware metrics represent bus usage by all partitions. Consequently, the collecting partition must be authorized to obtain this data (reference the "Allow performance information collection" option within the HMC partition configuration). If the collecting partition is authorized, buses that support hardware metrics are reported independent of partition assignments.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
BUIOPB	System bus number. Bus numbering begins with one. Before V4R5, bus numbering began at zero.	PD (5,0)
BUOPSR	Number of OPSTARTs received: RRCB in server storage.	PD (11,0)
BUSGLR	Signals received.	PD (11,0)
BUOPSS	Number of OPSTARTs sent.	PD (11,0)
BUSGLS	Signals sent.	PD (11,0)
BURSTQ	Restart queues sent.	PD (11,0)
BUBNAR	Occurrences of BNA received.	PD (11,0)
BUTPKT	Total packets (sent or received).	PD (11,0)
BUKBYO	Kilobytes DMAed out.	PD (11,0)
BUKBYI	Kilobytes DMAed in.	PD (11,0)
BUNOSR	Normal flow OPSTARTs received.	PD (11,0)
BUNRDR	Reserved.	PD (11,0)
BUORQS	OPSTART requests sent.	PD (11,0)
BUTIMO	Reserved.	PD (11,0)
BUBNAS	Reserved.	PD (11,0)
BUQSAS	Queue space available sent.	PD (11,0)
BUTYPE	Bus type. Supported values include: <ul style="list-style-type: none"> • 'S' = SPD Bus (no longer supported) • 'P' = PCI bus • 'V' = Virtual bus 	C (1)
BUCAT	Bus category. This field indicates if this bus record has some special characteristics, which may require a special interpretation of its performance data. Each bit in this field has an independent meaning: <ul style="list-style-type: none"> • X'00' = no special category applies • X'01' = this bus is attached to an I/O hub • X'02' = This record represents a switch. The data reported is the sum of all buses under the switch. The bus number reported is the first bus under the switch. 	BINCHAR (1)

Field Name	Description	Attribute
BUHUB	Hub number. If this bus is associated with an I/O hub, this is the number of that hub. Note: an I/O hub may be imbedded in the backplane	B (9,0)
BUMAXRATE	Maximum byte rate. When available from hardware, this is the estimated maximum rate that data may be both sent and received in bytes per second through the hardware port.	B (18,0)
BUCBSND	Command bytes sent. When available from hardware, this is the number of command bytes sent through the hardware port.	B (18,0)
BUDBSND	Data bytes sent. When available from hardware, this is the number of data bytes sent through the hardware port.	B (18,0)
BUCBRCV	Command bytes received. When available from hardware, this is the number of command bytes received through the hardware port.	B (18,0)
BUDBRCV	Data bytes received. When available from hardware, this is the number of data bytes received through the hardware port.	B (18,0)
DATETIME	Interval date and time: The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp

Related reference

Collection services data files: QAPMBUSINT

This file contains data for internal system buses.

Collection Services data files: System category and file relationships

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: File abbreviations

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRDTA) command See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection services data files: QAPMBUSINT

This file contains data for internal system buses.

The metrics supported are dependent on the instrumentation within the hardware chips. Support for a particular bus is dependent on both the type of bus as well as the chip family.

There may be one or more records each interval for a reported bus. The number of records as well as the metrics supported are dependent on both bus type and chip type.

These metrics are instrumented in the hardware and represent bus usage by all partitions. The collecting partition must be authorized to obtain this data (reference the "Allow performance information collection" option within the HMC partition configuration).

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DATETIME	Interval date and time. The date and time of the sample interval, expressed in local system time.	Timestamp
INTSEC	Elapsed interval seconds. The number of seconds since the last sample interval.	PD (7, 0)
BUNBR	Bus number. The hardware assigned number associated with the bus or hub.	B (9, 0)
BUTYPE	Bus type. Supported bus types are: <ul style="list-style-type: none"> • 4 - 12X Loop • 6 - I/O hub (may be imbedded in the backplane) 	B (4, 0)
BUDFMT	Bus data format. This field is being provided to help understand what data is instrumented by the hardware components of the bus should there be future differences.	Char (4)
BUATTR1	Bus attribute 1. The meaning of this field depends on the bus type (BUTYPE field). <ul style="list-style-type: none"> • Type 4: Port identifier. One record will be present for each supported port <ul style="list-style-type: none"> 0 = even port 1 = odd port • Type 6: Category <ul style="list-style-type: none"> 0 = Topside port 	B (4, 0)
BUPKTSND	Packets sent. Note: Not supported for type 6.	B (18, 0)
BUPKTRCV	Packets received. Note: Not supported for type 6.	B (18, 0)
BUBYTESND	Bytes sent. Note: Not supported for type 4.	B (18, 0)
BUBYTERCV	Bytes received. Note: Not supported for type 4.	B (18, 0)
BUMAXRATE	Maximum byte rate. The estimated maximum rate that data may be both sent and received in bytes per second.	B (18, 0)
BUDATA1	The meaning of this field depends on the bus type (BUTYPE) field: <ul style="list-style-type: none"> • Type 4: Reserved • Type 6: Command bytes sent 	B (18, 0)

Field Name	Description	Attribute
BUDATA2	The meaning of this field depends on the bus type (BUTYPE) field: <ul style="list-style-type: none"> Type 4: Reserved Type 6: Command bytes received 	B (18, 0)
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp

Related reference

Collection Services data files: [QAPMBUS](#)

This database file contains data for external system buses.

Collection Services data files: [System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: [File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRDTA) command See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMCIOP

This database file includes communications IOP file entries and lists the fields in the communications IOP file.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
IOPRN	IOP resource name	C (10)
CIOP	Reserved	C (1)
CITYPE	The type of IOP described by this record.	C (4)
CTIPKT	Total packets transferred.	PD (11,0)
CIKBYO	Total KB transmitted from an IOP to the system across the bus.	PD (11,0)
CIKBYI	Total KB transmitted to the IOP from the system across the bus.	PD (11,0)
CIOPSR	OPSTART bus unit message received from another bus unit using normal flow.	PD (11,0)
CIOPSS	OPSTART bus unit message received from another bus unit using reverse flow method 2 (always 0).	PD (11,0)

Field Name	Description	Attribute
CISGLR	Signals received.	PD (11,0)
CIOPST	OPSTARTs sent.	PD (11,0)
CISLGS	Signals sent.	PD (11,0)
CIRSTQ	Restart queues sent.	PD (11,0)
CIRQDO	DMA requests sent for output of data: The number of requests the IOP sends to the system for data to be sent from the IOP to the system across the bus.	PD (11,0)
CIRQDI	DMA requests sent for input of data: The number of requests the IOP sends to the system for data to be sent to the IOP from the system across the bus.	PD (11,0)
CIBNAR	Occurrences of BNA received.	PD (11,0)
CIPRCU	Processor utilization: The number of fixed-time intervals that this communications IOP spent in the idle state.	PD (11,0)
CIIDLC	Idle loop count (see notes): The number of times the communications IOP ran an idle loop. This is done when the IOP has no work to perform. This count is used with the idle loop time to calculate the primary IOP processor utilization in seconds.	PD (11,0)
CIIDLT	Idle loop time (see notes): The time (in hundredths of microseconds) for the primary IOP processor to run the idle loop once.	PD (11,0)
CIRAMU	Available local storage (in bytes): The number of bytes of free local storage in the IOP. The free local storage will probably be non-contiguous because of fragmentation.	PD (11,0)
CISYSF	The total time (in milliseconds) used by the IOP for basic system function that is running in the primary IOP processor.	PD (11,0)
CICOMM	Combined processing time (in milliseconds) accounted for by all of the communication protocol tasks that are running in the primary IOP processor.	PD (11,0)
CISDLC	Processing time (in milliseconds) used by SDLC communications tasks that are running in the primary IOP processor.	PD (11,0)
CIASYN	Processing time (in milliseconds) used by asynchronous communications tasks that are running in the primary IOP processor.	PD (11,0)
CIBSC	Processing time (in milliseconds) used for bisynchronous protocol tasks that are running in the primary IOP processor.	PD (11,0)
CIX25L	Processing time (in milliseconds) used by X.25 LLC tasks that are running in the primary IOP processor.	PD (11,0)

Field Name	Description	Attribute
CIX25P	Processing time (in milliseconds) used by X.25 PLC tasks that are running in the primary IOP processor.	PD (11,0)
CIX25D	Time (in milliseconds) accounted for by X.25 DLC tasks that are running in the primary IOP processor.	PD (11,0)
CILAN	LAN communications time: Total processing unit time (in milliseconds) used by token-ring network, Ethernet, frame relay, and fiber distributed data interface (FDDI) communications tasks that are running in the primary IOP processor.	PD (11,0)
CILAP	Processing time (in milliseconds) used by ISDN LAPD, LAPE, and PMI tasks that are running in the primary IOP processor.	PD (11,0)
CIQ931	Processing time (in milliseconds) used by ISDN Q.931 tasks that are running in the primary IOP processor.	PD (11,0)
CIF1ID	Subfunction 1 ID: The identifier for addition functions that may be running in the primary IOP processor.	C (2)
CIF1TM	Subfunction 1 time: The total processing unit time (in milliseconds) used by the IOP function that is running in the primary IOP processor.	PD (11,0)
CICPU2	Processor time in milliseconds for the second IO processor, which handles specialized functions. This field applies to Integrated xSeries Servers (excluding I/O adapter versions) and wireless IOPs. This field is zero for other IOPs. Collection Services will not report values for Integrated xSeries Servers.	PD (11,0)

Note:

The idle loop count and time are used to calculate the communications IOP utilization as follows:

1. Convert the product of the idle loop count times the idle loop time from hundredths of microseconds to seconds. Subtract this from the interval time, and divide the results by the interval time. For example:

$$\text{IOP Utilization} = (\text{INTSEC} - (\text{CIIDLCL} * \text{CIIDLT}) / 10^{**8}) / \text{INTSEC}$$

2. The performance monitor reports I/O processor (IOP) statistics different beginning with Version 3 Release 7. Therefore, performance statistics for IOPs introduced in Version 3 Release 7 or later releases are reported in the QAPMMIOP file. Performance statistics are reported in the QAPMMIOP file even if the IOP supports only one of the three IOP functions (communications, disk, or local workstation). Performance statistics for IOPs that were introduced before Version 3 Release 7 will continue to be reported in the appropriate IOP file (QAPMCIOP, QAPMDIOP, QAPMLIOP, and QAPMMIOP).
3. The function 1 identifier is for additional functions that may be running in the primary IOP. Each function identifier has an associated function time value. The function identifier may have the following value:

Value	Description
00	No time value supplied

Value	Description
11	Integrated xSeries Server pipe task (Integrated xSeries Server was previously known as file server I/O processor and FSIOP)
42	Localtalk task
43	Wireless task

Related reference

[Collection Services data files: System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

[Data files: File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

[Create Performance Data \(CRTPFRDTA\) command](#) See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMDDI

This database file defines the fields in a distributed data interface (DDI) file record.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds.	PD (7,0)
IOPRN	IOP resource name.	C(10)
DDIOPI	Reserved	C (1)
DITYPE	The resource type of the IOP or adapter represented by this record.	C (4)
DDLND	Line description: The name of the description for this line.	C (10)
DDLSP	Line speed: The line speed expressed in bits per second (bps).	PD (11,0)
DLTFT	Total number of Type II frames transmitted.	PD (11,0)
DLTFR	Total number of Type II frames received.	PD (11,0)
DLIFT	Total number of I-frames transmitted.	PD (11,0)
DLIFR	Total number of I-frames received.	PD (11,0)
DLICT	Total number of I-frame character transmitted.	PD (11,0)
DLICR	Total number of I-frame characters received.	PD (11,0)
DLPRCL	Protocol type: C for DDI	C (1)
DLRFT	Total number of receive-not-ready frames transmitted.	PD (11,0)

Field Name	Description	Attribute
DLRFR	Total number of receive-not-ready frames received.	PD (11,0)
DLFFT	Total number of frame-reject (FRMR) frames transmitted.	PD (11,0)
DLFFR	Total number of frame-reject (FRMR) frames received.	PD (11,0)
DLRJFR	Number of reject frames received.	PD (11,0)
DLRJFT	Number of reject frames transmitted.	PD (11,0)
DLSFT	Number of set asynchronous balanced mode extended frames transmitted.	PD (11,0)
DLSFR	Number of set asynchronous balanced mode extended frames received.	PD (11,0)
DLDFR	Number of disconnect (DISC) frames transmitted.	PD (11,0)
DLDFR	Number of disconnect (DISC) frames received.	PD (11,0)
DLDMT	Number of disconnect mode (DM) frames transmitted.	PD (11,0)
DLDMR	Number of disconnect mode (DM) frames received.	PD (11,0)
DLN2R	N2 retries end count: This count is updated when the host has attempted to contact a station n times, and the T1 timer ended n times before the station responded.	PD (11,0)
DLT1T	T1 timer end count: Number of times the T1 ended. This count is updated when the host has attempted to contact a station n times, and the T1 timer ended n times before the station responded.	PD (11,0)
DMFRV	Number of MAC frames received.	PD (11,0)
DMFCC	Number of MAC frames copied.	PD (11,0)
DMFTR	Number of MAC frames transmitted.	PD (11,0)
DMTKN	Number of MAC tokens received.	PD (11,0)
DMERR	MAC error count.	PD (11,0)
DMLFC	Lost frame count.	PD (11,0)
DMTVX	TVX expiration count.	PD (11,0)
DMNCC	Not copied count.	PD (11,0)
DMLAT	MAC late count.	PD (11,0)
DLROP	Ring operation count.	PD (11,0)
DMABE	PortA elasticity buffer (EB) errors.	PD (11,0)
DMATF	PortA LCT count: count of consecutive times the confidence test (LCT) has failed.	PD (11,0)
DMALR	PortA reject count.	PD (11,0)
DMAEC	PortA link error monitor (LEM) count.	PD (11,0)

Field Name	Description	Attribute
DMBBE	PortB elasticity buffer (EB) errors.	PD (11,0)
DMBTF	PortB LCT count: count of consecutive times the confidence test (LCT) has failed.	PD (11,0)
DMBLR	PortB reject count.	PD (11,0)
DMBEC	PortB link error monitor (LEM) count.	PD (11,0)
DMANR	Address not recognized.	PD (11,0)
DMFNC	Frame not copied.	PD (11,0)
DMTKE	Reserved	PD (11,0)
DMDUP	Duplicate address count.	PD (11,0)
DMDFR	Discarded frame count.	PD (11,0)
DMTXU	Transmit underruns.	PD (11,0)
DMRER	Recoverable errors.	PD (11,0)
DMNER	Nonrecoverable errors.	PD (11,0)
DMSIN	Spurious interruptions.	PD (11,0)
DDPORT	Reserved	C (10)

Related reference

Collection Services data files: [System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: File abbreviations

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRDTA) command See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMDIOP

This database file contains storage device (disk) IOP file entries.

It lists the fields in the storage device IOP file. Consider the following information in these fields:

- Device means disk.
- The idle loop count and time are used to calculate the storage device controller IOP utilization as follows:

Convert the product of the idle loop count times the idle loop time from hundredths of microseconds to seconds. Subtract this from the interval time, and divide the result by the interval time. For example:

$$\text{IOP Utilization} = (\text{INTSEC} - (\text{DIIDLC} * \text{DIIDLT}) / 10^{**8}) / \text{INTSEC}$$

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)

Field Name	Description	Attribute
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
IOPRN	IOP resource name.	C (10)
DIIOF	Reserved	C (1)
DITYPE	IOP type.	C (4)
DIIDLK	Idle loop count: The number of times the disk controller IOP ran an idle loop. This is done when the IOP has no work to perform. This count is used with the idle loop time.	PD (11,0)
DIIDLK	Idle loop time: The time (in hundredths of microseconds) to run the idle loop once.	PD (11,0)
DITPDK	Total packets transferred.	PD (11,0)
DIKBYO	Total KB transmitted from the IOP to the system across the bus.	PD (11,0)
DIKBYI	Total KB transmitted to the IOP from the system across the bus.	PD (11,0)
DIOPSR	OPSTART bus unit message received from another bus unit using normal flow.	PD (11,0)
DIOPSS	OPSTART bus unit message received from another bus unit using reverse flow method 2 (always 0).	PD (11,0)
DISGLR	Signals received.	PD (11,0)
DIOPST	OPSTARTs sent.	PD (11,0)
DISGLS	Signals sent.	PD (11,0)
DIRSTQ	Restart queues sent.	PD (11,0)
DIRQDO	DMA requests sent for output of data: The number of requests the IOP sends to the system for data to be sent from the IOP to the system across the bus.	PD (11,0)
DIRQDI	DMA requests sent for input of data: The number of requests the IOP sends to the system for data to be sent to the IOP from the system across the bus.	PD (11,0)
DIBNAR	Occurrences of BNA received.	PD (11,0)
DIRID0	Reserved	C (8)
DISMPO	Reserved	PD (11,0)
DIQLN0	Reserved	PD (11,0)
DINRQ0	Reserved	PD (11,0)
DIRID1	Reserved	C (8)
DISMP1	Reserved	PD (11,0)
DIQLN1	Reserved	PD (11,0)
DINRQ1	Reserved	PD (11,0)
DIRID2	Reserved	C (8)

Field Name	Description	Attribute
DISMP2	Reserved	PD (11,0)
DIQLN2	Reserved	PD (11,0)
DINRQ2	Reserved	PD (11,0)
DIRID3	Reserved	C (8)
DISMP3	Reserved	PD (11,0)
DIQLN3	Reserved	PD (11,0)
DINRQ3	Reserved	PD (11,0)
DIRID4	Reserved	C (8)
DISMP4	Reserved	PD (11,0)
DIQLN4	Reserved	PD (11,0)
DINRQ4	Reserved	PD (11,0)
DIRID5	Reserved	C (8)
DISMP5	Reserved	PD (11,0)
DIQLN5	Reserved	PD (11,0)
DINRQ5	Reserved	PD (11,0)
DIRID6	Reserved	C (8)
DISMP6	Reserved	PD (11,0)
DIQLN6	Reserved	PD (11,0)
DINRQ6	Reserved	PD (11,0)
DIRID7	Reserved	C (8)
DISMP7	Reserved	PD (11,0)
DIQLN7	Reserved	PD (11,0)
DINRQ7	Reserved	PD (11,0)
DIRID8	Reserved	C (8)
DISMP8	Reserved	PD (11,0)
DIQLN8	Reserved	PD (11,0)
DINRQ8	Reserved	PD (11,0)
DIRID9	Reserved	C (8)
DISMP9	Reserved	PD (11,0)
DIQLN9	Reserved	PD (11,0)
DINRQ9	Reserved	PD (11,0)
DIRIDA	Reserved	C (8)
DISMPA	Reserved	PD (11,0)
DIQLNA	Reserved	PD (11,0)
DINRQA	Reserved	PD (11,0)

Field Name	Description	Attribute
DIRIDB	Reserved	C (8)
DISMPB	Reserved	PD (11,0)
DIQLNB	Reserved	PD (11,0)
DINRQB	Reserved	PD (11,0)
DIRIDC	Reserved	C (8)
DISMPC	Reserved	PD (11,0)
DIQLNC	Reserved	PD (11,0)
DINRQC	Reserved	PD (11,0)
DIRIDD	Reserved	C (8)
DISMPD	Reserved	PD (11,0)
DIQLND	Reserved	PD (11,0)
DINRQD	Reserved	PD (11,0)
DIRIDE	Reserved	C (8)
DISMPE	Reserved	PD (11,0)
DIQLNE	Reserved	PD (11,0)
DINRQE	Reserved	PD (11,0)
DIRIDF	Reserved	C (8)
DISMPF	Reserved	PD (11,0)
DIQLNF	Reserved	PD (11,0)
DINRQF	Reserved	PD (11,0)

Note: The performance monitor reports I/O processor (IOP) statistics different beginning with Version 3 Release 7. Therefore, performance statistics for IOPs introduced in Version 3 Release 7 or later releases are reported in the QAPMMIOP file. Performance statistics are reported in the QAPMMIOP file even if the IOP supports only one of the three IOP functions (communications, disk, or local workstation). Performance statistics for IOPs that were introduced before Version 3 Release 7 will continue to be reported in the appropriate IOP file (QAPMCIOP, QAPMDIOP, QAPMLIOP, and QAPMMIOP).

Related reference

[Collection Services data files: System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: File abbreviations

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRDTA) command See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMDISK

This database file includes disk file entries and contains one record for each disk resource.

Typically, there is one disk resource per disk unit except for a multipath disk unit that has multiple disk resources associated with it. The associated disk response time boundaries (in milliseconds) are reported in the QAPMCONF file in GKEY fields B1-B5.

Field Name	Description	Attribute
INTNUM	Interval number: The <i>n</i> th sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
IOPRN	IOP resource name	C (10)
DIOPID	Reserved	C (1)
DSARM	Disk unit (arm) number: Specifies the unique identifier of the unit. Each actuator arm on the disk drives available to the machine represents a unit of auxiliary storage. The value of the unit number is assigned by the system when the unit is allocated to an auxiliary storage pool.	C (4)
DSTYPE	Disk unit type such as 4326 or 2105.	C (4)
DSDRN	Device resource name. Typically, there is one disk (device) resource per disk unit except for a multipath disk unit that has multiple disk resources associated with it (see note “3” on page 52).	C (10)
DSSCAN	Number of search string commands: This count is zero for disk types which do not support search string commands.	PD (5,0)
DSBLKR	Number of blocks read: Block is one sector on the disk unit.	PD (11,0)
DSBLKW	Number of blocks written: Block is one sector on the disk unit.	PD (11,0)

Field Name	Description	Attribute
DSIDLC	<p>Processor idle loop counter (see note “1” on page 51): The number of times the disk controller passed through the idle loop. This field is zero for disk types which do not have a dedicated disk processor.</p> <p>DSIDLC and DSIDLT are duplicated across all diskunits attached to the same disk controller.</p>	PD (11,0)
DSIDLT	<p>Processor idle loop time (see note “1” on page 51): The time (in hundredths of microseconds) to make one pass through the idle loop. This field is zero for disk types which do not have a dedicated disk processor. The value reported could be a multiple of the actual idle loop time. In that case, the value reported for the processor idle loop count field (DSIDLC) is reduced accordingly so that the calculated processor utilization is correct.</p> <p>DSIDLC and DSIDLT are duplicated across all disk units attached to the same disk controller.</p>	PD (11,0)
DSSK1	Number of seeks > 2/3: The number of times the arm traveled more than 2/3 of the disk on a seek.	PD (11,0)
DSSK2	Number of seeks > 1/3 and < 2/3: The number of times the arm traveled more than 1/3 but less than 2/3 of the disk on a seek.	PD (11,0)
DSSK3	Number of seeks > 1/6 and < 1/3: The number of times the arm traveled more than 1/6 but less than 1/3 of the disk on a seek.	PD (11,0)
DSSK4	Number of seeks > 1/12 and < 1/6: The number of times the arm traveled more than 1/12 but less than 1/6 of the disk on a seek.	PD (11,0)
DSSK5	Number of seeks < 1/12: The number of times the arm traveled from its current position but less than 1/12 of the disk on a seek.	PD (11,0)

Field Name	Description	Attribute
DSSK6	Number of zero seeks: The number of times the access arm did not physically move on a seek request. The operation may have resulted in a head switch.	PD (11,0)
DSQUEL	Total queue elements. The number of I/O operations waiting service at the time of a sample (DSSMPL). Divide DSQUEL by DSSMPL to get the <i>average queue length</i> .	PD (11,0)
DSNBSY	Number of times arm not busy. The number of times there were no outstanding I/O operations active at the time of a sample (DSSMPL). Subtract DSNBSY from DSSMPL and divide by DSSMPL to get the <i>disk utilization</i> .	PD (11,0)
DSSMPL	Number of samples taken: The number of samples taken for the DSQUEL and DSNBSY fields.	PD (11,0)
DSCAP	Drive capacity (in bytes): Total number of bytes of auxiliary storage provided on the unit for the storage of objects and internal machine functions when the auxiliary storage pool containing it is not under checksum protection. The unit reserved system space value is subtracted from the unit capacity to calculate this capacity.	PD (15,0)
DSAVL	Drive available space (in bytes): Total number of bytes of auxiliary storage space that is not currently assigned to objects or internal machine functions, and therefore is available on the unit.	PD (15,0)
DSASP	Auxiliary storage pool number: Specifies the auxiliary storage pool to which this unit is currently allocated. A value of 1 specifies the system auxiliary storage pool. A value from 2 through 32 specifies a basic auxiliary storage pool. A value from 33 to 255 specifies an independent auxiliary storage pool. A value of 0 indicates that this unit is currently not allocated.	PD (5,0)
DSCSS	Reserved	C (2)

Field Name	Description	Attribute
DSPCAP	Reserved	PD (11,0)
DSPAVL	Reserved	PD (11,0)
DMFLAG	' ' means this disk unit is not locally mirrored. 'A' means this is the designated first unit of a locally mirrored pair. 'B' means this is the designated second unit of a locally mirrored pair.	C (1)
DMSTS	Local mirroring status. 1 = active, 2 = resuming, 3 = suspended	PD (1,0)
DMIRN	Locally mirrored IOP resource name	C (10)
DMDRN	Locally mirrored device resource name	C (10)
DSRDS	Number of read data commands.	PD (11,0)
DSWRTS	Number of write data commands.	PD (11,0)
DSBUFO	Number of buffer overruns: The number of times that data was available to be read into the disk controller buffer from the disk, but the disk controller buffer still contained valid data that was not retrieved by the storage device controller. Consequently, the disk had to take an additional revolution until the buffer was available to accept data.	PD (11,0)
DSBUFU	Number of buffer underruns: The number of times that the disk controller was ready to transfer data to the disk on a write, but the disk controller buffer was empty. The data was not transferred in time by the disk IOP to the disk controller buffer. The disk was forced to take an extra revolution awaiting the data.	PD (11,0)
DSMDLN	Model Number: The model number of the disk drive.	C (4)
DSDCRH	Device cache read hits: The number of times that all of the data requested by the read operation was obtained from the device read or write cache.	PD (11,0)

Field Name	Description	Attribute
DSDCPH	Device cache partial read hits: The number of times that a portion, but not all, of the data requested by the read operation was obtained by the device read or write cache. A physical operation to the device media was required to obtain the remaining data.	PD (11,0)
DSDCWH	Device cache write hits: The number of times that the data associated with a write operation replaces, or is combined with, existing data in the device write cache, thereby eliminating a write operation.	PD (11,0)
DSDCFW	Device cache fast writers: The number of times that space was available in the device write cache for the data associated with a write operation and a response was returned immediately.	PD (11,0)
DSDROP	Device read operations: The number of read operations issued to the device by the controller. This includes operations generated by controller for data protection (RAID) or data compression. This does not include operations generated for diagnostics and operations to access the controller reserved area that occur during this idle time.	PD (11,0)
DSDWOP	Device write operations: The number of write operations issued to the device by the controller. This includes operations generated by controller for data protection (RAID) or data compression. This does not include operations generated for diagnostics and operations to access the controller reserved area that occur during this idle time.	PD (11,0)
DSCCRH	Controller cache read hits: The number of times that all of the data requested by the read operation was obtained from the controller read or write cache.	PD (11,0)

Field Name	Description	Attribute
DSPCPH	Controller cache partial read hits: The number of times that a portion of the data requested by the read operation was obtained from the controller read and write cache. An operation to the device was required to obtain the remaining data.	PD (11,0)
DSCCWH	Controller cache writes hits: The number of times that the data associated with the write operation replaces or is combined with existing data in the controller write cache. This eliminates a write operation.	PD (11,0)
DSCCFW	Controller cache fast writes: The number of times that space was available in the controller write cache for all of the data associated with a write operation and a response was returned immediately.	PD (11,0)
DSCOMP	Compressed Unit indicator. '0' if disk data is not compressed and '1' if disk data is compressed.	C (1)
DSPBU	Physical blocks used. For compressed units, this field contains the total number of physical blocks used (written) in the device user data area. For non-compressed units, this field contains 0.	PD (11,0)
DSPBA	Physical blocks allocated. For compressed units, this field contains the total number of physical blocks committed (reserved) in the device user data area for DASD extents. This value includes all of the Physical Blocks Used. For non-compressed units, this field contains 0.	PD (11,0)
DSLBW	Logical blocks written. For compressed units, this field contains the total number of logical blocks written in the device user data area. This value represents the total amount of data written to allocated extents. For non-compressed units, this field contains 0.	PD (11,0)

Field Name	Description	Attribute
DSLBA	Logical blocks allocated. For compressed units, this field contains the total number of logical blocks contained in allocated compression groups. This value represents the total sum of all allocated compression groups in the device user data area. For non-compressed units, this field contains 0.	PD (11,0)
DSPBCO	Physical blocks for compression overhead. For compressed units, this field contains the total number of physical blocks that are used for compression directory structures and reserved areas that are unavailable for storing user data. For non-compressed units, this field contains 0.	PD (11,0)
DSFGDR	Foreground directory reads. For compressed units, this field is the number of device read operations that have been performed to read directory structures required to complete host system commands. For non-compressed units, this field contains 0.	PD (11,0)
DSFGDW	Foreground directory writes. For compressed units this is the number of device write operations that have been performed to write directory structures required to complete host system commands. For non-compressed units, this field contains 0.	PD (11,0)
DSBGDR	Background directory reads. For compressed units, this is the number of device read operations that have been performed in the management of compression directory structures, but were not immediately required to complete host system commands. For non-compressed units, this field contains 0.	PD (11,0)
DSBGDW	Background directory writes. For compressed units, this is the number of device write operations. For non-compressed units, this field contains 0.	PD (11,0)

Field Name	Description	Attribute
DSFGRE	<p>Foreground read exceptions. For compressed units, this is the number of times an additional device read operation was issued to read data that had been stored in the exception area on a compressed device (this count applies only to multi-page operations). This count reflects only those operations immediately required to complete host system commands.</p>	PD (11,0)
DSFGWE	<p>Foreground write exceptions. For compressed units, this field is the number of times an additional device write operation was issued to write data into the exception area on a compressed device (this count applies only to multi-page operations). This count reflects only those operations immediately required to complete host system commands. For non-compressed units, this field contains 0.</p>	PD (11,0)
DSFGS	<p>Foreground sweeps. For compressed units, a sweep is the process used to store a 1-MB compression group in the correct number of sectors so there are no unused areas in the data region and no used areas in the exception region of the compression group. The number of foreground sweeps is the number of times an entire 1-MB compression group was required to be swept to complete host system commands. The sweep is needed because the data for a host system write operation does not fit into the physical space reserved. The new data does not compress as well as the data that was previously in the space. For non-compressed units, this field contains 0.</p>	PD (11,0)

Field Name	Description	Attribute
DSBGS	Background sweeps. For compressed units, a sweep is the process used to store a 1-MB compression group in the correct number of sectors so there are no unused areas in the data region and no used areas in the exception region of the compression group. The number of background sweeps is the number of times an entire 1-MB compression group was swept to maintain the compressed data storage efficiency. This count reflects only those sweeps that were not immediately required to complete host system commands. Background sweeps are intended to increase performance or increase usable capacity of drive. For non-compressed units, this field contains 0.	PD (11,0)
DSCERC	Controller simulated read cache hits: The number of times that all of the data requested by the read operation could have been, but was not, obtained from a controller read cache (not the controller write cache). This field is updated only when Extended Adaptive Cache Simulator is enabled.	PD (11,0)
DSASPN	Auxiliary storage pool resource name. Specifies the resource name of the auxiliary storage pool to which this unit is currently allocated. A value of blanks specifies the system auxiliary storage pool or a basic auxiliary storage pool.	C (10)
DSPS	Parity set. The valid value for this field is '1' or '0'. The value of this field is '1' when the disk unit is in a parity set; otherwise, it is '0'.	C (1)
DSHAPS	High availability parity set. The valid value for this field is '1' or '0'. The value of this field is '1' when the disk unit is in a high availability parity set; otherwise, it is '0'.	C (1)

Field Name	Description	Attribute
DSMU	Multipath unit. The valid value for this field is '1' or '0'. The value of this field is '1' when the disk resource represents a multipath disk unit (see note “3” on page 52); otherwise, it is '0'.	C (1)
DSIP	Initial path of multipath unit. The valid value for this field is '1' or '0'. The value of this field is '1' when the disk resource represents the initial path of a multipath disk unit; otherwise it is '0'. The initial path is the first path observed by the system. It can change after restarting the system (IPL). The resource name of the initial path can be used for reporting a multipath disk unit under a single resource name.	C (1)
DSPC	Production copy of remotely mirrored independent auxiliary storage pool. The valid value for this field is '1' or '0'. The value of this field is '1' when the disk unit is in a production copy of a remotely mirrored independent auxiliary storage pool; otherwise, it is '0'.	C (1)
DSMC	Mirror copy of remotely mirrored independent auxiliary storage pool. The valid value for this field is '1' or '0'. The value of this field is '1' when the disk unit is in a mirror copy of a remotely mirrored independent auxiliary storage pool; otherwise, it is '0'.	C (1)
DSRDT	RAID type: type of RAID parity set for this disk unit. This field only has meaning for disk units in a parity set (DSPS field set to '1'). <ul style="list-style-type: none"> • '0' = RAID 5 parity set • '1' = RAID 6 parity set • '2' = RAID 10 parity set 	C (1)

Field Name	Description	Attribute
DSIOPF	Managed by IOP. The valid value for this field is '1' or '0'. The value of this field is '1' when this disk unit is attached to the disk storage adapter which is managed by IOP; otherwise, it is '0'. When data is collected by operating system versions earlier than V5R4, this field is always set to '1', because earlier versions cannot determine if the disk unit was IOP-based or not.	C (1)
DSCAT	<p>Disk unit category. This field indicates if this disk unit has some special characteristics, which may require a special interpretation of its performance data. Each bit in this field has an independent meaning:</p> <ul style="list-style-type: none"> • X'00' = no special category applies. • X'01' = this disk unit is located in external storage media. This can also be determined by examining device type and model for this disk unit. • X'02' = data on this disk unit is encrypted. • X'04' = this is a virtual disk unit. This can also be determined by examining device type and model for this disk unit. • X'08' = this disk unit has an alternate path. • X'10' = this is a solid state disk unit. • X'20' = this disk unit is using a non-preferred path. 	C (1)
DSSRVT	Disk service time (see note "4" on page 52). Combined service time of all disk operations completed since last sample (milliseconds). Divide by number of read and write commands to obtain average service time. Set to zero if data is not available.	B(9,0)

Field Name	Description	Attribute
DSWT	Disk wait time. Combined wait (queue) time of all disk operations completed since last sample (milliseconds). Divide by number of read and write commands to obtain average wait (queue) time. Add to disk service time to obtain disk response time. Set to zero if data is not available.	B(9,0)
DSBKCT1	Disk operations in disk response time bucket 1 (see note “5” on page 52). Number of disk operations since last sample, the response time of which was less than the first disk response time boundary.	B(9,0)
DSBKRT1	Disk response time in disk response time bucket 1. Combined response time of all disk operations since last sample, the response time of which was less than the first disk response time boundary (milliseconds).	B(9,0)
DSBKST1	Disk service time in disk response time bucket 1. Combined service time of all disk operations since last sample, the response time of which was less than the first disk response time boundary (milliseconds).	B(9,0)
DSBKCT2	Disk operations in disk response time bucket 2 (see note “5” on page 52). Number of disk operations since last sample, the response time of which was greater than the first disk response time boundary but less than the second disk response time boundary.	B(9,0)
DSBKRT2	Disk response time in disk response time bucket 2. Combined response time of all disk operations since last sample, the response time of which was greater than the first disk response time boundary but less than the second disk response time boundary (milliseconds).	B(9,0)

Field Name	Description	Attribute
DSBKST2	Disk service time in disk response time bucket 2. Combined service time of all disk operations since last sample, the response time of which was greater than the first disk response time boundary but less than the second disk response time boundary (milliseconds).	B(9,0)
DSBKCT3	Disk operations in disk response time bucket 3 (see note “5” on page 52). Number of disk operations since last sample, the response time of which was greater than the second disk response time boundary but less than the third disk response time boundary.	B(9,0)
DSBKRT3	Disk response time in disk response time bucket 3. Combined response time of all disk operations since last sample, the response time of which was greater than the second disk response time boundary but less than the third disk response time boundary (milliseconds).	B(9,0)
DSBKST3	Disk service time in disk response time bucket 3. Combined service time of all disk operations since last sample, the response time of which was greater than the second disk response time boundary but less than the third disk response time boundary (milliseconds).	B(9,0)
DSBKCT4	Disk operations in disk response time bucket 4 (see note “5” on page 52). Number of disk operations since last sample, the response time of which was greater than the third disk response time boundary but less than the fourth disk response time boundary.	B(9,0)

Field Name	Description	Attribute
DSBKRT4	Disk response time in disk response time bucket 4. Combined response time of all disk operations since last sample, the response time of which was greater than the third disk response time boundary but less than the fourth disk response time boundary (milliseconds).	B(9,0)
DSBKST4	Disk service time in disk response time bucket 4. Combined service time of all disk operations since last sample, the response time of which was greater than the third disk response time boundary but less than the fourth disk response time boundary (milliseconds).	B(9,0)
DSBKCT5	Disk operations in disk response time bucket 5 (see note “5” on page 52). Number of disk operations since last sample, the response time of which was greater than the fourth disk response time boundary but less than the fifth disk response time boundary.	B(9,0)
DSBKRT5	Disk response time in disk response time bucket 5. Combined response time of all disk operations since last sample, the response time of which was greater than the fourth disk response time boundary but less than the fifth disk response time boundary (milliseconds).	B(9,0)
DSBKST5	Disk service time in disk response time bucket 5. Combined service time of all disk operations since last sample, the response time of which was greater than the fourth disk response time boundary but less than the fifth disk response time boundary (milliseconds).	B(9,0)
DSBKCT6	Disk operations in disk response time bucket 6 (see note “5” on page 52). Number of disk operations since last sample, the response time of which was greater than the fifth disk response time boundary.	B(9,0)

Field Name	Description	Attribute
DSBKRT6	Disk response time in disk response time bucket 6. Combined response time of all disk operations since last sample, the response time of which was greater than the fifth disk response time boundary (milliseconds).	B(9,0)
DSBKST6	Disk service time in disk response time bucket 6. Combined service time of all disk operations since last sample, the response time of which was greater than the fifth disk response time boundary (milliseconds).	B(9,0)
DSSECT	Disk unit sector size.	B(4,0)
DSIOARN	Disk storage adapter (IOA) resource name.	C(10)
DSSRLN	Disk unit serial number.	C(15)
DSVAL01	Reserved	B(18,0)
DSVAL02	Reserved	B(18,0)
DSVAL03	Reserved	B(18,0)
DSVAL04	Reserved	B(18,0)
DSPTROP	Path read commands. This is the number of read requests received by internal machine functions during the interval.	B(18,0)
DSPTWOP	Path write commands. This is the number of write requests received by internal machine functions during the interval.	B(18,0)
DSWWNN	World wide node name. A unique identifier representing the external storage subsystem the disk belongs to. This will be null for non-external disks.	BINCHAR(8)
DSLVLMP	Level of mirrored protection: a hexadecimal value that indicates the unit level of protection. The level of mirrored protection determines whether the system keeps running when different levels of hardware fail. The possible values are documented in the unit level of mirrored protection field of the MATRMD Machine Interface instruction in the IBM i information center.	BINCHAR (2)

Field Name	Description	Attribute
DSLSCMDS	The number of log sense commands issued for the device since last sample.	B (9,0)
DSLRT	Log sense response time. This is the combined response time of all the log sense commands issued for the device since last sample (microseconds).	B (18,0)
DATETIME	Interval date and time: The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp
DSQUEOPS	Deferred queue operations. The number of I/O operations placed on the deferred queue during the interval.	B (9,0)

Notes:

- The idle loop count and time are used to calculate the storage device controller utilization as follows:
Convert the product of the idle loop count times the idle loop time from hundredths of microseconds to seconds. Subtract this from the interval time, and divide the result by the interval time. For example:

$$\text{Disk processor utilization} = (\text{INTSEC} - (\text{DSIDLC} * \text{DSIDLT}) / 10^{**8}) / \text{INTSEC}$$

- The following formulas describe the traditional way that several of the fields in the previous table can be used to calculate utilization and service time for each arm. The preferred way is to use the DSSRVCT field. For a multipath disk unit, these formulas will give the utilization and service time for each path (resource).

- Arm utilization (DSUTL): The part of the total interval that the arm was being used for I/O operations.

$$\text{DSUTL} = \text{Arm Busy} = (\text{DSSMPL} - \text{DSNBSY}) / \text{DSSMPL}$$

- Arm accesses per second (DSAS): The number of reads and writes per second for this arm during the interval.

$$\text{DSAS} = (\text{DSRDS} + \text{DSWRTS}) / \text{INTSEC}$$

- Service time (DSSRVCT): The average time for an arm I/O operation. This includes disk controller time.

$$\text{DSSRVCT} = \text{DSUTL} / \text{DSAS}$$

Use the following formula to calculate the service time (DSSTM) for a multipath disk unit, where X_i is the calculated value of X for the i-th path and $\text{sum}(X_i)$ is the sum of X_i over all paths:

$$\text{DSSTM} = \text{sum}(\text{DSSRVCT}_i * (\text{DSRDS}_i + \text{DSWRTS}_i)) / \text{sum}(\text{DSRDS}_i + \text{DSWRTS}_i)$$

If the disk unit is managed by an IOP ($\text{DSIOPF} = '1'$) and if the operation rate is very low, the service time calculated with this formula should be ignored. This is a calculated value based on data obtained through sampling. When the number of operations is small compared to the number of samples, the statistical error makes the result unreliable.

The formulas shown above for disk utilization and disk service time are based on a simplified statistical model. The results produced by these formulas should only be used as an estimate.

3. Performance data is reported for each disk resource that is associated with a multipath disk unit. For a multipath disk unit, the following counters come from the device, which means that their values are duplicated for each disk resource that is reported:

- DSIDLK - Processor idle loop count
- DSIDLT - Processor idle loop time
- DSSK1-6 - Number of seeks
- DSBUFO - Number of buffer overruns
- DSBUFU - Number of buffer underruns
- DSDCRH - Device cache read hits
- DSDCPH - Device cache partial read hits
- DSDCWH - Device cache write hits
- DSDCFW - Device cache fast writes
- DSDROP - Device read operations (IOP-less devices only)
- DSDWOP - Device write operations (IOP-less devices only)

Other field values that are duplicated include disk unit capacity (DSCAP), disk unit available space (DSAVL), disk unit serial number (DSSRLN), and disk unit sector size (DSSECT).

The arm number (DSARM) and mirror flag (DMFLAG) of a particular multipath disk unit can be used to identify the records associated with that unit.

The device read operations (DSDROP) and device write operations (DSDWOP) fields are device level counters (duplicated for each disk resource that is reported) for IOP-less devices (DSIOPF = '0') only. If the device is managed by an IOP (DSIOPF = '1'), then these two fields contain path level counters, which means that their values are unique for each disk resource that is reported.

4. Measured service time may differ from service time calculated using formula from note “2” on page 51 above, because the formula is based on a simplified statistical model.

5. For disk units managed by IOP (DSIOPF = '1'), data for disk response time buckets is measured at different level in program stack compared to data used in the formulas from note “2” on page 51 above. Because of this, differences should be expected when comparing this data with results obtained using those formulas.

Related reference

Collection Services data files: QAPMCONF

This database file contains general information about the collection.

Collection Services data files: QAPMDISKRB

This database file includes disk file response bucket entries and contains one record for each device resource name. It is intended to be used in conjunction with the QAPMDISK file.

Collection Services data files: QAPMSMDSK

This database file contains summarized metrics from disk data (*DISK collection category) that may be used in support of system monitoring.

Collection Services data files: System category and file relationships

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: File abbreviations

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRDTA) command See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMDISKRB

This database file includes disk file response bucket entries and contains one record for each device resource name. It is intended to be used in conjunction with the QAPMDISK file.

This file reports separate response bucket entries for read operations and for write operations. The response times and service times are reported in microseconds. The associated disk response time boundaries (in microseconds) are reported in the QAPMCONF file in GKEY fields G1-GA.

Field Name	Description	Attribute
INTNUM	Interval number: The <i>n</i> th sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DSDRN	Device resource name. Typically, there is one disk (device) resource per disk unit except for a multipath disk unit that has multiple disk resources associated with it.	C (10)
DSRBKCTR1	Disk read operations in disk response time bucket 1. Number of read operations since last sample, the response time of which was less than the first disk response time boundary.	B (9, 0)
DSRBKRTR1	Disk response time in disk read response time bucket 1. Combined response time of all disk read operations since last sample, the response time of which was less than the first disk response time boundary (microseconds).	B (18, 0)
DSRBKSTR1	Disk service time in disk read response time bucket 1. Combined service time of all disk read operations since last sample, the response time of which was less than the first disk response time boundary (microseconds).	B (18, 0)
DSRBKCTRnn DSRBKRTRnn DSRBKSTRnn	Disk read operations, disk response time and disk service time are repeated for a total of 11 counter sets per record.	
DSRBKCTW1	Disk write operations in disk response time bucket 1. Number of disk write operations since last sample, the response time of which was less than the first disk response time boundary.	B (9, 0)

Field Name	Description	Attribute
DSRBKRTW1	Disk response time in disk write response time bucket 1. Combined response time of all disk write operations since last sample, the response time of which was less than the first disk response time boundary (microseconds).	B (18, 0)
DSRBKSTW1	Disk service time in disk write response time bucket 1. Combined service time of all disk write operations since last sample, the response time of which was less than the first disk response time boundary (in microseconds).	B (18, 0)
DSRBKCTWnn DSRBKRTWnn DSRBKSTWnn	Disk write operations, disk response time and disk service time are repeated for a total of 11 counter sets per record.	

Related reference

Collection Services data files: [QAPMCONF](#)

This database file contains general information about the collection.

Collection Services data files: [QAPMDISK](#)

This database file includes disk file entries and contains one record for each disk resource.

Collection Services data files: [System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: [File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFDRDTA) command See the Create Performance Data (CRTPFDRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMDOMINO

This database file contains data collected by the Domino® for i5/OS category.

This file contains 1 record per interval for each Domino server active on the system.

Note: These descriptions include the name of the metric as it is found in the Domino "show stat" function.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFDRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)

Field Name	Description	Attribute
DTECEN	Century digit: where 0 indicates 19XX and 1 indicates 20XX.	C (1)
DMSUBS	Server subsystem.	C (10)
DMJNAM	Server job name.	C (10)
DMJUSR	Server job user.	C (10)
DMJNBR	Server job number.	C (6)
DMSRVN	Server name (first 25 characters if the name is longer than this field).	C (25)
DMSSDT	Server start date time, (yyyymmddhhmmss).	C (14)
DMDBPM	Database.BufferPool.Maximum.Megabytes: The configured maximum size for database control pools that may be used.	B (9,0)
DMDBPP	Database.BufferPool.Peak.Megabytes: Maximum amount of the buffer pool that has been used by Domino over the life of the server.	B (9,0)
DMDBPR	Database.Database.BufferPool.PerCentReadsInBuffer: Percentage of database reads present in buffer pool.	B (5,2)
DMDBCH	Database.DbCache.Hits: Number of hits to the database cache.	B (18,0)
DMDBCL	Database.DbCache.Lookups: Number of lookups to the database cache.	B (18,0)
DMNLCH	Database.NAMELookupCacheHits: Number of cache hits when doing name lookups in the server's name and address book.	B (18,0)
DMNLCL	Database.NAMELookupCacheLookups: Number of lookups in the server's name and address book.	B (18,0)
DMA SPN	Platform.LogicalDisk.1.AuxStoragePool: The number of the auxiliary storage pool that includes the Domino data directory.	B (4,0)
DMA SPU	Platform.LogicalDisk.1.PctUsed: Percent of total disk space used in the auxiliary storage pool that includes the Domino data directory. Note: This metric is calculated by the server and is based on an internal sample interval as configured for the server.	B (5,2)
DMA SPB	Platform.LogicalDisk.1.PctUtil: Percent of time the drives are busy reading or writing in the auxiliary storage pool that includes the Domino data directory. Note: This metric is calculated by the server and is based on an internal sample interval as configured for the server.	B (5,2)
DMTRNS	Server.Trans.Total: Number of transactions.	B (18,0)

Field Name	Description	Attribute
DMUSRO	Server.Users: Number of users with open sessions on the server. (This is the current value at time data was sampled.)	B (9,0)
DMUSRP	Server.Users.Peak: Peak number of concurrent users since the server was started.	B (9,0)
DMUSRT	Server.Users.Peak.Time: Time that last peak users occurred (YYYYMMDDHHMMSS).	C (14)
DMMLCP	Mail.TotalPending: Number of outbound mail messages in this server's MAIL.BOX waiting to be processed by the Domino Router job. Mail will be pending until the Router job wakes up and moves outgoing mail from MAIL.BOX to the destination mail servers. If a mail server cannot be contacted, the message will remain pending in MAIL.BOX. (This is the current value at the time data was sampled.)	B (9,0)
DMMLWR	Mail.WaitingRecipients: Number of inbound mail messages in this server's MAIL.BOX waiting to be processed by the Domino Router job. Mail will be waiting until the Router job wakes up and moves incoming mail from MAIL.BOX into user mail files. (This is the current value at time data was sampled.)	B (9,0)
DMMLBX	Mail.Delivered: Combined number of inbound and outbound mail messages placed into this server's MAIL.BOX.	B (18,0)
DMCMCD	Domino.Command.CreateDocument: Count of 'CreateDocument' URLs that have come into the server.	B (18,0)
DMCMDD	Domino.Command.DeleteDocument: Count of 'DeleteDocument' URLs that have come into the server.	B (18,0)
DMCMED	Domino.Command.EditDocument: Count of 'EditDocument' URLs that have come into the server.	B (18,0)
DMCMOA	Domino.Command.OpenAgent: Count of 'OpenAgent' URLs that have come into the server.	B (18,0)
DMCMOB	Domino.Command.OpenDatabase: Count of 'OpenDatabase' URLs that have come into the server.	B (18,0)
DMCMOD	Domino.Command.OpenDocument: Count of 'OpenDocument' URLs that have come into the server.	B (18,0)
DMCMOF	Domino.Command.OpenForm: Count of 'OpenForm' URLs that have come into the server.	B (18,0)
DMCMOI	Domino.Command.OpenImageResource: Count of 'OpenImageResource' URLs that have come into the server.	B (18,0)

Field Name	Description	Attribute
DMCMOV	Domino.Command.OpenView: Count of 'OpenView' URLs that have come into the server.	B (18,0)
DMCMSD	Domino.Command.SaveDocument: Count of 'SaveDocument' URLs that have come into the server.	B (18,0)
DMCMTU	Domino.Command.Total: Count of all URLs that have come into the server.	B (18,0)
DMRQ1M	Domino.Requests.Per1Minute.Total: Total requests over the past minute. (This is the current value at the time data was sampled.)	B (9,0)
DMNPT1	NET.*: Domino port (1 of 4) for which data is being reported. Note: The asterisk (*) in the node name indicates the name of the port.	C (32)
DMNBR1	NET.*.BytesReceived: Number of network bytes received for this port. Note: The asterisk (*) in the node name indicates the name of the port.	B (18,0)
DMNBS1	NET.*.BytesSent: Number of network bytes sent for this port. Note: The asterisk (*) in the node name indicates the name of the port.	B (18,0)
DMNSI1	NET.*.Sessions.Established.Incoming: Number of Incoming sessions established for this port. Note: The asterisk (*) in the node name indicates the name of the port.	B (9,0)
DMNSO1	NET.*.Sessions.Established.Outgoing: Number of Outgoing sessions established for this port. Note: The asterisk (*) in the node name indicates the name of the port.	B (9,0)
DMN*	Note: The above 5 fields are repeated for ports 2, 3, and 4.	
DATETIME	Interval date and time: The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp

Related reference

[Collection Services data files: System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

[Data files: File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRTA) command See the Create Performance Data (CRTPFRTA) command for information on how to create performance database files.

Collection Services data files: QAPMDPS

This database file contains data port services performance data. Data port services is Licensed Internal Code (LIC) that supports the transfer of large volumes of data between a source system and one of *N* specified (switchable) target systems in a IBM i cluster.

Data port services, such as remote independent ASP mirroring, is used by LIC clients. There is one record per IP address per client per collection interval.

Field Name	Description	Attribute
INTNUM	Interval number: The <i>n</i> th sample database interval based on the start time specified in the Create Performance Data (CRTPFRTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
DTECEN	Century digit. 0 indicates 19xx, and 1 indicates 20xx.	C (1)
DPTYPE	Client type. The type of client that is registered to data port services: <ul style="list-style-type: none"> • 1 -- Remote independent ASP mirroring. 	B (4,0)
DPNAME	Client name. The name of the client registered to data port services. This name is unique for a particular client type but might not be unique across all client types. This name is defined as follows by client type: <ul style="list-style-type: none"> • 1 -- ASP resource name of remotely mirrored primary independent ASP. 	C (10)
DPIPV	IP version. This field defines the IP version (4 or 6) for the target IP address.	B (4,0)

Field Name	Description	Attribute
DPIPAD	Target IP address. The IP address of the target system. This record reports statistics for the client's communication on the connection associated with this IP address. An IP version 4 address, which is 4 bytes wide, is right-justified and padded with zeroes.	H (16)
DPIPAS	Target IP address status. The valid value for this field is 1 or 0. The value of this field is 1 if the target IP address is currently being used for messaging; otherwise, it is 0.	C (1)
DPNID	Target node ID. The node ID of the target system in the cluster.	C (8)
DPDTA1	Client data 1. Optional data provided by the client. This data is defined as follows by client type: <ul style="list-style-type: none"> • 1 -- ASP number of remotely mirrored primary independent ASP. 	B (9,0)
DPDTA2	Client data 2. Optional data provided by the client. This data is defined as follows by client type: <ul style="list-style-type: none"> • 1 -- Not defined. 	B (9,0)
DPDTA3	Client data 3. Optional data provided by the client. This data is defined as follows by client type: <ul style="list-style-type: none"> • 1 -- Not defined. 	C (10)
DPDTA4	Client data 4. Optional data provided by the client. This data is defined as follows by client type: <ul style="list-style-type: none"> • 1 -- Not defined. 	C (40)

Field Name	Description	Attribute
DPASYN	Asynchronous mode. The valid value for this field is 1 or 0. The value of this field is 1 for asynchronous mode; otherwise, this field is 0 for synchronous mode. For asynchronous mode, the client sends a message and receives an ACK back when the message is received but before it is processed by the remote client. For synchronous mode, the client sends a message and receives an ACK back after the message is received and processed by the remote client.	C (1)
DPMS	Messages sent. The number of messages sent by the client. This value is incremented when the client requests a send; it does not depend on whether the send is successful.	B (18,0)
DPAS	Acknowledgments sent. The number of acknowledgments (ACKs) sent by the client.	B (18,0)
DPNS	Negative acknowledgments sent. The number of negative acknowledgments (NACKs) sent by the client.	B (18,0)
DPMR	Messages received. The number of messages received by the client.	B (18,0)
DPAR	Acknowledgments received. The number of acknowledgments (ACKs) received by the client.	B (18,0)
DPNR	Negative acknowledgments received. The number of negative acknowledgments (NACKs) received by the client.	B (18,0)
DPMRO	Messages retried once. The number of client messages retried only once. The messages counted are those associated with a data port services initiated retry and not a TCP-initiated retry.	B (18,0)

Field Name	Description	Attribute
DPMRM	Messages retried more than once. The number of client messages retried more than once. The messages counted are those associated with data port services initiated retries and not TCP-initiated retries. If a message is retried two or more times, then this value is incremented by 1.	B (18,0)
DPTMR	Total message retries. The total number of client message retries. The retries counted are data port services initiated retries and not TCP-initiated retries. If a message is retried <i>n</i> times, then this value is incremented by <i>n</i> .	B (18,0)
DPMRR	Messages rerouted to alternate address. The number of messages rerouted to an alternate IP address because the attempt to transmit the message timed out too many times.	B (18,0)
DPMNA	Messages not acknowledged. The number of client messages sent that did not receive an ACK or NACK in response.	B (18,0)
DPMBR	Message bytes received. The number of bytes associated with messages received by the client. This does not include bytes associated with retries or ACK and NACK responses.	B (18,0)
DPMBS	Message bytes sent. The number of bytes associated with messages sent by the client. This does not include bytes associated with retries or ACK and NACK responses. This value is incremented when the client requests a send; it does not depend on whether the send is successful.	B (18,0)
DPSMS	Small messages sent. Number of messages of size less than or equal to 4K sent by the client.	B (18,0)
DPMMS	Medium messages sent. Number of messages of size greater than 4K but less than or equal to 64K sent by the client.	B (18,0)

Field Name	Description	Attribute
DPLMS	Large messages sent. Number of messages of size greater than 64K sent by the client.	B (18,0)
DPSRTT	Smoothed round trip time in microseconds. Current estimate of the average round trip time up to the time the data was collected (see DTETIM field). This estimate is maintained by data port services. The round trip time is the time it takes for a client message to be sent and acknowledged successfully.	B (18,0)
DPTRTT	Total round trip time in microseconds. The sum of all of the round trip times. The round trip time is the time it takes for a client message to be sent and acknowledged successfully. Divide this value by round trips to get the average round trip time.	B (18,0)
DPRT	Round trips. The number of round trips. Divide total round trip time by this value to get average round trip time.	B (18,0)
DATETIME	Interval date and time: The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp

Related reference

[Collection Services data files: System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

[Data files: File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

[Create Performance Data \(CRTPFRDTA\) command](#) See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMECL

This database file includes token-ring network file entries and lists the fields in the token-ring local area network (LAN) file.

Token-ring protocol statistics are reported for active token-ring line descriptions that are associated with token-ring ports and with asynchronous transfer mode ports that support token-ring LAN emulation.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
IOPRN	IOP resource name.	C(10)
EIOPI	Reserved	C (1)
ELITYPE	The resource type of the IOP or adapter represented by this record.	C (4)
ELLND	Line description: The name of the description for this line.	C (10)
ELLSP	Line speed: The line speed expressed in bits per second (bps).	PD (11,0)
ELTFT	Total number of Type II frames transmitted.	PD (11,0)
ELTFR	Total number of Type II frames received.	PD (11,0)
ELIFT	Total number of I-frames transmitted.	PD (11,0)
ELIFR	Total number of I-frames received.	PD (11,0)
ELICT	Total number of characters transmitted in all I-frames.	PD (11,0)
ELICR	Total number of characters received in all I-frames.	PD (11,0)
ELPRCL	Protocol type: E for token-ring network.	C (1)
ELRFT	Number of receive-not-ready frames transmitted.	PD (5,0)
ELRFR	Number of receive-not-ready frames received.	PD (5,0)
ELFFT	Number of frame-reject frames transmitted.	PD (5,0)
ELFFR	Number of frame-reject frames received.	PD (5,0)
ELRJFR	Number of reject frames received.	PD (5,0)
ELRJFT	Number of reject frames transmitted.	PD (5,0)
ELSFT	Number of set asynchronous balanced mode extended frames transmitted.	PD (5,0)
ELSFR	Number of set asynchronous balanced mode extended frames received.	PD (5,0)
ELDFT	Number of disconnect frames transmitted.	PD (5,0)
ELDFR	Number of disconnect frames received.	PD (5,0)
ELDMT	Number of disconnect mode frames transmitted.	PD (5,0)
ELDMR	Number of disconnect mode frames received.	PD (5,0)

Field Name	Description	Attribute
ELN2R	N2 retries end count: This count is updated when the host has attempted to contact a station n times and n times the T1 timer ended before the station responded.	PD (5,0)
ELT1T	T1 timer end count: Number of times the T1 timer ended. This count is updated when the host has attempted to contact a station n times and n times the T1 timer ended before the station responded.	PD (5,0)
EMFTR	Total frames transmitted: Total number of frames (LLC and MAC) transmitted. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (11,0)
EMFRV	Total frames received: Total number of frames (LLC and MAC) received. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (11,0)
EMMFT	MAC frames transmitted: Total number of MAC frames transmitted. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (11,0)
EMMFR	MAC frames received: Total number of MAC frames received. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (11,0)
EMRIT	Routing information frames transmitted: Total number of frames (LLC and MAC) with a routing-information field transmitted. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (11,0)
EMRIR	Routing information frames received: Total number of frames (LLC and MAC) with a routing-information field received. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (11,0)
EMLNE	Line error: Code violation of frame-check sequence error. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)
EMINE	Internal error: Adapter internal error. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)
EMBRE	Burst error: Burst of same polarity is detected by the physical unit after the starting delimiter of a frame or token. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)
EMAFE	Address-recognized indicator or frame-copied indicator error: Physical control field-extension field error. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)
EMABT	Abnormal ending delimiter: Abnormal ending delimiter transmitted because of internal error. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)

Field Name	Description	Attribute
EMLST	Lost frame: Physical trailer timer ended while IOA is in transmit stripping state. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)
EMRXC	Receive congestion: Frame not copied because no buffer was available for the IOA to receive. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)
EMFCE	Frame-copied error: The frame with a specific destination address was copied by another adapter. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)
EMFQE	Frequency error on the adapter. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)
EMTKE	Token error: The adapter that was ended by any token timer without detecting any frame or token. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)
EMDBE	Direct memory access bus error: IOP/IOA bus DMA error. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)
EMDPE	Direct memory access parity error: IOP/IOA DMA parity error. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)
EMANR	Total number of frames with address not recognized error. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)
EMFNC	Total number of frames with frame not copied error. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)
EMTSE	Total number of adapter frame transmit or frame strip process errors. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)
EMUAP	Unauthorized access priority: The access priority requested is not authorized. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)
EMUMF	Unauthorized MAC frame: The adapter is not authorized to send a MAC frame with the source class specified, or the MAC frame has a source class of zero, or the MAC frame physical control field attention field is > 1. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)
EMSFT	Soft error: Total number of soft errors as reported by the adapter. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)

Field Name	Description	Attribute
EMTBC	Total number of beacon frames transmitted. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)
EMIOA	IOA status overrun: Adapter interrupt status queue overrun, earliest status discarded. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)
EMFDC	Total number of frames discarded. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (11,0)
EMSIN	Total number of interrupts that MAC could not decode. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (11,0)
EMBRV	Total MAC bytes received ok: This contains a count of bytes in frames that are successfully received. It includes bytes from received multicast and broadcast frames. This number includes everything starting from destination address up to but excluding FCS. Source address, destination address, length or type, and pad are included.	PD(11,0)
EMBTR	Total MAC bytes transmitted ok: Total number of bytes transmitted successfully. This number includes everything starting from destination address up to but excluding FCS. Source address, destination address, length or type, and pad are included.	PD(11,0)
EMFNTR	Total frames not transmitted: This contains a count of frames that could not be transmitted due to the hardware not signaling transmission completion for an excessive period of time. This field does not apply to LAN emulation over asynchronous transfer mode.	PD(11,0)
EMRGUC	Ring use count. Percentage LAN utilization = $EMRG * C$. Most likely, the value of this field is zero, because only a few adapters use this function.	PD(11,0)
EMRGSC	Ring sample count. Percentage LAN utilization = $EMRG * C$. Most likely, the value of this field is zero, because only a few adapters use this function.	PD(11,0)
EMCVRF	FCS or code violations detected in repeated frames: This counter is incremented for every repeated frame that has a code violation or fails the frame check sequence (FCS) cyclic redundancy check. This field does not apply to LAN emulation over asynchronous transfer mode.	PD(5,0)
EMFNR	Frames transmitted that failed to return: This counter is incremented when a transmitted frame fails to return from around the ring due to time out or the reception of another frame. This field does not apply to LAN emulation over asynchronous transfer mode.	PD(5,0)

Field Name	Description	Attribute
EMUNDR	Number of underruns: This counter is incremented each time a DMA underrun is detected. This field does not apply to LAN emulation over asynchronous transfer mode.	PD(5,0)
EMDUP	The duplex state of the line. For some lines, this value might change over time. This field can have the following values: <ul style="list-style-type: none"> • Blank -- The duplex state is not known • F -- Full duplex: the line can simultaneously transmit and receive data • H -- Half duplex: the line can either transmit data or receive data, but the line cannot simultaneously transmit and receive data. 	C (1)
EMUPF	Unsupported protocol frames: Number of frames that were discarded because they specified an unsupported protocol. This count is included in the frames discarded counter. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (11,0)
ELPORT	Reserved	C (10)

Related reference

[Collection Services data files: System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

[Data files: File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

[Create Performance Data \(CRTPFRDTA\) command](#) See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMETH

This database file includes Ethernet file entries and lists the fields in the Ethernet file.

Ethernet LAN protocol statistics are reported for the active Ethernet line descriptions that are associated with Ethernet ports and with asynchronous transfer mode ports that support Ethernet LAN emulation.

There will be one record per line per port per interval. Port resource name should be used to uniquely associate records across intervals.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
IOPRN	IOP resource name.	C (10)

Field Name	Description	Attribute
ETIOPI	Reserved	C (1)
ETTYPE	The resource type of the IOP or adapter represented by this record.	C (4)
ETLLND	Line description: The name of the description for this line.	C (10)
ETLLSP	Line speed: The line speed expressed in bits per second (bps). For some lines, this value might change as time progresses.	PD (11,0)
ETLTFT	Total number of Type II frames transmitted.	PD (11,0)
ETLTFR	Total number of Type II frames received.	PD (11,0)
ETLIFT	Total number of I-frames transmitted.	PD (11,0)
ETLIFR	Total number of I-frames received.	PD (11,0)
ETLICT	Total number of characters transmitted in all I-frames.	PD (11,0)
ETLICR	Total number of characters received in all I-frames.	PD (11,0)
ETPRCL	Protocol type: T for Ethernet.	C (1)
ETLRFT	Number of receive-not-ready frames transmitted.	PD (5,0)
ETLRFR	Number of receive-not-ready frames received.	PD (5,0)
ETLFFT	Number of frame-reject frames transmitted.	PD (5,0)
ETLFFR	Number of frame-reject frames received.	PD (5,0)
ETLRJR	Number of reject frames received.	PD (5,0)
ETLRJT	Number of reject frames transmitted.	PD (5,0)
ETLSFT	Number of set asynchronous balanced mode extended frames transmitted.	PD (5,0)
ETLSFR	Number of set asynchronous balanced mode extended frames received.	PD (5,0)
ETLDFT	Number of disconnect frames transmitted.	PD (5,0)
ETLDFR	Number of disconnect frames received.	PD (5,0)
ETLDMT	Number of disconnect mode frames transmitted.	PD (5,0)
ETLDMR	Number of disconnect mode frames received.	PD (5,0)
ETLN2R	N2 retries end count: This count is updated when the host has attempted to contact a station n times and n times the T1 timer ended before the station responded.	PD (5,0)
ETLT1T	T1 timer end count: Number of times the T1 timer ended. This count is updated when the host has attempted to contact a station n times and n times the T1 timer ended before the station responded.	PD (5,0)

Field Name	Description	Attribute
ETLTIT	Number of times the TI timer (Inactivity Timer) expired. This count is updated when the host has attempted to contact a station n times and n times the T1 timer ended before the station responded.	PD (5,0)
ETLFRT	Number of times I-frame retransmission occurred.	PD (11,0)
ETLBRT	I frame bytes transmitted again.	PD (11,0)
ETLLBC	Local busy count: Number of times station entered local busy substate.	PD (5,0)
ETMFTG	Frames transmitted without error. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (11,0)
ETMFRG	Frames received without error. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (11,0)
ETMIFM	Inbound frames missed: A receiver buffer error or a missed frame was detected by the IOA. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)
ETMCRE	CRC error: Checksum errors detected by the receiver. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)
ETMEXR	More than 16 retries: Frame unsuccessfully transmitted due to excessive retries. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (11,0)
ETMOWC	Out of window collisions: Collision occurred after slot time of channel elapsed. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)
ETMALE	Alignment error: Inbound frame contained non-integer number of bytes and a CRC error. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)
ETMCRL	Carrier loss: Carrier input to the chipset on the IO adapters is false during transmission. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)
ETMTDR	Time-domain reflectometry: Counter used to approximate distance to a cable fault. This value is associated with the last occurrence of more than 16 retries. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)
ETMRBE	Receive buffer errors: A silo overflow occurred on receiving a frame. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)

Field Name	Description	Attribute
ETMSPI	Spurious interrupts: An interrupt was received but could not be decoded into a recognizable interrupt. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)
ETMDIF	Discarded inbound frames: Receiver discarded frame due to lack of AIF entries. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (11,0)
ETMROV	Receive overruns: Receiver has lost all or part of an incoming frame due to buffer shortage. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)
ETMMEE	Memory error: The chipset on the IO adapters is the bus master and did not receive ready signal within 25.6 usecs of asserting the address on the DAL** lines. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)
ETMIOV	Interrupt overrun: Interrupt not processed due to lack of status queue entries. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)
ETMTUN	Transmit underflow: Transmitter has truncated a message due to data late from memory. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)
ETMBBE	Babble errors: Transmitter exceeded maximum allowable time on channel. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)
ETMSQE	Signal quality error: Signal indicating the transmit is successfully complete did not arrive within 2 usecs of successful transmission. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)
ETMM1R	More than 1 retry to transmit: Frame required more than one retry for successful transmission. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (11,0)
ETM1R	Exactly one retry to transmit: Frame required 1 retry for successful transmission. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (11,0)
ETMDCN	Deferred conditions: The chipset on the IO adapters deferred transmission due to busy channel. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (11,0)

Field Name	Description	Attribute
ETMBRV	Total MAC bytes received ok: This contains a count of bytes in frames that are successfully received. It includes bytes from received multicast and broadcast frames. This number includes everything starting from destination address up to but excluding FCS. Source address, destination address, length or type, and pad are included.	PD (15,0)
ETMBTR	Total MAC bytes transmitted ok: Total number of bytes transmitted successfully. This number includes everything starting from destination address up to but excluding FCS. Source address, destination address, length or type, and pad are included.	PD (15,0)
ETMFNT	Total frames not transmitted: This contains a count of frames that could not be transmitted due to the hardware not signaling transmission completion for an excessive period of time. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (11,0)
ETMMFD	Total mail frames discarded. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)
ETMTFD	Transmit frames discarded. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (5,0)
ETMDUP	The duplex state of the line. For some lines, this value might change over time. This field can have the following values: <ul style="list-style-type: none"> • Blank -- The duplex state is not known • F -- Full duplex: the line can simultaneously transmit and receive data • H -- Half duplex: the line can either transmit data or receive data, but the line cannot simultaneously transmit and receive data. 	C (1)
ETMUPF	Unsupported protocol frames: Number of frames that were discarded because they specified an unsupported protocol. This count is included in the discarded inbound frames counter. This field does not apply to LAN emulation over asynchronous transfer mode.	PD (11)
ETMPORT	Port resource name.	C (10)
DATETIME	Interval date and time: The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp

Related reference

Collection Services data files: [QAPMETHP](#)

This database file includes the physical port Ethernet protocol statistics for active Ethernet line descriptions that are associated with an Ethernet port on a Single Root I/O Virtualization (SR-IOV) adapter.

Collection Services data files: System category and file relationships

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: File abbreviations

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRDTA) command See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMETHP

This database file includes the physical port Ethernet protocol statistics for active Ethernet line descriptions that are associated with an Ethernet port on a Single Root I/O Virtualization (SR-IOV) adapter.

Physical port data is reported only if the collecting partition has been authorized to obtain it. This authorization is a partition configuration attribute set on the Hardware Management Console (HMC).

There will be one record per interval per port . Port resource name can be used to uniquely associate records across intervals and to join with the records containing the virtual port Ethernet protocol statistics in the QAPMETH file.

Field Name	Description	Attribute
INTNUM	Interval number: The <i>n</i> th sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DATETIME	Interval date and time: The date and time of the sample interval, expressed in local system time.	Timestamp
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
ETMPORT	Port resource name.	C (10)
ETMFTG	Frames transmitted without error.	B (18,0)
ETMFRG	Frames received without error.	B (18,0)
ETMCRE	CRC error: Checksum errors detected by the receiver.	B (9,0)
ETMEXR	More than 16 retries: Frame unsuccessfully transmitted due to excessive retries.	B (9,0)
ETMOWC	Out of window collisions: Collision occurred after slot time of channel elapsed.	B (9,0)
ETMALE	Alignment error: Inbound frame contained non-integer number of bytes and a CRC error.	B (9,0)
ETMCRL	Carrier loss: Carrier input to the chipset on the IO adapters is false during transmission.	B (9,0)
ETMDIF	Discarded inbound frames: Receiver discarded frame due to lack of AIF entries.	B (18,0)
ETMROV	Receive overruns: Receiver has lost all or part of an incoming frame due to buffer shortage.	B (9,0)

Field Name	Description	Attribute
ETMMEE	Memory error: The chipset on the IO adapters is the bus master and did not receive ready signal within 25.6 usecs of asserting the address on the DAL** lines.	B (9,0)
ETMSQE	Signal quality error: Signal indicating the transmit is successfully complete did not arrive within 2 usecs of successful transmission.	B (9,0)
ETMM1R	More than 1 retry to transmit: Frame required more than one retry for successful transmission.	B (9,0)
ETM1R	Exactly one retry to transmit: Frame required 1 retry for successful transmission.	B (9,0)
ETMDCN	Deferred conditions: The chipset on the IO adapters deferred transmission due to busy channel.	B (9,0)
ETMBRV	Total MAC bytes received ok: This contains a count of bytes in frames that are successfully received. It includes bytes from received multicast and broadcast frames. This number includes everything starting from destination address up to but excluding FCS. Source address, destination address, length or type, and pad are included.	B (18,0)
ETMBTR	Total MAC bytes transmitted ok: Total number of bytes transmitted successfully. This number includes everything starting from destination address up to but excluding FCS. Source address, destination address, length or type, and pad are included.	B (18,0)
ETMTFD	Transmit frames discarded.	B (18,0)
ETMUPF	Unsupported protocol frames: Number of frames that were discarded because they specified an unsupported protocol. This count is included in the discarded inbound frames counter.	B (18,0)
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp

Related reference

[Collection Services data files: QAPMETH](#)

This database file includes Ethernet file entries and lists the fields in the Ethernet file.

[Collection Services data files: System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

[Data files: File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

[Create Performance Data \(CRTPFRDTA\) command](#) See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMFRLY

This database file includes frame relay counter entries.

QAPMFRLY is a database file for the frame relay counter.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5 0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds.	PD (7 0)
IOPRN	IOP resource name.	C(10)
YIOPI	Reserved	C (1)
YITYPE	The resource type of the IOP or adapter represented by this record.	C (4)
YLND	Network interface (NWI) description: The name of the description for this network interface.	C (10)
YLSP	Line speed: The line speed expressed in bits per second (bps).	PD (11,0)
YLTFT	Total number of frames transmitted.	PD (11,0)
YLTFR	Total number of frames received.	PD (11,0)
YLIFT	Total number of I-frames transmitted.	PD (11,0)
YLIFR	Total number of I-frames received.	PD (11,0)
YLICT	Total number of I-frames characters transmitted.	PD (11,0)
YLICR	Total number of I-frames characters received.	PD (11,0)
YLPRCL	Protocol type: Y for frame relay.	C (1)
YLRFT	Number of receive-not-ready (RNR) frames transmitted.	PD (11,0)
YLRFR	Number of receive-not-ready (RNR) frames received.	PD (11,0)
YLFFT	Number of frame-reject frames transmitted.	PD (11,0)
YLFFR	Total number of frame-reject frames received.	PD (11,0)
YLRJFR	Number of reject frames received.	PD (11,0)
YLRJFT	Number of reject frames transmitted.	PD (11,0)
YLSFT	Number of set asynchronous balanced mode extended (SABME) frames transmitted.	PD (11,0)
YLSFR	Number of set asynchronous balanced mode extended (SABME) frames received.	PD (11,0)
YLDFT	Number of disconnect (DISC) frames transmitted.	PD (11,0)
YLDFR	Number of disconnect (DISC) frames received.	PD (11,0)

Field Name	Description	Attribute
YLDMT	Number of disconnect mode (DM) frames transmitted.	PD (11,0)
YLDMR	Number of disconnect mode (DM) frames received.	PD (11,0)
YLN2R	N2 retries end count: This count is updated when the host has attempted to contact a station n times, and the T1 timer ended n times before the station responded.	PD (11,0)
YLT1T	T1 timer end count: Number of times the T1 timer ended. This count is updated when the host has attempted to contact a station n times, and the T1 timer ended n times before the station responded.	PD (11,0)
YMLTI	Local management interface (LMI) time-outs.	PD (11,0)
YMLSE	Local management interface (LMI) sequence errors.	PD (11,0)
YMLPE	Local management interface (LMI) protocol errors.	PD (11,0)
YMPDE	Port monitor data set ready (DSR) errors.	PD (11,0)
YMPCE	Port monitor clear to send (CTS) errors.	PD (11,0)
YMMER	MAC errors.	PD (11,0)
YLPORT	Reserved	C (10)

Related reference

Collection Services data files: System category and file relationships

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: File abbreviations

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRDTA) command See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMHDLC

This database file includes high-level data link control (HDLC) file entries.

Statistics are kept on a line basis for the fields in the HDLC file.

Field Name	Description	Attribute
INTNUM	Interval number: the nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
IOPRN	IOP resource name.	C (10)
SHIOP	Reserved	C (1)

Field Name	Description	Attribute
SHTYPE	The resource type of the IOP or adapter represented by this record.	C (4)
SHLND	Line description: The name of the description for this line.	C (10)
SHLSP	Line speed: The speed of the line in bits per second (bps.)	PD (11,0)
SHBTRN	Bytes transmitted: The number of bytes transmitted including bytes transmitted again.	PD (11,0)
SHBRCV	Bytes received: The number of bytes received including all bytes in frames that had any kind of error.	PD (11,0)
SHPRCL	Protocol type: S for SDLC.	C (1)
SHFTRN	Number of frames transmitted (I, supervisory, and frames not numbered) excluding frames transmitted again.	PD (11,0)
SHIFTR	Number of I-frames transmitted excluding I-frames transmitted again.	PD (11,0)
SHIFRT	Number of I-frames transmitted again.	PD (11,0)
SHFRT	Number of I, supervisory, and frames not numbered transmitted again.	PD (11,0)
SHEFFR	Error-free frames received: The number of I, supervisory, and frames not numbered received without error (whether or not they were transmitted again from the remote side.)	PD (11,0)
SHEFIR	Error-free I-frames received: The number of I-frames received without error (whether or not they were transmitted again from the remote side.)	PD (11,0)
SHFRIE	Frames received in error: The number of I, supervisory, and frames not numbered received in error. There are three error possibilities: (1) a supervisory or I-frame was received with an Nr count that is requesting retransmission of a frame, (2) an I-frame was received with an Ns count that indicates that frames were missed, (3) a frame is received with one of the following errors: a frame check sequence error, an abnormal end, a receive overrun, or a frame truncated error.	PD (11,0)
SHIFR	Frames received that are not valid: The number of not valid frames received. These are frames received with either: (1) short frame error-frame is less than 32 bits or (2) residue error-frame is not on a byte boundary.	PD (11,0)
SHRRFT	Number of receive ready supervisory frames transmitted.	PD (11,0)
SHRRFR	Number of receive ready supervisory frames received.	PD (11,0)

Field Name	Description	Attribute
SHRNRT	Number of receive not ready supervisory frames transmitted.	PD (11,0)
SHRNRR	Number of receive not ready supervisory frames received.	PD (11,0)
SHLNKR	Data link resets: The number of times a set normal response mode (SNRM) was received when the station was already in normal response mode.	PD (11,0)
SHCPT	The length of time (in tenths of seconds) that the system waits for the response to a poll while in normal disconnect mode before polling the next station.	PD (3,0)
SHPORT	Reserved	C (10)

Related reference

Collection Services data files: System category and file relationships

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: File abbreviations

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRDTA) command See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMHTTPB

This database file contains basic data collected by the IBM HTTP Server (powered by Apache) category.

This file represents basic data associated with each instance of the server. This file will contain one record per interval per server instance.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
DTECEN	Century digit: where 0 indicates 19XX and 1 indicates 20XX.	C (1)
HTJNAM	Server job name (server name) This field and next two server job fields identify the child job for the server.	C (10)
HTJUSR	Server job user.	C (10)
HTJNBR	Server job number.	C (6)
HTSSDT	Server start date/time (<i>yyyymmddhhmmss</i>): most recent start or restart time.	C (14)

Field Name	Description	Attribute
HTTHDA	Threads active: The number of threads doing work when the data was sampled.	B (9,0)
HTTHDI	Threads idle: The number of idle threads when the data was sampled.	B (9,0)
HTNINC	Inbound connections (not SSL): The number of non-SSL inbound connections accepted by the server.	B(18,0)
HTSINC	Inbound connections (SSL): The number of SSL inbound connections accepted by the server.	B (18,0)
HTRRCV	Requests received: The number of requests of all types received by the server.	B (18,0)
HTRSND	Responses sent: The number of responses of all types sent by the server.	B (18,0)
HTBRQR	Requests rejected: The number of requests received that were not valid.	B (18,0)
DATETIME	Interval date and time: The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp

Related reference

Collection Services data files: QAPMHTTTPD

This database file contains detail data collected by the HTTP Server (powered by Apache) category.

Collection Services data files: QAPMSMHTP

This database file contains summarized metrics from IBM HTTP Server (powered by Apache) data (*HTTP collection category) that can be used in support of system monitoring.

Collection Services data files: System category and file relationships

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: File abbreviations

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRTA) command See the Create Performance Data (CRTPFRTA) command for information on how to create performance database files.

Collection Services data files: QAPMHTTTPD

This database file contains detail data collected by the HTTP Server (powered by Apache) category.

This file contains detailed data that is repeated for different request types which are processed by the server. One record will be written to this file for each configured request type in each active server instance each interval.

Note: Request types are reported as long as they are configured for the server regardless of whether any data was processed by them.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRTA) command.	PD (5,0)

Field Name	Description	Attribute
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
DTECEN	Century digit: where 0 indicates 19XX and 1 indicates 20XX.	C (1)
HTJNAM	Server job name (server name): This and next two server job fields identify the child job for the server.	C (10)
HTJUSR	Server job user.	C (10)
HTJNBR	Server job number.	C (6)
HTRTYP	Request type: This identifies the type of request being reported by this record. Typical values are: <ul style="list-style-type: none"> • SR - Requests handled internally by server • SL - Requests of all types received via SSL (SSL is not actually a request type. This record reports activity that occurred over an SSL connection even though that activity is also reported with other applicable request types.) • PX - Proxy requests • CG - CGI requests • WS - WebSphere® requests • JV - IBM Java™ Servlet Engine requests • UM - Requests handled by user modules • FS - Static requests handled by FRCA (Fast Response Cache Accelerator) • FX - Requests proxied by FRCA 	C (2)
HTRQSR	Requests received.	B (18,0)
HTRQSS	Responses sent.	B (18,0)
HTBRQS	Error responses sent.	B (18,0)
HTNOCR	Non-cached requests processed. Note: Cache is not used and therefore this field is reserved for the following request types: SL, CG, WS, JV, and UM.	B (18,0)
HTBRCV	Bytes received.	B (18,0)
HTBSND	Bytes sent.	B (18,0)
HTNRTM	Processing time for non-cached requests in milliseconds.	B (9,0)

Field Name	Description	Attribute
HTCRTM	Processing time for cached requests in milliseconds. Note: cache is not used and therefore this field is reserved for the following request types: SL, CG, WS, JV, and UM.	B (9,0)
DATETIME	Interval date and time: The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp

Related reference

Collection Services data files: [QAPMHTTPB](#)

This database file contains basic data collected by the IBM HTTP Server (powered by Apache) category.

Collection Services data files: [QAPMSMHTP](#)

This database file contains summarized metrics from IBM HTTP Server (powered by Apache) data (*HTTP collection category) that can be used in support of system monitoring.

Collection Services data files: [System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: [File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRDTA) command See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMIDLC

This database file includes integrated services digital network (ISDN) data link control file entries and lists the fields in the ISDN data link control (IDLC) file.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
IOPRN	IOP resource name.	C(10)
ISIOP	Reserved	C (1)
ISTYPE	The resource type of the IOP or adapter represented by this record.	C (4)
ISLND	Line description: The name of the line description.	C (10)
ISNWI	Network interface description: The name of the network interface description.	C (10)

Field Name	Description	Attribute
ISLSP	Link speed: The speed of this channel in bits per second.	PD (11,0)
ISPRCL	Protocol type: I for IDLC.	C (1)
ILCRCE	Receive CRC errors: The number of received frames that contain a cycle redundancy check (CRC) error.	PD (11,0)
ILSFE	Short frame errors: The number of short frames received. A short frame is a frame that has fewer octets between its start flag and end flag than is permitted.	PD (11,0)
ILORUN	Receive overrun: The number of times the ISDN subsystem could not keep pace with incoming data because of local controller overload.	PD (11,0)
ILURUN	Transmit underrun: The number of times the ISDN subsystem could not keep pace with outgoing data because of local controller overload.	PD (11,0)
ILABRT	Aborts received: The number of frames received that contained HDLC abort indicators.	PD (11,0)
ILFRIE	Frames received in error: The sum of receive CRC errors, short frame errors, receive overrun, transmit underrun, aborts received, and frame sequence errors (ILCRCE, ILSFE, ILORUN, ILURUN, ILABRT, ISSEQE).	PD (11,0)
ISFRT	Retransmitted frames.	PD (11,0)
ISSEQE	Sequence errors: The number of received frames that contained sequence numbers indicating frames were lost.	PD (11,0)
ISFTRN	Total number of frames transmitted: This includes information (I), unnumbered information (UI), and supervisory (S) frames sent to a remote link station. This includes frames retransmitted and frames sent on transmissions stopped by transmit underruns, in addition to successful transmissions.	PD (11,0)
ISFRCV	Total number of frames received: This includes information (I), unnumbered information (UI), and supervisory (S) frames received from the remote link station. This includes no errors.	PD (11,0)
ISBTRN	Total bytes transmitted: The total number of bytes transmitted to a remote link station. This includes bytes retransmitted and bytes sent on transmissions stopped by a transmit underrun, in addition to successful transmissions.	PD (11,0)
ISBRCV	Total bytes received: The total number of bytes received from the remote link station. This includes no errors.	PD (11,0)
ISB1	B1 channel: Set to one if the B1 channel was used.	PD (1,0)
ISB2	B2 channel: Set to one if the B2 channel was used.	PD (1,0)

Field Name	Description	Attribute
ISCHAN	B channel used: The B channel used is associated with a bit in this field being set to 1. Bit 0 (most significant bit) and 31 (least significant bit) are reserved. Bits 1 to 30 are associated with B channels 30 to 1, respectively.	C (4)
ISPORT	Reserved	C (10)

Related reference

Collection Services data files: [System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: [File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRDTA) command See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMIOPD

This database file lists the fields in the IOP extended data file.

Data is reported for the Network Server (*IPCS category) and I/O adapters (*IOPBASE category). Network server data includes Integrated xSeries Server data and virtual I/O data. Virtual I/O data consists of one record for each virtual device in use. If Network Server is associated with a Network Server Host Adapter, virtual device might have more than one record reported per interval--one record for each Network Server Host Adapter, used by this virtual device. If concurrent maintenance is done (adding or removing hardware under an IOP), the user should cycle the collector to insure that I/O adapter data is reported correctly.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yyymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: the number of seconds since the last sample interval. For operating system data (data type 2), this value might not be the same as the change in the interval date and time (DTETIM) for the interval because the elapsed interval time comes directly from the Integrated xSeries Server .	PD (7,0)
IOPRN	IOP resource name.	C(10)
XIIOP	Reserved	C (1)

Field Name	Description	Attribute
XITYPE	The type of IOP represented by this record.	C (4)
XIDTYP	Data type: <ul style="list-style-type: none"> • 1 -- Reserved • 2 -- OS/2 or other operating system (*IPCS category) • 3 -- HPF386 (*IPCS category) • 4 -- LAN Server (*IPCS category) • 5 -- Virtual I/O (*IPCS category) • A -- I/O adapter (*IOPBASE category) 	C (1)
XIDTA1	Data field 1	C (2)
XIDTA2	Data field 2	C (12)
XICT01	Counter 1	PD (11)
XICT02	Counter 2	PD (11)
XICT03	Counter 3	PD (11)
XICT04	Counter 4	PD (11)
XICT05	Counter 5	PD (11)
XICT06	Counter 6	PD (11)
XICT07	Counter 7	PD (11)
XICT08	Counter 8	PD (11)
XICT09	Counter 9	PD (11)
XICT10	Counter 10	PD (11)
XICT11	Counter 11	PD (11)
XICT12	Counter 12	PD (11)
XICT13	Counter 13	PD (11)
XICT14	Counter 14	PD (11)
XICT15	Counter 15	PD (11)
XICT16	Counter 16	PD (11)
XICT17	Counter 17	PD (11)
XICT18	Counter 18	PD (11)
XICT19	Counter 19	PD (11)
XICT20	Counter 20	PD (11)
XICT21	Counter 21	PD (11)
XICT22	Counter 22	PD (11)
XICT23	Counter 23	PD (11)

Field Name	Description	Attribute
XICT24	Counter 24	PD (11)
XICT25	Counter 25	PD (11)
XICT26	Counter 26	PD (11)
XICT27	Counter 27	PD (11)
XICT28	Counter 28	PD (11)
XICT29	Counter 29	PD (11)
XICT30	Counter 30	PD (11)
XICT31	Counter 31	PD (11)
XICT32	Counter 32	PD (11)
XICT33	Counter 33	PD (11)
XICT34	Counter 34	PD (11)
XICT35	Counter 35	PD (11)
XICT36	Counter 36	PD (11)
XICT37	Counter 37	PD (11)
XICT38	Counter 38	PD (11)
XICT39	Counter 39	PD (11)
XICT40	Counter 40	PD (11)
XICT41	Counter 41	PD (11)
XICT42	Counter 42	PD (11)
XICT43	Counter 43	PD (11)
XICT44	Counter 44	PD (11)
XICT45	Counter 45	PD (11)
XICT46	Counter 46	PD (11)
XICT47	Counter 47	PD (11)
XICT48	Counter 48	PD (11)
XICT49	Counter 49	PD (11)
XICT50	Counter 50	PD (11)
XIADRN	Adapter resource name: If the resource reported is an adapter, then this field will contain the resource name of that adapter. If the resource reported is an IOP, then this field will contain the resource name of that IOP.	C (10)
XINWSD	Network server description name (blanks are reported if a network server description (NWSD) name is not applicable).	C (10)

Field Name	Description	Attribute
XINWSH	Network server host adapter name (blanks are reported if a network server host adapter (NWSH) name is not applicable.	C (10)

Note:

The following chart shows the types of counters used.

D (Delta counter): Number of occurrences in the interval (what most performance counters are).

S (State counter): The value at the time of collection or the maximum value during the interval.

XIDTYP = '1' (Reserved)	
XIDTYP = '2' (OS/2 or other operating system)	
Counter	Description
(CT01) D	CPU time (milliseconds). This value is normalized to the range of a single processor for adapters that have multiple processors.
(CT02) D	Number of times threads rescheduled
(CT03) D	Number of interrupts
(CT04) D	CPU time servicing interrupts (milliseconds)
(CT05) D	Number of page faults
(CT06) D	Number of pages swapped in
(CT07) D	Number of pages demand-loaded
(CT08) D	Number of pages swapped out
(CT09) D	Number of pages discarded
(CT10) D	Number of idle pages recovered
(CT11) D	Number of pages idled
(CT12) D	Number of idle pages reassigned
(CT13) S	Number of elements in free queue
(CT14) S	Length of time elements in free queue (milliseconds)
(CT15) S	Number of elements in used queue
(CT16) S	Length of time elements in used queue (milliseconds)
XIDTYP = '3' (HPFS386)	
XIDTYP = '4' (LAN server)	
Record types 3 (HPFS386) and 4 (LAN server) refer to functions that are no longer supported.	
XIDTYP = '5' (Virtual I/O)	
Counter	Description

XIDTYP = '1' (Reserved)	
XIDTYP = '2' (OS/2 or other operating system)	
Counter	Description
(DTA1) S	Type of a virtual device: <ul style="list-style-type: none"> • ' 1' = Adapter • ' 2' = Disk • ' 3' = Optical • ' 4' = Tape
(DTA2) S	<ul style="list-style-type: none"> • Characters 1-10: Virtual device name. Note: For tape and optical devices this is the device resource name. For disk devices, this is the name of the network server storage space. • Characters 11-12: Reserved (blank).
(CTO1) D	Read operations
(CTO2) D	Write operations
(CTO3) D	Other operations
(CTO4) D	Operations resulting in an error
(CTO5) D	Kilobytes read from virtual device
(CTO6) D	Kilobytes written to virtual device
(CTO7) S	Reserved
(CTO8) S	Reserved
XIDTYP = 'A'(I/O adapter data)	
(DTA1) S:	Reserved (blank)
(DTA2) S:	<ul style="list-style-type: none"> • Characters 1-4: I/O adapter type • Characters 5-7: I/O adapter model • Characters 8-12: Reserved (blank)
(CTO1) D:	Adapter time: Total processing time used by adapter tasks that are running in the primary IOP processor. Adapter tasks support the adapter and its attached hardware. For some old IOPs such as the 6112, adapter times are not reported.

Related reference

[Collection Services data files: System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

[Data files: File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

[Create Performance Data \(CRTPFRTA\) command](#) See the Create Performance Data (CRTPFRTA) command for information on how to create performance database files.

Collection Services data files: QAPMISUM

This database file contains interval summary information.

This file is produced when *JOBMI, *JOBOS, and *SYSLVL categories are all requested on the Create Performance Data (CRTPFRDTA) command. The wait group descriptions are reported in the QAPMJOBWTD file. One record is written per interval.

Field Name	Description	Attribute
INTNUM	Interval number. The <i>n</i> th sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds. The number of seconds since the last sample interval.	PD (7,0)
DTECEN	Century digit: where 0 indicates 19XX and 1 indicates 20XX.	C (1)
JWDSEQ	Description sequence number. Identifies the QAPMJOBWTD records associated with the wait data for this interval.	B (4,0)
JWCT01	Wait count 1. The number of times all jobs that encountered wait states that are associated with this group within the interval.	B (9,0)
JWTM01	Wait time 1. The time in microseconds all jobs spent waiting within this group within the interval.	B (18,0)
JWJC01	Contributor count 1. The number of threads or tasks that contributed to this group within the interval. A contributor is defined as a thread or task that had nonzero time for wait states associated with this group within the interval. This number includes threads or tasks that were blocked through the entire interval for this group.	B (9,0)
JBCT02-JWCT32 JWTM02-JWTM32 JWJC02-JWJC32	Counts, times, and contributor counts are repeated for up to 32 counter sets per record.	B (9,0) B (18,0) B (9,0)

Field Name	Description	Attribute
JBDBR	Synchronous database reads. Total number of physical synchronous database read operations for database functions for all jobs within the interval.	B (9,0)
JBNDDB	Synchronous nondatabase reads. Total number of physical synchronous nondatabase read operations for nondatabase functions for all jobs within the interval.	B (9,0)
JBDBW	Synchronous database writes. Total number of physical synchronous database write operations for database functions for all jobs within the interval.	B (9,0)
JBNDW	Synchronous nondatabase writes. Total number of synchronous physical nondatabase write operations for nondatabase functions for all jobs within the interval.	B (9,0)
JBADBR	Asynchronous database reads. Total number of asynchronous physical database read operations for database functions for all jobs within the interval.	B (9,0)
JBANDR	Asynchronous nondatabase reads. Total number of asynchronous physical nondatabase read operations for nondatabase functions for all jobs within the interval.	B (9,0)
JBADBW	Asynchronous database writes. Total number of asynchronous physical database write operations for database functions for all jobs within the interval.	B (9,0)
JBANDW	Asynchronous nondatabase writes. Total number of asynchronous physical nondatabase write operations for nondatabase functions for all jobs within the interval.	B (9,0)
JBCPU	Unscaled CPU time charged. The amount of unscaled processing time (in microseconds) charged to all jobs within the interval.	B (18,0)

Field Name	Description	Attribute
JBSCPU	Scaled CPU time charged. The amount of scaled processing time (in microseconds) charged to all jobs within the interval.	B (18,0)
JBTFLT	Page faults. Total page faults for all jobs within the interval.	B (9,0)
JBIPF	I/O pending faults. Total number of times a page fault occurred on an address that was currently part of an auxiliary storage I/O operation for all jobs within the interval.	B (9,0)
JBSKSC	Socket sends. Total number of socket send operations that were performed by all jobs within the interval.	B (9,0)
JBSKBS	Socket bytes sent. Total number of bytes sent via socket operations by all jobs within in the interval.	B (18,0)
JBSKRC	Socket receives. Total number of socket receive operations that were performed by all jobs within the interval.	B (9,0)
JBSKBR	Socket bytes received. Total number of bytes received via socket operations by all jobs within the interval.	B (18,0)
JBTDECNT	Total threads or tasks. Total number of threads or tasks reported within the interval. This count includes the following threads or tasks: <ul style="list-style-type: none"> • Threads or tasks that terminated during the interval • Transient threads or tasks • Threads or tasks that were active at the end of the interval, whether they were blocked or not 	B (9,0)
JBTDETR	Transient threads or tasks. Total number of transient threads or tasks within the interval. A transient thread or task is defined as a thread or task that started and ended during the interval.	B (9,0)

Field Name	Description	Attribute
JBJOBCNT	<p>Total jobs. Total number of jobs reported within the interval. This count includes the following jobs:</p> <ul style="list-style-type: none"> • Jobs that terminated during the interval • Transient jobs • Jobs that were active at the end of the interval 	B (9,0)
JBJOBTR	<p>Transient jobs. Total number of transient jobs within the interval. A transient job is defined as a job that started and ended during the interval.</p>	B (9,0)
JBRSP	<p>Display (5250) transaction time (in milliseconds) for all interactive jobs within in the interval.</p>	B (18,0)
JBNTR	<p>Number of display (5250) transactions for all interactive jobs within the interval.</p>	B (9,0)
JBLWT	<p>Logical database writes. Total number of times the internal database write function was called by all jobs within the interval. This number does not include I/O operations to readers/writers, or I/O operations caused by the CPYSPLF or DSPSPLF command. If SEQONLY(*YES) is specified, these numbers show each block of records written, not the number of individual records written.</p>	B (9,0)
JBLRD	<p>Logical database reads. Total number of times the database module was called by all jobs within the interval. This number does not include I/O operations to readers/writers, or I/O operations caused by the CPYSPLF or DSPSPLF command. If SEQONLY(*YES) is specified, these numbers show each block of records read, not the number of individual records read.</p>	B (9,0)

Field Name	Description	Attribute
JBDBU	Miscellaneous logical database operations. The number of miscellaneous logical database operations (updates, deletes, force-end-of-data, opens, closes, and releases) performed by all jobs within the interval.	B (9,0)
JBBCO	Database commit operations. Total number of database commit operations performed by all jobs within the interval.	B (9,0)
JBBRO	Database rollback operations. Total number of database rollback operations performed by all jobs within the interval.	B (9,0)
JBLBO	SQL cursor count. Total cumulative number of SQL cursors that were full opened by all jobs within the interval.	B (9,0)
JBLBS	SQL cursor reuse. Total cumulative number of SQL cursors that were pseudo-opened by all jobs within the interval. Pseudo-opens are also known as <i>reused SQL cursors</i> .	B (9,0)
JBRSD1	Reserved.	B (18,0)
JBRSD2	Reserved.	B (18,0)
JBRSD3	Reserved.	B (9,0)
JBRSD4	Reserved.	B (9,0)
DATETIME	Interval date and time. The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time. The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp
JBNUS	Full opens. The number of native database (non-SQL) files and SQL cursors that were full opened by all jobs within the interval. Subtracting the value within field JBLBO from JBNUS yields the number of non-SQL full opens.	B (9,0)
JBPGA	Total number of 4096-byte units of temporary and permanent storage that was allocated by all jobs within the interval.	B (9,0)

Field Name	Description	Attribute
JBPGD	Total number of 4096-byte units of temporary and permanent storage that was deallocated by all jobs within the interval.	B (9,0)
JBTMPPGA	Total number of 4096-byte units of temporary storage that was allocated by all jobs within the interval.	B (9,0)
JBTMPPGD	Total number of 4096-byte units of temporary storage that was deallocated by all jobs within the interval.	B (9,0)
JBSQLDBR	SQL synchronous database reads. Total number of physical synchronous database read operations that were done on behalf of an SQL operation for all jobs within the interval.	B (18,0)
JBSQLNDBR	SQL synchronous nondatabase reads. Total number of physical synchronous nondatabase read operations that were done on behalf of an SQL operation for all jobs within the interval.	B (18,0)
JBSQLDBW	SQL synchronous database writes. Total number of physical synchronous database write operations that were done on behalf of an SQL operation for all jobs within the interval.	B (18,0)
JBSQLNDBW	SQL synchronous nondatabase writes. Total number of synchronous physical nondatabase write operations that were done on behalf of an SQL operation for all jobs within the interval.	B (18,0)
JBSQLADBR	SQL asynchronous database reads. Total number of asynchronous physical database read operations that were done on behalf of an SQL operation for all jobs within the interval.	B (18,0)
JBSQLANDBR	SQL asynchronous nondatabase reads. Total number of asynchronous physical nondatabase read operations that were done on behalf of an SQL operation for all jobs within the interval.	B (18,0)

Field Name	Description	Attribute
JBSQLADBW	SQL asynchronous database writes. Total number of asynchronous physical database write operations that were done on behalf of an SQL operation for all jobs within the interval.	B (18,0)
JBSQLANDBW	Asynchronous nondatabase writes. Total number of asynchronous physical nondatabase write operations that were done on behalf of an SQL operation for all jobs within the interval.	B (18,0)
JBLWTSQL	<p>SQL-related logical database writes. Total number of times the internal database write function was called on behalf of an SQL operation by all jobs within the interval. This number does not include I/O operations to readers/writers, or I/O operations caused by the CPYSPLF or DSPSPLF command. If SEQONLY(*YES) is specified, these numbers show each block of records written, not the number of individual records written.</p> <p>This field can be compared to JBLWT to understand the portion of database writes that are due to SQL activity. Subtracting JBLWTSQL from JBLWT yields the number of non-SQL related database writes.</p>	B (18,0)

Field Name	Description	Attribute
JBLRDSQL	<p>SQL-related logical database reads. Total number of times the database module was called on behalf of an SQL operation by all jobs within the interval. This number does not include I/O operations to readers/writers, or I/O operations caused by the CPYSPLF or DSPSPLF command. If SEQONLY(*YES) is specified, these numbers show each block of records read, not the number of individual records read.</p> <p>This field can be compared to JBLRD to understand the portion of database reads that are due to SQL activity. Subtracting JBLRDSQL from JBLRD yields the number of non-SQL related database reads.</p>	B (18,0)
JBDBUSQL	<p>SQL-related miscellaneous logical database operations. The number of miscellaneous logical database operations (updates, deletes, force-end-of-data, opens, closes, and releases) performed on behalf of an SQL operation by all jobs within the interval.</p> <p>This field can be compared to JBDBU to understand the portion of database miscellaneous operations that are due to SQL activity. Subtracting JBDBUSQL from JBDBU yields the number of non-SQL related database miscellaneous operations.</p>	B (18,0)

Related reference

Collection Services data files: [QAPMJOBMI](#)

These database file entries contain task, primary, and secondary thread data that are collected with the *JOBMI category. "Job" implies job, task, or thread.

Collection Services data files: [QAPMJOBOS](#)

These database file entries contain data specific to system jobs.

Collection Services data files: [QAPMJOBWTD](#)

This database file contains a description of the counter sets found in file QAPMJOBWT.

Collection Services data files: [QAPMSYSTEM](#)

This database file reports system-wide performance data.

Collection Services data files: [System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: File abbreviations

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRDTA) command See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMJOBMI

These database file entries contain task, primary, and secondary thread data that are collected with the *JOBMI category. "Job" implies job, task, or thread.

Collection Services provides data only for jobs that consume CPU during an interval.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval for a job interval entry or the job end date and time for a job completion entry, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds.	PD (7,0)
DTECEN	Century digit.	C (1)
JBNAME	Job name/workstation name.	C (16)
JBUSER	Job user.	C (10)
JBNBR	Job number.	C (6)
JBTYPE	Job type. <ul style="list-style-type: none"> • A:Autostart • B:Batch • I:Interactive • M:Subsystem monitor • R:Spool reader • S:System • V:SLIC task • W:Spool writer • X:SCPF job 	C (1)

Field Name	Description	Attribute
JBSTYP	Job subtype. <ul style="list-style-type: none"> • T:MRT (System/36 environment only) • E:Evoke (communications batch) • P:Print driver job • J:Prestart job • F:M36 (Advanced/36 server job) • D:Batch immediate job • U:Alternative spool user 	C (1)
JBSTSF	Status flag: indicates job status relative to this interval. The values are: <ul style="list-style-type: none"> • 0 -- normal interval collection • 1 -- job started in interval • 2 -- job ended in interval • 3 -- job started and ended. Note: Jobs that are rerouted or transferred will result in a termination record (JBSTSF = 2) and a new job record (JBSTSF = 1).	PD (1,0)
JBTTYP	Task type (01:Resident task, 02:Supervisor task, 03:MI process task, 04:S36 emulation task).	C (2)
JBTTYE	Task type extender.	C (2)
JBPOOL	Job pool.	C (2)
JBPRTY	Job priority.	C (3)
JBCPU	Thread unscaled interval CPU time charged. The amount of unscaled processing time (in milliseconds) charged to this thread. It includes unscaled processing time used by this thread and any unscaled processing time charged to the thread by server tasks that worked on its behalf within the interval. For server tasks, this field will be zero.	PD (15,3)
JBRSP	Total transaction time (in seconds).	PD (15,3)

Field Name	Description	Attribute
JBSLC	Time-slice value (in milliseconds).	PD (11,0)
JBNTR	Number of transactions.	PD (11,0)
JBDBR	Number of synchronous database reads: Total number of physical synchronous database read operations for database functions.	PD (11,0)
JBNDDB	Number of synchronous nondatabase reads: Total number of physical synchronous nondatabase read operations for nondatabase functions.	PD (11,0)
JBWRT	Number of writes: Total number of physical database and nondatabase write operations.	PD (11,0)
JBAW	Total number of transitions from active state to wait state for this job.	PD (11,0)
JBWI	Total number of transitions from wait state to ineligible state for this job.	PD (11,0)
JBAI	Total number of transitions from active state to ineligible state for this job.	PD (11,0)
JBNDW	Number of synchronous nondatabase writes: Total number of synchronous physical nondatabase write operations for nondatabase functions.	PD (11,0)
JBDBW	Number of synchronous database writes: Total number of synchronous physical database write operations for database functions.	PD (11,0)
JBANDW	Number of asynchronous nondatabase writes: Total number of asynchronous physical nondatabase write operations for nondatabase functions.	PD (11,0)
JBADBW	Number of asynchronous database writes: Total number of asynchronous physical database write operations for database functions.	PD (11,0)

Field Name	Description	Attribute
JBANDR	Number of asynchronous nondatabase reads: Total number of asynchronous physical nondatabase read operations for nondatabase functions.	PD (11,0)
JBADBR	Number of asynchronous database reads: Total number of asynchronous physical database read operations for database functions.	PD (11,0)
JBPW	Number of synchronous permanent writes.	PD (11,0)
JBPAGF	Number of PAG faults. Total number of times the program access group (PAG) was referred to, but was not in main storage. The Licensed Internal Code no longer uses process access groups for caching data. Because of this implementation, this field will always be 0 for more current releases.	PD (11,0)
JBOBIN	Number of binary overflows.	PD (11,0)
JBODEC	Number of decimal overflows.	PD (11,0)
JBOFLP	Number of floating point overflows.	PD (11,0)
JBIPF	Number of times a page fault occurred on an address that was currently part of an auxiliary storage I/O operation.	PD (11,0)
JBWIO	Number of times the process explicitly waited for outstanding asynchronous I/O operations to complete.	PD (11,0)
JBSZWT	Total seize wait time (in milliseconds).	PD (15,3)
JBSKSC	Number of socket sends.	PD (11,0)
JBSKBS	Number of socket bytes sent.	PD (11,0)
JBSKRC	Number of socket receives.	PD (11,0)
JBSKBR	Number of socket bytes received.	PD (11,0)
JBXRFR	Stream file reads.	PD (11,0)
JBXRFW	Stream file writes.	PD (11,0)

Field Name	Description	Attribute
JBTCPU	Job unscaled interval CPU time charged. Thread unscaled interval CPU time charged (in milliseconds) totaled for all threads of the job within the interval. Note: This value may not equal the sum of JBTCPU for all threads due to timing differences in the collection and reporting of these values. This field is provided for primary threads only.	PD (15,3)
JBTHDF	Secondary thread flag. Identifies secondary threads of a multi-threaded job. The values are: 0 -- tasks and primary threads, 1 -- secondary threads.	PD (1,0)
JBTHID	Thread Identifier. A 4-byte displayable thread identifier. A hex string that is unique for threads within a process. It will be blank for tasks and prior release data.	C (8)
JBTHAC	Active threads. Current number of active threads in the process when the data was sampled. An active thread may be actively running, suspended, or waiting on a resource. Includes the primary thread.	PD (11,0)
JBTHCT	Threads created. Number of threads initiated within this job. Includes both active and terminated threads.	PD (11,0)
JBMTXT	Mutex wait time in milliseconds. Cumulative time the thread waited for a mutex.	PD (15,3)
JBIBM1	Reserved	PD (11,0)
JBINSX	Reserved.	PD (11,0)
JBSVIF	Server interactive flag. Set to '1' if the resource consumed by the function is charged to the interactive capability of the system.	C (1)
JBTFLT	Total page faults.	PD (11,0)
JBTDE	System task identifier.	C (8)
JBPTDE	Primary thread identifier.	C (8)
JBLDUM	Reserved.	PD (1,0)

Field Name	Description	Attribute
JBEDBC	Reserved	P (15,3)
JBTDDBC	Reserved	P (15,3)
JBCOP	Number of primary commit operations performed under the task.	PD (11,0)
JBCOS	Number of secondary commit operations performed under the task. This includes application and system-provided referential integrity commits.	PD (11,0)
JBDOP	Number of primary decommit operations performed under the task.	PD (11,0)
JBDOS	Number of secondary decommit operations performed under the task. This includes application and system-provided referential integrity decommits.	PD (11,0)
JBPJE	Number of physical journal write operations to disk performed under the task.	PD (11,0)
JBNSJE	Number of journal entries not directly related to SMAPP.	PD (11,0)
JBUJD	Number of SMAPP-induced journal entries deposited in user-provided journals.	PD (11,0)
JBSJD	Number of SMAPP-induced journal entries deposited in system-provided (default) journals.	PD (11,0)
JBBFW	Number of journal bytes written to disk. Such entries are packaged within the permanent area of the journal receiver. These are traditional journal entries which can be retrieved and displayed.	PD (15,0)
JBBFA	Number of bytes deposited within the permanent area of the journal receiver. This count includes both those bytes already written to disk and those still cached in main memory. These are traditional journal entries which can be retrieved and displayed.	PD (15,0)

Field Name	Description	Attribute
JBBTW	Number of transient area journal receiver bytes written to disk. The transient area contains hidden journal entries produced by the system, used during IPL, and routed to this transient area only if the customer specifies *RmvIntEnt on the CHGJRN command. This transient area is a separate area on the disk, distinct from the disk space used to store the normal journal entries.	PD (15,0)
JBBTA	Number of bytes generated for the journal receiver transient area. This count includes both transient bytes already written to disk and those still cached in main memory. The transient area contains hidden journal entries produced by the system, used during IPL, and routed to this transient area only if the customer specifies *RmvIntEnt on the CHGJRN command. This transient area is a separate area on the disk, distinct from the disk space used to store the normal journal entries.	PD (15,0)
JBTWT	Amount of time this task spent waiting for journal bundles to be written to disk (in milliseconds). This includes time spent waiting for physical disk write operations initiated by this task to be serviced, as well as time spent waiting for physical disk write operations initiated by other tasks whose journal entries reside in the same journal bundle.	PD (11,0)
JBTNW	Number of times this task waited for journal bundles to be written to disk.	PD (11,0)
JBXRRR	Number of random stream file read operations. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)) and user-defined file systems.	PD (11,0)

Field Name	Description	Attribute
JBXRRW	Number of random stream file write operations. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)) and user-defined file systems.	PD (11,0)
JBXRFS	Number of fsync operations. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)) and user-defined file systems.	PD (11,0)
JBXRBR	Stream file bytes read. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)) and user-defined file systems.	PD (15,0)
JBXRBW	Stream file bytes written. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)) and user-defined file systems.	PD (15,0)
JBFSH	Number of full secure sockets layer (SSL) handshakes that use server authentication.	PD (11,0)
JBASH	Number of abbreviated (or fast) secure sockets layer (SSL) handshakes that use server authentication.	PD (11,0)
JBFSHA	Number of full secure sockets layer (SSL) handshakes that use server and client authentication.	PD (11,0)
JBASHA	Number of abbreviated (or fast) secure sockets layer (SSL) handshakes that use server and client authentication.	PD (11,0)
JBPGA	Total number of 4096-byte units of temporary and permanent storage that have been allocated by the thread since the thread started.	P (11,0)

Field Name	Description	Attribute
JBPGD	Total number of 4096-byte units of temporary and permanent storage that have been deallocated by the thread since the thread started.	P (11,0)
JBCUSR	The user profile that the job was running under at the time the data was sampled.	C (10)
JBACPU	Accumulated job unscaled CPU time charged in milliseconds. The accumulated unscaled interval CPU time charged for all threads of the job since the job started. Note: This field is provided for primary threads only.	PD (15,3)
JBIPAF	The remote IP address family flag indicates the type of IP address information provided in field JBIPAD. The following are supported (see <sys/socket.h> and the API referenced under JBIPAD for more information on these values): <ul style="list-style-type: none"> • Hex 00 = Not set • Hex 02 = AF_INET (IPv4) • Hex 18 = AF_INET6 (IPv6) Note: An address may not be available if there is no current connection.	C (1)
JBIPAD	The binary form of IPv4 or IPv6 remote IP address most recently communicated with over sockets. If a sockets connection has not been established or has terminated (JBIPAF = X'00'), this field will be blank. An IPv4 address is 4 bytes long left justified in this field. An IPv6 address uses all 16 bytes. For examples and further explanation, refer to the Usage Notes section in the Convert IPv4 and IPv6 Addresses Between Text and Binary Form (inet_pton) API	C (16)
JBIPPT	The remote port number used in this connection.	P (5,0)
JBUAUF	Reserved.	C (1)

Field Name	Description	Attribute
JBPGRQ	Page frames requested. Number of new page frames required by thread to satisfy page fault, read or clear operation.	B (9,0)
JBPGRL	Page frames released. Number of page frames explicitly released by thread.	B (9,0)
JBMSLR	File system symbolic link reads. This count includes the following file systems: Root (/), QOpenSys, and user-defined file systems.	B (9,0)
JBMDYR	File system directory reads. This count includes the following file systems: Root (/), QOpenSys, and user-defined file systems.	B (9,0)
JBMLCH	File system directory lookup cache hits. This count includes the following file systems: Root (/), QOpenSys, and user-defined file systems.	B (9,0)
JBMLCM	File system lookup cache misses. This count includes the following file systems: Root (/), QOpenSys, and user-defined file systems.	B (9,0)
JBMOPN	File system opens. This count includes the following file systems: Root (/), QOpenSys, and user-defined file systems.	B (9,0)
JBMNDC	File system non-directory creates. Count of create operations for non-directory objects such as files or symbolic links. This count includes the following file systems: Root (/), QOpenSys, and user-defined file systems.	B (9,0)
JBMNDD	File system non-directory deletes. Count of delete operations for non-directory objects such as files or symbolic links. This count includes the following file systems: Root (/), QOpenSys, and user-defined file systems.	B (9,0)

Field Name	Description	Attribute
JBSCPU	<p>Thread scaled interval CPU time used charged. The amount of scaled processing time (in microseconds) charged to this thread. It includes scaled processing time used by this thread and any scaled processing time charged to the thread by server tasks that worked on its behalf within the interval.</p> <p>For server tasks, this field will be zero.</p> <p>Note: The ratio of JBSCPU to JBCPU shows the current processor speed in relation to nominal processor speed.</p>	B (18,0)
JBSTCPU	<p>Job scaled interval CPU time charged. Thread scaled interval CPU time charged (in microseconds) totaled for all threads of the job within the interval.</p> <p>Note: This may not equal the sum of JBSCPU for all threads due to timing differences in the collection and reporting of these values. This field is provided for primary threads only.</p>	B (18,0)
JBFLDR1	Reserved.	B (18,0)
JBFLDR2	Workload capping group delay time (in microseconds). The amount of time this thread could not be dispatched due to workload capping.	B (18,0)
JBFLDR3	Workload capping group. The identifier for the workload capping group this thread belonged to at the time this data was sampled. A value of zero is reported when no group was assigned.	B (9,0)
JBFLDR4	Reserved.	B (9,0)

Field Name	Description	Attribute
JBJVMF	<p>JVM started. Indicates if this process has ever started a JVM.</p> <ul style="list-style-type: none"> • ‘ ‘ = unknown / not defined • ‘0’ = No • ‘1’ = Yes • ‘2’ = JVM was active at time of sample <p>Note: Note: This field is provided for primary threads only.</p>	C (1)
JBJVMT	<p>JVM Type If JBJVMF is set to something other than x “00”, it indicates the type of JVM that was started.</p> <ul style="list-style-type: none"> • x’00’ = unknown / not defined • x’01’ = IBM Technology for Java - 32 Bit • x’02’ = IBM Technology for Java - 64 Bit • x’99’ = Classic JVM <p>Note: This field is provided for primary threads only.</p>	H (1)
JBPASE	<p>i5/OS PASE run time – Indicates if an i5/OS PASE runtime was active in the thread at the time this data was sampled.</p> <ul style="list-style-type: none"> • ‘ ‘ = unknown / not defined • ‘0’ = No • ‘1’ = Yes 	C (1)
JBJTHDT	<p>JVM thread type. For secondary threads within a process that has a JVM active, this field may be used to identify the type or function of the thread. Values other than those defined are reserved.</p> <p>Values supported by the IBM Technology for Java VM are:</p> <ul style="list-style-type: none"> • x’00’ = Thread not assigned • x’1E’ - x’3B’ = GC Thread • x’3C’ - x’59’ = Finalization Thread • x’5A’ - x’77’ = JIT Thread • x’78’ - x’95’ = JVM Internal Thread 	H (1)

Field Name	Description	Attribute
JBNFHN	An identifier of a resource affinity domain this software thread or task is associated with. Thread or task is associated with resource affinity domain at a create time, but operating system may decide to move it to another resource affinity domain at a later time.	H (2)
JBNFLVL	<p>Resource affinity level specifies the relative strength of the binding between a thread and the internal machine resources with which it has affinity (processors and main storage).</p> <ul style="list-style-type: none"> • Hex 00 = Processor normal, main storage normal • Hex 01 = Processor normal, main storage high • Hex 10 = Processor high, main storage normal • Hex 11 = Processor high, main storage high • Hex 03 = Processor normal, main storage none • Hex 20 = Processor low, main storage normal 	H (1)

Field Name	Description	Attribute
JBNFGRP	<p>Identifier of a resources affinity group or resource affinity domain. This identifier specifies how threads or tasks are related to other threads or tasks in their use of internal machine processing resources, or how they are related to specific resource affinity domains.</p> <ul style="list-style-type: none"> • Hex 00000000 = Independent This thread is not part of any affinity group and has no affinity to any specific resource affinity domain. Operating system determines which domain is used by this thread. • Hex 00010000 = Anonymous internal affinity group This thread is part of any anonymous internal affinity group which was created for an initial thread of this job. Operating system will choose the resource affinity domain for this group, but all threads within this job will have affinity to the same resource affinity domain. • Hex 40000000 - 7FFFFFFF = External affinity group identifier This thread is part of external affinity group, which was explicitly specified when this job was created. Operating system will choose the resource affinity domain for this group, but all threads for all jobs within this group will have affinity to the same resource affinity domain. • Hex FFFF0000 - FFFFFFFF = Affinity to a specific resource affinity domain This thread has affinity to a specific resource affinity domain. However, the resource affinity domain used by this thread is not specified directly. Rather an abstract number is used which is deterministically mapped by the operating system into a specific resource affinity domain. The same number is always mapped to the same domain and a set of consecutive values is mapped to different domains (for as 	H (4)

Field Name	Description	Attribute
JBNFHNC	Local dispatch time. Amount of CPU time used by the thread on the resource affinity domain this thread is associated with. The time is reported in internal model-independent units. See Note on the next field (JBNFFNC).	B (18, 0)
JBNFFNC	Non-local dispatch time. Amount of CPU time used by the thread on resource affinity domains other than the one this thread is associated with, but within the same group. The time is reported in internal model-independent units. Note: JBNFHNC and JBNFFNC fields do not have significance by themselves. The ratio of JBNFHNC to JBNFFNC shows relative amount of time this thread was dispatched to its optimal resource affinity domain.	B (18, 0)
JBNFHNP	Local page frames. Number of 4K page frames allocated for this thread during this interval from the resource affinity domain this thread is associated with.	B (9, 0)
JBNFFNP	Non-local page frame. Number of 4K page frames allocated for this thread during this interval from resource affinity domains other than the one this thread is associated with, but within the same group.	B (9, 0)
JBTNAME	Thread name. Name of secondary thread, at sample time. The field will be blank for primary threads, tasks, and unnamed secondary threads.	C (16)

Field Name	Description	Attribute
JBSLTCNT	<p>Short lifespan entry count. If this field is greater than zero, the entry does not represent a particular task or secondary thread. Instead it is a special record used to report data accumulated for tasks and threads whose lifespan was shorter than the reporting threshold that was in effect when the collection started.</p> <p>Short lifespan tasks are reported for the resource affinity domain they were associated with and short lifespan secondary threads are reported for the job to which they belong.</p> <p>See QAPMCONF GKEY F1 for the reporting thresholds that were in effect during this collection.</p>	B (9, 0)
JBSACPU	<p>Accumulated job scaled CPU time charged (in microseconds). The accumulated scaled interval CPU time charged for all threads of the job since the job started.</p> <p>Note: This field is provided for primary threads only.</p>	B (18, 0)
JBINDCPU	<p>Thread unscaled CPU time used (in microseconds). The amount of unscaled processor time that represents the work done solely within this thread without regard for how server task work is charged.</p>	B (18, 0)
JBSINDCPU	<p>Thread scaled CPU time used (in microseconds). The amount of scaled processor time that represents the work done solely within this thread without regard for how server task work is charged.</p>	B (18, 0)
JBCPUWC	<p>Processor elapsed time. The elapsed time (in microseconds) that a task executes.</p>	B (18, 0)

Field Name	Description	Attribute
JBVPDLY	Virtual processor delay time. The elapsed delay time (in microseconds) due to virtualization for a task while it was executing. Virtual processor delay time included virtual processor thread wait event time, virtual processor thread wait ready time, and virtual processor thread dispatch latency.	B (18, 0)
JBSEIZECNT	Seize count. The number of seizures held by this thread at the time the data was sampled.	B (9, 0)
JBPSLCKCNT	Process scoped lock count. The number of process scoped locks held by this thread at the time data was sampled.	B (9, 0)
JBTSLCKCNT	Thread scoped lock count. The number of thread scoped locks held by this thread at the time data was sampled.	B (9, 0)
JBPSRCDLCK	Process scoped database record lock count. The number of process scoped database record locks held by this thread at the time data was sampled.	B (9,0)
JBTSRCDLCK	Thread scoped database record lock count. The number of thread scoped database record locks held by this thread at the time data was sampled.	B (9, 0)
JBNFOGDT	Off-group dispatch time. Amount of CPU time used by the thread in a resource affinity group other than the one this thread is associated with. The time is reported in internal model-dependent units.	B (18, 0)
JBNFOGMA	Off-group page frames. Number of 4K page frames allocated for this thread during this interval from a resource affinity group other than the one this thread is associated with.	B (9, 0)
JBFLDR5	Reserved	B (18,0)
JBFLDR6	Reserved	B (18,0)
JBFLDR7	Reserved	B (18,0)
JBFLDR8	Reserved	B (18,0)

Field Name	Description	Attribute
JBPGEZSTL	Pages marked easy to steal: Number of pages allocated for this thread marked easy to steal.	B (9,0)
JBSQLCLK	SQL clock time. The amount of clock time (in microseconds) this thread has spent performing work done on behalf of an SQL operation.	B (18,0)
JBSQLCPU	Thread unscaled SQL CPU time used. The amount of unscaled processor time (in microseconds) this thread has used performing work done on behalf of an SQL operation.	B (18,0)
JBSQLSCPU	Thread scaled SQL CPU time used. The amount of scaled processor time (in microseconds) this thread has used performing work done on behalf of an SQL operation.	B (18,0)
JBSQLDBR	SQL synchronous database reads: Total number of physical synchronous database read operations done on behalf of an SQL operation.	B (18,0)
JBSQLNDBR	SQL synchronous nondatabase reads: Total number of physical synchronous nondatabase read operations done on behalf of an SQL operation.	B (18,0)
JBSQLDBW	SQL synchronous database writes: Total number of synchronous physical database write operations done on behalf of an SQL operation.	B (18,0)
JBSQLNDBW	SQL synchronous nondatabase writes: Total number of synchronous physical nondatabase write operations done on behalf of an SQL operation.	B (18,0)
JBSQLADBR	SQL asynchronous database reads: Total number of asynchronous physical database read operations done on behalf of an SQL operation.	B (18,0)

Field Name	Description	Attribute
JBSQLANDBR	SQL asynchronous non-database reads: Total number of asynchronous physical nondatabase read operations done on behalf of an SQL operation.	B (18,0)
JBSQLADBW	SQL asynchronous database writes: Total number of asynchronous physical database write operations done on behalf of an SQL operation.	B (18,0)
JBSQLANDBW	SQL asynchronous non-database writes: Total number of asynchronous physical nondatabase write operations done on behalf of an SQL operation.	B (18,0)
JBAGCRT	Activation groups created. The number of activation groups created by all threads within this job. Note: This field is provided for primary threads only.	B (18,0)
JBPGMSACT	Program and service program activations created. The number of ILE program and service program activations created by all threads within this job. Note: This field is provided for primary threads only.	B (18,0)
JBCURTMP	Current temporary storage. A snapshot of the total temporary storage charged to this job, expressed in 4096-byte units. Note: This field is provided for primary threads only.	B (18,0)
JBPEAKTMP	Peak temporary storage. The largest value that the total temporary storage charged to this job has ever been at any point within this job, expressed in 4096-byte units. Note: This field is provided for primary threads only.	B (18,0)

Field Name	Description	Attribute
JBMAXTMP	<p>Maximum temporary storage allowed. The largest value that peak temporary storage can be without notifying the operating system, expressed in 4096-byte units. This field will be zero if the job is allowed to use an unlimited amount of temporary storage.</p> <p>Note: This field is provided for primary threads only.</p>	B (18,0)
JBTMPPGA	Total number of 4096-byte units of temporary storage that have been allocated by the thread since the thread started.	B (9,0)
JBTMPPGD	Total number of 4096-byte units of temporary storage that have been deallocated by the thread since the thread started.	B (9,0)
JBHSQLSTMT	<p>Number of high level SQL statements. The number of high level SQL statements that executed during the Collection Services time interval. This count includes only initial invocation, independent SQL statements. It does not include dependent SQL statements invoked from within another SQL statement. This count also includes initial invocation, independent SQL statements which failed to execute successfully.</p> <p>Note: This field is provided for primary threads only.</p>	B (18,0)
JBTICC	<p>Thread instruction count charged. The number of hardware instructions, completed by the processor and charged to this thread. It includes instructions completed for this thread and any instructions completed for server tasks that worked on its behalf within the interval. For server tasks, this field will be zero.</p> <p>Note: This value is available only for partitions running on Power8® and later hardware. However it is not available when running in Power7® or Power6® mode.</p>	B (18,0)

Field Name	Description	Attribute
JBTICU	<p>Thread instruction count used. The number of hardware instructions, completed by the processor that represents the work done solely within this thread without regard for how server task work is charged.</p> <p>Note: This value is available only for partitions running on Power8® and later hardware. However it is not available when running in Power7® or Power6® mode.</p>	B (18,0)
JBTTMBU	<p>Thread virtual time. The amount of time (in microseconds) that a processor was running instructions on behalf of this thread.</p> <p>Note: This value is available only for partitions running on Power8® and later hardware. However it is not available when running in Power7® or Power6® mode.</p>	B (18,0)
JBPICC	<p>Process hardware instruction count charged. The number of hardware instructions, run by the processor and charged to this job. It is the sum for all threads of the instructions run for this job and any instructions run for server tasks that worked on its behalf within the interval.</p> <p>Note: This may not equal the sum of JBTICU for all threads due to timing differences in the collection and reporting of these values. This field is provided for primary threads only.</p>	B (18,0)
JBPRRSCPTY	<p>Processor resource priority. See the parameter PRCRSCPTY on the CHGJOB command for more information.</p> <ul style="list-style-type: none"> • Hex 00 = *SYSCTL • Hex 01 = *HIGH • Hex 02 = *NORMAL • Hex 03 = *LOW 	BINCHAR (1)

Field Name	Description	Attribute
DATETIME	Interval date and time: The date and time of the sample interval for a job interval entry or the job end date and time for a job completion entry, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time: The date and time of the sample interval for a job interval entry or the job end date and time for a job completion entry, expressed in Coordinated Universal Time (UTC).	Timestamp
JBPGAI	The number of 4096-byte units of temporary and permanent storage that have been allocated by the thread during the interval.	B (9,0)
JBPGDI	The number of 4096-byte units of temporary and permanent storage that have been deallocated by the thread during the interval.	B (9,0)
JBTMPPGAI	The number of 4096-byte units of temporary storage that have been allocated by the thread during the interval.	B (9,0)
JBTMPPGDI	The number of 4096-byte units of temporary storage that have been deallocated by the thread during the interval.	B (9,0)

Related reference

Collection Services data files: [QAPMISUM](#)

This database file contains interval summary information.

Collection Services data files: [QAPMJOBWT](#)

This database file contains information about job, task, and thread wait conditions.

Collection Services data files: [QAPMJOBWTG](#)

This database file contains information about job, task, and thread current wait conditions that is not available in the QAPMJOBWT file.

Collection Services data files: [QAPMJSUM](#)

These database file entries contain job summary information.

Collection Services data files: [QAPMSMJMI](#)

This database file contains summarized metrics from job data (*JOBMI collection category) that may be used in support of system monitoring.

Collection Services data files: [Task type extender](#)

A task type extender identifies the area of functional support provided by the task.

Collection Services data files: [System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: [File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFDRDTA) command See the Create Performance Data (CRTPFDRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMJOBOS

These database file entries contain data specific to system jobs.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFDRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval for a job interval entry or the job end date and time for a job completion entry, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds.	PD (7,0)
DTCEN	Century digit.	C (1)
JBNAME	Job name/workstation name.	C (10)
JBUSER	Job user.	C (10)
JBNBR	Job number.	C (6)
JBTYPE	Job type. <ul style="list-style-type: none"> • A:Autostart • B:Batch • I:Interactive • M:Subsystem monitor • R:Spool reader • S:System • V:SLIC task • W:Spool writer • X:SCPF job 	C (1)
JBSTYP	Job subtype. <ul style="list-style-type: none"> • T:MRT (System/36 environment only) • E:Evoke (communications batch) • P:Print driver job • J:Prestart job • F:M36 (Advanced/36 server job) • D:Batch immediate job • U:Alternative spool user 	C (1)

Field Name	Description	Attribute
JBSTSF	Status flag; indicates job status relative to this interval. The values are: <ul style="list-style-type: none"> • 0 -- normal interval collection • 1 -- job started in interval • 2 -- job ended in interval • 3 -- job started and ended. Note: Jobs that are rerouted or transferred will result in a termination record (JBSTSF = 2) and a new job record (JBSTSF = 1.)	PD (1,0)
JBSSYS	Name of the subsystem the job is running in.	C (10)
JBSLIB	Name of the library the subsystem description is in.	C (10)
JBROUT	The routing entry index for the subsystem this job is in.	PD (5,0)
JBACCO	Job accounting code. Field cannot be displayed.	C (15)
JBRSP	Total transaction time (in seconds). Note: Certain IBM i functions support the concept of a transaction. The definition of a transaction and the characteristics of a transaction are different depending on the type of job or the specific function of the job. For interactive jobs, display I/O transactions are counted. The transaction starts on detection of enter from the workstation; the transaction ends when the keyboard is unlocked. For SNADS jobs, a transaction is the processing of a distribution.	PD (15,3)
JBNTR	Number of transactions. Note: Certain IBM i functions support the concept of a transaction. The definition of a transaction and the characteristics of a transaction are different depending on the type of job or the specific function of the job. For interactive jobs, display I/O transactions are counted. The transaction starts on detection of enter from the workstation; the transaction ends when the keyboard is unlocked. For SNADS jobs, a transaction is the processing of a distribution.	PD (11,0)
JBAIQT	Total application input queuing time (in hundredths of a second).	PD (15,1)
JBNAIQ	Number of application input queuing transactions.	PD (11,0)
JBRUT	Total resource usage time (in seconds).	PD (15,3)
JBNRU	Number of resource usage transactions.	PD (11,0)
JBPLN	Number of print lines: Number of lines written by the program. This does not reflect what is actually printed. Spooled files can be ended, or printed with multiple copies.	PD (11,0)

Field Name	Description	Attribute
JBPPG	Number of print pages.	PD (11,0)
JBPFL	Number of print files.	PD (11,0)
JBLWT	Number of database writes (logical): Number of times the internal database write function was called. This does not include I/O operations to readers/writers, or I/O operations caused by the CPYSPLF or DSPSPLF command. If SEQONLY(*YES) is specified, these numbers show each block of records written, not the number of individual records written.	PD (11,0)
JBLRD	Number of database reads (logical): Number of times the database module was called. This does not include I/O operations to readers/writers, or I/O operations caused by the CPYSPLF or DSPSPLF command. If SEQONLY(*YES) is specified, these numbers show each block of records read, not the number of individual records read.	PD (11,0)
JBDBU	Number of miscellaneous database operations: Updates, deletes, force-end-of-data, commits, rollbacks, and releases (logical).	PD (11,0)
JBCPT	Number of communications writes: These do not include remote workstation activity. They include only activity related to intersystem communications function (ICF) files when the I/O is for an intersystem communications function (ICF) device.	PD (11,0)
JBCGT	Number of communications reads (logical): These do not include remote workstation activity. They include only activity related to intersystem communications function (ICF) files when the I/O is for an intersystem communications function (ICF) device.	PD (11,0)
JBSPD	Total suspended time (in milliseconds.)	PD (11,0)
JBRRT	Total time job waited during reroutes (in milliseconds.)	PD (11,0)
JBLND	Line description: Name of the communications line this workstation and its controller are attached to. This is only available for remote workstations.	C (10)
JBCUD	Controller description: Name of the controller this workstation is attached to.	C (10)
JB2LND	Secondary line description (pass-through and emulation only.)	C (10)
JB2CUD	Secondary controller description (pass-through and emulation only).	C (10)
JBIRN	IOP resource name.	C (10)
JBDRN	Device resource name.	C (10)
JBPORT	Workstation port number.	PD (3,0)

Field Name	Description	Attribute
JBSTN	Workstation number.	PD (3,0)
JBPTSF	Pass-through source flag.	PD (1,0)
JBPTTF	Pass-through target flag.	PD (1,0)
JBEAF	Emulation active flag.	PD (1,0)
JBPCSF	IBM i Access application flag.	PD (1,0)
JBDDMF	Target DDM job flag.	PD (1,0)
JBMRTF	MRT flag.	PD (1,0)
JBS36E	Is job running in System/36 environment? (Y/N)	C (1)
JBQT	Total queuing time to enter the MRT (in hundredths of seconds).	PD (11,0)
JBMMT	Total time spent at MRTMAX (in seconds).	PD (11,0)
JBNEQT	Total number of entries into the MRT.	PD (11,0)
JBPUTN	The number of times ACPUT was called to send user or control data. Calls that result in no data being sent are not counted.	PD (11,0)
JBPUTA	The total amount of user and control data that was sent by the user's program. This value does not include the LLID, MAPNAME, or FMH-7 data lengths.	PD (11,0)
JBGETN	The number of times ACGET was called to receive user or control data. Calls that result in no data being given to the user application will not be counted.	PD (11,0)
JBGETA	The total amount of user and control data that was received by the user's program. This value does not include the LLID, MAPNAME, or FMH-7 data lengths.	PD (11,0)
JBPGIN	The number of intervals that begin at the first put of a chain and end when CD is returned to the user.	PD (11,0)
JBPGIL	The amount of time (in milliseconds) spent in intervals that begin at the first put of a chain and end when CD is returned to the user.	PD (11,0)
JBGGIL	The amount of time (in milliseconds) spent in intervals that begin when the first get of a get chain completes and ends when the first get of a new chain is issued.	PD (11,0)
JBRTI	This is the number of request I/O commands (REQIOs) issued to transmit data of any kind (including FMH-7s.)	PD (11,0)
JBRRi	This is the number of REQIOs issued to receive data of any kind (including FMH-7s.)	PD (11,0)
JBXSLR	File system symbolic link reads. This count includes the following file systems: Root, QOpenSys, and user-defined file systems.	PD (11,0)

Field Name	Description	Attribute
JBXDYR	File system directory reads. This count includes the following file systems: Root, QOpenSys, and user-defined file systems.	PD (11,0)
JBDLCH	File system directory lookup cache hits.	PD (11,0)
JBDLCM	File system lookup cache misses. This count includes the following file systems: Root, QOpenSys, and user-defined file systems.	PD (11,0)
JBSJNM	Submitter's job name.	C (10)
JBSJUS	Submitter's job user.	C (10)
JBSJNB	Submitter's job number.	C (6)
JBSJFG	Submitted job flag. This flag is designed to differentiate locally submitted jobs from jobs that are submitted from remote systems. Currently, this flag supports locally submitted jobs only.	C (1)
JBRSYS	Reserved.	C (10)
JBDEVN	Reserved.	C (10)
JBRLNM	Reserved.	C (8)
JBLLNM	Reserved.	C (8)
JBMODE	Reserved.	C (8)
JBRMNT	Reserved.	C (8)
JBBUP	Reserved.	PD (11,0)
JBBDL	Reserved.	PD (11,0)
JBBFE	Reserved.	PD (11,0)
JBBCO	Database commit operations.	PD (11,0)
JBBRO	Database rollback operations.	PD (11,0)
JBLBO	The cumulative number of SQL cursors which have been full opened.	PD (11,0)
JBLBC	Reserved.	PD (11,0)
JBLBI	Reserved.	PD (11,0)
JBLBS	The cumulative number of SQL cursors which have been pseudo-opened. Pseudo-opens are also known as <i>reused SQL cursors</i> .	PD (11,0)
JBDQS	Reserved.	PD (11,0)
JBDQR	Reserved.	PD (11,0)
JBNDA	Reserved.	PD (11,0)
JBNUS	Full opens. The number of Native database (non-SQL) files and SQL cursors which have been full opened. Subtracting the value within field JBLBO from JBNUS will yield the number of non-SQL full opens.	PD (11,0)

Field Name	Description	Attribute
JBSIT1	Reserved.	PD (11,0)
JBSIT2	Reserved.	PD (11,0)
JBSIT3	Reserved.	PD (11,0)
JBGRUP	Job group.	C (3)
JBTDE	System task identifier (task count). This field cannot be displayed.	C (8)
JBFLAG	Job flag (See notes.) Field cannot be displayed.	C (2)
JBSVRT	Server type. The type of server represented by the job. A value of blank (or blank space) indicates that the job is not part of a server. For more information on server types, see Server jobs and Server table .	C (30)
JBFSOPN	File system opens. This count includes the following file systems: Root, QOpenSys, and user-defined files systems.	PD (11,0)
JBFSDC	File system directory creates. This count includes the following file systems: Root, QOpenSys, and user-defined files systems.	PD (11,0)
JBFSNDC	File system non-directory creates. Count of create operations for non-directory objects such as files or symbolic links. This count includes the following file systems: Root, QOpenSys, and user-defined files systems.	PD (11,0)
JBFSDD	File system directory deletes. This count includes the following file systems: Root, QOpenSys, and user-defined files systems.	PD (11,0)
JBFSNDD	File system non-directory deletes. Count of delete operations for non-directory objects such as files or symbolic links. This count includes the following file systems: Root, QOpenSys, and user-defined files systems.	PD (11,0)
JBSPLFC	Number of spooled files created by this job. This includes those spooled files which are spooled or restored under this job as well as all spooled files that are spooled under QPRTJOBS by this job.	B (18,0)
JBSBMJOBS	Number of jobs submitted or spawned by this job.	B (18,0)
JBSQLSTMT	Number of SQL statements. This field contains a count of the number of SQL statements executed during the Collection Services time interval. This count includes user initiated SQL statements and DB2 [®] for i internal SQL statements. The count includes SQL statements which failed to execute successfully.	B (18,0)

Field Name	Description	Attribute
JBLWTSQL	Number of SQL related database writes (logical). This field can be compared to JBLWT to understand the portion of database writes which are attributed to SQL activity within the job during the Collection Services time interval. Subtracting JBLWTSQL from JBLWT will yield the number of non-SQL related database writes.	B (18,0)
JBLRDSQL	Number of SQL related database reads (logical). This field can be compared to JBLRD to understand the portion of database reads which are attributed to SQL activity within the job during the Collection Services time interval. Subtracting JBLRDSQL from JBLRD will yield the number of non-SQL related database reads.	B (18,0)
JBDBUSQL	Number of SQL related database miscellaneous operations (logical). This field can be compared to JBDBU to understand the portion of database miscellaneous operations which are attributed to SQL activity within the job during the Collection Services time interval. Subtracting JBDBUSQL from JBDBU will yield the number of non-SQL related database miscellaneous operations.	B (18,0)
JBPASCMP	Number of SQL PAS compressions across all threads in this job. The SQL Program Associated Space (SQL PAS) is a thread scoped internal work area used when SQL statements are dynamically prepared and executed. The SQL PAS spaces are managed by DB2 for i and may undergo a compression to maintain optimal performance. This field is simply the total number of SQL PAS compressions across all threads within the job during the Collection Services time interval.	B (18,0)
JBPKGCMPI	Number of *SQLPKG compressions which were initiated by SQL activity in this job. *SQLPKG's are permanent objects which contain prepared SQL extended dynamic statements. These objects allow SQL statements to be prepared a single time for executions across many jobs. The spaces are managed by DB2 for i and may undergo a compression to maintain optimal performance. This field is simply the total number of *SQLPKG compressions initiated within this job, across all threads within the job during the Collection Services time interval.	B (18,0)

Field Name	Description	Attribute
JBCTHD	Connected thread identifier. For server jobs, this field can be used to identify the client application job thread which last used this server connection. This is optional information that a server may or may not provide. The connected thread may refer to a client application job thread which no longer exists. This field will contain hex zeros if the job isn't a server, the server does not support this information, or the server is waiting for a connection to be established. One server that does provide this information is the QSQRV SQL server mode server.	BINCHAR (8)
JBCJNAM	Connected job name. For server jobs, this field can be used to identify the client application job that established the connection. This is optional information that a server may or may not provide. This field will contain blank characters if the job isn't a server, the server does not support this information, or the server is waiting for a connection to be established. One server that does provide this information is the QSQRV SQL server mode server.	C (10)
JBCJUSR	Connected job user. For server jobs, this field can be used to identify the client application job that established the connection. This is optional information that a server may or may not provide. This field will contain blank characters if the job isn't a server, the server does not support this information, or the server is waiting for a connection to be established. One server that does provide this information is the QSQRV SQL server mode server.	C (10)
JBCJNBR	Connected job number. For server jobs, this field can be used to identify the client application job that established the connection. This is optional information that a server may or may not provide. This field will contain blank characters if the job isn't a server, the server does not support this information, or the server is waiting for a connection to be established. One server that does provide this information is the QSQRV SQL server mode server.	C (6)
DATETIME	Interval date and time: The date and time of the sample interval for a job interval entry or the job end date and time for a job completion entry, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time: The date and time of the sample interval for a job interval entry or the job end date and time for a job completion entry, expressed in Coordinated Universal Time (UTC).	Timestamp

Notes:

Bit
0 Pass-through service
1 Pass-through target
2 Emulation active
3 IBM i Access application
4 Target DDM job
5 MRT
6-15 not used

Related reference

Collection Services data files: [QAPMISUM](#)

This database file contains interval summary information.

Collection Services data files: [QAPMJOSR](#)

This file contains data for jobs that have performed save or restore operations.

Collection Services data files: [QAPMJSUM](#)

These database file entries contain job summary information.

Collection Services data files: [QAPMSMJOS](#)

This database file contains summarized metrics from job data (*JOBOS collection category) that may be used in support of system monitoring.

Collection Services data files: [System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: [File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRDTA) command See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMJOBS and QAPMJOBL

The QAPMJOBL file is provided for compatibility with the performance monitor and combines data from the QAPMJOBMI file and the QAPMJOBOS file.

The QAPMJOBS file is created when the performance monitor database files are migrated with the Convert Performance Collection (CVTPFRCOL) command to a newer release. Collection Services does not create the QAPMJOBS file.

The database files contain data for each job, task or thread (one record per job, task, or thread). Collection Services provides data only for jobs that consume CPU during an interval. "Job" means job, task, or thread. Data in this file comes from the *JOBMI and *JOBOS categories.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)

Field Name	Description	Attribute
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval for a job interval entry or the job end date and time for a job completion entry, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds.	PD (7,0)
JBSSYS	Name of the subsystem the job is running in.	C (10)
JBSLIB	Name of the library the subsystem description is in.	C (10)
JBNAME	Job name/workstation name.	C (16)
JBUSER	Job user.	C (10)
JBNBR	Job number.	C (6)
JBACCO	Job accounting code. Field cannot be displayed.	C (15)
JBTYPE	Job type (A:Autostart, B:Batch, I:Interactive, M:Subsystem monitor, R:Spool reader, S:System, V:SLIC task, W:Spool writer, X:SCPF job)	C (1)
JBSTYP	Job subtype. (T:MRT (System/36 environment only) E:Evoke (communications batch), P:Print driver job, J:Prestart job, F:M36 (Advanced/36 server job), D:Batch immediate job, U:Alternative spool user.)	C (1)
JBTYP	Task type. (01:Resident task, 02:Supervisor task, 03:MI process task, 04:S36 emulation task).	C (2)
JBTTYPE	Task type extender. See task type extender definitions for detailed information about a task type extender. (See note "1" on page 143.)	C (2)
JBFLAG	Job flag. (Bit, 0:Pass-through source, 1:Pass-through target, 2:Emulation active, 3:IBM i Access application, 4:Target DDM job, 5:MRT, 6-15: Not used) Field cannot be displayed.	C (2)
JBS36E	Is job running in System/36 environment? (Y/N)	C (1)
JBPOOL	Job pool.	C (2)

Field Name	Description	Attribute
JBPRTY	Job priority.	C (3)
JBCPU	<p>Thread unscaled interval CPU time charged. The amount of unscaled processing time (in milliseconds) charged to this thread. It includes unscaled processing time used by this thread and any unscaled processing time charged to the thread by server tasks that worked on its behalf within the interval. (See note “2” on page 143.)</p> <p>For server tasks, this field will be zero.</p>	PD (15,3)
JBRSP	<p>Total transaction time (in seconds.) Certain IBM i functions support the concept of a transaction. The definition of transaction and the characteristics of a transaction are different depending on the type of job or the specific function of the job. For interactive jobs, display I/O transactions are counted. The transaction starts on detection of enter from the workstation; the transaction ends when the keyboard is unlocked. For SNADS jobs, a transaction is the processing of a distribution.</p>	PD (15,3)
JBSLC	Time-slice value (in milliseconds.)	PD (11,0)
JBNTR	<p>Number of transactions. Certain IBM i functions support the concept of a transaction. The definition of transaction and the characteristics of a transaction are different depending on the type of job or the specific function of the job. For interactive jobs, display I/O transactions are counted. The transaction starts on detection of enter from the workstation; the transaction ends when the keyboard is unlocked. For SNADS jobs, a transaction is the processing of a distribution.</p>	PD (11,0)

Field Name	Description	Attribute
JBDBR	Number of synchronous database reads: Total number of physical synchronous database read operations for database functions. (See note “2” on page 143.)	PD (11,0)
JBNDDB	Number of synchronous nondatabase reads: Total number of physical synchronous nondatabase read operations for nondatabase functions. (See note “2” on page 143.)	PD (11,0)
JBWRT	Number of writes: Total number of physical database and nondatabase write operations. (See note “2” on page 143.)	PD (11,0)
JBAW	Total number of transitions from active state to wait state for this job. (See note “2” on page 143.)	PD (11,0)
JBWI	Total number of transitions from wait state to ineligible state for this job. (See note “2” on page 143.)	PD (11,0)
JBAI	Total number of transitions from active state to ineligible state for this job. (See note “2” on page 143.)	PD (11,0)
JBPLN	Number of print lines: Number of lines written by the program. This does not reflect what is actually printed. Spooled files can be ended, or printed with multiple copies. (See note “3” on page 143.)	PD (11,0)
JBPPG	Number of print pages. (See note “3” on page 143.)	PD (11,0)
JBPFL	Number of print files. (See note “3” on page 143.)	PD (11,0)

Field Name	Description	Attribute
JBLWT	Number of database writes (logical): Number of times the internal database write function was called. This does not include I/O operations to readers/writers, or I/O operations caused by the CPYSPLF or DSPSPLF command. If SEQONLY(*YES) is specified, these numbers show each block of records written, not the number of individual records written. (See note “3” on page 143 .)	PD (11,0)
JBLRD	Number of database reads (logical): Number of times the database module was called. This does not include I/O operations to readers/writers, or I/O operations caused by the CPYSPLF or DSPSPLF command. If SEQONLY(*YES) is specified, these numbers show each block of records read, not the number of individual records read. (See note “3” on page 143 .)	PD (11,0)
JDBDU	Number of miscellaneous database operations: Updates, deletes, force-end-of-data, commits, rollbacks, and releases (logical). (See note “3” on page 143 .)	PD (11,0)
JBCPT	Number of communications writes: These do not include remote workstation activity. They include only activity related to intersystem communications function (ICF) files when the I/O is for an ICF device. (See note “3” on page 143 .)	PD (11,0)
JBCGT	Number of communications reads (logical): These do not include remote workstation activity. They include only activity related to intersystem communications function (ICF) files when the I/O is for an ICF device. (See note “3” on page 143 .)	PD (11,0)
JBSPD	Total suspended time (in milliseconds.) (See note “3” on page 143 .)	PD (11,0)

Field Name	Description	Attribute
JBRRT	Total time job waited during reroutes (in milliseconds.) (See note “3” on page 143.)	PD (11,0)
JBLND	Line description: Name of the communications line this workstation and its controller is attached to. This is only available for remote workstations. (See note “3” on page 143.)	C (10)
JBCUD	Controller description: Name of the controller this workstation is attached to. (See note “3” on page 143.)	C (10)
JB2LND	Secondary line description (pass-through and emulation only.) (See note “3” on page 143.)	C (10)
JB2CUD	Secondary controller description (pass-through and emulation only.) (See note “3” on page 143.)	C (10)
JBBRG	Reserved	PD (9,0)
JBPRG	Reserved	PD (9,0)
JBNDW	Number of synchronous nondatabase writes: Total number of synchronous physical nondatabase write operations for nondatabase functions. (See note “2” on page 143.)	PD (11,0)
JBDBW	Number of synchronous database writes: Total number of synchronous physical database write operations for database functions. (See note “2” on page 143.)	PD (11,0)
JBANDW	Number of asynchronous nondatabase writes: Total number of asynchronous physical nondatabase write operations for nondatabase functions. (See note “2” on page 143.)	PD (11,0)
JBADBW	Number of asynchronous database writes: Total number of asynchronous physical database write operations for database functions. (See note “2” on page 143.)	PD (11,0)

Field Name	Description	Attribute
JBANDR	Number of asynchronous nondatabase reads: Total number of asynchronous physical nondatabase read operations for nondatabase functions. (See note “2” on page 143.)	PD (11,0)
JBADBR	Number of asynchronous database reads: Total number of asynchronous physical database read operations for database functions. (See note “2” on page 143.)	PD (11,0)
JBPW	Number of synchronous permanent writes. (See note “2” on page 143.)	PD (11,0)
JBCS	Reserved	PD (11,0)
JBPAGF	Number of PAG faults. Total number of times the program access group (PAG) was referred to, but was not in main storage. The Licensed Internal Code no longer uses process access groups for caching data. Because of this implementation, this field will always be 0 for more current releases. (See note “2” on page 143.)	PD (11,0)
JBEAO	Reserved	PD (11,0)
JBOBIN	Number of binary overflows. (See note “2” on page 143.)	PD (11,0)
JBODEC	Number of decimal overflows. (See note “2” on page 143.)	PD (11,0)
JBOFLP	Number of floating point overflows. (See note “2” on page 143.)	PD (11,0)
JBIPF	Number of times a page fault occurred on an address that was currently part of an auxiliary storage I/O operation. (See note “2” on page 143.)	PD (11,0)
JBWIO	Number of times the process explicitly waited for outstanding asynchronous I/O operations to complete. (See note “2” on page 143.)	PD (11,0)
JBIRN	IOP resource name. (See note “3” on page 143.)	C (10)

Field Name	Description	Attribute
JBDRN	Device resource name. (See note “3” on page 143.)	C (10)
JIOPB	Reserved	PD(3,0)
JIOPA	Reserved	PD(3,0)
JBPORT	Workstation port number. (See note “3” on page 143.)	PD (3,0)
JBSTN	Workstation number. (See note “3” on page 143.)	PD (3,0)
JBPTSF	Pass-through source flag.	PD (1,0)
JBPTTF	Pass-through target flag.	PD (1,0)
JBEAF	Emulation active flag.	PD (1,0)
JBPCSF	IBM i Access application flag.	PD (1,0)
JBDDMF	Target DDM job flag.	PD (1,0)
JBMRTF	MRT flag.	PD (1,0)
JBROUT	The routing entry index for the subsystem this job is in.	PD (5,0)
JBAPT	Reserved.	PD (11,0)
JBNSW	Reserved.	PD (11,0)
JBSST	Reserved.	PD (11,0)
JBQT2	Reserved.	PD (11,0)
JBCDR	Reserved.	PD (11,0)
JBCDS	Reserved.	PD (11,0)
JBAIQT	Total application input queuing time (in hundredths of a second.) (See note “3” on page 143.)	PD (15,1)
JBNAIQ	Number of application input queuing transactions. (See note “3” on page 143.)	PD (11,0)
JBRUT	Total resource usage time (in seconds.) (See note “3” on page 143.)	PD (15,3)
JBNRU	Number of resource usage transactions. (See note “3” on page 143.)	PD (11,0)
JBQT	Total queuing time to enter the MRT (in hundredths of seconds.) (See note “3” on page 143.)	PD (11,0)
JBMMT	Total time spent at MRTMAX (in seconds.) (See note “3” on page 143.)	PD (11,0)

Field Name	Description	Attribute
JBNEQT	Total number of entries into the MRT. (See note “3” on page 143.)	PD (11,0)
JBPUTN	The number of times ACPUT was called to send user or control data. Calls that result in no data being sent are not counted. (See note “3” on page 143.)	PD (11,0)
JBPUTA	The total amount of user and control data that was sent by the user's program. This value does not include the LLID, MAPNAME, or FMH-7 data lengths. (See note “3” on page 143.)	PD (11,0)
JBGETN	The number of times ACGET was called to receive user or control data. Calls that result in no data being given to the user application will not be counted. (See note “3” on page 143.)	PD (11,0)
JBGETA	The total amount of user and control data that was received by the user's program. This value does not include the LLID, MAPNAME, or FMH-7 data lengths. (See note “3” on page 143.)	PD (11,0)
JBPGIN	The number of intervals that begin at the first put of a chain and end when CD is returned to the user. (See note “3” on page 143.)	PD (11,0)
JBPGIL	The amount of time (in milliseconds) spent in intervals that begin at the first put of a chain and end when CD is returned to the user. (See note “3” on page 143.)	PD (11,0)
JBGGIL	The amount of time (in milliseconds) spent in intervals that begin when the first get of a get chain completes and ends when the first get of a new chain is issued. (See note “3” on page 143.)	PD (11,0)
JBRTI	This is the number of request I/O commands (REQIOs) issued to transmit data of any kind (including FMH-7s.) (See note “3” on page 143.)	PD (11,0)

Field Name	Description	Attribute
JBRRI	This is the number of REQIOs issued to receive data of any kind (including FMH-7s.) (See note “3” on page 143.)	PD (11,0)
JBSZWT	Total seize wait time in milliseconds. (See note “2” on page 143.)	PD (15,3)
JBSKSC	Number of socket sends. (See note “3” on page 143.)	PD (11,0)
JBSKBS	Number of socket bytes sent. (See note “3” on page 143.)	PD (11,0)
JBSKRC	Number of socket receives. (See note “3” on page 143.)	PD (11,0)
JBSKBR	Number of socket bytes received. (See note “3” on page 143.)	PD (11,0)
JBXRFR	Stream file reads. (See note “2” on page 143.)	PD (11,0)
JBXRFW	Stream file writes. (See note “2” on page 143.)	PD (11,0)
JBXSLR	File system symbolic link reads. (See note “3” on page 143.)	PD (11,0)
JBXDYR	File system directory reads. (See note “3” on page 143.)	PD (11,0)
JBDLCH	File system directory lookup cache hits. (See note “3” on page 143.)	PD (11,0)
JBDLCM	File system lookup cache misses.	PD (11,0)
JBSJNM	Submitter's job name. (See note “3” on page 143.)	C (10)
JBSJUS	Submitter's job user. File system directory lookup cache hits. (See note “3” on page 143.)	C (10)
JBSJNB	Submitter's job number. (See note “3” on page 143.)	C (6)
JBSJFG	Submitted job flag. This flag is designed to differentiate locally submitted jobs from jobs that are submitted from remote systems. Currently, this flag supports locally submitted jobs only. (See note “3” on page 143.)	C (1)
JBRSYS	Reserved.	C (10)
JBDEVN	Reserved.	C (10)
JBRLNM	Reserved.	C (8)

Field Name	Description	Attribute
JBLLNM	Reserved.	C (8)
JBMODE	Reserved.	C (8)
JBRMNT	Reserved.	C (8)
JBINSX	Reserved.	PD (11,0)
JBBUP	Reserved.	PD (11,0)
JBBDL	Reserved.	PD (11,0)
JBBFE	Reserved.	PD (11,0)
JBBCO	Database commit operations.	PD (11,0)
JBBRO	Database rollback operations.	PD (11,0)
JBLBO	The cumulative number of SQL cursors which have been full opened.	PD (11,0)
JBLBC	Reserved.	PD (11,0)
JBLBI	Reserved.	PD (11,0)
JLBLS	The cumulative number of SQL cursors which have been pseudo-opened. Pseudo-opens are also known as <i>reused SQL cursors</i> .	PD (11,0)
JBDQS	Reserved.	PD (11,0)
JBDQR	Reserved.	PD (11,0)
JBNDA	Reserved.	PD (11,0)
JBNUS	Full opens. The number of Native database (non-SQL) files and SQL cursors which have been full opened. Subtracting the value within field JBLBO from JBNUS will yield the number of non-SQL full opens.	PD (11,0)
JBSIT1	Reserved.	PD (11,0)
JBSIT2	Reserved.	PD (11,0)
JBSIT3	Reserved.	PD (11,0)
JBTCPU	Job unscaled interval CPU time charged. Thread unscaled interval CPU time charged (in milliseconds) totaled for all threads of the job within the interval. Note: This value may not equal the sum of JBCPU for all threads due to timing differences in the collection and reporting of these values. (See note “3” on page 143.)	PD (15,3)

Field Name	Description	Attribute
JBTHDF	Secondary thread flag. Identifies secondary threads of a multi-threaded job. The values are: 0 for tasks and primary threads; 1 for secondary threads.	PD (1,0)
JBTHID	Thread Identifier. A 4-byte displayable thread identifier. A hex string that is unique for threads within a process. It will be blank for tasks and prior release data.	C (8)
JBTHAC	Active threads. Current number of active threads in the process when the data was sampled. An active thread may be actively running, suspended, or waiting on a resource. Includes the primary thread. (See note “3” on page 143.)	PD (11,0)
JBTHCT	Threads created. Number of threads initiated within this job. Includes both active and terminated threads. (See note “3” on page 143.)	PD (11,0)
JBMTXT	Mutex wait time in milliseconds. Cumulative time the thread waited for a mutex. (See note “2” on page 143.)	PD (15,3)
JBIBM1	Reserved	PD (11,0)
JBSTSF	Status flag: indicates job status relative to this interval. The values are: 0 -- normal interval collection, 1 -- job started in interval, 2 -- job ended in interval, 3 -- job started and ended. Jobs that are rerouted or transferred will result in a termination record (JBSTSF = 2) and a new job record (JBSTSF = 1)	PD (1,0)
JBSVIF	Server interactive flag. Set to '1' if the resource consumed by the function is charged to the interactive capability of the system.	C (1)
JBTFLT	Total page faults.	PD (11,0)
JBEDBC	Reserved	P (15,3)
JBTDDBC	Reserved	P (15,3)

Field Name	Description	Attribute
JBSVRT	Server type. The type of server represented by the job. A value of blank (or blank space) indicates that the job is not part of a server.	C (30)
JBCOP	Number of primary commit operations performed under the task.	PD (11,0)
JBCOS	Number of secondary commit operations performed under the task. This includes application and system-provided referential integrity commits.	PD (11,0)
JBDOP	Number of primary decommit operations performed under the task.	PD (11,0)
JBDOS	Number of secondary decommit operations performed under the task. This includes application and system-provided referential integrity decommits.	PD (11,0)
JBPJE	Number of physical journal write operations to disk performed under the task.	PD (11,0)
JBNSJE	Number of journal entries not directly related to SMAPP.	PD (11,0)
JBUJD	Number of SMAPP-induced journal entries deposited in user-provided journals.	PD (11,0)
JBSJD	Number of SMAPP-induced journal entries deposited in system-provided (default) journals.	PD (11,0)
JBBFW	Number of journal bytes written to disk. Such entries are packaged within the permanent area of the journal receiver. These are traditional journal entries which can be retrieved and displayed.	PD (15,0)
JBBFA	Number of bytes deposited within the permanent area of the journal receiver. This count includes both those bytes already written to disk and those still cached in main memory. These are traditional journal entries which can be retrieved and displayed.	PD (15,0)

Field Name	Description	Attribute
JBBTW	Number of transient area journal receiver bytes written to disk. The transient area contains hidden journal entries produced by the system, used during IPL, and routed to this transient area only if the customer specifies *RmvIntEnt on the CHGJRN command. This transient area is a separate area on the disk, distinct from the disk space used to store the normal journal entries.	PD (15,0)
JBBTA	Number of bytes generated for the journal receiver transient area. This count includes both transient bytes already written to disk and those still cached in main memory. The transient area contains hidden journal entries produced by the system, used during IPL, and routed to this transient area only if the customer specifies *RmvIntEnt on the CHGJRN command. This transient area is a separate area on the disk, distinct from the disk space used to store the normal journal entries.	PD (15,0)
JBTWT	Amount of time this task spent waiting for journal bundles to be written to disk (in milliseconds). This includes time spent waiting for physical disk write operations initiated by this task to be serviced, as well as time spent waiting for physical disk write operations initiated by other tasks whose journal entries reside in the same journal bundle.	PD (11,0)
JBTNW	Number of times this task waited for journal bundles to be written to disk.	PD (11,0)
JBXRRR	Number of random stream file read operations. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)) and user-defined file systems.	PD (11,0)

Field Name	Description	Attribute
JBXRRW	Number of random stream file write operations. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)) and user-defined file systems.	PD (11,0)
JBXRFS	Number of fsync operations. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)) and user-defined file systems.	PD (11,0)
JBXRBR	Stream file bytes read. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)) and user-defined file systems.	PD (15,0)
JBXRBW	Stream file bytes written. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)) and user-defined file systems.	PD (15,0)
JBFSH	Number of full secure sockets layer (SSL) handshakes that use server authentication.	PD (11,0)
JBASH	Number of abbreviated (or fast) secure sockets layer (SSL) handshakes that use server authentication.	PD (11,0)
JBFSHA	Number of full secure sockets layer (SSL) handshakes that use server and client authentication.	PD (11,0)
JBASHA	Number of abbreviated (or fast) secure sockets layer (SSL) handshakes that use server and client authentication.	PD (11,0)
JBPGA	Total number of 4096-byte units of temporary and permanent storage that have been allocated by the thread since the thread started.	P (11,0)

Field Name	Description	Attribute
JBPGD	Total number of 4096-byte units of temporary and permanent storage that have been deallocated by the thread since the thread started.	P (11,0)
JBCUSR	The user profile that the job was running under at the time the data was sampled.	C (10)
JBFSOPN	File system opens. This count includes the following file systems: Root, QOpenSys, and user-defined files systems.	PD (11,0)
JBFSDC	File system directory creates. This count includes the following file systems: Root, QOpenSys, and user-defined files systems.	PD (11,0)
JBFSNDC	File system non-directory creates. Count of create operations for non-directory objects such as files or symbolic links. This count includes the following file systems: Root, QOpenSys, and user-defined files systems.	PD (11,0)
JBFSDD	File system directory deletes. This count includes the following file systems: Root, QOpenSys, and user-defined files systems.	PD (11,0)
JBFSNDD	File system non-directory deletes. Count of delete operations for non-directory objects such as files or symbolic links. This count includes the following file systems: Root, QOpenSys, and user-defined files systems.	PD (11,0)
JBACPU	Accumulated job unscaled CPU time charged in milliseconds. The accumulated unscaled interval CPU time charged for all threads of the job since the job started. Note: This field is provided for primary threads only.	PD (15,3)

Field Name	Description	Attribute
JBIPAF	<p>The remote IP address family flag indicates the type of IP address information provided in field JBIPAD. The following are supported (see <sys/socket.h> and the API referenced under JBIPAD for more information on these values):</p> <ul style="list-style-type: none"> • Hex 00 = Not set • Hex 02 = AF_INET (IPv4) • Hex 18 = AF_INET6 (IPv6) <p>Note: An address may not be available if there is no current connection.</p>	C (1)
JBIPAD	<p>The binary form of IPv4 or IPv6 remote IP address most recently communicated with over sockets. If a sockets connection has not been established or has terminated (JBIPAF = X'00'), this field will be blank. An IPv4 address is 4 bytes long left justified in this field. An IPv6 address uses all 16 bytes. For examples and further explanation, refer to the Usage Notes section in the Convert IPv4 and IPv6 Addresses Between Text and Binary Form (inet_pton) API</p>	C (16)
JBIPPT	<p>Remote port number. This field displays the port number that is used in this connection.</p>	Z (5,0)
JBUAUF	<p>Reserved.</p>	C (1)
JBPGRQ	<p>Page frames requested. Number of new page frames required by thread to satisfy page fault, read or clear operation.</p>	B (9,0)
JBPGRL	<p>Page frames released. Number of page frames explicitly released by thread.</p>	B (9,0)
JBMSLR	<p>File system symbolic link reads. This count includes the following file systems: Root (/), QOpenSys, and user-defined file systems.</p>	B (9,0)
JBMDYR	<p>File system directory reads. This count includes the following file systems: Root (/), QOpenSys, and user-defined file systems.</p>	B (9,0)

Field Name	Description	Attribute
JBMLCH	File system directory lookup cache hits. This count includes the following file systems: Root (/), QOpenSys, and user-defined file systems.	B (9,0)
JBMLCM	File system lookup cache misses. This count includes the following file systems: Root (/), QOpenSys, and user-defined file systems.	B (9,0)
JBMOPN	File system opens. This count includes the following file systems: Root (/), QOpenSys, and user-defined file systems.	B (9,0)
JBMNDC	File system non-directory creates. Count of create operations for non-directory objects such as files or symbolic links. This count includes the following file systems: Root (/), QOpenSys, and user-defined file systems.	B (9,0)
JBMNDD	File system non-directory deletes. Count of delete operations for non-directory objects such as files or symbolic links. This count includes the following file systems: Root (/), QOpenSys, and user-defined file systems.	B (9,0)
JBSCPU	Thread scaled interval CPU time used charged. The amount of scaled processing time (in microseconds) charged to this thread. It includes scaled processing time used by this thread and any scaled processing time charged to the thread by server tasks that worked on its behalf within the interval. For server tasks, this field will be zero. Note: The ratio of JBSCPU to JBCPU shows the current processor speed in relation to nominal processor speed.	B (18,0)

Field Name	Description	Attribute
JBSTCPU	Job scaled interval CPU time charged. Thread scaled interval CPU time charged (in microseconds) totaled for all threads of the job within the interval. Note: This may not equal the sum of JBSCPU for all threads due to timing differences in the collection and reporting of these values. This field is provided for primary threads only.	B (18,0)
JBSQLCPU	Thread unscaled SQL CPU time used. The amount of unscaled processor time (in microseconds) this thread has used performing work done on behalf of an SQL operation.	B (18,0)
<p>Notes:</p> <ol style="list-style-type: none"> 1. For Detailed information about a task type extender, see task type extender definitions. 2. These fields are provided on an individual task or thread basis. For multithreaded jobs, they are not summarized across threads. 3. These fields are provided for primary threads only. If the field is a numeric counter, it is a cumulative total for all threads of a multithreaded job. 		

Related reference

Collection Services data files: QAPMJOBMI

These database file entries contain task, primary, and secondary thread data that are collected with the *JOBMI category. "Job" implies job, task, or thread.

Collection Services data files: QAPMJOBOS

These database file entries contain data specific to system jobs.

Collection Services data files: Task type extender

A task type extender identifies the area of functional support provided by the task.

Collection Services data files: System category and file relationships

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: File abbreviations

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRDTA) command See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMJOBSR

This file contains data for jobs that have performed save or restore operations.

There will be one record per job for each operation type it has performed (see field JSTYPE).

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DATETIME	Interval date and time: The date and time of the sample interval for a job interval entry or the job end date and time for a job completion entry, expressed in local system time.	Timestamp
INTSEC	Elapsed interval seconds. The number of seconds since the last sample interval.	PD (7, 0)
JSTDE	System task identifier.	C (8)
JSTYPE	Record/operation type. This field identifies the type of data contained within the record. Record types are based on the save/restore operation performed: <ul style="list-style-type: none"> • '1' - IFS save • '2' - IFS restore • '3' - Library save • '4' - Library restore 	C (1)
JSOPSSTR	Operations started. The number of save or restore operations started.	B (9, 0)
JSGRPSTR	Groups started. The number of groups of objects started.	B (9, 0)
JSGPREPRC	Groups preprocessed. The number of groups of objects that have completed preprocessing.	B (9, 0)
JSGCHKRDY	Groups checkpoint ready. The number of groups of objects ready for checkpoint processing. (This metric is supported only for IFS save operations).	B (9, 0)
JSGCHKISSU	Groups checkpoint issued. The number of groups of objects that have started checkpoint processing. (This metric is supported only for save operations).	B (9, 0)
JSGCHKCMP	Groups checkpoint complete. The number of groups of objects that have completed checkpoint processing. (This metric is supported only for save operations).	B (9, 0)
JSGIOISSU	Groups I/O issued. The number of groups of objects that have started I/O processing.	B (9, 0)
JSGIOCMP	Groups I/O complete. The number of groups of objects that have completed I/O processing. (This metric is not supported for IFS save operations).	B (9, 0)
JSGRLSRDY	Groups release ready. The number of groups of objects ready to be released. (This metric is supported only for IFS operations).	B (9, 0)
JSGOUTRDY	Groups output ready. The number of groups of objects ready for output processing. (This metric is supported only for IFS operations).	B (9, 0)

Field Name	Description	Attribute
JSGRPCMP	Groups complete. The number of groups of objects completed.	B (9, 0)
JSCNTSTR	Container starts. The number of containers (libraries or directories) started.	B (9, 0)
JSCNTEND	Container ends. The number of containers (libraries or directories) completed.	B (9, 0)
JSIORQST	I/O requests. The number of I/O requests started.	B (9, 0)
JSIORESP	I/O responses. The number of I/O requests completed.	B (9, 0)
JSLDRQST	Internal object requests. The number of internal objects that have started I/O processing.	B (9, 0)
JSLDRESP	Internal object responses. The number of internal objects that have completed I/O processing.	B (9, 0)
JSCHKRQST	Checkpoint requests. The number of checkpoint requests started. (This metric is supported only for save operations).	B (9, 0)
JSCHKRESP	Checkpoint responses. The number of checkpoint requests completed. (This metric is supported only for save operations).	B (9, 0)
JSOPSCMP	Operations completed. The number of save or restore operations completed successfully.	B (9, 0)
JSOPSTRM	Operations terminated. The number of save or restore operations that ended unsuccessfully.	B (9, 0)
JSOBSUCC	Successful object count. The number of objects successfully saved or restored.	B (9, 0)
JSOBFJAIL	Unsuccessful object count. The number of objects not successfully saved or restored.	B (9, 0)
UTCTIME	UTC interval date and time: The date and time of the sample interval for a job interval entry or the job end date and time for a job completion entry, expressed in Coordinated Universal Time (UTC).	Timestamp

Related reference

Collection Services data files: [QAPMJOBOS](#)

These database file entries contain data specific to system jobs.

Collection Services data files: [System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: [File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRTA) command See the Create Performance Data (CRTPFRTA) command for information on how to create performance database files.

Collection Services data files: QAPMJOBWT

This database file contains information about job, task, and thread wait conditions.

At least one record will be written for each job, task, or thread that consumed CPU during the interval (multiple records are possible especially during service activities).

Normally these entries contain individual data for each task and secondary thread that consumed CPU during the interval; however, tasks and secondary threads that both start and end in an interval and have a lifespan that is shorter than the reporting threshold will not be individually reported. Instead records will be added to report this activity each interval by job and node. See field JBSLTCNT in file QAPMJOBMI to identify these entries.

The purpose of this file is to account for the time a job (this means a task, primary thread, or secondary thread) spends waiting and to provide some indication as to the type of wait. Since the reasons for a wait are too numerous to handle individually, they are grouped into sets of functionally related waits. For each group, both the number of waits and time the job spent waiting are reported. The QAPMJOBWTD file provides a description of the type of wait conditions for each counter set.

Although the file contains fields for up to 32 sets of counters, not all may be used. The counter sets (buckets) actually used are reported in a separate file QAPMJOBWTD.

User of this file should be aware of the dynamic nature of the content of this file. Counter sets can be added or redefined by the new release of the operating system. In addition, IBM service representatives can define new counter sets or redefine existing counter sets to allow more granular or more specialized view of the job wait statistics. As a result, user cannot assume that the content of this file is always the same.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
JWTDE	System task identifier.	X (8)
JWCURT	Current Wait Time: The time in microseconds the job has spent in the current wait. See JWCURB field for the counter set (bucket) which will be updated when the current wait completes. (This time is not included in other wait counter sets).	B (9,0)
JWCURE	Reserved.	B (9,0)
JWCURB	Current Counter Set (bucket): If this field is non-zero, it reflects the counter set that will be updated when the wait completes.	B (4,0)
JWDSEQ	Description sequence number: Identifies the QAPMJOBWTD records associated with this wait data.	B (4,0)
JWCT01	Count 1. The number of times the job encountered wait conditions associated with this group.	B (9,0)
JWTM01	Time 1. The time in microseconds the job spent waiting within this group.	B (9,0)
JWCTnn JWTMnn	Count and time are repeated for up to 32 counter sets per record. See note 1.	

Note:

1. When QAPMJOBWT file data was collected on a system with operating system version i5/OS V5R4, only the first 16 counter sets are provided.

2. A job that is waiting will not be reported if it has done no processing in the interval. However, current waits for jobs that have used no CPU are reported in the wait gap file QAPMJOBWTG.

Related reference

Collection Services data files: QAPMJOBWTD

This database file contains a description of the counter sets found in file QAPMJOBWT.

Collection Services data files: QAPMJOBMI

These database file entries contain task, primary, and secondary thread data that are collected with the *JOBMI category. "Job" implies job, task, or thread.

Collection Services data files: QAPMJOBWTG

This database file contains information about job, task, and thread current wait conditions that is not available in the QAPMJOBWT file.

Collection Services data files: [System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: [File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFDRDA) command See the Create Performance Data (CRTPFDRDA) command for information on how to create performance database files.

Collection Services data files: QAPMJOBWTD

This database file contains a description of the counter sets found in file QAPMJOBWT.

One record will be written for each active counter set when the first instance of wait data is encountered (normally at the beginning of the collection). Multiple instances of this data are possible during service activities.

Field Name	Description	Attribute
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval providing these descriptions, expressed in local system time.. Normally this is the first interval in the *MGTCOL object.	C (12)
DTECEN	Century digit: where 0 indicates 19XX and 1 indicates 20XX.	C (1)
JWDSEQ	Description sequence number: This provides a unique identifier for a set of descriptions. This value is used in file QAPMJOBWT field JWDSEQ to associate counter data with a set of descriptions. Each time updated descriptions are written to this file, this field will contain a new value for that set of descriptions.	B (4,0)
JWTNUM	Total number of wait counter sets reported.	B (4,0)
JWSNBR	Counter set number described by this record.	B (4,0)
JWDESC	Description of the type of data reported in the JWCT <i>nn</i> and JWTM <i>nn</i> fields. Note: This field is in Unicode.	G (50)
DATETIME	Interval date and time: The date and time of the sample interval providing these descriptions, expressed in local system time. Normally this is the first interval in the *MGTCOL object.	Timestamp

Field Name	Description	Attribute
UTCTIME	UTC interval date and time: The date and time of the sample interval providing these descriptions, expressed in Coordinated Universal Time (UTC). Normally this is the first interval in the *MGTCOL object.	Timestamp

Related reference

Collection Services data files: [QAPMJOBWT](#)

This database file contains information about job, task, and thread wait conditions.

Collection Services data files: [QAPMJOBWTG](#)

This database file contains information about job, task, and thread current wait conditions that is not available in the QAPMJOBWT file.

Collection Services data files: [System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: [File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRDTA) command See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMJOBWTG

This database file contains information about job, task, and thread current wait conditions that is not available in the QAPMJOBWT file.

One record will be written for each job, task, or thread that did not consume CPU during the interval – those that are not reported in QAPMJOBWT.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
JWTDE	System task identifier. This field can be used as a join field with QAPMJOBMI and field JBTDE to obtain information about the job associate with this record.	X (8)
JWCURE	Reserved.	B (9,0)
JWCURT	Current Wait Time: The time in microseconds the job has spent in the current wait (total time since the wait began, see note 1).	B (18,0)
JWCURINT	Current Wait Time this interval: The time in microseconds the job has spent waiting during this interval. (See note 1)	B (9,0)
JWDSEQ	Description sequence number: Identifies the QAPMJOBWTD records associated with this wait data.	B (4,0)

Field Name	Description	Attribute
JWCURB	Current Counter Set (bucket): If this field is non-zero and positive, it indicates the job is currently waiting and which counter set is associated with the current wait. If this field is zero, wait state information is not available for this job (for example, for the job which has terminated in this interval). In rare cases a value of -1 indicates the data was not obtainable when sampled.	B (4,0)

Note:

1. If job data was collected on a release prior to V6R1, the collected data does not contain sufficient information for the wait gap file:
 - Records are only written for the jobs which eventually ran during the collection. Jobs which never ran during collection will not be represented.
 - Total wait in this wait state (JWCURT field) is estimated and should not be viewed as an accurate measurement.

Related reference

Collection Services data files: System category and file relationships

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: File abbreviations

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRDTA) command See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMJSUM

These database file entries contain job summary information.

This file is produced only when *JOBMI, *JOBOS, and *SYSLVL categories are all requested from the Create Performance Data (CRTPFRDTA) command.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval for a job interval entry or the job end date and time for a job completion entry, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds.	PD (7,0)
DTECEN	Century digit.	C (1)

Field Name	Description	Attribute
JSCBKT	<p>Job group: Identifies the type of jobs for which data is being reported within this record. Values supported are:</p> <ul style="list-style-type: none"> • DDM: Distributed data management • CA4: IBM i Access • PAS: Pass-through • MRT: Multiple requester terminal • S6E: System/36 environment • CME: Communications batch • AUT: Autostart batch • BCH: Batch jobs (not included within other groups) • INT: Interactive jobs (job type "I" not reported in other buckets above) • SPL: Spool jobs and the Start CPF job. <p>Note: Every job is categorized and reported in one and only one of the above job groups.</p> <ul style="list-style-type: none"> • INF: Interactive Feature (This group reports the data that is associated with jobs that the machine considers to be interactive. The resource that is consumed in these jobs may be included in the Interactive Feature Utilization. 	C (3)
JSCPU	Processing unit time (in milliseconds) used.	PD (11,0)
JSTRNT	Total transaction time (in seconds.)	PD (15,3)
JSTRNS	Number of transactions.	PD (11,0)
JSPRTL	Number of print lines: Number of lines written by the program. This does not reflect what is actually printed. Spooled files can be ended or printed with multiple copies.	PD (11,0)
JSPRTP	Number of print pages.	PD (11,0)
JSSPD	Total suspended time (in milliseconds.)	PD (11,0)
JSRRT	Total time job waited during reroutes (in milliseconds.)	PD (11,0)

Field Name	Description	Attribute
JSNEW	New jobs.	PD (11,0)
JSTERM	Terminated jobs.	PD (11,0)
JSJBCT	Number of jobs.	PD (11,0)
JSPDBR	Number of synchronous database reads: Total number of physical synchronous database read operations for database functions.	PD (11,0)
JSPNDB	Number of synchronous nondatabase reads: Total number of physical synchronous nondatabase read operations for nondatabase functions.	PD (11,0)
JSPWRT	Number of writes: Total number of physical database and nondatabase write operations.	PD (11,0)
JSLDBR	Number of database reads (logical): Number of times the database module was called. This does not include I/O operations to readers/writers, or I/O operations caused by the CPYSPLF or DSPSPLF command. If SEQONLY(*YES) is specified, these numbers show each block of records read, not the number of individual records read.	PD (11,0)
JSLDBW	Number of database writes (logical): Number of times the internal database write function was called. This does not include I/O operations to readers/writers, or I/O operations caused by the CPYSPLF or DSPSPLF command. If SEQONLY(*YES) is specified, these numbers show each block of records written, not the number of individual records written.	PD (11,0)
JSLDBU	Number of miscellaneous database operations: Updates, deletes, force-end-of-data, and releases (logical.)	PD (11,0)

Field Name	Description	Attribute
JSCMPT	Number of communications writes: These do not include remote workstation activity. They include only activity related to intersystem communications function (ICF) files when the I/O is for an intersystem communications function (ICF) device.	PD (11,0)
JSCMGT	Number of communications reads (logical): These do not include remote workstation activity. They include only activity related to intersystem communications function (ICF) files when the I/O is for an intersystem communications function (ICF) device.	PD (11,0)
JSBRG	Reserved	PD (11,0)
JSPRG	Reserved	PD (11,0)
JSNDW	Number of synchronous nondatabase writes: Total number of synchronous physical nondatabase write operations for nondatabase functions.	PD (11,0)
JSDBW	Number of synchronous database writes: Total number of synchronous physical database write operations for database functions.	PD (11,0)
JSANDW	Number of asynchronous nondatabase writes: Total number of asynchronous physical nondatabase write operations for nondatabase functions.	PD (11,0)
JSADBW	Number of asynchronous database writes: Total number of asynchronous physical database write operations for database functions.	PD (11,0)
JSANDR	Number of asynchronous nondatabase reads: Total number of asynchronous physical nondatabase read operations for nondatabase functions.	PD (11,0)
JSADBR	Number of asynchronous database reads: Total number of asynchronous physical database read operations for database functions.	PD (11,0)

Field Name	Description	Attribute
JSPW	Number of synchronous permanent writes.	PD (11,0)
JSCS	Reserved	PD (11,0)
JSPAGF	Number of PAG faults. Total number of times the program access group (PAG) was referred to, but was not in main storage. The Licensed Internal Code no longer uses process access groups for caching data. Because of this implementation, this field will always be 0 for more current releases.	PD (11,0)
JSEAO	Reserved	PD (11,0)
JSOBIN	Number of binary overflows.	PD (11,0)
JSODEC	Number of decimal overflows.	PD (11,0)
JSOFLP	Number of floating point overflows.	PD (11,0)
JSIPF	Number of times a page fault occurred on an address that was currently part of an auxiliary storage I/O operation.	PD (11,0)
JSWIO	Number of times the process explicitly waited for outstanding asynchronous I/O operations to complete.	PD (11,0)
JSSKSC	Number of socket sends.	PD (11,0)
JSSKBS	Number of socket bytes sent.	PD (11,0)
JSSKRC	Number of socket receives.	PD (11,0)
JSSKBR	Number of socket bytes received.	PD (11,0)
JSXRFR	Stream file reads.	PD (11,0)
JSXRFW	Stream file writes.	PD (11,0)
JSXSLR	File system symbolic link reads.	PD (11,0)
JSXDYR	File system directory reads.	PD (11,0)
JSDLCH	File system directory lookup cache hits.	PD (11,0)
JSDLCM	File system lookup cache misses.	PD (11,0)
JSSZWT	Total seize wait time in milliseconds.	PD (11,0)

Field Name	Description	Attribute
DATETIME	Interval date and time: The date and time of the sample interval for a job interval entry or the job end date and time for a job completion entry, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time: The date and time of the sample interval for a job interval entry or the job end date and time for a job completion entry, expressed in Coordinated Universal Time (UTC).	Timestamp

Related reference

Collection Services data files: [QAPMJOBMI](#)

These database file entries contain task, primary, and secondary thread data that are collected with the *JOBMI category. "Job" implies job, task, or thread.

Collection Services data files: [QAPMJOBOS](#)

These database file entries contain data specific to system jobs.

Collection Services data files: [QAPMSYSTEM](#)

This database file reports system-wide performance data.

Collection Services data files: [System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: [File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

[Create Performance Data \(CRTPFRDTA\) command](#) See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMJVM

This file contains data for Java Virtual Machines (JVM) that are active within a process at the time the data was sampled. There is one record per interval for each process that has a JVM active.

Note: The only supported JVM is IBM Technology for Java (J9).

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval for a job interval entry or the job end date and time for a job completion entry, expressed in local system time.	C (12)

Field Name	Description	Attribute
INTSEC	Elapsed interval seconds. The number of seconds since the last sample interval.	PD (7,0)
DTECEN	Century digit.	C (1)
JVNAME	Job name/workstation name.	C (10)
JVUSER	Job user.	C (10)
JVNBR	Job number.	C (6)
JVTDE	System task identifier. The system task identifier associated with the initial thread of a job. This field can be used to join records to QAPMJOBMI field JBTDE.	H (8)
JVTYPE	Job type. <ul style="list-style-type: none"> • 0: IBM Technology for Java - 32 Bit • 1: IBM Technology for Java - 64 Bit 	C (1)
JVVRSN	JVM version (UTF-16 CCSID 1200).	G (10)
JVPID	Process identifier.	B (9,0)
JVPOLICY	Garbage collection policy (UTF-16 CCSID 1200).	G (15)
JVHEAPC	Current heap allocated. Current amount of heap storage allocated for this JVM in kilobytes.	B (18,0)
JVHEAPU	Heap in use. Amount of allocated heap actually being used in kilobytes.	B (18,0)
JVMLCMEM	Malloc memory size in kilobytes.	B (18,0)
JVINTMEM	Internal memory size in kilobytes.	B (18,0)
JVJITMEM	JIT memory size in kilobytes.	B (18,0)
JVSCLMEM	Shared class size in kilobytes.	B (18,0)
JVGCCNBR	Last garbage collection cycle number.	B (9,0)
JVGCCTME	Last garbage collection cycle time. Clock time spent performing garbage collection tasks during the last garbage collection cycle in milliseconds.	B (18,0)

Field Name	Description	Attribute
JVGCITME	Interval garbage collection time. Clock time spent performing garbage collection tasks during this collection interval in milliseconds.	B (18,0)
JVGCTTME	Total garbage collection time. The total amount of clock time spent performing garbage collection by all tasks since the JVM started.	B (18,0)
DATETIME	Interval date and time: The date and time of the sample interval for a job interval entry or the job end date and time for a job completion entry, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time: The date and time of the sample interval for a job interval entry or the job end date and time for a job completion entry, expressed in Coordinated Universal Time (UTC).	Timestamp

Related reference

[Collection Services data files: System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

[Data files: File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

[Create Performance Data \(CRTPFRDTA\) command](#) See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMLAPD

This database file includes integrated services digital network LAPD file entries and lists the fields in the LAPD file.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (yymmdd) and time (hhmmss): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
IOPRN	IOP resource name.	C(10)
LDIOP	Reserved.	C(1)

Field Name	Description	Attribute
LDTYPE	The resource type of the IOP or adapter represented by this record.	C (4)
LDNWI	Network interface: The name of the network interface description.	C (10)
LDLSP	Link speed: The speed of this channel in bits per second.	PD (11,0)
LDPRCL	Protocol type: D for LAPD.	C (1)
LPLOFA	Loss of frame alignment: Total number of times when a time period equivalent to two 48-bit frames has elapsed without having detected valid pairs of line code violations.	PD (11,0)
LPLECV	Reserved.	PD (11,0)
LPDTSI	Reserved.	PD (11,0)
LPDTSO	Reserved.	PD (11,0)
LPFECV	Reserved.	PD (11,0)
LPES	Errored seconds: Total number of seconds that had one or more path coding violations, one or more out of frame defects, one or more controlled slip events, or a detected alarm indication signal defect.	PD (5,0)
LPSES	Severely errored seconds: Total number of seconds that had 320 or more path coding violation error events, one or more out of frame defects, or a detected alarm indication signal event. <ul style="list-style-type: none"> • For ESF signals, the number of seconds that had 320 or more path coding violation error events, one or more out of frame defects, or a detected alarm indication signal defect. • For E1-CRC signals, the number of seconds that had 832 or more path coding violation error events or one or more out of frame defects. • For E1-noCRC signals, the number of seconds that had 2048 or more line coding violations. • For D4 signals, the number of seconds that had framing error events, an out of frame defect, or 1544 or more line coding violations. 	PD (5,0)
LPCOL	Collision detect: The number of times the TE detected that its transmitted frame had been corrupted by another TE attempting to use the same bus.	PD (11,0)
LLCRCE	Receive CRC errors: The number of received frames that contain a CRC (cycle redundancy check) error.	PD (11,0)

Field Name	Description	Attribute
LLSFE	Short frame errors: The number of short frames received. A short frame is a frame that has fewer octets between its start flag and end flag than is permitted.	PD (11,0)
LLORUN	Receive overrun: The number of times the ISDN subsystem could not keep pace with incoming data because of local controller overload.	PD (11,0)
LLURUN	Transmit underrun: The number of times the ISDN subsystem could not keep pace with outgoing data because of local controller overload.	PD (11,0)
LLABRT	Aborts received: The number of frames received that contained HDLC abort indicators.	PD (11,0)
LLFRIE	Frames received in error: The sum of receive cycle redundancy check (CRC) errors, short frame errors, receive overrun, transmit underrun, aborts received, and frame sequence errors (LLCRCE, LLSFE, LLORUN, LLURUN, LLABRT, LSSEQE).	PD (11,0)
LSFRT	Retransmitted frames.	PD (11,0)
LSSEQE	Sequence errors: The number of received frames that contained sequence numbers indicating frames were lost.	PD (11,0)
LSFTRN	Total number of frames transmitted: This includes information (I), unnumbered information (UI), and supervisory (S) frames sent to a remote link station. This includes frames retransmitted and frames sent on transmissions stopped by transmit underrun, in addition to successful transmissions.	PD (11,0)
LSFRCV	Total number of frames received: This includes information (I), unnumbered information (UI), and supervisory (S) frames received from the remote link station. This includes no errors.	PD (11,0)
LSBTRN	Total bytes transmitted: The total number of bytes transmitted to a remote link station. This includes bytes retransmitted and bytes sent on transmissions stopped by a transmit underrun, in addition to successful transmissions.	PD (11,0)
LSBRCV	Total bytes received: The total number of bytes received from the remote link station. This includes no errors.	PD (11,0)
LQTOC	Total outgoing calls: The number of outgoing call attempts. For X.31 this includes outgoing SETUP messages requesting a packet switched connection. For Q.932, outgoing REGISTER messages are not included in this count.	PD (11,0)

Field Name	Description	Attribute
LQROC	Retry for outgoing calls: The number of outgoing calls that were rejected by the network. For X.31 this includes retry for outgoing SETUP messages requesting a packet switched connection. For Q.932, retry for outgoing REGISTER messages are not included in this count.	PD (11,0)
LQTIC	Total incoming calls: The number of incoming call attempts. For X.31 this includes incoming SETUP messages requesting a packet switched connection. For Q.932, incoming REGISTER messages are not included in this count.	PD (11,0)
LQRIC	Rejected incoming calls: The number of incoming calls that are rejected by the TE. For passive bus, the call may be intended for another TE that shares the same passive bus. This includes calls rejected both directly by the IOP and by the IOM. For X.31 this includes rejected incoming SETUP messages requesting a packet switched connection. For Q.932, rejected incoming REGISTER messages are not included in this count.	PD (11,0)
LDCHLS1	S1 maintenance channel: Set to one if the S1 maintenance channel was active.	PD (1,0)
LPLES	Line errored seconds: The number of seconds that had one or more line coding violations.	PD (5,0)
LPCSS	Controlled slip seconds: The number of seconds that had one or more controlled slip events.	PD (5,0)
LPBES	Bursty errored seconds (error second type B): The number of seconds that had greater than one but fewer than 320 path coding violation error events, no severely errored frame defects, and no detected incoming alarm indication signal defects.	PD (5,0)
LPSEFS	Severely errored framing seconds: The number of seconds that had one or more out of frame defects or a detected alarm indication signal defect.	PD (5,0)
LPDM	Degraded minutes: The number of minutes during which the estimated error rate exceeds 1E-6 but does not exceed 1E-3.	PD (5,0)
LPUS	Unavailable seconds: The number of seconds during which the interface is unavailable.	PD (5,0)

Related reference

Collection Services data files: System category and file relationships

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: File abbreviations

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRDTA) command See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMLIOP

This database file includes twinaxial IOP data file entries and lists the fields in the twinaxial IOP data file.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
IOPRN	IOP resource name.	C(10)
LIIOF	Reserved	C (1)
LITYPE	IOP type.	C (4)
LIRIDC	Resource ID of controller: Field cannot be displayed.	C (8)
LITPKT	Total packets transferred.	PD (11,0)
LIKBYO	Total KB transmitted from the IOP to the system across the bus.	PD (11,0)
LIKBYI	Total KB transmitted to the IOP from the system across the bus.	PD (11,0)
LIOPSR	OPSTART bus unit message received from another bus unit using normal flow.	PD (11,0)
LIOPSS	OPSTART bus unit message received from another bus unit using reverse flow method 2.	PD (11,0)
LISGLR	Signal bus unit message received from another bus unit.	PD (11,0)
LIOPST	OPSTARTS sent to another bus unit using reverse flow method 2.	PD (11,0)
LISGLS	Signals sent to another bus unit.	PD (11,0)
LIRSTQ	Restart queues bus unit message sent to another bus unit.	PD (11,0)
LIRQDO	DMA requests sent for output of data: The number of requests the IOP sends to the system for data to be sent from the IOP to the system across the bus.	PD (11,0)
LIRQDI	DMA requests sent for input of data: The number of requests the IOP sends to the system for data to be sent to the IOP from the system across the bus.	PD (11,0)
LIBNAR	Occurrences of BNA received.	PD (11,0)
LIIOQC	Wait-on-I/O queue count: The number of I/O requests on the wait-on-I/O queue at sample time. The wait-on-I/O queue holds I/O requests that are being processed or waiting to be processed.	PD (11,0)

Field Name	Description	Attribute
LISQC	Suspend queue count: The number of elements on the suspend queue at sample time.	PD (11,0)
LIAQC	Active queue count: The number of elements on the active queue at sample time. The active queue holds I/O requests that were sent from the host system and were not yet sent to the wait-on-I/O queue.	PD (11,0)
LITWIU	Twinaxial use count: The number of times when the wait-on-I/O queue was sampled and the count was not zero (I/O in progress). If this value is divided by the sample count, the result (times 100) is the percentage of time when I/O is occurring.	PD (5,0)
LISMPL	Sample count: The number of times during the snapshot interval that the various IOP queues were sampled.	PD (5,0)
LIIDLC	Idle counts (see notes): The number of times the workstation IOP ran an idle loop. This is done when the IOP has no work to perform. This count is used with the idle loop time.	PD (11,0)
LIIDLT	Idle loop time (times 0.01 microsecond) (see notes): The time (in hundredths of microseconds) to run the idle loop once.	PD (11,0)

Notes: The idle loop count and time are used to calculate the communications IOP utilization as follows:

1. Convert the product of the idle loop count times the idle loop time from hundredths of microseconds to seconds. Subtract this from the interval time, and divide the results by the interval time. For example:

$$\text{IOP utilization} = (\text{INTSEC} - (\text{CIIDLC} * \text{CIIDLT})/10^{**}8) / \text{INTSEC}$$

2. The performance monitor reports I/O processor (IOP) statistics different beginning with Version 3 Release 7. Therefore, performance statistics for IOPs introduced in Version 3 Release 7 or later releases are reported in the QAPMMIOP file. Performance statistics are reported in the QAPMMIOP file even if the IOP supports only one of the three IOP functions (communications, disk, or local workstation). Performance statistics for IOPs that were introduced before Version 3 Release 7 will continue to be reported in the appropriate IOP file (QAPMCIOP, QAPMDIOP, QAPMLIOP, and QAPMMIOP).

Related reference

Collection Services data files: System category and file relationships

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: File abbreviations

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRDTA) command See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMLPARH

This database file contains logical partition configuration and utilization data as it is known to the hypervisor.

This data is collected if the collecting partition has been authorized to obtain it. This authorization is a partition configuration attribute set on the Hardware Management Console (HMC).

A POWER6® system with firmware level xx340_075 or later is required for this data to be available.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
DTECEN	Century digit. 0 indicates 19xx , and 1 indicates 20xx.	C (1)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	B (4,0)
HPPID	Partition identifier. This is the binary value that is consistent with the partition number in the QAPMCONF file with GKEY of PN.	B (4,0)
HPOSID	Operating system identifier. <ul style="list-style-type: none"> • -1 = unknown • 0 = IBM i partition • 1 = other OS 	B (4,0)
HPSHRF	Shared processor flag. Indicates if the partition uses shared processors: <ul style="list-style-type: none"> • 0 = Partition does not share physical processors. • 1 = Partition shares physical processors and partition is capped • 2 = Partition shares physical processors and partition is uncapped 	C(1)
HPATRF	Reserved.	C (1)
HPVPRC	Virtual processors. The number of virtual processors currently configured for this partition.	B (4,0)
HPVPID	Virtual shared pool ID. This is the identifier of the partition's current virtual shared processor pool.	B (4,0)
HPPPID	Reserved.	B (4,0)
HPVALA	Reserved.	B (4,0)
HPPRCCC	Current processing capacity. The partition capacity that is represented as the number of processor units currently allocated to this partition.	B (5,2)
HPINTCC	Reserved.	B (5,2)
HPMEMC	Partition memory. This is the amount of memory in megabytes that is currently allocated to the partition.	B (18,0)
HPPRCE	Processor entitled time. The amount of processor time in milliseconds that the partition was entitled to consume based on its processing capacity.	B (18,0)

Field Name	Description	Attribute
HPPRCEU	Processor entitled time used. The amount of processor time in milliseconds that the partition had use of a processor due to its entitled capacity. This value will not exceed the partition entitled time (field HPPRCE). For dedicated processor partitions, all time consumed is reported as capped time. For shared processor partitions this represents the capped capacity used.	B (18,0)
HPPRCUU	Uncapped processor time used. The amount of time in milliseconds a shared uncapped partition had use of a processor in excess of its entitled capacity. (Fields HPPRCEU and HPPRCUU should be added together for total processing time used by uncapped partitions.)	B (18,0)
HPPRCD	Donated processor time. The amount of processor time in milliseconds donated by the partition to the physical shared processor pool. This value may be non-zero only for dedicated partitions that are able to donate their unused CPU.	B (18,0)
HPPRCIDL	Processor idle time. The amount of processor time in milliseconds the partition was idle as reported by the partition to the hypervisor. For all partitions (especially dedicated partitions), the hypervisor reported processor time used includes time the partition was in control of the processor but did not use it for real work. The partition view of idle time is reflected here for partitions that report it (dependent on the operating system). The following formula yields time used from a partition perspective: $HPPRCEU + HPPRCUU - HPPRCIDL$	B (18,0)
HPCYCL	Partition cycles. The number of non-idle processor cycles occurring while the partition had use of a processor. This value is available only for partitions running on Power6® and Power7® hardware.	B (18,0)
HPINST	Partition instructions completed. The number of hardware instructions completed while the partition had use of a processor. When running on Power6® and Power7® hardware, partition idle loop instructions are not counted.	B (18,0)
HPMEML	Minimum memory - the minimum amount of memory (in units of megabytes) that is needed in this partition.	B (18,0)
HPMEMH	Maximum memory - the maximum amount of memory (in units of megabytes) that can be assigned to this partition.	B (18,0)

Field Name	Description	Attribute
HPVPRL	Minimum virtual processors. The minimum number of virtual processors that are needed in this partition.	B (4,0)
HPVPRH	Maximum virtual processors. The maximum number of virtual processors that can be assigned to this partition.	B (4,0)
HPPRCCL	Minimum processing capacity. The minimum amount of processing capacity that is needed in this partition.	B (5,2)
HPPRCCH	Maximum processing capacity. The maximum amount of processing capacity that can be assigned to this partition.	B (5,2)
HPINTCL	Reserved.	B (5,2)
HPINTCH	Reserved.	B (5,2)
HPVALB	Reserved.	H (4)
HPNAME	Partition name. Name of partition as entered into HMC (7 bit ASCII). Within this file the name is padded with blanks.	C (48)
HPVAL01 - HPVAL08	Reserved.	B (18,0)
HPPRCT	Processor virtual time. The amount of time in milliseconds the partition had use of a processor (time that hardware instructions were being counted). This value is available only for partitions running on Power8® and later hardware.	B (18,0)
DATETIME	Interval date and time: The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp

Related reference

Collection Services data files: System category and file relationships

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: File abbreviations

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRTA) command See the Create Performance Data (CRTPFRTA) command for information on how to create performance database files.

Collection Services data files: QAPMMIOP

This database file includes multifunction IOP file entries and lists the fields in the multifunction IOP file.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRTA) command.	PD (5,0)

Field Name	Description	Attribute
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
IOPRN	IOP resource name.	C(10)
MIIOP	Reserved	C (1)
MITYPE	IOP type.	C (4)
MIPRCU	Processor utilization: The number of fixed-time intervals that this multifunction IOP spent in the idle state.	PD (11,0)
MIRAMU	Available local storage (in bytes): The number of bytes of free local storage in the IOP. The free local storage will probably be non-contiguous because of fragmentation.	PD (11,0)
MITPKT	Total packets transferred.	PD (11,0)
MIKBYO	Total KB transmitted from an IOP to the system across the bus.	PD (11,0)
MIKBYI	Total KB transmitted to the IOP from the system across the bus.	PD (11,0)
MIOPSR	OPSTART bus unit message received from another bus unit using normal flow.	PD (11,0)
MIOPSS	OPSTART bus unit message received from another bus unit using reverse flow method 2 (always 0).	PD (11,0)
MISGLR	Signals received.	PD (11,0)
MIOPST	OPSTARTs sent.	PD (11,0)
MISLGS	Signals sent.	PD (11,0)
MIRSTQ	Restart queues sent.	PD (11,0)
MIRQDO	DMA requests sent for output of data: The number of requests the IOP sends to the system for data to be sent from the IOP to the system across the bus.	PD (11,0)
MIRQDI	DMA requests sent for input of data: The number of requests the IOP sends to the system for data to be sent to the IOP from the system across the bus.	PD (11,0)
MIBNAR	Occurrences of BNA received.	PD (11,0)
MIIDLCL	Idle loop count (<u>see notes</u>): The number of times the primary IOP processor ran an idle loop. This is done when the IOP has no work to perform. This count is used with the idle loop time to calculate the primary IOP processor utilization in seconds.	PD (11,0)

Field Name	Description	Attribute
MIIDLT	Idle loop time (see notes): the time (in hundredths of microseconds) for the primary IOP processor to run the idle loop once. The value reported could be a multiple of the actual idle loop time. In that case, the value reported for the idle loop count is reduced by the same multiple so that the calculated IOP processor utilization is correct	PD (11,0)
MISYSF	IOP system function time: Total processing unit time (in milliseconds) used by the IOP for basic system function that is running in the primary IOP processor.	PD (11,0)
MIDISK	Disk time: Total processing unit time (in milliseconds) used by disk tasks that are running in the primary IOP processor.	PD (11,0)
MICOMM	Total communications time: Total processing unit time (in milliseconds) used by all the communications protocol tasks that are running in the primary IOP processor.	PD (11,0)
MISDLC	SDLC communications time: Total processing unit time (in milliseconds) used by SDLC communications tasks that are running in the primary IOP processor.	PD (11,0)
MIASYN	ASYN communications time: Total processing unit time (in milliseconds) used by asynchronous communications tasks that are running in the primary IOP processor.	PD (11,0)
MIBSC	BSC communications time: Total processing unit time (in milliseconds) used by BSC communications tasks that are running in the primary IOP processor.	PD (11,0)
MIX25L	X.25 LLC communications time: Total processing unit time (in milliseconds) used by X.25 LLC communications tasks that are running in the primary IOP processor.	PD (11,0)
MIX25P	X.25 PLC communications time: Total processing unit time (in milliseconds) used by X.25 packet layer communications (PLC) tasks that are running in the primary IOP processor.	PD (11,0)
MIX25D	X.25 DLC communications time: Total processing unit time (in milliseconds) used by X.25 data link control (DLC) and Point-to-Point Protocol (PPP) communications tasks that are running in the primary IOP processor.	PD (11,0)
MILAN	LAN communications time: Total processing unit time (in milliseconds) used by token-ring network, Ethernet, frame relay, fiber distributed data interface (FDDI), and asynchronous transfer mode (ATM) communications tasks. This includes processing time due to token-ring and Ethernet LAN emulation.	PD (11,0)

Field Name	Description	Attribute
MISDL D	SDLC short-hold mode time: Total processing unit time (in milliseconds) used by SDLC short-hold mode tasks that are running in the primary IOP processor.	PD (11,0)
MIRV02	ISDN communications time: Total processing unit time (in milliseconds) used by ISDN LAPD, LAPE, and PMI communications tasks that are running in the primary IOP processor.	PD (11,0)
MIRV03	ISDN communications time: Total processing unit time (in milliseconds) used by ISDN Q.931 communications tasks that are running in the primary IOP processor.	PD (11,0)
MISP	Service processor time: Total processing unit time (in milliseconds) used by the service processor function that is running in the primary IOP processor.	PD (11,0)
MIF1ID	Subfunction 1 ID: The identifier for additional functions that may be running in the primary IOP processor.	C (2)
MIF1TM	Subfunction 1 time: Total processing unit time (in milliseconds) used by the IOP function that is running in the primary IOP processor	PD (11,0)
MIF2ID	Subfunction 2 ID: The identifier for additional functions that may be running in the primary IOP processor.	C (2)
MIF2TM	Subfunction 2 time: Total processing unit time (in milliseconds) used by the IOP function that is running in the primary IOP processor	PD (11,0)
MIF3ID	Subfunction 3 ID: The identifier for additional functions that may be running in the primary IOP processor.	C (2)
MIF3TM	Subfunction 3 time: Total processing unit time (in milliseconds) used by the IOP function that is running in the primary IOP processor.	PD (11,0)
MIF4ID	Subfunction 4 ID: The identifier for additional functions that may be running in the primary IOP processor.	C(2)
MIF4TM	Subfunction 4 time: Total processing unit time (in milliseconds) used by the IOP function that is running in the primary IOP processor.	PD (11,0)
MIF5ID	Subfunction 5 ID: The identifier for additional functions that are running in the primary IOP processor.	C(2)
MIF5TM	Subfunction 5 time in milliseconds used by the IOP function that is running in the primary IOP processor.	PD (11,0)

Field Name	Description	Attribute
MITWNX	Total processing unit time (in milliseconds) used by workstation and local twinaxial tasks that are running in the primary IOP processor.	PD (11,0)
MICPU2	Processor 2 utilization: The utilization (in milliseconds) of the second IOP processor that handles specialized function. This field applies to Integrated xSeries Server (excluding I/O adapter versions) and is zero for other IOPs. Collection Services will not report values for Integrated xSeries Server.	PD (11,0)
MIADP	Reserved.	PD (11,0)
MIOTH	Other function time: Total processing unit time (in milliseconds) used by other IOP functions that are running in the primary IOP processor. Other functions include those that cannot be reported in the subfunction 1-5 ID fields because all of the subfunction 1-5 ID fields are in use.	PD (11,0)
MIINT	Interrupt level time: Total processing unit time (in milliseconds) used by interrupt level processing that is running in the primary IOP processor. This does not include interrupt level processing time that can be associated with a particular task.	PD (11,0)
MIRA	Remote access time: Total processing unit time (in milliseconds) used by the remote access tasks that are running in the primary IOP processor.	PD (11,0)

Notes: The idle loop count and time are used to calculate the multifunction IOP utilization as follows:

1. Convert the product of the idle loop count times the idle loop time from hundredths of microseconds to seconds. Subtract this from the interval time, and divide the results by the interval time. For example:

$$\text{IOP utilization} = (\text{INTSEC} - (\text{MIIDLE} * \text{MIIDLT}) / 10^{**}8) / \text{INTSEC}$$

2. The performance monitor reports I/O processor (IOP) statistics different beginning with Version 3 Release 7. Therefore, performance statistics for IOPs introduced in Version 3 Release 7 or later releases are reported in the QAPMMIOP file. Performance statistics are reported in the QAPMMIOP file even if the IOP supports only one of the three IOP functions (communications, disk, or local workstation). Performance statistics for IOPs that were introduced before Version 3 Release 7 will continue to be reported in the appropriate IOP file (QAPMCIOP, QAPMDIOP, QAPMLIOP, and QAPMMIOP).
3. The function 1 - 5 identifiers are for additional functions that may be running in the primary IOP. Each function identifier has an associated function time value. The function identifier may have the following value:

Value	Description
00	No time value supplied.
11	Integrated xSeries Server pipe task (Integrated xSeries Server was previously known as file server I/O processor and FSIOP)
20	Storage subsystem task
22	Tape task
23	Diskette task

24	Optical task
30	Communications subsystem task
42	Localtalk task
43	Wireless task
60	Cryptography task

Related reference

[Collection Services data files: System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

[Data files: File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

[Create Performance Data \(CRTPFRDTA\) command](#) See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMPOOL and QAPMPOOLL

The QAPMPOOLL file is provided to allow for compatibility between Collection Services and the performance monitor. The QAPMPOOL file is created when the performance monitor database files are migrated with the Convert Performance Collection (CVTPFCOL) command to a newer release. Collection Services does not create the QAPMPOOL file. Rather, Collection Services creates the QAPMPOOLL file.

This data includes main storage pool file entries and lists the fields in the storage pool file.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
PONBR	Pool number: Specifies the unique identifier of this pool. The value is from 1 to 64.	C (2)
POACTL	Pool activity level setting: The maximum number of processes that can be active in the machine at the same time.	PD (5,0)
POSIZ	Pool size (in KB): The amount of main storage assigned to the pool.	PD (9,0)
PORES	Pool reserved size (in KB): Specifies the amount of storage from the pool that is dedicated to machine functions.	PD (9,0)
PODBF	Pool database faults: Total number of interruptions to processes (not necessarily assigned to this pool) that were required to transfer data into the pool to permit the MI instruction to process the database function.	PD (11,0)

Field Name	Description	Attribute
PONDBF	Pool nondatabase faults: Total number of interruptions to processes (not necessarily assigned to this pool) that were required to transfer data into the pool to permit the MI instruction to process nondatabase functions.	PD (11,0)
PODBPG	Pool database pages read: Total number of pages of database data transferred from auxiliary storage to the pool to permit the instruction to run as a consequence of set access state, implicit access group movement, and internal machine actions.	PD (11,0)
PONDPG	Pool nondatabase pages read: Total number of pages of database data transferred from auxiliary storage to the pool to permit the instruction to run as a consequence of set access state, implicit access group movement, and internal machine actions.	PD (11,0)
POAW	Number of active to wait transitions: Total number of transitions by processes assigned to this pool from active state to wait state.	PD (11,0)
POWI	Number of wait to ineligible: Total number of transitions by processes assigned to this pool from wait state to ineligible state.	PD (11,0)
POAI	Number of active to ineligible: Total number of transitions by processes assigned to this pool from active state to ineligible state.	PD (11,0)
PTTYPE	Type of tuning: The method used by the system to tune the storage pool: <ul style="list-style-type: none"> • 0 -- No tuning • 1 -- Static tuning • 2 -- Dynamic tuning of transfers into main storage • 3 -- Dynamic tuning of transfers into main storage and to auxiliary storage. 	C (1)
PTPAGE	Change page handling. The method used by the system to determine when to write changed pages to auxiliary storage: <ul style="list-style-type: none"> • 0 -- Use the system default • 1 -- Periodically transfer changed pages to auxiliary storage. 	C (1)
PTNDBF	Non-database blocking factor. The amount of data (in KB) that should be brought into main storage when a request is made to read non-database objects from auxiliary storage.	PD (3,0)
PTDBF1	Database blocking factor (class 1.) The amount of data (in KB) that should be brought into main storage when a request is made to read database objects from auxiliary storage.	PD (3,0)

Field Name	Description	Attribute
PTDEX1	<p>Database exchange operation type (class 1.) The exchange operation used to reduce the working set size.</p> <ul style="list-style-type: none"> • 0 -- Use the system default • 1 -- Allow exchange operations • 2 -- Disable exchange operations • 3 -- Disable exchange operations. <p>The data that already exists in main storage should be a good candidate to be replaced when additional storage is needed in the storage pool.</p>	C (1)
PTDTS1	<p>Database type of transfer to auxiliary storage (class 1.) The method the system uses to process a request to write an object to auxiliary storage.</p> <ul style="list-style-type: none"> • 0 -- Use the system default • 1 -- Purge object from main storage • 2 -- Write object to auxiliary storage • 3 -- Indicate object is a good candidate for replacement • 4 -- Use the system page replacement algorithm. 	C (1)
PTDBF2	Database blocking factor (class 2.) See PTDBF1 .	PD (3,0)
PTDEX2	Database allow exchange operations (class 2.) See PTDEX1 .	C (1)
PTDTS2	Database type of transfer to auxiliary storage (class 2.) See PTDTS1 .	C (1)
PTDBF3	Database blocking factor (class 3.) See PTDBF1 .	PD (3,0)
PTDEX3	Database allow exchange operations (class 3.) See PTDEX1 .	C (1)
PTDTS3	Database type of transfer to auxiliary storage (class 3.) See PTDTS1 .	C (1)
PTDBF4	Database blocking factor (class 4.) See PTDBF1 .	PD (3,0)
PTDEX4	Database allow exchange operations (class 4.) See PTDEX1 .	C (1)
PTDTS4	Database type of transfer to auxiliary storage (class 4.) See PTDTS1 .	C (1)

Related reference

[Collection Services data files: System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

[Data files: File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

[Create Performance Data \(CRTPFRDTA\) command](#) See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMPOOLB

This database file includes main storage pool file entries and lists the counters for system storage pools.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
DTECEN	Century digit.	C (1)
PONBR	Pool number: Specifies the unique identifier of this pool. The value is from 1 to 64.	C (3)
POACTL	Pool activity level setting: The maximum number of processes that can be active in the machine at the same time.	PD (5,0)
POSIZ	Pool size (in KB) (see note “1” on page 176): The amount of main storage assigned to the pool. If this field is set to the largest number it can hold (999999999), pool size is too large to fit in this field and the field POSIZB should be used instead.	PD (9,0)
PORES	Pool reserved size (in KB): Specifies the amount of storage from the pool that is dedicated to machine functions.	PD (9,0)
PODBF	Pool database faults (see note “1” on page 176): Total number of interruptions to processes (not necessarily assigned to this pool) that were required to transfer database data into the pool.	PD (11,0)
PONDBF	Pool nondatabase faults (see note “1” on page 176): Total number of interruptions to processes (not necessarily assigned to this pool) that were required to transfer nondatabase data into the pool.	PD (11,0)
PODBPG	Pool database pages read (see note “1” on page 176): Total number of pages of database data transferred from auxiliary storage to the pool.	PD (11,0)
PONDPG	Pool nondatabase pages read (see note “1” on page 176): Total number of pages of nondatabase data transferred from auxiliary storage to the pool.	PD (11,0)
POAW	Number of active to wait transitions: Total number of transitions by processes assigned to this pool from active state to wait state.	PD (11,0)
POWI	Number of wait to ineligible: Total number of transitions by processes assigned to this pool from wait state to ineligible state.	PD (11,0)

Field Name	Description	Attribute
POAI	Number of active to ineligible: Total number of transitions by processes assigned to this pool from active state to ineligible state.	PD (11,0)
POUNAL	Unallocated pool space (in KB) (see note “1” on page 176): The amount of pool storage available to be used for new transfers into the main storage pool without displacing any virtual data already in the pool. If this field is set to the largest number it can hold (999999999), unallocated pool space is too large to fit in this field and the field POUNALB should be used instead.	PD (9,0)
PDATA1	Reserved	B (18,0)
PDATA2	Reserved	B (18,0)
PDATA3	Reserved	B (18,0)
PDATA4	Reserved	B (18,0)
POPGS4	Pool 4K pages: Total number of 4K pages in the pool.	B (18,0)
POPGS64	Pool 64K pages: Total number of 64K pages in the pool.	B (18,0)
PODBF4	Pool database 4K page faults: Total number of interruptions to processes (not necessarily assigned to this pool) that were required to transfer 4K page database data into the pool.	B (18,0)
PODBF64	Pool database 64K page faults: Total number of interruptions to processes (not necessarily assigned to this pool) that were required to transfer 64K page database data into the pool.	B (18,0)
PONDBF4	Pool nondatabase 4K page faults: Total number of interruptions to processes (not necessarily assigned to this pool) that were required to transfer 4K page nondatabase data into the pool.	B (18,0)
PONDBF64	Pool nondatabase 64K page faults: Total number of interruptions to processes (not necessarily assigned to this pool) that were required to transfer 64K page nondatabase data into the pool.	B (18,0)
PODBPG4	Pool database 4K pages read: Total number of 4K pages of database data transferred from auxiliary storage to the pool.	B (18,0)
PODBPG64	Pool database 64K pages read: Total number of 64K pages of database data transferred from auxiliary storage to the pool.	B (18,0)
PONDPG4	Pool nondatabase 4K pages read: Total number of 4K pages of nondatabase data transferred from auxiliary storage to the pool.	B (18,0)
PONDPG64	Pool nondatabase 64K pages read: Total number of 64K pages of nondatabase data transferred from auxiliary storage to the pool.	B (18,0)

Field Name	Description	Attribute
POUNAL4	Unallocated 4K pages: Total number of 4K pages in the pool which may be used for new transfers into the pool without displacing any data already in the pool.	B (18,0)
POUNAL64	Unallocated 64K pages: Total number of 64K pages in the pool which may be used for new transfers into the pool without displacing any data already in the pool.	B (18,0)
POAGED4	Pool 4K pages aged: Number of 4K pages in the pool examined but not selected for reuse when the system is searching for a page to be allocated.	B (18,0)
POAGED64	Pool 64K pages aged: Number of 64K pages in the pool examined but not selected for reuse when the system is searching for a page to be allocated.	B (18,0)
POSTLN4	Pool 4K pages stolen: Number of 4K pages in the pool that already had a virtual address assigned to them but were reassigned to a different virtual address during page allocation.	B (18,0)
POSTLN64	Pool 64K pages stolen: Number of 64K pages in the pool that already had a virtual address assigned to them but were reassigned to a different virtual address during page allocation.	B (18,0)
POUNUSE4	Pool unused 4K pages allocated: Number of 4K pages in the pool that did not have a virtual address assigned to them but were assigned a virtual address during page allocation.	B (18,0)
POUNUSE64	Pool unused 64K pages allocated: Number of 64K pages in the pool that did not have a virtual address assigned to them but were assigned a virtual address during page allocation.	B (18,0)
POSYNC4	Pool 4K page synchronous IO operations: Number of synchronous IO operations executed to transfer 4K page data between the pool and auxiliary storage.	B (18,0)
POSYNC64	Pool 64K page synchronous IO operations: Number of synchronous IO operations executed to transfer 64K page data between the pool and auxiliary storage.	B (18,0)
POASYNC4	Pool 4K page asynchronous IO operations: Number of asynchronous IO operations executed to transfer 4K page data between the pool and auxiliary storage.	B (18,0)
POASYNC64	Pool 64K page asynchronous IO operations: Number of asynchronous IO operations executed to transfer 64K page data between the pool and auxiliary storage.	B (18,0)

Field Name	Description	Attribute
POPGOUT4	Pool 4K page outs: Number of changed 4K pages that were transferred from the pool to auxiliary storage to allow for page allocation.	B (18,0)
POPGOUT64	Pool 64K page outs: Number of changed 64K pages that were transferred from the pool to auxiliary storage to allow for page allocation.	B (18,0)
POPGABLE4	Pool pageable 4K pages: Number of 4K pages that are capable of having their data transferred from the pool to auxiliary storage.	B (18,0)
POPGABLE64	Pool pageable 64K pages: Number of 64K pages that are capable of having their data transferred from the pool to auxiliary storage.	B (18,0)
POATMPT4	Pool 4K page allocation attempts: Number of attempts made to allocate 4K pages whether successful or not. Unsuccessful attempts are retried and counted again until they succeed.	B (18,0)
POATMPT64	Pool 64K page allocation attempts: Number of attempts made to allocate 64K pages whether successful or not. Unsuccessful attempts are retried and counted again until they succeed.	B (18,0)
POAPS4	Pool 4K page affinity preference successes: Number of 4K page allocations that were made on the preferred resource affinity domain.	B (18,0)
POAPS64	Pool 64K page affinity preference successes: Number of 64K page allocations that were made on the preferred resource affinity domain.	B (18,0)
POAPMIG4	Pool 4K page affinity preference misses in group: Number of 4K page allocations that could not be made on the preferred resource affinity domain, but could be made within the preferred group of resource affinity domains.	B (18,0)
POAPMIG64	Pool 64K page affinity preference misses in group: Number of 64K page allocations that could not be made on the preferred resource affinity domain, but could be made within the preferred group of resource affinity domains.	B (18,0)
POAPMOG4	Pool 4K page affinity preference misses off-group: Number of 4K page allocations that could not be made on the preferred resource affinity domain or within the preferred group of resource affinity domains, but had to be made within some other resource affinity domain.	B (18,0)
POAPMOG64	Pool 64K page affinity preference misses off-group: Number of 64K page allocations that could not be made on the preferred resource affinity domain or within the preferred group of resource affinity domains, but had to be made within some other resource affinity domain.	B (18,0)

Field Name	Description	Attribute
POCRTPG64	Pool 64K pages created: Number of 64K pages created by combining 4K pages.	B (18,0)
POBRKPG64	Pool 64K pages broken up: Number of 64K pages broken up into individual 4K pages.	B (18,0)
POSIZB	Pool size (in KB) (see note “1” on page 176): The amount of main storage assigned to the pool.	B (18,0)
POUNALB	Unallocated pool space (in KB) (see note “1” on page 176): The amount of pool storage available to be used for new transfers into the main storage pool without displacing any virtual data already in the pool.	B (18,0)
DATETIME	Interval date and time: The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp
PONAME	Pool name. Specifies the name of the pool.	C (32)

Notes:

1. The following fields represent totals for both 4K and 64K pages. In these fields, any 64K pages that exist are treated like 16 individual 4K pages.

- POSIZ: Pool size (in KB)
- PODBF: Pool database faults
- PONDBF: Pool nondatabase faults
- PODBPG: Pool database pages read
- PONDPG: Pool nondatabase pages read
- POUNAL: Unallocated pool space (in KB)
- POSIZB: Pool size (in KB)
- POUNALB: Unallocated pool space (in KB)

To see the totals broken out by page size, see the following fields:

- POPGS4: Pool 4K pages
- POPGS64: Pool 64K pages
- PODBF4: Pool database 4K page faults
- PODBF64: Pool database 64K page faults
- PONDBF4: Pool nondatabase 4K page faults
- PONDBF64: Pool nondatabase 64K page faults
- PODBPG4: Pool database 4K pages read
- PODBPG64: Pool database 64K pages read
- PONDPG4: Pool nondatabase 4K pages read
- PONDPG64: Pool nondatabase 64K pages read
- POUNAL4: Unallocated 4K pages
- POUNAL64: Unallocated 64K pages

Related reference

Collection Services data files: QAPMSMPOL

This database file contains summarized metrics from pool data (*POOL collection category) that may be used in support of system monitoring.

Collection Services data files: System category and file relationships

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: File abbreviations

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRDTA) command See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMPOOLT

This database file includes main storage pool file entries and lists the tuning information for the storage pools.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
DTECEN	Century digit.	C (1)
PONBR	Pool number: Specifies the unique identifier of this pool. The value is from 1 to 64.	C (3)
PTTYPE	Type of tuning: The method used by the system to tune the storage pool: <ul style="list-style-type: none">• 0 -- No tuning• 1 -- Static tuning• 2 -- Dynamic tuning of transfers into main storage• 3 -- Dynamic tuning of transfers into main storage and to auxiliary storage.	C (1)
PTPAGE	Change page handling. The method used by the system to determine when to write changed pages to auxiliary storage: <ul style="list-style-type: none">• 0 -- Use the system default• 1 -- Periodically transfer changed pages to auxiliary storage.	C (1)
PTNDBF	Non-database blocking factor. The amount of data (in KB) that should be brought into main storage when a request is made to read non-database objects from auxiliary storage.	PD (3,0)

Field Name	Description	Attribute
PTDBF1	Database blocking factor (class 1.) The amount of data (in KB) that should be brought into main storage when a request is made to read database objects from auxiliary storage.	PD (3,0)
PTDEX1	Database exchange operation type (class 1.) The exchange operation used to reduce the working set size. <ul style="list-style-type: none"> • 0 -- Use the system default • 1 -- Allow exchange operations • 2 -- Disable exchange operations • 3 -- Disable exchange operations. The data that already exists in main storage should be a good candidate to be replaced when additional storage is needed in the storage pool.	C (1)
PTDTS1	Database type of transfer to auxiliary storage (class 1.) The method the system uses to process a request to write an object to auxiliary storage. <ul style="list-style-type: none"> • 0 -- Use the system default • 1 -- Purge object from main storage • 2 -- Write object to auxiliary storage • 3 -- Indicate object is a good candidate for replacement • 4 -- Use the system page replacement algorithm. 	C (1)
PTDBF2	Database blocking factor (class 2.) See PTDBF1 .	PD (3,0)
PTDEX2	Database allow exchange operations (class 2.) See PTDEX1 .	C (1)
PTDTS2	Database type of transfer to auxiliary storage (class 2.) See PTDTS1 .	C (1)
PTDBF3	Database blocking factor (class 3.) See PTDBF1 .	PD (3,0)
PTDEX3	Database allow exchange operations (class 3.) See PTDEX1 .	C (1)
PTDTS3	Database type of transfer to auxiliary storage (class 3.) See PTDTS1 .	C (1)
PTDBF4	Database blocking factor (class 4.) See PTDBF1 .	PD (3,0)
PTDEX4	Database allow exchange operations (class 4.) See PTDEX1 .	C (1)
PTDTS4	Database type of transfer to auxiliary storage (class 4.) See PTDTS1 .	C (1)
DATETIME	Interval date and time: The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp

Related reference

Collection Services data files: System category and file relationships

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: File abbreviations

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRDTA) command See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMPPP

This database file includes the fields in the Point-to-Point Protocol (PPP) file.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
DTECEN	Century digit: where 0 indicates 19XX and 1 indicates 20XX.	C (1)
IOPRN	IOP resource name	C (10)
PPTYPE	The resource type of the IOP or adapter represented by this record.	C (4)
PPLND	Line description: The name of the description for this line.	C (10)
PPLSP	Line speed: The speed of the line in bits per second (bps).	BIN (18,0)
PPRCL	Protocol type: P for PPP.	C (1)
PPBTRN	Bytes transmitted: The number of bytes transmitted including bytes transmitted again.	BIN (18,0)
PPBRCV	Bytes received: The number of bytes received including all bytes in frames that had any kind of error.	BIN (18,0)
PPFTRN	Frames transmitted: The number of frames transmitted.	BIN (18,0)
PPEFFR	Error-free frames received: The number of frames received without errors.	BIN (18,0)
PPFRIE	Frames received in error: The number of frames received with one of the following errors: a frame check sequence error, an abnormal end, a receive overrun, or a frame truncated error.	BIN (9,0)

Field Name	Description	Attribute
PPIFR	Invalid frames received: The number of frames received with a residue error (frame is not on a byte boundary).	BIN (9,0)
PPPORT	Reserved	C (10)
DATETIME	Interval date and time: The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp

Related reference

[Collection Services data files: System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

[Data files: File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

[Create Performance Data \(CRTPFRDTA\) command](#) See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMRESP

This database file includes local workstation response time file entries and contains transaction information based on data collected within the local workstation controller.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
IOPRN	IOP resource name.	C(10)
LRIOP	Reserved.	C (1)
LRBKT1	Transactions in first response time monitor bracket: The number of transactions from 0 up to and including n seconds for this workstation during the snapshot interval. The n value is the response time monitor 1 bracket upper limit, and is specified on the Advanced Local Response Time Options dialog from the Collection Services properties page within the System i® Navigator interface. A transaction is defined as the time from when the keyboard locked because the Enter key or a function key was pressed to the time when the keyboard unlocked because the display was refreshed.	PD (7,0)

Field Name	Description	Attribute
LRBKT2	Transactions in second response time monitor bracket: The number of transactions greater than the response time monitor 1 and up to and including response time monitor 2 limit.	PD (7,0)
LRBKT3	Transactions in third response time monitor bracket: The number of transactions greater than the response time monitor 2 and up to and including response time monitor 3 limit.	PD (7,0)
LRBKT4	Transactions in fourth response time monitor bracket: The number of transactions greater than the response time monitor 3 and up to and including response time monitor 4 limit.	PD (7,0)
LRBKT5	Transactions in fifth response time monitor bracket: The number of transactions above (longer) than the response time monitor 4 limit.	PD (7,0)
LRPORT	Workstation port number.	PD (3,0)
LRSTN	Workstation number.	PD (3,0)
LRTRNS	The total of all the individual times for all exchanges measured and reported by this record including overflows (LRBKT5). The total time in seconds for all transactions.	PD (7,0)
LRCUD	Controller description name.	C (10)
DATETIME	Interval date and time: The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp

Related reference

Collection Services data files: System category and file relationships

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: File abbreviations

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRDTA) command See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMSAP

This database file contains service access point (SAP) file entries and lists the fields in the SAP file.

SAP statistics are reported for active TRLAN, Ethernet, DDI, and frame relay line descriptions associated with TRLAN, Ethernet, DDI and Frame Relay ports, respectively. SAP statistics are also reported for ATM ports that support token-ring and Ethernet LAN emulation.

There will be one record per service access point per line per port per interval. Port resource name should also be used to uniquely associate records across intervals.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
IOPRN	IOP resource name.	C(10)
SCIOPI	Reserved	C (1)
SCTYPE	The resource type of the IOP or adapter represented by this record.	C (4)
SCSSAP	SSAP ID: The source SAP (SSAP) ID.	C (2)
SCLND	Line description: The name of the description for the line containing the SAP listed above. For frame relay, this is the network interface (NWI) description.	C (10)
SCLSPD	Line speed: The speed of the line in bits per second (bps). For some lines, this value might change as time progresses.	PD (11,0)
SCIRCV	UI frames received: Total number of UI frames received at this SSAP.	PD (11,0)
SCIXMT	UI frames transmitted: Total number of UI frames transmitted through this SSAP.	PD (11,0)
SCBRCV	UI bytes received: Total number of bytes received at this SSAP contained within a UI frame.	PD (11,0)
SCBXMT	UI bytes transmitted: Total number of bytes transmitted through this SSAP contained within a UI frame.	PD (11,0)
SCIDSC	Number of UI frames received and discarded by this SSAP.	PD (11,0)
SCPRCL	Protocol types: <ul style="list-style-type: none"> • E:Token-Ring • F:DDI • T:Ethernet • Y:Frame Relay 	C (1)
SCPORT	Port resource name.	C (10)
DATETIME	Interval date and time: The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp

Related reference

Collection Services data files: System category and file relationships

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: File abbreviations

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRDTA) command See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMSHRMP

This database file reports shared memory pool data.

Data is generated only when a partition is defined to use a shared memory pool. Data is reported for both the partition's use of the pool as well as pool metrics that are the sum of activity caused by all partitions using the pool.

A POWER6 system with firmware level xx340_075 is the minimum hardware requirement for this data to be available.

A POWER7® system is the minimum hardware requirement for the deduplication data to be available.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DATETIME	Interval date and time. The date and time of the sample interval, expressed in local system time.	Timestamp
INTSEC	Elapsed interval seconds. The number of seconds since the last sample interval.	PD (7, 0)
SMPOOLID	Shared memory pool identifier. The identifier of the shared memory pool which this partition is using.	B (5,0)
SMWEIGHT	Memory weight. Indicates the variable memory capacity weight assigned to the partition. Valid values are hex 0 -255. The larger the value, the less likely this partition is to lose memory.	B (3,0)
SMREALUSE	Physical real memory used. The amount of shared physical real memory, in bytes, that was being used by partition memory at sample time.	B (18, 0)
SMACCDLY	Real memory access delays. The number of partition processor waits that have occurred because of page faults on logical real memory.	B (18, 0)
SMACCWAIT	Real memory access wait time. The amount of time, in milliseconds, that partition processors have waited for real memory page faults to be satisfied.	B (18, 0)
SMOVRCAP	Reserved	B (18, 0)
SMENTIOC	Entitled memory capacity for I/O. The amount of memory, in bytes, currently assigned to the partition for use by I/O requests.	B (18, 0)

Field Name	Description	Attribute
SMMINIOC	Minimum entitled memory capacity for I/O. The minimum amount of entitled memory, in bytes, needed to function with the current I/O configuration.	B (18, 0)
SMOPTIOC	Optimal entitled memory capacity for I/O. The amount of entitled memory, in bytes, that would allow the current I/O configuration to function without any I/O memory mapping delays.	B (18, 0)
SMIOCUSE	Current I/O memory capacity in use. The amount of I/O memory, in bytes, currently mapped by I/O requests.	B (18, 0)
SMIOCMAX	Maximum I/O memory capacity used. The maximum amount of I/O memory, in bytes, that has been mapped by I/O requests since the partition was last IPLed or the value was reset by an explicit request.	B (18, 0)
SMIOMDLY	I/O memory mapping delays. The cumulative number of delays that have occurred because insufficient entitled memory was available to map an I/O request since the partition was last IPLed.	B (18, 0)
MPACCDLY	Pool real memory access delays. The number of virtual partition memory page faults within the shared memory pool for all partitions.	B (18, 0)
MPACCWAIT	Pool real memory access wait time. The amount of time, in milliseconds, that all partitions processors have spent waiting for page faults to be satisfied within the shared memory pool.	B (18, 0)
MPPHYMEM	Pool physical memory. The total amount of physical memory, in bytes, assigned to the shared memory pool	B (18, 0)
MPLOGMEM	Pool logical memory. The summation, in bytes, of the logical real memory of all active partition active partitions served by the shared memory pool.	B (18, 0)
MPENTIOC	Pool entitled I/O memory. The summation, in bytes, of the I/O entitlement of all active partitions served by the shared memory pool.	B (18,0)
MPIOCUSE	Pool entitled I/O memory in use. The summation, in bytes, of I/O memory mapped by I/O requests from all active partitions served by the shared memory pool.	B (18,0)
SMFIELD1	Partition logical memory deduplicated. The amount of the partition's logical memory (in bytes) mapped to a smaller set of physical pages in the shared memory pool because it was identical to other pages in the shared memory pool.	B (18,0)
SMFIELD2	Reserved	B (18,0)
SMFIELD3	Reserved	B (18, 0)

Field Name	Description	Attribute
SMFIELD4	Pool physical memory deduplicated. The amount of physical memory (in bytes) within the shared memory pool that logical pages of memory from the partitions sharing the pool have been mapped to because of deduplication.	B (18, 0)
MPFIELD1	Unscaled deduplication time. The amount of processing time, in microseconds, spent deduplicating logical partition memory within the shared memory pool.	B (18, 0)
MPFIELD2	Scaled deduplication time. The amount of scaled processing time, in microseconds, spent deduplicating logical partition memory within the shared memory pool.	B (18, 0)
MPFIELD3	Reserved	B (18, 0)
MPFIELD4	Reserved	B (18, 0)
MPFIELD5	Reserved	B (18, 0)
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp

Related reference

[Collection Services data files: System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

[Data files: File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

[Create Performance Data \(CRTPFRDTA\) command](#) See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMSMCMN

This database file contains summarized metrics from communication protocol data (*CMNBASE collection category) that may be used in support of system monitoring.

These metrics are calculated from more discrete data found in communications protocol files. The breakdown dimension identifies a grouping of lines for which data is provided. One record is written per database interval per breakdown dimension.

Field Name	Description	Attribute
INTNUM	Interval number. The <i>n</i> th sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DATETIME	Interval date and time. The date and time of the sample interval, expressed in local system time.	Timestamp
INTSEC	Elapsed interval seconds. The number of seconds since the last sample interval.	PD (7,0)

Field Name	Description	Attribute
SMCBDD	Communication protocol breakdown dimension. Identifies which communication protocols were used to calculate the data contained in this record. <ul style="list-style-type: none"> '01' - Line data: (ASYN, BSC, FRLY, HDLC, PPP, X25) '02' - LAN data: (ETH, ECL) 	C (2)
SMCNUM	Number of communication lines included in this data.	B (9,0)
SMCAUTILP	Average Line utilization. The average percent busy for included communication lines.	B (9,2)
SMCABRCV	Average kilobits received. The sum of data kilobits received divided by the number of included lines.	B (18,0)
SMCABSND	Average kilobits sent. The sum of data kilobits sent divided by the number of included lines.	B (18,0)
SMCMUTILP	Maximum Line utilization. The percent busy for the line with the highest utilization included within this breakdown dimension.	B (9,2)
SMCMLND	Line description. The name of the description for the line with the highest utilization.	C (10)
SMCB4F01	Reserved.	B (9,0)
SMCB8F01	Reserved.	B (18,0)
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp

Related reference

[Collection Services data files: System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

[Data files: File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

[Create Performance Data \(CRTPFRDTA\) command](#) See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMSMSDK

This database file contains summarized metrics from disk data (*DISK collection category) that may be used in support of system monitoring.

These metrics are calculated from more discrete data found in the QAPMDISK and QAPMDISKRB files. The breakdown dimension identifies a grouping of disk units for which data is provided. One record is written per database interval per breakdown dimension.

Field Name	Description	Attribute
INTNUM	Interval number. The <i>n</i> th sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)

Field Name	Description	Attribute
DATETIME	Interval date and time. The date and time of the sample interval, expressed in local system time.	Timestamp
INTSEC	Elapsed interval seconds. The number of seconds since the last sample interval.	PD (7,0)
SMDBDD	Disk breakdown dimension. Identifies which disk units were used to calculate the data contained in this record. <ul style="list-style-type: none"> '01' - All disk units '02' - Disk units in the system ASP '03' - Disk units in user ASPs '04' - Disk units in Independent ASPs 	C (2)
SMDNUM	Number of disk units included in this data.	B (9,0)
SMDABSY	Average disk busy percent. The disk unit busy percent averaged for the disk units.	B (9,2)
SMDMBSYP	Maximum disk busy percent. The largest single disk unit busy percent for included disk units.	B (9,2)
SMDMBPDRN	Device resource name for the unit with the highest disk busy percent.	C (10)
SMDASTGP	Average disk storage used. The percentage of total disk storage that is in use.	B (9,2)
SMDMSTGP	Maximum disk storage used. The percent of storage that in use for the unit with the highest usage percent.	B (9,2)
SMDMSTGD	Device resource name for the unit with the highest disk storage used.	C (10)
SMDSTGT	Disk storage capacity. The accumulated storage capacity of included disk units in gigabytes (GB).	B (9,0)
SMDSTGU	Disk storage in use. The accumulated storage in use within the included disk units in gigabytes (GB).	B (9,0)
SMDTROPS	Read operations. Accumulated number of read operations for reported disk units.	B (18,0)
SMDTRRSPT	Read response time. Accumulated read response time for reported disk units in microseconds.	B (18,0)
SMDTRSRVT	Read service time. Accumulated read service time for reported disk units in microseconds.	B (18,0)
SMDMRRSPT	Maximum read response time. The read response time for the disk unit with highest average read response time in microseconds.	B (18,0)
SMDMRRSPD	Device resource name for the unit with the highest read response time.	C (10)
SMDTWOPS	Write operations. Accumulated number of write operations for reported disk units.	B (18,0)

Field Name	Description	Attribute
SMDTWRSPT	Write response time. Accumulated write response time for reported disk units in microseconds.	B (18,0)
SMDTWSRVT	Write service time. Accumulated write service time for reported disk units in microseconds.	B (18,0)
SMDMWSRPT	Maximum disk write response time. The write response time for the disk unit with highest average write response time in microseconds.	B (18,0)
SMDMWRSPD	Device resource name for the unit with the highest write response time.	C (10)
SMDB4F01	Reserved.	B (9,0)
SMDB4F02	Reserved.	B (9,0)
SMDB8F01	Reserved.	B (18,0)
SMDB8F02	Reserved.	B (18,0)
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp
SMDNBSYP	Minimum disk busy percent. The lowest single disk unit busy percent for included disk units.	B (9,2)
SMDNBPDRN	Device resource name for the unit with the lowest disk busy percent.	C (10)
SMDNSTGP	Minimum disk storage used. The percent of storage that is in use for the unit with the lowest usage percent.	B (9,2)
SMDNSTGD	Device resource name for the unit with the lowest disk storage used.	C (10)
SMDNRRSPT	Minimum read response time. The read response time for the disk unit with the lowest average read response time in microseconds.	B (18,0)
SMDNRRSPD	Device resource name for the unit with the lowest read response time.	C (10)
SMDNWSRPT	Minimum disk write repose time. The write response time for the disk unit with the lowest average write response time in microseconds.	B (18,0)
SMDNWRSPD	Device resource name for the unit with the lowest write response time.	C (10)

Related reference

Collection Services data files: [QAPMDISK](#)

This database file includes disk file entries and contains one record for each disk resource.

Collection Services data files: [QAPMDISKRB](#)

This database file includes disk file response bucket entries and contains one record for each device resource name. It is intended to be used in conjunction with the QAPMDISK file.

Collection Services data files: [System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: File abbreviations

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRDTA) command See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMSMHTP

This database file contains summarized metrics from IBM HTTP Server (powered by Apache) data (*HTTP collection category) that can be used in support of system monitoring.

These metrics are calculated from more discrete data found in the QAPMHTTPB and QAPMHTTPD files. One record is written per database interval.

Field Name	Description	Attribute
INTNUM	Interval number. The <i>n</i> th sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DATETIME	Interval date and time. The date and time of the sample interval, expressed in local system time.	Timestamp
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
SMSERNUM	Number of servers included in this data.	B (9,0)
SMREQRAT	Requests received rate. The number of requests received per second.	PD (11,3)
SMREQMAX	Maximum requests received. The largest number of requests received by a server.	B (18,0)
SMREQNAM	Job name for the server with the largest number of requests received.	C (10)
SMREQUSR	Job user for the server with the largest number of requests received.	C (10)
SMREQJNO	Job number for the server with the largest number of requests received.	C (6)
SMRESRAT	Responses sent rate. The number of responses sent per second.	PD (11,3)
SMRESMAX	Maximum responses sent. The largest number of responses sent by a server.	B(18,0)
SMRESNAM	Job name for the server with the largest number of responses sent.	C (10)
SMRESUSR	Job user for the server with the largest number of responses sent.	C (10)
SMRESJNO	Job number for the server with the largest number of responses sent.	C (6)
SMNCARAT	Average non-cached requests processed rate. The percent of non-cached requests processed averaged for the servers.	PD (11,3)

Field Name	Description	Attribute
SMNCAMAX	Maximum non-cached requests processed rate. The highest percent of non-cached requests processed for a single server.	PD (11,3)
SMNCANAM	Job name for the server with the highest percent of non-cached requests processed.	C (10)
SMNCAUSR	Job user for the server with the highest percent of non-cached requests processed.	C (10)
SMNCAJNO	Job number for the server with the highest percent of non-cached requests processed.	C (6)
SMERRRAT	Average error reposes sent rate. The percent of error responses sent averaged for the servers.	PD (11,3)
SMERRMAX	Maximum error responses sent rate. The highest percent of error responses sent for a single server.	PD (11,3)
SMERRNAM	Job name for the server with the highest percent of error responses sent.	C (10)
SMERRUSR	Job user for the server with the highest percent of error responses sent.	C (10)
SMERRJNO	Job number for the server with the highest percent of error responses sent.	C (6)
SMNCTTIM	Total processing time for non-cached requests. The accumulated processing time for all non-cached requests for the servers, in milliseconds.	B (18,0)
SMNCTMAX	Highest average processing time for non-cached requests. The highest average processing time for non-cached requests, in milliseconds, for a single server.	PD (11,3)
SMNCTNAM	Job name for the server with the highest average processing time for non-cached requests.	C (10)
SMNCTUSR	Job user for the server with the highest average processing time for non-cached requests.	C (10)
SMNCTJNO	Job number for the server with the highest average processing time for non-cached requests.	C (6)
SMCATTIM	Total processing time for cached requests. The accumulated processing time for all cached requests for the servers, in milliseconds.	B (18,0)
SMCATMAX	Highest average processing time for cached requests. The highest average processing time for cached requests, in milliseconds, for a single server.	PD (11,3)
SMCATNAM	Job name for the server with the highest average processing time for cached requests.	C (10)
SMCATUSR	Job user for the server with the highest average processing time for cached requests.	C (10)
SMCATJNO	Job number for the server with the highest average processing time for cached requests.	C (6)

Field Name	Description	Attribute
SMREQBTL	Total bytes received. The accumulated bytes received for the servers.	B (18,0)
SMRESBTL	Total bytes sent. The accumulated bytes sent for the servers.	B (18,0)
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp
SMHP4F01	Reserved.	B (9,0)
SMHP4F02	Reserved.	B (9,0)
SMHP8F01	Reserved.	B (18,0)
SMHP8F02	Reserved.	B (18,0)

Related reference

Collection Services data files: [QAPMHTTPB](#)

This database file contains basic data collected by the IBM HTTP Server (powered by Apache) category.

Collection Services data files: [QAPMHTTPD](#)

This database file contains detail data collected by the HTTP Server (powered by Apache) category.

Collection Services data files: [System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: [File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

[Create Performance Data \(CRTPFRTA\) command](#) See the Create Performance Data (CRTPFRTA) command for information on how to create performance database files.

Collection Services data files: QAPMSMJMI

This database file contains summarized metrics from job data (*JOBMI collection category) that may be used in support of system monitoring.

These metrics are calculated from more discrete data found in the QAPMJOBMI file. The breakdown dimension identifies a grouping of jobs for which data is provided. One record is written per database interval per breakdown dimension.

Field Name	Description	Attribute
INTNUM	Interval number. The <i>n</i> th sample database interval based on the start time specified in the Create Performance Data (CRTPFRTA) command.	PD (5,0)
DATETIME	Interval date and time. The date and time of the sample interval, expressed in local system time.	Timestamp
INTSEC	Elapsed interval seconds. The number of seconds since the last sample interval.	PD (7,0)

Field Name	Description	Attribute
SMMBDD	Job breakdown dimension. Identifies which records from QAPMJOBMI were used to calculate the data in this record. <ul style="list-style-type: none"> '01' - Interactive (job type I) jobs (including threads) '02' - Batch (job type B) jobs (including threads) 	C (2)
SMMNUM	Number of entries included in this data.	B (9,0)
SMMTCUP	CPU used percent. Percent of unscaled CPU time consumed relative to the configured CPU entitlement of the partition.	B (9,2)
SMMTCPUT	CPU used. Accumulated unscaled CPU time consumed in microseconds. Note: Based on field JBTCPU in QAPMJOBMI.	B (18,0)
SMMMCPUP	Maximum CPU used percent. The largest amount of unscaled CPU time consumed relative to the configured CPU entitlement of the partition consumed by a job.	B (9,2)
SMMMCPUT	Maximum CPU used. The largest amount of unscaled CPU time consumed in microseconds by a job.	B (18,0)
SMMMCPUJ	Maximum CPU job identifier. The value of JBTDE for the job with the highest CPU usage.	C (8)
SMMMCNAME	Maximum CPU job name. Job name for the job with the highest CPU usage.	C (16)
SMMMCUSER	Maximum CPU job user. Job user for the job with the highest CPU usage.	C (10)
SMMMCNBR	Maximum CPU job number. Job number for the job with the highest CPU usage.	C (6)
SMMB4F01	Reserved.	B (9,0)
SMMB8F01	Reserved.	B (18,0)
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp

Related reference

Collection Services data files: [QAPMJOBMI](#)

These database file entries contain task, primary, and secondary thread data that are collected with the *JOBMI category. "Job" implies job, task, or thread.

Collection Services data files: [System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: [File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRTA) command See the Create Performance Data (CRTPFRTA) command for information on how to create performance database files.

Collection Services data files: QAPMSMJOS

This database file contains summarized metrics from job data (*JOBOS collection category) that may be used in support of system monitoring.

These metrics are calculated from more discrete data found in the QAPMJOBOS file. One record is written per database interval.

Field Name	Description	Attribute
INTNUM	Interval number. The <i>n</i> th sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DATETIME	Interval date and time. The date and time of the sample interval, expressed in local system time.	Timestamp
INTSEC	Elapsed interval seconds. The number of seconds since the last sample interval.	PD (7,0)
SMOBLIOR	Batch logical IO rate. The average number of logical database read and write operations per second for batch jobs (job type B).	B (9,2)
SMOARSPT	Average interactive response time. The average interactive response time in milliseconds for interactive jobs (job type I).	B (9,0)
SMOMRSPT	Maximum interactive response time. The largest response time in milliseconds for an interactive job (job type I).	B (9,0)
SMOMRSPJ	Maximum interactive response time job identifier. The value of JBTDE for the interactive job (job type I) with the highest interactive response time.	C (8)
SMOMRNAME	Maximum interactive response time job name. Job name for the interactive job (job type I) with the highest interactive response time.	C (10)
SMOMRUSER	Maximum interactive response time job user. Job user for the interactive job (job type I) with the highest interactive response time.	C (10)
SMOMRNBR	Maximum interactive response time job number. Job number for the interactive job (job type I) with the highest interactive response time.	C (6)
SMOITRNR	Interactive transaction rate. The number of transactions per second for interactive jobs (job type I).	B (9,2)
SMOSPLFR	Spoiled file creation rate. The number of spoiled files being created per second.	B (9,2)
SMOMSPLF	Maximum spoiled files created. The largest number of spoiled files created by a job.	B (9,0)
SMOMSPLFJ	Maximum spoiled files created job identifier. The value of JBTDE for the job creating the most spoiled files.	C (8)
SMOMSNAME	Maximum spoiled files created job name. Job name for the job creating the most spoiled files.	C (10)

Field Name	Description	Attribute
SMOMSUSER	Maximum spooled files created job user. Job user for the job creating the most spooled files.	C (10)
SMOMSNBR	Maximum spooled files created job number. Job number for the job creating the most spooled files.	C (6)
SMOB4F01	Reserved.	B (9,0)
SMOB4F02	Reserved.	B (9,0)
SMOB8F01	Reserved.	B (18,0)
SMOB8F02	Reserved.	B (18,0)
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp

Related reference

Collection Services data files: [QAPMJOBOS](#)

These database file entries contain data specific to system jobs.

Collection Services data files: [System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: [File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

[Create Performance Data \(CRTPFRDTA\) command](#) See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMSMPOL

This database file contains summarized metrics from pool data (*POOL collection category) that may be used in support of system monitoring.

These metrics are calculated from more discrete data found in the QAPMPOOLB file. One record is written per database interval.

Field Name	Description	Attribute
INTNUM	Interval number. The <i>n</i> th sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DATETIME	Interval date and time. The date and time of the sample interval, expressed in local system time.	Timestamp
INTSEC	Elapsed interval seconds. The number of seconds since the last sample interval.	PD (7,0)
SMPMFLTR	Machine pool fault rate. The number of faults per second (both database and non-database) in the machine pool.	B (9,0)
SMPUNUM	Number of user pools included in this data.	B (4,0)
SMPUAFLTR	Average user pool fault rate. The average number of faults per second (both database and non-database) per user pool.	B (9,0)

Field Name	Description	Attribute
SMPUMFLTR	Maximum user pool fault rate. The number of faults per second (both database and non-database) for the user pool with the highest fault rate.	B (9,0)
SMPUMFLTP	User pool number with the highest fault rate.	B (4,0)
SMPB4F01	Reserved.	B (9,0)
SMPB4F02	Reserved.	B (9,0)
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp
SMPUMFLTPN	User pool name with the highest fault rate.	C (32)

Related reference

Collection Services data files: QAPMPOOLB

This database file includes main storage pool file entries and lists the counters for system storage pools.

Collection Services data files: System category and file relationships

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: File abbreviations

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRDTA) command See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMSMSYS

This database file contains summarized metrics from system data (*SYSLVL collection category) that may be used in support of system monitoring.

These metrics are calculated from more discrete data found in the QAPMSYSTEM file. One record is written per database interval.

Field Name	Description	Attribute
INTNUM	Interval number. The <i>n</i> th sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DATETIME	Interval date and time. The date and time of the sample interval, expressed in local system time.	Timestamp
INTSEC	Elapsed interval seconds. The number of seconds since the last sample interval.	PD (7,0)
SMSCPUCPU	Configured CPU percent unscaled. The amount of unscaled system CPU consumed relative to the configured CPU time (processor units) available to the partition during the interval.	B (9,2)
SMSCPUUPU	Uncapped CPU percent unscaled. The amount of unscaled system CPU consumed relative to the maximum uncapped CPU time the partition could consume based on the smaller of the virtual processors assigned to the partition and the capacity of the shared virtual pool.	B (9,2)

Field Name	Description	Attribute
SMSCPUVPU	Virtual CPU percent unscaled. The amount of unscaled system CPU consumed relative to the number of virtual processors allocated to the partition during the interval.	B (9,2)
SMSCPUCPS	Configured CPU percent scaled. The amount of scaled system CPU consumed relative to the configured CPU time (processor units) available to the partition during the interval.	B (9,2)
SMSCPUUPS	Uncapped CPU percent scaled. The amount of scaled system CPU consumed relative to the maximum uncapped CPU time the partition could consume based on the smaller of the virtual processors assigned to the partition and the capacity of the shared virtual pool.	B (9,2)
SMSCPUVPS	Virtual CPU percent scaled. The amount of scaled system CPU consumed relative to the number of virtual processors allocated to the partition during the interval.	B (9,2)
SMSPRCSPDP	Processor speed percent. Processor speed, relative to nominal, shown as a percent (based on the ratio of scaled CPU consumed to unscaled CPU consumed). Note: This value may not be accurate at low utilizations.	B (9,2)
SMSVSPP	Virtual shared pool CPU percent. The amount of CPU consumed in the virtual shared pool by all partitions using the pool relative to the CPU available within the pool.	B (9,2)
SMSPSPP	Physical shared pool CPU percent. The amount of CPU consumed in the physical shared pool by all partitions using the pool relative to the CPU available within the pool.	B (9,2)
SMSTSTGU	Temporary storage used. The total amount of temporary storage (megabytes) in use within the system. This includes both system and user temporary storage.	B (18,0)
SMSTSTGP	Temporary storage percent. The percent of the system ASP that is in use for temporary storage.	B (9,2)
SMSCPUQPU	SQL CPU percent unscaled. The amount of unscaled system CPU consumed performing work done on behalf of SQL operations relative to the configured CPU time (processor units) available to the partition during the interval.	B (9,2)
SMSB4F01	Reserved.	B (9,0)
SMSB4F01	Reserved.	B (9,0)
SMSB8F01	Reserved.	B (18,0)
SMSB8F01	Reserved.	B (18,0)

Field Name	Description	Attribute
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp

Related reference

Collection Services data files: QAPMSYSTEM

This database file reports system-wide performance data.

Collection Services data files: System category and file relationships

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: File abbreviations

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRDTA) command See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMSNA

This database file defines the fields in the Systems Network Architecture (SNA) file record.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
SCTLNM	Controller description name.	C (10)
SLINNM	Line description name.	C (10)
STSKNM	T2 station I/O manager (SIOM) task name.	C (6)
SLIOMT	Line I/O manager task name.	C (6)
SACPNM	Adjacent control point (CP) name.	C (8)
SANWID	Adjacent network ID.	C (8)
SAPPN	APPN-capable (Y=yes, N=no).	C (1)
SCTYP	Controller type (A=APPC, H=Host).	C (1)
SSMFS	Send maximum frame size.	PD (11,0)
SRMFS	Receive maximum frame size.	PD (11,0)
STLLBU	Date (<i>yymmdd</i>) and time (<i>hhmmss</i>) when most recent connection was established with the adjacent system.	C (12)
SNLBU	Number of times a connection has been established with the remote system.	PD (11,0)

Field Name	Description	Attribute
STACVO	Cumulative elapsed time for automatically created and/or varied-on devices.	PD (11,0)
SNACVO	Number of automatically created and/or varied-on devices.	PD (11,0)
SNADD	Number of automatically deleted devices.	PD (11,0)
SNWAIN	Number of work activities coming in from other T2 SIOM tasks (for example, messages received).	PD (11,0)
SNWAOU	Number of work activities sent out to other T2 SIOM tasks (for example, messages received).	PD (11,0)
The following fields refer to end point session attributes:		
ENNSS	Number of network priority sessions started.	PD (11,0)
ENNSE	Number of network priority sessions ended.	PD (11,0)
ENNBB	Number of request units with begin bracket sent and received for all network priority sessions.	PD (11,0)
ENNEB	Number of request units with end bracket sent and received for all network priority sessions.	PD (11,0)
ENSPWT	The cumulative wait time for all network priority sessions (in milliseconds) caused by session-level send messages. This wait time measures the amount of time application data was blocked (could not be sent) waiting for a pacing response to be received from the adjacent system.	PD (11,0)
ENSPNW	Number of waits occurring for all network priority sessions for session-level send pacing. That is, the number of times application data was blocked (could not be sent) waiting for a pacing response to be received from the adjacent system.	PD (11,0)
ENSPPW	Number of potential waits occurring for all network priority sessions for session-level send pacing. This is the worst case that would occur if the sending of application data was delayed waiting for every pacing response sent by the adjacent system.	PD (11,0)
ENSPWS	The cumulative window size for all network priority sessions for session-level send pacing. Each time a pacing response is received from the adjacent system on a network priority session, this count is increased by window size specified by the pacing response.	PD (11,0)
ENIPWT	The cumulative wait time for all network priority sessions (in milliseconds) for internal session-level pacing. That is, the number of times application data was blocked (could not be sent) waiting for data to be delivered to the adjacent system.	PD (11,0)

Field Name	Description	Attribute
ENIPNW	Number of waits occurring for all network priority sessions for internal session-level pacing. That is, the number of times application data was blocked (could not be sent) waiting for data to be delivered to the adjacent system.	PD (11,0)
ENQNRE	Number of network priority request/response units entering the transmission priority queue.	PD (11,0)
ENQLRE	Length of network priority request/response units entering the transmission priority queue.	PD (11,0)
ENQNRL	Number of network priority request/response units leaving the transmission priority queue.	PD (11,0)
ENQLRL	Length of network priority request/response units leaving the transmission priority queue.	PD (11,0)
ENQTRR	Cumulative wait time in network transmission priority queue.	PD (11,0)
ENNRUD	Number of network priority request/response units delivered to the adjacent system.	PD (11,0)
ENLRUD	Length of network priority request/response units delivered to the adjacent system.	PD (11,0)
ENTRUD	Cumulative service time to deliver a network priority request/response unit to the adjacent system.	PD (11,0)
ENNRUR	Number of network priority request/response units received from the adjacent system.	PD (11,0)
ENLRUR	Length of network priority request/response units received from the adjacent system.	PD (11,0)
EHNSS	Number of high priority sessions started	PD (11,0)
EHNSE	Number of high priority sessions ended	PD (11,0)
EHNBB	Number of request units with begin bracket sent and received for all high priority sessions	PD (11,0)
EHNEB	Number of request units with end bracket sent and received for all high priority sessions	PD (11,0)
EHSPWT	The cumulative wait time for all high priority sessions (in milliseconds) caused by session-level send messages. This wait time measures the amount of time application data was blocked (could not be sent) waiting for a pacing response to be received from the adjacent system.	PD (11,0)
EHSPNW	Number of waits occurring for all high priority sessions for session-level send pacing. That is, the number of times application data was blocked (could not be sent) waiting for a pacing response to be received from the adjacent system.	PD (11,0)

Field Name	Description	Attribute
EHSPPW	Number of potential waits occurring for all high priority sessions for session-level send pacing. This is the worst case that would occur if the sending of application data was delayed waiting for every pacing response sent by the adjacent system.	PD (11,0)
EHSPWS	The cumulative window size for all high priority sessions for session-level send pacing. Each time a pacing response is received from the adjacent system on a network priority session, this count is increased by window size specified by the pacing response.	PD (11,0)
EHIPWT	The cumulative wait time for all high priority sessions (in milliseconds) for internal session-level pacing. That is, the number of times application data was blocked (could not be sent) waiting for data to be delivered to the adjacent system.	PD (11,0)
EHIPNW	Number of waits occurring for all high priority sessions for internal session-level pacing. That is, the number of times application data was blocked (could not be sent) waiting for data to be delivered to the adjacent system.	PD (11,0)
EHQNRE	Number of high priority request/response units entering the transmission priority queue.	PD (11,0)
EHQLRE	Length of high priority request/response units entering the transmission priority queue.	PD (11,0)
EHQNRL	Number of high priority request/response units leaving the transmission priority queue.	PD (11,0)
EHQLRL	Length of high priority request/response units leaving the transmission priority queue.	PD (11,0)
EHQTRR	Cumulative wait time in high transmission priority queue.	PD (11,0)
EHN Rud	Number of high priority request/response units delivered to the adjacent system.	PD (11,0)
EHL Rud	Length of high priority request/response units delivered to the adjacent system.	PD (11,0)
EHRud	Cumulative service time to deliver a high priority request/response unit to the adjacent system.	PD (11,0)
EHRUR	Number of high priority request/response units received from the adjacent system.	PD (11,0)
EHLRUR	Length of high priority request/response units received from the adjacent system.	PD (11,0)
EMNSS	Number of medium priority sessions started	PD (11,0)
EMNSE	Number of medium priority sessions ended	PD (11,0)
EMNBB	Number of request units with begin bracket sent and received for all medium priority sessions	PD (11,0)

Field Name	Description	Attribute
EMNEB	Number of request units with end bracket sent and received for all medium priority sessions	PD (11,0)
EMSPWT	The cumulative wait time for all medium priority sessions (in milliseconds) caused by session-level send messages. This wait time measures the amount of time application data was blocked (could not be sent) waiting for a pacing response to be received from the adjacent system	PD (11,0)
EMSPNW	Number of waits occurring for all medium priority sessions for session-level send pacing. That is, the number of times application data was blocked (could not be sent) waiting for a pacing response to be received from the adjacent system.	PD (11,0)
EMSPPW	Number of potential waits occurring for all medium priority sessions for session-level send pacing. This is the worst case that would occur if the sending of application data was delayed waiting for every pacing response sent by the adjacent system.	PD (11,0)
EMSPWS	The cumulative window size for all medium priority sessions for session-level send pacing. Each time a pacing response is received from the adjacent system on a network priority session, this count is increased by window size specified by the pacing response.	PD (11,0)
EMIPWT	The cumulative wait time for all medium priority sessions (in milliseconds) for internal session-level pacing. That is, the number of times application data was blocked (could not be sent) waiting for data to be delivered to the adjacent system.	PD (11,0)
EMIPNW	Number of waits occurring for all medium priority sessions for internal session-level pacing. That is, the number of times application data was blocked (could not be sent) waiting for data to be delivered to the adjacent system.	PD (11,0)
EMQNRE	Number of medium priority request/response units entering the transmission priority queue.	PD (11,0)
EMQLRE	Length of medium priority request/response units entering the transmission priority queue.	PD (11,0)
EMQNRL	Number of medium priority request/response units leaving the transmission priority queue.	PD (11,0)
EMQLRL	Length of medium priority request/response units leaving the transmission priority queue.	PD (11,0)
EMQTRR	Cumulative wait time in medium transmission priority queue.	PD (11,0)
EMNRUD	Number of medium priority request/response units delivered to the adjacent system.	PD (11,0)
EMLRUD	Length of medium priority request/response units delivered to the adjacent system.	PD (11,0)

Field Name	Description	Attribute
EMTRUD	Cumulative service time to deliver a medium priority request/response unit to the adjacent system.	PD (11,0)
EMNRUR	Number of medium priority request/response units received from the adjacent system.	PD (11,0)
EMLRUR	Length of medium priority request/response units received from the adjacent system.	PD (11,0)
ELNSS	Number of low priority sessions started	PD (11,0)
ELNSE	Number of low priority sessions ended.	PD (11,0)
ELNBB	Number of request units with begin bracket sent and received for all low priority sessions.	PD (11,0)
ELNEB	Number of request units with end bracket sent and received for all low priority sessions.	PD (11,0)
ELSPWT	The cumulative wait time for all low priority sessions (in milliseconds) caused by session-level send messages. This wait time measures the amount of time application data was blocked (could not be sent) waiting for a pacing response to be received from the adjacent system	PD (11,0)
ELSPNW	Number of waits occurring for all low priority sessions for session-level send pacing. That is, the number of times application data was blocked (could not be sent) waiting for a pacing response to be received from the adjacent system.	PD (11,0)
ELSPPW	Number of potential waits occurring for all low priority sessions for session-level send pacing. This is the worst case that would occur if the sending of application data was delayed waiting for every pacing response sent by the adjacent system.	PD (11,0)
ELSPWS	The cumulative window size for all low priority sessions for session-level send pacing. Each time a pacing response is received from the adjacent system on a network priority session, this count is increased by window size specified by the pacing response.	PD (11,0)
ELIPWT	The cumulative wait time for all low priority sessions (in milliseconds) for internal session-level pacing. That is, the number of times application data was blocked (could not be sent) waiting for data to be delivered to the adjacent system.	PD (11,0)
ELIPNW	Number of waits occurring for all low priority sessions for internal session-level pacing. That is, the number of times application data was blocked (could not be sent) waiting for data to be delivered to the adjacent system.	PD (11,0)
ELQRE	Number of low priority request/response units entering the transmission priority queue.	PD (11,0)

Field Name	Description	Attribute
ELQLRE	Length of low priority request/response units entering the transmission priority queue.	PD (11,0)
ELQNRL	Number of low priority request/response units leaving the transmission priority queue.	PD (11,0)
ELQLRL	Length of low priority request/response units leaving the transmission priority queue.	PD (11,0)
ELQTRR	Cumulative wait time in low transmission priority queue.	PD (11,0)
ELNRUD	Number of low priority request/response units delivered to the adjacent system.	PD (11,0)
ELLRUD	Length of low priority request/response units delivered to the adjacent system.	PD (11,0)
ELTRUD	Cumulative service time to deliver a low priority request/response unit to the adjacent system.	PD (11,0)
ELNRUR	Number of low priority request/response units received from the adjacent system.	PD (11,0)
ELLRUR	Length of low priority request/response units received from the adjacent system.	PD (11,0)
The following fields refer to intermediate sessions:		
INNSS	Number of network priority sessions started	PD (11,0)
INNSE	Number of network priority sessions ended	PD (11,0)
INNBB	Number of request units with begin bracket sent and received for all network priority sessions	PD (11,0)
INNEB	Number of request units with end bracket sent and received for all network priority sessions	PD (11,0)
INSPWT	The cumulative wait time for all network priority sessions (in milliseconds) caused by session-level send messages. This wait time measures the amount of time application data was blocked (could not be sent) waiting for a pacing response to be received from the adjacent system.	PD (11,0)
INSPNW	Number of waits occurring for all network priority sessions for session-level send pacing. That is, the number of times application data was blocked (could not be sent) waiting for a pacing response to be received from the adjacent system.	PD (11,0)
INSPPW	Number of potential waits occurring for all network priority sessions for session-level send pacing. This is the worst case that would occur if the sending of application data was delayed waiting for every pacing response sent by the adjacent system.	PD (11,0)

Field Name	Description	Attribute
INSPWS	The cumulative window size for all network priority sessions for session-level send pacing. Each time a pacing response is received from the adjacent system on a network priority session, this count is increased by window size specified by the pacing response.	PD (11,0)
INIPWT	The cumulative wait time for all network priority sessions (in milliseconds) for internal session-level pacing. That is, the number of times application data was blocked (could not be sent) waiting for data to be delivered to the adjacent system.	PD (11,0)
INIPNW	Number of waits occurring for all network priority sessions for internal session-level pacing. That is, the number of times application data was blocked (could not be sent) waiting for data to be delivered to the adjacent system.	PD (11,0)
INQNRE	Number of network priority request/response units entering the transmission priority queue.	PD (11,0)
INQLRE	Length of network priority request/response units entering the transmission priority queue.	PD (11,0)
INQNRL	Number of network priority request/response units leaving the transmission priority queue.	PD (11,0)
INQLRL	Length of network priority request/response units leaving the transmission priority queue.	PD (11,0)
INQTRR	Cumulative wait time in network transmission priority queue.	PD (11,0)
INNRUD	Number of network priority request/response units delivered to the adjacent system.	PD (11,0)
INLRUD	Length of network priority request/response units delivered to the adjacent system.	PD (11,0)
INTRUD	Cumulative service time to deliver a network priority request/response unit to the adjacent system.	PD (11,0)
INNRUR	Number of network priority request/response units received from the adjacent system.	PD (11,0)
INLRUR	Length of network priority request/response units received from the adjacent system.	PD (11,0)
IHNSS	Number of high priority sessions started.	PD (11,0)
IHNSE	Number of high priority sessions ended.	PD (11,0)
IHNBB	Number of request units with begin bracket sent and received for all high priority sessions.	PD (11,0)
IHNEB	Number of request units with end bracket sent and received for all high priority sessions.	PD (11,0)

Field Name	Description	Attribute
IHSPWT	The cumulative wait time for all high priority sessions (in milliseconds) caused by session-level send messages. This wait time measures the amount of time application data was blocked (could not be sent) waiting for a pacing response to be received from the adjacent system.	PD (11,0)
IHSPNW	Number of waits occurring for all high priority sessions for session-level send pacing. That is, the number of times application data was blocked (could not be sent) waiting for a pacing response to be received from the adjacent system.	PD (11,0)
IHSPPW	Number of potential waits occurring for all high priority sessions for session-level send pacing. This is the worst case that would occur if the sending of application data was delayed waiting for every pacing response sent by the adjacent system.	PD (11,0)
IHSPWS	The cumulative window size for all high priority sessions for session-level send pacing. Each time a pacing response is received from the adjacent system on a network priority session, this count is increased by window size specified by the pacing response.	PD (11,0)
IHIPWT	The cumulative wait time for all high priority sessions (in milliseconds) for internal session-level pacing. That is, the number of times application data was blocked (could not be sent) waiting for data to be delivered to the adjacent system.	PD (11,0)
IHIPNW	Number of waits occurring for all high priority sessions for internal session-level pacing. That is, the number of times application data was blocked (could not be sent) waiting for data to be delivered to the adjacent system.	PD (11,0)
IHQNRE	Number of high priority request/response units entering the transmission priority queue.	PD (11,0)
IHQLRE	Length of high priority request/response units entering the transmission priority queue.	PD (11,0)
IHQNRL	Number of high priority request/response units leaving the transmission priority queue.	PD (11,0)
IHQLRL	Length of high priority request/response units leaving the transmission priority queue.	PD (11,0)
IHQTRR	Cumulative wait time in high transmission priority queue.	PD (11,0)
IHNRUD	Number of high priority request/response units delivered to the adjacent system.	PD (11,0)
IHLRUD	Length of high priority request/response units delivered to the adjacent system.	PD (11,0)
IHTRUD	Cumulative service time to deliver a high priority request/response unit to the adjacent system.	PD (11,0)

Field Name	Description	Attribute
IHNRRUR	Number of high priority request/response units received from the adjacent system.	PD (11,0)
IHLRUR	Length of high priority request/response units received from the adjacent system.	PD (11,0)
IMNSS	Number of medium priority sessions started.	PD (11,0)
IMNSE	Number of medium priority sessions ended.	PD (11,0)
IMNBB	Number of request units with begin bracket sent and received for all medium priority sessions.	PD (11,0)
IMNEB	Number of request units with end bracket sent and received for all medium priority sessions.	PD (11,0)
IMSPWT	The cumulative wait time for all medium priority sessions (in milliseconds) caused by session-level send messages. This wait time measures the amount of time application data was blocked (could not be sent) waiting for a pacing response to be received from the adjacent system.	PD (11,0)
IMSPNW	Number of waits occurring for all medium priority sessions for session-level send pacing. That is, the number of times application data was blocked (could not be sent) waiting for a pacing response to be received from the adjacent system.	PD (11,0)
IMSPPW	Number of potential waits occurring for all medium priority sessions for session-level send pacing. This is the worst case that would occur if the sending of application data was delayed waiting for every pacing response sent by the adjacent system.	PD (11,0)
IMSPWS	The cumulative window size for all medium priority sessions for session-level send pacing. Each time a pacing response is received from the adjacent system on a network priority session, this count is increased by window size specified by the pacing response.	PD (11,0)
IMIPWT	The cumulative wait time for all medium priority sessions (in milliseconds) for internal session-level pacing. That is, the number of times application data was blocked (could not be sent) waiting for data to be delivered to the adjacent system.	PD (11,0)
IMIPNW	Number of waits occurring for all medium priority sessions for internal session-level pacing. That is, the number of times application data was blocked (could not be sent) waiting for data to be delivered to the adjacent system.	PD (11,0)
IMQNRE	Number of medium priority request/response units entering the transmission priority queue.	PD (11,0)
IMQLRE	Length of medium priority request/response units entering the transmission priority queue.	PD (11,0)

Field Name	Description	Attribute
IMQNRRL	Number of medium priority request/response units leaving the transmission priority queue.	PD (11,0)
IMQLRL	Length of medium priority request/response units leaving the transmission priority queue.	PD (11,0)
IMQTRR	Cumulative wait time in medium transmission priority queue.	PD (11,0)
IMNRUD	Number of medium priority request/response units delivered to the adjacent system.	PD (11,0)
IMLRUD	Length of medium priority request/response units delivered to the adjacent system.	PD (11,0)
IMTRUD	Cumulative service time to deliver a medium priority request/response unit to the adjacent system.	PD (11,0)
IMNRUR	Number of medium priority request/response units received from the adjacent system.	PD (11,0)
IMLRUR	Length of medium priority request/response units received from the adjacent system.	PD (11,0)
ILNSS	Number of low priority sessions started.	PD (11,0)
ILNSE	Number of low priority sessions ended.	PD (11,0)
ILNBB	Number of request units with begin bracket sent and received for all low priority sessions.	PD (11,0)
ILNEB	Number of request units with end bracket sent and received for all low priority sessions.	PD (11,0)
ILSPWT	The cumulative wait time for all low priority sessions (in milliseconds) caused by session-level send messages. This wait time measures the amount of time application data was blocked (could not be sent) waiting for a pacing response to be received from the adjacent system.	PD (11,0)
ILSPNW	Number of waits occurring for all low priority sessions for session-level send pacing. That is, the number of times application data was blocked (could not be sent) waiting for a pacing response to be received from the adjacent system.	PD (11,0)
ILSPPW	Number of potential waits occurring for all low priority sessions for session-level send pacing. This is the worst case that would occur if the sending of application data was delayed waiting for every pacing response sent by the adjacent system.	PD (11,0)
ILSPWS	The cumulative window size for all low priority sessions for session-level send pacing. Each time a pacing response is received from the adjacent system on a network priority session, this count is increased by window size specified by the pacing response.	PD (11,0)

Field Name	Description	Attribute
ILIPWT	The cumulative wait time for all low priority sessions (in milliseconds) for internal session-level pacing. That is, the number of times application data was blocked (could not be sent) waiting for data to be delivered to the adjacent system.	PD (11,0)
ILIPNW	Number of waits occurring for all low priority sessions for internal session-level pacing. That is, the number of times application data was blocked (could not be sent) waiting for data to be delivered to the adjacent system.	PD (11,0)
ILQNRE	Number of low priority request/response units entering the transmission priority queue.	PD (11,0)
ILQLRE	Length of low priority request/response units entering the transmission priority queue.	PD (11,0)
ILQNRL	Number of low priority request/response units leaving the transmission priority queue.	PD (11,0)
ILQLRL	Length of low priority request/response units leaving the transmission priority queue.	PD (11,0)
ILQTRR	Cumulative wait time in low transmission priority queue.	PD (11,0)
ILNRUD	Number of low priority request/response units delivered to the adjacent system.	PD (11,0)
ILLRUD	Length of low priority request/response units delivered to the adjacent system.	PD (11,0)
ILTRUD	Cumulative service time to deliver a low priority request/response unit to the adjacent system.	PD (11,0)
ILNRUR	Number of low priority request/response units received from the adjacent system.	PD (11,0)
ILLRUR	Length of low priority request/response units received from the adjacent system.	PD (11,0)
DATETIME	Interval date and time: The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp

Related reference

[Collection Services data files: System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

[Data files: File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

[Create Performance Data \(CRTPFRDTA\) command](#) See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMSNADS

This database file defines the fields in the SNA distribution services (SNADS) files record.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
SNJNAM	SNADS job name.	C(10)
SNJUSR	SNADS job user.	C(10)
SNJNBR	SNADS job number.	C(6)
SNFTYP	This is a SNADS function type indicating which SNADS function this job is running. The SNFTYP field is used to determine the type of activity that this SNADS job conducts. <ul style="list-style-type: none"> • 1 -- SNADS router • 2 -- SNADS receiver • 3 -- SNADS sender • 8 -- SNADS DLS Gate (Document Library Services) • 9 -- SNADS RPDS Gate (VM/MVS™ bridge, SMTP, X.400) 	PD(3,0)
SNNTR	Transaction count.	PD(11,0)
SNTRT	Transaction time: The time from a distribution being put on the queue to the time processing that distribution within this job is completed.	PD(11,0)
SNRUT	Resource usage time: The total time that distributions are processed, not including the time that they are waiting on the queue.	PD(11,0)
SNATN	Active transitions: The number of transitions between waiting for conditions to be satisfied (a distribution to process) and starting to process a distribution.	PD(11,0)
SNERR	Error count: Number of transactions that ended in error.	PD(11,0)
SNNRC	Number of recipients: The number of recipients identified in the distribution.	PD(11,0)
SNFSO	File server object (FSO) count: The number of transactions that required a data object or document to be processed.	PD(11,0)

Field Name	Description	Attribute
SNFSOB	FSO byte count: The size of the FSOs (data objects and documents) processed by transactions.	PD (11,0)
SNFOC	Fan-out count: The accumulated value of the number of distribution queues that received a copy of a distribution during routing. For a single distribution processed by the router, this value is the number of sender transactions (paths) the distribution will take leaving the system. This is the number of distribution copies that leave the system. (This field is only supported by the router job.)	PD (11,0)
SNLOC	Set to '1' when a local delivery queue received a copy of the distribution during routing. This indicates that the local system was a destination for the distribution. (This field is only supported by the router job.)	PD (11,0)
DATETIME	Interval date and time: The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp

Related reference

[Collection Services data files: System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

[Data files: File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

[Create Performance Data \(CRTPFRDTA\) command](#) See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMSQLPC

This database file contains the performance data about the SQL Plan Cache collected by the *SQL collection category.

Field Name	Description	Attribute
INTNUM	Interval number: The <i>n</i> th sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DATETIME	Interval date and time: The date and time of the sample interval, expressed in local system time.	Timestamp
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
SQCURQRY	Active queries. A snapshot, taken at sample time, of the total number of queries currently active.	B (18,0)
SQCURPLN	Plans in SQL plan cache. A snapshot, taken at sample time, of the total number of plans currently in the SQL plan cache.	B (18,0)

Field Name	Description	Attribute
SQPCSIZE	Plan cache size. The current size (in megabytes) of the SQL plan cache.	B (18,0)
SQPCLIMIT	Plan cache size limit. The maximum size (in megabytes) that the SQL plan cache is allowed to be.	B (18,0)
SQPCTHRESH	Plan cache size threshold. The maximum size (shown as a percentage of the plan cache size limit) that the SQL plan cache is allowed to be before DB2 automatically manages the SQL plan cache and replaces older plans with new plans.	B (18,0)
SQCURSUBC	Sub caches. A snapshot, taken at sample time, of the total number of sub caches.	B (18,0)
SQCURSMP	Reserved.	B (18,0)
SQCURMTI	MTIs. A snapshot, taken at sample time, of the total number of Maintained Temporary Indexes (MTIs).	B (18,0)
SQCURPRUNL	Pruning event listeners. A snapshot, taken at sample time, of the total number of pruning event listeners.	B (18,0)
SQCURROQ	Cached runtime objects. A snapshot, taken at sample time, of the total number of cached runtime objects (for queries) in the SQL plan cache.	B (18,0)
SQCURTROQ	Cached runtime objects with temporary results. A snapshot, taken at sample time, of the total number of cached runtime objects (for queries) in the SQL plan cache which may have retained part or all of the query answer set in a temporary copy.	B (18,0)
SQCURRROQ	Reusable runtime objects. A snapshot, taken at sample time, of the total number of reusable runtime objects (for queries) in the SQL plan cache.	B (18,0)
SQCURTEMP	Temporary storage. A snapshot, taken at sample time, of the total amount of temporary storage (in megabytes) associated with the SQL plan cache.	B (18,0)
SQPLNBLT	Plans built. The number of plans built during the interval.	B (18,0)
SQQRYRROQ	Queries run with reusable runtime objects. The number of queries executed during the interval using runtime objects (for queries) where the runtime objects were candidates for being cached in the SQL plan cache for reuse by the same or other jobs.	B (18,0)
SQQRYNRROQ	Queries run with non-reusable runtime objects. The number of queries executed during the interval using runtime objects (for queries) where the runtime objects cannot be cached in the SQL plan cache.	B (18,0)

Field Name	Description	Attribute
SQQRYNOROQ	Queries run without runtime objects. The number of queries executed during the interval where a plan in the SQL plan cache was used but there were no cached runtime objects (for queries) available for use.	B (18,0)
SQPROBES	Plan cache probes. The number of times the plan cache was probed during the interval.	B (18,0)
SQMATCH	Plan cache probe matches. The number of times a plan cache probe found a match during the interval.	B (18,0)
SQNOMATCH	Plan cache probe misses. The number of times a plan cache probe was unable to find a match during the interval.	B (18,0)
SQPCWAKE	Plan cache awakenings. The number of times the plan cache woke up during the interval.	B (18,0)
SQPCNAP	Plan cache naps. The number of times the plan cache fell asleep during the interval.	B (18,0)
SQPLNPRUN	Plans pruned. The number of plans pruned from the SQL plan cache during the interval due to plan cache size.	B (18,0)
SQPLNRMV	Plans removed. The number of obsolete plans removed from the SQL plan cache during the interval.	B (18,0)
SQOPEN	Query opens. The number of full and pseudo opens that occurred during the interval.	B (18,0)
SQFOPEN	Query full opens. The number of full opens that occurred during the interval.	B (18,0)
SQFOPENROQ	Query full opens using cached runtime objects. The number of full opens that occurred during the interval which used both a plan and a cached runtime object from the SQL plan cache.	B (18,0)
SQPOPNHCLS	Queries hard closed. The number of queries that were hard closed during the interval.	B (18,0)
SQMTICRT	MTIs created. The number of Maintained Temporary Indexes (MTIs) created during the interval.	B (18,0)
SQMTIDLT	MTIs deleted. The number of Maintained Temporary Indexes (MTIs) deleted during the interval.	B (18,0)
SQAQPWAKE	AQP interrogations. The number of executing queries checked by Adaptive Query Processing (AQP) during the interval.	B (18,0)
SQAQPRPL	Runtime object replacements by AQP. The number of runtime objects replaced because of Adaptive Query Processing (AQP).	B (18,0)

Field Name	Description	Attribute
SQFULLOPT	Full optimizations. The number of full optimizations that occurred during the interval.	B (18,0)
SQREOPT	Reoptimizations with valid plans. The number of reoptimizations that occurred during the interval when valid plans existed.	B (18,0)
SQPCFLD01	Reserved.	B (18,0)
SQPCFLD02	Reserved.	B (18,0)
SQPCFLD03	Reserved.	B (18,0)
SQPCFLD04	Reserved.	B (18,0)
SQPCFLD05	Reserved.	B (18,0)
SQPCFLD06	Reserved.	B (18,0)
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp

Related reference

[Collection Services data files: System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

[Data files: File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

[Create Performance Data \(CRTPFRDTA\) command](#) See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMSTND

This database file includes FDDI station file entries.

This is the station counter file for distributed data interface (DDI) information. These fields are in the DDI station counter file.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
IOPRN	IOP resource name.	C(10)
SDIOPI	Reserved	C (1)
SDTYPE	The resource type of the IOP or adapter represented by this record.	C (4)
SDPCEP	The provider connection end point (PCEP) ID.	C (8)

Field Name	Description	Attribute
SDLND	Line description: The name of the description for this line.	C (10)
SDSTNN	Station name: The name of the station on this line.	C (10)
SDLSPD	Line speed: The line speed expressed in bits per second (bps).	PD (11,0)
SDTXMT	Total number of Type II frames transmitted.	PD (11,0)
SDTRCV	Total number of Type II frames received.	PD (11,0)
SDBXMT	Total number of bytes transmitted in all I-frames.	PD (11,0)
SDBRCV	Total number of bytes received in all I-frames.	PD (11,0)
SDIXMT	Total number of I-frames transmitted.	PD (11,0)
SDIRCV	Total number of I-frames received.	PD (11,0)
SDIREX	Number of I-frames retransmitted.	PD (11,0)
SDBREX	Number of bytes retransmitted in I-frames.	PD (11,0)
SDRNRX	Number of receive-not-ready frames transmitted.	PD (5,0)
SDRNRR	Number of receive-not-ready frames received.	PD (5,0)
SDFRMX	Number of frame-reject frames transmitted.	PD (5,0)
SDFRMR	Number of frame-reject frames received.	PD (5,0)
SDREJR	Number of reject frames received.	PD (5,0)
SDREJX	Number of reject frames transmitted.	PD (5,0)
SDSABX	Number of set asynchronous balanced mode extended frames transmitted.	PD (5,0)
SDSABR	Number of set asynchronous balanced mode extended frames received.	PD (5,0)
SDDISX	Number of disconnect frames transmitted.	PD (5,0)
SDDISR	Number of disconnect frames received.	PD (5,0)
SDDMFX	Number of disconnect mode frames transmitted.	PD (5,0)
SDDMFR	Number of disconnect mode frames received.	PD (5,0)
SDN2RE	N2 retries end count: This count is updated when the host has attempted to contact a station n times, and the T1 timer ended n times before the station responded.	PD (5,0)
SDT1TE	T1 timer end count: Number of times the T1 timer ended. This count is updated when the host has attempted to contact a station n times, and the T1 timer ended n times before the station responded.	PD (5,0)
SDTITE	Ti timer end count: Number of times the Ti timer (inactivity timer) ended.	PD (5,0)
SDLBCT	Local busy count: Number of times station entered local busy substate.	PD (5,0)
SDPRCL	Protocol type: C for DDI.	C (1)

Related reference

Collection Services data files: System category and file relationships

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: File abbreviations

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRDTA) command See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMSTNE

This database file includes Ethernet station file entries and lists the fields in the Ethernet station file.

Ethernet LAN station statistics are reported for active Ethernet line descriptions that are associated with Ethernet ports and with ATM ports that support Ethernet LAN emulation.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
IOPRN	IOP resource name.	C(10)
STIOPI	Reserved	C (1)
STTYPE	The resource type of the IOP or adapter represented by this record.	C (4)
STPCEP	The provider connection endpoint (PCEP) ID.	C (8)
STLND	Line description: The name of the description for this line.	C (10)
STSTNN	Station name: The name of the station on this line.	C (10)
STLSPD	Line speed: The line speed expressed in bits per second (bps). For some lines, this value might change as time progresses.	PD (11,0)
STTXMT	Total number of Type II frames transmitted.	PD (11,0)
STTRCV	Total number of Type II frames received.	PD (11,0)
STBXMT	Total number of bytes transmitted in all I-frames.	PD (11,0)
STBRCV	Total number of bytes received in all I-frames.	PD (11,0)
STIXMT	Total number of I-frames transmitted.	PD (11,0)
STIRCV	Total number of I-frames received.	PD (11,0)
STIREX	Number of I-frames retransmitted.	PD (11,0)
STBREX	Number of bytes retransmitted in I-frames.	PD (11,0)
STRNRX	Number of receive-not-ready frames transmitted.	PD (5,0)
STRNRR	Number of receive-not-ready frames received.	PD (5,0)

Field Name	Description	Attribute
STFRMX	Number of frame-reject frames transmitted.	PD (5,0)
STFRMR	Number of frame-reject frames received.	PD (5,0)
STREJR	Number of reject frames received.	PD (5,0)
STREJX	Number of reject frames transmitted.	PD (5,0)
STSABX	Number of set asynchronous balanced mode extended frames transmitted.	PD (5,0)
STSABR	Number of set asynchronous balanced mode extended frames received.	PD (5,0)
STDISX	Number of disconnect frames transmitted.	PD (5,0)
STDISR	Number of disconnect frames received.	PD (5,0)
STDMFX	Number of disconnect mode frames transmitted.	PD (5,0)
STDMFR	Number of disconnect mode frames received.	PD (5,0)
STN2RE	N2 retries end count: This count is updated when the host has attempted to contact a station n times and n times the T1 timer ended before the station responded.	PD (5,0)
STT1TE	T1 timer end count: Number of times the T1 timer ended. This count is updated when the host has attempted to contact a station n times and n times the T1 timer ended before the station responded.	PD (5,0)
STTITE	Ti timer end count: Number of times the Ti timer (inactivity timer) ended.	PD (5,0)
STLBCT	Local busy count: Number of times station entered local busy substate.	PD (5,0)
STPRCL	Protocol type: T for Ethernet network.	C (1)
STPORT	Port resource name.	C (10)

Related reference

[Collection Services data files: System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

[Data files: File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

[Create Performance Data \(CRTPFRDTA\) command](#) See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMSTNL

This database file includes token-ring station file entries and lists the fields in the token-ring local area network (LAN) station file.

Token-ring LAN station statistics are reported for active token-ring line descriptions that are associated with token-ring ports and with ATM ports that support token-ring LAN emulation.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
IOPRN	IOP resource name.	C(10)
SLIOPI	Reserved	C (1)
SLTYPE	The resource type of the IOP or adapter represented by this record.	C (4)
SLPCEP	The provider connection end point (PCEP) ID.	C (8)
SLLND	Line description: The name of the description for this line.	C (10)
SLSTNN	Station name: The name of the station on this line.	C (10)
SLLSPD	Line speed: The line speed expressed in bits per second (bps).	PD (11,0)
SLTXMT	Total number of Type II frames transmitted.	PD (11,0)
SLTRCV	Total number of Type II frames received.	PD (11,0)
SLBXMT	Total number of bytes transmitted in all I-frames.	PD (11,0)
SLBRCV	Total number of bytes received in all I-frames.	PD (11,0)
SLIXMT	Total number of I-frames transmitted.	PD (11,0)
SLIRCV	Total number of I-frames received.	PD (11,0)
SLIREX	Number of I-frames retransmitted.	PD (11,0)
SLBREX	Number of bytes retransmitted in I-frames.	PD (11,0)
SLRNRX	Number of receive-not-ready frames transmitted.	PD (5,0)
SLRNRR	Number of receive-not-ready frames received.	PD (5,0)
SLFRMX	Number of frame-reject frames transmitted.	PD (5,0)
SLFRMR	Number of frame-reject frames received.	PD (5,0)
SLREJR	Number of reject frames received.	PD (5,0)
SLREJX	Number of reject frames transmitted.	PD (5,0)
SLSABX	Number of set asynchronous balanced mode extended frames transmitted.	PD (5,0)
SLSABR	Number of set asynchronous balanced mode extended frames received.	PD (5,0)
SLDISX	Number of disconnect frames transmitted.	PD (5,0)
SLDISR	Number of disconnect frames received.	PD (5,0)
SLDMFX	Number of disconnect mode frames transmitted.	PD (5,0)

Field Name	Description	Attribute
SLDMFR	Number of disconnect mode frames received.	PD (5,0)
SLN2RE	N2 retries end count: This count is updated when the host has attempted to contact a station n times and n times the T1 timer ended before the station responded.	PD (5,0)
SLT1TE	T1 timer end count: Number of times the T1 timer ended. This count is updated when the host has attempted to contact a station n times and n times the T1 timer ended before the station responded.	PD (5,0)
SLTITE	Ti timer end count: Number of times the Ti timer (inactivity timer) ended.	PD (5,0)
SLLBCT	Local busy count: Number of times station entered local busy substate.	PD (5,0)
SLPRCL	Protocol type: E for token-ring network.	C (1)

Related reference

Collection Services data files: System category and file relationships

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: File abbreviations

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRDTA) command See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMSTNY

This database file includes frame relay station file entries and lists the fields in the frame relay station file.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
IOPRN	IOP resource name.	C(10)
SYIOPI	Reserved	C (1)
SYTYPE	The resource type of the IOP or adapter represented by this record.	C (4)
SYPCPEP	The provider connection end point (PCEP) ID.	C (8)
SYLND	Network interface (NWI) description: The name of the description for this network interface.	C (10)
SYSTNN	Station name: The name of the station on this line.	C (10)

Field Name	Description	Attribute
SYLSPD	Line speed: The line speed expressed in bits per second (bps).	PD (11,0)
SYTXMT	Total number of Type II frames transmitted.	PD (11,0)
SYTRCV	Total number of Type II frames received.	PD (11,0)
SYBXMT	Total number of bytes transmitted in all I-frames.	PD (11,0)
SYBRCV	Total number of bytes received in all I-frames.	PD (11,0)
SYIXMT	Total number of I-frames transmitted.	PD (11,0)
SYIRCV	Total number of I-frames received.	PD (11,0)
SYIREX	Number of I-frames retransmitted.	PD (11,0)
SYBREX	Number of bytes retransmitted in I-frames.	PD (11,0)
SYRNRX	Number of receive-not-ready frames transmitted.	PD (5,0)
SYRNR	Number of receive-not-ready frames received.	PD (5,0)
SYFRMX	Number of frame-reject frames transmitted.	PD (5,0)
SYFRMR	Number of frame-reject frames received.	PD (5,0)
SYREJR	Number of reject frames received.	PD (5,0)
SYREJX	Number of reject frames transmitted.	PD (5,0)
SYSABX	Number of set asynchronous balanced mode extended frames transmitted.	PD (5,0)
SYSABR	Number of set asynchronous balanced mode extended frames received.	PD (5,0)
SYDISX	Number of disconnect frames transmitted.	PD (5,0)
SYDISR	Number of disconnect frames received.	PD (5,0)
SYDMFX	Number of disconnect mode frames transmitted.	PD (5,0)
SYDMFR	Number of disconnect mode frames received.	PD (5,0)
SYN2RE	N2 retries end count: This count is updated when the host has attempted to contact a station n times and n times the T1 timer ended before the station responded.	PD (5,0)
SYT1TE	T1 timer end count: Number of times the T1 timer ended. This count is updated when the host has attempted to contact a station n times and n times the T1 timer ended before the station responded.	PD (5,0)
SYTITE	Ti timer end count: Number of times the Ti timer (inactivity timer) ended.	PD (5,0)
SYLBCT	Local busy count: Number of times station entered local busy substate.	PD (5,0)
SYPRCL	Protocol type: Y for frame relay.	C (1)

Related reference

Collection Services data files: [System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: File abbreviations

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRDTA) command See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMSYS and QAPMSYSL

The QAPMSYS file is created when the performance monitor database files are migrated with the Convert Performance Collection (CVTPFRCOL) command to a newer release.

Collection Services does not create this file. The QAPMSYSL file is provided for compatibility with the performance monitor and combines data from QAPMJSUM, QAPMSYSCPU, and QAPMSYSTEM files. This file is produced when all of these categories are requested from the Create Performance Data (CRTPFRDTA) command. This file contains system interval file entries.

The following terms are used in the field descriptions and are repeated for each group of jobs:

- Number of database read operations. Total number of physical read operations for database functions.
- Number of nondatabase read operations. Total number of physical read operations for nondatabase functions.
- Number of write operations. Total number of physical write operations.
- Number of print lines. Number of lines written by the program, which does not reflect what is actually printed. Spooled files can be ended or printed with multiple copies.
- Number of database writes/reads (logical). Number of times the database module was called, which does not include I/O operations to readers/writers or I/O operations caused by the Copy Spooled File (CPYSPLF) or Display Spooled File (DSPSPLF) command. If SEQONLY(*YES) is in effect, these numbers show each block of records read or written, not the number of individual records read or written.
- Number of communications writes/reads (logical). These do not include remote workstation activity. They include only activity related to intersystem communications function (ICF) files when the I/O is for a communications device.

Users should note that blocked I/O is considered one I/O operation.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
SYDPGF	Directory page faults: Number of times a page of the auxiliary storage directory was transferred to main storage for a look-up or an allocation operation.	PD (11,0)

Field Name	Description	Attribute
SYAPGF	Access group member page faults: Number of times a page of an object contained in an access group was transferred to main storage independently of the access group. This transfer occurs when the containing access group was purged, or because portions of the containing access group are displaced from main storage.	PD (11,0)
SYMPGF	Microcode page faults: Number of times a page of microcode was transferred to main storage.	PD (11,0)
SYMCTR	Microtask read operations: Number of transfers of one or more pages of data from auxiliary storage because of a microtask rather than a process.	PD (11,0)
SYMCTW	Microtask write operations: Number of transfers of one or more pages of data from main storage to auxiliary storage because of a microtask rather than a process.	PD (11,0)
SYSASP	System auxiliary storage pool space available: Number of bytes of space on auxiliary storage available for allocation in the system ASP that is not currently assigned to machine interface (MI) objects or internal machine functions.	PD (15,0)
SYPRMW	Permanent data transferred from main storage: Number of 512-byte blocks of permanent data transferred from main storage to the system ASP in auxiliary storage since the last sample.	PD (11,0)
SYXSRW	Reserved	PD (11,0)
SYEAOT	Reserved	PD (11,0)
SYEAOL	Reserved	PD (11,0)
SYBSYC	Reserved	PD (11,0)
SYSIZC	Size count: Total number of size exceptions.	PD (11,0)
SYDECD	Decimal data count: Total number of decimal data exceptions.	PD (11,0)

Field Name	Description	Attribute
SYSEZC	Seize count: Total number of seize waits.	PD (11,0)
SYSZWT	Seize/wait time in milliseconds.	PD (11,0)
SYSYNL	Synchronous lock conflict count.	PD (11,0)
SYASYL	Asynchronous lock conflict count.	PD (11,0)
SYVFYC	Verify count.	PD (11,0)
SYAUTH	Object authority checks. The number of times that authority was checked for objects. An authority check for one object can result in zero, one, or more than one user authority lookups that can be cached or noncached (see SYNUAL field description).	PD (11,0)
SYCHNB	Reserved	PD (11,0)
SYEXPN	Total number of exceptions.	PD (11,0)
SYLRT1	Transactions in first response time monitor bracket: Total number of local workstation transactions with response time less than the value of boundary 1 specified on the Advanced Local Response Time Options dialog from the Collection Services properties page within the IBM i interface.	PD (9,0)
SYLRT2	Transactions in second response time monitor bracket: Total number of local workstation transactions with response time less than the value of boundary 2 and greater than the value of boundary 1 specified on the Advanced Local Response Time Options dialog from the Collection Services properties page within the IBM i interface.	PD (9,0)
SYLRT3	Transactions in third response time monitor bracket: Total number of local workstation transactions with response time less than the value of boundary 3 and greater than the value of boundary 2 specified on the Advanced Local Response Time Options dialog from the Collection Services properties page within the IBM i interface.	PD (9,0)

Field Name	Description	Attribute
SYLRT4	Transactions in fourth response time monitor bracket: Total number of local workstation transactions with response time less than the value of boundary 4 and greater than the value of boundary 3 specified on the Advanced Local Response Time Options dialog from the Collection Services properties page within the IBM i interface.	PD (9,0)
SYLRT5	Transactions in fifth response time monitor bracket: Total number of local workstation transactions with response time greater than the value of boundary 4 specified on the Advanced Local Response Time Options dialog from the Collection Services properties page within the IBM i interface.	PD (9,0)
SDCPU	Total processing unit time used (in milliseconds) by target distributed data management (DDM) job.	PD (11,0)
SDRES1	Reserved.	PD (15,3)
SDRES2	Reserved.	PD (11,0)
SDPRTL	Total number of print lines of all target DDM jobs.	PD (11,0)
SDPRTP	Total number of print pages of all target DDM jobs.	PD (11,0)
SDSPD	Total count of suspended time of target DDM jobs.	PD (11,0)
SDRRT	Total count of time a target DDM job waited during rerouting.	PD (11,0)
SDNEW	Number of new target DDM job.	PD (11,0)
SDTERM	Number of ended target DDM jobs.	PD (11,0)
SDJBCT	Number of DDM jobs.	PD (11,0)
SDPDBR	Total number of physical synchronous database reads by target DDM jobs.	PD (11,0)
SDPNDB	Total number of physical synchronous nondatabase reads by target DDM jobs.	PD (11,0)

Field Name	Description	Attribute
SDPWRT	Total number of physical synchronous database and nondatabase writes by target DDM jobs.	PD (11,0)
SDLDBR	Total number of logical database reads by target DDM jobs.	PD (11,0)
SDLDBW	Total number of logical database writes by target DDM jobs.	PD (11,0)
SDLDBU	Total number of miscellaneous database operations by target DDM jobs.	PD (11,0)
SDCMPT	Total number of communications writes by target DDM jobs.	PD (11,0)
SDCMGT	Total number of communications reads by target DDM jobs.	PD (11,0)
SDBRG	Reserved	PD (11,0)
SDPRG	Reserved	PD (11,0)
SDNDW	Number of synchronous nondatabase writes: Total number of synchronous physical nondatabase write operations for nondatabase functions by target DDM jobs.	PD (11,0)
SDDBW	Number of synchronous database writes: Total number of synchronous physical database write operations for database functions by target DDM jobs.	PD (11,0)
SDANDW	Number of asynchronous nondatabase writes: Total number of asynchronous physical nondatabase write operations for nondatabase functions by target DDM jobs.	PD (11,0)
SDADBW	Number of asynchronous database writes: Total number of asynchronous physical database write operations for database functions by target DDM jobs.	PD (11,0)
SDANDR	Number of asynchronous nondatabase reads: Total number of asynchronous physical nondatabase read operations for nondatabase functions by target DDM jobs.	PD (11,0)

Field Name	Description	Attribute
SDADBR	Number of asynchronous database reads: Total number of asynchronous physical database read operations for database functions by target DDM jobs.	PD (11,0)
SDPW	Number of permanent writes by target DDM jobs.	PD (11,0)
SDCS	Reserved	PD (11,0)
SDPAGF	Number of PAG faults. Total number of times the program access group (PAG) was referred to by target DDM jobs, but was not in main storage. The Licensed Internal Code no longer uses process access groups for caching data. Because of this implementation, this field will always be 0 for more current releases.	PD (11,0)
SDEAO	Reserved	PD (11,0)
SDOBIN	Number of binary overflows by target DDM jobs.	PD (11,0)
SDODEC	Number of decimal overflows by target DDM jobs.	PD (11,0)
SDOFLP	Number of floating point overflows by target DDM jobs.	PD (11,0)
SDIPF	Number of times a target distributed data management (DDM) job had a page fault on an address that was currently part of an auxiliary storage I/O operation.	PD (11,0)
SDWIO	Number of times a target distributed data management (DDM) job explicitly waited for outstanding asynchronous I/O operations to complete.	PD (11,0)
SDSKSC	DDM number of socket sends.	PD (11,0)
SDSKBS	DDM number of socket bytes sent.	PD (11,0)
SDSKRC	DDM number of socket receives.	PD (11,0)
SDSKBR	DDM number of socket bytes received.	PD (11,0)
SDXRFR	DDM stream file reads.	PD (11,0)
SDXRFW	DDM stream file writes.	PD (11,0)

Field Name	Description	Attribute
SDXSLR	DDM file system symbolic link reads.	PD (11,0)
SDXDYR	DDM file system directory reads.	PD (11,0)
SDDLCH	DDM file system lookup cache hits.	PD (11,0)
SDDLCM	DDM file system lookup cache misses.	PD (11,0)
SDSZWT	DDM seize/wait time in milliseconds.	PD (11,0)
SWCPU	Total processing unit time (in milliseconds) used by IBM i Access applications.	PD (11,0)
SWRES1	Reserved.	PD (15,3)
SWRES2	Reserved.	PD (11,0)
SWPRTL	Total number of print lines of all IBM i Access application jobs.	PD (11,0)
SWP RTP	Total number of print pages of all IBM i Access application jobs.	PD (11,0)
SWSPD	Total time IBM i Access application jobs were suspended.	PD (11,0)
SWRRT	Total time a IBM i Access applications job waited during rerouting.	PD (11,0)
SWNEW	Number of started IBM i Access application jobs.	PD (11,0)
SWTERM	Number of ended IBM i Access application jobs.	PD (11,0)
SWJBCT	Number of IBM i Access jobs.	PD (11,0)
SWPD BR	Total number of physical synchronous database reads by IBM i Access application jobs.	PD (11,0)
SWPNDB	Total number of physical synchronous nondatabase reads by IBM i Access application jobs.	PD (11,0)
SWPWRT	Total number of physical synchronous database and nondatabase writes by IBM i Access application jobs.	PD (11,0)
SWLDBR	Total number of logical database reads by IBM i Access application jobs.	PD (11,0)
SWLDBW	Total number of logical database writes by IBM i Access application jobs.	PD (11,0)

Field Name	Description	Attribute
SWLDBU	Total number of miscellaneous database operations by IBM i Access application jobs.	PD (11,0)
SWCMPT	Total number of communications writes by IBM i Access application jobs.	PD (11,0)
SWCMGT	Total number of communications reads by IBM i Access application jobs.	PD (11,0)
SWBRG	Reserved	PD (11,0)
SWPRG	Reserved	PD (11,0)
SWNDW	Number of synchronous nondatabase writes: Total number of synchronous physical nondatabase write operations for nondatabase functions by IBM i Access applications.	PD (11,0)
SWDBW	Number of synchronous database writes: Total number of synchronous physical database write operations for database functions by IBM i Access applications.	PD (11,0)
SWANDW	Number of asynchronous nondatabase writes: Total number of asynchronous physical nondatabase write operations for nondatabase functions by IBM i Access applications.	PD (11,0)
SWADBW	Number of asynchronous database writes: Total number of asynchronous physical database write operations for database functions by IBM i Access applications.	PD (11,0)
SWANDR	Number of asynchronous nondatabase reads: Total number of asynchronous physical nondatabase read operations for nondatabase functions by IBM i Access applications.	PD (11,0)
SWADBR	Number of asynchronous database reads: Total number of asynchronous physical database read operations for database functions by IBM i Access applications.	PD (11,0)
SWPW	Number of permanent writes by IBM i Access applications.	PD (11,0)

Field Name	Description	Attribute
SWCS	Reserved	PD (11,0)
SWPAGF	Number of PAG faults. Total number of times the program access group (PAG) was referred to by IBM i Access applications, but was not in main storage. The Licensed Internal Code no longer uses process access groups for caching data. Because of this implementation, this field will always be 0 for more current releases.	PD (11,0)
SWEAO	Reserved	PD (11,0)
SWOBIN	Number of binary overflows by IBM i Access applications.	PD (11,0)
SWODEC	Number of decimal overflows by IBM i Access applications.	PD (11,0)
SWOFLP	Number of floating point overflows by IBM i Access applications.	PD (11,0)
SWIPF	Number of times a IBM i Access application job had a page fault on an address that was currently part of an auxiliary storage I/O operation.	PD (11,0)
SWWIO	Number of times a IBM i Access application job explicitly waited for outstanding asynchronous I/O operations to complete.	PD (11,0)
SWSKSC	IBM i Access number of socket sends.	PD (11,0)
SWSKBS	IBM i Access number of socket bytes sent.	PD (11,0)
SWSKRC	IBM i Access number of socket receives.	PD (11,0)
SWSKBR	IBM i Access number of socket bytes received.	PD (11,0)
SWXRFR	IBM i Access stream file reads.	PD (11,0)
SWXRFW	IBM i Access stream file writes.	PD (11,0)
SWXSLR	IBM i Access file system symbolic link reads.	PD (11,0)
SWXDYR	IBM i Access file system directory reads.	PD (11,0)
SWDLCH	IBM i Access file system lookup cache hits.	PD (11,0)

Field Name	Description	Attribute
SWDLCM	IBM i Access file system lookup cache misses.	PD (11,0)
SWSZWT	IBM i Access seize/wait time in milliseconds.	PD (11,0)
SPCPU	Total processing unit time (in milliseconds) used by pass-through target jobs.	PD (11,0)
SPRES1	Total transaction time by pass-through target jobs.	PD (15,3)
SPRES2	Total number of transactions by pass-through target jobs.	PD (11,0)
SPPRTL	Total number of print lines of all pass-through target jobs.	PD (11,0)
SPPRTP	Total number of print pages of all pass-through target jobs.	PD (11,0)
SPSPD	Total count of suspended time of pass-through target jobs.	PD (11,0)
SPRRT	Total count of time a pass-through target job waited during rerouting.	PD (11,0)
SPNEW	Number of started pass-through target jobs.	PD (11,0)
SPTERM	Number of ended pass-through target jobs.	PD (11,0)
SPJBCT	Number of pass-through jobs.	PD (11,0)
SPPDBR	Total number of physical synchronous database reads by pass-through target jobs.	PD (11,0)
SPPNDB	Total number of physical synchronous nondatabase reads by pass-through target jobs.	PD (11,0)
SPPWRT	Total number of physical synchronous database and nondatabase writes by pass-through target jobs.	PD (11,0)
SPLDBR	Total number of logical database reads by pass-through target jobs.	PD (11,0)
SPLDBW	Total number of logical database writes by pass-through target jobs.	PD (11,0)
SPLDBU	Total number of miscellaneous database operations by pass-through target jobs.	PD (11,0)

Field Name	Description	Attribute
SPCMPT	Total number of communications writes by pass-through target jobs.	PD (11,0)
SPCMGT	Total number of communications reads by pass-through target jobs.	PD (11,0)
SPBRG	Reserved	PD (11,0)
SPPRG	Reserved	PD (11,0)
SPNDW	Number of synchronous nondatabase writes: Total number of synchronous physical nondatabase write operations for nondatabase functions by pass-through target jobs.	PD (11,0)
SPDBW	Number of synchronous database writes: Total number of synchronous physical database write operations for database functions by pass-through target jobs.	PD (11,0)
SPANDW	Number of asynchronous nondatabase writes: Total number of asynchronous physical nondatabase write operations for nondatabase functions by pass-through target jobs.	PD (11,0)
SPADBW	Number of asynchronous database writes: Total number of asynchronous physical database write operations for database functions by pass-through target jobs.	PD (11,0)
SPANDR	Number of asynchronous nondatabase reads: Total number of asynchronous physical nondatabase read operations for nondatabase functions by pass-through target jobs.	PD (11,0)
SPADBR	Number of asynchronous database reads: Total number of asynchronous physical database read operations for database functions by pass-through target jobs.	PD (11,0)
SPPW	Number of permanent writes by pass-through target jobs.	PD (11,0)
SPCS	Reserved	PD (11,0)

Field Name	Description	Attribute
SPPAGF	Number of PAG faults: Total number of times the program access group (PAG) was referred to by pass-through target jobs, but was not in main storage. The Licensed Internal Code no longer uses process access groups for caching data. Because of this implementation, this field will always be 0 for more current releases.	PD (11,0)
SPEAO	Reserved	PD (11,0)
SPOBIN	Number of binary overflows by pass-through target jobs.	PD (11,0)
SPODEC	Number of decimal overflows by pass-through target jobs.	PD (11,0)
SPOFLP	Number of floating point overflows by pass-through target jobs.	PD (11,0)
SPIPF	Number of times a pass-through target job had a page fault on an address that was currently part of an auxiliary storage I/O operation.	PD (11,0)
SPWIO	Number of times a pass-through target job explicitly waited for outstanding asynchronous I/O operations to complete.	PD (11,0)
SPSKSC	Passthrough number of socket sends.	PD (11,0)
SPSKBS	Passthrough number of socket bytes sent.	PD (11,0)
SPSKRC	Passthrough number of socket receives.	PD (11,0)
SPSKBR	Passthrough number of socket bytes received.	PD (11,0)
SPXRFR	Passthrough stream file reads.	PD (11,0)
SPXRFW	Passthrough stream file writes.	PD (11,0)
SPXSLR	Passthrough file system symbolic link reads.	PD (11,0)
SPXDYR	Passthrough file system directory reads.	PD (11,0)
SPDLCH	Passthrough file system lookup cache hits.	PD (11,0)
SPDLCM	Passthrough file system lookup cache misses.	PD (11,0)

Field Name	Description	Attribute
SPSZWT	Passthrough seize/wait time in milliseconds.	PD (11,0)
SMCPU	Total processing unit time (in milliseconds) used by multiple requester terminal (MRT) jobs (System/36 environment only).	PD (11,0)
SMRES1	Reserved.	PD (15,3)
SMRES2	Reserved.	PD (11,0)
SMPRTL	Total number of print lines of all MRT jobs (System/36 environment only).	PD (11,0)
SMPRTP	Total number of print pages of all MRT jobs (System/36 environment only).	PD (11,0)
SMSPD	Total time MRT jobs (System/36 environment only) were suspended.	PD (11,0)
SMRRT	Total time a MRT job (System/36 environment only) waited during rerouting.	PD (11,0)
SMNEW	Number of started MRT jobs (System/36 environment only).	PD (11,0)
SMTERM	Number of ended MRT jobs (System/36 environment only).	PD (11,0)
SMJBCT	Number of MRT jobs (System/36 environment only).	PD (11,0)
SMPDBR	Total number of physical synchronous database reads by MRT jobs (System/36 environment only).	PD (11,0)
SMPNDB	Total number of physical synchronous nondatabase reads by MRT jobs (System/36 environment only).	PD (11,0)
SMPWRT	Total number of physical synchronous database and nondatabase writes by MRT jobs (System/36 environment only).	PD (11,0)
SMLDBR	Total number of logical database reads by MRT jobs (System/36 environment only).	PD (11,0)
SMLDBW	Total number of logical database writes by MRT jobs (System/36 environment only).	PD (11,0)

Field Name	Description	Attribute
SMLDBU	Total number of miscellaneous database operations by MRT jobs (System/36 environment only).	PD (11,0)
SMCMPT	Total number of communications writes by MRT jobs (System/36 environment only).	PD (11,0)
SMCMGT	Total number of communications reads by MRT jobs (System/36 environment only).	PD (11,0)
SMBRG	Reserved	PD (11,0)
SMPRG	Reserved	PD (11,0)
SMNDW	Number of synchronous nondatabase writes: Total number of synchronous physical nondatabase write operations for nondatabase functions by MRT jobs (System/36 environment only).	PD (11,0)
SMDBW	Number of synchronous database writes: Total number of synchronous physical database write operations for database functions by MRT jobs (System/36 environment only).	PD (11,0)
SMANDW	Number of asynchronous nondatabase writes: Total number of asynchronous physical nondatabase write operations for nondatabase functions by MRT jobs (System/36 environment only).	PD (11,0)
SMADBW	Number of asynchronous database writes: Total number of asynchronous physical database write operations for database functions by MRT jobs (System/36 environment only).	PD (11,0)
SMANDR	Number of asynchronous nondatabase reads: Total number of asynchronous physical nondatabase read operations for nondatabase functions by MRT jobs (System/36 environment only).	PD (11,0)
SMADBR	Number of asynchronous database reads: Total number of asynchronous physical database read operations for database functions by MRT jobs (System/36 environment only).	PD (11,0)

Field Name	Description	Attribute
SMPW	Number of permanent writes by MRT jobs (System/36 environment only).	PD (11,0)
SMCS	Reserved	PD (11,0)
SMPAGF	Number of PAG faults: Total number of times the program access group (PAG) was referred to by MRT jobs (System/36 environment only), but was not in main storage. The Licensed Internal Code no longer uses process access groups for caching data. Because of this implementation, this field will always be 0 for more current releases.	PD (11,0)
SMEAO	Reserved	PD (11,0)
SMOBIN	Number of binary overflows by MRT jobs (System/36 environment only).	PD (11,0)
SMODEC	Number of decimal overflows by MRT jobs (System/36 environment only).	PD (11,0)
SMOFLP	Number of floating point overflows by MRT jobs (System/36 environment only).	PD (11,0)
SMIPF	Number of times a MRT job (System/36 environment only) had a page fault on an address that was currently part of an auxiliary storage I/O operation.	PD (11,0)
SMWIO	Number of times a MRT job (System/36 environment only) explicitly waited for outstanding asynchronous I/O operations to complete.	PD (11,0)
SMSKSC	MRTS Number of socket sends.	PD (11,0)
SMSKBS	MRTS Number of socket bytes sent.	PD (11,0)
SMSKRC	MRTS Number of socket receives.	PD (11,0)
SMSKBR	MRTS Number of socket bytes received.	PD (11,0)
SMXRFR	MRTS stream file reads.	PD (11,0)
SMXRFW	MRTS stream file writes.	PD (11,0)
SMXSLR	MRTS file system symbolic link reads.	PD (11,0)

Field Name	Description	Attribute
SMXDYR	MRTS file system directory reads.	PD (11,0)
SMDLCH	MRTS file system lookup cache hits.	PD (11,0)
SMDLCM	MRTS file system lookup cache misses.	PD (11,0)
SMSZWT	MRTS seize/wait time in milliseconds.	PD (11,0)
S6CPU	Total processing unit time (in milliseconds) used by System/36 environment jobs.	PD (11,0)
S6TRNT	Total response time.	PD (15,3)
S6TRNS	Number of transactions.	PD (11,0)
S6PRTL	Total number of print lines of all System/36 environment jobs.	PD (11,0)
S6PRTP	Total number of print pages of all System/36 environment jobs.	PD (11,0)
S6SPD	Total time System/36 environment jobs were suspended.	PD (11,0)
S6RRT	Total time a System/36 environment job waited during rerouting.	PD (11,0)
S6NEW	Number of started System/36 environment jobs.	PD (11,0)
S6TERM	Number of ended System/36 environment jobs.	PD (11,0)
S6JBCT	Number of System/36 environment jobs.	PD (11,0)
S6PDBR	Total number of physical synchronous database reads by System/36 environment jobs.	PD (11,0)
S6PNDB	Total number of physical synchronous nondatabase reads by System/36 environment jobs.	PD (11,0)
S6PWRT	Total number of physical synchronous database and nondatabase writes by System/36 environment jobs.	PD (11,0)
S6LDBR	Total number of logical database reads by System/36 environment jobs.	PD (11,0)
S6LDBW	Total number of logical database writes by System/36 environment jobs.	PD (11,0)

Field Name	Description	Attribute
S6LDBU	Total number of miscellaneous database operations by System/36 environment jobs.	PD (11,0)
S6CMPT	Total number of communications writes by System/36 environment jobs.	PD (11,0)
S6CMGT	Total number of communications reads by System/36 environment jobs.	PD (11,0)
S6BRG	Reserved	PD (11,0)
S6PRG	Reserved	PD (11,0)
S6NDW	Number of synchronous nondatabase writes: Total number of synchronous physical nondatabase write operations for nondatabase functions by System/36 environment jobs.	PD (11,0)
S6DBW	Number of synchronous database writes: Total number of synchronous physical database write operations for database functions by System/36 environment jobs.	PD (11,0)
S6ANDW	Number of asynchronous nondatabase writes: Total number of asynchronous physical nondatabase write operations for nondatabase functions by System/36 environment jobs.	PD (11,0)
S6ADBW	Number of asynchronous database writes: Total number of asynchronous physical database write operations for database functions by System/36 environment jobs.	PD (11,0)
S6ANDR	Number of asynchronous nondatabase reads: Total number of asynchronous physical nondatabase read operations for nondatabase functions by System/36 environment jobs.	PD (11,0)
S6ADBR	Number of asynchronous database reads: Total number of asynchronous physical database read operations for database functions by System/36 environment jobs.	PD (11,0)
S6PW	Number of permanent writes by System/36 environment jobs.	PD (11,0)

Field Name	Description	Attribute
S6CS	Reserved	PD (11,0)
S6PAGF	Number of PAG faults: Total number of times the program access group (PAG) was referred to by System/36 environment jobs, but was not in main storage. The Licensed Internal Code no longer uses process access groups for caching data. Because of this implementation, this field will always be 0 for more current releases.	PD (11,0)
S6EAO	Reserved	PD (11,0)
S6OBIN	Number of binary overflows by System/36 environment jobs.	PD (11,0)
S6ODEC	Number of decimal overflows by System/36 environment jobs.	PD (11,0)
S6OFLP	Number of floating point overflows by System/36 environment jobs.	PD (11,0)
S6IPF	Number of times a System/36 environment job had a page fault on an address that was currently part of an auxiliary storage I/O operation.	PD (11,0)
S6WIO	Number of times a System/36 environment job explicitly waited for outstanding asynchronous I/O operations to complete.	PD (11,0)
S6SKSC	S36E number of socket sends.	PD (11,0)
S6SKBS	S36E number of socket bytes sent.	PD (11,0)
S6SKRC	S36E number of socket receives.	PD (11,0)
S6SKBR	S36E number of socket bytes received.	PD (11,0)
S6XRFR	S36E file system directory reads.	PD (11,0)
S6XRFW	S36E file system directory writes.	PD (11,0)
S6XSLR	S36E file system symbolic link reads.	PD (11,0)
S6XDYR	S36E directory stream file reads.	PD (11,0)
S6DLCH	S36E file system lookup cache hits.	PD (11,0)
S6DLCM	S36E file system lookup cache misses.	PD (11,0)

Field Name	Description	Attribute
S6SZWT	S36E seize/wait time in milliseconds.	PD (11,0)
SECPU	Total processing unit time (in milliseconds) used by communications batch jobs.	PD (11,0)
SERES1	Reserved.	PD (15,3)
SERES2	Reserved.	PD (11,0)
SEPRTL	Total number of print lines of all communications batch jobs.	PD (11,0)
SEP RTP	Total number of print pages of all communications batch jobs.	PD (11,0)
SESPD	Total time communications batch jobs were suspended.	PD (11,0)
SERRT	Total time a communications batch job waited during rerouting.	PD (11,0)
SENEW	Number of started communications batch jobs.	PD (11,0)
SETERM	Number of ended communications batch jobs.	PD (11,0)
SEJBCT	Number of communications batch jobs.	PD (11,0)
SEPDBR	Total number of physical synchronous database reads by communications batch jobs.	PD (11,0)
SEP NDB	Total number of physical synchronous nondatabase reads by communications batch jobs.	PD (11,0)
SEP WRT	Total number of physical synchronous database and nondatabase writes by communications batch jobs.	PD (11,0)
SELDBR	Total number of logical database reads by communications batch jobs.	PD (11,0)
SELDBW	Total number of logical database writes by communications batch jobs.	PD (11,0)
SELDBU	Total number of miscellaneous database operations by communications batch jobs.	PD (11,0)
SECMPT	Total number of communications writes by communications batch jobs.	PD (11,0)

Field Name	Description	Attribute
SECMGT	Total number of communications reads by communications batch jobs.	PD (11,0)
SEBRG	Reserved	PD (11,0)
SEPRG	Reserved	PD (11,0)
SENDW	Number of synchronous nondatabase writes: Total number of synchronous physical nondatabase write operations for nondatabase functions by communications batch jobs.	PD (11,0)
SEDBW	Number of synchronous database writes: Total number of synchronous physical database write operations for database functions by communications batch jobs.	PD (11,0)
SEANDW	Number of asynchronous nondatabase writes: Total number of asynchronous physical nondatabase write operations for nondatabase functions by communications batch jobs.	PD (11,0)
SEADBW	Number of asynchronous database writes: Total number of asynchronous physical database write operations for database functions by communications batch jobs.	PD (11,0)
SEANDR	Number of asynchronous nondatabase reads: Total number of asynchronous physical nondatabase read operations for nondatabase functions by communications batch jobs.	PD (11,0)
SEADBR	Number of asynchronous database reads: Total number of asynchronous physical database read operations for database functions by communications batch jobs.	PD (11,0)
SEPW	Number of permanent writes by communications batch jobs.	PD (11,0)
SECS	Reserved	PD (11,0)

Field Name	Description	Attribute
SEPAGF	Number of PAG faults: Total number of times the program access group (PAG) was referred to by communications batch jobs, but was not in main storage. The Licensed Internal Code no longer uses process access groups for caching data. Because of this implementation, this field will always be 0 for more current releases.	PD (11,0)
SEEO	Reserved	PD (11,0)
SEOBIN	Number of binary overflows by communications batch jobs.	PD (11,0)
SEODEC	Number of decimal overflows by communications batch jobs.	PD (11,0)
SEOFPL	Number of floating point overflows by communications batch jobs.	PD (11,0)
SEIPF	Number of times a communications batch job had a page fault on an address that was currently part of an auxiliary storage I/O operation.	PD (11,0)
SEWIO	Number of times a communications batch job explicitly waited for outstanding asynchronous I/O operations to complete.	PD (11,0)
SESKSC	Evoke number of socket sends.	PD (11,0)
SESKBS	Evoke number of socket bytes sent.	PD (11,0)
SESKRC	Evoke number of socket receives.	PD (11,0)
SESKBR	Evoke number of socket bytes received.	PD (11,0)
SEXFR	Evoke file system directory reads.	PD (11,0)
SEXRFW	Evoke file system stream file writes.	PD (11,0)
SEXSLR	Evoke file system symbolic link reads.	PD (11,0)
SEXDYR	Evoke stream file reads.	PD (11,0)
SEDLCH	Evoke file system lookup cache hits.	PD (11,0)
SEDLCM	Evoke file system lookup cache misses.	PD (11,0)

Field Name	Description	Attribute
SESZWT	Evoke seize/wait time in milliseconds.	PD (11,0)
SACPU	Total processing unit time (in milliseconds) used by autostart jobs.	PD (11,0)
SARES1	Reserved.	PD (15,3)
SARES2	Reserved.	PD (11,0)
SAPRTL	Total number of print lines of all autostart jobs.	PD (11,0)
SAPRTP	Total number of print pages of all autostart jobs.	PD (11,0)
SASPD	Total time autostart jobs were suspended.	PD (11,0)
SARRT	Total time an autostart job waited during rerouting.	PD (11,0)
SANEW	Number of started autostart jobs.	PD (11,0)
SATERM	Number of ended autostart jobs.	PD (11,0)
SAJBCT	Number of autostart jobs.	PD (11,0)
SAPDBR	Total number of physical synchronous database reads by autostart jobs.	PD (11,0)
SAPNDB	Total number of physical synchronous nondatabase reads by autostart jobs.	PD (11,0)
SAPWRT	Total number of physical synchronous database and nondatabase writes by autostart jobs.	PD (11,0)
SALDBR	Total number of logical database reads by autostart jobs.	PD (11,0)
SALDBW	Total number of logical database writes by autostart jobs.	PD (11,0)
SALDBU	Total number of miscellaneous database operations by autostart jobs.	PD (11,0)
SACMPT	Total number of communications writes by autostart jobs.	PD (11,0)
SACMGT	Total number of communications reads by autostart jobs.	PD (11,0)
SABRG	Reserved	PD (11,0)
SAPRG	Reserved	PD (11,0)

Field Name	Description	Attribute
SANDW	Number of synchronous nondatabase writes: Total number of synchronous physical nondatabase write operations for nondatabase functions by communications batch jobs.	PD (11,0)
SADBW	Number of synchronous database writes: Total number of synchronous physical database write operations for database functions by autostart jobs.	PD (11,0)
SAANDW	Number of asynchronous nondatabase writes: Total number of asynchronous physical nondatabase write operations for nondatabase functions by autostart jobs.	PD (11,0)
SAADBW	Number of asynchronous database writes: Total number of asynchronous physical database write operations for database functions by autostart jobs.	PD (11,0)
SAANDR	Number of asynchronous nondatabase reads: Total number of asynchronous physical nondatabase read operations for nondatabase functions by autostart jobs.	PD (11,0)
SAADBR	Number of asynchronous database reads: Total number of asynchronous physical database read operations for database functions by autostart jobs.	PD (11,0)
SAPW	Number of permanent writes by autostart jobs.	PD (11,0)
SACS	Reserved	PD (11,0)
SAPAGF	Number of PAG faults: Total number of times the program access group (PAG) was referred to by autostart jobs, but was not in main storage. The Licensed Internal Code no longer uses process access groups for caching data. Because of this implementation, this field will always be 0 for more current releases.	PD (11,0)
SAEAO	Reserved	PD (11,0)
SAOBIN	Number of binary overflows by autostart jobs.	PD (11,0)

Field Name	Description	Attribute
SAODEC	Number of decimal overflows by autostart jobs.	PD (11,0)
SAOFLP	Number of floating point overflows by autostart jobs.	PD (11,0)
SAIPF	Number of times an autostart job had a page fault on an address that was currently part of an auxiliary storage I/O operation.	PD (11,0)
SAWIO	Number of times an autostart job explicitly waited for outstanding asynchronous I/O operations to complete.	PD (11,0)
SASKSC	Autostart number of socket sends.	PD (11,0)
SASKBS	Autostart number of socket bytes sent.	PD (11,0)
SASKRC	Autostart number of socket receives.	PD (11,0)
SASKBR	Autostart number of socket bytes received.	PD (11,0)
SAXRFR	Autostart stream file reads.	PD (11,0)
SAXRFW	Autostart stream file writes.	PD (11,0)
SAXSLR	Autostart file system symbolic link reads.	PD (11,0)
SAXDYR	Autostart file system directory reads.	PD (11,0)
SADLCH	Autostart file system lookup cache hits.	PD (11,0)
SADLCM	Autostart file system lookup cache misses.	PD (11,0)
SASZWT	Autostart seize/wait time in milliseconds.	PD (11,0)
SBCPU	Total processing unit time (in milliseconds) used by batch jobs.	PD (11,0)
SBRES1	Reserved.	PD (15,3)
SBRES2	Reserved.	PD (11,0)
SBPRTL	Total number of print lines of all batch jobs.	PD (11,0)
SBPRTP	Total number of print pages of all batch jobs.	PD (11,0)
SBSPD	Total time batch jobs were suspended.	PD (11,0)

Field Name	Description	Attribute
SBRRT	Total time a batch job waited during rerouting.	PD (11,0)
SBNEW	Number of started batch jobs.	PD (11,0)
SBTERM	Number of ended batch jobs.	PD (11,0)
SBJBCT	Number of batch jobs.	PD (11,0)
SBPDBR	Total number of physical synchronous database reads by batch jobs.	PD (11,0)
SBPNDB	Total number of physical synchronous nondatabase reads by batch jobs.	PD (11,0)
SBPWRT	Total number of physical synchronous database and nondatabase writes by batch jobs.	PD (11,0)
SBLDBR	Total number of logical database reads by batch jobs.	PD (11,0)
SBLDBW	Total number of logical database writes by batch jobs.	PD (11,0)
SBLDBU	Total number of miscellaneous database operations by batch jobs.	PD (11,0)
SBCMPT	Total number of communications writes by batch jobs.	PD (11,0)
SBCMGT	Total number of communications reads by batch jobs.	PD (11,0)
SBBRG	Reserved	PD (11,0)
SBPRG	Reserved	PD (11,0)
SBNDW	Number of synchronous nondatabase writes: Total number of synchronous physical nondatabase write operations for nondatabase functions by batch jobs.	PD (11,0)
SBDBW	Number of synchronous database writes: Total number of synchronous physical database write operations for database functions by batch jobs.	PD (11,0)
SBANDW	Number of asynchronous nondatabase writes: Total number of asynchronous physical nondatabase write operations for nondatabase functions by batch jobs.	PD (11,0)

Field Name	Description	Attribute
SBADBW	Number of asynchronous database writes: Total number of asynchronous physical database write operations for database functions by batch jobs.	PD (11,0)
SBANDR	Number of asynchronous nondatabase reads: Total number of asynchronous physical nondatabase read operations for database functions by batch jobs.	PD (11,0)
SBADBR	Number of asynchronous database reads: Total number of asynchronous physical database read operations for database functions by batch jobs.	PD (11,0)
SBPW	Number of permanent writes by batch jobs.	PD (11,0)
SBCS	Reserved	PD (11,0)
SBPAGF	Number of PAG faults: Total number of times the program access group (PAG) was referred to by batch jobs, but was not in main storage. The Licensed Internal Code no longer uses process access groups for caching data. Because of this implementation, this field will always be 0 for more current releases.	PD (11,0)
SBEAO	Reserved	PD (11,0)
SBOBIN	Number of binary overflows by batch jobs.	PD (11,0)
SBODEC	Number of decimal overflows by batch jobs.	PD (11,0)
SBOFLP	Number of floating point overflows by batch jobs.	PD (11,0)
SBIPF	Number of times a batch job had a page fault on an address that was currently part of an auxiliary storage I/O operation.	PD (11,0)
SBWIO	Number of times a batch job explicitly waited for outstanding asynchronous I/O operations to complete.	PD (11,0)
SBSKSC	Batch number of socket sends.	PD (11,0)
SBSKBS	Batch number of socket bytes received.	PD (11,0)

Field Name	Description	Attribute
SBSKRC	Batch number of socket receives.	PD (11,0)
SBSKBR	Batch number of socket bytes received.	PD (11,0)
SBXRFR	Batch stream file reads.	PD (11,0)
SBXRFW	Batch stream file writes.	PD (11,0)
SBXSLR	Batch file system symbolic link reads.	PD (11,0)
SBXDYR	Batch file system directory reads.	PD (11,0)
SBDLCH	Batch file system lookup cache hits.	PD (11,0)
SBDLCM	Batch file system lookup cache misses.	PD (11,0)
SBSZWT	Batch seize/wait time in milliseconds.	PD (11,0)
SICPU	Total processing unit time (in milliseconds) used by interactive jobs.	PD (11,0)
SITRNT	Total transaction time by interactive jobs.	PD (15,3)
SITRNS	Total number of transactions by interactive jobs.	PD (11,0)
SIPRTL	Total number of print lines of all interactive jobs.	PD (11,0)
SIPRTP	Total number of print pages of all interactive jobs.	PD (11,0)
SISPD	Total time interactive jobs were suspended.	PD (11,0)
SIRRT	Total time an interactive job waited during rerouting.	PD (11,0)
SINEW	Number of started interactive jobs.	PD (11,0)
SITERM	Number of ended interactive jobs.	PD (11,0)
SIJBCT	Number of interactive jobs.	PD (11,0)
SIPDBR	Total number of physical synchronous database reads by interactive jobs.	PD (11,0)
SIPNDB	Total number of physical synchronous nondatabase reads by interactive jobs.	PD (11,0)

Field Name	Description	Attribute
SIPWRT	Total number of physical synchronous database and nondatabase writes by interactive jobs.	PD (11,0)
SILDBR	Total number of logical database reads by interactive jobs.	PD (11,0)
SILDBW	Total number of logical database writes by interactive jobs.	PD (11,0)
SILDBU	Total number of miscellaneous database operations by interactive jobs.	PD (11,0)
SICMPT	Total number of communications writes by interactive jobs.	PD (11,0)
SICMGT	Total number of communications reads by interactive jobs.	PD (11,0)
SIBRG	Reserved	PD (11,0)
SIPRG	Reserved	PD (11,0)
SINDW	Number of synchronous nondatabase writes: Total number of synchronous physical nondatabase write operations for nondatabase functions by interactive jobs.	PD (11,0)
SIDBW	Number of synchronous database writes: Total number of synchronous physical database write operations for database functions by interactive jobs.	PD (11,0)
SIANDW	Number of asynchronous nondatabase writes: Total number of asynchronous physical nondatabase write operations for nondatabase functions by interactive jobs.	PD (11,0)
SIADBW	Number of asynchronous database writes: Total number of asynchronous physical database write operations for database functions by interactive jobs.	PD (11,0)
SIANDR	Number of asynchronous nondatabase reads: Total number of asynchronous physical nondatabase read operations for nondatabase functions by interactive jobs.	PD (11,0)

Field Name	Description	Attribute
SIADBR	Number of asynchronous database reads: Total number of asynchronous physical database read operations for database functions by interactive jobs.	PD (11,0)
SIPW	Number of permanent writes by interactive jobs.	PD (11,0)
SICS	Reserved	PD (11,0)
SIPAGF	Number of PAG faults: Total number of times the program access group (PAG) was referred to by interactive jobs but was not in main storage. The Licensed Internal Code no longer uses process access groups for caching data. Because of this implementation, this field will always be 0 for more current releases.	PD (11,0)
SIEAO	Reserved	PD (11,0)
SIOBIN	Number of binary overflows by interactive jobs.	PD (11,0)
SIODEC	Number of decimal overflows interactive jobs.	PD (11,0)
SIOFLP	Number of floating point overflows by interactive jobs.	PD (11,0)
SIIPF	Number of times an interactive job had a page fault on an address that was currently part of an auxiliary storage I/O operation.	PD (11,0)
SIWIO	Number of times an interactive job explicitly waited for outstanding asynchronous I/O operations to complete.	PD (11,0)
SISKSC	Interactive number of socket sends.	PD (11,0)
SISKBS	Interactive number of socket bytes sent.	PD (11,0)
SISKRC	Interactive number of socket receives.	PD (11,0)
SISKBR	Interactive number of socket bytes received.	PD (11,0)
SIXRFR	Interactive stream file reads.	PD (11,0)
SIXRFW	Interactive stream file writes.	PD (11,0)

Field Name	Description	Attribute
SIXSLR	Interactive file system symbolic link reads.	PD (11,0)
SIXDYR	Interactive file system directory reads.	PD (11,0)
SIDLCH	Interactive file lookup cache hits.	PD (11,0)
SIDLCM	Interactive file lookup cache misses.	PD (11,0)
SISZWT	Interactive seize/wait time in milliseconds.	PD (11,0)
SXCPU	Total processing unit time (in milliseconds) used by the start CPF (SCPF) job, spool reader jobs, or spool writer jobs.	PD (11,0)
SXRES1	Reserved.	PD (15,3)
SXRES2	Reserved.	PD (11,0)
SXPRTL	Total number of print lines of the SCPF job, spool reader jobs, or spool writer jobs.	PD (11,0)
SXP RTP	Total number of print pages of the SCPF job, spool reader jobs, or spool writer jobs.	PD (11,0)
SXSPD	Total time the SCPF job, spool reader jobs, or spool writer jobs were suspended.	PD (11,0)
SXRR T	Total time the SCPF job, spool reader jobs, or spool writer jobs waited during rerouting.	PD (11,0)
SXNEW	Number of started SCPF job, spool reader jobs, or spool writer jobs.	PD (11,0)
SXTERM	Number of ended SCPF job, spool reader jobs, or spool writer jobs.	PD (11,0)
SXJBCT	Number of SCPF job, spool reader jobs, or spool writer jobs.	PD (11,0)
SXPDBR	Total number of physical synchronous database reads by the SCPF job, spool reader jobs, or spool writer jobs.	PD (11,0)
SXP NDB	Total number of physical synchronous nondatabase reads by the SCPF job, spool reader jobs, or spool writer jobs.	PD (11,0)

Field Name	Description	Attribute
SXPWRT	Total number of physical synchronous database and nondatabase writes by the SCPF job, spool reader jobs, or spool writer jobs.	PD (11,0)
SXLDBR	Total number of logical database reads by the SCPF job, spool reader jobs, or spool writer jobs.	PD (11,0)
SXLDBW	Total number of logical database writes by the SCPF job, spool reader jobs, or spool writer jobs.	PD (11,0)
SXLDBU	Total number of miscellaneous database operations by the SCPF job, spool reader jobs, or spool writer jobs.	PD (11,0)
SXCMPT	Total number of communications writes by the SCPF job, spool reader jobs, or spool writer jobs.	PD (11,0)
SXCMGT	Total number of communications reads by the SCPF job, spool reader jobs, or spool writer jobs.	PD (11,0)
SXBRG	Reserved	PD (11,0)
SXPRG	Reserved	PD (11,0)
SXNDW	Number of synchronous nondatabase writes: Total number of synchronous physical nondatabase write operations for nondatabase functions by the SCPF job, spool reader jobs, or spool writer jobs.	PD (11,0)
SXDBW	Number of synchronous database writes: Total number of synchronous physical database write operations for database functions by the SCPF job, spool reader jobs, or spool writer jobs.	PD (11,0)
SXANDW	Number of asynchronous nondatabase writes: Total number of asynchronous physical nondatabase write operations for database functions by the SCPF job, spool reader jobs, or spool writer jobs.	PD (11,0)
SXADBW	Number of asynchronous database writes: Total number of asynchronous physical database write operations for database functions by the SCPF job, spool reader jobs, or spool writer jobs.	PD (11,0)

Field Name	Description	Attribute
SXANDR	Number of asynchronous nondatabase reads: Total number of asynchronous physical nondatabase read operations for nondatabase functions by the SCPF job, spool reader jobs, or spool writer jobs.	PD (11,0)
SXADBR	Number of asynchronous database reads: Total number of asynchronous physical database read operations for database functions by the SCPF job, spool reader jobs, or spool writer jobs.	PD (11,0)
SXPW	Number of permanent writes by the SCPF job, spool reader jobs, or spool writer jobs.	PD (11,0)
SXCS	Reserved	PD (11,0)
SXPAGF	Number of PAG faults: Total number of times the program access group (PAG) was referred to by the SCPF job, spool reader jobs, or spool writer jobs, but was not in main storage. The Licensed Internal Code no longer uses process access groups for caching data. Because of this implementation, this field will always be 0 for more current releases.	PD (11,0)
SXEAO	Reserved	PD (11,0)
SXOBIN	Number of binary overflows by the SCPF job, spool reader jobs, or spool writer jobs.	PD (11,0)
SXODEC	Number of decimal overflows by the SCPF job, spool reader jobs, or spool writer jobs.	PD (11,0)
SXOFLP	Number of floating point overflows by the SCPF job, spool reader jobs, or spool writer jobs.	PD (11,0)
SXIPF	Number of times the SCPF job or spool reader or spool writer job had a page fault on an address that was currently part of an auxiliary storage I/O operation.	PD (11,0)
SXWIO	Number of times the SCPF job or spool reader or spool writer job explicitly waited for outstanding asynchronous I/O operations to complete.	PD (11,0)

Field Name	Description	Attribute
SXSKSC	Spool number of socket sends.	PD (11,0)
SXSKBS	Spool number of socket bytes sent.	PD (11,0)
SXSKRC	Spool number of socket receives.	PD (11,0)
SXSKBR	Spool number of socket bytes received.	PD (11,0)
SXXRFR	Spool stream file reads.	PD (11,0)
SXXRFW	Spool stream file writes.	PD (11,0)
SXXSLR	Spool file system symbolic link reads.	PD (11,0)
SXXDYR	Spool file system directory reads.	PD (11,0)
SXXDLCH	Spool file system lookup cache hits.	PD (11,0)
SXXDLCM	Spool file system lookup cache misses.	PD (11,0)
SXSZWT	Spool seize/wait time in milliseconds.	PD (11,0)
SHCPU	Total processing unit time (in milliseconds) used by microcode/system jobs.	PD (11,0)
SMPLP	Machine pool paging: Number of pages transferred in and out of machine pool.	PD (11,0)
SMUPL	Highest user pool paging: Highest number of pages transferred in and out of any user pool.	PD (11,0)
SUPLI	Pool with highest paging: Pool number with highest number of pages transferred in and out.	C (2)
SMXDU	Maximum disk utilization. The largest utilization of all single path disk units and all paths of multipath disk units.	PD (11,0)
SMXDUI	Actuator with maximum utilization.	C (4)
SMMMT	Time (in seconds) spent at MRTMAX by all MRT requests.	PD (11,0)
SMME	Number of requesters that routed to a MRT.	PD (11,0)
SYFOPN	Number of full opens system wide.	PD (11,0)
SYIXRB	Number of index rebuilds system wide.	PD (11,0)

Field Name	Description	Attribute
SYJOXR	Start journal operations initiated by user.	PD (11,0)
SYJOXP	Stop journal operations initiated by user.	PD (11,0)
SYJOIR	Start journal operations initiated by system.	PD (11,0)
SYJOIP	Stop journal operations initiated by system.	PD (11,0)
SYJOXD	Journal deposits resulting from user-journaled objects.	PD (11,0)
SYJOID	Journal deposits resulting from system-journaled objects.	PD (11,0)
SYJOJP	Journal deposits resulting from system-journaled objects to user-created journals.	PD (11,0)
SYJOBJ	Bundle writes to user-created journals.	PD (11,0)
SYJOB D	Bundle writes to internal system journals.	PD (11,0)
SYJOJY	Exposed access paths currently being journaled by the system.	PD (11,0)
SYJOJN	Exposed access paths currently not being journaled.	PD (11,0)
SYJOSE	System-estimated access path recovery time exposure in milliseconds.	PD (11,0)
SYJORT	System-managed access path tuning adjustments.	PD (11,0)
SYJOND	System-estimated access path recovery time exposure in milliseconds if no access paths were being journaled by the system.	PD (11,0)
SYSCPU	Total processing time (in milliseconds) used by the first (or only) processing unit.	PD (9,0)
SYCPU2....4	Total processing time (in milliseconds) used by the second....fourth processing unit. This value is zero if there is no processing unit with this number on the system.	PD (9,0)

Field Name	Description	Attribute
SYCP5....32	Total processing time (in milliseconds) used by the fifth....thirty-second processing unit. This value is zero if there is no processing unit with this number on the system.	PD (9,0)
SYHEAO	Number of tolerated crossings of a 16 MB boundary within any teraspace. Also called teraspace EAO exceptions.	PD (11,0)
SYHFTS	Number of space address computations (not addressing teraspace) that required extra processing. This may occur when a subtraction or addition of a signed value causes a result that is within the first page of a space object or associated space for which the machine did not choose alignment. Also called false traps.	PD (11,0)
SYHFTH	Number of teraspace address computations that required extra processing. This occurs when a subtraction or addition of a signed value causes a result that is within the first page after any 16 MB boundary in teraspace. Also called false traps.	PD (11,0)
SYIFUS	Interactive CPU time. Total interactive CPU used (in milliseconds).	PD (9,0)
SYIFTE	Interactive CPU time over threshold. Interactive CPU used (in milliseconds) when exceeding interactive CPU threshold.	PD (9,0)
SYSDBC	Reserved.	PD (9,0)
SYSSWC	<p>Secondary workload CPU time. The aggregate CPU time (in milliseconds) of all jobs performing workloads that cannot fully exploit dedicated server resources.</p> <p>Note: This metric measures non-Domino CPU usage on Domino servers. On non-Domino servers, this metric is not supported, so the reported value is 0.</p>	PD (9,0)

Field Name	Description	Attribute
SYLPTB	LPAR time base. This field provides a way to determine the difference between the system clocks on different partitions of a single system. This field has no meaning when looked at on a stand-alone basis. However, when this value is established on two (or more) partitions of a system, the difference between these values is the time difference (in seconds) between the two partitions.	PD (11,0)
SYNUAL	Noncached user authority lookups. The number of times that a noncached user authority lookup was performed. An authority check for one object can result in zero, one, or more than one user authority lookups. A user authority lookup can occur for the user, the user's groups, or an adopted user and can be cached or noncached.	PD (15,0)
SYIFTA	Interactive CPU time available. The amount of interactive CPU time that was available for use within the partition. This is the interactive capacity configured for use within the partition (also represented as interactive threshold).	PD (11,0)
SYSPTU	CPU time used. Total processing time (in milliseconds) used by the partition	PD (11,0)
SYSCTA	Configured CPU time available. Total processing time (in milliseconds) that was configured or guaranteed to be available for this partition. This is the system processing capacity as determined by processor unit allocations during the interval. Note: For uncapped partitions, the actual CPU used can exceed this value.	PD (11,0)

Field Name	Description	Attribute
SYSUTA	Uncapped CPU time available. Total processing time (in milliseconds) that was available for use by this partition (adjusted for configuration changes over time). It includes both the guaranteed configured capacity as well as the shared pool time that was not used by other partitions. For capped and dedicated partitions, or if shared pool data is not available, this is the same as Uncapped CPU time configured (SYSUTC).	PD (11,0)
SYSUTC	Uncapped CPU time configured. The maximum amount of CPU time that this partition is configured (allowed) to use within the shared pool (adjusted for configuration changes over time). This field defines the minimum of the virtual processors configured and the configured shared pool processors. For capped and dedicated partitions, this is the same as configured CPU time available (SYSCTA).	PD (11,0)
SYSPLU	Shared pool CPU time used. Total amount of CPU used within the shared pool by all partitions that share the pool. Set to zero if a shared pool is not used or the data is not available.	PD (11,0)
SYSPLA	Shared pool CPU time available. Total amount of CPU available within the shared pool. This value is determined based on the number of physical processors that are allocated to the pool. Set to zero if a shared pool is not used or the data is not available.	PD (11,0)

Field Name	Description	Attribute
SYVCPU	Virtual processor time configured. The processing capacity (in milliseconds) visible to the operating system based on the number of virtual processors configured and adjusted for configuration changes over time. This field is similar to SYSUTC except it is not affected by the shared pool configuration or the capped/uncapped state of the partition. The formula SYVCPU/INTSEC will yield the average number of virtual processors configured in the interval. Note: Will be zero for data obtained prior to V5R4.	PD (11,0)
SYDPCH	Total Dispatch Time. The amount of time (in milliseconds) that the operating system has dispatched a job, task or thread to a processor. This is not the same as CPU time used due to the effects of processor virtualization. Note: This field will contain data only if file QAPMJOBWT data is available.	PD (11,0)
SYSHRF	Shared processor flag. Indicates if the partition uses shared processors: <ul style="list-style-type: none"> • ‘ ‘ = unknown • '0' = Partition does not share physical processors. • '1' = Partition shares physical processors. 	C (1)
SCBGN	Reserved.	Z (3,0)
SYSIUL	Reserved.	PD (5,0)
SYSICIU	Reserved.	PD (7,0)
SYSQCPU	Unscaled SQL CPU time used. The amount of unscaled processor time (in microseconds) spent performing work done on behalf of SQL operations.	B (18,0)

Related reference

Collection Services data files: [QAPMJSUM](#)

These database file entries contain job summary information.

Collection Services data files: [QAPMSYSCPU](#)

This database file reports utilization for virtual processor units.

Collection Services data files: QAPMSYSTEM

This database file reports system-wide performance data.

Collection Services data files: System category and file relationships

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: File abbreviations

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRDTA) command See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMSYSCPU

This database file reports utilization for virtual processor units.

Virtual processors represent the operating system's view, within a logical partition, of the processors assigned to it. The utilization reported for virtual processors is the operating system's view of how much it has used the virtual processor.

This file has been replaced by the QAPMSYSVP file. Only one record will be output regardless of the number of virtual processors configured.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
DTECEN	Century digit.	C (1)
SCTNUM	Total number of system CPUs reported. The number of reported CPUs can include CPUs that are not currently in use because of configuration changes. Field SCTACT contains the number of active processors.	Z (3,0)
SCBGN	CPU number of the first CPU reported in this record.	Z (3,0)
SCPU01.....32	Total processing time (in milliseconds) used by CPUs 1 to 32.	PD (9,0)
SCIFUS	Interactive CPU time. Total interactive CPU used (in milliseconds).	PD (9,0)

Field Name	Description	Attribute
SCIFTE	Interactive CPU time over threshold. Interactive CPU used (in milliseconds) when exceeding interactive CPU threshold.	PD (9,0)
SCTACT	Current number of active processors at the time the data was sampled.	Z (3,0)

Related concepts

[Reporting CPU utilization](#) Find out how the total CPU that is consumed across virtual processors is reported.

Related reference

Collection Services data files: [QAPMSYSVP](#)

This database file reports instrumented data for the partition's virtual processors. One record is written per processor per interval.

Collection Services data files: [System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: [File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

[Create Performance Data \(CRTPFRDTA\) command](#) See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMSYSPRC

This database file reports utilization data for a system's physical processor units based on data obtained from the hypervisor. One record is written per processor per interval.

Physical processors are actual hardware processors contained within the physical system. The utilization for a system's physical processor is the time that the processor was made available by the hypervisor to any partition for it to do work. Dedicated processors will appear to be 100% utilized as the hypervisor is not in control of how the partition is using the processor.

Physical processor data is reported only if the collecting partition has been authorized to obtain it. This authorization is a partition configuration attribute set on the Hardware Management Console (HMC).

A POWER6 system with firmware level xx340_075 or later is required for this data to be available.

Field Name	Description	Attribute
INTNUM	Interval number: The <i>n</i> th sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
DTECEN	Century digit.	C (1)
INTSEC	Elapsed interval seconds. The number of seconds since the last sample interval.	B (4, 0)

Field Name	Description	Attribute
SPPID	Processor identifier. Unique identifier for each processor.	H(2)
SPTYPE	Type of processor: '1' = Physical processor	C (1)
SPATTR1	Processor state: <ul style="list-style-type: none"> '1' = not installed '2' = Guarded off (This processor has some runtime recoverable errors or it has been check stopped). '3' = Unlicensed (This processor is installed, but the license has not been purchased). '4' = Shared '5' = Borrowed (If this processor is not assigned to any partition, it has been taken from a dedicated partition that is set to donate its unused processors). '6' = Dedicated 	C (1)
SPATTR2	Owning partition ID of the partition that owns this processor. If the processor is shared or unowned, a minus 1 will be reported.	B (4, 0)
SPTIME	Processing time. The time (in milliseconds) that this processor was dispatched to some partition.	B (18, 0)
SPVAL01-SPVAL10	Reserved for future use.	B (18, 0)
SPCHIPID	Chip identifier. The unique value among all hardware chips in the system, which identifies the specific hardware chip on which this processor resides.	BINCHAR (4)
SPMODUID	Module identifier. The unique value among all hardware modules in the system, which identifies the specific hardware module on which the chip that contains this processor resides.	BINCHAR (4)

Field Name	Description	Attribute
SPAFNDMNP	Primary affinity domain identifier. Within the most significant affinity domain in the system, this is the unique value which identifies the specific affinity domain which contains this processor.	BINCHAR (4)
SPAFNDMNS	Secondary affinity domain identifier. Within the second most significant affinity domain in the system, this is the unique value which identifies the specific affinity domain which contains this processor.	BINCHAR (4)
SPLPIDX	Logical processor index. The unique value among all processors installed on the system by which the hypervisor identifies this processor.	B (4,0)
DATETIME	Interval date and time: The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp

Related concepts

[Reporting CPU utilization](#) Find out how the total CPU that is consumed across virtual processors is reported.

Related reference

[Collection Services data files: System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

[Data files: File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

[Create Performance Data \(CRTPFRDTA\) command](#) See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMSYSTEM

This database file reports system-wide performance data.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)

Field Name	Description	Attribute
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
DTECEN	Century digit.	C (1)
SYDPGF	Directory page faults: Number of times a page of the auxiliary storage directory was transferred to main storage for a look-up or an allocation operation.	PD (11,0)
SYAPGF	Access group member page faults: Number of times a page of an object contained in an access group was transferred to main storage independently of the access group. This transfer occurs when the containing access group was purged, or because portions of the containing access group are displaced from main storage.	PD (11,0)
SYMPGF	Microcode page faults: Number of times a page of microcode was transferred to main storage.	PD (11,0)
SYMCTR	Microtask read operations: Number of transfers of one or more pages of data from auxiliary storage because of a microtask rather than a process.	PD (11,0)
SYMCTW	Microtask write operations: Number of transfers of one or more pages of data from main storage to auxiliary storage because of a microtask rather than a process.	PD (11,0)
SYSASP	System auxiliary storage pool space available: Number of bytes of space on auxiliary storage available for allocation in the system auxiliary storage pool that is not currently assigned to machine interface (MI) objects or internal machine functions.	PD (15,0)

Field Name	Description	Attribute
SYPRMW	Permanent data transferred from main storage: Number of 512-byte blocks of permanent data transferred from main storage to the system auxiliary storage pool in auxiliary storage since the last sample.	PD (11,0)
SYSIZC	Size count: Total number of size exceptions.	PD (11,0)
SYDECD	Decimal data count: Total number of decimal data exceptions.	PD (11,0)
SYSEZC	Seize count: Total number of seize wait exceptions.	PD (11,0)
SYSZWT	Seize/wait time in milliseconds.	PD (11,0)
SYSYNL	Synchronous lock conflict count.	PD (11,0)
SYASYL	Asynchronous lock conflict count.	PD (11,0)
SYVFYC	Verify count.	PD (11,0)
SYAUTH	Object authority checks. The number of times that authority was checked for objects. An authority check for one object can result in zero, one, or more than one user authority lookups that can be cached or noncached (see SYNUAL field description).	PD (11,0)
SYEXPN	Total number of exceptions.	PD (11,0)
SYLRT1	Transactions in first response time monitor bracket: Total number of local workstation transactions with response time less than the value of boundary 1 specified on the Advanced Local Response Time Options dialog from the Collection Services properties page within the System i Navigator interface.	PD (9,0)
SYLRT2	Transactions in second response time monitor bracket: Total number of local workstation transactions with response time less than the value of boundary 2 and greater than the value of boundary 1 specified on the Advanced Local Response Time Options dialog from the Collection Services properties page within the System i Navigator interface.	PD (9,0)

Field Name	Description	Attribute
SYLRT3	Transactions in third response time monitor bracket: Total number of local workstation transactions with response time less than the value of boundary 3 and greater than the value of boundary 2 specified on the Advanced Local Response Time Options dialog from the Collection Services properties page within the System i Navigator interface.	PD (9,0)
SYLRT4	Transactions in fourth response time monitor bracket: Total number of local workstation transactions with response time less than the value of boundary 4 and greater than the value of boundary 3 specified on the Advanced Local Response Time Options dialog from the Collection Services properties page within the System i Navigator interface.	PD (9,0)
SYLRT5	Transactions in fifth response time monitor bracket: Total number of local workstation transactions with response time greater than the value of boundary 4 specified on the Advanced Local Response Time Options dialog from the Collection Services properties page within the System i Navigator interface.	PD (9,0)
SHCPU	Total processing unit time (in milliseconds) used by microcode/system jobs.	PD (11,0)
SMPLP	Machine pool paging: Number of pages transferred in and out of machine pool.	PD (11,0)
SMUPL	Highest user pool paging: Highest number of pages transferred in and out of any user pool.	PD (11,0)
SUPLI	Pool with highest paging: Pool number with highest number of pages transferred in and out.	C (2)
SMXDU	Maximum disk utilization. The largest utilization of all single path disk units and all paths of multipath disk units.	PD (11,0)

Field Name	Description	Attribute
SMXDUI	Actuator with maximum utilization.	C (4)
SMMMT	Time (in seconds) spent at MRTMAX by all MRT requests.	PD (11,0)
SMME	Number of requesters that routed to an MRT.	PD (11,0)
SYFOPN	Number of full opens system wide.	PD (11,0)
SYIXRB	Number of data space index creates system wide.	PD (11,0)
SYJOXR	Start journal operations initiated by user.	PD (11,0)
SYJOXP	Stop journal operations initiated by user.	PD (11,0)
SYJOIR	Start journal operations initiated by system.	PD (11,0)
SYJOIP	Stop journal operations initiated by system.	PD (11,0)
SYJOXD	Journal deposits resulting from user-journaled objects.	PD (11,0)
SYJOID	Journal deposits resulting from system-journaled objects.	PD (11,0)
SYJOJP	Journal deposits resulting from system-journaled objects to user-created journals.	PD (11,0)
SYJOBJ	Bundle writes to user-created journals.	PD (11,0)
SYJOB D	Bundle writes to internal system journals.	PD (11,0)
SYJOJY	Exposed access paths currently being journaled by the system.	PD (11,0)
SYJOJN	Exposed access paths currently not being journaled.	PD (11,0)
SYJOSE	System-estimated access path recovery time exposure in milliseconds.	PD (11,0)
SYJORT	System-managed access path tuning adjustments.	PD (11,0)
SYJOND	System-estimated access path recovery time exposure in milliseconds if no access paths were being journaled by the system.	PD (11,0)

Field Name	Description	Attribute
SYHEAO	Number of tolerated crossings of a 16 MB boundary within any teraspace. Also called teraspace EAO exceptions.	PD (11,0)
SYHFTS	Number of space address computations (not addressing teraspace) that required extra processing. This may occur when a subtraction or addition of a signed value causes a result that is within the first page of a space object or associated space for which the machine did not choose alignment. Also called false traps.	PD (11,0)
SYHFTH	Number of teraspace address computations that required extra processing. This occurs when a subtraction or addition of a signed value causes a result that is within the first page after any 16 MB boundary in teraspace. Also called false traps.	PD (11,0)
SYSDBC	Reserved.	PD (9,0)
SYSSWC	<p>Secondary workload CPU time. The aggregate CPU time (in milliseconds) of all jobs performing workloads that cannot fully exploit dedicated server resources.</p> <p>Note: This metric measures non-Domino CPU usage on Domino servers. On non-Domino servers, this metric is not supported, so the reported value is 0.</p>	PD (9,0)
SYJOER	Number of SMAPP evaluations requested. This count reveals how many times implicitly journaled objects were examined for potential SMAPP eligibility alterations. The evaluation can result in one of three outcomes: 1 - no action; 2 - start protecting this index via SMAPP; 3 - cease protecting this index via SMAPP.	PD (11,0)
SYJOES	Number of SMAPP evaluations serviced. This is a count of evaluations which led to a decision to change the protection state for a related index.	PD (11,0)

Field Name	Description	Attribute
SYJOIB	Number of SMAPP index build time estimations. The number of times background SLIC tasks have been asked to look at database keyed logical files or SQL indexes in order to estimate how long it will take to rebuild the index from scratch. Indexes whose estimated rebuild times are large will be SMAPPed. A large count here suggests that applications are frequently opening and closing files.	PD (11,0)
SYJOS1	First journal entry type. This field reports the most frequently occurring among the various journal entry types that have caused the SLIC layer of journal code to empty the journal cache prematurely. The number of bundles forced by this entry type is reported in the field SYJOC1.	C (2)
SYJOC1	Number of journal bundles forced prematurely by the journal entry type reported in the field SYJOS1.	PD (15,0)
SYJOS2	Second journal entry type. This field reports the second most frequently occurring among the various journal entry types that have caused the SLIC layer of journal code to empty the journal cache prematurely. The number of bundles forced by this entry type is reported in the field SYJOC2.	C (2)
SYJOC2	Number of journal bundles forced prematurely by the journal entry type reported in the field SYJOS2.	PD (15,0)
SYJOS3	Third journal entry type. This field reports the third most frequently occurring among the various journal entry types that have caused the SLIC layer of journal code to empty the journal cache prematurely. The number of bundles forced by this entry type is reported in the field SYJOC3.	C (2)
SYJOC3	Number of journal bundles forced prematurely by the journal entry type reported in the field SYJOS3.	PD (15,0)

Field Name	Description	Attribute
SYSDNFE	The number of stream files which have been written to, but not forced to permanent storage. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)) and user-defined file systems.	PD (11,0)
SYSDNFO	The number of stream files currently exposed that have exceeded the target exposure time. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)) and user-defined file systems.	PD (11,0)
SYSDTET	Exposure time (in milliseconds). The number of milliseconds between the time a stream file is written to and the time the file is forced to permanent storage. This time is a total for all files that were exposed during the interval. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)) and user-defined file systems.	PD (15,0)
SYSDNST	The number of tasks running that are forcing stream files to permanent storage. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)) and user-defined file systems.	PD (5,0)
SYSDFAL	The number of stream files that have been exposed and needed to be forced. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)) and user-defined file systems.	PD (11,0)

Field Name	Description	Attribute
SYSDFRL	The total number of stream files that have been asynchronously forced to permanent storage. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)) and user-defined file systems.	PD (11,0)
SYSDPFD	The number of stream file pages that have been asynchronously forced to permanent storage. This count does not include pages forced by an fsync operation. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)) and user-defined file systems.	PD (15,0)
SYSDPFF	The number of stream file pages explicitly forced to permanent storage as a result of an fsync operation. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)) and user-defined file systems.	PD (15,0)
SYBTAC	The number of asynchronous clear operations performed. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)) and user-defined file systems.	PD (11,0)
SYBTAP	The number of asynchronous prebring operations performed. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)) and user-defined file systems.	PD (11,0)

Field Name	Description	Attribute
SYBTAPP	The number of parallel prebring operations performed. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)) and user-defined file systems.	PD (11,0)
SYBTAPC	The number of asynchronous create operations performed. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)) and user-defined file systems.	PD (11,0)
SYBTAPD	The number of asynchronous delete operations performed. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)) and user-defined file systems.	PD (11,0)
SYLPTB	LPAR time base. This field provides a way to determine the difference between the system clocks on different partitions of a single system. This field has no meaning when looked at on a stand-alone basis. However, when this value is established on two (or more) partitions of a system, the difference between these values is the time difference (in seconds) between the two partitions.	B (11,0)
SYNUAL	Noncached user authority lookups. The number of times that a noncached user authority lookup was performed. An authority check for one object can result in zero, one, or more than one user authority lookups. A user authority lookup can occur for the user, the user's groups, or an adopted user and can be cached or noncached.	PD (15,0)
SYIFUS	Interactive CPU time used. Total interactive CPU used (in milliseconds).	PD (9,0)

Field Name	Description	Attribute
SYIFTE	Interactive CPU time used over threshold. Interactive CPU used (in milliseconds) when exceeding interactive CPU threshold.	PD (9,0)
SYIFTA	Interactive CPU time available. The amount of interactive CPU time that was available for use within the partition. This is the interactive capacity configured for use within the partition (also represented as interactive threshold).	PD (11,0)
SYSPTU	CPU time used. Total processing time (in milliseconds) used by the partition	PD (11,0)
SYSCTA	Total CPU time configured for the partition. Total processing time (in milliseconds) that was configured or guaranteed for this partition. This is the system processing capacity as determined by processor unit allocations during the interval. Note: For uncapped partitions, the actual CPU used can exceed this value.	PD (11,0)
SYSUTA	CPU time that could have been used by this partition. Total processing time (in milliseconds) that could have been used by this partition (adjusted for configuration changes over time). It includes both the guaranteed configured capacity as well as the shared pool time that was not used by other partitions. For capped and dedicated partitions, or if shared pool data is not available, this is the same as Uncapped CPU time configured.	PD (11,0)

Field Name	Description	Attribute
SYSUTC	Uncapped CPU time configured. The maximum amount of CPU time that this partition is configured (allowed) to use within the shared pool (adjusted for configuration changes over time). This field defines the Minimum of the virtual processors configured and the configured shared pool processors. For capped and dedicated partitions, this is the same as total CPU time configured for the partition.	PD (11,0)
SYSPLU	Shared pool CPU time used. Total amount of CPU used within the shared pool by all partitions that share the pool. Set to zero if a shared pool is not used or the data is not available.	PD (11,0)
SYSPLA	Shared pool CPU time available. Total amount of CPU available within the shared pool. This value is determined based on the number of physical processors that are allocated to the pool. Set to zero if a shared pool is not used or the data is not available.	PD (11,0)
SYVCPU	Virtual processor time configured. The processing time capacity (in milliseconds) visible to the operating system based on the number of virtual processors configured and adjusted for configuration changes over time. This field is similar to SYSUTC except it is not affected by the shared pool configuration or the capped/uncapped state of the partition. The formula $SYVCPU/(INTSEC*1000)$ will yield the average number of virtual processors configured in the interval. Note: Will be zero for data obtained prior to V5R4	PD (11,0)
SYDPCH	Total Dispatch Time. The amount of time (in milliseconds) that the operating system has dispatched a job, task, or thread to a processor. This is not the same as CPU time used due to the effects of processor virtualization. Note: this field will contain data only if file QAPMJOBWT data is available	PD (11,0)

Field Name	Description	Attribute
SYSHRF	Shared processor flag. Indicates if the partition uses shared processors: ' ' = unknown '0' = Partition does not share physical processors. '1' = Partition shares physical processors.	C (1)
SYSIUL	Reserved.	PD (5,0)
SYSCIU	Reserved.	PD (7,0)
SYJDUM	Reserved.	PD (1,0)
SYJDDM	Reserved.	C (3)
SYJCA4	Reserved.	C (3)
SYJPAS	Reserved.	C (3)
SYJMRT	Reserved.	C (3)
SYJS6E	Reserved.	C (3)
SYJCME	Reserved.	C (3)
SYJAUT	Reserved.	C (3)
SYJBCH	Reserved.	C (3)
SYJINT	Reserved.	C (3)
SYJSPL	Reserved.	C (3)
SYVPID	Virtual shared pool ID. This is the identifier of the partition's current virtual shared processor pool.	B (4,0)
SYVPCAP	Virtual shared pool entitled capacity. The entitled capacity of the partition's current virtual shared processor pool (in units of 1/100 of a physical processor).	B (9,0)
SYPPLU	Physical shared pool CPU time used. Total amount of CPU time (in milliseconds) used within the physical shared processor pool by all partitions that share the pool. Set to zero if physical shared pool is not used or the data is not available.	B (18,0)

Field Name	Description	Attribute
SYPLA	Physical shared pool CPU time available. Total amount of CPU time (in milliseconds) available within the physical shared processor pool. This value is determined based on the number of physical processors that are allocated to the pool. Set to zero if physical shared pool is not used or the data is not available. Note that this field will reflect CPU time donated by the dedicated partitions associated with the pool, if these partitions were configured to donate the unused CPU cycles to the pool.	B (18,0)
SYPTHV	Hypervisor CPU time. Amount of CPU time (in milliseconds) used by hypervisor for its internal needs. This time is included in SYSPTU.	B (18,0)
SYPTINT	Interrupt CPU time. Amount of CPU time (in milliseconds) used by operating system for interrupt processing. This time is included in SYSPTU.	B (18,0)
SYPTWS	Waittask time. Amount of CPU time (in milliseconds) used by waittask in SMT mode. This time is not included in SYSPTU.	B (18,0)
SYPTDN	Donated CPU time. Amount of CPU time (in milliseconds) donated by this partition to the physical shared processor pool. This time is only reported for dedicated partitions configured to donate their unused CPU cycles to physical shared pool.	B (18,0)
SYSSPTU	Scaled CPU time used (milliseconds). On some system models, the processors may operate at different speeds at different times, depending on power consumption or operating temperature. Ratio of SYSSPTU to SYSPTU shows the current processor speed in relation to nominal processor speed.	B (18,0)

Field Name	Description	Attribute
SYUCAPF	Partition uncapped flag. Indicates if the partition capacity is uncapped: ' ' = unknown '0' = Partition capacity is capped or this partition does not share physical processors. '1' = Partition capacity is uncapped.	C (1)
SYDONF	Partition donation flag. Indicates if the partition supports donation of unused processing time to the physical shared processor pool: ' ' = unknown '0' = Partition does not support donation of processing time. '1' = Partition supports donation of processing time.	C (1)
SYPTWAIT	Virtual processor thread wait event time. The elapsed time in microseconds that blocked threads of the partition's virtual processors were waiting for an event that caused them to become ready to run.	B (18, 0)
SYPTREADY	Virtual processor thread wait ready time. The elapsed time in microseconds that ready to run threads of the partition's virtual processors waited to be dispatched while entitled capacity was exhausted.	B (18, 0)
SYPTLATEN	Virtual processor thread dispatch latency. The elapsed time in microseconds that ready to run threads of the partition's virtual processors waited to be dispatched while entitled capacity was not exhausted and a physical processor was not available.	B (18, 0)

Field Name	Description	Attribute
SYPTACT	Virtual processor thread active time. The elapsed time in milliseconds summed for all threads of a virtual processor for the time that the virtual processor is active in the partition. A virtual processor that is active is one that is varied on; a virtual processor that is not active is either varied off or not installed.	B (18, 0)
SYPTIDLE	Virtual processor thread idle time. The elapsed time in milliseconds summed for all threads of a virtual processor for the time that thread is idle in the partition. A processor thread that is idle is one that is varied on and running the partition's idle loop.	B (18, 0)
SYPTINTR	Virtual processor thread interrupt time. The elapsed time in milliseconds summed for all threads of a virtual processor for the time that thread is handling interrupts in the partition.	B (18, 0)
SYFRMCPU	Processor firmware time used (in milliseconds). The amount of processor firmware time used by this partition.	B (18, 0)
SYFRMSCPU	Processor scaled firmware time used (in milliseconds). The amount of scaled processor firmware time used by this partition.	B (18, 0)
SYPFOLDSW	Processor folding switch state. The current state of the processor folding switch. <ul style="list-style-type: none"> • ' ' = data not available • '0' = off • '1' = on • '2' = system controlled 	C (1)
SYPFOLDST	Processor folding state. The current state of processor folding. <ul style="list-style-type: none"> • ' ' = data not available • '0' = disabled • '1' = enabled 	C (1)
SYEMMAJCDE	Energy management major code (see minor code)	C (1) (binary char)

Field Name	Description	Attribute
SYEMMINCDE	<p>Energy management minor code. Major and minor code meanings are:</p> <ul style="list-style-type: none"> • Maj 0, Min 0 = Unspecified or unavailable • Maj 0, Min 2 = Disabled (nominal performance) • Maj 0, Min 1 = Enabled (maximum performance) • Maj 0, Min 3 = Enabled (power saver) • Maj 1, Min 0-127 = Enabled (dynamic power optimizer) 	C (1) (binary char)
SYEMATTR	<p>Energy management attributes.</p> <ul style="list-style-type: none"> • Bit 0 = Power draw limit type (0 = soft, 1 = hard) • Bit 1-7 = Reserved 	C(1) (binary char)
SYEMPWRLMT	Energy management power draw limit in watts.	B (9, 1)
SYSQLCPU	Unscaled SQL CPU time used. The amount of unscaled processor time (in microseconds) spent performing work done on behalf of SQL operations.	B (18,0)
SYSQLSCPU	Scaled SQL CPU time used. The amount of scaled processor time (in microseconds) spent performing work done on behalf of SQL operations.	B (18,0)
SYOSTMP	Current temporary storage allocated for non database operations by IBM i. A snapshot of the total temporary storage currently allocated for non database operations across the system, expressed in 4096-byte units.	B (18,0)
SYDBTMP	Current temporary storage allocated for database operations by IBM i. A snapshot of the total temporary storage currently allocated for database operations across the system, expressed in 4096-byte units.	B (18,0)

Field Name	Description	Attribute
SYAJOBTMP	Current temporary storage charged to active jobs. A snapshot of the total temporary storage currently charged to active jobs, expressed in 4096-byte units.	B (18,0)
SYEJOBTMP	Current temporary storage charged to ended jobs. A snapshot of the total temporary storage currently charged to ended jobs, expressed in 4096-byte units.	B (18,0)
SYUSERTMP	Current user temporary storage. A snapshot of the total user temporary storage currently allocated, expressed in 4096-byte units. Only the user temporary storage not charged to any job is accounted for here.	B (18,0)
SYPSLPU	Physical shared pool scaled CPU time used. Total amount of scaled CPU time (in milliseconds) used within the physical shared processor pool by all partitions that share the pool. Set to zero if physical shared pool is not used or the data is not available.	B (18,0)
SYTRUNIC	Non-idle hardware instruction count. Hardware instructions (in units of 1048576 instructions), completed by and summed for processor threads in run state. Note: This value is available only for partitions running on Power8® and later hardware. However it is not available when running in Power7® or Power6® mode.	B (18,0)
SYTRUNVTB	Non-idle processor virtual time. The amount of run state physical processor time (in milliseconds) summed for all processors. A processor is in run state when <u>any</u> of its threads are in the run state; a processor is in idle state when <u>all</u> of its threads are in idle state. Note: This value is available only for partitions running on Power8® and later hardware. However it is not available when running in Power7® or Power6® mode.	B (18,0)

Field Name	Description	Attribute
SYTITUIC	Interrupt instruction count. Hardware instructions (in units of 1048576 instructions), completed by and summed for processor threads in interrupt state. Note: This value is available only for partitions running on Power8® and later hardware. However it is not available when running in Power7® or Power6® mode.	B (18,0)
SYTFRMIC	Firmware instruction count. Hardware instructions (in units of 1048576 instructions), completed by firmware. Note: This value is available only for partitions running on Power8® and later hardware. However it is not available when running in Power7® or Power6® mode.	B (18,0)
DATETIME	Interval date and time: The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp
SYPMEM	Partition memory (MB). The amount of main storage assigned to the partition in megabytes.	B (18,0)

Related reference

Collection Services data files: [QAPMISUM](#)

This database file contains interval summary information.

Collection Services data files: [QAPMJSUM](#)

These database file entries contain job summary information.

Collection Services data files: [QAPMSMSYS](#)

This database file contains summarized metrics from system data (*SYSLVL collection category) that may be used in support of system monitoring.

Collection Services data files: [System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: [File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRDTA) command See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMSYSVP

This database file reports instrumented data for the partition's virtual processors. One record is written per processor per interval.

Field Name	Description	Attribute
INTNUM	Interval number: The <i>n</i> th sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DATETIME	Interval date and time. The date and time of the sample interval, expressed in local system time.	Timestamp
INTSEC	Elapsed interval seconds. The number of seconds since the last sample interval.	PD (7,0)
VPID	Virtual Processor identifier. Unique identifier for each of the partition's virtual processors.	B (4,0)
VPACTF	Active flag: <ul style="list-style-type: none"> • '1' indicates processor is varied on and available for use • '0' indicates processor is varied off and not available for use 	C (1)
VPFLAG	Processor status flag. Flag to provide for future additional status information.	BINCHAR (1)
VPACTTIME	Active time. The time (in milliseconds) that the processor was varied on and available for use.	B (18,0)
VPCPUU	Utilized processor time. The amount of unscaled processor time (in milliseconds) consumed on this virtual processor.	B (18,0)
VPCPUAC	Processor configured available time. The amount of configured processor time (in milliseconds) available to this processor. In a dedicated partition, the configured available processing time is the elapsed time. In a shared partition, configured available processing time is the elapsed time times the ratio of shared processor units to processors, tracked over time as the configuration changes.	B (18,0)

Field Name	Description	Attribute
VPCPUAU	<p>Processor uncapped available time. The amount of available processing time, (in milliseconds) tracked over time as the configuration changes.</p> <p>The total available time includes configured available time and an additional amount of shared processor pool available time that is available to the partition because it is effectively uncapped. The uncapped available time represents the upper limit on the partition's potential utilized time based on the configuration of the partition and the shared pool.</p> <p>In dedicated and effectively capped shared processor partitions, the processor uncapped available time equals the processor configured available processing time. In an effectively uncapped shared processor partition, the uncapped available time is the elapsed time multiplied by the minimum of the number of processors in the partition and the number of processors in the shared pool, tracked over time as the configuration changes.</p>	B (18,0)
VPRUNINS	<p>Non-idle hardware instruction count. Hardware instructions completed by and summed for processor threads in run state.</p> <p>Note: This value is available only for partitions running on Power8® and later hardware. However it is not available if running in Power7® or Power6® mode.</p>	B (18,0)

Field Name	Description	Attribute
VPRUNVTB	<p>Non-idle processor virtual time. The amount of run state physical processor time (in milliseconds). A processor is in run state when <u>any</u> of its threads are in the run state; a processor is in idle state when <u>all</u> of its threads are in idle state.</p> <p>Note: This value is available only for partitions running on Power8® and later hardware. However it is not available if running in Power7® or Power6® mode.</p>	B (18,0)
VPITUINS	<p>Interrupt instruction count. Hardware instructions completed by and summed for processor threads in interrupt state.</p> <p>Note: This value is available only for partitions running on Power8® and later hardware. However it is not available if running in Power7® or Power6® mode.</p>	B (18,0)
UTCTIME	<p>UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).</p>	Timestamp

Related reference

[Collection Services data files: System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

[Data files: File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

[Create Performance Data \(CRTPFRDTA\) command](#) See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMSYSWLC

This database file reports workload group data.

Data is generated only when one or more workload groups were in use during the collection. A record is written for each group that is active.

Field Name	Description	Attribute
INTNUM	<p>Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.</p>	PD (5,0)

Field Name	Description	Attribute
DATETIME	Interval date and time: The date and time of the sample interval, expressed in local system time.	Timestamp
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
SWGROU	Group ID. The identifier for the workload group.	B (9,0)
SWGNAME	Group Name. The name assigned to the workload group when allocated by License Management	C (10)
SWPRCASN	Processors assigned. The maximum number of processors which may be used concurrently by all threads of all processes which are associated with the workload group. This is the value associated with the group at the time data was sampled.	B (4,0)
SWPRCAVL	Processor time available (in microseconds). The amount of processor time that this group had available to it based on the number of processors assigned to the group over time.	B (18,0)
SWPRCUSE	Processor unscaled time used (in microseconds). The amount of unscaled processor time used within threads assigned to this group. Note: This does not include time charged to a thread by server tasks.	B (18,0)
SWSPRCUSE	Processor scaled time used (in microseconds). The amount of scaled processor time used within threads assigned to this group. Note: This does not include time charged to a thread by server tasks.	B (18,0)
SWDELAY	Dispatch latency time . The amount of time ready to run threads could not be dispatched due to the group's maximum concurrent processor limit.	B (18,0)

Field Name	Description	Attribute
SWPRCADD	Processes added. The number of process instances that became associated with this group during the interval.	B (18,0)
SWPRCRMV	Processes removed. The number of process instances that were disassociated from this group during the interval.	B (18,0)
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp

Related reference

Collection Services data files: System category and file relationships

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: File abbreviations

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRDTA) command See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMTAPE

This database file contains the tape device data collected in the *RMVSTG collection category.

It contains one record per interval per tape device connected to the system.

Field Name	Description	Attribute
INTNUM	Interval number: The <i>n</i> th sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DATETIME	Interval data and time. The date and time of the sample interval, expressed in local system time.	Timestamp
INTSEC	Elapsed interval seconds. The number of seconds since the last sample interval.	PD (7,0)
TPDRN	Tape device resource name.	C (10)
TPTYPE	Tape device type.	C (4)
TPMDLN	Model number. The model number of the tape drive.	C (4)
TPIOPRN	IOP resource name.	C (10)
TPIOARN	Storage adapter (IOA) resource name.	C (10)
TPRDS	Number of reads.	B (18, 0)

Field Name	Description	Attribute
TPWRTS	Number of writes.	B (18, 0)
TPBRD	Bytes read.	B (18, 0)
TPBWRT	Bytes written.	B (18, 0)
TPWREQ	Time spent waiting for a request from the client (in milliseconds).	B (18, 0)
TPWRESP	Time spent waiting for a response from the drive (in milliseconds).	B (18, 0)
TPSFCMD	Space by file mark commands.	B (18, 0)
TPFLMRKSPC	File marks spaced.	B (18, 0)
TPSBCMD	Space block commands.	B (18, 0)
TPBLCKSPC	Blocks spaced.	B (18, 0)
TPWFCMD	Write file mark commands.	B (18, 0)
TPFLMRKWRT	File marks written.	B (18, 0)
TPSEODCMD	Space to EOD commands.	B (18, 0)
TPWBCMD	Write buffer commands.	B (18, 0)
TPRESERVES	Reserve commands.	B (18, 0)
TPRELEASES	Release commands.	B (18, 0)
TPREWINDS	Rewind commands.	B (18, 0)
TPUNLOADS	Unload commands.	B (18, 0)
TPSTPOSCMD	Set tape position commands.	B (18, 0)
TPRDPOSCMD	Read tape position commands.	B (18, 0)
TPVAL1	Reserved	B (18, 0)
TPVAL2	Reserved	B (18, 0)
TPVAL3	Reserved	B (18, 0)
TPVAL4	Reserved	B (18, 0)
TPVAL5	Reserved	B (18, 0)
TPVAL6	Reserved	B (18, 0)
TPVAL7	Reserved	B (18, 0)
TPVAL8	Reserved	B (18, 0)
TPVAL9	Reserved	B (18, 0)
TPVAL10	Reserved	B (18, 0)
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp

Related reference

Collection Services data files: System category and file relationships

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: File abbreviations

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRDTA) command See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMTCP

This database file contains system-wide TCP/IP data.

There is one record per collection interval.

Note: The TCP/IP performance data includes data for both for Internet Protocol version 4 (IPv4) and Internet Protocol version 6 (IPv6).

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Number of seconds TCP/IP was active in this sample interval.	PD (7,0)
DTECEN	Century digit.	C (1)
TCDIRV	Number of input datagrams received from interfaces, including those received in error.	PD (15,0)
TCDIHE	Number of input datagrams discarded due to errors in their IP headers.	PD (11,0)
TCDIAE	Number of input datagrams discarded due to an address that is not valid in the IP headers.	PD (11,0)
TCDIUP	Number of input datagrams discarded due to unknown or unsupported protocol.	PD (11,0)
TCDIDS	Number of input datagrams discarded due to other problems (for example, lack of buffer space).	PD (11,0)
TCDIFW	Number of datagrams forwarded, including Source-Routed through this system.	PD (15,0)

Field Name	Description	Attribute
TCDIDL	Number of input datagrams successfully delivered to IP user-protocols (including ICMP).	PD (15,0)
TCDOTR	Number of datagrams which IP user-protocols supplied for transmission (including ICMP).	PD (15,0)
TCDONR	Number of output datagrams discarded because no route was found to transmit them to their destination.	PD (11,0)
TCDODS	Number of output datagrams discarded due to other problems (for example, lack of buffer space).	PD (11,0)
TCASMR	Number of IP fragments received which needed reassembly.	PD (15,0)
TCASMS	Number of datagrams successfully reassembled.	PD (15,0)
TCASMF	Number of failures detected by the reassembly algorithm.	PD (11,0)
TCFRGS	Number of datagrams successfully fragmented.	PD (15,0)
TCFRGF	Number of fragmentation failures.	PD (11,0)
TCFRGN	Number of datagram fragments generated.	PD (15,0)
TCAOPN	Number of times TCP connections made a transition from CLOSED state to SYN-SENT state.	PD (11,0)
TCPOPN	Number of times TCP connections made a transition from LISTEN state to SYN-RCVD state.	PD (11,0)
TCFOPN	Number of times TCP connection establishment attempts failed.	PD (11,0)
TCCRST	Number of times TCP connection was reset.	PD (11,0)
TCSGRV	Number of TCP segments received.	PD (15,0)
TCSGTR	Number of TCP segments sent.	PD (15,0)
TCSGRT	Number of TCP segments retransmitted.	PD (11,0)
TCSGER	Number of TCP segments received in error.	PD (11,0)

Field Name	Description	Attribute
TCUDRV	Number of UDP datagrams delivered to UDP users.	PD (15,0)
TCUDTR	Number of UDP datagrams sent.	PD (15,0)
TCUDNP	Number of received UDP datagrams for which there was no application on the destination port.	PD (11,0)
TCUDER	Number of received UDP datagrams that could not be delivered for other reasons.	PD (11,0)
TCICRV	Number of ICMP messages received.	PD (15,0)
TCICTR	Number of ICMP messages which were attempted to be sent.	PD (15,0)
TCICIE	Number of received ICMP messages that had ICMP-specific errors.	PD (11,0)
TCICOE	Number of ICMP messages that were not sent due to ICMP-specific problems.	PD (11,0)
DATETIME	Interval date and time: The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp

Related reference

Collection Services data files: QAPMTCPIFC

This database file contains TCP/IP data related to individual TCP/IP interfaces.

Collection Services data files: System category and file relationships

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: File abbreviations

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRTA) command See the Create Performance Data (CRTPFRTA) command for information on how to create performance database files.

Collection Services data files: QAPMTCPIFC

This database file contains TCP/IP data related to individual TCP/IP interfaces.

There are one or two records per TCP/IP interface per collection interval. If both Internet Protocol version 4 (IPv4) and Internet Protocol version 6 (IPv6) data are available for an interface, the primary record will contain the combined data. If the data was collected on a release that supports the collection of independent data for IPv6, a secondary record will contain the data specific to IPv6. If data is available for only one Internet Protocol version, the primary record will contain data specific to that Internet Protocol version and there will not be a secondary record.

Note: The TCP/IP performance data includes data for both for Internet Protocol version 4 (IPv4), for Internet Protocol version 6 (IPv6), or for both Internet Protocol version 4 and Internet Protocol version 6.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample interval based on the start time specified in the Create Performance Data (CRTPFRTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Number of seconds TCP/IP interface was active in this sample interval.	PD (7,0)
DTECEN	Century digit.	C (1)
TINUM	TCP/IP interface number.	PD (5,0)
TITYPE	TCP/IP interface type. Possible TCP/IP interface types include: <ul style="list-style-type: none"> • 01 = other • 05 = RFC877 X25 • 06 = Ethernet CSMACD • 07 = ISO88023 CSMACD • 09 = ISO88025 Token Ring • 15 = FDDI • 23 = PPP • 24 = Software Loopback • 28 = SLIP • 32 = Frame Relay This is a partial list. For a full list, see RFC 1213.	PD (5,0)
TILIND	Line description object name.	C (10)
TISTAT	Interface status. Possible values include: <ul style="list-style-type: none"> • 1 - Active • 2 - Inactive • 3 - Test 	PD (3,0)
TIMTU	MTU size for interface. For a primary record that contains both IPv4 and IPv6 data, this is the IPv4 MTU size.	PD (5,0)
TIBIRV	Number of bytes received on interface.	PD (15,0)

Field Name	Description	Attribute
TIPIUC	Number of unicast packets received.	PD (15,0)
TIPINU	Number of non-unicast packets received.	PD (15,0)
TIPIER	Number of inbound packets that contained errors.	PD (11,0)
TIPIUP	Number of inbound packets with protocol errors.	PD (11,0)
TIPIDS	Number of inbound packets discarded for other reasons (for example, lack of buffer space).	PD (11,0)
TIBOTR	Number of bytes transmitted out of interface.	PD (15,0)
TIPOUC	Number of unicast packets requested to be sent.	PD (15,0)
TIPONU	Number of non-unicast packets requested to be sent.	PD (15,0)
TIPOER	Number of outbound packets that could not be sent because of errors.	PD (11,0)
TIPODS	Number of outbound packets discarded for other reasons (for example, lack of buffer space).	PD (11,0)
TIIPV	Internet protocol version for which data in this sample interval was collected. Possible values include: <ul style="list-style-type: none"> • 0 - Both IPv4 and IPv6 • 1 - IPv4 • 2 - IPv6 	C (1)
TIRTYP	Record type indicates whether the record is primary or secondary for this sample interval. Possible values include: <ul style="list-style-type: none"> • 1 - Physical interface primary record • 2 - Physical interface secondary record 	C (1)
DATETIME	Interval date and time: The date and time of the sample interval, expressed in local system time.	Timestamp

Field Name	Description	Attribute
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp

Related reference

Collection Services data files: [QAPMTCP](#)

This database file contains system-wide TCP/IP data.

Collection Services data files: System category and file relationships

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: File abbreviations

The database files use abbreviations in the field and byte data tables.

[Create Performance Data \(CRTPFRDTA\) command](#) See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMUSRTNS

This database file contains performance data for the user-defined and Application Response Measurement (ARM) transactions.

One record is created for each type of transaction that occurs for a given job during the interval.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
DTECEN	Century digit: where 0 indicates 19XX and 1 indicates 20XX.	C (1)
UTNAM	Job name.	C (10)
UTUSR	Job user.	C (10)
UTNUM	Job number.	C (6)

Field Name	Description	Attribute
UTTYP	<p>Transaction type. The type of user-defined transaction reported in this record for this job. The transaction type has the same value as the application identifier parameter passed to the Start Transaction API and End Transaction API. If Collection Services encounters more than 15 transaction types for this job, it will combine the transaction data for any additional transaction types into the transaction type of *OTHER.</p> <p>When Application Response Measurement (ARM) transaction data is reported in the QAPMUSRTNS file, this field contains an ARM transaction type name. Names of ARM transaction types start with the prefix "QARM". You can find additional information about ARM transactions in the optional secondary file, QAPMARMTRT.</p>	C (20)
UTTIM	Total time in microseconds used by all transactions of this type for this job.	B (18,0)
UTNUMT	Total number of transactions of this type for this job. This represents the number of calls to the End Transaction API.	B (9,0)
UTSTR	<p>Number of calls to the Start Transaction API for this transaction type and job.</p> <p>For ARM transaction types, this field is 0, because ARM APIs do not go through the Start Transaction API.</p>	B (9,0)
UTBAD	Number of calls to the End Transaction API for this transaction type and job which passed a bad transaction start time. This can occur for various reasons including: The start time is zero. The start time is after the end time. The start time is before the job start time.	B (9,0)
UTNUMC	Number (N) of user-provided counters associated with this transaction type and job. These counters are reported in the first N UTCTn fields. This field is zero if there are no user-provided counters.	B (9,0)
UTCT1	<p>User-provided counter 1.</p> <p>For ARM transaction types, this field contains the total ARM transaction queuing time in milliseconds.</p>	B (18,0)
UTCT2	User-provided counter 2.	B (18,0)
UTCT3	User-provided counter 3.	B (18,0)
UTCT4	User-provided counter 4.	B (18,0)
UTCT5	User-provided counter 5.	B (18,0)
UTCT6	User-provided counter 6.	B (18,0)
UTCT7	User-provided counter 7.	B (18,0)

Field Name	Description	Attribute
UTCT8	User-provided counter 8.	B (18,0)
UTCT9	User-provided counter 9.	B (18,0)
UTCT10	User-provided counter 10.	B (18,0)
UTCT11	User-provided counter 11.	B (18,0)
UTCT12	User-provided counter 12.	B (18,0)
UTCT13	User-provided counter 13.	B (18,0)
UTCT14	User-provided counter 14.	B (18,0)
UTCT15	User-provided counter 15.	B (18,0)
UTCT16	User-provided counter 16.	B (18,0)
DATETIME	Interval date and time: The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp
<p>Note: ARM transaction data is reported only for applications which call the ARM API implementation that is shipped with the operating system.</p>		

Related reference

Collection Services data files: [QAPMARMTRT](#)

This database file contains information about Application Response Measurement (ARM) transaction types that are reported in the QAPMUSRTNS file.

Collection Services data files: [System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: [File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

[Create Performance Data \(CRTPFRDTA\) command](#) See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMWASAPP

This data includes information about applications running on the IBM WebSphere Application Server.

The data file contains one record for each application per interval. Applications can be either of the following types:

- Servlet sessions
- Web applications (servlets and JSPs)

Much of the data comes from WebSphere Performance Monitoring Infrastructure (PMI) data and transaction counters. Where PMI data is used directly, the name of the PMI field is provided.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)

Field Name	Description	Attribute
DTETIM	Interval date (<i>yymddd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
DTECEN	Century digit. 0 indicates 19XX and 1 indicates 20XX.	C (1)
WSNAME	Job name of server job.	C (10)
WSUSER	User name of server job.	C (10)
WSNBR	Job number of server job.	C (6)
WSJKEY	Server job key.	H (16)
WAKEY	Application key.	H (8)
WAAPP	Application name (first 10 characters if the name is longer than this field). This field is in unicode.	G (40)
Servlet session counters		
WACRT	Servlet sessions created. The number of servlet sessions that were created during the interval. (PMI: <code>servletSessionsModule.createdSessions</code>)	B (9,0)
WAINV	Servlet sessions invalidated. The number of servlet sessions that were invalidated during the interval. (PMI: <code>servletSessionsModule.invalidatedSessions</code>)	B (9,0)
WATLIF	Servlet Session Accumulated Lifetime. The accumulated servlet session lifetime in milliseconds (time invalidated - time created) during the interval. (PMI: <code>servletSessionsModule.sessionLifeTime</code>) To calculate average lifetime: WATLIF / WAINV	B (18,0)
WALIV	Servlet Session Current Live Count. The number of sessions that were cached in memory at the time the data was sampled. (PMI: <code>servletSessionsModule.liveSessions</code>)	B (9,0)
Web application counters – servlets		
WASLD	Servlets loaded. The total number of servlets loaded during the interval. This field includes both servlets and JSPs. (PMI: <code>webAppModule.numLoadedServlets</code> ; <code>CountStatistic</code>)	B (9,0)
WASRD	Servlets reloaded. The total number of servlets reloaded during the interval. This field includes both servlets and JSPs. (PMI: <code>webAppModule.numReloads</code> ; <code>CountStatistic</code>)	B (9,0)
WASCNT	Current servlets. Number of servlets at the time the data was sampled. This field does not include JSPs.	B (9,0)

Field Name	Description	Attribute
WASCNTNZ	Current servlets with non-zero response time. The number of servlets which had a response time > 0 at the time the data was sampled. This field does not include JSPs.	B (9,0)
WASREQ	Servlet requests. Total number of requests that servlets processed during the interval. This field does not include JSPs. (PMI: webAppModule.servlets.totalRequests; CountStatistic)	B (9,0)
WASRT	Servlet response time. Total accumulated response time in milliseconds during the interval for servlets. This field does not include JSPs. (PMI: webAppModule.servlets.responseTime; TimeStatistic) To calculate response time per servlet: WASRT / WASREQ	B (18,0)
WASWE	Current servlets with errors. The number of servlets which had an error count > 0 at the time the data was sampled. This field does not include JSPs. (PMI: Number of servlets where webAppModule.servlets.numErrors > 0)	B (9,0)
WASERR	Servlet error count. The total number of errors for all servlets. This field does not include JSPs. (PMI: webAppModule.servlets.numErrors; CountStatistic)	B (9,0)
Web application counters – JSPs		
WAJCNT	Current JSPs. Number of JSPs at the time the data was sampled.	B (9,0)
WAJREQ	JSP requests. Total number of requests that JSPs processed during the interval. (PMI: webAppModule.servlets.totalRequests; CountStatistic)	B (9,0)
WAJRT	Total JSP response time. Total accumulated response time in milliseconds during the interval for all JSPs. (PMI: webAppModule.servlets.responseTime; TimeStatistic) To calculate response time per JSP: WAJRT/WAJREQ	B (18,0)
WAJWE	JSP count with errors. Number of JSPs which had an error count > 0 at the time the data was sampled. (PMI: Number of JSPs where webAppModule.servlets.numErrors > 0).	B (9,0)

Field Name	Description	Attribute
WAJERR	JSP error count. The total number of errors for JSPs during the interval. (PMI: webAppModule.servlets.numErrors; CountStatistic).	B (9,0)
Reserved fields		
WARES1	Reserved	B (9,0)
WARES2	Reserved	B (9,0)
WARES3	Reserved	B (9,0)
WARES4	Reserved	B (9,0)
WARES5	Reserved	B (18,0)
WARES6	Reserved	B (18,0)
DATETIME	Interval date and time: The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp

Related reference

[WebSphere servlet session counters](#) See WebSphere servlet session counters for more information about WebSphere servlet session counters data.

[WebSphere Web application counters](#) See WebSphere Web application counters for more information about WebSphere Web application counters data.

[Collection Services data files: System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

[Data files: File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

[Create Performance Data \(CRTPFRDTA\) command](#) See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMWASCFG

This data includes configuration information about the different server jobs.

This information is static and therefore does not change during the life of the server. There will be one record per server. If a WebSphere server stops and is restarted later, it will have a different job name/user name/job number, but the same server name.

Field Name	Description	Attribute
WSNAME	Job name of server job.	C (10)
WSUSER	User name of server job.	C (10)
WSNBR	Job number of server job.	C (6)
WSJKEY	Server job key.	H (16)
WSLIB	WebSphere library name.	C (10)
WSIHP	Initial heap size in bytes.	B (18,0)

Field Name	Description	Attribute
WSMHP	Maximum heap size in bytes. 0 = *NOMAX	B (18,0)
WSPRF	Profile name (first 40 characters if the name is longer than this field). This field is in Unicode.	G (40)
WSNODE	Node name (first 40 characters if the name is longer than this field). This field is in Unicode.	G (40)
WSCCELL	Cell name (first 40 characters if the name is longer than this field). This field is in Unicode.	G (40)
WSSVR	Server name (first 40 characters if the name is longer than this field). This field is in Unicode.	G (40)
WSVER	WebSphere version (first 40 characters if the name is longer than this field). This field is in Unicode.	G (40)
WSED	WebSphere edition (first 40 characters if the name is longer than this field). This field is in Unicode.	G (40)
WSJDK	JDK version (first 40 characters if the name is longer than this field). This field is in Unicode.	G (40)
WSSEC	Security information (first 40 characters if the name is longer than this field). This field is in Unicode.	G (40)
WSSTRS	Starting statistics level (first 40 characters if the name is longer than this field). This field is in Unicode.	G (40)
WSREF	Pass by reference flag.	C (1)
WSJVM	Generic JVM invocation string (first 200 characters if the name is longer than this field). This field is in Unicode.	G (200)
WSCRES1	Reserved.	G (20)
WSCRES2	Reserved.	G (20)
WSCRES3	Reserved.	G (40)
WSCRES4	Reserved.	G (40)

Related reference

[Collection Services data files: System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

[Data files: File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

[Create Performance Data \(CRTPFRDTA\) command](#) See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMWASEJB

This data includes information about applications with enterprise Java beans (EJBs) running on the IBM WebSphere Application Server.

Each record represents one type of EJB (such as stateful, stateless, entity, or message-driven) per application per interval. If there is no bean activity for a particular EJB type, then no record will be written.

Much of the data comes from WebSphere Performance Monitoring Infrastructure (PMI) data and transaction counters. Where PMI data is used directly, the name of the PMI field is provided.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
DTECEN	Century digit. 0 indicates 19XX and 1 indicates 20XX.	C (1)
WSNAME	Job name of server job.	C (10)
WSUSER	User name of server job.	C (10)
WSNBR	Job number of server job.	C (6)
WSJKEY	Server job key.	H (16)
WAKEY	Application key	H (8)
WEAPP	Application name (first 10 characters if the name is longer than this field). This field is in Unicode.	G (40)
WETYPE	Type of bean. '1' = Stateful '2' = Stateless '3' = Entity '4' = Message driven	C (1)
WEHOME	EJB homes. Number of EJB homes at the time the data was sampled.	B (9,0)
WECRT	Beans created. The total number beans created during the interval. (PMI: beanModule.create; CountStatistic)	B (9,0)
WERMV	Beans removed. The total number of beans removed during the interval. (PMI: beanModule.remove; CountStatistic)	B (9,0)
WEPSV	Beans passivated. The total number of beans that were passivated during the interval. (PMI: beanModule.passivate; CountStatistic)	B (9,0)
WELOAD	Beans loaded. The total number of beans that were loaded during the interval. This field applies only to entity beans. (PMI: beanModule.load; CountStatistic)	B (9,0)
WESTORE	Beans stored. The total number of beans that were stored during the interval. This field applies only to entity beans. (PMI: beanModule.store; CountStatistic)	B (9,0)

Field Name	Description	Attribute
WERSP	Total accumulated bean method response time. The total response time in milliseconds for the bean methods (home, remote, local) during the interval. To calculate average response time per bean: WERSP / WECALL (PMI: beanModule.avgMethodRt; TimeStatistic)	B (18,0)
WERDY	Current ready beans. The number of ready beans at the time the data was sampled. (PMI: beanModule.readyCount; RangeStatistic)	B (9,0)
WELIV	Current live beans. The number of live beans at the time the data was sampled. (PMI: beanModule.concurrentLives; RangeStatistic)	B (9,0)
WECALL	Bean method calls. The total number of bean method calls during the interval. (PMI: beanModule.totalMethodCalls; CountStatistic)	B (9,0)
WERTP	Returns to pool. The total number of calls returning bean to the pool during the interval. This field applies only to stateless and entity beans. (PMI: beanModule.returnsToPool; CountStatistic)	B (9,0)
WEDISC	Returns discarded. The total number of times during the interval that the returning bean was discarded because the pool was full. This field applies only to stateless and entity beans. (PMI: beanModule.returnsDiscarded; CountStatistic)	B (9,0)
WEPOOL	Current beans in pool. The number of beans in the pool at the time the data was sampled. This field applies only to stateless and entity beans. (PMI: beanModule.poolSize; RangeStatistic)	B (9,0)
WEMSG	Messages delivered. The total number of messages delivered to the bean onMessage method during the interval. This field applies only to message driven beans. (PMI: beanModule.messageCount; CountStatistic)	B (9,0)
WERES1	Reserved.	B (9,0)
WERES2	Reserved.	B (9,0)
WERES3	Reserved.	B (9,0)
WERES4	Reserved.	B (9,0)
WERES5	Reserved.	B (18,0)
WERES6	Reserved.	B (18,0)
DATETIME	Interval date and time: The date and time of the sample interval, expressed in local system time.	Timestamp

Field Name	Description	Attribute
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp

Related reference

[WebSphere EJB counters](#) See WebSphere EJB counters for more information about WebSphere EJB counters data.

[Collection Services data files: System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

[Data files: File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

[Create Performance Data \(CRTPFRDTA\) command](#) See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMWASRSC

This data includes information about pooled resources associated with an IBM WebSphere Application Server.

Each record represents one pooled resource per interval. The type of pooled resource can be a JDBC connection pool, a J2C connection pool, or a thread pool. Not all fields are applicable to each pooled resource type. If a resource exists but is not being used (nothing created, destroyed, allocated or returned), then no record will be written.

Much of the data comes from WebSphere Performance Monitoring Infrastructure (PMI) data and transaction counters. Where PMI data is used directly, the name of the PMI field is provided.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
DTECEN	Century digit. 0 indicates 19XX and 1 indicates 20XX.	C (1)
WSNAME	Job name of server job.	C (10)
WSUSER	User name of server job.	C (10)
WSNBR	Job number of server job.	C (6)
WSJKEY	Server job key.	H (16)
WPKEY	Pooled resource key.	H (8)
WPRSCNM	Pooled resource name. This field is in Unicode.	G (40)

Field Name	Description	Attribute
WPTYPE	Type of pooled resource: '1' = JDBC '2' = J2C '3' = Thread pool	C (1)
WPCRT	Creates. The total number of connections or threads created during the interval. (PMI: JDBC: connectionPoolModule.numCreates; CountStatistic) (PMI: J2C: j2cModule.numManagedConnectionsCreated; CountStatistic) (PMI: Thread pool: threadPoolModule.threadCreates; CountStatistic)	B (9,0)
WPDST	Destroys. The total number of connections or threads destroyed during the interval. (PMI: JDBC: connectionPoolModule.numDestroys; CountStatistic) (PMI: J2C: j2cModule.numManagedConnectionsDestroyed; CountStatistic) (PMI: Thread pool: threadPoolModule.threadDestroys; CountStatistic)	B (9,0)
WPALC	Allocates. The total number of connections allocated during the interval. Does not apply to thread pool. (PMI: JDBC: connectionPoolModule.numAllocates; CountStatistic) (PMI: J2C: j2cModule.numManagedConnectionsAllocated; CountStatistic) (PMI: Thread pool: Set to 0)	B (9,0)
WPRTN	Returns. The total number of connections returned to the pool during the interval. Does not apply to thread pool. (PMI: JDBC: connectionPoolModule.numReturns; CountStatistic) (PMI: J2C: j2cModule.numManagedConnectionsReleased; CountStatistic) (PMI: Thread pool: Set to 0)	B (9,0)
WPACT	Active Count. The number of active connections or threads at the time the data was sampled. (PMI: JDBC: Calculate from Allocates>Returns; CountStatistic) (PMI: J2C: Calculate from Allocates>Returns; CountStatistic) (PMI: Thread pool: threadPoolModule.activeThreads; RangeStatistic)	B (9,0)

Field Name	Description	Attribute
WPWAITTM	Wait Time. The total accumulated time during the interval in milliseconds spent waiting until a connection is granted. Does not apply to thread pool. (PMI: JDBC: connectionPoolModule.avgWaitTime; TimeStatistic) (PMI: J2C: j2cModule.avgWait; TimeStatistic) (PMI: Thread pool: Set to 0)	B (18,0)
WPUSETM	Use Time. The total accumulated time during the interval in milliseconds during which a JDBC connection is used. Does not apply to J2C or thread pools. (PMI: JDBC: connectionPoolModule.avgUseTime; TimeStatistic) (PMI: J2C: j2cModule.useTime; TimeStatistic) (PMI: Thread: Set to 0)	B (18,0)
WPCONN	Number of managed connections. The total number of managed connections in use during the interval for JDBC and J2C pools. Does not apply to thread pool. (PMI: JDBC: connectionPoolModule.numManagedConnections; CountStatistic) (PMI: J2C: j2cModule.numManagedConnections; CountStatistic) (PMI: Thread: Set to 0)	B (9,0)
WPSMTD	Prepared statement discards. The total number of statements discarded by the least recently used (LRU) algorithm of the statement cache during the interval. Does not apply to J2C or thread pools. (PMI: JDBC: connectionPoolModule.prepStmtCacheDiscards; CountStatistic) (PMI: J2C: Set to 0) (PMI: Thread: Set to 0)	B (9,0)
WPJDBC	JDBC Time. The total accumulated time in milliseconds spent running in the JDBC driver during the interval. This includes time spent in the JDBC driver, network, and database (apply to 5.0 DataSource only). Does not apply to J2C or thread pools. (PMI: JDBC: connectionPoolModule.jdbcOperationTimer; TimeStatistic) (PMI: J2C: Set to 0) (PMI: Thread: Set to 0)	B (9,0)

Field Name	Description	Attribute
WPWAIT	Current Waiters. The number of JDBC or J2C threads that are waiting for a connection at the time the data was sampled. Does not apply to thread pool. (PMI: JDBC: connectionPoolModule.concurrentWaiters; RangeStatistic) (PMI: J2C: j2cModule.concurrentWaiters) (PMI: Thread: Set to 0)	B (9,0)
WPPCTU	Percent Used. The current average percent of the JDBC or J2C pool that is in use at the time the data was sampled. Does not apply to thread pool. (PMI: JDBC: connectionPoolModule.percentUsed; RangeStatistic) (PMI: J2C: j2cModule.percentUsed; RangeStatistic) (PMI: Thread: Set to 0)	B (5,0)
WPPCTM	Percent maxed. The current average percent of the time that all connections are in use at the time the data was sampled. (PMI: JDBC: connectionPoolModule.percentMaxed; RangeStatistic) (PMI: J2C: j2cModule.percentMaxed; RangeStatistic) (PMI: Thread: threadPoolModule.percentMaxed)	B (5,0)
WPTC	Thread count. The average number of connections or threads in the pool at the time the data was sampled. (PMI: JDBC: connectionPoolModule.poolSize; BoundedRangeStatistic) (PMI: J2C: j2cModule.freePoolSize) (PMI: Thread: threadPoolModule.poolSize; BoundedRangeStatistic)	B (9,0)
WPTHHS	Thread hangs started. The total number of threads declared hung during the interval. Does not apply to JDBC or J2C pools. (PMI: JDBC: Set to 0) (PMI: J2C: Set to 0) (PMI: Thread: threadPoolModule.declaredThreadHung; CountStatistic)	B (9,0)
WPTHE	Thread hangs ended. The total number of thread hangs cleared during the interval. Does not apply to JDBC or J2C pools. (PMI: JDBC: Set to 0) (PMI: J2C: Set to 0) (PMI: Thread: threadPoolModule.declaredThreadHangCleared; CountStatistic)	B (9,0)

Field Name	Description	Attribute
WPCTH	Current thread hangs. The number of hung threads at the time the data was sampled. Does not apply to JDBC or J2C pools. (PMI: JDBC: Set to 0) (PMI: J2C: Set to 0) (PMI: Thread: threadPoolModule.concurrentlyHungThreads; RangeStatistic)	B (9,0)
WPRES1	Reserved.	B (9,0)
WPRES2	Reserved.	B (9,0)
WPRES3	Reserved.	B (9,0)
WPRES4	Reserved.	B (9,0)
WPRES5	Reserved.	B (18,0)
WPRES6	Reserved.	B (18,0)
DATETIME	Interval date and time: The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp

Related reference

[WebSphere JDBC connection pool counters](#) See WebSphere JDBC connection pool counters for more information about WebSphere JDBC connection pool counters data.

[WebSphere J2C connection pool counters](#) See WebSphere J2C connection pool counters for more information about WebSphere J2C connection pool counters data.

[WebSphere thread pool counters](#) See WebSphere thread pool counters for more information about WebSphere thread pool counters data.

[Collection Services data files: System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

[Data files: File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

[Create Performance Data \(CRTPFRDTA\) command](#) See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMWASSVR

This data includes information about the server jobs running on the IBM WebSphere Application Server.

It contains one record for each server job per interval. Much of the data comes from WebSphere Performance Monitoring Infrastructure (PMI) data and transaction counters. Where PMI data is used directly, the name of the PMI field is provided.

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)

Field Name	Description	Attribute
DTETIM	Interval date (<i>yymddd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
DTECEN	Century digit. 0 indicates 19XX and 1 indicates 20XX.	C (1)
WSDTIM	Date and time data was collected (<i>YYYYMMDDhhmmss</i>).	C (14)
WSNAME	Job name of server job.	C (10)
WSUSER	User name of server job.	C (10)
WSNBR	Job number of server job.	C (6)
WSJKEY	Server job key.	H (16)
WSIHP	Initial heap size in bytes.	B (18,0)
WSMHP	Maximum heap size in bytes. 0 = *NOMAX	B (18,0)
WSUMEM	Amount of memory used by the JVM in bytes at the time the data was sampled. (PMI: <code>jvmRuntimeModule.usedMemory</code> ; <code>CountStatistic</code>)	B (18,0)
WSTMEM	Total memory in the JVM runtime in bytes at the time the data was sampled. (PMI: <code>jvmRuntimeModule.totalMemory</code> ; <code>BoundedRangeStatistic</code>)	B (18,0)
WSMMEM	Maximum observed total memory in the JVM runtime in bytes (over the life of the server job) at the time the data was sampled. (PMI: <code>jvmRuntimeModule.totalMemory</code> ; <code>BoundedRangeStatistic</code>)	B (18,0)
WSNHMU	Reserved	B (18,0)
WSNHMC	Reserved	B (18,0)
WSUPTM	Up time. The amount of time that the JVM was running in milliseconds during the interval. (PMI: <code>jvmRuntimeModule.upTime</code> ; <code>CountStatistic</code>)	B (9,0)
WSGBG	Global transactions begun. The total number of global transactions started on the server during the interval. (PMI: <code>transactionModule.globalTransBegun</code> ; <code>CountStatistic</code>)	B (9,0)
WSLBG	Local transactions begun. The total number of local transactions started on the server during the interval. (PMI: <code>transactionModule.localTransBegun</code> ; <code>CountStatistic</code>)	B (9,0)

Field Name	Description	Attribute
WSGTRT	Global transaction time. The accumulated time of global transactions in milliseconds during the interval. (PMI: transactionModule.globalTranDuration; TimeStatistic) To calculate time per global transaction: WSGTRT / (WSGCMT + WSGRBK)	B (18,0)
WSLTRT	Local transaction time. The accumulated time of local transactions in milliseconds during the interval. (PMI: transactionModule.localTranDuration; TimeStatistic) To calculate time per local transaction: WSLTRT / (WSLCMT + WSLRBK)	B (18,0)
WSGCMT	Global Transactions Committed. The total number of global transactions committed (completed) (PMI: transactionModule.globalTransCommitted; CountStatistic)	B (9,0)
WSLCMT	Local Transactions Committed. The total number of local transactions committed (completed) during the interval. (PMI: transactionModule.globalTransCommitted; ContStatistic)	B (9,0)
WSGRBK	Global Transactions Rolled Back. The total number of global transactions rolled back during the interval. (PMI: transactionModule.globalTransRolledBack; CountStatistic)	B (9,0)
WSLRBK	Local Transactions Rolled Back. The total number of local transactions rolled back during the interval. (PMI: transactionModule.globalTransRolledBack; CountStatistic)	B (9,0)
WSGTMO	Global Transactions Timed Out. The total number of global transactions timed out during the interval. (PMI: transactionModule.globalTransTimeout; CountStatistic)	B (9,0)
WSLTMO	Local Transactions Timed Out. The total number of local transactions timed out during the interval. (PMI: transactionModule.localTransTimeout; CountStatistic)	B (9,0)
WSGCC	Garbage collection count. Number of garbage collection events during the interval. JDK 5.0 only. (GarbageCollectorMXBean.getCollectionCount())	B (18,0)
WSGCT	Garbage collection time. The accumulated time of garbage collection events in milliseconds during the interval. JDK 5.0 only. (GarbageCollectorMXBean.getCollectionTime())	B (18,0)
WSRES1	Reserved.	B (9,0)

Field Name	Description	Attribute
WSRES2	Reserved.	B (9,0)
WSRES3	Reserved.	B (9,0)
WSRES4	Reserved.	B (9,0)
WSRES5	Reserved.	B (18,0)
WSRES6	Reserved.	B (18,0)
DATETIME	Interval date and time: The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time: The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp

Related reference

[WebSphere JVM data counters](#) See WebSphere JVM data counters for more information about WebSphere JVM data counters data.

[WebSphere transaction counters](#) See WebSphere transaction counters for more information about WebSphere transaction counters data.

[Collection Services data files: System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

[Data files: File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

[Create Performance Data \(CRTPFRDTA\) command](#) See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: QAPMX25

This database file includes X.25 file entries and lists the fields in the X.25 file.

The label designations for the field names are as follows:

- XH prefix in the label refers to HDLC counters
- XL refers to X.25 logical link control (LLC) counters
- XP refers to packet level control (PLC) counters

Field Name	Description	Attribute
INTNUM	Interval number: The nth sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command	PD (5,0)
DTETIM	Interval date (<i>yymmdd</i>) and time (<i>hhmmss</i>): The date and time of the sample interval, expressed in local system time.	C (12)
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
IOPRN	IOP resource name.	C(10)
XIOPID	Reserved.	C(1)
XITYPE	The resource type of the IOP or adapter represented by this record.	C (4)

Field Name	Description	Attribute
XLLND	Line description: The name of the description for this line.	C (10)
XLLSP	Line speed: The speed of this line in bits per second (bps).	PD (11,0)
XHBTRN	Bytes transmitted: The number of bytes transmitted, including bytes transmitted again.	PD (11,0)
XHBRCV	Bytes received: The number of bytes received, including all bytes in frames that had any kind of error.	PD (11,0)
XHPRCL	Protocol type: X for X.25.	C (1)
XHFTRN	Frames transmitted: The number of frames transmitted (I, supervisory, and frames not numbered), excluding frames transmitted again.	PD (11,0)
XHIFTR	I-frames transmitted: The number of I-frames transmitted, excluding I-frames transmitted again.	PD (11,0)
XHIFRT	I-frames transmitted again: The number of I-frames transmitted again.	PD (11,0)
XHFRT	Frames transmitted again: The number of I, supervisory, and frames not numbered transmitted again.	PD (11,0)
XHEFFR	Error-free frames received: The number of I, supervisory, and frames not numbered received without error (whether or not they were transmitted again from the remote side).	PD (11,0)
XHEFIR	Error-free I-frames received: The number of I-frames received without error (whether or not they were transmitted again from the remote side).	PD (11,0)
XHFRIE	Frames received in error: The number of I, supervisory, and frames not numbered received in error. There are three error possibilities: (1) a supervisory or I-frame was received with an Nr count that is requesting retransmission of a frame, (2) an I-frame was received with an Ns count that indicates that frames were missed, (3) a frame was received with one of the following errors: a frame check sequence error, an abnormal end, a receive overrun or a frame truncated error.	PD (11,0)
XHIFR	Frames received that are not valid: The number of not valid frames received. These are frames received with either: (1) a short frame error-frame is less than 32 bits, or (2) a residue error-frame is not on a byte boundary.	PD (11,0)
XHRRFT	Number of receive ready supervisory frames transmitted.	PD (11,0)
XHRRFR	Number of receive ready supervisory frames received.	PD (11,0)

Field Name	Description	Attribute
XHRNRT	Number of receive-not-ready supervisory frames transmitted.	PD (11,0)
XHRNRR	Number of receive-not-ready supervisory frames received.	PD (11,0)
XHLNKR	Link resets: The number of times when a set normal response mode (SNRM) was received when the station was already in normal response mode.	PD (11,0)
XLITR	Interface protocol data units transmitted (LLC level).	PD (11,0)
XLIRC	Interface protocol data units received.	PD (11,0)
XLIRT	Interface protocol data units transmitted again.	PD (11,0)
XLIRE	Interface protocol data units received in error (checksum).	PD (11,0)
XLLXTR	Number of XIDs transmitted.	PD (11,0)
XLXRC	Number of XIDs received.	PD (11,0)
XLTT	Number of tests transmitted.	PD (11,0)
XLTR	Number of tests received.	PD (11,0)
XLLJT	Number of LLC rejects transmitted.	PD (11,0)
XLLJR	Number of LLC rejects received.	PD (11,0)
XLRLD	Number of received LLC protocol data units discarded.	PD (11,0)
XLTO	Number of time-outs.	PD (11,0)
XLCED	Checksum errors detected.	PD (11,0)
XLSRA	Successful recovery attempts.	PD (11,0)
XLRA	Recovery attempts.	PD (11,0)
XLRSI	Number of reset indications from packet-link control.	PD (11,0)
XLCLS	Number of close station indications from packet-link control.	PD (11,0)
XLRNR	LLC receive-not-ready frames received.	PD (11,0)
XPTPT	Total packets transmitted.	PD (11,0)
XPTPR	Total packets received.	PD (11,0)
XPDPPT	Data packets transmitted.	PD (11,0)
XPDPPT	Data packets received.	PD (11,0)
XPRPT	Reset packets transmitted.	PD (11,0)
XPROR	Reset packets received.	PD (11,0)
XPRNR	Receive-not-ready packets received.	PD (11,0)
XHPORT	Reserved.	C (10)

Related reference

[Collection Services data files: System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

[Data files: File abbreviations](#)

The database files use abbreviations in the field and byte data tables.

[Create Performance Data \(CRTPFRDTA\) command](#) See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services data files: Field data for configuration database files

Configuration data is collected once per session. You can find the QAPMCONF, QAPMHDWR, and QAPMSBSD files in the configuration data files.

The following performance data files show the file names, brief descriptions, and references to field data detail (when provided) for the system configuration data, subsystem data, and hardware configuration data.

Field Name	Description
QAPMCONF	System configuration data.
QAPMHDWR	System hardware configuration.
QAPMSBSD	Subsystem data. No field and byte data.

Related concepts

[Collection Services](#) Use Collection Services to collect performance data for later analysis.

Related reference

[Collection Services data files: System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Collection Services data files: QAPMCONF

This database file contains general information about the collection.

QAPMCONF includes information about collection options, characteristics of the database files generated, and information about the system on which the data was collected. One record is written to this file for each item reported (see the GKEY field). This file is not optional. Data in this file is generated for every database collection. This data is reported only at the beginning of the collection. Although most of the data in this file does not change during the collection, some data might change. Changes are not reported.

The GKEY fields B1-B5 apply to the disk response time bucket data in the QAPMDISK file. The GKEY fields G1-GA apply to the disk response time bucket data in the QAPMDISKRB file.

GRES

Reserved.

Attributes: C (4)

GKEY

Identifier to indicate what data is contained in the GDES field. See descriptions in the following table.

Attributes: C (2)

GDES

Data for the associated GKEY value. See values in the following table. Unless otherwise noted, all system values pertain to the partition for which the data was collected. Unless otherwise indicated, all the data is left-aligned in this field.

Attributes: C (10)

GKEY	GDES
1	Performance data start date, expressed in local system time. Date is reported as a C(7) value with the following format: (yymmddc).
2	Performance data start time, expressed in local system time. Time is reported as a C(6) value with the following format: (hhmmss).
3	A 4-character model number followed by a 4-character system type.
4	Memory for the partition (zoned (10,0)) in KB (kilobytes).
5	Communications data is collected, which is set to Y only if any communication files were created.
6	Machine serial number (character 10).
7	First response time boundary (zoned (10,0)) in milliseconds. The first response time monitor bracket is from 0 up to and including the first response time boundary.
8	Second response time boundary (zoned (10,0)) in milliseconds. The second response time monitor bracket is from the first response time boundary up to and including the second response time boundary.
9	Third response time boundary (zoned (10,0)) in milliseconds. The third response time monitor bracket is from the second response time boundary up to and including the third response time boundary.
10	Fourth response time boundary (zoned (10,0)) in milliseconds. The fourth response time monitor bracket is from the third response time boundary up to and including the fourth response time boundary. Responses greater than the fourth response time boundary fall under the fifth response time monitor bracket.
11	System ASP capacity (zoned (10,0)) in KB (kilobytes). This value is the total amount of auxiliary storage allocated to the system ASP for the storage of data in KB. If this field is set to the largest number it can hold (9999999999), the system ASP capacity is too large to fit in this record. Use the record with GKEY 21 instead.
12	Checksum protection on (Y/N).
13	Number of virtual processors assigned to the partition (PD (3,0)) followed by the installed physical processor count (2-byte binary) followed by the active physical processor count (2 byte binary). <i>Virtual Processors:</i> For uncapped partitions, the number of virtual processors that are assigned to the partition establishes the maximum amount of physical processor resources that can be used by the partition. For capped partitions, the maximum amount of physical processor resources that the partition can use is limited by the number of processing units assigned, regardless of the number of virtual processors assigned. <i>Installed physical processors:</i> The maximum number of physical processors that could be active in the physical machine without installing additional processors. This number includes the number of permanently activated processors, the number of temporarily activated processors, and the number of any standby processors that might be present in the physical machine that are not activated. <i>Active physical processors:</i> The number of physical processors in the physical machine that are permanently or temporarily activated.
14	First remote response time boundary (zoned (10,0)) in milliseconds. The first response time monitor bracket is from 0 up to and including the first response time boundary. This data appears only when requested with the Start Performance Monitor (STRPFRMON) command.

GKEY	GDES
15	Second remote response time boundary (zoned (10,0)) in milliseconds. The second response time monitor bracket is from the first response time boundary up to and including the second response time boundary. This data appears only when requested with the Start Performance Monitor (STRPFRMON) command.
16	Third remote response time boundary (zoned (10,0)) in milliseconds. The third response time monitor bracket is from the second response time boundary up to and including the third response time boundary. This data appears only when requested with the STRPFRMON command.
17	Fourth remote response time boundary (zoned (10,0)) in milliseconds. The fourth response time monitor bracket is from the third response time boundary up to and including the fourth response time boundary. Responses greater than the fourth response time boundary fall under the fifth response time monitor bracket. This data appears only when requested with the STRPFRMON command.
21	System ASP capacity in KB (kilobytes). This value is the total amount of auxiliary storage allocated to the system ASP for the storage of data in KB. This number is reported as an unsigned 8-byte binary value.
AP	Permanent 16 MB addresses that remain for the machine. This address is reported as an unsigned 8-byte binary value.
AT	Temporary 16 MB addresses that remain for the machine. This address is reported as an unsigned 8-byte binary value.
B1	The first disk response time boundary in milliseconds (B(9,0)). The first disk response time bucket is from 0 up to the first response time boundary.
B2	The second disk response time boundary in milliseconds ((B(9,0)). The second disk response time bucket is from and including the first response time boundary up to the second boundary.
B3	The third disk response time boundary in milliseconds ((B(9,0)). The third disk response time bucket is from and including the second response time boundary up to the third boundary.
B4	The fourth disk response time boundary in milliseconds ((B(9,0)). The fourth disk response time bucket is from and including the third response time boundary up to the fourth boundary.
B5	The fifth disk response time boundary in milliseconds ((B(9,0)). The fifth disk response time bucket is from and including the fourth response time boundary up to the fifth boundary. The sixth disk response time bucket includes everything above and including the fifth response time boundary.
CD	Collection data. Possible values are: <ul style="list-style-type: none"> • 0: This collection is consistent with files that are created by the traditional performance monitor *SYS collection. • 1: Collection data is not *SYS. The database files that are generated from the collection might not be sufficient for applications (such as Performance Tools reports or PM for Power Systems) that depend on traditional performance monitor data.
CI	Collect internal data (Y/N).
CL	Collection library. The name of the library in which the management collection object resides.
CN	Collection name. The name of the management collection object.

GKEY	GDES
CP	Partition is allowed to collect performance data across partitions flag CHAR(1). Possible values are: <ul style="list-style-type: none"> '0': The partition is not allowed to collect performance data across partitions. '1': The partition is allowed to collect performance data across partitions.
CT	Collection Type. Indicates the type of database file collection (how this database file collection was created). Possible values are: <ul style="list-style-type: none"> '*STANDARD ' - Standard collection created by the CRTPFRTA system job '*SYSMON ' - System Monitor collection created by the CRTPFRTA2 system job '*USER ' - Collection created by a non-system use of CRTPFRTA command
DB	Database consistency. Possible values are: <ul style="list-style-type: none"> 0: No problem detected in database files. 1: Due to the interval size selected or to inconsistent collection intervals, the database files that are generated might contain missing intervals or other inconsistencies that might cause problems for applications that depend on traditional performance monitor data.
DL	Database limit is a B(4,1) value that is the percent of the total system CPU. For example, 125 means 12.5%.
DM	On demand memory information. The total amount of on demand memory in gigabytes (GB) that exists on the machine (4-byte binary) followed by the amount of on demand memory in gigabytes (GB) still available to be allocated (4-byte binary). Memory that is activated by permanent, temporary, or metered capacity upgrades is not considered available. This record appears only on systems with on demand memory.
DP	Capacity on demand processor information. The maximum capacity on demand physical processor count (2-byte binary) followed by the capacity on demand processors available count (2-byte binary). This record appears only on systems with on demand processors. <p><i>Maximum Capacity on Demand Physical Processors:</i> The maximum number of physical processors the physical machine could have if it were fully configured. This number includes both the number of <i>installed physical processors</i> (see GKEY 13) and the number of processors that would still need to be physically installed.</p> <p><i>Capacity on Demand Processors Available:</i> The number of physical processors that are available for purchase. This number includes both the number of <i>installed physical processors</i> (see GKEY 13) and the number of processors that would still need to be physically installed. Processors that are activated by permanent, temporary, or metered capacity upgrades are not considered available.</p>
DT	Database threshold is a B(4,1) value that is the percent of the total system CPU. For example, 125 means 12.5%.
ED	End date. The date associated with the last interval in the collection, expressed in local system time. This date is reported as a left-aligned CHAR(7) field. It appears in the following format: CYYMMDD.

GKEY	GDES
ET	<p>End time. The time associated with the last interval in the collection, expressed in local system time. This time is reported as a left-aligned CHAR(6) field. It appears in the following format: HHMMSS.</p> <p>Note: The following is a description of the contents of the End date and End time fields for both active and nonactive collections.</p> <ul style="list-style-type: none"> • For a nonactive collection, the date/time come from the last interval that exists in the management collection object. • For an *ACTIVE collection, the date/time come from the last interval that was processed by CRTPFRTA.
F	File level (PD(2,0)). This value specifies the level of the performance database files. The value is changed each time the format of any of the performance database files change.
FC	Processor feature code (character 4).
FI	Interactive feature (character 4). The Interactive feature field is blank for servers that have no interactive features.
FL	System firmware level CHAR(7).
FP	Processor feature (character 4).
FT	<p>Partition processor firmware time attribute. A 1-byte character field that indicates whether the partition accumulates processor firmware time.</p> <ul style="list-style-type: none"> • '0' - partition does not accumulate processor firmware time • '1' - partition accumulates processor firmware time
F1	<p>Threshold values used to control reporting of tasks and secondary threads that have short lifespans. Data format is an unsigned 4-byte binary task threshold followed by an unsigned 4-byte binary secondary thread threshold. Thresholds are reported in milliseconds.</p> <p>Tasks and secondary threads whose lifespan is shorter than the reporting threshold are not individually collected in the *JOBMI category data. Instead one entry per resource affinity domain is accumulated for tasks that are running in that resource affinity domain and one entry per job is accumulated for secondary threads of that job. See QAPMJOBMI field JBSLTCNT.</p> <p>The short lifespan thresholds that are used during data collection can be overridden by using system environment variables that specify the reporting threshold (number of milliseconds) to use. The following example causes data for all tasks and secondary threads to be individually collected:</p> <pre>ADDENVVAR ENVVAR(QPM_TASK_SL_THRESHOLD) VALUE(0) LEVEL(*SYS) ADDENVVAR ENVVAR(QPM_THREAD_SL_THRESHOLD) VALUE(0) LEVEL(*SYS)</pre>
G1	The first disk response time boundary in microseconds (B(9,0)). The first disk response time bucket is from 0 up to the first response time boundary.
G2	The second disk response time boundary in microseconds (B(9,0)). The second disk response time bucket is from and including the first response time boundary up to the second boundary.
G3	The third disk response time boundary in microseconds (B(9,0)). The third disk response time bucket is from and including the second response time boundary up to the third boundary.

GKEY	GDES
G4	The fourth disk response time boundary in microseconds (B(9,0)). The fourth disk response time bucket is from and including the third response time boundary up to the fourth boundary.
G5	The fifth disk response time boundary in microseconds (B(9,0)). The fifth disk response time bucket is from and including the fourth response time boundary up to the fifth boundary.
G6	The sixth disk response time boundary in microseconds (B(9,0)). The sixth disk response time bucket is from and including the fifth response time boundary up to the sixth boundary.
G7	The seventh disk response time boundary in microseconds (B(9,0)). The seventh disk response time bucket is from and including the sixth response time boundary up to the seventh boundary.
G8	The eighth disk response time boundary in microseconds (B(9,0)). The eighth disk response time bucket is from and including the seventh response time boundary up to the eighth boundary.
G9	The ninth disk response time boundary in microseconds (B(9,0)). The ninth disk response time bucket is from and including the eighth response time boundary up to the ninth boundary.
GA	The tenth disk response time boundary in microseconds (B(9,0)). The tenth disk response time bucket is from and including the ninth response time boundary up to the tenth boundary. The eleventh disk response time bucket includes everything above and including the tenth response time boundary.
HM	Hypervisor memory. This value is the total amount of memory, in megabytes, used by the hypervisor. This memory is physical machine memory and is not associated with the partition's memory allocation. The amount of memory is determined by the number of partitions and attributes of each partition. The value is reported as an unsigned 4-byte binary.
HT	SMT hardware threads. The current maximum number of SMT hardware threads on this IPL. Reported as a 2-byte binary field. '0' - no maximum.
I	Interval (PD(2,0)). The time interval (in minutes) between each collection of system performance data.
IL	Interactive limit as a percent of the configured processor units (see Processor units allocated to the partition (PU)). The value is reported in two different formats: a 2-byte binary B(4,1) value followed by a 4-byte binary B(5,2) value. For example, in the second format, a value of 1250 means 12.50%. For the most accurate data, use the second value.
IS	Interval seconds (PD(4,0)). The time interval (in seconds) between each collection of system performance data.
IT	Interactive threshold as a percent of the configured processor units (see Processor units allocated to the partition (PU)). The value is reported in two different formats: a 2-byte binary B(4,1) value followed by a 4-byte binary B(5,2) value. For example, in the second format, a value of 1250 means 12.50%. For the most accurate data, use the second value.

GKEY	GDES
MT	Processor multitasking. A 1-byte character field that indicates the multitasking capability for the current IPL. <ul style="list-style-type: none"> • '0' - Processor multitasking capability is disabled. • '1' - Processor multitasking capability is enabled. • '2' - Processor multitasking capability is system controlled.
NF	Processor nominal frequency in MHz (4-byte binary).
OS	Output file system (character 8). This value represents the system where the database files are generated.
PC	Partition count. The value is reported in two different formats: a zoned (2,0) value that is capped at 99 followed by an unsigned 4-byte binary value. For the most accurate data, use the second value.
PF	Processor folding support. A 1-byte character field that indicates whether processor folding is supported on the IPL. <ul style="list-style-type: none"> • '0' - Processor folding is not supported • '1' - Processor folding is supported
PN	Partition identifier. The value is reported in two different formats: a character 1 followed by an unsigned 4-byte binary value.
PP	Primary partition. The value is reported in two different formats: a character 1 followed by an unsigned 4-byte binary value.
PU	Processor units allocated to the partition. The value is reported as a 4-byte binary B(5,2). For example, 175 means 1.75 processor units.
R	Version number (PD(2,0)), followed by release number (PD(3,1)).
S	System name (character 8).
SJ	The Select job (SLTJOB) parameter value (character 10). This value may be *ALL or *ACTIVE. This parameter applies to the performance monitor. Collection Services does not use the SJ parameter.
SP	Shared processor/pool attributes. This record contains partition attributes related to shared processor pools. The first item identifies if the partition uses a shared pool. The rest of the data applies if sharing is in effect: <p>Byte 1: CHAR(1) - Processor sharing</p> <ul style="list-style-type: none"> • '0' = Partition does not share physical processors. • '1' = Partition shares physical processors. <p>Byte 2: CHAR(1) - capped/uncapped</p> <ul style="list-style-type: none"> • '0' = Partition is capped. • '1' = Partition is uncapped. <p>Byte 3: CHAR(1) - Identifies if the system supports variable processor speed</p> <ul style="list-style-type: none"> • ' ' = Unknown. • '0' = System does not support variable processor speed. • '1' = System supports variable processor speed.
S1	Value (character 1) of the QPFRADJ system value.
S2	Value (character 1) of the QDYNPTYSCD system value.

GKEY	GDES
S3	Value (character 1) of the QDYNPTYADJ system value.
T	Trace type (character 5). Specifies the type of internal trace that was started with the Start Performance Monitor command (*ALL or *NONE). Collection Services always reports *NONE.
T1	Performance data start date, expressed in local system time. Date is reported as a CHAR(10) value with the following format: (YYYY-MM-DD).
T2	Performance data start time, expressed in local system time. Time is reported as a left-aligned CHAR(8) value with the following format: (HH.MM.SS).
T3	<p>End date. The date associated with the last interval in the collection, expressed in local system time. This date is reported as a CHAR(10) field. It appears in the following format: (YYYY-MM-DD).</p> <p>Note: The following is a description of the contents of the End date and End time fields for both active and nonactive collections.</p> <ul style="list-style-type: none"> • For a nonactive collection, the date/time come from the last interval that exists in the management collection object. • For an *ACTIVE collection, the date/time come from the last interval that was processed by CRTPFRTDA.
T4	End time. The time associated with the last interval in the collection, expressed in local system time. This time is reported as a left-aligned CHAR(8) field. It appears in the following format: (HH.MM.SS).
TY	The Coordinated Universal Time offset. The time difference between the local system time of the collection and Coordinated Universal Time (UTC). The offset is reported as a left-aligned CHAR(5) field in one of the following formats: (0000) or (+HHMM) or (-HHMM). The offset is subtracted from local system time to obtain UTC time.
TZ	Timezone. The name of the time zone description (system value QTIMZON) used to represent local system time of the collection (character 10). This field is set to UNKNOWN for collections where the time zone was unable to be determined, such as data from a prior release that did not support collecting the time zone information.
UP	Partition usage counts. This record is present on systems that support 5770-SS1 feature 5052 (user entitlement key). One metric is returned as a 4-byte binary value: Usage count – the number of named users that are enabled in this partition.
US	<p>System usage counts. This record is present on systems that support 5770-SS1 feature 5052 (user entitlement key). Two metrics are returned as 4-byte binary values:</p> <ul style="list-style-type: none"> • Usage Limit – the number of named users allowed. This limit is system-based not partition based. Accurate reporting depends on license key information that must be entered by the customer on the reporting partition. • Usage count – the number of named users that are enabled in the system. This value is system-based not partition based.
U1	Performance data start date, expressed in Coordinated Universal Time (UTC). Date is reported as a CHAR(10) value with the following format: (YYYY-MM-DD).
U2	Performance data start time, expressed in Coordinated Universal Time (UTC). Time is reported as a CHAR(8) value with the following format: (HH.MM.SS).

GKEY	GDES
U3	<p>End date. The date associated with the last interval in the collection, expressed in Coordinated Universal Time (UTC). This date is reported as a CHAR(10) field. It appears in the following format: (YYYY-MM-DD).</p> <p>Note: The following is a description of the contents of the End date and End time fields for both active and nonactive collections.</p> <ul style="list-style-type: none"> • For a nonactive collection, the date/time come from the last interval that exists in the management collection object. • For an *ACTIVE collection, the date/time come from the last interval that was processed by CRTPFRTA.
U4	<p>End time. The time associated with the last interval in the collection, expressed in Coordinated Universal Time (UTC). This time is reported as a left-aligned CHAR(8) field. It appears in the following format: (HH.MM.SS).</p>
XP	<p>PM Agent data obtained. Indicates whether this collection was processed for PM Agent data requirements. Applies to the originating system only. This field is a 1-byte character field with a value of 1. This record is not present unless PM Agent data was obtained.</p>
XS	<p>Summary data created. Indicates whether summary data was created with this collection. This field is a 1-byte character field with a value of 1. This record is not present unless summary data was created.</p>

Related concepts

[Shared processor pools](#) See the Shared processors topic for information about processors whose processing capacity is shared among multiple logical partitions.

Related reference

[IBM i licensing on IBM system models that offer user entitlements](#) See the IBM i licensing topic for information about feature 5052 (user entitlement key).

Collection Services data files: QAPMHDWR

This file is an output file that is produced by the Display Hardware Resources (DSPHDWRSC) command.

This file contains one record for each hardware component in the partition.

The format of the output file is the same as that of the physical file model, QARZALLF, and its associated record format model, QRZALL.

When Collect Services starts, it issues the [DSPHDWRSC](#) command with the following parameters:

```
DSPHDWRSC TYPE(*AHW) OUTPUT(*OUTFILE)
OUTFILE(myperformance_lib/QAPMHDWR)
OUTMBR(myperformance_mbr *REPLACE)
OUTFILFMT (*type2)
```

myperformance_lib is the library of the output file.

myperformance_mbr is the name of the database file member.

Field Name	Description	Attribute
DORCEN	Century of retrieval: 0=19xx, 1=20xx	C (1)
DORDAT	Date of retrieval: year/month/day	C (6)
DORTIM	Time of retrieval: hour/minute/second	C (6)
DOSNAM	System name	C (8)
DOSTYP	System hardware type	C (4)

Field Name	Description	Attribute
DOSMOD	System model number	C (3)
DOSSER	System serial number	C (10)
DORECF	Record format identifier <ul style="list-style-type: none"> • 0 = *CMN communications resource • 1 = *LWS local work station • 2 = *PRC processor type • 3 = *STG storage resource • 4 = *LAN adapter information • 5 = *CSA coupled adapter resource • 6 = *CRP cryptographic resource 	C (1)
DOSVRM	Operating system level	C (6)
DORSVD	Reserved	C (36)
DORSVF	Reserved	C (2)
DOCRPF	Cryptographic function: 0=No, 1=Yes	C (1)
DOCSAF	Coupled system adapter function: 0=No, 1=Yes	C (1)
DOCMNF	Communications function: 0=No, 1=Yes	C (1)
DOLWSF	Local workstation function: 0=No, 1=Yes	C (1)
DOSTGF	Storage function: 0=No, 1=Yes	C (1)
DOPRCF	Processor function: 0=No, 1=Yes	C (1)
DORLVL	Resource level <p>For *CMN type records:</p> <ul style="list-style-type: none"> • 1 = Input/output processor • 2 = Input/output adapter • 3 = Communications port <p>For *LWS or *STG type records:</p> <ul style="list-style-type: none"> • 1 = Input/output processor • 2 = Controller • 3 = Device <p>For *PRC type records:</p> <ul style="list-style-type: none"> • 0 = Processor unit • 1 = Processor/main storage • 2 = Next level main storage <p>For *CRP type records:</p> <ul style="list-style-type: none"> • 0 = Input/output processor • 1 = Input/output adapter • 2 = Device 	C (1)

Field Name	Description	Attribute
DORDSC	Resource description <ul style="list-style-type: none"> • 00 = Communications processor • 01 = Communications adapter • 02 = Communications port • 03 = Work station controller • 04 = Printer device • 05 = Work station device • 06 = ASCII work station controller • 07 = Work station printer • 08 = Main card enclosure • 09 = Bus extender • 10 = System processor • 11 = Service processor • 12 = Main storage card • 13 = Storage controller • 14 = Tape controller • 15 = Disk storage controller • 16 = Diskette controller • 17 = Tape unit • 18 = Disk unit • 19 = Diskette unit • 20 = Tape input/output processor • 21 = Work station processor • 22 = System control panel • 23 = Next level main storage card • 24 = Combined function IO processor • 25 = MFIO processor • 26 = Virtual controller • 27 = Shared bus expansion adapter • 28 = Bus expansion adapter • 29 = Host bus • 30 = Non-host bus • 31 = Optical controller • 32 = Optical storage unit • 33 = Optical library • 34 = Tape library • 35 = Cryptographic processor • 36 = Cryptographic adapter • 37 = Cryptographic device • 38 = Read cache • 39 = Processor capacity card • 40 = Interactive card • 41 = Device services 	C (2)

Field Name	Description	Attribute
DORNAM	System-defined resource name	C (10)
DORPAR	System-defined previous level resource name	C (10)
DORTYP	Resource type	C (4)
DORMOD	Resource model number	C (3)
DORPRT	Resource part number	C (12)
DORSER	Resource serial number	C (10)
DORDSA	Resource direct select address	C (4)
DORUAA	Resource unit address	C (8)
DORSTS	Resource status <ul style="list-style-type: none"> • 0 = Not detected • 1 = Inoperative • 2 = Not ready • 3 = Operational 	C (1)
DORRID	Resource frame identification	C (2)
DOREIA	Resource EIA location	C (2)
DORCSL	Resource card position	C (3)
DORDSL	Resource device position	C (4)
DOCFGO	Configuration object name	C (10)
DOCFGP	Previous level configuration object name	C (10)

Field Name	Description	Attribute
DOREDS	<p>Resource extended description</p> <p>When resource description (DORDSC) is 00 - Communications processor:</p> <ul style="list-style-type: none"> • 01 = Comm processor • 02 = MFIO processor • 03 = Combined function IO processor • 04 = File server IO processor • 05 = AIX® IO processor <p>When resource description (DORDSC) is 01 - Communications adapter:</p> <ul style="list-style-type: none"> • 01 = Comm adapter • 02 = LAN adapter • 03 = ISDN adapter • 04 = Fax adapter • 05 = Virtual adapter • 06 = File server adapter <p>When resource description (DORDSC) is 02 - Communications port:</p> <ul style="list-style-type: none"> • 01 = Comm port • 02 = ISDN port • 03 = Token-ring port • 04 = Autocall port • 05 = Ethernet port • 06 = V.24 port • 07 = X.21 port • 08 = V.35 port • 09 = V.24 enhanced port • 10 = V.36 port • 11 = FDDI port • 12 = SDDI port • 13 = Fax port • 14 = Wireless connection • 15 = LAN port • 16 = Virtual port • 17 = ATM port 25 Mbps • 18 = ATM port 34 Mbps • 19 = ATM port 45 Mbps • 20 = ATM port 100 Mbps • 21 = ATM port 155 Mbps • 22 = ATM port 622 Mbps 	C (2)
DORSVC	Reserved	C (8)

Field Name	Description	Attribute
DOSYTM	Coupled system name	C (8)
DOSMTP	Coupled system type	C (4)
DOSMDL	Coupled system model	C (3)
DOSSRN	Coupled system serial number	C (10)
DORSVA	Reserved	C (8)
DORKBD	Keyboard country or region code	C (3)
DORCOL	Color-capable display: 0=No, 1=Yes	C (1)
DORSWD	Screen width: 0=Standard, 1=Wide	C (1)
DORIWS	Programmable workstation: 0=No, 1=Yes	C (1)
DORPOR	Port number: 00-06	C (2)
DORSWT	Switch setting: 00-06	C (2)
DORSVL	Reserved	C (8)
DORMSZ	Main storage card capacity in MB	PD (10,0)
DORSVP	Reserved	C (8)
DORAFI	Alternate frame identification	C (4)
DORACP	Alternate card position	C (5)
DORADP	Alternate device position	C (5)
DORTTY	Transport type definition	C (2)
DORTF1	Transport location field 1	C (4)
DORTF2	Transport location field 2	C (4)
DORTF3	Transport location field 3	C (4)
DORTFR	Reserved	C (8)
DORUAT	Unit address type	C (2)
DORUA1	Unit address field 1	C (4)
DORUA2	Unit address field 2	C (4)
DORUA3	Unit address field 3	C (4)
DORUA4	Unit address field 4	C (4)
DORUA5	Unit address field 5	C (4)
PRCFCD	Processor feature code	C (4)
PRCFD	Processor feature	C (4)
PRCIFD	Interactive feature	C (4)
LOCCOD	Location code	C (79)

Related reference

[Collection Services data files: System category and file relationships](#)

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

Data files: File abbreviations

The database files use abbreviations in the field and byte data tables.

Create Performance Data (CRTPFRDTA) command See the Create Performance Data (CRTPFRDTA) command for information on how to create performance database files.

Collection Services database files: Field data for trace database files

Trace data is collected only when you choose to do so. You can find the QAPMDMPT file in the trace data files.

Trace data includes internal system trace data. This is detailed data that you collect to gain additional information about specific jobs and transactions. This type of data should not be collected unless you use the Performance Tools licensed program to analyze it. The system supports the following performance data file when using the Start Performance Trace (STRPFTRC) command.

File Name	Description
QAPMDMPT	System trace data (no field or byte detail).

Collection Services data files: System category and file relationships

When you collect performance data using Collection Services, the data is stored in a management collection (*MGTCOL) object.

The Create Performance Data (CRTPFRDTA) command exports data from that management collection object and then writes the data to the performance data files. Each type of data that can be independently controlled and collected by Collection Services is represented by a data category. Each data category contains or provides data that is written to one or more performance data files. For a database file or member to be created, the category (or group of categories) that the file or member is dependent on must exist and be processed by CRTPFRDTA. The following table identifies the category-to-file relationships. There are three types of relationships.

Relationship	Description
Primary files	These files are related to and generated from the category.
Compatibility files	These files are logical files that join primary files to provide performance database compatibility with the previous file structure. If the system generates all participating files (primary categories), compatibility files are also generated.
Secondary files	These files are related to and contain some data that is derived from data contained in the category or in the primary file. However, they are not controlled by that category.

Users should note the following:

1. The CRTPFRDTA command generates a database file only when that file is a primary file for the selected category.
2. If a primary file is listed for multiple categories, you must select each of those categories to generate the file.
3. If a primary file for one category is listed as a secondary file for another category, you must select the second category to ensure complete information in your generated database file. For example, as shown in the table below, to generate a complete database file for QAPMECL, you must select both *CMNBASE and *CMNSTN.

4. The system generates compatibility files only when it generates all associated primary files.

The following table illustrates the relationships between system categories and performance database files.

Category	Primary files	Compatibility files	Secondary files
*APPN	QAPMAPPN		
*CMNBASE	QAPMASYN QAPMBSC QAPMDDI QAPMECL QAPMETH QAPMETHP QAPMFRLY QAPMHDLC QAPMIDLC QAPMLAPD QAPMPPP QAPMSMCMN QAPMX25		
*CMNSAP	QAPMSAP		
*CMNSTN	QAPMSTND QAPMSTNE QAPMSTNL QAPMSTNY none		QAPMDDI QAPMETH QAPMECL QAPMFRLY QAPMX25
*DISK	QAPMDISK QAPMDISKRB QAPMSMSDK QAPMXSTGV		QAPMSYSTEM
*DOMINO	QAPMDOMINO		
*DPS	QAPMDPS		
*EACACHE	none		QAPMDISK <u>See Note.</u>
*EXTSTG	QAPMXSTGD		
*HDWCFG	QAPMHDWR		
*HTTP	QAPMHTTPB QAPMHTTPD QAPMSMHTTP		
*IOPBASE	QAPMIOPD QAPMLIOP QAPMDIOP QAPMCIOP QAPMMIOP		
*IPCS	QAPMIOPD QAPMTSK		

Category	Primary files	Compatibility files	Secondary files
*JAVA	QAPMJVM		
*JOBMI	QAPMJOBMI QAPMJOBWT QAPMJOBWTD QAPMJOBWTG QAPMJSUM QAPMSMJMI QAPMISUM	QAPMJOBL QAPMSYSL	QAPMSYSTEM
*JOBOS	QAPMJOBOS QAPMJSUM QAPMJOSR QAPMSMJOS QAPMISUM	QAPMJOBL QAPMSYSL	QAPMSYSTEM
*LCLRSP	QAPMRESP		
*LPAR	QAPMLPARH		
*POOL	QAPMPOOLB QAPMSMPOL	QAPMPOOLL	
*POOLTUNE	QAPMPOOLT	QAPMPOOLL	
*RMVSTG	QAPMTAPE		
*SNA	QAPMSNA		
*SNADS	QAPMSNADS		
*SQL	QAPMSQLPC		
*SUBSYSTEM	QAPMSBSD		
*SYSBUS	QAPMBUS QAPMBUSINT		
*SYSCPU	QAPMSYSCPU QAPMSYSPRC QAPMSYSAFN QAPMSYSVP	QAPMSYSL	
*SYSINT	QAPMSYSINT		
*SYSLVL	QAPMSHRMP QAPMSMSYS QAPMSYSTEM QAPMSYSWLC QAPMISUM QAPMJSUM	QAPMSYSL	
*TCPBASE	QAPMTCP		
*TCPIFC	QAPMTCPIFC		
*USRTNS	QAPMUSRTNS		QAPMARMTRT

Category	Primary files	Compatibility files	Secondary files
Note: This category is not selectable by CRTPFRTDA. However, it causes additional data to be reported by the *DISK category.			

Related concepts

Collection Services data files: Field data for configuration database files

Configuration data is collected once per session. You can find the QAPMCONF, QAPMHDWR, and QAPMSBSD files in the configuration data files.

[Collection Services](#) Use Collection Services to collect performance data for later analysis.

Collection Services data files: Task type extender

A task type extender identifies the area of functional support provided by the task.

The task type extender field is used to logically group together tasks that perform similar operations. This field is used primarily for performance monitoring. The table below lists the task type extender as two EBCDIC characters followed by the task type extender description.

Performance tasks ('A' through 'A9')	
Field Name	Description
AP	Performance Collection Services probe
Bus transport tasks ('B' through 'B9')	
Field Name	Description
BB	Transport bus
BC	Transport cluster
BI	Transport SPD IOBU
BL	Transport log
BM	Transport SPD maintenance data
BR	Transport remote storage
BT	Transport twin optical
Client server tasks ('C' through 'C9')	
Field Name	Description
CS	Shared folder
Device Driver Tasks ('D' through 'D9')	
Field Name	Description
DA	Work station IOM
DB	PU2 station IOM
DC	Open station IOM
DD	Ethernet LAN IOM
DE	Bisynchronous 3270 IOM
DF	5294 station IOM
DG	X25 station IOM

Performance tasks ('A' through 'A9')	
Field Name	Description
DI	FDDI IOM
DJ	ISDN IOM
DK	Diskette IOM
DL	IDLC IOM
DO	Optical IOM
DP	PPP data link driver
DR	Cryptography driver
DS	DASD IOM
DT	IOP driver
DU	LAN driver
DV	Virtual terminal LUD IOM
DW	Wireless line IOM
DX	FAX line IOM
DY	Frame relay IOM
DZ	ILAN line IOM
D0	Service processor IOM
D1	Asynchronous station IOM
D2	Asynchronous line IOM
D3	Token-ring IOM
D4	Tape IOM
D5	Work station IOM
D6	Twinax IOM
D7	SDLC line IOM
D8	Bisynchronous IOM
D9	MTAM IOM
Other tasks ('E' through 'E9')	
Field Name	Description
EH	Maintain hardware resource information
EI	Miscellaneous I/O
EL	Error log
ES	Cryptography seed management
EV	Authority management extension verify
Integrated xSeries Server I/O management tasks ('F' through 'F9')	
Field Name	Description

Performance tasks ('A' through 'A9')	
Field Name	Description
F0	Integrated xSeries Server IOM
FP	AIX IOP IOM
FS	Integrated xSeries Server storage management IOM
IPCF tasks ('I' through 'I9')	
Field Name	Description
IR	IPCF router
IS	IPCF server
Streams kernel tasks ('K' through 'K9')	
Field Name	Description
KO	Streams server
Save and restore, load and dump tasks ('L' through 'L9')	
Field Name	Description
LM	Main load and dump
LP	Load and dump pipeline
MSCP tasks ('M' through 'M9')	
Field Name	Description
M0	MSCP
M1	Answer manager
M2	SNAP
Pass-through tasks ('P' through 'P9')	
Field Name	Description
PS	Source display pass-through
PT	Target display pass-through
Resource management task ('R' through 'R9')	
Field Name	Description
RC	Resource management machine data collector
RM	Resource management service
RP	Process
Storage management I/O tasks ('S' through 'S9')	
Field Name	Description
SA	Storage management asynchronous
SD	Storage management DASD server
SP	Page Out
SW	Save while active

Performance tasks ('A' through 'A9')	
Field Name	Description
SX	Expert cache
Database task ('T' through 'T9')	
Field Name	Description
TD	Database server
TX	Transaction management timer
Service function ('V' through 'V9')	
Service Function	Description
Server message block tasks ('W' through 'W9')	
Field Name	Description
WB	NetBIOS on TCP/IP
WS	Server message block
Other tasks ('Z' through 'Z9')	
Field Name	Description
ZF	Byte stream file asynchronous
ZI	Interrupt task class
ZR	Recovery
Advanced/36 tasks ('3' through '39')	
Field Name	Description
3A	Advanced/36 disk
3C	Advanced/36 workstation controller
3I	Advanced/36 diskette
3L	Advanced/36 communications line
3T	Advanced/36 tape
3W	Advanced/36 workstation/printer
36	Advanced/36 emulator main task

Historical data files

Historical performance data is generated from the management collection objects maintained by Collection Services. The **Performance > Graph History** task in IBM Navigator for i can be used to analyze the historical performance data in chart or table form. Use this topic to find the names, descriptions, and attributes of the historical database files.

Historical performance data is data that is collected by Collection Services that is reduced and summarized with the intent of providing data to be kept for a long time. The data is intended to be just a subset of all the original Collection Services collected data.

Collection Services collects performance data into a management collection object (*MGTCOL). If historical data creation is enabled in the Collection Services configuration, then historical data is automatically created for you at Collection Services cycle time. You also can select to create historical data at any time for a selected Collection Services management collection object. The Collection Services

management collection object must contain data that was collected on the same partition and that falls within the retention periods you configured for keeping historical data.

Additional field information, such as number of bytes and buffer position, is available by using the Display File Field Description (DSPFFD) command. For example, type the following command on any command line:

```
DSPFFD file(QSYS/QAPMHCONF)
```

Related concepts

[Collection Services support for historical data](#)

[Graph History](#)

Related tasks

[Creating historical data for Graph History](#)

Related reference

Display File Field Description (DSPFFD) command See the Display File Field Description (DSPFFD) command for information on how to display field information.

Historical data configuration database files

The configuration files contain general information about the historical performance data collection.

Historical data files: QAPMHCONF

This database file contains general information about the historical performance data collection.

One record is written to this file for each Collection Services management collection object that is used to create historical data.

Field Name	Description	Attribute
HCSTART	Historical performance data start date and time, expressed in local system time.	Timestamp
HCEND	Historical performance data end date and time, expressed in local system time.	Timestamp
HCSTARTUTC	Historical performance data start date and time, expressed in Coordinated Universal Time (UTC).	Timestamp
HCENDUTC	Historical performance data end date and time, expressed in Coordinated Universal Time (UTC).	Timestamp
HCINTSEC	Interval seconds. The time interval, in seconds, between each sample of historical data.	PD (7,0)
HCTIMZON	Time zone. The name of the time zone description (system value QTIMZON) used to represent local system time of the collection.	C (10)
HCUTCOFF	Coordinated Universal Time offset. The time difference between the local system time of the collection and Coordinated Universal Time (UTC). The offset is reported in one of the following formats: (0000) or (+HHMM) or (-HHMM). The offset is subtracted from local system time to obtain UTC time.	C (5)
HCFILELVL	File level. The level of the database files. The value is changed each time the format of any of the database files change.	B (9,0)

Field Name	Description	Attribute
HCOSVRM	Operating system VRM. The operating system release of the system where the collection took place.	C (10)
HCCOLLIB	Collection library. The name of the library where the management collection object used to create this set of historical data resides.	C (10)
HCCOLNAME	Collection name. The name of the management collection object that is used to create this set of historical data.	C (10)
HCSYSNAME	Partition name. The name of the partition where the collection took place.	C (8)
HCSYSSRL	System serial number. The serial number of the system where the collection took place.	C (10)
HCSYSTYPE	System type. The machine type of the system where the collection took place.	C (4)
HCSYSMODEL	System model. The model of the system where the collection took place.	C (4)
HCPRCFC	Processor feature code. The processor feature code for the system where the collection took place.	C (4)
HCPHYPRC	Installed physical processors. The maximum number of physical processors that could be active in the physical machine where the collection took place without installing additional processors. This number includes the number of permanently activated processors, the number of temporarily activated processors, and the number of any standby processors that might be present in the physical machine that are not activated.	B (9,0)
HCACTPRC	Active physical processors. The number of physical processors in the physical machine where the collection took place that are permanently or temporarily activated.	B (9,0)
HCVIRTPRC	Virtual processors assigned. For uncapped partitions, the number of virtual processors that are assigned to the partition establishes the maximum amount of physical processor resources that can be used by the partition. For capped partitions, the maximum amount of physical processor resources that the partition can use is limited by the number of processing units assigned, regardless of the number of virtual processors assigned.	B (9,0)

Field Name	Description	Attribute
HCODPRC	Maximum capacity on demand physical processors. The maximum number of physical processors the physical machine where the collection took place could have if it were fully configured. This number includes both the number of processors that are installed on the physical machine and the number of processors that would still need to be physically installed.	B (9,0)
HCODAPRC	Capacity on demand processors available. The number of physical processors that are available for purchase on the physical machine where the collection took place. This number includes both the number of processors that are installed on the physical machine and the number of processors that would still need to be physically installed.	B (9,0)
HCPU	Processor units. The number of processor units that are allocated to the partition where the collection took place.	B (5,2)
HCPRCMT	Processor multitasking flag. Indicates the multitasking capability for the partition where the collection took place. <ul style="list-style-type: none"> • '0' Processor multitasking capability is disabled • '1' Processor multitasking capability is enabled 	C (1)
HCSMT	SMT hardware threads. The maximum number of SMT hardware threads. A value of zero means that there is no maximum.	B (9,0)
HCPRCFOLD	Processor folding flag. Identifies if processor folding was supported on the partition where the collection took place. <ul style="list-style-type: none"> • '0' Processor folding is not supported • '1' Processor folding is supported 	C (1)
HCPRCSHR	Processor sharing flag. Identifies if the partition where the collection took place shares physical processors (in a shared processor pool). <ul style="list-style-type: none"> • '0' Partition does not share physical processors • '1' Partition shares physical processors 	C (1)
HCPRCSHRM	Processor sharing mode. Identifies if the partition where the collection took place is capped or uncapped. <ul style="list-style-type: none"> • '0' Partition is capped • '1' Partition is uncapped 	C (1)

Field Name	Description	Attribute
HCPRCSPED	Partition variable processor speed flag. Identifies if the system where the collection took place supports variable processor speed. <ul style="list-style-type: none"> '0' System does not support variable processor speed '1' System supports variable processor speed 	C (1)
HCSYSASP	System auxiliary storage pool capacity. This value is the total amount of auxiliary storage allocated to the system ASP for the storage of data in KB (kilobytes).	B (18,0)
HCMEM	Partition memory. The amount of memory, in KB (kilobytes), assigned to the partition where the collection took place.	B (18,0)
HCODMEM	Maximum on demand memory. The total amount of on demand memory, in gigabytes (GB), which exists on the system where the collection took place. This field is zero for systems without on demand memory.	B (9,0)
HCODAMEM	On demand memory available. The amount of on demand memory, in gigabytes (GB), still available to be allocated on the system where the collection took place. Memory that is activated by permanent, temporary, or metered capacity upgrades is not considered available. This field is zero for systems without on demand memory.	B (9,0)
HCPFRADJ	Performance adjustment flag. Indicates whether the partition where the collection took place is able to automatically manage the shared memory pools without any user interaction (system value QPFRADJ). <ul style="list-style-type: none"> '0' No adjustment '1' Adjust at IPL '2' Adjust at IPL and automatic adjustment '3' Automatic adjustment 	C (1)
HCFRMLVL	Firmware level. The firmware level of the system where the collection took place.	C (9)

Historical data files: QAPMHBKTD

This database file contains definitions for the counter sets found in files QAPMHMISUM and QAPMHDDISK.

One record is written for each active counter set.

Field Name	Description	Attribute
STIMEUTC	Start date and time. The date and time the counter set started being used, expressed in Coordinated Universal Time (UTC).	Timestamp

Field Name	Description	Attribute
ETIMEUTC	End date and time. The date and time the counter set stopped being used, expressed in Coordinated Universal Time (UTC).	Timestamp
BKTTYE	Counter set type. <ul style="list-style-type: none"> "JW": Job wait buckets "RT": Disk response time bucket boundaries 	C (2)
BKTSEQ	Sequence number. A unique identifier for a set of definitions. <ul style="list-style-type: none"> When BKTTYE = "JW", this value is used to associate the wait data in file QAPMHMISUM with the descriptions from field BKTDESC. When BKTTYE = "RT", this value is used to associate response time bucket data in file QAPMHDDISK with the disk response time boundaries (in microseconds) from field BKTVALU. 	B (4,0)
BKTTOT	Total number of counter sets reported.	B (4,0)
BKTNBR	Counter set number described by this record.	B (4,0)
BKTVALU	Value describing the data reported in this counter	B (18,0)
BKTDESC	Description of the data reported in this counter. Note: This field is in Unicode.	G (50)

Related reference

Historical data files: QAPMHMISUM

This database file reports historical performance data interval summary information.

Historical data files: QAPMHDDISK

This database file reports detailed historical disk performance data (*DISK collection category) collected by Collection Services.

Historical data summary database files

These files contain system level or summarized performance metrics that are useful in identifying trends or detecting changes in a system over a long time.

Historical data files: QAPMHMCMN

This database file reports historical summarized performance metrics from communication protocol data (*CMNBASE collection category) collected by Collection Services.

These metrics are calculated from the detailed data collected by the *CMNBASE collection category in Collection Services. Detailed data for the top contributors can be found in the QAPMHDCOMM file. The breakdown dimension identifies a grouping of lines for which data is provided. One record is written per database interval per breakdown dimension.

Field Name	Description	Attribute
INTNUM	Interval number. The <i>n</i> th sample database interval based on the start time specified in the Create Performance Data (CRTPFRTA) command.	PD (5,0)

Field Name	Description	Attribute
DATETIME	Interval date and time. The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time. The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp
INTSEC	Elapsed interval seconds. The number of seconds since the last sample interval.	PD (7,0)
SMCBDD	Communication protocol breakdown dimension. Identifies which communication protocols were used to calculate the data contained in this record. <ul style="list-style-type: none"> '01' - Line data: (ASYN, BSC, PPP) '02' - LAN data: (ETH) 	C (2)
SMCNUM	Number of communication lines included in this data.	B (9,0)
SMCAUTILP	Average line utilization. The average percent busy for included communication lines.	B (9,2)
SMCABRCV	Average kilobits received. The sum of data kilobits received divided by the number of included lines.	B (18,0)
SMCABSND	Average kilobits sent. The sum of data kilobits sent divided by the number of included lines.	B (18,0)
SMCMUTILP	Maximum line utilization. The percent busy for the line with the highest utilization included within this breakdown dimension.	B (9,2)
SMCMLND	Line description. The name of the description for the line with the highest utilization.	C (10)
SMCB4F01	Reserved.	B (9,0)
SMCB8F01	Reserved.	B (18,0)

Related reference

Historical data files: QAPMHDCOMM

This database file reports detailed historical communication protocol performance data (*CMNBASE collection category) collected by Collection Services.

Historical data files: QAPMHMSDK

This database file reports historical summarized performance metrics from disk data (*DISK collection category) collected by Collection Services.

These metrics are calculated from detailed data collected by the *DISK collection category in Collection Services. Detailed data for the top contributors can be found in the QAPMHDDISK file. The breakdown dimension identifies a grouping of disk units for which data is provided. One record is written per database interval per breakdown dimension.

Field Name	Description	Attribute
INTNUM	Interval number. The <i>n</i> th sample database interval based on the start time specified in the Create Performance Data (CRTPFRTA) command.	PD (5,0)

Field Name	Description	Attribute
DATETIME	Interval date and time. The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time. The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp
INTSEC	Elapsed interval seconds. The number of seconds since the last sample interval.	PD (7,0)
SMDBDD	Disk breakdown dimension. Identifies which disk units were used to calculate the data contained in this record. <ul style="list-style-type: none"> • '01' - All disk units • '02' - Disk units in the system ASP • '03' - Disk units in user ASPs • '04' - Disk units in Independent ASPs 	C (2)
SMDNUM	Number of disk units included in this data.	B (9,0)
SMDABSYP	Average disk busy percent. The disk unit busy percent averaged for the disk units.	B (9,2)
SMDMBSYP	Maximum disk busy percent. The largest single disk unit busy percent for included disk units.	B (9,2)
SMDMBPDRN	Device resource name for the unit with the highest disk busy percent.	C (10)
SMDASTGP	Average disk storage used. The percentage of total disk storage that is in use.	B (9,2)
SMDMSTGP	Maximum disk storage used. The percent of storage that in use for the unit with the highest usage percent.	B (9,2)
SMDMSTGD	Device resource name for the unit with the highest disk storage used.	C (10)
SMDSTGT	Disk storage capacity. The accumulated storage capacity of included disk units in gigabytes (GB).	B (9,0)
SMDSTGU	Disk storage in use. The accumulated storage in use within the included disk units in gigabytes (GB).	B (9,0)
SMDTROPS	Read operations. Accumulated number of read operations for reported disk units.	B (18,0)
SMDTRSPT	Read response time. Accumulated read response time for reported disk units in microseconds.	B (18,0)
SMDTRSRVT	Read service time. Accumulated read service time for reported disk units in microseconds.	B (18,0)
SMDMRRSPT	Maximum read response time. The read response time for the disk unit with highest average read response time in microseconds.	B (18,0)
SMDMRRSPD	Device resource name for the unit with the highest read response time.	C (10)

Field Name	Description	Attribute
SMDTWOPS	Write operations. Accumulated number of write operations for reported disk units.	B (18,0)
SMDTWSRPT	Write response time. Accumulated write response time for reported disk units in microseconds.	B (18,0)
SMDTWSRVT	Write service time. Accumulated write service time for reported disk units in microseconds.	B (18,0)
SMDMWRSPD	Maximum disk write response time. The write response time for the disk unit with highest average write response time in microseconds.	B (18,0)
SMDMWRSPD	Device resource name for the unit with the highest write response time.	C (10)
SMDNBSYP	Minimum disk busy percent. The lowest single disk unit busy percent for included disk units.	B (9,2)
SMDNBPDRN	Device resource name for the unit with the lowest disk busy percent.	C (10)
SMDNSTGP	Minimum disk storage used. The percent of storage that is in use for the unit with the lowest usage percent.	B (9,2)
SMDNSTGD	Device resource name for the unit with the lowest disk storage used.	C (10)
SMDNRRSPT	Minimum read response time. The read response time for the disk unit with the lowest average read response time in microseconds.	B (18,0)
SMDNRRSPD	Device resource name for the unit with the lowest read response time.	C (10)
SMDNWRSPD	Minimum disk write response time. The write response time for the disk unit with the lowest average write response time in microseconds.	B (18,0)
SMDNWRSPD	Device resource name for the unit with the lowest write response time.	C (10)
SMDB4F01	Reserved.	B (9,0)
SMDB4F02	Reserved.	B (9,0)
SMDB8F01	Reserved.	B (18,0)
SMDB8F02	Reserved.	B (18,0)

Related reference

Historical data files: QAPMHDDISK

This database file reports detailed historical disk performance data (*DISK collection category) collected by Collection Services.

Historical data files: QAPMHMISUM

This database file reports historical performance data interval summary information.

Data is only produced in this file when data was collected by Collection Services for all the following categories: *JOBMI, *JOBOS, and *SYSLVL. The wait group descriptions are reported in the QAPMHBKTD file. One record is written per interval.

Field Name	Description	Attribute
INTNUM	Interval number. The <i>n</i> th sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DATETIME	Interval date and time. The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time. The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp
INTSEC	Elapsed interval seconds. The number of seconds since the last sample interval.	PD (7,0)
JWDSEQ	Sequence number. Identifies the QAPMHBKTD records associated with the wait data for this interval.	B (4,0)
JWCT01	Wait count 1. The number of times all jobs encountered wait states that are associated with this group within the interval.	B (9,0)
JWTM01	Wait time 1. The time in microseconds all jobs spent waiting within this group within the interval.	B (18,0)
JWJC01	Contributor count 1. The number of threads or tasks that contributed to this group within the interval. A contributor is defined as a thread or task that had nonzero time for wait states associated with this group within the interval. This number includes threads or tasks that were blocked through the entire interval for this group.	B (9,0)
JBCT02-JWCT32 JWTM02-JWTM32 JWJC02-JWJC32	Counts, times, and contributor counts are repeated for up to 32 counter sets per record.	B (9,0) B (18,0) B (9,0)
JBDBR	Synchronous database reads. Total number of physical synchronous database read operations for database functions for all jobs within the interval.	B (9,0)

Field Name	Description	Attribute
JBNDDB	Synchronous nondatabase reads. Total number of physical synchronous nondatabase read operations for nondatabase functions for all jobs within the interval.	B (9,0)
JBDBW	Synchronous database writes. Total number of physical synchronous database write operations for database functions for all jobs within the interval.	B (9,0)
JBNDW	Synchronous nondatabase writes. Total number of synchronous physical nondatabase write operations for nondatabase functions for all jobs within the interval.	B (9,0)
JBADBR	Asynchronous database reads. Total number of asynchronous physical database read operations for database functions for all jobs within the interval.	B (9,0)
JBANDR	Asynchronous nondatabase reads. Total number of asynchronous physical nondatabase read operations for nondatabase functions for all jobs within the interval.	B (9,0)
JBADBW	Asynchronous database writes. Total number of asynchronous physical database write operations for database functions for all jobs within the interval.	B (9,0)
JBANDW	Asynchronous nondatabase writes. Total number of asynchronous physical nondatabase write operations for nondatabase functions for all jobs within the interval.	B (9,0)
JBCPU	Unscaled CPU time charged. The amount of unscaled processing time (in microseconds) charged to all jobs within the interval.	B (18,0)
JBSCPU	Scaled CPU time charged. The amount of scaled processing time (in microseconds) charged to all jobs within the interval.	B (18,0)
JBTFLT	Page faults. Total page faults for all jobs within the interval.	B (9,0)

Field Name	Description	Attribute
JBIPF	I/O pending faults. Total number of times a page fault occurred on an address that was currently part of an auxiliary storage I/O operation for all jobs within the interval.	B (9,0)
JBSKSC	Socket sends. Total number of socket send operations that were performed by all jobs within the interval.	B (9,0)
JBSKBS	Socket bytes sent. Total number of bytes sent via socket operations by all jobs within in the interval.	B (18,0)
JBSKRC	Socket receives. Total number of socket receive operations that were performed by all jobs within the interval.	B (9,0)
JBSKBR	Socket bytes received. Total number of bytes received via socket operations by all jobs within the interval.	B (18,0)
JBTDECNT	Total threads or tasks. Total number of threads or tasks reported within the interval. This count includes the following threads or tasks: <ul style="list-style-type: none"> • Threads or tasks that terminated during the interval • Transient threads or tasks • Threads or tasks that were active at the end of the interval, whether they were blocked or not 	B (9,0)
JBTDETR	Transient threads or tasks. Total number of transient threads or tasks within the interval. A transient thread or task is defined as a thread or task that started and ended during the interval.	B (9,0)
JBJOBCNT	Total jobs. Total number of jobs reported within the interval. This count includes the following jobs: <ul style="list-style-type: none"> • Jobs that terminated during the interval • Transient jobs • Jobs that were active at the end of the interval 	B (9,0)

Field Name	Description	Attribute
JBJOBTR	Transient jobs. Total number of transient jobs within the interval. A transient job is defined as a job that started and ended during the interval.	B (9,0)
JBRSP	Display (5250) transaction time (in milliseconds) for all interactive jobs within in the interval.	B (18,0)
JBNTR	Number of display (5250) transactions for all interactive jobs within the interval.	B (9,0)
JBLWT	Logical database writes. Total number of times the internal database write function was called by all jobs within the interval. This number does not include I/O operations to readers/writers, or I/O operations caused by the CPYSPLF or DSPSPLF command. If SEQONLY(*YES) is specified, these numbers show each block of records written, not the number of individual records written.	B (9,0)
JBLRD	Logical database reads. Total number of times the database module was called by all jobs within the interval. This number does not include I/O operations to readers/writers, or I/O operations caused by the CPYSPLF or DSPSPLF command. If SEQONLY(*YES) is specified, these numbers show each block of records read, not the number of individual records read.	B (9,0)
JBDBU	Miscellaneous logical database operations. The number of miscellaneous logical database operations (updates, deletes, force-end-of-data, opens, closes, and releases) performed by all jobs within the interval.	B (9,0)
JBBCO	Database commit operations. Total number of database commit operations performed by all jobs within the interval.	B (9,0)

Field Name	Description	Attribute
JBBRO	Database rollback operations. Total number of database rollback operations performed by all jobs within the interval.	B (9,0)
JBLBO	SQL cursor count. Total cumulative number of SQL cursors that were full opened by all jobs within the interval.	B (9,0)
JBLBS	SQL cursor reuse. Total cumulative number of SQL cursors that were pseudo-opened by all jobs within the interval. Pseudo-opens are also known as <i>reused SQL cursors</i> .	B (9,0)
JBNUS	Full opens. The number of native database (non-SQL) files and SQL cursors that were full opened by all jobs within the interval. Subtracting the value within field JBLBO from JBNUS yields the number of non-SQL full opens.	B (9,0)
JBPGA	Total number of 4096-byte units of temporary and permanent storage that was allocated by all jobs within the interval.	B (9,0)
JBPGD	Total number of 4096-byte units of temporary and permanent storage that was deallocated by all jobs within the interval.	B (9,0)
JBTMPPGA	Total number of 4096-byte units of temporary storage that was allocated by all jobs within the interval.	B (9,0)
JBTMPPGD	Total number of 4096-byte units of temporary storage that was deallocated by all jobs within the interval.	B (9,0)
JBSQLDBR	SQL synchronous database reads. Total number of physical synchronous database read operations that were done on behalf of an SQL operation for all jobs within the interval.	B (18,0)
JBSQLNDBR	SQL synchronous nondatabase reads. Total number of physical synchronous nondatabase read operations that were done on behalf of an SQL operation for all jobs within the interval.	B (18,0)

Field Name	Description	Attribute
JBSQLDBW	SQL synchronous database writes. Total number of physical synchronous database write operations that were done on behalf of an SQL operation for all jobs within the interval.	B (18,0)
JBSQLNDBW	SQL synchronous nondatabase writes. Total number of synchronous physical nondatabase write operations that were done on behalf of an SQL operation for all jobs within the interval.	B (18,0)
JBSQLADBR	SQL asynchronous database reads. Total number of asynchronous physical database read operations that were done on behalf of an SQL operation for all jobs within the interval.	B (18,0)
JBSQLANDBR	SQL asynchronous nondatabase reads. Total number of asynchronous physical nondatabase read operations that were done on behalf of an SQL operation for all jobs within the interval.	B (18,0)
JBSQLADBW	SQL asynchronous database writes. Total number of asynchronous physical database write operations that were done on behalf of an SQL operation for all jobs within the interval.	B (18,0)
JBSQLANDBW	Asynchronous nondatabase writes. Total number of asynchronous physical nondatabase write operations that were done on behalf of an SQL operation for all jobs within the interval.	B (18,0)

Field Name	Description	Attribute
JBLWTSQL	<p>SQL related logical database writes. Total number of times the internal database write function was called on behalf of an SQL operation by all jobs within the interval. This number does not include I/O operations to readers/writers, or I/O operations caused by the CPYSPLF or DSPSPLF command. If SEQONLY(*YES) is specified, these numbers show each block of records written, not the number of individual records written.</p> <p>This field can be compared to JBLWT to understand the portion of database writes that are due to SQL activity. Subtracting JBLWTSQL from JBLWT yields the number of non-SQL related database writes.</p>	B (18,0)
JBLRDSQL	<p>SQL-related logical database reads. Total number of times the database module was called on behalf of an SQL operation by all jobs within the interval. This number does not include I/O operations to readers/writers, or I/O operations caused by the CPYSPLF or DSPSPLF command. If SEQONLY(*YES) is specified, these numbers show each block of records read, not the number of individual records read.</p> <p>This field can be compared to JBLRD to understand the portion of database reads that are due to SQL activity. Subtracting JBLRDSQL from JBLRD yields the number of non-SQL related database reads.</p>	B (18,0)

Field Name	Description	Attribute
JBDBUSQL	SQL-related miscellaneous logical database operations. The number of miscellaneous logical database operations (updates, deletes, force-end-of-data, opens, closes, and releases) performed on behalf of an SQL operation by all jobs within the interval. This field can be compared to JBDBU to understand the portion of database miscellaneous operations that are due to SQL activity. Subtracting JBDBUSQL from JBDBU yields the number of non-SQL related database miscellaneous operations.	B (18,0)
JBRSDV1	Reserved.	B (18,0)
JBRSDV2	Reserved.	B (18,0)
JBRSDV3	Reserved.	B (9,0)
JBRSDV4	Reserved.	B (9,0)

Related reference

Historical data files: QAPMHBKTD

This database file contains definitions for the counter sets found in files QAPMHMISUM and QAPMHDDISK.

Historical data files: QAPMHMJMI

This database file reports historical summarized performance metrics from job data (*JOBMI collection category) collected by Collection Services.

These metrics are calculated from detailed data collected by the *JOBMI collection category in Collection Services. Detailed data for the top contributors can be found in the QAPMHDJOBM and QAPMHDJOBO files. The breakdown dimension identifies a grouping of jobs for which data is provided. One record is written per database interval per breakdown dimension.

Field Name	Description	Attribute
INTNUM	Interval number. The <i>n</i> th sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DATETIME	Interval date and time. The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time. The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp
INTSEC	Elapsed interval seconds. The number of seconds since the last sample interval.	PD (7,0)

Field Name	Description	Attribute
SMMBDD	Job breakdown dimension. Identifies which records from QAPMJOBMI were used to calculate the data in this record. <ul style="list-style-type: none"> '01' - Interactive (job type I) jobs (including threads) '02' - Batch (job type B) jobs (including threads) 	C (2)
SMMNUM	Number of entries included in this data.	B (9,0)
SMMTCPUP	CPU used percent. Percent of unscaled CPU time used relative to the configured CPU entitlement of the partition.	B (9,2)
SMMTCPUT	CPU used. Accumulated unscaled CPU time used in microseconds.	B (18,0)
SMMMCPUP	Maximum CPU used percent. The largest amount of unscaled CPU time used relative to the configured CPU entitlement of the partition used by a job.	B (9,2)
SMMMCPUT	Maximum CPU used. The largest amount of unscaled CPU time used in microseconds by a job.	B (18,0)
SMMMCPUJ	Maximum CPU job identifier. The value of JBTDE for the job with the highest CPU usage.	C (8)
SMMMCNAME	Maximum CPU job name. Job name for the job with the highest CPU usage.	C (16)
SMMMCUSER	Maximum CPU job user. Job user for the job with the highest CPU usage.	C (10)
SMMMCNBR	Maximum CPU job number. Job number for the job with the highest CPU usage.	C (6)
SMMB4F01	Reserved.	B (9,0)
SMMB8F01	Reserved.	B (18,0)

Related reference

Historical data files: QAPMHDJOBM

This database file reports detailed historical job and task performance data (*JOBMI collection category) collected by Collection Services.

Historical data files: QAPMHMJOS

This database file reports historical summarized performance metrics from job data (*JOBOS collection category) collected by Collection Services.

These metrics are calculated from detailed data collected by the *JOBOS collection category in Collection Services. Detailed data for the top contributors can be found in the QAPMHDJOBM and QAPMHDJOBO files. One record is written per database interval.

Field Name	Description	Attribute
INTNUM	Interval number. The <i>n</i> th sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)

Field Name	Description	Attribute
DATETIME	Interval date and time. The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time. The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp
INTSEC	Elapsed interval seconds. The number of seconds since the last sample interval.	PD (7,0)
SMOBLIOR	Batch logical IO rate. The average number of logical database read and write operations per second for batch jobs (job type B).	B (9,2)
SMOARSPT	Average interactive response time. The average interactive response time in milliseconds for interactive jobs (job type I).	B (9,0)
SMOMRSPT	Maximum interactive response time. The largest response time in milliseconds for an interactive job (job type I).	B (9,0)
SMOMRSPJ	Maximum interactive response time job identifier. The value of JBTDE for the interactive job (job type I) with the highest interactive response time.	C (8)
SMOMRNAME	Maximum interactive response time job name. Job name for the interactive job (job type I) with the highest interactive response time.	C (10)
SMOMRUSER	Maximum interactive response time job user. Job user for the interactive job (job type I) with the highest interactive response time.	C (10)
SMOMRNBR	Maximum interactive response time job number. Job number for the interactive job (job type I) with the highest interactive response time.	C (6)
SMOITRNR	Interactive transaction rate. The number of transactions per second for interactive jobs (job type I).	B (9,2)
SMOSPLFR	Spooled file creation rate. The number of spooled files created per second.	B (9,2)
SMOMSPLF	Maximum spooled files created. The largest number of spooled files created by a job.	B (9,0)
SMOMSPLFJ	Maximum spooled files created job identifier. The value of JBTDE for the job that created the most spooled files.	C (8)
SMOMSNAME	Maximum spooled files created job name. Job name for the job that created the most spooled files.	C (10)
SMOMSUSER	Maximum spooled files created job user. Job user for the job that created the most spooled files.	C (10)
SMOMSNBR	Maximum spooled files created job number. Job number for the job that created the most spooled files.	C (6)

Field Name	Description	Attribute
SMOB4F01	Reserved.	B (9,0)
SMOB4F02	Reserved.	B (9,0)
SMOB8F01	Reserved.	B (18,0)
SMOB8F02	Reserved.	B (18,0)

Related reference

Historical data files: [QAPMHDJOB0](#)

This database file reports detailed historical job performance data (*JOBOS collection category) collected by Collection Services.

Historical data files: QAPMHMPOL

This database file contains historical summarized performance metrics from pool data (*POOL collection category) collected by Collection Services.

These metrics are calculated from detailed data collected by the *POOL collection category in Collection Services. Detailed data for the top contributors can be found in the QAPMHDPOOL file. One record is written per database interval.

Field Name	Description	Attribute
INTNUM	Interval number. The <i>n</i> th sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DATETIME	Interval date and time. The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time. The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp
INTSEC	Elapsed interval seconds. The number of seconds since the last sample interval.	PD (7,0)
SMPMFLTR	Machine pool fault rate. The number of faults per second (both database and non-database) in the machine pool.	B (9,0)
SMPUNUM	Number of user pools included in this data.	B (4,0)
SMPUAFLTR	Average user pool fault rate. The average number of faults per second (both database and non-database) per user pool.	B (9,0)
SMPUMFLTR	Maximum user pool fault rate. The number of faults per second (both database and non-database) for the user pool with the highest fault rate.	B (9,0)
SMPUMFLTP	User pool number with the highest fault rate.	B (4,0)
SMPUMFLTPN	User pool name with the highest fault rate.	C (32)
SMPB4F01	Reserved.	B (9,0)
SMPB4F02	Reserved.	B (9,0)

Related reference

Historical data files: [QAPMHDPOOL](#)

This database file reports detailed historical main storage pool performance data (*POOL collection category) collected by Collection Services.

Historical data files: QAPMHMSQLP

This database file reports historical performance data about the SQL Plan Cache collected by the *SQL collection category in Collection Services.

One record is written per interval.

Field Name	Description	Attribute
INTNUM	Interval number. The <i>n</i> th sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DATETIME	Interval date and time. The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time. The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp
INTSEC	Elapsed interval seconds: The number of seconds since the last sample interval.	PD (7,0)
SQCURQRY	Active queries. A snapshot, which is taken at sample time, of the total number of queries currently active.	B (18,0)
SQPCSIZE	Plan cache size. The current size (in megabytes) of the SQL plan cache.	B (18,0)
SQPCTHRESH	Plan cache size threshold. The maximum size (shown as a percentage of the plan cache size limit) that the SQL plan cache is allowed to be before DB2 automatically manages the SQL plan cache and replaces older plans with new plans.	B (18,0)
SQCURMTI	MTIs. A snapshot, which is taken at sample time, of the total number of Maintained Temporary Indexes (MTIs).	B (18,0)
SQPLNBLT	Plans built. The number of plans built during the interval.	B (18,0)
SQMATCH	Plan cache probe matches. The number of times a plan cache probe found a match during the interval.	B (18,0)
SQNOMATCH	Plan cache probe misses. The number of times a plan cache probe was unable to find a match during the interval.	B (18,0)
SQPLNPRUN	Plans pruned. The number of plans that are pruned from the SQL plan cache during the interval due to plan cache size.	B (18,0)
SQPLNRMV	Plans removed. The number of obsolete plans removed from the SQL plan cache during the interval.	B (18,0)
SQOPEN	Query opens. The number of full and pseudo opens that occurred during the interval.	B (18,0)

Field Name	Description	Attribute
SQFOPEN	Query full opens. The number of full opens that occurred during the interval.	B (18,0)
SQFOPENROQ	Query full opens that used cached runtime objects. The number of full opens that occurred during the interval that used both a plan and a cached runtime object from the SQL plan cache.	B (18,0)
SQPOPNHCLS	Queries hard closed. The number of queries that were hard closed during the interval.	B (18,0)
SQMTICRT	MTIs created. The number of Maintained Temporary Indexes (MTIs) created during the interval.	B (18,0)
SQMTIDLT	MTIs deleted. The number of Maintained Temporary Indexes (MTIs) deleted during the interval.	B (18,0)
SQAQPWAKE	AQP interrogations. The number of executing queries checked by Adaptive Query Processing (AQP) during the interval.	B (18,0)
SQAQPRPL	Runtime object replacements by AQP. The number of runtime objects replaced because of Adaptive Query Processing (AQP).	B (18,0)
SQFULLOPT	Full optimizations. The number of full optimizations that occurred during the interval.	B (18,0)
SQREOPT	Reoptimizations with valid plans. The number of reoptimizations that occurred during the interval when valid plans existed.	B (18,0)

Historical data files: QAPMHMSYS

This database file reports historical summarized performance metrics from system data (*SYSLVL collection category) collected by Collection Services.

These metrics are calculated from data collected by the *SYSLVL collection category in Collection Services. One record is written per database interval.

Field Name	Description	Attribute
INTNUM	Interval number. The <i>n</i> th sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DATETIME	Interval date and time. The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time. The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp
INTSEC	Elapsed interval seconds. The number of seconds since the last sample interval.	PD (7,0)

Field Name	Description	Attribute
SMSCPUCPU	Configured CPU percent unscaled. The amount of unscaled system CPU used relative to the configured CPU time (processor units) available to the partition during the interval.	B (9,2)
SMSCPUUPU	Uncapped CPU percent unscaled. The amount of unscaled system CPU used relative to the maximum uncapped CPU time the partition could use based on the smaller of the virtual processors assigned to the partition and the capacity of the shared virtual pool.	B (9,2)
SMSCPUVPU	Virtual CPU percent unscaled. The amount of unscaled system CPU used relative to the number of virtual processors allocated to the partition during the interval.	B (9,2)
SMSCPUCPS	Configured CPU percent scaled. The amount of scaled system CPU used relative to the configured CPU time (processor units) available to the partition during the interval.	B (9,2)
SMSCPUUPS	Uncapped CPU percent scaled. The amount of scaled system CPU used relative to the maximum uncapped CPU time the partition could use based on the smaller of the virtual processors assigned to the partition and the capacity of the shared virtual pool.	B (9,2)
SMSCPUVPS	Virtual CPU percent scaled. The amount of scaled system CPU used relative to the number of virtual processors allocated to the partition during the interval.	B (9,2)
SMSPRCSPDP	Processor speed percent. Processor speed, relative to nominal, shown as a percent (based on the ratio of scaled CPU used to unscaled CPU used). Note: This value might not be accurate at low utilizations.	B (9,2)
SMSVSPP	Virtual shared pool CPU percent. The amount of CPU used in the virtual shared pool by all partitions that use the pool relative to the CPU available within the pool.	B (9,2)
SMSPSPP	Physical shared pool CPU percent. The amount of CPU used in the physical shared pool by all partitions that use the pool relative to the CPU available within the pool.	B (9,2)
SMSTSTGU	Temporary storage used. The total amount of temporary storage (megabytes) in use within the system. This value includes both system and user temporary storage.	B (18,0)
SMSTSTGP	Temporary storage percent. The percent of the system ASP that is in use for temporary storage.	B (9,2)

Field Name	Description	Attribute
SMSCPUQPU	SQL CPU percent unscaled. The amount of unscaled system CPU used to perform work that is done on behalf of SQL operations relative to the configured CPU time (processor units) available to the partition during the interval.	B (9,2)
SMSB4F01	Reserved.	B (9,0)
SMSB4F01	Reserved.	B (9,0)
SMSB8F01	Reserved.	B (18,0)
SMSB8F01	Reserved.	B (18,0)

Related reference

Historical data files: [QAPMHMSYST](#)

This database file reports historical system-wide performance data collected by the *SYSLVL collection category in Collection Services.

Historical data files: QAPMHMSYST

This database file reports historical system-wide performance data collected by the *SYSLVL collection category in Collection Services.

One record is written per interval.

Field Name	Description	Attribute
INTNUM	Interval number. The <i>n</i> th sample database interval based on the start time specified in the Create Performance Data (CRTPFRTA) command.	PD (5,0)
DATETIME	Interval date and time. The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time. The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp
INTSEC	Elapsed interval seconds. The number of seconds since the last sample interval.	PD (7,0)
SYSHRF	Shared processor flag. Indicates whether the partition uses shared processors: ' ' = Unknown '0' = Partition does not share physical processors. '1' = Partition shares physical processors.	C (1)

Field Name	Description	Attribute
SYUCAPF	Partition uncapped flag. Indicates whether the partition capacity is uncapped: '' = Unknown '0' = Partition capacity is capped or this partition does not share physical processors. '1' = Partition capacity is uncapped.	C (1)
SYDONF	Partition donation flag. Indicates whether the partition supports donation of unused processing time to the physical shared processor pool: '' = Unknown '0' = Partition does not support donation of processing time. '1' = Partition supports donation of processing time.	C (1)
SYSASP	System auxiliary storage pool space available. The number of bytes of space on auxiliary storage available for allocation in the system auxiliary storage pool that is not currently assigned to machine interface (MI) objects or internal machine functions.	PD (15,0)
SYPRMW	Permanent data transferred from main storage. The number of 512-byte blocks of permanent data transferred from main storage to the system auxiliary storage pool in auxiliary storage since the last sample.	PD (11,0)
SYSCTA	Total CPU time configured for the partition. Total processing time (in milliseconds) that was configured or guaranteed for this partition. This time is the system processing capacity as determined by processor unit allocations during the interval. Note: For uncapped partitions, the actual CPU used can exceed this value.	PD (11,0)
SYSPTU	CPU time used. Total processing time (in milliseconds) used by the partition.	PD (11,0)

Field Name	Description	Attribute
SYPTHV	Hypervisor CPU time. Amount of CPU time (in milliseconds) used by hypervisor for its internal needs. This time is included in SYSPTU.	B (18,0)
SYPTINT	Interrupt CPU time. Amount of CPU time (in milliseconds) used by operating system for interrupt processing. This time is included in SYSPTU.	B (18,0)
SYPTWS	Waittask time. Amount of CPU time (in milliseconds) used by waittask in SMT mode. This time is not included in SYSPTU.	B (18,0)
SYSUTA	CPU time that could be used by this partition. Total processing time (in milliseconds) that could be used by this partition (adjusted for configuration changes over time). It includes both the guaranteed configured capacity and the shared pool time that was not used by other partitions. For capped and dedicated partitions, or if shared pool data is not available, this time is the same as Uncapped CPU time configured.	PD (11,0)
SYSUTC	Uncapped CPU time configured. The maximum amount of CPU time that this partition is configured (allowed) to use within the shared pool (adjusted for configuration changes over time). This field defines the Minimum of the virtual processors configured and the configured shared pool processors. For capped and dedicated partitions, this time is the same as total CPU time configured for the partition.	PD (11,0)
SYSPLU	Shared pool CPU time used. Total amount of CPU used within the shared pool by all partitions that share the pool. Set to zero if a shared pool is not used or the data is not available.	PD (11,0)

Field Name	Description	Attribute
SYSPLA	Shared pool CPU time available. Total amount of CPU available within the shared pool. This value is determined based on the number of physical processors that are allocated to the pool. Set to zero if a shared pool is not used or the data is not available.	PD (11,0)
SYPPLU	Physical shared pool CPU time used. Total amount of CPU time (in milliseconds) used within the physical shared processor pool by all partitions that share the pool. Set to zero if physical shared pool is not used or the data is not available.	B (18,0)
SYPPLA	Physical shared pool CPU time available. Total amount of CPU time (in milliseconds) available within the physical shared processor pool. This value is determined based on the number of physical processors that are allocated to the pool. Set to zero if physical shared pool is not used or the data is not available. Note: This field reflects CPU time that is donated by the dedicated partitions that are associated with the pool, if these partitions were configured to donate the unused CPU cycles to the pool.	B (18,0)
SYPTDN	Donated CPU time. Amount of CPU time (in milliseconds) donated by this partition to the physical shared processor pool. This time is only reported for dedicated partitions that are configured to donate their unused CPU cycles to physical shared pool.	B (18,0)
SYSSPTU	Scaled CPU time used (milliseconds). On some system models, the processors can operate at different speeds at different times, depending on power consumption or operating temperature. Ratio of SYSSPTU to SYSPTU shows the current processor speed in relation to nominal processor speed.	B (18,0)

Field Name	Description	Attribute
SYPSLPU	Physical shared pool scaled CPU time used. Total amount of scaled CPU time (in milliseconds) used within the physical shared processor pool by all partitions that share the pool. Set to zero if physical shared pool is not used or the data is not available.	B (18,0)
SYVPCAP	Virtual shared pool entitled capacity. The entitled capacity of the partition's current virtual shared processor pool (in units of 1/100 of a physical processor).	B (9,0)
SYVCPU	Virtual processor time configured. The processing time capacity (in milliseconds) visible to the operating system based on the number of virtual processors configured and adjusted for configuration changes over time. This field is similar to SYSUTC except that it is not affected by the shared pool configuration or the capped/uncapped state of the partition. The formula $SYVCPU/(INTSEC*1000)$ yields the average number of virtual processors configured in the interval.	PD (11,0)
SYIFUS	Interactive CPU time used. Total interactive CPU used (in milliseconds).	PD (9,0)
SYIFTE	Interactive CPU time used over threshold. The amount of interactive CPU used (in milliseconds) when it exceeded the interactive CPU threshold.	PD (9,0)
SYIFTA	Interactive CPU time available. The amount of interactive CPU time that was available for use within the partition. This time is the interactive capacity configured for use within the partition (also represented as interactive threshold).	PD (11,0)
SYSQLCPU	Unscaled SQL CPU time used. The amount of unscaled processor time (in microseconds) spent performing work done on behalf of SQL operations.	B (18,0)

Field Name	Description	Attribute
SYSQLSCPU	Scaled SQL CPU time used. The amount of scaled processor time (in microseconds) spent performing work done on behalf of SQL operations.	B (18,0)
SYSDNFE	The number of stream files that were written to, but not forced to permanent storage. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)), and user-defined file systems.	PD (11,0)
SYSDNFO	The number of stream files currently exposed that exceeded the target exposure time. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)), and user-defined file systems.	PD (11,0)
SYSDETET	Exposure time (in milliseconds). The number of milliseconds between the time a stream file is written to and the time the file is forced to permanent storage. This time is a total for all files that were exposed during the interval. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)), and user-defined file systems.	PD (15,0)
SYSDNST	The number of tasks that were running that are forcing stream files to permanent storage. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)), and user-defined file systems.	PD (5,0)

Field Name	Description	Attribute
SYSDFAL	The number of stream files that were exposed and needed to be forced. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)), and user-defined file systems.	PD (11,0)
SYSDFRL	The total number of stream files that were asynchronously forced to permanent storage. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)), and user-defined file systems.	PD (11,0)
SYSDPFD	The number of stream file pages that were asynchronously forced to permanent storage. This count does not include pages that were forced by an fsync operation. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)), and user-defined file systems.	PD (15,0)
SYSDPFF	The number of stream file pages that were explicitly forced to permanent storage as a result of an fsync operation. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)), and user-defined file systems.	PD (15,0)
SYBTAC	The number of asynchronous clear operations performed. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)), and user-defined file systems.	PD (11,0)

Field Name	Description	Attribute
SYBTAP	The number of asynchronous prebring operations that were performed. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)), and user-defined file systems.	PD (11,0)
SYBTAPP	The number of parallel prebring operations that were performed. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)), and user-defined file systems.	PD (11,0)
SYBTAPC	The number of asynchronous create operations that were performed. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)), and user-defined file systems.	PD (11,0)
SYBTAPD	The number of asynchronous delete operations that were performed. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)), and user-defined file systems.	PD (11,0)
SYOSTMP	Current temporary storage allocated for non-database operations by IBM i. A snapshot of the total temporary storage that is allocated for non-database operations across the system, expressed in 4096-byte units.	B (18,0)
SYDBTMP	Current temporary storage allocated for database operations by IBM i. A snapshot of the total temporary storage that is allocated for database operations across the system, expressed in 4096-byte units.	B (18,0)
SYAJOBTMP	Current temporary storage charged to active jobs. A snapshot of the total temporary storage that is charged to active jobs, expressed in 4096-byte units.	B (18,0)

Field Name	Description	Attribute
SYEJOBTMP	Current temporary storage charged to ended jobs. A snapshot of the total temporary storage that is charged to ended jobs, expressed in 4096-byte units.	B (18,0)
SYUSERTMP	Current user temporary storage. A snapshot of the total user temporary storage that is allocated, expressed in 4096-byte units. Only the user temporary storage that is not charged to any job is accounted for here.	B (18,0)

Related reference

Historical data files: QAPMHMSYS

This database file reports historical summarized performance metrics from system data (*SYSVLV collection category) collected by Collection Services.

Historical data detailed database files

These files contain the detailed performance data which system level or summarized performance metrics are derived from and other relevant supplementary data.

This detailed data is used to look deeper into a problem identified by looking at summary historical data. Only the top number of contributors for each metric is stored as historical detailed data, as defined by the value of the historical detailed data filter.

Historical data files: QAPMHDCOMM

This database file reports detailed historical communication protocol performance data (*CMNBASE collection category) collected by Collection Services.

One record is written per line per interval for the top contributors of each metric defined in the QAPMHMCMN historical summary file.

Field Name	Description	Attribute
INTNUM	Interval number. The <i>n</i> th sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DATETIME	Interval date and time. The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time. The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp
INTSEC	Elapsed interval seconds. The number of seconds since the last sample interval.	PD (7,0)

Field Name	Description	Attribute
CMRCL	Protocol type: <ul style="list-style-type: none"> • A: Asynchronous • B: Binary synchronous • P: Point-to-Point (PPP) • T: Ethernet LAN 	C (1)
CMDUP	Duplex state. The duplex state of the line. For some lines, this value might change over time. This field can have the following values: <ul style="list-style-type: none"> • Blank: The duplex state is not known. • F: Full duplex. The line can simultaneously transmit and receive data. • H: Half duplex. The line can either transmit data or receive data, but not simultaneously. 	C (1)
CMLND	Line description. The name of the description for this line.	C (10)
CMLSP	Line speed. The speed of the line in bits per second (bps).	B (18,0)
CMBTRN	Bytes transmitted. The number of bytes transmitted successfully.	B (18,0)
CMBRCV	Bytes received. The number of bytes successfully received.	B (18,0)
CMRCVEF1	The meaning of this field depends on the protocol type (CMRCL). <ul style="list-style-type: none"> • A: Error-free protocol data units received. • B: Error-free data blocks received. • P: Error-free frames received. • T: Frames received without error. 	B (18,0)
CMRCVE1	The meaning of this field depends on the protocol type (CMRCL). <ul style="list-style-type: none"> • A: Protocol data units received in error. • B: Data blocks received in error. • P: Frames received in error. • T: Inbound frame errors. 	B (18,0)
CMTRNEF1	The meaning of this field depends on the protocol type (CMRCL). <ul style="list-style-type: none"> • A: Protocol data units transmitted successfully. • B: Data blocks transmitted successfully. • P: Total frames transmitted. • T: Frames transmitted without error. 	B (18,0)

Field Name	Description	Attribute
CMTRNE1	The meaning of this field depends on the protocol type (CMPRCL). <ul style="list-style-type: none"> • A: Reserved. • B: Blocks transmitted again. • P: Reserved. • T: Transmitted frame errors. 	B (18,0)
CMRCVEF2	The meaning of this field depends on the protocol type (CMPRCL). <ul style="list-style-type: none"> • B: Error-free data characters received. • A, P, and T: Reserved. 	B (18,0)
CMRCVE2	The meaning of this field depends on the protocol type (CMPRCL). <ul style="list-style-type: none"> • B: Data characters received in error. • A, P, and T: Reserved. 	B (18,0)
CMTRNEF2	The meaning of this field depends on the protocol type (CMPRCL). <ul style="list-style-type: none"> • B: Data characters transmitted successfully. • A, P, and T: Reserved. 	B (18,0)
CMTRNE2	The meaning of this field depends on the protocol type (CMPRCL). <ul style="list-style-type: none"> • B: Data characters transmitted again. • A, P, and T: Reserved. 	B (18,0)

Related reference

Historical data files: QAPMHMCMN

This database file reports historical summarized performance metrics from communication protocol data (*CMNBASE collection category) collected by Collection Services.

Historical data files: QAPMHDDISK

This database file reports detailed historical disk performance data (*DISK collection category) collected by Collection Services.

One record is written per disk unit per interval for the top contributors of each metric defined in the QAPMHMDISK historical summary file. The associated disk response time boundaries are reported in the QAPMHBKTD file.

Field Name	Description	Attribute
INTNUM	Interval number. The <i>n</i> th sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DATETIME	Interval date and time. The date and time of the sample interval, expressed in local system time.	Timestamp

Field Name	Description	Attribute
UTCTIME	UTC interval date and time. The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp
INTSEC	Elapsed interval seconds. The number of seconds since the last sample interval.	PD (7,0)
DSARM	Disk unit (arm) number: Specifies the unique identifier of the unit. Each actuator arm on the disk drives available to the machine represents a unit of auxiliary storage. The value of the unit number is assigned by the system when the unit is allocated to an auxiliary storage pool.	C (4)
DSDRN	Device resource name. Traditionally, one device resource name represents one disk unit. For a multipath disk unit that has multiple disk resources that are associated with it, this device resource name is the device resource name of the initial path.	C (10)
DSTYPE	Disk unit type. The disk drive type.	C (4)
DSMDLN	Disk unit model. The model number of the disk drive.	C (4)
DSSRLN	Serial number. The serial number of the disk drive.	C (15)
DSASP	ASP number. Specifies the auxiliary storage pool to which this unit is allocated. A value of 1 specifies the system auxiliary storage pool. A value from 2 through 32 specifies a basic auxiliary storage pool. A value from 33 to 255 specifies an independent auxiliary storage pool. A value of 0 indicates that this unit is not allocated.	PD (5,0)
DSASPN	ASP resource name. Specifies the resource name of the auxiliary storage pool to which this unit is allocated. A value of blanks specifies the system auxiliary storage pool or a basic auxiliary storage pool.	C (10)

Field Name	Description	Attribute
DSIOARN	IOA resource name. The resource name of the disk storage adapter.	C (10)
DSCAP	Disk capacity (in bytes): Total number of bytes of auxiliary storage that is provided on the unit for the storage of objects and internal machine functions when the auxiliary storage pool that contains it is not under checksum protection. The unit reserved system space value is subtracted from the unit capacity to calculate this capacity.	PD (15,0)
DSAVL	Disk available space (in bytes): Total number of bytes of auxiliary storage space that is not currently assigned to objects or internal machine functions, and therefore is available on the unit.	PD (15,0)
DSSECT	Sector size. The sector size of the disk unit.	B (4,0)
DMFLAG	<ul style="list-style-type: none"> • ' ' means that this disk unit is not locally mirrored. • 'A' means that this disk unit is the designated first unit of a locally mirrored pair. • 'B' means that this disk unit is the designated second unit of a locally mirrored pair. 	C (1)
DSPC	Production copy of remotely mirrored independent auxiliary storage pool. The valid value for this field is '1' or '0'. The value of this field is '1' when the disk unit is in a production copy of a remotely mirrored independent auxiliary storage pool. Otherwise, it is '0'.	C (1)
DSMC	Mirror copy of remotely mirrored independent auxiliary storage pool. The valid value for this field is '1' or '0'. The value of this field is '1' when the disk unit is in a mirror copy of a remotely mirrored independent auxiliary storage pool. Otherwise, it is '0'.	C (1)
DSPS	Parity set. The valid value for this field is '1' or '0'. The value of this field is '1' when the disk unit is in a parity set. Otherwise, it is '0'.	C (1)

Field Name	Description	Attribute
DSRDT	<p>RAID type. The type of RAID parity set for this disk unit. This field has meaning only for disk units in a parity set (DSPS field set to '1').</p> <ul style="list-style-type: none"> • '0' = RAID 5 parity set • '1' = RAID 6 parity set • '2' = RAID 10 parity set 	C (1)
DSMU	<p>Multipath unit. The value of this field is '1' when the disk unit is configured as a multipath disk unit. Otherwise, it is '0'.</p>	C (1)
DSCAT	<p>Disk unit category. This field indicates whether this disk unit has some special characteristics, which might require a special interpretation of its performance data. Each bit in this field has an independent meaning:</p> <ul style="list-style-type: none"> • X'00' = no special category applies. • X'01' = this disk unit is external storage media (also can be determined by examining device type and model for this disk unit). • X'02' = data on this disk unit is encrypted. • X'04' = this disk unit is a virtual disk unit (also can be determined by examining device type and model for this disk unit). • X'08' = this disk unit has an alternate path. • X'10' = this disk unit is a solid-state disk unit. • X'20' = this disk unit is using a non-preferred path. 	C (1)
DSPTRP	<p>Disk read commands. The number of read requests that were received by internal machine functions during the interval.</p>	B (18,0)
DSPTWOP	<p>Disk write commands. The number of write requests that were received by internal machine functions during the interval.</p>	B (18,0)

Field Name	Description	Attribute
DSBLKR	Blocks read. The number of blocks read during the interval. A block is one sector on the disk unit.	PD (11,0)
DSBLKW	Blocks written. The number of blocks written during the interval. A block is one sector on the disk unit.	PD (11,0)
DSQUEL	Total queue elements. The number of I/O operations that were waiting service at the time of a sample (DSSMPL). Divide DSQUEL by DSSMPL to get the average queue length.	PD (11,0)
DSNBSY	Times disk not busy. The number of times no outstanding I/O operations were active at the time of a sample (DSSMPL). Subtract DSNBSY from DSSMPL and then divide by DSSMPL to get the disk utilization.	PD (11,0)
DSSMPL	Samples taken. The number of samples taken for the DSQUEL and DSNBSY fields.	PD (11,0)
DSBUFO	Number of buffer overruns: The number of times that data was available to be read into the disk controller buffer from the disk, but the disk controller buffer still contained valid data that was not retrieved by the storage device controller. Therefore, the disk had to take an additional revolution until the buffer was available to accept data.	PD (11,0)
DSBUFU	Number of buffer underruns: The number of times that the disk controller was ready to transfer data to the disk on a write, but the disk controller buffer was empty. The data was not transferred in time by the disk IOP to the disk controller buffer. The disk was forced to take an extra revolution to wait for the data.	PD (11,0)

Field Name	Description	Attribute
DSDROP	Device read operations: The number of read operations that are issued to the device by the controller. This number includes operations that are generated by the controller for data protection (RAID) or data compression. This number does not include operations that are generated for diagnostics and operations to access the controller reserved area that occur during this idle time.	PD (11,0)
DSDWOP	Device write operations: The number of write operations that are issued to the device by the controller. This number includes operations that are generated by the controller for data protection (RAID) or data compression. This number does not include operations that are generated for diagnostics and operations to access the controller reserved area that occur during this idle time.	PD (11,0)
DSCCRH	Controller cache read hits: The number of times that all of the data that is requested by a read operation was obtained from the controller read or write cache.	PD (11,0)
DSPCPH	Controller cache partial read hits: The number of times that a portion of the data that is requested by a read operation was obtained from the controller read and write cache. An operation to the device was required to obtain the remaining data.	PD (11,0)
DSCCWH	Controller cache writes hits: The number of times that the data associated with the write operation replaces or is combined with existing data in the controller write cache. This eliminates a write operation.	PD (11,0)

Field Name	Description	Attribute
DSCCFW	Controller cache fast writes: The number of times that space was available in the controller write cache for all of the data that is associated with a write operation and a response was returned immediately.	PD (11,0)
DSSRVT	Disk service time. Combined service time of all disk operations completed since last sample (in milliseconds). Divide by number of read (DSPTROP) and write (DSPTWOP) commands to obtain average service time.	B (9,0)
DSWT	Disk wait time. Combined wait (queue) time of all disk operations completed since last sample (in milliseconds). Divide by number of read (DSPTROP) and write (DSPTWOP) commands to obtain average wait (queue) time. Add to disk service (DSSRVT) time to obtain disk response time.	B (9,0)
DSRSEQ	Sequence number. Identifies the QAPMHBKTD records associated with the response time bucket data for this interval.	B (4,0)
DSRBKCTR1	Disk read operations in disk response time bucket 1. Number of read operations since last sample, the response time of which was less than the first disk response time boundary.	B (9, 0)
DSRBKTR1	Disk response time in disk read response time bucket 1. Combined response time of all disk read operations since last sample, the response time of which was less than the first disk response time boundary (microseconds).	B (18, 0)
DSRBKSTR1	Disk service time in disk read response time bucket 1. Combined service time of all disk read operations since last sample, the response time of which was less than the first disk response time boundary (microseconds).	B (18, 0)

Field Name	Description	Attribute
DSRBKCTRnn DSRBKTRnn DSRBKSTRnn	Disk read operations, disk response time, and disk service time are repeated for a total of 11 counter sets per record.	B (9, 0) B (18, 0) B (18, 0)
DSRBKCTW1	Disk write operations in disk response time bucket 1. Number of disk write operations since last sample, the response time of which was less than the first disk response time boundary.	B (9, 0)
DSRBKRTW1	Disk response time in disk write response time bucket 1. Combined response time of all disk write operations since last sample, the response time of which was less than the first disk response time boundary (microseconds).	B (18, 0)
DSRBKSTW1	Disk service time in disk write response time bucket 1. Combined service time of all disk write operations since last sample, the response time of which was less than the first disk response time boundary (in microseconds).	B (18, 0)
DSRBKCTWnn DSRBKRTWnn DSRBKSTWnn	Disk write operations, disk response time, and disk service time are repeated for a total of 11 counter sets per record.	B (9, 0) B (18, 0) B (18, 0)

Related reference

Historical data files: [QAPMHBKTD](#)

This database file contains definitions for the counter sets found in files QAPMHMISUM and QAPMHDDISK.

Historical data files: [QAPMHMDSK](#)

This database file reports historical summarized performance metrics from disk data (*DISK collection category) collected by Collection Services.

Historical data files: QAPMHDJOBM

This database file reports detailed historical job and task performance data (*JOBMI collection category) collected by Collection Services.

One record is written per job or task per interval for the top contributors of each metric defined in the QAPMHMJMI, QAPMHMJOS, and QAPMHMSYS historical summary files. "Job" implies job or task.

Field Name	Description	Attribute
INTNUM	Interval number. The <i>n</i> th sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)

Field Name	Description	Attribute
DATETIME	Interval date and time. The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time. The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp
INTSEC	Elapsed interval seconds. The number of seconds since the last sample interval.	PD (7,0)
JBTDE	System task identifier. For multithreaded jobs, this is the system task identifier of the primary thread.	C (8)
JBNAME	Job name.	C (16)
JBUSER	Job user.	C (10)
JBNBR	Job number.	C (6)
JBCUSR	Current user. The user profile that the job was running under at the time the data was sampled.	C (10)
JBTYPE	Job type. <ul style="list-style-type: none"> • A: Autostart • B: Batch • I: Interactive • M: Subsystem monitor • R: Spool reader • S: System • V: SLIC task • W: Spool writer • X: SCPF job 	C (1)
JBSTYP	Job subtype. <ul style="list-style-type: none"> • T: MRT (System/36 environment only) • E: Evoke (communications batch) • P: Print driver job • J: Prestart job • F: M36 (Advanced/36 server job) • D: Batch immediate job • U: Alternative spool user 	C (1)
JBPOOL	Job pool.	C (2)

Field Name	Description	Attribute
JBPRTY	Job priority.	C (3)
JBTHAC	Active threads. The current number of active threads in the job when the data was sampled. An active thread can be actively running, suspended, or waiting on a resource. Includes the primary thread.	PD (11,0)
JBTHCT	Threads created. The number of threads initiated within this job. Includes both active and terminated threads.	PD (11,0)
JBSLTCNT	Short lifespan entry count. The number of tasks or threads whose lifespan was shorter than the reporting threshold that was in effect when the collection started. Short lifespan tasks are reported for the processor node they were associated with and short lifespan secondary threads are reported for the job to which they belong.	B (9, 0)
JBSLC	Time slice. The maximum amount of processor time (in milliseconds) that the system allows the job to run when it is allowed to begin.	PD (11,0)
JBTCPU	Unscaled CPU time charged. The amount of unscaled CPU time charged (in milliseconds) to the job during the interval.	PD (15,3)
JBACPU	Accumulated unscaled CPU time charged. The accumulated amount of unscaled CPU time charged (in milliseconds) to the job since the job started.	PD (15,3)
JBSTCPU	Scaled CPU time charged. The amount of scaled CPU time charged (in microseconds) to the job during the interval.	B (18,0)
JBSACPU	Accumulated scaled CPU time charged. The accumulated amount of scaled CPU time that is charged (in microseconds) to the job since the job started.	B (18, 0)

Field Name	Description	Attribute
JBSQLCPU	Unscaled SQL CPU time used. The amount of unscaled processor time (in microseconds) used by the job during the interval to perform work that was done on behalf of an SQL operation.	B (18,0)
JBSQLSCPU	Scaled SQL CPU time used. The amount of scaled processor time (in microseconds) used by the job during the interval to perform work that was done on behalf of an SQL operation.	B (18,0)
JBSQLCLK	SQL clock time. The amount of clock time (in microseconds) spent during the interval by the job to perform work that was done on behalf of an SQL operation.	B (18,0)
JBHSQLSTMT	High-level SQL statements. The number of high-level SQL statements that were executed during the interval. This count includes only initial invocation, independent SQL statements. It does not include dependent SQL statements invoked from within another SQL statement. This count also includes initial invocation, independent SQL statements that failed to execute successfully.	B (18,0)
JBAW	Active to wait transitions. The number of transitions from active state to wait state for this job during the interval.	PD (11,0)
JBWI	Wait to ineligible transitions. The number of transitions from wait state to ineligible state for this job during the interval.	PD (11,0)
JBAI	Active to ineligible transitions. The number of transitions from active state to ineligible state for this job during the interval.	PD (11,0)
JBDBR	Synchronous database reads. The number of physical synchronous database read operations for database functions during the interval.	PD (11,0)

Field Name	Description	Attribute
JBNDDB	Synchronous nondatabase reads. The number of physical synchronous nondatabase read operations for nondatabase functions during the interval.	PD (11,0)
JBDBW	Synchronous database writes. The number of synchronous physical database write operations for database functions during the interval.	PD (11,0)
JBNDW	Synchronous nondatabase writes. The number of synchronous physical nondatabase write operations for nondatabase functions during the interval.	PD (11,0)
JBADBR	Asynchronous database reads. The number of asynchronous physical database read operations for database functions during the interval.	PD (11,0)
JBANDR	Asynchronous nondatabase reads. The number of asynchronous physical nondatabase read operations for nondatabase functions during the interval.	PD (11,0)
JBADBW	Asynchronous database writes. The number of asynchronous physical database write operations for database functions during the interval.	PD (11,0)
JBANDW	Asynchronous nondatabase writes. The number of asynchronous physical nondatabase write operations for nondatabase functions during the interval.	PD (11,0)
JBSQLDBR	SQL synchronous database reads. The number of physical synchronous database read operations that are done on behalf of an SQL operation during the interval.	B (18,0)
JBSQLNDBR	SQL synchronous nondatabase reads. The number of physical synchronous nondatabase read operations that are done on behalf of an SQL operation during the interval.	B (18,0)

Field Name	Description	Attribute
JBSQLDBW	SQL synchronous database writes. The number of synchronous physical database write operations that are done on behalf of an SQL operation during the interval.	B (18,0)
JBSQLNDBW	SQL synchronous nondatabase writes. The number of synchronous physical nondatabase write operations that are done on behalf of an SQL operation during the interval.	B (18,0)
JBSQLADBR	SQL asynchronous database reads. The number of asynchronous physical database read operations that are done on behalf of an SQL operation during the interval.	B (18,0)
JBSQLANDBR	SQL asynchronous non-database reads. The number of asynchronous physical nondatabase read operations that are done on behalf of an SQL operation during the interval.	B (18,0)
JBSQLADBW	SQL asynchronous database writes. The number of asynchronous physical database write operations that are done on behalf of an SQL operation during the interval.	B (18,0)
JBSQLANDBW	SQL asynchronous non-database writes. The number of asynchronous physical nondatabase write operations that are done on behalf of an SQL operation during the interval.	B (18,0)
JBTFLT	Page faults. The number of page faults that occurred during the interval.	PD (11,0)
JBIPF	I/O pending faults. The number of times a page fault occurred on an address that was currently part of an auxiliary storage I/O operation during the interval.	PD (11,0)
JBWIO	Asynchronous I/O waits. The number of times the job explicitly waited for outstanding asynchronous I/O operations to complete during the interval.	PD (11,0)

Field Name	Description	Attribute
JBPGRQ	Page frames requested. The number of new page frames that are required by the job to satisfy page fault, read or clear operations during the interval.	B (9,0)
JBPGRL	Page frames released. The number of page frames that are explicitly released by the job during the interval.	B (9,0)
JBPGDI	Pages deallocated. The number of 4096-byte units of temporary and permanent storage deallocated by the job during the interval.	B (9,0)
JBTMPPGAI	Temporary pages allocated. The number of 4096-byte units of temporary storage allocated by the job during the interval.	B (9,0)
JBTMPPGDI	Temporary pages deallocated. The number of 4096-byte units of temporary storage deallocated by the job during the interval.	B (9,0)
JBCURTMP	Current temporary storage. A snapshot of the total temporary storage charged to this job, expressed in 4096-byte units.	B (18,0)
JBPEAKTMP	Peak temporary storage. The largest value that the total temporary storage that is charged to this job was since the job started, expressed in 4096-byte units.	B (18,0)
JBMAXTMP	Maximum temporary storage allowed. The largest value that peak temporary storage can be without notifying the operating system, expressed in 4096-byte units. This field is zero if the job is allowed to use an unlimited amount of temporary storage.	B (18,0)
JBSKSC	Socket sends. The number of times the job sent data through a socket during the interval.	PD (11,0)
JBSKBS	Socket bytes sent. The number of bytes the job sent through a socket during the interval.	PD (11,0)
JBSKRC	Socket receives. The number of times the job received data through a socket during the interval.	PD (11,0)

Field Name	Description	Attribute
JBSKBR	Socket bytes received. The number of bytes the job received through a socket during the interval.	PD (11,0)
JBSEIZECNT	Seize count. The number of seizures held by this job at the time the data was sampled.	B (9, 0)
JBPSLCKCNT	Process scoped lock count. The number of process scoped locks held by this job at the time data was sampled.	B (9, 0)
JBTSLCKCNT	Thread scoped lock count. The number of thread scoped locks held by this job at the time data was sampled.	B (9, 0)
JBPSRCDLCK	Process scoped database record lock count. The number of process scoped database record locks held by this job at the time data was sampled.	B (9,0)
JBTSRCDLCK	Thread scoped database record lock count. The number of thread scoped database record locks held by this job at the time data was sampled.	B (9, 0)
JBXRFR	Stream file reads. The number of stream file reads during the interval.	PD (11,0)
JBXRFW	Stream file writes. The number of stream file writes during the interval.	PD (11,0)
JBPJE	Physical journal writes. The number of physical journal write operations to disk performed during the interval.	PD (11,0)
JBNSJE	Non-SMS journal entries. The number of journal entries that are not directly related to SMAPP.	PD (11,0)
JBUJD	User journal deposits. The number of SMAPP-induced journal entries deposited in user-provided journals during the interval.	PD (11,0)
JBSJD	System journal deposits. The number of SMAPP-induced journal entries deposited in system-provided (default) journals during the interval.	PD (11,0)

Field Name	Description	Attribute
JBTWT	Journal bundle wait time. The amount of time (in milliseconds) the job waited for journal bundles to be written to disk during the interval. This time includes time that is spent waiting for physical disk write operations that are initiated by this task to be serviced and time that is spent waiting for physical disk write operations that are initiated by other tasks whose journal entries reside in the same journal bundle.	PD (11,0)
JBTNW	Journal bundle waits. The number of times the job waited for journal bundles to be written to disk during the interval.	PD (11,0)
JBXRRR	Random stream file read operations. The number of random stream file read operations during the interval. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)), and user-defined file systems.	PD (11,0)
JBXRRW	Random stream file write operations. The number of random stream file write operations during the interval. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)), and user-defined file systems.	PD (11,0)
JBXRFS	Fsync operations. The number of fsync operations during the interval. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)), and user-defined file systems.	PD (11,0)

Field Name	Description	Attribute
JBXRBR	Stream file bytes read. The number of stream file bytes read during the interval. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)), and user-defined file systems.	PD (15,0)
JBXRBW	Stream file bytes written. The number of stream file bytes written during the interval. This count includes files in the Root, QOpenSys, QDLS, QOPT (when the files are on a volume that is not formatted in Universal Disk Format (UDS)), and user-defined file systems.	PD (15,0)
JBAGCRT	Activation groups created. The number of activation groups created during the interval.	B (18,0)
JBPGMSACT	Program and service program activations created. The number of ILE program and service program activations created during the interval.	B (18,0)
JBFLDR2	Workload group delay time. The amount of time (in microseconds) this job was not dispatched due to workload grouping.	B (18,0)
JBFLDR3	Workload group. The identifier for the workload group this job belonged to at the time this data was sampled. A value of zero is reported when no group was assigned.	B (9,0)

Related reference

Historical data files: QAPMHMJMI

This database file reports historical summarized performance metrics from job data (*JOBMI collection category) collected by Collection Services.

Historical data files: QAPMHDJOB0

This database file reports detailed historical job performance data (*JOBOS collection category) collected by Collection Services.

One record is written per job per interval for the top contributors of each metric defined in the QAPMHMJMI, QAPMHMJOS, and QAPMHMSYS historical summary files.

Field Name	Description	Attribute
INTNUM	Interval number. The <i>n</i> th sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DATETIME	Interval date and time. The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time. The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp
INTSEC	Elapsed interval seconds. The number of seconds since the last sample interval.	PD (7,0)
JBTDE	System task identifier. For multithreaded jobs, this is the system task identifier of the primary thread.	C (8)
JBNAME	Job name.	C (10)
JBUSER	Job user.	C (10)
JBNBR	Job number.	C (6)
JBTYPE	Job type. <ul style="list-style-type: none"> • A: Autostart • B: Batch • I: Interactive • M: Subsystem monitor • R: Spool reader • S: System • V: SLIC task • W: Spool writer • X: SCPF job 	C (1)
JBSTYP	Job subtype. <ul style="list-style-type: none"> • T: MRT (System/36 environment only) • E: Evoke (communications batch) • P: Print driver job • J: Prestart job • F: M36 (Advanced/36 server job) • D: Batch immediate job • U: Alternative spool user 	C (1)

Field Name	Description	Attribute
JBFLAG	<p>Job flags. Each bit in this field has an independent meaning:</p> <ul style="list-style-type: none"> • Bit 0: Pass-through service • Bit 1: Pass-through target • Bit 2: Emulation active • Bit 3: IBM i Access application • Bit 4: Target DDM job • Bit 5: MRT • Bits 6-15: Reserved 	C (2)
JBSVRT	<p>Server type. The type of server represented by the job. A value of blank (or blank space) indicates that the job is not part of a server.</p> <p>For more information about server types, see Server jobs and Server table.</p>	C (30)
JBSSYS	Subsystem name. The name of the subsystem the job is running in.	C (10)
JBSLIB	Subsystem library. The name of the library the subsystem description is in.	C (10)
JBRSP	<p>Transaction response time. The response time (in seconds) for transactions during the interval.</p> <p>Note: Certain IBM i functions support the concept of a transaction. The definition of a transaction and the characteristics of a transaction are different depending on the type of job or the specific function of the job. For interactive jobs, display I/O transactions are counted. The transaction starts on detection of enter from the workstation. The transaction ends when the keyboard is unlocked. For SNADS jobs, a transaction is the processing of a distribution.</p>	PD (15,3)
JBNTR	<p>Transactions. The number of transactions during the interval.</p> <p>Note: Certain IBM i functions support the concept of a transaction. The definition of a transaction and the characteristics of a transaction are different depending on the type of job or the specific function of the job. For interactive jobs, display I/O transactions are counted. The transaction starts on detection of enter from the workstation. The transaction ends when the keyboard is unlocked. For SNADS jobs, a transaction is the processing of a distribution.</p>	PD (11,0)
JBSPLFC	Spooled files created. The number of spooled files created during the interval by this job. This number includes those spooled files that are spooled or restored under this job and all spooled files that are spooled under QPRTJOBS by this job.	B (18,0)

Field Name	Description	Attribute
JBPLN	Lines to be printed. The number of print lines written during the interval. This number does not reflect what is actually printed. Spooled files can be ended, or printed with multiple copies.	PD (11,0)
JBPPG	Pages to be printed. The number of print pages written during the interval. This number does not reflect what is actually printed. Spooled files can be ended, or printed with multiple copies.	PD (11,0)
JBPFL	Files to be printed. The number of print files written during the interval. This number does not reflect what is actually printed. Spooled files can be ended, or printed with multiple copies.	PD (11,0)
JBLWT	Database writes (logical). The number of times the internal database write function was called during the interval. This number does not include I/O operations to readers/writers, or I/O operations caused by the CPYSPLF or DSPSPLF command. If SEQONLY(*YES) is specified, these numbers show each block of records written, not the number of individual records written.	PD (11,0)
JBLRD	Database reads (logical). The number of times the database module was called during the interval. This number does not include I/O operations to readers/writers, or I/O operations caused by the CPYSPLF or DSPSPLF command. If SEQONLY(*YES) is specified, these numbers show each block of records read, not the number of individual records read.	PD (11,0)
JBDBU	Miscellaneous database operations (logical). The number of miscellaneous database operations during the interval. This number includes updates, deletes, force-end-of-data, commits, rollbacks, and releases (logical).	PD (11,0)
JBLWTSQL	SQL-related database writes (logical). This field can be compared to JBLWT to understand the portion of database writes that are attributed to SQL activity within the job during the interval. Subtracting JBLWTSQL from JBLWT yields the number of non-SQL related database writes.	B (18,0)
JBLRDSQL	SQL-related database reads (logical). This field can be compared to JBLRD to understand the portion of database reads that are attributed to SQL activity within the job during the interval. Subtracting JBLRDSQL from JBLRD yields the number of non-SQL related database reads.	B (18,0)

Field Name	Description	Attribute
JBDBUSQL	SQL-related database miscellaneous operations (logical). This field can be compared to JBDBU to understand the portion of database miscellaneous operations that are attributed to SQL activity within the job during the interval. Subtracting JBDBUSQL from JBDBU yields the number of non-SQL related database miscellaneous operations.	B (18,0)
JBBCO	Database commit operations. The number of database commit operations during the interval.	PD (11,0)
JBBRO	Database rollback operations. The number of database rollback operations during the interval.	PD (11,0)
JBLBO	SQL cursor count. The number of SQL cursors that were full opened during the interval.	PD (11,0)
JBLBS	SQL cursor reuse. The number of SQL cursors that were pseudo-opened during the interval. Pseudo-opens are also known as <i>reused SQL cursors</i> .	PD (11,0)
JBNUS	Full opens. The number of Native database (non-SQL) files and SQL cursors that were full opened during the interval. Subtracting the value within field JBLBO from JBNUS yields the number of non-SQL full opens.	PD (11,0)
JBXSLR	File system symbolic link reads. The number of file system symbolic link read operations during the interval. This count includes the following file systems: Root, QOpenSys, and user-defined file systems.	PD (11,0)
JBXDYR	File system directory reads. The number of file system directory reads operations during the interval. This count includes the following file systems: Root, QOpenSys, and user-defined file systems.	PD (11,0)
JBDLCH	File system lookup cache hits. The number of file system lookup cache hits during the interval. This count includes the following file systems: Root, QOpenSys, and user-defined file systems.	PD (11,0)
JBDLCM	File system lookup cache misses. The number of file system lookup cache misses during the interval. This count includes the following file systems: Root, QOpenSys, and user-defined file systems.	PD (11,0)
JBFSOPN	File system opens. The number of file system opens during the interval. This count includes the following file systems: Root, QOpenSys, and user-defined files systems.	PD (11,0)
JBFSDC	File system directory creates. The number of create operations for directory objects during the interval. This count includes the following file systems: Root, QOpenSys, and user-defined files systems.	PD (11,0)

Field Name	Description	Attribute
JBFSNDC	File system non-directory creates. The number of create operations for non-directory objects such as files or symbolic links during the interval. This count includes the following file systems: Root, QOpenSys, and user-defined files systems.	PD (11,0)
JBFSDD	File system directory deletes. The number of delete operations for directory objects during the interval. This count includes the following file systems: Root, QOpenSys, and user-defined files systems.	PD (11,0)
JBFSNDD	File system non-directory deletes. The number of delete operations for non-directory objects such as files or symbolic links during the interval. This count includes the following file systems: Root, QOpenSys, and user-defined files systems.	PD (11,0)

Notes:

Related reference

Historical data files: [QAPMHMJOS](#)

This database file reports historical summarized performance metrics from job data (*JOBOS collection category) collected by Collection Services.

Historical data files: QAPMHDPOL

This database file reports detailed historical main storage pool performance data (*POOL collection category) collected by Collection Services.

One record is written per pool per interval for the top contributors of each metric defined in the QAPMHMPOL historical summary file.

Field Name	Description	Attribute
INTNUM	Interval number. The <i>n</i> th sample database interval based on the start time specified in the Create Performance Data (CRTPFRDTA) command.	PD (5,0)
DATETIME	Interval date and time. The date and time of the sample interval, expressed in local system time.	Timestamp
UTCTIME	UTC interval date and time. The date and time of the sample interval, expressed in Coordinated Universal Time (UTC).	Timestamp
INTSEC	Elapsed interval seconds. The number of seconds since the last sample interval.	PD (7,0)
PONBR	Pool number. Specifies the unique identifier of this pool. The value is from 1 to 64.	C (3)
PONAME	Pool name. Specifies the name of the pool.	C (32)
POACTL	Pool activity level setting. The maximum number of processes that can be active in the machine at the same time.	PD (5,0)
POSIZB	Pool size. The amount of main storage, in KB (kilobytes), assigned to the pool.	B (18,0)

Field Name	Description	Attribute
POUNALB	Unallocated pool space. The amount of pool storage, in KB (kilobytes), available to be used for new transfers into the main storage pool without displacing any virtual data already in the pool.	B (18,0)
PORES	Machine reserved size. The amount of storage from the pool, in KB (kilobytes), that is dedicated to machine functions.	PD (9,0)
PODBF	Database faults. Total number of interruptions to processes (not necessarily assigned to this pool) that were required to transfer database data into the pool during the interval.	PD (11,0)
PONDBF	Nondatabase faults. Total number of interruptions to processes (not necessarily assigned to this pool) that were required to transfer nondatabase data into the pool during the interval.	PD (11,0)
PODBPG	Database pages read. Total number of pages of database data transferred from auxiliary storage to the pool during the interval.	PD (11,0)
PONDPG	Nondatabase pages read. Total number of pages of nondatabase data transferred from auxiliary storage to the pool during the interval.	PD (11,0)
POAW	Active to wait transitions. Total number of transitions by processes that are assigned to this pool from active state to wait state during the interval.	PD (11,0)
POWI	Wait to ineligible. Total number of transitions by processes assigned to this pool from wait state to ineligible state during the interval.	PD (11,0)
POAI	Active to ineligible. Total number of transitions by processes assigned to this pool from active state to ineligible state during the interval.	PD (11,0)

Related reference

Historical data files: [QAPMHMPOL](#)

This database file contains historical summarized performance metrics from pool data (*POOL collection category) collected by Collection Services.

Disk Watcher data files

Use this topic to find the names, descriptions and attributes of the Disk Watcher database files.

Disk Watcher data files: QAPYDWINTI

This file contains information about each sample taken in a Disk Watcher session.

One record is created per interval.

Field Name	Description	Attribute
INTERVAL	Interval number.	B (4)

Field Name	Description	Attribute
IISTARTTOD	Interval start time of day. The time of day data collection began for this interval.	Timestamp
IIENDTOD	Interval end time of day. The time of day data collection ended for this interval.	Timestamp
IIASPCNT	Auxiliary storage pool count. the number of ASPs for which disk I/O information was collected in this interval.	B (4)
IIPATHCNT	Disk unit path count. The number of disk unit paths for which disk I/O information was collected in this interval.	B (4)
IIDATAMISS	Data missed. Indicates whether data was missed in this interval. Data may be missed if the collection interval is too large because the data collection buffer could wrap it can be collected. 0 = data was not missed in this interval 1 = data was missed in this interval	C (1)
IICONDSTS	Condition status. For a conditional collection, indicates whether the condition was satisfied during this interval 0 = the condition was not satisfied in this interval or no condition exists 1 = the condition was satisfied	C (1)
IIRESERVE1	Reserved.	C (6)
IIRESERVE2	Reserved.	B (8)

Disk Watcher data files: QAPYDWOBJR

This file contains object resolution information.

Note: Resolution data may not be available for every object. There is a chance that the data could have been unavailable at the time collection was attempted.

This file includes object information associated with the records in the QAPYDWTRC file. One record is created per object on which an I/O operation was performed.

Field Name	Description	Attribute
SEGKEY	Segment key. The identifier of the base segment for this object.	H (8)
ORSEGTYPE	Segment type. The machine defined segment type.	C (2)
OROBJTYPE	Object type.	C (1)
OROBJSTYPE	Object subtype	C (1)
OROBJPATR	Object performance attributes. The object performance attribute field. Values for this field are documented under the Create Space (CRTS) MI instruction.	C (4)
OROBJNAME	Object name.	C (30)

Field Name	Description	Attribute
ORCONTEXT	Context name.	C (30)
OROBJASP	Object ASP. The auxiliary storage pool (ASP) in which this object resides.	B (4)
ORIFSPATH	IFS path name. If this is an IFS object, this value is the IFS path of the object. If this is not an IFS object, this field will be blank.	Varchar (256) Dft (16)

Disk Watcher data files: QAPYDWPGMR

This file contains program or procedure resolution information.

Note: Resolution data may not be available for every program or procedure. There is a chance that the data could have been unavailable at the time collection was attempted.

This file includes program or procedure information associated with the records in the QAPYDWTRC file. One record is created per program or procedure initiating an I/O operation.

Field Name	Description	Attribute
PROCKEY	Procedure key. The identifier of the program or procedure.	H (8)
PRSTRHDL	Procedure start handle. The start handle of this procedure.	H (8)
PRENDHDL	Procedure end handle. The end handle of this procedure.	H (8)
PRFRMTYPE	Frame type. The type of stack frame generated by this program: 0 = SLIC frame 1 = NMI frame 2 = OMI frame 3 = Java frame 4 = PASE frame	B (2)
PRMOBJTYP	MI object type. The object type of the program.	C (1)
PRMOBJSTYP	MI object subtype. The object subtype of the program.	C (1)
PRMPGMLIB	MI program library name. The name of the library where the program resides.	C (30)
PRMPGMNAME	MI program name. The name of the program which initiated an I/O operation.	C (30)
PRMODNAME	Module name. The ILE module name.	C (30)
PRNAME	Procedure name. The name of this procedure.	Varchar (256) Dft (64)

Disk Watcher data files: QAPYDWRUNI

This file contains information about the Disk Watcher session.

One record is created per Disk Watcher session. This record is overwritten with current data each time a new interval is collected.

Field Name	Description	Attribute
RIINTERVAL	Interval number. The last interval collected.	B (4)
RISTARTTOD	Start time of day. The start time of the collection.	Timestamp
RIENDTOD	End time of day. The end time of the collection.	Timestamp
RIFILELVL	Database file level. The level of the database files.	B (4)
RIRESERVE1	Reserved.	B (4)
RICOLLSIZE	Data written to file size. The amount of data written to the database files in kilobytes.	B (8)
RINUMPPROC	Number of physical processors. The number of physical processors on the system where the collection took place.	B (4)
RINUMVPROC	Number of virtual processors. The number of virtual processors on the system where the collection took place.	B (4)
RICOLLSTS	Collection status. S = Starting C = Collecting E = Ended	C (1)
RIENDRSN	Collection end reason. The reason data collection ended. Possible values are: I = Interval limit reached T = Time limit reached S = Storage limit reached C = Condition met A = System ASP threshold reached D = Database file ASP threshold reached E = End requested U = Unknown	C (1)
RITRCCOND	Trace data condition flag. Indicates whether trace data will be limited by a condition in this collection 0 = trace data is not limited by a condition in this collection 1 = trace data is limited by a condition in this collection	C (1)
RISYSNAME	System name. The name of the system on which the collection took place.	C (8)
RISYSSRL	System serial number. The serial number of the system on which the collection took place.	C (15)
RISYSTYPE	System type. The machine type of the system on which the collection took place.	C (4)
RISYSMODEL	System model. The model of the system on which the collection took place.	C (4)

Field Name	Description	Attribute
RIOSVRM	Operating system VRM. The operation system release on the system where the collection took place.	C (6)
RICALLJOB	Calling job name. The name of the job which initiated the Disk Watcher collection.	C (26)
RICURRUSER	Calling job current user. The current user of the calling job at the time Disk Watcher was started.	C (10)
RICOLLNAME	Collection name. The member name for this collection.	C (10)
RICOLLDESC	Collection description. A text description given to the collection.	C (50)
RISTRCMD	STRDW command string. The command string used to create this collection.	C (1000)
RIDFNCM	ADDDWDFN command string. The command string used to create the definition for this collection.	C (5000)

Disk Watcher data files: QAPYDWSTAT

This file provides summarized statistics for the specified disk units.

One record is created per sample per disk unit path.

Note: The path to a disk unit can be uniquely identified by the device resource name.

Field Name	Description	Attribute
INTERVAL	Interval number.	B (4)
DEVNAME	Device resource name associated with this disk unit path.	C (10)
STASPNUM	ASP number. The ASP number associated with this disk unit path.	B (2)
STUNITNUM	Unit number. The unit number for which I/O statistics are being returned.	B (2)
STDATAMISS	I/O data missed. Indicates that some I/O data for this disk unit was missed because the collection buffer wrapped during the interval. Reducing the amount of time between intervals may prevent this missed data. 0 = no data missed. 1 = data missed for this disk unit.	C (1)
STRESERVE1	Reserved	C (3)
STSECTORSZ	Sector size.	B (2)
STFIRSTIO	First I/O time. The time the first I/O occurred (in microseconds) from the session creation time.	B (8)
STLASTIO	Last I/O time. The time the last I/O occurred (in microseconds) from the session creation time.	B (8)

Field Name	Description	Attribute
STWRTMIN	Minimum write time. The minimum amount of time used to perform a write operation (in microseconds).	B (8)
STWRTMINDQ	Minimum deferred queue write time. the minimum amount of time the write request waited on the deferred queue (in microseconds).	B (8)
STWRTMAX	Maximum write time. The maximum amount of time used to perform a write operation (in microseconds).	B (8)
STWRTMAXDQ	Maximum deferred queue write time. The maximum amount of time the write request waited on the deferred queue (in microseconds).	B (8)
STRDMIN	Minimum read time. The minimum amount of time used to perform a read operation (in microseconds)	B (8)
STRDMINDQ	Minimum deferred queue read time. The minimum amount of time the read request waited on the deferred queue (in microseconds).	B (8)
STRDMAX	Maximum read time. The maximum amount of time used to perform a read operation (in microseconds).	B (8)
STRDMAXDQ	Maximum deferred queue read time. The maximum amount of time the read request waited on the deferred queue (in microseconds).	B (8)
STOTHMIN	Minimum other I/O time. The minimum amount of time used to perform an other I/O operation (in microseconds).	B (8)
STOTHMINDQ	Minimum deferred queue other I/O time. The minimum amount of time an other I/O operation waited on the deferred queue (in microseconds).	B (8)
STOTHMAX	Maximum other I/O time. The maximum amount of time used to perform an other I/O operation (in microseconds).	B (8)
STOTHMAXDQ	Maximum deferred queue other I/O time. The maximum amount of time an other I/O operation waited on the deferred queue (in microseconds).	B (8)

Field Name	Description	Attribute
STWRTTOTn STWRDQn STWRTCn STWRTPCn STRDTOTn STRDDQn STRDCn STRDPCn STOHTOTn STOHDQn STOHCn STOHPCn	These fields are repeated for a total of 13 counter sets per record. Each counter set represents a different time range. Range 1 - less than 100 microseconds Range 2 - 100 to 200 microseconds Range 3 - 200 to 400 microseconds Range 4 - 400 to 800 microseconds Range 5 - 800 to 1,600 microseconds Range 6 - 1,600 to 3,200 microseconds Range 7 - 3,200 to 6,400 microseconds Range 8 - 6,400 to 12,800 microseconds Range 9 - 12,800 to 25,600 microseconds Range 10 - 25,600 to 51,200 microseconds Range 11 - 51,200 to 102,400 microseconds Range 12 - 102,400 to 204,800 microseconds Range 13 - greater than 204,800 microseconds	
STWRTTOTn	Total write time. The total time spent performing write operations (in microseconds).	B (8)
STWRDQn	Deferred queue write time. The total amount of time the write request waited on the deferred queue (in microseconds).	B (8)
STWRTCn	Write count. The total number of write operations.	B (8)
STWRTPCn	Write page count. The total number of pages written.	B (8)
STRDTOTn	Total read time. The total time spent performing read operations (in microseconds).	B (8)
STRDDQn	Deferred queue read time. The total amount of time the read request waited on the deferred queue (in microseconds).	B (8)
STRDCn	Read count. The total number of read operations.	B (8)
STRDPCn	Read page count. The total number of pages read.	B (8)
STOHTOTn	Total other I/O time. The total time spent performing other I/O operations (in microseconds).	B (8)
STOHDQn	Deferred queue other I/O time. The total amount of time an other I/O operation waited on the deferred queue (in microseconds).	B (8)
STOHCn	Other I/O count. The total number of other I/O operations.	B (8)
STOHPCn	Other I/O pages count. The total number of pages involved in other I/O operations.	B (8)
STRESERVE2	Reserved	B (8)
STRESERVE3	Reserved	B (8)

Disk Watcher data files: QAPYDWTDER

This file provides task dispatching element (TDE) resolution information.

Note: Resolution data may not be available for every TDE. There is a chance that the data could have been unavailable at the time collection was attempted.

This file includes TDE information for the records in the QAPYDWTRC file. One record is created per unique task count in the QAPYDWTRC file.

Field Name	Description	Attribute
TSKCNT	Task count. The task count of the TDE.	B (8)
TRTHREADID	Thread ID. The thread identifier for this TDE.	B (8)
TRPTSKCNT	Primary thread task count. The task count of the primary thread. If this thread is the primary thread this value will be the same as the field TSKCNT.	B (8)
TRTDETYPE	TDE type. Indicates what type of TDE this entry refers to. T = Task. P = Primary thread. S = Secondary thread. L = Licensed Internal Code (LIC) thread. J = Java primary thread. V = Java secondary thread.	C (1)
TRTDENAME	Job or task name. The job or task name associated with this TDE. For jobs this will be the fully qualified job name which is made up of the job name, user name, and job number.	C (26)
TRCURRUSER	Current user. The current user associated with this TDE. This is the user associated with the job when the TDE information was initially collected. This value will not be updated if the user associated with the job changes.	C (10)

Disk Watcher data files: QAPYDWTRC

This file provides specific trace info for each input/output (I/O) operation that occurred for the specified ASP.

One record is created per I/O operation.

Field Name	Description	Attribute
TCDEVNAME	Device Resource name. The resource name associated with this disk unit path.	C (10)
TCASPNUM	ASP number. The number of the ASP where this I/O operation occurred.	B (2)
TCUNITNUM	Unit number. The unit number for which the I/O occurred.	B (2)
TCRESERVE1	Reserved	C (2)
TCSEGKEY	Segment key. Identifier for the base segment where the I/O operation occurred.	H (8)

Field Name	Description	Attribute
TCPROCKEY	Program or procedure key. Identifier for the program or procedure that requested or caused the I/O to occur.	H (8)
TCTASKCNT	Task count. The task count of the TDE that caused the I/O to occur.	B (8)
TCDQDEPTH	Deferred queue depth. If this I/O request was placed on the deferred queue, this is the number of I/O operations in the queue. If the I/O request was not placed on the deferred queue, this value will be 0.	B (4)
TCSYNCIO	Synchronous I/O. Indicates whether this I/O was addressed as synchronous: 0 = this I/O was not addressed as synchronous 1 = this I/O was addressed as synchronous	C (1)
TCRSYNCIO	Requested synchronous I/O. Indicates whether this I/O was requested as synchronous: 0 = this I/O was not addressed as synchronous 1 = this I/O was addressed as synchronous	C (1)
TCMLTPHIO	Multipath I/O. Indicates whether this I/O was to a fiver attached device that supports multi-path I/O operations: 0 = this I/O was to a device that does not support multi-path 1 = this I/O was to a device that does support multi-path	C (1)
TCIOTYPE	I/O Type. Indicates what type of I/O this is: R = I/O was a read W = I/O was a write O = I/O was a type other than a read or write	C (1)
TCSUBUNIT	Disk subunit. The mirroring subunit for which the I/O was performed: '-' = Not part of a mirrored unit 'A' = The primary mirrored unit of a pair 'B' = The alternate mirrored unit of a pair	C (1)

Field Name	Description	Attribute
TCSMIOTYPE	<p>Storage Management I/O type.</p> <p>The storage management I/O type (this is the type of I/O from the perspective of the requester) :</p> <p>SFt = Segment address range fault SC1 = Segment address range clear SRd = Segment address range read SWt = Segment address range write SRv = Segment address range remove SUp = Segment address range unpin SWp = Page out task write STv = Segment address range trivial request GRf = Access group read GPg = Access group purge SRP= Segment address range remove request IOP SCP = Segment address range clear request IOP GCP = Segment address range clear request POW SUP = Segment address range unpin request IOP SRQ = Segment address range read request IOP GRQ = Segment address range read request POW SFP = Segment address range fault request IOP GFP = Segment address range fault request POW SRR = Access group read IOP GRR = Access group read POW SWP = Segment address range write request IOP GWP = Segment address range write request POW GPP = Access group purge request IOP SPw = Segment address range page out wait request</p>	C (3)
TCRESERVE2	Reserved	C (4)
TCCACHEHNT	<p>Cache hint.</p> <p>Provides hint to the cache about whether cache is needed or not:</p> <p>0 = No cache hint 1 = Accelerated LRU cache hint 2 = Unmodified write cache hint</p>	B (1)
TCIOOPRTY	Reserved	B (1)
TCPOOLNUM	<p>Pool number.</p> <p>The main storage management pool number for which the I/O occurred. This value will be zero if the pool number could not be retrieved.</p>	B (2)

Field Name	Description	Attribute
TCIOFUNCTN	I/O function. The I/O operation command number: 0 = Other I/O function 2 = Report status 3 = Continuation 4 = Device reset 5 = Format DASD 6 = Write buffer 7 = Reallocate 15 = Special function 16 = Read 17 = Read DASD parameters 18 = Verify 20 = Skip read 22 = Read buffer 32 = Write 33 = Write pattern byte 36 = Skip write 37 = Inquiry 119 = Query command status 131 = Start reorganization 132 = Allocate 133 = Deallocate 134 = Write directory 135 = Scan read 136 = Read directory 137 = Query compression metrics 138 = Discard temporary data	B (4)
TCSECTNUM	Sector number. Sector number whether the I/O operation began.	B (8)
TCPAGECNT	Page count. Number of pages in the I/O request.	B (8)
TCIOHNDL	I/O handle. The location on which the I/O operation is being performed.	H (8)
TCDQTIME	Deferred queue time. The time this operation request spent on the deferred I/O queue (in microseconds).	B (8)
TCIOSTART	I/O start time. The start time of the I/O operation (in microseconds from the creation of the session). Note: If the Deferred queue time is greater than zero, then this is also the time that the operation was placed on the deferred queue.	B (8)
TCIOEND	I/O end time. The end time of the I/O operation (in microseconds from the creation of the session).	B (8)
TCPGMOFSET	Program offset. The offset of the program that requested or caused the I/O.	H (8)
TCRESERVE3	Reserved	B (8)
TCRESERVE4	Reserved	B (8)

Field Name	Description	Attribute
TCRESERVE5	Reserved	B (8)
TCRESERVE6	Reserved	B (8)
TCTASKCNT2	Task count. The task count of the TDE that caused the I/O to occur.	BINCHAR (8)

Data files: File abbreviations

The database files use abbreviations in the field and byte data tables.

These abbreviations include.

Abbreviation	Description
Primary files	These files are related to and generated from the category.
C	Character in the Attributes column.
H	Hexadecimal in the Attributes column.
PD	Packed decimal in the Attributes column.
Z	Zoned decimal in the Attributes column.
IOP	Input/output processor or I/O processor. The processors that control the activity between the host system and other devices, such as disks, display stations, and communication lines.
DCE	Data circuit-terminating equipment.
MAC	Medium-access control. An entity in the communications IOP.
LLC	Logical link control. An entity in the communications IOP.
Beacon frame	A frame that is sent when the ring is inoperable.
Type II frame	A connection-oriented frame (information frame) used by Systems Network Architecture (SNA).
I-frame	An information frame.
B	The DDS binary data type of 4 digits, which is 2 bytes, in the Attributes column.
G	Graphic - used to hold double-byte Unicode data.

CL commands for performance

The operating system includes several CL commands to help you manage and maintain system performance.

CL commands contained in the base operating system

These tables provide a list of most of the performance related CL commands that are a part of the base operating system.

Command	Function
Work with Active Jobs (WRKACTJOB)	Allows you to review and change the attributes and resource utilization of the jobs running on your system.
Work with Disk Status (WRKDSKSTS)	Displays the performance information and attributes for system disk units.
Work with System Status (WRKSYSSTS)	Provides an overview of current system activity. Specifically, it displays the number of jobs on the system and storage pool utilization information.
Work with System Activity (WRKSYSACT)	Allows you to work with jobs and tasks on your system.
Work with Object Locks (WRKOBJLCK)	Allows you to work with and display locks on a specified object, including locks waiting to be applied.
Work with Shared Storage Pools (WRKSHRPOOL)	Display the utilization information and change attributes of shared storage pools, including machine and base pool.

Command	Function
Analyze Command Performance (ANZCMDPFR)	Measures the performance of a single CL command or a set of CL commands.
Configure PM Agent (CFGPMAGT)	Configures PM Agent to send and receive PM Agent performance data.
Start Performance Trace (STRPFRTRC)	Starts the collection of multiprogramming level and transaction trace data.
End Performance Trace (ENDPFRTRC)	Ends the collection of multiprogramming level and transaction trace data.
Delete Performance Collection (DLTPFCOL)	Deletes a performance collection from the system.
Copy Performance Collection (CPYPFCOL)	Creates a copy of a performance collection.
Convert Performance Collection (CVTPFCOL)	Converts performance data from a previous release to the format needed for processing by the current release.
Save Performance Collection (SAVPFCOL)	Saves a copy of a single performance collection or a group of performance collections located in the same library.
Restore Performance Collection (RSTPFCOL)	Restores a performance collection or a group of performance collections in a single library.
Move Performance Collection (MOVPCOL)	Moves a performance collection from one library to another.

<i>Table 4. Collection Services CL commands</i>	
Command	Function
Create Performance Data (CRTPFRTA)	Creates a set of database files from performance information stored in a management collection (*MGTCOL) object.
Create Performance Summary (CRTPFRSUM)	Creates additional database files containing summary information for an existing Collection Services collection.
Change Management Collection (CHGMGTCOL)	Changes the attributes of the specified management collection.
Delete Management Collection (DLTMGTCOL)	Deletes a management collection from the system.
Start Performance Collection (STRPFRCOL)	Starts the system-level collection of performance data by Collection Services.
End Performance Collection (ENDPFRCOL)	Stops the system-level collection.
Check Performance Collection (CHKPFRCOL)	Determines the current status of the Collection Services server job (QYSPFCOL).
Configure Performance Collection (CFGPFRCOL)	Changes certain collection attributes and determines how Collection Services will manage data collection.

<i>Table 5. Disk Watcher CL commands</i>	
Command	Function
Add Disk Watcher Definition (ADDWDFN)	Allows you to specify the performance data that is to be collected during a Disk Watcher collection.
End Disk Watcher (ENDDW)	Ends a Disk Watcher collection.
Remove Disk Watcher Definition (RMVDWDFN)	Removes one or more Disk Watcher definitions from the system.
Start Disk Watcher (STRDW)	Starts the collection of disk performance data.

<i>Table 6. Job Watcher CL commands</i>	
Command	Function
Add Job Watcher Definition (ADDJWDFN)	Allows you to specify the performance data that is to be collected during a Job Watcher collection.
End Job Watcher (ENDJW)	Ends the Job Watcher collector.
Remove Job Watcher Definition (RMVJWDFN)	Allows you to remove one or more Job Watcher definitions from the system.
Start Job Watcher (STRJW)	Starts the Job Watcher collector.

<i>Table 7. Performance explorer (PEX) CL commands</i>	
Command	Function
Add PEX filter (ADDPEXFR)	Adds a new Performance Explorer (PEX) filter to the system.

<i>Table 7. Performance explorer (PEX) CL commands (continued)</i>	
Command	Function
<u>Print Performance Explorer Report (PRTPEXRPT)</u>	Prints a formatted listing of the data that was collected by the performance explorer.
<u>Start Performance Explorer (STRPEX)</u>	Starts a new Performance Explorer session or resumes a suspended Performance Explorer session.
<u>End Performance Explorer (ENDPEX)</u>	Stops the Performance Explorer session from collecting data.
<u>Add Performance Explorer Definition (ADDPEXDFN)</u>	Adds a new Performance Explorer definition to the system.
<u>Change Performance Explorer Definition (CHGPEXDFN)</u>	Changes an existing Performance Explorer definition.
<u>Create Performance Explorer Data (CRTPEXDTA)</u>	Creates the Performance Explorer database files based on the data in a Performance Explorer management collection object.
<u>Delete Performance Explorer Data (DLTPEXDTA)</u>	Deletes data that was collected by the Performance Explorer tool and was saved across a set of physical files in a particular library.
<u>Remove Performance Explorer Definition (RMVPEXDFN)</u>	Removes one or more Performance Explorer definitions from the system.
<u>Remove Performance Explorer Filter (RMVPEXFTR)</u>	Removes one or more Performance Explorer filters from the system.
<u>Work with Performance Explorer Definitions (WRKPEXDFN)</u>	Shows you the list of existing Performance Explorer (PEX) definitions. You can add new definitions or display, remove, or change existing definitions.
<u>Work with Performance Explorer Filters (WRKPEXFTR)</u>	Shows you a list of existing Performance Explorer filters. You can add new filters or display, remove, or change existing filters.

CL commands contained in IBM Performance Tools for i (5770-PT1)

This table provides a list of some CL commands that are a part of IBM Performance Tools for i. For more commands, see the Performance Tools for i Commands topic in the Programming topic collection.

<i>Table 8. General CL commands</i>	
Command	Function
<u>Analyze Performance Data (ANZPFRDTA)</u>	Produces recommendations to improve the performance of your system.
<u>Display Performance Data (DSPPFRDTA)</u>	Displays performance data collected by Collection Services.
<u>Print Activity Report (PRTACTRPT)</u>	Prints the activity report.
<u>Print Component Report (PRTCPTRPT)</u>	Prints the component report.
<u>Print Job Interval Report (PRTJOBTRPT)</u>	Prints the job interval report.
<u>Print Job Trace Report (PRTTRCRPT)</u>	Prints the job trace report.
<u>Print Lock Report (PRTLCKRPT)</u>	Prints the lock report.

Table 8. General CL commands (continued)

Command	Function
Print Pool Report (PRTPOLRPT)	Prints the pool report.
Print Resource Report (PRTSRSCRIPT)	Prints the resource report.
Print System Report (PRTSYSRPT)	Prints the system report.
Print Transaction Report (PRTTNSRPT)	Prints the transaction report.
Start Performance Tools (STRPFRT)	Calls the performance tools menu interface.

Related concepts

[Collection Services](#) Use Collection Services to collect job and system level performance data for later analysis.

[IBM i Job Watcher](#) Use Job Watcher to collect job performance data for any or all jobs, threads, and tasks on the system to diagnose job related performance problems.

[IBM i Disk Watcher](#) Use Disk Watcher to collect disk performance data to diagnose disk related performance problems.

[Performance Explorer](#) Use Performance Explorer (PEX) to collect detailed performance data about a specific application, program or system resource, and to provide detailed insight into a specific performance problem.

[IBM i Performance Tools for i](#) Learn more about the IBM Performance Tools for i features and tools.

Related reference

[IBM Performance Tools for i commands](#) The IBM Performance Tools for i commands display, report, graph, and analyze performance data by using the Performance Tools.

Notices

This information was developed for products and services offered in the U.S.A.

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not grant you any license to these patents. You can send license inquiries, in writing, to:

IBM Director of Licensing
IBM Corporation
North Castle Drive
Armonk, NY 10504-1785
U.S.A.

For license inquiries regarding double-byte (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

Intellectual Property Licensing
Legal and Intellectual Property Law
IBM Japan Ltd.
1623-14, Shimotsuruma, Yamato-shi
Kanagawa 242-8502 Japan

The following paragraph does not apply to the United Kingdom or any other country where such provisions are inconsistent with local law: INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this IBM product and use of those Web sites is at your own risk.

IBM may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

IBM Corporation
Software Interoperability Coordinator, Department YBWA
3605 Highway 52 N
Rochester, MN 55901
U.S.A.

Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement or any equivalent agreement between us.

Any performance data contained herein was determined in a controlled environment. Therefore, the results obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

All statements regarding IBM's future direction or intent are subject to change or withdrawal without notice, and represent goals and objectives only.

This information is for planning purposes only. The information herein is subject to change before the products described become available.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to the names and addresses used by an actual business enterprise is entirely coincidental.

COPYRIGHT LICENSE:

This information contains sample application programs in source language, which illustrate programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to IBM, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating platform for which the sample programs are written. These examples have not been thoroughly tested under all conditions. IBM, therefore, cannot guarantee or imply reliability, serviceability, or function of these programs. The sample programs are provided "AS IS", without warranty of any kind. IBM shall not be liable for any damages arising out of your use of the sample programs.

Each copy or any portion of these sample programs or any derivative work, must include a copyright notice as follows:

© (your company name) (year). Portions of this code are derived from IBM Corp. Sample Programs.

© Copyright IBM Corp. _enter the year or years_.

Programming interface information

This Performance reference information publication documents intended Programming Interfaces that allow the customer to write programs to obtain the services of IBM i.

Trademarks

IBM, the IBM logo, and ibm.com are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the Web at "[Copyright and trademark information](http://www.ibm.com/legal/copytrade.shtml)" at www.ibm.com/legal/copytrade.shtml.

Linux® is a registered trademark of Linus Torvalds in the United States, other countries, or both.

Microsoft, Windows, Windows NT, and the Windows logo are trademarks of Microsoft Corporation in the United States, other countries, or both.

Java and all Java-based trademarks and logos are trademarks of Oracle, Inc. in the United States, other countries, or both.

Other product and service names might be trademarks of IBM or other companies.

Terms and conditions

Permissions for the use of these publications is granted subject to the following terms and conditions.

Personal Use: You may reproduce these publications for your personal, noncommercial use provided that all proprietary notices are preserved. You may not distribute, display or make derivative works of these publications, or any portion thereof, without the express consent of IBM.

Commercial Use: You may reproduce, distribute and display these publications solely within your enterprise provided that all proprietary notices are preserved. You may not make derivative works of these publications, or reproduce, distribute or display these publications or any portion thereof outside your enterprise, without the express consent of IBM.

Except as expressly granted in this permission, no other permissions, licenses or rights are granted, either express or implied, to the publications or any information, data, software or other intellectual property contained therein.

IBM reserves the right to withdraw the permissions granted herein whenever, in its discretion, the use of the publications is detrimental to its interest or, as determined by IBM, the above instructions are not being properly followed.

You may not download, export or re-export this information except in full compliance with all applicable laws and regulations, including all United States export laws and regulations.

IBM MAKES NO GUARANTEE ABOUT THE CONTENT OF THESE PUBLICATIONS. THE PUBLICATIONS ARE PROVIDED "AS-IS" AND WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY, NON-INFRINGEMENT, AND FITNESS FOR A PARTICULAR PURPOSE.



Product Number: 5770-SS1