



SHARE

Technology - Connections - Results

What's New in Enterprise COBOL Version 4... Release 2!

Tom Ross
IBM

August 25, 2009
S1511



maxi
ove agility save tim
enges colleagues



Agenda

- New features of Enterprise COBOL V4R2
- Prerequisites for V4R2
- Requirements satisfied by V4R2



Briefly

- Enterprise COBOL for z/OS Version 4 Release 2
- Announced today, August 25
- General Availability, August 28
- Requires update to Language Environment
 - PK90754
- Full list of prerequisites at end of presentation



New features of V4 Release 2

- How about some details?



XML PARSE with validation

- Validation against XML schema
- No validation against DTD
 - An early requirement for XML PARSE (2001)
 - Good thing we did not do it, schema is better!
- What is validation? An XML schema?



XML PARSE with validation

- What is validation?
 - Validating an XML document determines whether the structure and content of the document conform to a set of rules
 - In Enterprise COBOL, the rules are expressed in an *XML schema*



XML PARSE with validation

- What is an XML schema?
 - A blueprint for a class of documents
 - Expressed in XML
 - Describes and constrains the structure and content of XML documents
 - Using a schema you can control the contents of attributes and elements. You have far more control over what is considered a valid XML document using a schema than with a DTD.

What is an XML schema?

```
01. <xsd:schema xmlns:xsd="http://www.w3.org/2001/XMLSchema">
02.   <xsd:element name="stockItem" type="stockItemType"/>
03.   <xsd:complexType name="stockItemType">
04.     <xsd:sequence>
05.       <xsd:element name="itemName" type="xsd:string" minOccurs="0"/>
06.       <xsd:element name="quantityOnHand">
07.         <xsd:simpleType>
08.           <xsd:restriction base="xsd:nonNegativeInteger">
09.             <xsd:maxExclusive value="100"/> </xsd:restriction>
10.         </xsd:simpleType>
11.       </xsd:element>
12.     </xsd:sequence>
13.     <xsd:attribute name="itemNumber" type="SKU" use="required"/>
14.   </xsd:complexType>
15.   <xsd:simpleType name="SKU">
16.     <xsd:restriction base="xsd:string">
17.       <xsd:pattern value="\d{3}-[A-Z]{2}"/> </xsd:restriction>
18.   </xsd:simpleType>
19. </xsd:schema>
```



What is an XML schema?

- The schema declares that the root element is **stockItem** (line 02),

01. `<xsd:schema xmlns:xsd="http://www.w3.org/2001/XMLSchema">`

02. `<xsd:element name="stockItem" type="stockItemType"/>`

- which has a mandatory **itemNumber** attribute of type SKU (line 13),

13. `<xsd:attribute name="itemNumber" type="SKU" use="required"/>`



What is an XML schema?

- stockItemType is defined by sequence (lines 04 - 12):
 - optional **itemName** element of type string (line 05)
 - required **quantityOnHand** with constrained range of 1 - 99 based on the type nonNegativeInteger (lines 06 - 11)

```
03. <xsd:complexType name="stockItemType">
04. <xsd:sequence>
05.   <xsd:element name="itemName" type="xsd:string" minOccurs="0"/>
06.   <xsd:element name="quantityOnHand">
07.     <xsd:simpleType>
08.       <xsd:restriction base="xsd:nonNegativeInteger">
09.         <xsd:maxExclusive value="100"/> </xsd:restriction>
10.     </xsd:simpleType>
11.   </xsd:element>
12. </xsd:sequence>
```



What is an XML schema?

- Type declarations can be inline and unnamed, as in lines 07 - 10, which include the **maxExclusive** facet to specify the legal values for the **quantityOnHand** element.

```
07.     <xsd:simpleType>
08.         <xsd:restriction base="xsd:nonNegativeInteger">
09.             <xsd:maxExclusive value="100"/>     </xsd:restriction>
10.     </xsd:simpleType>
```



What is an XML schema?

- For the itemNumber attribute, by contrast, the named type SKU is declared separately in lines 15 - 18, which include a pattern facet that uses regular expression syntax to specify that the legal values for that type consist of (in order):
 - 3 digits,
 - a hyphen-minus,
 - then two uppercase letters.

```
15. <xsd:simpleType name="SKU">  
16.   <xsd:restriction base="xsd:string">  
17.     <xsd:pattern value="\d{3}-[A-Z]{2}"/>   </xsd:restriction>  
18. </xsd:simpleType>
```



What is an XML schema?

```
<stockItem itemNumber="453-SR">  
<itemName>Stainless steel rope thimbles</itemName>  
<quantityOnHand>23</quantityOnHand>  
</stockItem>
```

- Root element is stockItem with attribute itemNumber
- itemNumber has 3 digits, a hyphen and 2 uppercase letters
- itemName contains a string
- quantityOnHand contains nonnegative integer less than 100



XML PARSE with validation

- How are schemas presented to the parser?
- COBOL validating parse uses XML System Services
- XML System services uses OSR...what?



XML PARSE with validation

- In Enterprise COBOL, a schema used for XML validation must be in a preprocessed format known as *Optimized Schema Representation*, or *OSR*.
- To generate a schema in OSR format from a text-form schema, use the z/OS UNIX command `xsdosrg`, which invokes the OSR generator provided by z/OS XML System Services.
- Example: to convert the text-form schema in file `item.xsd` to a schema in preprocessed format in file `item.osr`, you can use the following z/OS UNIX command:

```
xsdosrg -v -o /u/HLQ/xml/item.osr /u/HLQ/xml/item.xsd
```



XML PARSE with validation

- Use one of two forms of the **VALIDATING** phrase, depending on the location of the preprocessed schema:
 - In one form, you use the **FILE** keyword and specify an XML schema name. In this case, the schema must be in an MVS data set or a z/OS UNIX file.
 - In the other form, you specify the **identifier** of a data item that contains the schema.



XML PARSE with validation

```
XML PARSE xmldoc
```

```
    VALIDATING WITH FILE mySchema
```

```
    PROCESSING PROCEDURE p1
```

```
END-XML
```

If you use the FILE keyword and specify an XML schema name, the COBOL runtime library automatically retrieves the schema during execution of the XML PARSE statement.



XML PARSE with validation

- To associate an XML schema name with the external file that contains the schema, code the XML-SCHEMA clause in the SPECIAL-NAMES paragraph, specifying either a literal or a user-defined word to identify the file.
- For example, you can associate the XML schema name mySchema with the ddname DDSHEMA by coding the ddname as a literal in the XML-SCHEMA clause as follows:

ENVIRONMENT DIVISION.

CONFIGURATION SECTION.

SPECIAL-NAMES.

XML-SCHEMA mySchema IS 'DDSHEMA'.



XML PARSE with validation

- For running the program, you can associate ddname DDSHEMA with the z/OS UNIX file item.osr by coding a DD statement as follows:

```
//GO.DDSHEMA DD PATH='/u/HLQ/xml/item.osr'
```

- Or you can use an analogous TSO ALLOCATE command.
- Alternatively, DDSHEMA could be the name of an environment variable that identifies the external file by means of
 - a DSN option that specifies an MVS data set or
 - a PATH option that specifies a z/OS UNIX file



XML PARSE with validation

- VALIDATING WITH identifier
 - Requires schema in memory before XML PARSE statement
 - Use COBOL READ, EXEC CICS READ or SQL SELECT to get schema into memory
 - Supported under CICS
 - Could be efficient to read the schema into memory once and reuse it for subsequent XML documents
- VALIDATING WITH FILE
 - Reads schema into memory for every parse: convenient, but slow
 - Not supported under CICS



XML PARSE with validation

```
XML PARSE xmldoc
```

```
    VALIDATING WITH mySchema-id
```

```
    PROCESSING PROCEDURE p1
```

```
END-XML
```

If you do not use the FILE keyword and specify an XML schema identifier, the schema must be in the specified data item during execution of the XML PARSE statement.



XML PARSE with validation

VParse section.

Perform Get-schema

Display "Completed reading schema into memory"

Perform Validate-XML

Display "Completed validating PARSE"

If document-valid

 Perform Process-data-from-XML

End-if.



XML PARSE with validation

Data division.

File section.

FD F2

block contains 0

recording mode is F.

1 R2 Pic x(80).

Local-storage section.

01 fs2 Pic 99.

01 DOCL Pic 9(9) BINARY.

01 mySchema-id Pic X(1000000).

XML PARSE with validation



Get-schema section.

```
Open input F2
```

```
If FS2 not = 0 then Display 'OPEN failed,'  
    'FS=' FS2 Goback End-if
```

```
Set Not-EOF To TRUE
```

```
Compute DocL = 1
```

```
Perform Until EOF
```

```
    Read F2
```

```
        At End Set EOF To TRUE Display "EOF on F2"
```

```
        Not At End
```

```
            Display "Read: " R2(1:80)
```

```
            Move R2(1:80) To mySchema-id(DocL:80)
```

```
            Add 80 To DocL
```

```
            End-If
```

```
        End-Read
```

```
End-Perform
```

```
Close F2.
```



XML PARSE with validation

Validate-XML section.

```
Display "Reading and parsing XML ..."
```

```
Open input F1
```

```
Read F1
```

```
Display "Read: " R1(1:L)
```

```
XML parse R1(1:L)
```

```
  VALIDATING WITH myschema-id
```

```
  with encoding 1047
```

```
  processing procedure P
```

```
End-XML
```

```
Close F1.
```



XML PARSE with validation

- Any questions on XML PARSE with validation?



Performance improvements to parsing XML documents without validation

- In Enterprise COBOL V4R1, some users found that XML PARSE was slow with XMLPARSE(XMLSS)
- Typical setup was
 - STORAGE(00)
 - ANYHEAP(FREE)
- Solution
 - STORAGE(NONE) or
 - ANYHEAP(KEEP)
- In Enterprise COBOL V4R2 this problem is solved
 - You get the better performance with any settings



Compiler message severity customization

- New MSGEXIT suboption of EXIT compiler option
- Exit called for each compiler message
- Sample message exit IGYMSGXT included in SIGYSAMP
 - IGYMSGXT is explained in the Programming Guide
- User can change severity of diagnostic messages, convert FIPS messages to diagnostic, or suppress messages



Compiler message severity customization

- You can change the severity of a compiler message in the following ways:
 - Severity-I and severity-W compiler diagnostic messages, and FIPS messages, can be changed to have any severity from I through S
 - Assigning a severity to a FIPS message converts the FIPS message to a diagnostic message of the assigned severity



Compiler message severity customization

- As examples, you can:
 - Suppress optimizer warnings
 - Disallow REDEFINING a smaller item with a larger item by raising the severity of message 1154
 - Prevent inclusion of TEST information in the object file when the SYSDEBUG file cannot be opened, by raising the severity of message 4073
 - Disallow complex OCCURS DEPENDING ON by changing FIPS message 8235 from a category-E FIPS message to a severity-S compiler diagnostic message.



Compiler message severity customization

- Severity-E messages can be raised to severity S, but not lowered to severity I or W, because an error condition has occurred in the program
- Severity-S and severity-U messages cannot be changed to have a different severity
- You can request suppression of compiler messages as follows:
 - I, W, and FIPS messages can be suppressed
 - E and S messages cannot be suppressed
 - Suppressed messages do not affect compilation return code



Message severity customization examples

Evaluate EXIT-MESSAGE-NUM

- * Change severity of message 1154(W) to 12 ('S')
- * This is the case of redefining a large item
- * with a smaller item, IBM Req # MR0904063236

When(1154)

 Compute EXIT-USER-SEV = 12

- * Suppress all optimizer warning messages:
- * 3090, 3091, 3094, 3171 and 3235
- * This is IBM Req # MR00049476

When(3090) When(3091) When(3094) When(3171) When(3235)

 Compute EXIT-USER-SEV = -1



Message severity customization examples

- * Change severity of messages 3188(W) and 3189(W) to 12 ('S')
- * This is to force a fix for all SEARCH ALL cases that might
- * behave differently between COBOL compilers earlier than
- * Enterprise COBOL release V3R4 and later compilers such as
- * Enterprise COBOL Version 4 Release 2.

```
When(3188) When(3189)
  Compute EXIT-USER-SEV = 12
```

- * Change severity of message 4073(W) to 12 ('S')
- * Prevent inclusion of TEST information in object
- * if SYSDEBUG file cannot be opened.
- * This is IBM Req # MR0716082134

```
When(4073)
  Compute EXIT-USER-SEV = 12
```



Message severity customization example

Options in effect:

```
EXIT(NOINEXIT,NOPRTEXTIT,NOLIBEXIT,NOADEXIT,MSGEXIT(MSGXR TN))
FLAG(S,S)
```

- •
•

FIPS Messages	Total	Standard	Nonstandard	Obsolete		
	6	0	6	0		
Messages	Total	Informational	Warning	Error	Severe	Terminating
Suppressed:	2	1		1		

Messages suppressed by MSGEXIT: 2
Messages with severity modified by MSGEXIT: 2

* Statistics for COBOL program MSGXT2:
* Source records = 61
* Data Division statements = 14
* Procedure Division statements = 3
End of compilation 1, program MSGXT2, highest severity 8.



Compiler option BLOCK0 to exploit system-determined block size for QSAM output files

- Prior to this option, the default for files with no BLOCK CONTAINS clause was unblocked
 - One physical write for each logical write!
- BLOCK0 changes the default to blocked with no block size specified
 - BLOCK0 activates an implicit BLOCK CONTAINS 0 clause for all eligible files
- Eligible files are
 - QSAM (physical sequential)
 - No BLOCK CONTAINS clause
 - No RECORDING MODE U



COBOL user-defined words can include the underscore (_) character

- This includes data names and procedure names but also...
- Program names!
- Why?
 - You can use XML GENERATE to create XML with underscore in tag names - no post processing!
 - You can use variables with the same names as column names in DB2/SQL
 - You can share variable names across COBOL, PL/I, C/C++ and assembler
 - You can call C functions with underscores in names without using PGMNAME(LONGMIXED)



COBOL user-defined words can include the underscore (_) character

- COBOL words cannot start with underscore, but can end with underscore
- Literal program names can have underscore anywhere

```
PROGRAM-ID. my_func.  
WORKING-STORAGE SECTION.  
    77 x_ PIC X(8).  
    77 y_y PIC 99.  
    01 z_ PIC Z9.  
PROCEDURE DIVISION USING x_ y_y z_.  
    CALL '_cFunc'
```




Compiler listings display CICS options in effect

- Using the integrated CICS translator
- CICS 3.2 or CICS 4.1 with PTFs
- Now you can get DB2 and CICS options in effect in your COBOL listing!



Compiler listings display CICS options in effect

PP 5655-S71 IBM Enterprise COBOL for z/OS 4.2.0

Options in effect:

NOADATA
ADV
QUOTE
ARITH(COMPAT)
NOAWO
NOBLOCK0
BUFSIZE(4096)

.
.
.

CICS Options in effect:

CICS
DEBUG
EDF
NATLANG(EN)
APOST
NOSYSEIB
NOFEPI
NOCPSM
LINKAGE



Java interoperability – support for Java 5 and Java 6

- Java 5 was not supported with Enterprise COBOL V4R1
- Java 5 and Java 6 are supported with Enterprise COBOL V4R2
- Enterprise COBOL applications using object-oriented syntax for Java interoperability can now run with Java 5 or Java 6. Java SDK 1.4.2 continues to be supported
- COBOL requires a 31-bit Java SDK. 64-bit Java technology is not currently supported



Prerequisites

- z/OS, V1.9 (5694-A01), or later
- z/OS Language Environment V1.9, V1.10, or V1.11 with PTFs for APAR PK90754 installed
- Enterprise COBOL XML processing with the XMLPARSE(XMLSS) option requires:
 - z/OS XML Systems Services V1.9, V1.10, or V1.11, and PTFs for APAR OA28253
 - When parsing with validation under CICS, the PTFs for APAR OA29675 are also required



Prerequisites

- Including CICS options in effect as part of the COBOL listing requires
 - CICS Transaction Server for z/OS, V4.1 (5655-S97) and PTFs for APAR PK89224, or
 - CICS Transaction Server for z/OS, V3.2 (5655-M15) and PTFs for APAR PK91041
- Enterprise COBOL applications using object-oriented syntax for Java interoperability with Java 6 require
 - SDK for z/OS, Java Technology Edition V6 (5655-R31) and PTFs for APAR PK89762

Requirements satisfied by COBOL V4R2



- MR1216031446 - underscores for var name across COBOL, PL/I, C/C++ and HLASM.
- MR0317083231, MR120804208 - underscore XML GENERATE.
- MR071508264 - underscores in names so COBOL names can match DB2/SQL names
- MR0716082134(SYSDEBUG) MR00023071 (Obsolete FIPS) – satisfied by message severity customization
- MR00049476, MR0227075935, MR042506463, MR0524065843, MR072006118, MR0803072215, MR0904063236, MR110606344 - message severity customization
- MR0318042758, MR1126031815 – CICS options in effect in listing
- MR0529095034, MR1216031447 (SSLNGC03003), MR1107071627 – BLOCK0 compiler option



Backup detail slides