

IBM System Storage TS2360 Tape Drive Model S63 incorporates IBM LTO Ultrium 6 tape drive technology

Table of contents

1 Overview	7 Product number
2 Key prerequisites	8 Publications
3 Planned availability date	10 Technical information
3 Description	16 Terms and conditions
6 Product positioning	26 Pricing
7 Statement of general direction	29 Order now
	29 Corrections

At a glance



IBM® System Storage® TS2360 Tape Drive Model S63 is designed to deliver IBM tape reliability and performance at open systems prices. Features of the new Ultrium™ 6 model include:

- Specification data transfer rate of up to 160 MB/sec native compared to 140 MB/sec native for Linear Tape-Open™ (LTO™) Ultrium 5
- Support for LTO Generation 6 media specification tape cartridge compressed capacity of up to 6.25 TB with 2.5 to 1 compression
- The ability to read and write on Ultrium 6 and Ultrium 5 data cartridges, and read Ultrium 4 data cartridges
- 6 Gbps Serial Attached SCSI (SAS) attachment for Model S63
- Encryption support in the tape drive to work with application managed encryption
- 19-inch rack mount shelf option to accommodate two TS2360 Tape Drives side by side in the rack using just 2U of rack space
- Dual SAS ports per drive to improve availability
- IBM Long Term File System (LTFS) Single Drive Edition (SDE) for partitioning support
- Full-high drive form factor

For ordering, contact your IBM representative, an IBM Business Partner, or IBM Americas Call Centers at 800-IBM-CALL (Reference: YE001).

Overview

The new **IBM System Storage TS2360 Tape Drive Model S63** (SEO 3580S6X) external stand-alone or rack mountable unit, is designed to offer high capacity

and performance for the entry and midrange systems environment. The TS2360 incorporates the LTO **IBM System Storage Ultrium 6 Full-High SAS Tape Drive**. The TS2360 is designed to support the LTO Generation 6 media specification native data rate performance of up to 160 MB/sec compared to the IBM TS2350 LTO full-high tape drive (Ultrium 5) at up to 140 MB/sec native data transfer rate. The TS2360 tape drive supports the LTO Generation 6 media specifications for LTO tape drive technology. The TS2360 also supports LTO Generation 6 media specification of a compressed capacity of up to 6.25 TB with 2.5 to 1 compression (up to 2.5 TB native capacity) compared to previous LTO 5 compressed capacity of up to 3.0 TB with 2:1 compression (up to 1.5 TB native capacity) per tape cartridge. The TS2360 can read and write to Ultrium 6 and Ultrium 5 cartridges, and is read compatible with Ultrium 4 data cartridges. The Ultrium 6 tape drive is encryption-capable and designed to support application managed encryption.

The TS2360 Model S63 tape drive uses a 6 Gbps dual port SAS interface for connection to a wide spectrum of system servers. The new TS2360 attaches to selected IBM Power Systems™ models, and to IBM System x® and PC servers. The TS2360 also supports Microsoft™ Windows™, HP-UX, Oracle Solaris, and UNIX™.

The following IBM TS2360 Model S63 full-high LTO Ultrium 6 tape drive enhancements are designed to help improve performance, capacity, and reliability:

- Native LTO Generation 6 media specification data transfer rate of up to 160 MB/sec
- Support for LTO Generation 6 media specification tape cartridge compressed capacity of up to 6.25 TB with 2.5 to 1 compression
- 6 Gbps SAS attachment support
- A 1 GB internal buffer
- Application managed encryption support for full-high LTO Generation 6 SAS tape drives
- 16 KB cartridge memory with Ultrium 6 media
- Full-high drive form factor
- Two SAS ports per drive to improve availability and attachability
- IBM LTFS partitioning support

The enclosure width allows two TS2360 storage units to be mounted side by side in a 19-inch IBM server Rack Mount Shelf Kit, requiring four EIA units (4U) of rack space.

The TS2360 tape drive provides an excellent migration path from digital linear tape (DLT or SDLT), 1/4 in (QIC), 4 mm (DAT), 8 mm, or older LTO generation tape drives.

IBM LTFS SDE software is included with each TS2360 and leverages LTO6 tape partitioning. It is designed to enable a self-describing tape file format and to deliver an easy tape storage and distribution solution without the use of additional database applications. Customers of IBM LTFS software are those who require a standard tape cartridge format at a low cost and will use standalone IBM LTO6 tape drives. IBM LTFS is well-suited for those in the media and entertainment industry, and other fields that need massive data storage on tape for long retention periods, such as banking, scientific research, and government sectors. For further information and list of supported operating systems, refer to the following website

<http://www.ibm.com/tape/ltfs>

Key prerequisites

Appropriate levels of host software are required to attach the IBM System Storage TS2360 tape drive to selected IBM Power Systems, IBM System x, HP-UX, SUN, UNIX, and PC servers.

Refer to the [Technical information](#) section for details.

Planned availability date

December 7, 2012

Description

The IBM System Storage TS2360 Tape Drive, an external stand-alone or rack-mountable unit, contains an LTO Ultrium 6 tape drive designed for the heavy demands of backup tape storage. The TS2360 is supported for SAS attachment to IBM Power Systems, HP-UX, Oracle Solaris, UNIX, and PC servers.

TS2360 Tape Drive Model S63 incorporates sixth-generation IBM LTO Ultrium technology and offers the following improvements over the Ultrium 5 tape drive:

- **Increased performance:** Maximum tape drive throughput native data rate performance is up to 160 MB/sec.
Note: Although the Ultrium 6 tape drive provides the capability for excellent tape performance, other components of the system may limit the actual performance achieved. Also, although the compression technology used in the tape drive can typically double the amount of data that can be stored on the media, the actual degree of compression achieved is highly sensitive to the characteristics of the data being compressed.
- **Increased tape cartridge capacity:** LTO Generation 6 media specification compressed tape cartridge capacity of up to 6.25 TB is supported. The Ultrium 6 tape cartridge is expected to be announced in December 2012.
- **Compatible with Ultrium 5 cartridges:** The Ultrium 6 tape drive can read and write Ultrium 6 and 5 cartridges, and read Ultrium 4 cartridges.
- **Encryption support on Ultrium 6 SAS tape drives:** The IBM System Storage TS2360 LTO Ultrium 6 tape drive will support data encryption on the base drive with Ultrium 6 media, meeting LTO Generation 6 media specifications and application managed encryption.
- **Attachment options:** The TS2360 tape drive comes with a 6 Gbps SAS interface for connection to a wide spectrum of open system servers. The TS2360 is supported on IBM Power Systems, IBM System x, Oracle Solaris, HP-UX, Microsoft Windows, Linux, and other open systems.
- **Giant Magneto Resistive (GMR) head design:** The LTO 6 GMR head with beveled contouring reduces stiction/friction in the drive, especially with smoother LTO6 media types. This head design is well proven in enterprise tape products and helps minimize contact, debris accumulation, and wear on the tape as it moves over the read/write heads.
- **Digital speed matching:** The Ultrium 6 tape drive is designed to perform dynamic speed matching at one of fourteen speeds which reduces the number of backhitch repositions and improves throughput performance by more closely matching the speed of the data to or from the host. Speed matching on Ultrium 6 ranges from fourteen speeds, 60 to 160 MB/sec, versus seven speeds, 40 to 140 MB/sec on Ultrium 5.
- **WORM media support:** LTO Generation 6 media specification of compressed capacity of up to 6.25 TB WORM tape cartridges are designed for applications such as archiving and data retention, as well as those applications requiring an audit trail. These cartridges work with the IBM LTO Ultrium 6 tape drive to help prevent the alteration or deletion of user data.
- **Large internal data buffer:** There is 1 GB internal data buffer in the Ultrium 6 full-high tape drive.
- **IBM LTFS partitioning support:** The principal function of media partitioning is to allow for faster data access by splitting the cartridge into two media partitions. LTFS SDE is included with each TS2360. WORM media cannot be partitioned.

IBM LTFS software leverages LTO6 tape partitioning. It is designed to enable a self-describing tape file format and to deliver an easy tape storage and distribution solution without the use of additional database applications. Customers of IBM LTFS software are those who require a standard tape cartridge format at low-cost and will use stand alone IBM LTO6 tape drives. IBM LTFS is well-suited for those in the media and entertainment industry, and other fields that need massive data storage on tape for long retention periods, such as banking, scientific research, and government sectors. For further information and list of supported operating systems, refer to the following website

<http://www.ibm.com/tape/ltfs>

IBM maintains the latest levels of System Storage tape drive and library device drivers and documentation on the Internet. Utilize the Fix Central download portal by accessing the following website

<http://www.ibm.com/support/fixcentral>

There are a few pull down menus to navigate to the correct download as follows:

1. In the first pull down menu labeled "Product Group", select " System Storage ".
2. In the next pull down menu that appears which is labeled "Product Family", select "Tape Systems".
3. With the next pull down menu, "Product Type", select "Tape drivers and software".
4. This will bring up the "Product" menu, which provides selections for "Platform drivers, Tools, or Software".
5. Under "Platform drivers", in order to download your driver, select the correct operating system.
6. Two more pull down menus will appear with information. Click "Continue".
7. The next screen can be used to narrow the search, however just click "Continue" to view what is available.

The IBM Tape Device Drivers Installation and User's Guide can be found at the following website

<http://www-01.ibm.com/support/docview.wss?rs=577&uid=ssg1S7002972>

Proven IBM LTO Ultrium features enhanced in the IBM LTO Ultrium 6 tape drive include:

- **Highly integrated electronics using IBM engineered copper technology:** This technology is designed to reduce the total number of components in the drive, help lower chip temperatures, and reduce power requirements to deliver a more reliable drive. The sixth-generation drive electronics are designed to provide error correction of soft errors and in memory arrays.
- **Dual-stage 16-channel head actuator:** The actuator is designed to provide precision head alignment to help support higher track density and improved data integrity.
- **Independent tape loader, threader motors, and positive pin retention:** These are designed to help improve the reliability of loading and unloading a cartridge, and to retain the pin even if tension is dropped. An independent loader motor, coupled with the positive pin retention, is designed to cause the tape to thread with a higher level of reliability.
- **Graceful dynamic braking:** In the event of power failure, reel motors are designed to maintain tension and gradually decelerate instead of stopping abruptly, helping reduce tape breakage, stretching, or loose tape wraps during a sudden power outage.
- **Servo and track layout technology:** There are 2176 data tracks in Ultrium 6. The high-bandwidth servo system features a low mass servo to help more effectively track servo bands and improve data throughput with damaged media in less-than-optimal shock and vibration environments.

- **Surface Control Guiding Mechanism:** The IBM patented Surface Control Guiding Mechanism is designed to guide the tape along the tape path in the Ultrium 6 tape drive. This method uses the surface of the tape, rather than the edges, to control tape motion. This helps reduce tape damage (especially to the edges of the tape) and tape debris, which comes from the damaged edges and can accumulate in the head area.
- **Robust drive components optimized for automation environments:** To help enhance reliability and prolong the life of the drives, some of the most robust components available are used, such as an all metal clutch, steel ball bearings in the loader, robust leader block design, and a single circuit card.
- **Power management:** The Ultrium 6 tape drive power management function is designed to control the drive electronics to be either completely turned off or in a low-power mode when the circuit functions are not needed for drive operation. LTO6 is designed to have the most dramatic power savings implementation of any IBM LTO generation by bringing the wattage used by the drive down to a target of 5 watts at time of availability. Savings are realized in an unloaded state with no commands being issued to the drive over Ethernet or host interface.
- **Adaptive read equalization:** This feature is designed to automatically compensate for dynamic changes in readback signal response.
- **Dynamic amplitude asymmetry compensation:** This feature optimizes readback signals for linear readback responses from MR read head transducers.
- **Separate writing of multiple filemarks:** Separate writing of multiple filemarks is designed to cause any write command of two or more filemarks to cause a separate data set to be written containing all filemarks after the first. This feature has two advantages. First, it helps improve performance if a subsequent append overwrites somewhere after the first filemark, and second, write of multiple filemarks typically indicates a point where an append operation might occur after the first of these filemarks. This change helps prevent having to rewrite data sets containing customer data and the first filemark, if such an append occurs.
- **LTO Data Compression (LTO-DC):** The Ultrium 6, Ultrium 5, and Ultrium 4 use LTO-DC which is an implementation of a Lempel-Ziv class 1 (LZ-1) data compression algorithm. LTO-DC is an extension of Adaptive Lossless Data Compression (ALDC) and is an improvement over previous IBM lossless compression algorithms. "Scheme-Swapping" compression, patented by IBM, is designed to look ahead at incoming data and determine the most efficient storage method (either ALDC or pass-thru mode) to help provide optimal data compression and increase data throughput. The compression ratio for LTO Ultrium 6 is 2.5 to 1.
- **LTO Cartridge Memory (LTO-CM):** Contained within the LTO Ultrium data cartridge is the LTO-CM, which is a passive, contactless silicon storage device that is physically a part of the cartridge. The LTO-CM is designed to hold information about that specific cartridge, the media in the cartridge, and the data on the media. The storage capacity of the Generation 6 LTO-CM is 16320 bytes, double the capacity of Generation 5 & 4 LTO-CM 8160 bytes. Communication between the drive and the LTO-CM is via a low-level radio frequency field transmitted by the drive to the cartridge.
- **Statistical Analysis and Reporting System (SARS):** The Ultrium 6 tape drive uses SARS to help isolate failures between media and hardware. SARS uses the cartridge performance history saved in the CM module and the drive performance history kept in the drive flash EEPROM to help determine the likely cause of failure. SARS is designed to cause the drive to request a cleaner tape, to mark the media as degraded, and to indicate that the hardware has degraded.

Ultrium Data Cartridge

The TS2360 tape drive supports the LTO Generation 6 media specification of 6.25 TB compressed for LTO Generation 6 tape cartridges and 3.0 TB compressed for previous Ultrium 5 cartridges. The TS2360 can read and write to Ultrium 6 and Ultrium 5 cartridges, and is read compatible with Ultrium 4 cartridges.

These cartridges have been designed to provide several enhancements over previous tape technologies. They are designed to work with tape drives that have increased tape speeds and high-density data recording. The case is specially

designed for use in automated libraries and for repeated, unattended handling. The tape itself is an advanced metal particle tape developed for durability and capacity.

The TS2360 also offers IBM LTFS partitioning support which enables data to be written individually on media without affecting data on another partition. LTFS SDE is included with each TS2360.

With support for IBM LTO Ultrium-format tape data cartridges, the TS2360 tape drive provides an excellent migration path from digital linear tape (DLT or SDLT), 1/4 in (QIC), 4 mm (DAT), 8 mm, or older LTO generation tape drives. It can be a cost-effective solution for backup, save-and-restore, and archiving functions as the entry point for the family of IBM Ultrium tape products.

Accessibility by people with disabilities

A US Section 508 Voluntary Product Accessibility Template (VPAT) containing details on accessibility compliance can be requested at

http://www.ibm.com/able/product_accessibility/index.html

Section 508 of the US Rehabilitation Act

US Section 508 Voluntary Product Accessibility Template (VPAT) containing details on accessibility compliance can be requested at

http://www.ibm.com/able/product_accessibility/index.html

Product positioning

As you compare competitive tape solutions, consider:

- Capacity and performance requirements
- Data integrity, reliability, and availability
- Data security and encryption
- LTFS data partitioning and formatting
- Storage usage and application requirements
- Affordability
- Loyalty to legacy or existing tape formats
- Work environment, where space is limited

The IBM System Storage TS2360 Tape Drive and software applications are designed to address these requirements and constitute a functionally rich tape storage solution incorporating LTO Ultrium 6 tape drive technology.

The TS2360 Tape Drive Model S63 is an excellent choice if you use tape drives that require larger-capacity or higher-performance tape backup. The TS2360, an entry offering to the family of IBM Ultrium Tape products, is the answer to growing storage requirements and shrinking backup windows.

The TS2360 tape drive is an excellent tape storage solution if you use digital linear tape drives or require high-performance tape backup. In addition to reading and writing on IBM LTO Ultrium 5 or 6-format tape cartridges, the TS2360 tape drive provides an excellent functional alternative to DLT/SDLT, 1/4 in, 4 mm, 8 mm, IBM Magstar® MP 3570, or older LTO generation tape drives.

For capacity requirements greater than 6.25 TB (compressed) and for incorporating LTO Ultrium technology, the IBM System Storage TS2900 Tape Autoloader, IBM System Storage TS3100 or TS3200 Tape Library, or the IBM System Storage TS3310 and TS3500 Tape Libraries should be considered.

For mission-critical data protection needs, optimized for enterprise multimode and host attachment, or high-cycle and start/stop intensive tape applications, consider the IBM System Storage TS1130 or TS1140 Tape Drive with the IBM System Storage TS3500 Tape Library.

Statement of general direction

IBM intends to introduce tape cartridge media meeting the LTO Generation 6 media specifications.

IBM's statements regarding its plans, directions, and intent are subject to change or withdrawal without notice at IBM's sole discretion. Information regarding potential future products is intended to outline our general product direction and it should not be relied on in making a purchasing decision. The information mentioned regarding potential future products is not a commitment, promise, or legal obligation to deliver any material, code, or functionality. Information about potential future products may not be incorporated into any contract. The development, release, and timing of any future features or functionality described for our products remains at our sole discretion.

Product number

Description	Machine type	Model	Feature
TS2360 Tape Drive Model S63 with FHLT06 SAS Tape Drive with enclosure and power supply	3580	S63	
SEO Options Routing			0789
SEO Translation Admin Code - Options			0791
TAA Compliant Plant			0807
SEO SCSI Routing Code			0993
Admin SEO Translation Code			0996
Hungary CHW Plant 9SH			1764
Guad CHW Plant 9KQ			1765
ISTC CHW 9K2			1766
RTP CHW 9NR			1767
China Offload Routing			1770
Capacity Sched Svc			1772
Custom SLA Sched			1796
Consolidate Shipment			8031
TAA Compliant Order			8067
Options for Model S63:			
2.0M SAS/Mini-SAS 1x Cable			5402
2.0M Mini-SAS/Mini-SAS 1x Cable			5502
Rack Mount Shelf Kit w/PDU Line Cord			7003
Ultrium Cleaning Cartridge			8002
Ultrium 4 Data Cartridge (5-Pack)			8405
Ultrium 5 Data Cartridge (5-Pack)			8505
Attached to HP-UX System			9210
Attached to Oracle Solaris System			9211
Attached to windows System			9212
Attached to Linux™ System			9215
Attached to i5/OS™ or OS/400® Systems			9400
Attached to IBM AIX® System			9600
Power Cord Options:			
2.8M Power Cord 125V US/Canada			9800
2.8M Power Cord 250V France/Germany			9820
2.8M Power Cord 250V Denmark			9821
2.8M Power Cord 250V UK			9825
2.8M Power Cord 250V Israel			9827
2.8M Power Cord 250V Switzerland			9828
2.8M Power Cord 250V S. Africa			9829

2.8M Power Cord 250V Italy	9830
2.8M Power Cord 250V Australia	9831
2.8M Power Cord 250V US/Canada	9833
2.8M Power Cord 250V Uruguay/Argentina	9834
2.8M Power Cord 125V Taiwan	9835
2.8M Power Cord 250V China (PRC)	9840
2.8M Power Cord 250V Taiwan	9841
2.8M Power Cord 125V Japan	9842
2.8M Power Cord 250V Japan	9843
2.8M Power Cord 250V Korea	9844
2.8M Power Cord 250V India	9845
2.8M Power Cord 250V Brazil	9847
Rack Device to PDU Line Cord	9848

Single Entity Offerings (SEOs)

Description	Machine type	Model	SEO number
TS2360 Tape Drive Model S63 with FHLT06 SAS Tape Drive with enclosure and power supply	3580	S63	3580S6X
Options for Model S63:			
2.0M SAS/Mini-SAS 1x Cable			95P4711
2.0M Mini-SAS/Mini-SAS 1x Cable			95P4713
Rack Mount Shelf Kit w/PDU Line Cord			96P1565
Ultrium Cleaning Cartridge			23R7008
Ultrium 4 Data Cartridge (5-pack)			95P4278
Ultrium 5 Data Cartridge (5-pack)			46C2084
Power cord options:			
2.8M Power Cord 125V US/CAN			23R7141
2.8M Power Cord 250V US/CAN			23R7145
2.8M Power Cord 250V France/Germany			23R7146
2.8M Power Cord 250V Denmark			23R7147
2.8M Power Cord 250V UK			23R7148
2.8M Power Cord 250V Israel			23R7149
2.8M Power Cord 250V Switzerland			23R7150
2.8M Power Cord 250V S. Africa			23R7151
2.8M Power Cord 250V Italy			23R7152
2.8M Power Cord 250V Australia			23R7153
2.8M Power Cord 250V Uruguay/Argentina			23R7154
2.8M Power Cord 250V China (PRC)			23R7155
2.8M Power Cord 125V Taiwan			23R7158
2.8M Power Cord 250V Taiwan			23R6981
2.8M Power Cord 125V Japan			23R6982
2.8M Power Cord 250V Japan			23R6983
2.8M Power Cord 250V Korea			23R6984
2.8M Power Cord 250V India			23R6985
2.8M Power Cord 250V Brazil			23R6987
Rack Device to PDU Line Cord			23R7000

Business Partner information

If you are a Direct Reseller - System Reseller acquiring products from IBM , you may link directly to Business Partner information for this announcement. A PartnerWorld® ID and password are required (use IBM ID).

<https://www.ibm.com/partnerworld/mem/sla.jsp?num=112-161>

Publications

The following publication is shipped with the product. Additional copies are available.

Title	Order number
IBM System Storage TS2360 Tape	GA32-2228-00

Drive Model S63 Setup, Operator,
and Service Guide

The following publications are available. To order, contact your IBM representative.

Title	Order number
IBM System Storage TS2360 Tape Drive Model S63 Setup, Operator, and Service Guide	GA32-2228-00
IBM System Storage TS2360 Tape Drive Model S63 Quick Reference (English)	GC27-2278-01
IBM Tape Device Driver Installation and User's Guide (English)	GC27-2130-13
IBM Tape Device Driver Programming Reference (English)	GA32-0566-06

These publications are also available at

<http://www-05.ibm.com/e-business/linkweb/publications/servlet/pbi.wss>

Click on country, then enter publication number.

The device driver publications are also available at

<ftp://ftp.software.ibm.com/>

Note: Search on storage/devdrv/Doc/. All new IBM tape device drivers will only be posted to the web through the Fix Central download portal.

IBM maintains the latest levels of System Storage tape drive and library device drivers and documentation on the Internet. Utilize the Fix Central download portal by accessing the following website

<http://www.ibm.com/support/fixcentral>

There are a few pull down menus to navigate to the correct download as follows:

1. In the first pull down menu labeled "Product Group", select " System Storage ".
2. In the next pull down menu that appears which is labeled "Product Family", select "Tape Systems".
3. With the next pull down menu, "Product Type", select "Tape drivers and software".
4. This will bring up the "Product" menu, which provides selections for "Platform drivers, Tools, or Software".
5. Under "Platform drivers", in order to download your driver, select the correct operating system.
6. Two more pull down menus will appear with information. Click "Continue".
7. The next screen can be used to narrow the search, however just click "Continue" to view what is available.

The IBM Tape Device Drivers Installation and User's Guide can be found at the following website

<http://www-01.ibm.com/support/docview.wss?rs=577&uid=ssg1S7002972>

The IBM Systems Information Center provides you with a single information center where you can access product documentation for IBM systems hardware, operating systems, and server software. Through a consistent framework, you can efficiently

find information and personalize your access. The IBM Systems Information Center is at

<http://publib14.boulder.ibm.com/infocenter/systems>

IBM Publications Center Portal

<http://www.ibm.com/shop/publications/order>

The Publications Center is a worldwide central repository for IBM product publications and marketing material with a catalog of 70,000 items. Extensive search facilities are provided, as well as payment options via credit card. A large number of publications are available online in various file formats, which can currently be downloaded free of charge.

Services

Global Technology Services

IBM services include business consulting, outsourcing, hosting services, applications, and other technology management.

These services help you learn about, plan, install, manage, or optimize your IT infrastructure to be an On Demand Business. They can help you integrate your high-speed networks, storage systems, application servers, wireless protocols, and an array of platforms, middleware, and communications software for IBM and many non-IBM offerings. IBM is your one-stop shop for IT support needs.

For details on available services, contact your IBM representative or visit

<http://www.ibm.com/services/>

For details on available IBM Business Continuity and Recovery Services, contact your IBM representative or visit

<http://www.ibm.com/services/continuity>

For details on education offerings related to specific products, visit

<http://www.ibm.com/services/learning/index.html>

Select your country, and then select the product as the category.

Technical information

Specified operating environment

Physical specifications

- Width: 213 mm (8.4 in.)
- Depth: 332 mm (13.1 in.)
- Height: 109 mm (4.3 in.)
- Weight: 6.3 kg (13.84 lbs.)

To assure installability and serviceability in non-IBM industry-standard racks, review the installation planning information for any product-specific installation requirements.

Operating environment

- Temperature: 10° to 38° C (50° to 100° F)
- Relative humidity: 20% to 80%

- Wet bulb (caloric value): 26° C (78.8° F)
- Electrical power: 0.21 kVA 1.0 amps at 100 V ac, 0.5 amps at 240 V ac

Hardware requirements

The TS2360 tape drive comes with raven black covers. TS2360 Model S63 uses a SAS interface. The TS2360 tape drive can be attached to the IBM Power Systems , System x , and HP-UX, Oracle Solaris, and non-IBM servers that support those interface specifications. A current list of supported open system configurations is available from the following website

<http://www-1.ibm.com/storage/tape/lto>

Select the model, then "Product Details," " LTO Compatibility," to view "Independent Software Vendor Matrix (ISV)" for the product.

A power cord option number, if applicable, should also be specified.

Cables: For TS2360 Model S63, a SAS cable is required to attach a TS2360 tape drive to host a SAS adapter.

- SAS/Mini-SAS cables provide attachment from HBA with SFF-8470 to the TS2360 Ultrium 6 SAS drive with SFF-8088
- Mini-SAS/Mini-SAS cables provide attachment from the HBA with SFF-8088 SAS/Mini-SAS external cable to the TS2360 Ultrium 6 SAS drive with SFF-8088.

At least one of the above cables should be specified on the initial plant order.

The following cable options are available for SAS attachment:

- Feature number 5402 (SEO 95P4711) - 2.0M SAS/Mini-SAS Cable (from HBA with SFF-8470 to drive with SFF-8088)
- Feature number 5502 (SEO 95P4713) - 2.0M Mini-SAS/Mini-SAS Cable (from HBA with SFF-8088 to drive with SFF-8088)

Refer to the **Special Features** section of the TS2360 (3580) tape drive sales manual for detailed descriptions of these features.

Support for the following host bus adapters (HBAs)

For a current list of HBAs that support the TS2360, visit

<http://www-03.ibm.com/systems/support/storage/config/ssic/index.jsp>

Software requirements

For a current list of host software versions and release levels that support the TS2360, refer to the following website

<http://www-03.ibm.com/systems/support/storage/config/ssic/index.jsp>

Select the model, then "Product Details," and view "Interoperability matrix," for supported servers and operating systems for the product.

Tivoli® Storage Manager, BRMS, and other compatible software offerings provide storage and tape management software for the 3580 or TS2360 family of products. Supporting software and applications must be obtained separately from IBM , IBM Business Partners, or independent software vendors (ISVs). A list of compatible software is available from your IBM representative or at

<http://www-1.ibm.com/storage/tape/lto>

Select the model, then "Product Details," then " LTO Compatibility," and view "Independent Software Vendor (ISV) matrix for LTO " for the product.

IBM continues to work together with the ISVs to support the IBM LTO Ultrium tape drives or TS2360 family of products. Individual application vendors should be contacted for specific information and availability dates.

IBM maintains the latest levels of System Storage tape drive and library device drivers and documentation on the Internet. Utilize the Fix Central download portal by accessing the following website

<http://www.ibm.com/support/fixcentral>

There are a few pull down menus to navigate to the correct download as follows:

1. In the first pull down menu labeled "Product Group", select " System Storage ".
2. In the next pull down menu that appears which is labeled "Product Family", select "Tape Systems".
3. With the next pull down menu, "Product Type", select "Tape drivers and software".
4. This will bring up the "Product" menu, which provides selections for "Platform drivers, Tools, or Software".
5. Under "Platform drivers", in order to download your driver, select the correct operating system.
6. Two more pull down menus will appear with information. Click "Continue".
7. The next screen can be used to narrow the search, however just click "Continue" to view what is available.

The IBM Tape Device Drivers Installation and User's Guide can be found at the following website

<http://www-01.ibm.com/support/docview.wss?rs=577&uid=ssg1S7002972>

Compatibility

The IBM LTO Ultrium 6 tape drive can read and write IBM LTO 6 and 5 data cartridges, and read IBM LTO Ultrium 4 data cartridges. The LTO Generation 6 media specification of 6.25 TB compressed data cartridges can only be used on the new IBM LTO Ultrium 6 tape drives.

Limitations

SAS cable lengths are limited to 5.5 m (18 ft).

Installing more than one TS2360 tape drive on a SAS bus may impact tape drive or system performance. Intermixing of other SAS devices on the same bus as the TS2360 may also impact performance of those devices.

IBM Ultrium 6 Tape Cartridges will not be available until December 2012.

Although multiple systems may be attached to a tape drive, the systems cannot use the drive simultaneously.

While the compression technology can increase the amount of data stored on the media, the actual degree of compression achieved is highly sensitive to the characteristics of the data being compressed.

Planning information

Customer responsibilities

Physical planning is a customer responsibility. Detailed planning information is in the *IBM System Storage TS2360 Tape Drive Model S63 Setup, Operator, and Service Guide (GC27-2277)*. The TS2360 tape drive is designated as a customer setup unit (CSU). It is the customers' responsibility to install the unit. Customers are responsible for obtaining the appropriate SAS adapters, cables, and interposers (if required) for system attachment. Customers are also responsible for ordering media. For optimum performance, the customer must obtain the latest level of firmware prior to installing the unit. Customers can download the latest level of firmware from the LTO website

Downloading or obtaining from IBM and installing designated Machine Code (microcode, basic input/output system code (called "BIOS"), utility programs, device drivers, and diagnostics delivered with an IBM machine) and other software updates from an IBM Internet website or from other electronic media must be completed by the customer with the help of instructions that IBM provides. Customers may request IBM to install Machine Code changes; however, there may be a charge for that service.

Cable orders

For TS2360 Model S63, a SAS cable is required to attach a TS2360 tape drive to a host SAS adapter. SAS/Mini-SAS cables provide attachment from HBA with SFF-8470 to the drive with SFF-8088. Mini-SAS/Mini-SAS cables provide attachment from HBA SFF-8088 to the drive with SFF-8088. At least one SAS cable should be specified on the initial plant order.

The following cable options are available for SAS attachment:

- Feature number 5402 - 2.0M SAS/Mini-SAS Cable (from HBA with SFF-8470 to drive with SFF-8088)
- Feature number 5502 - 2.0M Mini-SAS/Mini-SAS Cable (from HBA with SFF-8088 to drive with SFF-8088)

Refer to the **Specify or Special Features** section of the 3580 Sales Manual for a detailed description of the cables available.

Installability

Installation time for the TS2360 tape drive is approximately 0.5 to 0.7 hours.

Packaging

Product	Shipment group	Number of boxes
3580	TS2360 with Tape Drive (3580 Model S63) Power cord option One cleaning cartridge Documentation CD that includes: <ul style="list-style-type: none">- IBM System Storage TS2360 Model S63 Tape Drive Setup, Operator, and Service Guide- IBM System Storage TS2360 Statement of Limited Warranty- IBM Translated Safety Notices Documentation kit that includes: <ul style="list-style-type: none">- License Agreement- IBM System Storage TS2360 Statement of Limited Warranty- IBM System Storage TS2360 Model S63 Quick Reference- CD pointer document- Device Driver pointer document- Compliance document LTFS Single Drive Edition (SDE) software CD	1

Supplies

For users: The LTO Ultrium 6 2.5 TB data cartridges for use in the TS2360 Model S63 tape drive can be purchased using feature numbers or SEO numbers when available with the initial order. IBM-branded media supplies can or will also be available directly through AAS. IBM-branded media supplies can or will also be available at 1-888-IBM-MEDIA (426-6334) in the US and Canada.

Refer to the 3589 Sales Manual for further information.

To request a list of dealers in your area, call IBM at 1-888-IBM-MEDIA (426-6334)

For remarketers: Remarketers can purchase IBM-branded media and media supplies, call 1-888-IBM-MEDIA.

For additional information, go to the following website

<http://www.storage.ibm.com/media>

For users and remarketers:

IBM-branded media and media supplies can be ordered directly through AAS using IBM machine type 3589.

IBM-branded media and media supplies can be also purchased through Priority Fulfillment Services and its distribution channel in North America, Latin America, and Asia Pacific.

For information about Priority Fulfillment Services distribution channels, call 1-888-IBM Media in the US and Canada or visit

<http://www.ibm.com/storage/media>

Security, auditability, and control

This product uses the security and auditability features of the host hardware, host software, and application software.

The customer is responsible for evaluation, selection, and implementation of security features, administrative procedures, and appropriate controls in application systems and communications facilities.

IBM Electronic Services

IBM has transformed its delivery of hardware and software support services to help you achieve higher system availability. Electronic Services is a Web-enabled solution that offers an exclusive, no-additional-charge enhancement to the service and support available for IBM servers. These services are designed to provide the opportunity for greater system availability with faster problem resolution and preemptive monitoring. Electronic Services comprises two separate, but complementary, elements: Electronic Services news page and Electronic Services Agent.

The Electronic Services news page is a single Internet entry point that replaces the multiple entry points traditionally used to access IBM Internet services and support. The news page enables you to gain easier access to IBM resources for assistance in resolving technical problems.

The Electronic Service Agent™ is no-additional-charge software that resides on your server. It monitors events and transmits system inventory information to IBM on a periodic, client-defined timetable. The Electronic Service Agent automatically reports hardware problems to IBM. Early knowledge about potential problems enables IBM to deliver proactive service that may result in higher system availability and performance. In addition, information collected through the Service Agent is made available to IBM service support representatives when they help answer your questions or diagnose problems. Installation and use of IBM Electronic Service Agent for problem reporting enables IBM to provide better support and service for your IBM server.

To learn how Electronic Services can work for you, visit

<http://www.ibm.com/support/electronic>

Terms and conditions

Volume orders: Contact your IBM representative.

IBM Global Financing

Yes

Onsite Service

To obtain copies of the IBM Statement of Limited Warranty, contact your reseller or IBM .

In the United States, call 800-IBM-SERV (426-7378), or write to:

Warranty Information
P.O. Box 12195
Research Triangle Park, NC 27709
Attn: Dept JDJA/B203

Warranty period

- Three years, IBM Ultrium media is warranted separately

Optional IBM features initially installed in an IBM machine carry the same warranty period as the machine. If installed after the initial machine installation, they carry the balance of the machine warranty or the optional feature warranty, whichever is greater.

Warranty service

If required, IBM provides repair or exchange service, depending on the type of warranty service specified below for the machine. IBM will attempt to resolve your problem over the telephone or electronically by access to an IBM website. Certain machines contain remote support capabilities for direct problem reporting, remote problem determination, and resolution with IBM . You must follow the problem determination and resolution procedures that IBM specifies. Following problem determination, if IBM determines On-site Service is required, scheduling of service will depend upon the time of your call, machine technology and redundancy, and availability of parts. Service levels are response-time objectives and are not guaranteed. The specified level of warranty service may not be available in all worldwide locations. Additional charges may apply outside IBM's normal service area. Contact your local IBM representative or your reseller for country- and location-specific information.

The type of service is Customer Replaceable Unit (for example, keyboard, mouse, speaker, memory, or hard disk drive).

Customer Replaceable Unit (CRU) Service

IBM provides a replacement CRU to you for you to install. CRU information and replacement instructions are shipped with your machine and are available from IBM at any time on your request. A CRU is designated as being either a Tier 1 (mandatory) or a Tier 2 (optional) CRU. Installation of Tier 1 CRUs, as specified in this announcement, is your responsibility. If IBM installs a Tier 1 CRU at your request, you will be charged for the installation. You may install a Tier 2 CRU yourself or request IBM to install it, at no additional charge, under the type of warranty service specified below, On-site Service.

Based upon availability, a CRU will be shipped for next business day (NBD) delivery. IBM specifies in the materials shipped with a replacement CRU whether a defective

CRU must be returned to IBM . When return is required, return instructions and a container are shipped with the replacement CRU, and you may be charged for the replacement CRU if IBM does not receive the defective CRU within 15 days of your receipt of the replacement.

The following parts have been designated as Tier 1 CRUs:

- The complete IBM TS2360 tape drive with enclosure
- External 2.0 m SAS Cables

On-site Service

At IBM's discretion, you will receive specified CRU service, or IBM will repair the failing machine at your location and verify its operation. You must provide a suitable working area to allow disassembly and reassembly of the IBM machine. The area must be clean, well lit, and suitable for the purpose.

Service level is:

- 9 hours per day, Monday through Friday, excluding holidays, next business day response. Calls must be received by 5 pm local time in order to qualify for next business day response.

Call IBM at 1-800-IBM-SERV (426-7378) to assist with problem isolation for hardware to determine if warranty service is required.

Calls must be received by 5:00 p.m. local time in order to qualify for NBD service.

International Warranty Service

International Warranty Service (IWS) is not available.

Licensing

Programs included with this product are licensed under the terms and conditions of the License Agreements that are shipped with the system.

Maintenance services

ServicePac , ServiceSuite , ServiceElect, and ServiceElite

ServicePac® , ServiceSuite® , ServiceElect, and ServiceElite provide hardware warranty service upgrades, maintenance, and selected support services in one agreement.

Warranty service upgrade

During the warranty period, a warranty service upgrade provides an enhanced level of On-site Service for an additional charge. A warranty service upgrade must be purchased during the warranty period and is for a fixed term (duration). It is not refundable or transferable and may not be prorated. If required, IBM will provide the warranty service upgrade enhanced level of On-site Service acquired by the customer. Service levels are response-time objectives and are not guaranteed.

IBM will attempt to resolve your problem over the telephone or electronically by access to an IBM website. You must follow the problem determination and resolution procedures that IBM specifies. Scheduling of service will depend upon the time of your call, machine technology, and availability of parts.

CRUs will be provided as part of the machine's standard warranty CRU Service.

Maintenance service

If required, IBM provides repair or exchange service, depending on the type of maintenance service specified below for the machine. IBM will attempt to resolve

your problem over the telephone or electronically by access to an IBM website. You must follow the problem determination and resolution procedures that IBM specifies. Scheduling of service will depend upon the time of your call, machine technology, and availability of parts. Service levels are response-time objectives and are not guaranteed.

CRU Service

If your problem can be resolved with a CRU (for example, keyboard, mouse, speaker, memory, or hard disk drive), IBM will ship the CRU to you for you to install. CRU information and replacement instructions are shipped with your machine and are available from IBM at any time on your request.

IBM specifies in the materials shipped with a replacement CRU whether a defective CRU must be returned to IBM. When return is required, return instructions and a container are shipped with the replacement CRU, and you may be charged for the replacement CRU if IBM does not receive the defective CRU within 15 days of your receipt of the replacement.

On-site Service

IBM On-site Exchange (IOE), IBM will exchange the failing Machine at your location and verify its operation. You must provide suitable working area to allow disassembly and reassembly of the IBM Machine. The area must be clean, well lit and suitable for the purpose.

Maintenance service (ICA)

Maintenance services are available for ICA legacy contracts.

Alternative service (warranty service upgrades)

During the warranty period, a warranty service upgrade provides an enhanced level of On-site Service for an additional charge. A warranty service upgrade must be purchased during the warranty period and is for a fixed term (duration). It is not refundable or transferable and may not be prorated. If required, IBM will provide the warranty service upgrade enhanced level of On-site Service acquired by the customer. Service levels are response-time objectives and are not guaranteed.

IBM will attempt to resolve your problem over the telephone or electronically by access to an IBM website. You must follow the problem determination and resolution procedures that IBM specifies. Scheduling of service will depend upon the time of your call, machine technology, and availability of parts.

A CRU will be provided as part of the machine's standard warranty CRU Service except that you may install a Tier 1 CRU yourself or request IBM to install it, at no additional charge, under the type of warranty service specified below, On-site Service.

Maintenance service

If required, IBM provides repair or exchange service, depending on the type of maintenance service specified below for the machine. IBM will attempt to resolve your problem over the telephone or electronically by access to an IBM website. You must follow the problem determination and resolution procedures that IBM specifies. Scheduling of service will depend upon the time of your call, machine technology, and availability of parts. Service levels are response-time objectives and are not guaranteed.

CRU Service

If your problem can be resolved with a CRU (for example, keyboard, mouse, speaker, memory, or hard disk drive), IBM will ship the CRU to you for you to install.

CRU information and replacement instructions are shipped with your machine and are available from IBM at any time on your request.

IBM specifies in the materials shipped with a replacement CRU whether a defective CRU must be returned to IBM . When return is required, return instructions and a container are shipped with the replacement CRU, and you may be charged for the replacement CRU if IBM does not receive the defective CRU within 15 days of your receipt of the replacement.

On-site Service

Non-IBM parts support

Warranty service

IBM is now shipping machines with selected non-IBM parts that contain an IBM field replaceable unit (FRU) part number label. These parts are to be serviced during the IBM machine warranty period. IBM is covering the service on these selected non-IBM parts as an accommodation to its customers, and normal warranty service procedures for the IBM machine apply.

Warranty service upgrades and maintenance services

Under certain conditions, IBM Integrated Technology Services repairs selected non-IBM parts at no additional charge for machines that are covered under warranty service upgrades or maintenance services.

IBM Service provides hardware problem determination on non-IBM parts (for example, adapter cards, PCMCIA cards, disk drives, or memory) installed within IBM machines covered under warranty service upgrades or maintenance services and provides the labor to replace the failing parts at no additional charge.

If IBM has a Technical Service Agreement with the manufacturer of the failing part, or if the failing part is an accommodations part (a part with an IBM FRU label), IBM may also source and replace the failing part at no additional charge. For all other non-IBM parts, customers are responsible for sourcing the parts. Installation labor is provided at no additional charge, if the machine is covered under a warranty service upgrade or a maintenance service.

Customer Replaceable Unit (CRU) Service

To obtain copies of the IBM Statement of Limited Warranty, contact your reseller or IBM .

In the United States, call 800-IBM-SERV (426-7378), or write to:

Warranty Information
P.O. Box 12195
Research Triangle Park, NC 27709
Attn: Dept JDJA/B203

Warranty period

- Three years, IBM Ultrium media is warranted separately

Optional IBM features initially installed in an IBM machine carry the same warranty period as the machine. If installed after the initial machine installation, they carry the balance of the machine warranty or the optional feature warranty, whichever is greater.

Warranty service

If required, IBM provides repair or exchange service, depending on the type of warranty service specified below for the machine. IBM will attempt to resolve your problem over the telephone or electronically by access to an IBM website. You must follow the problem determination and resolution procedures that IBM specifies. Scheduling of service will depend upon the time of your call, machine technology, and availability of parts. Service levels are response-time objectives and are not guaranteed. The specified level of warranty service may not be available in all worldwide locations. Additional charges may apply outside IBM's normal service area. Contact your local IBM representative or your reseller for country- and location-specific information.

Customer Replaceable Unit (CRU) Service

IBM provides a replacement CRU (for example, keyboard, mouse, speaker, memory, or hard disk drive) to you for you to install. CRU information and replacement instructions are shipped with your machine and are available from IBM at any time on your request. Installation of Tier 1 CRUs, as specified in this announcement, is your responsibility. If IBM installs a Tier 1 CRU, at your request, you will be charged for the installation.

Based upon availability, a CRU will be shipped for next business day (NBD) delivery. IBM specifies in the materials shipped with a replacement CRU whether a defective CRU must be returned to IBM. When return is required, return instructions and a container are shipped with the replacement CRU, and you may be charged for the replacement CRU if IBM does not receive the defective CRU within 15 days of your receipt of the replacement.

The following parts have been designated as Tier 1 CRUs:

- The complete IBM TS2360 tape drive with enclosure
- External 2.0 m SAS Cables

Call IBM at 1-800-IBM-SERV (426-7378) to assist with problem isolation for hardware to determine if warranty service is required.

Calls must be received by 5:00 p.m. local time in order to qualify for NBD service.

International Warranty Service

International Warranty Service (IWS) is not available.

Licensing

Programs included with this product are licensed under the terms and conditions of the License Agreements that are shipped with the system.

Maintenance services

ServicePac , ServiceSuite , ServiceElect, and ServiceElite

ServicePac , ServiceSuite , ServiceElect, and ServiceElite provide hardware warranty service upgrades, maintenance, and selected support services in one agreement.

Warranty service upgrade

Not available.

Maintenance service

If required, IBM provides exchange service, depending on the type of maintenance service specified below for the machine. IBM will attempt to resolve your problem over the telephone or electronically by access to an IBM website. You must

follow the problem determination and resolution procedures that IBM specifies. Scheduling of service will depend upon the time of your call, machine technology, and availability of parts. Service levels are response-time objectives and are not guaranteed.

CRU Service

If your problem can be resolved with a CRU (for example, keyboard, mouse, speaker, memory, or hard disk drive), IBM will ship the CRU to you for you to install. CRU information and replacement instructions are shipped with your machine and are available from IBM at any time on your request.

IBM specifies in the materials shipped with a replacement CRU whether a defective CRU must be returned to IBM . When return is required, return instructions and a container are shipped with the replacement CRU, and you may be charged for the replacement CRU if IBM does not receive the defective CRU within 15 days of your receipt of the replacement.

On-site Service

IBM On-site Exchange (IOE), IBM will exchange the failing Machine at your location and verify its operation. You must provide suitable working area to allow disassembly and reassembly of the IBM Machine. The area must be clean, well lit and suitable for the purpose.

Maintenance service (ICA)

Maintenance services are available for ICA legacy contracts.

Alternative service (warranty service upgrades)

Maintenance service

If required, IBM provides exchange service, depending on the type of maintenance service specified below for the machine. IBM will attempt to resolve your problem over the telephone or electronically by access to an IBM website. You must follow the problem determination and resolution procedures that IBM specifies. Scheduling of service will depend upon the time of your call, machine technology, and availability of parts. Service levels are response-time objectives and are not guaranteed.

CRU Service

If your problem can be resolved with a CRU (for example, keyboard, mouse, speaker, memory, or hard disk drive), IBM will ship the CRU to you for you to install. CRU information and replacement instructions are shipped with your machine and are available from IBM at any time on your request.

IBM specifies in the materials shipped with a replacement CRU whether a defective CRU must be returned to IBM . When return is required, return instructions and a container are shipped with the replacement CRU, and you may be charged for the replacement CRU if IBM does not receive the defective CRU within 15 days of your receipt of the replacement.

On-site Service

IBM On-site Exchange (IOE), IBM will exchange the failing Machine at your location and verify its operation. You must provide suitable working area to allow disassembly and reassembly of the IBM Machine. The area must be clean, well lit and suitable for the purpose.

Non-IBM parts support

Warranty service

IBM is now shipping machines with selected non-IBM parts that contain an IBM field replaceable unit (FRU) part number label. These parts are to be serviced during the IBM machine warranty period. IBM is covering the service on these selected non-IBM parts as an accommodation to its customers, and normal warranty service procedures for the IBM machine apply.

Warranty service upgrades and maintenance services

Under certain conditions, IBM Integrated Technology Services repairs selected non-IBM parts at no additional charge for machines that are covered under warranty service upgrades or maintenance services.

IBM Service provides hardware problem determination on non-IBM parts (for example, adapter cards, PCMCIA cards, disk drives, or memory) installed within IBM machines covered under warranty service upgrades or maintenance services and provides the labor to replace the failing parts at no additional charge.

If IBM has a Technical Service Agreement with the manufacturer of the failing part, or if the failing part is an accommodations part (a part with an IBM FRU label), IBM may also source and replace the failing part at no additional charge. For all other non-IBM parts, customers are responsible for sourcing the parts. Installation labor is provided at no additional charge, if the machine is covered under a warranty service upgrade or a maintenance service.

CRU and Machine Exchange Service

To obtain copies of the IBM Statement of Limited Warranty, contact your reseller or IBM .

In the United States, call 800-IBM-SERV (426-7378), or write to:

Warranty Information
P.O. Box 12195
Research Triangle Park, NC 27709
Attn: Dept JDJA/B203

Warranty period

- Three years, IBM Ultrium media is warranted separately

Optional IBM features initially installed in an IBM machine carry the same warranty period as the machine. If installed after the initial machine installation, they carry the balance of the machine warranty or the optional feature warranty, whichever is greater.

Warranty service

If required, IBM provides exchange service for the machine. IBM will attempt to resolve your problem over the telephone or electronically by access to an IBM website. You must follow the problem determination and resolution procedures that IBM specifies. Scheduling of service will depend upon the time of your call, machine technology, and availability of parts. Service levels are response-time objectives and are not guaranteed. The specified level of warranty service may not be available in all worldwide locations. Additional charges may apply outside IBM's normal service area. Contact your local IBM representative or your reseller for country- and location-specific information.

CRU and Machine Exchange service

At IBM's discretion you will receive specified CRU service, or IBM will initiate shipment of a replacement machine to your location. You are responsible for its installation and verification of operation. You must pack the failed machine into the shipping container that contained the replacement machine and return the failed machine to IBM . Transportation charges, both ways, are paid by IBM . You may be charged for the replacement machine if IBM does not receive the failed machine within 15 days of your receipt of the replacement.

Call IBM at 1-800-IBM-SERV (426-7378) to assist with problem isolation for hardware to determine if warranty service is required.

International Warranty Service

International Warranty Service (IWS) is not available.

Licensing

Programs included with this product are licensed under the terms and conditions of the License Agreements that are shipped with the system.

Maintenance services

ServicePac , ServiceSuite , ServiceElect, and ServiceElite

ServicePac , ServiceSuite , ServiceElect, and ServiceElite provide hardware warranty service upgrades, maintenance, and selected support services in one agreement.

Warranty service upgrade

During the warranty period, a warranty service upgrade provides an enhanced level of On-site Service for an additional charge. A warranty service upgrade must be purchased during the warranty period and is for a fixed term (duration). It is not refundable or transferable and may not be prorated. If required, IBM will provide the warranty service upgrade enhanced level of On-site Service acquired by the customer. Service levels are response-time objectives and are not guaranteed.

IBM will attempt to resolve your problem over the telephone or electronically by access to an IBM website. You must follow the problem determination and resolution procedures that IBM specifies. Scheduling of service will depend upon the time of your call, machine technology, and availability of parts.

On-site Service

IBM On-site Exchange (IOE), IBM will exchange the failing Machine at your location and verify its operation. You must provide suitable working area to allow disassembly and reassembly of the IBM Machine. The area must be clean, well lit and suitable for the purpose.

Maintenance service

If required, IBM provides exchange service for the machine. IBM will attempt to resolve your problem over the telephone or electronically by access to an IBM website. You must follow the problem determination and resolution procedures that IBM specifies. Scheduling of service will depend upon the time of your call, machine technology, and availability of parts. Service levels are response-time objectives and are not guaranteed.

On-site Service

IOE is provided. IBM will exchange the failing machine at your location and verify its operation. You must provide a suitable working area to allow disassembly and

reassembly of the IBM machine. The area must be clean, well lit, and suitable for the purpose.

Maintenance service (ICA)

Maintenance services are available for ICA legacy contracts.

Alternative service (warranty service upgrades)

During the warranty period, a warranty service upgrade provides an enhanced level of On-site Service for an additional charge. A warranty service upgrade must be purchased during the warranty period and is for a fixed term (duration). It is not refundable or transferable and may not be prorated. If required, IBM will provide the warranty service upgrade enhanced level of On-site Service acquired by the customer. Service levels are response-time objectives and are not guaranteed.

IBM will attempt to resolve your problem over the telephone or electronically by access to an IBM website. You must follow the problem determination and resolution procedures that IBM specifies. Scheduling of service will depend upon the time of your call, machine technology, and availability of parts.

On-site Service

IBM On-site Exchange (IOE) is provided. IBM will exchange the failing machine at your location and verify its operation. You must provide a suitable working area to allow disassembly and reassembly of the IBM machine. The area must be clean, well lit, and suitable for the purpose.

Maintenance service

If required, IBM provides exchange service for the machine. IBM will attempt to resolve your problem over the telephone or electronically by access to an IBM website. You must follow the problem determination and resolution procedures that IBM specifies. Scheduling of service will depend upon the time of your call, machine technology and redundancy, and availability of parts. Service levels are response-time objectives and are not guaranteed.

On-site Service

IOE is provided. IBM will exchange the failing machine at your location and verify its operation. You must provide a suitable working area to allow disassembly and reassembly of the IBM machine. The area must be clean, well lit, and suitable for the purpose.

Non-IBM parts support

Warranty service

IBM is now shipping machines with selected non-IBM parts that contain an IBM field replaceable unit (FRU) part number label. These parts are to be serviced during the IBM machine warranty period. IBM is covering the service on these selected non-IBM parts as an accommodation to its customers, and normal warranty service procedures for the IBM machine apply.

Warranty service upgrades and maintenance services

Under certain conditions, IBM Integrated Technology Services repairs selected non-IBM parts at no additional charge for machines that are covered under warranty service upgrades or maintenance services.

IBM Service provides hardware problem determination on non-IBM parts (for example, adapter cards, PCMCIA cards, disk drives, or memory) installed within IBM machines covered under warranty service upgrades or maintenance services and provides the labor to replace the failing parts at no additional charge.

If IBM has a Technical Service Agreement with the manufacturer of the failing part, or if the failing part is an accommodations part (a part with an IBM FRU label), IBM may also source and replace the failing part at no additional charge. For all other non-IBM parts, customers are responsible for sourcing the parts. Installation labor is provided at no additional charge, if the machine is covered under a warranty service upgrade or a maintenance service.

Warranty service upgrades

IBM hourly service rate classification

Two

Field-installable features

No

Model conversions

No

Machine installation

Customer setup. Customers are responsible for installation according to the instructions IBM provides with the machine.

Graduated program license charges apply

No

Licensed machine code

IBM Machine Code is licensed for use by a customer on the IBM machine for which it was provided by IBM under the terms and conditions of the IBM License Agreement for Machine Code, to enable the machine to function in accordance with its specifications, and only for the capacity authorized by IBM and acquired by the customer. You can obtain the agreement at

http://www.ibm.com/servers/eserver/support/machine_warranties/machine_code.html

This license machine code pertains to a machine using LMC model:

3580-S63

IBM may release changes to the Machine Code. IBM plans to make the Machine Code changes available for download from the IBM System Storage technical support website

http://www-304.ibm.com/jct01004c/systems/support/machine_warranties/index.html

You may also obtain updated code by contacting your IBM representative.

If the machine does not function as warranted and your problem can be resolved through your application of downloadable Machine Code, you are responsible for downloading and installing these designated Machine Code changes as IBM specifies. If you would prefer, you may request IBM to install downloadable Machine Code changes; however, you may be charged for that service.

Educational allowance

None

Pricing

Product charges

Description	Machine type	Model	Feature number	Field install only	Plant install only	
TS2360 Tape Drive Model S63 with FHLT05 SAS Tape Drive with enclosure and power supply	3580	S63		N	Y	
Options for Model S63/S6X:						
2.0M SAS/Mini-SAS 1x Cable			5402*	N	N	
2.0M Mini-SAS/Mini-SAS 1x Cable			5502*	N	N	
Rack Mount Shelf Kit w/PDU Line Cord			7003*	N	N	
Ultrium Cleaning Cartridge			8002*	N	Y	
Ultrium 4 Data Cartridge (5-pack)			8405*	N	Y	
Ultrium 5 Data Cartridge (5-pack)			8505*	N	Y	
Attached to HP-UX System			9210*	N/C	N	Y
Attached to Oracle Solaris System			9211*	N/C	N	Y
Attached to Windows System			9212*	N/C	N	Y
Attached to Linux System			9215*	N/C	N	Y
Attach to IBMi or OS/400 System			9400*	N/C	N	Y
Attach to IBM AIX System			9600*	N/C	N	Y
Power cord options:						
2.8M Power Cord 125V US/Canada			9800*	N	Y	
2.8M Power Cord 250V France/Germany			9820*	N	Y	
2.8M Power Cord 250V Denmark			9821*	N	Y	
2.8M Power Cord 250V UK			9825*	N	Y	
2.8M Power Cord 250V Israel			9827*	N	Y	
2.8M Power Cord 250V Switzerland			9828*	N	Y	
2.8M Power Cord 250V S. Africa			9829*	N	Y	
2.8M Power Cord 250V Italy			9830*	N	Y	
2.8M Power Cord 250V Australia			9831*	N	Y	
2.8M Power Cord 250V US/Canada			9833*	N	Y	
2.8M Power Cord 250V Uruguay/Argentina			9834*	N	Y	
2.8M Power Cord 125V Taiwan			9835*	N	Y	
2.8M Power Cord 250V China (PRC)			9840*	N	Y	
2.8M Power Cord 250V Taiwan			9841*	N	Y	
2.8M Power Cord 125V Japan			9842*	N	Y	
2.8M Power Cord 250V Japan			9843*	N	Y	
2.8M Power Cord 250V Korea			9844*	N	Y	

2.8M Power Cord 250V India	9845*	N	Y
2.8M Power Cord 250V Brazil	9847*	N	Y
Rack Device to PDU Line Cord	9848*	N	Y

The Single Entity Offerings (SEO)

Description	Machine type	Model	SEO number	Plant install only
TS2360 Tape Drive Model S63 with LTO SAS Tape Drive with enclosure and power supply	3580	S6X	3580S6X	Y
2.0M SAS/Mini-SAS 1x Cable			95P4711*	N
2.0M Mini-SAS/Min-SAS 1x Cable			95P4713*	N
Rack Mount Shelf Kit, w/PDU Line Cord			96P1565*	N
Ultrium Cleaning Cartridge			23R7008*	Y
Ultrium 4 Data Cartridge (5-Pack)			95P4278*	Y
Ultrium 5 Data Cartridge (5-Pack)			46C2084*	Y
Power Cord Options:				
2.8M Power Cord 125V US/Canada			23R7141*	Y
2.8M Power Cord 250V US/Canada			23R7145*	Y
2.8M Power Cord 250V France/Germany			23R7146*	Y
2.8M Power Cord 250V Denmark			23R7147*	Y
2.8M Power Cord 250V UK			23R7148*	Y
2.8M Power Cord 250V Israel			23R7149*	Y
2.8M Power Cord 250V Switzerland			23R7150*	Y
2.8M Power Cord 250V S. Africa			23R7151*	Y
2.8M Power Cord 250V Italy			23R7152*	Y
2.8M Power Cord 250V Australia			23R7153*	Y
2.8M Power Cord 250V Uruguay/Argentina			23R7154*	Y
2.8M Power Cord 250V China (PRC)			23R7155*	Y
2.8M Power Cord 125V Taiwan			23R7158*	Y
2.8M Power Cord 250V Taiwan			23R6981*	Y
2.8M Power Cord 125V Japan			23R6982*	Y
2.8M Power Cord 250V Japan			23R6983*	Y
2.8M Power Cord 250V Korea			23R6984*	Y
2.8M Power Cord 250V India			23R6985*	Y
2.8M Power Cord 250V Brazil			23R6987*	Y
Rack Device to PDU Line Cord			23R7000*	Y

* Previously announced features

Pricing terms

Prices in the following PDF prices link are suggested list prices on day of announcement for the U.S. only. They are provided for your information only. Dealer prices may vary, and prices may also vary by country. IBM list price does not include tax or shipping and is subject to change without notice.

[ENUS-112-161-LIST_PRICES_2012_11_06.PDF](#)

ServicePac for warranty and maintenance

ServicePac for Warranty and Maintenance

Machine type/ Model	ServicePac MTM	ServicePac SEO	Description
3580-S63	6756869	00AA254	3 Year Onsite Repair 9x5 Next Business Day
3580-S6X	6756869	00AA254	3 Year Onsite Repair 9x5 Next Business Day
3580-S63	675686A	00AA255	3 Year Onsite Repair 24x7 4 Hour Response
3580-S6X	675686A	00AA255	3 Year Onsite Repair 24x7 4 Hour Response
3580-S63	675686B	00AA256	5 Year Onsite Repair 24x7 4 Hour Response
3580-S6X	675686B	00AA256	5 Year Onsite Repair 24x7 4 Hour Response

ServicePac for Maintenance Agreement

Machine type/ Model	ServicePac MTM	ServicePac SEO	Description
3580-S63	6756F5Z	00AA257	1 Year Onsite Repair 9x5 Next Business Day
3580-S6X	6756F5Z	00AA257	1 Year Onsite Repair 9x5 Next Business Day
3580-S63	6756F6A	00AA258	1 Year Onsite Repair 24x7 4 Hour Response
3580-S6X	6756F6A	00AA258	1 Year Onsite Repair 24x7 4 Hour Response
3580-S63	6756F6B	00AA259	2 Year Onsite Repair 9x5 Next Business Day
3580-S6X	6756F6B	00AA259	2 Year Onsite Repair 9x5 Next Business Day
3580-S63	6756F6C	00AA260	2 Year Onsite Repair 24x7 4 Hour Response
3580-S6X	6756F6C	00AA260	2 Year Onsite Repair 24x7 4 Hour Response

ServicePac prices

For ServiceElect (ESA) maintenance service charges, contact IBM Global Services at 888-IBM-4343 (426-4343).

Billable exchange price

For all local charges, contact your IBM representative.

IBM Global Financing

IBM Global Financing offers competitive financing to credit-qualified customers to assist them in acquiring IT solutions. Offerings include financing for IT acquisition, including hardware, software, and services, from both IBM and other manufacturers or vendors. Offerings (for all customer segments: small, medium, and large enterprise), rates, terms, and availability can vary by country. Contact your local IBM Global Financing organization or visit

<http://www.ibm.com/financing>

IBM Global Financing offerings are provided through IBM Credit LLC in the United States, and other IBM subsidiaries and divisions worldwide to qualified commercial and government customers. Rates are based on a customer's credit rating, financing terms, offering type, equipment type, and options, and may vary by country. Other restrictions may apply. Rates and offerings are subject to change, extension, or withdrawal without notice.

Financing solutions from IBM Global Financing can help you stretch your budget and affordably acquire the new product. But beyond the initial acquisition, our end-to-end approach to IT management can also help keep your technologies current, reduce costs, minimize risk, and preserve your ability to make flexible equipment decisions throughout the entire technology life cycle.

Order now

To order, contact the Americas Call Centers or your local IBM representative, or your IBM Business Partner.

To identify your local IBM representative or IBM Business Partner, call 800-IBM-4YOU (426-4968).

Phone: 800-IBM-CALL (426-2255)
Fax: 800-2IBM-FAX (242-6329)
Internet: callserv@ca.ibm.com
Mail: IBM Teleweb Customer Support
ibm.com® Sales Execution Center, Americas North
3500 Steeles Ave. East, Tower 3/4
Markham, Ontario
Canada
L3R 2Z1

Reference: YE001

The Americas Call Centers, our national direct marketing organization, can add your name to the mailing list for catalogs of IBM products.

Note: Shipments will begin after the planned availability date.

Trademarks

Power Systems, i5/OS and Electronic Service Agent are trademarks of IBM Corporation in the United States, other countries, or both.

IBM, System Storage, System x, Magstar, OS/400, AIX, PartnerWorld, Tivoli, ServicePac, ServiceSuite and ibm.com are registered trademarks of IBM Corporation in the United States, other countries, or both.

Microsoft and Windows are trademarks of Microsoft Corporation in the United States, other countries, or both.

UNIX is a registered trademark of The Open Group in the United States and other countries.

Linux is a registered trademark of Linus Torvalds in the United States, other countries, or both.

Other company, product, and service names may be trademarks or service marks of others.

Terms of use

IBM products and services which are announced and available in your country can be ordered under the applicable standard agreements, terms, conditions, and prices in effect at the time. IBM reserves the right to modify or withdraw this announcement at any time without notice. This announcement is provided for your information only. Additional terms of use are located at:

<http://www.ibm.com/legal/us/en/>

For the most current information regarding IBM products, consult your IBM representative or reseller, or visit the IBM worldwide contacts page

<http://www.ibm.com/planetwide/us/>

Corrections

(Corrected on January 29, 2013)

The Attachment options bullet under the Description section has been updated. All occurrences of Sun Solaris have been updated to Oracle Solaris.

(Corrected on December 6, 2012)

ServicePac information was added to the Pricing section.