

IBM Power System H924 server offers enterprise-class deployment of the SAP HANA database and applications

Table of contents

2 Overview	26 Product number
3 Key prerequisites	36 Publications
3 Planned availability date	38 Technical information
3 Description	46 Terms and conditions
25 Product positioning	52 Prices
26 Statement of general direction	68 Order now
	68 Corrections

At a glance

IBM^(R) Power Systems^(TM) are designed for memory-intensive workloads like SAP HANA. These highly flexible systems with best-in-class virtualization give clients the ability to consolidate their workloads and can help to reduce the footprint in their data center.

The IBM Power^(R) System H924 (9223-42H) for SAP HANA server easily integrates into your organization's cloud and cognitive strategy and delivers industry-leading price/performance for your mission-critical workloads.

- Gain insights faster from your data with 4 TB in-memory database capabilities for SAP HANA, IBM Db2^(R), and Oracle.
- Deliver superior price/performance for your mission-critical applications with room to scale in IBM AIX^(R), IBM i, and Linux^(R) environments.
- Help guard against security threats because the server's features, reliability, and performance.
- Harness the integrated virtualization capabilities of the server to rapidly deploy, optimize, and recover workloads.
- Migrate from previous Power Systems servers with Live Partition Mobility capabilities. Every new Power H924 server comes with a temporary IBM PowerVM^(R) license for your old server to support a seamless move to IBM POWER9^(TM) technology-based servers.
- Use this cloud-enabled server to build an agile, containerized cloud on a server platform that is optimized for data and cognitive services.
- Extend IBM i, the integrated operating system, and connect to the cognitive capabilities of the IBM Cloud using secure APIs.

The Power System H924 (9223-42H) is a powerful 2-socket server and is an ideal system for SAP HANA. With best-in-class virtualization and up to 4096 GB of DDR4 ECC memory, this system can be used as a building block for SAP HANA clusters. The Power System H924 server ships with up to 24 activated cores and I/O configuration flexibility to meet today's growth and tomorrow's processing needs. The server features:

- The following fully activated IBM POWER9 processor module configurations in a 19-inch rack-mount, 4U (EIA units) form factor:
 - 8-core typical 3.8 to 4.0 GHz (max)
 - 10-core typical 3.5 to 3.9 GHz (max)

- 12-core typical 3.4 to 3.9 GHz (max)
- Up to 4096 GB of DDR4 ECC memory
 - Running at speeds of 2133, 2400, and 2666 Mbps
- Storage backplane options:
 - Base 12 SFF-3 Bays/RDX Bay.
 - Split feature to 6+6 SFF Bays: Add a second SAS Controller.
 - Expanded Function 18 SFF-3 Bays/Dual IOA with Write Cache and optional external SAS port.
 - Expanded Function 12 SFF-3 Bays/RDX Bay and optional external SAS port.
- Optional PCIe3 NVMe carrier card with two M.2 module slots
- Expansion capabilities for the EXP12SX/EXP24SX SFF Gen2-bay Drawer
- Hot-plug PCIe Gen4 and Gen3 slots
- Integrated:
 - Service processor
 - EnergyScale™ technology
 - Hot-plug and redundant cooling
 - USB 3.0 ports
 - Two HMC ports
 - One system port with RJ45 connector
- Four hot-plug, redundant power supplies
- 19-inch rack-mounting hardware (4U)

Overview

The next generation of Power Systems servers with POWER9 technology is built with innovations that can help deliver security and reliability for the data-intensive workloads of today's enterprises. POWER9 technology is designed from the ground up for data-intensive workloads like databases and analytics.

This new server generation has twice the memory footprint of IBM POWER8[®] servers, making it an ideal platform for in-memory and data-centric applications. Changes in the memory subsystem and the use of industry standard memory DIMMs take POWER9 technology to the next level by superseding a number of existing price/performance offerings. Designed to run commercial, cognitive, and database workloads POWER9 technology provides a highly competitive server platform, client references indicate POWER[®] servers help provide a robust and secure backbone of their IT infrastructure. More companies are using POWER technology in their IT infrastructure down from the shop level to large data center deployments.

The Power System H924 (9223-42H) for SAP HANA server by default has its Power Management mode set to Max Performance. This mode can dynamically optimize the processor frequency at any given time based on CPU utilization and operating environmental conditions. For a description of this feature and other power management options available for this server, see the [IBM EnergyScale for POWER9 Processor-Based Systems](#) website.

The Power H924 for SAP HANA server provides an optimized system configuration using enhanced processors, DDR4 ECC memory, and IBM PowerVM Enterprise Edition virtualization for enterprise-class deployment of the SAP HANA database and applications.

With this highly flexible system with best-in-class virtualization, clients can consolidate their workloads and reduce the footprint in their data center. In addition, clients can run mixed workloads with traditional SAP and nonproduction workloads running in a shared pool side by side with Production SAP HANA, leading to an efficient use of the system and a high utilization. SAP HANA Tailored Datacenter Integration Phase 5 (TDI5) gives clients the flexibility to use the storage and

networking of their choice, and change configurations, with support from SAP, all while achieving a lower TCO.

The Power H924 for SAP HANA server supports two processor sockets, offering 8-core or 16-core typical 3.8 to 4.0 GHz (max), 10-core or 20-core typical 3.5 to 3.9 GHz (max), or 24-core typical 3.4 to 3.9 GHz (max) configurations in a 19-inch rack-mount, 4U (EIA units) drawer configuration. All the cores are active.

The Power H924 for SAP HANA server supports a maximum of 32 DDR4 ECC DIMM slots. Memory features supported are 16 GB, 32 GB, 64 GB, and 128 GB and run at different speeds of 2133, 2400, and 2666 Mbps, offering a maximum system memory of 4096 GB.

- I/O options in the system unit include:
 - Three PCIe x16 Gen4, full-height, half length slots (CAPI)
 - Two PCIe x8 Gen4, full-height, half-length slots (with x16 connector) (CAPI)
 - Two PCIe x8 Gen3, full-height, half-length slots (with x16 connector)
 - Four PCIe x8 Gen3, full-height, half-length slots (one of these slots is used for the required base LAN adapter)
 - Storage feature: Twelve or eighteen 2.5-in. SFF-3 (Gen3 carrier) disk bays
 - RAID 0, 5, 6, 10, 5T2, 6T2, and 10T2 support
 - One RDX bay (only available with x12 disk bays, not available with x18 disk bays)
 - PCIe3 NVMe carrier card with two M.2 module slots
- One front and two rear USB 3.0 ports
- Service processor
- 2+2 Redundant hot-plug AC power supplies in each enclosure
- 19-inch rack-mount 4U configuration
- PowerVM

Feature exchange

Not applicable.

Key prerequisites

Linux is required as the primary operating system with a minimum of 75% of total cores activated.

AIX and IBM i can be chosen as secondary operating systems, with a maximum of 25% of total cores activated across both.

If the AIX and IBM i total core activation requirements exceed 25% then the Power S924 is the recommended server.

Planned availability date

March 20, 2018

Description

The POWER9 scale-out family is the first set of entry servers that comes completely cloud-enabled out of the box with integrated PowerVM Enterprise capabilities. Additionally, on-chip analytics and algorithms help clients run their workloads at an optimized processor frequency for performance and throughput. In combination

with the DDR4 memory footprint of 4 TB, IBM provides systems that are unmatched by the competition in terms of memory scaling as well as the core to memory ratio needed for data-centric and in-memory workloads. Live Partition Mobility capabilities are built in, to cloud-enable your POWER9 infrastructure and help you migrate from previous Power Systems. Every new H924 also has the option of a temporary PowerVM license for your old server to support a seamless move of workloads to POWER9. The Power System H924 server has built-in security that can help you be ready for current and future security threats.

The Power System H924 (9223-42H) for SAP HANA server supports two processor sockets, offering 8-core or 16-core typical 3.8 to 4.0 GHz (max), 10-core or 20-core typical 3.5 to 3.9 GHz (max), or 24-core typical 3.4 to 3.9 GHz (max) POWER9 processor-based configurations in a 19-inch rack-mount, 4U (EIA units) drawer configuration. All the cores are active. The Power H924 server supports a maximum of 32 DDR4 ECC DIMM slots. Memory features supported are 16 GB, 32 GB, 64 GB, and 128 GB, allowing for a maximum system memory of 4096 GB.

Summary of standard features for Power H924:

- POWER9 processor modules:
 - 8-core typical 3.8 to 4.0 GHz (max) POWER9 Processor (#EP1E)
 - 10-core typical 3.5 to 3.9 GHz (max) POWER9 Processor (#EP1F)
 - 12-core typical 3.4 to 3.9 GHz (max) POWER9 Processor (#EP1G)
- High-performance Mbps DDR4 ECC memory
 - 16 GB (#EM62), 32 GB (#EM63), 64 GB (#EM64), or 128 GB (#EM65) memory features; different sizes/configurations run at different frequencies of 2133, 2400, and 2666 Mbps
 - Up to 4 TB of DDR4 memory with two Power Systems processors
 - Up to 2 TB of DDR4 memory with one Power Systems processor
- Storage Backplane feature:
 - Base 12 SFF-3 Bays/RDX Bay.
 - Optionally, split the above SFF-3 bays and add a second integrated SAS controller without cache.
 - Expanded function 18 SFF-3 Bays/Dual IOA with Write Cache and Optional External SAS port.
 - Expanded function 12 SFF-3 Bays/RDX Bay/Dual IOA with Write Cache and Optional External SAS port.
 - Optionally, attach an EXP12SX/EXP24SX SAS HDD/SSD Expansion Drawer to the dual IOA.
- Up to two PCIe3 NVMe carrier cards with two M.2 module slots (with up to four Mainstream 400 GB SSD NVMe M.2 modules)
 - Quantity of one PCIe3 NVMe carrier card can be ordered only with a storage backplane. If PCIe3 NVMe carrier card is ordered with a storage backplane, then the optional split feature is not supported.
- PCIe slots with single processor:
 - One x16 Gen4 full-height, half-length (CAPI)
 - One x8 Gen4, full-height, half-length (with x16 connector) (CAPI)
 - Two x8 Gen3, full-height, half-length (with x16 connectors)
 - Four x8 Gen3 full-height, half-length (One of these slots is used for the required base LAN adapter.)
- PCIe slots with two processors:
 - Three x16 Gen4 full-height, half-length (CAPI)
 - Two x8 Gen4 full-height, half-length (with x16 connectors) (CAPI)
 - Two x8 Gen3 full-height, half-length (with x16 connectors)
 - Four x8 Gen3 full-height, half-length (One of these slots is used for the required base LAN adapter.)
- Integrated:

- Service processor
- EnergyScale technology
- Hot-swap and redundant cooling
- One front USB 3.0 ports
- Two rear USB 3.0 ports
- Two HMC 1GbE RJ45 ports
- One system port with RJ45 connector
- Four hot-plug, redundant power supplies
- 19-inch rack-mounting hardware (4U)

PowerVM

PowerVM, which delivers industrial-strength virtualization for AIX and Linux environments on POWER processor-based systems, has been enhanced with a virtualization-oriented performance monitor, and performance statistics are available through the HMC. These performance statistics can be used to understand the workload characteristics and to prepare for capacity planning.

H924 SW tier for IBM i

- IBM i SW tier is P20.
- The IBM i QPRCFEAT number is the same numeric value as the processor feature code.

Power H924 system configuration

The minimum Power H924 initial order must include a processor module, two 16 GB DIMMs, four power supplies and line cords, an operating system indicator, a cover set indicator, and a Language Group Specify. Also, the configuration must include one of the storage options and the network options below:

Storage options:

- For boot from NVMe: One NVMe carrier and one NVMe M.2 Module.
- For boot from local SFF-3 HDD/SDD: One storage backplane and one SFF-3 HDD or SDD.
- For boot from SAN: Internal HDD or SSD and RAID cards are not required if feature 0837 (Boot from SAN) is selected. A Fibre Channel adapter must be ordered if feature 0837 is selected.

Network options:

- One PCIe2 4-port 1 Gb Ethernet adapter.
- One of the supported 10 Gb Ethernet adapters

AIX or Linux is the primary operating system. The minimum defined initial order configuration is as follows:

Feature number	Description	Quantity	Notes
EU0B	Operator Panel LCD Display	1	
Processors			
EP1E	8-core typical 3.8 to 4.0 GHz (max) POWER9 Processor	1	
or			
EP1F	10-core typical 3.5 to 3.9 GHz (max) POWER9 Processor	1	

Feature number	Description	Quantity	Notes
Processor activations			
EP4E	One Processor Core Activation for #EP1E	8	
or			
EP4F	One Processor Core Activation for #EP1F	10	
Memory DIMMs			
EM62	16 GB DDR4 Memory	2	
or			
EM63	32 GB DDR4 Memory	2	
or			
EM64	64 GB DDR4 Memory	2	
or			
EM65	128 GB DDR4 Memory	2	
Storage Backplane			
EJ1C	Twelve SFF-3 Bays/RDX Bay	1	Optional split card EJ1E
or			
EJ1D	Eighteen SFF-3 Bays/RDX Bay/ Dual IOA with Write Cache	1	
or			
EJ1M	Twelve SFF-3 Bays/RDX Bay/2x EXT PT	1	
or			
EC59	PCIe3 NVMe carrier card w/2 M.2 module slots	1	Must order, at a minimum, one of feature ES14
Disk Drive			
ESDB	300 GB 15K RPM SAS SFF-3 Disk Drive (AIX/Linux)	1	
LAN Adapter			
5899	PCIe2 LP 4-port 1GbE Adapter	1	
Power supplies/ Power cord			
EB2M	AC Power Supply - 1400 W for Server (200 - 240 V AC)	4	
6458	Power Cord 4.3 m (14 ft), Drawer to IBM PDU (250V/10A)	4	6458 - (default)
9300/97xx	Language Group Specify	1	9300 - (default)
Front Bezel			
EJU3	Front IBM Bezel for 12-Bay BackPlane	1	
or			

Feature number	Description	Quantity	Notes
EJUG	Front IBM Bezel for 18-Bay BackPlane	1	
or			
EJU4	Front OEM Bezel for 12-Bay BackPlane	1	
or			
EJUH	Front OEM Bezel for 18-Bay BackPlane	1	
Primary operating system			
2146	Primary Operating System Indicator - AIX	1	
or			
2147	Primary Operating System Indicator - Linux	1	

- The racking approach for the initial order must be either a 7014-T00, 7014-T42, 7965-S42, or 7953-94Y. If an additional rack is required for I/O expansion drawers as an MES to an existing system, either a feature 0551, 0553, or ER05 rack must be ordered.
- If NVMe carrier card feature EC59 is selected, no disk units are required to be ordered. If neither feature EC59 nor feature 0837 (SAN boot) is ordered, then at least one disk unit is required to be ordered. If no HDD/SSD/SAN boot (#0837) is ordered, then feature EC59 (with at least one of #ES14) is the load source.
- One PCIe2 4-port 1 GbE Adapter (#5899) is defaulted. Options for servers with AIX and Linux as the primary operating system are one of a 10 Gb Ethernet adapter, either feature EC2S, EC2U, EN0H, EN0K, EN0S, EN0U, EN0W, or EN15.

The minimum defined initial order configuration, if no choice is made, when IBM i is the primary operating system, is:

Feature number	Description	Quantity	Notes
EU0B	Operator Panel LCD Display	1	
Processors			
EP1E	8-core typical 3.8 to 4.0 GHz (max) POWER9 Processor	1	
or			
EP1F	10-core typical 3.5 to 3.9 GHz (max) POWER9 Processor	1	
Processor activations			
EP4E	One Processor Core Activation for #EP1E	8	
or			
EP4F	One Processor Core Activation for #EP1F	10	
Memory DIMMs			
EM62	16 GB DDR4 Memory	2	
or			
EM63	32 GB DDR4 Memory	2	

Feature number	Description	Quantity	Notes
or			
EM64	64 GB DDR4 Memory	2	
or			
EM65	128 GB DDR4 Memory	2	
Storage Backplane			
EJ1C	Twelve SFF-3 Bays/RDX Bay	1	Optional split card EJ1E
or			
EJ1D	Eighteen SFF-3 Bays/RDX Bay/ Dual IOA with Write Cache	1	
or			
EJ1M	Twelve SFF-3 Bays/RDX Bay/2x EXT PT	1	
Disk Drive			
ESNJ	283 GB 15K RPM SAS SFF-3 4k Block Cached Disk Drive (IBM i)	2	One system data protection specify code required
LAN Adapter			
5899	PCIe2 LP 4-port 1 GbE Adapter	1	
or			
EN15	PCIe3 4-port 10 GbE SR Adapter	1	
or			
EC2S	PCIe3 2-Port 10 Gb NIC&ROCE SR/Cu Adapter	1	
or			
EC2U	PCIe3 2-Port 25/10 Gb NIC&ROCE SR/Cu Adapter	1	
Power supplies/ Power cord			
EB2M	AC Power Supply - 1400 W for Server (200 - 240 V AC)	4	
6458	Power Cord 4.3 m (14 ft), Drawer to IBM PDU (250V/10A)	4	6458 - (default)
9300/97xx	Language Group Specify	1	9300 - (default)
Front Bezel			
EJU3	Front IBM Bezel for 12-Bay BackPlane	1	
or			
EJUG	Front IBM Bezel for 18-Bay BackPlane	1	
Primary operating system			
2145	Primary Operating System Indicator - IBM i	1	

- The racking approach for the initial order must be either a 7014-T00, 7014-T42, 7965-S42, or 7953-94Y. If an additional rack is required for I/O expansion drawers as an MES to an existing system, either a feature 0551, 0553, or ER05 rack must be ordered.
- IBM i operating system performance: Clients with write-sensitive disk/HDD workloads should upgrade from the feature EJ1C/EJ1E base storage backplane to the feature EJ1M/EJ1D expanded function storage backplanes to gain the performance advantage of write cache.

Processor modules

A maximum of two processors with eight processor cores (#EP1E), or two processors with ten processor cores (#EP1F), or two processors with twelve processor cores (#EP1G) are allowed. All processor cores must be activated. The following defines the allowed quantities of processor activation entitlements.

- One 8-core, typical 3.8 to 4.0 GHz (max) processor (#EP1E) requires that eight processor activation codes be ordered. A maximum of eight processor activations (#EP4E) is allowed.
- Two 8-core, typical 3.8 to 4.0 GHz (max) processors (#EP1E) require that sixteen processor activation codes be ordered. A maximum of 16 processor activations (#EP4E) is allowed.
- One 10-core, typical 3.5 to 3.9 GHz (max) processor (#EP1F) requires that ten processor activation codes be ordered. A maximum of 10 processor activation code features (#EP4F) is allowed.
- Two 10-core, typical 3.5 to 3.9 GHz (max) processors (#EP1F) require that twenty processor activation codes be ordered. A maximum of 20 processor activation code features (#EP4F) is allowed.
- Two 12-core, typical 3.4 to 3.9 GHz (max) processors (#EP1G) require that twenty-four processor activation codes be ordered. A maximum of 24 processor activation code features (#EP4G) is allowed.

System memory

- A minimum 32 GB of memory is required on the Power H924 system.
- Memory upgrades require memory pairs. Base memory is two 16 GB DDR4 ECC memory modules (#EM62).

Plans for future memory upgrades should be taken into account when deciding which memory feature size to use at the time of initial system order.

Feature description	Feature number	Minimum DIMM quantity	Maximum DIMM quantity
16 GB DDR4 Memory	EM62	0	32
32 GB DDR4 Memory	EM63	0	32
64 GB DDR4 Memory	EM64	0	32
128 GB DDR4 Memory	EM65	0	32

Note: Different sizes/configurations run at different frequencies of 2133, 2400, and 2666 Mbps.

Power supply

- Four power supplies supporting a rack: 1+1 1400 Watt 200-240 Volt (#EB2M)

Redundant fans

Redundant fans are standard.

Power cords

Four power cords are required. A maximum of two feature 6458 cords is allowed on the system unless a valid I/O drawer or tower is attached to the system. The Power H924 server supports power cord 4.3 m (14 ft), Drawer to Wall/IBM PDU (250V/10A) in the base shipment group. See the feature listing for other options.

PCIe slots

The Power H924 server has up to 11 PCIe hot-plug slots, providing excellent configuration flexibility and expandability. For more information about PCIe slots, see the **Rack-integrated system with I/O Expansion Drawer** section below.

With two POWER9 processor single-chip modules (SCM), eleven PCIe slots are available, three are x16 Gen4 full-height, half-length slots (CAPI), two are x8 Gen4 full-height, half-length slots (with x16 connectors) (CAPI), two are x8 Gen3 full-height, half-length slots (with x16 connectors), and four are x8 Gen3 full-height, half-length slots (one of these slots is used for the required base LAN adapter).

With one POWER9 processor SCM, eight PCIe slots are available. One is x16 Gen4 full-height, half-length slot (CAPI), one is x8 Gen4 full-height, half-length slot (with x16 connector) (CAPI), two are x8 Gen3 full-height, half-length slots (with x16 connectors), and four are x8 Gen3 full-height, half-length slots (one of these slots is used for the required base LAN adapter).

The x16 slots can provide up to twice the bandwidth of x8 slots because they offer twice as many PCIe lanes. PCIe Gen4 slots can support up to twice the bandwidth of a PCIe Gen3 slot and PCIe Gen3 slots can support up to twice the bandwidth of a PCIe Gen2 slot, assuming an equivalent number of PCIe lanes.

At least one PCIe Ethernet adapter is required on the server by IBM to ensure proper manufacture, test, and support of the server. One of the x8 PCIe slots is used for this required adapter.

These servers are smarter about energy efficiency when cooling the PCIe adapter environment. They sense which IBM PCIe adapters are installed in their PCIe slots and if an adapter requires higher levels of cooling, they automatically speed up fans to increase airflow across the PCIe adapters. Note that faster fans increase the sound level of the server. Higher wattage PCIe adapters include the PCIe3 SAS adapters and SSD/flash PCIe adapters (#EJ10, #EJ14, and #EJ0J).

SAS bays and storage backplane options

- Base Storage Backplane 12 SFF-3 Bays/RDX Bay (#EJ1C)
- Feature EJ1E (6 +6 SFF-3 Bays split backplane for #EJ1C)
- Expanded function Storage Backplane 18 SFF-3 Bays/Dual IOA with Write Cache and optional external SAS port (#EJ1D)
- Expanded function Storage Backplane 12 SFF-3 Bays/RDX Bay/Dual IOA with Write Cache and optional external SAS port (#EJ1M)

The backplane options provide SFF-3 SAS bays in the system unit. These 2.5-inch or small form factor (SFF) SAS bays can contain SAS drives (HDD or SSD) mounted on a Gen3 tray or carrier. Thus the drives are designated SFF-3. SFF-1 or SFF-2 drives do not fit in an SFF-3 bay. All SFF-3 bays support concurrent maintenance or hot-plug capability.

These backplane options use leading-edge, integrated SAS RAID controller technology designed and patented by IBM. A custom-designed PowerPC^(R) based ASIC chip is the basis of these SAS RAID controllers and provides RAID 5 and RAID 6 performance levels, especially for SSD. Internally, SAS ports are implemented and provide plenty of bandwidth. The integrated SAS controllers are placed in dedicated slots and do not reduce the number of available PCIe slots.

The feature EJ1C Base Storage Backplane option provides twelve SFF-3 bays and one SAS controller with zero write cache.

By optionally adding the feature EJ1E Split Backplane, a second integrated SAS controller with no write cache is provided, and the twelve SSF-3 bays are logically divided into two sets of six bays. Each SAS controller independently runs one of the six-bay sets of drives.

This backplane option supports HDDs or SSDs or a mixture of HDDs and SSDs in the SFF-3 bays. "Mixing" HDDs and SSDs applies even within a single set of six bays of the split backplane option. Note, if mixing HDDs and SSDs, they must be in separate arrays.

This backplane option can offer different drive protection options: RAID 0, RAID 5, RAID 6, or RAID 10. RAID 5 requires a minimum of three drives of the same capacity. RAID 6 requires a minimum of four drives of the same capacity. RAID 10 requires a minimum of two drives. Hot spare capability is supported with RAID 5, RAID 6, or RAID 10.

Note that RAID 5 and RAID 6 result in more drive write activity than mirroring or than unprotected drives.

This backplane option is supported by AIX, Linux, VIOS, and IBM i. It is highly recommended but not required that the drives be protected. With IBM i, all drives are required to be protected by either RAID or Mirroring.

If the client needs a change after the server is installed, the backplane option can be changed. For example, the feature EJ1E split backplane feature can be added to an existing feature EJ1C backplane.

Unlike the hot-plug PCIe slots and SAS bays, concurrent maintenance is not available for the integrated SAS controllers. Scheduled downtime is required if a service action is required for these integrated resources.

In addition to supporting HDDs and SSDs in the SFF-3 SAS bays, the Expanded Function Storage Backplanes (#EJ1D and #EJ1M) support the optional attachment of an EXP12SX/EXP24SX drawer in mode 1. For these expanded function backplanes, all bays are accessed by both of the integrated SAS controllers. The bays support concurrent maintenance (hot-plug).

Cable management arm

A folding arm is attached to the server's rails at the rear of the server. The server's power cords and the cables from the PCIe adapters or integrated ports run through the arm and into the rack. The arm enables the server to be pulled forward on its rails for service access to PCIe slots, memory, processors, and so on without disconnecting the cables from the server. Approximately 1 meter (3 feet) of cord/cable length is needed for the arm.

Integrated I/O ports

In addition to the integrated SAS controllers and SAS ports associated with the storage backplane, there are two HMC ports, one system port, and three USB ports. The two HMC ports are RJ45 supporting 1 Gb Ethernet connections.

The one system port is RJ45 and is supported by AIX and Linux for attaching serial devices such as an asynchronous devices like a console. If the device does not have an RJ45 connection, a converter cable such as feature 3930 can provide a 9-pin D-shell connection. Note that serial devices can have very individual characteristics (different pin outs), and the feature 3930 may not be appropriate for all possible devices. In this case, the user should acquire an OEM converter cable appropriate for their device.

Three USB-3 ports are available for general client use; one is located in front and two in the rear. Additionally, there are two USB-2 ports in the service processor located in the rear of the system. These ports are for limited client use. A converter cable ECCF provides a USB-to-9-pin D-Shell connection for this function.

Rack-integrated system with I/O Expansion Drawer

Regardless of the rack-integrated system to which the PCIe Gen3 I/O Expansion Drawer is attached to, if the Expansion Drawer is ordered as factory integrated, the PDUs in the rack will be defaulted to be placed horizontally to enhance cable management.

Expansion Drawers complicate the access to vertical PDUs if located at the same height. IBM recommends accommodating PDUs horizontally on racks containing one or more PCIe Gen3 I/O Expansion Drawers.

After the rack with expansion drawers is delivered to the client, the client is allowed to rearrange the PDUs from horizontal to vertical. However, the configurator will continue to consider the PDUs as being placed horizontally for the matter of calculating the free space still available in the rack.

Vertical PDUs can be used only if CSRP (#0469) is on the order. When specifying CSRP, the client will provide the locations where the PCIe Gen3 I/O Expansion Drawers must be placed, avoiding locating those adjacent to vertical PDU locations, EIA 6 through 16 and 21 through 31.

RDX docking station

The RDX docking station EUA4 accommodates RDX removable disk cartridges of any capacity. The disk is in a protective rugged cartridge enclosure that plugs into the docking station. The docking station holds one removable rugged disk drive/cartridge at a time. The rugged removable disk cartridge and docking station performs saves, restores, and backups similar to tape drive. This docking station can be an excellent entry capacity/performance option.

EXP24SX SAS Storage Enclosure (#ESLS/#ELLS)

The EXP24SX is a storage expansion enclosure with twenty-four 2.5-inch SFF SAS bays. It supports up to 24 hot-plug HDDs or SSDs in only 2 EIA of space in a 19-inch rack. The EXP24SX SFF bays use SFF Gen2 (SFF-2) carriers or trays.

The EXP24SX drawer feature ESLS is supported on the Power H922 and H924 servers by AIX, IBM i, Linux, and VIOS. The EXP24SX drawer feature ELLS is supported on the Linux-only Power L922 server.

With AIX/Linux/VIOS, the EXP24SX can be ordered with four sets of six bays (mode 4), two sets of twelve bays (mode 2), or one set of twenty-four bays (mode 1). With IBM i, only one set of twenty-four bays (mode 1) is supported. It is possible to change the mode setting in the field using software commands along with a specifically documented procedure. The predecessor EXP24S did not support this mode change in the field.

Important: When changing modes, a skilled, technically qualified person should follow the special documented procedures. Improperly changing modes can potentially destroy existing RAID sets, prevent access to existing data, or allow other partitions to access another partition's existing data. Hire an expert to assist if you are not familiar with this type of reconfiguration work.

Four mini-SAS HD ports on the EXP24SX are attached to PCIe Gen3 SAS adapters or attached to an integrated SAS controller in a POWER9 scale-out server such as the Power H922 or H924 servers. The following PCIe3 SAS adapters support the EXP24SX:

- PCIe3 RAID SAS Adapter Quad-port 6 Gb x8 (#EJ0J, #EJ0M, #EL3B, or #EL59)
- PCIe3 12 GB Cache RAID Plus SAS Adapter Quad-port 6 Gb x8 (#EJ14)

Earlier generation PCIe2 or PCIe1 SAS adapters are not supported with the EXP24SX.

The attachment between the EXP24SX and the PCIe3 SAS adapters or integrated SAS controllers is through SAS YO12 or X12 cables. X12 and YO12 cables are designed to support up to 12 Gb SAS. The PCIe Gen3 SAS adapters support up to 6 Gb throughput. The EXP24SX has been designed to support up to 12 Gb throughput if future SAS adapters support that capability. All ends of the YO12 and X12 cables have mini-SAS HD narrow connectors. Cable options are:

- X12 cable: 3-meter copper (#ECDJ)
- YO12 cables: 1.5-meter copper (#ECDT), 3-meter copper (#ECDU)
- 3M 100 GbE Optical Cable QSFP28 (AOC) (#EB5R)
- 5M 100 GbE Optical Cable QSFP28 (AOC) (#EB5S)
- 10M 100 GbE Optical Cable QSFP28 (AOC) (#EB5T)
- 15M 100 GbE Optical Cable QSFP28 (AOC) (#EB5U)
- 20M 100 GbE Optical Cable QSFP28 (AOC) (#EB5V)
- 30M 100 GbE Optical Cable QSFP28 (AOC) (#EB5W)
- 50M 100 GbE Optical Cable QSFP28 (AOC) (#EB5X)
- 100M 100 GbE Optical Cable QSFP28 (AOC) (#EB5Y)

An AA12 cable interconnecting a pair of PCIe3 12 GB cache adapters (two #EJ14) is not attached to the EXP24SX. These higher-bandwidth cables could support 12 Gb throughput if future adapters support that capability. Copper feature ECE0 is 0.6 meters long, ECE3 is 3 meters long, and optical AA12 feature ECE4 is 4.5-meter long.

One no-charge specify code is used with each EXP24SX I/O Drawer (#ESLS/#ELLS) to communicate to IBM configurator tools and IBM Manufacturing which mode setting, adapter, and SAS cable are needed. With this specify code, no hardware is shipped. The physical adapters, controllers, and cables must be ordered with their own chargeable feature numbers. There are more technically supported configurations than are represented by these specify codes. IBM Manufacturing and IBM configurator tools such as e-config only understand and support EXP24SX configurations represented by these specify codes.

Specify code	Mode	Adapter/ Controller	Cable to Drw	Environment
#EJW0	Mode 1	CEC SAS Ports	2 YO12 cables	AIX/IBM i/ Linux/VIOS
#EJW1	Mode 1	One (unpaired) #EJ0J/ #EJ0M/ #EL3B/ #EL59	1 YO12 cable	AIX/IBM i/ Linux/VIOS
#EJW2	Mode 1	Two (one pair) #EJ0J/ #EJ0M/ #EL3B/ #EL59	2 YO12 cables	AIX/IBM i/ Linux/VIOS
#EJW3	Mode 2	Two (unpaired) #EJ0J/ #EJ0M/ #EL3B/ #EL59	2 X12 cables	AIX/Linux/ VIOS
#EJW4	Mode 2	Four (two pair) #EJ0J/ #EJ0M/ #EL3B/ #EL59	2 X12 cables	AIX/Linux/ VIOS
#EJW5	Mode 4	Four (unpaired) #EJ0J/ #EJ0M/	2 X12 cables	AIX/Linux/ VIOS

Specify code	Mode	Adapter/ Controller	Cable to Drw	Environment
		#EL3B/ #EL59		
#EJW6	Mode 2	One (unpaired) #EJ0J/ #EJ0M/ #EL3B/ #EL59	2 YO12 cables	AIX/Linux/ VIOS
#EJW7	Mode 2	Two (unpaired) #EJ0J/ #EJ0M/ #EL3B/ #EL59	2 YO12 cables	AIX/Linux/ VIOS
#EJWF	Mode 1	Two (one pair) #EJ14	2 YO12 cables	AIX/IBM i/ Linux/VIOS
#EJWG	Mode 2	Two (one pair) #EJ14	2 X12 cables	AIX/Linux/ VIOS
#EJWJ	Mode 2	Four (two pair) #EJ14	2 X12 cables	AIX/Linux/ VIOS
#EJWU	Mode 1	Controller EJ1G/EL67	1 YO12 cables	Linux

All of the above EXP24SX specify codes assume a full set of adapters and cables able to run all the SAS bays configured. The following specify codes communicate to IBM Manufacturing a lower-cost partial configuration is to be configured where the ordered adapters and cables can run only a portion of the SAS bays. The future MES addition of adapters and cables can enable the remaining SAS bays for growth. The following specify codes are used:

Specify	Mode	Adapter/ Controller	Cable to Drw	Environment
#EJWA (1/2 of #EJW7)	Mode 2	One (unpaired) #EJ0J/ #EJ0M/ #EL3B/ #EL59	1 YO12 cables	AIX/Linux/ VIOS
#EJWB (1/2 of #EJW4)	Mode 2	Two (one pair) #EJ0J/ #EJ0M/ #EL3B/ #EL59	1 X12 cable	AIX/Linux/ VIOS
#EJWC (1/4 of #EJW5)	Mode 4	One (unpaired) #EJ0J/ #EJ0M/ #EL3B/ #EL59	1 X12 cable	AIX/Linux/ VIOS
#EJWD (1/2 of #EJW5)	Mode 4	Two (unpaired) #EJ0J/ #EJ0M/ #EL3B/ #EL59	1 X12 cables	AIX/Linux/ VIOS
#EJWE (3/4 of #EJW5)	Mode 4	Three (unpaired) #EJ0J/ #EJ0M/ #EL3B/ #EL59	2 X12 cables	AIX/Linux/ VIOS
#EJWH (1/2 of #EJWJ)	Mode 2	Two (one pair) #EJ14	1 X12 cables	AIX/Linux/ VIOS

An EXP24SX drawer in mode 4 can be attached to two or four SAS controllers and provide a great deal of configuration flexibility. For example, if using unpaired

feature EJ0J adapters, these EJ0J adapters could be in the same server in the same partition, same server in different partitions, or even different servers.

An EXP24SX drawer in mode 2 has similar flexibility. If the I/O drawer is in mode 2, then half of its SAS bays can be controlled by one pair of PCIe3 SAS adapters, such as a 12 GB write cache adapter pair (#EJ14), and the other half can be controlled by a different PCIe3 SAS 12 GB write cache adapter pair or by zero-write-cache PCIe3 SAS adapters.

Note that for simplicity, IBM configurator tools such as e-config assume that the SAS bays of an individual I/O drawer are controlled by one type of SAS adapter. As a client, you have more flexibility than e-config understands.

A maximum of twenty-four 2.5-inch SSDs or 2.5-inch HDDs is supported in the EXP24SX 24 SAS bays. There can be no mixing of HDDs and SSDs in the same mode 1 drawer. HDDs and SSDs can be mixed in a mode 2 or mode 4 drawer, but they cannot be mixed within a logical split of the drawer. For example, in a mode 2 drawer with two sets of 12 bays, one set could hold SSDs and one set could hold HDDs, but you cannot mix SSDs and HDDs in the same set of 12 bays.

The indicator feature EHS2 helps IBM Manufacturing understand where SSDs are placed in a mode 2 or a mode 4 EXP24SX drawer. On one mode 2 drawer, use a quantity of one feature EHS2 to have SSDs placed in just half the bays, and use two EHS2 features to have SSDs placed in any of the bays. Similarly, on one mode 4 drawer, use a quantity of one, two, three, or four EHS2 features to indicate how many bays can have SSDs. With multiple EXP24SX orders, IBM Manufacturing will have to guess which quantity of feature ESH2 is associated with each EXP24SX. Consider using CSP (#0456) to reduce guessing.

Two-and-a-half-inch small form factor (SFF) SAS HDDs and SSDs are supported in the EXP24SX. All drives are mounted on Gen2 carriers/trays and thus named SFF-2 drives.

The EXP24SX drawer has many high-reliability design points:

- SAS drive bays that support hot swap
- Redundant and hot-plug-capable power and fan assemblies
- Dual line cords
- Redundant and hot-plug enclosure service modules (ESMs)
- Redundant data paths to all drives
- LED indicators on drives, bays, ESMs, and power supplies that support problem identification
- Through the SAS adapters/controllers, drives that can be protected with RAID and mirroring and hot-spare capability

Order two ESLA features for AC power supplies. The enclosure is shipped with adjustable depth rails and can accommodate 19-inch rack depths from 59.5 - 75 cm (23.4 - 29.5 in.). Slot filler panels are provided for empty bays when initially shipped from IBM.

EXP12SX SAS Storage Enclosure (#ESLL/#ELLL)

The EXP12SX is a storage expansion enclosure with twelve 3.5-inch LFF SAS bays. It supports up to 12 hot-plug HDDs in only 2 EIA of space in a 19-inch rack. The EXP12SX SFF bays use LFF Gen1 (LFF-1) carriers/trays. The 4k byte sector drives (#4096 or #4224) are supported. SSDs are not supported.

The EXP12SX drawer feature ESLL is supported on the Power H922 and H924 servers by AIX, Linux, and VIOS. The EXP24SX drawer feature ELLL is supported on the Linux-only Power L922 server.

With AIX/Linux/VIOS, the EXP12SX enclosure can be ordered with four sets of three bays (mode 4), two sets of six bays (mode 2), or one set of twelve bays (mode 1).

The mode setting can be changed in the field using software commands along with a specifically documented procedure.

Important: When changing modes, it is very important that you follow the documented procedures. Improperly changing modes can potentially destroy existing RAID sets, prevent access to existing data, or allow other partitions to access another partition's existing data. Hire an expert to assist if you are not familiar with this type of reconfiguration work.

Four mini-SAS HD ports on the EXP12SX are attached to PCIe Gen3 SAS adapters or attached to an integrated SAS controller in a POWER9 scale-out server such as the Power H922 or H924 server. The following PCIe3 SAS adapters support the EXP12SX:

- PCIe3 RAID SAS Adapter Quad-port 6 Gb x8 (#EJ0J, #EJ0M, #EL3B, or #EL59)
- PCIe3 12 GB Cache RAID Plus SAS Adapter Quad-port 6 Gb x8 (#EJ14)

Earlier generation PCIe2 or PCIe1 SAS adapters are not supported with the EXP12SX drawer.

The EXP12SX drawer and the PCIe3 SAS adapters or integrated SAS controllers are attached through SAS YO12 or X12 cables. X12 and YO12 cables are designed to support up to 12 Gb. The PCIe Gen3 SAS adapters support up to 6 Gb throughput. The EXP12SX has been designed to support up to 12 Gb throughput if future SAS adapters support that capability. All ends of the YO12 and X12 cables have mini-SAS HD narrow connectors. Cable options are:

- X12 cable: 3-meter copper (#ECDJ)
- YO12 cables: 1.5-meter copper (#ECDT), 3-meter copper (#ECDU)
- 3M 100 GbE Optical Cable QSFP28 (AOC) (#EB5R)
- 5M 100 GbE Optical Cable QSFP28 (AOC) (#EB5S)
- 10M 100 GbE Optical Cable QSFP28 (AOC) (#EB5T)
- 15M 100 GbE Optical Cable QSFP28 (AOC) (#EB5U)
- 20M 100 GbE Optical Cable QSFP28 (AOC) (#EB5V)
- 30M 100 GbE Optical Cable QSFP28 (AOC) (#EB5W)
- 50M 100 GbE Optical Cable QSFP28 (AOC) (#EB5X)
- 100M 100 GbE Optical Cable QSFP28 (AOC) (#EB5Y)

An AA12 cable interconnecting a pair of PCIe3 12 GB cache adapters (two #EJ14) is not attached to the EXP12SX drawer. These higher-bandwidth cables could support 12 Gb throughput if future adapters support that capability. Copper feature ECE0 is 0.6-meter long, feature ECE3 is 3-meter long, and optical AA12 feature ECE4 is 4.5-meter long.

One no-charge specify code is used with each EXP12SX I/O Drawer (#ELLL/#ESLL) to communicate to IBM configurator tools and IBM Manufacturing which mode setting, adapter, and SAS cable are needed. With this specify code, no hardware is shipped. The physical adapters, controllers, and cables must be ordered with their own chargeable feature numbers. There are more technically supported configurations than are represented by these specify codes. IBM Manufacturing and IBM configurator tools such as e-config only understand and support EXP12SX configurations represented by these specify codes.

Specify	Mode	Adapter/ Controller	Cable to Drw	Environment
#EJV0	Mode 1	CEC SAS Ports	2 YO12 cables	AIX/Linux/ VIOS
#EJV1	Mode 1	One (unpaired) #EJ0J/ #EJ0M/ #EL3B/ #EL59	1 YO12 cable	AIX/Linux/ VIOS

Specify	Mode	Adapter/ Controller	Cable to Drw	Environment
#EJV2	Mode 1	Two (unpaired) #EJ0J/ #EJ0M/ #EL3B/ #EL59	2 YO12 cables	AIX/Linux/ VIOS
#EJV3	Mode 2	Two (one pair) #EJ0J/ #EJ0M/ #EL3B/ #EL59	2 X12 cables	AIX/Linux/ VIOS
#EJV4	Mode 2	Four (two pair) #EJ0J/ #EJ0M/ #EL3B/ #EL59	2 X12 cables	AIX/Linux/ VIOS
#EJV5	Mode 4	Four (unpaired) #EJ0J/ #EJ0M/ #EL3B/ #EL59	2 X12 cables	AIX/Linux/ VIOS
#EJV6	Mode 2	One (unpaired) #EJ0J/ #EJ0M/ #EL3B/ #EL59	2 YO12 cables	AIX/Linux/ VIOS
#EJV7	Mode 2	Two (unpaired) #EJ0J/ #EJ0M/ #EL3B/ #EL59	2 YO12 cables	AIX/Linux/ VIOS
#EJV6	Mode 1	Two #EJ14 (one pair)	2 YO12 cables	AIX/Linux/ VIOS
#EJVG	Mode 2	Two #EJ14 (one pair)	2 X12 cables	AIX/Linux/ VIOS
#EJVJ	Mode 2	Four #EJ14 (two pair)	2 X12 cable	AIX/Linux/ VIOS
#EJVU	Mode 1	Controller EJ1G/EL67	1 YO12 cables	Linux

All of the above EXP12SX specify codes assume a full set of adapters and cables able to run all the SAS bays configured. The following specify codes communicate to IBM Manufacturing a lower cost, partial configuration is to be configured where the ordered adapters and cables can run only a portion of the SAS bays. The future MES addition of adapters and cables can enable the remaining SAS bays for growth. The following specify codes are used:

Specify	Mode	Adapter/ Controller	Cable to Drw	Environment
#EJVA (1/2 of #EJV7)	Mode 2	One (unpaired) #EJ0J/ #EJ0M/ #EL3B/ #EL59	1 YO12 cables	AIX/Linux/ VIOS
#EJVB (1/2 of #EJV4)	Mode 2	One pair #EJ0J/ #EJ0M/ #EL3B/ #EL59	1 X12 cable	AIX/Linux/ VIOS
#EJVC (1/4 of #EJV5)	Mode 4	One (unpaired) #EJ0J/ #EJ0M/	1 X12 cable	AIX/Linux/ VIOS

Specify	Mode	Adapter/ Controller	Cable to Drw	Environment
		#EL3B/ #EL59		
#EJVD (2/4 of #EJV5)	Mode 4	Two (unpaired) #EJ0J/ #EJ0M/ #EL3B/ #EL59	1 X12 cables	AIX/Linux/ VIOS
#EJVE (3/4 of #EJV5)	Mode 4	Three (unpaired) #EJ0J/ #EJ0M/ #EL3B/ #EL59	2 X12 cables	AIX/Linux/ VIOS

An EXP12SX drawer in mode 4 can be attached to two or four SAS controllers and provide a great deal of configuration flexibility. For example, if using unpaired feature EJ0J adapters, these EJ0J adapters could be in the same server in the same partition, same server in different partitions, or even different servers.

An EXP12SX drawer in mode 2 has similar flexibility. If the I/O drawer is in mode 2, then half of its SAS bays can be controlled by one pair of PCIe3 SAS adapters, such as a 12 GB write cache adapter pair (#EJ14), and the other half can be controlled by a different PCIe3 SAS 12 GB write cache adapter pair or by zero-write-cache PCIe3 SAS adapters.

Note that for simplicity, IBM configurator tools such as e-config assume that the SAS bays of an individual I/O drawer are controlled by one type of SAS adapter. As a client, you have more flexibility than e-config understands.

The 3.5-inch large form factor (LFF) SAS HDDs are supported in the EXP24SX. All drives are mounted on Gen1 carriers/trays and thus named LFF-1 drives. Only 4k byte sector drives are supported in the EXP24SX drawer. The 5xx byte sector drives are not announced or planned. Drives are 7200 rpm and sometimes referred to as *nearline*. These drives provide excellent cost per gigabyte. Note that formatting or rebuilding arrays on large disk drives can take hours. If higher performance is required, consider higher rpm disks or SSDs in the EXP24SX drawer.

EXP12SX drives for feature ESSL (multi-OS) are the 3.86 TB/4.0 TB 4k 7200 RPM (#ES62) and 7.72 TB/8.0 TB 4k 7200 RPM (#ES64) drives. Drives for feature ELLL (Linux-only) are the 3.86 TB/4.0 TB 4k 7200 RPM (#EL62) and the 7.72 TB/8.0 TB 4k 7200 RPM (#EL64) drives.

The EXP12SX drawer has many high-reliability design points:

- SAS bays that support hot swap
- Redundant and hot-plug power and fan assemblies
- Dual line cords
- Redundant and hot-plug ESMs
- Redundant data paths to all drives
- LED indicators on drives, bays, ESMs, and power supplies that support problem identification
- Through the SAS adapters/controllers, drives that can be protected with RAID and mirroring and hot-spare capability

Order two ESLA features for AC power supplies. The enclosure is shipped with adjustable depth rails and can accommodate 19-inch rack depths from 59.5 - 75 cm (23.4 - 29.5 in.). Slot filler panels are provided for empty bays when initially shipped from IBM.

EXP24SX and EXP12SX enclosures can be mixed on the same server. EXP24SX and EXP12SX enclosures can be mixed on the same PCIe3 adapter.

PCIe Gen3 I/O Drawer Cabling Option

A copper cabling option (#ECCS) is available for the scale-out servers. The cable option offers a much lower-cost connection between the server and the PCIe Gen3 I/O drawer fanout modules. The currently available Active Optical Cable (AOC) offers much longer length cables, providing rack placement flexibility. Plus AOC cables are much thinner and have tighter bend radius and thus are much easier to cable in the rack.

The 3M Copper CXP Cable Pair (#ECCS) has the same performance and same reliability, availability, and serviceability (RAS) characteristics as the AOC cables. One copper cable length of 3 m is offered. Note that the cable management arm of the scale-out servers requires about 1 m of cable.

Like the AOC cable pair, the copper pair is cabled in the same manner. One cable attaches to the top CXP port in the PCIe adapter in the x16 PCIe slot in the server system unit and then attaches to the top CXP port in the fanout module in the I/O drawer. Its cable pair attaches to the bottom CXP port of the same PCIe adapter and to the bottom CXP port of the same fanout module. Note that the PCIe adapter providing the CXP ports on the server was named a PCIe3 "Optical" Cable Adapter. In hindsight, this naming was unfortunate as the adapter's CXP ports are not unique to optical. But at the time, optical cables were the only connection option planned.

Copper and AOC cabling can be mixed on the same server. However, they cannot be mixed on the same PCIe Gen3 I/O drawer or mixed on the same fanout module.

Copper cables have the same operating system software prerequisites as AOC cables.

High-function (switched and monitored) PDUs

The high-function PDUs (power distribution units) provide switching, better monitoring, and 50% more C19 receptacles than previous Power System PDUs. Depending on country wiring standards, either two or four full-price features are orderable.

	208 V 3-phase delta	200 V - 240 V 1-phase or 3-phase wye
12 x C13	#EPTQ	#EPTN
9 x C19	#EPTL	#EPTJ

These PDUs can be mounted vertically in rack-side pockets or they can be mounted horizontally. If mounted horizontally, they each use 1 EIA (1U) of rack space. See feature EPTH for horizontal mounting hardware, which is used when IBM Manufacturing doesn't automatically factory-install the PDU. Two RJ45 ports on the front of the PDU enable the client to monitor each receptacle's electrical power usage and to remotely switch any receptacle on or off. The PDU is shipped with a generic PDU password, and IBM strongly urges clients to change it upon installation. These PDUs do provide the same low price as the low-function 12xC13 PDU feature (#7188).

Reliability, Availability, and Serviceability

Reliability, fault tolerance, and data correction

The reliability of systems starts with components, devices, and subsystems that are designed to be highly reliable. During the design and development process, subsystems go through rigorous verification and integration testing processes. During system manufacturing, systems go through a thorough testing process to help ensure the highest level of product quality.

Memory subsystem RAS

The memory has error detection and correction circuitry designed such that the failure of any one specific memory module within an ECC word by itself can be corrected absent any other fault.

Mutual surveillance

The service processor monitors the operation of the firmware during the boot process and also monitors the hypervisor for termination. The hypervisor monitors the service processor and reports a service reference code when it detects surveillance loss. In the PowerVM environment, it will perform a reset/reload if it detects the loss of the service processor.

Environmental monitoring functions

The Power Systems family does ambient and over temperature monitoring and reporting.

POWER9 processor functions

As in POWER8, the POWER9 processor has the ability to do processor instruction retry for some transient errors.

Cache availability

The L2 and L3 caches in the POWER9 processor in the memory buffer chip are protected with double-bit detect, single-bit correct error detection code (ECC). In addition, a threshold of correctable errors detected on cache lines can result in the data in the cache lines being purged and the cache lines removed from further operation without requiring a reboot in the PowerVM environment.

Modified data would be handled through Special Uncorrectable Error handling. L1 data and instruction caches also have a retry capability for intermittent errors and a cache set delete mechanism for handling solid failures.

Special Uncorrectable Error handling

Special Uncorrectable Error (SUE) handling prevents an uncorrectable error in memory or cache from immediately causing the system to terminate. Rather, the system tags the data and determines whether it will ever be used again. If the error is irrelevant, it will not force a check stop. If the data is used, termination may be limited to the program/kernel or hypervisor owning the data; or the I/O adapters controlled by an I/O hub controller would freeze if data were transferred to an I/O device.

PCI extended error handling

PCI extended error handling (EEH)-enabled adapters respond to a special data packet generated from the affected PCI slot hardware by calling system firmware, which will examine the affected bus, allow the device driver to reset it, and continue without a system reboot. For Linux, EEH support extends to the majority of frequently used devices, although some third-party PCI devices may not provide native EEH support.

Uncorrectable error recovery

When the auto-restart option is enabled, the system can automatically restart following an unrecoverable software error, hardware failure, or environmentally induced (AC power) failure.

Serviceability

The purpose of serviceability is to efficiently repair the system while attempting to minimize or eliminate impact to system operation. Serviceability includes system installation, MES (system upgrades/downgrades), and system maintenance/repair. Depending upon the system and warranty contract, service may be performed by the client, an IBM representative, or an authorized warranty service provider.

The serviceability features delivered in this system help provide a highly efficient service environment by incorporating the following attributes:

- Design for Customer Set Up (CSU), Customer Installed Features (CIF), and Customer Replaceable Units (CRU)
- Error Detection and Fault Isolation (ED/FI)
- First Failure Data Capture (FFDC)
- Lightpath service indicators
- Service labels and service diagrams available on the system and delivered through IBM Knowledge Center
- Step-by-step service procedures documented in IBM Knowledge Center or available through the Hardware Management Console
- Automatic reporting of serviceable events to IBM through the Electronic Service Agent™ Call Home application
- CRU videos planned to be available on the web at general availability
- Mobile access to important customer service functions available by scanning a QR label

Service environment

In the PowerVM environment, the HMC is a dedicated server that provides functions for configuring and managing servers for either partitioned or full-system partition using a GUI or command-line interface (CLI) or REST API. An HMC attached to the system allows support personnel (with client authorization) to remotely, or locally to the physical HMC that is in proximity of the server being serviced, log in to review error logs and perform remote maintenance if required.

The POWER9 processor-based platforms support several service environments:

- Attachment to one or more HMCs or vHMCs is a supported option by the system with PowerVM. This is the default configuration for servers supporting logical partitions with dedicated or virtual I/O. In this case, all servers have at least one logical partition.
- For non-HMC systems.
 - Full-system partition with PowerVM: A single partition owns all the server resources and only one operating system may be installed. The primary service interface is through the operating system and the service processor.

Service interface

Support personnel can use the service interface to communicate with the service support applications in a server using an operator console, a graphical user interface on the management console or service processor, or an operating system terminal. The service interface helps to deliver a clear, concise view of available service applications, helping the support team to manage system resources and service information in an efficient and effective way. Applications available through the service interface are carefully configured and placed to give service providers access to important service functions.

Different service interfaces are used, depending on the state of the system, hypervisor, and operating environment. The primary service interfaces are:

- LEDs
- Operator Panel
- Service Processor menu
- Operating system service menu
- Service Focal Point on the HMC or vHMC with PowerVM

In the light path LED implementation, the system can clearly identify components for replacement by using specific component-level LEDs, and can also guide the servicer directly to the component by signaling (turning on solid) the amber system fault LED, enclosure fault LED, and component FRU fault LED. The servicer can also use the identify function to blink the FRU-level LED. When this function is activated, a roll-up to the blue enclosure locate and system locate LEDs will occur. These

enclosure LEDs will turn on solid and can be used to follow the light path from the system to the enclosure and down to the specific FRU in the PowerVM environment.

First Failure Data Capture and error data analysis

First Failure Data Capture (FFDC) is a technique that helps ensure that when a fault is detected in a system, the root cause of the fault will be captured without the need to re-create the problem or run any sort of extending tracing or diagnostics program. For the vast majority of faults, a good FFDC design means that the root cause can also be detected automatically without servicer intervention.

FFDC information, error data analysis, and fault isolation are necessary to implement the advanced serviceability techniques that enable efficient service of the systems and to help determine the failing items.

In the rare absence of FFDC and Error Data Analysis, diagnostics are required to re-create the failure and determine the failing items.

Diagnostics

General diagnostic objectives are to detect and identify problems so they can be resolved quickly. Elements of IBM's diagnostics strategy include:

- Provide a common error code format equivalent to a system reference code with PowerVM, system reference number, checkpoint, or firmware error code.
- Provide fault detection and problem isolation procedures. Support remote connection ability to be used by the IBM Remote Support Center or IBM Designated Service.
- Provide interactive intelligence within the diagnostics with detailed online failure information while connected to IBM's back-end system.

Automatic diagnostics

Because of the FFDC technology designed into IBM servers, it is not necessary to perform re-create diagnostics for failures or require user intervention. Solid and intermittent errors are designed to be correctly detected and isolated at the time the failure occurs. Runtime and boot-time diagnostics fall into this category.

Stand-alone diagnostics with PowerVM

As the name implies, stand-alone or user-initiated diagnostics requires user intervention. The user must perform manual steps, including:

- Booting from the diagnostics CD, DVD, USB, or network
- Interactively selecting steps from a list of choices

Concurrent maintenance

The determination of whether a firmware release can be updated concurrently is identified in the readme information file that is released with the firmware. An HMC is required for the concurrent firmware update with PowerVM. In addition, concurrent maintenance of PCIe adapters is supported with PowerVM. Concurrent maintenance of the Operator Panel is supported through ASMI. Additional concurrent maintenance includes power supplies, fans, and HDD/SSD drives.

Service labels

Service providers use these labels to assist them in performing maintenance actions. Service labels are found in various formats and positions and are intended to transmit readily available information to the servicer during the repair process. Following are some of these service labels and their purpose:

- Location diagrams: Location diagrams are located on the system hardware, relating information regarding the placement of hardware components. Location diagrams may include location codes, drawings of physical locations, concurrent maintenance status, or other data pertinent to a repair. Location diagrams are

especially useful when multiple components such as DIMMs, CPUs, processor books, fans, adapter cards, LEDs, and power supplies are installed.

- Remove/replace procedures: Service labels that contain remove/replace procedures are often found on a cover of the system or in other spots accessible to the servicer. These labels provide systematic procedures, including diagrams detailing how to remove or replace certain serviceable hardware components.
- Arrows: Numbered arrows are used to indicate the order of operation and the serviceability direction of components. Some serviceable parts such as latches, levers, and touch points need to be pulled or pushed in a certain direction and in a certain order for the mechanical mechanisms to engage or disengage. Arrows generally improve the ease of serviceability.

QR labels

QR labels are placed on the system to provide access to key service functions through a mobile device. Once the QR label is scanned, it will go to a landing page specific to that server which contains many of the service functions of interest while physically located at the server. These include things such as installation and repair instructions, service diagrams, reference code look up, and so on.

Packaging for service

The following service enhancements are included in the physical packaging of the systems to facilitate service:

- Color coding (touch points): Blue-colored touch points delineate touchpoints on service components where the component can be safely handled for service actions such as removal or installation.
- Tool-less design: Selected IBM systems support tool-less or simple tool designs. These designs require no tools or simple tools such as flathead screw drivers to service the hardware components.
- Positive retention: Positive retention mechanisms help to assure proper connections between hardware components such as cables to connectors, and between two cards that attach to each other. Without positive retention, hardware components run the risk of becoming loose during shipping or installation, preventing a good electrical connection. Positive retention mechanisms like latches, levers, thumb-screws, pop Nylatches (U-clips), and cables are included to help prevent loose connections and aid in installing (seating) parts correctly. These positive retention items do not require tools.

Error handling and reporting

In the event of system hardware or environmentally induced failure, the system runtime error capture capability systematically analyzes the hardware error signature to determine the cause of failure. The analysis result will be stored in system NVRAM. When the system can be successfully restarted either manually or automatically, or if the system continues to operate, the error will be reported to the operating system. Hardware and software failures are recorded in the system log. When an HMC is attached in the PowerVM environment, an ELA routine analyzes the error, forwards the event to the Service Focal Point (SFP) application running on the HMC, and notifies the system administrator that it has isolated a likely cause of the system problem. The service processor event log also records unrecoverable checkstop conditions, forwards them to the SFP application, and notifies the system administrator.

The system has the ability to call home through the operating system to report platform-recoverable errors and errors associated with PCI adapters/devices.

In the HMC-managed environment, a call home service request will be initiated from the HMC and the pertinent failure data with service parts information and part locations will be sent to an IBM service organization. Customer contact information and specific system-related data such as the machine type, model, and serial number, along with error log data related to the failure, are sent to IBM Service.

Live Partition Mobility

With Live Partition Mobility, users can migrate an AIX or IBM i partition running on one POWER partition system to another POWER system without disrupting services. The migration transfers the entire system environment, including processor state, memory, attached virtual devices, and connected users. It provides continuous operating system and application availability during planned partition outages for repair of hardware and firmware faults.

Service processor

The service processor provides the capability to diagnose, check the status of, and sense the operational conditions of a system. It runs on its own power boundary and does not require resources from a system processor to be operational to perform its tasks.

Under PowerVM, the service processor supports surveillance of the connection to the HMC and to the system firmware (hypervisor). It also provides several remote power control options, environmental monitoring, reset, restart, remote maintenance, and diagnostic functions, including console mirroring. The service processors menus (ASMI) can be accessed concurrently with system operation, allowing nondisruptive abilities to change system default parameters.

Call home

Call home refers to an automatic or manual call from a client location to the IBM support structure with error log data, server status, or other service-related information. Call home invokes the service organization in order for the appropriate service action to begin. Call home can be done through HMC or most non-HMC-managed systems through Electronic Service Agent running on top of the operating system. While configuring call home is optional, clients are encouraged to implement this feature in order to obtain service enhancements such as reduced problem determination and faster and potentially more accurate transmittal of error information. In general, using the call home feature can result in increased system availability. The Electronic Service Agent application can be configured for automated call home. See the next section for specific details on this application.

IBM Electronic Services

Electronic Service Agent and the IBM Electronic Services web portal comprise the IBM Electronic Services solution, which is dedicated to providing fast, exceptional support to IBM clients. IBM Electronic Service Agent is a no-charge tool that proactively monitors and reports hardware events such as system errors, performance issues, and inventory. Electronic Service Agent can help focus on the client's company business initiatives, save time, and spend less effort managing day-to-day IT maintenance issues.

System configuration and inventory information collected by Electronic Service Agent also can be viewed on the secure Electronic Services web portal and used to improve problem determination and resolution between the client and the IBM support team. As part of an increased focus to provide even better service to IBM clients, Electronic Service Agent tool configuration and activation comes standard with the system. In support of this effort, a new HMC External Connectivity security whitepaper has been published, which describes data exchanges between the HMC and the IBM Service Delivery Center (SDC) and the methods and protocols for this exchange. To read the whitepaper and prepare for Electronic Service Agent installation, see the "Security" section at the [IBM Electronic Service Agent](#) website.

Select your country. Click "IBM Electronic Service Agent Connectivity Guide."

Benefits: increased uptime

Electronic Service Agent is designed to enhance the warranty and maintenance service by potentially providing faster hardware error reporting and uploading system information to IBM Support. This can optimize the time monitoring the symptoms, diagnosing the error, and manually calling IBM Support to open a

problem record. And 24x7 monitoring and reporting means no more dependency on human intervention or off-hours client personnel when errors are encountered in the middle of the night.

Security: The Electronic Service Agent tool is designed to help secure the monitoring, reporting, and storing of the data at IBM. The Electronic Service Agent tool is designed to help securely transmit either through the internet (HTTPS or VPN) or modem to provide clients a single point of exit from their site. Communication is one way. Activating Electronic Service Agent does not enable IBM to call into a client's system.

For additional information, see the [IBM Electronic Service Agent](#) website.

More accurate reporting

Because system information and error logs are automatically uploaded to the IBM Support Center in conjunction with the service request, clients are not required to find and send system information, decreasing the risk of misreported or misdiagnosed errors. Once inside IBM, problem error data is run through a data knowledge management system, and knowledge articles are appended to the problem record.

Customized support

By using the IBMid entered during activation, clients can view system and support information in the "My Systems" and "Premium Search" sections of the Electronic Services website.

The Electronic Services web portal is a single internet entry point that replaces the multiple entry points traditionally used to access IBM internet services and support. This web portal enables you to gain easier access to IBM resources for assistance in resolving technical problems. The newly improved My Systems and Premium Search functions make it even easier for Electronic Service Agent-enabled clients to track system inventory and find pertinent fixes.

My Systems provides valuable reports of installed hardware and software using information collected from the systems by IBM Electronic Service Agent. Reports are available for any system associated with the client's IBMid. Premium Search combines the function of search and the value of Electronic Service Agent information, providing advanced search of the technical support knowledgebase. Using Premium Search and the Service Agent information that has been collected from the system, clients are able to see search results that apply specifically to their systems.

For more information on how to utilize the power of IBM Electronic Services, see the following website or contact an [IBM Systems Services Representative](#).

Accessibility by people with disabilities

A US Section 508 Voluntary Product Accessibility Template (VPAT) containing details on accessibility compliance can be found on the [Product accessibility information](#) website.

Section 508 of the US Rehabilitation Act

Power H924 (9223-42H) for SAP HANA server is capable as of March 20, 2018, when used in accordance with IBM's associated documentation, of satisfying the applicable requirements of Section 508 of the Rehabilitation Act, provided that any assistive technology used with the product properly inter operates with it. A US Section 508 Voluntary Product Accessibility Template (VPAT) can be found on the [Product accessibility information](#) website.

Product positioning

Get the best out of SAP HANA with Power Systems. Power Systems is designed for data-intensive, in-memory workloads such as SAP HANA. With powerful, built-in, virtualization, reliability that you can bet your business on, and the performance that you expect from an enterprise-grade platform, Power Systems is the platform for SAP HANA.

This highly flexible system with best-in-class virtualization can help clients to consolidate their workloads and reduce the footprint in their data centers. In addition, you can run mixed workloads with traditional SAP and nonproduction workloads running in a shared pool side by side with production SAP HANA, leading to an efficient use of the system and a high utilization.

Power is supported for SAP HANA Tailored Datacenter Integration Phase 5 (TDI5), which gives you the flexibility to use the storage and networking of your choice, to change configurations, and have support from SAP, all while achieving a lower TCO. This means you can use nearly any Power System for SAP HANA, including H924, and re-use storage and networking already on hand.

Scale-up or scale-out your SAP HANA workload while maintaining the same level of flexibility. A separate purchase of SAP HANA is required for this use case.

Statement of general direction

IBM intends to support SAP HANA on the IBM Power System H924 server (9223-42H) in production mode, with the following Linux operating systems, following near-term certification of the environment:

- Red Hat Enterprise Linux for SAP with Red Hat Enterprise Linux 7 for Power LE version 7.4
- SUSE Linux Enterprise Server for SAP with SUSE Linux Enterprise Server 12 SP3

IBM's statements regarding its plans, directions, and intent are subject to change or withdrawal without notice at IBM's sole discretion. Information regarding potential future products is intended to outline our general product direction and it should not be relied on in making a purchasing decision. The information mentioned regarding potential future products is not a commitment, promise, or legal obligation to deliver any material, code, or functionality. Information about potential future products may not be incorporated into any contract. The development, release, and timing of any future features or functionality described for our products remain at our sole discretion.

Product number

The following are newly announced features on the specific models of the IBM Power Systems 9223 machine type:

Description	Machine		Feature number
	type	Model	
IBM Power System H924	9223	42H	
One CSC Billing Unit	9223	42H	0010
Ten CSC Billing Units	9223	42H	0011
Mirrored System Disk Level, Specify Code	9223	42H	0040
Device Parity Protection-All, Specify Code	9223	42H	0041
Mirrored System Bus Level, Specify Code	9223	42H	0043
Device Parity RAID-6 All, Specify Code	9223	42H	0047
RISC-to-RISC Data Migration	9223	42H	0205
AIX Partition Specify	9223	42H	0265
Linux Partition Specify	9223	42H	0266
IBM i Operating System Partition Specify	9223	42H	0267

Specify Custom Data Protection	9223	42H	0296
Mirrored Level System Specify Code	9223	42H	0308
RAID Hot Spare Specify	9223	42H	0347
V.24/EIA232 6.1m (20-Ft) PCI Cable	9223	42H	0348
V.35 6.1m (20-Ft) PCI Cable	9223	42H	0353
X.21 6.1m (20-Ft) PCI Cable	9223	42H	0359
Customer Specified Placement	9223	42H	0456
19 inch, 1.8 meter high rack	9223	42H	0551
19 inch, 2.0 meter high rack	9223	42H	0553
Rack Filler Panel Kit	9223	42H	0599
Load Source Not in CEC	9223	42H	0719
SAN Load Source Specify	9223	42H	0837
US TAA Compliance Indicator	9223	42H	0983
Product assembled in USA manufacturing plant	9223	42H	0984
Modem Cable - US/Canada and General Use	9223	42H	1025
USB 500 GB Removable Disk Drive	9223	42H	1107
Custom Service Specify, Rochester Minn, USA	9223	42H	1140
Quantity 150 of #1964	9223	42H	1818
Quantity 150 of #1953	9223	42H	1929
300GB 15k RPM SAS SFF-2 Disk Drive (AIX/Linux)	9223	42H	1953
600GB 10k RPM SAS SFF-2 Disk Drive (AIX/Linux)	9223	42H	1964
Primary OS - IBM i	9223	42H	2145
Primary OS - AIX	9223	42H	2146
Primary OS - Linux	9223	42H	2147
Factory Deconfiguration of 1-core	9223	42H	2319
2M LC-SC 50 Micron Fiber Converter Cable	9223	42H	2456
2M LC-SC 62.5 Micron Fiber Converter Cable	9223	42H	2459
3M Asynchronous Terminal/Printer Cable EIA-232	9223	42H	2934
Asynchronous Cable EIA-232/V.24 3M	9223	42H	2936
Serial-to-Serial Port Cable for Drawer/Drawer-3.7M	9223	42H	3124
Serial-to-Serial Port Cable for Rack/Rack- 8M	9223	42H	3125
Widescreen LCD Monitor	9223	42H	3632
0.3M Serial Port Converter Cable, 9-Pin to 25-Pin	9223	42H	3925
Serial Port Null Modem Cable, 9-pin to 9-pin, 3.7M	9223	42H	3927
Serial Port Null Modem Cable, 9-pin to 9-pin, 10M	9223	42H	3928
System Serial Port Converter Cable	9223	42H	3930
1.8 M (6-ft) Extender Cable for Displays (15-pin D-shell to 15-pin D-shell)	9223	42H	4242
Extender Cable - USB Keyboards, 1.8M	9223	42H	4256
VGA to DVI Connection Converter	9223	42H	4276
Rack Integration Services: BP only	9223	42H	4648
Rack Integration Services	9223	42H	4649
Rack Indicator- Not Factory Integrated	9223	42H	4650
Rack Indicator, Rack #1	9223	42H	4651
Rack Indicator, Rack #2	9223	42H	4652
Rack Indicator, Rack #3	9223	42H	4653
Rack Indicator, Rack #4	9223	42H	4654
Rack Indicator, Rack #5	9223	42H	4655
Rack Indicator, Rack #6	9223	42H	4656
Rack Indicator, Rack #7	9223	42H	4657
Rack Indicator, Rack #8	9223	42H	4658
Rack Indicator, Rack #9	9223	42H	4659
Rack Indicator, Rack #10	9223	42H	4660
Rack Indicator, Rack #11	9223	42H	4661
Rack Indicator, Rack #12	9223	42H	4662
Rack Indicator, Rack #13	9223	42H	4663
Rack Indicator, Rack #14	9223	42H	4664
Rack Indicator, Rack #15	9223	42H	4665
Rack Indicator, Rack #16	9223	42H	4666
Power Active Memory Expansion Enablement	9223	42H	4794
One Processor of 5250 Enterprise Enablement	9223	42H	4970
Full 5250 Enterprise Enablement	9223	42H	4974
Software Preload Required	9223	42H	5000
PowerVM Enterprise Edition	9223	42H	5228
Sys Console on HMC	9223	42H	5550
System Console-Ethernet LAN adapter	9223	42H	5557
PCIe2 8Gb 4-port Fibre Channel Adapter	9223	42H	5729
8 Gigabit PCI Express Dual Port Fibre Channel			

Adapter	9223	42H	5735
POWER GXT145 PCI Express Graphics Accelerator	9223	42H	5748
4 Port Async EIA-232 PCIe Adapter	9223	42H	5785
PCIe2 4-port 1GbE Adapter	9223	42H	5899
Opt Front Door for 1.8m Rack	9223	42H	6068
Opt Front Door for 2.0m Rack	9223	42H	6069
1.8m Rack Acoustic Doors	9223	42H	6248
2.0m Rack Acoustic Doors	9223	42H	6249
1.8m Rack Trim Kit	9223	42H	6263
2.0m Rack Trim Kit	9223	42H	6272
Power Cord 4.3m (14-ft), Drawer to IBM PDU (250V/10A)	9223	42H	6458
Power Cord 4.3m (14-ft), Drawer To OEM PDU (125V, 15A)	9223	42H	6460
Power Cord 4.3m (14-ft), Drawer to wall/OEM PDU (250V/15A) U. S.	9223	42H	6469
Power Cord 1.8m (6-ft), Drawer to wall (125V/15A)	9223	42H	6470
Power Cord 2.7m (9-ft), Drawer to wall/OEM PDU (250V/10A)	9223	42H	6471
Power Cord 2.7m (9-ft), Drawer to wall/OEM PDU (250V/16A)	9223	42H	6472
Power Cord 2.7m (9-ft), Drawer to wall/OEM PDU (250V/10A)	9223	42H	6473
Power Cord 2.7m (9-ft), Drawer to wall/OEM PDU, (250V/13A)	9223	42H	6474
Power Cord 2.7m (9-ft), Drawer to wall/OEM PDU, (250V/16A)	9223	42H	6475
Power Cord 2.7m (9-ft), Drawer to wall/OEM PDU, (250V/10A)	9223	42H	6476
Power Cord 2.7m (9-ft), Drawer to wall/OEM PDU, (250V/16A)	9223	42H	6477
Power Cord 2.7 M(9-foot), To wall/OEM PDU, (250V, 16A)	9223	42H	6478
Power Cord 2.7m (9-ft), Drawer to wall/OEM PDU, (125V/15A or 250V/10A)	9223	42H	6488
4.3m (14-Ft) 3PH/24A 380-415V Power Cord	9223	42H	6489
4.3m (14-Ft) 1PH/63A 200-240V Power Cord	9223	42H	6491
4.3m (14-Ft) 1PH/48-60A 200-240V Power Cord	9223	42H	6492
Power Cord 2.7m (9-ft), Drawer to wall/OEM PDU, (250V/10A)	9223	42H	6493
Power Cord 2.7m (9-ft), Drawer to wall/OEM PDU, (250V/10A)	9223	42H	6494
Power Cord 2.7M (9-foot), To wall/OEM PDU, (250V, 10A)	9223	42H	6496
Power Cable - Drawer to IBM PDU, 200-240V/10A	9223	42H	6577
Optional Rack Security Kit	9223	42H	6580
Power Cord 2.7M (9-foot), To wall/OEM PDU, (125V, 15A)	9223	42H	6651
4.3m (14-Ft) 3PH/16A 380-415V Power Cord	9223	42H	6653
4.3m (14-Ft) 1PH/24-30A Pwr Cord	9223	42H	6654
4.3m (14-Ft) 1PH/24-30A WR Pwr Cord	9223	42H	6655
4.3m (14-Ft) 1PH/24A Power Cord	9223	42H	6656
4.3m (14-Ft) 1PH/32A Power Cord	9223	42H	6657
4.3m (14-Ft) 1PH/24A Pwr Cd-Korea	9223	42H	6658
Power Cord 2.7M (9-foot), To wall/OEM PDU, (250V, 15A)	9223	42H	6659
Power Cord 4.3m (14-ft), Drawer to wall/OEM PDU (125V/15A)	9223	42H	6660
Power Cord 2.8m (9.2-ft), Drawer to IBM PDU, (250V/10A)	9223	42H	6665
4.3m (14-Ft) 3PH/32A 380-415V Power Cord-Australia	9223	42H	6667
Power Cord 4.3M (14-foot), Drawer to OEM PDU, (250V, 15A)	9223	42H	6669
Power Cord 2.7M (9-foot), Drawer to IBM PDU, 250V/10A	9223	42H	6671
Power Cord 2M (6.5-foot), Drawer to IBM PDU, 250V/10A	9223	42H	6672
Power Cord 2.7m (9-ft), Drawer to wall/OEM PDU, (250V/10A)	9223	42H	6680
Intelligent PDU+, 1 EIA Unit, Universal UTG0247 Connector	9223	42H	7109
Environmental Monitoring Probe	9223	42H	7118
Power Distribution Unit	9223	42H	7188

Power Distribution Unit (US) - 1 EIA Unit, Universal, Fixed Power Cord	9223	42H	7196
Ethernet Cable, 15m, Hardware Management Console to System Unit	9223	42H	7802
Linux Software Preinstall	9223	42H	8143
Linux Software Preinstall (Business Partners)	9223	42H	8144
USB Mouse	9223	42H	8845
Order Routing Indicator- System Plant	9223	42H	9169
Language Group Specify - US English	9223	42H	9300
New AIX License Core Counter	9223	42H	9440
New IBM i License Core Counter	9223	42H	9441
New Red Hat License Core Counter	9223	42H	9442
New SUSE License Core Counter	9223	42H	9443
Other AIX License Core Counter	9223	42H	9444
Other Linux License Core Counter	9223	42H	9445
3rd Party Linux License Core Counter	9223	42H	9446
VIOS Core Counter	9223	42H	9447
Other License Core Counter	9223	42H	9449
Ubuntu Linux License Core Counter	9223	42H	9450
Month Indicator	9223	42H	9461
Day Indicator	9223	42H	9462
Hour Indicator	9223	42H	9463
Minute Indicator	9223	42H	9464
Qty Indicator	9223	42H	9465
Countable Member Indicator	9223	42H	9466
Language Group Specify - Dutch	9223	42H	9700
Language Group Specify - French	9223	42H	9703
Language Group Specify - German	9223	42H	9704
Language Group Specify - Polish	9223	42H	9705
Language Group Specify - Norwegian	9223	42H	9706
Language Group Specify - Portuguese	9223	42H	9707
Language Group Specify - Spanish	9223	42H	9708
Language Group Specify - Italian	9223	42H	9711
Language Group Specify - Canadian French	9223	42H	9712
Language Group Specify - Japanese	9223	42H	9714
Language Group Specify - Traditional Chinese (Taiwan)	9223	42H	9715
Language Group Specify - Korean	9223	42H	9716
Language Group Specify - Turkish	9223	42H	9718
Language Group Specify - Hungarian	9223	42H	9719
Language Group Specify - Slovakian	9223	42H	9720
Language Group Specify - Russian	9223	42H	9721
Language Group Specify - Simplified Chinese (PRC)	9223	42H	9722
Language Group Specify - Czech	9223	42H	9724
Language Group Specify - Romanian	9223	42H	9725
Language Group Specify - Croatian	9223	42H	9726
Language Group Specify - Slovenian	9223	42H	9727
Language Group Specify - Brazilian Portuguese	9223	42H	9728
Language Group Specify - Thai	9223	42H	9729
10m (30.3-ft), IBM Passive QSFP+ MTP Optical Cable	9223	42H	EB2J
30m (90.3-ft), IBM Passive QSFP+ MTP Optical Cable	9223	42H	EB2K
AC Power Supply - 1400w for Server (200-240 VAC)	9223	42H	EB2M
Lift tool based on GenieLift GL-8 (standard)	9223	42H	EB3Z
10Gb Optical Transceiver SFP+	9223	42H	EB46
25Gb Optical Transceiver SFP28	9223	42H	EB47
0.5m SFP28/25GbE copper Cable	9223	42H	EB4J
1.0m SFP28/25GbE copper Cable	9223	42H	EB4K
1.5m SFP28/25GbE copper Cable	9223	42H	EB4L
2.0m SFP28/25GbE copper Cable	9223	42H	EB4M
2.0m QSFP28/100GbE copper split Cable to SFP28 4x25GbE	9223	42H	EB4P
Service wedge shelf tool kit for EB3Z	9223	42H	EB4Z
0.5m EDR IB Copper Cable QSFP28	9223	42H	EB50
1.0m EDR IB Copper Cable QSFP28	9223	42H	EB51
2.0M EDR IB Copper Cable QSFP28	9223	42H	EB52
1.5M EDR IB Copper Cable QSFP28	9223	42H	EB54
100Gb optical Transceiver QSFP28	9223	42H	EB59
3M EDR IB Optical Cable QSFP28	9223	42H	EB5A
5M EDR IB Optical Cable QSFP28	9223	42H	EB5B
10M EDR IB Optical Cable QSFP28	9223	42H	EB5C
15M EDR IB Optical Cable QSFP28	9223	42H	EB5D

20M EDR IB Optical Cable QSFP28	9223	42H	EB5E
30M EDR IB Optical Cable QSFP28	9223	42H	EB5F
50M EDR IB Optical Cable QSFP28	9223	42H	EB5G
100M EDR IB Optical Cable QSFP28	9223	42H	EB5H
0.5M 100GbE Copper Cable QSFP28	9223	42H	EB5J
1.0M 100GbE Copper Cable QSFP28	9223	42H	EB5K
1.5M 100GbE Copper Cable QSFP28	9223	42H	EB5L
2.0M 100GbE Copper Cable QSFP28	9223	42H	EB5M
25M EDR IB Optical Cable QSFP28	9223	42H	EB5N
3M 100GbE Optical Cable QSFP28 (AOC)	9223	42H	EB5R
5M 100GbE Optical Cable QSFP28 (AOC)	9223	42H	EB5S
10M 100GbE Optical Cable QSFP28 (AOC)	9223	42H	EB5T
15M 100GbE Optical Cable QSFP28 (AOC)	9223	42H	EB5U
20M 100GbE Optical Cable QSFP28 (AOC)	9223	42H	EB5V
30M 100GbE Optical Cable QSFP28 (AOC)	9223	42H	EB5W
50M 100GbE Optical Cable QSFP28 (AOC)	9223	42H	EB5X
100M 100GbE Optical Cable QSFP28 (AOC)	9223	42H	EB5Y
IBM i 7.2 Indicator	9223	42H	EB72
IBM i 7.3 Indicator	9223	42H	EB73
Rack Front Door (Black)	9223	42H	EC01
Rack Rear Door	9223	42H	EC02
Rack Side Cover	9223	42H	EC03
Rack Suite Attachment Kit	9223	42H	EC04
Slim Rear Acoustic Door	9223	42H	EC07
Slim Front Acoustic Door	9223	42H	EC08
Rear Door Heat Exchanger for 2.0 Meter Slim Rack	9223	42H	EC15
PCIe3 2-Port 10Gb NIC&ROCE SR/Cu Adapter	9223	42H	EC2S
PCIe3 2-Port 25/10Gb NIC&ROCE SR/Cu Adapter	9223	42H	EC2U
PCIe3 2-port 100GbE (NIC&RoCE) QSFP28 Adapter x16	9223	42H	EC3M
PCIe3 NVMe carrier card w/2 M.2 module slots	9223	42H	EC59
PCIe4 1-port 100Gb EDR IB CAPI adapter	9223	42H	EC63
PCIe4 2-port 100Gb EDR IB CAPI adapter	9223	42H	EC65
SAS X Cable 3m - HD Narrow 6Gb 2-Adapters to Enclosure	9223	42H	ECBJ
SAS X Cable 6m - HD Narrow 6Gb 2-Adapters to Enclosure	9223	42H	ECBK
SAS X Cable 10m - HD Narrow 6Gb 2-Adapters to Enclosure	9223	42H	ECBL
SAS X Cable 15m - HD Narrow 3Gb 2-Adapters to Enclosure	9223	42H	ECBM
SAS YO Cable 1.5m - HD Narrow 6Gb Adapter to Enclosure	9223	42H	ECBT
SAS YO Cable 3m - HD Narrow 6Gb Adapter to Enclosure	9223	42H	ECBU
SAS YO Cable 6m - HD Narrow 6Gb Adapter to Enclosure	9223	42H	ECBV
SAS YO Cable 10m - HD Narrow 6Gb Adapter to Enclosure	9223	42H	ECBW
SAS YO Cable 15m - HD Narrow 3Gb Adapter to Enclosure	9223	42H	ECBX
SAS AE1 Cable 4m - HD Narrow 6Gb Adapter to Enclosure	9223	42H	ECBY
SAS YE1 Cable 3m - HD Narrow 6Gb Adapter to Enclosure	9223	42H	ECBZ
SAS AA Cable 0.6m - HD Narrow 6Gb Adapter to Adapter	9223	42H	ECC0
SAS AA Cable 1.5m - HD Narrow 6Gb Adapter to Adapter	9223	42H	ECC2
SAS AA Cable 3m - HD Narrow 6Gb Adapter to Adapter	9223	42H	ECC3
SAS AA Cable 6m - HD Narrow 6Gb Adapter to Adapter	9223	42H	ECC4
3M Optical Cable Pair for PCIe3 Expansion Drawer	9223	42H	ECC7
10M Optical Cable Pair for PCIe3 Expansion Drawer	9223	42H	ECC8
System Port converter Cable for UPS	9223	42H	ECCF
3M Copper CXP Cable Pair for PCIe3 Expansion Drawer	9223	42H	ECCS
3.0M SAS X12 Cable (Two Adapter to Enclosure)	9223	42H	ECDJ
4.5M SAS X12 Active Optical Cable (Two Adapter to Enclosure)	9223	42H	ECDK
10M SAS X12 Active Optical Cable (Two Adapter to Enclosure)	9223	42H	ECDL
1.5M SAS Y012 Cable (Adapter to Enclosure)	9223	42H	ECDT
3.0M SAS Y012 Cable (Adapter to Enclosure)	9223	42H	ECDU

4.5M SAS Y012 Active Optical Cable (Adapter to Enclosure)	9223	42H	ECDV
10M SAS Y012 Active Optical Cable (Adapter to Enclosure)	9223	42H	ECDW
0.6M SAS AA12 Cable (Adapter to Adapter)	9223	42H	ECE0
3.0M SAS AA12 Cable	9223	42H	ECE3
4.5M SAS AA12 Active Optical Cable (Adapter to Adapter)	9223	42H	ECE4
2.0 Meter Slim Rack	9223	42H	ECR0
Rack Front Door High-End appearance	9223	42H	ECRF
Rack Rear Door Black	9223	42H	ECRG
Rack Side Cover	9223	42H	ECRJ
Rack Rear Extension 5-In	9223	42H	ECRK
Rack Front Door for Rack (Black/Flat)	9223	42H	ECRM
Indicator Assembled and Tested in China	9223	42H	ECS0
Custom Service Specify, Montpellier, France	9223	42H	ECSF
NeuCloud Indicator/Specify	9223	42H	ECSJ
Custom Service Specify, Mexico	9223	42H	ECSM
Custom Service Specify, Poughkeepsie, USA	9223	42H	ECSP
Integrated Solution Packing	9223	42H	ECSS
Optical Wrap Plug	9223	42H	ECW0
Boot Drive / Load Source in EXP12SX Specify (in #ESLL or #ELLL)	9223	42H	EHR1
Boot Drive / Load Source in EXP24SX Specify (in #ESLS or #ELLS)	9223	42H	EHR2
SSD Placement Indicator - #ESLS/#ELLS	9223	42H	EHS2
PCIe3 Optical Cable Adapter for PCIe3 Expansion Drawer	9223	42H	EJ08
PCIe3 RAID SAS Adapter Quad-port 6Gb x8	9223	42H	EJ0J
SAS Ports/Cabling for Dual IOA BackPlane	9223	42H	EJ0W
PCIe3 SAS Tape/DVD Adapter Quad-port 6Gb x8	9223	42H	EJ10
PCIe3 12GB Cache RAID PLUS SAS Adapter Quad-port 6Gb x8	9223	42H	EJ14
Base Storage Backplane 12 SFF-3 Bays/RDX Bay	9223	42H	EJ1C
Expanded Function Storage Backplane 18 SFF-3 Bays/Dual IOA with Write Cache/Opt Ext SAS port Split #EJ1C to 6+6 SFF-3 Bays: Add 2nd SAS Controller	9223	42H	EJ1D
Expanded Function Storage Backplane 12 SFF-3 Bays/RDX Bay/Opt Ext SAS port	9223	42H	EJ1E
PCIe3 Crypto Coprocessor BSC-Gen3 4767	9223	42H	EJ1M
Non-paired Indicator EJ14 PCIe SAS RAID+ Adapter	9223	42H	EJ33
Front IBM Bezel for 12-Bay BackPlane	9223	42H	EJRL
Front OEM Bezel for 12-Bay BackPlane	9223	42H	EJU3
Front IBM Bezel for 18-Bay BackPlane	9223	42H	EJU4
Front OEM Bezel for 18-Bay BackPlane	9223	42H	EJUG
Specify Mode-1 & CEC SAS Ports & (2)Y012 for EXP12SX #ESLL/ELLL	9223	42H	EJUH
Specify Mode-1 & (1)EJ0J/EJ0M/EL3B/EL59 & (1)Y012 for EXP12SX #ESLL/ELLL	9223	42H	EJV0
Specify Mode-1 & (2)EJ0J/EJ0M/EL3B/EL59 & (2)Y012 for EXP12SX #ESLL/ELLL	9223	42H	EJV1
Specify Mode-2 & (2)EJ0J/EJ0M/EL3B/EL59 & (2)X12 for EXP12SX #ESLL/ELLL	9223	42H	EJV2
Specify Mode-2 & (4)EJ0J/EJ0M/EL3B/EL59 & (2)X12 for EXP12SX #ESLL/ELLL	9223	42H	EJV3
Specify Mode-2 & (4)EJ0J/EJ0M/EL3B/EL59 & (2)X12 for EXP12SX #ESLL/ELLL	9223	42H	EJV4
Specify Mode-4 & (4)EJ0J/EJ0M/EL3B/EL59 & (2)X12 for EXP12SX #ESLL/ELLL	9223	42H	EJV5
Specify Mode-2 & (1)EJ0J/EJ0M/EL3B/EL59 & (2)Y012 for EXP12SX #ESLL/ELLL	9223	42H	EJV6
Specify Mode-2 & (2)EJ0J/EJ0M/EL3B/EL59 & (2)Y012 for EXP12SX #ESLL/ELLL	9223	42H	EJV7
Specify Mode-2 & (1)EJ0J/EJ0M/EL3B/EL59 & (1)Y012 for EXP12SX #ESLL/ELLL	9223	42H	EJVA
Specify Mode-2 & (2)EJ0J/EJ0M/EL3B/EL59 & (1)X12 for EXP12SX #ESLL/ELLL	9223	42H	EJVB
Specify Mode-4 & (1)EJ0J/EJ0M/EL3B/EL59 & (1)X12 for EXP12SX #ESLL/ELLL	9223	42H	EJVC
Specify Mode-4 & (2)EJ0J/EJ0M/EL3B/EL59 & (1)X12 for EXP12SX #ESLL/ELLL	9223	42H	EJVD
Specify Mode-4 & (3)EJ0J/EJ0M/EL3B/EL59 & (2)X12 for EXP12SX #ESLL/ELLL	9223	42H	EJVE
Specify Mode-1 & (2)EJ14 & (2)Y012 for EXP12SX #ESLL/ELLL	9223	42H	EJVF

Specify Mode-1 & CEC SAS Ports & (2)Y012 for EXP24SX #ESLS/ELS	9223	42H	EJW0
Specify Mode-1 & (1)EJ0J/EJ0M/EL3B/EL59 & (1)Y012 for EXP24SX #ESLS/ELLS	9223	42H	EJW1
Specify Mode-1 & (2)EJ0J/EJ0M/EL3B/EL59 & (2)Y012 for EXP24SX #ESLS/ELLS	9223	42H	EJW2
Specify Mode-2 & (2)EJ0J/EJ0M/EL3B/EL59 & (2)X12 for EXP24SX #ESLS/ELLS	9223	42H	EJW3
Specify Mode-2 & (4)EJ0J/EJ0M/EL3B/EL59 & (2)X12 for EXP24SX #ESLS/ELLS	9223	42H	EJW4
Specify Mode-4 & (4)EJ0J/EJ0M/EL3B/EL59 & (2)X12 for EXP24SX #ESLS/ELLS	9223	42H	EJW5
Specify Mode-2 & (1)EJ0J/EJ0M/EL3B/EL59 & (2)Y012 for EXP24SX #ESLS/ELLS	9223	42H	EJW6
Specify Mode-2 & (2)EJ0J/EJ0M/EL3B/EL59 & (2)Y012 for EXP24SX #ESLS/ELLS	9223	42H	EJW7
Specify Mode-2 & (1)EJ0J/EJ0M/EL3B/EL59 & (1)Y012 for EXP24SX #ESLS/ELLS	9223	42H	EJWA
Specify Mode-2 & (2)EJ0J/EJ0M/EL3B/EL59 & (1)X12 for EXP24SX #ESLS/ELLS	9223	42H	EJWB
Specify Mode-4 & (1)EJ0J/EJ0M/EL3B/EL59 & (1)X12 for EXP24SX #ESLS/ELLS	9223	42H	EJWC
Specify Mode-4 & (2)EJ0J/EJ0M/EL3B/EL59 & (1)X12 for EXP24SX #ESLS/ELLS	9223	42H	EJWD
Specify Mode-4 & (3)EJ0J/EJ0M/EL3B/EL59 & (2)X12 for EXP24SX #ESLS/ELLS	9223	42H	EJWE
Specify Mode-1 & (2)EJ14 & (2)Y012 for EXP24SX #ESLS/ELLS	9223	42H	EJWF
Specify Mode-2 & (2)EJ14 & (2)X12 for EXP24SX #ESLS/ELLS	9223	42H	EJWG
Specify Mode-2 & (2)EJ14 & (1)X12 for EXP24SX #ESLS/ELLS	9223	42H	EJWH
Specify Mode-2 & (4)EJ14 & (2)X12 for EXP24SX #ESLS/ELLS	9223	42H	EJWJ
PDU Access Cord 0.38m	9223	42H	ELC0
#ESD4 Load Source Specify (571GB 10K RPM SAS SFF-3 for IBM i)	9223	42H	ELS4
#ESDA Load Source Specify (283GB 15K RPM SAS SFF-3 for IBM i)	9223	42H	ELSA
#ESFU Load Source Specify (1.7TB HDD SFF-3)	9223	42H	ELT0
#ES81 Load Source Specify (1.9TB SFF-2 SSD)	9223	42H	ELT1
#ESF2 Load Source Specify (1.1TB HDD SFF-2)	9223	42H	ELT2
#ESF4 Load Source Specify (571GB HDD SFF-3)	9223	42H	ELT4
#ES86 Load Source Specify (387GB SFF-2 SSD 4k for IBM i)	9223	42H	ELT6
#ESF8 Load Source Specify (1.1TB HDD SFF-3)	9223	42H	ELT8
#ESFA Load Source Specify (283GB 15K RPM SAS SFF-3 4K Block - 4224)	9223	42H	ELTA
#ES8D Load Source Specify (775GB SFF-2 SSD 4k for IBM i)	9223	42H	ELTD
#ESFE Load Source Specify (571GB 15K RPM SAS SFF-3 4K Block - 4224)	9223	42H	ELTE
#ES8G Load Source Specify (1.55TB SFF-2 SSD 4k for IBM i)	9223	42H	ELTG
#ES8K Load Source Specify (1.9TB SFF-3 SSD)	9223	42H	ELTK
#ES7L Load Source Specify (387GB SFF-3 SSD 5xx for IBM i)	9223	42H	ELTL
#ESFN Load Source Specify (571GB 15K RPM SAS SFF-2 4K Block - 4224)	9223	42H	ELTN
#ES8P Load Source Specify (387GB SFF-3 SSD 4k for IBM i)	9223	42H	ELTP
#ES7Q Load Source Specify (775GB SFF-3 SSD 5xx for IBM i)	9223	42H	ELTQ
#ES8R Load Source Specify (775GB SFF-3 SSD 4k for IBM i)	9223	42H	ELTR
#ESFS Load Source Specify (1.7TB HDD SFF-2)	9223	42H	ELTS
#ESEU Load Source Specify (571GB HDD SFF-2)	9223	42H	ELTU
#ES8W Load Source Specify (1.55TB SFF-3 SSD 4k for IBM i)	9223	42H	ELTW
#ESEY Load Source Specify (283GB 15K RPM SAS SFF-2 4K Block - 4224)	9223	42H	ELTY
#ESNJ Load Source Specify (283GB HDD SFF-3)	9223	42H	ELUJ
#ESNL Load Source Specify (283GB HDD SFF-2)	9223	42H	ELUL
#ESNN Load Source Specify (571GB HDD SFF-3)	9223	42H	ELUN

#ESNQ Load Source Specify (571GB HDD SFF-2)	9223	42H	ELUQ
#ESE2 Load Source Specify (3.72TB SSD SFF-3)	9223	42H	ELZ2
#ES93 Load Source Specify (1.86TB SSD SFF-3)	9223	42H	ELZ3
#ES84 Load Source Specify (931GB SSD SFF-3)	9223	42H	ELZ4
#ES97 Load Source Specify (1.86TB SSD SFF-2)	9223	42H	ELZ7
#ESE8 Load Source Specify (3.72TB SSD SFF-2)	9223	42H	ELZ8
#ESGA Load Source Specify (387GB SSD SFF-3)	9223	42H	ELZA
#ESGC Load Source Specify (387GB SSD SFF-2)	9223	42H	ELZC
#ESGE Load Source Specify (387GB SSD SFF-3)	9223	42H	ELZE
#ESGJ Load Source Specify (775GB SSD SFF-3)	9223	42H	ELZJ
#ESGL Load Source Specify (775GB SSD SFF-2)	9223	42H	ELZL
#ESGN Load Source Specify (775GB SSD SFF-3)	9223	42H	ELZN
#ESGQ Load Source Specify (1.55TB SSD SFF-2)	9223	42H	ELZQ
#ESGS Load Source Specify (1.55TB SSD SFF-3)	9223	42H	ELZS
#ES8Z Load Source Specify (931GB SSD SFF-2)	9223	42H	ELZZ
16 GB DDR4 Memory	9223	42H	EM62
32 GB DDR4 Memory	9223	42H	EM63
64 GB DDR4 Memory	9223	42H	EM64
128 GB DDR4 Memory	9223	42H	EM65
PCIe Gen3 I/O Expansion Drawer	9223	42H	EMX0
AC Power Supply Conduit for PCIe3 Expansion Drawer	9223	42H	EMXA
PCIe3 6-slot Fanout Module for PCIe3 Expansion Drawer	9223	42H	EMXF
PCIe3 6-slot Fanout Module for PCIe3 Expansion Drawer	9223	42H	EMXG
1m (3.3-ft), 10Gb E'Net Cable SFP+ Act Twinax Copper	9223	42H	EN01
3m (9.8-ft), 10Gb E'Net Cable SFP+ Act Twinax Copper	9223	42H	EN02
5m (16.4-ft), 10Gb E'Net Cable SFP+ Act Twinax Copper	9223	42H	EN03
PCIe3 16Gb 2-port Fibre Channel Adapter	9223	42H	EN0A
PCIe3 4-port (10Gb FCoE & 1GbE) SR&RJ45	9223	42H	EN0H
PCIe3 4-port (10Gb FCoE & 1GbE) SFP+Copper&RJ45	9223	42H	EN0K
PCIe2 4-Port (10Gb+1GbE) SR+RJ45 Adapter	9223	42H	EN0S
PCIe2 4-port (10Gb+1GbE) Copper SFP+RJ45 Adapter	9223	42H	EN0U
PCIe2 2-port 10/1GbE BaseT RJ45 Adapter	9223	42H	EN0W
PCIe 1-port Bisync Adapter	9223	42H	EN13
PCIe3 4-port 10GbE SR Adapter	9223	42H	EN15
PCIe3 32Gb 2-port Fibre Channel Adapter	9223	42H	EN1A
PCIe3 16Gb 4-port Fibre Channel Adapter	9223	42H	EN1C
8-core Typical 3.8 to 4.0 GHz (max) POWER9 Processor	9223	42H	EP1E
10-core Typical 3.5 to 3.9 Ghz (max) POWER9 Processor	9223	42H	EP1F
12-core Typical 3.4 to 3.9 Ghz (max) POWER9 Processor	9223	42H	EP1G
One Processor Core Activation for #EP1E	9223	42H	EP4E
One Processor Core Activation for #EP1F	9223	42H	EP4F
One Processor Core Activation for #EP1G	9223	42H	EP4G
Horizontal PDU Mounting Hardware	9223	42H	EPTH
High Function 9xC19 PDU: Switched, Monitoring	9223	42H	EPTJ
High Function 9xC19 PDU 3-Phase: Switched, Monitoring	9223	42H	EPTL
High Function 12xC13 PDU: Switched, Monitoring	9223	42H	EPTN
High Function 12xC13 PDU 3-Phase: Switched, Monitoring	9223	42H	EPTQ
Quantity 150 of #ES62 3.86-4.0 TB 7200 rpm 4k LFF-1 Disk	9223	42H	EQ62
Quantity 150 of #ES64 7.72-8.0 TB 7200 rpm 4k LFF-1 Disk	9223	42H	EQ64
Quantity 150 of #ES78 387GB SFF-2 SSD 5xx	9223	42H	EQ78
Quantity 150 of #ES7E 775GB SFF-2 SSD 5xx	9223	42H	EQ7E
Quantity 150 of #ES80 1.9TB SFF-2 SSD 4k	9223	42H	EQ80
Quantity 150 of ES81 1.9TB SFF-2 SSD 4k	9223	42H	EQ81
Quantity 150 of #ES85 387GB SFF-2 SSD 4k	9223	42H	EQ85
Quantity 150 of #ES86 387GB SFF-2 SSD 4k	9223	42H	EQ86
Quantity 150 of #ES8C 775GB SFF-2 SSD 4k	9223	42H	EQ8C
Quantity 150 of #ES8D 775GB SFF-2 SSD 4k	9223	42H	EQ8D
Quantity 150 of #ES8F 1.55TB SFF-2 SSD 4k	9223	42H	EQ8F
Quantity 150 of #ES8G 1.55TB SFF-2 SSD 4k	9223	42H	EQ8G
Quantity 150 of #ES8Y 931GB SFF-2 SSD 4k	9223	42H	EQ8Y

Quantity 150 of ES8Z 931GB SFF-2 SSD 4k	9223	42H	EQ8Z
Quantity 150 of ES96 1.86TB SFF-2 SSD 4k	9223	42H	EQ96
Quantity 150 of ES97 1.86TB SFF-2 SSD 4k	9223	42H	EQ97
Quantity 150 of #ESE7 3.72TB SFF-2 SSD 4k	9223	42H	EQE7
Quantity 150 of ESE8 3.72TB SFF-2 SSD 4k	9223	42H	EQE8
Quantity 150 of #ESEU (571GB 10k SFF-2)	9223	42H	EQEU
Quantity 150 of #ESEV (600GB 10k SFF-2)	9223	42H	EQEV
Quantity 150 of #ESEY (283 GB SFF-2)	9223	42H	EQEY
Quantity 150 of #ESEZ (300GB SFF-2)	9223	42H	EQEZ
Quantity 150 of #ESF2 (1.1TB 10k SFF-2)	9223	42H	EQF2
Quantity 150 of #ESF3 (1.2TB 10k SFF-2)	9223	42H	EQF3
Quantity 150 of #ESFN (571GB SFF-2)	9223	42H	EQFN
Quantity 150 of #ESFP (600GB SFF-2)	9223	42H	EQFP
Quantity 150 of #ESFS (1.7TB 10k SFF-2)	9223	42H	EQFS
Quantity 150 of #ESFT (1.8TB 10k SFF-2)	9223	42H	EQFT
Quantity 150 of #ESG5 (387GB SAS 5xx)	9223	42H	EQG5
Quantity 150 of #ESGB (387GB SAS 4k)	9223	42H	EQGB
Quantity 150 of #ESGC (387GB SAS 4k)	9223	42H	EQGC
Quantity 150 of #ESGF (775GB SAS 5xx)	9223	42H	EQGF
Quantity 150 of #ESGK (775GB SAS 4k)	9223	42H	EQGK
Quantity 150 of #ESGL (775GB SAS 4k)	9223	42H	EQGL
Quantity 150 of #ESGP (1.55TB SAS 4k)	9223	42H	EQGP
Quantity 150 of #ESGQ (1.55TB SAS 4k)	9223	42H	EQGQ
42U Slim Rack	9223	42H	ER05
RFID Tags for Servers, Compute Nodes, Chassis, Racks, and HMCs	9223	42H	ERF1
Rear rack extension	9223	42H	ERG0
Mainstream 400GB SSD NVMe M.2 module	9223	42H	ES14
3.86-4.0 TB 7200 RPM 4K SAS LFF-1 Nearline Disk Drive (AIX/Linux)	9223	42H	ES62
7.72-8.0 TB 7200 RPM 4K SAS LFF-1 Nearline Disk Drive (AIX/Linux)	9223	42H	ES64
387GB SFF-2 SSD 5xx eMLC4 for AIX/Linux	9223	42H	ES78
775GB SFF-2 SSD 5xx eMLC4 for AIX/Linux	9223	42H	ES7E
387GB SFF-3 SSD 5xx eMLC4 for AIX/Linux	9223	42H	ES7K
387GB SFF-3 SSD 5xx eMLC4 for IBM i	9223	42H	ES7L
775GB SFF-3 SSD 5xx eMLC4 for AIX/Linux	9223	42H	ES7P
775GB SFF-3 SSD 5xx eMLC4 for IBM i	9223	42H	ES7Q
1.9TB Read Intensive SAS 4k SFF-2 SSD for AIX/ Linux	9223	42H	ES80
1.9TB Read Intensive SAS 4k SFF-2 SSD for IBM i	9223	42H	ES81
931GB Mainstream SAS 4k SFF-3 SSD for AIX/Linux	9223	42H	ES83
931GB Mainstream SAS 4k SFF-3 SSD for IBM i	9223	42H	ES84
387GB SFF-2 SSD 4k eMLC4 for AIX/Linux	9223	42H	ES85
387GB SFF-2 SSD 4k eMLC4 for IBM i	9223	42H	ES86
775GB SFF-2 SSD 4k eMLC4 for AIX/Linux	9223	42H	ES8C
775GB SFF-2 SSD 4k eMLC4 for IBM i	9223	42H	ES8D
1.55TB SFF-2 SSD 4k eMLC4 for AIX/Linux	9223	42H	ES8F
1.55TB SFF-2 SSD 4k eMLC4 for IBM i	9223	42H	ES8G
1.9TB Read Intensive SAS 4k SFF-3 SSD for AIX/ Linux	9223	42H	ES8J
1.9TB Read Intensive SAS 4k SFF-3 SSD for IBM i	9223	42H	ES8K
387GB SFF-3 SSD 4k eMLC4 for AIX/Linux	9223	42H	ES8N
387GB SFF-3 SSD 4k eMLC4 for IBM i	9223	42H	ES8P
775GB SFF-3 SSD 4k eMLC4 for AIX/Linux	9223	42H	ES8Q
775GB SFF-3 SSD 4k eMLC4 for IBM i	9223	42H	ES8R
1.55TB SFF-3 SSD 4k eMLC4 for AIX/Linux	9223	42H	ES8V
1.55TB SFF-3 SSD 4k eMLC4 for IBM i	9223	42H	ES8W
931GB Mainstream SAS 4k SFF-2 SSD for AIX/Linux	9223	42H	ES8Y
931GB Mainstream SAS 4k SFF-2 SSD for IBM i	9223	42H	ES8Z
1.86TB Mainstream SAS 4k SFF-3 SSD for AIX/Linux	9223	42H	ES92
1.86TB Mainstream SAS 4k SFF-3 SSD for IBM i	9223	42H	ES93
1.86TB Mainstream SAS 4k SFF-2 SSD for AIX/Linux	9223	42H	ES96
1.86TB Mainstream SAS 4k SFF-2 SSD for IBM i	9223	42H	ES97
S&H - No Charge	9223	42H	ESC0
S&H-b	9223	42H	ESC6
571GB 10K RPM SAS SFF-3 Disk Drive (IBM i)	9223	42H	ESD4
600GB 10K RPM SAS SFF-3 Disk Drive (AIX/Linux)	9223	42H	ESD5
283GB 15K RPM SAS SFF-3 Disk Drive (IBM i)	9223	42H	ESDA
300GB 15K RPM SAS SFF-3 Disk Drive (AIX/Linux)	9223	42H	ESDB
3.72TB Mainstream SAS 4k SFF-3 SSD for AIX/Linux	9223	42H	ESE1
3.72TB Mainstream SAS 4k SFF-3 SSD for IBM i	9223	42H	ESE2
3.72TB Mainstream SAS 4k SFF-2 SSD for AIX/Linux	9223	42H	ESE7
3.72TB Mainstream SAS 4k SFF-2 SSD for IBM i	9223	42H	ESE8

571GB 10K RPM SAS SFF-2 Disk Drive 4K Block - 4224	9223	42H	ESEU
600GB 10K RPM SAS SFF-2 Disk Drive 4K Block - 4096	9223	42H	ESEV
283GB 15K RPM SAS SFF-2 4K Block - 4224 Disk Drive	9223	42H	ESEY
300GB 15K RPM SAS SFF-2 4K Block - 4096 Disk Drive	9223	42H	ESEZ
1.1TB 10K RPM SAS SFF-2 Disk Drive 4K Block - 4224	9223	42H	ESF2
1.2TB 10K RPM SAS SFF-2 Disk Drive 4K Block - 4096	9223	42H	ESF3
571GB 10K RPM SAS SFF-3 Disk Drive 4K Block - 4224	9223	42H	ESF4
600GB 10K RPM SAS SFF-3 Disk Drive 4K Block - 4096	9223	42H	ESF5
1.1TB 10K RPM SAS SFF-3 Disk Drive 4K Block - 4224	9223	42H	ESF8
1.2TB 10K RPM SAS SFF-3 Disk Drive 4K Block - 4096	9223	42H	ESF9
283GB 15K RPM SAS SFF-3 4K Block - 4224 Disk Drive	9223	42H	ESFA
300GB 15K RPM SAS SFF-3 4K Block - 4096 Disk Drive	9223	42H	ESFB
571GB 15K RPM SAS SFF-3 4K Block - 4224 Disk Drive	9223	42H	ESFE
600GB 15K RPM SAS SFF-3 4K Block - 4096 Disk Drive	9223	42H	ESFF
571GB 15K RPM SAS SFF-2 4K Block - 4224 Disk Drive	9223	42H	ESFN
600GB 15K RPM SAS SFF-2 4K Block - 4096 Disk Drive	9223	42H	ESFP
1.7TB 10K RPM SAS SFF-2 Disk Drive 4K Block - 4224	9223	42H	ESFS
1.8TB 10K RPM SAS SFF-2 Disk Drive 4K Block - 4096	9223	42H	ESFT
1.7TB 10K RPM SAS SFF-3 Disk Drive 4K Block - 4224	9223	42H	ESFU
1.8TB 10K RPM SAS SFF-3 Disk Drive 4K Block - 4096	9223	42H	ESFV
387GB Enterprise SAS 5xx SFF-2 SSD for AIX/Linux	9223	42H	ESG5
387GB Enterprise SAS 5xx SFF-3 SSD for AIX/Linux	9223	42H	ESG9
387GB Enterprise SAS 5xx SFF-3 SSD for IBM i	9223	42H	ESGA
387GB Enterprise SAS 4k SFF-2 SSD for AIX/Linux	9223	42H	ESGB
387GB Enterprise SAS 4k SFF-2 SSD for IBM i	9223	42H	ESGC
387GB Enterprise SAS 4k SFF-3 SSD for AIX/Linux	9223	42H	ESGD
387GB Enterprise SAS 4k SFF-3 SSD for IBM i	9223	42H	ESGE
775GB Enterprise SAS 5xx SFF-2 SSD for AIX/Linux	9223	42H	ESGF
775GB Enterprise SAS 5xx SFF-3 SSD for AIX/Linux	9223	42H	ESGH
775GB Enterprise SAS 5xx SFF-3 SSD for IBM i	9223	42H	ESGJ
775GB Enterprise SAS 4k SFF-2 SSD for AIX/Linux	9223	42H	ESGK
775GB Enterprise SAS 4k SFF-2 SSD for IBM i	9223	42H	ESGL
775GB Enterprise SAS 4k SFF-3 SSD for AIX/Linux	9223	42H	ESGM
775GB Enterprise SAS 4k SFF-3 SSD for IBM i	9223	42H	ESGN
1.55TB Enterprise SAS 4k SFF-2 SSD for AIX/Linux	9223	42H	ESGP
1.55TB Enterprise SAS 4k SFF-2 SSD for IBM i	9223	42H	ESGQ
1.55TB Enterprise SAS 4k SFF-3 SSD for AIX/Linux	9223	42H	ESGR
1.55TB Enterprise SAS 4k SFF-3 SSD for IBM i	9223	42H	ESGS
SAP HANA Identifier for 9223-42H	9223	42H	ESH2
Specify AC Power Supply for EXP12SX/EXP24SX Storage Enclosure	9223	42H	ESLA
EXP12SX SAS Storage Enclosure	9223	42H	ESLL
EXP24SX SAS Storage Enclosure	9223	42H	ESLS
283GB 15K RPM SAS SFF-3 4k Block Cached Disk Drive (IBM i)	9223	42H	ESNJ
300GB 15K RPM SAS SFF-3 4k Block Cached Disk Drive (AIX/Linux)	9223	42H	ESNK
283GB 15K RPM SAS SFF-2 4k Block Cached Disk Drive (IBM i)	9223	42H	ESNL
300GB 15K RPM SAS SFF-2 4k Block Cached Disk Drive (AIX/Linux)	9223	42H	ESNM
571GB 15K RPM SAS SFF-3 4k Block Cached Disk Drive (IBM i)	9223	42H	ESNN
600GB 15K RPM SAS SFF-3 4k Block Cached Disk			

Drive (AIX/Linux)	9223	42H	ESNP
571GB 15K RPM SAS SFF-2 4k Block Cached Disk			
Drive (IBM i)	9223	42H	ESNQ
600GB 15K RPM SAS SFF-2 4k Block Cached Disk			
Drive (AIX/Linux)	9223	42H	ESNR
Quantity 150 of #ESNL (283GB 15k SFF-2)	9223	42H	ESPL
Quantity 150 of #ESNM (300GB 15k SFF-2)	9223	42H	ESPM
Quantity 150 of #ESNQ (571GB 15k SFF-2)	9223	42H	ESPQ
Quantity 150 of #ESNR (600GB 15k SFF-2)	9223	42H	ESPR
RDX USB Internal Docking Station for Removable			
Disk Cartridge	9223	42H	EU00
1TB Removable Disk Drive Cartridge	9223	42H	EU01
RDX USB External Docking Station for Removable			
Disk Cartridge	9223	42H	EU04
RDX 320 GB Removable Disk Drive	9223	42H	EU08
Operator Panel LCD Display	9223	42H	EU0B
1.5TB Removable Disk Drive Cartridge	9223	42H	EU15
Cable Ties & Labels	9223	42H	EU19
2TB Removable Disk Drive Cartridge (RDX)	9223	42H	EU2T
RDX USB External Docking Station	9223	42H	EUA4
Standalone USB DVD drive w/cable	9223	42H	EUA5
Core Use HW Feature	9223	42H	EUC6
Core Use HW Feature 10X	9223	42H	EUC7

Business Partner information

If you are a Direct Reseller - System Reseller acquiring products from IBM, you may link directly to Business Partner information for this announcement. A PartnerWorld^(R) ID and password are required (use IBMid).

[BP Attachment for Announcement Letter 118-001](#)

Publications

Power Systems hardware documentation provides clients with the following topical information:

- Licenses, notices, safety, and warranty information
- Planning for the system
- Installing and configuring the system
- Troubleshooting, service, and support
- Installing, configuring, and managing consoles, terminals, and interfaces
- Installing operating systems
- Creating a virtual computing environment
- Enclosures and expansion units
- Glossary

You can access the product documentation at [IBM Knowledge Center](#).

Product documentation is also available on DVD (SK5T-7087).

The following information is shipped with the 9223-42H:

- Power Hardware Information DVD SK5T-7087
- Installing the 9223-42H
- Important Notices
- Warranty Information

- [License Agreement for Machine Code](#)

Hardware documentation such as installation instructions, user's information, and service information is available to download or view at the [IBM Support](#) website.

You can access IBM i documentation at the [IBM i](#) website.

You can access AIX documentation at the [AIX](#) website.

You can access documentation about Linux on IBM systems at the [Linux information for IBM systems](#) website.

The IBM Systems Information Center provides you with a single information center where you can access product documentation for IBM systems hardware, operating systems, and server software. Through a consistent framework, you can efficiently find information and personalize your access. See the IBM Systems Information Center, at [IBM Knowledge Center](#).

The IBM Knowledge Center provides you with a single point of reference where you can access product documentation for IBM systems hardware, operating systems, and server software. Through a consistent framework, you can efficiently find information and personalize your access by going to [IBM Knowledge Center](#) for all your product information needs.

To access the IBM Publications Center Portal, go to the [IBM Publications Center](#) website.

The Publications Center is a worldwide central repository for IBM product publications and marketing material with a catalog of 70,000 items. Extensive search facilities are provided. A large number of publications are available online in various file formats, which can currently be downloaded.

Services

IBM Systems Lab Services

IBM Systems Lab Services can provide on-site professional services to help clients build their SAP HANA solutions using a tailored data center infrastructure strategy.

IBM Systems Lab Services consultants help design and implement flexible virtualization and capacity management to ensure server, storage, and networking resources meet business requirements and SAP HANA KPIs. Lab Services consultants can also advise on best practices for data migration to SAP HANA on Power from a variety of database environments and server platforms.

For more information on Lab Services offerings, clients should contact their IBM representative or go to the [Lab Services Power Systems](#) website.

Global Technology Services

IBM services include business consulting, outsourcing, hosting services, applications, and other technology management.

These services help you learn about, plan, install, manage, or optimize your IT infrastructure to be an on-demand business. They can help you integrate your high-speed networks, storage systems, application servers, wireless protocols, and an array of platforms, middleware, and communications software for IBM and many non-IBM offerings. IBM is your one-stop shop for IT support needs.

For details on available services, contact your IBM representative or go to the [IBM Global Technology Services^{\(R\)}](#) website.

For details on available IBM Business Continuity and Recovery Services, contact your IBM representative or go to the [Resiliency Services](#) website.

Technical information

Specified operating environment

Physical specifications

- Width: 482 mm (18.97 in.)
- Depth: 769.6 mm (30.3 in.)
- Height: 173.3 mm (6.8 in.)
- Weight: 39.9 kg (88 lb)

To assure installability and serviceability in non-IBM industry-standard racks, review the installation planning information for any product-specific installation requirements.

Operating environment

- Temperature: (nonoperating) 5°C - 45°C (41°F - 113°F); recommended temperature (operating) 18°C - 27°C (64°F - 80°F); allowable operating temperature 5°C - 40°C (41°F - 104°F)
- Relative humidity: Nonoperating 8% - 80%; recommended 5.5°C (42°F) dew point to 60% RH and 15°C (59°F) dew point
- Maximum dew point: 21°C (70°F)(allowable operating)
- Operating voltage: 1400 W PSU: 200 - 240 V AC
- Operating frequency: 47/63 Hz
- Maximum power consumption: 1880 watts (maximum)
- Power factor: 0.98
- Thermal output: 6,416 Btu/hour (maximum)
- Power-source loading
 - 1.94 kVa (maximum configuration)
 - Maximum altitude: 3,050 m (10,000 ft)

Note: The maximum measured value is the worst case power consumption expected from a fully populated server under an intensive workload. The maximum measured value also accounts for component tolerance and non-ideal operating conditions. Power consumption and heat load vary greatly by server configuration and utilization. The [IBM Systems Energy Estimator](#) should be used to obtain a heat output estimate based on a specific configuration.

Noise levels and declared A-weighted sound power level

- Rack-mount system: 6.4 bels operating; 5.2 bels idling

See the *Installation Planning Guide* in [IBM Knowledge Center](#) for additional details.

For example, the actual power noise level is impacted by multiple factors, including:

- Enablement of Maximum Performance mode increases fan speed, which increases power noise levels
- Usage of Maximum Performance mode further increases fan speed, which further increases power noise levels
- Using higher wattage PCIe adapters increases fan speed, which increases power noise levels
- Placing multiple servers in a rack increases the total power noise level coming from the rack

- Placing servers in racks with acoustic doors reduces the power noise levels.

EMC conformance classification

This equipment is subject to FCC rules and shall comply with the appropriate FCC rules before final delivery to the buyer or centers of distribution.

- US: FCC Class A
- Europe: CISPR 22 Class A
- Japan: VCCI-A
- Korea: Korean Requirement Class A
- China: People's Republic of China commodity inspection law Class A

Homologation -- Telecom environmental testing (Safety and EMC):

Homologation approval for specific countries has been initiated with the IBM Homologation and Type Approval (HT&A) organization in LaGaude, France. This Power Systems model and applicable features meet the environmental testing requirements of the country telecom and have been designed and tested in compliance with the Full Quality Assurance Approval (FQAA) process as delivered by the British Approval Board for Telecom (BABT), the UK Telecom regulatory authority.

This product is not certified for connection by any means whatsoever to interfaces of public telecommunications networks. Certification may be required by law prior to making any such connection. Contact an IBM representative or reseller for any questions.

Product safety/Country testing/Certification

- UL 60950-1:2007 Underwriters Laboratory, Safety Information
- CSA C22.2 No. 60950-1-07, Canadian Standards Association
- EN60950 European Norm
- IEC 60950, Edition 1, International Electrotechnical Commission, Safety Information
- Nordic deviations to IEC 60950-1 1st Edition

General requirements:

The product is in compliance with IBM Corporate Bulletin C-B 0-2594-000 Statement of Conformity of IBM Product to External Standard (Suppliers Declaration).

Hardware requirements

Power H924 system configuration

The minimum Power H924 initial order must include a processor module, two 16 GB DIMMs, four power supplies and line cords, an operating system indicator, a cover set indicator, and a Language Group Specify. Also, the configuration must include one of the storage options and the network options below:

Storage options:

- For boot from NVMe: One NVMe carrier and one NVMe M.2 Module.
- For boot from local SFF-3 HDD/SDD: One storage backplane and one SFF-3 HDD or SDD.
- For boot from SAN: Internal HDD or SSD and RAID card are not required if feature 0837 (Boot from SAN) is selected. A Fibre Channel adapter must be ordered if feature 0837 is selected.

Network options:

- One PCIe2 4-port 1 Gb Ethernet adapter.

- One of the supported 10 Gb Ethernet adapters

AIX or Linux is the primary operating system. The minimum defined initial order configuration is as follows:

Feature number	Description	Quantity	Notes
EU0B	Operator Panel LCD Display	1	
Processors			
EP1E	8-core typical 3.8 to 4.0 GHz (max) POWER9 Processor	1	
or			
EP1F	10-core typical 3.5 to 3.9 GHz (max) POWER9 Processor	1	
Processor activations			
EP4E	One Processor Core Activation for #EP1E	8	
or			
EP4F	One Processor Core Activation for #EP1F	10	
Memory DIMMs			
EM62	16 GB DDR4 Memory	2	
or			
EM63	32 GB DDR4 Memory	2	
or			
EM64	64 GB DDR4 Memory	2	
or			
EM65	128 GB DDR4 Memory	2	
Storage Backplane			
EJ1C	Twelve SFF-3 Bays/RDX Bay	1	Optional split card EJ1E
or			
EJ1D	Eighteen SFF-3 Bays/RDX Bay/ Dual IOA with Write Cache	1	
or			
EJ1M	Twelve SFF-3 Bays/RDX Bay/2x EXT PT	1	
or			
EC59	PCIe3 NVMe carrier card w/2 M.2 module slots	1	Must order, at a minimum, one of feature ES14
Disk Drive			
ESDB	300 GB 15K RPM SAS SFF-3 Disk Drive (AIX/Linux)	1	
LAN Adapter			
5899	PCIe2 LP 4-port 1GbE Adapter	1	

Feature number	Description	Quantity	Notes
Power supplies/ Power cord			
EB2M	AC Power Supply - 1400 W for Server (200 - 240 V AC)	4	
6458	Power Cord 4.3 m (14 ft), Drawer to IBM PDU (250V/10A)	4	6458 - (default)
9300/97xx	Language Group Specify	1	9300 - (default)
Front Bezel			
EJU3	Front IBM Bezel for 12-Bay BackPlane	1	
or			
EJUG	Front IBM Bezel for 18-Bay BackPlane	1	
or			
EJU4	Front OEM Bezel for 12-Bay BackPlane	1	
or			
EJUH	Front OEM Bezel for 18-Bay BackPlane	1	
Primary operating system			
2146	Primary Operating System Indicator - AIX	1	
or			
2147	Primary Operating System Indicator - Linux	1	

- The racking approach for the initial order must be either a 7014-T00, 7014-T42, 7965-S42, or 7953-94Y. If an additional rack is required for I/O expansion drawers as an MES to an existing system, either a feature 0551, 0553, or ER05 rack must be ordered.
- If NVMe carrier card feature EC59 is selected, no disk units are required to be ordered. If neither feature EC59 nor feature 0837 (SAN boot) is ordered, then at least one disk unit is required to be ordered. If no HDD/SSD/SAN boot (0837) is ordered, then feature EC59 (with at least one of #ES14) is the load source.
- One PCIe2 4-port 1 GbE Adapter (#5899) is defaulted. Options for servers with AIX and Linux as the primary operating system are one of a 10 Gb Ethernet adapter, either feature EC2S, EC2U, EN0H, EN0K, EN0S, EN0U, EN0W, or EN15.

The minimum defined initial order configuration, if no choice is made, when IBM i is the primary operating system, is:

Feature number	Description	Quantity	Notes
EU0B	Operator Panel LCD Display	1	
Processors			
EP1E	8-core typical 3.8 to 4.0 GHz (max) POWER9 Processor	1	
or			
EP1F	10-core typical 3.5 to 3.9 GHz (max) POWER9 Processor	1	

Feature number	Description	Quantity	Notes
Processor activations			
EP4E	One Processor Core Activation for #EP1E	8	
or			
EP4F	One Processor Core Activation for #EP1F	10	
Memory DIMMs			
EM62	16 GB DDR4 Memory	2	
or			
EM63	32 GB DDR4 Memory	2	
or			
EM64	64 GB DDR4 Memory	2	
or			
EM65	128 GB DDR4 Memory	2	
Storage Backplane			
EJ1C	Twelve SFF-3 Bays/RDX Bay	1	Optional split card EJ1E
or			
EJ1D	Eighteen SFF-3 Bays/RDX Bay/ Dual IOA with Write Cache	1	
or			
EJ1M	Twelve SFF-3 Bays/RDX Bay/2x EXT PT	1	
Disk Drive			
ESNJ	283 GB 15K RPM SAS SFF-3 4k Block Cached Disk Drive (IBM i)	2	One system data protection specify code required
LAN Adapter			
5899	PCIe2 LP 4-port 1 GbE Adapter	1	
or			
EN15	PCIe3 4-port 10 GbE SR Adapter	1	
or			
EC2S	PCIe3 2-Port 10 Gb NIC&ROCE SR/Cu Adapter	1	
or			
EC2U	PCIe3 2-Port 25/10 Gb NIC&ROCE SR/ Cu Adapter	1	
Power supplies/ Power cord			
EB2M	AC Power Supply - 1400 W for Server (200 - 240 V AC)	4	
6458	Power Cord 4.3 m (14 ft), Drawer	4	6458 - (default)

Feature number	Description	Quantity	Notes
	to IBM PDU (250V/10A)		
9300/97xx	Language Group Specify	1	9300 - (default)
Front Bezel			
EJU3	Front IBM Bezel for 12-Bay BackPlane	1	
or			
EJUG	Front IBM Bezel for 18-Bay BackPlane	1	
Primary operating system			
2145	Primary Operating System Indicator - IBM i	1	

- The racking approach for the initial order must be either a 7014-T00, 7014-T42, 7965-S42, or 7953-94Y. If an additional rack is required for I/O expansion drawers as an MES to an existing system, either a feature 0551, 0553, or ER05 rack must be ordered.
- IBM i operating system performance: Clients with write-sensitive disk/HDD workloads should upgrade from the feature EJ1C/EJ1E base storage backplane to the feature EJ1M/EJ1D expanded function storage backplanes to gain the performance advantage of write cache.

Hardware Management Console (HMC) machine code

An HMC is required to manage the Power H924 server implementing partitioning. Multiple POWER7^(R), POWER8, and POWER9 processor-based servers can be supported by a single HMC. Planned HMC hardware and software support:

- X86 based - 7042-CR7, 7042-CR8, 7042-CR9
 - vHMC x86
- POWER8 based Open Power: 7063-CR1
 - vHMC PowerVM based LPAR

If you are attaching an HMC to a new server or adding function to an existing server that requires a firmware update, the HMC machine code may need to be updated because HMC code must always be equal to or higher than the managed server's firmware. Access to firmware and machine code updates is conditioned on entitlement and license validation in accordance with IBM policy and practice. IBM may verify entitlement through customer number, serial number, electronic restrictions, or any other means or methods employed by IBM at its discretion.

To determine the HMC machine code level required for the firmware level on any server, go to the following web page to access the Fix Level Recommendation Tool (FLRT) on or after the planned availability date for this product. FLRT will identify the correct HMC machine code for the selected system firmware level; see the [IBM Support: Fix Central](#) website.

If a single HMC is attached to multiple servers, the HMC machine code level must be updated to be at or higher than the server with the most recent firmware level. All prior levels of server firmware are supported with the latest HMC machine code level.

The HMC code latest level contains the following:

- Support for managing Power H924 system.
- Support for the new HMC model 7063-CR1.
- Support for PowerVM functions such as the new HMC GUI interface for VIOS management.

- GUI for HMC's Performance and Capacity Monitoring function.
- An HMC command to initiate a remote restart operation. This removes the requirement of VMControl for the PowerVM Remote Restart function.
- For PowerVM GUI functions, VIOS is recommended.

For clients installing systems higher than the EIA 29 position (location of the rail that supports the rack-mounted server) in any IBM or non-IBM rack, acquire approved tools outlined in the server specifications section at [IBM Knowledge Center](#). In situations where IBM service is required and the recommended tools are not available, there could be delays in repair actions.

Software requirements

The Linux operating systems LPAR, in nonproduction implementation, (see statement of direction on planned support for same in production mode):

- SUSE Linux Enterprise Server 11 Service Pack 4, or later
- SUSE Linux Enterprise Server 12 Service Pack 3, or later
- SUSE Linux Enterprise Server for SAP with SUSE Linux Enterprise Server 11 Service Pack 4
- Red Hat Enterprise Linux 7 for Power LE, version 7.4, or later
- Red Hat Enterprise Linux for SAP with Red Hat Enterprise Linux 7 for Power LE, version 7.4, or later

If installing the AIX operating system LPAR with any I/O configuration (one of these):

- AIX Version 7.2 with the 7200-02 Technology Level and Service Pack 7200-02-02-1810, or later
- AIX Version 7.1 with the 7100-05 Technology Level and Service Pack 7100-05-02-1810, or later
- AIX Version 6.1 with the 6100-09 Technology Level and Service Pack 6100-09-11-1810, or later (AIX 6.1 service extension required)
- AIX Version 7.2 with the 7200-01 Technology Level and Service Pack 7200-01-04-1806, or later (planned availability May 4, 2018)
- AIX Version 7.2 with the 7200-00 Technology Level and Service Pack 7200-00-06-1806, or later (planned availability May 4, 2018)
- AIX Version 7.1 with the 7100-04 Technology Level and Service pack 7100-04-06-1806, or later (planned availability May 4, 2018)

If installing the AIX operating system Virtual I/O only LPAR (one of these):

- AIX Version 7.2 with the 7200-02 Technology Level and Service Pack 7200-02-01-1732, or later
- AIX Version 7.2 with the 7200-01 Technology Level and Service Pack 7200-01-01-1642, or later
- AIX Version 7.2 with the 7200-00 Technology Level and Service Pack 7200-00-01-1543, or later
- AIX Version 7.1 with the 7100-05 Technology Level and Service Pack 7100-05-01-1731, or later
- AIX Version 7.1 with the 7100-04 Technology Level and Service Pack 7100-04-01-1543, or later
- AIX Version 6.1 with the 6100-09 Technology Level and Service Pack 6100-09-06-1543, or later (AIX 6.1 service extension required)

If installing IBM i, the IBM i operating system levels supported are:

- IBM i 7.3 TR4
- IBM i 7.2 TR8

If installing VIOS:

- VIOS 2.2.6.21, or later

Limitations

- Integrated system port is not supported under AIX or Linux when the HMC ports are connected to an HMC. Either the HMC ports or the integrated system ports can be used, but not both. The FSP2 USB 2.0 port is used for communication to a UPS.
- The integrated system port is supported for modem and TTY terminal connections by AIX or Linux. Any other application using serial ports requires a serial port adapter to be installed in a PCI slot. The integrated system port does not support HACMP™ configurations.

Boot requirements

- If IBM i (#2145) is selected as the primary operating system and SAN boot is not selected (#0837), one of the following Load Source specify codes must be specified.
- If IBM i (#2145) is selected and the load source disk unit is not in the CEC (system unit), one of the following specify codes must also be selected:
 - #0719 Load Source Not in CEC and are to be placed in I/O drawers or in external SAN-attached disk
 - #EHR2 Load Source Specifies DASD are placed in an EXP24SX SFF Gen2 bay Drawer (#ESLS or #ELLS)
 - #0837 SAN Operating System Load Source Specify
- If IBM i (#2145) is selected, one of the following system console specify codes must be selected:
 - #5550 - System Console on HMC
 - #5557 - System Console - Internal LAN

Planning information

Cable orders

No additional cables are required.

Security, auditability, and control

This product uses the security and auditability features of host hardware and application software.

The customer is responsible for evaluation, selection, and implementation of security features, administrative procedures, and appropriate controls in application systems and communications facilities.

IBM Systems Lab Services

For details on available services, contact your IBM representative or go to the [IBM Systems Lab Services](#) website.

IBM Electronic Services

IBM has transformed its delivery of hardware and software support services to help you achieve higher system availability. Electronic Services is a web-enabled solution that offers an exclusive, no-additional-charge enhancement to the service and support available for IBM servers. These services are designed to provide the opportunity for greater system availability with faster problem resolution and preemptive monitoring. Electronic Services comprises two separate, but complementary, elements: Electronic Services news page and Electronic Services Agent.

The Electronic Services news page is a single internet entry point that replaces the multiple entry points traditionally used to access IBM Internet services and support. The news page enables you to gain easier access to IBM resources for assistance in resolving technical problems.

The Electronic Service Agent™ is no-additional-charge software that resides on your server. It monitors events and transmits system inventory information to IBM on a periodic, client-defined timetable. The Electronic Service Agent automatically reports hardware problems to IBM. Early knowledge about potential problems enables IBM to deliver proactive service that may result in higher system availability and performance. In addition, information collected through the Service Agent is made available to IBM service support representatives when they help answer your questions or diagnose problems. Installation and use of IBM Electronic Service Agent for problem reporting enables IBM to provide better support and service for your IBM server.

To learn how Electronic Services can work for you, go to the [IBM Electronic Support](#) website.

Terms and conditions

Volume orders

Contact your IBM representative.

IBM Global Financing

Yes

Products - terms and conditions

Warranty period

Warranty and additional coverage options:	Coverage summary ¹ :
Warranty Period:	3 years
Service Level:	IBM On-Site Limited, 9x5 Next Business Day
Service Upgrade Options :	
Warranty Service Upgrade	IBM On-Site Repair, 9x5 Same Day ² and 24x7 Same Day options
Maintenance Services (Post-Warranty):	IBM On-Site Repair, Next Business Day and Same Day options
IBM Hardware Maintenance Services - committed maintenance ³ :	Y

¹ See complete coverage details below.

² Offered in US and EMEA only.

³ Not offered in the US.

Three years.

To obtain copies of the IBM Statement of Limited Warranty, contact your reseller or IBM.

An IBM part or feature installed during the initial installation of an IBM machine is subject to the full warranty period specified by IBM. An IBM part or feature that replaces a previously installed part or feature assumes the remainder of the warranty period for the replaced part or feature. An IBM part or feature added to a machine without replacing a previously installed part or feature is subject to a full

warranty. Unless specified otherwise, the warranty period, type of warranty service, and service level of a part or feature are the same as those for the machine in which it is installed.

Any IBM Mainstream devices (previously called *read intensive device*) identified in this document have a maximum number of write cycles. IBM Mainstream device failures will be replaced during standard warranty and maintenance period for devices that have not reached the maximum number of write cycles. Devices that reach this limit may fail to operate according to specifications and must be replaced at the client's expense. Individual service life may vary and can be monitored using an operating system command.

The IBM warranty covers feature number EB4Z. For warranty terms associated with feature number EB3Z and the Lift tool based on GenieLift GL-8, see the separate warranty terms provided by Genie found in the Genie Operator's Manual at the [Genie](#) website.

For clients installing systems higher than the EIA 29 position (location of the rail that supports the rack-mounted server) in any IBM or non-IBM rack, acquire approved tools outlined in the server specifications section at [IBM Knowledge Center](#). In situations where IBM service is required and the recommended tools are not available, there could be delays in repair actions.

Warranty services

If required, IBM provides repair or exchange service depending on the types of warranty service specified for the machine. IBM will attempt to resolve your problem over the telephone, or electronically through an IBM website. Certain machines contain remote support capabilities for direct problem reporting, remote problem determination, and resolution with IBM. You must follow the problem determination and resolution procedures that IBM specifies. Following problem determination, if IBM determines on-site service is required, scheduling of service will depend upon the time of your call, machine technology and redundancy, and availability of parts. If applicable to your product, parts considered Customer Replaceable Units (CRUs) will be provided as part of the machine's standard warranty service.

Service levels are response-time objectives and are not guaranteed. The specified level of warranty service may not be available in all worldwide locations. Additional charges may apply outside IBM's normal service area. Contact your local IBM representative or your reseller for country-specific and location-specific information.

CRU Service

IBM provides replacement CRUs to you for you to install. CRU information and replacement instructions are shipped with your machine and are available from IBM upon your request. CRUs are designated as being either a Tier 1 (mandatory) or a Tier 2 (optional) CRU.

Tier 1 (mandatory) CRU

Installation of Tier 1 CRUs, as specified in this announcement, is your responsibility. If IBM installs a Tier 1 CRU at your request, you will be charged for the installation.

The following parts have been designated as Tier 1 CRUs:

- DASD SFF Drive
- DASD SSD Drive
- RDX Drive
- Enclosure
- Power Cable
- NVMe M.2 Carrier card and Flash Modules
- SAS Card
- Op Panel - Base

- Op Panel - LCD
- Memory DIMM
- All PCI Adapters
- FAN
- Upper Fan cable
- TPM Card
- Power Supplies
- Service Processor Card/FSP
- TOD Battery
- Air Baffle
- Bezel
- SAS Cable
- Front Heatsink
- Service Cover
- DASD Backplane Power Cable
- DASD Backplane Signal Cable

Tier 2 (optional) CRU

You may install a Tier 2 CRU yourself or request IBM to install it, at no additional charge.

Based upon availability, CRUs will be shipped for next-business-day (NBD) delivery. IBM specifies, in the materials shipped with a replacement CRU, whether a defective CRU must be returned to IBM. When return is required, return instructions and a container are shipped with the replacement CRU. You may be charged for the replacement CRU if IBM does not receive the defective CRU within 15 days of your receipt of the replacement.

CRU and On-site Service

At IBM's discretion, you will receive specified CRU service, or IBM will repair the failing machine at your location and verify its operation. You must provide a suitable working area to allow disassembly and reassembly of the IBM machine. The area must be clean, well-lit, and suitable for the purpose.

Service level is:

- 9 hours per day, Monday through Friday, excluding holidays, next-business-day response. Calls must be received by 3:00 PM local time in order to qualify for next-business-day response.

Warranty service

IBM is now shipping machines with selected non-IBM parts that contain an IBM field replaceable unit (FRU) part number label. These parts are to be serviced during the IBM machine warranty period. IBM is covering the service on these selected non-IBM parts as an accommodation to their customers, and normal warranty service procedures for the IBM machine apply.

International Warranty Service

International Warranty Service allows you to relocate any machine that is eligible for International Warranty Service and receive continued warranty service in any country where the IBM machine is serviced. If you move your machine to a different country, you are required to report the machine information to your Business Partner or IBM representative.

The warranty service type and the service level provided in the servicing country may be different from that provided in the country in which the machine was purchased. Warranty service will be provided with the prevailing warranty service

type and service level available for the eligible machine type in the servicing country, and the warranty period observed will be that of the country in which the machine was purchased.

The following types of information can be found on the [International Warranty Service](#) website

- Machine warranty entitlement and eligibility
- Directory of contacts by country with technical support contact information
- Announcement Letters

Warranty service upgrades

During the warranty period, warranty service upgrades provide an enhanced level of On-site Service for an additional charge. Service levels are response-time objectives and are not guaranteed. See the [Warranty services](#) section for additional details.

IBM will attempt to resolve your problem over the telephone or electronically by access to an IBM website. Certain machines contain remote support capabilities for direct problem reporting, remote problem determination, and resolution with IBM. You must follow the problem determination and resolution procedures that IBM specifies. Following problem determination, if IBM determines on-site service is required, scheduling of service will depend upon the time of your call, machine technology and redundancy, and availability of parts.

Maintenance service options

CRU and On-site Service

At IBM's discretion, you will receive CRU service or IBM will repair the failing machine at your location and verify its operation. You must provide a suitable working area to allow disassembly and reassembly of the IBM machine. The area must be clean, well-lit, and suitable for the purpose. The following on-site response-time objectives are available as warranty service upgrades for your machine. Available offerings are:

- On-Site Repair, Monday through Friday (excluding holidays), 8 AM to 5 PM, 4-hour on-site response objective. Response times are objectives and are not guaranteed
- On-Site Repair, 7 days a week, 24hrs/day.
- On-Site Repair, 7 days a week, 24hrs/day, 2-hour response objective. Response times are objectives and are not guaranteed.

Customer Replaceable Units (CRUs) may be provided as part of the machine's standard warranty CRU Service except that you may install a CRU yourself or request IBM installation, at no additional charge, under the CRU and On-site Service level specified above. For additional information on the CRU Service, see the warranty information.

Maintenance services

If required, IBM provides repair or exchange service depending on the types of maintenance service specified for the machine. IBM will attempt to resolve your problem over the telephone or electronically, through an IBM website. Certain machines contain remote support capabilities for direct problem reporting, remote problem determination, and resolution with IBM. You must follow the problem determination and resolution procedures that IBM specifies. Following problem determination, if IBM determines on-site service is required, scheduling of service will depend upon the time of your call, machine technology and redundancy, and availability of parts. Service levels are response-time objectives and are not guaranteed. The specified level of maintenance service may not be available in all worldwide locations. Additional charges may apply outside IBM's normal service area. Contact your local IBM representative or your reseller for country-specific and location-specific information.

The following service selections are available as maintenance options, at additional cost, for your machine type.

- On-Site Repair, Monday through Friday (excluding holidays), 8 AM to 5 PM, next business day.
- On-Site Repair, Monday through Friday (excluding holidays), 8 AM to 5 PM, 4-hour response objective. Response times are objectives and are not guaranteed.
- On-Site Repair, 7 days a week, 24hrs/day.
- On-Site Repair, 7 days a week, 24hrs/day, 2-hour response objective. Response times are objectives and are not guaranteed.

On-site Service

IBM will repair the failing machine at your location and verify its operation. You must provide a suitable working area to allow disassembly and reassembly of the IBM machine. The area must be clean, well-lit, and suitable for the purpose.

Customer Replaceable Unit (CRU) Service

If your problem can be resolved with a CRU (for example, keyboard, mouse, speaker, memory, or hard disk drive), and depending upon the maintenance service offerings in your geography, IBM will ship the replacement CRU to you for you to install. CRU information and replacement instructions are shipped with your machine and are available from IBM upon your request.

CRUs will be shipped based upon availability. IBM specifies, in the materials shipped with a replacement CRU, whether a defective CRU must be returned to IBM. When return is required, 1) return instructions and a container are shipped with the replacement CRU, and 2) you may be charged for the replacement CRU if IBM does not receive the defective CRU within 15 days of your receipt of the replacement.

CRUs are designated as being either a Tier 1 (mandatory) or a Tier 2 (optional) CRU.

Tier 1 (mandatory) CRUs: Installation of Tier 1 CRUs, as specified in this announcement, is your responsibility. If IBM installs a Tier 1 CRU at your request, you will be charged for the installation.

For machines with On-site Same-day Response Service, IBM will replace a Tier 1 CRU part at your request, at no additional charge.

The following parts have been designated as Tier 1 CRUs:

- DASD SFF Drive
- DASD SSD Drive
- RDX Drive
- Enclosure
- Power Cable
- NVMe M.2 Carrier card and Flash Modules
- SAS Card
- Op Panel - Base
- Op Panel - LCD
- Memory DIMM
- All PCI Adapters
- FAN
- Upper Fan cable
- TPM Card
- Power Supplies
- Service Processor Card/FSP
- TOD Battery

- Air Baffle
- Bezel
- SAS Cable Front
- Heatsink
- Service Cover
- DASD Backplane Power Cable
- DASD Backplane Signal Cable

Tier 2 (optional) CRUs: You may install a Tier 2 CRU yourself or request IBM to install it, at no additional charge.

Non-IBM parts service

Under certain conditions, IBM provides services for selected non-IBM parts at no additional charge for machines that are covered under warranty service upgrades or maintenance services.

This service includes hardware problem determination (PD) on the non-IBM parts (for example, adapter cards, PCMCIA cards, disk drives, memory) installed within IBM machines and provides the labor to replace the failing parts at no additional charge.

If IBM has a Technical Service Agreement with the manufacturer of the failing part, or if the failing part is an accommodations part (a part with an IBM FRU label), IBM may also source and replace the failing part at no additional charge. For all other non-IBM parts, customers are responsible for sourcing the parts. Installation labor is provided at no additional charge, if the machine is covered under a warranty service upgrade or a maintenance service.

Usage plan machine

No

IBM hourly service rate classification

Two

When a type of service involves the exchange of a machine part, the replacement may not be new, but will be in good working order.

General terms and conditions

Field-installable features

Yes

Model conversions

No

Machine installation

Customer setup. Customers are responsible for installation according to the instructions IBM provides with the machine.

Graduated program license charges apply

Yes

The applicable processor group is: Small

Licensed Machine Code

IBM Machine Code is licensed for use by a customer on the IBM machine for which it was provided by IBM under the terms and conditions of the IBM License Agreement for Machine Code, to enable the machine to function in accordance with its specifications, and only for the capacity authorized by IBM and acquired by the customer. You can obtain the agreement by contacting your IBM representative. It can also be found on the [License Agreement for Machine Code and Licensed Internal Code](#) website.

Machine using LMC Type Model 9223-42H

Access to Machine Code updates is conditioned on entitlement and license validation in accordance with IBM policy and practice. IBM may verify entitlement through customer number, serial number, electronic restrictions, or any other means or methods employed by IBM in its discretion.

If the machine does not function as warranted and your problem can be resolved through your application of downloadable Machine Code, you are responsible for downloading and installing these designated Machine Code changes as IBM specifies. If you would prefer, you may request IBM to install downloadable Machine Code changes; however, you may be charged for that service.

Machine Code License Acceptance Requirement

B.) Acceptance-By-Use Machine: No, the Machine Code license requires signed acceptance by the machine's end user directly with IBM, applicable to orders for a new machine, machine type conversion MES, and to machines transferred to another user.

Educational allowance

A reduced charge is available to qualified education customers. The educational allowance may not be added to any other discount or allowance.

The educational allowance is 8% for the products in this announcement.

Prices

For additional information and current prices, contact your local IBM representative.

The following are newly announced features on the specific models of the IBM Power Systems 9223 machine type:

Description	Model number	Feature number	Purchase price	Minimum Monthly Charge	Initial/ Monthly MES/ Both/ Support	RP CSU MES
IBM Power System H924	42H					Yes
One CSC Billing Unit	42H	0010			Both	Yes No
Ten CSC Billing Units	42H	0011			Both	Yes No
Mirrored System Disk Level, Sp	42H	0040			Both	Yes No
Device Parity Protection All	42H	0041			Both	Yes No
Mirrored System Bus Level	42H	0043			Both	Yes No
Device Parity RAID 6 All	42H	0047			Both	Yes No

RISC to RISC Data Migration	42H	0205	Initial	N/A	No
AIX Partition Specify	42H	0265	Both	Yes	No
Linux Partition Specify	42H	0266	Both	Yes	No
IBM i Partition Specify	42H	0267	Both	Yes	No
Specify Custom Data Protection	42H	0296	Both	Yes	No
Mirrored Level System Specify	42H	0308	Both	Yes	No
RAID Hot Spare Specify	42H	0347	Both	Yes	No
V.24/EIA232 6.1m (20 Ft) PCI C	42H	0348	Both	Yes	No
V.35 6.1m (20 Ft) PCI Cable	42H	0353	Both	Yes	No
X.21 6.1m (20 Ft) PCI Cable	42H	0359	Both	Yes	No
Customer Specified Placement	42H	0456	Initial	N/A	No
19 inch, 1.8 meter high rack	42H	0551	MES	Yes	No
19 inch, 2.0 meter high rack	42H	0553	MES	Yes	No
Rack Filler Panel Kit	42H	0599	Both	Yes	No
Load Source Not in CEC	42H	0719	Both	Yes	No
SAN Load Source Specify	42H	0837	Both	Yes	No
US TAA Compliance Indicator	42H	0983	Both	Yes	No
Asm in USA manufacturing plant	42H	0984	Both	Yes	No
Modem Cable US/Canada and GU	42H	1025	Both	Yes	No
USB 500 GB Removable Disk Dr	42H	1107	Both	Yes	No
Custom Serv. Specify, Roch	42H	1140	Both	Yes	No
Quantity 150 of #1964	42H	1818	Both	Yes	No
Quantity 150 of #1953	42H	1929	Both	Yes	No
300GB 15k RPM SAS SFF-2 Disk	42H	1953	Both	Yes	No
600GB 10k RPM SAS SFF-2 Disk	42H	1964	Both	Yes	No
Primary OS - IBM i	42H	2145	Both	Yes	No
Primary OS AIX	42H	2146	Both	Yes	No
Primary OS Linux	42H	2147	Both	Yes	No
Factory Deconfiguration of 1 c	42H	2319	Initial	N/A	No
LC-SC 50 Micron Fiber Conv Cab	42H	2456	Both	Yes	No
LC-SC 62.5 Mic.Fib.Conv.Cable	42H	2459	Both	Yes	No
Asynch.Termin/Print.Cbl EIA232	42H	2934	Both	Yes	No
Asynchronous Cable EIA 232/V	42H	2936	Both	Yes	No
Ser to Ser Port Cab Draw/Draw	42H	3124	Both	Yes	No
Serial to Se.Port Cbl Rack 8M					

Widescreen LCD Monitor	42H	3125	Both	Yes	No
0.3M Serial Prt Converter Cbl	42H	3632	Support	Yes	No
Serial Port Null Mod Cab 3.7M	42H	3925	Both	Yes	No
Ser.Port Null Modem Cable,10M	42H	3927	Both	Yes	No
System Serial Port Converter C	42H	3928	Both	Yes	No
6Foot Extend.Cbl for Displays	42H	3930	Both	Yes	No
Extender Cable USB Keybo 1.8M	42H	4242	Support	Yes	No
VGA to DVI Connection Converte	42H	4256	Both	Yes	No
Rack Integration Services: BP	42H	4276	Both	Yes	No
Rack Integration Services	42H	4648	Initial	N/A	No
Rack Integration Services	42H	4649	Initial	N/A	No
One and only one rack indicator feature is required on all orders (#4650 to #4666). No Factory Integration Ind.					
Rack Indicator, Rack 1	42H	4650	Initial	N/A	No
Rack Indicator, Rack 2	42H	4651	Initial	N/A	No
Rack Indicator, Rack 3	42H	4652	Initial	N/A	No
Rack Indicator, Rack 4	42H	4653	Initial	N/A	No
Rack Indicator, Rack 5	42H	4654	Initial	N/A	No
Rack Indicator, Rack 6	42H	4655	Initial	N/A	No
Rack Indicator, Rack 7	42H	4656	Initial	N/A	No
Rack Indicator, Rack 8	42H	4657	Initial	N/A	No
Rack Indicator, Rack 9	42H	4658	Initial	N/A	No
Rack Indicator, Rack 10	42H	4659	Initial	N/A	No
Rack Indicator, Rack 11	42H	4660	Initial	N/A	No
Rack Indicator, Rack 12	42H	4661	Initial	N/A	No
Rack Indicator, Rack 13	42H	4662	Initial	N/A	No
Rack Indicator, Rack 14	42H	4663	Initial	N/A	No
Rack Indicator, Rack 15	42H	4664	Initial	N/A	No
Rack Indicator, Rack 16	42H	4665	Initial	N/A	No
Power Active Memory Expansion	42H	4666	Initial	N/A	No
One Processor of 5250 Enterpri	42H	4794	Both	Yes	No
Full 5250 Enterprise Enablemen	42H	4970	Both	Yes	No
Software Preload Required	42H	4974	Both	Yes	No
PowerVM Enterprise Edition	42H	5000	Initial	N/A	No
Sys Console On HMC	42H	5228	Both	Yes	No
Sys Console-Ethernet LAN	42H	5550	Both	Yes	No
PCIe2 8Gb 4-port Fibre Channel	42H	5557	Initial	N/A	No
8 Gigabit PCI Express Dual Por	42H	5729	Both	Yes	No

POWER GXT145 PCI Express Graph	42H	5735	Both	Yes	No
4 Port Async EIA 232 PCIe Adap	42H	5748	Both	Yes	No
PCIe2 4-port 1GbE Adapter	42H	5785	Both	Yes	No
Opt Front Door for 1.8m Rack	42H	5899	Both	Yes	No
Opt Front Door for 2.0m Rack	42H	6068	MES	Yes	No
1.8m Rack Acoustic Doors	42H	6069	MES	Yes	No
2.0m Rack Acoustic Doors	42H	6248	MES	Yes	No
1.8m Rack Trim Kit	42H	6249	MES	Yes	No
2.0m Rack Trim Kit	42H	6263	MES	Yes	No
Pwr Crd 4.3m 14ft to IBM PDU	42H	6272	MES	Yes	No
Pwr Crd (14FT), Drwr - OEM PDU	42H	6458	Both	Yes	No
Pwr Crd 4.3m 14ft wall OEM PDU	42H	6460	Both	Yes	No
Pwr Crd 4.3m 14ft wall 125V/15A	42H	6469	Both	Yes	No
Pwr Crd 1.8m 6ft wall OEM PDU	42H	6470	Both	Yes	No
Pwr Crd 2.7m 9ft wall OEM PDU	42H	6471	Both	Yes	No
Pwr Crd 2.7m 9ft wall OEM PDU	42H	6472	Both	Yes	No
Pwr Crd 2.7m 9ft wall OEM PDU	42H	6473	Both	Yes	No
Pwr Crd 2.7m 9ft wall OEM PDU	42H	6474	Both	Yes	No
Pwr Crd 2.7m 9ft wall OEM PDU	42H	6475	Both	Yes	No
Pwr Crd 2.7m 9ft wall OEM PDU	42H	6476	Both	Yes	No
Pwr Crd 2.7m 9ft wall OEM PDU	42H	6477	Both	Yes	No
Pwr Crd 2.7m 9ft wall OEM PDU	42H	6478	Both	Yes	No
Pwr Crd 2.7m 9ft wall OEM PDU	42H	6488	Both	Yes	No
4.3m (14 Ft) 3PH/24A Power Cor	42H	6489	MES	Yes	No
4.3m (14 Ft) 1PH/63A Pwr Cord	42H	6491	MES	Yes	No
4.3m (14 Ft) 1PH/48 60A Pwr Co	42H	6492	MES	Yes	No
Pwr Crd 2.7m 9ft wall OEM PDU	42H	6493	Both	Yes	No
Pwr Crd 2.7m 9ft wall OEM PDU	42H	6494	Both	Yes	No
Pwr Crd 2.7m 9ft wall 250V,10A	42H	6496	Both	Yes	No
Power Cable Drawer to IBM PD	42H	6577	Both	Yes	No
Optional Rack Security Kit	42H	6580	MES	Yes	No
Pwr Crd 2.7m 9ft wall 125V,15A	42H	6651	Both	Yes	No
4.3m 3PH/16A Power Cord	42H	6653	MES	Yes	No
4.3m 1PH/24-30A Pwr Cord	42H	6654	MES	Yes	No
4.3m 14Ft 1PH/24 30A WR Pwr	42H	6655	MES	Yes	No
4.3m 14Ft 1PH/24A Power Cord	42H	6656	MES	Yes	No
4.3m 14Ft 1PH/32A Power Cord	42H	6657	MES	Yes	No
4.3m 14Ft 1PH/24A Pwr Cd Kor					

	42H	6658	MES	Yes	No
Pwr.Cord(9ft),To wall/OEM PDU	42H	6659	Both	Yes	No
Pwr Crd 14ft 4.3m wall/OEM PDU	42H	6660	Both	Yes	No
Pwr Crd 2.8m 9.2ft PDU	42H	6665	Both	Yes	No
4.3m 14Ft 3PH/32A Pwr Cd Aus	42H	6667	MES	Yes	No
Pwr Crd 4.3M, Drwr - OEM PDU	42H	6669	Both	Yes	No
Pwr Crd 2.7m, Drwr - IBM PDU	42H	6671	Both	Yes	No
Pwr Crd 2M, Drwr - IBM PDU	42H	6672	Both	Yes	No
Pwr Crd 2.7m 9ft wall OEM PDU	42H	6680	Both	Yes	No
IIntelligent PDU+ 1 EIA Unit	42H	7109	MES	Yes	No
Environmental Monitoring Probe	42H	7118	Both	Yes	No
Power Distribution Unit	42H	7188	MES	Yes	No
PowDistribUnit(US)Fixed PowCrd	42H	7196	Both	Yes	No
Eth Cbl 15M HW Management	42H	7802	Both	Yes	No
Linux Software Preinstall	42H	8143	Initial	N/A	No
Linux Software Preinstall BP	42H	8144	Initial	N/A	No
USB Mouse	42H	8845	Support	Yes	No
Order Routing Indicator System	42H	9169	Initial	N/A	No
Language Group Spcf-US Eng	42H	9300	Initial	N/A	No
New AIX License Core Counter	42H	9440	Initial	N/A	No
New IBM i Lic Core Counter	42H	9441	Initial	N/A	No
New Red Hat Lic Core Counter	42H	9442	Initial	N/A	No
New SUSE Lic Core Counter	42H	9443	Initial	N/A	No
Other AIX Lic Core Counter	42H	9444	Initial	N/A	No
Other Linux Lic Core Counter	42H	9445	Initial	N/A	No
3rd Party Linux Lic Core Cnt	42H	9446	Initial	N/A	No
VIOS Core Counter	42H	9447	Initial	N/A	No
Other License Core Counter	42H	9449	Initial	N/A	No
Ubuntu Linux License Core Cntr	42H	9450	Initial	N/A	No
Month Indicator	42H	9461	Initial	N/A	No
Day Indicator	42H	9462	Initial	N/A	No
Hour Indicator	42H	9463	Initial	N/A	No
Minute Indicator	42H	9464	Initial	N/A	No
Qty Indicator	42H	9465	Initial	N/A	No
Countable Member Indicator	42H	9466	Initial	N/A	No
Language Group Spcf-Dutch	42H	9700	Initial	N/A	No
Language Group Spcf-French	42H	9703	Initial	N/A	No
Language Group Spcf-German					

Language Group Spcf-Polish	42H	9704	Initial	N/A	No
Lang Group Specify - Norwegian	42H	9705	Initial	N/A	No
Lang.Group Spcf-Portuguese	42H	9706	Initial	N/A	No
Language Group Spcf-Spanish	42H	9707	Initial	N/A	No
Language Group Spcf-Italian	42H	9708	Initial	N/A	No
Langua Gr Speci Canadian Frenc	42H	9711	Initial	N/A	No
Language Group Spcf-Japanese	42H	9712	Initial	N/A	No
Language Group Specify Tr Chin	42H	9714	Initial	N/A	No
Language Group Spcf-Korean	42H	9715	Initial	N/A	No
Language Group Spcf-Turkish	42H	9716	Initial	N/A	No
Language Group Spcf-Hungarian	42H	9718	Initial	N/A	No
Language Group Spcf-Slovakian	42H	9719	Initial	N/A	No
Language Group Spcf-Russian	42H	9720	Initial	N/A	No
Lang Group Spcf Simpl Chinese	42H	9721	Initial	N/A	No
Language Group Spcf-Czech	42H	9722	Initial	N/A	No
Language Group Spcf-Romanian	42H	9724	Initial	N/A	No
Lang Group Specify - Croatian	42H	9725	Initial	N/A	No
Language Group Spcf-Slovenian	42H	9726	Initial	N/A	No
Lang Group Specify - Braz Port	42H	9727	Initial	N/A	No
Lang Group Specify - Thai	42H	9728	Initial	N/A	No
	42H	9729	Initial	N/A	No
10m QSFP+ MTP Optical Cable	42H	EB2J	Both	Yes	No
30m QSFP+ MTP Optical Cable	42H	EB2K	Both	Yes	No
Power Supply 1400W 200-240 VAC	42H	EB2M	Both	Yes	No
Lift tool GenieLift GL-8	42H	EB3Z	Both	Yes	No
10Gb Optical TransceiverSFP+	42H	EB46	Both	Yes	No
25Gb Opt Transceiver SFP28	42H	EB47	Both	Yes	No
0.5 SFP/25GbE CU Cable	42H	EB4J	Both	Yes	No
1.0 SFP/25GbE CU Cable	42H	EB4K	Both	Yes	No
1.5 SFP/25GbE CU Cable	42H	EB4L	Both	Yes	No
2.0 SFP/25GbE CU Cable	42H	EB4M	Both	Yes	No
2.5 QSFP28/100GbE CU Cable	42H	EB4P	Both	Yes	No
Service wedge shelf for EB3Z	42H	EB4Z	Both	No	No
0.5m EDR IB Copper Cable	42H	EB50	Both	Yes	No
1.0m EDR IB Copper Cable	42H	EB51	Both	Yes	No
2.0M EDR IB Copper Cable	42H	EB52	Both	Yes	No
1.5M EDR IB Copper Cable	42H	EB54	Both	Yes	No

100Gb optic Transceiver QSFP28	42H	EB59	Both	Yes	No
3M EDR IB Optical Cable	42H	EB5A	Both	Yes	No
5M EDR IB Optical Cable	42H	EB5B	Both	Yes	No
10M EDR IB Optical Cable	42H	EB5C	Both	Yes	No
15M EDR IB Optical Cable	42H	EB5D	Both	Yes	No
20M EDR IB Optical Cable	42H	EB5E	Both	Yes	No
30M EDR IB Optical Cable	42H	EB5F	Both	Yes	No
50M EDR IB Optical Cable	42H	EB5G	Both	Yes	No
100M EDR IB Optical Cable	42H	EB5H	Both	Yes	No
0.5M 100GbE Cu Cable QSFP28	42H	EB5J	Both	Yes	No
1.0M 100GbE Cu Cable QSFP28	42H	EB5K	Both	Yes	No
1.5M 100GbE Cu Cable QSFP28	42H	EB5L	Both	Yes	No
2.0M 100GbE Cu Cable QSFP28	42H	EB5M	Both	Yes	No
25M EDR IB Optical Cable	42H	EB5N	Both	Yes	No
3M 100GbE optic Cable QSFP28	42H	EB5R	Both	Yes	No
5M 100GbE optic Cable QSFP28	42H	EB5S	Both	Yes	No
10M 100GbE optic Cable QSFP28	42H	EB5T	Both	Yes	No
15M 100GbE optic Cable QSFP28	42H	EB5U	Both	Yes	No
20M 100GbE optic Cable QSFP28	42H	EB5V	Both	Yes	No
30M 100GbE optic Cable QSFP28	42H	EB5W	Both	Yes	No
50M 100GbE optic Cable QSFP28	42H	EB5X	Both	Yes	No
100M 100GbE optic Cable QSFP28	42H	EB5Y	Both	Yes	No
IBM i 7.2 Indicator	42H	EB72	Both	Yes	No
IBM i 7.3 Indicator	42H	EB73	Both	Yes	No
Rack Front Door (Black)	42H	EC01	MES	Yes	No
Rack Rear Door	42H	EC02	MES	Yes	No
Rack Side Cover	42H	EC03	MES	Yes	No
Rack Suite Attachment Kit	42H	EC04	MES	Yes	No
Slim Rear Acoustic Door	42H	EC07	MES	Yes	No
Slim Front Acoustic Door	42H	EC08	MES	Yes	No
Rear Door Heat Exchanger	42H	EC15	MES	Yes	No
PCIe3 2-Port 10Gb NIC&ROCE	42H	EC2S	Both	Yes	No
PCIe3 2-Port 25/10Gb NIC&Ro	42H	EC2U	Both	Yes	No
PCIe3 2-port 100GbE Adapterx16	42H	EC3M	Both	Yes	No
PCIe3 NVMe carrier card	42H	EC59	Both	Yes	No
PCIe4 1-port 100Gb EDR IB	42H	EC63	Both	Yes	No
PCIe4 2-port 100Gb EDR IB	42H	EC65	Both	Yes	No

SAS X Cable 3m - HD Narrow	42H	ECBJ	Both	Yes	No
SAS X Cable 6m - HD Narrow	42H	ECBK	Both	Yes	No
SAS X Cable 10m - HD Narrow	42H	ECBL	Both	Yes	No
SAS X Cable 15m -HD Narrow 3Gb	42H	ECBM	Both	Yes	No
SAS YO Cable 1.5m - HD Narrow	42H	ECBT	Both	Yes	No
SAS YO Cable 3m - HD Narrow	42H	ECBU	Both	Yes	No
SAS YO Cable 6m - HD Narrow	42H	ECBV	Both	Yes	No
SAS YO Cable 10m - HD Narrow	42H	ECBW	Both	Yes	No
SAS YO Cable 15m-HD Narrow 3Gb	42H	ECBX	Both	Yes	No
SAS AE1 Cable 4m - HD Narrow	42H	ECBY	Both	Yes	No
SAS YE1 Cable 3m - HD Narrow	42H	ECBZ	Both	Yes	No
SAS AA Cable 0.6m - HD Narrow	42H	ECC0	Both	Yes	No
SAS AA Cable 1.5m - HD Narrow	42H	ECC2	Both	Yes	No
SAS AA Cable 3m - HD Narrow	42H	ECC3	Both	Yes	No
SAS AA Cable 6m - HD Narrow	42H	ECC4	Both	Yes	No
3M Optical Cable Pair	42H	ECC7	Both	Yes	No
10M Optical Cable Pair	42H	ECC8	Both	Yes	No
Port Converter Cable for UPS	42H	ECCF	Both	Yes	No
3M Copper CXP Cable Pair	42H	ECCS	Both	Yes	No
3.0M SAS X12 Cable	42H	ECDJ	Both	Yes	No
4.5M SAS X12 Cable	42H	ECDK	Both	Yes	No
10M SAS X12 Cable	42H	ECDL	Both	Yes	No
1.5M SAS Y012 Cable	42H	ECDT	Both	Yes	No
3.0M SAS Y012 Cable	42H	ECDU	Both	Yes	No
4.5M SAS Y012 Cable	42H	ECDV	Both	Yes	No
10M SAS Y012 Cable	42H	ECDW	Both	Yes	No
0.6M SAS AA12 Cable	42H	ECE0	Both	Yes	No
3.0M SAS AA12 Cable	42H	ECE3	Both	Yes	No
4.5M SAS AA12 Cable	42H	ECE4	Both	Yes	No
2.0 M Slim Rack	42H	ECR0	MES	Yes	No
Rack Front Door	42H	ECRF	MES	Yes	No
Rack Rear Door Black	42H	ECRG	MES	Yes	No
Rack Side Cover	42H	ECRJ	MES	Yes	No
Rack Rear Extension 5-In	42H	ECRK	MES	Yes	No
Rack Front Door (Black/Flat)	42H	ECRM	MES	Yes	No
Assembled and Tested in China	42H	ECS0	Both	Yes	No
Custom Serv. Specify, France	42H	ECSF	Both	Yes	No

NeuCloud Indicator/Specify	42H	ECSJ	Both	Yes	No
Custom Serv. Specify, Mexico	42H	ECSM	Both	Yes	No
Custom Serv. Spec Poughkeepsie	42H	ECSP	Both	Yes	No
Integrated Solution Packing	42H	ECSS	Initial	N/A	No
Optical wrap Plug	42H	ECW0	Both	Yes	No
Boot Drive in EXP12SX Specify	42H	EHR1	Both	Yes	No
Boot / Load in EXP24SX Specify	42H	EHR2	Both	Yes	No
SSD Placement Ind- #ESLS/#ELLS	42H	EHS2	Both	Yes	No
PCIe3 Optical Cable Adapter	42H	EJ08	Both	Yes	No
PCIe3 RAID SAS Adapter 4-port	42H	EJ0J	Both	Yes	No
SAS Ports: Dual IOA Backplane	42H	EJ0W	Both	Yes	No
PCIe3 SAS Tape/DVD Adapter	42H	EJ10	Both	Yes	No
PCIe3 12GB Cache RAID+ SAS Ada	42H	EJ14	Both	Yes	No
Backplane 12 SFF & RDX Bay	42H	EJ1C	Both	No	No
Backplane 18 SFF & Dual IOA	42H	EJ1D	Both	No	No
Split#EJ1C Add 2nd Controller	42H	EJ1E	Both	No	No
Backplane 12 SFF & RDX Bay	42H	EJ1M	Both	No	No
PCIe3 Crypto Coproc BSC-3 4767	42H	EJ33	Both	Yes	No
Non-paired Indicator EJ0L PCIe	42H	EJRL	Both	Yes	No
Front IBM Bezel 12-Bay BackP	42H	EJU3	Both	Yes	No
Front OEM Bezel 12-Bay BackP	42H	EJU4	Both	Yes	No
Front IBM Bezel 18-Bay BackP	42H	EJUG	Both	Yes	No
Front OEM Bezel 18-Bay BackP	42H	EJUH	Both	Yes	No
Specify Mode-1 & CEC Ports 2Y0	42H	EJV0	Both	Yes	No
Specify Mode-1 for EXP12SX 1&1	42H	EJV1	Both	Yes	No
Specify Mode-1 for EXP12SX 2&2	42H	EJV2	Both	Yes	No
Specify Mode-2 for EXP12SX 2&2	42H	EJV3	Both	Yes	No
Specify Mode-2 for EXP12SX 4&2	42H	EJV4	Both	Yes	No
Specify Mode-4 for EXP12SX 4&2	42H	EJV5	Both	Yes	No
Specify Mode-2 for EXP12SX 1&2	42H	EJV6	Both	Yes	No
Specify Mode-2 for EXP12SX 2&2	42H	EJV7	Both	Yes	No
Specify Mode-2 for EXP12SX 1&1	42H	EJVA	Both	Yes	No
Specify Mode-2 for EXP12SX 2&1	42H	EJVB	Both	Yes	No
Specify Mode-4 for EXP12SX 1&1	42H	EJVC	Both	Yes	No
Specify Mode-4 for EXP12SX 2&1	42H	EJVD	Both	Yes	No
Specify Mode-4 for EXP12SX 3&2	42H	EJVE	Both	Yes	No
Specify Mode-1 for EXP12SX 2&2	42H	EJVF	Both	Yes	No

Specify Mode-1 & CEC Ports 2Y0	42H	EJW0	Both	Yes	No
Specify Mode-1 for EXP24SX 1&1	42H	EJW1	Both	Yes	No
Specify Mode-1 for EXP24SX 2&2	42H	EJW2	Both	Yes	No
Specify Mode-2 for EXP24SX 2&2	42H	EJW3	Both	Yes	No
Specify Mode-2 for EXP24SX 4&2	42H	EJW4	Both	Yes	No
Specify Mode-4 for EXP24SX 4&2	42H	EJW5	Both	Yes	No
Specify Mode-2 for EXP24SX 1&2	42H	EJW6	Both	Yes	No
Specify Mode-2 for EXP24SX 2&2	42H	EJW7	Both	Yes	No
Specify Mode-2 for EXP24SX 1&1	42H	EJWA	Both	Yes	No
Specify Mode-2 for EXP24SX 2&1	42H	EJWB	Both	Yes	No
Specify Mode-4 for EXP24SX 1&1	42H	EJWC	Both	Yes	No
Specify Mode-4 for EXP24SX 2&1	42H	EJWD	Both	Yes	No
Specify Mode-4 for EXP24SX 3&2	42H	EJWE	Both	Yes	No
Specify Mode-1 for EXP24SX 2&2	42H	EJWF	Both	Yes	No
Specify Mode-2 for EXP24SX 2&2	42H	EJWG	Both	Yes	No
Specify Mode-2 for EXP24SX 2&1	42H	EJWH	Both	Yes	No
Specify Mode-2 for EXP24SX 4&2	42H	EJWJ	Both	Yes	No
PDU Access Cord 0.38m	42H	ELC0	MES	Yes	No
#ESD4 Load Source Specify	42H	ELS4	MES	Yes	No
#ESDA Load Source Specify	42H	ELSA	MES	Yes	No
#ESFU Load Source Specify	42H	ELT0	Both	Yes	No
#ES81 Load Source Specify	42H	ELT1	MES	Yes	No
#ESF2 Load Source Specify	42H	ELT2	Both	Yes	No
#ESF4 Load Source Specify	42H	ELT4	Both	Yes	No
#ES86 Load Source Specify	42H	ELT6	Both	Yes	No
#ESF8 Load Source Specify	42H	ELT8	Both	Yes	No
#ESFA Load Source Specify	42H	ELTA	Both	Yes	No
#ES8D Load Source Specify	42H	ELTD	Both	Yes	No
#ESFE Load Source Specify	42H	ELTE	Both	Yes	No
#ES8G Load Source Specify	42H	ELTG	Both	Yes	No
#ES8K Load Source Specify	42H	ELTK	MES	Yes	No
#ES7L Load Source Specify	42H	ELTL	MES	Yes	No
#ESFN Load Source Specify 571G	42H	ELTN	Both	Yes	No
#ES8P Load Source Specify	42H	ELTP	Both	Yes	No
#ES7Q Load Source Specify	42H	ELTQ	MES	Yes	No
#ES8R Load Source Specify	42H	ELTR	Both	Yes	No
#ESFS Load Source Specify	42H	ELTS	Both	Yes	No

#ESEU Load Source Specify	42H	ELTU	Both	Yes	No
#ES8W Load Source Specify	42H	ELTW	Both	Yes	No
#ESEY Load Source Specify 283G	42H	ELTY	Both	Yes	No
#ESNJ Load Source Specify	42H	ELUJ	Both	Yes	No
#ESNL Load Source Specify	42H	ELUL	Both	Yes	No
#ESNN Load Source Specify	42H	ELUN	Both	Yes	No
#ESNQ Load Source Specify	42H	ELUQ	Both	Yes	No
#ESE2 Load Source Specify	42H	ELZ2	Both	Yes	No
#ES93 Load Source Specify	42H	ELZ3	Both	Yes	No
#ES84 Load Source Specify	42H	ELZ4	Both	Yes	No
#ES97 Load Source Specify	42H	ELZ7	Both	Yes	No
#ESE8 Load Source Specify	42H	ELZ8	Both	Yes	No
#ESGA Load Source Specify	42H	ELZA	MES	Yes	No
#ESGC Load Source Specify	42H	ELZC	Both	Yes	No
#ESGE Load Source Specify	42H	ELZE	Both	Yes	No
#ESGJ Load Source Specify	42H	ELZJ	MES	Yes	No
#ESGL Load Source Specify	42H	ELZL	Both	Yes	No
#ESGN Load Source Specify	42H	ELZN	Both	Yes	No
#ESGQ Load Source Specify	42H	ELZQ	Both	Yes	No
#ESGS Load Source Specify	42H	ELZS	Both	Yes	No
#ES8Z Load Source Specify	42H	ELZZ	Both	Yes	No
16 GB DDR4 Memory	42H	EM62	Both	Yes	No
32 GB DDR4 Memory	42H	EM63	Both	Yes	No
64 GB DDR4 Memory	42H	EM64	Both	Yes	No
128 GB DDR4 Memory	42H	EM65	Both	Yes	No
PCIe Gen3 I/O Expansion Drawer	42H	EMX0	Both	Yes	No
AC Power Supply Conduit	42H	EMXA	Both	Yes	No
PCIe3 6-slot Fanout Module	42H	EMXF	Support	Yes	No
PCIe3 6-slot Fanout Module	42H	EMXG	Both	Yes	No
1m 10GbE Cable SFP+ Act Twinax	42H	EN01	Both	Yes	No
3m 10GbE Cable SFP+ Act Twinax	42H	EN02	Both	Yes	No
5m 10GbE Cable SFP+ Act Twinax	42H	EN03	Both	Yes	No
PCIe3 16Gb 2-port Fibre Channe	42H	EN0A	Both	Yes	No
PCIe3 4-port 10Gb FCoE & 1GbE	42H	EN0H	Both	Yes	No
PCIe3 4-port 10GB FCoE & 1GbE	42H	EN0K	Both	Yes	No
PCIe2 4-pt(10+1 GbE)SR+RJ45	42H	EN0S	Both	Yes	No
PCIe2 4-pt(10+1GbE)CRSR+RJ45	42H	EN0U	Both	Yes	No

PCIe2 2-pt 10/1GbE BaseT RJ45	42H	EN0W	Both	Yes	No
PCIe 1-port Bisync Adapter	42H	EN13	Support	Yes	No
PCIe3 4-port 10GbE SR Adapter	42H	EN15	Both	Yes	No
PCIe3 32Gb 2-port FC Adapter	42H	EN1A	Both	Yes	No
PCIe3 16Gb 4-port FC Adapter	42H	EN1C	Both	Yes	No
8-core 3.8/4.0 GHZ POWER9	42H	EP1E	Both	No	No
10-core 3.5/3.9 GHZ POWER9	42H	EP1F	Both	No	No
12-core 3.4/3.9 GHZ POWER9	42H	EP1G	Both	No	No
One Proc Activation for #EP4E	42H	EP4E	Both	Yes	No
One Proc Activation for #EP4F	42H	EP4F	Both	Yes	No
One Proc Activation for #EP4G	42H	EP4G	Both	Yes	No
Horizontal PDU Mounting Hardwr	42H	EPTH	Both	Yes	No
High Function 9xC19 PDU	42H	EPTJ	Both	Yes	No
High Function 9xC19 PDU 3Phase	42H	EPTL	Both	Yes	No
High Function 12xC13 PDU	42H	EPTN	Both	Yes	No
High Function 12xC13 PDU 3-Phs	42H	EPTQ	Both	Yes	No
Qty 150 #ES62 3.86TB LFF Dsk	42H	EQ62	Both	Yes	No
Qty 150 #ES64 7.72TB LFF Dsk	42H	EQ64	Both	Yes	No
Qty 150 #ES78 SSD 387GB 5xx	42H	EQ78	Both	Yes	No
Qty 150 #ES7E SSD 775GB 5xx	42H	EQ7E	Both	Yes	No
Quantity 150 of ES80 1.9TB SSD	42H	EQ80	Support	Yes	No
Quantity 150 of ES81 1.9TB SSD	42H	EQ81	Support	Yes	No
Qty 150 #ES85 SSD 387GB 4k	42H	EQ85	Both	Yes	No
Qty 150 #ES86 SSD 387GB 4k	42H	EQ86	Both	Yes	No
Qty 150 #ES8C SSD 775GB 4k	42H	EQ8C	Both	Yes	No
Qty 150 #ES8D SSD 775GB 4k	42H	EQ8D	Both	Yes	No
Qty 150 #ES8F SSD 1.55TB 4k	42H	EQ8F	Both	Yes	No
Qty 150 #ES8G SSD 1.55TB 4k	42H	EQ8G	Both	Yes	No
Quantity 150 of ES8Y 931GB	42H	EQ8Y	Both	Yes	No
Quantity 150 of ES8Z 931GB	42H	EQ8Z	Both	Yes	No
Quantity 150 of ES96 1.86TB	42H	EQ96	Both	Yes	No
Quantity 150 of ES97 1.86TB	42H	EQ97	Both	Yes	No
Quantity 150 of #ESE7 3.72TB	42H	EQE7	Both	Yes	No
Quantity 150 of ESE8 3.72TB	42H	EQE8	Both	Yes	No
Quantity 150 of #ESEU 571GB	42H	EQEU	Both	Yes	No
Quantity 150 of #ESEV 600GB	42H	EQEV	Both	Yes	No
Quantity 150 of #ESEY 283 GB S					

Quantity 150 of #ESEZ	42H 300GB	EQEY	Both	Yes	No
Quantity 150 of #ESF2	42H 1.2TB	EQEZ	Both	Yes	No
Quantity 150 of #ESF3	42H 1.2TB	EQF2	Both	Yes	No
Quantity 150 of #ESFN	42H 571GB	EQF3	Both	Yes	No
Quantity 150 of #ESFP	42H 600GB	EQFN	Both	Yes	No
Quantity 150 of #ESFS	42H 1.7TB	EQFP	Both	Yes	No
Quantity 150 of #ESFT	42H 1.8TB	EQFS	Both	Yes	No
Quantity 150 of #ESG5	42H	EQFT	Both	Yes	No
Quantity 150 of #ESGB	42H	EQG5	Both	Yes	No
Quantity 150 of #ESGC	42H	EQGB	Both	Yes	No
Quantity 150 of #ESGF	42H	EQGC	Both	Yes	No
Quantity 150 of #ESGK	42H	EQGF	Both	Yes	No
Quantity 150 of #ESGL	42H	EQGK	Both	Yes	No
Quantity 150 of #ESGP	42H	EQGL	Both	Yes	No
Quantity 150 of #ESGQ	42H	EQGP	Both	Yes	No
42U Slim Rack	42H	EQGQ	Both	Yes	No
RFID Tags for Compute Nodes	42H	ER05	MES	Yes	No
Rear rack extension	42H	ERF1	Initial	N/A	No
Mainstream 400GB SSD NVMe	42H	ERG0	MES	Yes	No
3.86TB 7200 RPM SAS LFF Disk	42H	ES14	Both	Yes	No
7.72TB 7200 RPM SAS LFF Disk	42H	ES62	Both	Yes	No
387GB SFF-2 SSD 5xx for AIX/L	42H	ES64	Both	Yes	No
775GB SFF-2 SSD 5xx for AIX/L	42H	ES78	Both	Yes	No
387GB SFF-3 SSD 5xx for AIX/L	42H	ES7E	Both	Yes	No
387GB SFF-3 SSD 5xx for IBM i	42H	ES7K	Both	Yes	No
775GB SFF-3 SSD 5xx for AIX/L	42H	ES7L	Support	Yes	No
775GB SFF-3 SSD 5xx for IBM i	42H	ES7P	Both	Yes	No
1.9TB RI SAS 4k SFF-2 SSD AIX	42H	ES7Q	Support	Yes	No
1.9TB RI SAS 4k SFF-2 SSD IBM	42H	ES80	Support	Yes	No
931GB Mainstream SAS 4k SSD	42H	ES81	Support	Yes	No
931GB Mainstream SAS 4k SSD	42H	ES83	Both	Yes	No
387GB SFF-2 SSD 4k for AIX/Li	42H	ES84	Both	Yes	No
387GB SFF-2 SSD 4k for IBM i	42H	ES85	Both	Yes	No
775GB SFF-2 SSD 4k for AIX/Li	42H	ES86	Both	Yes	No
775GB SFF-2 SSD 4k for IBM i	42H	ES8C	Both	Yes	No
1.55TB SFF-2 SSD 4k for AIX/L	42H	ES8D	Both	Yes	No
1.55TB SFF-2 SSD 4k for IBM i	42H	ES8F	Both	Yes	No

	42H	ES8G	Both	Yes	No
1.9TB RI SAS 4k SFF-3 SSD AIX	42H	ES8J	Support	Yes	No
1.9TB RI SAS 4k SFF-3 SSD IBM	42H	ES8K	Support	Yes	No
387GB SFF-3 SSD 4k for AIX/Li	42H	ES8N	Both	Yes	No
387GB SFF-3 SSD 4k for IBM i	42H	ES8P	Both	Yes	No
775GB SFF-3 SSD 4k for AIX/Li	42H	ES8Q	Both	Yes	No
775GB SFF-3 SSD 4k for IBM i	42H	ES8R	Both	Yes	No
1.55TB SFF-3 SSD 4k for AIX/L	42H	ES8V	Both	Yes	No
1.55TB SFF-3 SSD 4k for IBM i	42H	ES8W	Both	Yes	No
931GB Mainstream SAS 4k SSD	42H	ES8Y	Both	Yes	No
931GB Mainstream SAS 4k SSD	42H	ES8Z	Both	Yes	No
1.86TB Mainstream SAS 4k SSD	42H	ES92	Both	Yes	No
1.86TB Mainstream SAS 4k SSD	42H	ES93	Both	Yes	No
1.86TB Mainstream SAS 4k SSD	42H	ES96	Both	Yes	No
1.86TB Mainstream SAS 4k SSD	42H	ES97	Both	Yes	No
S&H - No Charge	42H	ESC0	Both	Yes	No
S&H-b	42H	ESC6	Initial	N/A	No
571GB 10K RPM SAS SFF-3 Disk	42H	ESD4	Support	Yes	No
600GB 10K RPM SAS SFF3 Disk	42H	ESD5	Both	Yes	No
283GB 15K RPM SAS SFF-3 Disk	42H	ESDA	Support	Yes	No
300GB 15K RPM SAS SFF-3 Disk	42H	ESDB	Both	Yes	No
3.72TB Mainstream SAS 4k SSD	42H	ESE1	Both	Yes	No
3.72TB Mainstream SAS 4k SSD	42H	ESE2	Both	Yes	No
3.72TB Mainstream SAS 4k SSD	42H	ESE7	Both	Yes	No
3.72TB Mainstream SAS 4k SSD	42H	ESE8	Both	Yes	No
571GB 10K RPM SFF-2 Disk 4K	42H	ESEU	Both	Yes	No
600GB 10K RPM SFF-2 Disk 4K	42H	ESEV	Both	Yes	No
283GB 15K SAS SFF-2 4K BLK HDD	42H	ESEY	Both	Yes	No
300GB 15K SAS SFF-2 4K BLK HDD	42H	ESEZ	Both	Yes	No
1.1TB 10K RPM SFF-2 Disk 4K	42H	ESF2	Both	Yes	No
1.2TB 10K RPM SFF-2 Disk 4K	42H	ESF3	Both	Yes	No
571GB 10K RPM SFF-3 Disk 4K	42H	ESF4	Both	Yes	No
600GB 10K RPM SFF-3 Disk 4K	42H	ESF5	Both	Yes	No
1.1TB 10K RPM SFF-3 Disk 4K	42H	ESF8	Both	Yes	No
1.2TB 10K RPM SFF-3 Disk 4K	42H	ESF9	Both	Yes	No
283GB 15K SAS SFF-3 4K BLK HDD	42H	ESFA	Both	Yes	No
300GB 15K SAS SFF-3 4K BLK HDD	42H	ESFB	Both	Yes	No
571GB 15K SAS SFF-3 4K BLK HDD					

			42H	ESFE	Both	Yes	No
600GB	15K SAS SFF-3	4K	BLK HDD				
			42H	ESFF	Both	Yes	No
571GB	15K SAS SFF-2	4K	BLK HDD				
			42H	ESFN	Both	Yes	No
600GB	15K SAS SFF-2	4K	BLK HDD				
			42H	ESFP	Both	Yes	No
1.7TB	10K RPM SFF-2	Disk	4K				
			42H	ESFS	Both	Yes	No
1.8TB	10K RPM SFF-2	Disk	4K				
			42H	ESFT	Both	Yes	No
1.7TB	10K RPM SFF-3	Disk	4K				
			42H	ESFU	Both	Yes	No
1.8TB	10K RPM SFF-3	Disk	4K				
			42H	ESFV	Both	Yes	No
387GB	Enterprise SAS	5xx	SSD				
			42H	ESG5	Both	Yes	No
387GB	Enterprise SAS	5xx	SSD				
			42H	ESG9	Both	Yes	No
387GB	Enterprise SAS	5xx	SSD				
			42H	ESGA	Support	Yes	No
387GB	Enterprise SAS	4k	SSD				
			42H	ESGB	Both	Yes	No
387GB	Enterprise SAS	4k	SSD				
			42H	ESGC	Both	Yes	No
387GB	Enterprise SAS	4k	SSD				
			42H	ESGD	Both	Yes	No
387GB	Enterprise SAS	4k	SSD				
			42H	ESGE	Both	Yes	No
775GB	Enterprise SAS	5xx	SSD				
			42H	ESGF	Both	Yes	No
775GB	Enterprise SAS	5xx	SSD				
			42H	ESGH	Both	Yes	No
775GB	Enterprise SAS	5xx	SSD				
			42H	ESGJ	Support	Yes	No
775GB	Enterprise SAS	4k	SSD				
			42H	ESGK	Both	Yes	No
775GB	Enterprise SAS	4k	SSD				
			42H	ESGL	Both	Yes	No
775GB	Enterprise SAS	4k	SSD				
			42H	ESGM	Both	Yes	No
775GB	Enterprise SAS	4k	SSD				
			42H	ESGN	Both	Yes	No
1.55TB	Enterprise SAS	4k	SSD				
			42H	ESGP	Both	Yes	No
1.55TB	Enterprise SAS	4k	SSD				
			42H	ESGQ	Both	Yes	No
1.55TB	Enterprise SAS	4k	SSD				
			42H	ESGR	Both	Yes	No
1.55TB	Enterprise SAS	4k	SSD				
			42H	ESGS	Both	Yes	No
SAP HANA Identifier	9223-42H						
			42H	ESH2	Initial	N/A	No
Specify AC Power Supply							
			42H	ESLA	Both	Yes	No
EXP12SX	SAS Storage Enclosure						
			42H	ESLL	Both	Yes	No
EXP24SX	SAS Storage Enclosure						
			42H	ESLS	Both	Yes	No
283GB	15K SAS SFF-3	4k	HDD				
			42H	ESNJ	Both	Yes	No
300GB	15K SAS SFF-3	4k	HDD				
			42H	ESNK	Both	Yes	No
283GB	15K SAS SFF-2	4k	HDD				
			42H	ESNL	Both	Yes	No
300GB	15K SAS SFF-2	4k	HDD				
			42H	ESNM	Both	Yes	No
571GB	15K SAS SFF-3	4k	HDD				
			42H	ESNN	Both	Yes	No
600GB	15K SAS SFF-3	4k	HDD				
			42H	ESNP	Both	Yes	No
571GB	15K SAS SFF-2	4k	HDD				
			42H	ESNQ	Both	Yes	No
600GB	15K SAS SFF-2	4k	HDD				

Quantity 150 of #ESNL 283GB	42H	ESNR	Both	Yes	No
Quantity 150 of #ESNM 300GB	42H	ESPL	Both	Yes	No
Quantity 150 of #ESNQ 571GB	42H	ESPM	Both	Yes	No
Quantity 150 of #ESNR 600GB	42H	ESPQ	Both	Yes	No
RDX USB Internal Docking	42H	ESPR	Both	Yes	No
1TB Removable Disk Cartridge	42H	EU00	Both	Yes	No
RDX USB External Docking	42H	EU01	Both	Yes	No
RDX 320 GB Removable Disk Driv	42H	EU04	Support	Yes	No
Operator Panel LCD Display	42H	EU08	Support	Yes	No
1.5TB Removable Disk Cartridge	42H	EU0B	Both	Yes	No
Cable Ties & Labels	42H	EU15	Support	Yes	No
	42H	EU19	Both	Yes	No
2TB Removable Disk Cartrdg-RDX	42H	EU2T	Both	Yes	No
RDX USB External Docking Sta	42H	EUA4	Both	Yes	No
Standalone USB DVD drive w/c	42H	EUA5	Both	Yes	No
Core Use HW Feature	42H	EUC6	MES	Yes	No
Core Use HW Feature 10	42H	EUC7	MES	Yes	No

CSU = Customer setup

RP MES = Return parts, miscellaneous equipment specifications

Pricing terms

Prices in the following PDF prices link are suggested list prices on day of announcement for the U.S. only. They are provided for your information only. Dealer prices may vary, and prices may also vary by country. IBM list price does not include tax or shipping and is subject to change without notice.

[ENUS-118-001-LIST_PRICES_2018_02_13.PDF](#)

Annual minimum maintenance charges

Not applicable.

ServiceElect (ESA) charges

For ServiceElect (ESA) maintenance service charges, contact IBM Global Services at 888-IBM-4343 (426-4343).

IBM Global Financing

IBM Global Financing offers competitive financing to credit-qualified customers to assist them in acquiring IT solutions. Offerings include financing for IT acquisition, including hardware, software, and services, from both IBM and other manufacturers or vendors. Offerings (for all customer segments: small, medium, and large enterprise), rates, terms, and availability can vary by country. Contact your local IBM Global Financing organization or go to the [IBM Global Financing](#) website for more information.

IBM Global Financing offerings are provided through IBM Credit LLC in the United States and other IBM subsidiaries and divisions worldwide to qualified commercial and government customers. Rates are based on a customer's credit rating, financing terms, offering type, equipment type and options, and may vary by country. Other restrictions may apply. Rates and offerings are subject to change, extension, or withdrawal without notice.

Financing solutions from IBM Global Financing can help you stretch your budget and affordably acquire the new product. But beyond the initial acquisition, our end-to-end approach to IT management can also help keep your technologies current, reduce costs, minimize risk, and preserve your ability to make flexible equipment decisions throughout the entire technology lifecycle.

Order now

To order, contact the IBM Digital Sales Center, your local IBM representative, or your IBM Business Partner. To identify your local IBM representative or IBM Business Partner, call 800-IBM-4YOU (426-4968). For more information, contact the IBM Digital Sales Center.

Phone: 800-IBM-CALL (426-2255)

Fax: 800-2IBM-FAX (242-6329)

For IBM representative: askibm@ca.ibm.com

For IBM Business Partner: pwcs@us.ibm.com

IBM Digital Sales Offices 1177 S Belt Line Rd Coppell, TX 75019-4642, US

The IBM Digital Sales Center, our national direct marketing organization, can add your name to the mailing list for catalogs of IBM products.

Note: Shipments will begin after the planned availability date.

Trademarks

Power Systems, POWER9, EnergyScale, Electronic Service Agent and HACMP are trademarks of IBM Corporation in the United States, other countries, or both. IBM, Power, Db2, AIX, PowerVM, POWER8, POWER, PartnerWorld, Global Technology Services, PowerPC and POWER7 are registered trademarks of IBM Corporation in the United States, other countries, or both.

Linux is a registered trademark of Linus Torvalds in the United States, other countries, or both.

Other company, product, and service names may be trademarks or service marks of others.

Terms of use

IBM products and services which are announced and available in your country can be ordered under the applicable standard agreements, terms, conditions, and prices in effect at the time. IBM reserves the right to modify or withdraw this announcement at any time without notice. This announcement is provided for your information only. Additional terms of use are located at

[Terms of use](#)

For the most current information regarding IBM products, consult your IBM representative or reseller, or go to the IBM worldwide contacts page

[IBM United States](#)

Corrections

(Corrected on March 30, 2018)

The Software requirements section was revised.

(Corrected on March 16, 2018)

The Operating environment and Software requirements sections were revised.

(Corrected on February 23, 2018)

The Description and Hardware requirements sections were revised.