

IBM SPSS Collaboration and Deployment  
Services  
8.4

*RESTful Scoring Service Developer's  
Guide*



**Note**

Before using this information and the product it supports, read the information in [“Notices” on page 45.](#)

**Product Information**

This edition applies to version 8, release 4, modification 0 of IBM® SPSS® Collaboration and Deployment Services and to all subsequent releases and modifications until otherwise indicated in new editions.

© **Copyright International Business Machines Corporation 2000, 2022.**

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

---

# Contents

<b>Chapter 1. Scoring Service .....</b>	<b>1</b>
Scoring Service overview.....	1
Accessing the Scoring Service from a client.....	1
Specifying a request URL.....	1
Specifying request headers.....	2
Specifying a request body.....	3
Receiving response headers.....	4
Receiving a response body.....	4
<b>Chapter 2. API reference for the Scoring Service .....</b>	<b>7</b>
Service resource.....	7
Service GET.....	7
Configuration resource.....	8
Configuration GET.....	9
Metadata resource.....	10
Metadata GET.....	10
Score resource.....	13
Score POST.....	15
Metric item resource.....	18
Metric item GET.....	19
Metric value resource.....	22
Metric value GET.....	22
<b>Chapter 3. JSON reference for the Scoring Service .....</b>	<b>25</b>
The configurationReference object.....	25
The modelReference element.....	26
The configurationStatus element.....	26
The metadataResult object.....	27
The metadataInputTable element.....	28
The metadataContextTable element.....	29
The metadataOutputField element.....	30
The metricItem object.....	31
The metricValue object.....	31
The scoreRequest object.....	32
The requestInputTable element.....	33
The context element.....	35
The scoreResult object.....	36
The columnNames element.....	37
The rowValues element.....	38
The returnedRequestInputTable element.....	38
The scoringServiceDetails object.....	40
The scoreProviderDetails element.....	41
<b>Appendix A. Deprecated features.....</b>	<b>43</b>
<b>Notices.....</b>	<b>45</b>
Privacy policy considerations .....	46
Trademarks.....	46
<b>Glossary.....</b>	<b>49</b>
A.....	49

B.....	49
C.....	50
D.....	50
E.....	51
F.....	51
G.....	51
I.....	51
J.....	52
K.....	52
L.....	53
M.....	53
N.....	53
O.....	53
P.....	54
R.....	54
S.....	54
T.....	55
U.....	55
V.....	55
W.....	56
X.....	56
<b>Index.....</b>	<b>57</b>

---

# Chapter 1. Scoring Service

## Scoring Service overview

---

The Scoring Service allows client applications to employ real-time scores derived from predictive models developed in IBM SPSS Modeler, IBM SPSS Statistics, or third party tools. The service fetches a specified model, loads it, invokes the correct scoring implementation, and returns the result to the client. Supported models include regression (linear and logistic), decision trees, decision lists, neural networks, and naïve Bayes defined in IBM SPSS Modeler streams or in PMML from IBM SPSS Statistics.

Scoring can be either synchronous or asynchronous, depending on whether the client needs to wait for a score before proceeding or not. The service can load multiple models simultaneously for scoring and can be virtualized across multiple servers in a cluster configuration to handle large processing loads. The service logs all scoring activity for regulatory audit purposes. Configuring models for scoring and monitoring the service performance can be done using the IBM SPSS Deployment Manager.

## Accessing the Scoring Service from a client

---

Access to the Scoring Service is through standard HTTP and HTTPS methods. A client initiates a request to a server; the server processes the requests and returns the appropriate responses.

The request and response are built around the concept of a resource and its data.

- [“Specifying a request URL” on page 1](#). The base URL for accessing the service is the IP address of an enabled server.
- [“Specifying request headers” on page 2](#). Certain requests may require information in the request header.
- [“Specifying a request body” on page 3](#). For operations that transmit data to the server, specify a request body in JSON format.
- [“Receiving response headers” on page 4](#). Requests return headers as part of the response.
- [“Receiving a response body” on page 4](#). For a GET operation, the response body contains the requested information in the format of a JSON object or array of objects.

## Specifying a request URL

The base URL consists of a server and port specification appended with the service location.

The base URL for accessing the Scoring Service is the following:

```
http://{server}:{port}/scoring/rest
```

The following variables should be replaced with values for your system.

- `{server}` corresponds to the server name or IP address for your IBM SPSS Collaboration and Deployment Services Repository
- `{port}` is the port number on which to access the IBM SPSS Collaboration and Deployment Services Repository

Send the base URL appended with `/configuration` as a GET request to obtain information about the scoring configurations available in your IBM SPSS Collaboration and Deployment Services Repository. Most of the remaining URL requests include the identifier for a particular scoring configuration. The following sample URL requests illustrate typical use.

- GET `http://cdssvr:80/scoring/rest/service`

Gets information about the score providers available for your system. See the topic [“Service resource” on page 7](#) for more information.

- GET `http://cdssvr:80/scoring/rest/configuration`

Gets information about all available scoring configurations. Use this method to determine the identifier for the configuration you want to use for scoring or for performance analysis. See the topic [“Configuration resource” on page 8](#) for more information.

- GET `http://cdssvr:80/scoring/rest/configuration/KMeans/metadata`

Gets information about the inputs for the scoring configuration named *KMeans*. This information is useful for constructing the body of score requests. See the topic [“Metadata resource” on page 10](#) for more information.

- POST `http://cdssvr:80/scoring/rest/configuration/KMeans/score`

Retrieves a score using the scoring configuration named *KMeans*. The input data for the score is supplied in the request body. See the topic [“Score resource” on page 13](#) for more information.

- GET `http://cdssvr:80/scoring/rest/configuration/KMeans/metric`

Gets information about all available performance statistics for the scoring configuration named *KMeans*. See the topic [“Metric item resource” on page 18](#) for more information.

- GET `http://cdssvr:80/scoring/rest/configuration/KMeans/metric/CONFIGURATION_UPTIME`

Gets the current value for the amount of time the scoring configuration named *KMeans* has been available for scoring. See the topic [“Metric value resource” on page 22](#) for more information.

The URL encoding for your application server must be defined to support the characters used in your URL strings. For example, if a scoring configuration name contains multi-byte characters and the application server URL encoding is defined as ISO-8859-1, the server returns an error indicating that the configuration cannot be found. Setting the URL encoding to UTF-8 eliminates this problem. For information about setting the URL encoding for a specific server, see your application server documentation.

## Specifying request headers

Certain requests may require headers.

The following table identifies fields commonly used in request headers.

Table 1. Request header values	
Name	Value
Accept	Indicates the payload type to return to the client. Valid values include <code>application/json</code> , <code>text/xml</code> , and <code>application/xml</code> .
Authorization	Authentication string encoded using Base64
Client-Accept-Language	Tag defining the language for the response information. This field takes precedence over the <code>Accept-Language</code> field.
Accept-Language	Tag defining the language for the response information

### Accept

The *Accept* field defines the MIME type of the information contained in the body of the response returned to the client application.

## Authorization

The Scoring Service includes a security layer to limit access to authorized users. This layer uses HTTP basic access authentication, requiring the specification of a valid user name and password to be included in any service request.

To add authentication information to a request, include the *Authorization* field in the request header. The value for this field consists of the following components:

- The string *Basic* to indicate basic access authentication is being used
- A space
- The Base64 encoding of the concatenation of the user name, a colon, and the password

For example, the Base64 encoding for a user name of *user* and a password of *pass* is the following:

```
Base64 Encode(user:pass) = dXNlcjpwYXNz
```

The *Authorization* value for this user would be specified as the following string:

```
Basic dXNlcjpwYXNz
```

## Globalization

The Scoring Service can return responses containing globalized information. To specify a language for the response information, include either the *Client-Accept-Language* or the *Accept-Language* fields in the request header. For both fields, specify a language value in accordance with [RFC 1766](#).

The *Client-Accept-Language* field is used by other components of IBM SPSS Collaboration and Deployment Services that interact with the Scoring Service. If your request includes both language fields, this field is evaluated before the *Accept-Language* field, which is the standard HTTP field for language specification.

For example, to create a response in German, include the following header field in your request:

```
Client-Accept-Language: de
```

If your request also includes the following header field:

```
Accept-Language: fr
```

The response will still be in German as the *Client-Accept-Language* field takes precedence. In this case, you would either need to change the value of *Client-Accept-Language* to *fr* or omit this field entirely to receive a response in French.

## Specifying a request body

For operations that transmit data to the server, such as POST, specify a request body in JavaScript Object Notation, or JSON, format.

For information on JSON formatting, see [“Receiving a response body” on page 4](#). For information about the specific JSON elements and objects used by the Scoring Service, see [Chapter 3, “JSON reference for the Scoring Service,” on page 25](#).

This sample POST request retrieves scoring output for a specified set of input values:

```
{
  "id": "config_1",
  "requestInputTable": [
    {
      "name": "Table 1",
      "requestInputRow": [
        {
          "input": [
            { "name": "Age", "value": "1" },
            { "name": "BP", "value": "1" },
            { "name": "Cholesterol", "value": "1" },
            { "name": "Drug", "value": "1" },
            { "name": "K", "value": "1" },
            { "name": "Na", "value": "1" },

```

```

    {
      "name": "Gender", "value": "1"
    },
    {
      "context": []
    }
  ]
}

```

## Receiving response headers

Requests return headers as part of the response.

The following table lists response header values.

Table 2. Response header values for GET requests	
Name	Value
Status Code	200 OK or an error code
Server	The name of the server processing the request
X-Powered-By	Identifies the technology underlying the application
Content-Type	The MIME type of the content in the response body. For example, for JSON, the value could be <i>application/json; charset=ISO-8859-1</i> .
Content-Length	Length of the response body in bytes
Date	Current date and time
Set-Cookie	Specifies an HTTP session cookie

## Receiving a response body

The response body contains the requested information in the format specified by the **Accept** field in the request header. For JSON, the body is typically an object or an array of objects.

The following sections provide basic formatting rules for JSON. These rules also apply to the [request body](#).

See <http://www.json.org> for a complete description of JSON. For information about the specific JSON elements and objects used by the Scoring Service, see [Chapter 3, “JSON reference for the Scoring Service,”](#) on page 25.

### Elements

An element consists of a name-value pair having the following structure:

```
"<name>": <value>
```

- *<name>* is a string that identifies the element
- *<value>* corresponds to the value for the specific element. The value may be a boolean, string, number, object, or array.

String values must be enclosed in quotation marks and may contain backslash escape characters. Numeric values are not enclosed in quotation marks. A boolean value is either true or false, and is not enclosed in quotation marks.

For example, the following *label* element corresponds to a string value of *LATEST*:

```
"label": "LATEST"
```



The following *value* element corresponds to a numeric value of 38.0:

```
"value":38.0
```

The following *isRequired* element corresponds to a boolean value of *true*:

```
"isRequired":true
```

## Objects

An object represents an unordered collection of elements. Objects have the following structure:

```
{<element1>, ... ,<elementN>}
```

- *<element#>* corresponds to a particular element in the object. Individual object elements are separated by commas.

For example, the following object consists of the elements *state*, *modelReference*, *configurationStatus*, and *id*:

```
{
  "state":"ACTIVE",
  "modelReference":{
    "resourcePath":"\\june\\multiple_input_double_updated.str",
    "label":"LATEST",
    "id":"09775272cf8ee6e5000001328016b69284dc"
  },
  "configurationStatus":{
    "message":"Started",
    "statusCode":"INFORMATION"
  },
  "id":"AC2"
}
```

The values for the *modelReference* and *configurationStatus* elements are also objects consisting of three and two elements.

## Arrays

An array represents an ordered collection of values, elements, objects, or other arrays. Arrays have the following structure:

```
[<entry1>, ... ,<entryN>]
```

- *<entry#>* corresponds to a particular entry in the array. Individual array entries are separated by commas.

For example, the value for the following *metadataOutputField* element is an array containing two objects:

```
"metadataOutputField":[
  {
    "categoricalValues":[],
    "isReturned":true,
    "type":"long",
    "name":"Age",
    "description":"Age"
  },
  {
    "categoricalValues":[],
    "isReturned":true,
    "type":"string",
    "name":"$0-Anomaly",
    "description":"$0-Anomaly"
  }
]
```

Each object in the array consists of five elements having values describing individual output fields. For instance, the first output field has a name of *Age* and is of type *long*. The second output field has a name of *\$0-Anomaly* and is of type *string*.

## Processing a response body

The content of the JSON information depends on the parser that is used to generate the JSON data. As a result, you might encounter subtle differences in the JSON information that is transmitted by the service, particularly regarding null or missing values.

For example, one parser might return an empty array if an element has no values. In the following JSON, the **categoricalValues** element has no values.

```
"metadataInputField": [
  {
    "categoricalValues": [],
    "isRequired": <boolean>,
    "type": "<string>",
    "name": "<string>",
    "description": "<string>"
  }
]
```

A different parser might omit the element entirely if it has no values. In the following JSON, the **categoricalValues** element is absent from the object.

```
"metadataInputField": [
  {
    "isRequired": <boolean>,
    "type": "<string>",
    "name": "<string>",
    "description": "<string>"
  }
]
```

Alternatively, a parser might include a null value if an element has no values. In the following JSON, the **categoricalValues** element has a null value.

```
"metadataInputField": [
  {
    "categoricalValues": null,
    "isRequired": <boolean>,
    "type": "<string>",
    "name": "<string>",
    "description": "<string>"
  }
]
```

To ensure your application processes the response correctly, review how your parser behaves. To make your application more robust, consider defensive programming approaches to avoid problems with null or missing values in the JSON data.

# Chapter 2. API reference for the Scoring Service

## Service resource

Score providers provide the Scoring Service with the internal processing instructions necessary for specific model types. For the service to be able to create a scoring configuration for a model, a score provider for that type of model must be available.

The provider registers itself with the service, indicating which MIME types it supports. Each provider has a unique name and identifier to distinguish it from other providers, and each is versioned separately. Providers available to the scoring service include:

- **SmartScore Score Provider**, for processing PMML files
- **Modeler Score Provider**, for processing IBM SPSS Modeler streams

## Service GET

Gets information about the available score providers.

### Defined in

[“Service resource” on page 7](#)

### Request

```
GET http://{server}:{port}/scoring/rest/service
```

The following variables should be replaced with values for your system.

- **{server}** corresponds to the server name or IP address for your IBM SPSS Collaboration and Deployment Services Repository
- **{port}** is the port number on which to access the IBM SPSS Collaboration and Deployment Services Repository

Table 3. Request header values	
Name	Value
Accept	Indicates the payload type to return to the client. Valid values include application/json, text/xml, and application/xml.
Authorization	Authentication string encoded using Base64
Client-Accept-Language	Tag defining the language for the response information. This field takes precedence over the Accept-Language field.
Accept-Language	Tag defining the language for the response information

The HTTP request body should be empty.

### Response

A successful request returns the following information:

- Status code 200

- Response body in the specified format containing the service representation for the request. A JSON response object has the following general structure:

```
{
  "version": "<string>",
  "scoreProviderDetails": [
    {
      "supportedMimeTypes": ["<string>"],
      "version": "<string>",
      "name": "<string>",
      "id": "<string>"
    }
  ]
}
```

See the topic [“The scoringServiceDetails object”](#) on [page 40](#) for more information.

An unsuccessful request returns a response code other than 200.

## Example

This request retrieves information about which scoring providers are installed.

```
GET http://cdssvr:80/scoring/rest/service
```

This is the JSON response object, indicating that there are two scoring providers installed.

```
{
  "version": "5.0.0.0.155",
  "scoreProviderDetails": [
    {
      "supportedMimeTypes": ["application/x-vnd.spss-clementine-stream"],
      "version": "1.0",
      "name": "Modeler Score Provider",
      "id": "091ed7cda16d295c000001327c563c4593de"
    },
    {
      "supportedMimeTypes": ["application/x-vnd.spss-pmml"],
      "version": "1.0",
      "name": "Score Provider - SmartScore",
      "id": "091ed7cd82a9085b000001327c118593a316"
    }
  ]
}
```

The response indicates that the Scoring Service is able to generate scores for PMML files and IBM SPSS Modeler streams.

## Configuration resource

Before a model can be used for scoring, supplemental information must be defined. Such information constitutes a **scoring configuration** for the model, and defines scoring parameters such as the following:

- Identification information for the configuration itself
- Identification information for the model used for scoring
- The data provider for the input
- Settings for logging
- The order of the input attributes
- Cache size used for scoring models

A single model may be used in a variety of scoring situations that require different scoring parameters. For example, scores may be based on a test data provider for internal purposes and on a different data provider for production usage. Alternatively, the information being logged as result of scoring may depend on the scoring situation. To allow a model to be used in differing scoring circumstances, any model may be associated with multiple scoring configurations.

Scoring configurations can be suspended to temporarily prevent the processing of score requests. A suspended configuration must be reactivated before it can be used to generate scores.

Typically, you create scoring configurations using IBM SPSS Deployment Manager. You use the Scoring Service to generate scores or report performance metrics for those configurations.

## Configuration GET

Gets information about the available scoring configurations.

### Defined in

[“Configuration resource” on page 8](#)

### Request

```
GET http://{server}:{port}/scoring/rest/configuration
```

The following variables should be replaced with values for your system.

- `{server}` corresponds to the server name or IP address for your IBM SPSS Collaboration and Deployment Services Repository
- `{port}` is the port number on which to access the IBM SPSS Collaboration and Deployment Services Repository

Table 4. Request header values	
Name	Value
Accept	Indicates the payload type to return to the client. Valid values include application/json, text/xml, and application/xml.
Authorization	Authentication string encoded using Base64
Client-Accept-Language	Tag defining the language for the response information. This field takes precedence over the Accept-Language field.
Accept-Language	Tag defining the language for the response information

The HTTP request body should be empty.

### Response

A successful request returns the following information:

- Status code 200
- Response body in the specified format containing the configuration representation for the request. A JSON response array has the following general structure:

```
[
  {
    "state": "<string>",
    "modelReference": {
      "resourcePath": "<string>",
      "label": "<string>",
      "id": "<string>"
    },
    "configurationStatus": {
      "message": "<string>",
      "statusCode": "<string>"
    },
    "id": "<string>"
  }
]
```

See the topic [“The configurationReference object” on page 25](#) for more information.

An unsuccessful request returns a response code other than 200.

## Example

This request retrieves information about the scoring configurations available on the server named `cdssvr`.

```
GET http://cdssvr:80/scoring/rest/configuration
```

This is the JSON response object, indicating that there are two scoring configurations.

```
[
  {
    "state": "ACTIVE",
    "modelReference": {
      "resourcePath": "\\zsi\\multiple_Input_Double_updated.str",
      "label": "LATEST",
      "id": "09775272cf8ee6e5000001328016b69284dc"
    },
    "configurationStatus": { "message": "Started", "statusCode": "INFORMATION" },
    "id": "AC2"
  },
  {
    "state": "ACTIVE",
    "modelReference": {
      "resourcePath": "\\zsi\\KMeans.xml",
      "label": "LATEST",
      "id": "091ed68980eebc90000001317470503d82fb"
    },
    "id": "SmartScore(RTDPD)"
  }
]
```

The first configuration has an identifier of `AC2`. The `modelReference` element indicates that the configuration uses the latest version of the IBM SPSS Modeler stream *multiple\_Input\_Double\_updated.str* for score requests. The `configurationStatus` element reports that the configuration has been started.

In contrast, the second configuration, which has an identifier of *SmartScore(RTDPD)*, uses the latest version of the PMML file *KMeans.xml* for score requests.

## Metadata resource

Metadata describes the input and output structure used by a scoring model.

Metadata for a model includes the following information:

- Name for each table of input fields
- Name and data type for every input field
- Name and data type for every output field

Use the metadata information to create your scoring requests in a structure required by the scoring model.

## Metadata GET

Gets information about the input and output fields used by a specific scoring configuration.

### Defined in

[“Metadata resource” on page 10](#)

### Request

```
GET http://{server}:{port}/scoring/rest/configuration/{config_id}/metadata
```

The following variables should be replaced with values for your system.

- `{server}` corresponds to the server name or IP address for your IBM SPSS Collaboration and Deployment Services Repository
- `{port}` is the port number on which to access the IBM SPSS Collaboration and Deployment Services Repository

- `{config_id}` is the identifier for the scoring configuration. You can obtain the identifiers for the available scoring configurations by using a configuration request. See the topic [“Configuration GET”](#) on page 9 for more information.

Table 5. Request header values	
Name	Value
Accept	Indicates the payload type to return to the client. Valid values include <code>application/json</code> , <code>text/xml</code> , and <code>application/xml</code> .
Authorization	Authentication string encoded using Base64
Client-Accept-Language	Tag defining the language for the response information. This field takes precedence over the <code>Accept-Language</code> field.
Accept-Language	Tag defining the language for the response information

The HTTP request body should be empty.

## Response

A successful request returns the following information:

- Status code 200
- Response body in the specified format containing the metadata representation for the request. A JSON response object has the following general structure:

```
{
  "metadataInputTable": [
    {
      "name": "<string>",
      "id": "<string>",
      "metadataInputField": [
        {
          "categoricalValues": [<string>],
          "isRequired": <boolean>,
          "type": "<string>",
          "name": "<string>",
          "description": "<string>"
        }
      ]
    }
  ],
  "metadataOutputField": [
    {
      "categoricalValues": [<string>],
      "isReturned": <boolean>,
      "type": "<string>",
      "name": "<string>",
      "description": "<string>"
    }
  ],
  "metadataContextTable": [
    {
      "table": "<string>",
      "contextColumn": [
        {
          "categoricalValues": [<string>],
          "type": "<string>",
          "name": "<string>",
          "description": "<string>"
        }
      ]
    }
  ]
}
```

See the topic [“The metadataResult object”](#) on page 27 for more information.

An unsuccessful request returns a response code other than 200.

## Example

This request retrieves the metadata for the Kmeans scoring configuration.

```
GET http://cdssvr:80/scoring/rest/configuration/KMeans/metadata
```

This is the JSON response object.

```
{
  "metadataInputTable": [
    {
      "name": "DRUG1n",
      "id": "id5JAYKB9IXD",
      "metadataInputField": [
        {
          "categoricalValues": [], "isRequired": true, "type": "long",
          "name": "Age", "description": "Age"
        },
        {
          "categoricalValues": [], "isRequired": true, "type": "string",
          "name": "BP", "description": "BP"
        },
        {
          "categoricalValues": [], "isRequired": true, "type": "string",
          "name": "Cholesterol", "description": "Cholesterol"
        },
        {
          "categoricalValues": [], "isRequired": true, "type": "string",
          "name": "Drug", "description": "Drug"
        },
        {
          "categoricalValues": [], "isRequired": true, "type": "double",
          "name": "K", "description": "K"
        },
        {
          "categoricalValues": [], "isRequired": true, "type": "double",
          "name": "Na", "description": "Na"
        },
        {
          "categoricalValues": [], "isRequired": true, "type": "string",
          "name": "Gender", "description": "Gender"
        }
      ]
    }
  ],
  "metadataOutputField": [
    {
      "categoricalValues": [], "isReturned": true, "type": "long",
      "name": "Age", "description": "Age"
    },
    {
      "categoricalValues": [], "isReturned": true, "type": "string",
      "name": "Sex", "description": "Sex"
    },
    {
      "categoricalValues": [], "isReturned": true, "type": "string",
      "name": "BP", "description": "BP"
    },
    {
      "categoricalValues": [], "isReturned": true, "type": "string",
      "name": "Cholesterol", "description": "Cholesterol"
    },
    {
      "categoricalValues": [], "isReturned": true, "type": "double",
      "name": "Na", "description": "Na"
    },
    {
      "categoricalValues": [], "isReturned": true, "type": "double",
      "name": "K", "description": "K"
    },
    {
      "categoricalValues": [], "isReturned": true, "type": "string",
      "name": "Drug", "description": "Drug"
    },
    {
      "categoricalValues": [], "isReturned": true, "type": "string",
      "name": "$0-Anomaly", "description": "$0-Anomaly"
    },
    {
      "categoricalValues": [], "isReturned": true, "type": "double",
      "name": "$0-AnomalyIndex", "description": "$0-AnomalyIndex"
    },
    {
      "categoricalValues": [], "isReturned": true, "type": "long",
      "name": "$0-PeerGroup", "description": "$0-PeerGroup"
    },
    {
      "categoricalValues": [], "isReturned": true, "type": "string",
      "name": "$0-Field-1", "description": "$0-Field-1"
    },
    {
      "categoricalValues": [], "isReturned": true, "type": "double",
      "name": "$0-FieldImpact-1", "description": "$0-FieldImpact-1"
    },
    {
      "categoricalValues": [], "isReturned": true, "type": "string",
      "name": "$0-Field-2", "description": "$0-Field-2"
    },
    {
      "categoricalValues": [], "isReturned": true, "type": "double",
      "name": "$0-FieldImpact-2", "description": "$0-FieldImpact-2"
    }
  ]
}
```



```

        "categoricalValues": [], "isReturned": true, "type": "string",
        "name": "$0-Field-3", "description": "$0-Field-3"
      },
      {
        "categoricalValues": [], "isReturned": true, "type": "double",
        "name": "$0-FieldImpact-3", "description": "$0-FieldImpact-3"
      }
    ],
    "metadataContextTable": []
  }
}

```

The `metadataInputTable` element indicates that the configuration expects score requests to include seven input values for a single table. The following list identifies the input fields and their corresponding data types:

- Age is of type long
- BP is of type string
- Cholesterol is of type string
- Drug is of type string
- K is of type double
- Na is of type double
- Gender is of type string

The `metadataOutputTable` object indicates that the configuration returns score responses that include all input values plus several additional output values containing the scoring results.

The empty array for the `metadataContextTable` object indicates that the configuration does not use any context data.

## Score resource

Applying a predictive model to a set of data can produce a variety of scores, such as predicted values, predicted probabilities, and other values based on that model. The type of score produced is referred to as the **scoring function**. The following scoring functions are available:

Scoring function	Description
<b>PREDICT</b>	<i>Returns the predicted value of the target variable.</i>
<b>STDDEV</b>	<i>Standard deviation.</i>
<b>PROBABILITY</b>	<i>Probability associated with a particular category of a target variable. Applies only to categorical variables. In the absence of the optional third parameter, <i>category</i>, this is the probability that the predicted category is the correct one for the target variable. If a particular category is specified, then this is the probability that the specified category is the correct one for the target variable.</i>
<b>CONFIDENCE</b>	<i>A probability measure associated with the predicted value of a categorical target variable. Applies only to categorical variables.</i>
<b>NODEID</b>	<i>The terminal node number. Applies only to tree models.</i>
<b>CUMHAZARD</b>	<i>Cumulative hazard value. Applies only to Cox regression models.</i>
<b>NEIGHBOR</b>	<i>The ID of the kth nearest neighbor. Applies only to nearest neighbor models. In the absence of the optional third parameter, k, this is the ID of the nearest neighbor. The ID is the value of the case labels variable, if supplied, and otherwise the case number.</i>
<b>DISTANCE</b>	<i>The distance to the kth nearest neighbor. Applies only to nearest neighbor models. In the absence of the optional third parameter, k, this is the distance to the nearest neighbor. Depending on the model, either Euclidean or City Block distance will be used.</i>

The following table lists the set of scoring functions available for each type of model that supports scoring. The function type denoted as PROBABILITY (category) refers to specification of a particular category (the optional third parameter) for the PROBABILITY function.

<i>Table 6. Supported functions by model type</i>	
<b>Model type</b>	<b>Supported functions</b>
Tree (categorical target)	PREDICT, PROBABILITY, PROBABILITY (category), CONFIDENCE, NODEID
Tree (scale target)	PREDICT, NODEID, STDDEV
Boosted Tree (C5.0)	PREDICT, CONFIDENCE
Linear Regression	PREDICT, STDDEV
Automatic Linear Models	PREDICT
Binary Logistic Regression	PREDICT, PROBABILITY, PROBABILITY (category), CONFIDENCE
Conditional Logistic Regression	PREDICT
Multinomial Logistic Regression	PREDICT, PROBABILITY, PROBABILITY (category), CONFIDENCE
General Linear Model	PREDICT, STDDEV
Discriminant	PREDICT, PROBABILITY, PROBABILITY (category)
TwoStep Cluster	PREDICT
K-Means Cluster	PREDICT
Kohonen	PREDICT
Neural Net (categorical target)	PREDICT, PROBABILITY, PROBABILITY (category), CONFIDENCE
Neural Net (scale target)	PREDICT
Naive Bayes	PREDICT, PROBABILITY, PROBABILITY (category), CONFIDENCE
Anomaly Detection	PREDICT
Ruleset	PREDICT, CONFIDENCE
Generalized Linear Model (categorical target)	PREDICT, PROBABILITY, PROBABILITY (category), CONFIDENCE
Generalized Linear Model (scale target)	PREDICT, STDDEV
Generalized Linear Mixed Model (categorical target)	PREDICT, PROBABILITY, PROBABILITY (category), CONFIDENCE

Table 6. Supported functions by model type (continued)	
Model type	Supported functions
Generalized Linear Mixed Model (scale target)	PREDICT
Ordinal Multinomial Regression	PREDICT, PROBABILITY, PROBABILITY (category), CONFIDENCE
Cox Regression	PREDICT, CUMHAZARD
Nearest Neighbor (scale target)	PREDICT, NEIGHBOR, NEIGHBOR(K), DISTANCE, DISTANCE(K)
Nearest Neighbor (categorical target)	PREDICT, PROBABILITY, PROBABILITY (category), CONFIDENCE, NEIGHBOR, NEIGHBOR(K), DISTANCE, DISTANCE(K)
Bayesian Network	PREDICT, PROBABILITY, PROBABILITY (category), CONFIDENCE
Support Vector Machine (categorical target)	PREDICT, PROBABILITY, PROBABILITY (category), CONFIDENCE
Support Vector Machine (scale target)	PREDICT, STDDEV

- For the Binary Logistic Regression, Multinomial Logistic Regression, and Naive Bayes models, the value returned by the CONFIDENCE function is identical to that returned by the PROBABILITY function.
- For the K-Means model, the value returned by the CONFIDENCE function is the least distance.
- For tree and ruleset models, the confidence can be interpreted as an adjusted probability of the predicted category and is always less than the value given by PROBABILITY. For these models, the confidence value is more reliable than the value given by PROBABILITY.
- For neural network models, the confidence provides a measure of whether the predicted category is much more likely than the second-best predicted category.
- For Ordinal Multinomial Regression and Generalized Linear Model, the PROBABILITY function is supported when the target variable is binary.
- For nearest neighbor models without a target variable, the available functions are NEIGHBOR and DISTANCE.

## Score POST

Retrieves one or more scores for a specific scoring configuration.

### Defined in

[“Score resource” on page 13](#)

### Request

```
POST http://{server}:{port}/scoring/rest/configuration/{config_id}/score
```

The following variables should be replaced with values for your system.

- `{server}` corresponds to the server name or IP address for your IBM SPSS Collaboration and Deployment Services Repository

- *{port}* is the port number on which to access the IBM SPSS Collaboration and Deployment Services Repository
- *{config\_id}* is the identifier for the scoring configuration. You can obtain the identifiers for the available scoring configurations by using a configuration request. See the topic [“Configuration GET”](#) on page 9 for more information.

Table 7. Request header values	
Name	Value
Content-Type	Indicates the payload type of the score request that is sent from the client to the server. Valid values include application/json, text/xml, and application/xml.
Accept	Indicates the payload type to return to the client. Valid values include application/json, text/xml, and application/xml.
Authorization	Authentication string encoded using Base64
Client-Accept-Language	Tag defining the language for the response information. This field takes precedence over the Accept-Language field.
Accept-Language	Tag defining the language for the response information

The HTTP request body should contain the input data for the score request. A JSON request object has the following general structure:

```
{
  "id": "<string>",
  "requestInputTable": [
    {
      "name": "<string>",
      "requestInputRow": [
        {
          "input": [
            {
              "name": "<string>",
              "value": "<string>"
            }
          ]
        }
      ]
    }
  ],
  "context": [
    {
      "name": "<string>",
      "columnName": ["<string>"],
      "rowValues": [
        {
          "value": [
            {
              "value": "<string>"
            }
          ]
        }
      ]
    }
  ]
}
```

See the topic [“The scoreRequest object”](#) on page 32 for more information.

## Response

A successful request returns the following information:

- Status code 200

- Response body in the specified format containing the score information for the request. A JSON response object has the following general structure:

```
{
  "id": "<string>",
  "columnNames": {
    "name": "<string>"
  },
  "rowValues": [
    {
      "reserved": "<string>"
    },
    {
      "value": [
        {
          "value": "<string>"
        }
      ]
    }
  ]
},
"returnedRequestInputTable": [
  {
    "id": "<string>",
    "name": "<string>",
    "returnedRequestInputRow": [
      {
        "returnedRequestInputValue": [
          {
            "name": "<string>",
            "type": "<string>",
            "value": "<string>"
          }
        ]
      }
    ]
  }
]
},
"returnedDPDOutputTable": [
  {
    "id": "<string>",
    "name": "<string>",
    "returnedDPDOutputRow": [
      {
        "returnedDPDOutputValue": [
          {
            "name": "<string>",
            "type": "<string>",
            "value": "<string>"
          }
        ]
      }
    ]
  }
]
}
]
```

See the topic [“The scoreResult object”](#) on page 36 for more information.

An unsuccessful request returns a response code other than 200.

## Example

This request retrieves a score for the *config\_1* scoring configuration.

```
GET http://cdssvr:80/scoring/rest/configuration/config_1/metric
```

This is the JSON request body, which includes a single table consisting of one row. This row specifies the values for the seven model inputs for the configuration.

```
{
  "id": "config_1",
  "requestInputTable": [
    {
      "name": "Table 1",
      "requestInputRow": [
        {
          "input": [
            { "name": "Age", "value": "1" },
            { "name": "BP", "value": "1" },
            { "name": "Cholesterol", "value": "1" },
            { "name": "Drug", "value": "1" },
            { "name": "K", "value": "1" },
            { "name": "Na", "value": "1" },
            { "name": "Gender", "value": "1" }
          ]
        }
      ]
    }
  ]
},
"context": []
}
```

This is the JSON response object. The `columnNames` element indicates that the configuration returned scoring function values for *Prediction* and *Confidence*. The `rowValues` element contains a single object that reports the actual scoring values of 2 and 1.34153.

```
{
  "id": "954d9db3-049f-464c-b218-eadd628cf349",
  "columnNames": [
    {
      "name": "Prediction", "Confidence"
    }
  ],
  "rowValues": [
    {
      "reserved": null,
      "value": [
        { "value": "2" },
        { "value": "1.3415297614991626" }
      ]
    }
  ],
  "returnedRequestInputTable": [
    {
      "name": "Table 1",
      "id": "Table 1",
      "returnedRequestInputRow": [
        {
          "returnedRequestInputValue": [
            { "name": "Age", "type": "double", "value": "1" },
            { "name": "BP", "type": "string", "value": "1" },
            { "name": "Cholesterol", "type": "string", "value": "1" },
            { "name": "Drug", "type": "string", "value": "1" },
            { "name": "K", "type": "double", "value": "1" },
            { "name": "Na", "type": "double", "value": "1" },
            { "name": "Gender", "type": "string", "value": "1" }
          ]
        }
      ]
    }
  ],
  "returnedDPDOutputTable": []
}
```

The `returnedRequestInputTable` element contains the input values that resulted in these scores.

## Metric item resource

Scoring metrics are measurements that reflect the performance of a scoring configuration or the service itself. Available metric items include the following:

- **Service Scores.** Total number of scores produced by the service.
- **Service Uptime.** Amount of time, measured in seconds, that the service has been running.
- **Average Latency.** Average amount of time, measured in milliseconds, between the request for a score and the generation of the score.
- **Minimum Latency.** Smallest amount of time, measured in milliseconds, between the request for a score and the generation of the score.
- **Maximum Latency.** Largest amount of time, measured in milliseconds, between the request for a score and the generation of the score.
- **Score Data Initialization Time.** Amount of time, measured in milliseconds, that the data service takes to be initialized for a score request.
- **Average Data Initialization Time.** Average amount of time, measured in milliseconds, that the data service takes to be initialized for a score request.
- **Minimum Data Initialization Time.** Smallest amount of time, measured in milliseconds, that the data service takes to be initialized for a score request.
- **Maximum Data Initialization Time.** Largest amount of time, measured in milliseconds, that the data service takes to be initialized for a score request.
- **Score Data Access Time.** Amount of time, measured in milliseconds, that the data service takes to access the data.
- **Average Data Access Time.** Average amount of time, measured in milliseconds, that the data service takes to access the data.
- **Minimum Data Access Time.** Smallest amount of time, measured in milliseconds, that the data service takes to access the data.
- **Maximum Data Access Time.** Largest amount of time, measured in milliseconds, that the data service takes to access the data.

- **Score Computation Wait Time.** Amount of time, measured in milliseconds, that the score provider worker spends waiting for the data service.
- **Average Computation Wait Time.** Average amount of time, measured in milliseconds, that the score provider worker spends waiting for the data service.
- **Minimum Computation Wait Time.** Smallest amount of time, measured in milliseconds, that the score provider worker spends waiting for the data service.
- **Maximum Computation Wait Time.** Largest amount of time, measured in milliseconds, that the score provider worker spends waiting for the data service.
- **Score Computation Time.** Amount of time, measured in milliseconds, that the score provider worker spends computing the score.
- **Average Computation Time.** Average amount of time, measured in milliseconds, that the score provider worker spends computing the score.
- **Minimum Computation Time.** Smallest amount of time, measured in milliseconds, that the score provider worker spends computing the score.
- **Maximum Computation Time.** Largest amount of time, measured in milliseconds, that the score provider worker spends computing the score.
- **Average Log Serialization Time.** Average amount of time, measured in milliseconds, to create a log entry in XML format.
- **Minimum Log Serialization Time.** Smallest amount of time, measured in milliseconds, to create a log entry in XML format.
- **Maximum Log Serialization Time.** Largest amount of time, measured in milliseconds, to create a log entry in XML format.
- **Average Log Queue Time.** Average amount of time, measured in milliseconds, to place the XML log data on to the JMS queue.
- **Minimum Log Queue Time.** Smallest amount of time, measured in milliseconds, to place the XML log data on to the JMS queue.
- **Maximum Log Queue Time.** Largest amount of time, measured in milliseconds, to place the XML log data on to the JMS queue.
- **Configuration Scores.** Total number of scores produced by a specific scoring configuration.
- **Score Elapsed Time.** Amount of time, measured in milliseconds, since the previous score generation.
- **Configuration Uptime.** Amount of time, measured in seconds, that the scoring configuration has been available for scoring.
- **Cache Hits.** Number of successful attempts to retrieve data from the memory cache for a scoring configuration.
- **Cache Misses.** Number of failed attempts to retrieve data from the memory cache for a scoring configuration. Each failed attempt results in a new service call to retrieve the necessary data.

The scale for a particular metric item determines the number of decimal points included in the measurement.

## Metric item GET

Retrieves a list of available scoring metric items for a specific scoring configuration.

### Defined in

[“Metric item resource” on page 18](#)

### Request

```
GET http://{server}:{port}/scoring/rest/configuration/{config_id}/metric
```

The following variables should be replaced with values for your system.

- `{server}` corresponds to the server name or IP address for your IBM SPSS Collaboration and Deployment Services Repository
- `{port}` is the port number on which to access the IBM SPSS Collaboration and Deployment Services Repository
- `{config_id}` is the identifier for the scoring configuration. You can obtain the identifiers for the available scoring configurations by using a configuration request. See the topic [“Configuration GET” on page 9](#) for more information.

Table 8. Request header values	
Name	Value
Accept	Indicates the payload type to return to the client. Valid values include <code>application/json</code> , <code>text/xml</code> , and <code>application/xml</code> .
Authorization	Authentication string encoded using Base64
Client-Accept-Language	Tag defining the language for the response information. This field takes precedence over the <code>Accept-Language</code> field.
Accept-Language	Tag defining the language for the response information

The HTTP request body should be empty.

## Response

A successful request returns the following information:

- Status code 200
- Response body in the specified format containing the metric item information for the request. A JSON response array has the following general structure:

```
[
  {
    "unit": "<string>",
    "scale": <number>,
    "id": "<string>",
    "name": "<string>"
  }
]
```

See the topic [“The metricItem object” on page 31](#) for more information.

An unsuccessful request returns a response code other than 200.

## Example

This request retrieves information about all available metrics for the Kmeans scoring configuration.

```
GET http://cdssvr:80/scoring/rest/configuration/KMeans/metric
```

This is the JSON response array. Each object in the array corresponds to a separate metric.

```
[
  {
    "unit": "milliseconds", "scale": 3,
    "id": "CONFIGURATION_COMPUTATION_WAIT_TIME_MINIMUM", "name": "Minimum Computation Wait Time"
  },
  {
    "unit": "hits", "scale": 0,
    "id": "CONFIGURATION_CACHE_HITS", "name": "Cache Hits"
  },
  {
    "unit": "scores", "scale": 0,
    "id": "SERVICE_TOTAL_SCORES", "name": "Service Scores"
  }
]
```



```

    },
    {
      "unit": "milliseconds", "scale": 3,
      "id": "CONFIGURATION_DATA_INIT_TIME_AVERAGE", "name": "Average Data Initialization Time"
    },
    {
      "unit": "milliseconds", "scale": 3,
      "id": "CONFIGURATION_LOG_QUEUE_TIME_MINIMUM", "name": "Minimum Log Queue Time"
    },
    {
      "unit": "milliseconds", "scale": 3,
      "id": "CONFIGURATION_DATA_INIT_TIME_MAXIMUM", "name": "Maximum Data Initialization Time"
    },
    {
      "unit": "milliseconds", "scale": 3,
      "id": "CONFIGURATION_RESPONSE_TIME_MINIMUM", "name": "Minimum Latency"
    },
    {
      "unit": "seconds", "scale": 0,
      "id": "SERVICE_UPTIME", "name": "Service Uptime"
    },
    {
      "unit": "milliseconds", "scale": 3,
      "id": "CONFIGURATION_COMPUTATION_WAIT_TIME_AVERAGE", "name": "Average Computation Wait Time"
    },
    {
      "unit": "milliseconds", "scale": 3,
      "id": "CONFIGURATION_COMPUTATION_WAIT_TIME_MAXIMUM", "name": "Maximum Computation Wait Time"
    },
    {
      "unit": "milliseconds", "scale": 3,
      "id": "CONFIGURATION_LOG_QUEUE_TIME_AVERAGE", "name": "Average Log Queue Time"
    },
    {
      "unit": "milliseconds", "scale": 3,
      "id": "CONFIGURATION_COMPUTATION_TIME_MINIMUM", "name": "Minimum Computation Time"
    },
    {
      "unit": "milliseconds", "scale": 3,
      "id": "CONFIGURATION_LOG_SERIALIZE_TIME_MINIMUM", "name": "Minimum Log Serialization Time"
    },
    {
      "unit": "milliseconds", "scale": 3,
      "id": "CONFIGURATION_RESPONSE_TIME_AVERAGE", "name": "Average Latency"
    },
    {
      "unit": "milliseconds", "scale": 3,
      "id": "CONFIGURATION_LOG_QUEUE_TIME_MAXIMUM", "name": "Maximum Log Queue Time"
    },
    {
      "unit": "milliseconds", "scale": 3,
      "id": "CONFIGURATION_RESPONSE_TIME_MAXIMUM", "name": "Maximum Latency"
    },
    {
      "unit": "scores", "scale": 0,
      "id": "CONFIGURATION_TOTAL_SCORES", "name": "Configuration Scores"
    },
    {
      "unit": "milliseconds", "scale": 3,
      "id": "CONFIGURATION_DATA_ACCESS_TIME_MINIMUM", "name": "Minimum Data Access Time"
    },
    {
      "unit": "milliseconds", "scale": 3,
      "id": "CONFIGURATION_COMPUTATION_TIME_AVERAGE", "name": "Average Computation Time"
    },
    {
      "unit": "milliseconds", "scale": 3,
      "id": "CONFIGURATION_LOG_SERIALIZE_TIME_AVERAGE", "name": "Average Log Serialization Time"
    },
    {
      "unit": "milliseconds", "scale": 3,
      "id": "CONFIGURATION_COMPUTATION_TIME_MAXIMUM", "name": "Maximum Computation Time"
    },
    {
      "unit": "misses", "scale": 0,
      "id": "CONFIGURATION_CACHE_MISSES", "name": "Cache Misses"
    },
    {
      "unit": "milliseconds", "scale": 3,
      "id": "CONFIGURATION_LOG_SERIALIZE_TIME_MAXIMUM", "name": "Maximum Log Serialization Time"
    },
    {
      "unit": "seconds", "scale": 0,
      "id": "CONFIGURATION_UPTIME", "name": "Configuration Uptime"
    },
    {
      "unit": "milliseconds", "scale": 3,
      "id": "CONFIGURATION_DATA_ACCESS_TIME_AVERAGE", "name": "Average Data Access Time"
    },
    {
      "unit": "milliseconds", "scale": 3,
      "id": "CONFIGURATION_DATA_ACCESS_TIME_MAXIMUM", "name": "Maximum Data Access Time"
    },
    {
      "unit": "milliseconds", "scale": 3,
      "id": "CONFIGURATION_DATA_INIT_TIME_MINIMUM", "name": "Minimum Data Initialization Time"
    }
  ]
}

```

Use the [“Metric value GET” on page 22](#) method to retrieve the value for a specific metric item.

## Metric value resource

A metric value corresponds to actual value for a specific metric item. The identifier for any metric item can be used to retrieve the value for that metric.

### Metric value GET

Retrieves the value for a specific scoring configuration metric item.

#### Defined in

[“Metric value resource” on page 22](#)

#### Request

```
GET http://{server}:{port}/scoring/rest/configuration/{config_id}/metric/{name}
```

The following variables should be replaced with values for your system.

- *{server}* corresponds to the server name or IP address for your IBM SPSS Collaboration and Deployment Services Repository
- *{port}* is the port number on which to access the IBM SPSS Collaboration and Deployment Services Repository
- *{config\_id}* is the identifier for the scoring configuration. You can obtain the identifiers for the available scoring configurations by using a configuration request. See the topic [“Configuration GET” on page 9](#) for more information.
- *{name}* identifies the metric item whose value is being retrieved. You can obtain a list of available metric items by using a metric item request. See the topic [“Metric item GET” on page 19](#) for more information.

Table 9. Request header values	
Name	Value
Accept	Indicates the payload type to return to the client. Valid values include application/json, text/xml, and application/xml.
Authorization	Authentication string encoded using Base64
Client-Accept-Language	Tag defining the language for the response information. This field takes precedence over the Accept-Language field.
Accept-Language	Tag defining the language for the response information

The HTTP request body should be empty.

#### Response

A successful request returns the following information:

- Status code 200
- Response body in the specified format containing the metric value for the request. A JSON response object has the following general structure:

```
{
  "value":<number>
}
```

See the topic [“The metricValue object” on page 31](#) for more information.

An unsuccessful request returns a response code other than 200.

## Example

This request retrieves the value of the `CONFIGURATION_UPTIME` metric for the KMeans scoring configuration.

```
GET http://cdssvr:80/scoring/rest/configuration/KMeans/metric/CONFIGURATION_UPTIME
```

This is the JSON response object, indicating that the scoring configuration has been available for scoring for 38 seconds.

```
{  
  "value":38.0  
}
```



## Chapter 3. JSON reference for the Scoring Service

Describes all JSON objects used in the Scoring Service REST API.

### The configurationReference object

Describes a scoring configuration available in the IBM SPSS Collaboration and Deployment Services Repository. This object contains a reference to the model on which the configuration is based, as well as the identifier of the scoring configuration itself.

The “[Configuration GET](#)” on [page 9](#) method returns an array of configurationReference objects in the response body.

Table 10. Child elements for configurationReference

Element name	Value type	Description
id	string	Non-localized identifier for the configuration. Use the id value in URL requests to identify a specific configuration.
state	string	Indicates the current status of the configuration. A state value of <i>ACTIVE</i> indicates the configuration is consuming resources and can process incoming scoring requests. In contrast, a state value of <i>SUSPENDED</i> indicates the configuration is not consuming resources and cannot process any scoring requests.
<a href="#">modelReference</a>	object	Identifies the model used by a scoring configuration.
<a href="#">configurationStatus</a>	object	Reports the status of a scoring configuration.

### Example

The following array includes two configurationReference objects. The first has an identifier of AC2 and uses latest version of the file *multiple\_Input\_Double\_updated.str* for scoring requests. The second has an identifier of *withRTDPD* and uses the version of the file *MultipleSourceNodes.str* that is labeled *PRODUCTION*. The configurationStatus object for the *withRTDPD* configuration indicates that the configuration is unable to process any scoring requests due to a problem with the specified data provider.

```
[
  {
    "state": "ACTIVE",
    "modelReference": {
      "resourcePath": "\\june\\multiple_Input_Double_updated.str",
      "label": "LATEST",
      "id": "09775272cf8ee6e5000001328016b69284dc"
    },
    "configurationStatus": {
      "message": "Started",
      "statusCode": "INFORMATION"
    },
    "id": "AC2"
  },
  {
    "state": "ACTIVE",
    "modelReference": {
      "resourcePath": "\\july\\MultipleSourceNodes.str",
      "label": "PRODUCTION",
```

```

    "id": "091ed68980eebc90000001317470503d84a5"
  },
  "id": "withRTDPD"
}
]

```

## The modelReference element

Provides all of the information necessary to locate a specific version of a model file in the IBM SPSS Collaboration and Deployment Services Repository.

Table 11. Child elements for modelReference		
Element name	Value type	Description
id	string	Non-localized identifier for the scoring model
label	string	The label corresponding to the version of the model file
resourcePath	string	Full path to the file in the content repository

### Example

The following modelReference element corresponds to the latest version of the file *multiple\_Input\_Double\_updated.str* in the *june* folder. The path includes the backslash (\) escape character before each slash (/) to optimize client processing.

```

"modelReference": {
  "resourcePath": "\june\multiple_Input_Double_updated.str",
  "label": "LATEST",
  "id": "09775272cf8ee6e5000001328016b69284dc"
}

```

## The configurationStatus element

Provides information about the current status of a scoring configuration.

Table 12. Child elements for configurationStatus		
Element name	Value type	Description
message	string	Describes the status of the configuration.
statusCode	string	<p>Indicates the type of message. Valid values include the following strings:</p> <ul style="list-style-type: none"> <li><b>INFORMATION.</b> The message is informational, describing the current status of the configuration in the system.</li> <li><b>WARNING.</b> A problem exists that may affect the configuration results.</li> <li><b>ERROR.</b> A problem exists that prevents the configuration from processing requests.</li> </ul>

## Example

The following `configurationStatus` element indicates that the configuration has started and is available for processing scoring requests.

```
"configurationStatus":{
  "message": "Started",
  "statusCode": "INFORMATION"
}
```

## The metadataResult object

Describes the input and output fields used by a scoring configuration.

The “[Metadata GET](#)” on [page 10](#) method returns the `metadataResult` object in the response body.

Table 13. Child elements for metadataResult		
Element name	Value type	Description
<a href="#">metadataInputTable</a>	object array	The input tables for a scoring configuration
<a href="#">metadataContextTable</a>	object array	The context tables for a scoring configuration
<a href="#">metadataOutputField</a>	object array	The output fields for a scoring configuration

## Example

The following `metadataResult` object contains one input table, *DRUG*, consisting of three input fields. A scoring request returns four output fields. The empty `metadataContextTable` object indicates that the configuration does not use any context data.

```
{
  "metadataInputTable": [
    {
      "name": "DRUG",
      "id": "id5JAYKBB9IXD",
      "metadataInputField": [
        {
          "categoricalValues": [], "isRequired": true, "type": "long",
          "name": "Age", "description": "Age"
        },
        {
          "categoricalValues": [], "isRequired": true, "type": "string",
          "name": "BP", "description": "BP"
        },
        {
          "categoricalValues": [], "isRequired": true, "type": "string",
          "name": "Cholesterol", "description": "Cholesterol"
        }
      ]
    }
  ],
  "metadataOutputField": [
    {
      "categoricalValues": [], "isReturned": true, "type": "string",
      "name": "BP", "description": "BP"
    },
    {
      "categoricalValues": [], "isReturned": true, "type": "string",
      "name": "Cholesterol", "description": "Cholesterol"
    },
    {
      "categoricalValues": [], "isReturned": true, "type": "string",
      "name": "$0-Anomaly", "description": "$0-Anomaly"
    },
    {
      "categoricalValues": [], "isReturned": true, "type": "double",
      "name": "$0-AnomalyIndex", "description": "$0-AnomalyIndex"
    }
  ],
  "metadataContextTable": []
}
```

## The metadataInputTable element

Describes an input table for a scoring configuration.

Table 14. Child elements for metadataInputTable

Element name	Value type	Description
id	string	Non-localized identifier for the input table
name	string	Name, possibly localized, for the input table
<a href="#">metadataInputField</a>	object array	The input fields used for scoring

### Example

The following metadataInputTable element describes an input table named *DRUG*. The table consists of the input fields *Age*, *BP*, and *Cholesterol*.

```
"metadataInputTable": [
  {
    "name": "DRUG",
    "id": "id5JAYKB89IXD",
    "metadataInputField": [
      {
        "categoricalValues": [], "isRequired": true, "type": "long",
        "name": "Age", "description": "Age"
      },
      {
        "categoricalValues": [], "isRequired": true, "type": "string",
        "name": "BP", "description": "BP"
      },
      {
        "categoricalValues": [], "isRequired": true, "type": "string",
        "name": "Cholesterol", "description": "Cholesterol"
      }
    ]
  }
]
```

## The metadataInputField element

Describes the scoring input fields for a model. Each object in the array corresponds to an input field.

The objects in this array come directly from the model and all fields are required.

Table 15. Child elements for metadataInputField

Element name	Value type	Description
description	string	Optional description of the field
isRequired	boolean	Indicates whether or not a value for the field is required for scoring requests
name	string	Name of the field



Table 15. Child elements for metadataInputField (continued)		
Element name	Value type	Description
type	string	Data type of the field. <ul style="list-style-type: none"> <li>• boolean</li> <li>• date</li> <li>• daytime</li> <li>• decimal</li> <li>• double</li> <li>• float</li> <li>• integer</li> <li>• long</li> <li>• string</li> <li>• timestamp</li> </ul>
categoricalValues	string array	Set of expected values, if any, for a categorical field

## Example

The following metadataInputField element consists of an array of objects corresponding to the three fields in the table. The first input field, *Age*, has a type of *long*. The other two fields, *BP* and *Cholesterol*, are both of the *string* type. Values for all three fields are required in scoring requests.

```
"metadataInputField": [
  {
    "categoricalValues": [], "isRequired": true, "type": "long",
    "name": "Age", "description": "Age"
  },
  {
    "categoricalValues": [], "isRequired": true, "type": "string",
    "name": "BP", "description": "BP"
  },
  {
    "categoricalValues": [], "isRequired": true, "type": "string",
    "name": "Cholesterol", "description": "Cholesterol"
  }
]
```

## The metadataContextTable element

Describes a context table for a scoring configuration.

Table 16. Child elements for metadataContextTable		
Element name	Value type	Description
table	string	Name for the context table
<a href="#">contextColumn</a>	object array	The context data columns for the context table

## The contextColumn element

Describes the context data columns for a context table.

Table 17. Child elements for contextColumn		
Element name	Value type	Description
description	string	Optional description of the field
name	string	Name of the field

Table 17. Child elements for contextColumn (continued)

Element name	Value type	Description
type	string	Data type of the field. <ul style="list-style-type: none"> <li>• boolean</li> <li>• date</li> <li>• daytime</li> <li>• decimal</li> <li>• double</li> <li>• float</li> <li>• integer</li> <li>• long</li> <li>• string</li> <li>• timestamp</li> </ul>
categoricalValues	string array	Set of expected values, if any, for a categorical field

## The metadataOutputField element

Describes the output fields for a scoring configuration. Each object in this array corresponds to an output field. The model definition is directly responsible for the objects in this array.

Table 18. Child elements for metadataOutputField

Element name	Value type	Description
description	string	Optional description of the field
isReturned	boolean	Indicates if the output is returned in a score request. A true value is used if the output is returned in a score request, false otherwise. If this value is not present, the output will be returned.
name	string	Name of the field
type	string	Data type of the field. <ul style="list-style-type: none"> <li>• boolean</li> <li>• date</li> <li>• daytime</li> <li>• decimal</li> <li>• double</li> <li>• float</li> <li>• integer</li> <li>• long</li> <li>• string</li> <li>• timestamp</li> </ul>
categoricalValues	string array	Set of expected values, if any, for a categorical field

## Example

The following `metadataOutputField` element consists of an array of objects corresponding to the fields returned as output from a scoring request. The first field `Age`, has a type of *long*. The other field, `$O-Anomaly`, is of the *string* type.

```
"metadataOutputField": [
  {
    "categoricalValues": [], "isReturned": true, "type": "long",
    "name": "Age", "description": "Age"
  },
  {
    "categoricalValues": [], "isReturned": true, "type": "string",
    "name": "$O-Anomaly", "description": "$O-Anomaly"
  }
]
```

## The metricItem object

Identifies all performance measurements available for a scoring configuration. Each object in this array corresponds to a performance metric.

You can retrieve the value for a specific metric by supplying the metric identifier in a request URL. See the topic [“Metric value GET” on page 22](#) for more information.

The [“Metric item GET” on page 19](#) method returns the `metricItem` object in the response body.

Table 19. Child elements for <code>metricItem</code>		
Element name	Value type	Description
id	string	Non-localized identifier for the item
name	string	Name, possibly localized, for the item
scale	number	Identifies the number of digits to the right of the decimal point for the item value
unit	string	Unit of measurement for the item, such as milliseconds

## Example

The following `metricItem` object corresponds to the *Service Scores* metric for a configuration. The *unit* property indicates the metric is measured in *scores*. The *scale* property reports that the value of this metric has 0 decimal places. You can retrieve the current value of this metric by including the *id* value, `SERVICE_TOTAL_SCORES`, in a request URL.

```
{
  "unit": "scores",
  "scale": 0,
  "id": "SERVICE_TOTAL_SCORES",
  "name": "Service Scores"
}
```

## The metricValue object

Reports the current value for a performance metric.

See the topic [“The metricItem object” on page 31](#) for more information.

The [“Metric value GET” on page 22](#) method returns the `metricValue` object in the response body.

Table 20. Child elements for metricValue

Element name	Value type	Description
value	number	The value for a metric item

## Example

The value element of the following metricValue object indicates the current value of the requested metric item is 38.

```
{
  "value":38.0
}
```

## The scoreRequest object

Represents a request for a score as an object containing the input values for a scoring model.

You can obtain the structure for the input tables by using the “Metadata GET” on page 10 method.

The “Score POST” on page 15 method uses the scoreResult object in the request body.

Table 21. Child elements for scoreRequest

Element name	Value type	Description
id	string	Identifier for the scoring configuration being used to generate scores
<a href="#">requestInputTable</a>	object array	Input tables for the scoring model
<a href="#">context</a>	object array	Context tables containing indirect inputs for the scoring model

## Example

The following object corresponds to a scoring request for the *config\_1* scoring configuration. The request includes one table named *Table 1* that contains a single input row.

```
{
  "id": "config_1",
  "requestInputTable": [
    {
      "name": "Table 1",
      "requestInputRow": [
        {
          "input": [
            { "name": "Age", "value": "1" },
            { "name": "BP", "value": "1" },
            { "name": "Cholesterol", "value": "1" },
            { "name": "Drug", "value": "1" },
            { "name": "K", "value": "1" },
            { "name": "Na", "value": "1" },
            { "name": "Gender", "value": "1" }
          ]
        }
      ]
    }
  ],
  "context": []
}
```

## The requestInputTable element

Describes the input tables used in a score request. The value for this element is an object array in which each object represents an input table.

Table 22. Child elements for requestInputTable		
Element name	Value type	Description
name	string	Name, possibly localized, for the input table
<a href="#">requestInputRow</a>	element array	One or more rows of input data

### Example

The value for the following requestInputTable element corresponds to an array containing one object. That object represents a table named *Table 1* that contains a single input row consisting of the values for seven input fields.

```
"requestInputTable": [
  {
    "name": "Table 1",
    "requestInputRow": [
      {
        "input": [
          { "name": "Age", "value": "1" },
          { "name": "BP", "value": "1" },
          { "name": "Cholesterol", "value": "1" },
          { "name": "Drug", "value": "1" },
          { "name": "K", "value": "1" },
          { "name": "Na", "value": "1" },
          { "name": "Gender", "value": "1" }
        ]
      }
    ]
  }
]
```

If the model required data from two input tables, the array would contain multiple objects. For example, the following element represents two tables.

```
"requestInputTable": [
  {
    "name": "Table 1",
    "requestInputRow": [
      {
        "input": [
          { "name": "Age", "value": "1" },
          { "name": "BP", "value": "1" },
          { "name": "Cholesterol", "value": "1" }
        ]
      }
    ]
  },
  {
    "name": "Table 2",
    "requestInputRow": [
      {
        "input": [
          { "name": "Drug", "value": "1" },
          { "name": "K", "value": "1" },
          { "name": "Na", "value": "1" },
          { "name": "Gender", "value": "1" }
        ]
      }
    ]
  }
]
```

## The requestInputRow element

Represents rows of input values used to produce score results. The value for this element is an element array in which each element represents an input row.

Table 23. Child elements for requestInputRow		
Element name	Value type	Description
<a href="#">input</a>	object array	Values for input fields

## Example

The value for the following `requestInputRow` element corresponds to an array containing one element. The element represents a single input row consisting of the values for seven input fields.

```
"requestInputRow": [
  {
    "input": [
      { "name": "Age", "value": "1" },
      { "name": "BP", "value": "1" },
      { "name": "Cholesterol", "value": "1" },
      { "name": "Drug", "value": "1" },
      { "name": "K", "value": "1" },
      { "name": "Na", "value": "1" },
      { "name": "Gender", "value": "1" }
    ]
  }
]
```

To include multiple input rows, add `input` elements to the `requestInputRow` element. For example, the following element contains two rows of input data.

```
"requestInputRow": [
  {
    "input": [
      { "name": "Age", "value": "1" },
      { "name": "BP", "value": "1" },
      { "name": "Cholesterol", "value": "1" },
      { "name": "Drug", "value": "1" },
      { "name": "K", "value": "1" },
      { "name": "Na", "value": "1" },
      { "name": "Gender", "value": "1" }
    ]
  },
  {
    "input": [
      { "name": "Age", "value": "3" },
      { "name": "BP", "value": "2" },
      { "name": "Cholesterol", "value": "4" },
      { "name": "Drug", "value": "2" },
      { "name": "K", "value": "3" },
      { "name": "Na", "value": "1" },
      { "name": "Gender", "value": "2" }
    ]
  }
]
```

## The input element

Defines the scoring input data values. The value for this element is an object array in which each object represents a value for an input field. The format of the values must match the data type, as specified in the scoring configuration metadata.

Table 24. Child elements for input		
Element name	Value type	Description
name	string	Name of the input item
value	string	<p>A value, in string representation. If this attribute is not specified, the value is considered to be null. The text representation of the numeric types is obvious, but several types are not. The format of the non-numeric types must be as follows:</p> <ul style="list-style-type: none"><li>• <code>boolean=true</code>(not case sensitive) or <code>1</code> or <code>false</code>(not case sensitive) or <code>0</code></li><li>• <code>date=yyyy-MM-dd</code></li><li>• <code>daytime=HH:mm:ss</code></li><li>• <code>timestamp=yyyy-MM-dd 'T' HH:mm:ss</code></li></ul>

## Example

The value for the following `input` element corresponds to an array containing the values for seven input fields.

```
"input": [
  { "name": "Age", "value": "1" },
  { "name": "BP", "value": "1" },
  { "name": "Cholesterol", "value": "1" },
  { "name": "Drug", "value": "1" },
  { "name": "K", "value": "1" },
  { "name": "Na", "value": "1" },
  { "name": "Gender", "value": "1" }
]
```

## The context element

Describes the indirect inputs to the scoring model. The value for this element is an object array in which each object represents an input table.

Table 25. Child elements for context		
Element name	Value type	Description
name	string	Name, possibly localized, for the context table
columnName	string array	An ordered list of column names
<u>rowValues</u>	object array	A row of table data, following the order in the columnName list

## Example

The value for the following `context` element is an array containing an object representing a context table named *Context 1*. The table contains two columns named *Education* and *Area* having values of 2 and 3.

```
"context": [
  {
    "name": "Context 1",
    "columnName": ["Education", "Area"],
    "rowValues": [
      {
        "value": [
          { "value": "2" },
          { "value": "3" }
        ]
      }
    ]
  }
]
```

## The rowValues element

Represents a row of context field values. The value for this element is an object array in which each object represents a set of values.

The order of the values corresponds to the order of the field names in the columnName element.

Table 26. Child elements for rowValues		
Element name	Value type	Description
<u>value</u>	object array	Values for the indirect model inputs

## Example

The value for the following `rowValues` element corresponds to an array containing a single object representing two values.

```
"rowValues": [
  {
    "value": [
      { "value": "2" },
      { "value": "3" }
    ]
  }
]
```

## The value element

Provides values for the context fields. The value for this element is an object array in which each object represents a value.

Table 27. Child elements for value		
Element name	Value type	Description
value	string	A value, in string representation. If this attribute is not specified, the value is considered to be null. The text representation of the numeric types is obvious, but several types are not. The format of the non-numeric types must be as follows: <ul style="list-style-type: none"><li>• <code>boolean=true</code>(not case sensitive) or <code>1</code> or <code>false</code>(not case sensitive) or <code>0</code></li><li>• <code>date=yyyy-MM-dd</code></li><li>• <code>daytime=HH:mm:ss</code></li><li>• <code>timestamp=yyyy-MM-dd 'T' HH:mm:ss</code></li></ul>

## Example

The array for the following `value` element contains two values.

```
"value": [
  { "value": "2" },
  { "value": "3" }
]
```

## The scoreResult object

Represents the results of a scoring request as an object containing the output specified by the scoring configuration.

The “[Score POST](#)” on [page 15](#) method returns the `scoreResult` object in the response body.

Table 28. Child elements for scoreResult		
Element name	Value type	Description
id	string	Internal identifier for the score result
<a href="#">columnNames</a>	element array	Names of the scoring functions included in the result



Table 28. Child elements for scoreResult (continued)		
Element name	Value type	Description
<u>rowValues</u>	object array	Values for the scoring functions
<u>returnedRequestInputTable</u>	object array	Tables containing the input values on which the scores are based. The presence of this array is determined by the scoring configuration settings.

## Example

The following object corresponds to a scoring response for a model having seven input fields. The response contains a value of 2 for the *Prediction* scoring function and a value of 1.34153 for the *Confidence* scoring function.

```
{
  "id": "954d9db3-049f-464c-b218-eadd628cf349",
  "columnNames": [
    {
      "name": "Prediction", "Confidence"
    }
  ],
  "rowValues": [
    {
      "reserved": null,
      "value": [
        { "value": "2" },
        { "value": "1.3415297614991626" }
      ]
    }
  ],
  "returnedRequestInputTable": [
    {
      "name": "Table 1",
      "id": "Table 1",
      "returnedRequestInputRow": [
        {
          "returnedRequestInputValue": [
            { "name": "Age", "type": "double", "value": "1" },
            { "name": "BP", "type": "string", "value": "1" },
            { "name": "Cholesterol", "type": "string", "value": "1" },
            { "name": "Drug", "type": "string", "value": "1" },
            { "name": "K", "type": "double", "value": "1" },
            { "name": "Na", "type": "double", "value": "1" },
            { "name": "Gender", "type": "string", "value": "1" }
          ]
        }
      ]
    }
  ]
}
```

## The columnNames element

Identifies the scoring functions included in a score result. The value for this element is an element array in which each element represents a set of scoring functions.

Table 29. Child elements for columnNames		
Element name	Value type	Description
name	string array	Scoring function names.

## Example

The value for the following `columnNames` element identifies two scoring functions, *Prediction* and *Confidence*.

```
"columnNames": [
  {
    "name": "Prediction", "Confidence"
  }
]
```

## The rowValues element

Represents a row of scoring result values. The value for this element is an object array in which each object represents a set of scoring values.

Table 30. Child elements for rowValues		
Element name	Value type	Description
reserved	string	Internal string that is currently unused.
<a href="#">value</a>	object array	Scoring function values

### Example

The value for the following rowValues element reports scoring function values of 2 and 1.34153.

```
"rowValues": [
  {
    "reserved": null,
    "value": [{ "value": "2"}, { "value": "1.3415297614991626"}]
  }
]
```

## The value element

Provides the score result values. The value for this element is an object array in which each object represents a scoring value.

Table 31. Child elements for value		
Element name	Value type	Description
value	string	A scoring value, in string representation.

### Example

The value for the following value element is an array containing two objects. The first object reports a value of 4 and the second object reports a value of 2.434156.

```
"value": [
  { "value": "4"},
  { "value": "2.434156"}
]
```

## The returnedRequestInputTable element

Describes the input tables used in a score request. The value for this element is an object array in which each object represents an input table.

Table 32. Child elements for returnedRequestInputTable		
Element name	Value type	Description
id	string	Non-localized identifier for the input table
name	string	Name, possibly localized, for the input table
<a href="#">returnedRequestInputRow</a>	object array	One or more rows of input values used for scoring

## Example

The value for the following `returnedRequestInputTable` element is an array containing one object representing a table named *Table 1*.

```
"returnedRequestInputTable": [
  {
    "name": "Table 1",
    "id": "Table 1",
    "returnedRequestInputRow": [
      {
        "returnedRequestInputValue": [
          { "name": "Age", "type": "double", "value": "1" },
          { "name": "BP", "type": "string", "value": "1" },
          { "name": "Cholesterol", "type": "string", "value": "1" },
          { "name": "Drug", "type": "string", "value": "1" },
          { "name": "K", "type": "double", "value": "1" },
          { "name": "Na", "type": "double", "value": "1" },
          { "name": "Gender", "type": "string", "value": "1" }
        ]
      }
    ]
  }
]
```

## The `returnedRequestInputRow` element

Represents rows of input values used to produce score results. The value for this element is an object array in which each object represents an input row.

Table 33. Child elements for <code>returnedRequestInputRow</code>		
Element name	Value type	Description
<code>returnedRequestInputValue</code>	object array	Values used to produce the score results. A value might be null.

## Example

The value for the following `returnedRequestInputRow` element is an array containing one object representing a single row of input values.

```
"returnedRequestInputRow": [
  {
    "returnedRequestInputValue": [
      { "name": "Age", "type": "double", "value": "1" },
      { "name": "BP", "type": "string", "value": "1" },
      { "name": "Cholesterol", "type": "string", "value": "1" },
      { "name": "Drug", "type": "string", "value": "1" },
      { "name": "K", "type": "double", "value": "1" },
      { "name": "Na", "type": "double", "value": "1" },
      { "name": "Gender", "type": "string", "value": "1" }
    ]
  }
]
```

## The `returnedRequestInputValue` element

Represents the input values used to produce score results. The value for this element is an object array in which each object represents an input field.

Table 34. Child elements for <code>returnedRequestInputValue</code>		
Element name	Value type	Description
<code>name</code>	string	Name of the input item

Table 34. Child elements for returnedRequestInputValue (continued)

Element name	Value type	Description
type	string	Data type of the field. Valid entries include the following values: <ul style="list-style-type: none"> <li>• boolean</li> <li>• date</li> <li>• daytime</li> <li>• decimal</li> <li>• double</li> <li>• float</li> <li>• integer</li> <li>• long</li> <li>• string</li> <li>• timestamp</li> </ul>
value	string	A value, in string representation.

## Example

The value for the following returnedRequestInputValue element is an array containing several objects. Each object represents the value for a single input field. The inputs consist of four string fields and three double fields.

```
"returnedRequestInputValue": [
  { "name": "Age", "type": "double", "value": "1" },
  { "name": "BP", "type": "string", "value": "2" },
  { "name": "Cholesterol", "type": "string", "value": "3" },
  { "name": "Drug", "type": "string", "value": "4" },
  { "name": "K", "type": "double", "value": "3" },
  { "name": "Na", "type": "double", "value": "2" },
  { "name": "Gender", "type": "string", "value": "1" }
]
```

## The scoringServiceDetails object

Provides details about the capabilities of the Scoring Service. In addition to reporting the service version, this object includes information about each individual score provider currently installed.

The “[Service GET](#)” on [page 7](#) method returns the scoringServiceDetails object in the response body.

Table 35. Child elements for scoringServiceDetails

Element name	Value type	Description
version	string	The service version number
<a href="#">scoreProviderDetails</a>	object array	Information about the score providers available in the system

## Example

The following object indicates that version 5.0.0.0.155 of the Scoring Service is in use. The Modeler Score Provider score provider is available for scoring requests using IBM SPSS Modeler streams. In

addition, the Score Provider - SmartScore score provider is available for scoring requests using PMML files.

```
{
  "version": "5.0.0.155",
  "scoreProviderDetails": [
    {
      "supportedMimeTypes": ["application/x-vnd.spss-clementine-stream"],
      "version": "1.0",
      "name": "Modeler Score Provider",
      "id": "091ed7cda16d295c000001327c563c4593de"
    },
    {
      "supportedMimeTypes": ["application/x-vnd.spss-pmml"],
      "version": "1.0",
      "name": "Score Provider - SmartScore",
      "id": "091ed7cd82a9085b000001327c118593a316"
    }
  ]
}
```

## The scoreProviderDetails element

Provides details about the score providers in the system. The value of this element consists of an object array in which each object corresponds to a score provider.

The following table identifies the elements comprising each object in the array.

Table 36. Child elements for scoreProviderDetails		
Element name	Value type	Description
id	string	Non-localized identifier for the score provider
name	string	Name, possibly localized, for the score provider
version	string	The score provider version number
supportedMimeValue types	string array	One or more MIME types indicating the type of files that can be used with the score provider

## Example

The following scoreProviderDetails element consists of an array containing one object. The object corresponds to version 1.0 of the Modeler Score Provider score provider that is used for IBM SPSS Modeler stream files.

```
"scoreProviderDetails": [
  {
    "supportedMimeTypes": [
      "application/x-vnd.spss-clementine-stream"
    ],
    "version": "1.0",
    "name": "Modeler Score Provider",
    "id": "091ed7cda16d295c000001327c563c4593de"
  }
]
```



## Appendix A. Deprecated features

If you are migrating from an earlier release of IBM SPSS Collaboration and Deployment Services, you should be aware of the various features that have been deprecated since the last version.

If a feature is deprecated, IBM Corp. might remove this capability in a subsequent release of the product. Future investment will be focused on the strategic function listed under the recommended migration action. Typically, a feature is not deprecated unless an equivalent alternative is provided.

**No features have been deprecated in this release.** For reference purposes, the following table indicates features that were deprecated in recent previous versions of the product. Where possible, the table also indicates the recommended migration action.

Table 37. Features deprecated in previous versions	
Deprecation	Recommended migration action
Security Provider: Active Directory with local override, which supports extended groups and allowed users	Use the standard Active Directory security provider with any necessary groups added
IBM SPSS Collaboration and Deployment Services Enterprise View	Use the Analytic Data View feature
IBM SPSS Collaboration and Deployment Services Enterprise View Driver	Use the Analytic Data View feature
Scenario files	Scenario files (.scn) are no longer supported. Enterprise View source nodes cannot be modified in Deployment Manager. Old scenario files can be modified in IBM SPSS Modeler client and resaved as stream files. Also, scoring configurations that used a scenario file must be deleted and recreated based on a stream file.
Web Install for IBM SPSS Deployment Manager	Use the standalone installer
BIRT Report Designer for IBM SPSS	None
BIRT Report Designer for IBM SPSS viewer	None
IBM SPSS Collaboration and Deployment Services Portlet	Use the IBM SPSS Collaboration and Deployment Services Deployment Portal directly, or use the web services APIs
IBM SPSS Collaboration and Deployment Services Web Part	Use the IBM SPSS Collaboration and Deployment Services Deployment Portal directly, or use the web services APIs
Scoring Service V1 API	Scoring Service V2 API
Scheduling Server Service	None
Reporting Service	None
Authentication Service login operation	Authentication Service doLogin operation
Search Service search operation	Search Service search2.5 operation
SPSS AXIS/Castor web services client jar	Use the tools provided with the Java Runtime Environment, Integrated Development Environment, or Eclipse Web Tools Platform (WTP)

<i>Table 37. Features deprecated in previous versions (continued)</i>	
<b>Deprecation</b>	<b>Recommended migration action</b>
clemrt1_setLogFile() API function	None



## Notices

---

This information was developed for products and services offered in the US. This material might be available from IBM in other languages. However, you may be required to own a copy of the product or product version in that language in order to access it.

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not grant you any license to these patents. You can send license inquiries, in writing, to:

*IBM Director of Licensing  
IBM Corporation  
North Castle Drive, MD-NC119  
Armonk, NY 10504-1785  
US*

For license inquiries regarding double-byte (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

*Intellectual Property Licensing  
Legal and Intellectual Property Law  
IBM Japan Ltd.  
19-21, Nihonbashi-Hakozakicho, Chuo-ku  
Tokyo 103-8510, Japan*

INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM websites are provided for convenience only and do not in any manner serve as an endorsement of those websites. The materials at those websites are not part of the materials for this IBM product and use of those websites is at your own risk.

IBM may use or distribute any of the information you provide in any way it believes appropriate without incurring any obligation to you.

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

*IBM Director of Licensing  
IBM Corporation  
North Castle Drive, MD-NC119  
Armonk, NY 10504-1785  
US*

Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement or any equivalent agreement between us.

The performance data and client examples cited are presented for illustrative purposes only. Actual performance results may vary depending on specific configurations and operating conditions.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

Statements regarding IBM's future direction or intent are subject to change or withdrawal without notice, and represent goals and objectives only.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to actual people or business enterprises is entirely coincidental.

#### **COPYRIGHT LICENSE:**

This information contains sample application programs in source language, which illustrate programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to IBM, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating platform for which the sample programs are written. These examples have not been thoroughly tested under all conditions. IBM, therefore, cannot guarantee or imply reliability, serviceability, or function of these programs. The sample programs are provided "AS IS", without warranty of any kind. IBM shall not be liable for any damages arising out of your use of the sample programs.

## **Privacy policy considerations**

---

IBM Software products, including software as a service solutions, ("Software Offerings") may use cookies or other technologies to collect product usage information, to help improve the end user experience, to tailor interactions with the end user or for other purposes. In many cases no personally identifiable information is collected by the Software Offerings. Some of our Software Offerings can help enable you to collect personally identifiable information. If this Software Offering uses cookies to collect personally identifiable information, specific information about this offering's use of cookies is set forth below.

This Software Offering does not use cookies or other technologies to collect personally identifiable information.

If the configurations deployed for this Software Offering provide you as customer the ability to collect personally identifiable information from end users via cookies and other technologies, you should seek your own legal advice about any laws applicable to such data collection, including any requirements for notice and consent.

For more information about the use of various technologies, including cookies, for these purposes, See IBM's Privacy Policy at <http://www.ibm.com/privacy> and IBM's Online Privacy Statement at <http://www.ibm.com/privacy/details> the section entitled "Cookies, Web Beacons and Other Technologies" and the "IBM Software Products and Software-as-a-Service Privacy Statement" at <http://www.ibm.com/software/info/product-privacy>.

## **Trademarks**

---

IBM, the IBM logo, and [ibm.com](http://www.ibm.com) are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be

trademarks of IBM or other companies. A current list of IBM trademarks is available on the web at "Copyright and trademark information" at [www.ibm.com/legal/copytrade.shtml](http://www.ibm.com/legal/copytrade.shtml).

Adobe, the Adobe logo, PostScript, and the PostScript logo are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States, and/or other countries.

Intel, Intel logo, Intel Inside, Intel Inside logo, Intel Centrino, Intel Centrino logo, Celeron, Intel Xeon, Intel SpeedStep, Itanium, and Pentium are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

Linux is a registered trademark of Linus Torvalds in the United States, other countries, or both.

Microsoft, Windows, Windows NT, and the Windows logo are trademarks of Microsoft Corporation in the United States, other countries, or both.

UNIX is a registered trademark of The Open Group in the United States and other countries.

Java and all Java-based trademarks and logos are trademarks or registered trademarks of Oracle and/or its affiliates.

Other product and service names might be trademarks of IBM or other companies.



# Glossary

---

This glossary includes terms and definitions for IBM SPSS Collaboration and Deployment Services.

The following cross-references are used in this glossary:

- See refers you from a term to a preferred synonym, or from an acronym or abbreviation to the defined full form.
- See also refers you to a related or contrasting term.

To view glossaries for other IBM products, go to [www.ibm.com/software/globalization/terminology](http://www.ibm.com/software/globalization/terminology) (opens in new window).

## A

---

### **access control list (ACL)**

In computer security, a list associated with an object that identifies all the subjects that can access the object and their access rights.

#### **ACL**

See [access control list](#).

### **action**

A permission for an aspect of system functionality. For example, the ability to set up notifications is defined as an action. Actions are grouped and assigned to users through roles. See also [role](#).

### **Active Directory (AD)**

A hierarchical directory service that enables centralized, secure management of an entire network, which is a central component of the Microsoft Windows platform.

#### **AD**

See [Active Directory](#).

### **allowed user**

A subset of the users defined in a remote directory, such as SiteMinder or Windows Active Directory, that are allowed access to SPSS Predictive Enterprise Services. Allowed users are defined when only a few users in a remote directory need access to the application.

#### **API**

See [application programming interface](#).

### **appender**

A component that receives logging requests from a logger and writes log statements to a specified file or console. See also [logger](#).

### **application programming interface (API)**

An interface that allows an application program that is written in a high-level language to use specific data or functions of the operating system or another program.

## B

---

### **batch file**

A file that contains instructions that are processed sequentially, as a unit.

### **binary large object (BLOB)**

A data type whose value is a sequence of bytes that can range in size from 0 bytes to 2 gigabytes less 1 byte. This sequence does not have an associated code page and character set. BLOBs can contain, for example, image, audio, or video data.

#### **BLOB**

See [binary large object](#).

**break group**

A set of rows of returned data that are grouped according to a common column value. For example, in a column of states, the rows of data for each state are grouped together.

**burst report**

A report that generates multiple output files during a single run by using multiple input parameters taken from break groups in the report.

## C

---

**cascading permission**

A permission of a parent folder in the content repository that has been propagated to its child objects.

**character large object (CLOB)**

A data type whose value is a sequence of characters (single byte, multibyte, or both) that can range in size from 0 bytes to 2 gigabytes less 1 byte. In general, the CLOB data type is used whenever a character string might exceed the limits of the VARCHAR data type.

**CLOB**

See [character large object](#).

**common warehouse metamodel (CWM)**

A metamodel written to be a common standard by the Object Management Group (OMG).

**content repository**

A centralized location for storing analytical assets, such as models and data. Content repository includes facilities for security and access control, content management, and process automation.

**context data**

Input data that is passed with a scoring request in real time. For example, when a score is requested for a customer based on credit rating and geocode, the credit score and geocode will be the context data for the request.

**credential**

Information acquired during authentication that describes a user, group associations, or other security-related identity attributes, and that is used to perform services such as authorization, auditing, or delegation. For example, a user ID and password are credentials that allow access to network and system resources.

**CWM**

See [common warehouse metamodel](#).

## D

---

**data warehouse**

A subject-oriented collection of data that is used to support strategic decision making. The warehouse is the central point of data integration for business intelligence. It is the source of data for data marts within an enterprise and delivers a common view of enterprise data.

**distinguished name (DN)**

The name that uniquely identifies an entry in a directory. A distinguished name is made up of attribute:value pairs, separated by commas. For example, CN=person name and C=country or region.

**DN**

See [distinguished name](#).

**Document Object Model (DOM)**

A system in which a structured document, for example an XML file, is viewed as a tree of objects that can be programmatically accessed and updated. See also [Simple API for XML](#).

**document type definition (DTD)**

The rules that specify the structure for a particular class of SGML or XML documents. The DTD defines the structure with elements, attributes, and notations, and it establishes constraints for how each element, attribute, and notation can be used within the particular class of documents.

**DOM**

See [Document Object Model](#).

**dormant schedule**

A schedule associated with a deleted or unlabeled version of a job. A dormant schedule cannot be used until it is associated with a valid labeled job version.

**DTD**

See [document type definition](#).

## E

---

**EAR**

See [enterprise archive](#).

**enterprise archive (EAR)**

A specialized type of JAR file, defined by the Java EE standard, used to deploy Java EE applications to Java EE application servers. An EAR file contains EJB components, a deployment descriptor, and web archive (WAR) files for individual web applications. See also [Java archive](#), [web archive](#).

**execution server**

A server that enables analytical processing of resources stored in the repository. For example, to execute an IBM SPSS Statistics syntax in an IBM SPSS Collaboration and Deployment Services job, an IBM SPSS Statistics execution server must be designated.

**export**

The process of storing objects and metadata from the content repository to an external file.

**extended group**

A locally-defined group of remote users. Extended groups are defined when groups in the remote directory are not fine-grained enough.

**Extensible Markup Language (XML)**

A standard metalanguage for defining markup languages that is based on Standard Generalized Markup Language (SGML).

**Extensible Stylesheet Language (XSL)**

A language for specifying style sheets for XML documents. Extensible Stylesheet Language Transformation (XSLT) is used with XSL to describe how an XML document is transformed into another document.

## F

---

**field content assist**

A feature that provides predefined system and variable values for entry fields.

## G

---

**general job step**

A method for running native operating system commands and executable programs on a host or a remote process server. General jobs have access to files stored within the repository and on the file system and can be used to control the input/output of analytical processing.

## I

---

**import**

The process of adding objects and metadata defined in an external file generated by export, to the content repository.

**iterative consumer reporting job step**

A job step that is passed a set of input values generated by a preceding iterative producer reporting job step. The report in iterative consumer job step is executed for each tuple in the received data set.

**iterative producer reporting job step**

A job step that generates a set of values passed as input parameters to a following iterative consumer job step.

## J

---

**JAAS**

See [Java Authentication and Authorization Service](#).

**JAR**

See [Java archive](#).

**Java archive (JAR)**

A compressed file format for storing all of the resources that are required to install and run a Java program in a single file. See also [enterprise archive](#), [web archive](#).

**Java Authentication and Authorization Service (JAAS)**

In Java EE technology, a standard API for performing security-based operations. Through JAAS, services can authenticate and authorize users while enabling the applications to remain independent from underlying technologies.

**Java Generic Security Services (JGSS)**

A specification that provides Java programs access to the services that include the signing and sealing of messages and a generic authentication mechanism.

**Java Naming and Directory Interface (JNDI)**

An extension to the Java platform that provides a standard interface for heterogeneous naming and directory services.

**JGSS**

See [Java Generic Security Services](#).

**JNDI**

See [Java Naming and Directory Interface](#).

**job**

A mechanism for automating analytical processing. A job consists of job steps, executed sequentially or conditionally. Input parameters can be defined for a job. A job can be run on demand or triggered by time-based or message-based schedules, with records of job execution stored as job history.

**job step**

A discrete unit of processing in a job. Depending on the type, job steps can be run on the content repository host or specially defined execution or remote process servers. Objects stored in the repository or the file system can provide input for a job step, and job step output can be stored in the repository or written to the file system.

## K

---

**KDC**

See [key distribution center](#).

**Kerberos**

A network authentication protocol that is based on symmetric key cryptography. Kerberos assigns a unique key, called a ticket, to each user who logs on to the network. The ticket is embedded in messages that are sent over the network. The receiver of a message uses the ticket to authenticate the sender.

**key distribution center (KDC)**

A network service that provides tickets and temporary session keys. The KDC maintains a database of principals (users and services) and their associated secret keys. It is composed of the authentication server and the ticket granting ticket server.

**keystore**

In security, a file or a hardware cryptographic card where identities and private keys are stored, for authentication and encryption purposes. Some keystores also contain trusted or public keys.



## L

---

### **LDAP**

See [Lightweight Directory Access Protocol](#).

### **Lightweight Directory Access Protocol (LDAP)**

An open protocol that uses TCP/IP to provide access to directories that support an X.500 model and that does not incur the resource requirements of the more complex X.500 Directory Access Protocol (DAP). For example, LDAP can be used to locate people, organizations, and other resources in an Internet or intranet directory.

### **lock**

The process by which integrity of data is ensured by preventing more than one user from accessing or changing the same data or object at the same time.

### **logger**

A component that prepares log statements to be written to console or log file. See also [appender](#).

## M

---

### **message-based schedule**

A schedule that is used to trigger job execution by an event signalled by a Java Messaging Service (JMS) message. For example, when a job relies on the input from a third-party application, the application must send a JMS message when the input file is ready for processing.

### **metamodel**

A model that defines the language for expressing a model.

### **meta-object**

An instance of an XMI class as defined in the metamodel.

### **meta-object facility (MOF)**

A generalized facility and repository for storing abstract information about concrete object systems; dealing mostly with construction, standardized by the Object Management Group (OMG).

### **MIME**

See [Multipurpose Internet Mail Extensions](#).

### **MOF**

See [meta-object facility](#).

### **Multipurpose Internet Mail Extensions (MIME)**

An Internet standard that allows different forms of data, including video, audio, or binary data, to be attached to email without requiring translation into ASCII text.

## N

---

### **notification**

A mechanism that is used to generate email messages informing users of specific types of system events, such as changes to content repository objects and processing success and failure. Unlike subscriptions, notifications can be set up to send email to multiple users.

## O

---

### **Object Management Group (OMG)**

A non-profit consortium whose purpose is to promote object-oriented technology and the standardization of that technology. The Object Management Group was formed to help reduce the complexity, lower the costs, and hasten the introduction of new software applications.

### **ODS**

See [Output Delivery System](#).

### **OMG**

See [Object Management Group](#).

## **Output Delivery System (ODS)**

A method of controlling the destination for output within SAS. ODS can route SAS output to a SAS data file, a text listing file, HTML files, and files optimized for high-resolution printing.

## **P**

---

### **package**

An installable unit of a software product. Software product packages are separately installable units that can operate independently from other packages of that software product.

### **principal**

An entity that can communicate securely with another entity. A principal is identified by its associated security context, which defines its access rights.

## **R**

---

### **remote process server**

A remote system that is designated for running native operating system commands and executable programs.

### **repository content adapter**

An optional software package that enables storing and processing content from other IBM SPSS applications, such as Statistics, Modeler, and Data Collection, as well as third parties.

### **repository database**

A relational database that is used for storing content repository objects and metadata.

### **resource**

A content repository object.

### **resource definition**

A subset of content repository resources used to enable analytical processing, such as definitions of data sources, credentials, execution servers, and JMS message domains.

### **role**

A set of permissions or access rights. See also [action](#).

## **S**

---

### **SAX**

See [Simple API for XML](#).

### **schedule**

A content repository object that triggers job execution.

### **scoring configuration**

A configuration that defines model-specific settings for generating real-time scores, such as input data, processing rules, outputs, logging, etc.

### **security provider**

A system that performs user authentication. Users and groups can be defined locally (in which case, IBM SPSS Collaboration and Deployment Services itself is the security provider) or derived from a remote directory, such as Windows Active Directory or OpenLDAP.

### **service provider interface (SPI)**

An API that supports replaceable components and can be implemented or extended by a third party.

### **SGML**

See [Standard Generalized Markup Language](#).

### **shell script**

A program, or script, that is interpreted by the shell of an operating system.

**Simple API for XML (SAX)**

An event-driven, serial-access protocol for accessing XML documents, used. A Java-only API, SAX is used by most servlets and network programs to transmit and receive XML documents. See also [Document Object Model](#).

**single sign-on (SSO)**

An authentication process in which a user can access more than one system or application by entering a single user ID and password.

**SOAP**

A lightweight, XML-based protocol for exchanging information in a decentralized, distributed environment. SOAP can be used to query and return information and invoke services across the Internet.

**SPI**

See [service provider interface](#).

**SSO**

See [single sign-on](#).

**Standard Generalized Markup Language (SGML)**

A standard metalanguage for defining markup languages that is based on the ISO 8879 standard. SGML focuses on structuring information rather than presenting information; it separates the structure and content from the presentation. It also facilitates the interchange of documents across an electronic medium.

**stop word**

A word that is commonly used, such as "the," "an," or "and," that is ignored by a search application.

**subscription**

Email notices and Really Simple Syndication (RSS) feeds that repository users create to receive when the state of an asset changes.

## T

---

**TGT**

See [ticket-granting ticket](#).

**ticket-granting ticket (TGT)**

A ticket that allows access to the ticket granting service on the key distribution center (KDC). Ticket granting tickets are passed to the principal by the KDC after the principal has completed a successful request. In a Windows 2000 environment, a user logs on to the network and the KDC will verify the principal's name and encrypted password and then send a ticket granting ticket to the user.

**time-based schedule**

A schedule that triggers job execution at a specified time or date. For example, a time-based schedule may run a job at 5:00 pm every Thursday.

## U

---

**Universally Unique Identifier (UUID)**

The 128-bit numeric identifier that is used to ensure that two components do not have the same identifier.

**UUID**

See [Universally Unique Identifier](#).

## V

---

**Velocity**

A Java-based template engine that provides a simple and powerful template language to reference objects defined in Java code. Velocity is an open source package directed by the Apache Project.

## W

---

### **W3C**

See [World Wide Web Consortium](#).

### **WAR**

See [web archive](#).

### **web archive (WAR)**

A compressed file format, defined by the Java EE standard, for storing all the resources required to install and run a web application in a single file. See also [enterprise archive](#), [Java archive](#).

### **Web Services Description Language (WSDL)**

An XML-based specification for describing networked services as a set of endpoints operating on messages containing either document-oriented or procedure-oriented information.

### **World Wide Web Consortium (W3C)**

An international industry consortium set up to develop common protocols to promote evolution and interoperability of the World Wide Web.

### **WSDL**

See [Web Services Description Language](#).

## X

---

### **XMI**

See [XML Metadata Interchange](#).

### **XML**

See [Extensible Markup Language](#).

### **XML Metadata Interchange (XMI)**

A model-driven XML integration framework for defining, interchanging, manipulating, and integrating XML data and objects. XMI-based standards are in use for integrating tools, repositories, applications, and data warehouses.

### **XSL**

See [Extensible Stylesheet Language](#).

---

# Index

## A

accept field  
  requests [2](#)  
arrays  
  in JSON [4](#)  
authorization field  
  requests [2](#)

## C

categoricalValues element  
  for contextColumn elements [29](#)  
  for metadataInputField elements [28](#)  
  for metadataOutputField elements [30](#)  
columnName element  
  for context elements [35](#)  
columnNames elements [36](#), [37](#)  
configuration resources  
  GET method [9](#)  
  requests [9](#)  
  responses [9](#)  
  retrieving [9](#)  
  URL [9](#)  
configuration responses  
  configurationReference objects [25](#)  
  configurationStatus elements [26](#)  
  modelReference elements [26](#)  
configurationReference objects [25](#)  
configurationStatus elements  
  for configurationReference objects [25](#)  
context elements [32](#), [35](#)  
contextColumn elements [29](#)

## D

description element  
  for contextColumn elements [29](#)  
  for metadataInputField elements [28](#)  
  for metadataOutputField elements [30](#)

## E

elements  
  in JSON [4](#)

## G

GET method  
  for configuration resources [9](#)  
  for metadata resources [10](#)  
  for metric item resources [19](#)  
  for metric value resources [22](#)  
  for service resources [7](#)  
  response headers [4](#)  
glossary [49](#)

## H

headers  
  for requests [2](#)  
  for responses [4](#)

## I

id element  
  for configurationReference objects [25](#)  
  for metadataInputTable elements [28](#)  
  for metricItem objects [31](#)  
  for modelReference elements [26](#)  
  for returnedRequestInputTable elements [38](#)  
  for scoreProviderDetails elements [41](#)  
input elements [33](#), [34](#)  
isRequired element  
  for metadataInputField elements [28](#)  
  for metadataOutputField elements [30](#)

## J

JSON  
  arrays [4](#)  
  elements [4](#)  
  objects [4](#)  
  processing responses [6](#)

## L

label element  
  for modelReference elements [26](#)  
localization  
  requests [2](#)

## M

message element  
  for configurationStatus elements [26](#)  
metadata resources  
  GET method [10](#)  
  requests [10](#)  
  responses [10](#)  
  retrieving [10](#)  
  URL [10](#)  
metadata responses  
  contextColumn elements [29](#)  
  metadataContextTable elements [29](#)  
  metadataInputField elements [28](#)  
  metadataInputTable elements [28](#)  
  metadataOutputField elements [30](#)  
  metadataResult objects [27](#)  
metadataContextTable elements [27](#), [29](#)  
metadataInputField elements [28](#)  
metadataInputTable elements [27](#), [28](#)  
metadataOutputField elements [27](#), [30](#)

- metadataResult objects [27](#)
- metric item resources
  - GET method [19](#)
  - requests [19](#)
  - responses [19](#)
  - retrieving [19](#)
  - URL [19](#)
- metric item responses
  - metricItem objects [31](#)
- metric value resources
  - GET method [22](#)
  - requests [22](#)
  - responses [22](#)
  - retrieving [22](#)
  - URL [22](#)
- metric value responses
  - metricValue objects [31](#)
- metricItem objects [31](#)
- metricValue objects [31](#)
- modelReference elements
  - for configurationReference objects [25](#)

## N

- name element
  - for columnNames elements [37](#)
  - for context elements [35](#)
  - for contextColumn elements [29](#)
  - for input elements [34](#)
  - for metadataInputField elements [28](#)
  - for metadataInputTable elements [28](#)
  - for metadataOutputField elements [30](#)
  - for metricItem objects [31](#)
  - for requestInputTable elements [33](#)
  - for returnedRequestInputTable elements [38](#)
  - for returnedRequestInputValue elements [39](#)
  - for scoreProviderDetails elements [41](#)

## O

- objects
  - in JSON [4](#)

## P

- POST method
  - for score resources [15](#)

## R

- requestInputRow elements [33](#)
- requestInputTable elements [32](#), [33](#)
- requests
  - accept field [2](#)
  - authorization field [2](#)
  - for configuration resources [9](#)
  - for metadata resources [10](#)
  - for metric item resources [19](#)
  - for metric value resources [22](#)
  - for score resources [15](#)
  - for service resources [7](#)
  - headers [2](#)
  - localization [2](#)

- requests (*continued*)
  - URL [1](#)
- resourcePath element
  - for modelReference elements [26](#)
- responses
  - for configuration requests [9](#)
  - for metadata requests [10](#)
  - for metric item requests [19](#)
  - for metric value requests [22](#)
  - for score requests [15](#)
  - for service requests [7](#)
  - headers [4](#)
  - processing [6](#)
- retrieving
  - configuration resources [9](#)
  - metadata resources [10](#)
  - metric item resources [19](#)
  - metric value resources [22](#)
  - score resources [15](#)
  - service resources [7](#)
- returnedRequestInputRow elements [36](#), [38](#), [39](#)
- returnedRequestInputTable elements [38](#)
- returnedRequestInputValue elements [39](#)
- rowValues elements [35](#), [36](#), [38](#)

## S

- scale element
  - for metricItem objects [31](#)
- score providers [7](#)
- score requests
  - context elements [35](#)
  - input elements [34](#)
  - requestInputRow elements [33](#)
  - requestInputTable elements [33](#)
  - rowValues elements [35](#)
  - scoreRequest objects [32](#)
  - value elements [36](#)
- score resources
  - POST method [15](#)
  - requests [15](#)
  - responses [15](#)
  - retrieving [15](#)
  - URL [15](#)
- score responses
  - columnNames elements [37](#)
  - returnedRequestInputRow elements [39](#)
  - returnedRequestInputTable elements [38](#)
  - returnedRequestInputValue elements [39](#)
  - rowValues elements [38](#)
  - scoreResult objects [36](#)
  - value elements [38](#)
- scoreProviderDetails elements [40](#), [41](#)
- scoreRequest objects [32](#)
- scoreResult objects [36](#)
- scoringServiceDetails objects [40](#)
- service resources
  - GET method [7](#)
  - requests [7](#)
  - responses [7](#)
  - retrieving [7](#)
  - URL [7](#)
- service responses
  - scoreProviderDetails elements [41](#)

- service responses (*continued*)
  - scoringServiceDetails objects [40](#)
- state element
  - for configurationReference objects [25](#)
- statusCode element
  - for configurationStatus elements [26](#)
- supportedMimeTypes element
  - for scoreProviderDetails elements [41](#)

## T

- table element
  - for metadataContextTable elements [29](#)
- type element
  - for contextColumn elements [29](#)
  - for metadataInputField elements [28](#)
  - for metadataOutputField elements [30](#)
  - for returnedRequestInputValue elements [39](#)

## U

- unit element
  - for metricItem objects [31](#)
- URL
  - for configuration resources [9](#)
  - for metadata resources [10](#)
  - for metric item resources [19](#)
  - for metric value resources [22](#)
  - for requests [1](#)
  - for score resources [15](#)
  - for service resources [7](#)

## V

- value element
  - for input elements [34](#)
  - for metricValue objects [31](#)
  - for returnedRequestInputValue elements [39](#)
  - for value elements [36](#), [38](#)
- value elements [35](#), [36](#), [38](#)
- version element
  - for scoreProviderDetails elements [41](#)
  - for scoringServiceDetails objects [40](#)







