



## IBM TS3100 Tape Library

*Entry-level LTO tape library designed to provide reliable, high-capacity, high-performance tape backup*

---

### Highlights

- Support the latest generation of Linear Tape-Open (LTO) technology with up to two LTO Ultrium tape drives using a 2U form factor
  - Simplify user access to data stored on LTO Ultrium 8, 7, 6 and 5 cartridges through the use of IBM® Spectrum Archive™ featuring IBM Linear Tape File System™ technology
  - Manage libraries remotely through a standard web interface that supports flexibility and improved administrative control over storage operations
- 

IBM TS3100 Tape Library and its storage management applications are designed to exceed your capacity, performance, data protection, reliability, affordability and application requirements. TS3100 is designed as a functionally rich, entry-level tape-storage solution incorporating LTO tape technology. TS3100 is an excellent solution for large-capacity or high-performance tape backup with or without random access, as well as an excellent tape-automation option for IBM Power Systems™ and other open systems.

TS3100 is well-suited for handling the backup, restore and archive data-storage needs of small to midsized environments. With the use of one full-height LTO tape drive or two half-height LTO tape drives and with a 24-cartridge capacity, TS3100 leverages LTO technology to cost-effectively handle growing storage requirements. TS3100 is configured with two removable cartridge magazines, one on the left side (12 data cartridge slots) and one on the right (12 data cartridge slots). Additionally, the left magazine includes a single mail slot to help support continuous library operation while importing and exporting media. A bar code reader is standard in the library, supporting the library's operation in sequential or random-access mode. TS3100 also comes standard with remote management capabilities to allow for remote administration of the tape library through a web interface. Path failover is an optional feature for this library, designed to provide automatic switching to a preconfigured redundant control path in the event that a host adapter or control path drive is lost, without aborting the current job.



LTO Ultrium 8 technology is designed to provide greater capacity with continued support for encryption of data. The hardware encryption and decryption core and control core reside in the LTO Ultrium 8 tape drive. A large internal data buffer helps improve data-access rates and reduce cartridge fill and rewind times, and native dynamic channel calibration is designed to help increase data throughput. In addition to reading and writing to LTO Ultrium 8 tape cartridges, the LTO Ultrium 8 tape drive can read and write to LTO Ultrium 7 cartridges. The LTO Ultrium 8 tape drive is designed to support up to 300 MBps native data-transfer rates and up to 12 TB native physical capacity when using the LTO Ultrium 8 TB data cartridge (30 TB with 2.5:1 compression). TS3100, featuring LTO Ultrium 8 tape drives, has a capacity of up to 288 TB native (720 TB with 2.5:1 compression). The sequential or random-access library comes in a standalone base configuration with the option of an industry-standard 19-inch rack-mount kit. TS3100 also has an LCD and indicators for power, drive and network activity, error status and message information.



### Why IBM?

The performance and availability of your storage environment can either enhance or hamper your business processes. That's where IBM comes in. As a market leader in the storage industry, IBM can help you handle the challenges that your network or company as a whole encounters.

Innovative technology, open standards, excellent performance, and a broad portfolio of storage-proven software, hardware and solutions offerings—all backed by IBM with its recognized leadership—are just a few of the reasons why you should consider IBM storage offerings.

#### IBM TS3100 Tape Library at a glance

<b>Drive options</b>	LTO Ultrium 8 half-height: 6 Gbps SAS (FC # 8547); 8 Gbps Fibre Channel (FC # 8548) LTO Ultrium 7 full-height: 8 Gbps Fibre Channel (FC # 8444) LTO Ultrium 7 half-height: 6 Gbps SAS (FC # 8447); 8 Gbps Fibre Channel (FC # 8448) LTO Ultrium 6 full-height: 8 Gbps Fibre Channel (FC # 8344) LTO Ultrium 6 half-height: 6 Gbps SAS (FC # 8347); 8 Gbps Fibre Channel (FC # 8348) LTO Ultrium 5 full-height: 6 Gbps SAS (FC # 8245); 8 Gbps Fibre Channel (FC # 8244) LTO Ultrium 5 half-height: 6 Gbps SAS (FC # 8247); 8 Gbps Fibre Channel (FC # 8248)
<b>Available models</b>	TS3100 tape library model L2U 3573 L2U (MTM)
<b>Optional feature codes</b>	
<b>Path failover feature</b>	FC # 1682
<b>Transparent LTO encryption</b>	FC # 5900
<b>Rack mount</b>	FC # 7002
<b>Right-side magazine set</b>	FC # 8106
<b>Left-side magazine</b>	FC # 8109

<b>IBM TS3100 Tape Library at a glance</b>	
<b>LTO Ultrium tape cartridges</b>	LTO Ultrium 8, 7 media: MT 3589 LTO Ultrium 6 media: FC # 8605 LTO Ultrium 5 media: FC # 8505
<b>LTO Ultrium cleaning cartridge</b>	FC # 8002
<b>Tape drive type</b>	LTO Ultrium 8 half-height LTO Ultrium 7 half-height and full-height LTO Ultrium 6 half-height and full-height LTO Ultrium 5 half-height and full-height
<b>Number of drives</b>	1 – 2
<b>Number of tape cartridges</b>	24
<b>Number of mail slots</b>	1
<b>Physical capacity</b>	Capacity per cartridge Up to 30 TB compressed 2.5:1 with LTO Ultrium 8; 12 TB native Up to 15 TB compressed 2.5:1 with LTO Ultrium 7; 6 TB native Up to 6.25 TB compressed 2.5:1 with LTO Ultrium 6; 2.5 TB native Up to 3 TB compressed 2:1 with LTO Ultrium 5; 1.5 TB native Library capacity Up to 720 TB compressed 2.5:1 with LTO Ultrium 8; 288 TB native Up to 360 TB compressed 2.5:1 with LTO Ultrium 7; 144 TB native Up to 150 TB compressed 2.5:1 with LTO Ultrium 6; 60 TB native Up to 72 TB compressed 2:1 with LTO Ultrium 5; 36 TB native
<b>Data transfer rate</b>	Up to 300 MBps native with LTO Ultrium 8 Up to 300 MBps native with LTO Ultrium 7 Up to 160 MBps native with LTO Ultrium 6 Up to 140 MBps native with LTO Ultrium 5
<b>Dimensions (W x H x D)</b>	
<b>Standalone</b>	17.6 in. (447.5 mm) × 3.84 in. (97.6 mm) × 31.9 in. (810 mm)
<b>Rack mount</b>	17.6 in. (447.5 mm) × 3.44 in. (87.6 mm) × 29.13 in. (740 mm)
<b>Weight</b>	33 lb (15 kg) without rack mount
<b>Attachment support</b>	8 Gbps Fibre Channel 6 Gbps SAS interfaces
<b>Operating systems support</b>	Native device driver support is available for selected IBM System servers and other Linux and Microsoft Windows open-system servers. Latest support information: Visit the <a href="#">IBM System Storage Interoperation Center</a>
<b>Warranty</b>	Three-year, customer-replaceable unit (CRU) service in most countries

## For more information

To learn more about IBM TS3100 Tape Library, please contact your IBM representative or IBM Business Partner, or visit:

[ibm.com/us-en/marketplace/ts3100](http://ibm.com/us-en/marketplace/ts3100)

Additionally, IBM Global Financing provides numerous payment options to help you acquire the technology you need to grow your business. We provide full lifecycle management of IT products and services, from acquisition to disposition. For more information, visit: [ibm.com/financing](http://ibm.com/financing)



---

© Copyright IBM Corporation 2017

IBM Systems  
New Orchard Road  
Armonk, NY 10504

Produced in the United States of America  
August 2017

IBM, the IBM logo, [ibm.com](http://ibm.com), Power Systems, IBM Spectrum Archive, and Linear Tape File System are trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the web at "Copyright and trademark information" at [ibm.com/legal/copytrade.shtml](http://ibm.com/legal/copytrade.shtml)

Linux is a trademark of Linus Torvalds in the United States, other countries or both.

Microsoft and Windows are trademarks of Microsoft Corporation in the United States, other countries, or both.

Linear Tape File System, Linear Tape-Open, LTO, the LTO Logo, Ultrium and the Ultrium logo are trademarks of HP, IBM Corp. and Quantum in the U.S. and other countries.

This document is current as of the initial date of publication and may be changed by IBM at any time. Not all offerings are available in every country in which IBM operates.

The performance data discussed herein is presented as derived under specific operating conditions. Actual results may vary.

THE INFORMATION IN THIS DOCUMENT IS PROVIDED "AS IS" WITHOUT ANY WARRANTY, OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT. IBM products are warranted according to the terms and conditions of the agreements under which they are provided.

Actual available storage capacity may be reported for both uncompressed and compressed data and will vary and may be less than stated.



Please Recycle

---