

z/OS Language Environment Setup & Customization

March 2006

Thomas Petrolino IBM Poughkeepsie tapetro@us.ibm.com

©copyright IBM Corporation 2001, 2006





Trademarks

The following are trademarks of the International Business Machines Corporation in the United States and/or other countries.

- •CICS®
- •IMS
- Language Environment®
- •OS/390®
- •z/OS®

The following are trademarks or registered trademarks of other companies.

Java and all Java-related trademarks and logos are trademarks of Sun Microsystems, Inc., in the United States and other countries.

Linux is a registered trademark of Linus Torvalds in the United States, other countries, or both.

Microsoft, Windows and Windows NT are registered trademarks of Microsoft Corporation.

UNIX is a registered trademark of The Open Group in the United States and other countries.

SET and Secure Electronic Transaction are trademarks owned by SET Secure Electronic Transaction LLC.

* All other products may be trademarks or registered trademarks of their respective companies.

Notes:

Performance is in Internal Throughput Rate (ITR) ratio based on measurements and projections using standard IBM benchmarks in a controlled environment. The actual throughput that any user will experience will vary depending upon considerations such as the amount of multiprogramming in the user's job stream, the I/O configuration, the storage configuration, and the workload processed. Therefore, no assurance can be given that an individual user will achieve throughput improvements equivalent to the performance ratios stated here.

IBM hardware products are manufactured from new parts, or new and serviceable used parts. Regardless, our warranty terms apply.

All customer examples cited or described in this presentation are presented as illustrations of the manner in which some customers have used IBM products and the results they may have achieved. Actual environmental costs and performance characteristics will vary depending on individual customer configurations and conditions.

This publication was produced in the United States. IBM may not offer the products, services or features discussed in this document in other countries, and the information may be subject to change without notice. Consult your local IBM business contact for information on the product or services available in your area.

All statements regarding IBM's future direction and intent are subject to change or withdrawal without notice, and represent goals and objectives only.

Information about non-IBM products is obtained from the manufacturers of those products or their published announcements. IBM has not tested those products and cannot confirm the performance, compatibility, or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

Prices subject to change without notice. Contact your IBM representative or Business Partner for the most current pricing in your geography.

^{*} Registered trademarks of IBM Corporation





Reflection

- "Language Environment is 100% compatible with previous Run-Time environments" - An unnamed, misinformed marketing rep
- "Read the Language Environment Migration Guide(s) for details of migration problems you WILL encounter." - An unnamed Language Environment developer





Agenda

- o Introduction
- Which Libraries? When?
- O User Exits
- o Setting Run-Time Options
- o Key Run-Time Options
- O Additional Information
- o Appendix: AMODE 64 Run-Time Options





Language Environment is made up of several components

 Common Execution Library (CEL) 	568819801
 COBOL Run-Time Library 	568819802
•PL/I Run-Time Library	568819803
 FORTRAN Run-Time Library 	568819804
C/C++ Run-Time Library	568819805
•Enterprise PL/I (a.k.a. VisualAge PL/I)	568819806





Supported Releases

Supported Release Level	FMID	Support Withdrawn
z/OS V1.4	HLE7707	3/31/2007
z/OS V1.5	HLE7708	3/31/2007
z/OS V1.6	HLE7709	
z/OS V1.7	HLE7720	

7/12/2006 6





Upward Compatibility

•All releases of Language Environment are upward compatible. Applications compiled/linked with a particular release of Language Environment will run on that Language Environment level or higher (see APAR II11316)





- Downward Compatibility
 - •Starting with OS/390 2.10 Language Environment, applications can be compiled/linked at OS/390 2.10 Language Environment (or higher) and run on lower levels of Language Environment with downward compatibility toleration APARs.
 - •New function is excluded. You can only use function available on the lowest level target system. In many cases CEE3728S message will be received when this is attempted.





- Many z/OS elements, features, and functions require Language Environment to be <u>at</u> the level shipped with that release of z/OS...
 - BookManager, C/C++ compiler & class libraries, Communications Server (IP & SNA services), Cryptographic Services, DFSMS (CDRA), DCE Base Services, Distributed File Service, DFSORT Locale Processing, IBM HTTP Server Base, Infoprint Server, Integrated Security Services (DCE & LDAP Server), Library Server, msys for Operations, msys for Setup, NSF, OSA/SF, RMF, z/OS UNIX System Services, etc.
- See z/OS Program Directory section "LNKLSTxx Considerations" under "PARMLIB Member Considerations" section for additional information





Which Libraries? When?

- Customization
 - SCEESAMP
- •C/C++ compile steps
 - SCEEH.* in SYSLIB
- C/C++ XPLINK Bind step
 - SCEEBND2 in SYSLIB
 - SCEELIB in SYSLIN





Which Libraries? When?

- Non-XPLINK Prelink/Link step
 - SCEEOBJ (UNIX System Services), SCEECPP (C++) in prelink SYSLIB
 - SCEELKED in SYSLIB
 - SCEELIB in SYSLIN (for z/OS V1.2 C++ Class Library)
- Non-XPLINK Bind step
 - SCEELKEX then SCEELKED in SYSLIB
 - SCEELKEX not needed for Enterprise PL/I
 - SCEELIB in SYSLIN (for z/OS V1.2 C++ Class Library)





Which Libraries? When?

- Run/Go step
 - SCEERUN in STEPLIB/LPA/LNKLST
 - SCEELPA in LPALSTxx
 - •SCEERUN2 in STEPLIB/LNKLST for C/C++ XPLINK
 - Cannot be in LPALSTxx since PDSE
 - Can use Dynamic LPA to add these modules
 - Remove all pre-Language Environment runtime libraries from search order





- Run/Go step (continued)
 - •CICS TS...
 - SCEECICS (COBOL) then SCEERUN in DFHRPL
 - SCEERUN in STEPLIB (if not in LNKLST/LPALST)
 - CSD must be updated to include the definitions in SCEESAMP (autoinstall will do this)
 - •CEECCSD
 - CEECCSDX (for CICS TS 3.1 XPLINK support)
 - Create CESE/CESO/CIGZ transient data queues using CEECDCT in SCEESAMP





User Exits

- Allows customization of Language Environment initialization and termination behavior
- When linked with Language Environment, acts as a system wide exit
- When linked with an application, affects only that application
 - Supersedes exit linked with Language Environment





User Exits

- CEEBXITA Assembler user exit
- CEEBINT High-level language (HLL) user exit
- CEEEXTAN Abnormal termination exit
- CEEBLNUE Load notification user exit
- CEEBSTX/CEECSTX Storage tuning user exit





- Installation defaults (CEEDOPT/CEECOPT/CELQDOPT)
 - Also referred to as system-wide defaults
 - SMP/E USERMOD to Language Environment modules
 - SCEESAMP(CEEWCOPT) CICS TS only
 - SCEESAMP(CEEWDOPT) non-CICS environments
 - SCEESAMP(CEEWQDOP) AMODE 64
 - All options must be specified





- Installation Defaults (continued)
 - To change Installation defaults
 - 1. uninstall USERMOD, if already installed
 - 2. modify the options
 - 3. install/reinstall the USERMOD
 - Note: Reinstall may be needed if run-time options are added or changed in the service stream.
 (++HOLD(ACTION) will be used on these PTFs to identify when this needs to be done).



```
CEEDOPT
                      ABPERC=((NONE),OVR),
        CSECT
CEEDOPT
                                                                      00110000
        AMODE ANY
CEEDOPT
                                                                      00120000
        RMODE ANY
                                                                      00130000
CEEDOPT
        CEEXOPT ABPERC=((NONE),OVR)
                                                                     X00140000
              ABTERMENC=((ABEND),OVR),
                                                                     X00150000
              AIXBLD=((OFF),OVR),
                                                                     X00160000
              ALL31=((OFF),OVR),
                                                                     X00170000
              ANYHEAP=((16K,8K,ANYWHERE,FREE),OVR),
                                                                     X00180000
              BELOWHEAP=((8K,4K,FREE),OVR),
                                                                     X00190000
                                              continuation
              CBLOPTS=((ON),OVR),
                                                                     X00200000
              CBLPSHPOP=((ON),OVR),
                                                                     X00210000
              CBLQDA=((OFF),OVR),
                                                                     X00220000
                                                character
              CHECK=((ON),OVR),
                                                                     X00230000
              COUNTRY=((US),OVR),
                                                                     X00240000
                                                                     X00250000
              DEBUG=((OFF),OVR),
                                                                     X00260000
              DEPTHCONDLMT=((10),OVR),
```





- System defaults
 - New for z/OS V1.7
 - Options may be specified in a PARMLIB member
 - CEEPRMxx
 - Options may be specified with an operator command
 - SETCEE
 - Reduces the need to maintain USERMODs for CEEDOPT/CEECOPT/CELQDOPT





- System defaults (continued)
 - Specifying options in PARMLIB member
 - Member name CEEPRMxx
 - Options specified in groups
 - CEEDOPT
 - CEECOPT
 - CELQDOPT





- System defaults (continued)
 - Sample CEEPRMxx

7/12/2006 21





- System defaults (continued)
 - Using the CEEPRMxx member
 - At IPL
 - Add CEE=xx to IEASYSxx member
 - Use CEE=xx at system parameter prompt
 - •R 0,SYSP=AA,CEE=xx
 - After IPL, can select a different CEEPRM member
 - SET CEE=yy command





- System defaults (continued)
 - Using the SETCEE system command
 - Overrides the current system defaults
 - Usage
 - Specify one group per command
 - Up to 126 characters
 - •Example:

SETCEE ceedopt,rptstg(on),rptopts(on)

7/12/2006 23





- System defaults (continued)
 - Displaying the system defaults
 - D CEE displays the active members
 - Examples:

```
d cee
CEE3744I 17.56.05 DISPLAY
NO MEMBERS SPECIFIED

Or
d cee
CEE3744I 17.57.31 DISPLAY
CEE=(JM)
```



- System defaults (continued)
 - Displaying the system defaults
 - D CEE, groupname displays the options for a particular group
 - Example:

```
d cee,ceedopt

CEE3745I 17.59.44 DISPLAY CEEDOPT

CEE=(01)

LAST WHERE SET OPTION

CEEPRM01 ENVAR("testing=roger","verify=1 2 3")

CEEPRM01 HEAP(4194304,5242880,ANYWHERE,KEEP,

16384,16384)

CEEPRM01 PROFILE(OFF,"XXX")

CEEPRM01 RPTOPTS(ON)

7/12/2006
```

25






- Region Level Overrides (CEEROPT)
 - CICS TS and LRR users (e.g. IMS) only
 - Separate load module dynamically loaded at run-time during region initialization
 - SCEESAMP(CEEWROPT)
 - Must be found in search order, such as STEPLIB for IMS or DFHRPL for CICS TS
 - Specify only those options you wish to change











- Region Level Overrides (CEEROPT) (continued)
 - Certain options can be overridden dynamically in CICS TS region via CLER transaction
 - •ALL31
 - CBLPSHPOP
 - RPTOPTS
 - RPTSTG
 - TERMTHDACT
 - TRAP






- Application Level Overrides (CEEUOPT/CELQUOPT)
 - CSECT linked with the application
 - SCEESAMP(CEEWUOPT/CEEWQUOP)
 - Specify only those options you wish to change
 - Note: It is recommended to use options at this level when specific options are needed for an application.
 It is not a good idea to rely on installation defaults.
 This is especially important for vendors.











- Programmer Overrides
 - Compiled into program
 - #pragma runopts for C/C++
 - PLIXOPT for PL/I
 - not available for COBOL
 - Internally generates CEEUOPT/CELQUOPT
 - Specify all program requirements, never ever rely on installation/system/region defaults. This is especially important for vendors.





- Programmer Overrides (continued)
 - For example
 - #pragma runopts(ALL31(ON),ERRCOUNT(0),\
 STORAGE(NONE,NONE,NONE,30K),\
 TRAP(ON,SPIE),LIBSTACK(4K,4K,FREE),\
 STACK(2M,1M,ANYWHERE,KEEP),\
 ANYHEAP(16K,8K,ANYWHERE,FREE),\
 BELOWHEAP(8K,4K,FREE),\
 HEAP(1M,500K,ANYWHERE,KEEP))





- Programmer Overrides (continued)
 - For example
 - •DCL PLIXOPT CHAR(140) VAR
 INIT('ALL31(ON) ERRCOUNT(0)
 STORAGE(NONE,NONE,NONE,30K)
 TRAP(ON,SPIE) LIBSTACK(4K,4K,FREE)
 STACK(2M,1M,ANYWHERE,KEEP)
 ANYHEAP(16K,8K,ANYWHERE,FREE)
 BELOWHEAP(8K,4K,FREE)
 HEAP(1M,500K,ANYWHERE,KEEP)')
 STATIC EXTERNAL;





- Program Invocation Overrides
 - In UNIX System Services shell (case sensitive)
 - export _CEE_RUNOPTS='run-time options'
 - No application parameters allowed, thus '/' not needed
 - export _CEE_RUNOPTS='TERM(UADUMP)'
 - Can also contain AMODE 64 run-time options
 - Only applicable options are used, but propagation of all options are done for spawn()ed and exec()ed programs





- Program Invocation Overrides (continued)
 - In batch, on EXEC card
 - COBOL (with CBLOPTS(ON))
 - PARM='program arguments/run-time options'
 - C/C++, PL/I, FORTRAN, Language Environment-conforming Assembler
 - PARM='run-time options/program arguments'
 - First program must be Language Environment-conforming
 - The slash is required to delineate the run-time options, even when no program arguments.





- Program Invocation Overrides (continued)
 - In batch, on EXEC card (continued)
 - EXEC PGM=MYCOBAPP,PARM='TODAY/TER(UADUMP)'
 - EXEC PGM=MYCOBAPP,PARM='10/27/00'
 - The entire parameter is considered to be application arguments because there are no valid run-time options after the last forward-slash.
 - Note that PARM= is limited to 100 characters





- DD:CEEOPTS Overrides
 - New for z/OS V1.7
 - Optional data set in which run-time options may be specified
 - Allows up to 3K characters
 - Allows run-time options to be passed to non-Language Environment conforming main routines





- DD:CEEOPTS Overrides (continued)
 - Usage: Add or allocate a CEEOPTS DD
 - •As in-stream data:

```
//MYAPPL01 EXEC PROG=MYPRG,PARM='RPTOPTS(ON)/'
//CEEOPTS DD *

* THESE ARE MY OPTIONS:
ALL31(ON), HEAP(64K),
ENVAR("JOHN=MONTI"),
TERMTHDACT(UADUMP)
/*
```





- DD:CEEOPTS Overrides (continued)
 - Usage: Add or allocate a CEEOPTS DD
 - •As a sequential file:

```
//MYAPPL01 EXEC PROG=MYCPROG,PARM='RPTOPTS(ON)/'
//CEEOPTS DD DSN=JMONTI.MYCPROG.LEOPTS
```

•As a member of a PDS:

```
//MYAPPL01 EXEC PROG=MYCPROG,PARM='RPTOPTS(ON)/'
//CEEOPTS DD DSN=JMONTI.MYCPROG(LEOPTS)
```





- DD:CEEOPTS Overrides (continued)
 - Supported under:
 - Batch
 - TSO
 - Preinit (CEEPIPI) during call_main or init_sub(dp)
 - IMS without LRR
 - DB2
 - Not supported under:
 - CICS
 - IMS/LRR
 - Preinit Compatibility (PICI)
 - System Program C (SPC)
 - Exec()ed programs (BPXBATCH or UNIX shell programs)





- Options Merge (priority)
 - Program Invocation Overrides
 - DD:CEEOPTS Overrides
 - Programmer Overrides
 - Application Level Overrides
 - Region Level Overrides (where applicable)
 - System Defaults (CEEPRMxx and SETCEE)
 - Installation Defaults

Note: Some options can only be specified as Installation Defaults, e.g. CBLOPTS(ON)





- Installation Default options must be set based on needs of the applications
 - Language used (PL/I, COBOL, C/C++, FORTRAN) will drive some option settings
 - May require some compromise
 - Subsystem application runs under (CICS TS, IMS, batch, UNIX System Services, etc.) will drive some option settings
 - Specific applications can then override options as needed





- Tuning
- Diagnostics



Key Run-Time Options Tuning

- ALL31
- ANYHEAP
- BELOWHEAP
- HEAP
- HEAPPOOLS
- STACK
- RPTSTG





- ALL31(option)
 - •ON For AMODE 31 programs
 - OFF For AMODE 24 programs

(is determined dynamically under CICS TS)

(also determined non-CICS with z/OS V1.2)





ANYHEAP(initial, increment, location, disp)

initial Minimum size of initial heap segment

increment Minimum size of additional segments

location BELOW (<16MB), ANYWHERE

disp
 KEEP, FREE (action when empty)

•Notes:

Used internally by Language Environment





BELOWHEAP(initial, increment, disp)

initial Minimum size of initial heap segment

increment Minimum size of additional segments

disp
 KEEP, FREE (action when empty)

•Notes:

Used internally by Language Environment





HEAP(initial, increment, location, disp, init24, incr24)

initial Minimum size of initial heap segment

increment Minimum size of additional segments

location BELOW, ANYWHERE

disp
 KEEP, FREE (action when empty)

•Notes:

- COBOL working storage (for RENT programs)
- Dynamic storage (C malloc, C++ new, PL/I ALLOCATE)






HEAPPOOLS(ON|OFF, size1, prcnt1, ..., size12, prcnt12)

• size N Up to 12 cell pool sizes to be utilized

prcnt N Percentage of HEAP(initial) to be used for cell pool

- •Notes:
 - C/C++ and Enterprise PL/I only
 - Use RPTSTG(ON) to tune settings for each application





STACK(init, incr, location, disp, dsinit, dsincr)

init Actual size of initial stack segment

incr Minimum size of additional segments

location BELOW, ANYWHERE

disp
 KEEP, FREE (action when empty)

dsinit XPLINK initial stack

dsincr XPLINK increment stack





- STACK(init, incr, location, disp, dsinit, dsincr) (continued)
 - •Notes:
 - Dynamic Save Area
 - C/C++ and PL/I local variables
 - Must use STACK(,,BELOW) when running ALL31(OFF)





RPTSTG(option)

OFF Storage report not requested

ON Generates a report of stack/heap usage

including recommended settings

•Caution:

•Use only for application tuning. Do not make RPTSTG(ON) system wide default due to significant performance impact.

Consider CICS TS dynamic storage tuning as an alternative.





Storage Report for Enclave main 01/23/01 1:18:38 PM Language Environment V02 R10.00

STACK statistics:

Initial size:	131072
Increment size:	131072
Maximum used by all concurrent threads:	29024
Largest used by any thread:	29024
Number of segments allocated:	1
Number of segments freed:	0
THREADSTACK statistics:	
Initial size:	0
Increment size:	0
Maximum used by all concurrent threads:	0
Largest used by any thread:	0
Number of segments allocated:	0
Number of segments freed:	0

•





HEAP statistics:	
Initial size:	32768
Increment size:	32768
Total heap storage used (sugg. initial size):	417624
Successful Get Heap requests:	91
Successful Free Heap requests:	52
Number of segments allocated:	4
Number of segments freed:	0
•	
•	
BELOWHEAP statistics:	
Initial size:	10240
Increment size:	2048
Total heap storage used (sugg. initial size):	168
Successful Get Heap requests:	1
Successful Free Heap requests:	0
Number of segments allocated:	1
Number of segments freed:	0





HeapPools Summary:

Cell Size	Extent Percent	Cells Per Extent		Maximum Cells Used	Cells In Use
8	10	204	0	0	0
32	10	81	0	0	0
128	10	24	1	1	1
256	10	12	0	0	0
1024	10	3	1	2	2
2048	10	1	0	0	0

Suggested Percentages for current Cell Sizes:

HEAPP(ON, 8, 1, 32, 1, 128, 1, 256, 1, 1024, 7, 2048, 1)

Suggested Cell Sizes:

HEAPP(ON, 48,, 280,, 584,, 2048,, 0)



Key Run-Time Options Diagnostics

- ABTERMENC
- ERRCOUNT
- HEAPCHK
- STORAGE
- TERMTHDACT
- TRAP
- RPTOPTS
- USRHDLR





- ABTERMENC(option)
 - ABEND Step will be ABENDed (job terminates)
 - RETCODE Step ends with return code (job continues)





- ERRCOUNT(threshhold)
 - Conditions are not counted
 - >0 The number of conditions allowed before Language Environment terminates the process
 - •Notes:
 - ERRCOUNT(0) required by PL/I for ON-unit processing and by C/C++ for signal processing





HEAPCHK(ON|OFF, frequency, delay, level, call-depth)

OFF Normal processing

ON Checks HEAP structures on get/free

frequency How often the HEAP is checked

delay Number of get/free before starting

level Number of calls to be displayed in

Heap Storage Diagnostic Report

call-depth Number of calls to be displayed for

HEAPPOOLS Serviceability





HEAPCHK(ON|OFF, frequency, delay, level, call-depth)
 (continued)

•Caution:

 Use only for application tuning/diagnostics. Do not make HEAPCHK(ON) system wide default due to serious performance impact.

•Notes:

- To generate only Heap Storage Diagnostic Report use, e.g.
 - •HEAPCHK(ON,0,0,10,0)
- To activate only HEAPPOOLS Serviceability use, e.g.
 - HEAPCHK(ON,0,0,0,5)





Heap Storage Diagnostics

reap scorag	e Diagnost	LUS				
Stg Addr	ID	Length	Entry	E Addr	E Offset	Load Mod
1FB3C038	0000000	00000C20	CEEV#GTS	0CE7C610	+00000000	CEEPLPKA
			CEEVGQP	0CE855E0	+000001FC	CEEPLPKA
			setlocale	0CC7BFA0	+000000FC	CEEEV003
			tzset	0CBD34E8	+0000059A	CEEEV003
			_cinit	0CAC3588	+00002E48	CEEEV003
			CEEZINV	0CEB4870	+00000C58	CEEPLPKA
1FB3CC58	0000000	00000828	CEEV#GH	0CE84690	+00000000	CEEPLPKA
			realloc_na	ame_buffer		
				0CC7BAD8	+00000070	CEEEV003
			setlocale	0CC7BFA0	+0000013C	CEEEV003
			tzset	0CBD34E8	+0000059A	CEEEV003
			_cinit	0CAC3588	+00002E48	CEEEV003
			CEEZINV	0CEB4870	+00000C58	CEEPLPKA





STORAGE(getheap, freeheap, stack, reserve)

getheap One byte value used to initialize every

heap allocation

freeheap One byte value used to initialize every

heap free

stack
 One byte value used to initialize every

stack allocation

reserve Amount of space to reserve for out of

storage condition processing





- STORAGE(getheap, freeheap, stack, reserve) (continued)
 - Notes:
 - STORAGE(AA,EE,,) useful for debugging
 - When HEAPCHK(ON), free elements are checked to ensure they contain the freeheap value
 - STORAGE(00,,,) is equivalent to COBOL WSCLEAR
 - •STORAGE(,,00,) is <u>very</u> expensive
 - Especially for C/C++
 - Solution: STORAGE(,,CLEAR)
 - •Sets to binary zeros the unused portion of the initial stack segment just prior to the "main" getting control
 - Available via APAR PK02614 (z/OS V1.4 and later)





TERMTHDACT(option)

QUIET Messages off, no dump

MSG Messages only, no dump

TRACE CEEDUMP with traceback only

DUMP CEEDUMP

UADUMP CEEDUMP, optional system dump

UAONLY System dump only, no CEEDUMP

UATRACE System dump and traceback

UAIMM System dump of original error





- TERMTHDACT(option) (continued)
 - •Notes:
 - UAIMM requires TRAP(ON, NOSPIE)
 - Takes dump in Language Environment ESTAE via SETRP prior to Language Environment condition handling for program checks only
 - SYSMDUMP DD card required for system dump





TRAP(option)

ON,SPIE Condition handling enabled

ON, NOSPIE Allows user applications to have their

own SPIE routine, Language Environment

condition handling will take place via the

ESTAE

OFF Condition handling disabled, some

functionality not available (AVOID)

•Notes:

•TRAP(ON, SPIE) highly recommended for normal processing





RPTOPTS(option)

OFF Options report not requested

ON Generate a report of all current

options (upon successful termination)

- •Notes:
 - Automatically included in CEEDUMP





Options Report for Enclave main 07/13/05 12:18:07 PM Language Environment V01 R07.00

7/12/2006

LAST WHERE SET OPTION Installation default ABPERC(NONE) Installation default ABTERMENC (ABEND) Installation default NOAIXBLD Invocation command ALL31(OFF) Installation default ANYHEAP (16384,8192, ANYWHERE, FREE) Installation default NOAUTOTASK Programmer default BELOWHEAP (10240, 2048, KEEP) Installation default CBLOPTS (ON) Installation default CBLPSHPOP(ON) Installation default CBLQDA(OFF) Installation default CHECK (ON) PARMLIB (CEEPRMxx) COUNTRY (KY) Installation default NODEBUG DD:CEEOPTS DEPTHCONDLMT(15) Installation default ENVAR("") SETCEE command ERRCOUNT (0)





- USRHDLR(CEEWUCHA)
 - User condition handler to provide traditional CICS TS ABEND behavior
 - Convert unhandled COBOL detected software errors to U1xxx ABEND issued by COBOL II
 - Allow EXEC CICS HANDLE ABEND LABEL statements to get control
 - Convert PL/I software-raised conditions back to APLS abends





- USRHDLR(CEEWUCHA) (continued)
 - Prevents message IGZ0014W warning of backlevel IGZETUN or IGZEOPT
 - Use CEEUOPT instead
 - Installed as usermod via CEEWWCHA
 - Found in SCEESAMP
 - •CEEWUCHA must be defined in PPT and must be available at run-time (e.g., STEPLIB, LPA, etc.)
 - Not recommended for batch





Additional Information

- All Language Environment documentation available:
 - z/OS CD collection
 - Language Environment website:
 - http://www.ibm.com/servers/eserver/zseries/zos/le/
- Language Environment Programming Reference
- Language Environment Programming Guide
- Language Environment Customization
- Language Environment Run-Time Application Migration Guide
 - Run-time Option Summary and Recommendations chapter





Appendix: AMODE 64 Run-Time Options

Existing run-time options supported in AMODE 64:

ARGPARSE/NOARGPARSE REDIR/NOREDIR

ENVAR RPTOPTS

EXECOPTS/NOEXECOPS RPTSTG

FILETAG STORAGE *

HEAPCHK TERMTHDACT *

INFOMSGFILTER TEST/NOTEST

NATLANG TRACE *

POSIX TRAP

PROFILE

- All other existing run-time options are not supported
- * indicates some suboptions have changed or are not supported





HEAPPOOLS64(ON|OFF,cell1 size, cell1 count,...,cell12 size, cell12 count)

•ON|OFF Are heappools on?

•cellX size Size of cells with this pool (8 to 64K)

•cellX count Number of cells in this pool (min 4)

NOTE: Different from AMODE 24/31 (HEAPPOOLS) – was percentage (not changing in AMODE 24/31)





- HEAP64(init64,inc64,disp64,init31, inc31, disp31, init24, inc24, disp24)
 - Controls user heap storage
- IOHEAP64(init64,inc64,disp64,init31, inc31, disp31, init24, inc24, disp24)
 - Controls I/O storage for the run-time
- LIBHEAP64(init64,inc64,disp64,init31, inc31, disp31, init24, inc24, disp24)
 - Controls heap storage usage for the run-time (non I/O)





AMODE 64 Heap Run-Time Options Parameters

init64 Initial size of above the bar storage (in MB)

inc64 Increment size of above the bar storage (in MB)

disp64 KEEP or FREE (how to treat 64 increments)

init31 Initial size of above the line storage (in bytes)

• inc31 Increment size of above the line storage (bytes)

disp31 KEEP or FREE (how to treat 31 increments)

init24 Initial size of below the line storage (in bytes)

inc24 Increment size of below the line storage (bytes)

disp24 KEEP or FREE (how to treat 24 increments)





- STACK64(initial, increment, maximum) Controls the allocation of user stack
- THREADSTACK64(initial, increment, maximum) Controls the allocation of user stack

initial
 Size of initial stack (in MB)

increment
 Size of increments of stack (in MB)

maximum Maximum stack size (in MB)

- NOTES:
- Stack is always above the bar, one contiguous segment, downward growing (XPLINK)
- Initially we reserve "maximum" space
- Only use initial size and increase in increments until maximum is reached.
- Only what is actually used counts towards MEMLIMIT

7/12/2006 ZSP04592-USEN-00 76