IBM Cognos Analytics Version 11.2.0

Getting Started User Guide



Contents

Chapter 1. Cognos Analytics offerings	1
Chapter 2. Getting started with Cognos Analytics	7
Logging in	
The Open menu	9
The Content view	
The search	11
The view switcher	
Upload files and launch components at the same time	13
Get started video tutorials and samples	14
Chapter 3. Access permissions	15
Simple and granular access permissions	15
Setting permissions for content	
Viewing your permissions for content	17
Viewing your permissions for capabilities	17
Chapter 4. Sources of data	19
Data modules	19
Packages	
Data sets	20
Creating data sets	20
Reusing report queries in data sets	23
Uploaded files	
Uploading files	
Updating data in uploaded files	27
Chapter 5. Getting started in IBM Cognos Analytics - Explorations	29
Starting an exploration from an existing dashboard or story	
Starting a new exploration from the Open menu	29
Starting a new exploration from a data asset in the Content page	
Adding a data source	
Chapter 6. Reports	31
Viewing and interacting with reports	
Run variations of reports with report views	
Report versions	
Subscribing to reports	
Chapter 7. Dashboards and stories	35
Chapter 8. Notebooks	
Creating a notebook	
Notebook actions	
Reading data from a data source	
Writing data to a data source	
Searching for data objects	43
File paths that contain a forward slash	45
Finding the ID of a file	45

Python notebook examples	
R notebook examples	
Uploading external notebooks	
Importing Watson Studio notebooks to Cognos Analytics	
Connecting Watson Studio notebooks to Cognos Analytics	
Best practices for displaying notebook visualizations in dashboards	57
Chapter 9. Managing content	59
Creating folders	
Copying or moving entries	59
Copying and pasting assets	60
Sharing content	
Sharing content from the canvas	
Sharing assets from the Team content folder	
Creating custom URLs to display and run Cognos Analytics content	74
<pre>promptParameters option syntax</pre>	76
Creating shortcuts	
Creating URLs to other sites	77
Hiding entries	
Setting properties for entries	
Chapter 10. Managing your schedules and subscriptions	
Scheduling an entry	
Differences between a schedule and a subscription	
Deleting a subscription	
Creating a job to schedule multiple entries	
Chapter 11. Personal settings	
Notifications	
My schedules and subscriptions	
Personal application settings	
Language settings	
Setting the default format for report runs	
Credentials	
Setting logging levels	
Chapter 12. Integrating with other Cognos products	
IBM Cognos Software Development Kit	
Functionality mapping from Cognos BI to Cognos Analytics	90
Move from guirks to standards mode HTML	
Opening companion apps	
Index	

Chapter 1. Cognos Analytics offerings

IBM[®] Cognos[®] Analytics is available through multiple offerings. Each offering might support different components, features, data sources, documentation, and other aspects of the product.

The following Cognos Analytics offerings are available in version 11.1.7:

Table 1. Cognos Analytics offerings	
Offering	Description
Cognos Analytics on Premises	Cognos Analytics that is installed and run in a customer's environment. Long Term Support version is 11.1.7.
Cognos Analytics Trial	Cognos Analytics on Demand, 30 day trial version, that is available in the Premium tier. The product version is updated to the latest version upon availability.
Cognos Analytics on Demand	Cognos Analytics installed on Cloud that is available digitally via self-service. The product version is updated to the latest version upon availability. This offering has three tiers: Standard, Plus, and Premium.
Cognos Analytics on Cloud Hosted	Cognos Analytics that is hosted on a cloud. The product version is updated in consultation with the customer, and it must be one of the three latest versions of Cognos Analytics. For example, if the latest version of Cognos Analytics is 11.1.7, the customer must be on version 11.1.5 or later.
Cognos Analytics for Cloud Pak for Data	Cognos Analytics as an add-on in the IBM Cloud Pak for Data. The Cognos Analytics version is updated upon availability.

For more information on Cognos Analytics on Cloud Hosted, see the license terms for this offering.

The following table specifies the functionality that is supported by different offerings of Cognos Analytics, version 11.1.7 and later. For Cognos Analytics on Demand, "Yes" with no further qualification means that the feature is applicable to all tiers. "N/A" means "Not applicable".

Table 2. Supported functionality between Cognos Analytics offerings									
Functionality	Cognos Analytics on- premises	Cognos Analytics trial	Cognos Analytics on Demand	Cognos Analytics on Cloud Hosted	Cognos Analytics for Cloud Pak for Data				
Portal	Yes	Yes	Yes	Yes	Yes				
Data modules (self- service modeling)	Yes	Yes	Yes	Yes	Yes				
Dashboards and stories	Yes	Yes	Yes	Yes	Yes				
Explorations (<u>10</u>)	Yes	Yes	Plus, Premium	Yes	Yes				
Reporting and scheduling	Yes	Yes	Premium	Yes	Yes				

Table 2. Supported functionality between Cognos Analytics offerings (continued)								
Functionality	Cognos Analytics on- premises	Cognos Analytics trial	Cognos Analytics on Demand	Cognos Analytics on Cloud Hosted	Cognos Analytics for Cloud Pak for Data			
Assistant	Yes	Yes	Yes	Yes	Yes			
IBM Cognos Analytics Reports mobile app (14)	Yes	No	No	Yes	No			
IBM Cognos Analytics Mobile mobile app (15)	Yes	Yes	Yes	Yes	No			
Jupyter Notebooks	Yes	No	No	Yes (<u>13</u>)	No			
Watson Knowledge Catalog integration	Yes	Yes	Yes	Yes	N/A			
Slack integration	Yes	Yes	Yes	Yes	N/A			
IBM Cognos for Microsoft Office	Yes	No	No	Yes	Yes			
Dynamic cubes	Yes	No	No	No	No			
Cognos SDK	Yes	No	No	Yes	No			
Cognos Workspace	Yes	No	No	Yes	No			
Access to client tools - license dependent (9)	Yes	No	No (<u>9</u>)	Yes	Yes (<u>9</u>)			
Event Studio (<u>1</u>)	Yes	No	No	Yes	Yes			
Analysis Studio (<u>1</u>)	Yes	No	No	No	No			
Query Studio (<u>1</u>)	Yes	No	No	No	No			
PowerPlay Studio - with existing licence (<u>1</u>)	Yes	No	No	No	No			
Administration	Yes	Yes	Yes	Yes	Yes			
		(Limited)	(Limited)					
IBM Support	Yes	No	Yes	Yes	Yes			
Uploading fonts and images	Yes	No	No	Yes	No			
Customization (themes, extensions, palettes, views, parameters, custom visualizations)	Yes	Yes	Yes (<u>7</u>)	Yes	Yes			
Customization (user profiles)	Yes	No	No	Yes	Yes			
Uploading files (<u>11</u>)	Yes	Yes	Yes	Yes	Yes			
Access to on-premises	Yes	Yes (<u>5</u>)	Yes (<u>6</u>)	Yes	Yes			
uala sources					(Limited)			

Table 2. Supported functionality between Cognos Analytics offerings (continued)								
Functionality	Cognos Analytics on- premises	Cognos Analytics trial	Cognos Analytics on Demand	Cognos Analytics on Cloud Hosted	Cognos Analytics for Cloud Pak for Data			
Access to cloud data sources	Yes	Yes	Yes	Yes	Yes			
					(Limited)			
Access to PowerCubes	Yes	No	No	Yes	No			
Access to Planning Analytics as a data source	Yes	Yes	Yes	Yes	No			
Access to other data sources	See	See	See	See	See			
Compatible query mode (CQM) data sources	Yes	No	No	No	No			
Dynamic query mode (DQM) data sources	Yes	Yes	Yes	Yes	Yes			
Execution of triggers	Yes	No	No	Yes	No			
IBM ID authentication	Yes	Yes	Yes	Yes	No			
On-premises or cloud- based authentication providers	Yes	No	No	Yes	No			
Single signon (<u>2</u>)	Yes	No	No	Yes	Yes			
Report output to file system	Yes	No	No	Yes (<u>12</u>)	No			
Report bursting	Yes	No	No	Yes	Yes			
Access to the underlying file system	Yes	No	No	No	No			
GO Sales database samples	Yes	No	No	Yes	No			
Samples based on uploaded files	Yes	Yes	Yes	Yes	Yes			
Multiple users per license	Yes	Yes (<u>4</u>)	Yes	Yes	Yes			
Per user pricing	Yes	N/A	Yes	Yes	No			
PVU/capacity pricing	Yes	N/A	No	Yes	No			
Multiple environments (development, production)	Yes	No	No	Yes	Yes			
Long Term Support (LTS) release - 11.1.7	Yes	Yes	Yes	Yes	Yes			

Table 2. Supported functionality between Cognos Analytics offerings (continued)								
Functionality	Cognos Analytics on- premises	Cognos Analytics trial	Cognos Analytics on Demand	Cognos Analytics on Cloud Hosted	Cognos Analytics for Cloud Pak for Data			
Multi-dispatcher environments	Yes	Yes	Yes	Yes (<u>3</u>)	Yes			
Minimum number of users	N/A	1	1	100	No			
Maximum number of users	N/A	5	N/A	N/A	No			
Digital purchase	No	Yes	Yes	No	No			
Access on-premises printer	Yes	No	No	No	No			
Works with MotioCI	Yes	No	No	No (<u>8</u>)	No			
Import and export of deployments	Yes	No	No	Yes	Yes			
Audit extensions	Yes	No	No	No	No			
Save to cloud	Yes	No	No	Yes (<u>12</u>)	Yes			
Kerberos Client for SSO	Yes	No	No	No	No			
Creating jobs	Yes	No	No	Yes	Yes			

The following list contains additional information related to table 2:

- 1. Legacy studios include Event Studio, Query Studio, Analysis Studio, and PowerPlay Studio. The studios can be explicitly enabled only in Cognos Analytics on-premises.
- 2. Single signon is available with OIDC authentication providers, which support this feature.
- 3. In Cognos Analytics on Cloud Hosted, support for multi-dispatcher environments is limited to production environments.
- 4. Cognos Analytics trial supports up to 5 users.
- 5. Cognos Analytics trial can access 1 on-premises data source.
- 6. Cognos Analytics on Demand is limited to 2 secure gateway connections that can access 5 onpremises data sources per data source.
- 7. Standard tier users can use custom visualizations published by other users. Plus tier users have the same privileges as Standard users, and can also develop custom visualizations. Premium tier users have the same privileges as Plus users, and can also upload visualizations that were developed by other users.
- 8. Cognos Analytics on Cloud Hosted might work with MotioCI. However, IBM doesn't claim support for this configuration, and it doesn't support the plug-in that enables "Active Versioning" and "Authoring Integration."
- 9. Client tools that are currently available for download include Framework Manager and Transformer. Framework Manager can be used with Cognos Analytics on Demand only if the customer has an existing support and subscription (S&S) for the on-premises offering, and only as a means to move the on-premises metadata models to the on Demand offering. The expectation is that new metadata models will be created in Data Modules. Otherwise, Framework Manager is not provided with the on Demand offering. Cognos Analytics for Cloud Pak for Data supports only Framework Manager.
- 10. The Explore component is available in Cognos Analytics versions 11.1.x and later.

- 11. The limit per one upload of data is 100 MB. The limit of stored data per user is 500 MB.
- 12. Save to cloud is available to Cognos Analytics on Cloud Hosted customers starting with Cognos Analytics version 11.1.5.
- 13. Available with the subscription to Watson Studio. For more information, see <u>this article</u> (https:// medium.com/ibm-watson/ibm-cognos-analytics-watson-studio-cloud-better-togetherac011059878f).
- 14. Compatible with iOS 13.x and 14.x, iPad OS 13.x and 14.x, and Android 10.x and 11.x.
- 15. Compatible with iOS 13.x and 14.x.

Cognos Analytics on Cloud server locations

Cognos Analytics on Cloud is hosted in the following locations:

- Washington, DC
- Amsterdam, Netherlands
- Sao Paulo, Brazil
- Tokyo, Japan
- Sydney, Australia

Cognos Analytics on Cloud Hosted can be deployed on any IBM Cloud data center, but currently has a footprint in the following locations:

- Montreal, Canada
- Washington, DC
- San Jose, CA
- London, England
- Frankfurt, Germany

6 IBM Cognos Analytics Version 11.2.0 : Getting Started User Guide

Chapter 2. Getting started with Cognos Analytics

IBM Cognos Analytics integrates reporting, modeling, analysis, dashboards, stories, explorations, and event management.

After Cognos Analytics is installed and configured, administrators set up security and connect data sources. You can get started yourself by uploading your own data files, and creating visualizations in dashboards or stories. Using data modules and packages, report authors can create reports for business users and analysts. Administrators maintain the system on an ongoing basis.

Whether you're an analyst, report author, data modeler, or an administrator, you start by logging in to the Cognos Analytics portal from your desktop or mobile device. For more information, see <u>"Logging in" on</u> page 9.

For links to videos, getting started resources, expert blogs, events, and more, you can visit the <u>IBM</u> <u>Cognos Analytics community</u> (https://community.ibm.com/community/user/businessanalytics/ communities/community-home?CommunityKey=6b10df83-0b3c-4f92-8b1f-1fd80d0e7e58).

If you want to start with video tutorials and sample data, see <u>"Get started video tutorials and samples" on</u> page 14.

Depending on the work you do, you use different areas of the user interface. Cognos Analytics capabilities control access to the different areas of the interface, and you see only those interfaces that you work with.

Welcome portal

For a new user, this is the perfect place to start exploring Cognos Analytics.



Dashboards and stories

View, monitor, and communicate data insights and analysis with dashboards or stories. You can assemble a view that contains visualizations such as graphs, charts, plots, tables, maps, or any other visual representation of data. Enrich dashboards and stories with web pages and other content.

You enter the IBM Cognos Analytics dashboards or stories user interface from the Cognos Analytics portal

by opening an existing dashboard from **Team content** or **My content**, or by clicking **New** +, and then **Dashboard** or **Story**.

For more information, see the Cognos Analytics Dashboards and Stories User Guide.

Reports

Create and edit a wide range of professional reports. Use templates or customize your reports with prompts, bursting, advanced charts and visualizations.

You enter the IBM Cognos Analytics - Reporting user interface from the Cognos Analytics portal by

opening an existing report from **Team content** or **My content**, or by clicking **New** +, and then **Report**.

For more information, see the Cognos Analytics Reporting Guide.

Explorations

Explore is a flexible workspace where you can discover and analyze data. You can also explore an existing visualization from a dashboard or story. Uncover hidden relationships and identify patterns that turn your data into insights.

You enter the IBM Cognos Analytics Exploration user interface from the Cognos Analytics portal by

opening an existing Exploration from **Team content** or **My content**, or by clicking **New** +, and then **Exploration**.

For more information, see the Cognos Analytics Explorations User Guide.

Notebooks

If IBM Cognos Analytics Jupyter Notebook is enabled in Cognos Analytics, you can work with notebook documents, also referred to as notebooks, much like with other content in Cognos Analytics.

You enter the notebook user interface from the Cognos Analytics portal by opening an existing notebook

from **Team content** or **My content**, or by clicking **New** +, and then **Notebook**.

For more information, see "Getting started with Notebook" in the *IBM Cognos Analytics Notebook User Guide*.

Data modules

Modelers and administrators create data modules and make them available to users for use with reports, dashboards, or stories. You can use the IBM Cognos Analytics web modeling interface to quickly create data modules from various sources, such as data servers, uploaded files, packages, and previously saved data modules. The tool is intent-driven and AI-infused and generates a data module by using keywords that you define.

You enter the IBM Cognos Analytics web modeling user interface from the Cognos Analytics portal by

opening an existing data module from **Team content** or **My content**, or by clicking **New** +, and then **Data module**.

For more information, see the IBM Cognos Analytics Data Modeling Guide.

Manage and administer

Create and manage accounts (users, groups, and roles), schedules, or data server connections. Perform configuration tasks, and customize the product experience and user interface.

You enter the IBM Cognos Analytics administration user interface from the Cognos Analytics portal by clicking **Manage**, and then selecting the tabs that represent the different administration areas, such as **Data server connections** or **Configuration**. To access the legacy administration tool for more options, tap **Administration console**.

Changes that you make in either the **Manage** interface or the **Administration console** affect both interfaces.

For more information, see IBM Cognos Analytics Managing Guide and the IBM Cognos Analytics Administration and Security Guide.

Logging in

IBM Cognos Analytics supports authenticated and anonymous user access. To use the application as an authenticated user, you must successfully log in.

To log in, provide your credentials, such as user ID and password, as required by your organization. Anonymous users do not need to log in.

If multiple namespaces are configured for your Cognos Analytics environment, you can log in to the different namespaces in the same session. Each namespace requires its own credentials.

Procedure

- 1. In the login page, select the namespace that you want to log in to.
- 2. Type your user ID and password, and click **Log in**.
 - Your session starts.
- 3. To log in to a different namespace in the same session, from the personal menu her in the application bar, click **Log into an additional namespace**.

What to do next

You log out to end your session. Even if you used multiple namespaces in the session, you log out only

once. To log out, from the personal menu R in the application bar, click **Log out**. If you close your web browser without logging out, your session ends.

The Open menu

The **Open menu** is the main access point to the IBM Cognos Analytics content and functionalities.

Click the **Open menu** icon \equiv in the application bar to access the menu options.



From this menu, you can access the existing Cognos Analytics content (**Content** option), and start creating new content (**New** option). You can also access the recently viewed content (**Recent** option), start uploading your own data files (**Upload files** option), and access the administrative user interfaces (**Manage** option).

Click the **Content** option to view the **My content**, **Team content**, and other folders. The Cognos Analytics content is stored in these two folders. The content includes any objects that can be created and used in Cognos Analytics: dashboards, reports, stories, explorations, data modules, but also data files, packages, and more.

For more information, see "The Content view" on page 10

The Content view

The **Content** view shows objects that are created and managed in Cognos Analytics.

The objects such as dashboards, stories, reports, explorations, notebooks, and more, can be considered primary content types. In addition to these primary content types, there are objects such as folders, data modules, packages, uploaded files, jobs, schedules, events, URLs, shortcuts, and more, that users and administrators create or import to provide data, and manage the content.

To access the content view, click the **Open menu** icon \equiv in the application bar, and select the **Content** option. The following page is opened:

≡ IBM Cognos Analyti	cs 🗍 3 iter	ns open 🗸 🗸		Q Dash	ooards				0	?	¢	2
Content							Upload	l data	Ť	New	+	
My content	Team content	External content	Samples									
Team content / Sampl	les / Dashboards			Ŷ	t↓	C7	Ø	G	Ø	88	=	i
Name				Туј	e		Last	Modifi	ed			^
Policy anal	ysis			Da	hboard		2/27	/2018	, 2:51 F	PM	:	
🔲 🔠 Product lin	e dashboard			Da	hboard		2/14	/2018	, 9:53 A	M	:	
🔲 🔠 Storm ever	nts			Da	hboard		5/14	/2018	, 1:12 F	PM	:	Ŷ

The page shows the following folders (tabs):

Team content

This is the main folder where all shared application content is stored. The items in **Team content** are public and available to all Cognos Analytics users with proper permissions.

My content

Items in this folder are private, and only you can see them.

Samples

This folder is available when product samples are installed.

External content

This folder is available when the **Watson Studio URL** is configured in the **Manage** administration component.

Custom folders

Custom folders are created by administrators for specific user roles. If such folders exist, they are displayed on separate tabs. Only members of roles with permissions for a specific folder can view the folder.

The contents of each folder can be displayed in the **List view** 😬 (default) or **Tiles view** 😬.

The folder toolbar includes the options to display and organize multiple items. For example, click the

Settings icon to change the row size, or the **Tiles view** icon to change the display of items from list to tiles. The options in the toolbar change depending on which and how many items are selected.

Select an individual item, and click its **Action menu** : . The menu contains a complete list of actions that are available for the selected item, based on the user permissions. From this menu you can edit an item, view its properties, add a shortcut, or delete the item.

The search

Search is a quick and easy way to find content in your IBM Cognos Analytics application.

You can search for items such as dashboards, stories, data modules, reports, folders, and so on. You can also search for table or column labels, XML report specifications, URL items, shortcuts, templates, and more. Search doesn't return results for content that's archived, but you can access archived content from a report that's listed in one of your folders.

IBM Cognos Analytics 🗇 3 items open 🗸 🗸 ? Д, Saved searches Content Dashboards Samples My content External content Team content Samples Team content / Caching Y ↑↓ C7 O G ŝ Name Last Modified Type \square Data Table Report Report 2/12/2021, 10:28 AM Report Simple List Report 2/12/2021, 10:28 AM 2/12/2021, 10:17 AM Simple Vida Report Report

The search field is located in the application bar, as shown in the following screen capture:

To find items, type keywords, and click the Enter key. After the search results are listed, you can save your search by clicking the **Save search** button. If your search returns too many results, you can click the filter

icon ee , and select the options that you want. The filter option is only available after you do an initial search.

≡ IB	M Cognos Analytics		Q weather re	ports	×	0	?	¢	8
Sh	owing results for 'weather reports'				Close	Save	search	B	
Sho	wing 6 items							8	
	Name	Location		Туре	Last Mod	fied			^
	Historical weather report	Team content > The Weather Co	mpany, an I	Report	11/4/202	0, 2:10 P	М	:	
	B Historical weather report	Team content > smartsAutomat	on > The We	Report	11/4/202	0, 2:10 P	М	:	1
	Examine coffee hourly sales by store	Team content > Samples > By in	dustry > Reta	Report	2/2/2021	, 3:09 PM	1	÷	

From the search results page, you can initiate actions on the returned items. If you select multiple items (by clicking their check boxes), the related actions that are available for all or at least one item are shown in the actions toolbar, above the search results.

≣ IBM Cognos Analytics ☐ 기 1 item open ∨	୍ go s	ales	×	0	ф (
Showing results for 'go sales'			Close	Save search	n 🗎
Showing 50 items 49 items selected	Create a new job 🍫 🛛 Ado	d to job + Take owners	hip 🗷 Add sh	ortcut 🏟	Cancel
Name	Location	Туре	Last Modifie	d	Â
GO sales map	Team content > Samples > By feature > Con	e Report	3/9/2021, 9:	:56 PM	
G0 sales performance	Team content > Samples > By feature > Con	e Report	3/9/2021, 9:	:56 PM	
GO sales (analysis)	Team content > smartsTestUI > Models_une	en Package	6/8/2016, 13	1:46 AM	v

To view the actions for a specific item, select the check box for this item (all other items must be

deselected), and click its **Action menu** icon [‡]. The actions that are available for the selected item are shown. For example, the following screen capture shows actions for a report.

≡ IBM Cognos Analytics آت 2 items open ∨	۵	go sales	×	o 🖓 🗘 🔊
Showing results for 'go sales'			Close	Run as
Showing 50 items				Edit report Create report view
1 item selected	Ma	ore + Create ~	Copy to 📋	Create a new job
Name	Location	Туре	Last Mor	Add to job
GO sales map	Team content > Samples > By feature > C	Report	3/9/202	Share
GO sales performance	Team content > Samples > By feature > C	Report	3/9/202	Add shortcut
🔲 🖻 GO sales (analysis)	Team content > smartsTestUI > Models	Package	6/8/201	Copy to
				Details

The same actions are available from the actions toolbar above the items.

The view switcher

The view switcher in the application bar provides a convenient way to navigate between the open views, and close them when they are no longer needed.

You can navigate between different types of items, such as folders, reports, dashboards, stories, schedules, from this view.



Upload files and launch components at the same time

Use **Quick upload** to upload files to IBM Cognos Analytics 11.1.0 and simultaneously start a data module, exploration, dashboard, or notebook.

Drag files onto the welcome page to activate the **Quick upload** functionality. When **Quick upload** appears, drop the files into the appropriate box to immediately start building a data module, exploration, dashboard, or notebook. The uploaded files are stored in the folder from which you uploaded them, or in your **My content** folder.



For more information about uploaded files, see "Uploaded files" on page 25.

Get started video tutorials and samples

If your administrator installs and configures the samples that are available with IBM Cognos Analytics, you can experiment with sample data, metrics, and report templates.

If you're a beginning user, as part of the base samples, there are Get started tutorials with samples (including data), videos, and written procedures to guide you through creating your first reports, active reports, dashboards and stories.

These **Get started** samples and the sample data are in **Team content**, in the **Get started** folder. The **Data** folder includes Microsoft Excel files that were uploaded and saved for you to use with the **Get started** tutorials. The **Version 11.0.x base samples** report is added only to inform you about the version of IBM Cognos Analytics that these samples are included with. To complete the tutorials, open the samples to

see the finished product, then click the **Play** button \triangleright to watch the tutorial video. For the dashboard samples, the **Play** button is embedded.

For more information, see the IBM Cognos Analytics Samples Guide.

Chapter 3. Access permissions

Access permissions are used to secure the organization's data.

Your administrator adds you to the groups and roles that have the capabilities and permissions you need to work with secured functions, features, and your organization's content. For example, report authors typically have access to the reporting, but not the managing part of the user interface. Members of the report author role have **Write** permission on a report, but members of a sales group might have only **Run** permission for the same report.

If you want to see what you are permitted to do with a specific report or other entry, see <u>"Viewing your</u> permissions for content" on page 17.

If you lack sufficient access permissions for an item, item owners or users with more extensive access permissions can authorize you to use their credentials. For more information, see <u>"Managing your</u> credentials" on page 87.

For information on administering user access to groups, roles, and capabilities, see the *IBM Cognos Analytics Managing Guide*.

Simple and granular access permissions

Access permissions determine a user's ability to perform a specific action, or access a feature or object.

Permissions for a specific user are a combination of permissions for that user and permissions for the groups and roles where the user is a member. When a user is a member of more than one group or role, deny permissions for one group or role take precedence over granular permissions for a different group or role.

Users have **Read**, **Run**, **Write**, and **Full** permissions for items. These simple permissions represent combinations of more granular permissions that administrators use to control access.

Simple permissions mapped to granular permissions

The following simple permissions include combinations of granular permissions:

Read

Includes the read and traverse granular permissions.

Run

Includes the read, execute, and traverse granular permissions.

Write

Includes the read, write, execute, and traverse granular permissions.

Full

Includes the read, write, execute, traverse, and set policy granular permissions.

Granular permissions and permitted actions

The underlying, granular permissions are described in the following list:

Read

View all the properties of an entry, including the report specification and report output.

Note: To run a report with full interactivity, a user must have read permissions on the package or data model that is referenced in the report. For more information about the actions you can do in a report that runs with full interactivity, see "Limited and fully interactive reports" in the *IBM Cognos Analytics Reporting User Guide*.

Create a shortcut to an entry.

Write

Modify properties of an entry.

Delete an entry.

Create entries in a container, such as a package or a folder.

Modify the report specification for reports created in Reporting and Query Studio.

Create new outputs for a report.

Execute

Process an entry.

For entries such as reports, agents, and metrics, the user can run the entry.

For data sources, connections, and signons, the entries can be used to retrieve data from a data provider. The user cannot read the database information directly. The report server can access the database information on behalf of the user to process a request. IBM Cognos software verifies whether users have execute permissions for an entry before they can use the entry.

For credentials, users can permit someone else to use their credentials. To use the run as the owner report option, a user must have execute permissions for the account.

Set policy

Read and modify the security settings for an entry.

Traverse

View the contents of a container entry, such as a package or a folder, and view general properties of the container itself without full access to the content.

Setting permissions for content

Set access permissions to specify which users, groups, or roles can access your content.

About this task

You can set permissions for content that you own, such as reports, dashboards, stories, packages, and so on. Permissions can be granted, denied, or set as default.

Note: A value of **Default** means that permission is neither granted nor denied.

For information about the types of permissions that you can specify for entries, see <u>"Simple and granular</u> access permissions" on page 15.

When you set access permissions, you can reference both authentication provider users, groups, and roles, and Cognos groups and roles. However, if you plan to deploy your application in the future, we recommend that you use only the Cognos groups and roles to simplify the process.

Procedure

- 1. In **Team content** or **My content**, find your entry, and from its context menu \cdot , click **Properties**.
- 2. On the **Permissions** tab, select the check box **Override parent permissions**, and click the add + icon.
- 3. Open the namespace that contains the users, groups, or roles for which you want to specify

permissions for the entry. To quickly find the entries, click the search ${\cal Q}$ icon, or click the filter ∇ icon to narrow the view of entries within the namespace.

- 4. Select the users, groups, or roles that you need. You can control-select multiple entries. Click **Add**. The selected users, groups, or roles are added to the security policy of your entry with the basic permission **Read**.
- 5. To change the permission to **Run**, **Write**, or **Full**, click the set access icon, and change the permission.
- 6. Click on the permission name to view the granular permissions that this permission is comprised of. To
 - change the granular permissions, click the set access 🖄 icon for a permission, and change the access type to **Grant**, **Deny**, or **Default**.
- 7. If you want the children entries inherit the same permissions, select the **Apply to all children** check box.
- 8. Click Apply.

Viewing your permissions for content

To secure IBM Cognos Analytics content, administrators assign permissions. You can check your permissions for a report or another entry in the properties for the entry.

About this task

The Read, Run, Write, and Full permissions represent groupings of more granular permissions that administrators assign. For more information, see <u>"Simple and granular access permissions" on page 15</u>.

Procedure

- 1. For an entry in a list, tap the context menu ; , and then tap **Properties**.
- 2. On the **General** tab, tap **Advanced**.

View the **Permission** property, and your permission value for the entry.

Viewing your permissions for capabilities

As a user or member of a group or role, you are assigned the capabilities that you need to work with different IBM Cognos Analytics functions and features.

About this task

If you are missing a capability that you require, contact your administrator.

Procedure

- 1. Tap your personal menu $\stackrel{\textbf{O}}{\rightarrow}$, then tap **Profile and settings** > **Profile**.
- 2. Under Advanced options, tap View details for either Groups and roles or My capabilities.

18 IBM Cognos Analytics Version **11.2.0** : Getting Started User Guide

Chapter 4. Sources of data

To create and run reports, dashboards, stories, or explorations you need data. This data might be made available to you by an administrator who creates packages or data modules, or you could upload your own data files.

You can use data modules, packages, data sets, and uploaded files as sources of data for your IBM Cognos applications.

When data modules and models are built, and queries are planned and executed, the data source is required to describe the column data type to the query service. The query service maps the source column data types to the types it supports. If the source data type is not supported by the query service, the query service treats it as an unknown type. For more information, see "Supported SQL data types" in *IBM Cognos Analytics Data Modeling Guide*.

Data modules

Data modules contain data from data servers, uploaded files, data sets, other data modules, and from relational, dynamic query mode packages.

Data modules are created in the web modeling component in IBM Cognos Analytics, and saved in **Team content** or **My content**. You can use multiple input sources for a single data module.

Tip: If you create a data module using data from an uploaded file and you want the data to be available to other users, store both the data module and the file in **Team content**. This ensures that another user can run a report that references the data. This restriction applies to report authors and consumers. Administrators can run reports that use data from any user's **My content** folder.

Data modules can be used as sources for reports, dashboards, stories, explorations, notebooks, data sets, and other data modules.

For more information, see the IBM Cognos Analytics Data Modules Guide.

Data modules that are sourced from IBM Planning Analytics cubes are created in the administration component.

Packages

A package is a subset of a model, which can be the whole model, that is made available to the IBM Cognos Analytics application.

Relational packages are created in IBM Cognos Framework Manager, and OLAP packages in IBM Cognos Cube Designer and in IBM Cognos Administration. For more information, see the chapter on publishing packages in the *IBM Cognos Framework Manager User Guide*.

Not all types of packages can be used in all Cognos Analytics components. Only Reporting can use all types of packages traditionally supported in earlier versions of Cognos Analytics.

For dashboards and stories, the following packages are supported:

- Relational, dynamic query mode packages.
- Relational, compatible query mode packages if there is a JDBC connection defined for each data source in the package.
- Dimensional OLAP packages that are based on PowerCubes, dynamic cubes, TM1 data sources, dimensionally modeled relational (DMR) data sources, and other data sources.

The modeling component supports only relational, dynamic query mode packages as sources for data modules.

For more information, see the IBM Cognos Analytics Data Modeling Guide.

Note: Cognos Analytics doesn't support Framework Manager namespaces, which are containers that organize and uniquely qualify content in a model. The namespaces are shown as folders when Framework Manager packages are viewed in data modules, dashboards, and other content.

Data sets

Data sets are customized collections of data items that you use frequently. As you make updates to the data set, the dashboards, stories, or explorations that use that data set are also updated the next time you run them.

You can create data sets from packages or data modules, and use as sources to create dashboards, stories, explorations, and data modules.

You can't create a report directly from a data set. However, to use the data from the data set in a report, create a data module from the data set, and then use the data module as a source for your report.

The data set mechanism is based on the Cognos Analytics report foundation. You add data to a data set in a similar manner as you add data to a list report. You can switch between **Page design** and **Page preview** modes. The **Query** view provides an alternative way to modify the data sets. In this view, you can copy and paste queries from existing reports, manage advanced filters and prompts, and rename queries.

nsertable objects	₩ ∇ ~ ₹↓ ~	···· 🔟		
°ta 🔟	Dealer Name	City	Address	Current Quarter [Quantity Sold]
0 End	Weston Auto	Arvada	9825 W 58th Ave	307
Doo a	Colfax Auto	Denver	1350 W Colfax Ave	267
Seles	Northern Auto Sales	Denver	3320 W 38th Ave	338
>	Suwanda's Auto	Westminster	200 W 136th Ave	213
> I Recalls	Great Outdoors Auto	Denver	9190 E 33rd Ave	324
> Dealers	South Parker Auto	Aurora	6462 S Parker Rd	271
> I Models	Narezney's Auto	Colorado Springs	1905 S Federal Blvd	257
	North Parker Auto	Aurora	2651 Parker Rd	277
	Club Auto Sales	Federal Heights	9190 N Federal Blvd	291
	Broadway Auto	Littleton	6300 S Broadway	219
-	Summarize det: Row suppressic Reset	ailed values, suppre	ssing duplicates, for rel	ational data sources

Here is an example of a data set in the **Page preview** mode.

Creating data sets

Create data sets to group customized collections of data items that you use frequently.

If a data set is based on a package with multiple data server connections or signons, the connection or signon that you choose is saved with the data set. If the package connection information changes later, users might see the ambiguous connection message. To avoid this message, edit the data set choosing the new connection or signon, and save the data set using the **Save as** option. Select yes when asked whether you want to overwrite the data set. The data set is saved with the new connection or signon and its subsequent refreshes use the new information.

Before you begin

The package or data module that you plan to use as a source for your data set must already be saved in **Team content** or **My content**.

About this task

The list in the data set can be associated with only one query. If you want to add data items from different queries to your data set, you can create a custom query in the **Queries** view that contains data items from different queries.

When creating or editing data sets, you can reuse queries from Cognos Analytics reports. For more information, see "Reusing report queries in data sets" on page 23.

Procedure

- 1. Locate the package or data module in **Team content** or **My content**.
- 2. From the package or data module context menu , click **Create data set**.

The data set editor is opened in the **Page design** mode.

3. Drag the data items from the **Insertable objects** pane to the work area. The items appear as columnar data in a similar fashion to a list report.

To preview data in the data set, switch from the Page design mode to the Page preview mode.

4. For relational data or for data modules, select the **Summarize detailed values, suppressing duplicates, for relational data sources** checkbox.

If you aren't sure if this checkbox must be selected, clear it and then select it again to see how the data is aggregated. Condensed data with fewer rows usually leads to better performing reports and dashboards. A reason for not aggregating the data in your data set is that you lose some details in the process, and the data from one system might not match the data from another system. This is especially true for calculations, such as an average.

5. Select **Row suppression** if you want to hide rows with no data or zeros.

Suppressing rows without data gives you a more concise view of your data set.

6. Refine the data in the data set by using the options in the on-demand toolbar

Ŧ	$\nabla \sim$			Ū
---	---------------	--	--	---

To view the toolbar, click any column.

To add filters to the columns or individual items of the data set, click the item, and then click the filter

icon abla in the toolbar. You can add a customized filter or use one of the predefined filters.

To sort the values, click the sort icon \mathbb{F} , and select from the available sort options.

To view the column expression, click the **More** icon , and select **Edit Query Expression**.

7. Use the **Query** view to access more data set functionality.

From the **Data set** menu, click **Queries** to open the Query Explorer.

In this view, you can copy and paste queries from existing reports, manage advanced filters and prompts, or rename the queries.

Here is an example of a data set in the **Queries** view:

Insertable objects	₽ % ⊡ ฿ ~	ē B	Query			
Ø.			DATA			
			Auto group & sum	imarize Yes		
Query	Initial query		QUERY HINTS	QUERY HINTS		
dP Join	Inniai query		Auto-sort			
U Union			Maximum rows re	trieved		
∩ Intersect	Report query		Use local cache			
⊖ Except		_	Refresh on promp	ot		
sqL SQL		211	MISCELLANEOUS	5		
MOX MDX		Initial que	ery Name	Joined query		
	Joined query					

Note: The query names are used as table names when the data set is used to create data modules. Use logical names that clearly describe the data when renaming the queries.

8. Click the **More** icon to access additional functionality:

	Page preview 🗸 :		
	Open report from clipboard		
	Copy report to clipboard		
Q	Find		
0	Validate report		
	Validate options		
	Auto correct		
	Show generated SQL/MDX		
XML.	Show specification		

Click Validate report to validate the data set, or click Show generated SQL/MDX to view the data set SQL.

- 9. Click the save icon 🛅, and choose one of the following options to save the data set:
 - To save the data set for the first time or to save changes to the data set, click **Save**. This option saves the metadata, but doesn't load the data. Depending on the data set, loading data might take some time.
 - To save an updated data set as a new data set, click **Save as**. This option saves the metadata, but doesn't load the data. Depending on the data set, loading data might take some time.
 - To save the data set and load the data, click **Save and load data**. In addition to saving the new or changed metadata, this option loads data. The data is immediately available when you create a dashboard or story.

Results

The data set object 80 is created in a location that you saved it to.

What to do next

To edit the data set, open it from Team content or My content.

You can replace data items in the data set with data items from a different query. In the **Page design** or **Page preview** mode, click the **Reset** button. The previously selected data items are removed, and you can start adding new ones to the list.

You can also replace the data module or package that was used as a source for the data set. Right-click the source name in the **Insertable objects** pane, and select the **Replace data module** or **Replace package** option, as shown in the following screen capture:



Reusing report queries in data sets

You can reuse existing queries from Cognos Analytics reports by copying either individual queries or entire report specifications into data sets.

The data set and the report from which you copy the queries must be based on the same type of data source, either a data module or a package.

When you copy an individual report query, you add the query to the data set, and can continue working with the data set.

When you copy the report specification, the data set is overwritten and you can use the query (or queries) from the report in the data set. The report layout is not copied. The data set is renamed to the default **New data set**. You can then save it as a new data set.

Procedure

- 1. Create or open an existing data set.
- 2. From **Team content** or **My content**, open the Cognos Analytics report in the edit mode.
- 3. Use the following steps to copy an individual query into your data set:
 - a) In the report, from the **Report** menu, click **Queries** to open the report **Queries** view.
 - b) Right-click the query that you want to copy, and click **Copy**.
 - c) Go back to the data set, and from the **Data set** menu, click **Queries**.
 - d) Right-click anywhere in the empty space in the **Queries** view, and click **Paste**. The new query is added to the view.
 - e) Save the data set.
- 4. Use the following steps to copy the report specification:
 - a) From any page in the report, click the **More** icon 🕴 , and select **Copy report to clipboard**.
 - b) Go back to the data set, click the **More** icon 🕴 , and select **Open report from clipboard**.
 - c) Paste the report specification into the empty box that is displayed, and click **OK**.

You are back in the data set list view. The data source and the query in the data set were replaced. The data set name is shown as **New data set**, even if you started with a data set named differently. d) Open the **Queries** view. All queries from the report are copied into the data set.

- e) Save the data set using the **Save as** option.
- 5. From the **Data set** menu, click **Pages** > **Page1**. You are back in the data set list view.
- 6. Click the **Reset** button to break the list association with the previous query.

The data items are removed from the list. You can now add data items from a different query, including the copied report queries, to the list.

7. In the Insertable objects pane, click the Data items tab \widehat{III} .

The report queries and their data items are shown in the tab.

- 8. Drag items from one query to the data set list.
- 9. Save the data set.

Results

Here is an example of the **Queries** view after a query labeled Report query was copied into the data set. The report query was joined with a preexisting query labeled Initial query.



Later, the data items from the Joined query were used to populate the list in the data set.

Insertable objects	₩				
°te 🔟	City	Dealer Name	Phone number	Model	Current Month [Quantity Sold]
	Arvada	Weston Auto	1 (303) 449-1354	Champlain	30
 > iii Initial query > iii Report query > iii Joined query iii City iii Dealer Name iii Phone number 	Aurora	South Parker Auto	1 (303) 449-5441	Champlain	25
	Denver	Great Outdoors Auto	1 (303) 808-3333	Labrador	155
	Colorado Springs	Narezney's Auto	1 (719) 874-4559	Champlain	25
	Denver	Northern Auto Sales	1 (303) 449-6548	Beaufort	100
	Littleton	Broadway Auto	1 (303) 326-6889	Beaufort	70
D Model	Denver	Colfax Auto	1 (303) 808-9383	Champlain	25
Σ Current Month [Quantity Sold]	Aurora	North Parker Auto	1 (303) 808-3432	Champlain	25
	Arvada	Weston Auto	1 (303) 449-1354	Salish	115
	Denver	Colfax Auto	1 (303) 808-9383	Salish	100
	Aurora	South Parker Auto	1 (303) 449-5441	Salish	105
	Arvada	Weston Auto	1 (303) 449-1354	Hudson	200

Uploaded files

If you want to do some quick analysis and visualizations with data files, you can upload the files to IBM Cognos Analytics by yourself. Your data files must meet size and structure requirements.

The data in the files must be in a simple columnar format. Pivot tables or crosstabs aren't supported.

The size limits for uploaded files are configured by administrators in **Manage** > **Configuration** > **System** > **Data**. The settings that need to be modified are **Size limit per upload of data (MB)** and **Size limit of stored data per user (MB)**.

The following file size limitations apply to individual users:

- Maximum size of each individual file. The default is 100 MB.
- Maximum size of all uploaded files. The default is 500 MB.

The file types that you can upload into Cognos Analytics are specified below.

Microsoft Excel workbook files

The supported Microsoft Excel file formats include .xls and .xlsx workbook files.

The file formats .xlsb and .xlsm aren't supported.

All worksheets in a multi-tab workbook are uploaded simultaneously. Each worksheet appears as a separate table in Cognos Analytics.

The following conditions apply to uploading Microsoft Excel files:

- .xlsx files that are saved in OpenOffice aren't supported.
- Password-protected Excel files aren't supported.
- Filters in Excel files are ignored. You can use the filtering options in data modules to reapply the filters.
- Comments before the first header row are interpreted as column headers.

Text before the first row that describes the worksheet is incorrectly read as a column header. If you need a description of the worksheet, leave an empty row at the end of your data, and add the description under the empty row.

• Totals and subtotals are treated as part of the data.

Totals can be mistaken as unsummarized data, and give misleading results. Consider removing totals and subtotals from your data before uploading the file.

• Each file can contain a maximum of 2000 columns.

However, for better query performance, avoid uploading files with hundreds of columns. Try to remove redundant columns and rows from the files before uploading the files.

Delimiter-separated values files

The supported delimiter symbols include commas, tabs, semi-colons, and pipes (|). The file extension can be .csv, .tsv, .tab, or .txt.

The following conditions apply to uploading delimiter-separated values files:

- Quotation mark characters escape literal values. Single quotation marks (') and double quotation marks (") are supported.
- Record separators separate rows. Newline (\n), carriage return (\r), and carriage return followed by newline (\r\n) are supported.
- If your file is encoded as Unicode, it must contain a byte order mark (BOM) as the first character.
- Each string value in a file can contain a maximum of 5000 characters. Any extra characters are truncated.

• The date and time values in the files must be in a supported format. Otherwise, the data might not be rendered properly in visualizations. Cognos Analytics supports the ISO 8601 standard formats for times.

The following date formats are supported:

- M/d/yy
- MMM d, y
- MMMM d, y
- dd-MM-yy
- dd-MMM-yy
- yyyy-MM-dd

The following time formats are supported:

- h:mm a
- h:mm:ss a
- h:mm:ss a z
- HH:mm
- HH:mm z
- HH:mm:ss
- HH:mm:ss.SS
- HH:mm:ss z
- HH:mm:ss.SS z

Jupyter Notebook (.ipynb) files

You can upload Jupyter Notebook (.ipynb) files that were created in a Jupyter environment outside of Cognos Analytics.

For more information, see "Uploading external notebooks" on page 55.

Compressed files

The supported, compressed file types that you can upload are .zip and .gz files.

You can compress multiple files of supported types into a .zip or .gz file for a one-step upload.

When the files in the archive contain related data, joins between tables in the files are created automatically. The files are saved together in **Public content** or **My content**, and you can quickly start creating dashboards, explorations, or data modules based on the .zip or .gz file. You can also reload all files in the archive at once.

The files in the archive are uploaded sequentially, while the same files, uncompressed, are uploaded concurrently. As a result, a compressed archive of files, such .zip, takes longer to upload than the same files uploaded individually, at the same time. For example, if each individual file takes 8 seconds to upload, a batch of 10 files uploaded as separate files, at the same time, takes about 8 seconds because the processing is done in parallel. If the same files are compressed into one .zip file, the upload takes 80 seconds (8 sec x 10 files) because the processing is done in sequence.

You cannot replace or update one file without processing all files in the .zip or .gz file. For more information, see "Updating data in uploaded files" on page 27.

Uploading files

You can upload supported file types that are stored in any location to which your computer has local or LAN access.

You can upload each data file individually or upload multiple files concurrently. Multiple files can also be compressed for a one-step upload.

Procedure

1. Use the following methods to upload files:

- In the Cognos Analytics welcome page, click the **Open menu** icon ≡ in the application bar, and then click **Upload files**. Browse for the files on your local drive or on the LAN, and select one or multiple files to upload them.
- Drag one or multiple files from your local drive onto the welcome page to activate the **Quick upload** functionality. When **Quick upload** appears, drop the files into the appropriate box to immediately start building a data module, exploration, dashboard, or a notebook.
- From the **Content** view, click **Upload data**. Locate the files on your local drive or on the LAN, and select one or multiple files to upload them. The files are saved to the folder from which you initiated the upload.

Tip: At different upload stages, progress and error messages are shown for single-file uploads and consolidated, progress messages for multi-file uploads.

2. Optional: If the **Replace data** message is displayed, it means that a file was uploaded before, and you can either replace or append data to the file. For more information, see <u>"Updating data in uploaded</u> files" on page 27.

Results

By default, the uploaded files are saved in **My content**. When the upload was initiated from a specific folder in **Team content** or **My content**, the files are saved to that folder.

If an administrator specified a different default, shared location in **Team content** for uploaded files at the role, tenant, or global level, you can save the uploaded files to this location.

What to do next

Use uploaded files to create dashboards, stories, explorations, data modules, or data sets.

To join two uploaded files, create a data module using them as sources.

Reporting can't use uploaded files directly. However, they can be incorporated into a data module, which can then be used as a source in Reporting.

Updating data in uploaded files

You can replace or append data in an uploaded file with data from a different file.

The column names and data types, and the order of columns must be identical in both files. An empty file, which is a file that contains a header but no data, cannot be used for the update.

Procedure

1. In **Team content** or **My content**, locate the uploaded file that you want to update.

- 2. From the file context menu i, choose one of the following options:
 - Replace file

This option replaces all rows of data in your uploaded file with rows of data from the file that you select.

• Append file

This option appends new rows of data to your uploaded file from the file that you select.

Tip: While the file is being updated, progress and error messages are displayed.

Chapter 5. Getting started in IBM Cognos Analytics -Explorations

Explore is a flexible workspace where you can discover and analyze data. You can also explore an existing visualization from a dashboard or story. Uncover hidden relationships and identify patterns that turn your data into insights. Correlated insights are represented by a green icon with a number on the x-axis, y-axis, or the title of a chart.

Starting explorations

Use one of several methods to start explorations.

Starting an exploration from an existing dashboard or story

When you are working on a dashboard or story, you can create or edit an exploration directly from a visualization.

About this task

Complete these steps to open a visualization in a new exploration or to add to an existing exploration:

Procedure

- 1. Open an existing dashboard or story.
- 2. Select a visualization.
- 3. Click the **Explore** icon ⁶ in the toolbar.
- 4. Select New exploration or Add to existing.

Starting a new exploration from the Open menu

From the **welcome** page, you can start a new exploration from the **New** menu.

Procedure

- 1. Click the **Open menu** icon \equiv , and then click **+** New.
- 2. Click Exploration.
- 3. Select a data source and click Add.

A starting points page is generated from the data source you selected.

Starting a new exploration from a data asset in the Content page

You can select the Action menu on a recently used data asset in any of the Content folders.

Procedure

- 1. In a folder in the **Content** page, such as **Team content** or **My content**, locate the data asset, such as a data module, that you want to use as a source for your exploration.
- 2. Select the data asset checkbox, and from its **Action menu** ; select **Create exploration**.

Adding a data source

Add a data source to your exploration to explore its data.

Procedure

- 1. In the **Selected sources** pane, click the **Add a source** + icon.
- 2. Go to **My content** or the **Team content** folder, and select the data source that you want to add. Click **Add**.
- 3. Expand the data source in the **Selected sources** pane to see what's available.
- 4. Use the starting points page to generate a relationship diagram from your data.

Chapter 6. Reports

IBM Cognos Analytics standard and active reports are created in the IBM Cognos Analytics - Reporting component.

After a report is saved in the portal, you can view, run, or edit it. You can view report outputs in various formats and languages. You can also distribute the report by email or by bursting, or send it to mobile devices. Reports can also be scheduled to run at regular time intervals.

For information about managing reports, see Chapter 9, "Managing content," on page 59.

Viewing and interacting with reports

IBM Cognos Analytics reports are located in **Team content**, **My content**, or other folders, where you can open or run them from.

The report opens in a viewer. You now have different options, such as subscribe, save as a report view, edit in reporting, and more. The available options depend on the type of report that you view. When a report runs in the interactive viewer, you also have options to see different data in the report by filtering, drilling up and down, and more.

Choose the options that best suit your needs for viewing frequency and personalization. If you want to see a report on a regular basis, subscribe to it. If it's really important, you can set it as your home page. If you entered prompt and parameter values and you want to save those so you don't have to enter them every time, save the report as a report view. If you choose to edit, the report opens in Reporting with all the tools you need. For more information, see *The user interface* in *IBM Cognos Analytics Reporting User Guide*.

Depending on the report type, the appropriate actions are available in the viewer:

- Subscribe (from the More menu in the application bar). Delivers reports with your prompt values and options.
- Save as report view (from the Save menu in the Reporting toolbar). Saves your prompt values and options in a view.
- The Edit toggle switch Come Edit. Enables the Reporting edit mode Come Edit.
- Run as. Choose the output format.
- Save and Save as (from the Save menu 🛅 in the Reporting toolbar).

If you view saved report output, and you want to be alerted when there's a new version of the report, tap **Notify me**.

You can find entries in **Team content** by searching. But you can also save and organize your items in **My content**, which is useful for saving report views with your custom prompts or for saving report output versions.

When a report runs in the interactive viewer, the following options are available in the toolbar that appears when you select a report object:

- Sort data ^{∓↓}.
- In lists, group data 🖽.
- Summarize data Σ .
- Convert a list or crosstab to a chart, or change a chart to a different chart type

- In crosstabs and charts, suppress columns or rows \blacksquare or swap columns and rows \rightleftarrows .
- Drill through to another report.
- Add calculated members =.
- Drill up, drill down, and perform dimensional operations, such as top/bottom filtering @.
- Run the report as Excel or CSV output.
- Select and interact with the elements of a chart, such as the bars in a bar chart.
- View lineage information for a data item @.
- Access a business glossary, such as the IBM InfoSphere[®] Information Governance Catalog, for a data item [®].
- Create, edit or remove filters abla.
- Share or embed report output, preserving the context of the current view of the report, such as prompt values.

To share or embed report output, click the **Share** icon **«**.

• Run a report as the report owner or with the capabilities granted to the owner.

In the Cognos Analytics portal, access the **Properties** slideout of the report, click the **Report** tab, and then open the **Advanced** section.

Run variations of reports with report views

If you want to run an existing IBM Cognos Analytics report with different prompt values, schedules, delivery methods, run options, languages, or output formats, you can create a report view. Creating a report view does not change the original report.

To create a report view [lio], run a report using the prompt values or other run options that you want and in the save options, select **Save as report view**. Your prompt values and run options are saved in the view. If you want to edit the prompt values for the report view, open the report view properties panel.

You can also create a report view in **My content** or **Team content**. Tap the context menu inext to a report, and then tap **Create report view**.

In the properties panel for the report view, you can see a link to the source report. If the source report is moved to another location, the report view link is maintained. If the source report is deleted, the report view link breaks.

Report versions

If you run IBM Cognos Analytics reports, you see the latest data from the source. But often you view report versions and outputs, such as when a report you subscribe to is delivered. Report outputs are generated by subscriptions, schedules, multiple formats or languages, bursting, and delivery methods that include save, print, and email.

In many instances, you are notified and receive a link to view report output, but you can also view saved and archived versions for reports in your content lists.

Save a report version

When you view a report, tap the save icon in the Reporting toolbar, or the more icon in the application bar. The location of the save option depends on the type of report you view.
You also have the **Save as** option (from the save menu (B)) of saving the report version under a different name or in a different location.

View report versions and archived versions

For a report in a content list, tap : , and then tap **View versions**.

Set the maximum number of report versions that you can save

For a report in a content list, tap the context menu :, and then tap **Properties**. On the **Report** tab, under **Advanced** > **Report output versions**, enter a number to represent the maximum number of report versions to save.

Delete saved outputs for report versions

For a report in a content list, tap i, and then **View versions**. Tap an entry in the list, and then tap the delete icon. Deleting removes all saved output formats for the version.

Subscribing to reports

If you use an IBM Cognos Analytics report regularly, you can subscribe to it. When you subscribe, you pick the time, date, format, and where you want it delivered. When you subscribe to a report, the subscription includes all your prompt and parameter values.

About this task

The subscription option is available when you run and view a report, but not when you are in editing mode or when you view saved output.

Tip: To ensure that you are in view mode, and not in edit mode, turn off the Edit toggle DEdit.

If you edit a report, you must save it before you can subscribe.

After you subscribe, each time your report is delivered, you are notified by a red circle on the Notifications

button 🕼 in the application bar. The number in the red circle indicates the number of notifications that

you have not yet viewed. Tap the Notifications button 🚰 to find a message with a link to view the report output.

Procedure

- 1. Run a report.
- 2. In the application bar, tap, and then tap **Subscribe**.
- 3. Select your subscription options, and then tap **Create**. Your subscription is created.

What to do next

After you create your subscriptions, you can view and manage them. For more information, see <u>"My</u> schedules and subscriptions" on page 85.

IBM Cognos Analytics Version 11.2.0 : Getting Started User Guide

Chapter 7. Dashboards and stories

IBM Cognos Analytics provides dashboards and stories to communicate your insights and analysis. You can assemble a view that contains visualizations, such as a graph, chart, plot, table, map, or any other visual representation of data. You can customize a dashboard, story, or visualization by changing its visual properties.

Dashboards

A dashboard helps you to monitor events or activities at a glance by providing key insights and analysis about your data on one or more pages or screens. You can explore the data that is shown in a visualization by using the interactive title, drilling up or down columns, and viewing the details of a data point.

You can change the visualization type or change the columns that are used in the visualization. You can use filters to focus on one area of your data or to see the impact of one column, and you can use calculations to answer questions that cannot be answered by the source columns.

For information about managing dashboards, see Chapter 9, "Managing content," on page 59.

Stories

A story is a type of view that contains a set of scenes that are displayed in sequence over time. Types of stories include slide show and guided journey.

Stories are similar to dashboards because they also use visualizations to share your insights. Stories differ from dashboards because they provide an over-time narrative and can convey a conclusion or recommendation.

For example, each slide in a story contains an analysis, insight, or piece of information that is revealed as the viewer runs a slide show. The slides build upon each other until the final slide, which provides a conclusion or summary. You can also create the effect of animation by having visualizations and objects appear and disappear during a scene in a story.

You can quickly assemble a story by reusing analysis, insights, and visualizations that you set aside in your collection of pins. You can also add new visualizations, media, web pages, images, shapes, and text to your story.

For information about managing stories, see Chapter 9, "Managing content," on page 59.

36 IBM Cognos Analytics Version 11.2.0 : Getting Started User Guide

Chapter 8. Notebooks

If IBM Cognos Analytics for Jupyter Notebook is enabled in IBM Cognos Analytics, you can work with notebook documents.

You can work with notebook documents, also referred to as notebooks, much like other content in Cognos Analytics.

Note: Before working with notebooks in Cognos Analytics, you should know how to work with and develop notebooks in Jupyter Notebook. You should be familiar with the Jupyter Notebook Editor.

Cognos Analytics for Jupyter Notebook supports the following notebook functionality:

Create and upload notebooks

Create notebooks. Edit, save, copy, and move notebooks. When you open a notebook, you work in the Jupyter Notebook Editor.

Create a notebook from the **Open menu** \equiv , by selecting the **New** option.

Upload notebooks that were created outside of Cognos Analytics. For more information, see "Uploading external notebooks" on page 55.

Run and work with data in a notebook

The CADataConnector API provides the read_data() and write_data() methods to read Cognos Analytics data sources and write to a data source. For example, you can run a notebook that reads external data, produces output, and saves the output as a data source.

You can use the Python and R programming languages in your notebooks.

For more information, see <u>"Reading data from a data source" on page 39</u> and <u>"Writing data to a data</u> source" on page 42.

Include notebook output in a dashboard, story, or report

Embed the output from a notebook code cell in a dashboard, story, or report. For example, you have a notebook that creates a visualization that is not available in Cognos Analytics. You can add this visualization to a dashboard or story by embedding the code cell that creates it.

For more information adding notebook output to a dashboard or story, see Adding a Notebook widget in the Dashboards and Stories User Guide.

For more information adding notebook output to a report, see *Including output from a notebook* in the *Reporting User Guide*.

To ensure that the notebook visualizations display properly in dashboards, use some <u>coding best</u> practices.

Samples

The samples show you how to work with notebooks in Cognos Analytics. If the samples are installed, you'll see them in **Team content** > **Samples** > **Notebooks**. For more information, see *Importing and configuring the Jupyter samples* in the *Samples Guide*.

Note: Before you can work with notebooks, Cognos Analytics for Jupyter Notebook must be installed and configured in your Cognos Analytics environment. Contact your administrator to confirm that you have the capability to work with notebooks. If you don't have the notebook capability, you won't see any of the functionality described in the following sections.

Creating a notebook

When you create a notebook, it opens in the Jupyter Notebook Editor.

Procedure

1. From the **Open menu** \equiv , click **New**, and then click **Notebook**.

Tip: If you don't see the **Notebook** selection, the notebook capability might not be enabled for you. Contact your administrator to find out.

The notebook opens in the Jupyter Notebook Editor.

2. To save the notebook, do the following steps:

a) Click **Save** (1), and then click **Save as**.

b) Choose the destination, type a name for the notebook, and click **Save**.

Notebook actions

After you've saved a notebook, you can perform actions on it from the welcome page or from **My content** or **Team content**.

Click the **Action menu** : for the notebook, and select one of the following actions:

Edit

Open the notebook in the Jupyter Notebook Editor.

Run

Run the notebook in the background. A message is displayed when the notebook starts running and

when it finishes. Also a notification is added to your unread notifications Q .

View

When you view a notebook, you can see its contents but you can't edit or run it.

Properties

View the notebook properties. This is where you can schedule a notebook to run at regular intervals or on a specific date and time. For more information, see "Scheduling an entry" in the *IBM Cognos Analytics Getting Started Guide*.

Create a new job

Add a notebook to a job that runs the notebook at a scheduled time. For more information, see "Using jobs to schedule multiple entries" in the *IBM Cognos Analytics Getting Started Guide*.

Take ownership

Take ownership of the notebook. When you own a notebook, you can change the permissions for it. This action is available only in **Team content** since you already own the notebooks in **My content**. For more information, see "Simple and granular access permissions" in the *IBM Cognos Analytics Getting Started Guide*.

Copy or move

Copy or move the notebook. For more information, see *Copying or moving entries* in the *IBM Cognos Analytics Getting Started Guide*.

Create a shortcut

Create a shortcut to your notebook in My content or Team content.

Share

You can copy the URL of the notebook and use it in other places. If Cognos Analytics is connected to a collaboration tool, such as Slack, you can send a link to your notebook to other users. For more information, see "Sharing content" in the *IBM Cognos Analytics Getting Started Guide*.

Remove from Recent

Remove the notebook from the **Recent** view. It still exists in **My content** or **Team content**.

Delete

Delete the notebook from Cognos Analytics.

Tip: You can also access these actions in **My content** or **Team content** from the actions toolbar for a notebook. A subset of these actions is available if you do not have the **Edit notebook** capability.

Reading data from a data source

You can read Cognos Analytics data in a notebook using the Python or R programming languages.

You can read the following types of Cognos Analytics data sources in a notebook:

- Uploaded CSV or XLS files
- Data sets
- Data modules
- Framework Manager packages, including OLAP data

Note: Cognos Analytics does not support reading from data that requires user input. For example, a query subject in Framework Manager with a parameterized filter.

To quickly insert the read_data() method in a notebook cell, do the following steps:

- 1. Create or edit a notebook and position your cursor in the cell after which you want to do the read.
- 2. Click Sources 🖁.
- 3. Navigate to a data source, select it, and then click **Open**. The method is inserted in the cell with the data source to read specified.

Alternatively, you can type the code in a cell:

In Python

data = CADataConnector.read_data(parameters as described in the following sections)

One of the following items is returned from the method:

DataFrame

Returned by default.

List of DataFrame

Returned when the **sheet_name** parameter is specified and multiple sheets are requested.

Iterator of DataFrame

Returned when the **chunksize** or **iterator** parameter is specified.

Parameters common to all data sources

For examples of how to code the read_data() method, see "Python notebook examples" on page 46.

The following parameters can be specified for all supported data source types:

Parameter	Required or optional	Description
path id	Specify one of path or id	Path to the data source. If the data source is in My content , specify .my_folders at the start of the path. If the data source is in Team content , specify .public_folders at the start of the path. For example, to specify a file called sales-notebook that is stored in My content , specify
		path=".my_folders/sales-notebook"
		The ID of the file. For information about how to get the ID of a file, see <u>"Finding the ID of a file" on page 45</u> . For example:
		id="i1F8D76C0FAD34J9CA50118746935D9X7"
usecols	optional	List of integers or strings that identifies a subset of columns to be returned. You can specify one or more columns by the position number of the column in the file or by column name. For example, to request columns City and Quantity , specify In Python
		usecols=["City","Quantity"]
		If not specified, then all columns are returned.
		Note: This parameter is not applicable for OLAP data in a Framework Manager package.
chunksize	optional	An integer. If specified, the method returns an iterator. The value specifies the number of rows to return each time the method is invoked. For example, to return 3 rows, specify
		chunksize=3
		If both chunksize and iterator are not specified, then a DataFrame is returned.
iterator	optional	If specified, the method returns an iterator. Specifying
		iterator=True
		without chunksize specified returns one row each time the method is invoked.
		Specifying iterator=True with chunksize specified, returns chunksize rows each time the method is invoked.
		Reset the iterator using the reset method:
		In Python
		<pre>iterator.reset()</pre>
		method.

Parameter	Required or optional	Description
nrows	optional	The maximum number of rows returned. Specify an integer. If omitted, the maximum number of rows returned is 10,000. If
		nrows=0
		is specified, then the column headings are returned.

XLS file parameters

Uploaded files are treated as sheets of data. Reading one of these data sources returns the rows for the specified sheet of data in the data source.

The following parameter applies only to XLS files:

sheet_name

Optional. Integer, string, or a list of integers or strings. Specifies the integer position of a specific sheet or tab in an XLS file. The first sheet is 0. If you specify a list of strings or integers, then a list of the corresponding sheets is returned. If not specified, the value defaults to 0. Example:

In Python

sheet_name=["sheet2","sheet3"]

Data module parameters

Reading data from a data module must reflect the modeling done on the data source. For example, a join between two tables and aggregation types to apply.

The following parameters apply only to data modules:

Parameter	Required or optional	Description
table_name	Optional	String or list of strings. Restrict the scope of the request to specific table(s) in the data module. Specify the table(s) by table name(s).
		If you omit table_name , the read_data() method returns a DataFrame that contains the names of the tables defined in the data module. Example:
		In Python
		<pre>table_name=["table1","table2"]</pre>
calculation	Optional	String or list of strings. Read a calculation from a data module. Specify a calculated column in the data module.

Package parameters

Reading data from a package must reflect the modeling done on the data source. For example, the relationship between objects in the package.

The following parameters apply only to packages:

Parameter	Required or optional	Description					
query_subject	Optional	String or list of strings. Restrict the scope of the request to the specific query subjects(s) in the package. Specify the query subject(s) by query subject name(s). Example:					
		query_subject="query1"					
folder_name	Optional	String or list of strings. Restrict the scope of the request to a folder in the package. Displays the contents of all folder(s) with that name in the package. If you want to see only the content of folder c that's in folder b that's in folder a specify the folder_name parameter as a list:					
		In Python					
		folder_name=["a","b","c"]					
		This returns only the folder c in this path, even if there are other folders with the name c in the package.					
metadata	Optional. Applies	Value can be True or False.					
	only to OLAP data in a Framework	Specifying					
	Manager package.	metadata=True					
		returns the query subjects in the package. Specifying					
		metadata=False					
		returns the data in the package. If not specified, then a default value of False is used.					

Note: You can use either single or double quotation marks in a method but not a mix of both.

Writing data to a data source

You can write Cognos Analytics data in a notebook using the Python or R programming languages.

You can save or create the data source in My content or Team content.

To write data to the data source, specify the following code in a notebook cell:

In Python

data = CADataConnector.write_data(parameters as described in the followin	g sections)
---	-------------

Parameter	Required or optional	Description
data	required	Pandas.DataFrame. Contains the table of data, which is written to the file.

Parameter	Required or optional	Description
path id	Specify one of path or id	Path to the data source. If the data source is in My content , specify .my_folders at the start of the path. If the data source is in Team content , specify .public_folders at the start of the path. For example, to specify a file called sales-notebook that is stored in My content , specify
		<pre>path=".my_folders/sales-notebook"</pre>
		The ID of the file. For information about how to get the ID of a file, see <u>"Finding the ID of a file" on page 45</u> . For example:
		id="i1F8D76C0FAD34J9CA50118746935D9X7"
mode	optional	 x Create the file and write to it. If the file exists, the method fails with an exception. Default value. w Overwrite any data that exists in the file. The columns that you are writing to the file must match the ones in the file. Create the file if it doesn't exist. a Append to the end of the file. The columns that you are adding to the file must match the ones in the file. Create the file if it doesn't exist. Example:
		mode="w"

Note: You can use either single or double quotation marks in a method but not a mix of both.

For examples of how to code the write_data() method, see <u>"Python notebook examples" on page 46</u> and "R notebook examples" on page 49.

Searching for data objects

You can search for data objects in a notebook using the Python or R programming languages.

The search_data() method is used to find data objects so that they can be further processed using the CADataConnector.

The result provides a list of data objects and their connection paths, which may be copy/pasted for use with the various connection and access functions in the CADataConnector.

To search for data objects, specify the following code in a notebook cell:

In Python

data = CADataConnector.search_data(parameters as described in the following sections)

In R

data <- CADataConnector::search_data(parameters as described in the following sections)</pre>

Paramet er	Req uire d or opti ona l	Description
query='se arch	opti onal	search_term can be any data object.
		objects available are selected, to a maximum of 50. See an <u>example of the resulting</u> <u>output</u> .
types= <i>typ</i> <i>es</i>	opti onal	<i>types</i> can be replaced with any number of (separated by either ' ' or ',') the following data object types:
		• uploadedFile
		• dataset
		dataset2
		• module
		• package
		Example:
		types='module,dataset'
		If types= <i>types</i> is not specified, the default is all of the types listed above.
max=nu	opti	<i>number</i> is any number greater than zero.
mber	Unat	Example:
		max=20
		If max= <i>number</i> is not specified, the default is
		max=50
		Use a higher number if you see a message that the maximum results were returned.

Note: You can use either single or double quotation marks in a method but not a mix of both.

Example output when no parameters are specified

When no parameters are supplied, the output appears in a list:

```
Results found: 50. ( see more results by using "max=" parameter with a number higher than 50 )
Туре
                             Open path
package
                       .public_folders/Samples/Models/GO sales (analysis)
package
                       .public_folders/Samples_LG_DQ/Models/GO Data Warehouse (query)
.public_folders/Samples/Models/GO sales (query)
package
                       .public_folders/Samples/Models/GO Sales (query)
.public_folders/Samples/Models/GO data warehouse (query)
package
package
                       .public_folders/Samples_LG_DQ/Models/GO Data Warehouse (analysis)
.public_folders/Samples/By feature/Audit
.public_folders/Samples/Models/GO data warehouse (analysis)
package
package
package
package .public_folders/Samples/Hodels/GO Sales (analysis)
package .public_folders/Samples/Data/Sporting goods company
uploadedFile .public_folders/Samples/By feature/Notebooks/Data/Source files/Notebook data/
Weather
uploadedFile .public_folders/Samples/By feature/Notebooks/Data/Source files/
Hospital_floor_plan.xlsx
. . . . .
```

Python notebook examples

CADataConnector.search_data('boston')

Returns everything with 'boston' in the name or data, to a maximum of the default number of results.

CADataConnector.search_data(types='module,package',max=100)

Returns only modules or packages to a maximum of 100 results.

CADataConnector.search_data(max=20)

Returns everything to a maximum of 20 results.

Note: All or none of the parameters may be used. If the query is to be used, it must be the first parameter. The other parameters are named and are not position-dependent.

R notebook examples

CADataConnector::search_data('boston')

Returns everything with 'boston' in the name or data, to a maximum of the default number of results.

CADataConnector::search_data(types='module,package',max=100)

Returns only modules or packages to a maximum of 100 results.

CADataConnector::search_data(max=20)

Returns everything to a maximum of 20 results.

Note: All or none of the parameters may be used. If the query is to be used, it must be the first parameter. The other parameters are named and are not position-dependent.

File paths that contain a forward slash

To reference a file or folder name that contains a folder slash in the CADataConnector API, you must use a specific syntax.

To enable the CADataConnector API to differentiate between a forward slash that indicates folder structure and a forward slash that is part of a file or folder name, enclose each folder or file name in single or double quotation marks, separate each folder or file name in the path with a comma, and enclose the whole thing in square brackets.

```
In the following example, the path to a file named my/data.csv is my/folder-1/my/folder-2/my/ data.csv.
```

```
data = CADataConnector.read_data(path=["my/folder-1","my/folder-2","my/data.csv"])
```

Finding the ID of a file

To reference a file in the CADataConnector API, you can use its ID.

Procedure

- 1. In a content page, such as **My Content** or **Team content**, click the **Action menu** if for a file, and select **Properties**.
- 2. On the **General** tab, click **Advanced**. The **ID** field contains the file ID.

Python notebook examples

Here are some examples that demonstrate how to work with Cognos Analytics data sources in a notebook using the Python programming language.

Tip: To switch your notebook's programming mode from **R** to **Python**, from the **Kernel** menu, select **Change kernel > Python**.

Reading a file

The following example reads a file called SampleFile_GOSales.xls, outputs the entire file, and then specifies the **nrows** and **usecols** parameters to output the **City** and **Quantity** columns for the first 2 rows of data in the file.

U	da	a.head	0																
		Retailer country	Province or State	City	Postal code	Short postal code	Order method type	Retailer type	Retailer	Product line	Product type		Year	Quarter	Quantity	Unit cost	Unit price	Unit sale price	R
1	0	United Kingdom	West Midlands	Birmingham	829 5DW	B 2	Web	Outdoors Shop	Seamate Chandlers	Camping Equipment	Cooking Gear		2014	Q3	1868	2.90	6.59	6.26	1
	1	Canada	Saskatchewan	Regina	S1J 3C5	S1J	Web	Sports Store	Ultra Sports	Camping Equipment	Cooking Gear		2017	Q2	3659	3.01	6.59	6.26	2
	2	United States	Florida	Miami	33176	33176	Web	Sports Store	Island Sports	Camping Equipment	Cooking Gear		2016	Q2	1218	2.93	6.59	6.46	
	3	United Kingdom	West Midlands	Birmingham	820 3BA	82	Web	Department Store	Leisure Land	Camping Equipment	Cooking Gear		2015	Q4	1638	2.93	6.59	6.19	1
	4	United Kingdom	West Midlands	Birmingham	820 38A	B 2	Web	Department Store	Leisure Land	Camping Equipment	Cooking Gear		2016	Q4	1315	2.93	6.59	6.26	
	5 rc	ws × 22 i	columns																
data = CADataConnect data				or.read_d	ata(pa nro	th=".g ws=2,	ublic_f	folders/j: s=['City',	imdataset 'Quantit	ts/Sample ty'])	File_GC)Sa:	Les.x	ls",					
		CI	ty Quantity																
Î	0	Birmingha	m 1868																

Reading part of a file

Specify **iterator** and **chunksize** to work with chunks of data, rather than the whole data source all at once. The following example reads 20,000 rows at a time from the SampleFile_GOSales.xls file.

4]:	for	chunk display	in iter: y(chunk.h	iead(2))																
		Retailer country	Province St	or ate	City	Postal code	Short postal code	Order method type	Retailer type	Retailer	Product line	Pro	duct type		Year	Quarter	Quantity	Unit cost	Unit price	Unit sale price	Reve
	0	United Kingdom	W	lest Birn	ningham	B29 5DW	B 2	Web	Outdoors Shop	Seamate Chandlers	Camping Equipment	Co	oking Gear		2014	Q3	1868	2.90	6.59	6.26	1169
	1	Canada	Saskatchev	van	Regina	S1J 3C5	S1J	Web	Sports Store	Ultra Sports	Camping Equipment	Co	oking Gear	-	2017	02	3659	3.01	6.59	6.26	2290
	21	ows × 22	columns																		
		Retailer country	Province or State	City	Posta	Short postal code	Orde metho typ	r Retaile d typ	er Retaile	r Prod	uct Produc line typ	e "	. Yea	ar	Quarte	r Quantit	y Unit cost	Unit price	Unit	sale	Reven
	0	Germany	Bayern	Müncher	80800	80800	We	b Eyewea Stor	ar Weitblic	k Perso Accesso	ries Eyewea	ar	. 201	7	Q	108	2 25.70	61.84	59.63	6522	64158.
		United	Greater	Londor	E14	E1	1160	Sport	ts Tota	al Perso	nal Evene		201	6	0	1 20	6 26 15	61.84	80.22	0000	12383

Writing to a file

The following example writes the contents of a DataFrame table of data in to a file called regions sales, which is then stored in **My content**.

in [20]:	im ne	port par wData =	das a pd.Da
En [21]:	ne	wData	
Out[21]:		Regions	Sales
	0	Americas	300
	1	Europe	400
	2	Asia	500

Reading a data module

A data module has relationships, aggregations, calculated columns, and so on, defined on its data. The read_data() method defines a section of data from a data module by selecting columns from the tables

in the module. The data that is returned includes the relationships, aggregations, calculated columns, and so on, defined in the data module.

Specifying the read_data() method without the **table_name** parameter returns a **DataFrame** that contains the names of all the tables defined in the data module, as shown in the following example:

Min [26]:	da da	ta = CADataConnect ta	or.read_data(path=".p	ubli	c_folders/jimdatasets/sample data module")
Out[26]:	Name		Table Name		
	0 American Time Use XIsx		M1_American_time_use_xlsx Da		
	1	Banking Loss Events Xisx	M1_Banking_loss_events_xisx	Data	

In the following example, the M1_American_time_use_xlsx table in the sample data module data module is read and the columns **Year** and **Children** are returned.



Reading a calculated column from a data module **mms**

Use the **calculation** parameter to read a calculated column from a data module.

The following example reads 2 calculations from the calculation_data_module data module.



Reading a package

Like a data module, a package has relationships, aggregations, calculated columns, and so on, defined on its data. In addition, a package logically groups data into query subjects and folders. You can use the read_data() method to navigate through the structure of a package by using the **query_subject** and **folder_name** parameters.

The following code reads the Go data warehouse package:

In [1]: t	<pre>toplevel = CADataConnector.read_data(path=".public_folders/jimdatasets/60 data warehouse (query)") </pre>									
MIn [2]: t	toplevel									
Out[2]:	Name	Query Subject	Туре							
	0 HR (query)	N/A	Folder							
	1 Sales and Marketing (query)	N/A	Folder							
	2 Finance (query)	N/A	Folder							
	2 Filters	N/A	Folder							

Specifying the **folder_name** parameter returns the contents of all folder(s) with that name in the package. If you want to return only the content of one specific folder, for example folder c, that's inside folder b, that's inside folder a, put a list of the folder names in the **folder_name** parameter. The

following example uses the **folder_name** parameter to get all of the query subjects in the Employee expense folder:

hr							
	Na	me Query Subject	Туре				
0	Employee expense (que	ery) N/A	Folder				
1	Employee expense plan (que	ery) N/A	Folder				
2	Employee position summary (qu	ary) N/A	Folder				
3	Employee ranking (qui	ery) N/A	Folder				
4	Employee recruitment (que	ery) N/A	Folder				
5	Employee succession (que	ery) N/A	Folder				
6	Employee summary (que	ery) N/A	Folder				
7	Employee survey (qui	ery) N/A	Folder				
8	Employee survey target (que	ery) N/A	Folder				
9	Employee training (gu	arv) N/A	Folder				
x	= CADataConnector.re	ad_data(path='	.public_folders/j	mdataset	s/GO data ware	ehouse (gue	ery)°,i
ext	- CADataConnector.re	ead_data(path='	.public_folders/j	mdataset	s/GO data ware	ahouse (que	ery)*,f
ext	<pre>CADataConnector.re Name</pre>	ead_data(path=	.public_folders/j: Query Subject	.mdataset Type	s/GO data ware	ahouse (gue	ery)*,:
o vite o	CADataConnector.re Name Employee expense fact [E	ead_data (path=' mployee expense (qu	".public_folders/j: Query Subject ery)) [Employee expense f	mdataset Type Data Sheet	s/GO data ware	shouse (gue	ery)*,
9xg 9xg 0	CADataConnector.re Name Employee expense fact [E Account	ead_data(path=' mployee expense (qu (Employee	".public_folders/j: Query Subject ery]] [Employee expense f expense (query]] [Account]	mdataset Type Data Sheet Data Sheet	s/GO data ware	ahouse (que	ery)*,
x; x;)	CADataConnector.re Name Employee expense fact [E Account Employee by manager [Er	ead_data(path=' mployee expense (qu (Employee nployee expense (que	".public_folders/j: Query Subject ery]] [Employee expense f expense (query]] [Account] iry]].[Employee by manager]	Type Data Sheet Data Sheet Data Sheet	s/GO data ware	shouse (que	ery)*,
ex; ex; 0 1 2 3	CADataConnector.re Name Employee expense fact [E Account Employee by manager [Er Employee by region	ead_data(path=' mployee expense (qu (Employee expense (que (Employee expense (que	" , public_folders/j: Query Subject ery)] (Employee expense f e expense (query)] (Account) ny)] (Employee by manager) query)] (Employee by region)	mdataset Type Data Sheet Data Sheet Data Sheet Data Sheet	s/GO data ware	ehouse (que	ery)°,
exp exp 0 1 2 3 4	CADataConnector re Name Employee expense fact [E Account Employee by manager [Er Employee expense	ead_data(path=" mployee expense (qu (Employee poloyee expense (que Employee expense (que (Employee expense (".public_folders/j: Guery Subject ery]].(Employee expense f expense (uew)].(Account) ny]].(Employee by manager] uew)].(Employee by region) query).(Employee expense)	Type Data Sheet Data Sheet Data Sheet Data Sheet Data Sheet Data Sheet	s/GO data ware	ahouse (que	ery)",
ex; ex; 0 1 2 3 4 5	CADataConnector .re Name Employee expense fact [E Acount Employee by manager [Er Employee	ead_data (path=' mployee expense (qu [Employee nployee expense (qu [Employee expense (c [Employee expense ([Employee exp	* .public_folders/j: Cuery Subject ery]].[Employee expense f expense (query]].[Account] ny]].[Employee by manager] query].[Employee by region] query].[Employee by region] query].[Employee expense]	mdataset Type Data Sheet Data Sheet Data Sheet Data Sheet Data Sheet Data Sheet	s/GO data ware	shouse (que	ary)*,
ex; ex; 0 1 2 3 4 5 6	CADataConnector .re Name Employee expense fact [E Account Employee by region Employee by region Crganization (consolidated)	ead_data (path=" mployee expense (qu [Employee expense (cu [Employee expense (c [Employee expense (c [Employee expense (c [Employee expense (c	Cuery Subject Query Subject ery/l (Employee expense (ry/l, (Employee by manager) uery/l, (Employee by region) query/l, (Employee by region) query/l, (Employee by region) query/l, (Dignizization) (uery/l) (Organization) (uery/l) (mdataset Type Data Sheet Data Sheet Data Sheet Data Sheet Data Sheet Data Sheet Data Sheet Data Sheet	s/GO data ware	ehouse (que	ary)*,:
9×1 9×1 0 1 2 3 4 5 6 7	CADataConnector.re Name Employee expense fact [E Account Employee by manager [E Employee by manager Crganization Organization Congenization	ead_data (path=" mployee expense (qu [Employee comployee expense (qu [Employee expense (qu [Employee expense) (q [Employee expense) (q Employee expense) (q	*,public_folders/ji Query Subject er/ji[Employee expense [e expense (query)] [Account] ([Employee by managed query] [Employee by major] query] [Employee by major] query] [Comployee by major] query] [Comployee comployee expense] ense (query] [Comployee comployee expense] ense (query] [Comployee comployee expense] ense (query) [Comployee comployee expense] ense (query) [Comployee comployee expense] ense (query) [Comployee expense	mdataset Type Data Sheet Data Sheet Data Sheet Data Sheet Data Sheet Data Sheet Data Sheet Data Sheet	s/GO data ware	shouse (que	ery)",:
	CADataConnector.rc Name Employee expense fact Engloyee expense fact Engloyee by region Engloyee by region Engloyee by region Engloyee by region Cogarization (consolidated) Poation-department Ime	ead_data (path=' mployee expense (qu (Employee pployee expense (q (Employee expense (q Employee expense (q Employee expense (q (Employee expense (q (Employee expense (q (Employee expense (q))))))))))))))))))))))))))))))))))))	", public_folders/j: Ouery Subject ery([Employee sepense [express (query)[Account ory([Employee by manager] geny)[Employee sepense] enne (query)[Organization (query)[Organization (query)[Organization gene sconses (query),[[Tmei])	mdataset Type Data Sheet Data Sheet Data Sheet Data Sheet Data Sheet Data Sheet Data Sheet Data Sheet	s/GO data ware	shouse (que	ery)*,

The following code returns the query items that are in the Employee expense fact query subject:

In [20]:	expfac	<pre>expfacts = CADataConnector.read_data(path=".public_folders/jimdatasets/GO data warehouse (query)",</pre>										
In [21]:	expfacts											
Out[21]:	Exp	ense unit quantity	Expense total	Expense unit quantity YTD	Expense total YTD							
	0	4.004779e+06	168696729.2	4.004779e+06	168696729.2							

The following code returns the query items that are in the Account query subject:

ŊIn [24]:	accounts = CADataConnector.read_data(path*',public_folders/jindatasets/GO data warehouse (query)*, query_subject=(exp['Query Subject'][1]]) accounts.columns									
Out[24]:	<pre>Index(')account mame (level 1)', 'Account mame (level 2)', 'Account mame (level 3)', 'Account mame (level 4)', 'Account mame (level 5)', 'Account mame (level 6)', 'Account mame (level 7)', 'Account mame (level 6)', 'Account mame (level 1)', 'Account mame (level 12)', 'Account mame (level 13)', 'Account mame (level 12)', 'Account mame (level 13)', 'Account mame (level 12)', 'Account mame (level 13)', 'Account mame (level 16)', 'Account mame', 'Account news', 'Account mame (level 16)', 'Account mame', 'Account code (level 3)', 'Account mame (level 16)', 'Account code (level 3)', 'Account code (level 6)', 'Account code (level 3)', 'Account code (level 6)', 'Account code (level 3)', 'Account code (level 10)', 'Account code (level 7), 'Account code (level 10)', 'Accou</pre>									
	'Account code (level 13)', 'Account code (level 14)', 'Account code (level 15)', 'Account code (level 16)', 'Account key', 'Account code', 'Account type code', 'Account class code'], dtwe='objec')									

The following code selects the first two query subjects in the Employee expense folder. **Expense total** is returned from the first query subject (**Employee expense fact**) and **Account code** is returned from the second query subject (**Account**).

Min [25]:	ex	p_by_accour	nt = expfacts	 CADataConnector.read_data[path=':public_folders/[indatasets/00 data warehouse [query]', query_subject='gng/loary Subject'][0], warehouse [query]', usecols=['Expense total','Account code'])
In [26]:	ex	p_by_accour	nt	
Out[26]:		Expense total	Account code	
	0	95723630.59	601100	
	1	39936062.73	601500	
	2	4008748.74	601600	
	3	10555741.81	605050	
	4	14514144.54	605500	
	5	3958400.79	605800	

Reading the metadata for OLAP data in a Framework Manager package

The following code shows the **metadata** parameter set to true, which returns the query subjects in the package:



R notebook examples

Here are some examples that demonstrate how to work with Cognos Analytics data sources in a notebook using the R programming language.

Tip: To switch your notebook's programming mode from **Python** to **R**, from the **Kernel** menu, select **Change kernel** > **R**.

A basic read

The following example reads a file called SampleFile_GOSales.xls and displays the first six rows of it.

• ;	-	Product type	Product line	Retailer	Retailer type	Order method type	Short postal code	Postal code	City	Province or State	Retailer country
48 1	1	Cooking Gear	Camping Equipment	Seamate Chandlers	Outdoors Shop	Web	B2	B29 5DW	Birmingham	West Midlands	United Kingdom
5 2	2	Cooking Gear	Camping Equipment	Ultra Sports	Sports Store	Web	S1J	S1J 3C5	Regina	Saskatchewan	Canada
	-	Cooking Gear	Camping Equipment	Island Sports	Sports Store	Web	33176	33176	Miami	Florida	United States
.88 1		Cooking Gear	Camping Equipment	Leisure Land	Department Store	Web	B2	B20 3BA	Birmingham	West Midlands	United Kingdom
)	Cooking Gear	Camping Equipment	Leisure Land	Department Store	Web	B2	B20 3BA	Birmingham	West Midlands	United Kingdom
.90 1	/	Cooking Gear	Camping Equipment	Jensen Mountaineering	Outdoors Shop	Sales visit	E1	E15 3JR	London	Greater	United Kingdom

Reading a file

The following example reads a file called SampleFile_GOSales.xls and specifies the **nrows** and **usecols** parameters to output the **City** and **Quantity** columns for the first two rows of data in the file.

```
In [1]: data <- CADataConnector$read_data(
    path=".public_folders/jimdatasets/SampleFile_GOSales.xls",
    usecols=list('City', 'Quantity'),
    nrows=2
)
data</pre>
```

City	Quantity
Birmingham	1868
Regina	3659

Reading part of a file

Specify **iterator** and **chunksize** to work with chunks of data, rather than the whole data source all at once. The following example reads 20,000 rows at a time from the SampleFile_GOSales.xls file. As the file is read, the number of rows in the chunk is displayed.



Writing to a file

The following example writes the contents of a DataFrame table of data in to a file called regions sales, which is then stored in **My content**.



Reading a data module

A data module has relationships, aggregations, calculated columns, and so on, defined on its data. The read_data() method defines a section of data from a data module by selecting columns from the tables in the module. The data that is returned includes the relationships, aggregations, calculated columns, and so on, defined in the data module.

Specifying the read_data() method without the **table_name** parameter returns a DataFrame that contains the names of all the tables defined in the data module, as shown in the following example:

In [6]:

data <- CADataConnector\$read_data(
 path=".public_folders/Samples/Data/Coffee sales and marketing"
)
data</pre>

Name	Table Name	Туре
Sales Receipts	i201904_sales_reciepts	Data
Pastry Inventory	pastry_inventory	Data
Sales Targets	sales_targets	Data
Customer	customer	Data
Dates	Dates	Data
Product	product	Data
Sales Outlet	sales_outlet	Data
Staff	staff	Data
Generation	generations	Data
Spoilage_Expense	N/A	Calculation
beverages_sale	N/A	Calculation
beverages_sale_1	N/A	Calculation
beverages_sale_2	N/A	Calculation
beverages_sale_3	N/A	Calculation
beverages_sale_4	N/A	Calculation

In the following example, the pastry_inventory table in the Coffee sales and marketing data module is read and the columns **Date** and **Quantity Sold** are returned.

)

```
In [8]: data <- CADataConnector$read_data(</pre>
             path=".public_folders/Samples/Data/Coffee sales and marketing",
             table name='pastry_inventory',
             usecols=list("Date", "Quantity Sold")
         data
```

Date	Quantity Sold
2019-04-04	48
2019-04-05	0
2019-04-11	127
2019-04-12	133
2019-04-13	123
2019-04-17	149
2019-04-19	159
2019-04-20	163
2019-04-21	161
2019-04-22	102
2019-04-23	93
2019-04-26	102
2019-04-01	46
2019-04-02	46
2019-04-03	41
2019-04-06	70
2019-04-07	104
2019-04-08	118
2019-04-09	91
2019-04-10	110
2019-04-14	167
2019-04-15	149
2019-04-16	144
2019-04-18	117
2019-04-24	105
2019-04-25	109
2019-04-27	77

Reading a package

Like a data module, a package has relationships, aggregations, calculated columns, and so on, defined on its data. In addition, a package logically groups data into query subjects and folders. You can use the read_data() method to navigate through the structure of a package by using the query_subject and folder_name parameters.

The following code reads the Go data warehouse package:

Filters

Specifying the **folder_name** parameter returns the contents of all folders with that name in the package. If you want to return only the content of one specific folder, for example folder c, that's inside folder b, that's inside folder a, put a list of the folder names in the **folder_name** parameter. The following example uses the **folder_name** parameter to get all of the query subjects in the Employee expense folder:

N/A Folder

)

```
In [4]: hr <- CADataConnector$read data(</pre>
             path=".public folders/Samples DQ 10.2.2 DB2/Models/GO Data Warehouse (query)",
             folder_name=toplevel[1,1]
        hr
```

Name	Query Subject	Туре
Employee expense (query)	N/A	Folder
Employee expense plan (query)	N/A	Folder
Employee position summary (query)	N/A	Folder
Employee ranking (query)	N/A	Folder
Employee recruitment (query)	N/A	Folder
Employee succession (query)	N/A	Folder
Employee summary (query)	N/A	Folder
Employee survey (query)	N/A	Folder
Employee survey target (query)	N/A	Folder
Employee training (query)	N/A	Folder

```
In [5]: exp <- CADataConnector$read_data(</pre>
            path=".public_folders/Samples_DQ_10.2.2_DB2/Models/GO_Data Warehouse (query)"
             folder_name=hr[1,1]
```

```
)
exp
```

Name	Query Subject	Туре
Employee expense fact	[Employee expense (query)].[Employee expense fact]	Data
Account	[Employee expense (query)].[Account]	Data
Employee by manager	[Employee expense (query)].[Employee by manager]	Data
Employee by region	[Employee expense (query)].[Employee by region]	Data
Employee expense	[Employee expense (query)].[Employee expense]	Data
Organization	[Employee expense (query)].[Organization]	Data
Organization (consolidated)	[Employee expense (query)].[Organization (consolidated)]	Data
Position-department	[Employee expense (query)].[Position-department]	Data
Time	[Employee expense (query)].[Time]	Data
YTD Time	[Employee expense (query)].[YTD Time]	Data

The following code returns the query items that are in the Employee expense fact query subject:



The following code returns the query items that are in the **Account** query subject:

In [14]:	<pre>accounts <- CADataConnector\$read_data(path=".public_folders/Samples_DQ_10.2.2_DB2/Models/GO Data Warehouse (query)", query_subject=list(exp[2,2])) accounts[0,]</pre>									
	Account name (level 1)	Account name (level 2)	Account name (level 3)	Account name (level 4)	Account name (level 5)	Account name (level 6)	Account name (level 7)	Account name (level 8)	na	Debit or credit

Reading the metadata for OLAP data in a Framework Manager package

The following code shows the **metadata** parameter set to true, which returns the query subjects in the package:

In [5]: data <- CADataConnector\$read_data(
 path=".public_folders/powercube",
 query_subject="[powercube].[Products].[Products]",
 metadata=TRUE
)
 data</pre>

Name	Query Subject
Products	[powercube].[Products].[Products].[Products]
Product line	[powercube].[Products].[Products].[Product line]
Product type	[powercube].[Products].[Products].[Product type]
Product	[powercube].[Products].[Products].[Product]

Uploading external notebooks

You can upload Jupyter Notebooks (.ipynb or .zip extension) that were created in a Jupyter environment outside of IBM Cognos Analytics.

The uploaded notebooks are matched against the following JSON schemas:

- https://github.com/jupyter/nbformat/blob/master/nbformat/v3/ nbformat.v3.schema.json(version 3 (v3) notebooks)
- https://github.com/jupyter/nbformat/blob/master/nbformat/v4/ nbformat.v4.schema.json(version 4 (v4) notebooks)

If a notebook doesn't conform to either of these schemas, the upload is rejected.

Jupyter Server creates all new notebooks using the v4 schema.

About this task

The process of uploading notebook files is similar to the process of uploading spreadsheets and text files that are used as data sources in Cognos Analytics. For example, the notebook files have the same size limitations as other uploaded file types. For more information, see Upload data files.

Procedure

Use the following methods to upload the notebooks:

- From the **Open menu**, click **Upload files**. Locate the notebook files (.ipynb or .zip) on your local drive or on the LAN, and select one or multiple files to upload them.
- In the welcome page, drag one or multiple .ipynb or .zip files from your local drive onto the welcome page to activate the **Quick upload** functionality. When **Quick upload** appears, drop the files into the **Notebook** box.
- From **Team content** or **My content**, click **Upload files**. Locate the notebook files on your local drive or on the LAN, and select one or multiple files to upload them. The files are saved to the folder from which you initiated the upload.

Results

A notebook is created for each uploaded .ipynb file in **My content**. However, when the upload was initiated from a specific folder, the notebooks are created in that folder.

What to do next

You can seamlessly open an uploaded v4 notebook in the edit mode. To open a v3 notebook in the edit mode, the Jupyter server temporarily converts it to the v4 format. If you save the notebook, it is saved in the v4 format.

Tip: Older versions of Jupyter might not read the v4 format. To preserve the original notebook version, close it without saving.

You can view both v3 and v4 notebooks in the view-only mode. Because you can't interact with notebooks in this mode, there is no need to convert v3 notebooks to v4.

You can import uploaded v3 and v4 notebooks into a Cognos Analytics dashboard. The **Notebook** widget in the dashboards conforms to the v4 JSON schema so the visualizations in v4 notebooks display seamlessly in the dashboard. To ensure that the v3 notebook visualizations display properly in the dashboard, you must open and save the v3 notebooks in the edit mode before you import them into the dashboard.

Importing Watson Studio notebooks to Cognos Analytics

If you are using Cognos Analytics on Cloud, you may have been given access to a Watson Studio environment that is external to your Cognos Analytics environment. If so, you can import notebooks that were authored in the Watson Studio environment. You can then select a content cell from an imported notebook and add it to a report or dashboard.

Before you begin

Confirm that you have been given access to an external Watson Studio environment.

Procedure

- 1. Click the Open menu icon \equiv and select **Content**.
- 2. Select the External content tab.
- 3. Navigate to a Watson Studio notebook and click its name.
- 4. In the Save as window, enter a name for the notebook that you're importing.
- 5. Navigate to a location in **My content** or **Team content**.
- 6. Click **Save**.

Results

You or a colleague can now select a content cell from the imported notebook and add it to a report or a dashboard. For more information, see "Adding a Notebook widget" or "Including output from a notebook" in the *IBM Cognos Analytics Notebook Guide*.

Connecting Watson Studio notebooks to Cognos Analytics

If you are running Cognos Analytics on Cloud or Cognos Analytics on Cloud Pak for Data, you can configure Watson Studio notebooks to connect to Cognos Analytics.

Once it is configured, your Watson Studio notebook can

- · read data assets from Cognos Analytics
- write data to Cognos Analytics

If you are using Cognos Analytics on Cloud

To connect your notebook to Cognos Analytics, add these two lines to the notebook:

from ca_data_connector import CADataConnector

CADataConnector.connect({'url':'CA_on_Cloud_URL'});

where CA_on_Cloud_URL is the URL that you use to connect to Cognos Analytics on Cloud.

If you are using Cognos Analytics on Cloud Pak for Data

To connect your notebook to Cognos Analytics, add this line to the notebook:

CADataConnector.connect({'url':'CA_URL_in_Cloud_Pak_for_Data'});

where CA_URL_in_Cloud_Pak_for_Data is the URL that you use to connect to your Cognos Analytics instance on Cloud Pak for Data.

Note: You don't need to include your credentials in the line above. Cloud Pak for Data will use the credentials from your current Notebook session.

Best practices for displaying notebook visualizations in dashboards

As a notebook author, you can use some coding best practices to ensure that notebook visualizations are properly displayed when they are rendered in dashboards.

Resizing a Bokeh visualization

For the dashboard to properly resize any Bokeh visualization, don't hardcode the visualization width and height elements in the notebook. Also, when creating any figure, plot, or column, use the parameter sizing_mode='scale_width'.

Here is an example of the correct coding practice:

```
from bokeh.plotting import figure, show
x = [1, 2, 3]
y = [1, 2, 3]
p = figure(sizing_mode='scale_width')
p.line(x, y)
```

The visualizations that are coded this way scale properly in the dashboard, maintaining their aspect ratio.

Reloading a Bokeh visualization after a browser refresh

For a dashboard to properly reload a Bokeh visualization after a browser refresh, include the Bokeh initialization statement output_notebook() in the applicable notebook output cells.

Here is an example of the correct coding practice:

```
# Notebook cell 1
from bokeh.plotting import figure, show
x = [1, 2, 3]
y = [1, 2, 3]
p = figure(sizing_mode='scale_width')
p.line(x, y)
# Notebook cell 2
output_notebook()
show(p)
```

Chapter 9. Managing content

The IBM Cognos Analytics content includes reports, report views, dashboards, stories, packages, uploaded files, folders, URLs, shortcuts, and so on.

Tip: To simplify the documentation process, the content items are often referred to as entries.

To organize and manage the content, you can create a folder hierarchy for entries. You can move, copy, disable, or delete the entries. You can also hide an entry to prevent it from unnecessary use, share the entry with other users, or embed it in a custom website.

Creating folders

Group related items into folders to mange content more easily.

For example, you can have folders for your dashboards, reports, or different types of items that you want to keep together.

After the folder is created, you can move or copy items to this folder. You can also secure the folder so that only users to whom you give permissions can access the content in the folder.

Procedure

- 1. In the **Content** view, open **My content**, **Team content**, or other folders.
- 2. From the actions toolbar, click the **Add folder** icon 🗔.

Copying or moving entries

When you create a copy of an entry, you create a replica of that entry in another location in the portal. When you move an entry, you remove it from the current folder and place it in another folder. When you copy and move entries, the IDs and links are either maintained or overwritten.

Before you begin

You must have read permissions for the entry that you are attempting to copy or move. You must also have traverse permissions for the current folder, and write and traverse permissions for the target folder.

About this task

If you copy or move a report from one folder to another, the report retains its ID and any links, including the link to the associated package. However, when you overwrite an existing entry, the link behavior depends on whether you copy or move the entry.

- If you copy and overwrite an existing entry, the copied entry ID and links replace those of the existing entry. In this case, you might need to update links, such as links to job schedules for reports.
- If you move and overwrite an existing entry, the existing entry ID and links are maintained. In this case, references to the moved entry are broken.

Procedure

- 1. Locate the entry in **Team content**, **My content**, or a different folder, and select the entry checkbox.
- 2. From the entry **Action menu** ; , or from the **More** option in the action toolbar, click **Copy or move to**.
- 3. Locate the target folder, and click **Copy**.

Copying and pasting assets

You can reuse an asset that you created by copying and pasting it between a dashboard, report, exploration, or story.

From (Source)	To (Target)
Dashboard	Dashboard, report, exploration, story
Exploration	Exploration, dashboard, report, story
Story	Story, dashboard, report, exploration
Report	Report

The following table shows how you can copy and paste assets.

The pasted asset can lose properties because dashboards, reports, explorations, and stories do not support all properties. For example, some properties apply only to reports and not to dashboards. A message informs you about the properties that are not supported.

If you copy and paste assets between instances of Cognos Analytics, the instances must have the same version.

Before you begin

Before pasting your asset into the target report, select the location, such as a table cell or the page body.

In a dashboard, exploration, and story, you can't copy and paste from one browser tab to another browser tab or copy and paste between tabs in the same browser. Only in a report you can copy and paste from one browser's tab to another report in another browser's tab.

For copying and pasting between reports, you can use either the same tab or different tabs of the same browser. However, if the source report is larger (typically more than 5 MB), then use the same browser tab for pasting. The following message is displayed: **Due to the report size the paste can be done in the same tab only**.

When you paste multiple assets in a report, a dialog box is displayed to allow pasting the assets in a new table.

Would you like to create a table for your steed assets?		
Number of assets: 2		
Table size		
Number of columns:	2]
Number of rows:	1]
Table style		
Maximize width		
Show borders		
	Yes No]

By default, the table has two columns with the number of rows calculated based on the number of assets that are being pasted. You can override the number of rows and columns. If the table does not have enough cells, then you get the following message: **The table is too small for the number of assets**. If you click **No**, then the table is not created and the assets are pasted one below the other. If you close the dialog box by clicking the **x** icon, the paste action is canceled.

In reporting, data items that do not match the report visualization slot type are dropped.

A certain mix of data sources that are supported by Dashboard, Exploration, and Story are not supported by Reporting. When this happens a proper warning is shown. For example, Reporting does not support a mix of modules and packages or multiple modules or multiple packages by using classic query mode. The following warning for mixing packages looks is displayed: **A report can reference multiple packages that use the dynamic query mode, or one package that uses the compatible query mode.**

In addition, Reporting does not support dimensional modules, except for IBM Planning Analytics modules.

When you copy from Dashboard, Exploration, and Story to paste in a report, the original widget size is kept only if the size is specified in pixels. If the widget size is set in percentage, then it will not be used during paste, instead the Reporting default is used.

When you copy and paste from a report to another report, all the assets that are referenced by the copied asset from the source report are also pasted in the target report. For example, queries referencing other queries.

Note: IBM Cognos Analytics might change the name of the source assets to avoid name conflict with assets that are already present in the target report.

When you copy and paste from a report to another report, and you select the page body or a table and perform the copy action, then all their assets will be copied over. For example, you have a table with 10

cells each cell with a list, crosstab, visualization. You do not need to select them one by one. Select the table and perform the copy action. A message will display that one asset is copied. Cognos Analytics copied all assets, 10 in this example. Copying and pasting a page, results in similar behavior.

You can paste multiple times in the same or different target Dashboard, report, exploration, or story.

You cannot paste the following widgets and assets from a dashboard to a report:

- Text
- Image
- Media
- Web page
- Shape
- Data player
- Driver analysis
- Decision tree
- Sunburst
- Spiral

Note: Some attributes such as custom titles, named colors, data sets, stand-alone spreadsheet data sources, and border colors can't be carried over when you paste an asset. Make sure that you review the messages that appear after pasting and if necessary, update the asset in its new location.

Procedure

- 1. Select one or more assets.
- 2. Use the keyboard shortcut for your operating system to copy.
 - A message is displayed that assets are copied.
- 3. In the dashboard, report, exploration, or story that you pasting to, use the keyboard shortcut for your operating system to paste.

Sharing content

If an administrator connects Cognos Analytics to Slack or enables email sharing, you can send Cognos Analytics report and dashboard content to other users. You can also share your Cognos Analytics content via URL links and embedded html in web pages. For Dashboards only, you can save your content as an exported PDF document.

You can share content from two locations:

- your Cognos Analytics canvas
- the Team content folder

Sharing content from the canvas

In Cognos Analytics, you can send Cognos Analytics content that you are currently viewing on your

Reporting or Dashboard canvas to your colleagues via 🗠 Email or 🗰 Slack.

For more information, see the Blog post <u>Increased Collaboration with Slack Integration in IBM Cognos</u> Analytics 11.1!

Before you begin

Your administrator must configure a mail server and/or a collaboration platform before you can use this feature.

Procedure

1. While viewing your Cognos Analytics content in the Reporting or Dashboard component, click the **Share** icon **%**.

Tip: A different **Share** icon appears in a context menu, after you click the More icon ******* for a content folder or on the **Welcome** page. However, the **Share** panel that you invoke from a context menu only allows you to share saved report outputs or dashboards. To share an image of an asset that

is open and that you are currently viewing, you must click the **Share** icon 쓕 in the application bar.

2. In the **Share** panel, click the **Send** tab.

Tip: If the **Send** tab does not appear, the administrator did not configure a mail server and did not configure a collaboration platform.

- 3. Click one of these platforms:
 - Email go to step <u>"4" on page 63.</u>

Tip: If **Email** does not appear as a platform, your administrator did not enable content sharing by email.

• Slack_platform_name - go to step "5" on page 63.

Tip: If a **Slack** platform appears grayed out, your administrator has disabled the platform. If you are not part of a slack workspace, you can join it through the pop-up window and then click on the workspace again in Cognos Analytics to continue sharing your content.

- 4. If you selected **Email**, in the **Share with email** panel, perform these steps:
 - a) Search for a recipient name, group, role, distribution list, or contact and then click **Search directory**. Repeat this step as necessary.

Tips:

- To add an external email address, enter the full address and then press Enter.
- If you start typing someone's name that you emailed recently, the full name quickly appears and you can select it.
- You can narrow the search results and speed up retrieval time by typing more characters in the recipient fields.
- Search results appear for all namespaces that you are logged into. You may need to scroll to see results for a different namespace.
- You can also browse for a recipient, by clicking **Directory** > *namespace*.

To quickly find an entry:

– Type text in the \mathbf{Q} Find field.

You can click the Search Method icon $\overleftarrow{\circ}$ to find entries that either contain, start with, or are an exact match with the text that you type.

- Click the filter \mathbf{V} icon to narrow the view of entries.
- b) Enter the email subject.
- c) Enter the message that you want to send.

Tip: To format your message, use the Styles and Format buttons.

- 5. If you selected *Slack_platform_name*, in the **Share with Slack:** *platform_name* panel, perform these steps:
 - a) Enter a channel or recipient name.

Tip: Start typing either a Slack channel name (starting with the hashtag symbol (#) or a Slack user name if you want to send a Direct Message in Slack. As you type, the list of possible choices is filtered, until you can select the one you want.

b) Enter the message that you want to send.

Tip: You must include some text in your message.

6. Select **Include link** if you want your recipient to click a link to your content.

Tip: Include link appears only if your content is located in the **Team content** folder. Other users cannot link to content located in **My content**.

- 7. Select Include image if you want to attach an image of your content to your Email or Slack message.
- 8. If you selected the **Include image** option, you can go to the **Modify your image (optional)** pane on the left and <u>edit the image</u> before you send it.
- 9. Click Send.

Results

Your message (and your image, if applicable) is sent to your selected recipients via email or Slack.

Editing canvas content for sharing

You can annotate a screen shot image of your Cognos Analytics content before you share it via email or Slack.

Before you begin

Open a dashboard or report, go to the view that you want to edit, and then begin the steps to send a message via email or via Slack.

Procedure

1. Go to the Modify your image (optional) pane on the left.

Tips:

• As you annotate your image, the only way you can lose your changes is to click **Cancel** in the **Share with Slack** panel on the right. If you accidentally click the top or left toolbar, the **Modify your image (optional)** temporarily disappears. However, you can resume your editing where you left off by

clicking the Share icon ⁶⁶.

- Use the Expand button 2⁷ to enlarge the **Modify your image** window and hide the **Share with Slack**
 - or **Share with Email** panel. Use the Collapse button \nearrow^{\prime} to revert to the original view.
- 2. To add text, an arrow, or a freehand line to your image, follow these steps:
 - a) Go to the toolbar and of the **Modify your image (optional)** pane and click one of these icons:
 - The Textbox icon
 - The Arrow icon 🖌
 - The Pen icon 🖉
 - b) Select a color.
 - c) Type your text or draw an arrow or line.
 - d) Click Done.
- 3. To add a rectangle to your image, follow these steps:
 - a) Go to the toolbar of the **Modify your image (optional)** pane and click the Rectangle icon \Box .

b) Click the Border icon \Box , and then select the border color.

Tip: If you previously selected a border color, the Border icon appears in that color.

c) Click the Fill icon , and then select the fill color.

Tip: If you previously selected a fill color, the Fill icon appears in that color.

- d) Hover over the image and click, drag, and then release to draw a rectangle.
- e) Click Done.
- 4. To edit any text, arrow, freehand line, or rectangle that you added, follow these steps:
 - a) Ensure that you selected **Done** in the previous steps so that the Modify your image toolbar appears
 - b) Click on the image.
 - c) To select an object, click on it.

A rectangle with drag handles appears around the object.

Tip: You can also press **Tab** successively to select each object that you created in the order that you created them. For more information, see <u>"Keyboard commands to edit canvas content" on page</u> 65.

d) To move a selected object, move your cursor over the selected object so that the cursor changes to

the Move cursor icon \circledast and then drag the object to the position you want.

- e) To resize a selected object, select and drag one of its handles.
- f) To delete one or more selected objects, click the Delete icon \fbox .
- g) To delete every object that you added to the image, from the Modify your image toolbar *****, click **Clear**.
- 5. To crop your image, follow these steps:
 - a) Go to the toolbar of the **Modify your image (optional)** pane and click the Crop icon \square .
 - b) On the image, click, drag, and then release to draw a highlighted rectangle over the area that you want to crop.
 - c) Click Done.
- 6. If necessary, complete any remaining steps to send a message via email or Slack.

Results

Your message and edited Cognos Analytics content are shared with the Slack recipients that you selected.

Keyboard commands to edit canvas content

You can use keyboard shortcuts as an alternative way to invoke a command by pressing a combination of keyboard keys.

The following tables list keyboard shortcuts to edit an image on your canvas that you plan to share with your colleagues.

PC keyboard command	Macintosh keyboard command	Description
t	t	Activate the Textbox Tool
a	a	Activate the Arrow Tool
р	р	Activate the Pen Tool
r	r	Activate the Rectangle Tool
с	с	Activate the Crop Tool

PC keyboard command	Macintosh keyboard command	Description
q	q	Rotate object(s) clockwise 10 degrees
Shift + Q	Shift + Q	Rotate object(s) counter- clockwise 10 degrees
Delete/Backspace	Delete	Delete object(s)
]]	If the active select object is a textbox, shrink the word- wrapped area horizontally by 5 px.
Shift + {	Shift + {	If the active select object is a textbox, shrink the word- wrapped area horizontally by 50 px.
]]	If the active select object is a textbox, expand the word wrapped area horizontally by 5 px.
Shift + }	Shift + }	If the active select object is a textbox, expand the word wrapped area horizontally by 50 px.
Ctrl + z	Ctrl + z / Command + z	Undo Previous Action
Ctrl + y	Ctrl + y / Command + y /	Redo Previous Action
Escape	Escape	Close Entire Panel

PC keyboard command	Macintosh keyboard command	Description
Tab	Tab	Move the tool selection on the toolbar from Left to Right one at a time. If you press Tab on the final tool (for example, Clear/Done) the focus moves from the toolbar to the image.
Shift + Tab	Shift + Tab	Move the tool selection on the toolbar from Right to Left one at a time. Pressing Shift + Tab on the First tool moves the focus from the toolbar to the parent element.
Enter	Enter/Return	Activate the selected tool/color

PC keyboard command	Macintosh keyboard command	Description
Up Arrow	Up Arrow	Scroll the image up (If applicable)
Down Arrow	Down Arrow	Scroll the image down (If applicable)

PC keyboard command	Macintosh keyboard command	Description
Left Arrow	Left Arrow	Scroll the image left (If applicable)
Right Arrow	Right Arrow	Scroll the image right (If applicable)
Up Arrow	Up Arrow	Move the selected Object(s) up by 5 px.
Down Arrow	Down Arrow	Move the selected Object(s) down by 5 px.
Left Arrow	Left Arrow	Move the selected Object(s) left by 5 px.
Right Arrow	Right Arrow	Move the selected Object(s) right by 5 px.
Shift + Up Arrow	Shift + Up Arrow	Move the selected Object(s) up by 50 px.
Shift + Down Arrow	Shift + Down Arrow	Move the selected Object(s) down by 50 px.
Shift + Left Arrow	Shift + Left Arrow	Move the selected Object(s) left by 50 px.
Shift + Right Arrow	Shift + Right Arrow	Move the selected Object(s) right by 50 px.
Shift + Alt + Up Arrow	Alt + Up Arrow	Scale the selected Object(s) up by 5 px. Bottom Right Corner is selected for scaling.
Shift + Alt + Down Arrow	Alt + Down Arrow	Scale the selected Object(s) down by 5 px. Bottom Right Corner is selected for scaling.
Shift + Alt + Left Arrow	Alt + Left Arrow	Scale the selected Object(s) left by 5 px. Bottom Right Corner is selected for scaling.
Shift + Alt + Right Arrow	Alt + Right Arrow	Scale the selected Object(s) right by 5 px. Bottom Right Corner is selected for scaling.
Shift + Alt + Up Arrow	Shift + Alt + Up Arrow	Scale the selected Object(s) up by 50 px. Bottom Right Corner is selected for scaling.
Shift + Alt + Down Arrow	Shift + Alt + Down Arrow	Scale the selected Object(s) down by 50 px. Bottom Right Corner is selected for scaling.
Shift + Alt + Left Arrow	Shift + Alt + Left Arrow	Scale the selected Object(s) left by 50 px. Bottom Right Corner is selected for scaling.
Shift + Alt + Right Arrow	Shift + Alt + Right Arrow	Scale the selected Object(s) right by 50 px. Bottom Right Corner is selected for scaling.

PC keyboard command	Macintosh keyboard command	Description
Tab	Tab	Press successively to select each object that you created in the order that you created them. If the final object is already selected, hitting Tab will move focus from the image to the Share Panel.
Shift + Tab	Shift + Tab	Press successively to select each object that you created in the order that you created them. If the first object is already selected, hitting Shift + Tab will move the focus from the image to the toolbar.
Enter	Enter/Return	Enter Textbox Editing Mode if the active select object is a textbox.
Escape	Escape	Deselect any active object. If the selected object is a textbox and is currently in Textbox Editing Mode, it exits Textbox Editing Mode.
Escape	Escape	Deselect the active object and stop drawing. If the active select object is a textbox, exit Textbox Editing Mode
Enter	Enter/Return	Begin drawing an object with the virtual cursor by simulating a mouse down event.
Enter	Enter/Return	End drawing an object with the virtual cursor by simulating a mouse
Up Arrow	Up Arrow	Move the Virtual Cursor up by 5 px.
Down Arrow	Down Arrow	Move the Virtual Cursor down by 5 px.
Left Arrow	Left Arrow	Move the Virtual Cursor left by 5 px.
Right Arrow	Right Arrow	Move the Virtual Cursor right by 5 px.
Shift + Up Arrow	Shift + Up Arrow	Move the Virtual Cursor up by 50 px.
Shift + Down Arrow	Shift + Down Arrow	Move the Virtual Cursor down by 50 px.
Shift + Left Arrow	Shift + Left Arrow	Move the Virtual Cursor left by 50 px.
Shift + Right Arrow	Shift + Right Arrow	Move the Virtual Cursor right by 50 px.
Exporting dashboard content to PDF

You can export your dashboard content to a PDF that you can print or share electronically.

About this task

When you export a PDF from the **Share** panel, the same process is used to create the PDF as when you click the more icon in an open dashboard.

For tips on preparing your content for export and to understand browser differences, see *Exporting a dashboard to PDF*.

Procedure

- 1. Open your Cognos Analytics dashboard and navigate to the view that you want to send to a co-worker.
- 2. Click the **Share** icon **%** in the application bar.

Tip: Although the **Share** icon S also appears when you click the context menu icon in a content folder or on the **Welcome** page, you are limited to sharing links or embedded html. You cannot save the image as a PDF because the content does not appear in your window.

- 3. Click the **Export** tab.
- 4. Select the settings you want from the **Page size** and **Orientation** menus.
- 5. To apply filters, select the **Include filters** check box.
- 6. Click Export.

The print window for the browser opens.

7. You can now save your PDF. For browser-specific details, see Exporting a dashboard to PDF.

What to do next

You can view the PDF or send it by email. If your administrator has configured a collaboration platform, such as Slack, you can drag the exported PDF file from your desktop into the Message box of a Slack channel or direct message.

Sharing assets from the Team content folder

You can share with your colleagues report outputs or dashboards that are located in the **Team content** folder.

Sharing assets from Team content via email

You can share Cognos Analytics report outputs or dashboards in the **Team content** folder by \square **Email**.

Before you begin

Your administrator must configure a mail server before you can use this feature.

About this task

Cognos Analytics allows you to select **Share** in an asset's context menu from several access points:

- the Team content folder
- the **Home** 🙆 page, in the list of recently opened assets
- the Search results \mathbf{Q} pane

Note: The following task describes accessing the context menu from the **Team content** folder. However, you can use any of the access points listed above.

Procedure

- 1. Save your dashboard or report output in the Team content folder.
 - Tip: Other users are not authorized to open content in your My content folder.
- 2. Navigate to the saved asset in the Team content folder.
- 3. Click the More icon i for the asset and then, in the context menu, click **Share**.

Tip: A different **Share** icon ∞ appears in the application bar at the top of your window when you are viewing content on your canvas:

• If you are editing a new report or dashboard on your canvas and you click the **Share** icon ⁶⁶ in the application bar, the **Share** panel only allows you to share the content from your current view.

Previously saved report output cannot be shared by clicking the **Share** icon ⁶ in the application bar.

• If you are viewing a saved report output PDF and you click the **Share** icon ⁶⁵ in the application bar, the **Share** panel only allows you to share the saved PDF version as a link or an attachment.

4. In the **Share** panel, click the **Send** tab.

Tip: If the **Send** tab does not appear, the administrator did not configure a mail server and did not configure a collaboration platform.

5. Click Email.

Tip: If **Email** does not appear as a platform, your administrator did not enable content sharing by email.

The Share with email panel appears.

6. Search for a recipient name, group, role, distribution list, or contact and then click **Directory**. Repeat this step as necessary.

Tips:

- To add an external email address, enter the full address and then press Enter.
- If you start typing someone's name that you emailed recently, the full name quickly appears and you can select it.
- You can narrow the search results and speed up retrieval time by typing more characters in the recipient fields.
- Search results appear for all namespaces that you are logged into. You may need to scroll to see results for a different namespace.
- You can also browse for a recipient, by clicking **Directory** > *namespace*.

To quickly find an entry:

– Type text in the \mathbf{Q} Find field.

You can click the Search Method icon to find entries that either contain, start with, or are an exact match with the text that you type.

- Click the filter \mathbf{V} icon to narrow the view of entries.
- 7. Keep the default subject or enter a new one.
- 8. Enter the message that you want to send.

Tip: To format your message, use the **Styles** and **Format** buttons.

9. Select Include link if you want your recipient to click a link to your content.

Tip: Include link appears only if your content is located in the **Team content** folder. Other users cannot link to content located in **My content**.

10. If report output exists in a valid attachment format, you can attach one or more outputs to your email.

Tip: For more information, see "Valid report output formats for email attachments" on page 71.

- a) Select Attach report output.
- b) Click **Add**.

The **Pick report output** panel appears. Each output option appears only if it already exists as a saved report output. However, HTML format cannot be attached to an email.

- c) Select a report version.
- d) Select a burst key, if the field appears in the panel.
- e) Select a format.
- f) Select a language.
- g) Click Add.
- h) If there are additional version outputs that you want to attach, repeat steps <u>"10.b" on page 71</u> to <u>"10.g" on page 71</u>.
- i) Click Done.
- 11. Click Send.

Results

Your message is sent to your selected recipients via email.

Valid report output formats for email attachments

Most formats of saved report outputs can be attached to an email that you send to your colleagues.

You can attach report output versions that were saved in the following formats:

- Excel
- Excel Data
- PDF
- CSV
- XML

Note: A report output saved in HTML format cannot be attached to an email. Although HTML output can be viewed in Cognos Analytics, it is not compatible as an email attachment.

Sharing assets from Team content via Slack

In Cognos Analytics, you can send Cognos Analytics report outputs or dashboards in the **Team content**

folder by **TF Slack**.

For more information, see the Blog post <u>Increased Collaboration with Slack Integration in IBM Cognos</u> <u>Analytics 11.1!</u>

Before you begin

Your administrator must configure a collaboration platform before you can use this feature.

About this task

Cognos Analytics allows you to select **Share** in an asset's context menu from several access points:

• the Team content 🙆 folder

- the **Home** Dage, in the list of recently opened assets
- the Search results \mathbf{Q} pane
- the **Recent** () pane

Note: The following task describes accessing the context menu from the **Team content** folder. However, you can use any of the access points listed above.

Procedure

1. Save your Cognos Analytics dashboard or report output in the **Team content** folder.

Tip: Other users are not authorized to open content in your My content folder.

- 2. Navigate to the saved asset in the **Team content** folder.
- 3. Click the More icon i for the asset and then, in the context menu, click **Share**.

Tip: A different **Share** icon ⁶⁶ appears in the application bar at the top of your window when you are viewing content on your canvas:

• If you are editing a new report or dashboard on your canvas and you click the **Share** icon ⁶ in the application bar, the **Share** panel only allows you to share the content from your current view.

Previously saved report output cannot be shared by clicking the **Share** icon % in the application bar.

- If you are viewing a saved report output PDF and you click the **Share** icon ∞ in the application bar, the **Share** panel only allows you to share the saved PDF version as a link or an attachment.
- 4. In the **Share** panel, click the **Send** tab.

Tip: If the Send tab does not appear, the administrator did not configure a collaboration platform.

5. Click *Slack_platform_name*.

Tip: If a **Slack** platform appears grayed out, your administrator has disabled the platform. If you are not part of a slack workspace, you can join it through the pop-up window and then click on the workspace again in Cognos Analytics to continue sharing your content.

The Share with Slack: platform_name panel appears.

6. Enter a channel or recipient name.

Tip: Start typing either a Slack channel name (starting with the hashtag symbol (#) or a Slack user name if you want to send a Direct Message in Slack. As you type, the list of possible choices is filtered, until you can select the one you want.

7. Enter the message that you want to send.

Tip: You must include some text in your message.

8. Select Include link if you want your recipient to click a link to your content.

Tip: Include link appears only if your content is located in the **Team content** folder. Other users cannot link to content located in **My content**.

9. Click Send.

Results

Your message is sent to your selected recipients via Slack.

Linking to saved content

In Cognos Analytics, you can create a URL for any view in your dashboard or report. You can then send the URL by email or embed the URL in a web page or another dashboard or report.

You can share content objects, such as reports and dashboards, with a URL that opens the content object directly, instead of having to browse to the content object from the Cognos Analytics welcome screen. You can also embed Cognos Analytics content objects (except for data modules) in customized web pages. An embedded content object does not display the application or navigation bars.

Procedure

1. Save your Cognos Analytics dashboard or report output in the **Team content** folder.

Tip: Other users are not authorized to open content in your My content folder.

- 2. Navigate to the view that you want to send to a co-worker.
- 3. Click the More icon i for the asset and then, in the context menu, click **Share**.

Tip: A different **Share** icon ⁶ appears in the application bar at the top of your window if you are viewing content on your canvas. However, if you click that icon, the **Share** panel only allows you to share the content from your current view, not previously saved output.

4. In the **Share** panel, click the **Link** tab.

Tip: You can modify the URL to perform other actions, such as opening a report for editing instead or running the report, or changing the output format of the report. For more information, see *Creating custom URLs to display and run Cognos Analytics content* in *IBM Cognos Analytics Getting Started User Guide*.

5. If you want to send the link to a co-worker by email, do the following:

a) In the **Link** section, click the **Copy** icon \Box .

The URL is copied to your clipboard.

- b) Paste the URL into your email and send the email.
- 6. If you want to embed the html code for your view in a web page, go to the **Embed code** section, and follow these steps:
 - a) If you want to change the height and width of the iframe that will contain the code, adjust the values in the **Width** and **Height** fields.
 - b) click the Copy icon \Box

The URL is copied to your clipboard.

c) Paste the URL into the html text of your web page.

Authentication sample with embedded content

The embedded content sample shows how to use the IBM Cognos Analytics REST API to sign in a user and then display embedded content.

Procedure

- 1. Copy the embedded_content folder from the *<installation_location>*\samples folder to the *<installation_location>*\webcontent folder.
- 2. Open the \webcontent\embedded_content\preLoginSample.html file in a text editor, and locate the <select> element:

3. For any of the configured namespaces that you want to see as a selection in the login page, define the <option> element within the <select> element, using the following syntax:

```
<option value="namespace_ID">namespace_name</option>
```

The *namespace_ID* corresponds to the **Namespace ID** property, as defined for the namespace in Cognos Configuration, under **Security** > **Authentication**. The *namespace_name* can be any word; however, the name defined in Cognos Configuration is preferred.

- 4. Open the \webcontent\embedded_content\iFrameSample.html file, and replace the iFrame objects with **Embed** iFrame objects from your Cognos Analytics installation.
- 5. In a web browser, type http://<server_name>:<port>/embedded_content/ preLoginSample.html

Results

A sign-in web page is displayed. After you sign in, the embedded content objects are shown.

Creating custom URLs to display and run Cognos Analytics content

You can create URLs that open or run IBM Cognos Analytics content objects, such as reports, dashboards, stories, and data modules. This feature extends the **Share** > **Link** command that creates a URL to display Cognos Analytics content objects to provide more control over the actions that are taken when the content object is displayed or run.

When you link to saved content, you create a URL that opens or runs Cognos Analytics content objects. You can create these URLs if you require more control over the actions invoked by them.

The following report types are supported in custom URLs: standard reports, report views, active reports, data sets, Query Studio reports, Analysis Studio reports, and their saved outputs.

If the content object is a report that has saved output, the saved output may be displayed, depending on the chosen URL parameters. Otherwise, the content object is run. If the content object is saved output, it is displayed. An error message is displayed if the saved output has been deleted.

Syntax

The syntax of the custom URLs takes one of the following two forms.

- http://<servername>:<port>/bi/?pathRef=<path>&<option1>=<value1>&<option2>=<value2>...
- http://<servername>:<port>/bi/?objRef=<id>&<option1>=<value1>&<option2>=<value2>...

pathRef or objRef identify the content object to use.

pathRef

Specifies the location of the object. This value does not change if the version of Cognos Analytics is changed or if the object is exported or imported in a deployment.

The easiest way to determine the value of **pathRef** is to create a URL by using the **Share** command. This URL contains the value of **pathRef**.

objRef

Specifies the id of the object. This value does not change if the content object is moved to a different location in **My content** or **Team content**.

The value of **objRef** is the **ID** value in the properties pane of the object.

perspective

Specifies which perspective to use: classicViewer or authoring. This parameter should normally not be specified, as the system will determine it based on properties of the object referenced by the URL.

A number of optional parameters can be appended to the URL. The following two options can be used in any perspective:

ui_appbar

Specifies whether to display the Application bar (true) or not (false). The default value is true.

ui_navbar

Specifies whether to display the Navigation bar (true) or not (false). The default value is true.

The following options can be used if the content object is a report.

action

Specifies whether to view saved output, run a report, or author an object. The following values are supported: viewOutput, run, edit. The default value is determined by the object's properties. When viewOutput is specified and there is no saved output, the object is run.

a11y

When running a report, specifies whether to include accessibility features (true) or not (false). The default value is false.

bidi

When running a report, specifies whether to enable bidirectional support (true) or not (false). The default value is false.

contentLocale

Specify the locale in which the report output is created when running or which locale to view when the report output was saved using multiple locales. The default is determined from the user's preferences. Use an ISO country code for the value. For example, for German, specify contentLocale=de.

For this parameter to work, you must have a multilingual reporting environment. For more information, see "Setting up a multilingual reporting environment" in the *IBM Cognos Analytics Reporting User Guide*.

format

When running a report, specifies the output format. When viewing saved output, specifies which of the available formats to view.

The possible values are: HTML, PDF, spreadsheetML, xlsxData, CSV and XML. layoutDataXML, XLWA, rawXML, XHTML, singleXLS, and HTMLFragment. The default value is determined from the object's properties or the user's preferences.

productLocale

Specify the product locale to use. The default is determined from the user's preferences.

prompt

When running a report, specifies whether to show the prompt page (true) or not (false). The default value is false.

p_<prompt_name>

When running a report, specifies the value to use for the parameter named <prompt_name>.

promptParameters

When running a report, specifies prompt parameters as a JavaScript Object Notation (JSON) object. You can pass more complex parameter values to use when you run a report. For more information, see promptParameters option syntax.

- The easiest way to create a custom URL is to use the **Share** command for the content object that you want to create a custom URL for, and then to modify the options in this URL.
- Custom URLs can be long and your Cognos Analytics server environment might impose a length limit on the query portion of the URL You can work around this limitation by using the URL fragment identifier (#) in the URL. Here are some examples.
 - http://<servername>:<port>/bi/#pathRef=<path>&<option1>=<value1>&<option2>=<value2>...
 - http://<servername>:<port>/bi/?pathRef=<path>&<option1>=<value1>#<option2>=<value2>...
- If you use a custom URL in an HTML item in a report, replace instances of & with & amp;.

Note: You can either specify a URL or use the HTTP POST method to send the options to the Cognos Analytics server. However, you must specify all parameters using the same method: either URL or HTTP POST.

Example

The following example uses the HTTP POST method to specify a customized URL.

```
<html>
<body>
<div class="acordion">
<div class="submit">
<form method="POST" id="cognosPost" accept-charset="UTF-8"
action="http://cognos_analytics_IP_address:9300/bi/">
<input type="hidden" name="pathRef" value=".public_folders/folder1/report1"
style="display: none">
<input type="hidden" name="promptParameters" id="promptParameters"
value='{"name":"p_Line","value":{"use":"Camping Equipment"}}'
style="display: none">
<input type="hidden" name="format" value="HTML" style="display: none">
<input type="hidden" name="format" value="HTML" style="display: none">
<input type="hidden" name="format" value="false" style="display: none">
<input type="hidden" name="Download" value="false" style="display: none">
<input type="bidden" name="btn" value="Run report with Camping Equipment">
</div>
</div>
</div>
</div>
</html>
```

promptParameters option syntax

You can use the **promptParameters** option to pass complex parameter values for use when you run a report. The parameter values are contained in a JavaScript Object Notation (JSON) object.

Syntax

The syntax of the **promptParameters** option is promptParameters=[{<parameter_1>}, {<parameter_2>,...]. The syntax of each parameter value depends on the type of parameter value and are described as follows.

Specific values

```
{
    "name":"<parameter_name>",
    "value":[
        {"use":"<use_value1>","display":"<display_value_1>"},
        {"use":"<use_value2>"},
        ...
    ]
}
```

<parameter_name> is the name of the parameter, <use_value1> is the use value, and
<display_value_1> is the display value. The display value is optional.

Bounded range

<parameter_name> is the name of the parameter, <use_start_value> is the lower use value,
<display_start_value> is the lower display value, and <use_end_value> is the upper use value. The
display value is optional.

Unbounded start range

<parameter_name> is the name of the parameter, <use_end_value> is the upper use value, <display_end_value> is the upper display value. The display value is optional.

Unbounded end range

<parameter_name> is the name of the parameter, <use_start_value> is the lower use value, <display_start_value> is the lower display value. The display value is optional.

Creating shortcuts

You can create shortcuts for entries, such as dashboards, explorations, reports, and folders. The shortcut context menu provides the same options as the target context menu. For example, the **Run as option** is available from both the report and its shortcut context menus.

Procedure

- 1. Locate the entry in Team content, My content, or a different folder, and select the entry checkbox.
- 2. From the entry **Action menu** ; , or from the **More** option in the actions toolbar, click **Add shortcut**.
- 3. Find a location for the shortcut, and click **Create shortcut**.

Creating URLs to other sites

A URL is a standard way of identifying the location of any external file or website. Create URLs to keep the files and websites you use most frequently at your fingertips. Clicking a URL opens the file or website in the browser.

About this task

The URL must contain a valid server name that is included in the valid domains list, as specified by your administrator. Otherwise, you cannot create the URL.

Administrators maintain the list of valid domains. For more information, see the *IBM Cognos Analytics Installation and Configuration Guide*.

Procedure

1. In a subfolder within Team content, or in My content, ensure that no items are selected.

Tip: You can't add a URL directly to a too folder, such as Team content or Samples.

- 2. In the actions toolbar, click the **Add link** icon @.
- 3. In the Add a URL box, type the URL name.

- 4. If you want, specify the **Description**.
- 5. In the **URL** field, type the URL.

If the URL points to a website address, the protocol must be included. For example, to create a URL for the IBM website, type http://www.ibm.com

The URL must use a valid domain, as specified by your administrator. To view a list of acceptable domains, click **View acceptable domains**.

6. Click Add.

Hiding entries

To prevent unnecessary use of IBM Cognos Analytics items, such as reports, packages, folders, jobs, or data servers, you have the option of hiding them.

This is especially important for drill-through reports that can waste system resources when they are run unnecessarily.

To hide an entry, open its context menu and click **Properties**. On the **General** tab, open the **Advanced** section, and select the **Hide this entry** checkbox.

To show hidden entries in your content lists, click the **Personal menu** icon $\stackrel{\frown}{\leftarrow}$ icon in the application bar, and then click **Profile and settings**. On the **Settings** tab, turn on the **Show hidden entries** toggle switch.

Hidden entries are visible, but faded in the following parts of the user interface:

- · Search results.
- Properties panel, **Permissions** tab.
- Personal tabs.
- Job steps that refer to hidden entries already in a job.
- Agent tasks that refer to hidden entries already in an agent.
- Details in a report run history.

The following rules apply to hidden entries:

- A hidden report is accessible as a drill-through target. Drill-through targets include parameter values to avoid resource-intensive query operations. However, users still require appropriate permissions to use this target report in a drill-through activity.
- A hidden drill-through definition is not displayed in the **Go To** page if the user interface does not show hidden entries.
- A visible shortcut can point to a hidden entry. If the shortcut points to a hidden folder, any hidden entries in the folder are not visible.

Setting properties for entries

You can control the way entries appear and behave in IBM Cognos Analytics by modifying their properties.

You can view and set general and advanced properties for reports, folders, dashboards, stories, uploaded files, data modules, and other entries. When you open the properties panel, you see the **General** tab and the **Permissions** tab for all entries, and the tabs that are appropriate for the entry you're viewing, such as **Report** and **Schedule** for reports.

To open the properties panel for an entry, from its context menu ***, click **Properties**. You can also click the properties icon $\overline{\bullet}$ in the application bar.

Tip: To specify **Team content** properties, in the actions toolbar, click the **Details** icon (i). In the **Details** pane that opens, click **Properties**.

Chapter 10. Managing your schedules and subscriptions

You can schedule entries to run at a time that is convenient for you or when demands on the system are low. Or you may want to run them at a regular weekly or monthly interval. Similarly, you can subscribe to reports that were made public by other people.

To use scheduling, you must have permissions for the **Scheduling** capability. For more information, see the *IBM Cognos Analytics Manage Guide*.

For information about creating schedules or subscriptions, see <u>"Scheduling an entry" on page 79</u> or <u>"Subscribing to reports" on page 33</u>.

Scheduling an entry

You schedule an entry, such as a report, report view, or a notebook, to run it later or at a recurring date and time.

About this task

Only one schedule can be associated with each entry. If you require multiple schedules for a report, you can create report views, and then create a schedule for each view.

You can schedule entries individually, or use jobs to schedule multiple entries at once. Jobs have their own schedules independent from the individual entries schedules. For more information, see <u>"Creating a</u> job to schedule multiple entries" on page 81.

To schedule an entry, you need the permissions that are required to run the entry. For example, to schedule a report or report view, you must have read, write, execute, and traverse permissions for it. To schedule a child report view, you must have execute permissions for the parent report. You also need the required access permissions for any data sources that the entry relies on.

The scheduling options that are available to you depend on your permissions for the **Scheduling** capability.

For more information, see the IBM Cognos Analytics Managing Guide.

Procedure

- 1. Click the entry context menu ; , and then click **Properties**.
- 2. In the **Properties** pane, click the **Schedule** tab, and then click **New**.
- 3. In the Create schedule pane, specify the schedule options.
- 4. To access additional scheduling options, click **Classic View**. Specify your options, and click **OK**. When you return to the previous view, click **Create**.

The schedule entry appears in the **Create schedule** page.

What to do next

After you create a schedule, the entry or job runs at the time and date specified. You can then view the schedules and manage them. For more information, see "My schedules and subscriptions" on page 85.

If you no longer need a schedule, you can delete it. You can also disable schedules without losing any of the scheduling details. The schedules can be enabled later.

Differences between a schedule and a subscription

In IBM Cognos Analytics, you can create and maintain both schedules and subscriptions. Although they share some similar characteristics, there are also key differences.

The following table shows the main differences between schedules and subscriptions.

Schedule	Subscription
Only the report owner can create the schedule.	Many people can create a subscription from the same report.
The scheduler must have Read, Write, and Execute permissions for the report.	A subscriber requires only Read and Execute permissions for the report. If you have an Analytics Viewer license, you can subscribe to reports, but not schedule them. For more information, see "License roles" in <i>Managing IBM Cognos Analytics</i> .
There can only be one schedule per report.	There can be up to 32 subscriptions for the same report.
Created by tapping the More button for the report's list entry.	Created by running a report and, in view mode,
	tapping the More button 🛄 in the application bar.
Anyone with read access can view the schedule.	Only the subscriber can view their subscription.
The owner <u>controls the maximum number of saved</u> report versions.	Only the most recent saved report output is available.
You can specify that an email be sent to many people.	If you specify email delivery, it can be sent only to you.
The report can be run daily, weekly, monthly, yearly, or in response to a trigger that is set by the administrator, such as a database refresh.	The report can be run daily or weekly.

Deleting a subscription

You can delete one or more subscriptions that you created.

Before you begin

After you <u>subscribe</u> to a report, you can <u>view a list of your schedules and subscriptions</u>. If you want to delete one of your subscriptions, follow the steps below.

Procedure

- 1. Click the **Personal menu** icon $\stackrel{\frown}{\cap}$ in the application bar, and then click the **Profile and settings** link below your user name.
- 2. On the **Settings** tab, turn on the **Show hidden entries** toggle switch.
- 3. Click My content, and then click the Subscriptions folder.

Tip: The Subscriptions folder is gray, as it is a hidden folder that is now enabled to be shown.

Your subscriptions appear as a list of report views 🐻.

- 4. Click the More button in next to the subscription that you want to delete.
- 5. Click Delete III.

Results

The subscription is removed from the My schedules and subscriptions list.

Creating a job to schedule multiple entries

You can set the same schedule for multiple entries by creating a job. A job identifies a collection of reports, report views, and other jobs that are scheduled together and share the same schedule settings. When a scheduled job runs, all the entries in the job run.

If a job item is unavailable, you can select a different link by clicking Link to an entry.

Jobs contain steps, which are references to individual reports, jobs, and report views. You can specify whether to run the steps all at once or in sequence.

- When steps are run all at once, all the steps are submitted at the same time. The job is successful when all the steps run successfully. If a step fails, the other steps in the job are unaffected and still run, but the job has a **Failed** status.
- When the steps are run in sequence, you can specify the order in which the steps run. A step is submitted only after the preceding step runs successfully. You can choose to have the job stop or have the other steps continue if a step fails.

You can schedule a job to run at a specific time, on a recurring basis, or based on a trigger, such as a database refresh or an email. For more information about trigger-based entry scheduling, see the *Administration and Security Guide*.

The individual reports, jobs, and report views in steps can also have individual schedules. Run options for individual step entries override run options set for the job. You can set run options for the job that serve as the default for step entries that do not have their own run options.

You can run reports to produce outputs based on the options that you define, such as format, language, and accessibility.

Permissions required to include an entry as part of a job vary depending on the type of entry. The permissions are the same as for scheduling an entry. For more information on scheduling an entry, see <u>"Scheduling an entry" on page 79</u>

Procedure

1. From the **Open menu** menu in the application bar, click **New**, and select **Job**.

The **Steps** page appears.

- 2. Click the Add job step icon 🛡
- 3. Select reports to be included in the job.
 - a) Navigate to a folder containing reports you want.
 - b) Select check boxes for one or more reports.

Tips:

- Ctrl-click to select multiple check boxes.
- Use the **Select all in folder** and **Deselect all in folder** links followed by Ctrl-clicking check boxes to quickly finish your selections in a folder.
- Click Add job steps.
- c) Repeat steps "3.a" on page 81 and "3.b" on page 81 to select reports in other folders.

The **Steps** window lists the steps defined for your job. Each step listing shows:

• the name of a report that you selected

Tip: Hover over the report name to see the navigation path to the report location.

· whether the step options are defined by the report or are customized

- 4. To change the current step options for any step in your job:
 - a) Click the Edit options icon 🧷 for the step that you want to modify.
 - b) Edit the Format, Accessibility, Bursting, Delivery, Languages, or Prompt options.
 - c) Click **Close**.
- 5. To change the default run options for future steps:
 - a) Select Change default step options.
 - b) Edit the Format, Accessibility, Bursting, Delivery, prompts, or Languages options.
 - c) Click **Close**.
- 6. To remove a step, hover over the step and then click the Remove job step icon \bigcirc .
- 7. Under Run order, select whether the steps should Run all at once or Run in sequence.
 - If you select Run in sequence, the steps are executed in the order they appear in the Steps list.
 - If the **Run all at once** option is grayed out, your administrator has disabled it.

For more information, see "Disabling the Run all at once option in jobs" in the Cognos Analytics Managing Guide

• If you want the job to continue to run even if one of the steps fails, select the **Continue on error** check box.

Tip: To change the order of steps, click a step and drag it to the position that you want.

- 8. In the application bar, click the Save icon \square .
- 9. Navigate to a folder in which to save your job, enter a job name in the **Save as** box, and then click **Save**.

Run now and Schedule links appear in the Run Options section.

- 10. To run the report immediately, click Run now and click Finish. .
- 11. To schedule at a recurring time, follow these steps:
 - a) Click **Schedule**.
 - b) Click **New**.
 - c) Enter the details of when you want the job to run.
 - d) Click **Create**.

Tip: If this message appears: "Your credentials are required to complete this operation", click **Renew** and then enter your Cognos Analytics userid and password.

Results

A job, denoted by the job icon ⁹, is created in the folder you selected and will run at the next scheduled time.

What to do next

You can select operations from the following menu after you click the More icon *** for the job you created:

⊳ Run as
I. View versions
🍫 Create a new job
🖉 Edit the job
Copy or move
ū Delete
😂 Properties

84 IBM Cognos Analytics Version 11.2.0 : Getting Started User Guide

Chapter 11. Personal settings

Use personal settings to customize your IBM Cognos Analytics experience. You can view and edit your personal and regional information, monitor the system activities, set up logging, and so on.

To view or change any of the personal settings, click the Personal menu icon $\stackrel{\sf O}{\rightarrow}$ in the application bar.

To view notifications about the latest system activities that are applicable to you, click the notifications icon \bigcirc in the application bar.

Notifications

Notifications help you stay on top of important data. If you subscribe to a report or report view, you are notified every time your subscription is delivered. If you view saved output and you want to know when there's a new version of the report, you can subscribe to it.

The Subscribe option is available in view mode of a saved output version of a report when you tap the

More button in the application bar.

Tip: To ensure that you are in view mode, and not in edit mode, turn the edit toggle Edit off.

If you request notification and then someone runs that report, you get a notification with a link to the updated version.

When you subscribe, if you choose the **Save the report on the system** delivery option, you receive a notification with a link to the new report version. To see all your notifications, tap the Notifications button

🕂 in the application bar.

For more information, see "Subscribing to reports" on page 33.

My schedules and subscriptions

You can view all your scheduled activities and subscriptions on the **My schedules and subscriptions** panel.

About this task

You can view a list of your scheduled activities that are current, past, or upcoming on a specific day. You can filter the list so that only the entries that you want appear. A bar chart shows you an overview of daily activities, by hour. If you switch views, you must refresh to see current data. For example, if you switch from **Past Activities** to **Upcoming Activities**, you must refresh to see current data in the panes.

You can see the **My schedules and subscriptions** option in the Personal menu $\overset{\frown}{\sim}$ only if your administrator has granted you access to the Scheduling capability. For more information, see "Assigning capabilities based on license roles" in the *IBM Cognos Analytics Managing Guide*.

You can enable, disable, modify, or delete subscriptions, and view their saved outputs or archived versions. If you view the versions, you can also open the version details panel for information such as the run status, error messages, and run time.

For more information, see "Differences between a schedule and a subscription" on page 80.

Procedure

1. In the application bar, click your user name $\stackrel{\sf O}{\sim}$ icon , and then click **My schedules and subscriptions**.

2. To see both a listing and a graph of your schedules and subscriptions for a specific time frame, click

the Schedule drop-down menu *Y*, and then click Upcoming, Past, or Current.

3. To perform actions on a schedule or subscription in the list, click the More icon in the list item, and then click an action.

Personal application settings

You can set up preferences for your IBM Cognos Analytics application.

To set your preferences, click the **Personal menu** icon $\stackrel{old on}{\frown}$ in the application bar, and then click the **Profile and settings** link below your user name.

Language settings

You can select the language that you prefer for the IBM Cognos Analytics user interface. If your data and reports are available in multiple languages, you can also select the language that you prefer for the content.

You specify the language settings in the **Personal menu** $\overset{\frown}{\leftarrow}$. Click the **Profile and settings** link below your user name. On the **Settings** tab, select the **Product language** or **Content language**. Refresh your browser. The new language setting takes effect.

There is also support for bidirectional languages such as Hebrew, Arabic, Urdu, and Farsi. Report authors can control the display of native digits and the direction of text, crosstabs, and charts. For more information about support for bidirectional languages in reporting, see *Support for bidirectional languages* in the *Reporting User Guide*.

For general information about language settings, see the IBM Cognos Analytics Manage Guide.

Setting the default format for report runs

You can set the default run format for your IBM Cognos Analytics reports.

Procedure

- 1. Click the **Personal menu** icon $\stackrel{igorded{eq}}{\rightarrow}$, and then click the **Profile and settings** link below your user name.
- 2. On the Settings tab, for Report format, select one of the available formats.

Credentials

Your credentials are the user name and password that you use to sign in to IBM Cognos Analytics. Your credentials are associated with groups, roles, capabilities, and permissions that determine what parts of the user interface you can access and how you can interact with content.

If you change the password you use to sign in to Cognos Analytics, be sure to renew your credentials. Your saved credentials are used to run scheduled requests when you're not signed in, for example, overnight. Credentials are automatically renewed once a day, but a schedule run can fail, if it runs after you change your password, but before your credentials are automatically renewed.

If you are prompted for credentials when you connect to a data server, you can save your credentials so you aren't prompted for them every time that you use the same data server. Your saved data server credentials are listed in your advanced, personal preferences. You can view and delete listed entries.

To see what groups and roles and what capabilities are available with your sign-in credentials, see "Viewing your permissions for capabilities" on page 17.

Renewing your credentials

Your credentials are renewed automatically once a day or at an interval that is determined by your administrator, but if you change your log-in password, update your credentials manually.

About this task

It is important to manually renew your credentials when you change your sign-in password, if your credentials are used to run schedules.

Procedure

- 1. Click the **Personal menu** icon $\stackrel{\textbf{O}}{\frown}$, then click **Profile and settings**.
- 2. On the **Profile** tab, under **Advanced options**, for **Credentials**, click **Renew**.

Managing your credentials

If you own an entry, you can authorize trusted users to use your credentials when those users lack sufficient access permissions to perform specific tasks. In your personal, advanced preferences, you can view, add to, or delete from the list of groups, users, and roles that are authorized to use your credentials.

About this task

If you want to add groups, users, or roles from multiple namespaces, you can use the type in method described as a choice in step 3.

Procedure

- 1. Click the **Personal menu** icon \aleph , then click **Profile and settings**.
- 2. On the Profile tab, under Advanced options, locate My credentials, and click Manage.

3. To add a group, user or role, click +, then do one of the following actions:

- Select a namespace from the Name list. You can then search by keyword or filter by type to find what you want faster.
- To type the names of entries you want to add, click the **Options** icon ∨ and select **Type in**. Type the names of groups, roles, or users by using the following format, where a semicolon (;) separates each entry:

namespace/group_name;namespace/role_name;namespace/user_name;

Here is an example:

Cognos/Authors;LDAP/scarter;

- 4. Select the names that you want and click **Add**.
- Your selections are now listed in the My credentials slide-out panel.
- 5. Click Apply.

Managing your data server credentials

You can view and delete your saved data server credentials in your personal, advanced preferences.

Procedure

- 1. Click the **Personal menu** icon $\stackrel{\frown}{\leftarrow}$, then click **Profile and settings**.
- 2. On the **Profile** tab, under **Advanced options**, for **Data server credentials**, click **Manage**.

Setting logging levels

In addition to the logging capabilities that exist on the IBM Cognos server, you can produce logs and error reports for your own workstation. This type of client-side logging is important for troubleshooting and can cover JavaScript anomalies that are not detectable from the server environment.

About this task

You can turn logging on or off as well as set the logging level. Under normal circumstances, logging is on, but the level is set to **Error**. In some circumstances, IBM customer support might direct you to increase the logging level. Set it to one of the following levels:

Error

Basic level of logging that tracks only major error messages that occur during processing on the client workstation.

Warning

The next level of logging that includes all the information from the Error level of logging and includes warnings about situations that might not affect your system function.

Information

This level of logging aggregates all previous levels of logging and includes more detail about the regular operation of the user interface. You might notice that performance at this level is slower.

Debug

This level of logging contains the most information. Use it if you are testing your own extensions or when you are advised by a member of the software development team or customer support. You can expect that performance at this level is noticeably slower.

Logging levels are stored in the browser cache. If you clear the browser cache, logging levels return to the default setting.

Procedure

- 2. On the **Profile** tab, under **Advanced options**, for **Logging**, click **Manage**.
- 3. Ensure that logging is on.
- 4. Set the **Logging level** to the level directed by the customer support representative.
- 5. To retrieve logs from the browser console, press the **F12** key on your keyboard or from the browser menu, click **Developer**, and then click **Web Console**.

Tip: For the Firefox web browser, you can use an add-on, such as Firebug to make it easier to retrieve and save log files from the console.

6. After you are done troubleshooting, return to the **Logging** preferences window and ensure that logging is set back to **Error** to prevent logging from slowing down your system while you are working.

What to do next

For more information about troubleshooting your system, see the *IBM Cognos Analytics Troubleshooting Guide*.

Chapter 12. Integrating with other Cognos products

IBM Cognos Analytics integrates with supported versions of other IBM Cognos products so your analytics capabilities can grow with your needs.

To access the following applications, they must be installed, and IBM Cognos Analytics must be installed with the custom option which enables other applications. For information on opening companion applications, see "Opening companion apps" on page 91.

Cognos Planning - Analyst

For supported versions, you can access published plan data in IBM Cognos Analytics by using the Generate Framework Manager Model wizard. For more information, see the *IBM Cognos Analyst User Guide*.

Cognos Planning - Contributor

For supported versions, you can access unpublished (real-time) Contributor cubes in IBM Cognos Analytics by custom installing the IBM Cognos Analytics - Contributor Data Server component that is included with IBM Cognos Planning - Contributor.

For supported versions, you can access published plan data in IBM Cognos Analytics by using the Generate Framework Manager Model administration extension in Contributor. For more information, see the *IBM Cognos Contributor Administration Guide*.

Cognos Finance

You can access IBM Cognos Finance cubes that are secured against a Series 7 namespace by using the IBM Cognos Finance Network API Service. You can also export data and metadata from IBM Cognos Finance for use in Framework Manager.

Cognos Controller

You can access IBM Cognos Analytics to create IBM Cognos Controller Standard Reports by using a predefined Framework Manager model that is created when IBM Cognos Controller is installed. You can also access published Controller data and structures in Framework Manager for custom reporting and analysis.

Cognos Transformer

You can use IBM Cognos PowerCubes and Transformer models, that were generated by supported Transformer versions, directly in IBM Cognos Analytics. The cubes and models are upwards compatible and require no migration or upgrade tools. You can run reports and analyses in IBM Cognos Analytics against the IBM Cognos PowerCubes.

Cognos TM1[®]

IBM Cognos TM1 integrates business planning, performance measurement and operational data to enable companies to optimize business effectiveness and customer interaction regardless of geography or structure. Cognos TM1 provides immediate visibility into data, accountability within a collaborative process, and a consistent view of information, allowing managers to quickly stabilize operational fluctuations and take advantage of new opportunities. For more information, see the *IBM Cognos TM1 User Guide*.

Cognos PowerPlay

You use IBM[®] Cognos[®] PowerPlay[®] Studio to create and view reports that are based on PowerCube data sources. For more information, see the *IBM Cognos PowerPlay Studio User Guide*.

IBM Cognos Software Development Kit

The IBM Cognos Software Development Kit provides a platform-independent automation interface for working with IBM Cognos Analytics services and components.

Developers in your organization can use IBM Cognos Software Development Kit to create custom reports, manage deployment, and integrate security and portal functionality to suit your needs, locale, and existing software infrastructure. The Software Development Kit uses a collection of cross-platform web services, libraries, and programming interfaces.

You can choose to automate only a specific task, or you can program the entire process from modeling through to reporting, scheduling, and distribution.

The Software Development Kit is included in the Cognos Analytics installer package.

For more information, see the IBM Cognos Software Development Kit Developer Guide.

Functionality mapping from Cognos BI to Cognos Analytics

IBM Cognos Analytics is the next version of IBM Cognos Business Intelligence.

г

The following table describes where you can find BI functionality in Cognos Analytics. The companion applications are only available in the user interface if they are installed and if legacy applications are enabled in a custom installation of Cognos Analytics. Some, but not all of the companion applications, are installed separately.

Table 3. BI to Cognos Analytics functionality mapping	
IBM Cognos Business Intelligence	IBM Cognos Analytics
Cognos Connection	Welcome portal
Cognos Viewer	The viewer is not named. Depending on the item you view, there is different functionality in the viewer.
Report Studio	Reporting: to create a new report, in the Welcome portal, click $+$,
	then click Report . For a report entry in a content list, if you click, then click Edit , the report opens in Reporting.
No equivalent, new in Cognos	Data modeling: to create a new data module, in the Welcome portal,
Analytics.	click the New $+$ icon, and then click Data module .
Cognos Administration	Managing: incorporates part of the administration functionality. Access from the Welcome portal. Link to the full Administration console from the Manage panel.
Workspace Advanced	Reporting: incorporates Workspace Advanced functionality. Page preview in Reporting is similar to Page preview in Workspace Advanced.
Drill-through definitions	Companion application: to access Drill-through, in the Welcome
	portal navigation bar, click New +, then Other . Drill-through definitions support Framework Manager packages, but not data modules.
Event Studio	Companion application: to access Event Studio, in the Welcome
	portal navigation bar, click New $+$, then Other.
My Inbox	Notifications: if you select Save to the system for subscriptions and report output versions, you go to Notifications in the Welcome portal, open the notice and click a link to the report version.
	Also, you can access My Inbox from your personal settings.
Analysis Studio	Companion application: to access, in the Welcome portal, click New +, then Other .
Query Studio	Companion application: to access, in the Welcome portal, click New
	+, then Other .

Table 3. BI to Cognos Analytics functionality mapping (continued)	
IBM Cognos Business Intelligence	IBM Cognos Analytics
Workspace	Dashboarding: incorporates Workspace functionality. However, for some additional functionality, you can access the Workspace companion application if it was installed. In the Welcome portal navigation bar, click New +, then Other .
Framework Manager	Framework Manager

Move from quirks to standards mode HTML

Because of the move from quirks to standards mode HTML in much of the user interface, you might need to make minor changes to existing reports. You might also need to update your web browser settings.

Many IBM Cognos Analytics user interfaces now use standards mode HTML, including the Cognos Analytics portal, Cognos Analytics – Reporting, and HTML viewers and reports. Because reports have moved from quirks to standard HTML, there might be small differences in the look of your reports. These differences do not have an impact on the majority of reports that were created in previous Cognos versions. However, minor changes might be required in a small number of existing reports.

If you use the Microsoft Internet Explorer web browser after you upgrade to Cognos Analytics, you might need to change your browser settings. Previously, when Cognos 10.2.x was used with the Internet Explorer browser, you either had to enable the **Automatically recover from page layout errors with Compatibility Mode** option or add websites to the **Compatibility View Settings**. Because Cognos Analytics uses standards mode HTML, you must change settings that enabled compatibility mode to avoid problems with caching. To ease your transition to standards mode HTML, legacy components, such as IBM Cognos Query Studio and IBM Cognos Analysis Studio that still require it now use meta tags to automatically switch into compatibility mode.

For more information, see Cognos Analytics conversion to Standards Mode.

Opening companion apps

Companion applications might be accessible in the IBM Cognos Analytics user interface.

About this task

You can access the following applications if you have the required capabilities and if the applications are enabled during installation:

- Cognos Analysis Studio
- Cognos Query Studio
- Cognos Event Studio
- Cognos Workspace
- Drill-through definitions
- My Inbox
- My Watch Items
- Create new jobs

The following applications are separately installed. To see them, the custom installation option must be selected when IBM Cognos Analytics is installed, and you must have the appropriate capabilities:

- IBM Cognos PowerPlay
- IBM Cognos Planning

Procedure

- 1. To see My Inbox and My Watch Items, in the **Welcome** portal, click your **Personal menu** $\stackrel{\sf O}{\rightarrow}$.
- 2. To see all other companion applications, in the **Welcome** portal navigation bar, click +, then **Other**.
- 3. Click the companion application that you want.

Index

A

agent views <u>32</u> Analysis Studio <u>91</u> appending data uploaded files <u>27</u> assets copy <u>60</u> paste 60

С

CADataConnector <u>39</u>, <u>42</u>, <u>43</u> capabilities viewing permissions <u>17</u> copy or move effect on links <u>59</u> copy paste <u>60</u> credentials renewing <u>87</u> Credentialsauthorize trusted users managing <u>87</u>

D

data modules <u>19</u> Data server credentialsmanage view saved credentials <u>87</u> data sets creating <u>20</u> data sources <u>19</u>

E

entries hiding <u>78</u> setting permissions <u>16</u> execute permissions 15

F

file ID <u>39</u> files uploading 25, 27

G

get started overview 7

Н

hiding entries 78

Ι

IBM Cognos Software Development Kit <u>89</u> integrating other IBM Cognos products IBM Cognos Analytics <u>89</u> interactive viewer <u>31</u>

L

learn the product <u>14</u> links copy or move operations 59

Μ

Manage data server credentials <u>87</u> managing reports <u>31</u> My content <u>31</u>

Ν

notebook actions for <u>38</u> creating <u>38</u> examples <u>46</u>, <u>49</u> Jupyter <u>55</u> reading data in <u>39</u> searching for data in <u>43</u> uploading <u>55</u> writing data to <u>42</u> notifications <u>85</u>

0

organizing entries in the portal 31

Ρ

packages 19 permissions execute 15 read 15 set 16 set policy 15 traverse 15 types 16 viewing 17 write 15 personal settings preferences 86 preferences viewing my capabilities 17 product description 7 properties

properties (continued) setting for Team content 78

Q

Query Studio <u>91</u> quick launch uploading files <u>13</u>

R

read permissions 15 read_data() method 39 replacing data uploaded files 27 report versions delete saved output 32 save versions 32 saved outputs 32 view archives 32 view versions 32 report views 32 report s managing 31 personalize 32 scheduling 79

S

samples 14, 37 schedules 85 scheduling reports 79 search_data() method 43 security groups and roles 17 permissions 15 set default report format 86 set policy permissions 15 shortcuts creating 77 sources data modules 19 data sets 20 packages 19 uploaded files 25 subscribe to reports 33 subscriptions 33, 85

T

Team content setting properties <u>78</u> traverse permissions <u>15</u>

U

uploaded files appending data <u>27</u> notebooks <u>55</u> quick launch <u>13</u> replacing data <u>27</u> uploading files $\underline{27}$

V

visualizations copy <u>60</u> paste <u>60</u>

W

Workspace <u>91</u> write permissions <u>15</u> write_data() method <u>42</u>

