Db2 12 for z/OS

Managing Security Last updated: 2024-09-06



Notes

Before using this information and the product it supports, be sure to read the general information under "Notices" at the end of this information.

Subsequent editions of this PDF will not be delivered in IBM Publications Center. Always download the latest edition from IBM Documentation.

2024-09-06 edition

This edition applies to Db2 12 for z/OS (product number 5650-DB2), Db2 12 for z/OS Value Unit Edition (product number 5770-AF3), and to any subsequent releases until otherwise indicated in new editions. Make sure you are using the correct edition for the level of the product.

Specific changes are indicated by a vertical bar to the left of a change. A vertical bar to the left of a figure caption indicates that the figure has changed. Editorial changes that have no technical significance are not noted.

[©] Copyright International Business Machines Corporation 1982, 2024.

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Contents

About this information	İX
Who should read this information	x
Db2 Utilities Suite for z/OS	x
Terminology and citations	X
Accessibility features for Db2 for z/OS	xi
How to send comments	xi
How to read syntax diagrams	xii
, .	
Chapter 1. Getting started with Db2 security	1
Db2 security solutions	
Db2 data access control	
ID-based access control within Db2	
Role-based access control within Db2	
Ownership-based access control within Db2	
Access control through multilevel security	4
Access control external to Db2	
Db2 subsystem access control	
Managing access requests from local applications	5
Managing access requests from remote applications	5
Data set protection	6
Scenario: Securing data access with Db2 facilities at Spiffy Computer	6
Determining security objectives	7
Securing manager access to employee data	7
Securing access to payroll operations and management	
Managing access privileges of other authorities	
Chapter 2. Managing access through authorization IDs and roles	
Chapter 2. Managing access through authorization IDs and roles Authorization IDs and roles	19
Chapter 2. Managing access through authorization IDs and roles Authorization IDs and roles Authorization IDs	19
Chapter 2. Managing access through authorization IDs and roles Authorization IDs and roles Authorization IDs Roles in a trusted context.	19 20
Chapter 2. Managing access through authorization IDs and roles Authorization IDs and roles Authorization IDs Roles in a trusted context Privileges and authorities.	19 20 20 20 21 22
Chapter 2. Managing access through authorization IDs and roles Authorization IDs and roles Authorization IDs Roles in a trusted context Privileges and authorities Explicit privileges	19 20 20 21 22 22
Chapter 2. Managing access through authorization IDs and roles Authorization IDs and roles Authorization IDs Roles in a trusted context Privileges and authorities Explicit privileges Implicit privileges through object ownership	19 20 20 21 22 22 22 28
Chapter 2. Managing access through authorization IDs and roles Authorization IDs and roles Authorization IDs Roles in a trusted context Privileges and authorities Explicit privileges Implicit privileges through object ownership Administrative authorities in Db2 for z/OS.	19 20 20 21 22 22 22 28 30
Chapter 2. Managing access through authorization IDs and roles Authorization IDs and roles Authorization IDs Roles in a trusted context Privileges and authorities Explicit privileges Implicit privileges through object ownership Administrative authorities in Db2 for z/OS Common administrative authorities for the Db2 product family	19 20 20 21 22 22 22 28 30 51
Chapter 2. Managing access through authorization IDs and roles Authorization IDs and roles Authorization IDs Roles in a trusted context Privileges and authorities Explicit privileges Implicit privileges through object ownership Administrative authorities in Db2 for z/OS Common administrative authorities for the Db2 product family Utility authorities for Db2 catalog and directory	19 20 20 20 21 22 22 22 22 28 30 51 53
Chapter 2. Managing access through authorization IDs and roles Authorization IDs and roles Authorization IDs Roles in a trusted context Privileges and authorities Explicit privileges Implicit privileges through object ownership Administrative authorities in Db2 for z/OS. Common administrative authorities for the Db2 product family Utility authorities for Db2 catalog and directory Privileges by authorization ID and authority	19 20 20 20 21 22 22 22 22 28 30 51 53 54
Chapter 2. Managing access through authorization IDs and roles Authorization IDs and roles Authorization IDs Roles in a trusted context Privileges and authorities Explicit privileges Implicit privileges through object ownership Administrative authorities in Db2 for z/OS Common administrative authorities for the Db2 product family Utility authorities for Db2 catalog and directory Privileges by authorization ID and authority Managing administrative authorities.	19 20 20 21 22 22 22 28 30 51 53 54 63
Chapter 2. Managing access through authorization IDs and roles Authorization IDs and roles Authorization IDs Roles in a trusted context Privileges and authorities Explicit privileges Implicit privileges through object ownership Administrative authorities in Db2 for z/OS. Common administrative authorities for the Db2 product family Utility authorities for Db2 catalog and directory Privileges by authorization ID and authority Managing administrative authorities Separating the SYSADM authority	19 20 20 21 22 22 22 28 30 51 53 54 63
Chapter 2. Managing access through authorization IDs and roles Authorization IDs and roles Authorization IDs Roles in a trusted context Privileges and authorities Explicit privileges Implicit privileges through object ownership Administrative authorities in Db2 for z/OS Common administrative authorities for the Db2 product family Utility authorities for Db2 catalog and directory Privileges by authorization ID and authority Managing administrative authorities Separating the SYSADM authority	19 20 20 21 22 22 22 22 28 30 51 53 54 63 63 63
Chapter 2. Managing access through authorization IDs and roles Authorization IDs and roles Authorization IDs Roles in a trusted context Privileges and authorities Explicit privileges Implicit privileges through object ownership Administrative authorities in Db2 for z/OS Common administrative authorities for the Db2 product family Utility authorities for Db2 catalog and directory Privileges by authorization ID and authority Managing administrative authorities Separating the SYSADM authority Creating roles or trusted contexts with the SECADM authority	19 20 20 21 22 22 22 22 28 30 51 53 54 63 63 63 63 64 64 64 64 64 64 64 64 64 64 64 64 64
Chapter 2. Managing access through authorization IDs and roles Authorization IDs Roles in a trusted context Privileges and authorities Explicit privileges Implicit privileges through object ownership Administrative authorities in Db2 for z/OS. Common administrative authorities for the Db2 product family Utility authorities for Db2 catalog and directory Privileges by authorization ID and authority. Managing administrative authorities Separating the SYSADM authority. Migrating the SYSADM authority. Altering tables with the system DBADM authority.	19 20 20 20 21 22 22 22 22 22 28 30 51 53 54 63 63 66 69 70 70 70 70 70 70 70 70 70 70 70 70 70
Chapter 2. Managing access through authorization IDs and roles Authorization IDs Roles in a trusted context Privileges and authorities Explicit privileges Implicit privileges through object ownership Administrative authorities in Db2 for z/OS. Common administrative authorities for the Db2 product family Utility authorities for Db2 catalog and directory. Privileges by authorization ID and authority Managing administrative authorities Separating the SYSADM authority Migrating the SYSADM authority Altering roles or trusted contexts with the SECADM authority Altering tables with the pATAACCESS authority.	19 20 20 21 22 22 22 22 28 30 51 53 54 63 63 66 69 70 70 70 70
Chapter 2. Managing access through authorization IDs and roles. Authorization IDs. Roles in a trusted context. Privileges and authorities. Explicit privileges. Implicit privileges through object ownership. Administrative authorities in Db2 for z/OS. Common administrative authorities for the Db2 product family. Utility authorities for Db2 catalog and directory. Privileges by authorization ID and authority. Managing administrative authorities. Separating the SYSADM authority. Migrating the SYSADM authority. Attering tables with the system DBADM authority. Accessing data with the DATAACCESS authority. Granting and revoking privileges with the ACCESSCTRL authority.	19 20 20 20 21 22 22 22 22 28 30 51 53 54 63 63 66 69 70 70 70 71
Chapter 2. Managing access through authorization IDs and roles Authorization IDs and roles Authorization IDs Roles in a trusted context Privileges and authorities Explicit privileges Implicit privileges through object ownership Administrative authorities in Db2 for z/OS Common administrative authorities for the Db2 product family Utility authorities for Db2 catalog and directory Privileges by authorization ID and authority Managing administrative authorities Separating the SYSADM authority Migrating the SYSADM authority Altering roles or trusted contexts with the SECADM authority Altering tables with the system DBADM authority Granting and revoking privileges with the ACCESSCTRL authority Managing explicit privileges	19 20 20 21 22 22 22 28 30 51 53 54 63 63 66 69 70 70 71 72
Chapter 2. Managing access through authorization IDs and roles Authorization IDs and roles Authorization IDs Roles in a trusted context. Privileges and authorities Explicit privileges. Implicit privileges through object ownership Administrative authorities in Db2 for z/OS Common administrative authorities for the Db2 product family Utility authorities for Db2 catalog and directory Privileges by authorization ID and authority Managing administrative authorities Separating the SYSADM authority Migrating the SYSADM authority Altering tables with the system DBADM authority Accessing data with the DATAACCESS authority Granting and revoking privileges with the ACCESSCTRL authority	19 20 20 21 22 22 22 28 30 51 53 54 63 63 66 69 70 70 70 71 72
Chapter 2. Managing access through authorization IDs and roles Authorization IDs Roles in a trusted context Privileges and authorities Explicit privileges Implicit privileges through object ownership. Administrative authorities in Db2 for z/OS. Common administrative authorities for the Db2 product family Utility authorities for Db2 catalog and directory. Privileges by authorization ID and authority Managing administrative authorities Separating the SYSADM authority. Migrating the SYSADM authority. Altering tables with the system DBADM authority. Accessing data with the DATAACCESS authority. Managing explicit privileges Granting privileges to a role Granting privileges to the PUBLIC ID.	19 20 20 21 22 22 22 28 30 51 53 54 63 63 63 64 67 70 71 72 73 73
Chapter 2. Managing access through authorization IDs and roles Authorization IDs Roles in a trusted context Privileges and authorities Explicit privileges. Implicit privileges through object ownership. Administrative authorities in Db2 for z/OS. Common administrative authorities for the Db2 product family Utility authorities for Db2 catalog and directory Privileges by authorization ID and authority. Managing administrative authorities Separating the SYSADM authority. Migrating the SYSADM authority. Creating roles or trusted contexts with the SECADM authority. Altering tables with the system DBADM authority. Accessing data with the DATAACCESS authority. Granting and revoking privileges with the ACCESSCTRL authority. Managing explicit privileges Granting privileges to a role. Granting privileges to remote users.	19 20 20 21 22 22 22 22 22 23 30 51 53 54 63 63 63 64 67 70 71 72 73 73
Chapter 2. Managing access through authorization IDs and roles Authorization IDs and roles Authorization IDs Roles in a trusted context Privileges and authorities. Explicit privileges Implicit privileges through object ownership Administrative authorities in Db2 for z/OS Common administrative authorities for the Db2 product family Utility authorities for Db2 catalog and directory Privileges by authorization ID and authority Managing administrative authorities Separating the SYSADM authority Migrating the SYSADM authority Attering tables with the system DBADM authority Attering tables with the SYSADM authority Granting and revoking privileges with the ACCESSCTRL authority Managing explicit privileges Granting privileges to a role Granting privileges to remote users Granting privileges through views Output the prival of the output of	19 20 20 20 21 22 22 22 22 28 30 51 53 54 63 63 63 63 63 64 69 70 70 70 70 71 72 72 72 72 73 73 73

	75
Revoking privileges with the REVOKE statement	80
Managing implicit privileges through object ownership	89
Ownership of objects with unqualified names	89
Ownership of objects with qualified names	
Ownership of objects within a trusted context	90
Changing object ownership	91
Granting implicit privileges of object ownership	91
Managing implicit privileges through plan or package ownership	
Establishing or changing plan or package ownership	
Establishing plan and package ownership in a trusted context	92
How Db2 resolves unqualified names	
Validating authorization for executing plans or packages	
Caching authorization IDs for better performance	
Authorizing plan or package access through applications	98
Managing privileges for routines	
Privileges required for executing routines	100
Examples of granting privileges for routines	
Authorization behaviors for dynamic SOL statements	
Run behavior	105
Bind behavior	105
Define behavior	
Invoke behavior	
Common attribute values for bind, define, and invoke behaviors	
Determining authorization IDs for dynamic SOL statements in routines	
Simplifying access authorization for routines	
Using composite privileges	
Performing multiple actions in one statement	
Retrieving privilege records in the Db2 catalog	
Catalog tables with privilege records	113
	110
Retrieving all authorization IDs or roles with granted privileges	
Retrieving all authorization IDs or roles with granted privileges Retrieving multiple grants of the same privilege	113 114
Retrieving all authorization IDs or roles with granted privileges Retrieving multiple grants of the same privilege Retrieving all authorization IDs or roles with the DBADM and system DBADM authorities	
Retrieving all authorization IDs or roles with granted privileges Retrieving multiple grants of the same privilege Retrieving all authorization IDs or roles with the DBADM and system DBADM authorities Retrieving all IDs or roles with access to the same table	113 114 115 115
Retrieving all authorization IDs or roles with granted privileges Retrieving multiple grants of the same privilege Retrieving all authorization IDs or roles with the DBADM and system DBADM authorities Retrieving all IDs or roles with access to the same table Retrieving all IDs or roles with access to the same routine	113 114 115 115 116
Retrieving all authorization IDs or roles with granted privileges Retrieving multiple grants of the same privilege Retrieving all authorization IDs or roles with the DBADM and system DBADM authorities Retrieving all IDs or roles with access to the same table Retrieving all IDs or roles with access to the same routine Retrieving plans or packages with access to the same table	
Retrieving all authorization IDs or roles with granted privileges. Retrieving multiple grants of the same privilege. Retrieving all authorization IDs or roles with the DBADM and system DBADM authorities Retrieving all IDs or roles with access to the same table. Retrieving all IDs or roles with access to the same routine. Retrieving plans or packages with access to the same table. Retrieving plans or packages with access to the same table.	113 114 115 115 116 117 117
Retrieving all authorization IDs or roles with granted privileges. Retrieving multiple grants of the same privilege. Retrieving all authorization IDs or roles with the DBADM and system DBADM authorities Retrieving all IDs or roles with access to the same table. Retrieving all IDs or roles with access to the same routine. Retrieving plans or packages with access to the same table. Retrieving plans or packages with access to the same table. Retrieving plans or packages with access to the same table. Retrieving privilege information through views.	113 114 115 115 116 117 117 117
Retrieving all authorization IDs or roles with granted privileges. Retrieving multiple grants of the same privilege. Retrieving all authorization IDs or roles with the DBADM and system DBADM authorities Retrieving all IDs or roles with access to the same table. Retrieving all IDs or roles with access to the same routine. Retrieving plans or packages with access to the same table. Retrieving plans or packages with access to the same table. Retrieving privilege information through views. Implementing multilevel security with Db2. Multilevel security.	113 114 115 115 116 117 117 118 118 118
Retrieving all authorization IDs or roles with granted privileges. Retrieving multiple grants of the same privilege. Retrieving all authorization IDs or roles with the DBADM and system DBADM authorities Retrieving all IDs or roles with access to the same table. Retrieving all IDs or roles with access to the same routine. Retrieving plans or packages with access to the same table. Retrieving plans or packages with access to the same table. Retrieving privilege information through views. Implementing multilevel security with Db2. Multilevel security. Mandatory access checking.	113 114 115 115 116 117 117 118 118 118 123
Retrieving all authorization IDs or roles with granted privileges. Retrieving multiple grants of the same privilege. Retrieving all authorization IDs or roles with the DBADM and system DBADM authorities Retrieving all IDs or roles with access to the same table. Retrieving plans or packages with access to the same routine. Retrieving plans or packages with access to the same table. Retrieving privilege information through views. Implementing multilevel security with Db2. Multilevel security. Mandatory access checking. Implementing multilevel security at the object level.	113 114 115 115 116 117 117 118 118 123 123 125
Retrieving all authorization IDs or roles with granted privileges. Retrieving multiple grants of the same privilege. Retrieving all authorization IDs or roles with the DBADM and system DBADM authorities Retrieving all IDs or roles with access to the same table. Retrieving plans or packages with access to the same routine. Retrieving plans or packages with access to the same table. Retrieving privilege information through views. Implementing multilevel security with Db2. Multilevel security. Mandatory access checking. Implementing multilevel security at the object level. Implementing multilevel security with row-level granularity.	113 114 115 115 116 117 117 117 118 118 123 125 127
Retrieving all authorization IDs or roles with granted privileges. Retrieving multiple grants of the same privilege. Retrieving all authorization IDs or roles with the DBADM and system DBADM authorities Retrieving all IDs or roles with access to the same table. Retrieving plans or packages with access to the same routine. Retrieving privilege information through views. Implementing multilevel security with Db2. Multilevel security. Mandatory access checking. Implementing multilevel security at the object level. Implementing multilevel security with row-level granularity. Restricting access to the security label column.	113 114 115 115 115 116 117 117 117 118 118 123 125 127 129
Retrieving all authorization IDs or roles with granted privileges. Retrieving multiple grants of the same privilege. Retrieving all authorization IDs or roles with the DBADM and system DBADM authorities Retrieving all IDs or roles with access to the same table. Retrieving plans or packages with access to the same table. Retrieving privilege information through views. Implementing multilevel security with Db2. Multilevel security. Mandatory access checking. Implementing multilevel security at the object level. Implementing multilevel security with row-level granularity. Restricting access to the security label column. Managing data in a multilevel-secure environment.	113 113 114 115 115 116 117 117 117 117 118 123 125 127 129 129 130
Retrieving all authorization IDs or roles with granted privileges Retrieving multiple grants of the same privilege Retrieving all authorization IDs or roles with the DBADM and system DBADM authorities Retrieving all IDs or roles with access to the same table Retrieving plans or packages with access to the same routine. Retrieving privilege information through views Implementing multilevel security with Db2 Multilevel security Mandatory access checking Implementing multilevel security at the object level. Implementing multilevel security with row-level granularity Restricting access to the security label column Managing data in a multilevel-secure environment Implementing multilevel security in a distributed environment	113 114 114 115 115 116 117 117 117 117 118 118 123 125 127 129 129 130 137
Retrieving all authorization IDs or roles with granted privileges. Retrieving multiple grants of the same privilege. Retrieving all authorization IDs or roles with the DBADM and system DBADM authorities Retrieving all IDs or roles with access to the same table. Retrieving plans or packages with access to the same table. Retrieving privilege information through views. Implementing multilevel security with Db2. Multilevel security. Mandatory access checking. Implementing multilevel security at the object level. Implementing multilevel security with row-level granularity. Restricting access to the security label column. Managing data in a multilevel-secure environment. Implementing multilevel security in a distributed environment.	113 114 114 115 115 116 117 117 117 117 117 118 123 123 125 127 129 129 130 137
Retrieving all authorization IDs or roles with granted privileges. Retrieving multiple grants of the same privilege. Retrieving all authorization IDs or roles with the DBADM and system DBADM authorities Retrieving all IDs or roles with access to the same table. Retrieving plans or packages with access to the same routine. Retrieving privilege information through views. Implementing multilevel security with Db2. Multilevel security. Mandatory access checking. Implementing multilevel security at the object level. Implementing multilevel security with row-level granularity. Restricting access to the security label column. Managing data in a multilevel-secure environment. Implementing multilevel security in a distributed environment.	113 114 114 115 115 116 117 117 117 117 118 123 125 127 129 129 130 137
Retrieving all authorization IDs or roles with granted privileges. Retrieving multiple grants of the same privilege. Retrieving all authorization IDs or roles with the DBADM and system DBADM authorities Retrieving all IDs or roles with access to the same table. Retrieving plans or packages with access to the same routine. Retrieving privilege information through views. Implementing multilevel security with Db2. Multilevel security. Mandatory access checking. Implementing multilevel security at the object level. Implementing multilevel security with row-level granularity. Restricting access to the security label column. Managing data in a multilevel-secure environment. Implementing multilevel security in a distributed environment. Establishing RACF protection for Db2.	113 114 115 115 116 117 117 117 118 117 118 123 125 127 129 129 129 130 137 139
Retrieving all authorization IDs or roles with granted privileges. Retrieving multiple grants of the same privilege. Retrieving all authorization IDs or roles with the DBADM and system DBADM authorities. Retrieving all IDs or roles with access to the same table. Retrieving plans or packages with access to the same table. Retrieving privilege information through views. Implementing multilevel security with Db2. Multilevel security. Mandatory access checking. Implementing multilevel security at the object level. Implementing multilevel security with row-level granularity. Restricting access to the security label column. Managing data in a multilevel-secure environment. Implementing multilevel security in a distributed environment. Implementing multilevel security in a distributed environment. Defining Db2 resources to RACF.	113 114 114 115 115 116 117 117 117 117 118 123 125 127 129 130 137 139 139
Retrieving all authorization IDs or roles with granted privileges. Retrieving multiple grants of the same privilege. Retrieving all authorization IDs or roles with the DBADM and system DBADM authorities. Retrieving all IDs or roles with access to the same table. Retrieving plans or packages with access to the same routine. Retrieving privilege information through views. Implementing multilevel security with Db2. Multilevel security. Mandatory access checking. Implementing multilevel security at the object level. Implementing multilevel security with row-level granularity. Restricting access to the security label column. Managing data in a multilevel-secure environment. Implementing multilevel security in a distributed environment. Implementing multilevel security in a distributed environment. Permitting RACF protection for Db2. Defining Db2 resources to RACF. Permitting RACF access.	113 114 114 115 115 116 117 117 117 117 117 117 118 123 125 127 129 130 137 137 139 139 139
Retrieving all authorization IDs or roles with granted privileges. Retrieving multiple grants of the same privilege. Retrieving all authorization IDs or roles with the DBADM and system DBADM authorities Retrieving all IDs or roles with access to the same table. Retrieving plans or packages with access to the same table. Retrieving privilege information through views. Implementing multilevel security with Db2. Multilevel security. Mandatory access checking. Implementing multilevel security at the object level. Implementing multilevel security with row-level granularity. Restricting access to the security label column. Managing data in a multilevel-secure environment. Implementing multilevel security in a distributed environment. Implementing RACF protection for Db2. Defining Db2 resources to RACF. Permitting RACF access. Managing authorization for stored procedures.	113 113 114 114 115 115 116 115 117 117 117 117 117 123 125 127 129 130 137 139 139 145 153
Retrieving all authorization LDs or roles with granted privileges Retrieving multiple grants of the same privilege Retrieving all authorization IDs or roles with the DBADM and system DBADM authorities Retrieving all IDs or roles with access to the same table. Retrieving plans or packages with access to the same routine Retrieving privilege information through views. Implementing multilevel security with Db2. Multilevel security Mandatory access checking. Implementing multilevel security at the object level. Implementing multilevel security with row-level granularity. Restricting access to the security label column. Managing data in a multilevel-secure environment. Implementing multilevel security in a distributed environment. Implementing multilevel security in a distributed environment. Implementing RACF protection for Db2. Defining Db2 resources to RACF. Permitting RACF access. Managing authorization for stored procedures. Protecting connection requests that use the TCP/IP protocol.	113 114 114 115 115 116 117 117 117 118 123 125 127 129 130 137 139 139 139 139 139 145 153 162
Retrieving all authorization IDs or roles with granted privileges Retrieving multiple grants of the same privilege Retrieving all authorization IDs or roles with the DBADM and system DBADM authorities Retrieving all IDs or roles with access to the same table. Retrieving plans or packages with access to the same routine. Retrieving privilege information through views Implementing multilevel security with Db2. Multilevel security Mandatory access checking. Implementing multilevel security at the object level. Implementing multilevel security with row-level granularity. Restricting access to the security label column. Managing data in a multilevel-secure environment. Implementing multilevel security in a distributed environment. Implementing multilevel security in a distributed environment. Defining Db2 resources to RACF. Permitting RACF protection for Db2. Defining Db2 resources to RACF. Permitting RACF access. Managing authorization for stored procedures. Protecting connection requests that use the TCP/IP protocol. Establishing Kerberos authentication through RACF.	113 114 114 115 115 116 117 117 117 118 123 125 127 129 130 137 139 139 139 139 139 139 139 145 162
Retrieving all authorization IDs or roles with granted privileges. Retrieving all authorization IDs or roles with the DBADM and system DBADM authorities Retrieving all IDs or roles with access to the same table. Retrieving all IDs or roles with access to the same routine. Retrieving plans or packages with access to the same table. Retrieving privilege information through views. Implementing multilevel security with Db2. Multilevel security Mandatory access checking. Implementing multilevel security at the object level. Implementing multilevel security with row-level granularity. Restricting access to the security label column. Managing data in a multilevel-secure environment. Implementing multilevel security in a distributed environment. Managing Acc protection for Db2. Defining Db2 resources to RACF. Permitting RACF access. Managing authorization for stored procedures. Protecting connection requests that use the TCP/IP protocol. Establishing Kerberos authentication through RACF.	113 114 114 115 115 116 117 117 117 118 123 125 127 129 130 137 139 139 139 139 139 139 139 145 162 164 164
Retrieving all authorization IDs or roles with granted privileges. Retrieving multiple grants of the same privilege. Retrieving all authorization IDs or roles with the DBADM and system DBADM authorities Retrieving all IDs or roles with access to the same table. Retrieving plans or packages with access to the same table. Retrieving privilege information through views. Implementing multilevel security with Db2. Multilevel security. Mandatory access checking. Implementing multilevel security at the object level. Implementing multilevel security with row-level granularity. Restricting access to the security label column. Managing data in a multilevel-secure environment. Implementing multilevel security in a distributed environment. Implementing multilevel security in a distributed environment. Permitting RACF protection for Db2. Defining Db2 resources to RACF. Managing authorization for stored procedures. Managing authorization for stored procedures. Protecting connection requests that use the TCP/IP protocol. Establishing Kerberos authentication through RACF. Implementing Db2 support for enterprise identity mapping. Configuring the z/OS LDAP server.	113 114 114 115 115 116 117 117 117 118 123 123 125 127 129 130 137 139 139 139 139 139 139 145 153 162 164 165 166
Retrieving all authorization IDs or roles with granted privileges. Retrieving all authorization IDs or roles with the DBADM and system DBADM authorities Retrieving all IDs or roles with access to the same table. Retrieving plans or packages with access to the same table. Retrieving privilege information through views. Implementing multilevel security with Db2. Multilevel security. Mandatory access checking. Implementing multilevel security at the object level. Implementing multilevel security with row-level granularity. Restricting access to the security label column. Managing data in a multilevel-secure environment. Implementing multilevel security in a distributed environment. Implementing Db2 resources to RACF. Permitting RACF access. Managing authorization for stored procedures. Protecting connection requests that use the TCP/IP protocol. Establishing Kerberos authentication through RACF.	113 114 114 115 115 116 117 117 117 118 123 125 127 129 130 137 139 139 139 139 139 139 139 139 139

Implementing Db2 support for distributed identity filters.	
Managing connection requests from local applications	
Processing of connection requests	
Using secondary IDs for connection requests	
Processing of sign-on requests	174
Using secondary IDs for sign-on requests	
Using sample connection and sign-on exit routines for CICS transactions	176 I
Managing connection requests from remote applications	177 177
Security mechanisms for DRDA and SNA	
Communications database for the server	180. 180
Enabling change of user passwords	182
Authorization failure code	182
Managing inbound SNA-based connection requests	182
Managing inbound TCP/IP-based connection requests	102 180
Managing dopial-of-service attacks	200
Proventing SOL injection attacks	200
Managing outbound connection requests	200 201 201
Translating outbound LDs	201 210
Fights and the second second second second	212
Senaing passwords of password prirases	
Chapter 4. Managing access through row permissions and column m	lasks221
Row and column access control	
Row permission	
Column masks	223
Rules of row and column access control	224
Creating row permissions	227
Creating column masks	
Modifying column masks to reference UDFs	
Using INSERT on tables with row access control	224
Creating triggers for tables with row and column access control	234
Creating triggers for tables with row and column access control	234
Creating triggers for tables with row and column access control	234 235 237
Creating triggers for tables with row and column access control Chapter 5. Managing access through trusted contexts Trusted contexts	
Creating triggers for tables with row and column access control Chapter 5. Managing access through trusted contexts Trusted contexts Trusted connections	234 235 237 238
Creating triggers for tables with row and column access control Chapter 5. Managing access through trusted contexts Trusted contexts Trusted connections Defining trusted contexts	234 235 237 238 239
Creating triggers for tables with row and column access control Chapter 5. Managing access through trusted contexts Trusted contexts Trusted connections Defining trusted contexts Creating local trusted connections	234 235 237 237 237 238 239 239 240
Creating triggers for tables with row and column access control Chapter 5. Managing access through trusted contexts Trusted contexts Trusted connections Defining trusted contexts Creating local trusted connections Establishing remote trusted connections by Db2 for z/OS requesters	234 235 237 237 237 238 238 239 240 241
Creating triggers for tables with row and column access control Chapter 5. Managing access through trusted contexts Trusted contexts Trusted connections Defining trusted contexts Creating local trusted connections Establishing remote trusted connections by Db2 for z/OS requesters Establishing remote trusted connections to Db2 for z/OS servers	234 235 237 237 238 239 240 241 241 243
Creating triggers for tables with row and column access control Chapter 5. Managing access through trusted contexts Trusted contexts Trusted connections Defining trusted contexts Creating local trusted connections Establishing remote trusted connections by Db2 for z/OS requesters Establishing remote trusted connections to Db2 for z/OS servers Switching users of a trusted connection	234 235 237 237 237 238 239 240 240 243 243
Creating triggers for tables with row and column access control Chapter 5. Managing access through trusted contexts. Trusted contexts Trusted connections Defining trusted contexts Creating local trusted connections. Establishing remote trusted connections by Db2 for z/OS requesters Establishing remote trusted connections to Db2 for z/OS servers Switching users of a trusted connection. Reusing a local trusted connection through the DSN command processor and D	234 235 237 238 239 240 240 241 241 243 244 244 244 244
Creating triggers for tables with row and column access control Chapter 5. Managing access through trusted contexts. Trusted contexts Trusted connections Defining trusted contexts Creating local trusted connections Establishing remote trusted connections by Db2 for z/OS requesters Establishing remote trusted connections to Db2 for z/OS servers Switching users of a trusted connection Reusing a local trusted connection through the DSN command processor and D Reusing a remote trusted connection by Db2 for z/OS requesters	234 235 237 238 239 240 241 241 243 244 0B2I244 244
Creating triggers for tables with row and column access control Chapter 5. Managing access through trusted contexts. Trusted contexts Trusted connections Defining trusted contexts Creating local trusted connections Establishing remote trusted connections by Db2 for z/OS requesters Establishing remote trusted connections to Db2 for z/OS servers Switching users of a trusted connection Reusing a local trusted connection through the DSN command processor and D Reusing a remote trusted connection by Db2 for z/OS requesters Reusing a remote trusted connection through the DSN command processor and D Reusing a remote trusted connection by Db2 for z/OS servers Reusing a remote trusted connection through Db2 for z/OS servers	234 235 237 238 239 240 241 243 243 244 DB2I243 244 244 245 245
Creating triggers for tables with row and column access control Chapter 5. Managing access through trusted contexts. Trusted contexts Trusted connections Defining trusted contexts Creating local trusted connections. Establishing remote trusted connections by Db2 for z/OS requesters Establishing remote trusted connections to Db2 for z/OS servers. Switching users of a trusted connection. Reusing a local trusted connection through the DSN command processor and D Reusing a remote trusted connection by Db2 for z/OS requesters Reusing a remote trusted connection through the DSN command processor and D Reusing a remote trusted connection through the DSN command processor and D Reusing a remote trusted connection through Db2 for z/OS servers. Reusing a local trusted connection through Db2 for z/OS servers. Reusing a local trusted connection through Db2 for z/OS servers. Reusing a local trusted connection through Db2 for z/OS servers. Reusing a local trusted connection through Db2 for z/OS servers. Reusing a local trusted connection through Db2 for z/OS servers. Reusing a local trusted connection through Db2 for z/OS servers. Reusing a local trusted connection through Db2 for z/OS servers. Reusing a local trusted connection through Db2 for z/OS servers. Reusing a local trusted connection through Db2 for z/OS servers. Reusing a local trusted connection through Db2 for z/OS servers. Reusing a local trusted connection through Db2 for z/OS servers. Reusing a local trusted connection through Db2 for z/OS servers. Reusing a local trusted connection through Db2 for z/OS servers. Reusing a local trusted connection through Db2 for z/OS servers. Reusing a local trusted connection through RESAF.	234 235 237 238 239 240 241 243 244 0B2I244 243 244 243 244 245 245 245 245
Creating triggers for tables with row and column access control Chapter 5. Managing access through trusted contexts. Trusted contexts Trusted connections Defining trusted contexts Creating local trusted connections. Establishing remote trusted connections by Db2 for z/OS requesters Establishing remote trusted connections to Db2 for z/OS servers Switching users of a trusted connection. Reusing a local trusted connection through the DSN command processor and D Reusing a remote trusted connection by Db2 for z/OS requesters Reusing a remote trusted connection through the DSN command processor and D Reusing a remote trusted connection through the DSN command processor and D Reusing a remote trusted connection through Db2 for z/OS servers Reusing a local trusted connection through Db2 for z/OS servers Reusing a local trusted connection through RRSAF Reusing a local trusted connection through the SOL CONNECT statement	234 235 237 238 239 240 241 243 244 0B2I244 244 245 245 245 245 246 247
Creating triggers for tables with row and column access control Chapter 5. Managing access through trusted contexts. Trusted contexts Trusted connections Defining trusted contexts Creating local trusted connections by Db2 for z/OS requesters Establishing remote trusted connections to Db2 for z/OS servers Switching users of a trusted connection through the DSN command processor and D Reusing a local trusted connection by Db2 for z/OS requesters Reusing a remote trusted connection through the DSN command processor and D Reusing a remote trusted connection through the DSN command processor and D Reusing a remote trusted connection through the DSN command processor and D Reusing a remote trusted connection through Db2 for z/OS servers Reusing a local trusted connection through Db2 for z/OS servers Reusing a local trusted connection through Db2 for z/OS servers Reusing a local trusted connection through Db2 for z/OS servers Reusing a local trusted connection through the SQL CONNECT statement Defining external security profiles	234 235 237 237 238 239 240 241 243 244 0B2I243 244 245 245 245 245 246 247 247
Creating triggers for tables with row and column access control Chapter 5. Managing access through trusted contexts Trusted contexts Trusted connections Defining trusted contexts Creating local trusted connections Establishing remote trusted connections by Db2 for z/OS requesters Establishing remote trusted connections to Db2 for z/OS servers Switching users of a trusted connection through the DSN command processor and D Reusing a local trusted connection by Db2 for z/OS requesters Reusing a remote trusted connection by Db2 for z/OS requesters Reusing a remote trusted connection through the DSN command processor and D Reusing a remote trusted connection through the DSN command processor and D Reusing a remote trusted connection through the DSN command processor and D Reusing a local trusted connection through the DSN command processor and D Reusing a local trusted connection through the DSN command processor and D Reusing a local trusted connection through Db2 for z/OS servers Reusing a local trusted connection through Db2 for z/OS servers Reusing a local trusted connection through RRSAF Reusing a local trusted connection through the SQL CONNECT statement Defining external security profiles How secondary roles are used during the switching of users of trusted connection	234 235 237 238 239 240 241 241 243 244 0B2I244 245 245 245 245 245 245 245 247 247 247 247
Creating triggers for tables with row and column access control	234 235 237 238 239 240 241 243 244 0B2I243 244 0B2I245 245 246 245 245 246 247 247 s248 249
Creating triggers for tables with row and column access control	234 235 237 238 239 240 241 243 244 243 244 245 244 245 245 245 245 245 245 245
Creating triggers for tables with row and column access control	234 235 237 238 239 240 241 243 244 0B2I244 245 245 245 245 245 245 245 245 247 247 s248 249 249
Creating triggers for tables with row and column access control Chapter 5. Managing access through trusted contexts Trusted connections Defining trusted contexts Creating local trusted connections Establishing remote trusted connections by Db2 for z/OS requesters Establishing remote trusted connections to Db2 for z/OS servers Switching users of a trusted connection through the DSN command processor and D Reusing a local trusted connection by Db2 for z/OS requesters Reusing a remote trusted connection by Db2 for z/OS requesters Reusing a local trusted connection through the DSN command processor and D Reusing a remote trusted connection through Db2 for z/OS servers Reusing a local trusted connection through Db2 for z/OS servers Reusing a local trusted connection through Db2 for z/OS servers Reusing a local trusted connection through RRSAF Reusing a local trusted connection through the SQL CONNECT statement Defining external security profiles How secondary roles are used during the switching of users of trusted connection Enabling users to perform actions on behalf of others Performing tasks on objects for other users	234 235 237 238 239 240 241 243 244 0B2I244 245 245 245 245 245 245 245 245 247 247 247 247 247 247 247 247 247 247
Creating triggers for tables with row and column access control Chapter 5. Managing access through trusted contexts Trusted contexts Trusted connections Defining trusted contexts Creating local trusted connections by Db2 for z/OS requesters Establishing remote trusted connections to Db2 for z/OS servers Switching users of a trusted connection through the DSN command processor and D Reusing a local trusted connection by Db2 for z/OS requesters Reusing a remote trusted connection through the DSN command processor and D Reusing a remote trusted connection through Db2 for z/OS servers Reusing a local trusted connection through Db2 for z/OS servers Reusing a local trusted connection through Db2 for z/OS servers Reusing a local trusted connection through Db2 for z/OS servers Reusing a local trusted connection through Db2 for z/OS servers Reusing a local trusted connection through Db2 for z/OS servers Reusing a local trusted connection through Db2 for z/OS servers Reusing a local trusted connection through RSAF Reusing a local trusted connection through the SQL CONNECT statement Defining external security profiles How secondary roles are used during the switching of users of trusted connections Enabling users to perform actions on behalf of others Performing tasks on objects for other users Chapter 6. Managing access through data definition control	234 235 237 237 238 239 240 241 243 244 0B2I244 245 245 245 245 245 245 245 245 245
Creating triggers for tables with row and column access control	234 235 237 237 238 239 240 241 243 244 0B2I244 245 245 245 245 245 245 245 245 247 247 s248 249 249 249 249
Creating triggers for tables with row and column access control Chapter 5. Managing access through trusted contexts Trusted contexts Trusted connections Defining trusted contexts Creating local trusted connections by Db2 for z/OS requesters Establishing remote trusted connections to Db2 for z/OS servers Switching users of a trusted connection through the DSN command processor and D Reusing a local trusted connection by Db2 for z/OS requesters Reusing a local trusted connection through the DSN command processor and D Reusing a remote trusted connection through Db2 for z/OS servers Reusing a remote trusted connection through Db2 for z/OS servers Reusing a local trusted connection through Db2 for z/OS servers Reusing a local trusted connection through Db2 for z/OS servers Reusing a local trusted connection through Db2 for z/OS servers Reusing a local trusted connection through Db2 for z/OS servers Reusing a local trusted connection through Db2 for z/OS servers Reusing a local trusted connection through the SQL CONNECT statement Defining external security profiles How secondary roles are used during the switching of users of trusted connection: Enabling users to perform actions on behalf of others Performing tasks on objects for other users Chapter 6. Managing access through data definition control Statements controlled by data definition control support Data definition control support Performing tables	234 235 237 238 239 240 241 243 244 0B2I 244 245 245 245 245 245 245 245 245 245
Creating triggers for tables with row and column access control	234 235 237 238 239 240 241 243 243 244 0B2I 244 245 245 245 245 245 245 245 245 245
Creating triggers for tables with row and column access control	234 235 237 238 239 240 241 243 244 0B2I244 245 245 245 245 245 245 245 247 247 s247 s248 249 249 249 249 249 249
Creating triggers for tables with row and column access control. Chapter 5. Managing access through trusted contexts. Trusted contexts. Trusted connections. Defining trusted connections. Establishing remote trusted connections by Db2 for z/OS requesters. Establishing remote trusted connections to Db2 for z/OS servers. Switching users of a trusted connection through the DSN command processor and D Reusing a local trusted connection by Db2 for z/OS requesters. Reusing a local trusted connection through the DSN command processor and D Reusing a remote trusted connection through Db2 for z/OS servers. Reusing a remote trusted connection through Db2 for z/OS servers. Reusing a local trusted connection through Db2 for z/OS servers. Reusing a local trusted connection through Db2 for z/OS servers. Reusing a local trusted connection through the SQL CONNECT statement. Defining external security profiles. How secondary roles are used during the switching of users of trusted connection Enabling users to perform actions on behalf of others. Performing tasks on objects for other users. Chapter 6. Managing access through data definition control. Statements controlled by data definition control support. Data definition control support. Registration tables. Installing data definition control support. Enabling data definition c	234 235 237 238 239 240 241 243 244 0B2I244 245 245 245 245 245 245 247 247 247 247 247 247 247 247 247 247

Controlling data definition by application name with exceptions	256
Controlling data definition by object name	258
Controlling data definition by object name with exceptions	259
Registering object sets	261
Disabling data definition control	262
Managing registration tables and indexes	263
Creating registration tables and indexes	263
Naming registration tables and indexes	264
Dropping registration tables and indexes	265
Creating table spaces for registration tables	265
Adding columns to registration tables	266
Updating registration tables	267
Chapter 7 Managing access through exit routines	260
Chapter 7. Managing access through exit routines	. 209
Connection routines and sign-on routines.	209
Specifying connection and sign-on routines	270
Sample connection and sign-on routines	270
When connection and sign-on routines are taken	271
Exit parameter list for connection and sign-on routines.	272
Authorization ID parameter list for connection and sign-on routines	274
Input values for connection routines	275
Input values for sign-on routines	275
Expected output for connection and sign-on routines	276
Processing in sample connection and sign-on routines	276
Performance considerations for connection and sign-on routines	278
Debugging connection and sign-on routines	278
Session variables in connection and sign-on routines	200
Access control authorization exit routine	200
The default access control authorization routine	202
When access control authorization routing is taken	203
Considerations for the access control authorization routine	203 202
Parameter list for access control authorization routines	203
Expected output for access control authorization routines	301
Debugging access control authorization routines	304
Determining whether the access control authorization routine is active	207
RACF access control module	
Chapter 8. Managing program authorization	309
Chapter 9. Protecting data through encryption and BACE	211
Encrypting your data with z/OS DESMS data sat operyntian	211
Tupes of DP2 data sets that can be operinted by using DESMS data set operintion	210
Types of DB2 data sets that can be encrypted by using DFSMS data set encryption	214
Encrypting log, catalog, and unectory data sets with 2/05 DFSMS data set encryption	3 1 4 21 E
Encrypting and deta gets using a storage group with 7/OS DESMS data set encryption	515 214
Light a construction to operate the data sets associated with a particular	
tabla	217
Changing Db2 data cote from ancruated to unancruated	210
Encrypted ElashCopy image copies copies made with DESMSdss concurrent copy and	
system-level backling	220
System-level backups	201
Encrypting your data with Secure Socket Laver (SSL) support	J∠⊥ 272
AT-TIS configuration	202
SSL authentication levels	227
Configuring SSL authentication levels	324
Configuring the Dh2 server for SSI	323

Configuring the Db2 requester for SSL	
Protecting data sets through RACF	
Adding groups to control Db2 data sets	
Creating generic profiles for data sets	
Authorizing Db2 IDs to use data set profiles	
Enabling Db2 IDs to create data sets	
Encrypting your data through Db2 built-in functions	
Defining columns for data encrypted using the ENCRYPT TDES built-in function	
Defining columns for data encrypted using the ENCRYPT DATAKEY built-in function	
Defining column-level encryption for the ENCRYPT TDES built-in function	
Defining the ENCRYPT TDES function for value-level encryption	
Using predicates for encrypted data	
Optimizing performance of data encrypted with the ENCRYPT_TDES function	
Chapter 10 Auditing access to Dh2	245
Chapter 10. Auditing access to DD2	
Determining active security measures	
DD2 audit trace	
Authorization IDs traced by auditing	
Audit classes	
Audit trace reports	
Audit trace records	350
Limitations of the audit trace	350
Starting the audit trace	
Stopping the audit trace	352
Collecting audit trace records	352
Formatting audit trace records	353
Auditing in a distributed data environment	353
Db2 audit policies	354
Audit category	354
Creating and activating audit policies	
Updating or stopping tamper-proof audit policies	
Auditing the use of an administrative authority	
Auditing tables without specifying the AUDIT clause	
Additional sources of audit information	
Determining ID privileges and authorities	
Auditing specific IDs or roles	
Auditing specific tables	
Preventing audits of tables	
Ensuring data accuracy and integrity	366
Ensuring data presence and uniqueness	
Protecting data integrity	367
Tracking data changes	368
Checking for lost and incomplete transactions	360
Ensuring data consistency	360
Lisuing data consistency.	
Using leaks for data consistency.	
Osilig locks for uala consistency.	
Information resources for Db2 for z/OS and related products	375
Nations	200
Programming Interface Information	
Irademarks	
Ierms and conditions for product documentation	
Privacy policy considerations	
Glossarv	
•	

I

ndex	3

About this information

This information provides guidance that you can use to manage security in a DB2[®] for z/OS[®] environment.

Throughout this information, "Db2" means "Db2 12 for z/OS". References to other Db2 products use complete names or specific abbreviations.

Important: To find the most up to date content for Db2 12 for z/OS, always use <u>IBM Documentation</u> or download the latest PDF file from <u>PDF format manuals for Db2 12 for z/OS (Db2 for z/OS in IBM</u> Documentation).

Most documentation topics for Db2 12 for z/OS assume that the highest available function level is activated and that your applications are running with the highest available application compatibility level, with the following exceptions:

- The following documentation sections describe the Db2 12 migration process and how to activate new capabilities in function levels:
 - Migrating to Db2 12 (Db2 Installation and Migration)
 - What's new in Db2 12 (Db2 for z/OS What's New?)
 - Adopting new capabilities in Db2 12 continuous delivery (Db2 for z/OS What's New?)
- <u>FL 501</u> A label like this one usually marks documentation changed for function level 500 or higher, with a link to the description of the function level that introduces the change in Db2 12. For more information, see <u>How Db2</u> function levels are documented (Db2 for z/OS What's New?).

The availability of new function depends on the type of enhancement, the activated function level, and the application compatibility levels of applications. In the initial Db2 12 release, most new capabilities are enabled only after the activation of function level 500 or higher.

Virtual storage enhancements

Virtual storage enhancements become available at the activation of the function level that introduces them or higher. Activation of function level 100 introduces all virtual storage enhancements in the initial Db2 12 release. That is, activation of function level 500 introduces no virtual storage enhancements.

Subsystem parameters

New subsystem parameter settings are in effect only when the function level that introduced them or a higher function level is activated. Many subsystem parameter changes in the initial Db2 12 release take effect in function level 500. For more information about subsystem parameter changes in Db2 12, see Subsystem parameter changes in Db2 12 (Db2 for z/OS What's New?).

Optimization enhancements

Optimization enhancements become available after the activation of the function level that introduces them or higher, and full prepare of the SQL statements. When a full prepare occurs depends on the statement type:

- · For static SQL statements, after bind or rebind of the package
- For non-stabilized dynamic SQL statements, immediately, unless the statement is in the dynamic statement cache
- For stabilized dynamic SQL statements, after invalidation, free, or changed application compatibility level

Activation of function level 100 introduces all optimization enhancements in the initial Db2 12 release. That is, function level 500 introduces no optimization enhancements.

SQL capabilities

New SQL capabilities become available after the activation of the function level that introduces them or higher, for applications that run at the equivalent application compatibility level or higher. New SQL capabilities in the initial Db2 12 release become available in function level 500 for applications that run at the equivalent application compatibility level or higher. You can continue to run SQL statements

compatibly with lower function levels, or previous Db2 releases, including Db2 11 and DB2 10. For details, see Application compatibility levels in Db2 12 (Db2 Application programming and SQL)

Who should read this information

This information is primarily intended for security, system, and database administrators. It assumes that the user is familiar with the basic concepts and facilities of Db2 for z/OS (Db2), z/OS, RACF[®], and Structured Query Language (SQL).

Db2 Utilities Suite for z/OS

Important: Db2 Utilities Suite for z/OS is available as an optional product. You must separately order and purchase a license to such utilities, and discussion of those utility functions in this publication is not intended to otherwise imply that you have a license to them.

Db2 12 utilities can use the DFSORT program regardless of whether you purchased a license for DFSORT on your system. For more information about DFSORT, see https://www.ibm.com/support/pages/dfsort.

Db2 utilities can use IBM[®] Db2 Sort for z/OS as an alternative to DFSORT for utility SORT and MERGE functions. Use of Db2 Sort for z/OS requires the purchase of a Db2 Sort for z/OS license. For more information about Db2 Sort for z/OS, see Db2 Sort for z/OS documentation.

Related concepts

Db2 utilities packaging (Db2 Utilities)

Terminology and citations

When referring to a Db2 product other than Db2 for z/OS, this information uses the product's full name to avoid ambiguity.

The following terms are used as indicated:

Db2

Represents either the Db2 licensed program or a particular Db2 subsystem.

IBM rebranded DB2 to Db2, and Db2 for z/OS is the new name of the offering that was previously known as "DB2 for z/OS". For more information, see <u>Revised naming for IBM Db2 family products on IBM z/OS platform</u>. As a result, you might sometimes still see references to the original names, such as "DB2 for z/OS" and "DB2", in different IBM web pages and documents. If the PID, Entitlement Entity, version, modification, and release information match, assume that they refer to the same product.

IBM OMEGAMON for Db2 Performance Expert on z/OS

Refers to any of the following products:

- IBM IBM OMEGAMON for Db2 Performance Expert on z/OS
- IBM Db2 Performance Monitor on z/OS
- IBM Db2 Performance Expert for Multiplatforms and Workgroups
- IBM Db2 Buffer Pool Analyzer for z/OS

C, C++, and C language

Represent the C or C++ programming language.

CICS®

Represents CICS Transaction Server for z/OS.

IMS

Represents the IMS Database Manager or IMS Transaction Manager.

MVS™

Represents the MVS element of the z/OS operating system, which is equivalent to the Base Control Program (BCP) component of the z/OS operating system.

RACF

Represents the functions that are provided by the RACF component of the z/OS Security Server.

Accessibility features for Db2 for z/OS

Accessibility features help a user who has a physical disability, such as restricted mobility or limited vision, to use information technology products successfully.

Accessibility features

The following list includes the major accessibility features in z/OS products, including Db2 for z/OS. These features support:

- Keyboard-only operation.
- Interfaces that are commonly used by screen readers and screen magnifiers.
- Customization of display attributes such as color, contrast, and font size

Tip: <u>IBM Documentation</u> (which includes information for Db2 for z/OS) and its related publications are accessibility-enabled for the IBM Home Page Reader. You can operate all features using the keyboard instead of the mouse.

Keyboard navigation

For information about navigating the Db2 for z/OS ISPF panels using TSO/E or ISPF, refer to the z/OS TSO/E Primer, the z/OS TSO/E User's Guide, and the z/OS ISPF User's Guide. These guides describe how to navigate each interface, including the use of keyboard shortcuts or function keys (PF keys). Each guide includes the default settings for the PF keys and explains how to modify their functions.

Related accessibility information

IBM and accessibility

See the *IBM Accessibility Center* at <u>http://www.ibm.com/able</u> for more information about the commitment that IBM has to accessibility.

How to send your comments about Db2 for z/OS documentation

Your feedback helps IBM to provide quality documentation.

Send any comments about Db2 for z/OS and related product documentation by email to db2zinfo@us.ibm.com.

To help us respond to your comment, include the following information in your email:

- The product name and version
- The address (URL) of the page, for comments about online documentation
- The book name and publication date, for comments about PDF manuals
- The topic or section title
- · The specific text that you are commenting about and your comment

Related concepts

About Db2 12 for z/OS product documentation (Db2 for z/OS in IBM Documentation)

Related reference

PDF format manuals for Db2 12 for z/OS (Db2 for z/OS in IBM Documentation)

How to read syntax diagrams

Certain conventions apply to the syntax diagrams that are used in IBM documentation.

Apply the following rules when reading the syntax diagrams that are used in Db2 for z/OS documentation:

- Read the syntax diagrams from left to right, from top to bottom, following the path of the line.
 - The ► ► symbol indicates the beginning of a statement.
 - The —— symbol indicates that the statement syntax is continued on the next line.
 - The \blacktriangleright —— symbol indicates that a statement is continued from the previous line.
 - The —— < symbol indicates the end of a statement.
- Required items appear on the horizontal line (the main path).
 - ▶ required_item →
- Optional items appear below the main path.
- ➡ required_item ·

– optional_item —

If an optional item appears above the main path, that item has no effect on the execution of the statement and is used only for readability.

• If you can choose from two or more items, they appear vertically, in a stack.

If you *must* choose one of the items, one item of the stack appears on the main path.

▶ required_item _____ required_choice1 _____
required_choice2 _____

If choosing one of the items is optional, the entire stack appears below the main path.

If one of the items is the default, it appears above the main path and the remaining choices are shown below.



• An arrow returning to the left, above the main line, indicates an item that can be repeated.



If the repeat arrow contains a comma, you must separate repeated items with a comma.



A repeat arrow above a stack indicates that you can repeat the items in the stack.

• Sometimes a diagram must be split into fragments. The syntax fragment is shown separately from the main syntax diagram, but the contents of the fragment should be read as if they are on the main path of the diagram.



fragment-name

required item		
requirea_item		
	ontional name	J
	— — optional name —	/

- For some references in syntax diagrams, you must follow any rules described in the description for that diagram, and also rules that are described in other syntax diagrams. For example:
 - For *expression*, you must also follow the rules described in Expressions (Db2 SQL).
 - For references to *fullselect*, you must also follow the rules described in fullselect (Db2 SQL).
 - For references to *search-condition*, you must also follow the rules described in <u>Search conditions</u> (Db2 SQL).
- With the exception of XPath keywords, keywords appear in uppercase (for example, FROM). Keywords must be spelled exactly as shown.
- XPath keywords are defined as lowercase names, and must be spelled exactly as shown.
- Variables appear in all lowercase letters (for example, *column-name*). They represent user-supplied names or values.
- If punctuation marks, parentheses, arithmetic operators, or other such symbols are shown, you must enter them as part of the syntax.

Related concepts

Commands in Db2 (Db2 Commands) Db2 online utilities (Db2 Utilities) Db2 stand-alone utilities (Db2 Utilities)

xiv Db2 12 for z/OS: Managing Security (Last updated: 2024-09-06)

Chapter 1. Getting started with Db2 security

Db2 *security* refers to the protection of sensitive data and system resources by controlling access to Db2 objects, subsystems, and other assets.

Db2 security is set through a security plan, implemented through privilege and authority management, and reinforced through the audit of accesses to protected data. A *security plan* defines the security objectives of your organization and specifies the policies and techniques that you use to meet these objectives. A *security audit* traces all data access and determines whether your security plan works as designed and implemented.

If you are new to Db2 security, skim through the succeeding topics for a brief overview of the techniques that you can use to manage access to your Db2 and protect your data before reading the scenario.

Related concepts Introduction to the RACF access control module (RACF Access Control Module Guide) **Related information** Db2 for z/OS considerations for GDPR readiness (Db2 for z/OS in IBM Documentation)

Db2 security solutions

With each new release, Db2 gets faster and more secure.

Over the years, Db2 recognizes and addresses the following security problems:

- Privilege theft or mismanagement
- · Application or application server tampering
- Data or log tampering
- Storage media theft
- · Unauthorized access to objects

Db2 offers the following security solutions to address the problems:

- Authentication
- Authorization
- Data integrity
- Confidentiality
- System integrity
- Audit

Db2 data access control

Access to data can originate from users through interactive terminal sessions, local or remote stored procedures, utilities, or IMS or CICS transactions. It can also originate from application programs that run in batch mode, remote applications that use DDF or CLI and JDBC drivers, or web-based applications supported by WebSphere[®] Application Servers.

Given the variety of access originators, the term *process* is used to represent all access to data. For example, within a Db2 subsystem, a process can be a primary authorization ID, one or more secondary IDs, a role, or an SQL ID.

A process can gain access to Db2 data through several routines. As shown in the following diagram, Db2 provides different ways for you to control access from all but the data set protection route.



Figure 1. Db2 data access control

One of the ways that Db2 controls access to data is by using authorization IDs or roles. Db2 relies on IDs or roles to determine whether to allow or prohibit certain processes. Db2 assigns privileges and authorities to IDs or roles so that the owning users can take actions on objects. In this sense, it is an ID or a role, not a user, that owns an object. In other words, Db2 does not base access control on a specific user or person who need access. For example, if you allow other users to use your IDs, Db2 recognizes only the IDs, not the people or programs that use them.

Related concepts

Db2 subsystem access control

You can control whether a process can gain access to a specific Db2 subsystem from outside of Db2. A common approach is to grant access through RACF or a similar security system.

ID-based access control within Db2

Db2 provides a wide range of granularity when you grant privileges to an ID within Db2. You can grant privileges and authorities to groups, secondary IDs, or to roles.

For example, you could, separately and specifically, grant to an ID the privilege to retrieve data from the table, to insert rows, to delete rows, or to update specific columns. By granting or not granting privileges on views of the table, you can specify exactly what an ID can do to the table, down to the granularity of specific fields. You can also grant to an ID specific privileges on databases, plans, packages, and the entire Db2 subsystem. If you grant or revoke privileges on a procedure or procedure package, all versions of that procedure or procedure package have those privileges.

Db2 also defines sets of related privileges, called *administrative authorities*. When you grant one of the administrative authorities to a person's ID, that person has all of the privileges that are associated with that administrative authority. You can efficiently grant many privileges by granting one administrative authority.

You can also efficiently grant multiple privileges by granting the privilege to execute an application plan or a package. When an ID executes a plan or package, the ID implicitly uses all of the privileges that the owner needed when binding the plan or package. Therefore, granting to an ID the privilege to execute a plan or package can provide a finely detailed set of privileges and can eliminate the need to grant other privileges separately.

Example: Assume that an application plan issues the INSERT and SELECT statements on several tables. You need to grant INSERT and SELECT privileges only to the plan owner. However, any authorization ID that is later granted the EXECUTE privilege on the plan can perform those same INSERT and SELECT statements by executing the plan. You do not need to explicitly grant the INSERT and SELECT privileges to the ID. **Recommendation:** Instead of granting privileges to many primary authorization IDs, consider associating each of those primary IDs with the same secondary ID or a role if running in a trusted context. Then grant the privileges to the secondary ID or role. You can associate a primary ID with one or more secondary IDs or roles when the primary ID gains access to the Db2 subsystem. Db2 makes the association within an exit routine. The assignment of privileges to the secondary ID or role is controlled entirely within Db2.

Related concepts

Role-based access control within Db2

A *privilege* enables the user of an ID to execute certain SQL statements or to access the objects of another user. A *role* groups the privileges together so that they can be simultaneously granted to and revoked from multiple users.

Ownership-based access control within Db2

Object ownership carries with it a set of related privileges on the object. Db2 provides separate controls for creation and ownership of objects.

Role-based access control within Db2

A *privilege* enables the user of an ID to execute certain SQL statements or to access the objects of another user. A *role* groups the privileges together so that they can be simultaneously granted to and revoked from multiple users.

A role is a database object that is created in Db2. It is defined through the SQL CREATE ROLE statement and a trusted connection. A role cannot be used outside of a trusted context unless the user in a role grants privileges to an ID.

Related concepts

ID-based access control within Db2

Db2 provides a wide range of granularity when you grant privileges to an ID within Db2. You can grant privileges and authorities to groups, secondary IDs, or to roles.

Ownership-based access control within Db2

Object ownership carries with it a set of related privileges on the object. Db2 provides separate controls for creation and ownership of objects.

Ownership-based access control within Db2

Object ownership carries with it a set of related privileges on the object. Db2 provides separate controls for creation and ownership of objects.

If you want to prevent users from obtaining implicit privileges from object ownership, you can make a Db2 role the owner of the object. To do this, you need to create the object in a trusted context that is defined with the ROLE AS OBJECT OWNER AND QUALIFIER clause.

Related concepts

ID-based access control within Db2

Db2 provides a wide range of granularity when you grant privileges to an ID within Db2. You can grant privileges and authorities to groups, secondary IDs, or to roles.

Role-based access control within Db2

A *privilege* enables the user of an ID to execute certain SQL statements or to access the objects of another user. A *role* groups the privileges together so that they can be simultaneously granted to and revoked from multiple users.

Related tasks

Changing object ownership

You can make a Db2 role, a primary authorization ID, or a secondary authorization ID the owner of an object. You can change the ownership from one user to another or from an authorization ID to a role.

Access control through multilevel security

Multilevel security, also known as label-based access control, allows you to classify objects and users with security labels. The security labels are based on hierarchical security levels and non-hierarchical security categories.

Db2 multilevel security solution uses the multilevel security feature in the z/OS operating system. It prevents unauthorized users from accessing information at a higher classification than their authorization. It also prevents users from declassifying information.

Using multilevel security with row-level granularity, you can define strong security for Db2 objects and perform security checks, including row-level security checks. Row-level security checks allow you to control which users have authorization to view, modify, or perform other actions on specific rows of data.

Related reference

Implementing multilevel security with Db2

Multilevel security allows you to classify objects and users with security labels that are based on hierarchical security levels and non-hierarchical security categories. Multilevel security prevents unauthorized users from accessing information at a higher classification than their authorization. It also prevents users from declassifying information.

Access control external to Db2

You can control access to Db2 by using a Db2-supplied exit routine or an exit routine that you write.

If your installation uses one of the access control authorization exit routines, you can use it to control authorization and authentication checking, instead of using other techniques and methods.

Related concepts

Access control authorization exit routine

You can provide your own access control authorization exit routine by using an exit point that Db2 provides. Alternatively, after you carefully consider several important factors, you might choose to let RACF perform Db2 authorization checking for you.

Db2 subsystem access control

You can control whether a process can gain access to a specific Db2 subsystem from outside of Db2. A common approach is to grant access through RACF or a similar security system.

A RACF system provides several advantages. For example, you can use RACF for the following objectives:

- · Identify and verify the identifier that is associated with a process
- · Connect those identifiers to RACF group names
- · Log and report unauthorized attempts to access protected resources

Profiles for access to Db2 from various environments and Db2 address spaces are defined as resources to RACF. Each request to access Db2 is associated with an ID. RACF determines whether the ID is authorized for Db2 resources. If the ID is authorized, RACF permits access to Db2.

You can also consider using the security capabilities of IMS or CICS to manage access to Db2:

• *IMS terminal security* lets you limit the entry of a transaction code to a particular logical terminal (LTERM) or group of LTERMs in the system. To protect a particular program, you can authorize a transaction code that is to be entered only from any terminal on a list of LTERMs. Alternatively, you can associate each LTERM with a list of the transaction codes that a user can enter from that LTERM. IMS then passes the validated LTERM name to Db2 as the initial primary authorization ID

• *CICS transaction code security* works with RACF to control the transactions and programs that can access Db2. Within Db2, you can use the ENABLE and DISABLE options of the bind operation to limit access to specific CICS subsystems.

Related concepts

Db2 data access control

Access to data can originate from users through interactive terminal sessions, local or remote stored procedures, utilities, or IMS or CICS transactions. It can also originate from application programs that run in batch mode, remote applications that use DDF or CLI and JDBC drivers, or web-based applications supported by WebSphere[®] Application Servers.

Managing access requests from local applications

If you request access to a local Db2 subsystem, your request is often subject to several checks before you are granted access.

If you run Db2 under TSO and use the TSO logon ID as the Db2 primary authorization ID, TSO verifies your ID when you log on. When you gain access to Db2, you can use a self-written or IBM-supplied DSN3@ATH exit routine that is connected to Db2 to perform the following actions:

- Check the authorization ID again
- · Change the authorization ID
- · Associate the authorization ID with secondary IDs

After these actions are performed, the authorization ID can use the services of an external security system again.

Related concepts

Managing access requests from remote applications

You can require remote users to pass several access checks before they reach Db2. You can use RACF or a similar security subsystem to control access from a remote location.

Managing access requests from remote applications

You can require remote users to pass several access checks before they reach Db2. You can use RACF or a similar security subsystem to control access from a remote location.

While controlling access from a remote locations, RACF can do the following tasks:

- Verify an ID that is associated with a remote attachment request and check the ID with a password
- Generate *PassTickets* on the sending side. PassTickets can be used instead of passwords. A PassTicket lets a user gain access to a host system without sending the RACF password across the network.
- Verify a Kerberos ticket if your distributed environment uses Kerberos to manage user access and perform user authentication

You can also control access authentication by using the Db2 *communications database* (CDB). The CDB is a set of tables in the Db2 catalog that are used to establish conversations with remote database management systems. The CDB can translate IDs before it sends them to the remote system.

You can use the RACF DSNR general resource class for Db2 for access authentication. With RACF DSNR, you can control access to the Db2 server by the IDs that are defined to the *ssnm*.DIST profile with READ. In addition, you can use the port of entry (POE) checking by RACF and z/OS Communications Server to protect against unauthorized remote connections to Db2.

Related concepts

Managing access requests from local applications

If you request access to a local Db2 subsystem, your request is often subject to several checks before you are granted access.

Data set protection

The data in a Db2 subsystem is contained in data sets. The data sets can be accessed without going through Db2. To protect your data, you need to control all access routes by using different access control methods and mechanisms. For example, you can determine who can use offline utilities by assigning appropriate access.

RACF for data set protection

If you want to use RACF for data set protection outside of the Db2 subsystem, define RACF profiles for data sets and permit access to the data sets for certain Db2 IDs. For more information, see <u>"Protecting</u> data sets through RACF" on page 330.

Data encryption

You have the following encryption options for protecting sensitive data:

- z/OS DFSMS data set encryption. For more information, see <u>"Encrypting your data with z/OS DFSMS</u> data set encryption" on page 311.
- IBM System Storage® DS8000® support for data encryption with the IBM Full Disk Encryption drives
- IBM System Storage TS1130 encryption solution
- Secure Socket Layer (SSL) protocol through the z/OS Communications Server IP Application Transparent Transport Layer (AT-TLS) service
- IBM Encryption Facility for z/OS
- Advanced Encryption Standard (AES) for encrypting user IDs and passwords over network connections
- Db2 edit procedures or field procedures, which can use the Integrated Cryptographic Service Facility (ICSF)
- IBM InfoSphere Guardium Data Encryption for Db2 and IMS Databases
- · Encryption tools and facilities that used outside of Db2

You can consider compressing your data sets before encrypting the data. Data compression is not a substitute for encryption. In some cases, the compression method does not actually shorten the data. In those cases, the data is left uncompressed and readable. If you encrypt and compress your data, compress it first. After you obtain the maximum compression, encrypt the result. When you retrieve your data, first decrypt the data. After the data is decrypted, decompress the result.

Scenario: Securing data access with Db2 facilities at Spiffy Computer

This scenario describes a simple approach to securing local and remote access to the sensitive data of employees, payroll operations, and payroll management at Spiffy Computer Company. It shows how to enforce a security plan by using authorization IDs, roles, privileges, authorities, and the audit trace.

You should base your security plan, techniques, and procedures on your actual security objectives; do not view this sample security plan as an exact model for your security needs. Instead, use it to understand various possibilities and address problem areas that you might encounter when you implement your security plan.

Determining security objectives

An important step in defining and implementing an effective security plan is to determine your security objectives.

About this task

Suppose that the Spiffy Computer Company management team determines the following security objectives:

- Managers can see, but not update, all of the employee data for members of their own departments.
- Managers of managers can see all of the data for employees of departments that report to them.
- The employee table resides at a central location. Managers at remote locations can query the data in the table.
- The payroll operations department makes changes to the employee table. Members of the payroll operations department can update any column of the employee table except for the salary, bonus, and commission columns.
- Members of payroll operations can update any row except for rows that are for members of their own department. Because changes to the table are made only from a central location, distributed access does not affect payroll operations.
- Changes to the salary, bonus, and commission columns are made through a process that involves the payroll update table. When an employee's compensation changes, a member of the payroll operations department can insert rows in the payroll update table. For example, a member of the payroll operations department might insert a row in the compensation table that lists an employee ID and an updated salary. Next, the payroll management group can verify inserted rows and transfer the changes to the employee table.
- No one else can see the employee data. The security plan cannot fully achieve this objective because some ID must occasionally exercise SYSADM authority. While exercising SYSADM authority, an ID can retrieve any data in the system. The security plan uses the trace facility to monitor the use of that power.

Securing manager access to employee data

As a security measurement, the Spiffy Computer Company sets clear restrictions on how its managers can access employee data.

Specifically, the Spiffy security plan imposes the following security restrictions on managers:

- Managers can retrieve, but not change, all information in the employee table for members of their own departments.
- Managers of managers have the same privileges for their own departments and for the departments that directly report to them.

Creating views of employee data

The Spiffy security planners decide to use views for implementing the restrictions on managers' access to employee data.

Procedure

To create a view of employee data for every employee that reports to a manager, the Spiffy security planners perform the following steps:

1. Add a column that contains manager IDs to DSN8C10.DEPT, as shown in the following statement:

```
ALTER TABLE DSN8C10.DEPT
ADD MGRID CHAR(8) FOR SBCS DATA NOT NULL WITH DEFAULT;
```

Populate the MGRID column with the user ID for each department manager.

2. Create a view that selects employee information about employees that work for a given manager, as shown in the following statement:

```
CREATE VIEW DEPTMGR AS
SELECT * FROM DSN8C10.EMP, DSN8C10.DEPT
WHERE WORKDEPT = DEPTNO
AND MGRID = USER;
```

3. Ensure that every manager has the SELECT privilege on the view.

Granting managers the SELECT privilege

The security planners for Spiffy Computer Company can take an "individual" approach or a "functional" approach when they grant the SELECT privilege on a view to managers.

About this task

With an individual approach, they can grant privileges to individual IDs and revoke them if the user of the ID leaves the company or transfers to another position. With a functional approach, they can create RACF groups, and grant privileges to the group IDs, with the intention of never revoking them. When an individual ID needs those privileges, connect that ID to the group; disconnect the ID when its user leaves or transfers.

The Spiffy security planners know that the functional approach is usually more convenient in the following situations:

- Each function, such as the manager function, requires many different privileges. When functional privileges are revoked from one user, they must be granted to another user.
- Several users need the same set of privileges.
- The privileges are given with the grant option, or the privileges let users create objects that must persist after their original owners leave or transfer. In both cases, revoking the privileges might not be appropriate. The revokes cascade to other users. To change ownership, you might need to drop objects and re-create them.

Some of the Spiffy requirements for securing manager access suggest the functional approach. However, in this case, the function needs only one privilege. The privilege does not carry the grant option, and the privilege does not allow new objects to be created.

Therefore, the Spiffy security planners choose the individual approach, and plan to re-examine their decision later. Spiffy security planners grant all managers the SELECT privilege on the views for their departments.

Example

To grant the SELECT privilege on the DEPTMGR view to the manager with ID EMP0060, the planners use the following GRANT statement:

```
GRANT SELECT ON DEPTMGR TO EMP0060;
```

Managing distributed access

Some Spiffy managers must use views to query data in the central employee table from remote locations. The security plan must ensure that this type of distributed access is secure. Therefore, security administrators must implement a sound plan for distributed access.

Planning for distributed access

The Spiffy security planners need to determine how the managers can securely access employee data in a distributed environment.

About this task

To secure distributed access to employee data, the Spiffy security planners must address the following questions:

- Which IDs should hold privileges on which views?
- · How do the central location and the remote locations divide security responsibilities for IDs?

The Spiffy security planners answer those questions with the following decisions:

- IDs that are managed at the central location hold privileges on views for departments that are at remote locations. For example, the ID MGRD11 has the SELECT privilege on the view DEPTD11.
- If the manager of Department D11 uses a remote system, the ID at that system must be translated to MGRD11. Then a request is sent to the central system. All other IDs are translated to CLERK before they are sent to the central system.
- The communications database (CDB) manages the translated IDs, like MGRD11.
- An ID from a remote system must be authenticated on any request to the central system.

Related tasks

Implementing distributed access at the central server

To enable distributed access to sensitive employee data, the Spiffy security plan requires certain security measures to be implemented at the central server location.

Implementing distributed access at remote locations

To enable distributed access to sensitive employee data, the Spiffy security plan requires certain security measures to be implemented at the remote locations.

Implementing distributed access at the central server

To enable distributed access to sensitive employee data, the Spiffy security plan requires certain security measures to be implemented at the central server location.

About this task

The following actions must occur at the central server location:

- The central Db2 subsystem must authenticate every incoming ID with RACF.
- For SNA connections, the Spiffy security planners must include an entry in table SYSIBM.LUNAMES in the CDB; the entry in the LUNAME column identifies the LU name of every remote location. The entry must specify that connections must be verified.

Example: The following table shows an entry in SYSIBM.LUNAMES for LUREMOTE.

Table 1. The SYSIBM.LUNAMES table at the central location				
LUNAME USERNAMES SECURITY_IN ENCRYPTPSWDS				
LUREMOTE	blank	V	Ν	

The value of V for SECURITY_IN indicates that incoming remote connections must include verification. The value of N for ENCRYPTPSWDS indicates that passwords are not in internal RACF encrypted format.

The security plan treats all remote locations alike, so it does not require encrypted passwords. The option to require encrypted passwords is available only between two Db2 subsystems that use SNA connections.

- For TCP/IP connections, the Spiffy security planners must set the TCP/IP ALREADY VERIFIED field of installation panel DSNTIP5 to NO. This setting ensures that the incoming requests that use TCP/IP are not accepted without authentication.
- The Spiffy security planners must grant all privileges and authorities that are required by the manager of Department D11 to the ID, MGRD11. The security planners must grant similar privileges to IDs that correspond to the remaining managers.

Related tasks

Planning for distributed access

The Spiffy security planners need to determine how the managers can securely access employee data in a distributed environment.

Implementing distributed access at remote locations

To enable distributed access to sensitive employee data, the Spiffy security plan requires certain security measures to be implemented at the remote locations.

Implementing distributed access at remote locations

To enable distributed access to sensitive employee data, the Spiffy security plan requires certain security measures to be implemented at the remote locations.

About this task

The following actions must occur at the remote locations to enable distributed access for the Spiffy security plan:

• For SNA connections, the Spiffy security planners must include an entry in table SYSIBM.LUNAMES for the LU name of the central location. The entry must specify an outbound ID translation for attachment requests to that location.

For example, the following table shows an entry in SYSIBM.LUNAMES for LUCENTRAL.

Table 2. The SYSIBM.LUNAMES table at the remote location					
LUNAME USERNAMES SECURITY_OUT					
LUCENTRAL O P					

The value of O for USERNAMES indicates that translation checking is performed on outbound IDs, but not on inbound IDs. The value of P for SECURITY_OUT indicates that outbound connection requests contain a user password and a RACF PassTicket.

• For TCP/IP connections, the Spiffy security planners must include an entry in table SYSIBM.IPNAMES for the LU name that is used by the central location. The content of the LUNAME column is used to generate RACF PassTickets. The entry must specify outbound ID translation for requests to that location.

For example, the following table shows an entry in SYSIBM.IPNAMES for LUCENTRAL.

Table 3. The SYSIBM.IPNAMES table at the remote location					
LINKNAME USERNAMES SECURITY_OUT IPADDR					
LUCENTRAL R central.vnet.ibm.com					

• The Spiffy security planners must include entries in table SYSIBM.USERNAMES to translate outbound IDs.

For example, the following table shows two entries in SYSIBM.USERNAMES.

Table 4. The SYSIBM.USERNAMES table at the remote location			
ТҮРЕ	AUTHID	LINKNAME	NEWAUTHID
0	MEL1234	LUCENTRAL	MGRD11
0	blank	LUCENTRAL	CLERK

MEL1234 is translated to MGRD11 before it is sent to the LU that is specified in the LINKNAME column. All other IDs are translated to CLERK before they are sent to that LU.

Exception: For a product other than Db2 for z/OS, the actions at the remote location might be different. If you use a different product, check the documentation for that product. The remote product must satisfy the requirements that are imposed by the central subsystem.

Related tasks

Planning for distributed access

The Spiffy security planners need to determine how the managers can securely access employee data in a distributed environment.

Implementing distributed access at the central server

To enable distributed access to sensitive employee data, the Spiffy security plan requires certain security measures to be implemented at the central server location.

Auditing manager access

The Spiffy payroll data is extremely sensitive. The security plan requires the audit trace to be automatically started for all classes whenever Db2 is started.

About this task

To ensure that an audit record exists for every access to the employee table, the Spiffy security planners create an audit policy for the employee table. Every week, the security planners scan the records and determine the number of accesses by each manager.

The report highlights any number of accesses outside an expected range. The Spiffy system operator makes a summary of the reports every two months, and scans it for unusual patterns of access. A large number of accesses or an unusual pattern might reveal use of a manager's logon ID by an unauthorized employee.

Related concepts

Auditing access to Db2

Security auditing allows you to inspect and examine the adequacy and effectiveness of the policies and procedures that you put in place to secure your data.

Db2 audit policies

An *audit policy* is a set of criteria that determines the categories to be audited. It helps you configure and control the audit requirements of your security policies and to monitor data access by applications and individual users (authorization IDs or roles), including administrative authorities.

Securing access to payroll operations and management

As a security measurement, the Spiffy security plan sets clear restrictions on how members of the payroll operations department access and handle sensitive payroll information.

The plan imposes the following restrictions on members of the payroll operations department:

- Members of the payroll operations department can update any column of the employee table except for SALARY, BONUS, and COMM.
- Members of payroll operations can update any row except for rows that are for members of their own department.

Because changes to the table are made only from the central location, distributed access does not affect payroll operations.

Creating views of payroll operations

The Spiffy security planners decide to use views for implementing the security objectives for members of the payroll operations department.

Examples

Example: PAYDEPT view

The PAYDEPT view shows all the columns of the employee table except for job, salary, bonus, and commission. The view does not show the rows for members of the payroll operations department.

The WORKDEPT value for the payroll operations department is P013. The owner of the employee table uses the following statement to create the PAYDEPT view:

```
CREATE VIEW PAYDEPT AS
SELECT EMPNO, FIRSTNME, MIDINIT, LASTNAME, WORKDEPT,
PHONENO, HIREDATE, JOB, EDLEVEL, SEX, BIRTHDATE
FROM DSN8C10.EMP
WHERE WORKDEPT<>'P013'
WITH CHECK OPTION;
```

The CHECK OPTION ensures that every row that is inserted or updated through the view conforms to the definition of the view.

Example: Example: PAYMGR view

A second view, the PAYMGR view, gives Spiffy payroll managers access to any record, including records for the members of the payroll operations department.

The owner of the employee table uses the following statement to create the PAYMGR view:

```
CREATE VIEW PAYMGR AS
SELECT EMPNO, FIRSTNME, MIDINIT, LASTNAME, WORKDEPT,
PHONENO, HIREDATE, JOB, EDLEVEL, SEX, BIRTHDATE
FROM DSN8C10.EMP
WITH CHECK OPTION;
```

Neither PAYDEPT nor PAYMGR provides access to compensation amounts. When a row is inserted for a new employee, the compensation amounts remain null. An update process can change these values at a later time. The owner of the employee table creates, owns, and grants privileges on both views.

Related tasks Creating Db2 views (Db2 Administration Guide) Related reference CREATE VIEW statement (Db2 SQL)

Securing compensation accounts with update tables

The Spiffy security plan does not allow members of payroll operations to update compensation amounts directly. Instead, a separate payroll update table contains the employee ID, job, salary, bonus, and commission.

About this task

Members of payroll operations make all job, salary, and bonus changes to the payroll update table, except those for their own department. After they verify the prospective changes, the managers of payroll operations run an application program. The program reads the payroll update table and makes the corresponding changes to the employee table. Only the payroll update program has the privilege of updating job, salary, and bonus in the employee table.

The Spiffy Computer Company calculates commission amounts separately by using a complicated formula. The formula considers the employee's job, department, years of service with the company, and

responsibilities for various projects. The formula is embedded in the commission program, which is run regularly to insert new commission amounts in the payroll update table. The plan owner must have the SELECT privilege on the employee table and other tables to run the commission program.

Securing compensation updates with other measures

By separating potential salary changes into the payroll update table, the Spiffy security planners allow payroll management to verify changes before they go into effect.

About this task

At Spiffy Computer Company, managers check the changes against a written change request that is signed by a required level of management. The Spiffy security planners consider that check to be the most important control on salary updates, but the plan also includes the following controls:

- The employee ID in the payroll update table is a foreign key column that refers to the employee ID in the employee table. Enforcing the referential constraint prevents an employee ID from being changed to an invalid value.
- The employee ID in the payroll update table is also a primary key for that table. Therefore, the values in the employee ID column must be unique. Because of enforced uniqueness, every change that is made for any one employee during a given operating period must appear in the same row of the table. No two rows can carry conflicting changes.

The Spiffy security plan documents an allowable range of salaries, bonuses, and commissions for each job level. To keep the values within the allowable ranges, the Spiffy security planners use table check constraints for the salaries, bonuses, and commissions. The planners use this approach because it is both simple and easy to control.

In a similar situation, you might also consider the following ways to ensure that updates and inserts stay within certain ranges:

- Keep the ranges in a separate Db2 table. To verify changes, query the payroll update table and the table of ranges. Retrieve any rows for which the planned update is outside the allowed range.
- Build the ranges into a validation routine. Apply the validation routine to the payroll update table to automatically reject any insert or update that is outside the allowed range.
- Embody the ranges in a view of the payroll table, using WITH CHECK OPTION, and make all updates to the view. The ID that owns the employee table also owns the view.
- Create a trigger to prevent salaries, bonuses, and commissions from increasing by more than the percent that is allowed for each job level.

Granting privileges to payroll operations and management

The Spiffy security plan strongly suggests the functional approach for the payroll operations department.

About this task

The functional approach meets the security needs of the payroll operations for the following reasons:

- Payroll operations members require several privileges, including the SELECT, INSERT, UPDATE, and DELETE privileges on the PAYDEPT view.
- Several members of the department require the same set of privileges.
- If members of the department leave, others are hired or transferred to replace the departing members.

Therefore, the security plan calls for the creation of two RACF groups, with one for the payroll operations and another for the payroll management.

Creating a RACF group for payroll operations

The Spiffy security plan calls for the creation of a RACF group for the payroll operations department. DB2USER can define the group and retain its ownership, or it can assign the ownership to an ID that is used by payroll management.

About this task

The owner of the employee table can grant the privileges that the group requires. The owner grants all required privileges to the group ID, with the intent not to revoke them. The primary IDs of new members of the department are connected to the group ID, which becomes a secondary ID for each of them. The primary IDs of members who leave the department are disconnected from the group ID.

Example

The following statement grants the SELECT, INSERT, UPDATE, and DELETE privileges on the PAYDEPT view to the payroll operations group ID PAYOPS:

GRANT SELECT, INSERT, UPDATE, DELETE ON PAYDEPT TO PAYOPS;

This statement grants the privileges without the GRANT OPTION to keep members of payroll operations from granting privileges to other users.

Creating a RACF group for payroll management

The Spiffy payroll managers require different privileges and a different RACF group ID. The security planners add a RACF group for payroll managers and name it PAYMGRS.

About this task

The security planners associate the payroll managers' primary IDs with the PAYMGRS secondary ID. Next, privileges on the PAYMGR view, the compensation application, and the payroll update application are granted to PAYMGRS. The payroll update application must have the appropriate privileges on the update table.

Example

The following statement grants the SELECT, INSERT, UPDATE, and DELETE privileges on the PAYMGR view to the payroll managers' group ID PAYMGRS:

GRANT SELECT, INSERT, UPDATE, DELETE ON PAYMGR TO PAYMGRS;

The following statement grants the EXECUTE privilege on the compensation application:

GRANT EXECUTE ON PLAN COMPENS TO PAYMGRS;

Auditing payroll operations and management

You can create an audit policy for the payroll update table to audit payroll operation and management activities.

About this task

The audit trace records the number of accesses by the payroll operations and payroll management groups. The Spiffy security planners scan the reports of payroll access for large numbers or unusual patterns of access.

Related concepts

Auditing access to Db2

Security auditing allows you to inspect and examine the adequacy and effectiveness of the policies and procedures that you put in place to secure your data.

Db2 audit policies

An *audit policy* is a set of criteria that determines the categories to be audited. It helps you configure and control the audit requirements of your security policies and to monitor data access by applications and individual users (authorization IDs or roles), including administrative authorities.

Managing access privileges of other authorities

In addition to the privileges for the managers and the payroll operation and management personnel, the security plan considers the privileges for other roles.

Managing access by the DBADM authority

An ID with the DBADM authority on a database has many privileges on that database and its tables. These privileges include the SELECT, INSERT, DELETE, UPDATE, and ALTER statements on any table in the database. They also include the CREATE and DROP statements on indexes for those tables.

About this task

For security reasons, the Spiffy security planners prefer not to grant all of the privileges that come with DBADM authority on DSN8D12A. DSN8D12A is the database that holds the employee table and the payroll update table.

The Spiffy security planners prefer to grant DBCTRL authority on the database because granting DBCTRL authority does not expose as many security risks as granting DBADM authority. DBCTRL authority allows an ID to support the database without allowing the ID to retrieve or change the data in the tables. However, database DSN8D12A contains several additional tables. These additional tables require some of the privileges that are included in DBADM authority but not included in DBCTRL authority.

The Spiffy security planners decide to compromise between the greater security of granting DBCTRL authority and the greater flexibility of granting DBADM authority. To balance the benefits of each authority, the Spiffy security planners create an administrative ID with some, but not all of the DBADM privileges. The security plan calls for a RACF group ID with the following authorities and privileges:

- DBCTRL authority over DSN8D81A
- The INDEX privilege on all tables in the database except the employee table and the payroll update table
- The SELECT, INSERT, UPDATE, and DELETE privileges on certain tables, excluding the employee table and the payroll update table

An ID with SYSADM authority grants the privileges to the group ID.

In a similar situation, you also might consider putting the employee table and the payroll update table in a separate database. Then you can grant DBADM authority on DSN8D12A, and grant DBCTRL authority on the database that contains the employee table and the payroll update table.

Related tasks

Managing access by the SYSADM authority

An ID with SYSADM authority can access data from any table in the entire Db2 subsystem, including the employee table and the payroll update table. The Spiffy security planners want to minimize the security risk by granting the SYSADM authority to as few users as possible.

Managing access by object owners

The Spiffy security plan must consider the ID that owns and grants privileges on the tables, views, and programs. The ID that owns these objects has many implicit privileges on the objects. The owner of the objects can also grant privileges on the objects to other users.

Managing access by other users

Users must be authorized to access the employee table or the payroll table. Exceptions occur when any unauthorized user tries to access the tables.

Related reference

System DBADM administrative authority

The system DBADM authority allows an administrator, an authorization ID or a role, to manage databases across a Db2 subsystem, while having no access to the data in the databases. In other words, the system DBADM authority enables you to create, alter, and drop Db2 objects and issue commands for a Db2 subsystem, but does not give you the authority to access the data or the ability to grant or revoke privileges.

DBADM administrative authority

The DBADM authority includes the DBCTRL privileges over a specific database. A user with the DBADM authority can access any tables in a specific database by using SQL statements.

Managing access by the SYSADM authority

An ID with SYSADM authority can access data from any table in the entire Db2 subsystem, including the employee table and the payroll update table. The Spiffy security planners want to minimize the security risk by granting the SYSADM authority to as few users as possible.

About this task

The planners know that the subsystem might require SYSADM authority only for certain tasks and only for relatively short periods. They also know that the privileges that are associated with the SYSADM authority give an ID control over all of the data in a subsystem.

To limit the number of users with SYSADM authority, the Spiffy security plan grants the authority to DB2OWNER, the ID that is responsible for Db2 security. That does not mean that only IDs that are connected to DB2OWNER can exercise privileges that are associated with SYSADM authority. Instead, DB2OWNER can grant privileges to a group, connect other IDs to the group as needed, and later disconnect them.

The Spiffy security planners prefer to have multiple IDs with SYSCTRL authority instead of multiple IDs with SYSADM authority. IDs with SYSCTRL authority can exercise most of the SYSADM privileges and can assume much of the day-to-day work. IDs with SYSCTRL authority cannot access data directly or run plans unless the privileges for those actions are explicitly granted to them. However, they can run utilities, examine the output data sets, and grant privileges that allow other IDs to access data. Therefore, IDs with SYSCTRL authority cannot easily access the data. As part of the Spiffy security plan, DB20WNER grants SYSCTRL authority to selected IDs.

The Spiffy security planners also use ROLEs, RACF group IDs, and secondary IDs to relieve the need to have SYSADM authority continuously available. SYSADM grants the necessary privileges to a ROLE, RACF group ID, or secondary ID. IDs that have this ROLE, RACF group ID, or secondary ID can then bind plans and packages it owns.

Related tasks

Managing access by the DBADM authority

An ID with the DBADM authority on a database has many privileges on that database and its tables. These privileges include the SELECT, INSERT, DELETE, UPDATE, and ALTER statements on any table in the database. They also include the CREATE and DROP statements on indexes for those tables.

Managing access by object owners

The Spiffy security plan must consider the ID that owns and grants privileges on the tables, views, and programs. The ID that owns these objects has many implicit privileges on the objects. The owner of the objects can also grant privileges on the objects to other users.

Managing access by other users

Users must be authorized to access the employee table or the payroll table. Exceptions occur when any unauthorized user tries to access the tables.

Managing access by object owners

The Spiffy security plan must consider the ID that owns and grants privileges on the tables, views, and programs. The ID that owns these objects has many implicit privileges on the objects. The owner of the objects can also grant privileges on the objects to other users.

About this task

The Spiffy security planners want to limit the number of IDs that have privileges on the employee table and the payroll update table to the smallest convenient value. To meet that objective, they decide that the owner of the employee table should issue all of the CREATE VIEW and GRANT statements. They also decide to have the owner of the employee table own the plans and packages that are associated with employee data. The employee table owner implicitly has the following privileges, which the plans and packages require:

- The owner of the payroll update program must have the SELECT privilege on the payroll update table and the UPDATE privilege on the employee table.
- The owner of the commission program must have the UPDATE privilege on the payroll update table and the SELECT privilege on the employee table.

The owners of several other payroll programs must have the proper privileges to do payroll processing, such as printing payroll checks, writing summary reports, and so on.

To bind these plans and packages, an ID must have the BIND or BINDADD privileges. The list of privileges that are required by the owner of the employee table suggests the functional approach. The Spiffy security planners create a RACF group for the owner of the employee table.

Related tasks

Managing access by the DBADM authority

An ID with the DBADM authority on a database has many privileges on that database and its tables. These privileges include the SELECT, INSERT, DELETE, UPDATE, and ALTER statements on any table in the database. They also include the CREATE and DROP statements on indexes for those tables.

Managing access by the SYSADM authority

An ID with SYSADM authority can access data from any table in the entire Db2 subsystem, including the employee table and the payroll update table. The Spiffy security planners want to minimize the security risk by granting the SYSADM authority to as few users as possible.

Managing access by other users

Users must be authorized to access the employee table or the payroll table. Exceptions occur when any unauthorized user tries to access the tables.

Managing access by other users

Users must be authorized to access the employee table or the payroll table. Exceptions occur when any unauthorized user tries to access the tables.

About this task

The following users are authorized to access the employee and payroll tables:

- Department managers
- Members of the payroll operations department
- Payroll managers
- The payroll update program

The audit report lists each exception in full. Auditors check each exception to determine whether it was a planned operation by the users with SYSADM or DBADM authority, or the employee table owner.

The audit report also lists denials of access to the tables. Those denials represent attempts by unauthorized IDs to use the tables. Some are possibly accidental; others can be attempts to violate the security system.

After running the periodic reports, the security planners archive the audit records. The archives provide a complete audit trail of access to the employee data through Db2.

Related tasks

Managing access by the DBADM authority

An ID with the DBADM authority on a database has many privileges on that database and its tables. These privileges include the SELECT, INSERT, DELETE, UPDATE, and ALTER statements on any table in the database. They also include the CREATE and DROP statements on indexes for those tables.

Managing access by the SYSADM authority

An ID with SYSADM authority can access data from any table in the entire Db2 subsystem, including the employee table and the payroll update table. The Spiffy security planners want to minimize the security risk by granting the SYSADM authority to as few users as possible.

Managing access by object owners

The Spiffy security plan must consider the ID that owns and grants privileges on the tables, views, and programs. The ID that owns these objects has many implicit privileges on the objects. The owner of the objects can also grant privileges on the objects to other users.

Chapter 2. Managing access through authorization IDs and roles

Db2 controls access to its objects and data through authorization identifiers (IDs) and roles and the privileges that are assigned to them. Each privilege and its associated authorities enable you to take specific actions on an object. Therefore, you can manage access to Db2 objects through authorization IDs and roles.

As the following diagram shows, you can grant privileges and authorities to IDs or roles and control access to data and processes in several primary ways:



Figure 2. Access to objects and data within Db2

- 1. Managing access to Db2 through RACF and subsystem access authorization.
- 2. Managing access to Db2 subsystem through connection and sign-on routines or trusted contexts.
- 3. Granting and revoking explicit privileges through authorization IDs and roles or through external access control.

Db2 has primary authorization IDs, secondary authorization IDs, roles, and SQL IDs. Some privileges can be exercised by only one type of ID or a role; other privileges can be exercised by multiple IDs or roles. The Db2 catalog records the privileges that IDs are granted and the objects that IDs own.

- 4. Managing implicit privileges through ownership of objects other than plans and packages.
- 5. Managing implicit privileges through ownership of plans and packages.
- 6. Controlling access through security labels on tables.
- 7. Activating and deactivating row and column access control on tables.

Certain privileges and authorities are assigned when you install Db2. You can reassign these authorities by changing the DSNZPARM subsystem parameter.

As a security planner, you must be aware of these ways to manage privileges and authorities through authorization IDs and roles before you write a security plan. After you decide how to authorize access to data, you can implement it through your security plan.

Authorization IDs and roles

You can control access to Db2 objects by assigning privileges and authorities to an authorization ID or a role.

Authorization IDs

Every process that connects to or signs on to Db2 is represented by one or more Db2 short identifiers (IDs), which are called *authorization IDs*. Authorization IDs are assigned to a process by default procedures or by user-written exit routines.

When authorization IDs are assigned, every process receives exactly one ID that is called the *primary authorization ID*. All other IDs are *secondary authorization IDs*. Furthermore, one ID (either primary or secondary) is designated as the current *SQL ID*. You can change the value of the SQL ID during your session.

Role

A role is available within a trusted context. You can define a role and assign it to authorization IDs in a trusted context. When associated with a role and using the trusted connection, an authorization ID inherits all the privileges that are granted to that role.

Primary authorization ID

Generally, the primary authorization ID identifies a process. For example, in a process that is initiated through the TSO attachment facility, the primary authorization ID is identical to the TSO logon ID. As another example, statistics and performance trace records use a primary authorization ID to identify a process.

Secondary authorization ID

A secondary authorization ID, which is optional, can hold additional privileges that are available to the process. For example, a secondary authorization ID can be a Resource Access Control Facility (RACF) group ID.

SQL ID

An SQL authorization ID (SQL ID) holds the privileges that are exercised when a process issues certain dynamic SQL statements. The SQL ID can be set equal to the primary ID or any of the secondary IDs. If an authorization ID of a process has the SYSADM authority and the SEPARATE SECURITY subsystem parameter is set to NO, the process can set its SQL ID to any authorization ID. If SEPARATE SECURITY is set to YES, the SYSADM authority can set its SQL ID to one of the secondary IDs only. This rule applies even when SET CURRENT SQLID is a static statement. CURRENT SQLID cannot be set to a role.

RACF ID

The RACF ID is generally the source of the primary and secondary authorization IDs (RACF groups). When you use the RACF Access Control Module or multilevel security, the RACF ID is used directly.

Related concepts

Roles in a trusted context

A *role* is a database entity that groups one or more privileges together in a trusted context. System administrators can use roles to control access to enterprise objects in a way that parallels the structure of the enterprise.

Privileges and authorities

You can control access within Db2 by granting or revoking privileges and related authorities that you assign to authorization IDs or roles. A *privilege* enables its holder to perform a specific operation, sometimes on a specific object.

Related reference

SEPARATE SECURITY field (SEPARATE_SECURITY subsystem parameter) (Db2 Installation and Migration)

Roles in a trusted context

A *role* is a database entity that groups one or more privileges together in a trusted context. System administrators can use roles to control access to enterprise objects in a way that parallels the structure of the enterprise.

A role is available only in a trusted context. A *trusted context* is an independent database entity that you can define based on a system authorization ID and connection trust attributes. The trust attributes specify a set of characteristics about a specific connection. These attributes include the IP address, domain name, or SERVAUTH security zone name of a remote client and the job or task name of a local client.

Db2 for z/OS extends the trusted context concept to allow for the assignment of a role to a trusted context. An authorization ID that uses the trusted context can inherit the privileges that are assigned to this role, in addition to the privileges that are granted to the ID.

Using roles provides the flexibility for managing context-specific privileges and simplifies the processing of authorization. Specific roles can be assigned to the authorization IDs that use the trusted connection. When your authorization ID is associated with an assigned role in the trusted context, you inherit all privileges that are granted by that role, instead of those by the default role, because the role-based privileges override the privileges that are associated with the default role.

Related concepts

Authorization IDs

Every process that connects to or signs on to Db2 is represented by one or more Db2 short identifiers (IDs), which are called *authorization IDs*. Authorization IDs are assigned to a process by default procedures or by user-written exit routines.

Trusted contexts

A *trusted context* is an independent database entity that you can define based on a system authorization ID and connection trust attributes.

Trusted connections

A *trusted connection* is a database connection that is established when the connection attributes match those of a trusted context that is defined at the server. A trusted connection can be established locally or at a remote location.

Related tasks

Defining trusted contexts

Before you can create a trusted connection, you must define a trusted context by using a system authorization ID and connection trust attributes.

Creating local trusted connections

You can establish a trusted connection to a local Db2 subsystem by using RRSAF, CAF, or the DSN command processor under TSO and DB2I.

Establishing remote trusted connections by Db2 for z/OS requesters

A Db2 for z/OS requester can establish a trusted connection to a remote location by setting up the new TRUSTED column in the SYSIBM.LOCATIONS table.

Establishing remote trusted connections to Db2 for z/OS servers

When the Db2 for z/OS server receives a remote request to establish a trusted connection, Db2 checks to see if an authentication token accompanies the request.

Privileges and authorities

You can control access within Db2 by granting or revoking privileges and related authorities that you assign to authorization IDs or roles. A *privilege* enables its holder to perform a specific operation, sometimes on a specific object.

Privileges can be explicit or implicit. An *explicit privilege* is a specific type of privilege. Each explicit privilege has a name and is the result of a GRANT statement or a REVOKE statement. For example, the SELECT privilege on a table or view is an explicit privilege.

An *implicit privilege* comes from the ownership of objects, including plans and packages. For example, users are granted implicit privileges on objects that are referenced by a plan or package when they are authorized to execute the plan or package. Another example of an implicit privilege is the privilege to drop a synonym that one owns.

An administrative *authority* is a set of privileges, often covering a related set of objects. Authorities often include privileges that are not explicit, have no name, and cannot be specifically granted. For example, when an ID is granted the SYSOPR administrative authority, the ID is implicitly granted the ability to terminate any utility job.

The phrase "privilege set of a process" means the entire set of privileges and authorities that can be used by a process (which is represented by one or more authorization IDs) in a specific situation.

Related concepts

Authorization IDs

Every process that connects to or signs on to Db2 is represented by one or more Db2 short identifiers (IDs), which are called *authorization IDs*. Authorization IDs are assigned to a process by default procedures or by user-written exit routines.

Explicit privileges

You can explicitly grant privileges on objects to authorization IDs or roles.

You can explicitly grant privileges on the following objects:

- Collections
- Databases
- Distinct types or JAR
- · Functions or procedures
- Global variables
- Packages
- Plans
- Routines
- Schemas
- Sequences
- Systems
- Tables and views
- Usage
- Use

Related concepts

Privileges by authorization ID and authority

When a process gains access to Db2, it has a primary authorization ID, one or more secondary authorization IDs, an SQL ID, and perhaps a specific role if it runs in a trusted context. To be able to
perform certain actions, an authorization ID or role must hold the required privileges. To perform other actions, a set of IDs or roles must hold the required privileges.

Related reference

Implicit privileges through object ownership

When you create a Db2 object by issuing an SQL statement, you establish its name and its ownership. By default, the owner implicitly holds certain privileges on the object.

Administrative authorities in Db2 for z/OS

Each administrative authority in Db2 for z/OS is vested with a specific set of privileges.

Utility authorities for Db2 catalog and directory

The Db2 catalog is in the DSNDB06 database. Authorities that are granted on DSNDB06 also cover database DSNDB01, which contains the Db2 directory.

Explicit collection privileges

You can explicitly grant privileges on collections.

GUPI

Db2 supports the following collection privileges:

Table 5. Explicit collection privileges		
Collection privilege	Operations allowed for a named package collection	
CREATE IN	The BIND PACKAGE subcommand, to create packages in the collection	

GUPI

Explicit database privileges

You can explicitly grant privileges on databases.

GUPI

Db2 supports the following database privileges:

Table 6. Explicit database privileges		
Database privilege	Operations allowed on a named database	
CREATETAB	The CREATE TABLE statement, to create tables in the database.	
CREATETS	The CREATE TABLESPACE statement, to create table spaces in the database	
DISPLAYDB	The DISPLAY DATABASE command, to display the database status	
DROP	The DROP and ALTER DATABASE statements, to drop or alter the database	
IMAGCOPY	The QUIESCE, COPY, and MERGECOPY utilities, to prepare for, make, and merge copies of table spaces in the database; the MODIFY RECOVERY utility, to remove records of copies	
LOAD	The LOAD utility, to load tables in the database	
RECOVERDB	The RECOVER, REBUILD INDEX, and REPORT utilities, to recover objects in the database and report their recovery status	
REORG	The REORG utility, to reorganize objects in the database	
REPAIR	The REPAIR and DIAGNOSE utilities (except REPAIR DBD and DIAGNOSE WAIT) to generate diagnostic information about, and repair data in, objects in the database	

Table 6. Explicit database privileges (continued)

Database privilege	Operations allowed on a named database
STARTDB	The START DATABASE command, to start the database
STATS	The RUNSTATS, CHECK, LOAD, REBUILD INDEX, REORG INDEX, and REORG TABLESPACE, and MODIFY STATISTICS utilities, to gather statistics, check indexes and referential constraints for objects in the database, and delete unwanted statistics history records from the corresponding catalog tables
STOPDB	The STOP DATABASE command, to stop the database

Database privileges that are granted on DSNDB04 apply to all implicitly created databases. For example, if you have the DBADM authority on DSNDB04, you can select data from any table in any implicitly created database. If you have the STOPDB privilege on DSNDB04, you can stop any implicitly created database. However, you cannot grant the same authorities or privileges to others on any implicitly created database.

GUPI

Explicit package privileges

You can explicitly grant privileges on packages.

GUPI

Db2 supports the following package privileges:

Table 7. Explicit package privileges		
Package privilege	Operations allowed for a named package	
BIND	The BIND, REBIND, and FREE PACKAGE subcommands, and the DROP PACKAGE statement, to bind or free the package, and, depending on the installation option BIND NEW PACKAGE, to bind a new version of a package	
COPY	The COPY option of BIND PACKAGE, to copy a package	
EXECUTE	Execute the package and, depending on the specification of the package-name in the PKLIST, include the package in the PKLIST option for the BIND PLAN statement	
GRANT ALL	All package privileges	

GUPI

Explicit plan privileges

You can explicitly grant privileges on plans.

GUPI

Db2 supports the following plan privileges:

Table 8. Explicit plan privileges		
Plan privilege	Plan privilege Subcommands allowed for a named application plan	
BIND	BIND, REBIND, and FREE PLAN, to bind or free the plan	
EXECUTE	RUN, to use the plan when running the application	

GUPI

Explicit routine privileges

You can explicitly grant privileges on routines.

GUPI

Db2 supports the following routine privileges:

Table 9. Explicit routine privileges		
Routine privileges Objects available for usage		
EXECUTE ON FUNCTION	A user-defined function	
EXECUTE ON PROCEDURE	A stored procedure	

GUPI

Explicit schema privileges

You can explicitly grant privileges on schemas.

GUPI

Db2 supports the following schema privileges:

Table 10. Explicit schema privileges		
Schema privileges	Operations available for usage	
CREATEIN	Create distinct types, user-defined functions, triggers, and stored procedures in the designated schemas	
ALTERIN	Alter user-defined functions or stored procedures, or specify a comment for distinct types, user-defined functions, triggers, and stored procedures in the designated schemas	
DROPIN	Drop distinct types, user-defined functions, triggers, and stored procedures in the designated schemas	

GUPI

Explicit system privileges

You can explicitly grant privileges on systems.

GUPI

Db2 supports the following system privileges:

Table 11. Explicit system privileges		
System privilege	Operations allowed on the system	
ARCHIVE	The ARCHIVE LOG command, to archive the current active log, the DISPLAY ARCHIVE command, to give information about input archive logs, the SET LOG command, to modify the checkpoint frequency specified during installation, and the SET ARCHIVE command, to control allocation and deallocation of tape units for archive processing.	
BINDADD	The BIND subcommand with the ADD option, to create new plans and packages	

Table 11. Explicit system privileges (continued)

System privilege	Operations allowed on the system
BINDAGENT	The BIND, REBIND, and FREE subcommands, and the DROP PACKAGE statement, to bind, rebind, or free a plan or package, or copy a package, on behalf of the grantor. The BINDAGENT privilege is intended for separation of function, not for added security. A bind agent with the EXECUTE privilege might be able to gain all the authority of the grantor of BINDAGENT.
BSDS	The RECOVER BSDS command, to recover the bootstrap data set
CREATEALIAS	The CREATE ALIAS statement, to create an alias for a table or view name
CREATEDBA	The CREATE DATABASE statement, to create a database and have DBADM authority over it
CREATEDBC	The CREATE DATABASE statement, to create a database and have DBCTRL authority over it
CREATESG	The CREATE STOGROUP statement, to create a storage group
CREATE_SECURE_ OBJECT	The CREATE and ALTER statements, to create secure objects, such as a secure trigger or a user-defined function. If a trigger is defined for tables that are enforced with row or column access control, it must be secure. If a user- defined function is referenced in the definition of a row permission or column mask, it must be secure. In addition, if a user-defined function is invoked in a query and its arguments reference columns with column masks, the user- defined function must be secure.
CREATETMTAB	The CREATE GLOBAL TEMPORARY TABLE statement, to define a created temporary table
DEBUGSESSION	The DEBUGINFO connection attribute, to control debug session activity for SQL stored procedures, non-inline SQL functions, and Java [™] stored procedures
DISPLAY	The DISPLAY ARCHIVE, DISPLAY BUFFERPOOL, DISPLAY DATABASE, DISPLAY LOCATION, DISPLAY LOG, DISPLAY THREAD, and DISPLAY TRACE commands, to display system information
EXPLAIN	 The SQL EXPLAIN PLAN and EXPLAIN ALL statements, to issue the statements without requiring additional privileges
	 The SQL PREPARE and DESCRIBE TABLE statements, to prepare and describe the statements without requiring additional privileges on the object
	 The BIND command, to allow users to specify the EXPLAIN(ONLY) and SQLERROR(CHECK) options without creating a plan or package
	 Dynamic SQL statements that have the special register CURRENT EXPLAIN MODE set to EXPLAIN, to allow the capture of information about the statements, without executing them
	An authorization ID or role with any of the following authority or privilege can grant the EXPLAIN privilege:
	The SECADM authority
	The ACCESSCTRL authority
	 The SYSADM authority if the SEPARATE SECURITY system parameter is set to NO at the installation
	The EXPLAIN privilege with the WITH GRANT OPTION.
MONITOR1	Receive trace data that is not potentially sensitive

Table 11. Explicit system privileges (continued)

System privilege	Operations allowed on the system	
MONITOR2	Receive all trace data	
RECOVER	The RECOVER INDOUBT command, to recover threads	
STOPALL	The STOP DB2 command, to stop Db2	
STOSPACE	The STOSPACE utility, to obtain data about space usage	
TRACE	The START TRACE, STOP TRACE, and MODIFY TRACE commands, to control tracing	

GUPI

Related tasks

Managing explicit privileges

You can use the SQL GRANT and REVOKE statements to grant and remove privileges if you enable authorization checking during Db2 installation. You can grant to or revoke privileges from authorization IDs or roles if they run in a trusted context. You can revoke only privileges that are explicitly granted.

Related reference

GRANT statement (system privileges) (Db2 SQL)

Explicit table and view privileges

You can explicitly grant privileges on tables and views.

GUPI

Db2 supports the following table and view privileges:

Table 12. Explicit table and view privileges	
Table or view privilege	SQL statements allowed for a named table or view
ALTER	ALTER TABLE, to change the table definition
DELETE	DELETE, to delete rows
INDEX	CREATE INDEX, to create an index on the table
INSERT	INSERT, to insert rows
REFERENCES	ALTER or CREATE TABLE, to add or remove a referential constraint that refers to the named table or to a list of columns in the table
SELECT	SELECT, to retrieve data
TRIGGER	CREATE TRIGGER, to define a trigger on a table
UPDATE	UPDATE, to update all columns or a specific list of columns
GRANT ALL	SQL statements of all privileges

GUPI

Explicit usage privileges

You can explicitly grant privileges on usage.

GUPI

Db2 supports the following usage privileges:

Table 13. Explicit usage privileges	
Usage privileges	Objects available for usage
USAGE ON DISTINCT TYPE	A distinct type
USAGE ON JAR (Java class for a routine)	A Java class
USAGE ON SEQUENCE	A sequence

GUPI

Explicit use privileges

You can explicitly grant privileges on use.

GUPI

Db2 supports the following use privileges:

Table 14. Explicit use privileges		
Use privileges	Objects available for use	
USE OF BUFFERPOOL	A buffer pool	
USE OF STOGROUP	A storage group	
USE OF TABLESPACE	A table space	

GUPI

Implicit privileges through object ownership

When you create a Db2 object by issuing an SQL statement, you establish its name and its ownership. By default, the owner implicitly holds certain privileges on the object.

GUPT However, this general rule does not apply to a plan or package that is not created with SQL CREATE statements. In other words, when you own an object other than a plan or package, you have implicit privileges over the object. The following table describes the implicit privileges of ownership for each type of object:

	Table 15.	Implicit	privileges o	of ownership	by object type
--	-----------	----------	--------------	--------------	----------------

Object type	Implicit privileges of ownership	
Alias	To drop the alias	
Database	DBCTRL or DBADM authority over the database, depending on the privilege (CREATEDBC or CREATEDBA) that is used to create it. DBCTRL authority does not include the privilege to access data in tables in the database.	
Distinct type	To use or drop a distinct type	
Global variable	To create, alter, comment on, use, or drop the variable.	
Index	To alter, comment on, or drop the index	
JAR (Java class for a routine)	To replace, use, or drop the JAR	
Package	To bind, rebind, free, copy, execute, drop, or comment on the package	
Plan	To bind, rebind, free, execute, or comment on the plan	

Table 15. Implicit pri	vileges of ownership by object type (continued)
Object type	Implicit privileges of ownership
Role	To create, alter, commit, drop, or comment on the role
Sequence	To alter, comment on, use, or drop the sequence
Storage group	To alter or drop the group and to name it in the USING clause of a CREATE INDEX or CREATE TABLESPACE statement
Stored procedure	To execute, alter, drop, start, stop, or display a stored procedure
Synonym	To use or drop the synonym
Table	• To alter or drop the table or any indexes on it
	 To lock the table, comment on it, or label it
	 To create an index or view for the table
	 To select or update any column (if there is no row permission or column mask defined or if the row permission and the column mask definition allows the access)
	• To insert, delete, select, or update any row (if there is no row permission defined or if the row permission definition allows the access)
	 To use the LOAD utility for the table
	 To define referential constraints on any table or set of columns
	 To create a trigger on the table
	To comment on the table
Table space	To alter or drop the table space and to name it in the IN clause of a CREATE TABLE statement
Trusted context	To create, alter, commit, revoke, or comment on the trusted context
User-defined functions	To execute, alter, drop, start, stop, or display a user-defined function
View	• To drop, comment on, or label the view, or to select any row or column
	• To execute UPDATE, INSERT, or DELETE on the view if the view is defined with the INSTEAD OF TRIGGER clause

GUPI

Related concepts

Explicit privileges

You can explicitly grant privileges on objects to authorization IDs or roles.

Privileges by authorization ID and authority

When a process gains access to Db2, it has a primary authorization ID, one or more secondary authorization IDs, an SQL ID, and perhaps a specific role if it runs in a trusted context. To be able to perform certain actions, an authorization ID or role must hold the required privileges. To perform other actions, a set of IDs or roles must hold the required privileges.

Related reference

Administrative authorities in Db2 for z/OS Each administrative authority in Db2 for z/OS is vested with a specific set of privileges.

Utility authorities for Db2 catalog and directory

The Db2 catalog is in the DSNDB06 database. Authorities that are granted on DSNDB06 also cover database DSNDB01, which contains the Db2 directory.

Administrative authorities in Db2 for z/OS

Each administrative authority in Db2 for z/OS is vested with a specific set of privileges.

GUPI

The following table lists the Db2 for z/OS administrative authorities and the grantable privileges that each of them has.

Authority	Included authorities	Additional grantable privileges
Installation SYSADM	SYSADM, SYSCTRL, Installation SYSOPR, SYSOPR, SECADM, ACCESSCTRL,System DBADM, DATAACCESS, DBADM, DBCTRL, DBMAINT, PACKADM	Privileges on security: GRANT REVOKE
SYSADM	SYSCTRL, Installation SYSOPR (except for	Privileges on all plans:
	accessing Db2 when the	EXECUTE
	subsystem is started with ACCESS(MAINT), or issuing	Privileges on all routines:
	the ACTIVATE command	EXECUTE
or running the CATMAINT utility), SYSOPR, SECADM "1" on page 36, "2" on page 36, ACCESSCTRL, System DBADM, DATAACCESS,	Privileges on all packages:	
	All privileges	
	Privileges on distinct types:	
	DBMAINT, PACKADM	USAGE
		Privileges on sequences:
		USAGE
		System privileges:
		DEBUGSESSION
		EXPLAIN privilege

Table 16. Administrative authorities and their grantable privileges

Authority	Included authorities	Additional grantable privileges
SYSCTRL	SYSCTRL Installation SYSOPR (except for accessing Db2 when the subsystem is started with ACCESS(MAINT), or issuing the ACTIVATE command or running the CATMAINT utility),	System privileges:
		BINDADD BINDAGENT BSDS CREATEALIAS CREATEDBA CREATEDBC CREATESG CREATETMTAB MONITOR1 MONITOR2 STOSPACE
		Privileges on all tables:
	(except the ability to	ALTER INDEX REFERENCES TRIGGER
	grant certain authorities, such as SYSADM, DBADM,	Privileges on all catalog tables:
	PACKADM, and certain privileges, such as DELETE.	SELECT
	INSERT, SELECT, and UPDATE on user tables	Privileges on updatable catalog tables (except SYSIBM.SYSAUDITPOLICIES):
	or views, EXECUTE on plans, packages, functions,	DELETE INSERT UPDATE
	or stored procedures, PACKADM on collections.	Privileges on all plans:
	and USAGE on distinct	BIND
	DBCTRL, DBMAINT,	Privileges on all packages:
		BIND COPY
		Privileges on all collections:
		CREATEIN
		Privileges on all schemas:
		ALTERIN CREATEIN DROPIN
		Privileges on use:
		BUFFERPOOLS STOGROUP TABLESPACE
Installation	SYSOPR	System privileges:
STSOPR		ARCHIVE BINDAGENT STARTDB (cannot alter access mode)
		Privileges on system-defined packages and routines:
		EXECUTE
		Privileges on all catalog tables:
		SELECT
		Privileges on updatable catalog tables (except SYSAUDITPOLICIES):
		DELETE INSERT UPDATE

Table 16. Administrative authorities and their grantable privileges (continued)

Table 16. Administrative authorities and their grantable privileges (continued)			
Authority	Included authorities	Additional grantable privileges	
SYSOPR	None	Privileges:	
		DISPLAY RECOVER STOPALL TRACE	
		Privileges on routines:	
		DISPLAY START STOP	

Authority	Included authorities	Additional grantable privileges
System DBADM	SQLADM	System privileges:
		BINDADD BINDAGENT CREATEALIAS CREATEDBA CREATEDBC CREATETMTAB DISPLAY EXPLAIN MONITOR1 MONITOR2 SQLADM STOPALL TRACE
		Privileges on all collections:
		CREATEIN
		Privileges on all user databases:
		CREATETAB CREATETS DISPLAYDB DROP IMAGCOPY RECOVERDB STARTDB STATS STOPDB
		Privileges on all user tables (except for those defined with row permissions or column masks):
		ALTER INDEX REFERENCES TRIGGER
		Privileges on all packages:
		BIND COPY
		Privileges on all plans:
		BIND
		Privileges on system-defined packages and routines:
		EXECUTE
		Privileges on all schemas:
		ALTERIN CREATEIN DROPIN
		Privileges on all sequences:
		ALTER
		Privileges on all distinct types:
		USAGE
		Privileges on use:
		TABLESPACE
		Privileges on all catalog tables:
		SELECT
		Privileges on updatable catalog tables (except SYSIBM.SYSAUDITPOLICIES):
		DELETE INSERT UPDATE

Table 16. Administrative authorities and their grantable privileges (continued)		
Authority	Included authorities	Additional grantable privileges
SECADM	ACCESSCTRL	Privileges on all catalog tables:
		SELECT
		Privileges on all updatable catalog tables:
		DELETE INSERT UPDATE
		Privileges on security:
		GRANT REVOKE
		Privileges on security-related objects:
		ALTER CREATE DROP
ACCESSCTRL	None	Privileges on all catalog tables:
		SELECT
		Privileges on updatable catalog tables (except SYSIBM.SYSAUDITPOLICIES):
		DELETE INSERT UPDATE
		Privileges on security:
		GRANT REVOKE

Authority	Included authorities	Additional grantable privileges
DATAACCESS	None	System privileges:
		DEBUGSESSION
		Privileges on all user tables, views, and MQTs:
		DELETE INSERT SELECT UPDATE
		Privileges on all plans, packages, and routines:
		EXECUTE
		Privileges on all user databases:
		LOAD RECOVERDB REORG REPAIR
		Privileges on all JARs:
		USAGE
		Privileges on all sequences:
		USAGE
		Privileges on all distinct types:
		USAGE
		Privileges on all catalog tables:
		SELECT
		Privileges on updatable catalog tables (except SYSIBM.SYSAUDITPOLICIES):
		DELETE INSERT UPDATE
SQLADM	None	System privileges:
		EXPLAIN MONITOR1 MONITOR2
		Privileges on system-defined packages and routines:
		EXECUTE
		Privileges on all catalog tables:
		SELECT
		Privileges on updatable catalog tables (except SYSIBM.SYSAUDITPOLICIES):
		DELETE INSERT UPDATE
		Privileges on all user databases:
		STATS

Table 16 Administr . ritio rantahla rivilo *d*) +6 d thair c (c) ntin

I

Table 16. Administrative authorities and their grantable privileges (continued)		
Authority	Included authorities	Additional grantable privileges
DBADM	DBCTRL, DBMAINT	Privileges on tables in a database:
		ALTER DELETE INDEX INSERT REFERENCES SELECT TRIGGER UPDATE
		Privileges on views:
		DROP
DBCTRL	DBMAINT	Privileges on a database:
		DROP LOAD RECOVERDB REORG REPAIR
DBMAINT	None	Privileges on a database:
		CREATETAB CREATETS DISPLAYDB IMAGCOPY STATS STARTDB STOPDB
PACKADM	None	Privileges on a collection:
		CREATEIN
		Privileges on all packages in a collection:
		BIND COPY EXECUTE

Note:

- 1. Except when the SEPARATE_SECURITY subsystem parameter value is YES. For more information, see <u>SEPARATE SECURITY field (SEPARATE_SECURITY subsystem parameter)</u> (Db2 Installation and Migration).
- 2. Use of following security capabilities always requires SECADM authority, regardless of the SEPARATE_SECURITY setting.
 - TRANSFER OWNERSHIP statements
 - Stopping secure audit policies

GUPI

I

Related concepts

Explicit privileges

You can explicitly grant privileges on objects to authorization IDs or roles.

Privileges by authorization ID and authority

When a process gains access to Db2, it has a primary authorization ID, one or more secondary authorization IDs, an SQL ID, and perhaps a specific role if it runs in a trusted context. To be able to perform certain actions, an authorization ID or role must hold the required privileges. To perform other actions, a set of IDs or roles must hold the required privileges.

Related tasks

Auditing the use of an administrative authority You can create and activate an audit policy to audit how a Db2 administrative authority is used.

Related reference

Implicit privileges through object ownership

When you create a Db2 object by issuing an SQL statement, you establish its name and its ownership. By default, the owner implicitly holds certain privileges on the object.

Utility authorities for Db2 catalog and directory

The Db2 catalog is in the DSNDB06 database. Authorities that are granted on DSNDB06 also cover database DSNDB01, which contains the Db2 directory.

Related information

Managing administrative authorities

Db2 provides a range of auditable administrative authorities that help you control access to sensitive business data. The granularity and flexibility in Db2 administrative authority help you achieve adequate separation of duties and responsibilities and prevent a single user from possessing unlimited privileges.

Exploring the granularity in Db2 administrative authorities

Installation SYSADM administrative authority

Installation SYSADM authority is assigned to one or two IDs when Db2 is installed; it cannot be assigned to a role. These IDs have all the privileges of the SYSADM authority.

GUPT No other IDs can revoke the installation SYSADM authority; you can remove the authority only by changing the module that contains the subsystem initialization parameters (typically DSNZPARM).

In addition, Db2 does not record the installation SYSADM authority in the catalog. Therefore, the catalog does not need to be available to check installation SYSADM authority. The authority outside of the catalog is crucial. For example, if the directory table space DBD01 is stopped, Db2 might not be able to check the authority to start it again. In this case, only an installation SYSADM can start it.

IDs with the installation SYSADM authority can also perform the following actions:

- Run the CATMAINT utility
- Access Db2 when the subsystem is started with ACCESS(MAINT)
- Start databases DSNDB01 and DSNDB06 when they are stopped or in restricted status
- Run the DIAGNOSE utility with the WAIT statement
- Start and stop the database that contains the application registration table (ART) and the object registration table (ORT).
- Grant, revoke, and manage security-related objects regardless of the setting of the SEPARATE_SECURITY system parameter.
- Set the values of security parameters

The following tables summarizes any included authorities, and privileges held and grantable to others, by the installation SYSADM administrative authority.

Table 17. Included authorities and grantable privileges for installation SYSADM authority		
Included authorities	SYSADM, SYSCTRL, Installation SYSOPR, SYSOPR, SECADM, ACCESSCTRL,System DBADM, DATAACCESS, DBADM, DBCTRL, DBMAINT, PACKADM	
Additional grantable privileges	Privileges on security: GRANT REVOKE	

GUPI

SYSADM administrative authority

The SYSADM authority includes all the privileges, including system privileges, for creating objects and accessing all data. Depending on the setting of the SEPARATE_SECURITY system parameter, the SYSADM authority can also create security objects and grant and revoke privileges.

GUPI Regardless of the SEPARATE_SECURITY setting, an authorization ID or role with the SYSADM authority can perform the following actions. If SEPARATE_SECURITY is set to NO, it can also grant other IDs the required privileges to perform the same actions.

- Use all the privileges of DBADM over any database
- Use EXECUTE privileges on all packages
- Use EXECUTE privileges on all routines
- Use USAGE privilege on distinct types, JARs, and sequences
- Use BIND on any plan and COPY on any package
- Use privileges over views that are owned by others
- Create and drop synonyms and views for other IDs on any table
- Drop database DSNDB07

An authorization ID or role with the SYSADM authority can also perform the following actions but cannot grant other IDs the privileges to perform them:

- Drop or alter any Db2 object, except system databases
- Issue a COMMENT ON statement for any table, view, index, column, package, plan
- Issue a LABEL ON statement for any table or view
- Terminate any utility job
- Create roles and trusted contexts (if SEPARATE_SECURITY is set to NO)
- Set the current SQL ID to any valid value (if SEPARATE_SECURITY is set to NO)
- Use any valid value for OWNER in BIND or REBIND (if SEPARATE_SECURITY is set to NO)

When SEPARATE_SECURITY is set to NO, users with SYSADM authority can manage most security objects, perform grants, and revoke privileges that are granted by others, and users with SYSCTRL authority can manage roles, perform most grants, and revoke privileges that are granted by others.

However, the following newer security capabilities always require explicit SECADM authority, even if SEPARATE_SECURITY is set to NO:

- TRANSFER OWNERSHIP statements
- Stopping secure audit policies

Although an authorization ID or role with the SYSADM authority cannot grant the preceding privileges explicitly, it can accomplish this goal by granting to other IDs the SYSADM authority.

Regardless of the SEPARATE_SECURITY setting, an authorization ID or role with the SYSADM authority can revoke any privileges that were granted by itself. When SEPARATE_SECURITY is set to NO, the same ID or role can also revoke privileges that were granted by others. However, when SEPARATE_SECURITY is set to YES, the same ID or role cannot revoke privileges that were granted by others.

The following tables summarizes any included authorities, and privileges held and grantable to others, by the SYSADM administrative authority.

Table 18. Included authorities and grantable privileges for SYSADM authority	
Included authorities	SYSCTRL, Installation SYSOPR (except for accessing Db2 when the subsystem is started with ACCESS(MAINT), or issuing the ACTIVATE command or running the CATMAINT utility), SYSOPR, SECADM <u>"1" on page 36, "2" on page 36,</u> ACCESSCTRL, System DBADM, DATAACCESS, SQLADM, DBADM, DBCTRL, DBMAINT, PACKADM
Additional grantable privileges	Privileges on all plans:
	EXECUTE
	Privileges on all routines:
	EXECUTE
	Privileges on all packages:
	All privileges
	Privileges on distinct types:
	USAGE
	Privileges on sequences:
	USAGE
	System privileges:
	DEBUGSESSION
	EXPLAIN privilege

Note:

- 1. Except when the SEPARATE_SECURITY subsystem parameter value is YES. For more information, see <u>SEPARATE SECURITY field (SEPARATE_SECURITY subsystem parameter)</u> (Db2 Installation and Migration).
- 2. Use of following security capabilities always requires SECADM authority, regardless of the SEPARATE_SECURITY setting.
 - TRANSFER OWNERSHIP statements
 - Stopping secure audit policies

GUPI

Related tasks

Installation step 10: Establish subsystem security (optional) (Db2 Installation and Migration) Separating the SYSADM authority

Granularity and flexibility in Db2 administrative authority allows you to separate security administration, database administration, and data access control from system administration. Separating the SYSADM authority (a combination of security and system administration) can help you simplify your system administration and strengthen the security administration of your business data.

Related reference

SECADM administrative authority

The SECADM authority enables you to manage security-related objects in Db2 and control access to all database resources. It does not have any inherent privilege to access data stored in the objects, such as tables.

SEPARATE SECURITY field (SEPARATE_SECURITY subsystem parameter) (Db2 Installation and Migration)

SYSCTRL administrative authority

The SYSCTRL authority is designed for administering a system that contains sensitive data. With the SYSCTRL authority, you have nearly complete control of the Db2 subsystem. However, you cannot access user data directly unless you are explicitly granted the privileges to do so.

GUPI Regardless of the SEPARATE_SECURITY setting, an authorization ID or role with the SYSCTRL authority can perform the following actions:

- Act as installation SYSOPR (when the catalog is available) or DBCTRL over any database
- Run any allowable utility on any database
- Issue a COMMENT ON, LABEL ON, or LOCK TABLE statement for any table
- Create a view on any catalog table for itself or for other IDs
- Create tables and aliases for itself or for others IDs
- Bind a new plan or package and name any ID as the owner of the plan or package
- Create roles (only if SEPARATE_SECURITY is set to NO)
- Use any valid value for OWNER in BIND or REBIND (only if SEPARATE_SECURITY is set to NO)
- Has implicit ACCESSCTRL authority to grant most privileges (only if SEPARATE_SECURITY is set to NO)

However, you cannot perform the following actions without the required additional privileges:

- Execute SQL statements that change data in any user tables or views
- Run plans or packages
- Set the current SQL ID to a value that is not one of its primary or secondary IDs
- Start or stop the database that contains the application registration table (ART) and the object registration table (ORT)
- Act fully as SYSADM or as DBADM over any database
- Access Db2 when the subsystem is started with ACCESS(MAINT)

The SYSCTRL authority is intended to separate system control functions from administrative functions. However, SYSCTRL is not a complete solution for a high-security system. If any plans have their EXECUTE privilege granted to PUBLIC, an ID or role with the SYSCTRL authority can grant itself the SYSADM authority. The only control over such actions is to audit the activity of IDs with high levels of authority.

When SEPARATE_SECURITY is set to NO, users with SYSADM authority can manage most security objects, perform grants, and revoke privileges that are granted by others, and users with SYSCTRL authority can manage roles, perform most grants, and revoke privileges that are granted by others.

However, the following newer security capabilities always require explicit SECADM authority, even if SEPARATE_SECURITY is set to NO:

- TRANSFER OWNERSHIP statements
- Stopping secure audit policies

The following tables summarizes any included authorities, and privileges held and grantable to others, by the SYSCTRL administrative authority.

Table 19. Included authorities and grantable privileges for SYSCTRL authority	
Included authorities	Installation SYSOPR (except for accessing Db2 when the subsystem is started with ACCESS(MAINT), or issuing the ACTIVATE command or running the CATMAINT utility), SYSOPR, ACCESSCTRL (except the ability to grant certain authorities, such as SYSADM, DBADM, PACKADM, and certain privileges, such as DELETE, INSERT, SELECT, and UPDATE on user tables or views, EXECUTE on plans, packages, functions, or stored procedures, PACKADM on collections, and USAGE on distinct types, JARs, and sequences) DBCTRL, DBMAINT,
Additional grantable privileges	System privileges:
	BINDADD BINDAGENT BSDS CREATEALIAS CREATEDBA CREATEDBC CREATESG CREATETMTAB MONITOR1 MONITOR2 STOSPACE
	Privileges on all tables:
	ALTER INDEX REFERENCES TRIGGER
	Privileges on all catalog tables:
	SELECT
	Privileges on updatable catalog tables (except SYSIBM.SYSAUDITPOLICIES):
	DELETE INSERT UPDATE
	Privileges on all plans:
	BIND
	Privileges on all packages:
	BIND COPY
	Privileges on all collections:
	CREATEIN
	Privileges on all schemas:
	ALTERIN CREATEIN DROPIN
	Privileges on use:
	BUFFERPOOLS STOGROUP TABLESPACE

GUPI

Related tasks

Installation step 10: Establish subsystem security (optional) (Db2 Installation and Migration) Separating the SYSADM authority

Granularity and flexibility in Db2 administrative authority allows you to separate security administration, database administration, and data access control from system administration. Separating the SYSADM

authority (a combination of security and system administration) can help you simplify your system administration and strengthen the security administration of your business data.

Related reference

SEPARATE SECURITY field (SEPARATE_SECURITY subsystem parameter) (Db2 Installation and Migration) SYSCTRL administrative authority

The SYSCTRL authority is designed for administering a system that contains sensitive data. With the SYSCTRL authority, you have nearly complete control of the Db2 subsystem. However, you cannot access user data directly unless you are explicitly granted the privileges to do so.

Installation SYSOPR administrative authority

Installation SYSOPR authority is assigned to one or two IDs when Db2 is installed; it cannot be assigned to a role. These IDs have all the privileges of the SYSOPR authority.

GUPT No IDs can revoke the installation SYSOPR authority; you can remove it only by changing the module that contains the subsystem initialization parameters (typically DSNZPARM).

In addition, the installation SYSOPR authority is not recorded in the Db2 catalog. Therefore, the catalog does not need to be available to check the installation SYSOPR authority.

IDs with the installation SYSOPR authority can perform the following actions:

- Access Db2 when the subsystem is started with ACCESS(MAINT).
- Access all catalog tables and tables in the system databases.
- Have the BINDAGENT privilege to specify the owner of a package, free a package, and bind or free a plan.
- Issue the -ACTIVATE command to activate new capabilities in Db2.
- Issue dynamic SQL statements that are not controlled by the Db2 resource limit facility.
- Issue the START DATABASE command to recover objects that have LPL entries or group buffer pool RECOVERY-pending status. These IDs cannot change the access mode.
- Run all allowable utilities on the directory and catalog databases (DSNDB01 and DSNDB06).
- Run the CATMAINT utility to install or migrate to Db2.
- Run the REPAIR utility with the DBD statement.
- Start and stop the database that contains the application registration table (ART) and the object registration table (ORT).
- Set the SQL ID field to SYSINSTL, regardless of the SEPARATE SECURITY setting.

The following tables summarizes any included authorities, and privileges held and grantable to others, by the installation SYSOPR administrative authority.

Table 20. Included authorities and grantable privileges for installation SYSOPR authority	
Included authorities	SYSOPR

Table 20. Included authorities and grantable privileges for installation SYSOPR authority (continued)	
Additional grantable privileges	System privileges:
	ARCHIVE BINDAGENT STARTDB (cannot alter access mode)
	Privileges on system-defined packages and routines:
	EXECUTE
	Privileges on all catalog tables:
	SELECT
	Privileges on updatable catalog tables (except SYSAUDITPOLICIES):
	DELETE INSERT UPDATE

GUPI

GUPI Related reference -ACTIVATE command (Db2) (Db2 Commands) CATMAINT (Db2 Utilities)

SYSOPR administrative authority

A user with the SYSOPR authority can issue all Db2 commands except ARCHIVE LOG, START DATABASE, STOP DATABASE, and RECOVER BSDS.

GUPT In addition, that user can run the DSN1SDMP utility and terminate any utility job. With the GRANT option, that user can grant these privileges to others.

The following tables summarizes any included authorities, and privileges held and grantable to others, by the SYSOPR administrative authority.

Table 21. Included authorities and grantable privileges for SYSOPR authority	
Included authorities	None
Additional grantable privileges	Privileges:
	DISPLAY RECOVER STOPALL TRACE
	Privileges on routines:
	DISPLAY START STOP

GUPI

SECADM administrative authority

The SECADM authority enables you to manage security-related objects in Db2 and control access to all database resources. It does not have any inherent privilege to access data stored in the objects, such as tables.

GUPI With the SECADM authority, you can perform the following tasks:

• Create, alter, drop, and comment on row permissions

- Create, alter, drop, and comment on column masks
- · Activate and deactivate row access control
- Activate and deactivate column access control
- Create, drop, and comment on roles
- Create, alter, drop, and comment on trusted contexts
- · Create and comment on secure triggers and user-defined functions
- Alter the SECURED or NOT SECURED clause on triggers and user-defined functions
- Create audit policies by inserting rows into the SYSIBM.SYSAUDITPOLICIES catalog table
- Access and update the SYSIBM.SYSAUDITPOLICIES catalog table which records audit policy definitions
- Has implicit SELECT access on all catalog tables and implicit INSERT, DELETE, and UPDATE privileges on updatable catalog tables, when the SQL statements are issued dynamically
- Grant and revoke all grantable privileges and authorities
- Issue the SQL statement TRANSFER OWNERSHIP
- Issue the TRACE command to start, stop, and display a trace
- Set the values of security parameters

If the SEPARATE_SECURITY system parameter is set to YES, no other authority can grant the ACCESSCTRL, System DBADM, and DATAACCESS authorities or the CREATE_SECURE_OBJECT privilege, not even SYSADM. For example, only SECADM, not SYSADM or DBADM, can activate or deactivate row or column access control for a table.

The following tables summarizes any included authorities, and privileges held and grantable to others, by the SECADM administrative authority.

Table 22. Included authorities and grantable privileges for SECADM authority	
Included authorities	ACCESSCTRL
Additional grantable privileges	Privileges on all catalog tables:
	SELECT
	Privileges on all updatable catalog tables:
	DELETE INSERT UPDATE
	Privileges on security:
	GRANT REVOKE
	Privileges on security-related objects:
	ALTER CREATE DROP
1	1

GUPI

Related tasks

Separating the SYSADM authority

Granularity and flexibility in Db2 administrative authority allows you to separate security administration, database administration, and data access control from system administration. Separating the SYSADM authority (a combination of security and system administration) can help you simplify your system administration and strengthen the security administration of your business data.

Related reference

SEPARATE SECURITY field (SEPARATE_SECURITY subsystem parameter) (Db2 Installation and Migration)

ACCESSCTRL administrative authority

The ACCESSCTRL authority allows you to grant explicit privileges to authorization IDs or roles by issuing SQL GRANT statements. It enables you to grant privileges on all objects and resources, except the CREATE_SECURE_OBJECT privilege and the system DBADM, DATAACCESS, and ACCESSCTRL authorities.

GUPI With the ACCESSCTRL authority, you can use the BY clause to revoke explicitly granted privileges from authorization IDs or roles, except the CREATE_SECURE_OBJECT privilege and the system DBADM, DATAACCESS, and ACCESSCTRL authorities. In addition, you have implicit SELECT access on all catalog tables and implicit INSERT, DELETE, and UPDATE privileges on updatable catalog tables (except SYSIBM.SYSAUDITPOLICIES).

Only an authorization ID or a role with the SECADM authority can grant or revoke the ACCESSCTRL authority. Revoking the ACCESSCTRL authority does not revoke the privileges that it has already granted.

The following tables summarizes any included authorities, and privileges held and grantable to others, by the ACCESSTRL administrative authority.

Table 23. Included authorities and grantable privileges for ACCESSCTRL authority	
Included authorities	None
Additional grantable privileges	Privileges on all catalog tables:
	SELECT
	Privileges on updatable catalog tables (except SYSIBM.SYSAUDITPOLICIES):
	DELETE INSERT UPDATE
	Privileges on security:
	GRANT REVOKE

GUPI

Related tasks

Granting and revoking privileges with the ACCESSCTRL authority

If you separate database administration from system and security administration, a database administrator must have the ACCESSCTRL or SECADM authority to grant or revoke user privileges in a Db2 subsystem.

System DBADM administrative authority

The system DBADM authority allows an administrator, an authorization ID or a role, to manage databases across a Db2 subsystem, while having no access to the data in the databases. In other words, the system DBADM authority enables you to create, alter, and drop Db2 objects and issue commands for a Db2 subsystem, but does not give you the authority to access the data or the ability to grant or revoke privileges.

GUPI With the system DBADM authority, you can issue SQL statements to perform the following tasks:

- · Create and drop aliases, auxiliary tables, and distinct types
- Create, alter, and drop databases, tables, global temporary tables, table spaces, and sequences
- Create triggers, functions, indexes, procedures, and views with additional required privileges
- Comment on all but security-related objects (i.e., roles, trusted contexts)
- Issue other SQL statements, such as the EXPLAIN, LABEL, PREPARE, and RENAME statements

You can also issue Db2 commands to perform the following tasks:

• Display status, configuration, and resource information

- Start and stop procedures and profiles
- Start, stop, and access databases
- Start, stop, and modify traces
- Bind, rebind, and free packages and plans
- Set the OWNER in BIND or REBIND to any ID (if SEPARATE_SECURITY is set to NO)
- Alter and terminate the execution of Db2 utility job steps
- Recover threads that are left in an indoubt state or complete backout processing for units of recovery that are left incomplete during an earlier restart

With the system DBADM authority, you can also run certain Db2 utilities. The utilities include CHECK INDEX, CHECK LOB, COPY, COPYTOCOPY, DIAGNOSE, MODIFY RECOVERY, MODIFY STATISTICS, QUIESCE, REBUILD INDEX, RECOVER, REPORT, and RUNSTATS. In addition, you have implicit SELECT access on all catalog tables and implicit INSERT, DELETE, and UPDATE privileges on updatable catalog tables (except SYSIBM.SYSAUDITPOLICIES).

The system DBADM authority allows you to execute system-defined routines (recorded in the SYSIBM.SYSROUTINES catalog table), including stored procedures or functions, and any packages executed within the routines. It also allows you to drop non-security objects without requiring the ownership or other privileges to drop.

Only an authorization ID or a role with the SECADM authority can grant or revoke the system DBADM authority. By default, the system DBADM has all the privileges of the DATAACCESS and ACCESSCTRL authorities. If you do not want a user (an authorization ID or role) with the system DBADM authority to grant any explicit privileges, you can specify the WITHOUT ACCESSCTRL clause in the GRANT statement when you grant the authority. If you do not want a user with the system DBADM authority to access any user data in the databases, you can specify the WITHOUT DATAACCESS clause in the GRANT statement when you grant the authority. If necessary, you can still grant explicit privileges (i.e., SELECT) to the system DBADM user to access data or perform grants.

The following tables summarizes any included authorities, and privileges held and grantable to others, by the system DBADM administrative authority.

Table 24. Included authorities and grantable privileges for system DBADM authority	
Included authorities SQLADM	

Table 24. Included authorities and grantable privileges for system DBADM authority (continued)	
Additional grantable privileges	System privileges:
	BINDADD BINDAGENT CREATEALIAS CREATEDBA CREATEDBC CREATETMTAB DISPLAY EXPLAIN MONITOR1 MONITOR2 SQLADM STOPALL TRACE
	Privileges on all collections:
	CREATEIN
	Privileges on all user databases:
	CREATETAB CREATETS DISPLAYDB DROP IMAGCOPY RECOVERDB STARTDB STATS STOPDB
	Privileges on all user tables (except for those defined with row permissions or column masks):
	ALTER INDEX REFERENCES TRIGGER
	Privileges on all packages:
	BIND COPY
	Privileges on all plans:
	BIND
	Privileges on system-defined packages and routines:
	EXECUTE
	Privileges on all schemas:
	ALTERIN CREATEIN DROPIN
	Privileges on all sequences:
	ALTER
	Privileges on all distinct types:
	USAGE
	Privileges on use:
	TABLESPACE
	Privileges on all catalog tables:
	SELECT
	Privileges on updatable catalog tables (except SYSIBM.SYSAUDITPOLICIES):
	DELETE INSERT UPDATE

I

Related tasks

Altering tables with the system DBADM authority

The system DBADM authority separates object management from data access and access control. It allows object management without requiring the ownership of the object in a Db2 subsystem.

DATAACCESS administrative authority

The DATAACCESS authority allows you to access and update data in user tables, views, and materialized query tables in a Db2 subsystem. It also allows you to execute plans, packages, functions, and procedures.

Only an authorization ID or a role with the SECADM authority can grant or revoke the DATAACCESS authority. With the DATAACCESS authority, you have implicit SELECT access on all catalog tables and implicit INSERT, DELETE, and UPDATE privileges on updatable catalog tables (except SYSIBM.SYSAUDITPOLICIES).

The following tables summarizes any included authorities, and privileges held and grantable to others, by the DATACCESS administrative authority.

Table 25. Included authorities and grantable privileges for DATAACCESS authority	
Included authorities	None
Additional grantable privileges	System privileges:
	DEBUGSESSION
	Privileges on all user tables, views, and MQTs:
	DELETE INSERT SELECT UPDATE
	Privileges on all plans, packages, and routines:
	EXECUTE
	Privileges on all user databases:
	LOAD RECOVERDB REORG REPAIR
	Privileges on all JARs:
	USAGE
	Privileges on all sequences:
	USAGE
	Privileges on all distinct types:
	USAGE
	Privileges on all catalog tables:
	SELECT
	Privileges on updatable catalog tables (except SYSIBM.SYSAUDITPOLICIES):
	DELETE INSERT UPDATE

Related tasks

Accessing data with the DATAACCESS authority

A database administrator must have the DATAACCESS authority to access data in all user tables, views, and materialized query tables in a Db2 subsystem.

SQLADM administrative authority

The SQLADM authority allows you to issue the SQL EXPLAIN statements, issue certain commands, run the RUNSTATS and MODIFY STATISTICS utilities on all user databases, and execute system-defined routines, such as stored procedures or functions, and any packages that are executed within the routines.

See <u>GRANT</u> statement (system privileges) (Db2 SQL) for a list of commands that can be issued with only SQLADM authority.

Only an authorization ID or a role with the SECADM or ACCESSCTRL authority can grant or revoke the SQLADM authority. With the SQLADM authority, you have implicit SELECT access on all the catalog tables and implicit INSERT, DELETE, and UPDATE privileges on updatable catalog tables (except SYSIBM.SYSAUDITPOLICIES).

The following tables summarizes any included authorities, and privileges held and grantable to others, by the SQLADM administrative authority.

Table 26. Included authorities and grantable privileges for SQLADM authority	
Included authorities	None
Additional grantable privileges	System privileges:
	EXPLAIN MONITOR1 MONITOR2
	Privileges on system-defined packages and routines:
	EXECUTE
	Privileges on all catalog tables:
	SELECT
	Privileges on updatable catalog tables (except SYSIBM.SYSAUDITPOLICIES):
	DELETE INSERT UPDATE
	Privileges on all user databases:
	STATS

DBADM administrative authority

L

The DBADM authority includes the DBCTRL privileges over a specific database. A user with the DBADM authority can access any tables in a specific database by using SQL statements.

GUPI With the DBADM authority, you can also perform the following actions:

- Drop or alter any table space, table, or index in the database
- Issue a COMMENT, LABEL, or LOCK TABLE statement for any table in the database
- Issue a COMMENT statement for any index in the database

If the value of the DBACRVW subsystem parameter is set to YES during the Db2 installation, an ID with the DBADM authority can complete the following tasks:

- Create a view for another authorization ID on tables in that database.
- Create a materialized query table or alter a table to become a materialized query table for another authorization ID. This action requires that DBADM authority is held on the database in which the tables

of the fullselect reside and that the authorization ID has DBADM authority on the database in which the materialized query table is to reside.

• Create an alias for itself or another authorization ID for a table in that database.

For more information, see <u>DBADM CREATE AUTH field</u> (DBACRVW subsystem parameter) (Db2 Installation and Migration).

An ID with DBADM authority on one database can create a view on tables and views in that database and other databases only if the ID has all the privileges that are required to create the view. For example, an ID with DBADM authority cannot create a view on a view that is owned by another ID.

If a user has the DBADM authority with the GRANT option, that user can grant these privileges to others.

The following tables summarizes any included authorities, and privileges held and grantable to others, by the DBADM administrative authority.

Table 27. Included authorities and grantable privileges for DBADM authority	
Included authorities	DBCTRL, DBMAINT
Additional grantable privileges	Privileges on tables in a database:
	ALTER DELETE INDEX INSERT REFERENCES SELECT TRIGGER UPDATE
	Privileges on views:
	DROP

GUPI

DBCTRL administrative authority

The DBCTRL authority includes the DBMAINT privileges on a specific database. A user with the DBCTRL authority can run utilities that can change the data.

GUPT If the value of the DBADM CREATE AUTH field on the DSNTIPP installation panel is set to YES during the Db2 installation, an ID with DBCTRL authority can create an alias for another user ID on any table in the database.

If a user has the DBCTRL authority with the GRANT option, that user can grant those privileges to others.

The following tables summarizes any included authorities, and privileges held and grantable to others, by the DBCTRL administrative authority.

Table 28. Included authorities and grantable privileges for DBCTRL authority		
Included authorities DBMAINT		
Additional grantable privileges	Privileges on a database:	
	DROP LOAD RECOVERDB REORG REPAIR	

GUPI

DBMAINT administrative authority

A user with the DBMAINT authority can grant the privileges on a specific database to an ID.

GUPI With the DBMAINT authority, that user can perform the following actions within that database:

Create objects

- Run utilities that don't change data
- Issue commands
- Terminate all utilities on the database except DIAGNOSE, REPORT, and STOSPACE

If a user has the DBMAINT authority with the GRANT option, that user can grant those privileges to others.

The following tables summarizes any included authorities, and privileges held and grantable to others, by the DBMAINT administrative authority.

Table 29. Included authorities and grantable privileges for DBMAINT authority		
Included authorities None		
Additional grantable privilegesPrivileges on a database:		
	CREATETAB CREATETS DISPLAYDB IMAGCOPY STATS STARTDB STOPDB	

GUPI

PACKADM administrative authority

The PACKADM authority has the package privileges on all packages in specific collections and the CREATE IN privilege on these collections.

GUPI If the BIND NEW PACKAGE installation option is set to BIND, the PACKADM authority also has the privilege to add new packages or new versions of existing packages.

If a user has the PACKADM authority with the GRANT option, that user can grant those privileges to others.

The following tables summarizes any included authorities, and privileges held and grantable to others, by the PACKADM administrative authority.

Table 30. Included authorities and grantable privileges for PACKADM authority		
Included authorities None		
Additional grantable privileges	Privileges on a collection:	
	CREATEIN	
	Privileges on all packages in a collection:	
	BIND COPY EXECUTE	

GUPI

Common administrative authorities for the Db2 product family

Several Db2 administrative authorities provide the same functionality in Db2 for z/OS and Db2 for Linux[®], UNIX, and Windows. With these authorities, administrators who manage Db2 on multiple operating systems can manage their database environments in a consistent approach.

GUPI The following authorities provide the same administrative functionality in Db2 for z/OS and Db2 for Linux, UNIX, and Windows:

Table 31. Common Db2 administrative authorities		
Administrative authority	Capabilities	
System DBADM	 Manages resources in all databases Does not have access to data or the ability to grant and revoke privileges Executes system-defined routines (that is, stored procedures or functions) and any package within the routines Has implicit SELECT access on all catalog tables 	
SECADM	 Controls access to all database resources Manages security-related objects (that is, roles, trusted contexts, row permissions, and column masks) Grants and revokes explicit privileges that are granted by itself and others Has implicit SELECT access on all catalog tables 	
ACCESSCTRL	 Grants privileges on all but security-related objects and resources Revokes privileges on all but security-related objects and resources that are granted by itself or others Does not grant the system DBADM, DATAACCESS, or ACCESSCTRL authority Has implicit SELECT access on all catalog tables 	
DATAACCESS	 Has the ability to access data in all user tables, views, and materialized query tables Has the ability to execute all plans, packages, functions, and procedures Has implicit SELECT access on all catalog tables 	
SQLADM	 Issues EXPLAIN SQL statements and PROFILE commands Executes RUNSTATS and MODIFY STATISTICS utilities on all user databases Performs tasks that require EXPLAIN and MONITOR2 privileges Executes system defined routines (that is, stored procedures or functions) and any package executed within the routines Has implicit SELECT access on all the catalog tables 	

Db2 for z/OS provides both the system DBADM authority and the DBADM authority, with each having a set of privileges. The system DBADM authority allows you to manage objects in all databases across a Db2 subsystem, but doesn't give you access to the data in the databases. In addition, with the system DBADM authority, you can perform administrative tasks and issue commands for a Db2 subsystem, but you don't have the authority to execute objects or the ability to grant or revoke privileges.

Unlike the system DBADM authority, the DBADM authority allows you to manage objects in a specific database and gives you access to the data in that database. You also get the privileges of the DBCTRL and DBMAINT authorities over the same database.

Related reference

System DBADM administrative authority

The system DBADM authority allows an administrator, an authorization ID or a role, to manage databases across a Db2 subsystem, while having no access to the data in the databases. In other words, the system DBADM authority enables you to create, alter, and drop Db2 objects and issue commands for a Db2 subsystem, but does not give you the authority to access the data or the ability to grant or revoke privileges.

SECADM administrative authority

The SECADM authority enables you to manage security-related objects in Db2 and control access to all database resources. It does not have any inherent privilege to access data stored in the objects, such as tables.

ACCESSCTRL administrative authority

The ACCESSCTRL authority allows you to grant explicit privileges to authorization IDs or roles by issuing SQL GRANT statements. It enables you to grant privileges on all objects and resources, except the CREATE_SECURE_OBJECT privilege and the system DBADM, DATAACCESS, and ACCESSCTRL authorities.

DATAACCESS administrative authority

The DATAACCESS authority allows you to access and update data in user tables, views, and materialized query tables in a Db2 subsystem. It also allows you to execute plans, packages, functions, and procedures.

SQLADM administrative authority

The SQLADM authority allows you to issue the SQL EXPLAIN statements, issue certain commands, run the RUNSTATS and MODIFY STATISTICS utilities on all user databases, and execute system-defined routines, such as stored procedures or functions, and any packages that are executed within the routines.

Related information

Managing administrative authorities

Db2 provides a range of auditable administrative authorities that help you control access to sensitive business data. The granularity and flexibility in Db2 administrative authority help you achieve adequate separation of duties and responsibilities and prevent a single user from possessing unlimited privileges.

Utility authorities for Db2 catalog and directory

The Db2 catalog is in the DSNDB06 database. Authorities that are granted on DSNDB06 also cover database DSNDB01, which contains the Db2 directory.

An ID with the ACCESSCTRL or SECADM authority can control access to the catalog in the following ways:

- By granting privileges or authorities on that database or on its tables or views
- · By binding plans or packages that access the catalog

An ID with the ACCESSCTRL or SECADM authority can control access to the directory by granting privileges to run utilities on DSNDB06, but that ID cannot grant privileges on DSNDB01 directly.

The following table shows the utilities IDs with different authorities that can run on the DSNDB01 and DSNDB06 databases. Do not run REPAIR DBD against DSNDB01 and DSNDB06 because they are system databases; you will receive a system restriction violation message if you do. Also, you can use the LOAD utility to add lines to SYSIBM.SYSSTRINGS, but you cannot run it on other DSNDB01 or DSNDB06 tables.

-		-	-			
Utilities	Installation SYSOPR, SYSCTRL, SYSADM, Installation SYSADM	DBCTRL, DBADM on DSNDB06	DBMAINT on DSNDB06	System DBADM	DATAACCESS	SQLADM
LOAD	No	No	No	No	No	No
REPAIR DBD	No	No	No	No	No	No
CHECK DATA	Yes	No	No	No	Yes	No
CHECK LOB	Yes	No	No	Yes	No	No
REORG TABLESPACE	Yes	No	No	No	Yes	No

Table 32. Utility privileges on the Db2 catalog and directory

Table 32. Utility privileges on the Db2 catalog and directory (continued)

Utilities	Installation SYSOPR, SYSCTRL, SYSADM, Installation SYSADM	DBCTRL, DBADM on DSNDB06	DBMAINT on DSNDB06	System DBADM	DATAACCESS	SQLADM
STOSPACE	Yes	No	No	No	No	No
REBUILD INDEX	Yes	Yes	No	Yes	Yes	No
RECOVER	Yes	Yes	No	Yes	Yes	No
REORG INDEX	Yes	Yes	No	No	Yes	No
REPAIR	Yes	Yes	No	No	Yes	No
REPORT	Yes	Yes	No	Yes	Yes	No
CHECK INDEX	Yes	Yes	Yes	Yes	No	No
COPY	Yes	Yes	Yes	Yes	No	No
MERGECOPY	Yes	Yes	Yes	Yes	No	No
MODIFY	Yes	Yes	Yes	Yes	No	No
QUIESCE	Yes	Yes	Yes	Yes	No	No
RUNSTATS	Yes	Yes	Yes	Yes	No	Yes

Related concepts

Explicit privileges

You can explicitly grant privileges on objects to authorization IDs or roles.

Privileges by authorization ID and authority

When a process gains access to Db2, it has a primary authorization ID, one or more secondary authorization IDs, an SQL ID, and perhaps a specific role if it runs in a trusted context. To be able to perform certain actions, an authorization ID or role must hold the required privileges. To perform other actions, a set of IDs or roles must hold the required privileges.

Related reference

Implicit privileges through object ownership

When you create a Db2 object by issuing an SQL statement, you establish its name and its ownership. By default, the owner implicitly holds certain privileges on the object.

Administrative authorities in Db2 for z/OS

Each administrative authority in Db2 for z/OS is vested with a specific set of privileges.

Privileges by authorization ID and authority

When a process gains access to Db2, it has a primary authorization ID, one or more secondary authorization IDs, an SQL ID, and perhaps a specific role if it runs in a trusted context. To be able to perform certain actions, an authorization ID or role must hold the required privileges. To perform other actions, a set of IDs or roles must hold the required privileges.

For better performance, consider limiting the number of secondary IDs in your catalog table. A process can have up to 1012 secondary IDs. The more secondary IDs that must be checked, the longer the check takes. Also, make sure that the role and the current SQL ID have the necessary privileges for dynamic SQL statements. Because the role and the current SQL ID are checked first, the operation is fastest if they have all the necessary privileges.

Related concepts

Explicit privileges You can explicitly grant privileges on objects to authorization IDs or roles.

Related reference

Implicit privileges through object ownership

When you create a Db2 object by issuing an SQL statement, you establish its name and its ownership. By default, the owner implicitly holds certain privileges on the object.

Administrative authorities in Db2 for z/OS

Each administrative authority in Db2 for z/OS is vested with a specific set of privileges.

Utility authorities for Db2 catalog and directory

The Db2 catalog is in the DSNDB06 database. Authorities that are granted on DSNDB06 also cover database DSNDB01, which contains the Db2 directory.

Privileges required for common job roles and tasks

The labels of the administrative authorities often suggest the job roles and responsibilities of the users who are empowered with the authorities.

GUPT For example, you might expect a system administrator to have the SYSADM authority. However, some organizations do not divide job responsibilities in the same way. The following table lists some of common job roles, the tasks that usually accompany them, and the Db2 authorities or privileges that are needed to perform those tasks.

Job title	Tasks	Required privileges
System installation operator	Install or migrate Db2	Installation SYSOPR authorityInstallation SYSADM authority
System operator	Issues commands to: • Start and stop Db2 • Control traces • Display databases and threads • Recover indoubt threads • Start, stop, and display routines	SYSOPR authority
System administrator	Performs emergency backup, with access to all data.	SYSADM authority
Security administrator	Authorizes other users, for some or all levels below.	 SYSCTRL authority (if SEPARATE_SECURITY is set to NO) SECADM authority ACCESSCTRL authority
Database administrator	Designs, creates, loads, reorganizes, and monitors databases, tables, and other objects in the database.	 DBADM authority on a database. The DBADM authority on DSNDB04 allows you access to objects in all implicitly created databases. Use of storage groups and buffer pools
Database administrator	 Designs and creates databases, tables, and other objects Administers all databases in the subsystem 	System DBADM authority

Table 33. Required privileges for common jobs and tasks

Table 33. Required privileges for common jobs and tasks (continued)			
Job title	Tasks	Required privileges	
Database administrator	Manages data and executes plans and packages in a Db2 subsystem	DATAACCESS authority	
Database administrator	Manages access to data in a Db2 subsystem	ACCESSCTRL authority	
System programmer	Installs a Db2 subsystem.Recovers the Db2 catalog.Repairs data.	Installation SYSADM, which is assigned when Db2 is installed. (Consider securing the password for an ID with this authority so that the authority is available only when needed.)	
Application programmer	 Develops and tests Db2 application programs. Creates tables of test data. 	 BIND on existing plans or packages, or BINDADD CREATE IN on some collections Privileges on some objects CREATETAB on some database, with a default table space provided CREATETAB on DSNDB04. It enables you to create tables in DSNDB04 and all implicitly created databases Privileges on some objects with the SQLADM authority 	
Production binder	Binds, rebinds, and frees application packages and plans	A ROLE, secondary ID, or RACF group of which the binder has BINDADD, CREATE IN on collections privileges required by application packages and plans	
Package administrator	Manages collections and the packages in them, and delegates the responsibilities.	PACKADM authority	
User analyst	Defines the data requirements for an application program, by examining the Db2 catalog.	 SELECT on the SYSTABLES, SYSCOLUMNS, and SYSVIEWS catalog tables CREATETMTAB system privilege to create temporary tables 	
Program user	Executes an application program.	EXECUTE for the application plan	
Information center consultant	 Defines the data requirements for a query user. Provides the data by creating tables and views, loading tables, and granting access. 	 DBADM authority over some databases SELECT on the SYSTABLES, SYSCOLUMNS, and SYSVIEWS catalog tables 	

Job title	Tasks	Required privileges	
 Query user Issues SQL statements to retrieve, add, or change data. Saves results as tables or in global temporary tables. 	 Issues SQL statements to retrieve, add, or change data. 	EXPLAIN privilege on some tables and views SELECT INSERT UPDATE DELETE on some	
	tables and views		
	temporary tables.	 CREATETAB, to create tables in other than the default database 	
		 CREATETAB, to create tables in the implicitly created database 	
		 CREATETMTAB system privilege to create temporary tables 	
		 SELECT on SYSTABLES, SYSCOLUMNS, or views thereof. QMF provides the views. 	

Table 33. Required privileges for common jobs and tasks (continued)

GUPI

Related concepts

Checking access authorization for data definition statements Db2 checks for the necessary authorization privileges and authorities when you use data definition statements on certain Db2 objects.

Related reference

Privileges required for handling plans and packages An ID, or a role that runs in a trusted context, needs specific privileges to perform actions on plans and packages.

Privileges required for using dynamic SQL statements An ID needs specific privileges to issue dynamic SQL statements.

Checking access authorization for data definition statements

Db2 checks for the necessary authorization privileges and authorities when you use data definition statements on certain Db2 objects.

At both bind and run time, DB2 determines whether the authorization ID that you are using has the necessary privileges to access the following objects:

- Alias
- Table
- Explicitly created auxiliary table
- Explicitly created table space
- Explicitly created index
- Storage group
- Database

At run time, Db2 determines whether the authorization ID that you are using has the necessary privileges to access the following objects:

- Buffer pool that is involved with an implicitly created table space
- Buffer pool and storage group that are involved with an implicitly created auxiliary index and LOB table space
- Buffer pool and storage group that are involved with implicitly created XML indexes and XML table space
- Trigger
- Function

- Procedure
- Sequence
- View
- Trusted context
- JAR
- Role
- Distinct type
- Table, buffer pool, and storage group for an implicitly created unique key index, primary key index, or ROWID index.

Related reference

Privileges required for common job roles and tasks

The labels of the administrative authorities often suggest the job roles and responsibilities of the users who are empowered with the authorities.

Privileges required for handling plans and packages

An ID, or a role that runs in a trusted context, needs specific privileges to perform actions on plans and packages.

Privileges required for using dynamic SQL statements An ID needs specific privileges to issue dynamic SOL statements.

Privileges required for handling plans and packages

An ID, or a role that runs in a trusted context, needs specific privileges to perform actions on plans and packages.

GUPI The following table lists the IDs and describes the privileges that they need for performing each type of plan or package operation. A user-defined function, stored procedure, or trigger package does not need to be included in a package list. A trigger package cannot be deleted by FREE PACKAGE or DROP PACKAGE. The DROP TRIGGER statement must be used to delete the trigger package.

Table 34. Required privileges for basic operations on plans and packages			
Operation	ID or role	Required privileges	
Execute a plan	Primary ID, any secondary ID, or role	Any of the following privileges:	
		Ownership of the plan	
		 EXECUTE privilege for the plan 	
		DATAACCESS authority	
		SYSADM authority	
Bind embedded SQL	Package owner	Any of the following privileges:	
statements, for any bind operation		 Applicable privileges required by the statements 	
		 Authorities that include the privileges 	
		 Ownership that implicitly includes the privileges 	
		Object names include the value of QUALIFIER, where it applies.	
Operation	ID or role	Required privileges	
---	-----------------------	--	
BIND EXPLAIN	Plan or package owner	Any of the following privileges:	
without generating a		 Ownership of the plan or package 	
puchage		• BIND	
		• BINDAGENT	
		EXPLAIN privilege	
		• PACKADM	
		• SQLADM	
		 System DBADM authority 	
		• SYSCTRL	
		• SYSADM	
Include package in	Plan owner	Any of the following privileges:	
PKLIST		 Ownership of the package 	
		 EXECUTE privilege for the package 	
		 PACKADM authority over the package collection 	
		SYSADM authority	
BIND a new plan	Primary ID or role	Any of the following privileges:	
using the default		BINDADD privilege	
authorization ID		System DBADM authority	
		SYSCTRL authority	
		SYSADM authority	
BIND a new package using the default owner or primary authorization ID	Primary ID or role	If the value of the field BIND NEW PACKAGE on installation panel DSNTIPP is BIND, any of the following privileges:	
		 BIND privilege and CREATE IN privilege for the collection 	
		 PACKADM authority for the collection 	
		System DBADM authority	
		SYSADM or SYSCTRL authority	
		If BIND NEW PACKAGE is BINDADD, any of the following privileges:	
		 BINDADD privilege and either the CREATE IN or PACKADM privilege for the collection 	
		System DBADM authority	
		SYSADM or SYSCTRL authority	

Table 34. Required privileges for basic operations on plans and packages (continued)

Operation	ID or role	Required privileges
BIND REPLACE or	Primary ID, any secondary	Any of the following privileges:
REBIND for a	ID, or role	 Ownership of the plan or package
using the default		 BIND privilege for the plan or package
owner or primary		 BINDAGENT from the plan or package owner
authorization ID		 PACKADM authority for the collection (for a package only)
		System DBADM authority
		SYSADM or SYSCTRL authority.
BIND a new version of a package, with	Primary ID or role	If BIND NEW PACKAGE is BIND, any of the following privileges:
default owner		 BIND privilege on the package or collection
		 BINDADD privilege and CREATE IN privilege for the collection
		 PACKADM authority for the collection
		 System DBADM authority
		 SYSADM or SYSCTRL authority
		If BIND NEW PACKAGE is BINDADD, any of the following:
		 BINDADD privilege and either the CREATE IN or PACKADM privilege for the collection
		System DBADM authority
		SYSADM or SYSCTRL authority
FREE or DROP a	Primary ID, any secondary ID, or role	Any of the following privileges:
package		 Ownership of the package
		 BINDAGENT from the package owner
		 PACKADM authority for the collection
		System DBADM authority
		SYSADM or SYSCTRL authority
COPY a package	Primary ID, any secondary ID, or role	Any of the following:
		 Ownership of the package
		 COPY privilege for the package
		 BINDAGENT from the package owner
		PACKADM authority for the collection
		System DBADM authority
		SYSADM or SYSCTRL authority

Table 34. Required privileges for basic operations on plans and packages (continued)

Table 34. Required privileges for basic operations on plans and packages (continued)		
Operation	ID or role	Required privileges
FREE a plan	Primary ID, any secondary ID, or role	Any of the following privileges:
		Ownership of the plan
		 BIND privilege for the plan
		 BINDAGENT from the plan owner
		System DBADM authority
		SYSADM or SYSCTRL authority
Name a new OWNER other than the primary authorization ID for any bind operation	Primary ID, any secondary ID, or role	Any of the following privileges:
		• New owner is the primary or any secondary ID
		 BINDAGENT from the new owner
		 System DBADM authority (if SEPARATE_SECURITY is set to NO)
		 SYSADM or SYSCTRL authority (if SEPARATE_SECURITY is set to NO)

Notes:

- 1. The package for a user-defined function, stored procedure, or trigger package does not need to be included in a package list.
- 2. A trigger package cannot be deleted by FREE PACKAGE or DROP PACKAGE. The DROP TRIGGER statement must be used to delete the trigger package.

GUPI

Related concepts

Checking access authorization for data definition statements Db2 checks for the necessary authorization privileges and authorities when you use data definition statements on certain Db2 objects.

Related reference

Privileges required for common job roles and tasks The labels of the administrative authorities often suggest the job roles and responsibilities of the users who are empowered with the authorities.

Privileges required for using dynamic SQL statements An ID needs specific privileges to issue dynamic SQL statements.

Privileges required for using dynamic SQL statements

An ID needs specific privileges to issue dynamic SQL statements.

GUPI The following table lists the IDs and describes the privileges that they need for issuing each type of SQL statement:

Table 35. Required privileges for basic operations on dynamic SQL statements		
Operation	ID or role	Required privileges
GRANT	Current SQL ID or role	Any of the following privileges:
		 The applicable privilege with the grant option
		 An authority that includes the privilege, with the grant option (not needed for SYSADM or SYSCTRL)
		 Ownership that implicitly includes the privilege
REVOKE	Current SQL ID or role	Must either have granted the privilege that is being revoked, or hold SYSCTRL or SYSADM authority.
CREATE, for unqualified object name	Current SQL ID or role	Applicable table, database, or schema privilege
Qualify name of object created	ID or role named as owner	Applicable table or database privilege. The qualifier can be any ID at all and does not need to have any privilege if the current SQL ID or the role (if in a trusted context with the ROLE AS OBJECT OWNER AND QUALIFIER clause specified) has the SYSADM. system DBADM, or SYSCTRL authority (wherever applicable) or the DBADM or DBCTRL authority for the database (wherever applicable).
Other dynamic SQL if DYNAMICRULES uses run behavior	All primary IDs, role, secondary IDs, and the current SQL ID together	As required by the statement. Unqualified object names are qualified by the value of the special register CURRENT SQLID.
Other dynamic SQL if DYNAMICRULES uses bind behavior	Plan or package owner	As required by the statement. DYNAMICRULES behavior determines how unqualified object names are qualified.
Other dynamic SQL if DYNAMICRULES uses define behavior	Function or procedure owner	As required by the statement. DYNAMICRULES behavior determines how unqualified object names are qualified.
Other dynamic SQL if DYNAMICRULES uses invoke behavior	ID of the SQL statement that invoked the function or procedure or role	As required by the statement. DYNAMICRULES behavior determines how unqualified object names are qualified.

GUPI

Related concepts

Checking access authorization for data definition statements Db2 checks for the necessary authorization privileges and authorities when you use data definition statements on certain Db2 objects.

Related reference

Privileges required for common job roles and tasks The labels of the administrative authorities often suggest the job roles and responsibilities of the users who are empowered with the authorities.

Privileges required for handling plans and packages

An ID, or a role that runs in a trusted context, needs specific privileges to perform actions on plans and packages.

Managing administrative authorities

Db2 provides a range of auditable administrative authorities that help you control access to sensitive business data. The granularity and flexibility in Db2 administrative authority help you achieve adequate separation of duties and responsibilities and prevent a single user from possessing unlimited privileges.

Depending on the setting of the SEPARATE_SECURITY subsystem parameter, you can separate Db2 security administration, database administration, and data access control from system administration. You can set the parameter by using the SEPARATE SECURITY field on panel DSNTIPP1 during installation or migration. The SEPARATE_SECURITY subsystem parameter does not apply to or affect users with installation SYSADM authority.

If you set SEPARATE_SECURITY to YES, the SYSADM authority can no longer manage security-related objects (such as roles, trusted contexts, row permissions, and column masks) or have the ability to grant or revoke privileges that are granted by others. The SYSCTRL authority can no longer manage roles or grant or revoke privileges that are granted by others, either. Instead, the SECADM authority will manage all security-related objects. The SECADM and ACCESSCTRL authorities control access to all databases even though they cannot access any user data in the databases.

In addition, the SYSADM authority can only set CURRENT SQLID to its primary or one of its secondary authorization IDs. The SYSADM, SYSCTRL, and system DBADM authorities can only set BIND OWNER to the primary or one of the secondary authorization IDs of the binder. Finally, the SYSADM authority will not have implicit insert, update, delete access to the SYSIBM.SYSAUDITPOLICIES table.

If you set SEPARATE_SECURITY to NO (which is the default), the SYSADM authority retains all the existing privileges and responsibilities and gets implicit privileges of the SECADM authority. In other words, the SYSADM authority continues to be the security administrator and manage all security-related objects, perform grants, and revoke privileges that are granted by others. In addition, it gets implicit insert, update, delete access on the SYSIBM. SYSAUDITPOLICIES table and is able to set CURRENT SQLID and BIND OWNER to any value.

Setting SEPARATE_SECURITY to NO also allows the SYSCTRL authority to get most of the implicit privileges of the ACCESSCTRL authority. SYSCTRL can manage roles, perform certain grants, revoke privileges that are granted by others, and set BIND OWNER to any value.

The installation SYSADM authority is not affected by the setting of the SEPARATE_SECURITY parameter. Installation SYSADM can manage security-related objects, grant and revoke authorities or privileges, and set CURRENT SQLID and BIND OWNER to any value regardless of the setting of the SEPARATE_SECURITY parameter.

Related reference

Administrative authorities in Db2 for z/OS Each administrative authority in Db2 for z/OS is vested with a specific set of privileges.

Separating the SYSADM authority

Granularity and flexibility in Db2 administrative authority allows you to separate security administration, database administration, and data access control from system administration. Separating the SYSADM authority (a combination of security and system administration) can help you simplify your system administration and strengthen the security administration of your business data.

Procedure

GUPT To separate the SYSADM authority, choose the system and security administration model that best meets the security needs of your business:

 Maintain the existing system administration model in which the SYSADM authority continues to be able to perform security administration You must first set the SEPARATE_SECURITY subsystem parameter to NO (which is the default value) during installation or migration. As shown below, this setting allows the system administrator to continue to be the security administrator and the SYSADM authority to get implicit privileges of the SECADM authority.



When SEPARATE_SECURITY is set to NO, users with SYSADM authority can manage most security objects, perform grants, and revoke privileges that are granted by others, and users with SYSCTRL authority can manage roles, perform most grants, and revoke privileges that are granted by others.

However, the following newer security capabilities always require explicit SECADM authority, even if SEPARATE_SECURITY is set to NO:

- TRANSFER OWNERSHIP statements
- Stopping secure audit policies
- Separate security administration from system administration (SYSADM)

You must first set the SEPARATE_SECURITY system parameter on panel DSNTIPP1 to YES during installation or migration. As shown below, this setting separates the security administration from the SYSADM authority. A system administrator can no longer manage access control, audit policies, or security-related objects, including roles and trusted contexts. The SYSCTRL authority can no longer manage roles. Neither the SYSADM authority nor the SYSCTRL authority can grant or revoke privileges that are granted by others.



In addition to setting the SEPARATE_SECURITY system parameter, you also need to set one of the system SECADM parameters to an authorization ID or a role during installation that will perform security administration. To ensure complete separation of system and security administration, do not set the SECADM system parameter to a SYSADM ID. Instead, set SECADM to a SECADM ID and installation SYSADM to an installation SYSADM ID.

• Separate system database administration with the data access authority and the access control authority from system and security administration.

Db2 provides both the system DBADM authority and the DBADM authority, with each having a different set of privileges. The system DBADM authority allows you to manage objects in all databases across a Db2 subsystem, but doesn't give you access to the data in the databases. In addition, with the system DBADM authority, you can perform administrative tasks and issue commands for a Db2 subsystem, but you don't have the authority to execute objects or the ability to grant or revoke privileges.

Unlike the system DBADM authority, the DBADM authority allows you to manage objects in a specific database and gives you access to the data in that database. You also get the privileges of the DBCTRL and DBMAINT authorities over the same database.

If you want the system database administrators to have access to data and the ability to grant and revoke privileges, you can grant them the system DBADM, DATAACCESS, and ACCESSCTRL authorities, as shown below. By default, the DATAACCESS and ACCESSCTRL authorities are granted when the system DBADM authority is granted.



System Administration

Requires SYSOPR, ARCHIVE, BSDS, CREATESG, STOSPACE

If you want the system database administrators to have access to data, but not the ability to grant or revoke privileges, you can grant them the system DBADM and DATAACCESS authorities, but not the ACCESSCTRL authority, as shown below. You can also grant system database administrators the SYSOPR authority and the privileges to perform ARCHIVE, BSDS, CREATESG, STOSPACE, or other system-related tasks.

System DBADM	SECADM		
Database Administrator	Security Administrator		
Data Access	Access Control		
DATAACCESS	ACCESSCTRL		
System Administration			

Requires SYSOPR, ARCHIVE, BSDS, CREATESG, STOSPACE

• Separate system database administration from the data access authority, the access control authority, security administration, and system administration.



Requires SYSOPR, ARCHIVE, BSDS, CREATESG, STOSPACE

If you want the system database administrators to manage database objects, but have no access to data or the ability to grant and revoke privileges, you can grant them the system DBADM authority, but not the SYSADM, DATAACCESS, or ACCESSCTRL authority.

Related reference

System DBADM administrative authority

The system DBADM authority allows an administrator, an authorization ID or a role, to manage databases across a Db2 subsystem, while having no access to the data in the databases. In other words, the system DBADM authority enables you to create, alter, and drop Db2 objects and issue commands for a Db2 subsystem, but does not give you the authority to access the data or the ability to grant or revoke privileges.

SECADM administrative authority

The SECADM authority enables you to manage security-related objects in Db2 and control access to all database resources. It does not have any inherent privilege to access data stored in the objects, such as tables.

ACCESSCTRL administrative authority

The ACCESSCTRL authority allows you to grant explicit privileges to authorization IDs or roles by issuing SQL GRANT statements. It enables you to grant privileges on all objects and resources, except the CREATE_SECURE_OBJECT privilege and the system DBADM, DATAACCESS, and ACCESSCTRL authorities.

DATAACCESS administrative authority

The DATAACCESS authority allows you to access and update data in user tables, views, and materialized query tables in a Db2 subsystem. It also allows you to execute plans, packages, functions, and procedures.

SQLADM administrative authority

The SQLADM authority allows you to issue the SQL EXPLAIN statements, issue certain commands, run the RUNSTATS and MODIFY STATISTICS utilities on all user databases, and execute system-defined routines, such as stored procedures or functions, and any packages that are executed within the routines.

Migrating the SYSADM authority

To take advantage of the granularity of Db2 administrative authority and simplify your system database administration, you can separate the privileges of the SYSADM authority and migrate them to other administrative authorities based on the security needs of your business. This will allow you to eliminate or minimize the need for granting the SYSADM authority.

About this task

If you decide to separate the SYSADM authority into the SECADM and other administrative authorities, consider setting the SEPARATE_SECURITY system parameter on panel DSNTIPP1 to YES during installation or migration. This setting enables you to achieve complete separation of administrative duties.

Procedure

To migrate the SYSADM authority that is currently assigned to authorization IDs or roles:

1. In your security policies, identify the administration model that you will use for separating the SYSADM authority and define the criteria for assigning specific administrative authorities to specific authorization IDs or roles.

Suppose that you choose the following model to separate the current SYSADM authority into the system DBADM, SECADM, DATAACCESS, ACCESSCTRL, and SQLADM authorities:



You can define the following set of criteria for granting administrative authorities:

- The system DBADM authority can be granted to database administrators who need to manage objects
- The DATAACCESS authority can be granted to database administrators who need to access data
- The ACCESSCTRL authority can be granted to database administrators who need to control access to Db2 subsystems
- The SECADM authority can be assigned (during installation) to security administrators who perform security administration and manage access control
- The SQLADM authority can be assigned to performance analysts who are responsible for analyzing the performance of Db2 subsystems
- The EXPLAIN privilege can be granted to application architects who need to explain SQL statements or collect metadata information about the statements
- The SYSOPR authority and the ARCHIVE, BSDS, CREATESG, and STOSPACE privileges can be granted to system administrators for performing system administrative tasks.
- 2. Perform a query to list all the users and roles that are currently granted the SYSADM authority.

The SYSADM authority can be granted to authorization IDs or roles. You can query the catalog and find out the users and roles who are currently granted the SYSADM authority.

Suppose that your query returns a list of the following six users, user groups, or roles that are assigned the SYSADM authority:

- John (Security administrator)
- Sally (Application Architect)
- Bob (Performance Analyst)

- ApplProgrammer_role (Application Programmer role)
- SysAdmin_Role (System administrator role)
- DBAdmGrp (database administrator group).
- 3. Divide the responsibilities of the SYSADM authority and grant to different IDs or roles based on your security policies, as shown below:
 - John is granted the SECADM authority to perform security-related administration tasks and control access to Db2.
 - Sally is granted the DATAACCESS authority because she requires DML privileges on tables during application development, but she does not need access control or database administration.
 - Bob is granted the SQLADM authority who analyzes the performance of Db2 subsystems, but does not need access to data.
 - ApplProg_role is granted the EXPLAIN privilege because all application programmers need to explain SQL statements and collect metadata information in trusted context definitions.
 - DBAdmGrp is granted the system DBADM authority for managing and maintaining objects. Since database administrators belong to the DBAdmGrp RACF group, they should not be able to access data or grant and revoke privileges.
 - SysAdmin_role is granted the SYSOPR authority and the ARCHIVE, BSDS, CREATESG, and STOSPACE privileges to perform system administrative tasks.
- 4. Revoke the SYSADM authority from all current IDs or roles.

Once the authorities are granted, you can revoke the SYSADM authority from John, Sally, Bob, ApplProgrammer_ role and DBAdmGrp. Revoking the SYSADM authority causes the revoking of dependent privileges, by default. If you want to leave the grants that they had made, you can issue the REVOKE statement with the NOT INCLUDING DEPENDENT PRIVILEGES clause, assuming the REVOKE_DEP_PRIVILEGES system parameter is set to SQLSTMT.

5. Once the SYSADM authority is revoked, set the SEPARATE_SECURITY system parameter to YES on panel DSNTIPP1.

With the installation SYSADM authority, you can perform an online change of the SEPARATE_SECURITY system parameter and set it to YES. This further ensures that SYSADM is separated into SECADM and other authorities.

Related reference

System DBADM administrative authority

The system DBADM authority allows an administrator, an authorization ID or a role, to manage databases across a Db2 subsystem, while having no access to the data in the databases. In other words, the system DBADM authority enables you to create, alter, and drop Db2 objects and issue commands for a Db2 subsystem, but does not give you the authority to access the data or the ability to grant or revoke privileges.

SECADM administrative authority

The SECADM authority enables you to manage security-related objects in Db2 and control access to all database resources. It does not have any inherent privilege to access data stored in the objects, such as tables.

ACCESSCTRL administrative authority

The ACCESSCTRL authority allows you to grant explicit privileges to authorization IDs or roles by issuing SQL GRANT statements. It enables you to grant privileges on all objects and resources, except the CREATE_SECURE_OBJECT privilege and the system DBADM, DATAACCESS, and ACCESSCTRL authorities.

DATAACCESS administrative authority

The DATAACCESS authority allows you to access and update data in user tables, views, and materialized query tables in a Db2 subsystem. It also allows you to execute plans, packages, functions, and procedures.

SQLADM administrative authority

The SQLADM authority allows you to issue the SQL EXPLAIN statements, issue certain commands, run the RUNSTATS and MODIFY STATISTICS utilities on all user databases, and execute system-defined routines, such as stored procedures or functions, and any packages that are executed within the routines.

Creating roles or trusted contexts with the SECADM authority

If you separate security administration from system and database administration, you need to have the SECADM authority to manage security-related objects in Db2 and control access to all database objects and resources in a subsystem.

Before you begin

To separate security administration from system administration, you must set the SEPARATE_SECURITY system parameter on panel DSNTIPP1 to YES during installation or migration.

If you set field 1 (RESTART or DEFER) to DEFER and set field 2 (objects to restart or defer) to ALL in installation panel DSNTIPS, you cannot use trusted connections.

About this task

With the separation of security administration from system administration, the SYSADM authority can no longer define roles or trusted contexts or manage any other security-related objects; the SECADM authority is, instead, responsible for performing security administrative tasks, including creating roles and trusted contexts, activating row and column access control, and granting security-related authorities and privileges on objects.

Procedure

To create roles or trusted contexts with the SECADM authority:

• Issue the following CREATE ROLE statement to create CTXROLE by using an authorization ID or role that is given the SECADM authority.

If SEPARATE_SECURITY is set to YES, the SECADM authority is required to create roles and trusted contexts.

GUPI

CREATE ROLE CTXROLE;

GUPI

Db2 checks to make sure that you have the required privilege to create roles and, upon successful verification, allows the creation of role CTXROLE.

• Issue the following CREATE TRUSTED CONTEXT statement to create CTX1 and associate CTXROLE with CTX1:

GUPI

```
CREATE TRUSTED CONTEXT CTX1
BASED UPON CONNECTION USING SYSTEM AUTHID USER1
DEFAULT ROLE CTXROLE
ATTRIBUTES (ADDRESS '9.67.40.219')
WITH USE FOR USER2, USER3
ENABLE;
```

GUPI

Db2 checks to make sure that you have the required privilege to create trusted contexts and, upon successful verification, allows the creation of trusted context CTX1.

Related reference

SECADM administrative authority

The SECADM authority enables you to manage security-related objects in Db2 and control access to all database resources. It does not have any inherent privilege to access data stored in the objects, such as tables.

Altering tables with the system DBADM authority

The system DBADM authority separates object management from data access and access control. It allows object management without requiring the ownership of the object in a Db2 subsystem.

About this task

Suppose that you are a database administrator DB2ADMIN1 and need to alter TABLE1, but do not have any table privileges on the table. You must first be granted the system DBADM authority before you can alter the table.

Procedure

To alter tables with the system DBADM authority:

1. Obtain the system DBADM authority from a security administrator

An authorization ID or role with the SECADM authority can grant you the system DBADM authority by issuing the following statement:

GUPI

GRANT DBADM WITHOUT DATAACCESS WITHOUT ACCESSCTRL ON SYSTEM TO DB2ADMIN1;

GUPI

Db2 inserts a row in SYSIBM.SYSUSERAUTH with the column SDBADMAUTH set to 'Y', where column GRANTEE is set to DB2ADMIN1.

2. With the system DBADM authority, issue the ALTER TABLE statement to alter table TABLE1.

Db2 checks to make sure that you have the required privilege set, including the ALTER TABLE privilege that is allowed by the system DBADM authority. The table is altered successfully.

Related reference

System DBADM administrative authority

The system DBADM authority allows an administrator, an authorization ID or a role, to manage databases across a Db2 subsystem, while having no access to the data in the databases. In other words, the system DBADM authority enables you to create, alter, and drop Db2 objects and issue commands for a Db2 subsystem, but does not give you the authority to access the data or the ability to grant or revoke privileges.

Accessing data with the DATAACCESS authority

A database administrator must have the DATAACCESS authority to access data in all user tables, views, and materialized query tables in a Db2 subsystem.

About this task

Suppose that you are a database administrator DB2ADMIN1 and need access to data in TABLE1. You must first be granted the DATAACCESS authority.

Procedure

To access data with the DATAACCESS authority:

1. Obtain the DATAACCESS authority from a security administrator.

The SECADM (an authorization ID or role) can grant you the DATAACCESS authority by issuing the following statement:

GUPI

GRANT DATAACCESS ON SYSTEM TO DB2ADMIN1;

GUPI

Db2 inserts a row in SYSIBM.SYSUSERAUTH with the new column DATAACCESSAUTH set to 'Y', where column GRANTEE is set DB2ADMIN1.

2. After obtaining the DATAACCESS authority, issue an SQL SELECT statement to select from table TABLE1.

Db2 checks to make sure that you have the required privilege set, including the SELECT privilege that is granted by the DATAACCESS authority. The SELECT statement completes successfully.

Related reference

DATAACCESS administrative authority

The DATAACCESS authority allows you to access and update data in user tables, views, and materialized query tables in a Db2 subsystem. It also allows you to execute plans, packages, functions, and procedures.

Granting and revoking privileges with the ACCESSCTRL authority

If you separate database administration from system and security administration, a database administrator must have the ACCESSCTRL or SECADM authority to grant or revoke user privileges in a Db2 subsystem.

About this task

GUPI The ACCESSCTRL authority allows you to grant and revoke (BY clause) privileges on all resources in a Db2 subsystem. However, it cannot grant the CREATE_SECURE_OBJECT privilege or the system DBADM, DATAACCESS, and ACCESSCTRL authorities.

If you are a database administrator DB2ADMIN1 and need to grant application developer APPDEV1 load privileges on DBTEMP1, you must first have the ACCESSCTRL authority for yourself.

Procedure

To grant or revoke privileges with the ACCESSCTRL authority:

1. Obtain the ACCESSCTRL authority from a security administrator.

The SECADM (an authorization ID or role) can grant you the ACCESSCTRL authority by issuing the following statement:

GRANT ACCESSCTRL ON SYSTEM TO DB2ADMIN1;

Db2 inserts a row in SYSIBM.SYSUSERAUTH with the new column ACCESSCTRLAUTH set to 'Y', where column GRANTEE is set to DB2ADMIN.1.

You can specify WITH GRANT OPTION when you issue the GRANT statement, but the option is ignored when the authority is ACCESSCTRL, DBADM, or DATAACCESS.

2. After obtaining the ACCESSCTRL authority, grant APPDEV1 load privileges on DBTEMP1 by issuing the following GRANT statement:

GRANT LOAD ON DATABASE DBTEMP1 TO APPDEV1;

Db2 checks to make sure that you have the required privilege set, including the GRANT privilege that is allowed by the ACCESSCTRL authority. The GRANT statement completes successfully.

Related reference

ACCESSCTRL administrative authority

The ACCESSCTRL authority allows you to grant explicit privileges to authorization IDs or roles by issuing SQL GRANT statements. It enables you to grant privileges on all objects and resources, except the CREATE_SECURE_OBJECT privilege and the system DBADM, DATAACCESS, and ACCESSCTRL authorities.

Managing explicit privileges

You can use the SQL GRANT and REVOKE statements to grant and remove privileges if you enable authorization checking during Db2 installation. You can grant to or revoke privileges from authorization IDs or roles if they run in a trusted context. You can revoke only privileges that are explicitly granted.

About this task

You can grant privileges in the following ways:

- Grant a specific privilege on one object in a single statement
- Grant a list of privileges
- Grant privileges on a list of objects
- Grant ALL, for all the privileges of accessing a single table, or for all privileges that are associated with a specific package

If you grant privileges on a procedure or a package, all versions of that procedure or package have those privileges. Db2 ignores duplicate grants and keeps only one record of a grant in the catalog. The suppression of duplicate records applies not only to explicit grants, but also to the implicit grants of privileges that are made when a package is created.

For example, suppose that Susan grants the SELECT privilege on the EMP table to Ray. Then suppose that Susan grants the same privilege to Ray again, without revoking the first grant. When Susan issues the second grant, Db2 ignores it and maintains the record of the first grant in the catalog.

Database privileges that are granted on DSNDB04 apply to all implicitly created databases. For example, if you have the DBADM authority on DSNDB04, you can select data from any table in any implicitly created database. If you have the STOPDB privilege on DSNDB04, you can stop any implicitly created database. However, you cannot grant the same authorities or privileges to others on any implicitly created database.

Related information

Managing implicit privileges through object ownership Ownership of an object carries with it a set of related privileges on the object. Db2 provides separate controls for creation and ownership of objects.

Granting privileges to a role

You can grant privileges to a role by using the GRANT statement. You can associate primary authorization IDs with a role in the definition of the trusted context and then use the GRANT statement with the ROLE option to grant privileges to the role.

About this task

You can improve access control by granting privileges to roles. When you grant certain privileges to a role, you make those privileges available to all users that are associated with the role in the specific trusted context.

You can also simplify the administration of granting privileges by using roles rather than individual authorization IDs. To make a role a grantor, you need to specify the ROLE AS OBJECT OWNER clause when you define the trusted context. For a static GRANT statement, the grantor is the role that owns the plan or package. For a dynamic GRANT statement, the role for the primary authorization ID that executes the GRANT statement becomes the grantor.

Granting privileges to the PUBLIC ID

You can grant to the PUBLIC ID privileges or authorities other than CREATE_SECURE_OBJECT, system DBADM, DATAACCESS, or ACCESSCTRL.

About this task

When you grant privileges to PUBLIC, the privileges become available to all IDs at the local Db2 site, including the owner IDs of packages that are bound from a remote location. Public access is generally not a good practice when it comes to the protection of sensitive business data and critical system resources. Many compliance requirements prohibit public access to any system components. For example, the Payment Card Industry (PCI) Data Security Standard Requirements and Security Assessment Procedures restrict the use of PUBLIC.

When you grant any privilege to PUBLIC, Db2 catalog tables record the grantee of the privilege as PUBLIC. Db2 also grants the following implicit table privileges to PUBLIC for declared temporary tables:

- All table privileges on the tables and the authority to drop the tables
- The CREATETAB privilege to define temporary tables in the work file database
- The USE privilege to use the table spaces in the work file database

You do not need any additional privileges to access the work file database and the temporary tables that are in it. You cannot grant or revoke table privileges for temporary tables. The Db2 catalog does not record these implicit privileges for declared temporary tables.

Because PUBLIC is a special identifier that is used by Db2 internally, you should not use PUBLIC as a primary ID or secondary ID. When a privilege is revoked from PUBLIC, authorization IDs to which the privilege was specifically granted retain the privilege.

However, when an ID uses PUBLIC privileges to perform actions, the actions and the resulting objects depend on the privileges that are currently in effect for PUBLIC. If PUBLIC loses a privilege, objects that are created with that privilege can be dropped or invalidated. The following examples demonstrate how certain objects depend on PUBLIC not losing its privileges.

Example

Suppose that Juan has the ID USER1 and that Meg has the ID USER2. Juan creates a table TAB1 and grants ALL PRIVILEGES on it to PUBLIC. Juan does not explicitly grant any privileges on the table to Meg's ID, USER2. Using the PUBLIC privileges, Meg creates a view on TAB1. Because the ID USER2 requires the SELECT privilege on TAB1 to create the view, the view is dropped if PUBLIC loses the privilege.

Related tasks

Granting privileges to remote users

A query that arrives at your local Db2 subsystem through the distributed data facility (DDF) is accompanied by an authorization ID. After connection processing, the ID can be translated to another value and be associated with secondary authorization IDs.

Granting privileges to remote users

A query that arrives at your local Db2 subsystem through the distributed data facility (DDF) is accompanied by an authorization ID. After connection processing, the ID can be translated to another value and be associated with secondary authorization IDs.

About this task

Db2 also uses the ID to determine if the connection is associated with a trusted context. As the end result of these processes, the remote query is associated with a set of IDs that is known to your local Db2 subsystem. You assign privileges to these IDs in the same way that you assign privileges to IDs that are associated with local queries.

Related tasks

Granting privileges to the PUBLIC ID You can grant to the PUBLIC ID privileges or authorities other than CREATE_SECURE_OBJECT, system DBADM, DATAACCESS, or ACCESSCTRL.

Granting privileges through views

You can grant most table privileges (except ALTER, REFERENCES, TRIGGER, and INDEX) on a view. By creating a view and granting privileges through it, you can give an ID access to only a specific combination of data.

About this task

The ability to grant privileges through views is sometimes called *field-level access control* or *field-level sensitivity*.

Suppose that you want the ID MATH110 to be able to extract the following column data from the sample employee table for statistical investigation: HIREDATE, JOB, EDLEVEL, SEX, SALARY, BONUS, and COMM for DSN8910.EMP. However, you want to impose the following restrictions:

- · No access to employee names or identification numbers
- No access to data for employees hired before 1996
- No access to data for employees with an education level less than 13
- · No access to data for employees whose job is MANAGER or PRES

You can create and name a view that shows exactly that combination of data.

Procedure

To grant privileges to the view that you create:

1. Issue the following CREATE statement to create the view that you want:

GUPI

```
CREATE VIEW SALARIES AS
SELECT HIREDATE, JOB, EDLEVEL, SEX, SALARY, BONUS, COMM
FROM DSN8C10.EMP
WHERE HIREDATE > '1995-12-31' AND
EDLEVEL >= 13 AND
JOB <> 'MANAGER' AND
JOB <> 'PRES';
```

GUPI

2. Issue the following statement to grant the SELECT privilege on the SALARIES view to MATH110:

GUPI

GRANT SELECT ON SALARIES TO MATH110;

GUPI

Results

After you grant the privilege, MATH110 can execute SELECT statements on the restricted set of data only. Alternatively, you can give an ID access to only a specific combination of data by using multilevel security with row-level granularity.

Related tasks

Granting privileges with the GRANT statement You can assign privileges to an ID or a role by issuing the GRANT statement.

Revoking privileges with the REVOKE statement

You can use the REVOKE statement to remove the privileges that you explicitly grant to an ID or a role.

Granting privileges through administrative authorities

A Db2 administrative authority is generally vested with a predefined group of privileges. If you need to grant a user a specific set of privileges that are already included in an authority, you can grant the user the authority, instead of individual privileges.

About this task

For each administrative authority that you grant, Db2 adds a row in the system authorization table and sets the corresponding column to Y or G. For example, if you grant a user the SYSOPR authority on a database, Db2 adds a row in the SYSIBM.SYSUSERAUTH table and sets the SYSOPRAUTH column to Y or G. In addition, Db2 sets the columns for the DISPLAY, RECOVER, STOPALL and TRACE privileges to Y or G because these privileges are included in the SYSOPR authority.

If you include other privileges in the same GRANT statement for the SYSOPR authority, Db2 adds a corresponding row for each of the additional privileges in the SYSIBM.SYSUSERAUTH table. For example, if you include SYSOPR and MONITOR2 on the same GRANT statement, Db2 adds two rows in the SYSIBM.SYSUSERAUTH table, one for the SYSOPR authority and the other for the MONITOR2 privilege.

Related reference

Administrative authorities in Db2 for z/OS Each administrative authority in Db2 for z/OS is vested with a specific set of privileges.

Granting privileges with the GRANT statement

You can assign privileges to an ID or a role by issuing the GRANT statement.

About this task

Suppose that the Spiffy Computer Company wants to create a database to hold information that is usually posted on hallway bulletin boards. For example, the database might hold notices of upcoming holidays and bowling scores.

To create and maintain the tables and programs that are needed for this application, the Spiffy Computer Company develops the security plan shown in the following diagram.



Figure 3. Security plan for the Spiffy Computer Company

The Spiffy Computer Company's system of privileges and authorities associates each role with an authorization ID. For example, the System Administrator role has the ADMIN authorization ID.

User ID: ADMIN Authority: SYSADM Privileges: Ownership of SG1

GUPT The system administrator uses the ADMIN authorization ID, which has the SYSADM authority, to create a storage group (SG1) and to issue the following statements:

1. GRANT PACKADM ON COLLECTION BOWLS TO PKA01 WITH GRANT OPTION;

This statement grants to PKA01 the CREATE IN privilege on the collection BOWLS and BIND, EXECUTE, and COPY privileges on all packages in the collection. Because ADMIN used the WITH GRANT OPTION clause, PKA01 can grant those privileges to others.

2. GRANT CREATEDBA TO DBA01;

This statement grants to DBA01 the privilege to create a database and to have DBADM authority over that database.

3. GRANT USE OF STOGROUP SG1 TO DBA01 WITH GRANT OPTION;

This statement allows DBA01 to use storage group SG1 and to grant that privilege to others.

4. GRANT USE OF BUFFERPOOL BPO, BP1 TO DBA01 WITH GRANT OPTION;

This statement allows DBA01 to use buffer pools BP0 and BP1 and to grant that privilege to others.

5. GRANT CREATE IN COLLECTION DSN8CC91 TO ROLE ROLE1;

This statement grants to ROLE1 the privilege to create new packages in collections DSN8CC91.

GUPI

User ID: PKA01 Authority: PACKADM over the collection BOWLS

The package administrator, PKA01, controls the binding of packages into collections. PKA01 can use the CREATE IN privilege on the collection BOWLS and the BIND, EXECUTE, and COPY privileges on all packages in the collection. PKA01 also has the authority to grant these privileges to others.

User ID: DBA01 Authority: DBADM over DB1 Privileges: CREATE DBA Use of SG1 with GRANT Use of BP0 and BP1 with GRANT Ownership of DB1

The database administrator, DBA01, using the CREATEDBA privilege, creates the database DB1. When DBA01 creates DB1, DBA01 automatically has DBADM authority over the database.

User ID: DBUTIL1, DBUTIL2 Authority: DBCTRL over DB1

The database administrator at Spiffy Computer Company wants help with running the COPY and RECOVER utilities. Therefore DBA01 grants DBCTRL authority over database DB1 to DBUTIL1 and DBUTIL2.

GUPI To grant DBCTRL authority, the database administrator issues the following statement:

GRANT DBCTRL ON DATABASE DB1 TO DBUTIL1, DBUTIL2;

GUPI

Related tasks Granting privileges through views

76 Db2 12 for z/OS: Managing Security (Last updated: 2024-09-06)

You can grant most table privileges (except ALTER, REFERENCES, TRIGGER, and INDEX) on a view. By creating a view and granting privileges through it, you can give an ID access to only a specific combination of data.

Granting privileges to secondary IDs

The Spiffy Computer Company uses RACF to manage external access to Db2. Therefore, Spiffy can use secondary authorization IDs to define user groups and associate primary authorization IDs with those user groups.

About this task

The primary authorization IDs are the RACF user IDs. The secondary authorization IDs are the names of the groups with which the primary IDs are associated.

Spiffy can grant Db2 privileges to primary IDs indirectly, by granting privileges to secondary IDs that are associated with the primary IDs. This approach associates privileges with a *functional ID* rather than an *individual ID*. Functional IDs, also called group IDs, are granted privileges based on the function that certain job roles serve in the system. Multiple primary IDs can be associated with a functional ID and receive the privileges that are granted to that functional ID. In contrast, individual IDs are connected to specific people. Their privileges need to be updated as people join the company, leave the company, or serve different roles within the company. Functional IDs have the following advantages:

• Functional IDs reduce system maintenance because they are more permanent than individual IDs. Individual IDs require frequent updates, but each functional ID can remain in place until Spiffy redesigns its procedures.

Example: Suppose that Joe retires from the Spiffy Computer Company. Joe is replaced by Mary. If Joe's privileges are associated with functional ID DEPT4, those privileges are maintained in the system even after Joe's individual ID is removed from the system. When Mary enters the system, she will have all of Joe's privileges after her ID is associated with the functional ID DEPT4.

- Functional IDs reduce the number of grants that are needed because functional IDs often represent groups of individuals.
- Functional IDs reduce the need to revoke privileges and re-create objects when they change ownership.

Example: Suppose that Bob changes jobs within the Spiffy Computer Company. Bob's individual ID has privileges on many objects in the system and owns three databases. When Bob's job changes, he no longer needs privileges over these objects or ownership of these databases. Because Bob's privileges are associated with his individual ID, a system administrator needs to revoke all of Bob's privileges on objects and drop and re-create Bob's databases with a new owner. If Bob received privileges by association with a functional ID, the system administrator would only need to remove Bob's association with the functional ID.

Granting privileges to user groups

You can simplify the assignment and management of privileges by creating user groups and by granting privileges to the groups. In this way, you can efficiently assign the same set of privileges to all the users of a given group at the same time.

About this task

Suppose that the database administrator at Spiffy wants several employees in the Software Support department to create tables in the DB1 database. The database administrator creates DEVGROUP as a RACF group ID for this purpose. To simplify the process, the database administrator decides that each CREATE TABLE statement should implicitly create a unique table space for the table. Hence, DEVGROUP needs the CREATETAB privilege, the CREATETS privilege, the privilege to use the SG1 storage group and, the privilege to use one of the buffer pools, BP0, for the implicitly created table spaces. The following diagram shows this group and their privileges:

RACF Group ID: DEV GROUP Privileges: (All without GRANT) CREATETAB on DB1 CREATETS on DB1 Use of SG1 Use of BP0

GUPT The database administrator, DBA01, owns database DB1 and has the privileges to use storage group SG1 and buffer pool BP0. The database administrator holds both of these privileges with the GRANT option. The database administrator issues the following statements:

1. GRANT CREATETAB, CREATETS ON DATABASE DB1 TO DEVGROUP;

2. GRANT USE OF STOGROUP SG1 TO DEVGROUP;

3. GRANT USE OF BUFFERPOOL BPO TO DEVGROUP; GUPI

Because the system and database administrators at Spiffy still need to control the use of those resources, the preceding statements are issued without the GRANT option.

Three programmers in the Software Support department write and test a new program, PROGRAM1. Their IDs are PGMR01, PGMR02, and PGMR03. Each programmer needs to create test tables, use the SG1 storage group, and use one of the buffer pools. All of those resources are controlled by DEVGROUP, which is a RACF group ID.

Therefore, granting privileges over those resources specifically to PGMR01, PGMR02, and PGMR03 is unnecessary. Each ID should be associated with the RACF group DEVGROUP and receive the privileges that are associated with that functional ID. The following diagram shows the DEVGROUP and its members:

```
RACF group ID: DEVGROUP
Group members: PGMR01, PGMR02, PGMR03
```

The security administrator connects as many members as required to the group DEVGROUP. Each member can exercise all the privileges that are granted to the group ID.

Granting privileges for binding plans

Binding requires additional privileges. You must have the required privileges to bind a plan.

About this task

GUPT Suppose that three programmers can share the tasks that are done by the DEVGROUP ID. Someone creates a test table, DEVGROUP.T1, in database DB1 and loads it with test data. Someone writes a program, PROGRAM1, to display bowling scores that are contained in T1. Someone must bind the plan and packages that accompany the program.

Binding requires an additional privilege. ADMIN, who has the SYSADM authority, grants the required privilege by issuing the following statement:

GRANT BINDADD TO DEVGROUP;

GUPI

With that privilege, any member of the RACF group DEVGROUP can bind plans and packages that are to be owned by DEVGROUP. Any member of the group can rebind a plan or package that is owned by DEVGROUP. The following diagram shows the BINDADD privilege granted to the group:

```
RACF group ID: DEVGROUP
Privilege: BINDADD
```

The Software Support department proceeds to create and test the program.

Granting privileges for rebinding plans and packages

You can use the GRANT statement to grant privileges for rebuilding plans and packages.

About this task

Spiffy has a different set of tables, which contain actual data that is owned by the ROLE PRODCTN. PROGRAM1 is written with unqualified table names. For example, table T1 was referred to as simply T1, not DEVGROUP.T1. The new packages and plan must refer to table PRODCTN.T1. To move the completed program into production, someone must perform the following steps:

- Rebind the application plan with the owner PRODCTN.
- Rebind the packages into the collection BOWLS, again with the owner PRODCTN.

Spiffy gives that job to a production binder with the ID BINDER. BINDER needs privileges to bind a plan or package that DEVGROUP owns, to bind a plan or package with OWNER (PRODCTN), and to add a package to the collection BOWLS. BINDER acquires these abilities through its RACF DEVGROUP group and ROLE PRODCTN. ROLE PRODCTN needs to have all the necessary privileges.

Suppose that ID BINDER has ROLE PRODCTN when binding in a trusted context and that ROLE PRODCTN has the following privileges:

Db2 Role: PRODCTN Privileges: BINDADD CREATE IN collection BOWLS Privileges on SQL objects referenced in application

BINDER can bind plans and packages for owner ROLE PRODCTN because it performs binds in a trusted context with ROLE PRODCTN.

PACKADM, the package administrator for BOWLS, can grant the CREATE privilege with the following statement:

GUPI

GRANT CREATE ON COLLECTION BOWLS TO ROLE PRODCTN;

GUPI

With the plan in place, the database administrator at Spiffy wants to make the PROGRAM1 plan available to all employees by issuing the following statement:

GUPI

GRANT EXECUTE ON PLAN PROGRAM1 TO PUBLIC;

GUPI

More than one ID has the authority or privileges that are necessary to issue this statement. For example, ADMIN has SYSADM authority and can grant the EXECUTE privilege. Also, any ID in a trusted context with ROLE PRODCTN that owns PROGRAM1 can issue the statement. When EXECUTE is granted to PUBLIC, other IDs do not need any explicit authority on T1.

Finally, the plan to display bowling scores at Spiffy Computer Company is complete. The production plan, PROGRAM1, is created, and all IDs have the authority to execute the plan.

Granting privileges for accessing distributed data

Some time after the system and database administrators at Spiffy Computer Company implement their security plan, the company president tells them that other applications on other systems must connect to

the local Db2 subsystem. She wants people at every location to be able to access bowling scores through PROGRAM1 on the local subsystem.

Procedure

GUPI The administrators perform the following steps to enable access from all Spiffy locations:

- 1. Add a CONNECT statement to the program, naming the location at which table PRODCTN.T1 resides. In this case, the table and the package reside at only the central location.
- 2. Issue the following statement so that PKA01, who has PACKADM authority, can grant the required privileges to DEVGROUP:

GRANT CREATE IN COLLECTION BOWLS TO DEVGROUP;

- 3. Bind the SQL statements in PROGRAM1 as a package.
- 4. Bind the SQL statements in PROGRAM1 as a package by the package owner:

GRANT EXECUTE ON PACKAGE PROGRAM1 TO PUBLIC;

Results

Any system that is connected to the original Db2 location can run PROGRAM1 and execute the package by using DRDA access. However, if the remote system is another Db2, a plan must be bound there that includes the package in its package list. GUPI

Revoking privileges with the REVOKE statement

You can use the REVOKE statement to remove the privileges that you explicitly grant to an ID or a role.

Procedure

You can revoke the privilege that you grant to an ID by issuing the following statement:

REVOKE authorization-specification FROM auth-id

Generally, you can revoke only the privileges that you grant. If you revoke privileges on a procedure or package, the privileges are revoked from all versions of that procedure or package.

However, an ID with the SECADM or ACCESSCTRL authority can revoke a privilege that has been granted by another ID with the following statement:

REVOKE authorization-specification FROM auth-id BY auth-id

If the SEPARATE SECURITY system parameter on panel DSNTIPP1 is set to NO (the default) during installation, an ID with the SYSADM or SYSCTRL authority can revoke a privilege that has been granted by another ID. In this case, the SYSADM authority implicitly has the privileges of the SECADM authority, and the SYSCTRL authority implicitly has the privileges of the ACCESSCTRL authority.

The BY clause specifies the authorization ID that originally granted the privilege. If two or more grantors grant the same privilege to an ID, executing a single REVOKE statement does not remove the privilege. To remove it, each grant of the privilege must be revoked.

The WITH GRANT OPTION clause of the GRANT statement allows an ID to pass the granted privilege to others. If the privilege is removed from the ID, its revocation can cascade to others depending on the setting of the REVOKE DEP PRIV system parameter. For example, when a privilege is removed from authorization ID X, it is also removed from any ID to which X granted it, unless that ID also has the privilege from some other source.

¹ Db2 does not cascade a revoke of the SYSADM authority from the installation SYSADM authorization IDs.

Examples

Example

Suppose that DBA01 grants DBCTRL authority with the GRANT option on database DB1 to DBUTIL1. Then DBUTIL1 grants the CREATETAB privilege on DB1 to PGMR01. If DBA01 revokes DBCTRL from DBUTIL1, PGMR01 loses the CREATETAB privilege. If PGMR01 also granted the CREATETAB privilege to OPER1 and OPER2, they also lose the privilege.

Example

Suppose that PGMR01 from the preceding example created table T1 while holding the CREATETAB privilege. If PGMR01 loses the CREATETAB privilege, table T1 is not dropped, and the privileges that PGMR01 has as owner of the table are not deleted. Furthermore, the privileges that PGMR01 grants on T1 are not deleted. For example, PGMR01 can grant SELECT on T1 to OPER1 as long as PGMR01 owns of the table. Even when the privilege to create the table is revoked, the table remains, the privilege remains, and OPER1 can still access T1.

Example

Consider the following REVOKE scenario:

- 1. Grant #1: SYSADM, SA01, grants SELECT on TABLE1 to USER01 with the GRANT option.
- 2. Grant #2: USER01 grants SELECT on TABLE1 to USER02 with the GRANT option.
- 3. Grant #3: USER02 grants SELECT on TABLE1 back to SA01.
- 4. USER02 then revokes SELECT on TABLE1 from SA01.

The cascade REVOKE process of Grant #3 determines if SA01 granted SELECT to anyone else. It locates Grant #1. Because SA01 did not have SELECT from any other source, this grant is revoked. The cascade REVOKE process then locates Grant #2 and revokes it for the same reason. In this scenario, the single REVOKE action by USER02 triggers and results in the cascade removal of all the grants even though SA01 has the SYSADM authority. The SYSADM authority is not considered.

GUPI

Related tasks

Granting privileges with the GRANT statement

You can assign privileges to an ID or a role by issuing the GRANT statement.

"Revoking dependent privileges" on page 81

Revoking a privilege or authority, such as the SYSADM authority, from one user (an authorization ID or role) can result in the automatic removal of that privilege from other users and the privileges that it has granted. To prevent this, you can assign the REVOKE DEP PRIV parameter different values to control whether or not dependent privileges or authorities should be removed.

Revoking dependent privileges

Revoking a privilege or authority, such as the SYSADM authority, from one user (an authorization ID or role) can result in the automatic removal of that privilege from other users and the privileges that it has granted. To prevent this, you can assign the REVOKE DEP PRIV parameter different values to control whether or not dependent privileges or authorities should be removed.

Procedure

To specify the REVOKE DEP PRIV parameter, use one of the following approaches:

- Set REVOKE DEP PRIV to SQLSTMT (the default) if you want to use the dependent privileges clause on the REVOKE statement to control the revocation of dependent privileges.
 - Specify the NOT INCLUDING DEPENDENT PRIVILEGES clause on the REVOKE statement when you
 need to revoke a privilege or authority from a user but retain all the grants that are already made
 by that user. However, if the same privilege is later granted to that user again and subsequently
 revoked with the INCLUDING DEPENDENT PRIVILEGES clause specified, all dependent privileges
 including the grants made by the user earlier are removed.

- Specify the INCLUDING DEPENDENT PRIVILEGES clause (the default) when you need to revoke a
 privilege or authority (other than ACCESSCTRL, DATAACCESS, and system DBADM) from a user and
 remove all the privileges or authorities that are already granted by that privilege or authority.
- Set REVOKE DEP PRIV to YES if you want to remove all dependent privileges or authorities whenever you revoke a privilege or authority other than ACCESSCTRL, DATAACCESS, and system DBADM.

You will receive an error if you specify the NOT INCLUDING DEPENDENT PRIVILEGES clause on the REVOKE statement when you revoke a privilege or authority other than ACCESSCTRL, DATAACCESS, and system DBADM.

• Set REVOKE DEP PRIV to NO if you want to retain all dependent privileges or authorities whenever you revoke a privilege or authority.

You will receive an error if you specify the INCLUDING DEPENDENT PRIVILEGES clause on the REVOKE statement.

Results

If REVOKE DEP PRIV is set to NO or SQLSTMT or if the NOT INCLUDING DEPENDENT PRIVILEGES clause is specified on the REVOKE statement, dependent privileges or authorities are not revoked when a privilege or authority is revoked from a user. However, any packages, views, or MQTs that are owned by that user are invalidated, inoperative, or dropped.

Revoking dependent privileges does not occur in any of the following conditions:

- If the ACCESSCTRL authority is revoked from a user, grants made by the user are not revoked. However, if the user has already revoked its own grants prior to the removal of the ACCESSCTRL authority, that revocation of dependent privileges continues to take effect unless otherwise instructed through the REVOKE_DEP_PRIV parameter or the REVOKE statement.
- If the SECADM authority is removed from a user, grants made by the user are not revoked. However, if the user has already revoked its own grants prior to the removal of the SECADM authority, that revocation of dependent privileges continues to take effect unless otherwise instructed through the REVOKE_DEP_PRIV parameter or the REVOKE statement.

Revoking privileges granted by multiple IDs

A user can be granted the same privilege by multiple IDs at different times, but that privilege and any dependent privileges can be simultaneously revoked.

About this task

GUPT Suppose that DBUTIL1 grants the CREATETAB privilege to PGMR01 and that DBUTIL2 also grants the CREATETAB privilege to PGMR01. The second grant is recorded in the catalog, with its date and time, but it has no other effect until the grant from DBUTIL1 to PGMR01 is revoked. After the first grant is revoked, Db2 must determine the authority that PGMR01 used to grant CREATETAB to OPER1. The following diagram illustrates the situation; the arrows represent the granting of the CREATETAB privilege.

DBUTIL2 Time 2 DBUTIL1 Time 1 PGMR01 Time 3 OPER1

Figure 4. Authorization granted by two or more IDs

Suppose that DBUTIL1 issues the GRANT statement at Time 1 and that DBUTIL2 issues the GRANT statement at Time 2. DBUTIL1 and DBUTIL2 both use the following statement to issue the grant:

GRANT CREATETAB ON DATABASE DB1 TO PGMR01 WITH GRANT OPTION;

At Time 3, PGMR01 grants the privilege to OPER1 by using the following statement:

GRANT CREATETAB ON DATABASE DB1 TO OPER1;

After Time 3, DBUTIL1's authority is revoked, along with all of the privileges and authorities that DBUTIL1 granted. However, PGMR01 also has the CREATETAB privilege from DBUTIL2, so PGMR01 does not lose the privilege. The following criteria determine whether OPER1 loses the CREATETAB privilege when DBUTIL1's authority is revoked:

- If Time 3 *comes after* Time 2, OPER1 does not lose the privilege. The recorded dates and times show that, at Time 3, PGMR01 could have granted the privilege entirely on the basis of the privilege that was granted by DBUTIL2. That privilege was not revoked.
- If Time 3 *precedes* Time 2, OPER1 does lose the privilege. The recorded dates and times show that, at Time 3, PGMR01 could have granted the privilege only on the basis of the privilege that was granted by DBUTIL1. That privilege was revoked, so the privileges that are dependent on it are also revoked. **GUPI**

Revoking privileges granted by other IDs

An ID with the SYSADM or SYSCTRL authority can revoke privileges that are granted by other IDs.

Procedure

GUPI To revoke privileges granted by other IDs, choose one of the following approaches:

• Issue a REVOKE statement and include BY ALL in that statement.

This statement will revoke privileges granted by all other IDs.

The following example revokes the CREATETAB privileges that are granted to PGMR01 on database DB1 by all IDs:

REVOKE CREATETAB ON DATABASE DB1 FROM PGMR01 BY ALL;

• Issue a REVOKE statement and include the specific ID in that statement.

This statement will revoke privileges that were granted by a specific ID and leave intact the same privileges if they were granted by any other ID.

The following example revokes privileges that are granted by DBUTIL1 and leaves intact the same privileges if they were granted by any other ID:

REVOKE CREATETAB, CREATETS ON DATABASE DB1 FROM PGMR01 BY DBUTIL1;

GUPI

Related reference

REVOKE statement (Db2 SQL)

Revoking privileges granted by a role

You can use the REVOKE statement to revoke privileges that are granted by a role in a trusted context.

About this task

To revoke privileges that are granted by a role, you can issue the REVOKE statement in the trusted context that was defined with the ROLE AS OBJECT OWNER clause. Also, make sure the role that revokes a privilege matches the one that grants the privilege. For a static REVOKE statement, the revoker is the role that owns the plan or package. For a dynamic REVOKE statement, the role for the primary authorization ID that executes the REVOKE statement becomes the revoker.

An authorization ID or role that has the SYSADM or SYSCTRL authority can use the BY (ROLE *role-name*) clause of the REVOKE statement to revoke privileges that are granted by a role.

Revoking all privileges from a role

You can revoke all privileges that are assigned to a role by dropping the role itself or by using the REVOKE statement.

About this task

GUP1 When you attempt to drop a role, make sure that the role does not own any objects. If the role owns objects, the DROP statement is terminated. If the role does not own any objects, the role is dropped. As a result, all privileges that are held by this role are revoked, and the revocation is cascaded.

Revoking privileges for views

If a table privilege is revoked from the owner of a view on the table, the corresponding privilege on the view is revoked. The same privilege is also revoked from other IDs if it was granted by the view owner.

About this task

GUPI If the SELECT privilege on the base table is revoked from the owner of the view, the view is dropped. However, if another grantor granted the SELECT privilege to the view owner before the view was created, the view is not dropped.

For example, suppose that OPER2 has the SELECT and INSERT privileges on table T1 and creates a view of the table. If the INSERT privilege on T1 is revoked from OPER2, all insert privileges on the view are revoked. If the SELECT privilege on T1 is revoked from OPER2, and if OPER2 did not have the SELECT privilege from another grantor before the view was created, the view is dropped.

If a view uses a user-defined function, the view owner must have the EXECUTE privilege on the function. If the EXECUTE privilege is revoked, the revoke fails because the view is using the privilege and the RESTRICT clause prevents the revoke.

An authorization ID with the SYSADM authority can create a view for another authorization ID. In this case, the view could have both a creator and an owner. The owner is automatically given the SELECT privilege on the view. However, the privilege on the base table determines whether the view is dropped.

For example, suppose that IDADM, with SYSADM authority, creates a view on TABLX with OPER as the owner of the view. OPER now has the SELECT privilege on the view, but not necessarily any privileges on the base table. If SYSADM is revoked from IDADM, the SELECT privilege on TABLX is gone and the view is dropped.

If one ID creates a view for another ID, the catalog table SYSIBM.SYSTABAUTH needs either one or two rows to record the associated privileges. The number of rows that Db2 uses to record the privilege is determined by the following criteria:

- If IDADM creates a view for OPER when OPER has enough privileges to create the view by itself, only one row is inserted in SYSTABAUTH. The row shows only that OPER granted the required privileges.
- If IDADM creates a view for OPER when OPER does not have enough privileges to create the view by itself, two rows are inserted in SYSTABAUTH. One row shows IDADM as GRANTOR and OPER as GRANTEE of the SELECT privilege. The other row shows any other privileges that OPER might have on the view because of privileges that are held on the base table. **GUPI**

Revoking privileges for materialized query tables

If the SELECT privilege on a source table is revoked from the owner of a materialized query table, the corresponding privilege on the materialized query table is revoked. The same privilege is also revoked from other IDs if it was granted by the table owner.

About this task

GUPT If the SELECT privilege on the source table is revoked from the owner of a materialized query table, the materialized query table is dropped. However, if another grantor granted the SELECT privilege to the

materialized query table owner before the materialized query table was created, the materialized query table is not dropped.

Example: Suppose that OPER7 has the SELECT privilege on table T1 and creates a materialized query table T2 by selecting from T1. If the SELECT privilege on T1 is revoked from OPER7, and if OPER7 did not have the SELECT privilege from another grantor before T2 was created, T2 is dropped.

If a materialized query table uses a user-defined function, the owner of the materialized query table must have the EXECUTE privilege on the function. If the EXECUTE privilege is revoked, the revoke fails because the materialized query table is using the privilege and the RESTRICT clause prevents the revoke.

Revoking privileges for plans or packages

If the owner of an application plan or package loses a required privilege and does not have that privilege from another source, Db2 invalidates the package.

About this task

GUPT Suppose that OPER2 has the SELECT and INSERT privileges on table T1 and creates a package that uses SELECT, but not INSERT. When privileges are revoked from OPER2, the plan is affected in the following ways:

- If the INSERT privilege is revoked, the plan is unaffected.
- If the revoked privilege was EXECUTE on a user-defined function, Db2 marks the package **inoperative** instead of invalid.

If authorization data is cached for a package and an ID loses EXECUTE authority on the package, that ID is removed from the cache. Similarly, if authorization data is cached for routines, a revoke or cascaded revoke of EXECUTE authority on a routine, or on all routines in a schema (schema.*), from any ID causes the ID to be removed from the cache.

If authorization data is cached for plans, a revoke of EXECUTE authority on the plan from any ID causes the authorization cache to be invalidated.

If an application is caching dynamic SQL statements, and a privilege is revoked that was needed when the statement was originally prepared and cached, that statement is removed from the cache. Subsequent PREPARE requests for that statement do not find it in the cache and therefore execute a full PREPARE. If the plan or package is bound with KEEPDYNAMIC(YES), which means that the application does not need to explicitly re-prepare the statement after the point of commit or rollback, you might get an error on an OPEN, DESCRIBE, or EXECUTE of that statement following the next COMMIT or ROLLBACK. The error can occur because a prepare operation is performed implicitly by Db2. If you no longer have sufficient authority for the prepare, the OPEN, DESCRIBE, or EXECUTE request fails.

Revoking SYSADM authority from an authorization ID without affecting some dependent objects

If you revoke SYSADM authority from an ID that has installation SYSADM authority, you can avoid certain side effects.

About this task

When you revoke SYSADM authority from an ID that does not have installation SYSADM authority, the following actions occur:

- The REVOKE statement drops dependent views and materialized query tables for which SYSADM authority was used to create those views or materialized query tables.
- If SYSADM authority was used to create a package, that package is invalidated when SYSADM authority is revoked.

Procedure

To avoid dropping dependent views or materialized query tables, or invalidating dependent packages when you revoke SYSADM authority from an ID, follow this procedure.

1. Determine which IDs currently hold installation SYSADM authority.

Those IDs are the values of the SYSADM and SYSADM2 subsystem parameters. During this procedure, you will temporarily replace one of those values.

- 2. Give installation SYSADM authority to the ID from which you want to revoke SYSADM authority. To do that:
 - a) Run the installation CLIST in UPDATE mode. In PROTECTION PANEL 2, replace the value of field SYSTEM ADMIN 1 (subsystem parameter SYSADM) or SYSTEM ADMIN 2 (subsystem parameter SYSADM2) with the name of the authorization ID from which you want to revoke SYSADM authority.
 - b) After the installation CLIST completes, run job DSNTIJUZ to produce a new subsystem parameter load module.
 - c) Issue the **-SET SYSPARM** command to load the subsystem parameter load module that you created in step <u>"2.b" on page 86</u>

Updating SYSADM or SYSADM2 requires installation SYSADM authority or SECADM authority. For example, if you are replacing the SYSADM subsystem parameter value, you need to run the **-SET SYSPARM** command using the authorization ID to which subsystem parameter SYSADM2 is set.

- 3. Issue the REVOKE statement to revoke SYSADM authority from the ID to which you assigned installation SYSADM authority in step "2" on page 86.
- 4. Change the value of subsystem parameter SYSADM or SYSADM2 back to the value that it had in step <u>"1" on page 86</u>.

Related tasks

Updating subsystem parameter and application default values (Db2 Installation and Migration)

Related reference

-SET SYSPARM command (Db2) (Db2 Commands) REVOKE statement (system privileges) (Db2 SQL)

Restrictions on privilege revocation

You can specify the RESTRICT clause of the REVOKE statement to impose limitations on privilege revocation.

About this task

GUPT Whether specified or not, the RESTRICT clause of the REVOKE statement always applies to the following objects:

- User-defined functions
- JARs (Java classes for a routine)
- Stored procedures
- Distinct types
- Sequences

When an attempt is made to revoke a privilege on one of these objects, Db2 determines whether the revokee owns an object that is dependent on the privilege. If such a dependency exists, the REVOKE statement proceeds only if the revokee also holds this privilege from another grantor or holds this privilege indirectly (such as if PUBLIC has this privilege, or if the revokee has SYSADM authority).

Example

Consider the following scenario:

- 1. UserA creates a user-defined function named UserA.UDFA.
- 2. UserA grants EXECUTE on UserA.UDFA to UserB.
- 3. User B then creates a user-defined function UserB.UDFB that is sourced on UserA.UDFA.

At this point, UserA attempts to revoke the EXECUTE privilege on UserA.UDFA from UserB. The revoke succeeds or fails based on the following criteria:

- If UserB has the EXECUTE privilege on UserA.UDFA only from UserA, the revoke fails with an accompanying message that indicates that a dependency on this privilege.
- If UserB has the EXECUTE privilege on UserA.UDFA from another source, directly or indirectly, the EXECUTE privilege that was granted by UserA is revoked successfully.

For distinct types, the following objects that are owned by the revokee can have dependencies:

- A table that has a column that is defined as a distinct type
- A user-defined function that has a parameter that is defined as a distinct type
- A stored procedure that has a parameter that is defined as a distinct type
- · A sequence that has a parameter that is defined as a distinct type

For user-defined functions, the following objects that are owned by the revokee can have dependencies:

- · Another user-defined function that is sourced on the user-defined function
- A view that uses the user-defined function
- A table that uses the user-defined function in a check constraint or user-defined default clause
- A trigger package that uses the user-defined function

For JARs (Java classes for a routine), the following objects that are owned by the revokee can have dependencies:

- A Java user-defined function that uses a JAR
- A Java stored procedure that uses a JAR

For stored procedures, a trigger package that refers to the stored procedure in a CALL statement can have dependencies.

For sequences, the following objects that are owned by the revokee can have dependencies:

- Triggers that contain NEXT VALUE or PREVIOUS VALUE expressions that specify a sequence
- Inline SQL routines that contain NEXT VALUE or PREVIOUS VALUE expressions that specify a sequence

One way to ensure that the REVOKE statement succeeds is to drop the object that has a dependency on the privilege. To determine which objects are dependent on which privileges before attempting the revoke, use the following SELECT statements.

For a distinct type:

• List all tables that are owned by the revokee USRT002 that contain columns that use the distinct type USRT001.UDT1:

SELECT * FROM SYSIBM.SYSC	OLUMNS	WHERE
TBCREATOR = 'USRT002'	AND)
TYPESCHEMA = 'USRT001'	AND)
TYPENAME = 'UDT1'	AND)
COLTYPE = 'DISTINCT';		

• List the user-defined functions that are owned by the revokee USRT002 that contain a parameter that is defined as distinct type USRT001.UDT1:

```
SELECT * FROM SYSIBM.SYSPARMS WHERE
OWNER = 'USRT002' AND
TYPESCHEMA = 'USRT001' AND
TYPENAME = 'UDT1' AND
ROUTINETYPE = 'F';
```

 List the stored procedures that are owned by the revokee USRT002 that contain a parameter that is defined as distinct type USRT001.UDT1:

```
SELECT * FROM SYSIBM.SYSPARMS WHERE
OWNER = 'USRT002' AND
TYPESCHEMA = 'USRT001' AND
TYPENAME = 'UDT1' AND
ROUTINETYPE = 'P';
```

• List the sequences that are owned by the revokee USRT002 that contain a parameter that is defined as distinct type USRT001.UDT1:

```
SELECT SYSIBM.SYSSEQUENCES.SCHEMA, SYSIBM.SYSSEQUENCES.NAME
FROM SYSIBM.SYSSEQUENCES, SYSIBM.SYSDATATYPES WHERE
SYSIBM.SYSSEQUENCES.DATATYPEID = SYSIBM.SYSDATATYPES.DATATYPEID AND
SYSIBM.SYSDATATYPES.SCHEMA ='USRT001' AND
SYSIBM.SYSDATATYPES.NAME ='UDT1';
```

For a user-defined function:

 List the user-defined functions that are owned by the revokee USRT002 that are sourced on userdefined function USRT001.SPECUDF1:

SELECT * FROM SYSIBM.SYSROUTINES WHERE OWNER = 'USRTO02' AND SOURCESCHEMA = 'USRTO01' AND SOURCESPECIFIC = 'SPECUDF1' AND ROUTINETYPE = 'F';

 List the views that are owned by the revokee USRT002 that use user-defined function USRT001.SPECUDF1:

```
SELECT * FROM SYSIBM.SYSVIEWDEP WHERE
DCREATOR = 'USRT002' AND
BSCHEMA = 'USRT001' AND
BNAME = 'SPECUDF1' AND
BTYPE = 'F';
```

• List the tables that are owned by the revokee USRT002 that use user-defined function USRT001.A_INTEGER in a check constraint or user-defined default clause:

```
SELECT * FROM SYSIBM.SYSCONSTDEP WHERE
DTBCREATOR = 'USRT002' AND
BSCHEMA = 'USRT001' AND
BNAME = 'A_INTEGER' AND
BTYPE = 'F';
```

• List the trigger packages that are owned by the revokee USRT002 that use user-defined function USRT001.UDF4:

SELECT * FROM SYSIBM.SYSPACKDEP WHERE DOWNER = 'USRT002' AND BQUALIFIER = 'USRT001' AND BNAME = 'UDF4' AND BTYPE = 'F';

For a JAR (Java class for a routine), list the routines that are owned by the revokee USRT002 and that use a JAR named USRT001.SPJAR:

```
SELECT * FROM SYSIBM.SYSROUTINES WHERE
OWNER = 'USRT002' AND
JARCHEMA = 'USRT001' AND
JAR_ID = 'SPJAR';
```

For a stored procedure that is used in a trigger package, list the trigger packages that refer to the stored procedure USRT001.WLMLOCN2 that is owned by the revokee USRT002:

SELECT * FROM SYSIBM.SYSPACKDEP WHERE DOWNER = 'USRT002' AND BQUALIFIER = 'USRT001' AND

BNAME	=	'WLMLOCN2'	AND
BTYPE	=	'0';	

For a sequence:

• List the sequences that are owned by the revokee USRT002 and that use a trigger named USRT001.SEQ1:

```
SELECT * FROM SYSIBM.SYSPACKDEP WHERE
BNAME = 'SEQ1'
BQUALIFIER = 'USRT001'
BTYPE = 'Q'
DOWNER = 'USRT002'
DTYPE = 'T';
```

• List the sequences that are owned by the revokee USRT002 and that use a inline SQL routine named USRT001.SEQ1:

```
SELECT * FROM SYSIBM.SYSSEQUENCESDEP WHERE
DCREATOR = 'USRT002'
DTYPE = 'F'
BNAME = 'SEQ1'
BSCHEMA = 'USRT001';
```

GUPI

Managing implicit privileges through object ownership

Ownership of an object carries with it a set of related privileges on the object. Db2 provides separate controls for creation and ownership of objects.

In general, when you create an object, the owner of the object can be your primary authorization ID, one of your secondary authorization IDs, or the role that you are associated with in a trusted context.

Ownership of objects with unqualified names

If an object name is unqualified, the object type and the way it is created determine its ownership.

GUPI If the name of a table, view, index, alias, or synonym is unqualified, you can establish the object's ownership in the following ways:

- If you issue the CREATE statement dynamically, perhaps using SPUFI, QMF, or some similar program, the owner of the created object is your current SQL ID. That ID must have the privileges that are needed to create the object.
- If you issue the CREATE statement statically, by running a plan or package that contains it, the ownership of the created object depends on the option that is used for the bind operation. You can bind the plan or package with either the QUALIFIER option, the OWNER option, or both.
 - If the plan or package is bound with the QUALIFIER option only, the authorization ID in the QUALIFIER option is the owner of the object. The QUALIFIER option allows the binder to name a qualifier to use for all unqualified names of tables, views, indexes, aliases, or synonyms that appear in the plan or package.
 - If the plan or package is bound with the OWNER option only, the authorization ID in the OWNER option is the owner of the object.
 - If the plan or package is bound with both the QUALIFIER option and the OWNER option, the authorization ID in the QUALIFIER option is the owner of the object.
 - If neither option is specified, the authorization ID of the binder of the plan or package is implicitly the object owner.

If the name of a user-defined function, stored procedure, distinct type, sequence, or trigger is unqualified, you can establish the ownership of one of these objects in these ways:

• If you issue the CREATE statement dynamically, the owner of the created object is your current SQL ID. That ID must have the privileges that are needed to create the object.

• If you issue the CREATE statement statically, by running a plan or package that contains it, the owner of the object is the plan or package owner. You can use the OWNER bind option to explicitly name the object owner. If you do not use the OWNER bind option, the binder of the package or plan is implicitly the object owner.

If the name of a user-defined function, stored procedure, distinct type, sequence, or trigger is unqualified, the implicit qualifier is determined based on the schema name in dynamic statements and the PATH bind option in static statements. The owner of a JAR (Java class for a routine) that is used by a stored procedure or a user-defined function is the current SQL ID of the process that performs the INSTALL_JAR function.

Ownership of objects with qualified names

If an object name is qualified, the type of object indicates its ownership.

GUPI If you create a table, view, index, or alias with a qualified name, the owner of the object is the schema name. The schema name identifies the schema to which the object belongs. You can consider all of the objects that are qualified by the same schema name as a group of related objects.

If you create a distinct type, user-defined function, stored procedure, sequence, or trigger with a qualified name, the owner of the object is the authorization ID of the process. The owner of a JAR (Java class for a routine) that is used by a stored procedure or a user-defined function is the current SQL ID of the process that performs the INSTALL_JAR function.

Ownership of objects within a trusted context

You can simplify the administration of authorization by having roles as object owners. In addition, object ownership carries with it a set of related privileges on the object; you can prevent users from obtaining implicit privileges from object ownership by making roles object owners.

GUPT If the owner of an object is an authorization ID and you need to transfer the ownership to another ID, you need to drop the object first and re-create it with the new authorization ID as the owner. You don't need to take these steps if the owner is a role because all users that are associated with that role have the owner privilege.

The definition of a trusted context determines the ownership of objects that are created in the trusted context. Assume that you issue the CREATE statement dynamically and that the trusted context is defined with the ROLE AS OBJECT OWNER clause. In this case, the associated role is the owner of the objects, regardless of whether the objects are explicitly qualified.

In contrast, assume that you issue the CREATE statement statically and that the plan or package is bound in the trusted context with the ROLE AS OBJECT OWNER clause. In this case, the role that owns the plan or package also owns the objects that are created, regardless of whether the objects are explicitly qualified. GUPI

Related concepts

Trusted contexts

A *trusted context* is an independent database entity that you can define based on a system authorization ID and connection trust attributes.

Related reference

Establishing plan and package ownership in a trusted context

You can issue the BIND and REBIND commands in a trusted context with the ROLE AS OBJECT OWNER clause to specify the ownership of a plan or package. In this trusted context, you can specify only a role, not an authorization ID, as the OWNER of a plan or package.

Changing object ownership

You can make a Db2 role, a primary authorization ID, or a secondary authorization ID the owner of an object. You can change the ownership from one user to another or from an authorization ID to a role.

About this task

GUPI

Object ownership carries with it a set of privileges on the object. Because owner privileges are implicit, you cannot revoke them from the current owner. You can manage implicit ownership privileges in one of the following ways:

- Transfer the ownership of an existing object from one user to another. You can issue the TRANSFER OWNERSHIP statement to transfer the ownership of a database or system object from one user to another. The new owner can be an authorization ID or a role.
- Change the ownership of an existing object from an authorization ID to a role. If the owner of an object
 is a role, all users that are associated with the role have the same owner privileges. You can change the
 current owner from an authorization ID to a role by using the CATMAINT UPDATE utility with the OWNER
 option. To do so, you must also have the installation SYSADM authority and define a trusted context with
 the ROLE AS OBJECT OWNER AND QUALIFIER clause.
- Assign the ownership of a new object to a role. You can make a role the owner of an object by creating the object in a trusted context that is defined with the ROLE AS OBJECT OWNER AND QUALIFIER clause.
- Assign the ownership of a new object to a secondary authorization ID. You can make the object owning ID a secondary ID with which several primary IDs are associated. You can change the list of primary IDs that are associated with the secondary ID without dropping and re-creating the object.

GUPI

Related tasks

Changing the ownership of objects from an authorization ID to a role (Db2 Utilities) **Related reference** TRANSFER OWNERSHIP statement (Db2 SQL) CREATE TRUSTED CONTEXT statement (Db2 SQL)

Granting implicit privileges of object ownership

Certain implicit privileges of ownership correspond to the privileges that can be granted by a GRANT statement. For the privileges that do correspond, the owner of the object can grant them to other users.

About this task

GUPI The owner of a table can grant the SELECT privilege on the table to any other user.

Example

To grant the SELECT privilege on TABLE3 to USER4, the owner of the table can issue the following statement:

GRANT SELECT ON TABLE3 TO USER4

GUPI

Managing implicit privileges through plan or package ownership

If you are the owner of a plan or package, you must hold privileges to perform actions on the plan or package. You can grant privileges to execute the plan or package to any ID.

GUPT When the EXECUTE privilege on a plan or package is granted to an ID, the ID can execute a plan or package without holding the privileges for every action that the plan or package performs. However, the ID is restricted by the SQL statements in the original program.

Example: The program might contain the following statement:

```
EXEC SQL
SELECT * INTO :EMPREC FROM DSN8C10.EMP
WHERE EMPNO='000010';
```

The statement puts the data for employee number 000010 into the host structure EMPREC. The data comes from table DSN8C10.EMP, but the ID does not have unlimited access to DSN8910.EMP. Instead, the ID that has EXECUTE privilege for this plan can access rows in the DSN8C10.EMP table only when EMPNO = '000010'.

If any of the privileges that are required by the package are revoked from the owner, the package is invalidated. The package must be rebound, and the new owner must have the required privileges.

Establishing or changing plan or package ownership

You can use the BIND and REBIND subcommands to create or change an application plan or a package.

About this task

On either subcommand, you can use the OWNER option to name the owner of the resulting plan or package. Consider the following factors when naming an owner:

- Any user can name the primary ID or any secondary ID.
- An ID with the BINDAGENT privilege can name the grantor of that privilege.
- An ID with SYSCTRL or SYSADM authority can name any authorization ID on a BIND command, but not on a REBIND command.

If you omit the OWNER option, your primary ID becomes the owner on BIND, and the previous owner retains ownership on REBIND.

Some systems that can bind a package at a Db2 system do not support the OWNER option. When the OWNER option is not supported, the primary authorization ID is always the owner of the package because a secondary ID cannot be named as the owner.

Related reference

Establishing plan and package ownership in a trusted context

You can issue the BIND and REBIND commands in a trusted context with the ROLE AS OBJECT OWNER clause to specify the ownership of a plan or package. In this trusted context, you can specify only a role, not an authorization ID, as the OWNER of a plan or package.

Establishing plan and package ownership in a trusted context

You can issue the BIND and REBIND commands in a trusted context with the ROLE AS OBJECT OWNER clause to specify the ownership of a plan or package. In this trusted context, you can specify only a role, not an authorization ID, as the OWNER of a plan or package.

GUPT If you specify the OWNER option, the specified role becomes the owner of the plan or package. If you don't specify the OWNER option, the role that is associated with the binder becomes the owner. If the ROLE AS OBJECT OWNER clause is omitted for the trusted context, the current rules for plan and package ownership apply.

Considerations: If you want a role to own the package at the remote Db2, you need to define the role ownership in the trusted context at the remote server. Make sure to establish the connection to the remote Db2 as trusted when binding or re-binding the package at the remote server.

If you specify the OWNER option in a trusted connection during the remote BIND processing, the outbound authorization ID translation is not performed for the OWNER.

If the plan owner is a role and the application uses a package bound at a remote Db2 for z/OS server, the privilege of the plan owner to execute the package is not considered at the remote Db2 server. The privilege set of the authorization ID (either the package owner or the process runner determined by the DYNAMICRULES behavior) at the Db2 for z/OS server must have the EXECUTE privilege on the package at

the Db2 server. GUPI

Related concepts

Trusted contexts

A *trusted context* is an independent database entity that you can define based on a system authorization ID and connection trust attributes.

Related tasks

Establishing or changing plan or package ownership You can use the BIND and REBIND subcommands to create or change an application plan or a package.

Related reference

Ownership of objects within a trusted context

You can simplify the administration of authorization by having roles as object owners. In addition, object ownership carries with it a set of related privileges on the object; you can prevent users from obtaining implicit privileges from object ownership by making roles object owners.

How Db2 resolves unqualified names

A plan or package can contain SQL statements that use unqualified table and view names.

GUPT For static SQL, the default qualifier for those names is the owner of the plan or package. However, you can use the QUALIFIER option of the BIND command to specify a different qualifier. For static statements, the PATH bind option determines the path that Db2 searches to resolve unqualified distinct types, user-defined functions, stored procedures, sequences, and trigger names.

When you perform bind operations on packages or plans that contain static SQL, you should use group and ROLE authority rather than individual ID authority whenever possible. The combinations of OWNER, QUALIFIER, SCHEMA, and ROLE ownership provide you more flexibility.

For plans or packages that contain dynamic SQL, DYNAMICRULES behavior determines how Db2 qualifies unqualified object names. For unqualified distinct types, user-defined functions, stored procedures, sequences, and trigger names in dynamic SQL statements, Db2 uses the schema name as the qualifier. Db2 finds the schema name in the CURRENT PATH special register. For unqualified tables, views, aliases, and indexes, Db2 uses the CURRENT SCHEMA special register as the qualifier.

Exception: ALTER, CREATE, DROP, COMMENT ON, GRANT, and REVOKE statements follow different conventions for assigning qualifiers. For static SQL, you must specify the qualifier for these statements in the QUALIFIER bind option. For dynamic SQL, the qualifier for these statements is the value in the CURRENT SCHEMA special register. GUPI

Validating authorization for executing plans or packages

You can use the VALIDATE option to control how Db2 handles existence and authorization errors.

About this task

GUPT The owner of a plan or package must have authorization to execute all static SQL statements that are embedded in the plan or package. A bind operation always checks whether a local object exists and whether the owner has the required privileges on it. However, you do not need to have the authorization

when the plan or package is bound. The objects to which the plan or package refers do not even need to exist at bind time. If the initial checking fails, an error message is returned. You can choose whether the failure prevents the bind operation from completion by using the VALIDATE option on the BIND PLAN and BIND PACKAGE commands.

The following values for the VALIDATE option determine how Db2 is to handle existence and authorization errors:

RUN

If you choose RUN for the VALIDATE option, the bind succeeds even when existence or authorization errors exist. Db2 checks existence and authorization at run time.

BIND

If you choose BIND for the VALIDATE option, which is recommended, the bind fails when existence or authorization errors exist. **Exception:** If you use the SQLERROR(CONTINUE) option on the BIND PACKAGE command, the bind succeeds, but the package's SQL statements that have errors cannot execute.

The corresponding existence and authorization checks for remote objects are always made at run time. Authorization to execute dynamic SQL statements is also checked at run time. Applications that use the Resource Recovery Services attachment facility (RRSAF) to connect to Db2 do not require a plan.

Checking authorization at a Db2 database server

A remote requester, either a Db2 for z/OS server or other requesting system, runs a package at the Db2 intermediate server. Db2 checks for the privileges that are required for service requests.

About this task

GUPT As shown in the following diagram, a statement in the package uses an alias or a three-part name to request services from a Db2 database server.



Figure 5. Execution at a second Db2 server

The ID that is checked for the required privileges to run at the Db2 database server can be:

• The owner of the plan, if not a role, that is running at the requester site (if the requester is Db2 for z/OS)

If the owner of the plan is a role and the application uses a package bound at a remote Db2 for z/OS server, the authorization ID at the Db2 for z/OS server must have the EXECUTE privilege on the package at the Db2 server. The authorization ID can be the package owner or the process runner that is determined by the DYNAMICRULES behavior.

The owner of the package that is running at the Db2 server

In addition, if a remote alias is used in the SQL statement, the alias must be defined at the requester site. The ID that is used depends on the following factors:

• Whether the requester is a Db2 for z/OS server or a different system
- The value of the DYNAMICRULES bind option
- Whether the SQL statement that is executed at the Db2 database server is static or dynamic

Checking authorization for executing an RRSAF application without a plan

RRSAF provides the capability for an application to connect to Db2 and run without a Db2 plan.

About this task

If an RRSAF application does not have a plan, the following authorization rules are true:

- For the following types of packages, the primary or secondary authorization ID and role of the process are used for checking authorization to execute the package:
 - A local package
 - A remote package that is on a Db2 for z/OS system and is accessed using DRDA
- At a Db2 for z/OS system, the authorization to execute the DESCRIBE TABLE statement includes checking the primary and secondary authorization IDs.
- For a double hop situation, the authorization ID that must hold the required privileges to execute SQL statements at the second server is determined as if the requester is not a Db2 for z/OS system.

Caching authorization IDs for better performance

You can specify that Db2 is to cache authorization IDs for plans, packages, or routines (user-defined functions and stored procedures). Caching IDs can help improve performance, especially when IDs are frequently reused.

One cache exists for each plan, one global cache exists for packages, and a global cache exists for routines. The global cache for packages and routines is allocated at Db2 startup. For a data sharing group, each member does its own authorization caching.

Caching authorization IDs for plans

Authorization checking is fastest when the plan is reused by an ID or role that already appears in the cache and when the EXECUTE privilege is granted to PUBLIC.

About this task

You can set the size of the plan authorization cache by using the BIND PLAN subcommand. The default cache size is specified by the AUTHCACH subsystem parameter, with an initial default setting of 3072 bytes.

The AUTHCACH subsystem parameter or CACHESIZE option enables you to specify the size of the cache to acquire for the plan. Db2 uses this cache for caching the authorization IDs of those users that are running a plan. Db2 uses the CACHESIZE value to determine the amount of storage to acquire for the authorization cache. Db2 acquires storage from the EDM storage pool.

The size of the cache that you specify depends on the number of individual authorization IDs that are actively using the plan. The plan authorization cache includes 32 bytes of overhead information. In addition, each entry in the plan authorization cache is up to 132 bytes. Therefore, the minimum cache size of 256 bytes is enough for only one authorization ID entry. The maximum size of 4096 bytes is enough for 30 entries. The default AUTHCACH size of 3072 can contain 23 entries.

If you run the plan infrequently, or if authority to run the plan is granted to PUBLIC, you might want to turn off caching for the plan so that Db2 does not use unnecessary storage. To do this, specify a value of 0 for the CACHESIZE option.

Any plan that you run repeatedly is a good candidate for tuning by modifying the plan authorization cache size. Also, if you have a plan that a large number of users run concurrently, you might want to use a larger plan authorization cache size.

Related tasks

Caching authorization IDs for packages

Db2 authorization can cache roles or primary authorization IDs for handling packages. Db2 checks and caches a role if it is in effect and authorized. If a role is not in effect or authorized, Db2 checks and caches the primary authorization ID.

Caching authorization IDs for routines

Db2 authorization can cache roles or primary authorization IDs for handling routines. Db2 checks and caches a role if it is in effect and authorized. If a role is not in effect or authorized, Db2 checks and caches the primary authorization ID.

Caching authorization IDs for packages

Db2 authorization can cache roles or primary authorization IDs for handling packages. Db2 checks and caches a role if it is in effect and authorized. If a role is not in effect or authorized, Db2 checks and caches the primary authorization ID.

About this task

Caching roles or authorization IDs for packages can provide benefits for handling the following objects at run time:

- · Stored procedures
- Remotely bound packages
- Local packages in a package list in which the plan owner does not have execute authority on the package at bind time, but does at run time
- Local packages that are not explicitly listed in a package list, but are implicitly listed by *collection-id.**, *.*, or *.package-id

Important: Statistics trace field QTPACNOT records the number of authorization checks for package execution authority that could not use the package authorization cache. If a package executes successfully because the authorization ID of the process has installation SYSADM or installation SYSOPR authority, or a package for a system-defined routine executes successfully because the authorization ID of the process has installation SYSADM, installation SYSOPR, system DBADM, or SQLADM authority, an entry for that package is not added to the cache. However, statistics trace field QTPACNOT is incremented.

If a large value of QTPACNOT is related to many successful package executions under authorization IDs with installation SYSADM, installation SYSOPR, system DBADM or SQLADM authority, as described above, the large value does not indicate that there is a problem with package authorization caching.

The size of the package authorization cache is fixed at 10 MB.

What to do next

To cache more package authorization information, use any of the following strategies:

- Granting package execute authority to collection.*
- Granting package authority to a secondary ID or role when running in a trusted context
- Granting package execute authority to PUBLIC for some packages or collections

Related tasks

Caching authorization IDs for plans

Authorization checking is fastest when the plan is reused by an ID or role that already appears in the cache and when the EXECUTE privilege is granted to PUBLIC.

Caching authorization IDs for routines

Db2 authorization can cache roles or primary authorization IDs for handling routines. Db2 checks and caches a role if it is in effect and authorized. If a role is not in effect or authorized, Db2 checks and caches the primary authorization ID.

Related reference

Caching of EXECUTE on plans, packages, and routines

The results of authorization checks on the EXECUTE privilege for plans are not cached when those checks are performed by the authorization access control exit routine. The results of authorization checks on the EXECUTE privilege for packages and routines are cached if package and routine authorization caching is enabled on your system.

Caching authorization IDs for routines

Db2 authorization can cache roles or primary authorization IDs for handling routines. Db2 checks and caches a role if it is in effect and authorized. If a role is not in effect or authorized, Db2 checks and caches the primary authorization ID.

About this task

The routine authorization cache stores roles or authorization IDs with the EXECUTE privilege on a specific routine. A routine is identified as *schema.routine-name.type*, where the routine name is one of the following names:

- · The specific function name for user-defined functions
- The procedure name for stored procedures
- '*' for all routines in the schema

Important: Statistics trace field QTRACNOT records the number of authorization checks for routine execution authority that could not use the routine authorization cache. If a user-defined routine executes successfully because the authorization ID of the process has installation SYSADM or installation SYSOPR authority, or a system-defined routine executes successfully because the authorization ID of the process has installation SYSADM, installation SYSOPR, system DBADM or SQLADM authority, an entry for that routine is not added to the cache. However, statistics trace field QTRACNOT is incremented.

If a large value of QTRACNOT is related to many successful routine executions under authorization IDs with installation SYSADM, installation SYSOPR, system DBADM, or SQLADM authority, as described above, the large value does not indicate that there is a problem with routine authorization caching.

The size of the routine authorization cache is fixed at 10 MB

What to do next

To cache more authorization information about routines, use the following strategies:

- Granting EXECUTE on schema.*
- Granting package authority to a secondary ID or role when running in a trusted context
- Granting routine execute authority to PUBLIC for some or all routines in the schema.

Related tasks

Caching authorization IDs for plans

Authorization checking is fastest when the plan is reused by an ID or role that already appears in the cache and when the EXECUTE privilege is granted to PUBLIC.

Caching authorization IDs for packages

Db2 authorization can cache roles or primary authorization IDs for handling packages. Db2 checks and caches a role if it is in effect and authorized. If a role is not in effect or authorized, Db2 checks and caches the primary authorization ID.

Related reference

Caching of EXECUTE on plans, packages, and routines

The results of authorization checks on the EXECUTE privilege for plans are not cached when those checks are performed by the authorization access control exit routine. The results of authorization checks on the EXECUTE privilege for packages and routines are cached if package and routine authorization caching is enabled on your system.

Authorizing plan or package access through applications

Because an ID executes a package or plan by running an application program, implementing control measures in an application program can be useful.

About this task

Example: Consider the following SQL statement:

GUPI

```
EXEC SQL
SELECT * INTO :EMPREC FROM DSN8C10.EMP
WHERE EMPNO='000010';
```

GUPI

The statement permits access to the row of the employee table WHERE EMPNO='000010'. If you replace the value 000010 with a host variable, the program could supply the value of the variable and permit access to various employee numbers. Routines in the program could limit that access to certain IDs, certain times of the day, certain days of the week, or other special circumstances.

Stored procedures provide an alternative to controls in the application. By encapsulating several SQL statements into a single message to the Db2 server, a stored procedure can protect sensitive portions of the application program. Also, stored procedures can include access to non-Db2 resources, as well as Db2.

Recommendation: Do not use programs to extend security. Whenever possible, use other techniques, such as stored procedures or views, as a security mechanism. Using programs to extend security has the following drawbacks:

- Program controls are separate from other access controls, can be difficult to implement properly, are difficult to audit, and are relatively simple to bypass.
- Almost any debugging facility can be used to bypass security checks in a program.
- Other programs might use the plan without doing the needed checking.
- Errors in the program checks might allow unauthorized access.
- Because the routines that check security might be quite separate from the SQL statement, the security check could be entirely disabled without requiring a bind operation for a new plan.
- A BIND REPLACE operation for an existing plan does not necessarily revoke the existing EXECUTE privileges on the plan. (Revoking those privileges is the default, but the plan owner has the option to retain them. For packages, the EXECUTE privileges are always retained.)

For those reasons, if the program accesses any sensitive data, the EXECUTE privileges on the plan and on packages are also sensitive. They should be granted only to a carefully planned list of IDs.

Restricting access of plans or packages to particular systems

If you use controls in an application program, you can limit the access of a plan or package to the particular systems for which the application program is designed.

About this task

GUPI Db2 does not ensure that only specific programs are used with a plan, but program-to-plan control can be enforced in IMS and CICS. Db2 provides a consistency check to avoid accidental mismatches between program and plan, but the consistency check is not a security check.

You can use the ENABLE and DISABLE options on the BIND and REBIND subcommands to restrict access of plans and packages to a particular system.

Examples

Example

The ENABLE IMS option allows the plan or package to run from any IMS connection. Unless other systems are also named, ENABLE IMS does not allow the plan or package to run from any other type of connection.

Example

DISABLE BATCH prevents a plan or package from running through a batch job, but it allows the plan or package to run from all other types of connection.

You can exercise even finer control with the ENABLE and DISABLE options. You can enable or disable particular IMS connection names, CICS application IDs, requesting locations, and so forth.

Related reference

Authorization checking for executing packages

If PKLIST is specified in the BIND and REBIND options and the *location.collection* is an asterisk (*), Db2 defers the package authorization check until run time. Make sure that you use a specific location name or omit this part of the identifier if you do not want the package authorization check deferred until run time.

Authorization checking for executing packages

If PKLIST is specified in the BIND and REBIND options and the *location.collection* is an asterisk (*), Db2 defers the package authorization check until run time. Make sure that you use a specific location name or omit this part of the identifier if you do not want the package authorization check deferred until run time.

GUPT If you execute the packages remotely, make sure that the privileges required for a remote bind (BIND PACKAGE *location.collection*) are granted at the server location. The ID that owns the package must have all of the privileges that are required to run the package at the server, and BINDADD² and CREATE IN privileges at the server.

Exceptions:

- For a BIND COPY operation, the owner must have the COPY privilege at the local Db2 site or subsystem, where the package that is being copied resides.
- If the creator of the package is not the owner, the creator must have SYSCTRL authority or higher, or must have been granted the BINDAGENT privilege by the owner. That authority or privilege is granted at the local Db2.

Binding a plan with a package list (BIND PLAN PKLIST) is done at the local Db2, and bind privileges must be held there. Authorization to execute a package at a remote location is checked at execution time, as follows:

- If the server is a Db2 for z/OS subsystem:
 - If the subsystem parameter PRIVATE_PROTOCOL is set to NO, the authorization ID of the process (primary ID or any secondary ID) must have the EXECUTE privilege for the package at the Db2 server.
 - If subsystem parameter PRIVATE_PROTOCOL is set to AUTH, the owner of the plan at the Db2 requester must have the EXECUTE privilege on the package at the Db2 server.
- If the server is not Db2 for z/OS, the primary authorization ID must have whatever privileges are needed. Check that product's documentation.

Related tasks

Restricting access of plans or packages to particular systems

² Or BIND, depending on the installation option BIND NEW PACKAGE.

If you use controls in an application program, you can limit the access of a plan or package to the particular systems for which the application program is designed.

Managing privileges for routines

You can control authorization for creating, defining, and invoking routines, including user-defined functions (UDFs) and stored procedures

Privileges required for executing routines

A number of steps are involved in implementing, defining, and invoking user-defined functions (UDFs) and stored procedures, which are types of *routines*.

GUPT The following table summarizes the common tasks and the privileges that are required for executing routines, including UDFs and stored procedures.

Table 36. Common tasks and	equired privilege	s for routines
----------------------------	-------------------	----------------

Role	Tasks	Required privileges
Implementer	If SQL is in the routine: codes, precompiles, compiles, and link-edits the program to use as the routine. Binds the program as the routine package.	If binding a package, BINDADD system privilege and CREATE IN on the collection.
	If no SQL is in the routine: codes, compiles, and link-edits the program.	
Definer	Issues a CREATE FUNCTION statement to define a UDF or CREATE PROCEDURE statement to define a stored procedure.	CREATEIN privilege on the schema. EXECUTE authority on the routine package when invoked.
Invoker	Invokes a routine from an SQL application.	EXECUTE authority on the routine.

The routine *implementer* typically codes the routine in a program and precompiles the program. If the program contains SQL statements, the implementer binds the DBRM. In general, the authorization ID that binds the DBRM into a package is the package owner. The implementer is the routine package owner. As package owner, the implementer implicitly has EXECUTE authority on the package and has the authority to grant EXECUTE privileges to other users to execute the code within the package.

The implementer grants EXECUTE authority on the routine package to the definer. EXECUTE authority is necessary only if the package contains SQL. For user-defined functions (UDFs), the definer requires EXECUTE authority on the package. For stored procedures, the EXECUTE privilege on the package is checked for the definer and other IDs.

The routine *definer* owns the routine. The definer issues a CREATE FUNCTION statement to define a UDF or a CREATE PROCEDURE statement to define a stored procedure. The definer of a routine is determined as follows:

- If the SQL statement is embedded in an application program, the definer is the authorization ID of the owner of the plan or package.
- If the SQL statement is dynamically prepared, the definer is the SQL authorization ID that is contained in the CURRENT SQLID special register. If the SQL statement is executed in a trusted context that is specified with the ROLE AS OBJECT OWNER clause, the definer is the role in effect.

The definer grants EXECUTE authority on the routine to the invoker, that is, any user that needs to invoke the routine.

The routine *invoker* invokes the routine from an SQL statement in the invoking plan or package. The invoker for a routine is determined as follows:

• For static invocations, the authorization of the owner of the package that contains the invocation of the UDF is used.

• For dynamic invocations, the DYNAMICRULES bind option of the package that contains the invocation of the user-defined determines the authorization that is used. For more information about how Db2 applies the DYNAMICRULES bind option, see DYNAMICRULES bind option (Db2 Commands).

GUPI

Related concepts

How Db2 determines the authorization for invoking user-defined functions (Db2 Application programming and SQL)

Related tasks

Examples of granting privileges for routines

You can grant users the required privileges for implementing, defining, and using routines, including stored procedures and user-defined functions (UDFs).

Examples of granting privileges for routines

You can grant users the required privileges for implementing, defining, and using routines, including stored procedures and user-defined functions (UDFs).

About this task

The following examples describe how to use and assign the various authorizations and privileges that are required for various roles to get an external scalar user-defined function (UDF) up and running.

Tip: In this example scenario, the implementer and definer are not the same person, which is possible because the example is an external SQL scalar UDF. However, for compiled SQL scalar (SQL PL) UDFs, the same person always implements and defines the UDF because the package is created as part of the routine definition. For more information, see Creating user-defined functions (Db2 Administration Guide).

Procedure

GUPI

- 1. The *implementer* defines the UDF and becomes the package owner of the UDF.
 - a) For example, assume that the implementer codes the following external user-defined function in C and names the function C_SALARY:

/**	***************************************				
* <u>1</u>	his routine	accepts an employee ser	ial	number and a percent raise. *	
* 1	f the employ	/ee is a manager, the ra	ise	is not applied. Otherwise, *	
* t	he new sala	ry is computed, truncated	d i:	f it exceeds the employee's *	
k 11	nanager's sal	lary, and then applied to	o tl	he database. *	
***	**********	*****	***:	*********************************/	
vc	id C_SALARY		/*	main routine */	
(char	*employeeSerial	/*	in: employee serial no. */	
	decimal	*percentRaise	/*	in: percentage raise */	
	decimal	*newSalary,	/*	out: employee's new salary */	
	short int	*niEmployeeSerial	/*	in: indic var, empl ser */	
	short int	*niPercentRaise	/*	in: indic var, % raise */	
	short int	*niNewSalary,	/*	out: indic var, new salary */	
	char	*sqlstate,	/*	out: SQLSIAIE / */	
	char	<pre>*inName,</pre>	/*	in: family name of function*/	
	char	*specificName,	/*	in: specific name of func */	
`	cnar	*message	/*	out: diagnostic message */	
) v					
٤		TN DECLADE CECTION.			
	EXEC SUL DEU	AIN DECLARE SECTION;	1	bact war for ample carial	
	dooimol	hyeal ADV.	/*	host var for ompl selar */	
	obor	hydroproent 2 .	/*	host var for ompl dopt po ut/	
	docimal	hyManadorSalary	/*	host var omp's mor's calaryt	
		DECIADE SECTION.	/*	nost var, emp s mgr s sarary*/	
	ENEC SQL ENL	DECLARE SECTION,			
	colstate = 6	۰.			
	moment(more	(2, 2, 3, 3, 3, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5,			
	*********	**********************	***·	*****	
	* Conv the e	employee's serial into a	ho	st variable *	
	*****	****	***:	****	
	strcpv(hvEN	(PNO.employeeSerial).			

```
* Get the employee's work department and current salary
 EXEC SQL SELECT WORKDEPT, SALARY
      INTO :hvWORKDEPT, :hvSALARY
FROM EMP
      WHERE EMPNO = :hvEMPNO;
 * See if the employee is a manager
 EXEC SQL SELECT DEPTNO
      INTO :hvWORKDEPT
      FROM DEPT
WHERE MGRNO = :hvEMPNO;
 * If the employee is a manager, do not apply the raise
 if( SQLCODE == 0 )
   newSalary = hvSALARY;
  ş
 * Otherwise, compute and apply the raise such that it does not
* exceed the employee's manager's salary
                                   *
 else
  ş
   * Get the employee's manager's salary
   EXEC SQL SELECT SALARY
        INTO :hvManagerSalary
        FROM EMP
WHERE EMPNO = (SELECT MGRNO
                 FROM DSN8610.DEPT
                 WHERE DEPTNO = :hvWORKDEPT);
   * Compute proposed raise for the employee
   newSalary = hvSALARY * (1 + percentRaise/100);
   * Don't let the proposed raise exceed the manager's salary
   if( newSalary > hvManagerSalary
    newSalary = hvManagerSalary;
   * Apply the raise
   hvSALARY = newSalary;
   EXEC SQL UPDATE EMP
        SET SALARY = :hvSALARY
WHERE EMPNO = :hvEMPNO;
  }
 return;
} /* end C_SALARY */
```

The implementer requires the UPDATE privilege on table EMP and SELECT privilege on tables EMP and DEPT. Users with the EXECUTE privilege on function C_SALARY do not need the UPDATE privilege on the table.

- b) Because this program contains SQL, the implementer performs the following steps:
 - i) Precompile the program that implements the user-defined function.
 - ii) Link-edit the user-defined function with DSNRLI (RRS attachment facility), and name the program's load module C_SALARY.
 - iii) Bind the DBRM into package MYCOLLID.C_SALARY.

After performing these steps, the implementer is the *function package owner*.

c) The implementer then grants EXECUTE privilege on the user-defined function package to the definer.

```
GRANT EXECUTE ON PACKAGE MYCOLLID.C_SALARY
TO definer
```

As package owner, the implementer can also grant execute privileges to other users, which allows those users to execute code within the package. For example:

GRANT EXECUTE ON PACKAGE MYCOLLID.C_SALARY TO other_user

- 2. The *definer* completes the following steps:
 - a) Issue the CREATE FUNCTION statement. For example, the following CREATE FUNCTION statement defines a UDF named SALARY_CHANGE to Db2:

```
CREATE FUNCTION
  SALARY_CHANGE(
    VARCHAR( 6 )
    DECIMAL(5,2))
  RETURNS
    DECIMAL( 9,2 )
  SPECIFIC schema.SALCHANGE
  LANGUAGE C
  DETERMINISTIC
 MODIFIES SQL DATA
EXTERNAL NAME C_SALARY
PARAMETER STYLE DB2SQL
  RETURNS NULL ON NULL CALL
 NO EXTERNAL ACTION
 NO SCRATCHPAD
  NO FINAL CALL
  ALLOW PARALLEL
  NO COLLID
  ASUTIME LIMIT 1
 STAY RESIDENT NO
  PROGRAM TYPE SUB
 WLM ENVIRONMENT WLMENV
  SECURITY DB2
 NO DBINFO;
```

After issuing the CREATE FUNCTION statement, the person who defined the function owns the UDF. This person (the *definer*) can execute the UDF package. In this case, the owner of the UDF package (the implementer) granted to the definer the EXECUTE privilege on the package that contains the UDF.

b) The definer also grants the EXECUTE privilege on SALARY_CHANGE to all invokers of the routine.

```
GRANT EXECUTE ON FUNCTION SALARY_CHANGE
T0 invoker1, invoker2, invoker3, invoker4
```

- 3. The invokers code application programs that invoke the UDF.
 - a) For example, assume that the application program contains a static SQL statement that invokes the user-defined function SALARY_CHANGE. SALARY_CHANGE gives an employee a 10% raise if the employee is not a manager. The static SQL statement follows:

```
EXEC SQL SELECT FIRSTNME,
LASTNAME
SALARY_CHANGE( :hvEMPNO, 10.0 )
INTO :hvFIRSTNME,
:hvLASTNAME,
:hvSALARY
FROM EMP
WHERE EMPNO = :hvEMPNO;
```

b) The invoker then precompiles, compiles, link-edits, and binds the DBRM for the invoking application into the *invoking package*. An invoking package or invoking plan is the package or plan that contains the SQL that invokes the user-defined function. After performing these steps, the invoker is the owner of the invoking plan or package.

The invoker must also hold the SELECT privilege on the EMP table and the EXECUTE privilege on the SALARY_CHANGE function.

Authorization ID validation for an example UDF

Db2 uses the rules for static SQL to determine the authorization ID (invoker) that executes the userdefined function (UDF) package. For a static statement, the invoker is the authorization ID of the plan or package owner.

GUPT The invoking package SALARY_ADJ contains a static SQL SELECT statement that invokes the userdefined function SALARY_CHANGE.

• While execution occurs in invoking package SALARY_ADJ, Db2 uses the authorization ID of the invoker (the package owner).

The invoker requires the EXECUTE privilege on the user-defined function SALARY_CHANGE, which the package SALARY_ADJ invokes. Because the user-defined function definer has the EXECUTE privilege on the user-defined function package C_SALARY, the invoker does not require the explicit EXECUTE privilege.

• When execution changes to the user-defined function package C_SALARY, Db2 uses the authorization ID of the implementer (the package owner). The package owner is the authorization ID with authority to execute all static SQL in the user-defined function package C_SALARY.

Related concepts

Privileges required for executing routines

A number of steps are involved in implementing, defining, and invoking user-defined functions (UDFs) and stored procedures, which are types of *routines*.

How Db2 determines the authorization for invoking user-defined functions (Db2 Application programming and SQL)

Related tasks

Creating user-defined functions (Db2 Administration Guide)

Related reference

CREATE FUNCTION statement (external scalar function) (Db2 SQL)

Authorization behaviors for dynamic SQL statements

The two key factors that influence authorization behaviors are the DYNAMICRULES value and the run time environment of a package. The combination of the DYNAMICRULES value and the run time environment determine the values for the dynamic SQL attributes. Those attribute values are called the *authorization behaviors*.

GUPI The DYNAMICRULES option on the BIND or REBIND command determines the values that apply at run time for the following dynamic SQL attributes:

- The authorization ID or role that is used to check authorization
- The qualifier that is used for unqualified objects
- The source for application programming options that Db2 uses to parse and semantically verify dynamic SQL statements

The DYNAMICRULES option also determines whether dynamic SQL statements can include GRANT, REVOKE, ALTER, CREATE, DROP, and RENAME statements.

In addition to the DYNAMICRULES value, the run time environment of a package controls how dynamic SQL statements behave at run time. The two possible run time environments are:

- The package runs as part of a stand-alone program.
- The package runs as a stored procedure or user-defined function package, or runs under a stored procedure or user-defined function.

A package that runs under a stored procedure or user-defined function is a package whose associated program meets one of the following conditions:

- The program is called by a stored procedure or user-defined function.

- The program is in a series of nested calls that start with a stored procedure or user-defined function.

Run behavior

Db2 processes dynamic SQL statements by using their standard attribute. These attributes are collectively called the *run behavior*.

The run behavior consists of the following attributes:

- **GUPT** Db2 uses the authorization IDs (primary, secondary and the current SQL ID) of the application process to check for authorization of dynamic SQL statements. It also checks the role in effect if running in a trusted context.
- Dynamic SQL statements use the values of application programming options that were specified during installation. The installation option USE FOR DYNAMICRULES has no effect.
- The GRANT, REVOKE, CREATE, ALTER, DROP, and RENAME statements can be executed
 dynamically. GUP1

Related concepts

Bind behavior Db2 uses the bind behavior to process dynamic SQL statements.

Define behavior

When the package is run as or under a stored procedure or a user-defined function package, Db2 processes dynamic SQL statements by using the define behavior.

Invoke behavior

When the package is run as, or runs under, a stored procedure or a user-defined function package, Db2 processes dynamic SQL statements by using the invoke behavior.

Related reference

Common attribute values for bind, define, and invoke behaviors Certain attribute values apply to dynamic SQL statements in plans or packages that specify the bind, define, or invoke behavior.

Bind behavior

Db2 uses the bind behavior to process dynamic SQL statements.

GUPI The bind behavior consists of the following attributes:

- Db2 uses the authorization ID or role of the plan or package for authorization checking of dynamic SQL statements.
- Unqualified table, view, index, and alias names in dynamic SQL statements are implicitly qualified by the default schema, which is the value of the bind option QUALIFIER. If you do not specify the QUALIFIER bind option, Db2 uses the plan or package owner as the qualifier.

The values of the authorization ID or role and the qualifier for unqualified objects are the same as those that are used for embedded or static SQL statements.

• The bind behavior consists of the common attribute values for bind, define, and invoke behaviors.

Related concepts

Run behavior

Db2 processes dynamic SQL statements by using their standard attribute. These attributes are collectively called the *run behavior*.

Define behavior

When the package is run as or under a stored procedure or a user-defined function package, Db2 processes dynamic SQL statements by using the define behavior.

Invoke behavior

When the package is run as, or runs under, a stored procedure or a user-defined function package, Db2 processes dynamic SQL statements by using the invoke behavior.

Related reference

Common attribute values for bind, define, and invoke behaviors Certain attribute values apply to dynamic SQL statements in plans or packages that specify the bind, define, or invoke behavior.

Define behavior

When the package is run as or under a stored procedure or a user-defined function package, Db2 processes dynamic SQL statements by using the define behavior.

GUPI The define behavior consists of the following attribute values:

- Db2 uses the authorization ID or role of the user-defined function or the stored procedure owner for authorization checking of dynamic SQL statements in the application package.
- The default qualifier for unqualified objects is the user-defined function or the stored procedure owner.
- Define behavior consists of the common attribute values for bind, define, and invoke behaviors.

When the package is run as a stand-alone program, Db2 processes dynamic SQL statements using bind behavior or run behavior, depending on the DYNAMICRULES value specified.

Related concepts

Run behavior

Db2 processes dynamic SQL statements by using their standard attribute. These attributes are collectively called the *run behavior*.

Bind behavior

Db2 uses the bind behavior to process dynamic SQL statements.

Invoke behavior

When the package is run as, or runs under, a stored procedure or a user-defined function package, Db2 processes dynamic SQL statements by using the invoke behavior.

Related reference

<u>Common attribute values for bind, define, and invoke behaviors</u> Certain attribute values apply to dynamic SQL statements in plans or packages that specify the bind, define, or invoke behavior.

Invoke behavior

When the package is run as, or runs under, a stored procedure or a user-defined function package, Db2 processes dynamic SQL statements by using the invoke behavior.

GUPI The invoke behavior consists of the following attribute values:

- Db2 uses the authorization ID of the user-defined function or the stored procedure invoker to check the authorization for dynamic SQL statements in the application package. It uses the following rules:
 - The current SQL ID of the invoker is checked for the required authorization.
 - Secondary authorization IDs and roles that are associated with the primary authorization ID are also checked if they are needed for the required authorization.
- The default qualifier for unqualified objects is the user-defined function or the stored procedure invoker.
- Invoke behavior consists of the common attribute values for bind, define, and invoke behaviors.

When the package is run as a stand-alone program, Db2 processes dynamic SQL statements using bind behavior or run behavior, depending on the DYNAMICRULES specified value.

Related concepts

Run behavior

Db2 processes dynamic SQL statements by using their standard attribute. These attributes are collectively called the *run behavior*.

Bind behavior

Db2 uses the bind behavior to process dynamic SQL statements.

Define behavior

When the package is run as or under a stored procedure or a user-defined function package, Db2 processes dynamic SQL statements by using the define behavior.

Related reference

<u>Common attribute values for bind, define, and invoke behaviors</u> Certain attribute values apply to dynamic SQL statements in plans or packages that specify the bind, define, or invoke behavior.

Common attribute values for bind, define, and invoke behaviors

Certain attribute values apply to dynamic SQL statements in plans or packages that specify the bind, define, or invoke behavior.

The following attribute values apply:

• **GUPI** You can execute the statement SET CURRENT SQLID in a package or plan that is bound with any DYNAMICRULES value. However, Db2 does not use the current SQL ID as the authorization ID for dynamic SQL statements.

Db2 always uses the current SQL ID as the qualifier for the EXPLAIN output PLAN_TABLE.

- If the value of installation option USE FOR DYNAMICRULES is YES, Db2 uses the application programming default values that were specified during installation to parse and semantically verify dynamic SQL statements. If the value of USE for DYNAMICRULES is NO, Db2 uses the precompiler options to parse and semantically verify dynamic SQL statements.
- The GRANT, REVOKE, CREATE, ALTER, DROP, and RENAME statements cannot be executed dynamically.

The following table shows the DYNAMICRULES values and run time environments, and the dynamic SQL behaviors that they yield.

Table 37. How DYNAMICRULES and the run time environment deter	rmine dynamic SQL statement behavior
---	--------------------------------------

DYNAMICRULES value	Dynamic SQL statements in a stand-alone program environment	Dynamic SQL statements in a user-defined function or stored procedure environment
BIND	Bind behavior	Bind behavior
RUN	Run behavior	Run behavior
DEFINEBIND	Bind behavior	Define behavior
DEFINERUN	Run behavior	Define behavior
INVOKEBIND	Bind behavior	Invoke behavior
INVOKERUN	Run behavior	Invoke behavior

The following table shows the dynamic SQL attribute values for each type of dynamic SQL behavior.

Table 38. Definitions of dynamic SQL statement behaviors

Dynamic SQL attribute	Bind behavior	Run behavior	Define behavior	Invoke behavior
Authorization ID	Plan or package owner	Authorization IDs of the process and role, if applicable	User-defined function or stored procedure owner	Authorization ID of invoker ¹

Table 38. Definitions of dynamic SQL statement behaviors (continued)

Dynamic SQL attribute	Bind behavior	Run behavior	Define behavior	Invoke behavior
Default qualifier for unqualified objects	Bind OWNER or QUALIFIER value	Current Schema register determines the qualifier	User-defined function or stored procedure owner	Authorization ID of invoker or role
CURRENT SQLID ²	Not applicable	Applies	Not applicable	Not applicable
Source for application programming options	Determined by <i>dsnhdecp</i> ³ parameter DYNRULS ⁴	Install panel DSNTIPF	Determined by <i>dsnhdecp</i> ³ parameter DYNRULS ⁴	Determined by <i>dsnhdecp</i> ³ parameter DYNRULS ⁴
Can execute GRANT, REVOKE, CREATE, ALTER, DROP, RENAME?	No	Yes	No	No

- 1. If the invoker is the primary authorization ID of the process or the current SQL ID, the following rules apply:
 - The ID or role of the invoker is checked for the required authorization.
 - Secondary authorization IDs are also checked if they are needed for the required authorization.
- 2. Db2 uses the current SQL ID as the authorization ID for dynamic SQL statements only for plans and packages that have DYNAMICRULES run behavior. For the other dynamic SQL behaviors, Db2 uses the authorization ID that is associated with each dynamic SQL behavior, as shown in this table.

The initial current SQL ID is independent of the dynamic SQL behavior. For stand-alone programs, the current SQL ID is initialized to the primary authorization ID.You can execute the SET CURRENT SQLID statement to change the current SQL ID for packages with any dynamic SQL behavior, but Db2 uses the current SQL ID only for plans and packages with run behavior.

- 3. dsnhdecp is the application default load module. The default name is DSNHDECP.
- 4. The value of *dsnhdecp* parameter DYNRULS, which you specify in field USE FOR DYNAMICRULES in installation panel DSNTIPF, determines whether Db2 uses the precompiler options or the application programming defaults for dynamic SQL statements. **GUP1**

Related concepts

Run behavior

Db2 processes dynamic SQL statements by using their standard attribute. These attributes are collectively called the *run behavior*.

Bind behavior

Db2 uses the bind behavior to process dynamic SQL statements.

Define behavior

When the package is run as or under a stored procedure or a user-defined function package, Db2 processes dynamic SQL statements by using the define behavior.

Invoke behavior

When the package is run as, or runs under, a stored procedure or a user-defined function package, Db2 processes dynamic SQL statements by using the invoke behavior.

Determining authorization IDs for dynamic SQL statements in routines

You can determine the authorization IDs under which dynamic SQL statements in routines run based on various factors. These factors include the ownership of the stored procedure or the stored procedure package.

GUPT Suppose that A is a stored procedure and C is a program that is neither a user-defined function nor a stored procedure. Also suppose that subroutine B is called by both stored procedure A and program

C. Subroutine B, which is invoked by a language call, is neither a user-defined function nor a stored procedure. AP is the package that is associated with stored procedure A, and BP is the package that is associated with subroutine B. A, B, and C execute as shown in the following diagram.



Figure 6. Authorization for dynamic SQL statements in programs and routines

Stored procedure A was defined by IDASP and is therefore owned by IDASP. The stored procedure package AP was bound by IDA and is therefore owned by IDA. Package BP was bound by IDB and is therefore owned by IDB. The authorization ID under which EXEC SQL CALL A runs is IDD, the owner of plan DP.

The authorization ID under which dynamic SQL statements in package AP run is determined in the following way:

- If package AP uses DYNAMICRULES bind behavior, the authorization ID for dynamic SQL statements in package AP is IDA, the owner of package AP.
- If package AP uses DYNAMICRULES run behavior, the authorization ID for dynamic SQL statements in package AP is the value of CURRENT SQLID when the statements execute.
- If package AP uses DYNAMICRULES define behavior, the authorization ID for dynamic SQL statements in package AP is IDASP, the definer (owner) of stored procedure A.
- If package AP uses DYNAMICRULES invoke behavior, the authorization ID for dynamic SQL statements in package AP is IDD, the invoker of stored procedure A.

The authorization ID under which dynamic SQL statements in package BP run is determined in the following way:

- If package BP uses DYNAMICRULES bind behavior, the authorization ID for dynamic SQL statements in package BP is IDB, the owner of package BP.
- If package BP uses DYNAMICRULES run behavior, the authorization ID for dynamic SQL statements in package BP is the value of CURRENT SQLID when the statements execute.
- If package BP uses DYNAMICRULES define behavior:
 - When subroutine B is called by stored procedure A, the authorization ID for dynamic SQL statements in package BP is IDASP, the definer of stored procedure A.
 - When subroutine B is called by program C:

- If package BP uses the DYNAMICRULES option DEFINERUN, Db2 executes package BP using DYNAMICRULES run behavior, which means that the authorization ID for dynamic SQL statements in package BP is the value of CURRENT SQLID when the statements execute.
- If package BP uses the DYNAMICRULES option DEFINEBIND, Db2 executes package BP using DYNAMICRULES bind behavior, which means that the authorization ID for dynamic SQL statements in package BP is IDB, the owner of package BP.
- If package BP uses DYNAMICRULES invoke behavior:
 - When subroutine B is called by stored procedure A, the authorization ID for dynamic SQL statements in package BP is IDD, the authorization ID under which EXEC SQL CALL A executed.
 - When subroutine B is called by program C:
 - If package BP uses the DYNAMICRULES option INVOKERUN, Db2 executes package BP using DYNAMICRULES run behavior, which means that the authorization ID for dynamic SQL statements in package BP is the value of CURRENT SQLID when the statements execute.
 - If package BP uses the DYNAMICRULES option INVOKEBIND, Db2 executes package BP using DYNAMICRULES bind behavior, which means that the authorization ID for dynamic SQL statements in package BP is IDB, the owner of package BP.

Now suppose that B is a user-defined function, as shown in the following diagram.



Figure 7. Authorization for dynamic SQL statements in programs and nested routines

User-defined function B was defined by IDBUDF and is therefore owned by ID IDBUDF. Stored procedure A invokes user-defined function B under authorization ID IDA. Program C invokes user-defined function B under authorization ID IDC. In both cases, the invoking SQL statement (EXEC SQL SELECT B) is static.

The authorization ID under which dynamic SQL statements in package BP run is determined in the following way:

- If package BP uses DYNAMICRULES bind behavior, the authorization ID for dynamic SQL statements in package BP is IDB, the owner of package BP.
- If package BP uses DYNAMICRULES run behavior, the authorization ID for dynamic SQL statements in package BP is the value of CURRENT SQLID when the statements execute.
- If package BP uses DYNAMICRULES define behavior, the authorization ID for dynamic SQL statements in package BP is IDBUDF, the definer of user-defined function B.

- If package BP uses DYNAMICRULES invoke behavior:
 - When user-defined function B is invoked by stored procedure A, the authorization ID for dynamic SQL statements in package BP is IDA, the authorization ID under which B is invoked in stored procedure A.
 - When user-defined function B is invoked by program C, the authorization ID for dynamic SQL statements in package BP is IDC, the owner of package CP, and is the authorization ID under which B is invoked in program C. GUPI

Related tasks

Simplifying access authorization for routines

You can simplify authorization for routines in several ways without violating any of the authorization standards at your installation.

Using composite privileges

SQL statements that name more than one object require privileges on all of the tables included in the statement.

Performing multiple actions in one statement

A REBIND or FREE subcommand can name more than one plan or package. If no owner is named, the set of privileges that is associated with the primary ID, the associated role, and the secondary IDs must include the BIND privilege for each object.

Simplifying access authorization for routines

You can simplify authorization for routines in several ways without violating any of the authorization standards at your installation.

Procedure

GUPI) To simplify authorization, consider the following strategies :

- Have the implementer bind the user-defined function package using DYNAMICRULES define behavior. With this behavior in effect, Db2 only needs to check the definer's ID to execute dynamic SQL statements in the routine. Otherwise, Db2 needs to check the many different IDs that invoke the user-defined function.
- If you have many different routines, group those routines into schemas. Then grant EXECUTE on the routines in the schema to the appropriate users.

Users have execute authority on any functions that you add to that schema.

To grant the EXECUTE privilege on a schema to PUBLIC, issue the following statement:

GRANT EXECUTE ON FUNCTION schemaname.* TO PUBLIC;

GUPI

Related reference

Determining authorization IDs for dynamic SQL statements in routines

You can determine the authorization IDs under which dynamic SQL statements in routines run based on various factors. These factors include the ownership of the stored procedure or the stored procedure package.

Using composite privileges

SQL statements that name more than one object require privileges on all of the tables included in the statement.

About this task

GUPT An SQL statement can name more than one object. A SELECT operation, for example, can join two or more tables, or an INSERT statement can use a subquery. These operations require privileges on all of the tables that are included in the statement. However, you might be able to issue such a statement dynamically even though one of your IDs alone does not have all the required privileges.

If the DYNAMICRULES run behavior is in effect when the dynamic statement is prepared and your primary ID, any associated role, or any of your secondary IDs has all the needed privileges, the statement is validated. However, if you embed the same statement in a host program and try to bind it into a plan or package, the validation fails. The validation also fails for the dynamic statement if DYNAMICRULES bind, define, or invoke behavior is in effect when you issue the dynamic statement. In each case, all the required privileges must be held by the single authorization ID, determined by DYNAMICRULES behavior.

Related reference

Determining authorization IDs for dynamic SQL statements in routines You can determine the authorization IDs under which dynamic SQL statements in routines run based on various factors. These factors include the ownership of the stored procedure or the stored procedure package.

Performing multiple actions in one statement

A REBIND or FREE subcommand can name more than one plan or package. If no owner is named, the set of privileges that is associated with the primary ID, the associated role, and the secondary IDs must include the BIND privilege for each object.

Example

GUPT Suppose that a user with a secondary ID of HQFINANCE has the BIND privilege on plan P1 and that another user with a secondary ID of HQHR has the BIND privilege on plan P2. Assume that someone with HQFINANCE and HQHR as secondary authorization IDs issues the following command:

REBIND PLAN(P1,P2)

P1 and P2 are successfully rebound, even though neither the HQFINANCE nor HQHR has the BIND privilege for both plans.

Related reference

Determining authorization IDs for dynamic SQL statements in routines

You can determine the authorization IDs under which dynamic SQL statements in routines run based on various factors. These factors include the ownership of the stored procedure or the stored procedure package.

Retrieving privilege records in the Db2 catalog

You can query the Db2 catalog tables by using the SQL SELECT statement. Executing the SQL statement requires appropriate privileges and authorities. You can control access to the catalog by granting and revoking these privileges and authorities.

Catalog tables with privilege records

An authorization ID can hold different privileges. Db2 records information about the privileges of an ID in catalog tables.

GUPI The following catalog tables contain information about the privileges that IDs can hold:

Table 39. Privileges information in Db2 catalog tables			
Table name	Records privileges held for or authorization related to		
SYSIBM.SYSCOLAUTH	Updating columns		
SYSIBM.SYSDBAUTH	Databases		
SYSIBM.SYSPLANAUTH	Plans		
SYSIBM.SYSPACKAUTH	Packages		
SYSIBM.SYSRESAUTH	Buffer pools, storage groups, collections, table spaces, JARs, and distinct types		
SYSIBM.SYSROUTINEAUTH	User-defined functions and stored procedures		
SYSIBM.SYSSCHEMAAUTH	Schemas		
SYSIBM.SYSTABAUTH	Tables and views		
SYSIBM.SYSUSERAUTH	System authorities		
SYSIBM.SYSSEQUENCEAUTH	Sequences		
SYSIBM.SYSCONTEXT	Associating a role with a trusted context		
SYSIBM.SYSCTXTTRUSTATTRS	Associating trust attributes with a trusted context		
SYSIBM.SYSCONTEXTAUTHIDS	Associating users with a trusted context		

GUPI

Retrieving all authorization IDs or roles with granted privileges

Catalog tables that contain authorization information include GRANTEE and GRANTEETYPE columns. Depending on the settings of these columns, you can modify the WHERE clause of the SELECT statement to retrieve all IDs or roles with the same privileges.

About this task

GUPI No single catalog table contains information about all privileges. If GRANTEETYPE is blank, the value of GRANTEE is the primary or secondary authorization ID that has been granted a privilege. If GRANTEETYPE is "L", the value of GRANTEE is a role.

To retrieve all IDs or roles with privileges, you can issue the SQL code as shown in the following example:

SELECT GRANTEE, 'PACKAGE ' FROM SYSIBM.SYSPACKAUTH WHERE GRANTEETYPE IN (' ','L') UNTON UNION SELECT GRANTEE, 'TABLE ' FROM SYSIBM.SYSTABAUTH WHFRF GRANTEETYPE IN (' ','L') UNION SELECT GRANTEE, 'COLUMN ' FROM SYSIBM.SYSCOLAUTH WHERE GRANTEETYPE IN (' ','L') UNION SELECT GRANTEE, 'ROUTINE ' FROM SYSIBM.SYSROUTINEAUTH WHERE GRANTEETYPE IN ('','L') UNION FROM SYSIBM.SYSPLANAUTH SELECT GRANTEE, 'PLAN WHERE GRANTEETYPE IN (' ','L') UNION SELECT GRANTEE, 'SYSTEM ' FROM SYSIBM.SYSUSERAUTH WHERE GRANTEETYPE IN (' ','L') UNION SELECT GRANTEE, 'DATABASE' FROM SYSIBM.SYSDBAUTH WHERE GRANTEETYPE IN (' ','L') UNION SELECT GRANTEE, 'SCHEMA ' FROM SYSIBM.SYSSCHEMAAUTH WHERE GRANTEETYPE IN (' ', 'L') UNTON SELECT GRANTEE, 'USER ' FROM SYSIBM.SYSRESAUTH WHERE GRANTEETYPE IN (' ','L') UNION SELECT GRANTEE, 'SEQUENCE ' FROM SYSIBM.SYSSEQUENCEAUTH WHERE GRANTEETYPE IN (' ', 'L');

Periodically, you should compare the list of IDs or roles that is retrieved by this SQL code with the following lists:

- · Lists of users from subsystems that connect to Db2 (such as IMS, CICS, and TSO)
- · Lists of RACF users and groups
- · Lists of users from other DBMSs that access your Db2 subsystem
- Lists of remote connections.

If Db2 lists IDs or roles that do not exist elsewhere, you should revoke their privileges.

Retrieving multiple grants of the same privilege

You can query the catalog to find information about duplicate grants of the same privilege on objects. If multiple grant records clutter your catalog, consider revoking unnecessary grants, which removes duplicate grant data from the catalog.

Procedure

Issue the following SQL statement:

GUPI

```
SELECT GRANTEE, NAME, COUNT(*)
FROM SYSIBM.SYSPLANAUTH
GROUP BY GRANTEE, NAME
HAVING COUNT(*) > 2
ORDER BY 3 DESC;
```

GUPI

This statement orders the duplicate grants by frequency, so that you can easily identify the most duplicated grants. Similar statements for other catalog tables can retrieve information about multiple grants on other types of objects.

If several grantors grant the same privilege to the same grantee, the Db2 catalog can become cluttered with similar data. This similar data is often unnecessary, and it might cause poor performance.

Example

Example 1: Suppose that Judy, Kate, and Patti all grant the SELECT privilege on TABLE1 to Chris. If you care that Chris's ID has the privilege but not who granted the privilege, you might consider two of the SELECT grants to be redundant and unnecessary performance liabilities.

However, you might want to maintain information about authorities that are granted from several different IDs, especially when privileges are revoked.

Example 2: Suppose that the SELECT privilege from the previous example is revoked from Judy. If Chris has the SELECT privilege from only Judy, Chris loses the SELECT privilege. However, Chris retains the SELECT privilege because Kate and Patti also granted the SELECT privilege to Chris. In this case, the similar grants prove not to be redundant.

Retrieving all authorization IDs or roles with the DBADM and system DBADM authorities

You can retrieve all authorization IDs or roles that have the DBADM and system DBADM authorities.

About this task

Issue the following statement to retrieve all authorization IDs or roles that have the DBADM authority:

GUPI

```
SELECT DISTINCT GRANTEE
FROM SYSIBM.SYSDBAUTH
WHERE DBADMAUTH <>' ' AND GRANTEETYPE IN (' ','L');
```

Issue the following statement to retrieve all authorization IDs or roles that have the system DBADM authority on specific databases in the Db2 system:

```
SELECT DISTINCT GRANTEE
FROM SYSIBM.SYSUSERAUTH
WHERE SDBADMAUTH <>' ' AND GRANTEETYPE IN (' ','L');
```

GUPI

Retrieving all IDs or roles with access to the same table

You can retrieve all IDs or roles (GRANTEETYPE="L") that are explicitly authorized to access the same object.

About this task

GUPI To retrieve all IDs or roles (GRANTEETYPE="L") that are explicitly authorized to access the sample employee table (DSN8C10.EMP in database DSN8D12A), issue the following statement:

```
SELECT DISTINCT GRANTEE FROM SYSIBM.SYSTABAUTH
WHERE TTNAME='EMP' AND TCREATOR='DSN8910' AND
GRANTEETYPE IN (' ','L');
```

To retrieve all IDs or roles (GRANTEETYPE="L") that can change the sample employee table (IDs with administrative authorities and IDs to which authority is explicitly granted), issue the following statement:

```
SELECT DISTINCT GRANTEE FROM SYSIBM.SYSTABAUTH
WHERE TTNAME='EMP' AND
TCREATOR='DSN8910' AND
GRANTEETYPE IN (' ','L') AND
(ALTERAUTH <> ' ' OR
DELETEAUTH <> ' ' OR
INSERTAUTH <> ' ' OR
UPDATEAUTH <> ' ')
UNION
SELECT GRANTEE FROM SYSIBM.SYSUSERAUTH
```

```
WHERE SYSADMAUTH <> ' '
UNION
SELECT GRANTEE FROM SYSIBM.SYSDBAUTH
WHERE DBADMAUTH <> ' ' AND NAME='DSN8D91A';
```

To retrieve the columns of DSN8C10.EMP for which update privileges have been granted on a specific set of columns, issue the following statement:

```
SELECT DISTINCT COLNAME, GRANTEE, GRANTEETYPE FROM SYSIBM.SYSCOLAUTH
WHERE CREATOR='DSN8C10' AND TNAME='EMP'
ORDER BY COLNAME;
```

The character in the GRANTEETYPE column shows whether the privileges have been granted to a primary or secondary authorization ID (blank), a role (L), or are used by an application plan or package (P).

To retrieve the IDs that have been granted the privilege of updating one or more columns of DSN8C10.EMP, issue the following statement:

```
SELECT DISTINCT GRANTEE FROM SYSIBM.SYSTABAUTH
WHERE TTNAME='EMP' AND
TCREATOR='DSN8910' AND
GRANTEETYPE IN (' ','L') AND
UPDATEAUTH <> ' ';
```

The query returns only the IDs or roles (GRANTEETYPE="L") to which update privileges have been specifically granted. It does not return IDs or roles that have the privilege because of SYSADM or DBADM authority. You could include them by forming a union with additional queries, as shown in the following example:

```
SELECT DISTINCT GRANTEE GRANTEETYPE FROM SYSIBM.SYSTABAUTH
WHERE TTNAME='EMP' AND
        TCREATOR='DSN8910' AND
        GRANTEETYPE IN (' ','L') AND
        UPDATEAUTH <> ' '
UNION
SELECT GRANTEE FROM SYSIBM.SYSUSERAUTH
WHERE SYSADMAUTH <> ' '
UNION
SELECT GRANTEE FROM SYSIBM.SYSDBAUTH
WHERE DBADMAUTH <> ' ' AND NAME='DSN8D91A';
```

```
GUPI
```

Retrieving all IDs or roles with access to the same routine

You can retrieve the IDs or roles (GRANTEETYPE="L") that are authorized to access the same routines.

Example

GUPI To retrieve the IDs or roles (GRANTEETYPE="L") that are authorized to access stored procedure PROCA in schema SCHEMA1, issue the following statement:

```
SELECT DISTINCT GRANTEE FROM SYSIBM.SYSROUTINEAUTH
WHERE SPECIFICNAME='PROCA' AND
    SCHEMA='SCHEMA1' AND
    GRANTEETYPE IN (' ','L') AND
    ROUTINETYPE='P';
```

You can write a similar statement to retrieve the IDs or roles (GRANTEETYPE="L") that are authorized to access a user-defined function. To retrieve the IDs or roles that are authorized to access user-defined function UDFA in schema SCHEMA1, issue the following statement:

```
SELECT DISTINCT GRANTEE FROM SYSIBM.SYSROUTINEAUTH
WHERE SPECIFICNAME='UDFA' AND
SCHEMA='SCHEMA1' AND
GRANTEETYPE IN (' ','L') AND
ROUTINETYPE='F';
```

```
GUPI
```

Retrieving plans or packages with access to the same table

You can retrieve all the plans or packages that are granted access to the same table.

About this task

GUPT For example, to retrieve the names of application plans and packages that refer to table DSN8C10.EMP directly, issue the following statement:

```
SELECT DISTINCT GRANTEE FROM SYSIBM.SYSTABAUTH
WHERE GRANTEETYPE = 'P' AND
TCREATOR = 'DSN8C10' AND
TTNAME = 'EMP';
```

The preceding query does not distinguish between plans and packages. To identify a package, use the COLLID column of table SYSTABAUTH, which names the collection in which a package resides and is blank for a plan.

A plan or package can refer to the table indirectly, through a view.

To find all views that refer to the table:

1. Issue the following query:

```
SELECT DISTINCT DNAME FROM SYSIBM.SYSVIEWDEP
WHERE BTYPE = 'T' AND
BCREATOR = 'DSN8C10' AND
BNAME = 'EMP';
```

- 2. Write down the names of the views that satisfy the query. These values are instances of DNAME_list.
- 3. Find all plans and packages that refer to those views by issuing a series of SQL statements. For each instance of *DNAME_list*, issue the following statement:

```
SELECT DISTINCT GRANTEE FROM SYSIBM.SYSTABAUTH
WHERE GRANTEETYPE = 'P' AND
TCREATOR = 'DSN8C10' AND
TTNAME = DNAME_list;
```

```
GUPI
```

Retrieving privilege information through views

An ID with the SQLADM, system DBADM, DATAACCESS, ACCESSCTRL, SECADM, SYSADM, or SYSCTRL authority automatically has the privilege of retrieving data from catalog tables. If you do not want to grant the SELECT privilege on all catalog tables to PUBLIC, consider using views to let each ID retrieve information about its own privileges.

About this task

GUPT The following view includes the owner and the name of every table on which a user's primary authorization ID has the SELECT privilege:

```
CREATE VIEW MYSELECTS AS
SELECT TCREATOR, TTNAME FROM SYSIBM.SYSTABAUTH
WHERE SELECTAUTH <> ' ' AND
GRANTEETYPE = ' ' AND
GRANTEE IN (USER, 'PUBLIC', CURRENT SQLID);
```

The keyword USER in that statement is equal to the value of the primary authorization ID. To include tables that can be read by a secondary ID, set the current SQLID to that secondary ID before querying the view.

To make the view available to every ID, issue the following GRANT statement:

GRANT SELECT ON MYSELECTS TO PUBLIC;

Similar views can show other privileges. This view shows privileges over columns:

```
CREATE VIEW MYCOLS (OWNER, TNAME, CNAME, REMARKS, LABEL)
AS SELECT DISTINCT TBCREATOR, TBNAME, NAME, REMARKS, LABEL
FROM SYSIBM.SYSCOLUMNS, SYSIBM.SYSTABAUTH
WHERE TCREATOR = TBCREATOR AND
TTNAME = TBNAME AND
GRANTEETYPE = ' ' AND
GRANTEE IN (USER,'PUBLIC',CURRENT SQLID);
```

GUPI

Implementing multilevel security with Db2

Multilevel security allows you to classify objects and users with security labels that are based on hierarchical security levels and non-hierarchical security categories. Multilevel security prevents unauthorized users from accessing information at a higher classification than their authorization. It also prevents users from declassifying information.

Using multilevel security with row-level granularity, you can define security for Db2 objects and perform security checks, including row-level security checks. Row-level security checks allow you to control which users have authorization to view, modify, or perform other actions on specific rows of data.

You can implement multilevel security with the following combinations:

Db2 authorization with multilevel security with row-level granularity

In this combination, Db2 grants are used for authorization at the Db2 object level (database, table, and so forth). Multilevel security is implemented only at the row level within Db2.

External access control and multilevel security with row-level granularity

In this combination, external access control (such as the RACF access control module) is used for authorization at the Db2 object level. External access control also uses security labels to perform mandatory access checking on Db2 objects as part of multilevel security. Multilevel security is also implemented on the row level within Db2.

Important: The following information about multilevel security is specific to Db2. It does not describe all aspects of multilevel security. However, this specific information assumes that you have general knowledge of multilevel security.

Related concepts

Multilevel security

Multilevel security is a security policy that allows you to classify objects and users based on a system of hierarchical security levels and a system of non-hierarchical security categories.

Access control through multilevel security

Multilevel security, also known as label-based access control, allows you to classify objects and users with security labels. The security labels are based on hierarchical security levels and non-hierarchical security categories.

Multilevel security

Multilevel security is a security policy that allows you to classify objects and users based on a system of hierarchical security levels and a system of non-hierarchical security categories.

Multilevel security provides the capability to prevent unauthorized users from accessing information at a higher classification than their authorization, and prevents users from declassifying information.

Multilevel security offers the following advantages:

• Multilevel security enforcement is mandatory and automatic.

- Multilevel security can use methods that are difficult to express through traditional SQL views or queries.
- Multilevel security does not rely on special views or database variables to provide row-level security control.
- Multilevel security controls are consistent and integrated across the system, so that you can avoid defining users and authorizations more than once.
- Multilevel security does not allow users to declassify information.

Using multilevel security, you can define security for Db2 objects and perform other checks, including row-level security checks. Row-level security checks allow you to control which users have authorization to view, modify, or perform other actions on specific rows of data.

Multilevel security and row access control are mutually exclusive. While you can activate column access control on a table that has a security label column and enforce it on a security label column, you cannot do the same with row access control. If a table has a security label column, you cannot enable it with row access control. The opposite is also true; if a table is activated with row access control, you cannot alter it to include a security label column.

Security labels

Multilevel security restricts access to an object or a row based on the *security label* of the object or row and the security label of the user.

For local connections, the security label of the user is the security label that the user specified during sign-on. This security label is associated with the Db2 primary authorization ID and accessed from the RACF ACEE control block. If no security label is specified during sign-on, the security label is the user's default security label.

For normal TCP/IP connections, the security label of the user can be defined by the security zone. IP addresses are grouped into security zones on the Db2 server. For trusted TCP/IP connections, the security label of the user is the security label established under the trusted context.

For SNA connections, the default security label for the user is used instead of the security label that the user signed on with.

Security labels can be assigned to a user by establishing a trusted connection within a trusted context. The trusted context definition specifies the security label that is associated with a user on the trusted connection. You can define trusted contexts if you have the SYSADM authority.

Security labels are based on security levels and security categories.

You can use the COMCRIT subsystem parameter to require that all tables in the subsystem are defined with security for the Common Criteria environment.

When defining security labels, do not include national characters, such as @, #, and \$. Use of these characters in security labels may cause CCSID conversion errors.

Security levels

Along with security categories, hierarchical *security levels* are used as a basis for mandatory accesschecking decisions. When you define the security level of an object, you define the degree of sensitivity of that object. Security levels ensure that an object of a certain security level is protected from access by a user of a lower security level.

Security categories

Security categories are the non-hierarchical basis for mandatory access-checking decisions. When making security decisions, mandatory access control checks whether one set of security categories includes the security categories that are defined in a second set of security categories.

Users and objects in multilevel security

In multilevel security, a *user* is any entity that requires access to system resources; the entity can be a human user, a stored procedure, or a batch job. An *object* is any system resource to which access must be controlled; the resource can be a data set, a table, a table row, or a command.

Related reference

Implementing multilevel security with Db2

Multilevel security allows you to classify objects and users with security labels that are based on hierarchical security levels and non-hierarchical security categories. Multilevel security prevents unauthorized users from accessing information at a higher classification than their authorization. It also prevents users from declassifying information.

COMCRIT in macro DSN6SPRM (Db2 Installation and Migration)

Determining the security label of a user

Db2 provides several built-in session variables that contain information about the server and application process. You can obtain the value of a built-in session variable by invoking the GETVARIABLE command with the name of the built-in session variable.

One of the built-in session variables is the user's security label. You can issue the GETVARIABLE('SYSIBM.SECLABEL') command to obtain the security label of a user.

Global temporary tables with multilevel security

For a declared temporary table with a column definition, no syntax exists to specify a security label on a DECLARE GLOBAL TEMPORARY TABLE statement. An attempt to specify a security label results in an error.

If a DECLARE GLOBAL TEMPORARY TABLE statement uses a fullselect or a LIKE predicate or a CREATE GLOBAL TEMPORARY TABLE statement uses a LIKE predicate, the resulting temporary table can inherit the security label column from the referenced table or view. However, the temporary table does not inherit any security attributes on that column. That means that the inherited column in the temporary table is not defined AS SECURITY LABEL. The column in the temporary table is defined as NOT NULL, with no default. Therefore, any statements that insert data in the temporary table must provide a value for the inherited column.

Related concepts

Materialized query tables with multilevel security Materialized query tables are tables that contain information that is derived and summarized from other tables.

Constraints in a multilevel-secure environment

Although a referential constraint is not allowed for the security label column, Db2 enforces referential constraints for other columns in the table that are not defined with a security label.

Field, edit, and validation procedures in a multilevel-secure environment

In a multilevel-secure environment, field procedures, edit procedures, and validation procedures operate in certain ways.

Triggers in a multilevel-secure environment

When a transition table is generated as the result of a trigger, the security label of the table or row from the original table is not inherited by the transition table. Therefore, multilevel security with row-level checking is not enforced for transition tables and transition values.

Related information

Materialized query tables with multilevel security

Materialized query tables are tables that contain information that is derived and summarized from other tables.

If one or more of the source tables for a materialized query table has multilevel security with row-level granularity enabled, some additional rules apply to working with the materialized query table and the source tables.

Related concepts

Global temporary tables with multilevel security

For a declared temporary table with a column definition, no syntax exists to specify a security label on a DECLARE GLOBAL TEMPORARY TABLE statement. An attempt to specify a security label results in an error.

Constraints in a multilevel-secure environment

Although a referential constraint is not allowed for the security label column, Db2 enforces referential constraints for other columns in the table that are not defined with a security label.

Field, edit, and validation procedures in a multilevel-secure environment In a multilevel-secure environment, field procedures, edit procedures, and validation procedures operate in certain ways.

Triggers in a multilevel-secure environment

When a transition table is generated as the result of a trigger, the security label of the table or row from the original table is not inherited by the transition table. Therefore, multilevel security with row-level checking is not enforced for transition tables and transition values.

Related information

Constraints in a multilevel-secure environment

Although a referential constraint is not allowed for the security label column, Db2 enforces referential constraints for other columns in the table that are not defined with a security label.

Constraints operate in an multilevel-secure environment in the following ways:

- A unique constraint is allowed on a security label column.
- A referential constraint is not allowed on a security label column.
- A check constraint is not allowed on a security label column.

Multilevel security with row-level checking is not enforced when Db2 checks a referential constraint.

Related concepts

Global temporary tables with multilevel security

For a declared temporary table with a column definition, no syntax exists to specify a security label on a DECLARE GLOBAL TEMPORARY TABLE statement. An attempt to specify a security label results in an error.

Materialized query tables with multilevel security

Materialized query tables are tables that contain information that is derived and summarized from other tables.

Field, edit, and validation procedures in a multilevel-secure environment

In a multilevel-secure environment, field procedures, edit procedures, and validation procedures operate in certain ways.

Triggers in a multilevel-secure environment

When a transition table is generated as the result of a trigger, the security label of the table or row from the original table is not inherited by the transition table. Therefore, multilevel security with row-level checking is not enforced for transition tables and transition values.

Related information

Field, edit, and validation procedures in a multilevel-secure environment

In a multilevel-secure environment, field procedures, edit procedures, and validation procedures operate in certain ways.

- Field procedures are not allowed on a security label column. Edit procedures that are defined as WITH ROW ATTRIBUTES are not allowed on a table with a security label column.
- Validation procedures are allowed on a table that is defined with a security label column. When an authorized user with write-down privilege makes an INSERT or UPDATE request for a row, the validation procedure passes the new row with the security label of the user. If the authorized user does not have write-down privilege, the security label of the row remains the same.

Related concepts

Global temporary tables with multilevel security

For a declared temporary table with a column definition, no syntax exists to specify a security label on a DECLARE GLOBAL TEMPORARY TABLE statement. An attempt to specify a security label results in an error.

Materialized query tables with multilevel security

Materialized query tables are tables that contain information that is derived and summarized from other tables.

Constraints in a multilevel-secure environment

Although a referential constraint is not allowed for the security label column, Db2 enforces referential constraints for other columns in the table that are not defined with a security label.

Triggers in a multilevel-secure environment

When a transition table is generated as the result of a trigger, the security label of the table or row from the original table is not inherited by the transition table. Therefore, multilevel security with row-level checking is not enforced for transition tables and transition values.

Related information

Triggers in a multilevel-secure environment

When a transition table is generated as the result of a trigger, the security label of the table or row from the original table is not inherited by the transition table. Therefore, multilevel security with row-level checking is not enforced for transition tables and transition values.

If an ALTER TABLE statement is used to add a security label column to a table with a trigger on it, the same rules apply to the new security label column that would apply to any column that is added to the table with the trigger on it.

When a BEFORE trigger is activated, the value of the NEW transition variable that corresponds to the security label column is set to the security label of the user if either of the following criteria are met:

- Write-down control is in effect and the user does not have the write-down privilege
- The value of the security label column is not specified

Related concepts

Global temporary tables with multilevel security

For a declared temporary table with a column definition, no syntax exists to specify a security label on a DECLARE GLOBAL TEMPORARY TABLE statement. An attempt to specify a security label results in an error.

Materialized query tables with multilevel security

Materialized query tables are tables that contain information that is derived and summarized from other tables.

Constraints in a multilevel-secure environment

Although a referential constraint is not allowed for the security label column, Db2 enforces referential constraints for other columns in the table that are not defined with a security label.

Field, edit, and validation procedures in a multilevel-secure environment In a multilevel-secure environment, field procedures, edit procedures, and validation procedures operate in certain ways.

Related information

Mandatory access checking

Mandatory access checking evaluates dominance relationships between user security labels and object security labels and determines whether to allow certain actions based on certain rules.

- If the security label of the user dominates the security label of the object, the user can read from the object.
- If the security label of a user and the security label of the object are equivalent, the user can read from and write to the object.
- If the security label of the user dominates the security label of the object, the user cannot write to the object unless the user has the write-down RACF privilege.
- If the security label of the user is disjoint with the security label of the object, the user cannot read or write to that object.

Exception: IDs with the installation SYSADM authority bypass mandatory access checking at the Db2 object level because actions by installation SYSADM do not invoke the external access control exit routine (DSNX@XAC). However, multilevel security with row-level granularity is enforced for IDs with installation SYSADM authority.

After the user passes the mandatory access check, a discretionary check follows. The discretionary access check restricts access to objects based on the identity of a user, the user's role (if one exists), and the groups to which the user belongs. The discretionary access check ensures that the user is identified as having a "need to know" for the requested resource. The check is discretionary because a user with a certain access permission is capable of passing that permission to any other user.

Dominance relationships between security labels

Mandatory access checking is based on the dominance relationships between user security labels and object security labels. One security label dominates another security label in certain conditions.

- The security level that defines the first security label is greater than or equal to the security level that defines the second security label.
- The set of security categories that defines one security label includes the set of security categories that defines the other security label.

Comparisons between user security labels and object security labels can result in four types of relationships:

Dominant

One security label dominates another security label when both of the following conditions are true:

• The security level that defines the first security label is greater than or equal to the security level that defines the second security label.

• The set of security categories that defines the first security label includes the set of security categories that defines the other security label.

Reading data requires that the user security label dominates the data security label.

Reverse dominant

One security label reverse dominates another security label when both of the following conditions are true:

- The security level that defines the first security label is less than or equal to the security level that defines the second security label.
- The set of security categories that defines the first security label is a subset of the security categories that defines the other security label.

Equivalent

One security label is equivalent to another security label when they are the same or have the same level and set of categories. If both dominance and reverse dominance are true for two security labels, they are equivalent. The user security label must be equivalent to the data security label to be able to read and write data without being able to write down.

Disjoint

A security label is disjoint or incompatible with another security label if incompatible security categories cause neither security label to dominate the other security label. Two security labels are disjoint when each of them has at least one category that the other does not have. Disjoint access is not allowed, even when a user is allowed to write down. If a user security label that is disjoint to the data security label issues an INSERT, UPDATE, or LOAD command, Db2 issues an error.

Example: Suppose that the security level "secret" for the security label HIGH is greater than the security level "sensitive" for the security label MEDIUM. Also, suppose that the security label HIGH includes the security categories Project_A, Project_B, and Project_C, and that the security label MEDIUM includes the security categories Project_A and Project_B. The security label HIGH dominates the security label MEDIUM because both conditions for dominance are true.

Example: Suppose that the security label HIGH includes the security categories Project_A, Project_B, and Project_C, and that the security label MEDIUM includes the security categories Project_A and Project_Z. In this case, the security label HIGH does not dominate the security label MEDIUM because the set of security categories that define the security label HIGH does not contain the security category Project_Z.

Related concepts

Write-down control

Mandatory access checking prevents a user from declassifying information. It prevents a user from writing to an object unless the security label of the user is equivalent to or dominated by that of the object.

Related tasks

Granting write-down privileges To grant the write-down privilege, you need to define a profile and then allow users to access the profile.

Write-down control

Mandatory access checking prevents a user from declassifying information. It prevents a user from writing to an object unless the security label of the user is equivalent to or dominated by that of the object.

Db2 requires either the equivalence of the security labels or the *write-down privilege* of the user to write to Db2 objects.

Example: Suppose that user1 has a security label of HIGH and that row_x has a security label of MEDIUM. Because the security label of the user and the security label of the row are not equivalent, user1 cannot write to row_x. Therefore, write-down control prevents user1 from declassifying the information that is in row_x.

Example: Suppose that user2 has a security label of MEDIUM and that row_x has a security label of MEDIUM. Because the security label of the user and the security label of the row are equivalent, user2 can read from and write to row_x. However, user2 cannot change the security label for row_x unless

user2 has write-down privilege. Therefore write-down control prevents user2 from declassifying the information that is in row_x.

Related concepts

Dominance relationships between security labels

Mandatory access checking is based on the dominance relationships between user security labels and object security labels. One security label dominates another security label in certain conditions.

Related tasks

Granting write-down privileges To grant the write-down privilege, you need to define a profile and then allow users to access the profile.

Granting write-down privileges

To grant the write-down privilege, you need to define a profile and then allow users to access the profile.

Procedure

To grant write-down privilege to users:

1. Issue the following RACF command to define an IRR.WRITEDOWN.BYUSER profile.

RDEFINE FACILITY IRR.WRITEDOWN.BYUSER UACC(NONE)

Issue the following RACF command to allow users to access the IRR.WRITEDOWN.BYUSER profile that you just created.

```
PERMIT IRR.WRITEDOWN.BYUSER ID(USRT051 USRT052 USRT054 USRT056 -
USRT058 USRT060 USRT062 USRT064 USRT066 USRT068 USRT041) -
ACCESS(UPDATE) CLASS(FACILITY)
```

Related concepts

Dominance relationships between security labels

Mandatory access checking is based on the dominance relationships between user security labels and object security labels. One security label dominates another security label in certain conditions.

Write-down control

Mandatory access checking prevents a user from declassifying information. It prevents a user from writing to an object unless the security label of the user is equivalent to or dominated by that of the object.

Implementing multilevel security at the object level

You can implement multilevel security with Db2 at the object level.

Procedure

To implement multilevel security with Db2 at the object level:

1. Define security labels in RACF for all Db2 objects that require mandatory access checking by using the RDEFINE command.

Define security labels for the following RACF resource classes:

- DSNADM (administrative authorities)
- DSNR (access to Db2 subsystems)
- MDSNBP and GSNBP (buffer pools)
- MDSNCL and GDSNCL (collections)
- MDSNJR and MDSNJR (JAR)
- MDSNPN and GDSNPN (plans)
- MDSNSC and GDSNSC (schema)
- MDSNSG and GDSNSG (storage groups)

- MDSNSM and GDSNSM (system privileges)
- MDSNSP and GDSNSP (stored procedures)
- MDSNSQ and GDSNSQ (sequences)
- MDSNTB and GDSNTB (tables, views, indexes)
- MDSNTS and GDSNTS (table spaces)
- MDSNUF and GDSNUF (user-defined functions)

Recommendation: Define the security label SYSMULTI for Db2 subsystems that are accessed by users with different security labels and tables that require row-level granularity.

2. Specify a proper hierarchy of security labels.

In general, the security label of an object that is higher in the object hierarchy should dominate the security labels of objects that are lower in the hierarchy. RACF and Db2 do not enforce the hierarchy; they merely enforce the dominance rules that you establish.

You can use RACF to define security labels for the Db2 objects in the following object hierarchy:

- Subsystem or data sharing group
 - Database
 - Table space
 - Table
 - Column
 - Row
 - View
 - Storage group
 - Buffer pool
 - Plan
 - Collection
 - Package
 - Schema
 - Stored procedure or user-defined function
 - Java Archive (JAR)
 - Distinct type
 - Sequence

The following examples suggest dominance relationships among objects in the Db2 object hierarchy.

Example: A collection should dominate a package.

Example: A subsystem should dominate a database. That database should dominate a table space. That table space should dominate a table. That table should dominate a column.

Example: If a view is based on a single table, the table should dominate the view. However, if a view is based on multiple tables, the view should dominate the tables.

3. Define security labels and associate users with the security labels in RACF. If you are using a TCP/IP connection, you need to define security labels in RACF for the security zones into which IP addresses are grouped. These IP addressed represent remote users.

Give users with SYSADM, SYSCTRL, and SYSOPR authority the security label of SYSHIGH.

- 4. Activate the SECLABEL class in RACF. If you want to enforce write-down control, turn on write-down control in RACF.
- 5. Install the external security access control authorization exit routine (DSNX@XAC), such as the RACF access control module.

Related tasks

Implementing multilevel security with row-level granularity

Many applications need row-level security within the relational database so that access can be restricted to a specific set of rows. This security control often needs to be mandatory so that users are unable to bypass the row-level security mechanism. Using mandatory controls with z/OS and RACF provides consistency across the system.

Restricting access to the security label column

If you do not want users to see a security label column, you can create views that do not include the column.

Implementing multilevel security with row-level granularity

Many applications need row-level security within the relational database so that access can be restricted to a specific set of rows. This security control often needs to be mandatory so that users are unable to bypass the row-level security mechanism. Using mandatory controls with z/OS and RACF provides consistency across the system.

About this task

You can implement multilevel security with row-level granularity with or without implementing multilevel security on the object level. If you implement multilevel security on the object level, you must define security labels in RACF for all Db2 objects and install the external security access control authorization exit routine. If you do not use the access control authorization exit routine or RACF access control, you can use Db2 native authorization control.

You can implement multilevel security with row-level granularity with or without implementing multilevel security on the object level.

Recommendation: Use multilevel security at the object level with multilevel security with row-level granularity. Using RACF with multilevel security provides an independent check at run time and always checks the authorization of a user to the data.

Db2 performs multilevel security with row-level granularity by comparing the security label of the user to the security label of the row that is accessed. Because security labels can be equivalent without being identical, Db2 uses the RACROUTE REQUEST=DIRAUTH macro to make this comparison when the two security labels are not the same. For read operations, such as SELECT, Db2 uses ACCESS=READ. For update operations, Db2 uses ACCESS=READWRITE.

The write-down privilege for multilevel security with row-level granularity has the following properties:

- A user with the write-down privilege can update the security label of a row to any valid value. The user can make this update independent of the user's dominance relationship with the row.
- Db2 requires that a user have the write-down privilege to perform certain utilities.
- If write-down control is not enabled, all users with valid security labels are equivalent to users with the write-down privilege.

Related tasks

Implementing multilevel security at the object level You can implement multilevel security with Db2 at the object level.

Restricting access to the security label column

If you do not want users to see a security label column, you can create views that do not include the column.

Creating tables with multilevel security

You can use multilevel security with row-level checking to control table access. You can do so by creating or altering a table that has a column with the AS SECURITY LABEL attribute.

About this task

GUPI Tables with multilevel security in effect can be dropped by using the DROP TABLE statement. Users must have a valid security label to execute CREATE TABLE, ALTER TABLE, and DROP TABLE statements on tables with multilevel security enabled.

The performance of tables that you create and alter can suffer if the security label is not included in indexes. The security label column is used whenever a table with multilevel security enabled is accessed. Therefore, the security label column should be included in indexes on the table. If you do not index the security label column, you cannot maintain index-only access.

When a user with a valid security label creates a table, the user can implement row-level security by including a security label column. The security label column can have any name, but it must be defined as CHAR(8) and NOT NULL WITH DEFAULT. It also must be defined with the AS SECURITY LABEL clause.

After the user specifies the AS SECURITY LABEL clause on a column, users can indicate the security label for each row by entering values in that column. When a user creates a table and includes a security label column, SYSIBM.SYSTABLES indicates that the table has row-level security enabled. Once a user creates a table with a security label column, the security on the table cannot be disabled. The table must be dropped and re-created to remove this protection.

Example

To create a table that is named TABLEMLS1 and that has row-level security enabled, issue the following statement:

```
CREATE TABLE TABLEMLS1
(EMPNO CHAR(6) NOT NULL,
EMPNAME VARCHAR(20) NOT NULL,
DEPTNO VARCHAR(5)
SECURITY CHAR(8) NOT NULL WITH DEFAULT AS SECURITY LABEL,
PRIMARY KEY (EMPNO) )
IN DSN8D71A.DSN8S71D;
```

Adding multilevel security to existing tables

If you have a valid security label, you can implement row-level security on an existing table by adding a security label column to the table.

About this task

The security label column can have any name, but it must be defined as CHAR(8) and NOT NULL WITH DEFAULT. It also must be defined with the AS SECURITY LABEL clause.

Example: Suppose that the table EMP does not have row-level security enabled. To alter EMP so that it has row-level security enabled, issue the following statement:

GUPI

```
ALTER TABLE EMP
ADD SECURITY CHAR(8) NOT NULL WITH DEFAULT AS SECURITY LABEL;
```

GUPI

After a user specifies the AS SECURITY LABEL clause on a column, row-level security is enabled on the table and cannot be disabled. The security label for existing rows in the table at the time of the alter is the same as the security label of the user that issued the ALTER TABLE statement.

Important: Packages and dynamic statements are invalidated when a table is altered to add a security label column.

Removing tables with multilevel security

With valid privileges, you can drop a table that has row-level security in effect.

About this task

It is the required privilege that you have on the table, not the row-level security of the table, that determines whether or not a DROP statement succeeds. When you drop a table that has row-level security, Db2 generates an audit record.

Caching security labels

Db2 caches security labels to improve performance when multilevel security with row-level granularity is used.

About this task

Db2 caches all security labels that are checked (successfully and unsuccessfully) during processing. At commit or rollback, the security labels are removed from the cache. If a security policy that employs multilevel security with row-level granularity requires an immediate change and long-running applications have not committed or rolled back, you might need to cancel the application.

Restricting access to the security label column

If you do not want users to see a security label column, you can create views that do not include the column.

Procedure

GUPI To restrict access to the security label column, choose one of the following options:

Create a view that only includes those columns that are not security columns.
 For example, suppose that the ORDER table has the following columns: ORDERNO, PRODNO, CUSTNO, SECURITY. Suppose that SECURITY is the security label column, and that you do not want users to see the SECURITY column. Use the following statement to create a view that hides the security label column from users:

```
CREATE VIEW V1 AS
SELECT ORDERNO, PRODNO, CUSTNO FROM ORDER;
```

Retrieve the value of the SYSIBM.SECLABEL session variable, and create a view that includes only the rows that match the session variable value.

This will create a view that gives each user access only to the rows that include that user's security label column.

For example, you would use the following statement to create a view that allows access only to the rows that match the user's security label:

```
CREATE VIEW V2 AS SELECT * FROM ORDER
WHERE SECURITY=GETVARIABLE('SYSIBM.SECLABEL');
```

GUPI

Related tasks

Implementing multilevel security at the object level

You can implement multilevel security with Db2 at the object level.

Implementing multilevel security with row-level granularity

Many applications need row-level security within the relational database so that access can be restricted to a specific set of rows. This security control often needs to be mandatory so that users are unable to bypass the row-level security mechanism. Using mandatory controls with z/OS and RACF provides consistency across the system.

Managing data in a multilevel-secure environment

Multilevel security with row-level checking affects the results of the SELECT, INSERT, UPDATE, MERGE, DELETE, and TRUNCATE statements.

For example, row-level checking ensures that Db2 does not return rows that have a HIGH security label to a user that has a LOW security label. Users must have a valid security label to execute the SELECT, INSERT, UPDATE, MERGE, DELETE, and TRUNCATE statements.

This effect also applies to the results of the LOAD, UNLOAD, and REORG TABLESPACE utilities on tables that are enabled with multilevel security.

Using the SELECT statement with multilevel security

When a user with a valid security label selects data from one or more tables with row-level security enabled, Db2 compares the security label of the user to the security label of each row.

About this task

GUPI The results from the comparison of the security label of the user to the security label of each row are returned according to the following rules:

- If the security label of the user dominates the security label of the row, Db2 returns the row.
- If the security label of the user does not dominate the security label of the row, Db2 does not return the data from that row, and Db2 does not generate an error report.

Example

Suppose that Alan has a security label of HIGH, Beth has a security label of MEDIUM, and Carlos has a security label of LOW. Suppose that DSN8910.EMP contains the data that is shown in the following table and that the SECURITY column has been declared with the AS SECURITY LABEL clause.

Table 40. Sample data from DSN8910.EMP			
EMPNO	LASTNAME	WORKDEPT	SECURITY
000010	HAAS	A00	LOW
000190	BROWN	D11	HIGH
000200	JONES	D11	MEDIUM
000210	LUTZ	D11	LOW
000330	LEE	E21	MEDIUM

Now, suppose that Alan, Beth, and Carlos each submit the following SELECT statement:

```
SELECT LASTNAME
FROM EMP
ORDER BY LASTNAME;
```

Because Alan has the security label HIGH, he receives the following result:

BROWN HAAS
```
JONES
LEE
LUTZ
```

Because Beth has the security label MEDIUM, she receives the following result:

HAAS JONES LEE LUTZ

Beth does not see BROWN in her result set because the row with that information has a security label of HIGH.

Because Carlos has the security label LOW, he receives the following result:

HAAS LUTZ

Carlos does not see BROWN, JONES, or LEE in his result set because the rows with that information have security labels that dominate Carlos's security label. Although Beth and Carlos do not receive the full result set for the query, Db2 does not return an error code to Beth or Carlos.

Using the INSERT statement with multilevel security

When a user with a valid security label inserts data into a table with row-level security, the security label of the row is determined according to a specific set of rules.

About this task

- **GUPT** If the user has write-down privilege or write-down control is not enabled, the user can set the security label for the row to any valid security label. If the user does not specify a value for the security label, the security label of the row becomes the same as the security label of the user.
- If the user does not have write-down privilege and write-down control is enabled, the security label of the row becomes the same as the security label of the user.

Considerations for INSERT from a fullselect

For statements that insert the result of a fullselect, Db2 does not return an error code if the fullselect contains a table with a security label column. Db2 allows it if the target table does not contain a security label column while the source table contains one.

Considerations for SELECT...FROM...INSERT statements

If the user has write-down privilege or write-down control is not in effect, the security label of the user might not dominate the security label of the row. For statements that insert rows and select the inserted rows, the INSERT statement succeeds. However, the inserted row is not returned.

Considerations for INSERT with subselect

If you insert data into a table that does not have a security label column, but a subselect in the INSERT statement does include a table with a security label column, row-level checking is performed for the subselect. However, the inserted rows will not be stored with a security label column.

Example

Suppose that Alan has a security label of HIGH, that Beth has a security label of MEDIUM and write-down privilege defined in RACF, and that Carlos has a security label of LOW. Write-down control is enabled.

Now, suppose that Alan, Beth, and Carlos each submit the following INSERT statement:

```
INSERT INTO DSN8910.EMP(EMPNO, LASTNAME, WORKDEPT, SECURITY)
VALUES('099990', 'SMITH', 'C01', 'MEDIUM');
```

Because Alan does not have write-down privilege, Alan cannot choose the security label of the row that he inserts. Therefore Db2 ignores the security label of MEDIUM that is specified in the statement. The security label of the row becomes HIGH because Alan's security label is HIGH.

Because Beth has write-down privilege on the table, she can specify the security label of the new row. In this case, the security label of the new row is MEDIUM. If Beth submits a similar INSERT statement that specifies a value of LOW for the security column, the security label for the row becomes LOW.

Because Carlos does not have write-down privilege, Carlos cannot choose the security label of the row that he inserts. Therefore Db2 ignores the security label of MEDIUM that is specified in the statement. The security label of the row becomes LOW because Carlos' security label is LOW.

Using the UPDATE statement with multilevel security

When a user with a valid security label updates a table with row-level security enabled, Db2 compares the security label of the user to the security label of the row.

About this task

GUPI) The update to the table proceeds according to the following rules:

- If the security label of the user and the security label of the row are equivalent, the row is updated and the value of the security label is determined by whether the user has write-down privilege:
 - If the user has write-down privilege or write-down control is not enabled, the user can set the security label of the row to any valid security label.
 - If the user does not have write-down privilege and write-down control is enabled, the security label of the row is set to the value of the security label of the user.
- If the security label of the user dominates the security label of the row, the result of the UPDATE statement is determined by whether the user has write-down privilege:
 - If the user has write-down privilege or write-down control is not enabled, the row is updated and the user can set the security label of the row to any valid security label.
 - If the user does not have write-down privilege and write-down control is enabled, the row is not updated.
- If the security label of the row dominates the security label of the user, the row is not updated.

Recommendation: To avoid failed updates, qualify the rows that you want to update with the following predicate, for the security label column SECLABEL:

WHERE SECLABEL=GETVARIABLE('SYSIBM.SECLABEL')

Using this predicate avoids failed updates because it ensures that the user's security label is equivalent to the security label of the rows that Db2 attempts to update.

Considerations for SELECT...FROM...UPDATE statements: If the user has write-down privilege or if the write-down control is not in effect, the security label of the user might not dominate the security label of the row. For statements that update rows and select the updated rows, the UPDATE statement succeeds. However, the updated row is not returned.

Example

Suppose that Alan has a security label of HIGH, that Beth has a security label of MEDIUM and write-down privilege defined in RACF, and that Carlos has a security label of LOW. Write-down control is enabled.

Suppose that DSN8910.EMP contains the data that is shown in the following table and that the SECURITY column has been declared with the AS SECURITY LABEL clause.

Table 41. Sample data from DSN8910.EMP			
EMPNO	LASTNAME	WORKDEPT	SECURITY
000190	BROWN	D11	HIGH
000200	JONES	D11	MEDIUM
000210	LUTZ	D11	LOW

Now, suppose that Alan, Beth, and Carlos each submit the following UPDATE statement:

UPDATE DSN8910.EMP SET DEPTNO='X55', SECURITY='MEDIUM' WHERE DEPTNO='D11';

Because Alan has a security label that dominates the rows with security labels of MEDIUM and LOW, his write-down privilege determines whether these rows are updated. Alan does not have write-down privilege, so the update fails for these rows. Because Alan has a security label that is equivalent to the security label of the row with HIGH security, the update on that row succeeds. However, the security label for that row remains HIGH because Alan does not have the write-down privilege that is required to set the security label to any value. The results of Alan's update are shown in the following table:

Table 42. Sample data from DSN8910.EMP after Alan's update				
EMPNO EMPNAME DEPTNO SECURITY				
000190	BROWN	X55	HIGH	
000200	JONES	D11	MEDIUM	
000210 LUTZ D11 LOW				

Because Beth has a security label that dominates the row with a security label of LOW, her write-down privilege determines whether this row is updated. Beth has write-down privilege, so the update succeeds for this row and the security label for the row becomes MEDIUM. Because Beth has a security label that is equivalent to the security label of the row with MEDIUM security, the update succeeds for that row. Because the row with the security label of HIGH dominates Beth's security label, the update fails for that row. The results of Beth's update are shown in the following table:

Table 43. Sample data from DSN8910.EMP after Beth's update				
EMPNO EMPNAME DEPTNO SECURITY				
000190	BROWN	D11	HIGH	
000200	JONES	X55	MEDIUM	
000210 LUTZ X55 MEDIUM				

Because Carlos's security label is LOW, the update fails for the rows with security labels of MEDIUM and HIGH. Because Carlos has a security label that is equivalent to the security label of the row with LOW security, the update on that row succeeds. However, the security label for that row remains LOW because Carlos does not have the write-down privilege, which is required to set the security label to any value. The results of Carlos's update are shown in the following table:

Table 44. Sample data from DSN8910.EMP after Carlos's update			
EMPNO	EMPNAME	DEPTNO	SECURITY
000190	BROWN	D11	HIGH
000200	JONES	D11	MEDIUM
000210	LUTZ	X55	LOW



Using the MERGE statement with multilevel security

MERGE is an SQL statement that combines the conditional INSERT and UPDATE operations on a target table. Data that is not already present in the target table is inserted with the INSERT part of the MERGE statement. Data that is already present in the target table is updated with the UPDATE part of the MERGE statement.

Results

GUPT Because the MERGE statement consists of the INSERT and UPDATE operations, the multilevel security rules for the INSERT operation apply to the INSERT part of the MERGE statement and the multilevel security rules for the UPDATE operation apply to the UPDATE part of the MERGE statement.

INSERT rules for MERGE statements

For the INSERT part of the MERGE statement, when a user with a valid security label inserts data into a table with row-level security enabled, the security label of the row is determined according to the following rules:

- If the user has write-down privilege or if the write-down control is not enabled, the user can set the security label for the row to any valid security label. If the user does not specify a value for the security label, the security label of the row becomes the same as the security label of the user.
- If the user does not have write-down privilege and if the write-down control is enabled, the security label of the row becomes the same as the security label of the user.

UPDATE rules for MERGE statements

For the UPDATE part of the MERGE statement, when a user with a valid security label updates a table with row-level security enabled, Db2 compares the security label of the user to the security label of the row. The update proceeds according to the following rules:

- If the security label of the user and the security label of the row are equivalent, the row is updated and the value of the security label is determined by whether the user has write-down privilege:
 - If the user has write-down privilege or if the write-down control is not enabled, the user can set the security label of the row to any valid security label.
 - If the user does not have write-down privilege and if the write-down control is enabled, the security label of the row is set to the value of the security label of the user.
- If the security label of the user dominates the security label of the row, the result of the UPDATE operation is determined by whether the user has write-down privilege:
 - If the user has write-down privilege or if the write-down control is not enabled, the row is updated and the user can set the security label of the row to any valid security label.
 - If the user does not have write-down privilege and if the write-down control is enabled, the row is not updated.
- If the security label of the row dominates the security label of the user, the row is not updated.

SELECT...FROM...MERGE statement considerations

If the user has write-down privilege or if the write-down control is not in effect, the security label of the user might not dominate the security label of the row. For statements that merge rows and select the merged rows, the MERGE statement succeeds. However, the merged row is not returned.

GUPI

Using the DELETE statement with multilevel security

When a user with a valid security label deletes data from a table with row-level security, Db2 compares the security label of the user to that of the row.

About this task

GUPI The delete proceeds according to the following rules:

- If the security label of the user and the security label of the row are equivalent, the row is deleted.
- If the security label of the user dominates the security label of the row, the user's write-down privilege determines the result of the DELETE statement:
 - If the user has write-down privilege or write-down control is not enabled, the row is deleted.
 - If the user does not have write-down privilege and write-down control is enabled, the row is not deleted.
- If the security label of the row dominates the security label of the user, the row is not deleted.

Example

Suppose that Alan has a security label of HIGH, that Beth has a security label of MEDIUM and write-down privilege defined in RACF, and that Carlos has a security label of LOW. Write-down control is enabled.

Suppose that DSN8910.EMP contains the data that is shown in the following table and that the SECURITY column has been declared with the AS SECURITY LABEL clause.

Table 45. Sample data from DSN8910.EMP				
EMPNO	LASTNAME WORKDEPT SECURITY			
000190	BROWN	D11	HIGH	
000200	JONES	D11	MEDIUM	
000210	LUTZ	D11	LOW	

Now, suppose that Alan, Beth, and Carlos each submit the following DELETE statement:

```
DELETE FROM DSN8910.EMP
    WHERE DEPTNO='D11';
```

Because Alan has a security label that dominates the rows with security labels of MEDIUM and LOW, his write-down privilege determines whether these rows are deleted. Alan does not have write-down privilege, so the delete fails for these rows. Because Alan has a security label that is equivalent to the security label of the row with HIGH security, the delete on that row succeeds. The results of Alan's delete are shown in the following table:

Table 46. Sample data from DSN8910.EMP after Alan's delete			
EMPNO	EMPNAME	DEPTNO	SECURITY
000200	JONES	D11	MEDIUM
000210 LUTZ D11 LOW			

Because Beth has a security label that dominates the row with a security label of LOW, her write-down privilege determines whether this row is deleted. Beth has write-down privilege, so the delete succeeds for this row. Because Beth has a security label that is equivalent to the security label of the row with MEDIUM security, the delete succeeds for that row. Because the row with the security label of HIGH dominates Beth's security label, the delete fails for that row. The results of Beth's delete are shown in the following table:

Table 47. Sample data from DSN8910.EMP after Beth's delete				
EMPNO EMPNAME DEPTNO SECURITY				
000190 BROWN D11 HIGH				

Because Carlos's security label is LOW, the delete fails for the rows with security labels of MEDIUM and HIGH. Because Carlos has a security label that is equivalent to the security label of the row with LOW security, the delete on that row succeeds. The results of Carlos's delete are shown in the following table:

Table 48. Sample data from DSN8910.EMP after Carlos's delete				
EMPNO EMPNAME DEPTNO SECURITY				
000190 BROWN D11 HIGH				
000200 JONES D11 MEDIUM				

Important: Do not omit the WHERE clause from DELETE statements. If you omit the WHERE clause from the DELETE statement, checking occurs for rows that have security labels. This checking behavior might have a negative impact on performance.

Considerations for SELECT...FROM...DELETE statements: If the user has write-down privilege or writedown control is not in effect, the security label of the user might not dominate the security label of the row. For statements that delete rows and select the deleted rows, the DELETE statement succeeds. However, the deleted row is not returned.

Using the TRUNCATE statement with multilevel security

When a user with a valid security label uses a TRUNCATE statement to delete all data from a table with row-level security enabled, Db2 compares the security label of the user to the security label of each row.

About this task

GUPI The delete proceeds according to the following rules:

- If the security label of the user and the security label of the row are equivalent, the row is deleted.
- If the security label of the user dominates the security label of the row, the user's write-down privilege determines the result of the DELETE statement:
 - If the user has write-down privilege or write-down control is not enabled, the row is deleted.
 - If the user does not have write-down privilege and write-down control is enabled, the row is not deleted.
- If the security label of the row dominates the security label of the user, the row is not deleted.
- If the row cannot be deleted as a result of the security label verification, the TRUNCATE statement fails. GUPI

Using utilities with multilevel security

You need a valid security label and additional authorizations to run certain LOAD, UNLOAD, and REORG TABLESPACE jobs on tables that have multilevel security enabled. All other utilities check only for authorization to operate on the table space; they do not check for row-level authorization.

About this task

There are valid security label and additional authorizations required to run certain LOAD, UNLOAD, and REORG TABLESPACE jobs on tables that have multilevel security enabled:

LOAD

You must have the write-down privilege to run LOAD REPLACE on a table space that contains a table with multilevel security enabled. In this case, you can specify the values for the security label column.

UNLOAD

Additional restrictions apply to UNLOAD jobs on tables that have multilevel security enabled. Each row is unloaded only if the security label of the user dominates the security label of the row. If security label of the user does not dominate the security label of the row, the row is not unloaded and Db2 does not issue an error message.

REORG TABLESPACE

REORG TABLESPACE jobs on tables that have multilevel security enabled have the following restrictions:

- For jobs with the UNLOAD EXTERNAL option, each row is unloaded only if the security label of the user dominates the security label of the row. If the security label of the user does not dominate the security label of the row, the row is not unloaded and Db2 does not issue an error message.
- For jobs with the DISCARD option, a qualifying row is discarded only if the user has the write-down privilege and the security label of the user dominates the security label of the row.

Implementing multilevel security in a distributed environment

SQL statements that originate from remote requesters can participate in a multilevel secure environment if all information on the requester has the same security label and all users of the requester are permitted to that security label.

Management of multilevel security in a distributed environment requires physical control of the participating systems and careful management of the network. Managed systems must be prevented from communicating with other systems that do not have equivalent security labels.

Configuring TCP/IP with multilevel security

A communications server IP stack that runs in a multilevel secure environment can be configured as either a restricted stack or an unrestricted stack.

About this task

Recommendations: Use an unrestricted stack for Db2. An unrestricted stack is configured with an ID that is defined with a security label of SYSMULTI. A single z/OS system can concurrently run a mix of restricted and unrestricted stacks. Unrestricted stacks allow Db2 to use any security label to open sockets.

All users on a TCP/IP connection have the security label that is associated with the IP address that is defined on the server. If a user requires a different security label, the user must enter through an IP address that has that security label associated with it. If you require multiple IP addresses on a remote z/OS server, a workstation, or a gateway, you can configure multiple virtual IP addresses. This strategy can increase the number of security labels that are available on a client.

Remote users that access Db2 by using a TCP/IP network connection use the security label that is associated with the RACF SERVAUTH class profile when the remote user is authenticated. Security labels are assigned to the database access thread when the Db2 server authenticates the remote server by using the RACROUTE REQUEST = VERIFY service.

If you use a trusted context for your TCP/IP connection, you can define a default security label for all users or specific security labels for individual users who use the trusted context. The security label that is defined in the trusted context overrides the one for the TCP/IP connection in RACF.

Related tasks

Configuring SNA with multilevel security

Security labels are assigned to the database access thread when the Db2 server authenticates the remote server by using the RACROUTE REQUEST = VERIFY service. The service establishes a security label for the authorization ID that is associated with the database access thread.

Configuring SNA with multilevel security

Security labels are assigned to the database access thread when the Db2 server authenticates the remote server by using the RACROUTE REQUEST = VERIFY service. The service establishes a security label for the authorization ID that is associated with the database access thread.

About this task

For SNA connections, this security label is the default security label that is defined for the remote user. **Related tasks**

Configuring TCP/IP with multilevel security

A communications server IP stack that runs in a multilevel secure environment can be configured as either a restricted stack or an unrestricted stack.

Chapter 3. Managing access through RACF

You can control whether a local or remote application can gain access to a specific Db2 subsystem from different environments. You can set different levels of security depending on whether the requesting application uses SNA or Transmission Control Protocol/Internet Protocol (TCP/IP) protocols to access Db2.

After the local system authenticates the incoming ID, it treats the ID like a local connection request or a local sign-on request. You can process the ID with your connection or sign-on exit routine and associate secondary authorization IDs with the ID. If you are sending a request to a remote Db2 subsystem, that subsystem can subject your request to various security checks.

You can use an external security system, such as RACF, IMS, or CICS, to authorize and authenticate a remote request before it reaches your Db2 subsystem. The discussion in the following topics assumes that you use RACF, or an equivalent system, for external access control.

Establishing RACF protection for Db2

You can install and use RACF to protect your Db2 resources.

Procedure

To establish RACF protection for Db2, complete the following steps in any order:

- Define Db2 resources to RACF for protection.
- Grant RACF access to the protected Db2 resources.

Defining Db2 resources to RACF

To establish RACF protection for your Db2 subsystem, you must define your Db2 resources to RACF and authorize RACF for authentication checking.

Procedure

To define your DB2 resources to RACF:

- Define the names of protected access profiles.
- Enable RACF checking for the DSNR and SERVER classes.

What to do next

You can also perform the following tasks:

- Control whether two DBMSs that use VTAM® LU 6.2 can establish sessions with each other.
- Authorize IDs that are associated with stored procedures address spaces to run the appropriate attachment facility.
- Authorize the ID that is associated with the DDF address space (*ssnm*DIST) to use z/OS UNIX System Services if you use TCP/IP.

Related tasks

Permitting RACF access

You must perform certain tasks in a required order to enable a process to use protected RACF resources.

Managing authorization for stored procedures

Db2 for z/OS provides a variety of methods to help you ensure that users are properly authorized to create and execute stored procedures. Db2 also provides ways for you to keep stored procedures secure.

Protecting connection requests that use the TCP/IP protocol

You can set your Db2 subsystem to send or receive connection requests that use the TCP/IP network protocol. You need to authorize the started task user ID (SYSDSP) that is associated with the DDF address space (*ssnm*DIST) to use the z/OS UNIX System Services.

Establishing Kerberos authentication through RACF

Kerberos security is a network security technology that was developed at the Massachusetts Institute of Technology. The Kerberos security technology does not require passwords to flow in readable text because it uses encrypted tickets that contain authentication information for the users.

Naming protected access profiles

The RACF resource class for Db2 is DSNR, which is contained in the RACF class descriptor table. The profiles in that class help you control access to a Db2 subsystem from another environment. The environment can be IMS, CICS, the distributed data facility (DDF), Time Sharing Option (TSO), the call attachment facility (CAF), Db2 REST services, or batch.

About this task

Each profile has a name of the form *subsystem.environment*, where:

- subsystem is the name of a Db2 subsystem, of one to four characters; for example, DSN or DB2T.
- environment denotes the environment, by one of the following terms:
 - MASS for IMS (including MPP, BMP, Fast Path, and DL/I batch).
 - SASS for CICS.
 - DIST for DDF.

- RRSAF for Resource Recovery Services attachment facility. Stored procedures use RRSAF in WLMestablished address spaces.
- REST for Db2 REST services.
- ACCEL for IBM Integrated Synchronization access by IBM Db2 Analytics Accelerator for z/OS or by IBM Db2 for z/OS Data Gate.
- BATCH for all others, including TSO, CAF, and utilities.

To control access, you need to define a profile, as a member of class DSNR, for every combination of subsystem and environment you want to use. For example, suppose that you want to access:

- · Subsystem DSN from TSO and DDF
- Subsystem DB2P from TSO, DDF, IMS, and RRSAF
- Subsystem DB2T from TSO, DDF, CICS, RRSAF, and Db2 REST services

Then define the profiles with the following names:

DSN.BATCH DSN.DIST DB2P.BATCH DB2P.DIST DB2P.MASS DB2P.RRSAF DB2T.BATCH DB2T.DIST DB2T.SASS DB2T.RRSAF DB2T.REST

You can do that with a single RACF command, which also names an owner for the resources:

RDEFINE DSNR (DSN.BATCH DSN.DIST DB2P.BATCH DB2P.DIST DB2P.MASS DB2P.RRSAF DB2T.BATCH DB2T.DIST DB2T.SASS DB2T.RRSAF DB2T.REST) OWNER(DB20WNER)

In order to access a subsystem in a particular environment, a user must be on the access list of the corresponding profile. You add users to the access list by using the RACF **PERMIT** command. If you do not want to limit access to particular users or groups, you can give universal access to a profile with a command like this:

RDEFINE DSNR (DSN.BATCH) OWNER(DB2OWNER) UACC(READ)

Related concepts

Db2 support for RACF PassTickets

Db2 supports the ability to send and receive RACF PassTicketsto authenticate a user who is accessing a Db2 server.

Authorization of REST service users (Db2 REST services)

Related tasks

Enabling RACF checking for the DSNR and SERVER classes You can allow RACF to check for the DSNR and SERVER classes.

Enabling partner LU verification

With RACF and VTAM, you can control whether two logical units (LU) that use LU 6.2 can connect to each other.

Configuring Db2 data sharing groups for member-specific and group access with RACF PassTickets You can use PassTickets for both member-specific and group access to a Db2 data sharing group by adopting an appropriate naming scheme and using a distributed dynamic IP address (DDVIPA) for the group.

Enabling RACF checking for the DSNR and SERVER classes

You can allow RACF to check for the DSNR and SERVER classes.

About this task

If you are using stored procedures in a WLM-established address space, you might also need to enable RACF checking for the SERVER class.

Procedure

Issue the following command:

SETROPTS CLASSACT(DSNR)

Related concepts

Db2 support for RACF PassTickets

Db2 supports the ability to send and receive RACF PassTicketsto authenticate a user who is accessing a Db2 server.

Related tasks

Naming protected access profiles

The RACF resource class for Db2 is DSNR, which is contained in the RACF class descriptor table. The profiles in that class help you control access to a Db2 subsystem from another environment. The environment can be IMS, CICS, the distributed data facility (DDF), Time Sharing Option (TSO), the call attachment facility (CAF), Db2 REST services, or batch.

Enabling partner LU verification

With RACF and VTAM, you can control whether two logical units (LU) that use LU 6.2 can connect to each other.

Configuring Db2 data sharing groups for member-specific and group access with RACF PassTickets

You can use PassTickets for both member-specific and group access to a Db2 data sharing group by adopting an appropriate naming scheme and using a distributed dynamic IP address (DDVIPA) for the group.

Enabling partner LU verification

With RACF and VTAM, you can control whether two logical units (LU) that use LU 6.2 can connect to each other.

About this task

Each member of a connecting pair must establish a profile for the other member. For example, if LUAAA and LUBBB are to connect and know each other by those LUNAMES, issue RACF commands similar to these:

At LUAAA: RDEFINE APPCLU *netid*.LUAAA.LUBBB UACC(NONE) ... At LUBBB: RDEFINE APPCLU *netid*.LUBBB.LUAAA UACC(NONE) ...

Here, netid is the network ID, given by the VTAM start option NETID.

When you create those profiles with RACF, use the SESSION operand to supply:

- The VTAM password as a session key (SESSKEY suboperand)
- The maximum number of days between changes of the session key (INTERVAL suboperand)
- An indication of whether the LU pair is locked (LOCK suboperand)

Finally, to enable RACF checking for the new APPCLU resources, issue this RACF command at both LUAAA and LUBBB:

SETROPTS CLASSACT(APPCLU)

Related concepts

Db2 support for RACF PassTickets

Db2 supports the ability to send and receive RACF PassTicketsto authenticate a user who is accessing a Db2 server.

Related tasks

Naming protected access profiles

The RACF resource class for Db2 is DSNR, which is contained in the RACF class descriptor table. The profiles in that class help you control access to a Db2 subsystem from another environment. The environment can be IMS, CICS, the distributed data facility (DDF), Time Sharing Option (TSO), the call attachment facility (CAF), Db2 REST services, or batch.

Enabling RACF checking for the DSNR and SERVER classes You can allow RACF to check for the DSNR and SERVER classes.

Configuring Db2 data sharing groups for member-specific and group access with RACF PassTickets You can use PassTickets for both member-specific and group access to a Db2 data sharing group by adopting an appropriate naming scheme and using a distributed dynamic IP address (DDVIPA) for the group.

Db2 support for RACF PassTickets

Db2 supports the ability to send and receive RACF PassTicketsto authenticate a user who is accessing a Db2 server.

RACF PassTickets are one-time-only passwords that are generated by a requesting product or function. They are an alternative to the RACF password and password phrase that removes the need to send RACF passwords and password phrases across the network in clear text. They make it possible to move the authentication of a mainframe application user ID from RACF to another authorized function executing on the host system or to the workstation local area network (LAN) environment.

Db2 supports the following uses of RACF PassTickets

- Sending PassTickets with remote requests to a remote Db2 subsystem or data sharing group
- Receiving PassTickets from a remote Db2 subsystem or data sharing group
- Receiving PassTickets for sysplex WLB-enabled clients
- <u>"Configuring Db2 data sharing groups for member-specific and group access with RACF PassTickets" on</u> page 143
- Receiving PassTickets for RACF-protected user IDs (deprecated "1" on page 143)

Notes:

1. Receiving RACF-protected user IDs with RACF PassTickets is deprecated. This deprecation does not apply to RACF PassTickets in general or any other use for them in Db2 for z/OS.

Related tasks

Naming protected access profiles

The RACF resource class for Db2 is DSNR, which is contained in the RACF class descriptor table. The profiles in that class help you control access to a Db2 subsystem from another environment. The environment can be IMS, CICS, the distributed data facility (DDF), Time Sharing Option (TSO), the call attachment facility (CAF), Db2 REST services, or batch.

Enabling RACF checking for the DSNR and SERVER classes You can allow RACF to check for the DSNR and SERVER classes.

Enabling partner LU verification

With RACF and VTAM, you can control whether two logical units (LU) that use LU 6.2 can connect to each other.

Configuring Db2 data sharing groups for member-specific and group access with RACF PassTickets You can use PassTickets for both member-specific and group access to a Db2 data sharing group by adopting an appropriate naming scheme and using a distributed dynamic IP address (DDVIPA) for the group.

Configuring Db2 data sharing groups for member-specific and group access with RACF PassTickets

You can use PassTickets for both member-specific and group access to a Db2 data sharing group by adopting an appropriate naming scheme and using a distributed dynamic IP address (DDVIPA) for the group.

Procedure

- 1. Configure the data sharing group with a common location name and port, such as LOCATION name MYLOC1 and port 446.
- 2. Install each data sharing member on a separate LPAR. Alternatively, you can specify the GRPIPV4 and IPV4 combination in the BSDS for each member.
- 3. Configure the data sharing members with a common IPNAME specification, or if using SNA communications, a common LUNAME (GENERIC) specification, in the BSDS for each member. You must also both define and start a location alias for each member, as shown in the following example Db2 data sharing group.

Member DB2A

RESPORT (BSDS):	5001
IPNAME or GENERIC (BSDS):	SYEC1GLU
Location alias:	MYLOC1_DB2A with port: 1446
Member DB2B	
RESPORT (BSDS):	5002

IPNAME or GENERIC (BSDS):

SYEC1GLU MYLOC1_DB2B with port: 2446

Location alias:

Member DB2C

RESPORT (BSDS):	5003
IPNAME or GENERIC (BSDS):	SYEC1GLU
Location alias:	MYLOC1_DB2C with port: 3446

- 4. Create a DDVIPA to serve the Sysplex, which can spray multiple ports. You can use one of the following approaches:
 - Define the VIPADISTRIBUTE independently of the data sharing group.
 - Specify the VIPADISTRIBUTE as the GRPIPV4 the in the BSDS for each member.

For the example group, define the VIPADISTRIBUTE with a PORT clause that contains the following list of port numbers: 446, 1446, 2446, and 3446. The VIPADISTRIBUTE IP address is 1.1.1.100. For more information, see <u>Supported methods for specifying DVIPAs (Db2 Data Sharing Planning and Administration)</u>.

- 5. Create and activate equal PTKTDATA profiles named SYEC1GLU(GENERIC LUNAME/IPNAME) for both the serving Db2 sysplex and the requesting Db2 sysplex.
- 6. Add rows in the communications database (CDB) tables of the requesting Db2 Sysplex, as shown in the following example.

SYSIBM.LOCATIONS

LOCATION	LINKNAME	PORT
MYLOC1	SYEC1GLU	446
MYLOC1_DB2A	SYEC1GLU	1446
MYLOC1_DB2B	SYEC1GLU	2446
MYLOC1_DB2C	SYEC1GLU	3446

SYSIBM.IPNAMES

LINKNAME	SECURITY_OUT	IPADDR
SYEC1GLU	R	1.1.1.100

Results

When you issue CONNECT TO MYLOC1 with the example configuration, the requesting Db2 contacts any of the serving Db2 members listening on port 446. Because the LINKNAME matches the IPNAME or GENERICLU of any serving Db2 member, the PassTicket created on the requesting system can be evaluated on the serving system.

When you issue CONNECT TO MYLOC1_DB2A, the DDVIPA directs the connection to the DB2A member only, and because the PassTicket on the requesting system was generated under the LINKNAME of SYEC1GLU, and DB2A has a GENERICLU of SYEC1GLU, DB2A can evaluate the PassTicket successfully. The same is true when accessing the other members specifically.

Related concepts

Db2 support for RACF PassTickets Db2 supports the ability to send and receive RACF PassTicketsto authenticate a user who is accessing a Db2 server.

Security for Db2 data sharing (Db2 Data Sharing Planning and Administration)

Related tasks

Naming protected access profiles

The RACF resource class for Db2 is DSNR, which is contained in the RACF class descriptor table. The profiles in that class help you control access to a Db2 subsystem from another environment. The environment can be IMS, CICS, the distributed data facility (DDF), Time Sharing Option (TSO), the call attachment facility (CAF), Db2 REST services, or batch.

Enabling RACF checking for the DSNR and SERVER classes You can allow RACF to check for the DSNR and SERVER classes.

Enabling partner LU verification

With RACF and VTAM, you can control whether two logical units (LU) that use LU 6.2 can connect to each other.

Enabling Db2 to receive RACF PassTickets Db2 supports the ability to receive RACF PassTickets from remote requests.

Enabling Db2 to send RACF PassTickets

Db2 supports the ability to send RACF PassTickets with your remote requests to a remote Db2 subsystem or data sharing group.

Populating the communications database for use with TCP/IP (Db2 Installation and Migration)

Related reference

IPNAMES catalog table (Db2 SQL) LOCATIONS catalog table (Db2 SQL)

Permitting RACF access

You must perform certain tasks in a required order to enable a process to use protected RACF resources.

Procedure

To enable a process to use protected RACF resources:

- 1. Define RACF user IDs for Db2-started tasks
- 2. Add RACF groups
- 3. Grant users and groups access

Related tasks

Defining Db2 resources to RACF

To establish RACF protection for your Db2 subsystem, you must define your Db2 resources to RACF and authorize RACF for authentication checking.

Managing authorization for stored procedures

Db2 for z/OS provides a variety of methods to help you ensure that users are properly authorized to create and execute stored procedures. Db2 also provides ways for you to keep stored procedures secure.

Protecting connection requests that use the TCP/IP protocol

You can set your Db2 subsystem to send or receive connection requests that use the TCP/IP network protocol. You need to authorize the started task user ID (SYSDSP) that is associated with the DDF address space (*ssnm*DIST) to use the z/OS UNIX System Services.

Establishing Kerberos authentication through RACF

Kerberos security is a network security technology that was developed at the Massachusetts Institute of Technology. The Kerberos security technology does not require passwords to flow in readable text because it uses encrypted tickets that contain authentication information for the users.

Defining RACF user IDs for Db2-started tasks

A Db2 subsystem provides started-task address spaces.

About this task

Db2 uses the following started-task address spaces:

- ssnmDBM1 for database services
- ssnmMSTR for system services
- *ssnm*DIST for the distributed data facility
- Your WLM-established address spaces for stored procedures

You must associate each of these address spaces with a RACF user ID. You can also assign each of them to a RACF group name. The RACF user IDs and group names that are associated with Db2 address spaces are listed in the following table:

	-	
Address Space	RACF User ID	RACF Group Name
DSNMSTR	SYSDSP	DB2SYS
DSNDBM1	SYSDSP	DB2SYS
DSNDIST	SYSDSP	DB2SYS
DSNWLM	SYSDSP	DB2SYS
DB2TMSTR	SYSDSPT	DB2TEST
DB2TDBM1	SYSDSPT	DB2TEST
DB2TDIST	SYSDSPT	DB2TEST
DB2TSPAS	SYSDSPT	DB2TEST
DB2PMSTR	SYSDSPD	DB2PROD
DB2PDBM1	SYSDSPD	DB2PROD
DB2PDIST	SYSDSPD	DB2PROD
CICSSYS	CICS	CICSGRP
IMSCNTL	IMS	IMSGRP

Table 49. Db2 address spaces and associated RACF user IDs and group names

If you have IMS or CICS applications issuing Db2 SQL requests, you must associate RACF user IDs, and can associate group names, with:

- The IMS control region
- The CICS address space
- The four Db2 address spaces

If the IMS and CICS address spaces are started as batch jobs, provide their RACF IDs and group names with the USER and GROUP parameters on the JOB statement. If they are started as started-tasks, assign the IDs and group names as you do for the Db2 address spaces, by changing the RACF STARTED class or the RACF started procedures table.

The RACF user ID and group name do not need to match those that are used for the Db2 address spaces, but they must be authorized to run the Resource Recovery Services attachment facility (for

WLM-established stored procedures address spaces). Note that the WLM-established stored procedures started tasks IDs require an OMVS segment.

You can use two methods that RACF provides RACF STARTED class: if you use the STARTED class, the changes take effect without a subsequent IPL; if you use the started procedures table (ICHRIN03), you must perform another IPL for the changes to take effect. You cannot start the Db2 address spaces with batch jobs.

Procedure

To associate user IDs and groups with started tasks, use one of the following two methods the RACF provides:

 Use the RACF STARTED class to associate RACF user IDs and group names with the Db2 started procedures address spaces. If you use the STARTED class, the changes take effect without a subsequent IPL.

If your installation has not previously set up the RACF STARTED class, complete these steps:

a) Enable generic profile checking for the class:

SETROPTS GENERIC(STARTED)

b) Define the RACF identities for the Db2 started tasks:

RDEFINE	STARTED	DSNMSTR.**	STDATA(USER(SYSDP)	GROUP(DB2SYS)	TRUSTED(NO))
RDEFINE	STARTED	DSNDBM1.**	STDATA (USER (SYSDP)	GROUP(DB2SYS)	TRUSTED(NO))
RDEFINE	STARTED	DSNDIST.**	STDATA(USER(SYSDP)	GROUP(DB2SYS)	TRUSTED(NO))
RDEFINE	STARTED	DSNWLM.**	STDATA(USER(SYSDP)	GROUP(DB2SYS)	TRUSTED(NO))
RDEFINE	STARTED	DB2TMSTR.**	STDATA(USER(SYSDSPT)	GROUP(DB2TEST)	TRUSTED(NO))

The user ID associated with the *ssnm*DIST started task and *ssnm*DBM1 started task requires an OMVS segment for DDF functions and system profile functions. For more information, see <u>Enabling</u> Db2 to access TCP/IP services in z/OS UNIX System Services (Db2 Installation and Migration)

c) Refresh the in-storage profiles:

SETROPTS RACLIST(STARTED) REFRESH

Use the RACF-started procedures table (ICHRIN03) to associate RACF user IDs and group names with the Db2 started procedures address spaces. You need to change, reassemble, and link edit the resulting object code to z/OS. If you use ICHRIN03, you must perform another IPL for the changes to take effect.

The following example shows a sample job that reassembles and link edits the RACF started-procedures table (ICHRIN03):

//* ///** ///****	REASSEMBL TABLE ICH FOR EACH FOR AN IM AN IPL WI MODULE) I	E AND LINKED RIN03 TO INCI DB2 CATALOGEI S OR CICS SYS TH A CLPA (OF S REQUIRED FO	IT THE RACF STARTED-PROCEDURES LUDE USERIDS AND GROUP NAMES O PROCEDURE. OPTIONALLY, ENTRIES STEM MIGHT BE INCLUDED. R AN MLPA SPECIFYING THE LOAD OR THESE CHANGES TO TAKE EFFECT.
ENTC(* *	DUNT DC	AL2(((ENDTAU NUMBER OF EI	BLE-BEGTABLE)/ENTLNGTH)+32768) NTRIES AND INDICATE RACF FORMAT
* PI *	ROVIDE FOU	R ENTRIES FOR	R EACH DB2 SUBSYSTEM NAME.
BEGT/	ABLE DS	0H	
*	ENTRI	ES FOR SUBSYS	STEM NAME "DSN"
	DC	CL8'DSNMSTR	SYSTEM SERVICES PROCEDURE
	DC	CL8'SYSDSP'	USERID
	DC	CL8'DB2SYS'	GROUP NAME
	DC	X'00'	NO PRIVILEGED ATTRIBUTE
	DC	XL7'00'	RESERVED BYTES
ENTI	NGTH EOU	*-BEGTABLE	CALCULATE LENGTH OF EACH ENTRY

	DC	CL8'DSNDBM1'	DATAR	BASE SERVICES PROCEDURE	
			Divitiva	LISERTD	
		X'00'		NO PRIVILEGED ATTRIBUTE	
				DESEDVED BYTES	
		X'00'			
				DESEDVED RVTES	
				USERTD	
	DC			GROUP NAME	
	DC	X'00'		NO PRIVILEGED ATTRIBUTE	
	DC	XI 7'00'		RESERVED BYTES	
	DC			WIM-ESTABITSHED S P ADDRESS	SPACE
	DC	CL8'SYSDSP'		USERTD	
	DC	CL8'DB2SYS'		GROUP NAME	
	DC	X'00'		NO PRIVILEGED ATTRIBUTE	
	DC	XL7'00'		RESERVED BYTES	
*	ENTRI	ES FOR SUBSYSTEM	1 NAME	= "DB2T"	
	DC	CL8'DB2TMSTR'		SYSTEM SERVICES PROCEDURE	
	DC	CL8'SYSDSPT'		USERID	
	DC	CL8'DB2TEST'		GROUP NAME	
	DC	X'00'		NO PRIVILEGED ATTRIBUTE	
	DC	XL7'00'		RESERVED BYTES	
	DC	CL8'DB2TDBM1'		DATABASE SERVICES PROCEDURE	
	DC	CL8'SYSDSPT'		USERID	
	DC	CL8'DB2TEST'		GROUP NAME	
	DC	X'00'		NO PRIVILEGED ATTRIBUTE	
	DC	XL7'00'		RESERVED BYTES	
	DC	CL8'DB2TDIST'		DDF PROCEDURE	
	DC	CL8'SYSDSPT'		USERID	
	DC	CL8'DB2TEST'		GROUP NAME	
	DC	X'00'		NO PRIVILEGED ATTRIBUTE	
	DC	XL7'00'		RESERVED BYTES	
	DC	CL8'SYSDSPT'		USERID	
	DC	CL8'DB2TEST'		GROUP NAME	
	DC	X'00'		NO PRIVILEGED ATTRIBUTE	
	DC			RESERVED BYIES	
*	ENIRI	ES FUR SUBSYSIE	1 NAM		
	DC			SYSTEM SERVICES PROCEDURE	
		VIOO!			
				DECEDVED BYTES	
				NATARASE SEDVICES DOCEDUDE	
				IISEDIN	
				GROUP NAME	
	DC	X'00'			
	DC	XI 7'00'		RESERVED BYTES	
	DC	CL8'DB2PDTST'		DDE PROCEDURE	
	DC	CL8'SYSDSPD'		USERTD	
	DC	CL8'DB2PROD'		GROUP NAME	
	DC	X'00'		NO PRIVILEGED ATTRIBUTE	
	DC	XL7'00'		RESERVED BYTES	
	DC	CL8'SYSDSPD'		USERID	
	DC	CL8'DB2PROD'		GROUP NAME	
	DC	X'00'		NO PRIVILEGED ATTRIBUTE	
	DC	XL7'00'		RESERVED BYTES	
*	OPTIO	NAL ENTRIES FOR	CICS	AND IMS CONTROL REGION	
	DC	CL8'CICSSYS'		CICS PROCEDURE NAME	
	DC	CL8'CICS'		USERID	
	DC	CL8'CICSGRP'		GROUP NAME	
	DC	X'00'		NO PRIVILEGED ATTRIBUTE	
	DC	XL7'00'		RESERVED BYTES	
		CL8'TMSCNTL'	IMS (CONTROL REGION PROCEDURE	
	DC	OLO INCONTE		HOEDED	
	DC DC	CL8'IMS'		USERID	
	DC DC DC	CL8'IMS' CL8'IMSGRP'		USERID GROUP NAME	
	DC DC DC DC	CL8'IMS' CL8'IMSGRP' X'00'		USERID GROUP NAME NO PRIVILEGED ATTRIBUTE	
	DC DC DC DC DC	CL8'IMS' CL8'IMSGRP' X'00' XL7'00'		USERID GROUP NAME NO PRIVILEGED ATTRIBUTE RESERVED BYTES	
ENDTABLE	DC DC DC DC DC DS	CL8'IMS' CL8'IMSGRP' X'00' XL7'00' 0D		USERID GROUP NAME NO PRIVILEGED ATTRIBUTE RESERVED BYTES	

Related tasks

Adding RACF groups

You can issue the **ADDGROUP** command to add a new RACF group.

Granting users and groups access

You can use the PERMIT command to grant users or groups access to resources in class DSNR.

Associating started procedures and jobs with user IDs

Adding RACF groups

You can issue the **ADDGROUP** command to add a new RACF group.

About this task

You need first to issue the following **ADDUSER** command to add user DB2OWNER and give it class authorization for DSNR and USER.

ADDUSER DB2OWNER CLAUTH(DSNR USER) UACC(NONE)

DB2OWNER can now add users to RACF and issue the RDEFINE command to define resources in class DSNR. It also has control over and responsibility for the entire Db2 security plan in RACF.

To add group Db2 to the existing SYS1 group and make DB2OWNER the owner of the new group, issue the following RACF command:

ADDGROUP DB2 SUPGROUP(SYS1) OWNER(DB2OWNER)

To connect DB2OWNER to group Db2 with the authority to create new subgroups, add users, and manipulate profiles, issue the following RACF command:

CONNECT DB2OWNER GROUP(DB2) AUTHORITY(JOIN) UACC(NONE)

To make Db2 the default group for commands issued by DB2OWNER, issue the following RACF command:

ALTUSER DB20WNER DFLTGRP(DB2)

To create the group DB2USER and add five users to it, issue the following RACF commands:

ADDGROUP DB2USER SUPGROUP(DB2) ADDUSER (USER1 USER2 USER3 USER4 USER5) DFLTGRP(DB2USER)

To define a user to RACF, use the RACF ADDUSER command. That invalidates the current password. You can then log on as a TSO user to change the password.

Db2 considerations when using RACF groups:

- When a user is newly connected to, or disconnected from, a RACF group, the change is not effective until the next logon. Therefore, before using a new group name as a secondary authorization ID, a TSO user must log off and log on, or a CICS or IMS user must sign on again.
- A user with the SPECIAL, JOIN, or GROUP-SPECIAL RACF attribute can define new groups with any name that RACF accepts and can connect any user to them. Because the group name can become a secondary authorization ID, you should control the use of those RACF attributes.
- Existing RACF group names can duplicate existing Db2 authorization IDs. That duplication is unlikely for the following reasons:
 - A group name cannot be the same as a user name.
 - Authorization IDs that are known to Db2 are usually known to RACF.

However, you can create a table with an owner name that is the same as a RACF group name and use the IBM-supplied sample connection exit routine. Then any TSO user with the group name as a secondary ID has ownership privileges on the table. You can prevent that situation by designing the connection exit routine to stop unwanted group names from being passed to Db2.

Related tasks

Defining RACF user IDs for Db2-started tasks

A Db2 subsystem provides started-task address spaces.

Granting users and groups access

You can use the PERMIT command to grant users or groups access to resources in class DSNR.

Granting users and groups access

You can use the PERMIT command to grant users or groups access to resources in class DSNR.

About this task

Suppose that the DB2OWNER group in the following example is authorized for class DSNR, owns the profiles, and has the right to change them. You can issue the following commands to authorize the DB2USER members, the system administrators, and operators to be TSO users.

These users can run batch jobs and Db2 utilities on the three systems: DSN, DB2P, and DB2T. The ACCESS(READ) operand allows use of Db2 without the ability to manipulate profiles.

PERMITDSN.BATCHCLASS(DSNR)ID(DB2USER)ACCESS(READ)PERMITDB2P.BATCHCLASS(DSNR)ID(DB2USER)ACCESS(READ)PERMITDB2T.BATCHCLASS(DSNR)ID(DB2USER)ACCESS(READ)

Defining profiles for IMS and CICS: You want the IDs for attaching systems to use the appropriate access profile. For example, to let the IMS user ID use the access profile for IMS on system DB2P, issue the following RACF command:

PERMIT DB2P.MASS CLASS(DSNR) ID(IMS) ACCESS(READ)

To let the CICS group ID use the access profile for CICS on system DB2T, issue the following RACF command:

PERMIT DB2T.SASS CLASS(DSNR) ID(CICSGRP) ACCESS(READ)

Providing installation authorities to default IDs: When Db2 is installed, IDs are named to have special authorities—one or two IDs for SYSADM and one or two IDs for SYSOPR. Those IDs can be connected to the group DB2USER; if they are not, you need to give them access. The next command permits the default IDs for the SYSADM and SYSOPR authorities to use subsystem DSN through TSO:

PERMIT DSN.BATCH CLASS(DSNR) ID(SYSADM,SYSOPR) ACCESS(READ)

Using secondary IDs: You can use secondary authorization IDs to define a RACF group. After you define the RACF group, you can assign privileges to it that are shared by multiple primary IDs. For example, suppose that DB2OWNER wants to create a group GROUP1 and to give the ID USER1 administrative authority over the group. USER1 should be able to connect other existing users to the group. To create the group, DB2OWNER issues this RACF command:

ADDGROUP GROUP1 OWNER(USER1) DATA('GROUP FOR DEPT. G1')

To let the group connect to the DSN system through TSO, DB2OWNER issues this RACF command:

PERMIT DSN.BATCH CLASS(DSNR) ID(GROUP1) ACCESS(READ)

USER1 can now connect other existing IDs to the group GROUP1 by using the RACF CONNECT command:

CONNECT (USER2 EPSILON1 EPSILON2) GROUP(GROUP1)

If you add or update secondary IDs for CICS transactions, you must start and stop the CICS attachment facility to ensure that all threads sign on and get the correct security information.

Allowing users to create data sets: You can use RACF to protect the data sets that store Db2 data. If you use the approach and when you create a new group of Db2 users, you might want to connect it to a group that can create data sets. To allow USER1 to create and control data sets, DB2OWNER creates a generic

profile and permits complete control to USER1 and to the four administrators. The SYSDSP parameter also gives control to Db2.

ADDSD 'DSNC111.DSNDBC.ST*' UACC(NONE) PERMIT 'DSNC111.DSNDBC.ST*' ID(USER1 SYSDSP SYSAD1 SYSAD2 SYSOP1 SYSOP2) ACCESS(ALTER)

Related tasks

Defining RACF user IDs for Db2-started tasks A Db2 subsystem provides started-task address spaces.

Adding RACF groups You can issue the **ADDGROUP** command to add a new RACF group.

Granting authorization on Db2 commands

IDs must be authorized to issue Db2 commands. If you authorize IDs by issuing Db2 GRANT statements, the GRANT statements must be made to a primary authorization ID, a secondary authorization ID, a role, or PUBLIC.

About this task

When RACF is used for access control, an ID must have appropriate RACF authorization on Db2 commands or must be granted authorization for Db2 commands to issue commands from a logged-on MVS console or from TSO SDSF.

Procedure

To ensure that an ID can issue Db2 commands from logged-on MVS consoles or TSO SDSF, choose one of the following:

- Grant authorization for Db2 commands to the primary, secondary authorization ID, or role.
- Define RACF classes and permits for Db2 commands.
- Grant SYSOPR authority to appropriate IDs.

Permitting access from remote requesters

You can use the DSNR RACF class to access the distributed data address space and to control access from remote requesters.

About this task

The following RACF commands let the users in the group DB2USER access DDF on the DSN subsystem. These DDF requests can originate from any partner in the network.

Procedure

 For example, to permit READ access on profile DSN.DIST in the DSNR class to DB2USER, issue the following RACF command:

PERMIT DSN.DIST CLASS(DSNR) ID(DB2USER) ACCESS(READ)

If you want to ensure that a specific user can access only when the request originates from a specific LU name, you can use WHEN(APPCPORT) on the PERMIT command.

For example, to permit access to Db2 distributed processing on subsystem DSN when the request comes from USER5 at LUNAME equal to NEWYORK, issue the following RACF command:

• For connections that come through TCP/IP, use the RACF APPCPORT class or the RACF SERVAUTH class with TCP/IP Network Access Control to protect unauthorized access to Db2.

To use the RACF APPCPORT class, perform the following steps:

a) Activate the ACCPORT class by issuing the following RACF command:

SETROPTS CLASSACT(APPCPORT) REFRESH

b) Define the general resource profile and name it TCPIP. Specify NONE for universal access and APPCPORT for class. Issue the following RACF command:

RDEFINE APPCPORT TCPIP UACC(NONE)

c) Permit READ access on profile TCPIP in the APPCPORT class. To permit READ access to USER5, issue the following RACF command:

```
PERMIT TCPIP ACCESS(READ) CLASS(APPCPORT) ID(USER5)
```

 d) Permit READ access on profile DSN.DIST in the DSNR class. To permit READ access to USER5, issue the following RACF command:

PERMIT DSN.DIST CLASS(DSNR) ID(USER5) ACCESS(READ) +
 WHEN(APPCPORT(TCPIP))

e) Refresh the APPCPORT class by issuing the following RACF command:

SETROPTS REFRESH RACLIST(APPCPORT)

If the RACF APPCPORT class is active on your system, and a resource profile for the requesting LU name already exists, you must permit READ access to the APPCPORT resource profile for the user IDs that Db2 uses.

You must permit READ access even when you are using the DSNR resource class. Similarly, if you are using the RACF APPL class and that class restricts access to the local Db2 LU name or generic LU name, you must permit READ access to the APPL resource for the user IDs that Db2 uses.

Recommendation: Use z/OS Communications Server IP Network Access Control and z/OS Security Server RACF SERVAUTH class if you want to use the port of entry (POE) for remote TCP/IP connections.

- To use the RACF SERVAUTH class and TCP/IP Network Access Control, perform the following steps:
- a) Set up and configure TCP/IP Network Access Control by using the NETACCESS statement that is in your TCP/IP profile.

For example, suppose that you need to allow z/OS system access only to IP addresses from 9.0.0.0 to 9.255.255.255. You want to define these IP addresses as a security zone, and you want to name the security zone IBM. Suppose also that you need to deny access to all IP addressed outside of the IBM security zone, and that you want to define these IP addresses as a separate security zone. You want to name this second security zone WORLD. To establish these security zones, use the following NETACCESS clause:

NETACCESS INBOUND	OUTBOUND
; NETWORK/MASK	SAF
9.0.0.0/8	IBM
DEFAULT	WORLD
ENDNETACCESS	

Now, suppose that USER5 has an IP address of 9.1.2.3. TCP/IP Network Access Control would determine that USER5 has an IP address that belongs to the IBM security zone. USER5 would be granted access to the system. Alternatively, suppose that USER6 has an IP address of 1.1.1.1. TCP/IP Network Access Control would determine that USER6 has an IP address that belongs to the WORLD security zone. USER6 would not be granted access to the system.

b) Activate the SERVAUTH class by issuing the following TSO command:

```
SETROPTS CLASSACT(SERVAUTH)
```

c) Activate RACLIST processing for the SERVAUTH class by issuing the following TSO command:

SETROPTS RACLIST(SERVAUTH)

d) Define the IBM and WORLD general resource profiles in RACF to protect the IBM and WORLD security zones by issuing the following commands:

RDEFINE SERVAUTH (EZB.NETACCESS.ZOSV1R5.TCPIP.IBM) UACC(NONE) RDEFINE SERVAUTH (EZB.NETACCESS.ZOSV1R5.TCPIP.WORLD) UACC(NONE)

e) Permit USER5 and SYSDSP read access to the IBM profile by using the following commands.

PERMIT EZB.NETACCESS.ZOSV1R5.TCPIP.IBM ACCESS(READ) CLASS(SERVAUTH) ID(USER5) PERMIT EZB.NETACCESS.ZOSV1R5.TCPIP.IBM ACCESS(READ) CLASS(SERVAUTH) ID(SYSDSP)

f) Permit SYSDSP read access to the WORLD profile by using the following command:

PERMIT EZB.NETACCESS.ZOSV1R5.TCPIP.WORLD ACCESS(READ) CLASS(SERVAUTH) ID(SYSDSP)

g) For these permissions to take effect, refresh the RACF database by using the following command:

SETROPTS REFRESH RACLIST(SERVAUTH)

Enabling IMS transactions to use RACF authorization control of Db2 objects

You can enable IMS transactions to use RACF authorization control of Db2 objects and other resources.

Procedure

To enable IMS transactions to exploit RACF authorization of Db2 objects and resources:

- 1. Configure IMS to use APPC/OTMA security FULLor create an IMS Build Security Environment exit routine (DFSBSEX0). Code DFSBSEX0 to return RC4 in register 15, which will instruct IMS to create the ACEE in the dependent region.
- 2. Install the default Db2 exit routine DSNX@XAC.
- 3. Define a RACF profile for each Db2 object and resource to be accessed by IMS transactions.
- 4. Issue the RACF PERMIT command to authorize IMS transaction authorization IDs that are allowed to access these Db2 objects and resources.

Related concepts

The default Db2 exit routine (RACF Access Control Module Guide) Related information

Related Information

IMS build security environment exit routine Administering APPC/IMS

Managing authorization for stored procedures

Db2 for z/OS provides a variety of methods to help you ensure that users are properly authorized to create and execute stored procedures. Db2 also provides ways for you to keep stored procedures secure.

Procedure

- _ <u>"Authorizing IDs for using RRSAF" on page 154</u>
- "Specifying WLM-established server address spaces for stored procedures" on page 154
- __• "Managing authorizations for creation of stored procedures in WLM environments" on page 155
- __ "Authorizing users to refresh WLM environments" on page 156
- __ "Controlling stored procedure access to non-Db2 resources by using RACF" on page 157
- __• "Granting the CREATEIN privilege on schemas for stored procedures" on page 157
- __ "Granting privileges for using distinct types" on page 158

- __ "Granting privileges for using JAR files" on page 159
- __ "Granting privileges for executing stored procedures and stored procedure packages" on page 160
- ___• "Controlling remote execution of stored procedures by using trusted contexts" on page 161

Authorizing IDs for using RRSAF

When started, WLM-established address spaces use the Resource Recovery Services attachment facility (RRSAF) to attach to Db2. You must authorize the IDs that are associated with WLM-established stored procedures address spaces so that they can use RRSAF.

Procedure

To authorize user IDs that are associated with WLM-established stored procedures address spaces to use RRSAF:

1. Create a *ssnm*.RRSAF profile in RACF.

For example, you can define *ssnm*.RRSAF in the DSNR resource class with a universal access authority of NONE by issuing the following command:

RDEFINE DSNR (DB2P.RRSAF DB2T.RRSAF) UACC(NONE)

2. Refresh the in-storage profiles with the profile that you just defined. For example, you can issue the following command:

SETROPTS RACLIST(DSNR) REFRESH

 Add user IDs that are associated with WLM-established stored procedures address spaces to the RACF-started procedures table.

For example, you can issue the following command:

RDEFINE STARTED DSNWLM.** STDATA(USER(SYSDP) GROUP(DB2SYS) TRUSTED(NO))

4. Refresh the in-storage profiles. For example, you can issue the following command:

SETROPTS RACLIST(STARTED) REFRESH

5. Grant read access to *ssnm*.RRSAF to the IDs that are associated with the stored procedures address spaces.

For example, you can issue the following command:

PERMIT DB2P.RRSAF CLASS(DSNR) ID(SYSDSP) ACCESS(READ)

Related information

Summary of RACF commands (CICS Transaction Server for z/OS)

Specifying WLM-established server address spaces for stored procedures

You can manage access to WLM through the server resource class and specify address spaces as WLMestablished server address spaces for running stored procedures.

Procedure

To specify address spaces as WLM-established server address spaces that can run stored procedures:

1. Define a new SERVER class by using the server resource class.

If you do not define a SERVER class, any address space that connects to WLM as a server address space can run stored procedures.

2. Authorize a RACF profile to associate with the SERVER class. For example:

RDEFINE SERVER (DB2.ssnm.applenv)

In this command, *applenv* is the name of the application environment that is associated with the stored procedure. For example, assume that you want to define the following profile names:

- DB2.DB2T.TESTPROC
- DB2.DB2P.PAYROLL
- DB2.DB2P.QUERY

To define these profile names, use the following RACF command:

RDEFINE SERVER (DB2.DB2T.TESTPROC DB2.DB2P.PAYROLL DB2.DB2P.QUERY)

3. Activate the resource class.

For example, you can issue the following command:

SETROPTS RACLIST(SERVER) REFRESH

4. Grant read access to the user IDs that are associated with the stored procedures address space. For example, you can issue the following commands:

PERMITDB2.DB2T.TESTPROCCLASS(SERVER)ID(SYSDSP)ACCESS(READ)PERMITDB2.DB2P.PAYROLLCLASS(SERVER)ID(SYSDSP)ACCESS(READ)PERMITDB2.DB2P.QUERYCLASS(SERVER)ID(SYSDSP)ACCESS(READ)

Related information

Summary of RACF commands (CICS Transaction Server for z/OS)

Managing authorizations for creation of stored procedures in WLM environments

You can group and isolate applications into different WLM environments based on their security requirements. You can then authorize or prevent users from creating stored procedures in a security-sensitive environment.

About this task

Db2 invokes RACF to determine if users are allowed to create stored procedures in a WLM environment. The WLM ENVIRONMENT keyword on the CREATE PROCEDURE statement identifies the WLM environment to use for running the stored procedure.

Db2 checks the resource authorization by using the DSNR RACF class as follows:

• In a Db2 data sharing environment, Db2 checks the following RACF resource name, where *db2-groupname* is the name of the Db2 data sharing group:

db2-groupname.WLMENV.wlm-environment

• In a non-data sharing environment, Db2 checks the following RACF resource name, where *db2-ssid* is the Db2 subsystem name:

db2-ssid.WLMENV.wlm-environment

Attempts fail when unauthorized users try to create or run stored procedures.

Procedure

Use RACF commands:

• To authorize individual users or groups of users to create stored procedures in a specific WLM environment, issue the RACF PERMIT command. For example, you can authorize the user whose ID

is DB2USER1 to create stored procedures on the Db2 subsystem DB2A (non-data sharing) in a WLM environment named PAYROLL:

PERMIT DB2A.WLMENV.PAYROLL CLASS(DSNR) ID(DB2USER1) ACCESS(READ)

When user ID DB2USER1 attempts to create a stored procedure in the PAYROLL WLM environment, Db2 performs a resource authorization check by using the DSNR RACF class and grants permission.

 To prevent users on a particular Db2 subsystem from creating stored procedures, issue the RACF DEFINE command. You can also use this command to revoke the default universal access of a WLM environment and set it to NONE,

For example, you can issue the following command to prevent all users on Db2 subsystem DB2A (non-data sharing) from creating stored procedures or user-defined functions in the WLM environment named PAYROLL:

RDEFINE DSNR (DB2A.WLMENV.PAYROLL) UACC(NONE)

Related tasks

Assigning stored procedures and functions to WLM application environments (Db2 Performance) **Related information** Summary of RACF commands (CICS Transaction Server for z/OS)

Authorizing users to refresh WLM environments

When you prepare a new version of a stored procedure in a WLM application environment, you need to activate the updated stored procedure by refreshing the application environment.

About this task

You can refresh the WLM environment by issuing a VARY REFRESH command at a z/OS command line. Alternatively, you can execute the WLM_REFRESH stored procedure, which is supplied by Db2 and executes the VARY REFRESH command. This stored procedure is useful when users need to refresh the WLM environment but are not authorized to issue operator commands.

Procedure

To authorize users to use the WLM_REFRESH stored procedure:

1. Grant access to the RACF resource profile for each application environment.

Db2 checks the resource authorization by using the DSNR RACF class as follows:

• In a Db2 data sharing environment, Db2 checks the following RACF resource name, where *db2-groupname* is the name of the Db2 data sharing group:

```
db2-groupname.WLMENV.wlm-environment
```

• In a non-data sharing environment, Db2 checks the following RACF resource name, where *db2-ssid* is the Db2 subsystem name:

```
db2-ssid.WLMENV.wlm-environment
```

For example, assume that you want to authorize RACF group DEVL7083 to access the WLM_REFRESH RACF resource profile for application environment DB9AWLM on subsystem DB9A. To authorize the RACF group in this way, you can issue this command:

```
RDEFINE DSNR (DB9A.WLM_REFRESH.DB9AWLM)
PE DB9A.WLM_REFRESH.DB9AWLM +
CLASS(DSNR) ID(DEVL7083) ACCESS(READ)
END
```

2. Grant the EXECUTE privilege on the stored procedure to users or groups who need to refresh the environment.

For example, you can issue the following GRANT statement to authorize the RACF group DEVL7083 to execute the WLM_REFRESH stored procedure on application environment DB9AWLM:

GUPI

GRANT EXECUTE ON PROCEDURE SYSPROC.WLM_REFRESH TO DEVL7083;

GUPI

You need to grant the EXECUTE privilege only once because you supply the application environment name as a variable when you execute the stored procedure.

Related reference

WLM_REFRESH stored procedure (Db2 SQL) GRANT statement (function or procedure privileges) (Db2 SQL) **Related information** Summary of RACF commands (CICS Transaction Server for z/OS)

Controlling stored procedure access to non-Db2 resources by using RACF

You can control Db2 stored procedure access to non-Db2 resources (such as VSAM files) by using RACF (or another external security product).

Procedure

GUPT To control access to non-Db2 resources for an existing stored procedure that does not require RACF (or another external security product):

- 1. Issue the ALTER PROCEDURE statement with the SECURITY USER clause.
- 2. Ensure that the user ID that calls the stored procedure has RACF authority to the resources.
- 3. Enable RACF checking for the caller's ID.
- 4. For improved performance, specify the following keywords in the COFVLF*xx* member of library SYS1.PARMLIB to cache the RACF profiles in the virtual look-aside facility (VLF) of z/OS. For example:

CLASS NAME(IRRACEE) EMAJ(ACEE)

GUPI

Related reference

CREATE PROCEDURE statement (SQL - external procedure) (deprecated) (Db2 SQL) CREATE PROCEDURE statement (external procedure) (Db2 SQL) ALTER PROCEDURE statement (SQL - external procedure) (deprecated) (Db2 SQL) ALTER PROCEDURE statement (external procedure) (Db2 SQL)

Related information

COFVLFxx (virtual lookaside facility parameters) (MVS Initialization and Tuning Reference)

Granting the CREATEIN privilege on schemas for stored procedures

When a stored procedure is created, it is explicitly or implicitly qualified by a schema. Users must have the required CREATEIN privilege on the schema before they can create stored procedures.

About this task

Many users create stored procedures in the same schema at an application level. These users need the CREATEIN privilege on the schema. You can grant this privilege to a secondary ID or role that is

associated with individual users. Those users can then issue a SET CURRENT SQLID statement to the secondary ID or role prior to creating stored procedures in the schema.

Procedure

Issue a GRANT statement with the appropriate options, depending on whether you are granting the privilege to a secondary ID or to a role.

• For a secondary ID, issue a GRANT statement with the CREATEIN ON SCHEMA clause. Specify the schema name and secondary ID. For example, assume that you want a user with the secondary ID of PAOLORW to be able to create stored procedures in a schema named DEVL7083. To give this user the necessary privilege, you can issue this statement:

GRANT CREATEIN ON SCHEMA DEVL7083 TO PAOLORW;

If the ID PAOLORW issues a CREATE PROCEDURE statement without having the required CREATEIN privilege on the schema, an error occurs, and the procedure is not created.

• For a role, issue a GRANT statement with the CREATEIN ON SCHEMA clause. Specify the schema name and the role that will be in effect when the stored procedure is created. (For users to be associated with a role, the trusted context that links them to the role needs to be defined with the ROLE AS OBJECT OWNER AND QUALIFIER clause.) For example, assume that you want to grant the CREATEIN privilege to a role named ADMINISTRATOR so that users who are associated with the ADMINISTRATOR role can create stored procedures in a schema named DEVL7083. To grant this privilege, you can issue this statement:

GRANT CREATEIN ON SCHEMA DEVL7083 TO ROLE ADMINISTRATOR;

If a user who is associated with the role named ADMINISTRATOR issues a CREATE PROCEDURE statement without having the required CREATEIN privilege on the schema, an error occurs, and the procedure is not created.

Results

After a secondary ID or role is granted the CREATEIN privilege for a stored procedure and then creates a stored procedure, that ID or role is the owner of that stored procedure.

Related reference

GRANT statement (schema privileges) (Db2 SQL)

Granting privileges for using distinct types

Stored procedures can pass parameters that have a distinct type as a data type. When a distinct type is used as a stored procedure parameter, users who create the stored procedure need the USAGE privilege on the distinct type.

About this task

When you create a distinct type, you, as the owner of that type, implicitly have the USAGE privilege on the type. You also have the EXECUTE privilege on the associated cast functions. If other users want to create stored procedures that pass a parameter with that distinct type, you need to explicitly grant the USAGE privilege to them.

Procedure

Issue the GRANT statement with the USAGE ON TYPE clause, and specify the name of the distinct type.

• You can grant privileges for using distinct types to an authorization ID. For example, assume that you want the user whose authorization ID is PAOLORW to be able to use the US_DOLLARS distinct type, which you created. Specifically, this user needs to create a stored procedure that passes a parameter with this data type. To grant this privilege, you can issue this statement:

GUPI

GRANT USAGE ON TYPE US_DOLLARS TO PAOLORW;

GUPI

• You can grant privileges for using distinct types to a role. For example, if you want the role named ADMINISTRATOR to be able to use the US_DOLLARS distinct type, you can issue this statement:

GUPI

GRANT USAGE ON TYPE US_DOLLARS TO ROLE ADMINISTRATOR;

GUPI

Related reference

GRANT statement (type or JAR file privileges) (Db2 SQL)

Granting privileges for using JAR files

To use Java archive (JAR) files, you need to have the USAGE privilege on the JAR.

About this task

If you have the USAGE privilege on the JAR, you can specify a JAR file in the EXTERNAL NAME clause of a stored procedure with a language type of Java.

Procedure

Issue the GRANT statement, specifying the USAGE clause.

For example, assume that you want the user whose AUTHID is PAOLORW to create a Java stored procedure, EMPDTL1J. Assume that the external name of the stored procedure is to be DEVL7083.EmpJar:EmpDtl1J.GetEmpDtls, where:

DEVL7083.EmpJar

Is the JAR file name.

EmpDtl1J

Is the class name.

GetEmpDtls

Is the method name.

AUTHID PAOLORW needs the USAGE privilege (from the JAR file owner ID or schema that was used for executing the INSTALL_JAR stored procedure). The following statement grants this privilege:

GUPI

GRANT USAGE ON JAR DEVL7083.EmpJar TO PAOLORW;

GUPI

In addition, if specified, the contents of the JAR file must already be installed in the Db2 catalog at the time the stored procedure is created.

Related reference

GRANT statement (type or JAR file privileges) (Db2 SQL)

Granting privileges for executing stored procedures and stored procedure packages

After you create a stored procedure, you need to grant EXECUTE privilege to users who plan to run the stored procedure and the stored procedure package. You can use the GRANT statement to grant the required privileges.

About this task

GUPI Invoking a stored procedure requires the EXECUTE privilege on the stored procedure.

For external stored procedures (including external SQL procedures), and for native SQL procedures, additional authority is needed for the stored procedure package and for most packages that run in the stored procedure. This is true for external security as well as for Db2 data access control.

Procedure

To grant privileges for executing stored procedures and stored procedure packages:

- 1. Issue the SQL GRANT statement with the EXECUTE ON PROCEDURE clause to the appropriate authorization ID or role.
 - To grant the EXECUTE privilege to an authorization ID, use the GRANT statement with the EXECUTE ON PROCEDURE clause. For example, to grant EXECUTE privilege for a stored procedure named SPNAME to a user whose authorization ID is PAOLORW, you can issue the following statement:

```
GRANT EXECUTE ON PROCEDURE SPNAME TO PAOLORW;
```

• To grant the EXECUTE privilege to a role, use the GRANT statement with the EXECUTE ON PROCEDURE clause and the ROLE clause. For example, to grant EXECUTE privilege for a stored procedure named SPNAME to a role named ADMINISTRATOR, you can issue the following statement:

GRANT EXECUTE ON PROCEDURE SPNAME TO ROLE ADMINISTRATOR;

The DYNAMICRULES behavior for the plan or package that contains the CALL statement determines which authorization ID or role holds the privilege.

- 2. Issue the SQL GRANT EXECUTE ON PACKAGE statement with the appropriate options, depending on whether you are granting the privilege to an authorization ID or a role:
 - To grant the EXECUTE privilege on the package to an authorization ID, issue the GRANT statement with the EXECUTE ON PACKAGE clause. For example, to grant the privilege to execute a package named PKGNAME to a user whose authorization ID is PAOLORW, you can issue this statement:

GRANT EXECUTE ON PACKAGE PKGNAME TO PAOLORW;

• To grant the EXECUTE privilege on the package to a role, issue the GRANT statement with the EXECUTE ON PACKAGE clause and the ROLE clause. For example, to grant this privilege to execute a package named PKGNAME to a role named ADMINISTRATOR, you can issue this statement:

GRANT EXECUTE ON PACKAGE PKGNAME TO ROLE ADMINISTRATOR;

The complete syntax of the GRANT statement that you should use depends on the type of package.

Related reference

CALL statement (Db2 SQL) GRANT statement (function or procedure privileges) (Db2 SQL) GRANT statement (package privileges) (Db2 SQL)

Controlling remote execution of stored procedures by using trusted contexts

You can use trusted contexts and roles to control how a stored procedure can be executed. A *trusted context* is an independent database entity that is based on a system authorization ID (SYSTEM AUTHID) and connection trust attributes.

Before you begin

If you set field 1 (RESTART or DEFER) to DEFER and set field 2 (objects to restart or defer) to ALL in installation panel DSNTIPS, you cannot use trusted connections.

About this task

GUPT For a remote stored procedure CALL, the SYSTEM AUTHID is derived from the system user ID that is provided by an external entity, such as a middleware server. This ID is derived when the connection is initiated. The connection trust attributes are as follows, specified in the CREATE TRUSTED CONTEXT statement:

ADDRESS

IP address or domain name. (The protocol is restricted to TCP/IP only.)

SERVAUTH

A resource in the RACF SERVAUTH class.

ENCRYPTION

Minimum level of encryption for the connection:

NONE

No encryption. This is the default value.

LOW

DRDA data stream encryption.

HIGH

Secure Sockets Layer (SSL) encryption.

Procedure

To call a stored procedure in trusted contexts:

1. Define a role by issuing the CREATE ROLE statement.

A *role* is a database entity that groups together one or more privileges and that can be assigned to users by using a trusted context. A role can be used in conjunction with a trusted context and stored procedures to identify one or more authorization IDs that can execute a stored procedure.

For example, assume that you want to call stored procedure DEVL7083.EMPDTL1C, which resides on Db2 subsystem DB9A by using authorization ID PAOLORW. Assume also that you want to define a role called SP_CALLER for use by PAOLORW. You can issue the following SQL statement:

CREATE ROLE SP_CALLER;

 Grant the EXECUTE privilege on a stored procedure to that role. For example, to grant the EXECUTE privilege to the role called SP_CALLER for the stored procedure named EMPDTL1C, you can issue the following statement:

GRANT EXECUTE ON PROCEDURE DEVL7083.EMPDTL1C TO ROLE SP_CALLER;

3. Have an authorized user bind the stored procedure package.

The user either needs SYSADM authority or must have explicitly bind authority for that stored procedure.

For example, assume that an authorized user wants to bind stored procedure DEVL7083.EMPDTL1C into stored procedure package DEVL7083.EMPDTL1CPKG. You can issue the following statement:

BIND PACKAGE(DEVL7083) MEMBER(EMPDTL1CPKG)

4. Grant the EXECUTE privilege on the stored procedure package to the authorization ID or role that needs to run it.

For example, to grant the EXECUTE privilege on stored procedure package DEVL7083.EMPDTL1CPKG to the role named SP_CALLER, you can issue this statement:

```
GRANT EXECUTE ON PACKAGE DEVL7083.EMPDTL1CPKG TO ROLE SP_CALLER;
```

5. Define the trusted context.

For example, assume that you want to define a trusted context named TRUSTED_EMPDTL1C that uses:

- System authorization ID PAOLORW
- Default role SP_CALLER
- IP address 9.30.28.113

To define this trusted context, you can issue the following statement:

```
CREATE TRUSTED CONTEXT TRUSTED_EMPDTL1C
BASED UPON CONNECTION USING SYSTEM AUTHID PAOLORW
ATTRIBUTES (ADDRESS '9.30.28.113')
DEFAULT ROLE SP_CALLER
ENABLE;
```

GUPI

6. Optional: Verify that the authorization ID can execute the stored procedure by running the application program that invokes the stored procedure and looking at the system output.

For example, assume that an application named CALLEMPD uses a CALL *:host-variable* statement to invoke the stored procedure named DEVL7083.EMPDTL1C. Assume also that the application program generates trace output. You might see the following system output:

```
DEVL7083.CALLEMPD - Run started.
Data returned in result sets is limited to the first 50 rows.
Data returned in result set columns is limited to the first 100
bytes or characters.
DEVL7083.CALLEMPD - Calling the stored procedure.
DEVL7083.CALLEMPD - Run completed.
```

Related reference

CREATE TRUSTED CONTEXT statement (Db2 SQL) CREATE ROLE statement (Db2 SQL) GRANT statement (function or procedure privileges) (Db2 SQL)

Protecting connection requests that use the TCP/IP protocol

You can set your Db2 subsystem to send or receive connection requests that use the TCP/IP network protocol. You need to authorize the started task user ID (SYSDSP) that is associated with the DDF address space (*ssnm*DIST) to use the z/OS UNIX System Services.

Procedure

To secure connection requests over TCP/IP:

- 1. Create an OMVS segment in the RACF user profile for the started task user ID (SYSDSP)
- 2. Specify a z/OS UNIX user identifier of 0 and the maximum number of files of that the user is allowed to have concurrently active to 131702 in the following command:

ADDUSER ddfuid OMVS(UID(0) FILEPROCMAX(131702))

If the *ddfuid* ID already exists, use:

```
ALTUSER ddfuid OMVS(UID(0) FILEPROCMAX(131702))
```

The started task user ID of the Db2 distributed address space only needs a z/OS UNIX user identifier of 0 (UID(0)). A UID 0 is considered a superuser. If you don't want to grant the superuser authority to the started task user ID that is associated with the *ssnm*DIST address space during the Db2 installation, you can specify a value other than 0 for the UID parameter. Make sure that the value is a valid z/OS UNIX user identifier.

3. If you want to assign a z/OS group name to the address space, assign an OMVS segment to the z/OS group name by using one of the following RACF commands:

ADDGROUP ddfgnm OMVS(GID(nnn))...

ALTGROUP ddfgnm OMVS(GID(nnn))...

where *ddfgnm* is the z/OS group name and *nnn* is any valid, unique identifier.

The standard way to assign a z/OS userid and a z/OS group name to a started address space is to use the z/OS Security Server (RACF) STARTED resource class. This method enables you to dynamically assign a z/OS user ID by using commands instead of requiring an IPL to have the assignment take effect. The alternative method to assign a z/OS user ID and a z/OS group name to a started address space is to change the RACF started procedures table, ICHRIN03.

Results

You can also manage TCP/IP requests in a trusted context. A trusted context allows you to use a trusted connection without needing additional authentication and to acquire additional privileges through the definition of roles.

The TCP/IP Already Verified (DSN6FAC TCPALVER) controls whether Db2 accepts TCP/IP connection requests that contain only a user ID. However, in the case of a trusted context, it is the definition of the trusted context, not the TCPALVER setting, handles the requirement for switching users of a trusted connection.

Do not set DSN6FAC TCPALVER to YES if you use a trusted context. If you set TCPALVER to YES in the definition of the trusted context, you need to define the authorization ID that establishes the trusted connection in the USER clause to enforce the authentication requirement.

Related tasks

Defining Db2 resources to RACF

To establish RACF protection for your Db2 subsystem, you must define your Db2 resources to RACF and authorize RACF for authentication checking.

Permitting RACF access

You must perform certain tasks in a required order to enable a process to use protected RACF resources.

Managing authorization for stored procedures

Db2 for z/OS provides a variety of methods to help you ensure that users are properly authorized to create and execute stored procedures. Db2 also provides ways for you to keep stored procedures secure.

Establishing Kerberos authentication through RACF

Kerberos security is a network security technology that was developed at the Massachusetts Institute of Technology. The Kerberos security technology does not require passwords to flow in readable text because it uses encrypted tickets that contain authentication information for the users.

Establishing Kerberos authentication through RACF

Kerberos security is a network security technology that was developed at the Massachusetts Institute of Technology. The Kerberos security technology does not require passwords to flow in readable text because it uses encrypted tickets that contain authentication information for the users.

About this task

Db2 can use Kerberos security services to authenticate remote users. With Kerberos security services, remote users need to issue their Kerberos name and password to access Db2. They can use the same name and password for access throughout the network, which makes a separate password to access Db2 unnecessary.

A remote user who is authenticated to Db2 by means of Kerberos authentication must be registered in RACF profiles. An organization that runs a Kerberos server establishes its own *realm*. The name of the realm in which a client is registered is part of the client's name and can be used by the application server to accept or reject a request.

Procedure

To authenticate and register a remote user in RACF profiles:

1. Define the Kerberos realm to RACF by issuing the following command:

RDEFINE REALM KERBDFLT KERB(KERBNAME(localrealm) PASSWORD(mykerpw)

You must specify the name of the local realm in the definition. You must also specify a Kerberos password for RACF to grant Kerberos tickets.

2. Define local principals to RACF by issuing the following command:

AU RONTOMS KERB(KERBNAME(rontoms)) ALU RONTOMS PASSWORD(new1pw) NOEXPIRE

Make sure to change RACF passwords before the principals become active Kerberos users.

3. Map foreign Kerberos principals by defining KERBLINK profiles to RACF with a command similar to the following:

RDEFINE KERBLINK /.../KERB390.ENDICOTT.IBM.COM/RWH APPLDATA('RONTOMS')

You must also define a principal name for the user ID that is used in the *ssnmDIST* started task address space, as shown in the following example:

ALU SYSDSP PASSWORD(pw) NOEXPIRE KERB(KERBNAME(SYSDSP))

The *ssnm*DIST address space must have the RACF authority to use its SAF ticket parsing service. The user ID that is used for the *ssnmDIST* started task address space is SYSDSP.

4. Define foreign Kerberos authentication servers to the local Kerberos authentication server by issuing the following command:

RDEFINE REALM /.../KERB390.ENDICOTT.IBM.COM/KRBTGT/KER2000.ENDICOTT.IBM.COM + KERB(PASSWORD(realm0pw))

You must supply a password for the key to be generated. REALM profiles define the trust relationship between the local realm and the foreign Kerberos authentication servers. PASSWORD is a required keyword, so all REALM profiles have a KERB segment.

What to do next

Data sharing environments: Data sharing sysplex environments that use Kerberos security must have a Kerberos Security Server instance running on each system in the sysplex. The instances must either be in the same realm and share the same RACF database, or have different RACF databases and be in different realms.

Related tasks

Defining Db2 resources to RACF

To establish RACF protection for your Db2 subsystem, you must define your Db2 resources to RACF and authorize RACF for authentication checking.

Permitting RACF access

You must perform certain tasks in a required order to enable a process to use protected RACF resources.

Managing authorization for stored procedures

Db2 for z/OS provides a variety of methods to help you ensure that users are properly authorized to create and execute stored procedures. Db2 also provides ways for you to keep stored procedures secure.

Protecting connection requests that use the TCP/IP protocol

You can set your Db2 subsystem to send or receive connection requests that use the TCP/IP network protocol. You need to authorize the started task user ID (SYSDSP) that is associated with the DDF address space (*ssnm*DIST) to use the z/OS UNIX System Services.

Implementing Db2 support for enterprise identity mapping

Enterprise identity mapping (EIM) enables the mapping of user identities across servers that are integrated but that do not share user registries. Db2 supports the EIM capability by implementing the SAF user mapping plug-in callable service, which is part of the z/OS Security Server (RACF).

Before you begin

You can exploit the EIM support by using the IBM WebSphere Application Server 6.0.1, the IBM Db2 Driver for JDBC and SQLJ, and the IBM Db2 Driver for ODBC and CLI.

You must install the z/OS SAF user mapping plug-in service to implement the Db2 support for the EIM.

Procedure

To implement the Db2 support for EIM:

- 1. Configure the z/OS LDAP server with a TDBM backend
- 2. Set up RACF for the LDAP server
- 3. Configure the z/OS EIM domain controller
- 4. Add the SAF user mapping data set to LNKLIST

Results

If you enable Db2 support for EIM, Db2 can retrieve the mapped user ID from the SAF user mapping plug-in and specify the information in the ICTX structure. During the ENVIR=CREATE processing, Db2 passes the information to RACF through the RACROUTE REQUEST=VERIFY macro service. When RACF successfully authenticates the user, the ICTX structure is anchored in the ACEEICTX field.

Note: The SAF user identity mapping plug-in service will not be supported in the future release of Db2 for z/OS.

Related reference

z/OS Security Server RACF Command Language Reference z/OS IBM Tivoli Directory Server Administration and Use for z/OS z/OS Integrated Security Services Enterprise Identity Mapping (EIM) Guide and Reference

Configuring the z/OS LDAP server

When Db2 receives an authenticated user registry name, it invokes the SAF user mapping plug-in service. This service uses the EIM domain, which is an LDAP server, to retrieve the z/OS user ID that is used as the primary authorization ID.

About this task

You can use the LDAP configuration (**ldapcnf**) utility to configure and set up a z/OS LDAP server. The LDAP configuration utility requires the ldap.profile input file that is shipped in the /usr/lpp/ ldap/etc directory. The ldap.profile file contains the settings that you need to set up the LDAP server.

Procedure

To configure a z/OS LDAP server:

- 1. Copy and modify the ldap.profile file based on your own environment.
- 2. Issue the following command to run the LDAP configuration utility with the ldap.profile file that you modified:

ldapcnf -i ldap.profile

The LDAP configuration utility generates the following output files:

- SLAPDCNF member as the LDAP server configuration file
- SLAPDENV member as the LDAP server environment variable file
- PROG member for APF authorization
- GLDSRV procedure for starting the LDAP server
- DSNAOINI configuration file for Db2 CLI
- TDBSPUFI Db2 SQL DDL statements for creating the TDBM environment
- DBCLI Db2 SQL BIND statements for binding the CLI/ODBC packages and plan
- RACF member for creating the RACF profiles that protect the LDAP server service task and grant permissions for the user ID to run the LDAP server

These output files are stored in the OUTPUT_DATASET_NAME that you specified in the ldap.profile file.

- 3. Submit the following output JCL files after Db2 is started:
 - DBCLI member file
 - RACF member file
- 4. Submit the TDBSPUFI member file by using the Db2 SPUFI interactive tool.
- 5. Start the LDAP server from SDSF or the operator's console.

The name of the LDAP server procedure file is the same as the user ID that is specified on the LDAPUSRID statement. The pre-assigned value is GLDSRV.

To start the LDAP server from SDSF, enter:

/s GLDSRV

To start the LDAP server from the operator's console, enter:

s GLDSRV

- 6. Copy the schema.user.ldif file from the /usr/lpp/ldap/etc directory to a local directory
- 7. Use the following **ldapmodify** utility to modify the schema entry for the TDBM backend
ldapmodify -h ldaphost -p ldapport -D binddn -w passwd -f file

The following example shows how to use the **ldapmodify** utility:

```
ldapmodify -h v25ec099.svl.ibm.com -p 3389
-D "cn=LDAP Administrator"
-w secret -f schema.user.ldif
```

At the top of the schema.user.ldif file, find the following line, and supply the appropriate TDBM suffix in that line

dn: cn=schema, <suffix>

The suffix is the same value that is used in the TDBM_SUFFIX statement in the ldap.profile file, as in the following example:

dn: cn=schema, o=IBM, c=US

8. Use the **ldapadd** utility to load the suffix entry and to create a user ID that is used by the SAF user mapping plug-in for binding with the LDAP server. You can use the following **ldapadd** utility statement:

ldapadd -h ldaphost -p ldapport -D binddn -w passwd -f file

The following is an example of using the **ldapadd** utility:

```
ldapadd -h v25ec099.svl.ibm.com -p 3389
-D "cn=LDAP Administrator"
    -w secret -f setup.ldap.ldif
```

Setting up RACF for the z/OS LDAP server

After you configure the z/OS LDAP server, you need to set up RACF to activate identity mapping. You also need to grant Db2 authority to use the SAF user mapping plug-in service.

Procedure

To set up RACF for the z/OS LDAP server:

1. Enable identity mapping by activating the FACILITY class.

The FACILITY class must be active to enable identity mapping. Use the following **SETROPTS** command if it is not already active at your installation:

SETROPTS CLASSACT(FACILITY)

2. Define a KEYMSTR profile to store an encryption key.

Make sure to choose a key that is known only to the security administrator, and store it in the KEYMSTR profile that you defined, as shown in the following example:

RDEF KEYSMSTR LDAP.BINDPW.KEY SSIGNON(KEYMASKED(0123456789ABCDEF))

The LDAP BIND passwords are encrypted with the key that is stored in the LDAP.BINDPW.KEY profile. The value of the key in this example is 0123456789ABCDEF.

3. Authorize Db2 to request lookup services by defining and granting READ access to the SYSDSP user in the following RACF profiles:

RDEF FACILITY IRR.RGETINFO.EIM UACC(NONE) PE IRR.RGETINFO.EIM ACCESS(READ) ID(SYSDSP) CL(FACILITY) RDEF FACILITY IRR.RDCEKEY UACC(NONE) PE IRR.RDCEKEY ACCESS(READ) ID(SYSDSP) CL(FACILITY) 4. Define the IRR.PROXY.DEFAULTS profile in the FACILITY class, as follows:

```
RDEF FACILITY IRR.PROXY.DEFAULTS

PROXY(LDAPHOST('ldap://v25ec099.svl.ibm.com:3389')

BINDDN('cn=eim user,o=IBM,c=US') BINDPW('secret'))

EIM(DOMAINDN('ibm-eimDomainName=My Domain,o=IBM,c=US')

LOCALREG('My Target Registry'))

SETROPTS RACLIST(FACILITY) REFRESH
```

Grant Db2 the authority to use the SAF user mapping plug-in service by issuing the following commands:

```
RDEF PROGRAM IRRSPIM ADDMEM ('USER.PRIVATE.DLLLIB'//NOPADCHK)
PE IRRSPIM ACCESS(READ) ID(SYSDSP) CL(PROGRAM)
RDEF PROGRAM IRRSPIME ADDMEM ('USER.PRIVATE.DLLLIB'//NOPADCHK)
PE IRRSPIME ACCESS(READ) ID(SYSDSP) CL(PROGRAM)
```

```
SETROPTS WHEN(PROGRAM) REFRESH
```

Setting up the EIM domain controller

After you set up the LDAP server and RACF, you need to use the RACF *eimadmin* utility to create and configure an EIM domain controller.

Procedure

To create an EIM domain controller in this situation:

1. Create an EIM domain by issuing the following command:

```
eimadmin -aD -d 'ibm-eimDomainName=My Domain,o=IBM,c=US'
-h ldap://v25ec099.svl.ibm.com:3389
-b "cn=LDAP Administrator" -w secret
```

The example shows that the new domain name is "My Domain." It also shows that the TDBM_SUFFIX statement in the ldap.profile file is defined as o=IBM,c=US.

Grant the EIM user access to the EIM domain for performing lookup services by issuing the following command:

```
eimadmin -aC -c MAPPING -q "cn=eim user, o=IBM, c=US" -f DN
-d 'ibm-eimDomainName=My Domain,o=IBM,c=US'
-h ldap://v25ec099.svl.ibm.com:3389
-b 'cn=LDAP Administrator' -w secret
```

3. Create the source registry in the EIM domain by issuing the following command:

```
eimadmin -aR -r "My Source Registry" -y KERBEROS
-d 'ibm-eimDomainName=My Domain,o=IBM,c=US'
-h ldap://v25ec099.svl.ibm.com:3389
-b 'cn=LDAP Administrator' -w secret
```

4. Create the target registry in the EIM domain by issuing the following command:

```
eimadmin -aR -r "My Target Registry" -y RACF
-d 'ibm-eimDomainName=My Domain,o=IBM,c=US'
-h ldap://v25ec099.svl.ibm.com:3389
-b 'cn=LDAP Administrator' -w secret
```

5. Add the enterprise identifier "Cat" to the EIM domain by issuing the following command:

eimadmin -aI -i "Cat" -d 'ibm-eimDomainName=My Domain,o=IBM,c=US' -h ldap://v25ec099.svl.ibm.com:3389 -b 'cn=LDAP Administrator' -w secret

You can add multiple enterprise identifiers to the same EIM domain at any time.

6. Associate registry user IDs with the identifiers in the EIM domain by issuing the following commands:

```
eimadmin -aA -u "Kitty" -r "My Source Registry" -t SOURCE
-i "Cat" -d 'ibm-eimDomainName=My Domain,o=IBM,c=US'
-h ldap://v25ec099.svl.ibm.com:3389
-b 'cn=LDAP Administrator' -w secret
eimadmin -aA -u "Buffy" -r "My Target Registry" -t TARGET
-o "db2/stlec1/valadist" -i "Cat"
-d 'ibm-eimDomainName=My Domain,o=IBM,c=US'
-h ldap://v25ec099.svl.ibm.com:3389
-b 'cn=LDAP Administrator' -w secret
```

Specify the "-o" flag with the "*db2/location-name/subsystem-name*"+ "dist" value when you define a user ID for Db2 to use as the primary authorization ID in your target registry. As the examples show, when Db2 calls the SAF user mapping plug-in service to retrieve the primary authorization ID, Db2 specifies the additional *db2/location-name/subsystem-name*"+ "dist" information for the plug-in service to look up.

If a target identity is found with the same information, the target identity "Buffy" is returned. If the target identity does not contain any additional information, user ID "Buffy" is also returned to Db2. However, if the target registry contains multiple user identities and if none of them contains the recommended additional information, no user identity is returned to Db2.

Adding the SAF user mapping plug-in data set to LNKLIST

The SAF user mapping plug-in IRRSPIME resides in a z/OS data set. This data set must be included in the LNKLST. If the data set is not included, you need to add it to the LNKLST.

Procedure

To add the z/OS data set that contains the SAF user mapping plug-in to the LNKLST:

1. Define a new LNKLST by issuing the following command from the operator console:

SETPROG LNKLST, DEFINE, NAME=MYLNKLST, COPYFROM=CURRENT

2. Add the USER.PRIVATE.DLLLIB data set on the USER01 volume to the new MYLNKLST by issuing the following command:

SETPROG LNKLST,ADD,NAME=MYLNKLST,DSNAME=USER.PRIVATE.DLLLIB, VOLUME=USER01

3. Activate the new MYLNKLST by issuing the following command:

SETPROG LNKLST, ACTIVATE, NAME=MYLNKLST

4. Use the MYLNKLST to update the current tasks in the system by issuing the following command:

SETPROG LNKLST,UPDATE,JOB=*

Implementing Db2 support for distributed identity filters

A *distributed identity filter* is a RACF mapping association between a RACF user ID and one or more distributed user identities. You can use the RACF **RACMAP** command to associate a distributed user identity with a RACF user ID.

About this task

Db2 provides support for z/OS identify propagation and distributed identity filters. You need to create distributed identity filters to take advantage of this support.

Procedure

To create a distributed identity filter:

1. Activate the RACF general resource IDIDMAP class and enable it for RACLIST processing by issuing the following command:

```
SETROPTS CLASSACT(IDIDMAP) RACLIST(IDIDMAP)
```

2. Define a distributed identity filter and associate the distributed user name with a RACF user ID by issuing the RACF **RACMAP** command.

To define a filter for a non-LDAP user name, specify the user name as a simple character string to be defined in a non-LDAP registry. Suppose that the distributed user name is 'MARY' which is defined in user registry 'Registry01'. If you want to map this user name to RACF user ID 'DB2USER1', you can issue the **RACMAP** command, as follows

```
RACMAP ID(DB2USER1) MAP
USERDIDFILTER(NAME('MARY'))
REGISTRY(NAME('Registry01'))
WITHLABEL('Filter for MARY from Registry01')
```

3. Refresh the IDIDMAP class profile by issuing the following command:

SETROPTS RACLIST(IDIDMAP) REFRESH

4. If necessary, review the distributed identity filter by issuing the following RACMAP LISTMAP command:

RACMAP ID(DB2USER1) LISTMAP

If the new filter is successfully created, the following ouput is returned:

Results

The new filter assigns RACF user ID DB2USER1 when the distributed identity is user MARY from Registry01. When user MARY authenticates her identity at her distributed application server and performs tasks that access a remote Db2 server system, Db2 passes distributed user name MARY and registry name Registry01 as character strings to RACF.

During Db2 remote connection processing, Db2 calls the RACF RACROUTE REQUEST=VERIFY ENVIR=CREATE macro service. RACF uses these data values to search the IDIDMAP profiles for a matching filter. RACF finds the matching filter labeled 'Filter for MARY from Registry01 and assigns it the DB2USER1 user ID. The remote connection then executes its transactions with the authority of the DB2USER1 user ID. If in place, audit records for this transaction contains both RACF user ID DB2USER1, distributed user MARY, and registry name Registry01 that Db2 passes to RACF.

Related reference

z/OS Security Server RACF Security Administrator's Guide

Managing connection requests from local applications

Different local processes enter the access control procedure at different points, depending on the environment in which they originate.

The following processes go through connection processing only:

- Requests originating in TSO foreground and background (including online utilities and requests through the call attachment facility)
- JES-initiated batch jobs
- Requests through started task control address spaces (from the z/OS START command)

The following processes go through connection processing and can later go through the sign-on processing:

- The IMS control region.
- The CICS recovery coordination task.
- DL/I batch.
- Applications that connect using the Resource Recovery Services attachment facility (RRSAF).

The following processes go through sign-on processing:

- Requests from IMS dependent regions (including MPP, BMP, and Fast Path)
- CICS transaction subtasks

IMS, CICS, RRSAF, and DDF-to-DDF connections can send a sign-on request, typically to execute an application plan. That request must provide a primary ID, and can also provide secondary IDs. After a plan is allocated, it need not be deallocated until a new plan is required. A different transaction can use the same plan by issuing a new sign-on request with a new primary ID.

Processing of connection requests

A connection request makes a new connection to Db2; it does not reuse an application plan that is already allocated. Therefore, an essential step in processing the request is to check that the ID is authorized to use Db2 resources.

Db2 completes the following steps to process a connection request:

1. Db2 obtains the initial primary authorization ID. As shown in the following table, the source of the ID depends on the type of address space from which the connection was made.

Table 50. Sources of initial primary authorization IDs	
Source	Initial primary authorization ID
TSO	TSO logon ID.
ВАТСН	USER parameter on JOB statement.
IMS control region or CICS	USER parameter on JOB statement.
IMS or CICS started task	Entries in the started task control table.
Remote access requests	Depends on the security mechanism used.

Table 50. Sources of initial primary authorization IDs

2. RACF is called through the z/OS system authorization facility (SAF) to check whether the ID that is associated with the address space is authorized to use the following resources:

- The Db2 resource class (CLASS=DSNR)
- The Db2 subsystem (SUBSYS=ssnm)
- The requested connection type

The SAF return code (RC) from the invocation determines the next step, as follows:

- If RC > 4, RACF determined that the RACF user ID is not valid or does not have the necessary authorization to access the resource name. Db2 rejects the request for a connection.
- If RC = 4, the RACF return code is checked.
 - If RACF return code value is **equal to 4**, the resource name is not defined to RACF and Db2 rejects the request with reason code X'00F30013'.
 - If RACF return code value is **not equal to 4**, RACF is not active. Db2 continues with the next step, but the connection request and the user are not verified.
- If RC = 0, RACF is active and has verified the RACF user ID; Db2 continues with the next step.
- 3. If RACF is active and has verified the RACF user ID, Db2 runs the connection exit routine. To use Db2 secondary IDs, you must replace the exit routine.

If you do not want to use secondary IDs, do nothing. The IBM-supplied default connection exit routine continues the connection processing. The process has the following effects:

- The Db2 primary authorization ID is set based on the following rules:
 - If a value for the initial primary authorization ID exists, the value becomes the Db2 primary ID.
 - If no value exists (the value is blank), the primary ID is set by default, as shown in the following table.

Table 51. Sources of default authorization identifiers		
Source	Default primary authorization ID	
TSO	TSO logon ID	
ВАТСН	USER parameter on JOB statement	
Started task, or batch job with no USER parameter	Default authorization ID set when Db2 was installed (UNKNOWN AUTHID on installation panel DSNTIPP)	
Remote request	None. The user ID is required and is provided by the DRDA requester.	

- The SQL ID is set equal to the primary ID.
- No secondary IDs exist.
- 4. Db2 determines if TSO and BATCH connections that use DSN, RRSAF, and Utilities are trusted.

For a TSO and BATCH connection that uses DSN, RRSAF, and Utilities, Db2 checks to see if a matching trusted context is defined for the primary authorization ID and the job name. If a matching trusted context is found, the connection is established as trusted.

Related concepts

Connection routines and sign-on routines

Your Db2 subsystem has two exit points for authorization routines, one in connection processing and one in sign-on processing. Both exit points perform crucial steps in the assignment of values to primary IDs, secondary IDs, and SQL IDs.

Related tasks

Using sample connection and sign-on exit routines for CICS transactions For a CICS transaction to use the sample connection or sign-on exit routines, the external security system, such as RACF, must be defined to CICS.

Specifying connection and sign-on routines

Your connection routine must have a CSECT name and entry point of DSN3@ATH. The name of the load module for the connection routine can be the same name, or it can be a different name. Your sign-on routine must have a CSECT name and entry point of DSN3@SGN. The name of the load module for the sign-on routine can be the same, or it can be a different name.

Debugging connection and sign-on routines

The diagnostic aids can assist you in debugging connection exit routines and sign-on exit routines.

Related reference

Processing of sign-on requests

Requests can come from IMS-dependent regions, CICS transaction subtasks, or RRS connections. For each of these types of requests, the initial primary ID is obtained immediately before a plan for

the transaction is allocated. A new sign-on request can run the same plan without de-allocating and reallocating the plan.

Using secondary IDs for connection requests

If you want to use Db2 secondary authorization IDs, you must replace the default connection exit routine. If you want to use RACF group names as Db2 secondary IDs, the easiest method is to use the IBM-supplied sample routine.

About this task

The following table lists the difference between the default and sample connection exit routines.

Table 52. Differences between the default and sample connection exit routines		
Default connection exit routine	Sample connection exit routine	
Supplied as object code.	Supplied as source code. You can change the code.	
Installed as part of the normal Db2 installation procedure.	Must be compiled and placed in the Db2 library.	
Provides values for primary IDs and SQL IDs, but does not provide values for secondary IDs.	Provides values for primary IDs, secondary IDs, and SQL IDs.	

The sample connection exit routine has the following effects:

- The sample connection exit routine sets the Db2 primary ID in the same way that the default routine sets the Db2 primary ID, and according to the following rules:
 - If the initial primary ID is not blank, the initial ID becomes the Db2 primary ID.
 - If the initial primary ID is blank, the sample routine provides the same default value as does the default routine.
 - If the sample routine cannot find a nonblank primary ID, Db2 uses the default ID (UNKNOWN AUTHID) from the DSNTIPP installation panel. In this case, no secondary IDs are supplied.
- The sample connection exit routine sets the SQL ID based on the following criteria:
 - The routine sets the SQL ID to the TSO data set name prefix in the TSO user profile table if the following conditions are true:
 - The connection request is from a TSO-managed address space, including the call attachment facility, the TSO foreground, and the TSO background.
 - The TSO data set name prefix is equal to the primary ID or one of the secondary IDs.
 - In all other cases, the routine sets the SQL ID equal to the primary ID.
- The secondary authorization IDs depend on RACF options:
 - If RACF is not active, no secondary IDs exist.
 - If RACF is active but its "list of groups" option is not active, one secondary ID exists (the default connected group name) if the attachment facility supplied the default connected group name.
 - If RACF is active and the "list of groups" option is active, the routine sets the list of Db2 secondary IDs to the list of group names to which the RACF user ID is connected. Those RACF user IDs that are in REVOKE status do not become Db2 secondary IDs. The maximum number of groups is 1012. The list of group names is obtained from RACF and includes the default connected group name.

If the default connection exit routine and the sample connection exit routine do not provide the flexibility and features that your subsystem requires, you can write your own exit routine.

Processing of sign-on requests

Requests can come from IMS-dependent regions, CICS transaction subtasks, or RRS connections. For each of these types of requests, the initial primary ID is obtained immediately before a plan for the transaction is allocated. A new sign-on request can run the same plan without de-allocating and reallocating the plan.

Unlike the connection processing, the sign-on processing does not check the RACF for the user ID of the address space. Db2 completes the following steps to process sign-on requests:

1. Db2 determines the initial primary ID as follows:

For IMS sign-ons from message-driven regions, if the user has signed on, the initial primary authorization ID is the user's sign-on ID. IMS passes to Db2 the IMS sign-on ID and the associated RACF connected group name, if one exists. If the user has not signed on, the primary ID is the LTERM name, or if that is not available, the PSB name. For a batch-oriented region, the primary ID is the value of the USER parameter on the job statement, if that is available. If that is not available, the primary ID is primary

For remote requests, the source of the initial primary ID is determined by entries in the SYSIBM.USERNAMES table. For connections using Resource Recovery Services attachment facility, the processing depends on the type of signon request:

- SIGNON
- AUTH SIGNON
- CONTEXT SIGNON

For SIGNON, the primary authorization ID is retrieved from ACEEUSRI if an ACEE is associated with the TCB (TCBSENV). This is the normal case. However, if an ACEE is not associated with the TCB, SIGNON uses the primary authorization ID that is associated with the address space, that is, from the ASXB. If the new primary authorization ID was retrieved from the ACEE that is associated with the TCB and ACEEGRPN is not null, Db2 uses ACEEGRPN to establish secondary authorization IDs.

With AUTH SIGNON, an APF-authorized program can pass a primary authorization ID for the connection. If a primary authorization ID is passed, AUTH SIGNON also uses the value that is passed in the secondary authorization ID parameter to establish secondary authorization IDs. If the primary authorization ID is not passed, but a valid ACEE is passed, AUTH SIGNON uses the value in ACEEUSRI for the primary authorization ID if ACEEUSRL is not 0. If ACEEUSRI is used for the primary authorization ID, AUTH SIGNON uses the value in ACEEGRPN as the secondary authorization ID if ACEEGRPL is not 0.

For CONTEXT SIGNON, the primary authorization ID is retrieved from data that is associated with the current RRS context using the context_key, which is supplied as input. CONTEXT SIGNON uses the CTXSDTA and CTXRDTA functions of RRS context services. An authorized function must use CTXSDTA to store a primary authorization ID prior to invoking CONTEXT SIGNON. Optionally, CTXSDTA can be used to store the address of an ACEE in the context data that has a context_key that was supplied as input to CONTEXT SIGNON. Db2 uses CTXRDTA to retrieve context data. If an ACEE address is passed, CONTEXT SIGNON uses the value in ACEEGRPN as the secondary authorization ID if ACEEGRPL is not 0.

2. Db2 runs the sign-on exit routine. **User action:** To use Db2 secondary IDs, you must replace the exit routine.

If you **do not** want to use secondary IDs, do nothing. Sign-on processing is then continued by the IBM-supplied default sign-on exit routine, which has the following effects:

- The initial primary authorization ID remains the primary ID.
- The SQL ID is set equal to the primary ID.
- No secondary IDs exist.

You can replace the exit routine with one of your own, even if it has nothing to do with secondary IDs. If you do, remember that IMS and CICS recovery coordinators, their dependent regions, and RRSAF take the exit routine only if they have provided a user ID in the sign-on parameter list.

3. Db2 determines if the user of a trusted RRSAF SIGNON connection is allowed to switch.

For a RRSAF SIGNON connection that is trusted, Db2 checks to see if the primary authorization ID is allowed to switch in the trusted connection. If the primary authorization ID is not allowed to switch, the connection is returned to the unconnected state.

Related concepts

Connection routines and sign-on routines

Your Db2 subsystem has two exit points for authorization routines, one in connection processing and one in sign-on processing. Both exit points perform crucial steps in the assignment of values to primary IDs, secondary IDs, and SQL IDs.

Related tasks

Using sample connection and sign-on exit routines for CICS transactions

For a CICS transaction to use the sample connection or sign-on exit routines, the external security system, such as RACF, must be defined to CICS.

Specifying connection and sign-on routines

Your connection routine must have a CSECT name and entry point of DSN3@ATH. The name of the load module for the connection routine can be the same name, or it can be a different name. Your sign-on routine must have a CSECT name and entry point of DSN3@SGN. The name of the load module for the sign-on routine can be the same, or it can be a different name.

Debugging connection and sign-on routines

The diagnostic aids can assist you in debugging connection exit routines and sign-on exit routines.

Related reference

Processing of sign-on requests

Requests can come from IMS-dependent regions, CICS transaction subtasks, or RRS connections. For each of these types of requests, the initial primary ID is obtained immediately before a plan for the transaction is allocated. A new sign-on request can run the same plan without de-allocating and reallocating the plan.

Using secondary IDs for sign-on requests

If you want the primary authorization ID to be associated with Db2 secondary authorization IDs, you must replace the default sign-on exit routine.

About this task

The procedure is similar to that for connection processing. If you want to use RACF group names as Db2 secondary IDs, the easiest method is to use the IBM-supplied sample routine. An installation job can automatically replace the default routine with the sample routine.

Distinguish carefully between the two routines. The default sign-on routine provides no secondary IDs and has the following effects:

- The initial primary authorization ID remains the primary ID.
- The SQL ID is set equal to the primary ID.
- No secondary IDs exist.

Like the sample connection routine, the sample sign-on routine supports Db2 secondary IDs and has the following effects:

- The initial primary authorization ID is left unchanged as the Db2 primary ID.
- The SQL ID is made equal to the Db2 primary ID.
- The secondary authorization IDs depend on RACF options:
 - If RACF is not active, no secondary IDs exist.
 - If RACF is active but its "list of groups" option is not active, one secondary ID exists; it is the name
 passed by CICS or by IMS.

If RACF is active and you have selected the option for a list of groups, the routine sets the list of Db2 secondary IDs to the list of group names to which the RACF user ID is connected, up to a limit of 1012 groups. The list of group names includes the default connected groupname.

Using sample connection and sign-on exit routines for CICS transactions

For a CICS transaction to use the sample connection or sign-on exit routines, the external security system, such as RACF, must be defined to CICS.

About this task

Define an external security system, such as RACF, to CICS with the following specifications:

- The CICS system initialization table must specify external security.
 - For CICS Version 4 or later, specify SEC=YES.
 - For earlier releases of CICS, specify EXTSEC=YES.

If you are using the CICS multiple region option (MRO), you must specify SEC=YES or EXTSEC=YES for every CICS system that is connected by interregion communication (IRC).

- If your version of CICS uses a sign-on table (SNT), the CICS sign-on table must specify EXTSEC=YES for each signed on user that uses the sign-on exit.
- When the user signs on to a CICS terminal-owning region, the terminal-owning region must propagate the authorization ID to the CICS application-owning region.

You must change the sample sign-on exit routine (DSN3SSGN) before using it if the following conditions are all true:

- You have the RACF list-of-groups option active.
- You have transactions whose initial primary authorization ID is not defined to RACF.

Related concepts

Connection routines and sign-on routines

Your Db2 subsystem has two exit points for authorization routines, one in connection processing and one in sign-on processing. Both exit points perform crucial steps in the assignment of values to primary IDs, secondary IDs, and SQL IDs.

Related reference

Processing of connection requests

A connection request makes a new connection to Db2; it does not reuse an application plan that is already allocated. Therefore, an essential step in processing the request is to check that the ID is authorized to use Db2 resources.

Processing of sign-on requests

Requests can come from IMS-dependent regions, CICS transaction subtasks, or RRS connections. For each of these types of requests, the initial primary ID is obtained immediately before a plan for the transaction is allocated. A new sign-on request can run the same plan without de-allocating and reallocating the plan.

Sample connection and sign-on routines

The sample Db2 exit routines are provided in the source code as members of prefix.SDSNSAMP.

Exit parameter list for connection and sign-on routines

The parameter list of connection and sign-on routines contains pointers to other information, such as the authorization ID list.

Managing connection requests from remote applications

If you control requests from remote applications, your Db2 subsystem might be accepting requests from applications that use SNA network protocols, TCP/IP network protocols, or both.

Security mechanisms for DRDA and SNA

DRDA encryption is not intended to provide confidentiality and integrity of passwords or data over a network that is not secure, such as the Internet. DRDA encryption uses an anonymous key exchange, Diffie-Hellman, which does not provide authentication of the server or the client. DRDA encryption is vulnerable to man-in-the-middle attacks.

Db2 for z/OS and z/OS support a wide variety of cryptographic authentication schemes and protocols, such as the use of the z/OS Communications Server IP Application Transparent Transport Layer Security (AT-TLS), to provide an authenticated key agreement that helps prevent man-in-the-middle and related attacks. These methods mathematically bind the agreed-upon key to other agreed-upon data to secure data over a network that is not secure.

DRDA and SNA have different security mechanisms. DRDA allows a user to be authenticated by using SNA security mechanisms or DRDA mechanisms, which are independent of the underlying network protocol. Make sure to use network security, such as client certificate authentication, SSL connections that use AT-TLS, or IPSec, to secure DRDA authentication mechanisms over a network that is not secure.

DRDA encryption for LOBs or XML requires the entire data to be materialized in memory before encrypting or decrypting it. When you use DRDA encryption for LOBs or XML, ensure that each LOB or XML is not larger than 2GB-64 bytes, which is the Db2 pool limit. Consider using the Secure Socket Layer (SSL) protocol, instead of DRDA encryption, for large data.

For an SNA network connection, a DRDA requester can send security tokens by using a SNA attach or a DRDA command. Db2 for z/OS as a requester uses SNA security mechanisms if it uses a SNA network connection (except for Kerberos) and DRDA security mechanisms for TCP/IP network connections (or when Kerberos authentication is chosen, regardless of the network type).

Related concepts

Encrypting your data with Secure Socket Layer (SSL) support Db2 supports Secure Socket Layer (SSL) protocol by using the z/OS Communications Server IP Application Transparent Transport Layer Security (AT-TLS).

Related tasks

Managing inbound TCP/IP-based connection requests

DRDA connections that use TCP/IP have fewer security controls than do connections that use SNA protocols. When planning to control inbound TCP/IP connection requests, you must decide whether you want the requests to have authentication information, such as RACF passwords, RACF PassTickets, and Kerberos tickets, passed along with authorization IDs.

Sending encrypted passwords from workstation clients

As a server, Db2 for z/OS can accept requests from remote workstation clients that use 256-bit Advanced Encryption Standard (AES) or 56-bit Data Encryption Standards (DES) encryption security over a TCP/IP network connection.

Related reference

TCP/IP ALREADY VERIFIED field (TCPALVER subsystem parameter) (Db2 Installation and Migration)

Related information

Protecting data through encryption and RACF

You can use the Db2 Secure Socket Layer (SSL) support or built-in data encryption functions to protect your sensitive data. You can also use the security features of RACF, or an equivalent system, to protect your data sets.

Security mechanisms for Db2 for z/OS as a requester

As a requester, Db2 for z/OS chooses SNA or DRDA security mechanisms based on the network protocol and the authentication mechanisms that you use. Make sure to use network security, such as client certificate authentication, SSL connections that use AT-TLS, or IPSec, to secure DRDA authentication mechanisms over a network that is not secure.

If you use SNA protocols, Db2 supports the following SNA authentication mechanisms:

- User ID only (already verified)
- User ID and password
- User ID and PassTicket

Authentication is performed based on SNA protocols, which means that the authentication tokens are sent in an SNA attach (FMH-5).

If you use TCP/IP protocols, Db2 supports the following DRDA authentication mechanisms:

- User ID only (already verified)
- User ID and password
- User ID and PassTicket

If you use TCP/IP protocols with the z/OS Integrated Cryptographic Service Facility, Db2 also supports the following DRDA authentication mechanisms:

- Encrypted user ID and encrypted password
- Encrypted user ID and encrypted security-sensitive data

Security-sensitive data is any input or output data. Examples are rows that are retrieved from a remote server, rows that are sent to the remote server, and SQL statement text.

Authentication is performed based on DRDA protocols, which means that the authentication tokens are sent in DRDA security flows. See <u>"Security mechanisms for DRDA and SNA" on page 177</u> for more information about using DRDA encryption.

Related concepts

Encrypting your data with Secure Socket Layer (SSL) support

Db2 supports Secure Socket Layer (SSL) protocol by using the z/OS Communications Server IP Application Transparent Transport Layer Security (AT-TLS).

Related tasks

Managing inbound TCP/IP-based connection requests

DRDA connections that use TCP/IP have fewer security controls than do connections that use SNA protocols. When planning to control inbound TCP/IP connection requests, you must decide whether you want the requests to have authentication information, such as RACF passwords, RACF PassTickets, and Kerberos tickets, passed along with authorization IDs.

Sending encrypted passwords from workstation clients

As a server, Db2 for z/OS can accept requests from remote workstation clients that use 256-bit Advanced Encryption Standard (AES) or 56-bit Data Encryption Standards (DES) encryption security over a TCP/IP network connection.

Related reference

Security mechanisms for Db2 for z/OS as a server

As a server, Db2 for z/OS can accept either SNA or DRDA authentication mechanisms. Make sure to use network security, such as client certificate authentication, SSL connections that use AT-TLS, or IPSec, to secure DRDA authentication mechanisms over a network that is not secure.

TCP/IP ALREADY VERIFIED field (TCPALVER subsystem parameter) (Db2 Installation and Migration)

Related information

Protecting data through encryption and RACF

You can use the Db2 Secure Socket Layer (SSL) support or built-in data encryption functions to protect your sensitive data. You can also use the security features of RACF, or an equivalent system, to protect your data sets.

Security mechanisms for Db2 for z/OS as a server

As a server, Db2 for z/OS can accept either SNA or DRDA authentication mechanisms. Make sure to use network security, such as client certificate authentication, SSL connections that use AT-TLS, or IPSec, to secure DRDA authentication mechanisms over a network that is not secure.

Db2 authenticates remote users from the security tokens that are obtained from the SNA ATTACH (FMH-5) or from the DRDA security commands that are described by each of the protocols. See <u>"Security</u> mechanisms for DRDA and SNA" on page 177 for more information about using DRDA encryption.

If you use TCP/IP protocols, Db2 accepts connection requests from remote clients that use AES or DES encryption to protect user credentials. Specifically, Db2 supports the following authentication methods for connection requests over a TCP/IP network:

- User ID only (already verified at the requester)
- User ID and password
- User ID and PassTicket
- Kerberos tickets
- Unencrypted user ID and encrypted password
- Encrypted user ID and encrypted password
- User ID, password, and new password

Db2 as a server also supports the following authentication mechanisms if the z/OS Integrated Cryptographic Service Facility is installed and active:

- · Encrypted user ID and encrypted security-sensitive data
- Encrypted user ID, encrypted password, and encrypted security-sensitive data
- Encrypted user ID, encrypted password, encrypted new password, and encrypted security-sensitive data

Security-sensitive data is any input or output data. Examples are rows that are retrieved from a remote server, rows that are sent to the remote server, and SQL statement text.

Related concepts

Encrypting your data with Secure Socket Layer (SSL) support

Db2 supports Secure Socket Layer (SSL) protocol by using the z/OS Communications Server IP Application Transparent Transport Layer Security (AT-TLS).

Related tasks

Managing inbound TCP/IP-based connection requests

DRDA connections that use TCP/IP have fewer security controls than do connections that use SNA protocols. When planning to control inbound TCP/IP connection requests, you must decide whether you want the requests to have authentication information, such as RACF passwords, RACF PassTickets, and Kerberos tickets, passed along with authorization IDs.

Sending encrypted passwords from workstation clients

As a server, Db2 for z/OS can accept requests from remote workstation clients that use 256-bit Advanced Encryption Standard (AES) or 56-bit Data Encryption Standards (DES) encryption security over a TCP/IP network connection.

Related reference

Security mechanisms for Db2 for z/OS as a requester

As a requester, Db2 for z/OS chooses SNA or DRDA security mechanisms based on the network protocol and the authentication mechanisms that you use. Make sure to use network security, such as client

certificate authentication, SSL connections that use AT-TLS, or IPSec, to secure DRDA authentication mechanisms over a network that is not secure.

TCP/IP ALREADY VERIFIED field (TCPALVER subsystem parameter) (Db2 Installation and Migration)

Related information

Protecting data through encryption and RACF

You can use the Db2 Secure Socket Layer (SSL) support or built-in data encryption functions to protect your sensitive data. You can also use the security features of RACF, or an equivalent system, to protect your data sets.

Communications database for the server

The *communications database* (CDB) is a set of Db2 catalog tables that let you control aspects of how requests leave a Db2 subsystem and how requests come in. Columns in the SYSIBM.LUNAMES and SYSIBM.USERNAMES tables pertain to security on the inbound side (the server).

SYSIBM.LUNAMES columns

The SYSIBM.LUNAMES table is used only for requests that use SNA protocols.

GUPI

LUNAME CHAR(8)

The LUNAME of the remote system. A blank value identifies a default row that serves requests from any system that is not specifically listed elsewhere in the column.

SECURITY_IN CHAR(1)

The acceptance option for a remote request from the corresponding LUNAME:

V

The option is "verify." An incoming request must include one of the following authentication entities:

- User ID and password
- User ID and RACF PassTicket
- User ID and RACF encrypted password (not recommended)
- Kerberos security tickets
- User ID and DRDA encrypted password
- User ID, password, and new password
- User ID and encrypted password, or encrypted user ID and encrypted password

Α

The option is "already verified." This is the default. With A, a request does not need an authentication token, although the token is checked if it is sent.

With this option, an incoming connection request is accepted if it includes any of the following authentication tokens:

- User ID only
- · All authentication methods that option V supports

If the USERNAMES column of SYSIBM.LUNAMES contains I or B, RACF is not invoked to validate incoming connection requests that contain only a user ID.

ENCRYPTPSWDS CHAR(1)

This column only applies to Db2 for z/OS or Db2 for z/OS partners when passwords are used as authentication tokens. It indicates whether passwords received from and sent to the corresponding LUNAME are encrypted:

Υ

Yes, passwords are encrypted. For outbound requests, the encrypted password is extracted from RACF and sent to the server. For inbound requests, the password is treated as if it is encrypted.

Ν

No, passwords are not encrypted. This is the default; any character other than Y is treated as N. Specify N for CONNECT statements that contain a USER parameter.

Recommendation: When you connect to a Db2 for z/OS partner that is at Version 5 or a subsequent release, use RACF PassTickets (SECURITY_OUT='R') instead of using passwords.

USERNAMES CHAR(1)

This column indicates whether an ID accompanying a remote request, sent from or to the corresponding LUNAME, is subject to translation and "come from" checking. When you specify I, O, or B, use the SYSIBM.USERNAMES table to perform the translation.

Ι

An inbound ID is subject to translation.

0

An outbound ID, sent to the corresponding LUNAME, is subject to translation.

В

Both inbound and outbound IDs are subject to translation.

blank

No IDs are translated.

GUPI

Related reference

SYSIBM.USERNAMES columns The SYSIBM.USERNAMES table is used by both SNA and TCP/IP connections.

SYSIBM.USERNAMES columns

The SYSIBM.USERNAMES table is used by both SNA and TCP/IP connections.

GUPI

TYPE CHAR(1)

Indicates whether the row is used for inbound or outbound translation:

S

The row is used to obtain the system authorization ID for establishing a trusted connection.

Ι

The row applies to inbound IDs (not applicable for TCP/IP connections).

0

The row applies to outbound IDs.

The field should contain only I or O. Any other character, including blank, causes the row to be ignored.

AUTHID VARCHAR(128)

An authorization ID that is permitted and perhaps translated. If blank, any authorization ID is permitted with the corresponding LINKNAME; all authorization IDs are translated in the same way. Outbound translation is not performed on CONNECT statements that contain an authorization ID for the value of the USER parameter.

LINKNAME CHAR(8)

Identifies the VTAM or TCP/IP network locations that are associated with this row. A blank value in this column indicates that this name translation rule applies to any TCP/IP or SNA partner.

If you specify a nonblank value for this column, one or both of the following situations must be true:

- A row exists in table SYSIBM.LUNAMES that has an LUNAME value that matches the LINKNAME value that appears in this column.
- A row exists in table SYSIBM.IPNAMES that has a LINKNAME value that matches the LINKNAME value that appears in this column.

NEWAUTHID VARCHAR(128)

The translated authorization ID. If blank, no translation occurs.

GUPI

Related reference

SYSIBM.LUNAMES columns The SYSIBM.LUNAMES table is used only for requests that use SNA protocols.

Enabling change of user passwords

You can specify YES in the EXTENDED SECURITY field of the DSNTIPR installation panel so that Db2 can return information about errors and expired passwords to the DRDA requester.

About this task

When the DRDA requester is notified that the RACF password has expired, and the requester has implemented function to allow passwords to be changed, the requester can prompt the user for the old password and a new password. The requester sends the old and new passwords to the Db2 server. This function is supported through Db2 Connect.

With the extended security option, Db2 passes the old and new passwords to RACF. If the old password is correct, and the new password meets the installation's password requirements, the user's password is changed and the DRDA connection request is honored.

When a user changes a password, the user ID, the old password, and the new password are sent to Db2 by the client system. The client system can optionally encrypt these three tokens before they are sent.

Authorization failure code

If the EXTENDED SECURITY field is set to YES on the DSNTIPR installation panel, Db2 returns detailed reason codes to a DRDA client when a DDF connection request fails.

When using SNA protocols, the requester must have included support for extended security sense codes. One such product is Db2 Connect.

If the proper requester support is present, the requester generates SQLCODE -30082 (SQLSTATE '08001') with a specific indication for the failure. Otherwise, a generic security failure code is returned.

Managing inbound SNA-based connection requests

Requests from a remote LU are subject to security checks before they come into contact with Db2. Those checks control what LUs can attach to the network and verify the identity of a partner LU.

About this task

Db2 itself imposes several checks before accepting an attachment request.

Processing of remote attachment requests

The Db2 server completes a specific sequence of authentication process before accepting a remote attachment request that uses the SNA protocol.

1. As the following diagram shows, if the remote request has no authentication token, Db2 checks the security acceptance option in the SECURITY_IN column of table SYSIBM.LUNAMES. No password is sent or checked for the plan or package owner that is sent from a Db2 subsystem.



Figure 8. Db2 processing of remote attachment requests

- 2. If the acceptance option is "verify" (SECURITY_IN = V), a security token is required to authenticate the user. Db2 rejects the request if the token missing.
- 3. If the USERNAMES column of SYSIBM.LUNAMES contains I or B, the authorization ID, and the plan or package owner that is sent by a Db2 subsystem, are subject to translation under control of the SYSIBM.USERNAMES table. If the request is allowed, it eventually goes through sign-on processing. If USERNAMES does not contain I or B, the authorization ID is not translated.
- 4. Db2 calls RACF by the RACROUTE macro with REQUEST=VERIFY to check the ID. Db2 uses the PASSCHK=NO option if no password is specified and ENCRYPT=YES if the ENCRYPTPSWDS column of SYSIBM.LUNAMES contains Y. If the ID, password, or PassTicket cannot be verified, Db2 rejects the request.

In addition, depending on your RACF environment, the following RACF checks may also be performed:

- If the RACF APPL class is active, RACF verifies that the ID has been given access to the Db2 APPL. The APPL resource that is checked is the LU name that the requester used when the attachment request was issued. This is either the local Db2 LU name or the generic LU name.
- If the RACF APPCPORT class is active, RACF verifies that the ID is authorized to access z/OS from the Port of Entry (POE). The POE that RACF uses in the verify call is the requesting LU name.

5. The remote request is now treated like a local connection request with a DIST environment for the DSNR resource class. Db2 calls RACF by the RACROUTE macro with REQUEST=AUTH, to check whether the authorization ID is allowed to use Db2 resources that are defined to RACF.

The RACROUTE macro call also verifies that the user is authorized to use Db2 resources from the requesting system, known as the port of entry (POE).

- 6. Db2 invokes the connection exit routine. The parameter list that is passed to the routine describes where a remote request originated.
- 7. If no password exists, RACF is not called. The ID is checked in SYSIBM.USERNAMES.
- 8. If a password exists, Db2 calls RACF through the RACROUTE macro with REQUEST=VERIFY to verify that the ID is known with the password. ENCRYPT=YES is used if the ENCRYPTPSWDS column of SYSIBM.LUNAMES contains Y. If Db2 cannot verify the ID or password, the request is rejected.
- 9. Db2 searches SYSIBM.USERNAMES for a row that indicates how to translate the ID. The need for a row that applies to a particular ID and sending location imposes a "come-from" check on the ID: If no such row exists, Db2 rejects the request.
- 10. If an appropriate row is found, Db2 translates the ID as follows:
 - If a nonblank value of NEWAUTHID exists in the row, that value becomes the primary authorization ID.
 - If NEWAUTHID is blank, the primary authorization ID remains unchanged.
- 11. The remote request is now treated like a local sign-on request. Db2 invokes the sign-on exit routine. The parameter list that is passed to the routine describes where a remote request originated.
- 12. The remote request now has a primary authorization ID, possibly one or more secondary IDs, and an SQL ID. A request from a remote Db2 is also known by a plan or package owner. Privileges and authorities that are granted to those IDs at the Db2 server govern the actions that the request can take.

Controlling LU attachments to the network

VTAM checks to prevent an unauthorized logical unit (LU) from attaching to the network and presenting itself to other LUs as an acceptable partner in communication. It requires each LU that attaches to the network to identify itself by a password.

About this task

If that requirement is in effect for your network, your Db2 subsystem, like every other LU on the network, must:

- 1. Choose a VTAM password.
- 2. Code the password with the PRTCT parameter of the VTAM APPL statement, when you define your Db2 to VTAM.

Verifying partner LUs

RACF and VTAM check the identity of a logical unit (LU) that sends a request to your Db2 subsystem.

Procedure

Perform the following steps to specify partner-LU verification:

- 1. Code VERIFY=REQUIRED on the VTAM APPL statement, when you define your Db2 to VTAM.
- 2. Establish a RACF profile for each LU from which you permit a request.

Accepting remote attachment requests

When VTAM has established a conversation for a remote application, that application sends a remote request, which is a request to attach to your local Db2 subsystem.

About this task

Make sure that you do not confuse the remote request with a local attachment request that comes through one of the Db2 attachment facilities—IMS, CICS, TSO, and so on. A remote attachment request is defined by Systems Network Architecture and LU 6.2 protocols; specifically, it is an SNA Function Management Header 5.

In order to accept remote attachment requests, you must first define your Db2 to VTAM with the conversation-level security set to "already verified". That is, you need to code SECACPT=ALREADYV on the VTAM APPL statement. The SECACPT=ALREADYV setting provides more options than does SECACPT=CONV or "conversation", which is not recommended.

The primary tools for controlling remote attachment requests are entries in tables SYSIBM.LUNAMES and SYSIBM.USERNAMES in the communications database. You need a row in SYSIBM.LUNAMES for each system that sends attachment requests, a dummy row that allows any system to send attachment requests, or both. You might need rows in SYSIBM.USERNAMES to permit requests from specific IDs or specific LUNAMES, or to provide translations for permitted IDs.

Managing inbound IDs through Db2

If you manage incoming IDs through Db2, you can avoid calls to RACF. You can accept many IDs by specifying them in a single row in the SYSIBM.USERNAMES table.

About this task

To manage incoming IDs through Db2, put an I in the USERNAMES column of SYSIBM.LUNAMES for the particular LU. If an O is already specified because you are also sending requests to that LU, change O to B. Attachment requests from that LU now go through the sign-on processing, and its IDs are subject to translation.

Managing inbound IDs through RACF

If you manage incoming IDs through RACF, you must register every acceptable ID with RACF, and Db2 must call RACF to process every request.

About this task

You can use RACF or Kerberos can authenticate the user. Kerberos cannot be used if you do not have RACF on the system.

To manage incoming IDs through RACF, leave USERNAMES blank for that LU, or leave the O unchanged, if already specified. Requests from that LU now go through the connection processing, and its IDs are not subject to translation.

Authenticating partner LUs

If RACF has already validated the identity of an LU and if you trust incoming IDs from the LU, you do not need to validate them by an authentication token.

About this task

You can choose whether to require an authentication token from a particular LU.

Procedure

To authenticate partner LUs, choose one of the following options:

• If you do not want Db2 to require an authentication token from a particular LU, check that you have defined Db2 to VTAM with SECACPT=ALREADYV. Then put an A in the SECURITY_IN column of the row in the SYSIBM.LUNAMES table that corresponds to the other LU.

Your acceptance level for requests from that LU is now "already verified". Requests from that LU are accepted without an authentication token.

• If you want Db2 to require an authentication token from a particular LU, put a V in the SECURITY_IN column in the SYSIBM.LUNAMES table.

Your acceptance level for requests from that LU is now "verify".

What to do next

If you require an authentication token, you must register every acceptable incoming ID and its password with RACF.

If an authentication token does accompany a request, Db2 calls RACF to check the authorization ID against it.

[other]: Each request to RACF to validate authentication tokens results in an I/O operation, which has a high performance cost.

[other]: To eliminate the I/O, allow RACF to cache security information in VLF. To activate this option, add the IRRACEE class to the end of z/OS VLF member COFVLFxx in SYS1.PARMLIB, as follows:

```
CLASS NAME(IRRACEE)
EMAJ (ACEE)
```

Related reference

LUNAMES catalog table (Db2 SQL)

Encrypting passwords

You can encrypt passwords to secure network connection requests.

Procedure

To encrypt passwords, use one of the following methods:

- RACF using PassTickets.
- DRDA password encryption support. Db2 for z/OS as a server supports DRDA encrypted passwords and encrypted user IDs with encrypted passwords. See <u>"Security mechanisms for DRDA and SNA" on page 177</u> for more information about using DRDA encryption.
- The SET ENCRYPTION PASSWORD statement. This encryption method should not be used for distributed access because the unencrypted passwords in the SET ENCRYPTION PASSWORD statement flow from the client to the server.

Related concepts

Security mechanisms for DRDA and SNA

DRDA encryption is not intended to provide confidentiality and integrity of passwords or data over a network that is not secure, such as the Internet. DRDA encryption uses an anonymous key exchange, Diffie-Hellman, which does not provide authentication of the server or the client. DRDA encryption is vulnerable to man-in-the-middle attacks.

Encrypting your data with Secure Socket Layer (SSL) support

Db2 supports Secure Socket Layer (SSL) protocol by using the z/OS Communications Server IP Application Transparent Transport Layer Security (AT-TLS).

Related tasks

Managing inbound TCP/IP-based connection requests

DRDA connections that use TCP/IP have fewer security controls than do connections that use SNA protocols. When planning to control inbound TCP/IP connection requests, you must decide whether you want the requests to have authentication information, such as RACF passwords, RACF PassTickets, and Kerberos tickets, passed along with authorization IDs.

Sending encrypted passwords from workstation clients

As a server, Db2 for z/OS can accept requests from remote workstation clients that use 256-bit Advanced Encryption Standard (AES) or 56-bit Data Encryption Standards (DES) encryption security over a TCP/IP network connection.

Related reference

TCP/IP ALREADY VERIFIED field (TCPALVER subsystem parameter) (Db2 Installation and Migration)

Related information

Protecting data through encryption and RACF

You can use the Db2 Secure Socket Layer (SSL) support or built-in data encryption functions to protect your sensitive data. You can also use the security features of RACF, or an equivalent system, to protect your data sets.

Authenticating users through Kerberos

If your distributed environment uses Kerberos to manage users and perform user authentication, Db2 for z/OS can use Kerberos security services to authenticate remote users.

Related tasks

Establishing Kerberos authentication through RACF

Kerberos security is a network security technology that was developed at the Massachusetts Institute of Technology. The Kerberos security technology does not require passwords to flow in readable text because it uses encrypted tickets that contain authentication information for the users.

Translating inbound IDs

Duplication of authorization IDs on different logical units (LUs) is a serious security exposure. For tighter security, make sure that each of the authorization IDs has the same meaning throughout your entire network.

About this task

Suppose that the ID DBADM1 is known to the local Db2 and has DBADM authority over certain databases there; suppose also that the same ID exists in some remote LU. If an attachment request comes in from DBADM1, and if nothing is done to alter the ID, the wrong user can exercise privileges of DBADM1 in the local Db2. The way to protect against that exposure is to translate the remote ID into a different ID before the attachment request is accepted.

You must be prepared to translate the IDs of plan owners, package owners, and the primary IDs of processes that make remote requests. Do not plan to translate all IDs in the connection exit routine—the routine does not receive plan and package owner IDs.

If you have decided to manage inbound IDs through Db2, you can translate an inbound ID to some other value. Within Db2, you grant privileges and authorities only to the translated value. The "translation" is not affected by anything you do in your connection or sign-on exit routine. The *output* of the translation becomes the *input* to your sign-on exit routine.

Recommendation: Do not translate inbound IDs in an exit routine; translate them only through the SYSIBM.USERNAMES table.

The examples in the following table shows the possibilities for translation and how to control translation by SYSIBM.USERNAMES. You can use entries to allow requests only from particular LUs or particular IDs, or from combinations of an ID and an LU. You can also translate any incoming ID to another value.

Table 53. Your SYSIBM.USERNAMES table. (Row numbers are added for reference.)				
Row	ТҮРЕ	AUTHID	LINKNAME	NEWAUTHID
1	I	blank	LUSNFRAN	blank
2	I	BETTY	LUSNFRAN	ELIZA
3	Ι	CHARLES	blank	сниск
4	I	ALBERT	LUDALLAS	blank
5	I	BETTY	blank	blank

The following table shows the search order of the SYSIBM.USERNAMES table.

		Posult
AUTHID		Result
Name	Name	If NEWAUTHID is specified, AUTHID is translated to NEWAUTHID for the specified LINKNAME.
Name	Blank	If NEWAUTHID is specified, AUTHID is translated to NEWAUTHID for all LINKNAMEs.
Blank	Name	If NEWAUTHID is specified, it is substituted for AUTHID for the specified LINKNAME.
Blank	Blank	Unavailable resource message (SQLCODE -904) is returned.

Table 54. Precedence search order for SYSIBM.USERNAMES table

Db2 searches SYSIBM.USERNAMES to determine how to translate for each of the requests that are listed in the following table.

Table 55. How Db2 translates inbound authorization ids

Request	How Db2 translates request
ALBERT requests from LUDALLAS	Db2 searches for an entry for AUTHID=ALBERT and LINKNAME=LUDALLAS. Db2 finds one in row 4, so the request is accepted. The value of NEWAUTHID in that row is blank, so ALBERT is left unchanged.
BETTY requests from LUDALLAS	Db2 searches for an entry for AUTHID=BETTY and LINKNAME=LUDALLAS; none exists. Db2 then searches for AUTHID=BETTY and LINKNAME=blank. It finds that entry in row 5, so the request is accepted. The value of NEWAUTHID in that row is blank, so BETTY is left unchanged.
CHARLES requests from LUDALLAS	Db2 searches for AUTHID=CHARLES and LINKNAME=LUDALLAS; no such entry exists. Db2 then searches for AUTHID=CHARLES and LINKNAME=blank. The search ends at row 3; the request is accepted. The value of NEWAUTHID in that row is CHUCK, so CHARLES is translated to CHUCK.
ALBERT requests from LUSNFRAN	Db2 searches for AUTHID=ALBERT and LINKNAME=LUSNFRAN; no such entry exists. Db2 then searches for AUTHID=ALBERT and LINKNAME=blank; again no entry exists. Finally, Db2 searches for AUTHID=blank and LINKNAME=LUSNFRAN, finds that entry in row 1, and the request is accepted. The value of NEWAUTHID in that row is blank, so ALBERT is left unchanged.
BETTY requests from LUSNFRAN	Db2 finds row 2, and BETTY is translated to ELIZA.
CHARLES requests from LUSNFRAN	Db2 finds row 3 before row 1; CHARLES is translated to CHUCK.

Table 55. How Db2 translates inbound authorization ids (continued)

Request	How Db2 translates request
WILBUR requests from LUSNFRAN	No provision is made for WILBUR, but row 1 of the SYSIBM.USERNAMES table allows any ID to make a request from LUSNFRAN and to pass without translation. The acceptance level for LUSNFRAN is "already verified", so WILBUR can pass without a password check by RACF. After accessing Db2, WILBUR can use only the privileges that are granted to WILBUR and to PUBLIC (for DRDA access).
WILBUR requests from LUDALLAS	Because the acceptance level for LUDALLAS is "verify" as recorded in the SYSIBM.LUNAMES table, WILBUR must be known to the local RACF. Db2 searches in succession for one of the combinations WILBUR/LUDALLAS, WILBUR/blank, or blank/LUDALLAS. None of those is in the table, so the request is rejected. The absence of a row permitting WILBUR to request from LUDALLAS imposes a "come- from" check: WILBUR can attach from some locations (LUSNFRAN), and some IDs (ALBERT, BETTY, and CHARLES) can attach from LUDALLAS, but WILBUR cannot attach if coming from LUDALLAS.

In the process of accepting remote attachment requests, any step that calls RACF is likely to have a relatively high performance cost. To trade some of that cost for a somewhat greater security exposure, have RACF check the identity of the other LU just once. Then trust the partner LU, translating the inbound IDs and not requiring or using passwords. In this case, no calls are made to RACF from within Db2; the penalty is only that you make the partner LU responsible for verifying IDs.

If you update tables in the CDB while the distributed data facility is running, the changes might not take effect immediately. If incoming authorization IDs are managed through Db2 and if the ICSF is installed and properly configured, you can use the DSNLEUSR stored procedure to encrypt translated authorization IDs and store them in the NEWAUTHID column of the SYSIBM.USERNAMES table. Db2 decrypts the translated authorization IDs during connection processing.

Associating inbound IDs with secondary IDs

Your decisions on password encryption and ID translation determine the value that you use for the primary authorization ID on an attachment request.

About this task

They also determine whether those requests are next treated as connection requests or as sign-on requests. That means that the remote request next goes through the same processing as a local request, and that you have the opportunity to associate the primary ID with a list of secondary IDs in the same way you do for local requests.

Managing inbound TCP/IP-based connection requests

DRDA connections that use TCP/IP have fewer security controls than do connections that use SNA protocols. When planning to control inbound TCP/IP connection requests, you must decide whether you want the requests to have authentication information, such as RACF passwords, RACF PassTickets, and Kerberos tickets, passed along with authorization IDs.

About this task



Attention: To protect your authentication information, use the z/OS Communications Server IP Application Transparent Transport Layer Security (AT-TLS) to secure your network connections. To complement the use of AT-TLS, set the TCPALVER subsystem parameter of installation panel DSNTIP5 to SERVER_ENCRYPT. Setting this parameter to SERVER_ENCRYPT provides the strongest level of security. Connections are accepted only if user credentials are provided to authenticate the user ID, and strong encryption is used to protect the user ID and credentials.

Procedure

To manage inbound TCP/IP-based connection requests:

• For requests that use RACF passwords or PassTickets, enter the following RACF command to indicate which user IDs that use TCP/IP are authorized to access DDF (the distributed data facility address space):

```
PERMIT ssnm.DIST CLASS(DSNR) ID(yyy) ACCESS(READ)
WHEN(APPCPORT(TCPIP))
```

Consider the following questions:

Do you permit access by TCP/IP? If the serving Db2 for z/OS subsystem has a DRDA port and resynchronization port specified in the BSDS, Db2 is enabled for TCP/IP connections.

Do you manage inbound IDs through Db2 or RACF? All IDs must be passed to RACF or Kerberos for processing. No option exists to handle incoming IDs through Db2.

Do you trust the partner? TCP/IP does not verify partner LUs, as SNA does. If your requesters support mutual authentication, use Kerberos to handle this authentication on the requester side.

If you use passwords, are they encrypted? Passwords can be encrypted through:

- RACF using PassTickets
- DRDA password encryption support. Db2 for z/OS as a server supports DRDA-encrypted passwords and encrypted user IDs with encrypted passwords. See <u>"Security mechanisms for DRDA and SNA"</u> on page 177 for more information about using DRDA encryption.

If you use Kerberos, are users authenticated? If your distributed environment uses Kerberos to manage users and perform user authentication, Db2 for z/OS can use Kerberos security services to authenticate remote users.

Do you translate inbound IDs? Inbound IDs are not translated when you use TCP/IP.

How do you associate inbound IDs with secondary IDs? To associate an inbound ID with secondary IDs, modify the default connection exit routine (DSN3@ATH). TCP/IP requests do not use the sign-on exit routine.

Related concepts

Security mechanisms for DRDA and SNA

DRDA encryption is not intended to provide confidentiality and integrity of passwords or data over a network that is not secure, such as the Internet. DRDA encryption uses an anonymous key exchange, Diffie-Hellman, which does not provide authentication of the server or the client. DRDA encryption is vulnerable to man-in-the-middle attacks.

Encrypting your data with Secure Socket Layer (SSL) support

Db2 supports Secure Socket Layer (SSL) protocol by using the z/OS Communications Server IP Application Transparent Transport Layer Security (AT-TLS).

Related tasks

Sending encrypted passwords or password phrases from Db2 for z/OS clients

As a requester, a Db2 for z/OS client can send connection requests that use 256-bit Advanced Encryption Standard (AES) or 56-bit Data Encryption Standards (DES) encryption security through a TCP/IP network to remote servers.

Sending encrypted passwords from workstation clients

As a server, Db2 for z/OS can accept requests from remote workstation clients that use 256-bit Advanced Encryption Standard (AES) or 56-bit Data Encryption Standards (DES) encryption security over a TCP/IP network connection.

Related reference

TCP/IP ALREADY VERIFIED field (TCPALVER subsystem parameter) (Db2 Installation and Migration)

Related information

Protecting data through encryption and RACF

You can use the Db2 Secure Socket Layer (SSL) support or built-in data encryption functions to protect your sensitive data. You can also use the security features of RACF, or an equivalent system, to protect your data sets.

Enabling Db2 to receive RACF PassTickets

Db2 supports the ability to receive RACF PassTickets from remote requests.

About this task

This task describes how to enable basic capability for Db2[®] to receive RACF PassTickets. If you are using PassTickets with RACF-protected user IDs or by using PassTickets across a data sharing group, additional setup is required.

Procedure

To enable a Db2 subsystem or data sharing group to receive PassTickets:

1. Activate the RACF PTKTDATA class by issuing the following RACF commands:

SETROPTS CLASSACT(PTKTDATA) SETROPTS RACLIST(PTKTDATA)

2. Define a PTKTDATA profile with a secured signon application key mask for all Db2 systems that will receive PassTickets from this requesting Db2 subsystem or data sharing group by issuing the following RACF command:

```
RDEFINE PTKTDATA applname SSIGNON(KEYMASKED(key-description)) APPLDATA('NO REPLAY PROTECTION')
```

Where:

- *applname* is either the LUNAME or the IPNAME of a stand-alone Db2 subsystem or the GENERICLU or the IPNAME assigned to each member of a Db2 data sharing group. This value must match the system name as it appears in the LINKNAME column of the SYSIBM.LOCATIONS table of a requesting Db2 subsystem or data sharing group.
- key-description is the secured signon application key.
- The APPLDATA('NO REPLAY PROTECTION') parameter is required if PassTickets of any PTKTDATA profile are generated faster than one per second.

This profile must be available to both the Db2 subsystem or to each member of a data sharing group that sends the PassTicket and the Db2 subsystem or data sharing group that receives that PassTicket, and both instances of this profile must match.

For more information about secured signon PTKTDATA profiles, see the RACF topic Defining profiles in the PTKTDATA class (Security Server RACF Security Administrator's Guide).

3. Refresh the RACF PTKTDATA definition with the new profiles by issuing the following command:

```
SETROPTS RACLIST(PTKTDATA) REFRESH
```

Example

The following example shows the RACF commands that define a secured signon PTKTDATA profile for SYEC1GLU and that enable the new PTKTDATA profile:

```
RDEFINE PTKTDATA SYEC1GLU SSIGNON(KEYMASKED(F0123456789ABCDE))
APPLDATA('NO REPLAY PROTECTION') SETROPTS RACLIST(PTKTDATA) REFRESH
```

What to do next

• To send RACF PassTickets from a Db2 subsystem or data sharing group, complete the steps in <u>"Enabling</u> Db2 to send RACF PassTickets" on page 215.

- If you are using PassTickets across a data sharing environment, complete the steps in "Enabling caching of MFA-based authentication credentials for clients with sysplex workload balancing" on page 193.
- If you are using RACF-protected user IDs, complete the steps in <u>"Enabling Db2 to receive PassTickets</u> for RACF-protected user IDs (deprecated)" on page 192. (Deprecated <u>"1" on page 192</u>)

Notes:

1. Receiving RACF-protected user IDs with RACF PassTickets is deprecated. This deprecation does not apply to RACF PassTickets in general or any other use for them in Db2 for z/OS.

Related concepts

Db2 support for RACF PassTickets

Db2 supports the ability to send and receive RACF PassTicketsto authenticate a user who is accessing a Db2 server.

Enabling Db2 to receive PassTickets for RACF-protected user IDs (deprecated)

To enable a Db2 server to receive requests from a Db2 requester over TCP/IP connections that use RACF-protected user IDs and RACF PassTickets (as passwords), you must define an additional PTKTDATA profile and grant permission to that profile in RACF.

Before you begin

Complete the steps in "Enabling Db2 to receive RACF PassTickets" on page 191.

Deprecated function:

Receiving RACF-protected user IDs with RACF PassTickets is deprecated. This deprecation does not apply to RACF PassTickets in general or any other use for them in Db2 for z/OS. For best results, use one of the following alternatives:

- Configure client certification authentication. For more information, see <u>"Encrypting your data with</u> Secure Socket Layer (SSL) support" on page 323.
- In Db2 13 at function level 505 or later, enable token-based authentication. For more information, see Enabling Db2 for token authentication.

About this task

RACF-protected user IDs cannot be associated with passwords and instead must use RACF PassTickets for authentication purposes. You must complete the following steps in RACF if RACF-protected user IDs are used in connection requests from a Db2 for z/OS requester to a Db2 for z/OS server.

Procedure

To enable Db2 as a server that can receive PassTickets for RACF-protected user IDs:

1. Define a PTKTDATA profile at the server system or sysplex that permits a particular stand-alone Db2 subsystem or a member of a Db2 data sharing group to evaluate whether a password is a PassTicket when a Db2 requester attempts to access that subsystem or member. If this permission profile does not exist, a connection that uses a RACF-protected user ID fails to connect. Issue one of the following commands:

RDEFINE PTKTDATA IRRPTAUTH.applname.userid

RDEFINE PTKTDATA IRRPTAUTH.applname.*

Where:

• *applname* is either the LUNAME or the IPNAME of the stand-alone subsystem or the GENERICLU or the IPNAME assigned to each member of the data sharing group.

- *userid* is either an asterisk ("*") or a specific RACF-protected user ID that you want to allow into the serving subsystem or a member of a data sharing group.
- 2. Permit the user ID that is assigned in the STARTED profile in the *ssnm*DIST address space to read the new profile by issuing one of the following commands:

```
PERMIT IRRPTAUTH.applname.userid CLASS(PTKTDATA) -
ID(dist_userid) ACCESS(READ)
```

PERMIT IRRPTAUTH.applname.* CLASS(PTKTDATA) -ID(dist_userid) ACCESS(READ)

Where *dist_userid* is the user ID that is assigned in the STARTED profile in the *ssnm*DIST address space. If you use different STARTED user IDs for the *ssnm*DIST address space of members of the same Db2 data sharing group, you must give READ permission to this PTKTDATA profile to each of these user IDs.

3. Issue the SETROPTS command to enable the PTKTDATA profile that you created in the previous steps:

SETROPTS RACLIST(PTKTDATA) REFRESH

Example

The following example shows the RACF commands that define a PTKTDATA profile for SYEC1GLU for any user ID, that grant the *ssnm*DIST address space STARTED profile user ID (SYSDSP) READ access to that PTKTDATA profile; and that enable the new PTKTDATA profile:

```
RDEFINE PTKTDATA IRRPTAUTH.SYEC1GLU.*
PERMIT IRRPTAUTH.SYEC1GLU.* CLASS(PTKTDATA) -
ID(SYSDSP) ACCESS(READ)
SETROPTS RACLIST(PTKTDATA) REFRESH
```

Related concepts

Db2 support for RACF PassTickets

Db2 supports the ability to send and receive RACF PassTicketsto authenticate a user who is accessing a Db2 server.

Related tasks

Enabling Db2 to send RACF PassTickets

Db2 supports the ability to send RACF PassTickets with your remote requests to a remote Db2 subsystem or data sharing group.

Enabling Db2 to receive RACF PassTickets Db2 supports the ability to receive RACF PassTickets from remote requests.

Enabling caching of MFA-based authentication credentials for clients with sysplex workload balancing Sysplex group authentication enables the use of multi-factor authentication (MFA) and RACF PassTickets in Db2 data sharing environments.

Enabling caching of MFA-based authentication credentials for clients with sysplex workload balancing

Sysplex group authentication enables the use of multi-factor authentication (MFA) and RACF PassTickets in Db2 data sharing environments.

Before you begin

- For clients that do not have sysplex workload balancing or seamless failover enabled, see the alternate approach described in <u>"Enabling caching of MFA and RACF PassTickets credentials for clients without</u> sysplex workload balancing" on page 196.
- The MFA support that is provided by Db2 is based on the IBM Z Multi-Factor Authentication product, which provides enhanced logon security, addresses regulatory and industry requirements, and provides

centralized and simplified management. If you are using IBM Z Multi-Factor Authentication, it must already be configured on MVS or across the z/OS sysplex and must be configured in accordance with how clients will provide user authentication credentials from remote applications.

- If you are using RACF PassTickets:
 - The security product that you are using must be online.
 - Complete the steps in "Enabling Db2 to receive RACF PassTickets" on page 191.

About this task

MFA and RACF PassTickets are two distinct methods of providing additional authentication credentials at logon to verify a user's identity. Requiring an additional authentication credential ensures that a user's account cannot be compromised if one of their credentials is discovered.

sysplex group authentication eliminates connection authentication failures that occur when a Db2 client has sysplex workload balancing or seamless failover enabled by using either of the following methods:

- The enableWLB keyword in the <wlb> section of the IBM data server driver configuration file (db2dsdriver.cfg) for the non-java client
- The enablesysplexWLB JDBC database property

Without sysplex group authentication, connection authentication requests will fail because the drivers that perform sysplex workload balancing and seamless failover attempt to connect with multiple members of a data sharing group on behalf of the original client application connection. These extra connection attempts fail because the additional authentication credential expires or becomes void because it's valid only for the initial connection request and cannot be reused for subsequent connection requests.

Procedure

- 1. Ensure that the ICSF load library, SCSFMODO, is in the LINKLIST of the LPAR where Db2 is running.
- 2. For every member of a data sharing group for which you want to enable sysplex group authentication, ensure that Db2 is running with a Db2 subsystem parameters (ZPARM) module in which AUTHEXIT_CACHEREFRESH (DSN6SPRM) is set to ALL.

To use RACF PassTickets for passwords without using IBM Multi-Factor Authentication for z/OS, complete the following additional steps on RACF:

3. Enable Db2 as a serving data sharing group that can receive PassTickets with connection authentication tokens by defining a PTKTDATA profile that permits a member of a Db2 data sharing group to evaluate whether a password is a PassTicket when being accessed by a distributed client. If this permission profile does not exist, an authorization failure will occur when the PassTicket use has exceeded 10 minutes.

RDEFINE PTKTDATA IRRPTAUTH.applname.*

RDEFINE PTKTDATA IRRPTAUTH.applname.userid

Where:

- *applname* is either the generic LU or the IPNAME defined to each member of the data sharing group. All members of a data sharing group must be defined with the same generic LU or IPNAME.
- *userid* is an asterisk (*) or a specific client user ID that you want to allow into the serving data sharing group and be authenticated with a PassTicket as a password.

This profile must be available to all the systems of a sysplex where a member of the serving Db2 data sharing group is started.

4. Issue one of the following commands to permit the user ID that is assigned in the STARTED profile in the DDF address space (*ssnm*DIST) to read the profile that you created in step <u>"3" on page 194</u>:

```
PERMIT IRRPTAUTH.applname.* CLASS(PTKTDATA) -
ID(dist_userid) ACCESS(READ)
```

```
PERMIT IRRPTAUTH.applname.userid CLASS(PTKTDATA) -
ID(dist_userid) ACCESS(READ)
```

Where *dist_userid* is the user ID that is assigned in the STARTED profile in the DDF address space (*ssnm*DIST). If you use different STARTED user IDs for the *ssnm*DIST address spaces of members of the same Db2 data sharing group, you must give READ permission to this PTKTDATA profile to each of these user IDs

5. Issue the SETROPTS command to enable the PTKTDATA profile that you created in the previous steps:

SETROPTS RACLIST(PTKTDATA) REFRESH

Notes:

- When a particular PassTicket-based authentication token hasn't been used by a client in an authentication request for more than two hours, the token expires and is removed from the cache.
- If Db2 receives a RACF ALTUSER REVOKE or a DELUSER command for an authorization ID that matches an entry for an authorization ID in the cache, that entry expires across the entire data sharing group.

Example

The following example shows the RACF commands that: define a PTKTDATA profile for SYEC1GLU for any user ID; grant the DDF address space (*ssnm*DIST) STARTED profile user ID (SYSDSP) READ access to that PTKTDATA profile; and enable the new PTKTDATA profiles:

```
RDEFINE PTKTDATA IRRPTAUTH.SYEC1GLU.*
PERMIT IRRPTAUTH.SYEC1GLU.* CLASS(PTKTDATA) -
ID(SYSDSP) ACCESS(READ)
SETROPTS RACLIST(PTKTDATA) REFRESH
```

Related concepts

Db2 support for RACF PassTickets

Db2 supports the ability to send and receive RACF PassTicketsto authenticate a user who is accessing a Db2 server.

Related tasks

Enabling caching of MFA-based authentication credentials for clients with sysplex workload balancing Sysplex group authentication enables the use of multi-factor authentication (MFA) and RACF PassTickets in Db2 data sharing environments.

Enabling Db2 to send RACF PassTickets Db2 supports the ability to send RACF PassTickets with your remote requests to a remote Db2 subsystem or data sharing group.

Enabling Db2 to receive RACF PassTickets Db2 supports the ability to receive RACF PassTickets from remote requests.

Enabling Db2 to receive PassTickets for RACF-protected user IDs (deprecated)

To enable a Db2 server to receive requests from a Db2 requester over TCP/IP connections that use RACF-protected user IDs and RACF PassTickets (as passwords), you must define an additional PTKTDATA profile and grant permission to that profile in RACF.

Enabling caching of MFA and RACF PassTickets credentials for clients without sysplex workload balancing

You can enable Db2 to store multi-factor authentication (MFA) credentials in the Db2 global authentication cache for distributed clients that do not use sysplex workload balancing or seamleass failover, and specify the amount of time that the entry remains if unused.

Before you begin

- For clients that have sysplex workload balancing or seamless failover enabled, see <u>"Enabling caching of</u> MFA-based authentication credentials for clients with sysplex workload balancing" on page 193.
- The multi-factor authentication support that is provided by Db2 is based on the IBM Z Multi-Factor Authentication product, which provides enhanced logon security, addresses regulatory and industry requirements, and provides centralized and simplified management. If you are using IBM Z Multi-Factor Authentication, it must already be configured on MVS or across the z/OS sysplex and must be configured in accordance with how clients will provide user authentication credentials from remote applications.
- If you are using RACF PassTickets:
 - The security product that you are using must be online.
 - Complete the steps in "Enabling Db2 to receive RACF PassTickets" on page 191.

About this task

Multi-factor authentication (MFA) and RACF PassTickets are two distinct methods of providing additional authentication credentials at logon to verify a user's identity. Requiring an additional authentication credential ensures that a user's account cannot be compromised if one of their credentials is discovered.

Caching of MFA-based authentication credentials eliminates connection authentication failures that occur when clients that are not sysplex-WLB enabled connect to multiple members of a data sharing group on behalf of the original client application connection. Without caching of MFA-based authentication credentials enabled, connection authentication requests will fail because the additional authentication credential expires or becomes void because it's valid only for the initial connection request and cannot be reused for subsequent connection requests.

Procedure

To enable the caching of MFA credentials for clients that are not sysplex-aware, complete the following steps:

1. If the AUTHEXIT_CACHEREFRESH subsystem parameter setting was NONE when Db2 started, issue a -STOP DB2 command.

This step is required because online updates to the MFA_AUTHCACHE_UNUSED_TIME subsystem parameter are only supported if the AUTHEXIT_CACHEREFRESH setting is ALL when Db2 starts. Otherwise, Db2 issues message DSNZ014I with DSNZCMD1 for *load-csect-name* for any online attempt to update the MFA_AUTHCACHE_UNUSED_TIME value.

- 2. Update the following subsystem parameters settings:
 - Set AUTHEXIT_CACHEREFRESH to ALL. In a Db2 data sharing group, this value must be set on every member. For more information, see <u>AUTH EXIT CACHE REFR (AUTHEXIT_CACHEREFRESH</u> subsystem parameter) (Db2 Installation and Migration).
 - Set MFA_AUTHCACHE_UNUSED_TIME to a non-zero value, in the range 120–7200. The value that you specify is the number of seconds that an authentication cache entry for MFA-based authentication credentials can remain unused in the cache. The time limit resets each time that the cached authentication entry is used by a new connection from the same IP address. For

more information, see MFA AUTH UNUSED TIME field (MFA_AUTHCACHE_UNUSED_TIME subsystem parameter) (Db2 Installation and Migration).

If the members of a data sharing group are started with different MFA_AUTHCACHE_UNUSED_TIME settings, the entire group uses the value the largest value specified for any member. For example, if member DB2A is started with a value of 120 and member DB2B is started with 7200, member DB2A requests the matching cached credentials in DB2B every 120 seconds until the cache in DB2B times out. The request for matching credentials in other members occurs only when either the cached credentials are not found in the current member or the cached credentials in the current member exceed its unused time and a new replay of the credentials has been received on a new connection request from the same IP address. For best results, set the parameter for all members of the group to the same "maximum" value.

The request for matching credentials in other members occurs when the cached credentials are not found in the current member or the cached credentials in the current member exceed its unused time, and a new replay of the credentials is received on a new connection request from the same IP address.

3. Issue a -START DB2 command.

What to do next

If Db2 issues message DSN3582I, take the required actions. For more information, see the system programmer response in DSN3582I (Db2 Messages).

Related tasks

Enabling caching of MFA-based authentication credentials for clients with sysplex workload balancing Sysplex group authentication enables the use of multi-factor authentication (MFA) and RACF PassTickets in Db2 data sharing environments.

Getting started with RACF support for IBM MFA

Processing of TCP/IP-based connection requests

The Db2 server completes a sequence of authentication tasks when handling a remote connection request that uses the TCP/IP protocol.

1. As the following diagram shows, Db2 checks to see if an authentication token (RACF encrypted password, RACF PassTicket, DRDA encrypted password, or Kerberos ticket) accompanies the remote request. See <u>"Security mechanisms for DRDA and SNA" on page 177</u> for more information about using DRDA encryption.



Figure 9. Db2 processing of TCP/IP-based connection requests

2. If no authentication token is supplied, Db2 checks the TCPALVER subsystem parameter to see if Db2 accepts IDs without authentication information.

Recommendation: Setting the TCPALVER subsystem parameter to SERVER_ENCRYPT provides the best security because connections are accepted only if user credentials are provided to authenticate the user ID, and strong encryption is used to protect the user ID and credentials in the network. For more information, see <u>"Sending encrypted passwords or password phrases from Db2 for z/OS clients"</u> on page 216.

- If TCPALVER=SERVER_ENCRYPT, Db2 requires a userid and a password. In addition, it requires that the security credentials be AES-encrypted or that the connection is accepted on a port that ensures AT-TLS policy protection, such as a Db2 Security Port (SECPORT). Kerberos tickets are accepted. RACF PassTickets, or non-encrypted security credentials, are accepted only when the connection is secured by the TCP/IP network.
- If TCPALVER=NO or SERVER, Db2 requires the minimum of a userid and a password.
- If TCPALVER=YES or CLIENT, Db2 accepts TCP/IP connection requests that contain only a userid.

For more information, see <u>TCP/IP ALREADY VERIFIED field</u> (TCPALVER subsystem parameter) (Db2 Installation and Migration)

3. The identity is a RACF ID that is authenticated by RACF if a password or PassTicket is provided, or the identity is a Kerberos principal that is validated by Kerberos Security Server, if a Kerberos ticket is provided. Ensure that the ID is defined to RACF in all cases. When Kerberos tickets are used, the RACF ID is derived from the Kerberos principal identity. To use Kerberos tickets, ensure that you map Kerberos principal names with RACF IDs.

In addition, depending on your RACF environment, the following RACF checks may also be performed:

• If the RACF APPL class is active, RACF verifies that the ID has access to the Db2 APPL. The APPL resource that is checked is the LU name that the requester used when the attachment request was issued. This is either the local Db2 LU name or the generic LU name.

- If the RACF APPCPORT class is active, RACF verifies that the ID is authorized to access z/OS from the port of entry (POE). The POE that RACF uses in the RACROUTE VERIFY call depends on whether all the following conditions are true:
 - The TCP/IP Network Access Control is configured
 - The RACF SERVAUTH class is active

If all these conditions are true, RACF uses the remote client's POE security zone name that is defined in the TCP/IP Network Access Control file. If one or more of these conditions is not true, RACF uses the literal string 'TCPIP'.

If this is a request to change a password, the password is changed.

- 4. The remote request is now treated like a local connection request (using the DIST environment for the DSNR resource class). Db2 calls RACF to check the ID's authorization against the *ssnm*.DIST resource.
- 5. Db2 invokes the connection exit routine. The parameter list that is passed to the routine describes where the remote request originated.
- 6. The remote request has a primary authorization ID, possibly one or more secondary IDs, and an SQL ID. (The SQL ID cannot be translated.) The plan or package owner ID also accompanies the request. Privileges and authorities that are granted to those IDs at the Db2 server govern the actions that the request can take.

Related concepts

Security mechanisms for DRDA and SNA

DRDA encryption is not intended to provide confidentiality and integrity of passwords or data over a network that is not secure, such as the Internet. DRDA encryption uses an anonymous key exchange, Diffie-Hellman, which does not provide authentication of the server or the client. DRDA encryption is vulnerable to man-in-the-middle attacks.

Encrypting your data with Secure Socket Layer (SSL) support

Db2 supports Secure Socket Layer (SSL) protocol by using the z/OS Communications Server IP Application Transparent Transport Layer Security (AT-TLS).

Related tasks

Managing inbound TCP/IP-based connection requests

DRDA connections that use TCP/IP have fewer security controls than do connections that use SNA protocols. When planning to control inbound TCP/IP connection requests, you must decide whether you want the requests to have authentication information, such as RACF passwords, RACF PassTickets, and Kerberos tickets, passed along with authorization IDs.

Sending encrypted passwords from workstation clients

As a server, Db2 for z/OS can accept requests from remote workstation clients that use 256-bit Advanced Encryption Standard (AES) or 56-bit Data Encryption Standards (DES) encryption security over a TCP/IP network connection.

Related reference

Processing of outbound connection requests A Db2 subsystem completes a sequence of tasks when sending out a connection request.

TCP/IP ALREADY VERIFIED field (TCPALVER subsystem parameter) (Db2 Installation and Migration)

Related information

Protecting data through encryption and RACF

You can use the Db2 Secure Socket Layer (SSL) support or built-in data encryption functions to protect your sensitive data. You can also use the security features of RACF, or an equivalent system, to protect your data sets.

Global authentication cache

Db2 can cache user credentials when processing remote TCP/IP connections.

When processing a TCP/IP connection, Db2 authenticates a user ID by using RACF. If the user ID is successfully authenticated, Db2 caches the user credentials for three minutes during which Db2

reuses the cached credentials for subsequent connection requests from the same user ID. Db2 deletes the cache entries if the password is changed through a DRDA password change request or if the AUTHEXIT_CACHEREFRESH system parameter is set and the user permissions are changed in RACF.

Db2 does not differentiate PassTickets from passwords while caching user credentials.

Caching of MFA based credentials

Db2 stores multi-factor authentication (MFA) based credentials in the global authentication cache for clients that have sysplex workload balancing (WLB) or seamless failover enabled. The credentials can remain unused in the cache for up to two hours.

For clients that do not have sysplex WLB or seamless failover enabled, the MFA_AUTHCACHE_UNUSED_TIME subsystem parameter, controls whether MFA based credentials are stored in , and how long they are allowed to remain cached if unused.

Related tasks

Enabling caching of MFA and RACF PassTickets credentials for clients without sysplex workload balancing You can enable Db2 to store multi-factor authentication (MFA) credentials in the Db2 global authentication cache for distributed clients that do not use sysplex workload balancing or seamleass failover, and specify the amount of time that the entry remains if unused.

Getting started with RACF support for IBM MFA

Related reference

AUTH EXIT CACHE REFR (AUTHEXIT_CACHEREFRESH subsystem parameter) (Db2 Installation and Migration)

MFA AUTH UNUSED TIME field (MFA_AUTHCACHE_UNUSED_TIME subsystem parameter) (Db2 Installation and Migration)

Managing denial-of-service attacks

With Db2, you can manage denial-of-service attacks in the network connections to a Db2 server.

About this task

The most common type of denial-of-service attack occurs when an attacker "floods" a network with connection requests to a Db2 server. If this occurs, the attacker quickly exhausts the threshold for the maximum number of remote connections that are defined to the Db2 server system. As a result, no additional remote connections can be accepted by the Db2 server, including those from legitimate client systems.

To prevent the typical denial-of-service attacks, Db2 monitors the traffic of inbound connections and terminates those that don't contain data for establishing a valid connection.

Preventing SQL injection attacks

SQL injection attacks might occur when dynamic SQL statements are constructed from user input and the input is inadequately checked. You can use several techniques to prevent or reduce SQL injection attacks.

Procedure

To eliminate or reduce the risk of SQL injection attacks:

- Avoid dynamic SQL, whenever possible.
- Use pureQuery[®] or SQLJ rather than JDBC for Java.
- Use system security techniques, such as views and access control mechanisms, whenever possible.

Understand the limitations of security within an application. System security can use security and integrity mechanisms that are not available to application programs. The level of assurance that can be provided in system security can be much higher. If the applications are run on the client or have fewer protection layers and firewalls than the database, make sure to address those limitations.

- Use row permissions and column masks to protect data even if the statement is compromised by SQL injection attacks.
- Put input data into host variables with just the value or use a parameter marker in dynamic SQL.
- Make sure to check all input:
 - Check that the input is the intended data type and format. This is generally required for all programs to ensure that they work properly but especially crucial for data intended as part of an SQL statement.
 - Accept numbers for a numeric comparison only.
 - Do not allow special characters if they do not apply.

Managing outbound connection requests

If you plan to send requests to another Db2 subsystem, you need to consider the subsystem's security measures for network connections. You need to know what those measures are and make entries in your CDB to correspond to them.

About this task

If you are planning to send remote requests to a DBMS that is not Db2 for z/OS, you need to satisfy the requirements of that system.

Db2 chooses how to send authentication tokens based on the network protocols that are used (SNA or TCP/IP). If the request is sent using SNA, the authentication tokens are sent in the SNA attachment request (FMH5), unless you are using Kerberos. If you use Kerberos, authentication tokens are sent with DRDA security commands. If the request uses TCP/IP, the authentication tokens are always sent using DRDA security commands. See <u>"Security mechanisms for DRDA and SNA" on page 177</u> for more information about using DRDA encryption.

At least one authorization ID is always sent to the server to be used for authentication. That ID is one of the following values:

- The primary authorization ID of the process.
- If you connect to the server using a CONNECT statement with the USER keyword, the ID that you specify as the USER ID. The CONNECT statement allows non-RACF user IDs on the USER keyword. If connecting to a remote location, the user ID is not authenticated by RACF.

However, other IDs can accompany some requests. You need to understand what other IDs are sent because they are subject to translation. You must include these other IDs in table SYSIBM.USERNAMES to avoid an error when you use outbound translation. The following table shows the IDs that you send in the different situations:

Table 56. IDs that accompany the primary ID on a remote request		
In this situation:	You send this ID also:	
An SQL query, using Db2DRDA-protocol access	The plan owner	
A remote BIND, COPY, or REBIND PACKAGE command	The package owner	

If the connection is to a remote non-Db2 for z/OS server using DRDA protocol and if the outbound translation is specified, a row for the plan owner in the USERNAMES table is optional.

Related concepts

Security mechanisms for DRDA and SNA

DRDA encryption is not intended to provide confidentiality and integrity of passwords or data over a network that is not secure, such as the Internet. DRDA encryption uses an anonymous key exchange,

Diffie-Hellman, which does not provide authentication of the server or the client. DRDA encryption is vulnerable to man-in-the-middle attacks.

Encrypting your data with Secure Socket Layer (SSL) support

Db2 supports Secure Socket Layer (SSL) protocol by using the z/OS Communications Server IP Application Transparent Transport Layer Security (AT-TLS).

Related tasks

Managing inbound TCP/IP-based connection requests

DRDA connections that use TCP/IP have fewer security controls than do connections that use SNA protocols. When planning to control inbound TCP/IP connection requests, you must decide whether you want the requests to have authentication information, such as RACF passwords, RACF PassTickets, and Kerberos tickets, passed along with authorization IDs.

Sending encrypted passwords from workstation clients

As a server, Db2 for z/OS can accept requests from remote workstation clients that use 256-bit Advanced Encryption Standard (AES) or 56-bit Data Encryption Standards (DES) encryption security over a TCP/IP network connection.

Related reference

TCP/IP ALREADY VERIFIED field (TCPALVER subsystem parameter) (Db2 Installation and Migration)

Related information

Protecting data through encryption and RACF

You can use the Db2 Secure Socket Layer (SSL) support or built-in data encryption functions to protect your sensitive data. You can also use the security features of RACF, or an equivalent system, to protect your data sets.

Communications database for the requester

The *communications database* (CDB) is a set of Db2 catalog tables that let you control aspects of remote requests. Columns in the SYSIBM.LUNAMES, SYSIBM.IPNAMES, SYSIBM.USERNAMES, and SYSIBM.LOCATIONS tables pertain to security that related to the requesting system.

SYSIBM.LUNAMES columns

The SYSIBM.LUNAMES table is used only for outbound requests that use SNA protocols.

GUPI

LUNAME CHAR(8)

The LUNAME of the remote system. A blank value identifies a default row that serves requests from any system that is not specifically listed elsewhere in the column.

SECURITY_OUT (CHAR 1)

Indicates the security option that is used when local Db2 SQL applications connect to any remote server that is associated with the corresponding LUNAME.

Α

The letter A signifies the security option of already verified, and it is the default. With A, outbound connection requests contain an authorization ID and no authentication token. The value that is used for an outbound request is either the Db2 user's authorization ID or a translated ID, depending on the value in the USERNAMES column.

R

The letter R signifies the RACF PassTicket security option. Outbound connection requests contain a user ID and a RACF PassTicket. The LUNAME column is used as the RACF PassTicket application name.

The value that is used for an outbound request is either the Db2 user's authorization ID or a translated ID, depending on the value in the USERNAMES column. The translated ID is used to build the RACF PassTicket. Do not specify R for CONNECT statements with a USER parameter.
Ρ

The letter P signifies the password security option. Outbound connection requests contain an authorization ID and a password. The password is obtained from RACF if ENCRYPTPSWDS=Y, or from SYSIBM.USERNAMES if ENCRYPTPSWDS=N. If you get the password from SYSIBM.USERNAMES, the USERNAMES column of SYSIBM.LUNAMES must contain B or O. The value that is used for an outbound request is the translated ID.

Important: Use of the RACF KDFAES encryption algorithm for a VTAM (SNA) connection is not supported when SECURITY_OUT=P and ENCRYPTPSWDS=Y.

ENCRYPTPSWDS CHAR(1)

Indicates whether passwords received from and sent to the corresponding LUNAME are encrypted. This column only applies to Db2 for z/OS and Db2 for z/OS partners when passwords are used as authentication tokens.

Υ

Yes, passwords are encrypted. For outbound requests, the encrypted password is extracted from RACF and sent to the server. For inbound requests, the password is treated as encrypted.

Ν

No, passwords are not encrypted. This is the default; any character but Y is treated as N.

Recommendation: When you connect to a Db2 for z/OS partner that is at Version 5 or a subsequent release, use RACF PassTickets (SECURITY_OUT='R') instead of encrypting passwords.

USERNAMES CHAR(1)

Indicates whether an ID accompanying a remote attachment request, which is received from or sent to the corresponding LUNAME, is subject to translation and "come from" checking. When you specify I, O, or B, use the SYSIBM.USERNAMES table to perform the translation.

Ι

An inbound ID is subject to translation.

0

An outbound ID, sent to the corresponding LUNAME, is subject to translation.

В

Both inbound and outbound IDs are subject to translation.

blank

No IDs are translated.

GUPI

Related reference

SYSIBM.IPNAMES columns

The SYSIBM.IPNAMES table is used only for outbound requests that use TCP/IP protocols.

SYSIBM.USERNAMES columns

The SYSIBM.USERNAMES table is used by outbound connection requests that use SNA and TCP/IP protocols.

SYSIBM.LOCATIONS columns

The SYSIBM.LOCATIONS table contains a row for every accessible remote server. Each row associates a LOCATION name with the TCP/IP or SNA network attributes for the remote server. Requesters are not defined in the SYSIBM.LOCATIONS table.

SYSIBM.IPNAMES columns

The SYSIBM.IPNAMES table is used only for outbound requests that use TCP/IP protocols.

GUPI

LINKNAME CHAR(8)

The name used in the LINKNAME column of SYSIBM.LOCATIONS to identify the remote system.

IPADDR

Specifies an IP address or domain name of a remote TCP/IP host.

SECURITY_OUT

Indicates the DRDA security option that is used for outbound connections when local Db2 SQL applications connect to any remote server that is associated with this TCP/IP host.

Α

Specifies the default *already verified* option, which means that outbound connection requests contain an authorization ID and no password.

The value that is used for an outbound request is either the Db2 user's authorization ID or a translated ID, depending on the value in the USERNAMES column.

The authorization ID is not encrypted when it is sent to the partner.

For otherwise equivalent behavior with encryption, see 'D'.

D

Specifies the user ID and security-sensitive data encryption option, which means that outbound connection requests contain an authorization ID and no password.

The authorization ID that is used for an outbound request is either the Db2 user's authorization ID or a translated ID, depending on the USERNAMES column.

This option specifies that the user ID and the security-sensitive data are to be encrypted. Security-sensitive data is any input or output data. Examples are rows that are retrieved from a remote server, rows that are sent to the remote server, and SQL statement text.

For otherwise equivalent behavior if you do not require encryption, see 'A'.

Е

Specifies the *user ID, password, and security-sensitive data encryption* option, which means connection requests contain an authorization ID and a password.

This option indicates that the user ID, password, and security-sensitive data are to be encrypted. Security-sensitive data is any input or output data. Examples are rows that are retrieved from a remote server, rows that are sent to the remote server, and SQL statement text.

For otherwise equivalent behavior if you do not require security-sensitive data encryption, see 'P'.

The password is obtained from the SYSIBM.USERNAMES table.

If you specify 'E' for SECURITY OUT, the supported USERNAMES column values depend on the LOCATIONS.TRUSTED column value:

- If the LOCATIONS.TRUSTED column value is 'Y', the USERNAMES value can be 'O' or 'S'.
- If the LOCATIONS.TRUSTED column value is 'N', the USERNAMES must be 'O'.

Ρ

Specifies the *password* security option, which means that outbound connection requests contain an authorization ID and a password.

The password is obtained from the SYSIBM.USERNAMES table.

If you specify 'P' and the server supports encryption, the user ID and the password are encrypted. If the server does not support encryption, the user ID and the password are sent to the partner in clear text.

For otherwise equivalent behavior if you also need to encrypt security-sensitive data, see 'E'.

If you specify 'P' for SECURITY OUT, the supported USERNAMES column values depend on the LOCATIONS.TRUSTED column value:

- If the LOCATIONS.TRUSTED column value is 'Y', the USERNAMES value can be 'O' or 'S'.
- If the LOCATIONS.TRUSTED column value is 'N', the USERNAMES value must be 'O'.

R

Specifies the RACF PassTicket option, which means that outbound connection requests contain a user ID and a RACF PassTicket.

When a RACF PassTicket is generated, the LINKNAME column value is used as the RACF PassTicket application name and must match the following at the target server.

- LUNAME if the remote site is a Db2 subsystem that is defined with only an LUNAME value and no GENERIC LU name value or IPNAME value
- GENERIC if the remote site is a Db2 subsystem that is defined with a GENERIC LU name value in addition to an LUNAME value but no IPNAME value
- IPNAME if the remote site is a Db2 subsystem that is defined with an IPNAME value that triggers the remote Db2 subsystem's DDF to activate only its TCP/IP communications support.

The value that is used for an outbound request is either the Db2 user's authorization ID or a translated ID, depending on the value in the USERNAMES column. The translated ID is used to build the RACF PassTicket.

Important: Do not specify R for CONNECT statements with a USER parameter. If a user ID and password are explicitly specified in a CONNECT statement, Db2 does not translate them.

The authorization ID is not encrypted when it is sent to the partner.

USERNAMES CHAR(1)

This column indicates whether an outbound request translates the authorization ID. When you specify 'O', use the SYSIBM.USERNAMES table to perform the translation.

0

The outbound ID is subject to translation. Rows in the SYSIBM.USERNAMES table are used to perform ID translation. If a connection to any remote server is to be established as trusted, a row in the SYSIBM.USERNAMES table is used to obtain the system authorization ID.

S

The system authorization ID used within a trusted context is obtained from the SYSIBM.USERNAMES table. If the system authorization ID that is specified in the AUTHID column is different from the primary authorization ID, Db2 sends the user switch request on behalf of the primary authorization ID after successfully establishing the trusted connection.

blank

No translation is done.

Supported combinations for SECURITY_OUT and USERNAMES column values

The following table summarizes the supported USERNAMES values for specific IPNAMES.SECURITY_OUT and LOCATIONS.TRUSTED column values. Db2 returns an error if other unsupported combinations of these values are specified.

IPNAMES.SECURITY_OUT option	LOCATIONS.TRUSTED option	IPNAMES.USERNAMES values supported
'A'	Any	blank
'D'	Any	blank
'E'	'N'	'0'
'E'	'Υ	'0' or 'S'
'P'	'N'	'0'
'P'	'Υ	'0' or 'S'
'R'	Any	'O' , 'S', or blank
'T'	'N'	'O' or blank

GUPI

Related tasks

Establishing remote trusted connections by Db2 for z/OS requesters A Db2 for z/OS requester can establish a trusted connection to a remote location by setting up the new TRUSTED column in the SYSIBM.LOCATIONS table.

Related reference

SYSIBM.LUNAMES columns The SYSIBM.LUNAMES table is used only for outbound requests that use SNA protocols.

SYSIBM.USERNAMES columns

The SYSIBM.USERNAMES table is used by outbound connection requests that use SNA and TCP/IP protocols.

SYSIBM.LOCATIONS columns

The SYSIBM.LOCATIONS table contains a row for every accessible remote server. Each row associates a LOCATION name with the TCP/IP or SNA network attributes for the remote server. Requesters are not defined in the SYSIBM.LOCATIONS table.

IPNAMES catalog table (Db2 SQL)

SYSIBM.USERNAMES columns

The SYSIBM.USERNAMES table is used by outbound connection requests that use SNA and TCP/IP protocols.

GUPI

TYPE CHAR(1)

Indicates whether the row is used for inbound or outbound translation:

S

The row is used to obtain the outbound system authorization ID for establishing a trusted connection.

Ι

The row applies to inbound IDs.

0

The row applies to outbound IDs.

The field should contain only I, O, or S. Any other character, including blank, causes the row to be ignored.

AUTHID VARCHAR(128)

An authorization ID that is permitted and perhaps translated. If blank, any authorization ID is permitted with the corresponding LINKNAME, and all authorization IDs are translated in the same way.

LINKNAME CHAR(8)

Identifies the VTAM or TCP/IP network locations that are associated with this row. A blank value in this column indicates that this name translation rule applies to any TCP/IP or SNA partner.

If you specify a nonblank value for this column, one or both of the following situations must be true:

- A row exists in table SYSIBM.LUNAMES that has an LUNAME value that matches the LINKNAME value that appears in this column.
- A row exists in table SYSIBM.IPNAMES that has a LINKNAME value that matches the LINKNAME value that appears in this column.

NEWAUTHID VARCHAR(128)

The translated authorization ID. If blank, no translation occurs.

PASSWORD VARCHAR(255)

A password or password phrase that is sent with an outbound request if passwords or phrases are not encrypted by RACF. The column is not used if passwords or phrases are encrypted or if the row is for inbound requests. A password or password phrase can be stored as encrypted data by calling the DSNLEUSR stored procedure. To send the encrypted value of the PASSWORD column through a network, you must specify one of the encryption options in the SYSIBM.IPNAMES table.

GUPI

Related reference

SYSIBM.LUNAMES columns

The SYSIBM.LUNAMES table is used only for outbound requests that use SNA protocols.

SYSIBM.IPNAMES columns

The SYSIBM.IPNAMES table is used only for outbound requests that use TCP/IP protocols.

SYSIBM.LOCATIONS columns

The SYSIBM.LOCATIONS table contains a row for every accessible remote server. Each row associates a LOCATION name with the TCP/IP or SNA network attributes for the remote server. Requesters are not defined in the SYSIBM.LOCATIONS table.

SYSIBM.LOCATIONS columns

The SYSIBM.LOCATIONS table contains a row for every accessible remote server. Each row associates a LOCATION name with the TCP/IP or SNA network attributes for the remote server. Requesters are not defined in the SYSIBM.LOCATIONS table.

GUPI

LOCATION CHAR(16)

Indicates the unique location name by which the remote server is known to local Db2 SQL applications.

LINKNAME CHAR(8)

Identifies the VTAM or TCP/IP network locations that are associated with this row. A blank value in this column indicates that this name translation rule applies to any TCP/IP or SNA partner.

If you specify a non-blank value for this column, one or both of the following situations must be true:

- A row exists in table SYSIBM.LUNAMES that has an LUNAME value that matches the LINKNAME value that appears in this column.
- A row exists in table SYSIBM.IPNAMES that has a LINKNAME value that matches the LINKNAME value that appears in this column.

For information on the effects of changing values for TCP/IP connections to values for VTAM connections in CDB (communications database) tables, see <u>When updates to CDB values take effect</u> for VTAM (SNA) connections (Db2 Installation and Migration).

PORT CHAR(32)

Indicates that TCP/IP is used for outbound connections when the following statement is true:

• A row exists in SYSIBM.IPNAMES, where the LINKNAME column matches the value that is specified in the SYSIBM.LOCATIONS LINKNAME column.

If the previously mentioned row is found, and the SECURE column has a value of 'N', the value of the PORT column is interpreted as follows:

- If PORT is blank, the default DRDA port (446) is used.
- If PORT is nonblank, the value that is specified for PORT can take one of two forms:
 - If the value in PORT is left-justified with one to five numeric characters, the value is assumed to be the TCP/IP port number of the remote database server.
 - Any other value is assumed to be a TCP/IP service name, which you can convert to a TCP/IP port number by using the TCP/IP getservbyname socket call. TCP/IP service names are not case-sensitive.

If the previously mentioned row is found, and the SECURE column has a value of 'Y', the value of the PORT column is interpreted as follows:

• If PORT is blank, the default secure DRDA port (448) is used.

• If PORT is nonblank, the value that is specified for PORT takes the value of the configured secure DRDA port at the remote server.

TPN VARCHAR(64)

Used only when the local Db2 begins an SNA conversation with another server. When used, TPN indicates the SNA LU 6.2 transaction program name (TPN) that will allocate the conversation. A length of zero for the column indicates the default TPN. For DRDA conversations, this is the DRDA default, which is X'07F6C4C2'.

DBALIAS(128)

Used to access a remote database server. If DBALIAS is blank, the location name is used to access the remote database server. This column does not change the name of any database objects sent to the remote site that contains the location qualifier.

TRUSTED

Indicates whether the connection to the remote server can be trusted. This is restricted to TCP/IP only. This column is ignored for connections that use SNA.

Υ

The location is trusted. Access to the remote location requires a trusted context that is defined at the remote location.

Ν

The location is not trusted.

SECURE

Indicates the use of the Secure Socket Layer (SSL) protocol for outbound connections when local Db2 applications connect to the remote database server by using TCP/IP.

Υ

A secure SSL connection is required for the outbound connection.

Ν

A secure connection is not required for the outbound connection.

GUPI

Related reference

SYSIBM.LUNAMES columns

The SYSIBM.LUNAMES table is used only for outbound requests that use SNA protocols.

SYSIBM.IPNAMES columns

The SYSIBM.IPNAMES table is used only for outbound requests that use TCP/IP protocols.

SYSIBM.USERNAMES columns

The SYSIBM.USERNAMES table is used by outbound connection requests that use SNA and TCP/IP protocols.

Processing of outbound connection requests

A Db2 subsystem completes a sequence of tasks when sending out a connection request.



Figure 10. Steps in sending a request from a Db2 subsystem

1. The Db2 subsystem that sends the request checks whether the primary authorization ID has the privilege to execute the plan or package.

Db2 determines which value in the LINKNAME column of the SYSIBM.LOCATIONS table matches either the LUNAME column in the SYSIBM.LUNAMES table or the LINKNAME column in the SYSIBM.IPNAMES table. This check determines whether SNA or TCP/IP protocols are used to carry the DRDA request. See <u>"Security mechanisms for DRDA and SNA" on page 177</u> for more information about using DRDA encryption.

- 2. When a plan is executed, the authorization ID of the plan owner is sent with the primary authorization ID. When a package is bound, the authorization ID of the package owner is sent with the primary authorization ID. If the USERNAMES column of the SYSIBM.LUNAMES table contains O or B, or if the USERNAMES column of the SYSIBM.IPNAMES table contains O, both IDs are subject to translation under control of the SYSIBM.USERNAMES table. Ensure that these IDs are included in SYSIBM.USERNAMES, or SQLCODE -904 is issued. Db2 translates the ID as follows:
 - If a nonblank value of NEWAUTHID is in the row, that value becomes the new ID.
 - If NEWAUTHID is blank, the ID is not changed.

If the SYSIBM.USERNAMES table does not contain a new authorization ID to which the primary authorization ID is translated, the request is rejected with SQLCODE -904.

If the USERNAMES column does not contain O or B, the IDs are not translated.

3. SECURITY_OUT is checked for outbound security options as shown in the following diagram.



Figure 11. Details of Step 3

Α

Already verified. No password is sent with the authorization ID. This option is valid only if the server accepts already verified requests.

- For SNA, the server must have specified A in the SECURITY_IN column of SYSIBM.LUNAMES.
- For TCP/IP, the server must have specified YES in the TCP/IP ALREADY VERIFIED field of installation panel DSNTIP5.

R

RACF PassTicket. If the primary authorization ID was translated, that translated ID is sent with the PassTicket.

Ρ

Password. The outbound request must be accompanied by a password:

• If the requester is Db2 for z/OS and uses SNA protocols, passwords can be encrypted if you specify Y in the ENCRYPTPSWDS column of SYSIBM.LUNAMES. If passwords are encrypted, the

password is obtained from RACF. If passwords are not encrypted, the password is obtained from the PASSWORD column of SYSIBM.USERNAMES.

• If the requester uses TCP/IP protocols, the password is obtained from the PASSWORD column of SYSIBM.USERNAMES. If the Integrated Cryptographic Service Facility is enabled and properly configured and the server supports encryption, the password is encrypted.

Recommendation: Use RACF PassTickets to avoid sending unencrypted passwords over the network.

D

User ID and security-sensitive data encryption. No password is sent with the authorization ID. If the Integrated Cryptographic Service Facility (ICSF) is enabled and properly configured and the server supports encryption, the authorization ID is encrypted before it is sent. If the ICSF is not enabled or properly configured, SQL return code –904 is returned. If the server does not support encryption, SQL return code –30082 is returned.

Е

User ID, password, and security-sensitive data encryption. If the ICSF is enabled and properly configured and the server supports encryption, the password is encrypted before it is sent. If the ICSF is not enabled or properly configured, SQL return code –904 is returned. If the server does not support encryption, SQL return code –30082 is returned.

Security options D and E control *security-sensitive data* encryption. Security-sensitive data is any input or output data. Examples are rows that are retrieved from a remote server, rows that are sent to the remote server, and SQL statement text.

4. Send the request.

Related concepts

Security mechanisms for DRDA and SNA

DRDA encryption is not intended to provide confidentiality and integrity of passwords or data over a network that is not secure, such as the Internet. DRDA encryption uses an anonymous key exchange, Diffie-Hellman, which does not provide authentication of the server or the client. DRDA encryption is vulnerable to man-in-the-middle attacks.

Encrypting your data with Secure Socket Layer (SSL) support

Db2 supports Secure Socket Layer (SSL) protocol by using the z/OS Communications Server IP Application Transparent Transport Layer Security (AT-TLS).

Related tasks

Managing inbound TCP/IP-based connection requests

DRDA connections that use TCP/IP have fewer security controls than do connections that use SNA protocols. When planning to control inbound TCP/IP connection requests, you must decide whether you want the requests to have authentication information, such as RACF passwords, RACF PassTickets, and Kerberos tickets, passed along with authorization IDs.

Sending encrypted passwords from workstation clients

As a server, Db2 for z/OS can accept requests from remote workstation clients that use 256-bit Advanced Encryption Standard (AES) or 56-bit Data Encryption Standards (DES) encryption security over a TCP/IP network connection.

Related reference

Processing of TCP/IP-based connection requests

The Db2 server completes a sequence of authentication tasks when handling a remote connection request that uses the TCP/IP protocol.

TCP/IP ALREADY VERIFIED field (TCPALVER subsystem parameter) (Db2 Installation and Migration)

Related information

Protecting data through encryption and RACF

You can use the Db2 Secure Socket Layer (SSL) support or built-in data encryption functions to protect your sensitive data. You can also use the security features of RACF, or an equivalent system, to protect your data sets.

Translating outbound IDs

If an ID on your system is duplicated on a remote system, you can translate outbound IDs to avoid confusion. You can also translate IDs to ensure that they are accepted by the remote system.

Procedure

To indicate that you want to translate outbound user IDs, perform the following steps:

- 1. Specify an O in the USERNAMES column of the SYSIBM.IPNAMES or SYSIBM.LUNAMES table.
- 2. Use the NEWAUTHID column of the SYSIBM.USERNAMES table to specify the ID to which the outbound ID is translated.

Example

Suppose that the remote system accepts from you only the IDs XXGALE, GROUP1, and HOMER.

1. Specify that outbound translation is in effect for the remote system LUXXX by specifying in SYSIBM.LUNAMES the values that are shown in the following table.

Table 57. SYSIBM.LUNAMES to specify that outbound translation is in effect for the remote system LUXXX			
LUNAME USERNAMES			
LUXXX O			

If your row for LUXXX already has I for the USERNAMES column (because you translate inbound IDs that come from LUXXX), change I to B for both inbound and outbound translation.

2. Translate the ID GALE to XXGALE on all outbound requests to LUXXX by specifying in SYSIBM.USERNAMES the values that are shown in the following table.

Table 58. Values in SYSIBM. USERNAMES to translate GALE to XXGALE on outbound requests to LUXXX

ТҮРЕ	AUTHID	LINKNAME	NEWAUTHID	PASSWORD
0	GALE	LUXXX	XXGALE	GALEPASS

3. Translate EVAN and FRED to GROUP1 on all outbound requests to LUXXX by specifying in SYSIBM.USERNAMES the values that are shown in the following table.

Table 59. Values in SYSIBM. USERNAMES to translate EVAN and FRED to GROUP1 on outbound requests to LUXXX

ТҮРЕ	AUTHID	LINKNAME	NEWAUTHID	PASSWORD
0	EVAN	LUXXX	GROUP1	GRP1PASS
0	FRED	LUXXX	GROUP1	GRP1PASS

4. Do not translate the ID HOMER on outbound requests to LUXXX. (HOMER is assumed to be an ID on your Db2, and on LUXXX.) Specify in SYSIBM.USERNAMES the values that are shown in the following table.

Table 60. Values in SYSIBM. USERNAMES to not translate HOMER on outbound requests to LUXXX				
ТҮРЕ	AUTHID LINKNAME NEWAUTHID PASSWORD			
0	HOMER	LUXXX	(blank)	HOMERSPW

5. Reject any requests from BASIL to LUXXX before they are sent. To do that, leave SYSIBM.USERNAMES empty. If no row indicates what to do with the ID BASIL on an outbound request to LUXXX, the request is rejected.

If you send requests to another LU, such as LUYYY, you generally need another set of rows to indicate how your IDs are to be translated on outbound requests to LUYYY.

However, you can use a single row to specify a translation that is to be in effect on requests to all other LUs. For example, if HOMER is to be sent untranslated everywhere, and DOROTHY is to be translated to GROUP1 everywhere, specify in SYSIBM.USERNAMES the values that are shown in the following table.

Table 61. Values in SYSIBM. USERNAMES to not translate HOMER and to translate DOROTHY to GROUP1				
ТҮРЕ	AUTHID	LINKNAME	NEWAUTHID	PASSWORD
0	HOMER	(blank)	(blank)	HOMERSPW
0	DOROTHY	(blank)	GROUP1	GRP1PASS

You can also use a single row to specify that all IDs that accompany requests to a single remote system must be translated. For example, if every one of your IDs is to be translated to THEIRS on requests to LUYYY, specify in SYSIBM.USERNAMES the values that are shown in the following table.

Table 62. Values in SYSIBM. USERNAMES to translate every ID to THEIRS				
TYPE AUTHID LINKNAME NEWAUTHID PASSWORD				PASSWORD
0	(blank)	LUYYY	THEIR	THEPASS

If the ICSF is installed and properly configured, you can use the DSNLEUSR stored procedure to encrypt the translated outbound IDs that are specified in the NEWAUTHID column of SYSIBM.USERNAMES. Db2 decrypts the translated outbound IDs during connection processing.

Sending passwords or password phrases

Db2 provides several security mechanisms to send password or password phrase information.

About this task

Specifically, Db2 supports the following security mechanisms:

- RACF encrypted passwords
- RACF PassTickets
- Kerberos tickets
- DRDA-encrypted passwords or password phrases or DRDA-encrypted user IDs with encrypted passwords or password phrases. See <u>"Security mechanisms for DRDA and SNA" on page 177</u> for more information about using DRDA encryption.

If you have to send passwords or password phrases through the network, you can put the password or password phrase for a user ID in the PASSWORD column of the SYSIBM.USERNAMES table.

Recommendation: Use the DSNLEUSR stored procedure to encrypt passwords or password phrases in SYSIBM.USERNAMES. If the ICSF is installed and properly configured, you can use the DSNLEUSR stored procedure to encrypt passwords or password phrases in the SYSIBM.USERNAMES table. Db2 decrypts the password or password phrase during connection processing.

Db2 for z/OS allows the use of RACF encrypted passwords or RACF PassTickets. However, workstations, such as Windows workstations, do not support these security mechanisms. RACF encrypted passwords are not a secure mechanism because they can be replayed. RACF PassTickets are not compatible with SECURITY_ENCRYPT; they are allowed only when the connections are secured by the TCP/IP network.

Recommendation: Do not use RACF encrypted passwords unless you are connecting to a previous release of Db2 for z/OS.

Related concepts

Security mechanisms for DRDA and SNA

DRDA encryption is not intended to provide confidentiality and integrity of passwords or data over a network that is not secure, such as the Internet. DRDA encryption uses an anonymous key exchange, Diffie-Hellman, which does not provide authentication of the server or the client. DRDA encryption is vulnerable to man-in-the-middle attacks.

Encrypting your data with Secure Socket Layer (SSL) support

Db2 supports Secure Socket Layer (SSL) protocol by using the z/OS Communications Server IP Application Transparent Transport Layer Security (AT-TLS).

Related tasks

Managing inbound TCP/IP-based connection requests

DRDA connections that use TCP/IP have fewer security controls than do connections that use SNA protocols. When planning to control inbound TCP/IP connection requests, you must decide whether you want the requests to have authentication information, such as RACF passwords, RACF PassTickets, and Kerberos tickets, passed along with authorization IDs.

Sending encrypted passwords from workstation clients

As a server, Db2 for z/OS can accept requests from remote workstation clients that use 256-bit Advanced Encryption Standard (AES) or 56-bit Data Encryption Standards (DES) encryption security over a TCP/IP network connection.

Related reference

TCP/IP ALREADY VERIFIED field (TCPALVER subsystem parameter) (Db2 Installation and Migration)

Related information

Protecting data through encryption and RACF

You can use the Db2 Secure Socket Layer (SSL) support or built-in data encryption functions to protect your sensitive data. You can also use the security features of RACF, or an equivalent system, to protect your data sets.

Sending RACF-encrypted passwords

For Db2 subsystems that use SNA protocols to communicate with each other, you can specify password encryption in the SYSIBM.LUNAMES table.

About this task

Table 63. Specifying password encryption in SYSIBM.LUNAMES			
LUNAME USERNAMES ENCRYPTPSWDS			
LUXXX	0	Y	

The partner Db2 must also specify password encryption in its SYSIBM.LUNAMES table. Both partners must register each ID and its password with RACF. Then, for every request to LUXXX, your Db2 calls RACF to supply an encrypted password to accompany the ID. With password encryption, you do not use the PASSWORD column of SYSIBM.USERNAMES, so the security of that table becomes less critical.

Related concepts

Enabling a z/OS application to send RACF PassTickets

If Db2 has been enabled to receive a RACF PassTicket as a password, a z/OS application that connects to Db2 can be enabled to generate and use a RACF PassTicket as a password in the connection request.

Related tasks

Enabling Db2 to send RACF PassTickets

Db2 supports the ability to send RACF PassTickets with your remote requests to a remote Db2 subsystem or data sharing group.

Sending encrypted passwords or password phrases from Db2 for z/OS clients

As a requester, a Db2 for z/OS client can send connection requests that use 256-bit Advanced Encryption Standard (AES) or 56-bit Data Encryption Standards (DES) encryption security through a TCP/IP network to remote servers.

Sending encrypted passwords from workstation clients

As a server, Db2 for z/OS can accept requests from remote workstation clients that use 256-bit Advanced Encryption Standard (AES) or 56-bit Data Encryption Standards (DES) encryption security over a TCP/IP network connection.

Enabling Db2 to send RACF PassTickets

Db2 supports the ability to send RACF PassTickets with your remote requests to a remote Db2 subsystem or data sharing group.

Procedure

To enable Db2 to generate and send PassTickets, specify 'R' in the SECURITY_OUT column of the SYSIBM.IPNAMES or SYSIBM.LUNAMES table for each remote system that you want to send RACF PassTickets to.

You can also use the z/OS R_GenSec service to perform PassTicket functions through a native SAF service. See z/OS Security Server RACF Callable Services for more information.

What to do next

To enable Db2 to receive PassTickets from remote requests, see <u>Enabling Db2 to receive RACF</u> PassTickets.

Related concepts

Enabling a z/OS application to send RACF PassTickets

If Db2 has been enabled to receive a RACF PassTicket as a password, a z/OS application that connects to Db2 can be enabled to generate and use a RACF PassTicket as a password in the connection request.

Db2 support for RACF PassTickets

Db2 supports the ability to send and receive RACF PassTicketsto authenticate a user who is accessing a Db2 server.

Related tasks

Sending RACF-encrypted passwords For Db2 subsystems that use SNA protocols to communicate with each other, you can specify password encryption in the SYSIBM.LUNAMES table.

Sending encrypted passwords or password phrases from Db2 for z/OS clients

As a requester, a Db2 for z/OS client can send connection requests that use 256-bit Advanced Encryption Standard (AES) or 56-bit Data Encryption Standards (DES) encryption security through a TCP/IP network to remote servers.

Sending encrypted passwords from workstation clients

As a server, Db2 for z/OS can accept requests from remote workstation clients that use 256-bit Advanced Encryption Standard (AES) or 56-bit Data Encryption Standards (DES) encryption security over a TCP/IP network connection.

Enabling a z/OS application to send RACF PassTickets

If Db2 has been enabled to receive a RACF PassTicket as a password, a z/OS application that connects to Db2 can be enabled to generate and use a RACF PassTicket as a password in the connection request.

For information about building applications that are authorized to generate and use RACF PassTickets, see the RACF topic Generating and evaluating a PassTicket .

Requirements:

- When you authorize an application to generate a RACF PassTicket, you must specify a specific Db2 subsystem or members of a specific Db2 data sharing group. Only those applications that meet this requirement will be able to generate a RACF PassTicket. For more information about using PassTickets to permit application user IDs to access Db2, see the aforementioned RACF topic.
- Only z/OS application requests that originate from a Db2 for z/OS DRDA requester can connect to Db2 with a RACF-protected user ID. The use of RACF-protected user IDs is not supported by non-z/OS DRDA requesters.

Related tasks

Sending RACF-encrypted passwords

For Db2 subsystems that use SNA protocols to communicate with each other, you can specify password encryption in the SYSIBM.LUNAMES table.

Enabling Db2 to send RACF PassTickets

Db2 supports the ability to send RACF PassTickets with your remote requests to a remote Db2 subsystem or data sharing group.

Sending encrypted passwords or password phrases from Db2 for z/OS clients

As a requester, a Db2 for z/OS client can send connection requests that use 256-bit Advanced Encryption Standard (AES) or 56-bit Data Encryption Standards (DES) encryption security through a TCP/IP network to remote servers.

Sending encrypted passwords from workstation clients

As a server, Db2 for z/OS can accept requests from remote workstation clients that use 256-bit Advanced Encryption Standard (AES) or 56-bit Data Encryption Standards (DES) encryption security over a TCP/IP network connection.

Sending encrypted passwords or password phrases from Db2 for z/OS clients

As a requester, a Db2 for z/OS client can send connection requests that use 256-bit Advanced Encryption Standard (AES) or 56-bit Data Encryption Standards (DES) encryption security through a TCP/IP network to remote servers.

About this task

If the Db2 for z/OS client supports DRDA Security Manager (SECMGR) 9 or higher, and if z/OS ICSF is configured and started, the Db2 for z/OS client can send AES requests to a remote server. After the first successful connection, the Db2 for z/OS client can determine whether the remote server supports AES encryption security. If the remote server supports DRDA SECMGR 9 (or higher), the remote server accepts AES requests and encrypts the user IDs and passwords or password phrases that the client sends in AES.

If AES encryption is not available for the remote Db2 for z/OS server, the Db2 for z/OS client tries DES encryption. If DES encryption fails, the Db2 for z/OS client sends the user ID and password or password phrase in clear text.

See <u>"Security mechanisms for DRDA and SNA" on page 177</u> for more information about using DRDA encryption. See the Db2 for z/OS Program Directory for ICSF hardware and software requirements for AES encryption.

As a client, Db2 for z/OS supports only the IPNAMES.SECURITY_OUT option 'P' ("password") for AES encryption and decryption. Db2 for z/OS does not support the IPNAMES.SECURITY_OUT option 'D' ("user ID and security-sensitive data encryption") or 'E' ("user ID, password, and security-sensitive data encryption"). These outbound security options remain encrypted in DES.



Attention: To protect your authentication information, use the z/OS Communications Server IP Application Transparent Transport Layer Security (AT-TLS) to secure your network connections. To complement the use of AT-TLS, set the TCPALVER subsystem parameter of installation panel DSNTIP5 to SERVER_ENCRYPT. Setting this parameter to SERVER_ENCRYPT provides the strongest level of security. Connections are accepted only if user credentials are provided to authenticate the user ID, and strong encryption is used to protect the user ID and credentials.

Related concepts

Enabling a z/OS application to send RACF PassTickets

If Db2 has been enabled to receive a RACF PassTicket as a password, a z/OS application that connects to Db2 can be enabled to generate and use a RACF PassTicket as a password in the connection request.

Program directories for Db2 12 (Db2 for z/OS in IBM Documentation)

Security mechanisms for DRDA and SNA

DRDA encryption is not intended to provide confidentiality and integrity of passwords or data over a network that is not secure, such as the Internet. DRDA encryption uses an anonymous key exchange, Diffie-Hellman, which does not provide authentication of the server or the client. DRDA encryption is vulnerable to man-in-the-middle attacks.

Encrypting your data with Secure Socket Layer (SSL) support

Db2 supports Secure Socket Layer (SSL) protocol by using the z/OS Communications Server IP Application Transparent Transport Layer Security (AT-TLS).

Encrypted password, user ID, or data security under the IBM Data Server Driver for JDBC and SQLJ (Db2 Application Programming for Java)

Related tasks

Sending RACF-encrypted passwords For Db2 subsystems that use SNA protocols to communicate with each other, you can specify password encryption in the SYSIBM.LUNAMES table.

Enabling Db2 to send RACF PassTickets

Db2 supports the ability to send RACF PassTickets with your remote requests to a remote Db2 subsystem or data sharing group.

Sending encrypted passwords from workstation clients

As a server, Db2 for z/OS can accept requests from remote workstation clients that use 256-bit Advanced Encryption Standard (AES) or 56-bit Data Encryption Standards (DES) encryption security over a TCP/IP network connection.

Managing inbound TCP/IP-based connection requests

DRDA connections that use TCP/IP have fewer security controls than do connections that use SNA protocols. When planning to control inbound TCP/IP connection requests, you must decide whether you want the requests to have authentication information, such as RACF passwords, RACF PassTickets, and Kerberos tickets, passed along with authorization IDs.

Related reference

TCP/IP ALREADY VERIFIED field (TCPALVER subsystem parameter) (Db2 Installation and Migration)

Related information

Protecting data through encryption and RACF

You can use the Db2 Secure Socket Layer (SSL) support or built-in data encryption functions to protect your sensitive data. You can also use the security features of RACF, or an equivalent system, to protect your data sets.

Sending encrypted passwords from workstation clients

As a server, Db2 for z/OS can accept requests from remote workstation clients that use 256-bit Advanced Encryption Standard (AES) or 56-bit Data Encryption Standards (DES) encryption security over a TCP/IP network connection.

About this task

Depending on the DRDA level, a remote client can use AES or DES encryption algorithm for sending passwords, user IDs and associated passwords, or other security-sensitive data to a Db2 for z/OS server. If the client explicitly requests AES encryption, only user IDs, passwords, or both are encrypted in AES, and any data in the request is encrypted in DES. Any persistent attempt to encrypt the data in AES causes the client to reject the connection request. See <u>"Security mechanisms for DRDA and SNA" on page 177</u> for more information about using DRDA encryption. See the Db2 for z/OS Program Directory for ICSF hardware and software requirements for AES encryption.

To enable the Db2 for z/OS AES server support, you must install and configure z/OS Integrated Cryptographic Services Facility (ICSF). During Db2 startup, DSNXINIT invokes the MVS LOAD macro service to load various ICSF services, including the ICSF CSNESYE and CSNESYD modules that Db2 calls for processing AES encryption and decryption requests. If ICSF is not installed or if ICSF services are not available, Db2 cannot provide AES support, and Db2 terminates the connection.

To use DES encryption, you can enable Db2 Connect to send encrypted passwords by setting database connection services (DCS) authentication to DCS_ENCRYPT in the DCS directory entry. When a client application issues an SQL CONNECT statement, the client negotiates this support with the database server. If supported, a shared private key is generated by the client and server using the Diffie-Hellman public key technology, and the password is encrypted using 56-bit DES with the shared private key. The encrypted password cannot be replayed, and the shared private key is generated on every connection. If the server does not support password encryption, the application receives SQLCODE -30073 (DRDA security manager level 6 is not supported).



Attention: To protect your authentication information, use the z/OS Communications Server IP Application Transparent Transport Layer Security (AT-TLS) to secure your network connections. To complement the use of AT-TLS, set the TCPALVER subsystem parameter of installation panel DSNTIP5 to SERVER_ENCRYPT. Setting this parameter to SERVER_ENCRYPT provides the strongest level of security. Connections are accepted only if user credentials are provided to authenticate the user ID, and strong encryption is used to protect the user ID and credentials.

Related concepts

Enabling a z/OS application to send RACF PassTickets

If Db2 has been enabled to receive a RACF PassTicket as a password, a z/OS application that connects to Db2 can be enabled to generate and use a RACF PassTicket as a password in the connection request.

Program directories for Db2 12 (Db2 for z/OS in IBM Documentation)

Security mechanisms for DRDA and SNA

DRDA encryption is not intended to provide confidentiality and integrity of passwords or data over a network that is not secure, such as the Internet. DRDA encryption uses an anonymous key exchange, Diffie-Hellman, which does not provide authentication of the server or the client. DRDA encryption is vulnerable to man-in-the-middle attacks.

Encrypting your data with Secure Socket Layer (SSL) support

Db2 supports Secure Socket Layer (SSL) protocol by using the z/OS Communications Server IP Application Transparent Transport Layer Security (AT-TLS).

Encrypted password, user ID, or data security under the IBM Data Server Driver for JDBC and SQLJ (Db2 Application Programming for Java)

Related tasks

Sending RACF-encrypted passwords

For Db2 subsystems that use SNA protocols to communicate with each other, you can specify password encryption in the SYSIBM.LUNAMES table.

Enabling Db2 to send RACF PassTickets

Db2 supports the ability to send RACF PassTickets with your remote requests to a remote Db2 subsystem or data sharing group.

Sending encrypted passwords or password phrases from Db2 for z/OS clients

As a requester, a Db2 for z/OS client can send connection requests that use 256-bit Advanced Encryption Standard (AES) or 56-bit Data Encryption Standards (DES) encryption security through a TCP/IP network to remote servers.

Managing inbound TCP/IP-based connection requests

DRDA connections that use TCP/IP have fewer security controls than do connections that use SNA protocols. When planning to control inbound TCP/IP connection requests, you must decide whether you want the requests to have authentication information, such as RACF passwords, RACF PassTickets, and Kerberos tickets, passed along with authorization IDs.

Sending encrypted passwords or password phrases from Db2 for z/OS clients

As a requester, a Db2 for z/OS client can send connection requests that use 256-bit Advanced Encryption Standard (AES) or 56-bit Data Encryption Standards (DES) encryption security through a TCP/IP network to remote servers.

Related reference

TCP/IP ALREADY VERIFIED field (TCPALVER subsystem parameter) (Db2 Installation and Migration)

Related information

Protecting data through encryption and RACF

You can use the Db2 Secure Socket Layer (SSL) support or built-in data encryption functions to protect your sensitive data. You can also use the security features of RACF, or an equivalent system, to protect your data sets.

220 Db2 12 for z/OS: Managing Security (Last updated: 2024-09-06)

Chapter 4. Managing access through row permissions and column masks

Row and column access control enables you to manage access to a table at the level of a row, a column, or both. You can implement row access control through row permissions and column access control through column masks.

Row and column access control

Row and column access control is a Db2 security solution that uses SQL to control access to a table at the level of a row, a column, or both.

Traditionally, access control at the row and column level is implemented through views. Using views as an access control method works well only when access rules, restrictions, and conditions are monolithic and simple. It however becomes ineffective when view definitions become too complex because of the complexity and granularity of privacy and security policies. It also becomes costly when a large number of views must be manually updated and maintained. In addition, the ability to update views proves to be challenging. As privacy and security policies evolve, required updates to views may negatively affect the security logic particularly when database applications reference the views directly by name. Db2 row and column access control helps resolve all these problems.

Implemented through SQL and managed by the Db2 security administrator, row and column access control allows you to manage access to a table with filtering and data masking. Unlike multilevel security, row and column access control is integrated into a database system, and all applications and tools that use SQL to access the database are automatically subject to the same control. This effectively eliminates the need to filter security-sensitive data at the application level and ensures that the data is protected when the applications and tools use SQL to access it.

Row and column access control is based on a security policy that specifies the rules and conditions under which a user, group, or role can access rows, columns, or both of a base table. The access control is not needed at the view level because the view automatically receives row and column access control that is activated on the underlining base table. The row and column access control rules do not affect how a read-only view is determined. All users access the same base table (as opposed to alternative views of a table), but access restrictions are based on individual user permissions and masks that are specified by a policy associated with the table.

An authorization ID or role with the SECADM authority can manage row and column access control. The SECADM authority can activate or deactivate row and column access control for a table, grant or revoke the CREATE_SECURE_OBJECT system privilege, and create, alter, or drop row permissions and column masks. The SYSADM authority can perform the same tasks if the SEPARATE SECURITY system parameter on panel DSNTIPP1 is set to NO during installation.

Row and column access control can be activated for a table before or after row permissions or column masks are created for the table. If row permissions or column masks already exist, activating row and column access control simply makes the permissions or masks become effective. If row permissions or column masks do not yet exist, activating row access control for a table means that Db2 will generate a default row permission that prevents any access to the table by SQL, and activating column access control means to wait for the column masks to be created.

When a table is activated for row or column access control, all users, including the table owner and the SECADM, SYSADM, or DBADM authorities, are subject to the same security rules and restrictions. This ensures that access to security-sensitive data is truly on a need basis and prevents system and database administrators from unnecessarily accessing it. Since security policies or rules are expressed and enforced through SQL, row and column access control is inherently flexible.

Row access control and multilevel security are mutually exclusive. If a table is activated for row access control, it cannot be altered to include a security label column; if a table has a security label column, it cannot be activated for row access control. Column access control, on the other hand, is not affected by

multilevel security. If a table is activated for column level access control, it can be altered to include a security label column, and vice versa.

Related concepts

Row permission

A *row permission* is a database object that describes a specific row access control rule for a table. In the form of an SQL search condition, the rule specifies the conditions under which a user, group, or role can access the rows of data in the table.

Column masks

A *column mask* is a database object that describes a specific column access control rule for a column. In the form of an SQL CASE expression, the rule specifies the condition under which a user, group, or role can receive the masked values that are returned for a column.

Related reference

Explicit system privileges

You can explicitly grant privileges on systems.

SECADM administrative authority

The SECADM authority enables you to manage security-related objects in Db2 and control access to all database resources. It does not have any inherent privilege to access data stored in the objects, such as tables.

Row permission

A *row permission* is a database object that describes a specific row access control rule for a table. In the form of an SQL search condition, the rule specifies the conditions under which a user, group, or role can access the rows of data in the table.

Stored in the system catalog, row permissions can be created on all base tables except materialized query tables, and they are maintained on an individual basis. The definition of each row permission may reference the user, group, or role in the search condition.

If multiple row permissions are defined for a table and when row access control is activated, the search condition in each row permission is connected by the logical OR operator to form the row access control search condition. This row access control search condition is applied whenever the table is accessed. It acts as a filter to the table before any other user-specified operations, such as predicates and ordering, are processed. It also acts like the WITH CHECK OPTION clause of a view to ensure that a row to be inserted or updated conforms to the definitions of the row permissions in an INSERT, UPDATE, or MERGE statement.

Only an authorization ID or role with the SECADM or SYSADM authority can manage row permissions. If the SEPARATE_SECURITY system parameter on panel DSNTIPP1 is set to YES during installation or migration, you must have the SECADM authority to create, alter, or drop row permissions. If SEPARATE_SECURITY is set to NO, you must have the SECADM or SYSADM authority.

Related concepts

Column masks

A *column mask* is a database object that describes a specific column access control rule for a column. In the form of an SQL CASE expression, the rule specifies the condition under which a user, group, or role can receive the masked values that are returned for a column.

Related tasks

Creating row permissions

A *row permission* specifies the conditions under which users can access a row. With the SECADM authority, you can use the CREATE PERMISSION statement to create a row permission.

Creating column masks

A *column mask* specifies the rules for users to receive the masked values that are returned for the column. With the SECADM authority, you can use the CREATE MASK statement to create a column mask.

Related reference

Rules of row and column access control

The rules of row and column access control apply to both read and write operations on a table. The conditions that are specified in row permissions and column masks apply to both data retrieval operations and data change operations.

Explicit system privileges

You can explicitly grant privileges on systems.

SECADM administrative authority

The SECADM authority enables you to manage security-related objects in Db2 and control access to all database resources. It does not have any inherent privilege to access data stored in the objects, such as tables.

Column masks

A *column mask* is a database object that describes a specific column access control rule for a column. In the form of an SQL CASE expression, the rule specifies the condition under which a user, group, or role can receive the masked values that are returned for a column.

Stored in the system catalog, column masks can be created on all base tables except materialized query tables and maintained on an individual basis. The definition of each column mask may reference the user, group, or role in the search conditions in the CASE WHEN clause.

While multiple columns in a table may have column masks, only one column mask can be created for a single column. When column access control is activated for the table, the CASE expression in the column mask definition is applied to an output column to determine the masked values that are returned to an application. The application of column masks affects the final output only; it does not impact the operations, such as predicates and ordering, in an SQL statement. In addition, the application of column masks must not change the values in a row that is being inserted or updated in an INSERT, UPDATE, or MERGE statement.

Only an authorization ID or role with the SECADM or SYSADM authority can manage column masks. If the SEPARATE_SECURITY system parameter on panel DSNTIPP1 is set to YES during installation or migration, you must have the SECADM authority to create, alter, or drop column masks. If SEPARATE_SECURITY is set to NO, you must have the SECADM or SYSADM authority.

The application of enabled column masks does not interfere with the operations of other clauses within the statement such as the WHERE, GROUP BY, HAVING, SELECT DISTINCT, or ORDER BY. The rows that are returned in the final result table remain the same, except that the values in the resulting rows might have been masked by the column masks. As such, if the masked column also appears in an ORDER BY clause with a *sort-key* expression, the order is based on the original values of the column and the masked values in the final result table might not reflect that order. Similarly, the masked values might not reflect the uniqueness enforced by a SELECT DISTINCT statement or a COUNT (DISTINCT *expression*) function. If the masked column is embedded in an expression, the result of the expression might become different because the column mask is applied on the column before the expression evaluation can take place.

Related concepts

Row permission

A *row permission* is a database object that describes a specific row access control rule for a table. In the form of an SQL search condition, the rule specifies the conditions under which a user, group, or role can access the rows of data in the table.

Related tasks

Creating row permissions

A *row permission* specifies the conditions under which users can access a row. With the SECADM authority, you can use the CREATE PERMISSION statement to create a row permission.

Creating column masks

A *column mask* specifies the rules for users to receive the masked values that are returned for the column. With the SECADM authority, you can use the CREATE MASK statement to create a column mask.

Related reference

CREATE MASK statement (Db2 SQL)

Rules of row and column access control

The rules of row and column access control apply to both read and write operations on a table. The conditions that are specified in row permissions and column masks apply to both data retrieval operations and data change operations.

Explicit system privileges

You can explicitly grant privileges on systems.

SECADM administrative authority

The SECADM authority enables you to manage security-related objects in Db2 and control access to all database resources. It does not have any inherent privilege to access data stored in the objects, such as tables.

Rules of row and column access control

The rules of row and column access control apply to both read and write operations on a table. The conditions that are specified in row permissions and column masks apply to both data retrieval operations and data change operations.

GUPI

The following table shows an example of how row and column access control rules are applied depending on the types of data operations. Assume that tables T1 and T2 are activated for row and column access control and that both tables include columns C1 and C2.

Table 64. Rules and access types for row and column access control			
SQL statement	Row permission	Column mask (defined for column C1)	
SELECT SUBSTR(C1,8,4) FROM T1;	 If user-defined row permissions exist for the table, only the rows that satisfy the permissions are returned. If no user-defined row permissions exist for the table, the default row permission is applied and no row is returned. 	 The column mask is applied to column C1 that is referenced in the select list of the outermost SELECT clause. It does not interfere with the operations of other clauses within the statement, such as the WHERE, GROUP BY, HAVING, SELECT DISTINCT, or ORDER BY clauses. Some column mask restrictions may apply to the other clauses within the statement. The masked value that is determined by the evaluation of the CASE expression in the column mask is returned in place of the column value in the output row. If column C1 is embedded in an expression, the column mask is applied to the input column before the evaluation of the expression takes place. 	
	• If no user-defined row permissions exist for the table, the default row permission is applied and no row is returned.	 clauses within the statement, such as the WHERE, GROUP BY, HAVING, SELEC DISTINCT, or ORDER BY clauses. Some column mask restrictions may apply to to other clauses within the statement. The masked value that is determined by the evaluation of the CASE expression in the column mask is returned in place of the column value in the output row. If column C1 is embedded in an expression the column mask is applied to the input column before the evaluation of the evaluation of the expression takes place. 	

Table 64. Rules and access types for row and column access control (continued)		
SQL statement	Row permission	Column mask (defined for column C1)
INSERT INTO T1(C1, C2) VALUES('A', 'B');	 For each row to be inserted: If a user-defined row permission exists, the row can be inserted only when that row can be subsequently retrieved by the authorization ID of the INSERT statement. If the row cannot be inserted, the INSERT statement returns an error. If no user-defined row permissions exist for the table only the default row permission is applied and no row is inserted. The INSERT statement returns an error. The ENFORCED FOR ALL ACCESS clause ensures that users cannot insert data that they cannot read. 	
INSERT INTO T1(C1) SELECT SUBSTR(T2.C1, 8, 4) FROM T2 WHERE T2.C2 > 10;		• When the columns are used to derive the new values for an INSERT statement, the original column values, not the masked values, are used. If the columns have column masks, those column masks are applied to ensure the evaluation of the access control rules at run time masks the column to itself, not to a constant or an expression. This ensures that the masked values are the same as the original column values. If a column mask does not mask the column to itself, the new row is not inserted and an error is returned at run time.
		 For example, column T2.C1 is used to derive the value of a new row for INSERT. The column value of T2.C1, not the masked value, is used to derive the new value. Because column T2.C1 has a column mask, the column mask is applied to ensure the evaluation of the access control rule in the column mask masks column T2.C1 to itself, not to a constant or an expression. This ensures the masked value is the same as the original column value. If the column mask of T2.C1 does not mask column T2.C1 to itself, the new value cannot be used and an error is returned at run time. The column mask rules that apply to the new value for INSERT are the same as those for SELECT.

Table 64. Rules and access types for row and column access control (continued)			
SQL statement	Row permission	Column mask (defined for column C1)	
UPDATE T1 SET C2 = (SELECT SUBSTR(T2.C1. 8.	The following rules are applied in the order as shown:		
	1. Identify candidate rows for updates:		
4) FROM T2 WHERE T2.C2 > 10);	If a user-defined row permission exists, only the rows of the table that satisfy the row permission can be the candidate rows for UPDATE. If no user-defined row permissions exist for the table, only the default row permission is applied and no rows are updated.		
	2. If there are rows to be updated, for	each row to be updated:	
	 When the columns are used to destatement, the original column vathe columns have column masks, that the evaluation of the access itself, not to a constant or an expression of the same as the original column value column to itself, the new rvalue correturned at run time. 	rive the new values for an UPDATE lues, not the masked values, are used. If those column masks are applied to ensure control rules at run time masks the column to ression. This ensures the masked values are values. If a column mask does not mask the annot be used for the update and an error is	
	 For example, column T2.C1 is used to derive the new value for the up The column value of T2.C1, not the masked value, is used to derive th value. Because column T2.C1 has a column mask, the column mask is to ensure that the evaluation of the access control rule in the column masks column T2.C1 to itself, not to a constant or an expression. This that the masked value is the same as the original column value. If the mask of T2.C1 does not mask column T2.C1 to itself, the new value caused for the update and an error is returned at run time The column mask rules that apply to the new value for UPDATE are th as those for SELECT. If there are rows to be updated, for each row to be updated only that row can be subsequently retrieved by the authorization ID of the statement. If the row cannot be updated, the UPDATE statement retu error. The ENFORCED FOR ALL ACCESS clause ensures that users can update data that they cannot read. 		
MERGE	The row and column access control rul	es for the LIPDATE and INSERT operations	
	in the MERGE statement are the same statements.	as those for the UPDATE and INSERT	
DELETE	 If a user-defined row permission exists for the table, only the rows that satisfy the permission are the candidate rows for an DELETE statement. If no user-defined row permissions exist for the table, the default row permission is applied and no row can be deleted. 		

GUPI

Related concepts

Row permission

A *row permission* is a database object that describes a specific row access control rule for a table. In the form of an SQL search condition, the rule specifies the conditions under which a user, group, or role can access the rows of data in the table.

Column masks

A *column mask* is a database object that describes a specific column access control rule for a column. In the form of an SQL CASE expression, the rule specifies the condition under which a user, group, or role can receive the masked values that are returned for a column.

Related tasks

Creating row permissions

A *row permission* specifies the conditions under which users can access a row. With the SECADM authority, you can use the CREATE PERMISSION statement to create a row permission.

Creating column masks

A *column mask* specifies the rules for users to receive the masked values that are returned for the column. With the SECADM authority, you can use the CREATE MASK statement to create a column mask.

Using INSERT on tables with row access control

You can use the INSERT statement on tables that are activated for row access control.

Creating triggers for tables with row and column access control

With the required authority and privileges, you can create triggers for tables that are activated for row and access control.

Modifying column masks to reference UDFs

With the SECADM authority, you can modify column masks on tables that are activated for column access control.

Creating row permissions

A *row permission* specifies the conditions under which users can access a row. With the SECADM authority, you can use the CREATE PERMISSION statement to create a row permission.

Before you begin

If the SEPARATE_SECURITY system parameter on panel DSNTIPP1 is set to YES during installation or migration, you must have the SECADM authority to create a row permission. If SEPARATE_SECURITY is set to NO, you must have the SECADM or SYSADM authority.

About this task

Suppose that you are a data security administrator (SECADM) for a national health organization (NetHMO) and responsible for safeguarding sensitive patient information. You want to create a data privacy and security policy and implement it through row permissions on tables that are enabled with row access control. The permission definitions prescribe the conditions under which patients, physicians, pharmacists, or account administrators can only receive certain rows based on their roles or account authentication IDs.

Procedure

To create a row permission:

1. Issue the CREATE TABLE statement to create table HOSPITAL.PATIENT.

The HOSPITAL.PATIENT table contains columns for recording a patient's social security number (SSN), account authorization ID (USERID), name (NAME), address (ADDRESS), pharmacy (PHARMACY), account balance (ACCT_BALANCE), and doctor (PCP_ID), as shown below:

GUPI

GUPI

2. Issue the CREATE ROLE statements to create the following roles and determine the rules for each role to access the HOSPITAL.PATIENT table

The row access control rules specify the specific types of information that users in a specific role can access and the conditions under which the role can access the information.

GUPI

CREATE ROLE PCP; CREATE ROLE DRUG_RESEARCH; CREATE ROLE ACCOUNTING; CREATE ROLE MEMBERSHIP; CREATE ROLE PATIENT;

GUPI

Issue the CREATE PERMISSION statement to create row permissions that allow each role to access data in specific rows.

You can use the built-in function VERIFY_TRUSTED_CONTEXT_ROLE_FOR_USER to determine whether the user identified in special register SESSION_USER is associated with a particular ROLE that is specified as the input argument to the function.

In the following example, Role PATIENT is allowed to access his or her own row. Role PCP is allowed to access his or her patients' rows. Roles MEMBERSHIP, ACCOUNTING, and DRUG_RESEARCH are allowed to access all rows.

GUPI

```
CREATE PERMISSION NETHMO.ROW_ACCESS ON HOSPITAL.PATIENT

FOR ROWS WHERE (VERIFY_TRUSTED_CONTEXT_ROLE_FOR_USER(SESSION_USER,

'PATIENT') = 1 AND

HOSPITAL.PATIENT.USERID = SESSION_USER) OR

(VERIFY_TRUSTED_CONTEXT_ROLE_FOR_USER(SESSION_USER,

'PCP') = 1 AND

HOSPITAL.PATIENT.PCP_ID = SESSION_USER) OR

(VERIFY_TRUSTED_CONTEXT_ROLE_FOR_USER(SESSION_USER,

'MEMBERSHIP') = 1 OR

VERIFY_TRUSTED_CONTEXT_ROLE_FOR_USER(SESSION_USER,

'ACCOUNTING') = 1 OR

VERIFY_TRUSTED_CONTEXT_ROLE_FOR_USER(SESSION_USER,

'DRUG_RESEARCH') = 1)

ENFORCED FOR ALL ACCESS

ENABLE;
```

```
COMMIT;
```

GUPI

The definitions of the new row permissions are stored in the new catalog table SYSIBM.SYSCONTROLS.

4. Issue the ALTER TABLE statement with the ACTIVATE ROW ACCESS CONTROL clause to activate row access control for table HOSPITAL.PATIENT.

GUPI

ALTER TABLE HOSPITAL.PATIENT ACTIVATE ROW ACCESS CONTROL;

COMMIT;

GUPI

The ALTER TABLE serialization process takes place and invalidates all packages and dynamic cached statements that reference table HOSPITAL.PATIENT. The value 'R' in the new column SYSTABLES.CONTROL indicates that the table is activated for row access control.

Db2 also implicitly creates a default row permission which restricts all access from HOSPITAL.PATIENT. The default row permission definition is stored in the new catalog table SYSIBM.SYSCONTROLS.

Whenever table HOSPITAL.PATIENT is referenced in a data manipulation statement, all row permissions that have been created for it, including the default row permission, are implicitly applied by Db2 to control the rows in the table that are accessible. A row access control search condition is derived from the logical OR operators that connect the search condition in each row permission. This search condition acts as a filter to HOSPITAL.PATIENT before any user-specified operations, such as predicates, grouping, ordering. are processed.

If necessary, SECADM can deactivate row access control from table HOSPITAL.PATIENT by simply issuing the following ALTER TABLE statement:

GUPI

ALTER TABLE HOSPITAL.PATIENT DEACTIVATE ROW ACCESS CONTROL;

COMMIT;

GUPI

Db2 invalidates all packages and dynamic cached statements that reference HOSPITAL.PATIENT. Db2 reflects the removal of row access control by setting SYSTABLES.CONTROL to blank. This also means that table HOSPITAL.PATIENT does not have any access control and that users can retrieve data from all its rows.

Related concepts

Row permission

A *row permission* is a database object that describes a specific row access control rule for a table. In the form of an SQL search condition, the rule specifies the conditions under which a user, group, or role can access the rows of data in the table.

Column masks

A *column mask* is a database object that describes a specific column access control rule for a column. In the form of an SQL CASE expression, the rule specifies the condition under which a user, group, or role can receive the masked values that are returned for a column.

Related tasks

Creating column masks

A *column mask* specifies the rules for users to receive the masked values that are returned for the column. With the SECADM authority, you can use the CREATE MASK statement to create a column mask.

Using INSERT on tables with row access control

You can use the INSERT statement on tables that are activated for row access control.

Creating triggers for tables with row and column access control

With the required authority and privileges, you can create triggers for tables that are activated for row and access control.

Modifying column masks to reference UDFs

With the SECADM authority, you can modify column masks on tables that are activated for column access control.

Related reference

Rules of row and column access control

The rules of row and column access control apply to both read and write operations on a table. The conditions that are specified in row permissions and column masks apply to both data retrieval operations and data change operations.

Explicit system privileges You can explicitly grant privileges on systems.

SECADM administrative authority

The SECADM authority enables you to manage security-related objects in Db2 and control access to all database resources. It does not have any inherent privilege to access data stored in the objects, such as tables.

Creating column masks

A *column mask* specifies the rules for users to receive the masked values that are returned for the column. With the SECADM authority, you can use the CREATE MASK statement to create a column mask.

Before you begin

GUPI If the SEPARATE_SECURITY system parameter on panel DSNTIPP1 is set to YES during installation or migration, you must have the SECADM authority to create a column mask. If SEPARATE_SECURITY is set to NO, you must have the SECADM or SYSADM authority.

About this task

Suppose that you are a data security administrator (SECADM) for a national health organization (NetHMO) and responsible for safeguarding sensitive patient information. You want to create a data privacy and security policy and implement it through column masks on tables that are enabled with column access control. The mask definitions prescribe the conditions under which patients, physicians, pharmacists, or account administrators can only receive certain masked values from the column based on their roles or account authentication IDs.

Procedure

To create a column mask:

1. Issue the CREATE TABLE statement to create table HOSPITAL.PATIENT

The HOSPITAL.PATIENT table contains columns for recording a patient's social security number (SSN), account authorization ID (USERID), name (NAME), address (ADDRESS), pharmacy (PHARMACY), account balance (ACCT_BALANCE), and doctor (PCP_ID), as shown below:

```
CREATE TABLE HOSPITAL.PATIENT (
SSN CHAR(11),
USERID VARCHAR(18),
NAME VARCHAR(128),
ADDRESS VARCHAR(128),
PHARMACY VARCHAR(5000),
ACCT_BALANCE DECIMAL(12,2) WITH DEFAULT,
PCP_ID VARCHAR(18));
```

Issue the CREATE ROLE statements to create the following roles that access the HOSPITAL.PATIENT table.

CREATE ROLE PCP; CREATE ROLE DRUG_RESEARCH; CREATE ROLE ACCOUNTING; CREATE ROLE MEMBERSHIP; CREATE ROLE PATIENT; 3. Issue the CREATE MASK statement to create column masks that allow each role to receive certain masked values from specific columns.

You can use the built-in function VERIFY_TRUSTED_CONTEXT_ROLE_FOR_USER to determine whether the user identified in special register SESSION_USER is associated with a particular ROLE that is specified as the input argument to the function.

The following example shows how column mask SSN_MASK is created. Roles PATIENT and ACCOUNTING are allowed to receive column values from column SSN. Other roles that access the column will receive masked values.

```
CREATE MASK NETHMO.SSN_MASK ON HOSPITAL.PATIENT FOR
COLUMN SSN RETURN
CASE WHEN VERIFY_TRUSTED_CONTEXT_ROLE_FOR_USER(SESSION_USER,
'PATIENT') = 1 OR
VERIFY_TRUSTED_CONTEXT_ROLE_FOR_USER(SESSION_USER,
'ACCOUNTING') = 1
THEN SSN
ELSE CHAR('XXX-XX-') || SUBSTR(SSN,8,4)
END
ENABLE;
```

COMMIT;

You can issue the CREATE MASK statements to create column masks USERID_MASK, NAME_MASK, and ADDRESS_MASK. The definitions of all these column masks are stored in the new catalog table SYSIBM.SYSCONTROLS.

4. Use the ALTER TABLE statement with the ACTIVATE COLUMN ACCESS CONTROL clause to activate column access control for table HOSPITAL.PATIENT

ALTER TABLE HOSPITAL.PATIENT ACTIVATE COLUMN ACCESS CONTROL;

COMMIT;

The ALTER TABLE serialization process takes place and invalidates all packages and dynamic cached statements that reference table HOSPITAL.PATIENT. The value 'C' in the new column SYSTABLES.CONTROL indicates that the table is activated for column access control.

Whenever column SSN of table HOSPITAL.PATIENT is referenced in the outermost SELECT clause of a data manipulation statement, column mask SSN_MASK is implicitly applied by Db2 to control the masked values that are returned for it.

If necessary, SECADM can deactivate column access control from table HOSPITAL.PATIENT by simply issuing the following ALTER TABLE statement:

ALTER TABLE HOSPITAL.PATIENT DEACTIVATE COLUMN ACCESS CONTROL;

COMMIT;

Db2 invalidates all packages and dynamic cached statements that reference HOSPITAL.PATIENT. Db2 reflects the removal of column access control by setting SYSTABLES.CONTROL to blank.

Related concepts

Row permission

A *row permission* is a database object that describes a specific row access control rule for a table. In the form of an SQL search condition, the rule specifies the conditions under which a user, group, or role can access the rows of data in the table.

Column masks

A *column mask* is a database object that describes a specific column access control rule for a column. In the form of an SQL CASE expression, the rule specifies the condition under which a user, group, or role can receive the masked values that are returned for a column.

Related tasks

Creating row permissions

A *row permission* specifies the conditions under which users can access a row. With the SECADM authority, you can use the CREATE PERMISSION statement to create a row permission.

Using INSERT on tables with row access control

You can use the INSERT statement on tables that are activated for row access control.

Creating triggers for tables with row and column access control

With the required authority and privileges, you can create triggers for tables that are activated for row and access control.

Modifying column masks to reference UDFs

With the SECADM authority, you can modify column masks on tables that are activated for column access control.

Related reference

Rules of row and column access control

The rules of row and column access control apply to both read and write operations on a table. The conditions that are specified in row permissions and column masks apply to both data retrieval operations and data change operations.

Explicit system privileges

You can explicitly grant privileges on systems.

SECADM administrative authority

The SECADM authority enables you to manage security-related objects in Db2 and control access to all database resources. It does not have any inherent privilege to access data stored in the objects, such as tables.

Modifying column masks to reference UDFs

With the SECADM authority, you can modify column masks on tables that are activated for column access control.

Before you begin

GUPI If the SEPARATE_SECURITY system parameter on panel DSNTIPP1 is set to YES during installation or migration, you must have the SECADM authority to modify a column mask. If SEPARATE_SECURITY is set to NO, you must have the SECADM or SYSADM authority.

About this task

Suppose that table HOSPITAL.PATIENT contains columns to record a patient's social security number (SSN), account authorization ID (USERID), name (NAME), address (ADDRESS), pharmacy (PHARMCY), account balance (ACCT_BALANCE), and doctor (PCD_ID). The table is activated for column access control.

Also, suppose that database developer Paul has created a new powerful accounting application NetHMLAccountingUDF (an external scalar user-defined function). You want to modify column mask ACCT_BALANCE_MASK for column HOSPITAL.PATIENT.ACCT_BALANCE to include NetHMLAccountingUDF.

Procedure

To modify column mask ACCT_BALANCE_MASK to include NetHMLAccountingUDF:

1. Make sure that all the operations in the new UDF are secure.

Only secure UDFs can be invoked in a column mask. The SECURED attribute is required if the userdefined function is referenced in the definition of a row permission or column mask. This is because the user-defined function may access sensitive data. The SECURED attribute is also required for a user-defined function that is invoked in an SQL statement when the function arguments reference columns that are activated with column access control. Make sure that all the operations inside the new application NetHMLAccountingUDF are actually secure. Then, you can issue the following GRANT CREATE_SECURE_OBJECT statement to allow userid PAUL the privilege for creating a secure UDF:

```
GRANT CREATE_SECURE_OBJECT TO PAUL;
```

COMMIT;

Db2 records the grant in SYSUSERAUTH: GRANTOR = GRANTORID, GRANTEE = PAUL, AUTHHOWGOT = E, and CREATESECUREAUTH = Y. This means that authid GRANTORID has used the SECADM authority (AUTHHOWGOT = E) to grant userid PAUL the CREATE_SECURE_OBJECT privilege.

With the CREATE_SECURE_OBJECT privilege, Paul issues the following ALTER FUNCTION statement to secure NetHMLAccountingUDF:

ALTER FUNCTION NETHMOACCOUNTINGUDF(ACCT_BALANCE) SECURED;

COMMIT;

Db2 sets the new column in catalog SYSROUTINES.SECURE to Y and invalidates all packages and dynamic cached statements that reference NetHMOAccountingUDF(ACCT_BALANCE).

2. After the UDF has been altered to be secure, revoke the CREATE_SECURE_OBJECT privilege from userid PAUL by issuing the following REVOKE CREATE_SECURE_OBJECT statement:

REVOKE CREATE_SECURE_OBJECT FROM PAUL;

COMMIT;

Db2 completes the privilege removal by deleting the row from SYSUSERAUTH with GRANTOR = GRANTORID, GRANTEE = PAUL, AUTHHOWGOT = E, and CREATESECUREAUTH = Y.

3. Drop the existing column mask ACCT_BALANCE_MASK for column ACCT_BALANCE

You can issue the DROP MASK statement to remove the existing column mask, but do not follow it with the COMMIT statement. This will prevent any ongoing transactions from accessing table HOSPITAL.PATIENT before you can put a new column mask in place.

DROP MASK ACCT_BALANCE_MASK;

Db2 invalidates all packages and dynamic cached statements that reference table HOSPITAL.PATIENT. It also deletes the row for ACCT_BALANCE_MASK in the catalog table SYSIBM.SYSCONTROLS. Since there isn't a COMMIT statement immediately after the DROP MASK statement, Db2 keeps possessing the lock on HOSPITAL.PATIENT and doesn't commit the work it has done for the DROP MASK statement. Any transactions that try to access HOSPITAL.PATIENT may be timed out.

4. Create a new column mask ACCT_BALANCE_MASK for column ACCT_BALANCE

You can issue the CREATE MASK statement to create a new column mask and follow it immediately with the COMMIT statement. This will enable Db2 to commit all the work it has done so far for HOSPITAL.PATIENT and allow other transactions to access HOSPITAL.PATIENT.

```
CREATE MASK NETHMO.ACCT_BALANCE_MASK ON HOSPITAL.PATIENT FOR
COLUMN ACCT_BALANCE RETURN
CASE WHEN VERIFY_TRUSTED_CONTEXT_ROLE_FOR_USER
(SESSION_USER,'ACCOUNTING') = 1
THEN NETHMOACCOUNTINGUDF(ACCT_BALANCE)
ELSE 0.00
END
ENABLE;
```

```
COMMIT;
```

Db2 invalidates all packages and dynamic cached statements that reference table HOSPITAL.PATIENT and inserts the new ACCT_BALANCE_MASK definition into the catalog table SYSIBM.SYSCONTROLS. It also records the dependency on NetHMOAccountingUDF in SYSIBM.SYSDEPENDENCIES for ACCT_BALANCE_MASK.

The COMMIT statement immediately after the CREATE MASK statement ensures that Db2 commits all the work it has done so far on HOSPITAL.PATIENT and releases the lock from the table. This allows other transactions to access the same table without being timed out.

Using INSERT on tables with row access control

You can use the INSERT statement on tables that are activated for row access control.

About this task

Suppose that you are responsible for managing patient memberships and you are associated with role MEMBERSHIP that is already created for table HOSPITAL.PATIENT. Table HOSPITAL.PATIENT is also activated for row access control, and Role MEMBERSHIP is allowed to access, create, and retrieve rows in the table.

Suppose that table HOSPITAL.PATIENT contains columns to record a patient's social security number (SSN), account authorization ID (USERID), name (NAME), address (ADDRESS), pharmacy (PHARMCY), account balance (ACCT_BALANCE), and doctor (PCD_ID). You want to add a new row for a new patient Bob.

Procedure

GUPI To add a row to a table that is enforced with row access control:

1. Ensure that role MEMBERSHIP is allowed to access, insert, and update rows when row permission rules are set for table HOSPITAL.PATIENT by the SECADM authority.

```
CREATE PERMISSION NETHMO.ROW_ACCESS ON HOSPITAL.PATIENT
FOR ROWS WHERE (VERIFY_TRUSTED_CONTEXT_ROLE_FOR_USER(SESSION_USER,
'MEMBERSHIP') = 1 )
ENFORCED FOR ALL ACCESS
ENABLE;
```

COMMIT;

2. Issue the INSERT statement to insert a new row for patient Bob:

```
INSERT INTO HOSPITAL.PATIENT(SSN, USERID, NAME, ADDRESS)
VALUES('123-45-6789','BobXYZ100','Bob','123 Some St.');
```

COMMIT;

3. Verify that Bob was successfully added by issuing the following SELECT statement:

```
SELECT * FROM HOSPITAL.PATIENT WHERE SSN = '123-45-6789';
```

COMMIT;

The following result is returned and shows that a new row for Bob was successfully added to the table.

SSNUSERIDNAMEADDRESSPHARMACYACCT_BALANCEPCP_ID123-45-6789BobXYZ100Bob123 Some St.?0.00?DSNT400ISQLCODE = 000, SUCCESSFUL EXECUTION
SUCCESSFUL RETRIEVAL OF 1 ROW(S)SUCCESSFUL RETRIEVAL OF 1 ROW(S)SUCCESSFUL RETRIEVAL OF 1 ROW(S)

GUPI

Creating triggers for tables with row and column access control

With the required authority and privileges, you can create triggers for tables that are activated for row and access control.

Before you begin

If the SEPARATE_SECURITY system parameter on panel DSNTIPP1 is set to YES during installation or migration, you must have the SECADM authority to create triggers for tables that are activated with row and column access control. If SEPARATE_SECURITY is set to NO, you must have the SECADM or SYSADM authority.

About this task

Suppose that table HOSPITAL.PATIENT is activated for row and column access control. The table contains columns to record a patient's social security number (SSN), account authorization ID (USERID), name (NAME), address (ADDRESS), pharmacy (PHARMCY), account balance (ACCT_BALANCE), and doctor (PCD_ID). Paul, a database developer, needs to create a new AFTER UPDATE trigger for HOSPITAL.PATIENT to monitor the history of the ACCT_BALANCE column.

Procedure

To create a trigger for a table that is enforced with row and access control:

1. Make sure that all operations on the transition variables and transition tables inside the new trigger body are secure.

Only secure triggers can be defined on tables that are already enforced with row and column access control. The SECURED attribute is required for a trigger when the associated table is row or column access control enforced or the associated view whose underlying table is enforced with row or column access control. If a trigger exists but is not secure, row or column access control cannot be activated for the associated table.

Make sure that all operations on the transition variables and transition tables inside the new trigger body are actually secure. Then, you can issue the following GRANT CREATE_SECURE_OBJECT statement to allow userid PAUL the privilege for creating secure triggers for table HOSPITAL.PATIENT:

GUPI

```
GRANT CREATE_SECURE_OBJECT TO PAUL;
COMMIT;
```

GUPI

Db2 records the grant in SYSUSERAUTH: GRANTOR = GRANTORID, GRANTEE = PAUL, AUTHHOWGOT = E, and CREATESECUREAUTH = Y. This means that authid GRANTORID has used the SECADM authority (AUTHHOWGOT = E) to grant userid PAUL the CREATE_SECURE_OBJECT privilege.

Create a new trigger for table HOSPITAL.PATIENT

With the CREATE_SECURE_OBJECT privilege, Paul can create a secure NETHMO_ACCT_BALANCE_TRIGGER by issuing the following CREATE TRIGGER statement:

GUPI

```
CREATE TRIGGER NETHMO_ACCT_BALANCE_TRIGGER NO CASCADE

AFTER UPDATE OF ACCT_BALANCE ON HOSPITAL.PATIENT SECURED

REFERENCING OLD AS 0 NEW AS N

FOR EACH ROW MODE DB2SQL

BEGIN ATOMIC

INSERT INTO ACCT_HISTORY

(SSN, BEFORE_BALANCE, AFTER_BALANCE, WHEN, BY_WHO)

VALUES(0.SSN, 0.ACCT_BALANCE, N.ACCT_BALANCE,

CURRENT TIMESTAMP, SESSION_USER);

END!
```

COMMIT!

GUPI

Db2 inserts a new row into SYSIBM.SYSTRIGGERS with SYSTRIGGERS.SECURE = 'Y'. Db2 completes other catalog table updates for the trigger creation.

3. After trigger NETHMO_ACCT_BALANCE_TRIGGER is created, revoke the CREATE_SECURE_OBJECT privilege from userid PAUL by issuing the following REVOKE CREATE_SECURE_OBJECT statement:

GUPI

REVOKE CREATE_SECURE_OBJECT FROM PAUL;

COMMIT;

GUPI

Db2 completes the privilege removal by deleting the row with GRANTOR = GRANTORID, GRANTEE = PAUL, AUTHHOWGOT = E, and CREATESECUREAUTH = Y from SYSUSERAUTH. This means that authid GRANTORID has used the SECADM authority (AUTHHOWGOT = E) to revoke the CREATE_SECURE_OBJECT privilege from userid PAUL.

Chapter 5. Managing access through trusted contexts

You can use trusted contexts to manage access to your Db2 subsystems, which helps you improve data security.

You can use trusted connections within a trusted context. When you do this, you can reuse the authorization and switch users of the connection without the database server needing to authenticate the IDs. If you set field 1 (RESTART or DEFER) to DEFER and set field 2 (objects to restart or defer) to ALL in installation panel DSNTIPS, you cannot use trusted connections.

Trusted contexts

A *trusted context* is an independent database entity that you can define based on a system authorization ID and connection trust attributes.

The trust attributes specify a set of characteristics about a specific connection. These attributes include the IP address, domain name, or SERVAUTH security zone name of a remote client and the job or task name of a local client.

A trusted context allows for the definition of a unique set of interactions between Db2 and the external entity, including the following abilities:

- The ability for the external entity to use an established database connection with a different user without the need to authenticate that user at the Db2 server. This ability eliminates the need to manage end-user passwords by the external entity. Also, a database administrator can assume the identity of other users and perform actions on their behalf.
- The ability for a Db2 authorization ID to acquire one or more privileges within a trusted context that are not available to it outside of that trusted context. This is accomplished by associating a role with the trusted context.

The following client applications provide support for the trusted context:

- The Db2 Universal Java Driver introduces new APIs for establishing trusted connections and switching users of a trusted connection.
- The Db2 CLI/ODBC Driver introduces new keywords for connecting APIs to establish trusted connections and switch users of a trusted connection.
- The WebSphere Application Server 6.0 exploits the trusted context support through its "propagate client identity" property.

Related concepts

Trusted connections

A *trusted connection* is a database connection that is established when the connection attributes match those of a trusted context that is defined at the server. A trusted connection can be established locally or at a remote location.

Roles in a trusted context

A *role* is a database entity that groups one or more privileges together in a trusted context. System administrators can use roles to control access to enterprise objects in a way that parallels the structure of the enterprise.

Related tasks

Defining trusted contexts

Before you can create a trusted connection, you must define a trusted context by using a system authorization ID and connection trust attributes.

Creating local trusted connections

You can establish a trusted connection to a local Db2 subsystem by using RRSAF, CAF, or the DSN command processor under TSO and DB2I.

Establishing remote trusted connections by Db2 for z/OS requesters

A Db2 for z/OS requester can establish a trusted connection to a remote location by setting up the new TRUSTED column in the SYSIBM.LOCATIONS table.

Establishing remote trusted connections to Db2 for z/OS servers

When the Db2 for z/OS server receives a remote request to establish a trusted connection, Db2 checks to see if an authentication token accompanies the request.

Related reference

Establishing plan and package ownership in a trusted context

You can issue the BIND and REBIND commands in a trusted context with the ROLE AS OBJECT OWNER clause to specify the ownership of a plan or package. In this trusted context, you can specify only a role, not an authorization ID, as the OWNER of a plan or package.

Ownership of objects within a trusted context

You can simplify the administration of authorization by having roles as object owners. In addition, object ownership carries with it a set of related privileges on the object; you can prevent users from obtaining implicit privileges from object ownership by making roles object owners.

Trusted connections

A *trusted connection* is a database connection that is established when the connection attributes match those of a trusted context that is defined at the server. A trusted connection can be established locally or at a remote location.

A trusted context allows you to establish a trusted relationship between Db2 and an external entity, such as a middleware server. Db2 evaluates a series of trust attributes to determine if a specific context is to be trusted. Currently, the only attribute that Db2 considers is the database connection. The relationship between a connection and a trusted context is established when the connection to the server is first created, and that relationship remains as long as that connection exists.

Related concepts

Trusted contexts

A *trusted context* is an independent database entity that you can define based on a system authorization ID and connection trust attributes.

Roles in a trusted context

A *role* is a database entity that groups one or more privileges together in a trusted context. System administrators can use roles to control access to enterprise objects in a way that parallels the structure of the enterprise.

Related tasks

Defining trusted contexts

Before you can create a trusted connection, you must define a trusted context by using a system authorization ID and connection trust attributes.

Creating local trusted connections

You can establish a trusted connection to a local Db2 subsystem by using RRSAF, CAF, or the DSN command processor under TSO and DB2I.

Establishing remote trusted connections by Db2 for z/OS requesters

A Db2 for z/OS requester can establish a trusted connection to a remote location by setting up the new TRUSTED column in the SYSIBM.LOCATIONS table.

Establishing remote trusted connections to Db2 for z/OS servers
When the Db2 for z/OS server receives a remote request to establish a trusted connection, Db2 checks to see if an authentication token accompanies the request.

Defining trusted contexts

Before you can create a trusted connection, you must define a trusted context by using a system authorization ID and connection trust attributes.

About this task

A system authorization ID is the Db2 primary authorization ID that is used to establish the trusted connection. For local connections, the system authorization ID is derived as shown in the following table.

Table 65. System authorization ID for local connections		
Source	System authorization ID	
Started task (RRSAF)	USER parameter on JOB statement or RACF USER	
TSO	TSO logon ID	
ВАТСН	H USER parameter on JOB statement	

For remote connections, the system authorization ID is derived from the system user ID that is provided by an external entity, such as a middleware server.

The connection trust attributes identify a set of characteristics about the specific connection. The connection trust attributes are required for the connection to be considered a trusted connection. For a local connection, the connection trust attribute is the job or started task name. For a remote connection, the connection trust attribute is the client's IP address, domain name, or SERVAUTH security zone name. The connection trust attributes are as follows:

ADDRESS

Specifies the client's IP address or domain name, used by the connection to communicate with Db2. The protocol must be TCP/IP.

SERVAUTH

Specifies the name of a resource in the RACF SERVAUTH class. This resource is the network access security zone name that contains the IP address of the connection to communicate with Db2.

ENCRYPTION

Specifies the minimum level of encryption of the data stream (network encryption) for the connection. Supported values are as follows:

- NONE No encryption. This is the default.
- LOW DRDA data stream encryption.
- HIGH Secure Socket Layer (SSL) encryption.

JOBNAME

Specifies the local z/OS started task or job name. The value of JOBNAME depends on the source of the address space, as shown in the following table.

Table 66. JOBNAME for local connections			
Source	JOBNAME		
Started task (RRSAF)	Job or started task name		
TSO	TSO logon ID		
ВАТСН	Job name on JOB statement		

The JOBNAME attribute cannot be specified with the ADDRESS, SERVAUTH, or ENCRYPTION attributes.

Related concepts

Trusted contexts

A *trusted context* is an independent database entity that you can define based on a system authorization ID and connection trust attributes.

Trusted connections

A *trusted connection* is a database connection that is established when the connection attributes match those of a trusted context that is defined at the server. A trusted connection can be established locally or at a remote location.

Roles in a trusted context

A *role* is a database entity that groups one or more privileges together in a trusted context. System administrators can use roles to control access to enterprise objects in a way that parallels the structure of the enterprise.

Related tasks

Creating local trusted connections

You can establish a trusted connection to a local Db2 subsystem by using RRSAF, CAF, or the DSN command processor under TSO and DB2I.

Establishing remote trusted connections by Db2 for z/OS requesters A Db2 for z/OS requester can establish a trusted connection to a remote location by setting up the new TRUSTED column in the SYSIBM.LOCATIONS table.

Establishing remote trusted connections to Db2 for z/OS servers When the Db2 for z/OS server receives a remote request to establish a trusted connection, Db2 checks to see if an authentication token accompanies the request.

Creating local trusted connections

You can establish a trusted connection to a local Db2 subsystem by using RRSAF, CAF, or the DSN command processor under TSO and DB2I.

About this task

When you attempt to create a local trusted connection, Db2 searches for a trusted context that matches the primary authorization ID and the job or started task name that you supply. If Db2 finds a matching trusted context, Db2 checks if the DEFAULT SECURITY LABEL attribute is defined in the trusted context.

If the DEFAULT SECURITY LABEL attribute is defined with a security label, Db2 verifies the security label with RACF. This security label is used for multilevel security verification for the system authorization ID. If verification is successful, the connection is established as trusted. If the verification is not successful, the connection without any additional privileges.

In addition, the Db2 online utilities can run in a trusted connection if a matching trusted context is defined, if the primary authorization ID matches the SYSTEM AUTHID value of the trusted context, and if the job name matches the JOBNAME attribute defined for the trusted context.

Related concepts

Trusted contexts

A *trusted context* is an independent database entity that you can define based on a system authorization ID and connection trust attributes.

Trusted connections

A *trusted connection* is a database connection that is established when the connection attributes match those of a trusted context that is defined at the server. A trusted connection can be established locally or at a remote location.

Roles in a trusted context

A *role* is a database entity that groups one or more privileges together in a trusted context. System administrators can use roles to control access to enterprise objects in a way that parallels the structure of the enterprise.

Related tasks

Defining trusted contexts

Before you can create a trusted connection, you must define a trusted context by using a system authorization ID and connection trust attributes.

Establishing remote trusted connections by Db2 for z/OS requesters

A Db2 for z/OS requester can establish a trusted connection to a remote location by setting up the new TRUSTED column in the SYSIBM.LOCATIONS table.

Establishing remote trusted connections to Db2 for z/OS servers When the Db2 for z/OS server receives a remote request to establish a trusted connection, Db2 checks to see if an authentication token accompanies the request.

Establishing remote trusted connections by Db2 for z/OS requesters

A Db2 for z/OS requester can establish a trusted connection to a remote location by setting up the new TRUSTED column in the SYSIBM.LOCATIONS table.

About this task

How Db2 obtains the system authorization ID to establish the trusted connection depends on the value of the SECURITY_OUT option in the SYSIBM.IPNAMES table. The SECURITY_OUT option in the SYSIBM.IPNAMES table must be 'E', 'P', or 'R'.

When the z/OS requester receives an SQL CONNECT with or without the USER and USING clauses to a remote location or if an application references a remote table or procedure, Db2 looks at the SYSIBM.LOCATIONS table to find a matching row. If Db2 finds a matching row, it checks the TRUSTED column. If the value of TRUSTED column is set to 'Y', Db2 looks at the SYSIBM.IPNAMES table. The values in the SECURITY_OUT column and USERNAMES column are used to determine the system authorization ID as shown in the following table.

IPNAMES.SECURI TY_OUT values	IPNAMES.USERN AMES value	Result
'P' or 'E'	'S'	The system authorization ID credentials that are used to establish the trusted connection are obtained from the row in the SYSIBM.USERNAMES table with TYPE 'S'.
		Db2 sends the user switch request on behalf of the primary authorization ID without authentication under two conditions. First, the system authorization ID value in the AUTHID column is different from the primary authorization ID. Second, a trusted connection is successfully established.
'P' or 'E'	'O'	If a row with TYPE 'S' is defined in the SYSIBM.USERNAMES table, the system authorization ID credentials that are used to establish the trusted connection are obtained from the row.
		After successfully establishing the trusted connection, Db2 obtains the translated authorization ID information for the primary authorization ID from the row in the SYSIBM.USERNAMES table with TYPE 'O'. Db2 sends the user switch request on behalf of the primary authorization ID with authentication.

IPNAMES.SECURI TY_OUT values	IPNAMES.USERN AMES value	Result
'R'	blank	If a row with TYPE 'S' is not defined in the SYSIBM.USERNAMES table, Db2 obtains the system authorization ID information that is used to establish the trusted connection from the row in the SYSIBM.USERNAMES table with TYPE 'O'.
'R'	'S'	The primary authorization ID is used as the system authorization ID to establish the trusted connection.
'R'	'O'	The system authorization ID that is used to establish the trusted connection is obtained from the row in the SYSIBM.USERNAMES table with TYPE='S'.
		After establishing the trusted connection successfully, Db2 sends the user switch request on behalf of the primary authorization ID without authentication.

If the IPNAMES.SECURITY_OUT option is not correctly set up, Db2 returns an error.

For more information about the supported configurations for IPNAMES.SECURITY_OUT and related column values, see <u>"SYSIBM.IPNAMES columns" on page 203</u>.

Related concepts

Trusted contexts

A *trusted context* is an independent database entity that you can define based on a system authorization ID and connection trust attributes.

Trusted connections

A *trusted connection* is a database connection that is established when the connection attributes match those of a trusted context that is defined at the server. A trusted connection can be established locally or at a remote location.

Roles in a trusted context

A *role* is a database entity that groups one or more privileges together in a trusted context. System administrators can use roles to control access to enterprise objects in a way that parallels the structure of the enterprise.

Related tasks

Defining trusted contexts

Before you can create a trusted connection, you must define a trusted context by using a system authorization ID and connection trust attributes.

Creating local trusted connections

You can establish a trusted connection to a local Db2 subsystem by using RRSAF, CAF, or the DSN command processor under TSO and DB2I.

Establishing remote trusted connections to Db2 for z/OS servers

When the Db2 for z/OS server receives a remote request to establish a trusted connection, Db2 checks to see if an authentication token accompanies the request.

Related reference

IPNAMES catalog table (Db2 SQL) SYSIBM.IPNAMES columns The SYSIBM.IPNAMES table is used only for outbound requests that use TCP/IP protocols.

Establishing remote trusted connections to Db2 for z/OS servers

When the Db2 for z/OS server receives a remote request to establish a trusted connection, Db2 checks to see if an authentication token accompanies the request.

About this task

The authentication token can be a password, a RACF passticket, or a Kerberos ticket. The requester goes through the standard authorization processing at the server. If the authorization is successful, Db2 invokes the connection exit routine, which associates the primary authorization ID, possibly one or more secondary authorization IDs, and an SQL ID with the remote request. Db2 searches for a matching trusted context. If Db2 finds a matching trusted context, it validates the following attributes:

- If the SERVAUTH attribute is defined for the identified trusted context and TCP/IP provides a RACF SERVAUTH profile name to Db2 during the establishment of the connection, Db2 matches the SERVAUTH profile name with the SERVAUTH attribute value.
- If the SERVAUTH attribute is not defined or the SERVAUTH name does not match the SERVAUTH that is defined for the identified trusted context, Db2 matches the remote client's TCP/IP address with the ADDRESS attribute that is defined for the identified trusted context.
- If the ENCRYPTION attribute is defined, Db2 validates whether the connection is using the proper encryption as specified in the value of the ENCRYPTION attribute.
- If the DEFAULT SECURITY LABEL attribute is defined for the system authorization ID, Db2 verifies the security label with RACF. This security label is used for verifying multilevel security for the system authorization ID. However, if the system authorization ID is also in the ALLOW USER clause with SECURITY LABEL, then that one is used.

If the validation is successful, Db2 establishes the connection as trusted. If the validation is not successful, the connection is established as a normal connection without any additional privileges, Db2 returns a warning, and SQLWARN8 is set.

Related concepts

Trusted contexts

A *trusted context* is an independent database entity that you can define based on a system authorization ID and connection trust attributes.

Trusted connections

A *trusted connection* is a database connection that is established when the connection attributes match those of a trusted context that is defined at the server. A trusted connection can be established locally or at a remote location.

Roles in a trusted context

A *role* is a database entity that groups one or more privileges together in a trusted context. System administrators can use roles to control access to enterprise objects in a way that parallels the structure of the enterprise.

Related tasks

Defining trusted contexts

Before you can create a trusted connection, you must define a trusted context by using a system authorization ID and connection trust attributes.

Creating local trusted connections

You can establish a trusted connection to a local Db2 subsystem by using RRSAF, CAF, or the DSN command processor under TSO and DB2I.

Establishing remote trusted connections by Db2 for z/OS requesters

A Db2 for z/OS requester can establish a trusted connection to a remote location by setting up the new TRUSTED column in the SYSIBM.LOCATIONS table.

Switching users of a trusted connection

When a trusted connection is established, Db2 enables the trusted connection to be reused by a different user on a transaction boundary.

You can reuse a trusted connection at a local Db2 subsystem by using RRSAF, the DSN command processor under TSO, DB2I, and the SQL CONNECT statement with the USER and USING clauses. To reuse the trusted connection, you must add the specific user to the trusted context. If you specify 'PUBLIC' as the user, Db2 allows the trusted connection to be used by any authorization ID; the trusted connection can be used by a different user with or without authentication. However, you can require authentication by specifying the WITH AUTHENTICATION clause.

You can use RRSAF, the DSN command processor under TSO, and DB2I to switch to a new user on a trusted connection without authentication. If authentication is required, you can use the SQL CONNECT statement with the USER and USING clauses. The SQL CONNECT semantics prevent the use of CONNECT TO with the USER and USING clauses to switch authorization IDs on a remote connection.

Related tasks

Enabling users to perform actions on behalf of others Within a trusted context, you can allow users to perform actions on objects on behalf of others.

Performing tasks on objects for other users

If you have DBADM authority, you can assume the identity of other users within a trusted context and perform tasks on their behalf.

Reusing a local trusted connection through the DSN command processor and DB2I

You can use the DSN command processor and DB2I to switch the user on a trusted connection if the DSN ASUSER option is specified.

About this task

Db2 establishes a trusted connection if the primary authorization ID and job name match a trusted context that is defined in Db2. The user ID that is specified for the ASUSER option goes through the standard authorization processing. If the user ID is authorized, Db2 runs the connection exit routine to associate the primary and secondary IDs.

Db2 then searches to see if the primary authorization ID is allowed to use the trusted connection without authentication. If the primary authorization ID is allowed to use the trusted connection without authentication, Db2 determines if the SECURITY LABEL attribute is defined in the trusted context for the user either explicitly or implicitly. If the SECURITY LABEL attribute is defined with a security label, Db2 verifies the security label with RACF. If the verification of the security label is successful, the trusted connection is established and used by the user ID that is specified for the ASUSER option. Db2 uses the security label for multilevel security verification for the user.

If the primary authorization ID that is associated with the user ID that is specified for the ASUSER option is not allowed or requires authentication information, the connection request fails. If the security label verification is not successful, the connection request fails.

Related tasks

Reusing a remote trusted connection by Db2 for z/OS requesters After establishing a trusted connection with a system authorization ID, the Db2 for z/OS requester automatically switches the user on the connection to the primary authorization ID on the remote trusted connection.

Reusing a remote trusted connection through Db2 for z/OS servers

The Db2 for z/OS server performs a sequence of tasks when it receives a request to switch users on a trusted connection.

Reusing a local trusted connection through RRSAF

If you use Resource Recovery Services Attachment Facility (RRSAF) to switch to a new user on a trusted connection, Db2 obtains the primary authorization ID and runs the sign-on exit routine.

Reusing a local trusted connection through the SQL CONNECT statement You can switch users on a trusted connection by using the SQL CONNECT statement with the USER and USING clauses.

Reusing a remote trusted connection by Db2 for z/OS requesters

After establishing a trusted connection with a system authorization ID, the Db2 for z/OS requester automatically switches the user on the connection to the primary authorization ID on the remote trusted connection.

About this task

The Db2 for z/OS requester reuses a remote trusted connection in the following scenarios:

- The system authorization ID is different from the primary authorization ID that is associated with the application user.
- The system authorization ID is different from the authorization ID that is specified in the SQL CONNECT statement with the USER and USING clauses.
- Outbound translation is required for the primary authorization ID.

Related tasks

Reusing a local trusted connection through the DSN command processor and DB2I You can use the DSN command processor and DB2I to switch the user on a trusted connection if the DSN ASUSER option is specified.

Reusing a remote trusted connection through Db2 for z/OS servers The Db2 for z/OS server performs a sequence of tasks when it receives a request to switch users on a trusted connection.

Reusing a local trusted connection through RRSAF

If you use Resource Recovery Services Attachment Facility (RRSAF) to switch to a new user on a trusted connection, Db2 obtains the primary authorization ID and runs the sign-on exit routine.

Reusing a local trusted connection through the SQL CONNECT statement You can switch users on a trusted connection by using the SQL CONNECT statement with the USER and USING clauses.

Reusing a remote trusted connection through Db2 for z/OS servers

The Db2 for z/OS server performs a sequence of tasks when it receives a request to switch users on a trusted connection.

About this task

The Db2 z/OS server performs these tasks in the following sequence:

- 1. Db2, on successful authorization, invokes the connection exit routine. The invocation associates the primary authorization ID, possibly one or more secondary authorization IDs, and an SQL ID with the remote request. This new set of IDs replaces the previous set of IDs that was associated with the request.
- 2. Db2 determines if the primary authorization ID is allowed to use the trusted connection. If the WITH AUTHENTICATION clause is specified for the user, Db2 requires an authentication token for the user. The authentication token can be a password, a RACF passticket, or a Kerberos ticket.

3. Assuming that the primary authorization ID is allowed, Db2 determines the trusted context for any SECURITY LABEL definition. If a specific SECURITY LABEL is defined for this user, it becomes the SECURITY LABEL for this user. If no specific SECURITY LABEL is defined for this user but a DEFAULT SECURITY LABEL is defined for the trusted context, Db2 verifies the validity of this SECURITY LABEL for this user through RACF by issuing the RACROUTE VERIFY request.

If the primary authorization ID is allowed, Db2 performs a connection initialization. This results in an application environment that truly mimics the environment that is initialized if the new user establishes the connection in the normal Db2 manner. For example, any open cursor is closed, and temporary table information is dropped.

4. If the primary authorization ID is not allowed to use the trusted connection or if SECURITY LABEL verification fails, the connection is returned to an unconnected state. The only operation that is allowed is to establish a valid authorization ID to be associated with the trusted connection. Until a valid authorization is established, if any SQL statement is issued, an error (SQLCODE -900) is returned.

Related tasks

Reusing a local trusted connection through the DSN command processor and DB2I You can use the DSN command processor and DB2I to switch the user on a trusted connection if the DSN ASUSER option is specified.

Reusing a remote trusted connection by Db2 for z/OS requesters After establishing a trusted connection with a system authorization ID, the Db2 for z/OS requester automatically switches the user on the connection to the primary authorization ID on the remote trusted connection.

Reusing a local trusted connection through RRSAF

If you use Resource Recovery Services Attachment Facility (RRSAF) to switch to a new user on a trusted connection, Db2 obtains the primary authorization ID and runs the sign-on exit routine.

Reusing a local trusted connection through the SQL CONNECT statement You can switch users on a trusted connection by using the SQL CONNECT statement with the USER and USING clauses.

Reusing a local trusted connection through RRSAF

If you use Resource Recovery Services Attachment Facility (RRSAF) to switch to a new user on a trusted connection, Db2 obtains the primary authorization ID and runs the sign-on exit routine.

About this task

Db2 searches to determine if the primary authorization ID is allowed to use the trusted connection without authentication. If the primary authorization ID is allowed, Db2 determines if SECURITY LABEL is explicitly or implicitly defined in the trusted context for the user. If SECURITY LABEL is defined, Db2 verifies the SECURITY LABEL with RACF by using the RACROUTE VERIFY request. If the SECURITY LABEL verification is successful, the trusted connection is used by the new user.

If the primary authorization ID is not allowed to use the trusted connection without authentication, Db2 returns the connection to an unconnected state. The only action that you can take is to try running the sign-on exit routine again. Until a valid authorization is established, any SQL statement that you issue causes Db2 to return an error.

Related tasks

Reusing a local trusted connection through the DSN command processor and DB2I You can use the DSN command processor and DB2I to switch the user on a trusted connection if the DSN ASUSER option is specified.

<u>Reusing a remote trusted connection by Db2 for z/OS requesters</u> After establishing a trusted connection with a system authorization ID, the Db2 for z/OS requester automatically switches the user on the connection to the primary authorization ID on the remote trusted connection.

Reusing a remote trusted connection through Db2 for z/OS servers

The Db2 for z/OS server performs a sequence of tasks when it receives a request to switch users on a trusted connection.

Reusing a local trusted connection through the SQL CONNECT statement You can switch users on a trusted connection by using the SQL CONNECT statement with the USER and USING clauses.

Reusing a local trusted connection through the SQL CONNECT statement

You can switch users on a trusted connection by using the SQL CONNECT statement with the USER and USING clauses.

About this task

Db2, on successful authorization, invokes the connection exit routine if it is defined. The connection then has a primary authorization ID, zero or more secondary IDs, and an SQL ID.

Db2 searches to determine if the primary authorization ID is allowed to use the trusted connection. If the primary authorization ID is allowed, Db2 determines if the SECURITY LABEL attribute is defined in the trusted context for the user either explicitly or implicitly. If the SECURITY LABEL attribute is defined with a security label, Db2 verifies the security label with RACF. If the security label verification is successful, Db2 switches the user on the trusted connection. Db2 uses the security label for multilevel security verification for the user.

If the primary authorization ID is not allowed to use the trusted connection or if the security label verification is not successful, Db2 returns the connection to an unconnected state. The only action you can take is to establish a valid authorization ID to be associated with the trusted connection. Until a valid authorization is established, any SQL statement that you issue causes Db2 to return an error.

Related tasks

Reusing a local trusted connection through the DSN command processor and DB2I You can use the DSN command processor and DB2I to switch the user on a trusted connection if the DSN ASUSER option is specified.

Reusing a remote trusted connection by Db2 for z/OS requesters After establishing a trusted connection with a system authorization ID, the Db2 for z/OS requester automatically switches the user on the connection to the primary authorization ID on the remote trusted connection.

Reusing a remote trusted connection through Db2 for z/OS servers The Db2 for z/OS server performs a sequence of tasks when it receives a request to switch users on a trusted connection.

Reusing a local trusted connection through RRSAF

If you use Resource Recovery Services Attachment Facility (RRSAF) to switch to a new user on a trusted connection, Db2 obtains the primary authorization ID and runs the sign-on exit routine.

Defining external security profiles

You can control the users who can be switched in a trusted connection by defining an external security profile in RACF and authorizing users to use the profile.

Procedure

To define an external security profile in RACF:

1. Create a general resource profile in RACF for the DSNR class by issuing the following command:

RDEFINE DSNR (TRUSTEDCTX.PROFILE1) UACC(NONE)

2. Add users to the TRUSTEDCTX.PROFILE1 profile and define their level of access authority by issuing the following command:

PERMIT TRUSTEDCTX.PROFILE1 CLASS(DSNR) ID(USER1 USER2) ACCESS(READ)

3. Associate the profile with the trusted context definition by using the EXTERNAL SECURITY PROFILE keyword in the trusted context user clause definition.

Results

You can remove users who can be switched in a trusted connection individually from the TRUSTEDCTX.PROFILE1 profile in RACF. You can also remove all users by simply dissociating the profile from the trusted context definition.

How secondary roles are used during the switching of users of trusted connections

You can define secondary roles in a trusted context definition. The secondary roles are used only for users that are switched in a trusted connection.

Db2 considers secondary roles in the following environments:

- When Db2 native authorization is used, in a similar way to secondary authorization checking.
- During a search of the plan authorization cache, package authorization cache, routine authorization cache, or dynamic statement cache.
- When the VERIFY_ROLE_FOR_USER built-in function is executed.

Users can be permitted access to multiple profiles in RACF or an equivalent z/OS security product. To set up secondary roles, you perform the following actions in a CREATE TRUSTED CONTEXT or ALTER TRUSTED CONTEXT SQL statement, using the EXTERNAL SECURITY PROFILE clause:

- · Specify multiple security profiles to which users have access
- · Associate a different role with each of those security profiles

For example, suppose that user ADMF002 has been permitted access to PROFILE1 and PROFILE2 in RACF.

Now suppose that you execute the following CREATE TRUSTED CONTEXT statement:

```
CREATE TRUSTED CONTEXT CTX1
BASED UPON CONNECTION USING SYSTEM AUTHID ADMF001
NO DEFAULT ROLE
ENABLE ATTRIBUTES (JOBNAME 'DB2PROD')
WITH USE FOR
EXTERNAL SECURITY PROFILE PROFILE1 ROLE SECROLE_1,
EXTERNAL SECURITY PROFILE PROFILE2 ROLE SECROLE_2;
```

The statement specifies that a user with access to external security profile PROFILE1 is associated with role SECROLE_1, and a user with access to external security profile PROFILE2 is associated with role SECROLE_2.

After a trusted connection is established for system authorization ID ADMF001 and job name DB2PROD, when a switch user request is issued to use the trusted connection under authorization ID ADMF002, ADMF002 can receive additional privileges from roles SECROLE_1 and SECROLE_2, which are associated with profiles PROFILE1 and PROFILE2.

Related concepts

Trusted connections

A *trusted connection* is a database connection that is established when the connection attributes match those of a trusted context that is defined at the server. A trusted connection can be established locally or at a remote location.

Roles in a trusted context

A *role* is a database entity that groups one or more privileges together in a trusted context. System administrators can use roles to control access to enterprise objects in a way that parallels the structure of the enterprise.

Related tasks

Defining trusted contexts

Before you can create a trusted connection, you must define a trusted context by using a system authorization ID and connection trust attributes.

Enabling users to perform actions on behalf of others

Within a trusted context, you can allow users to perform actions on objects on behalf of others.

About this task

You can specify the DSN ASUSER option with the authorization ID of the object owner. During the connection processing, the authorization ID is used to determine if a trusted context exists for this authorization ID. If a trusted context exists, a trusted connection is established. The primary authorization ID that is associated with the user ID and specified in the ASUSER option is used to determine if the user can be switched on the trusted connection.

If the user ID that is specified in the ASUSER option is allowed to use the trusted connection, the user runs under the authorization ID of the object owner and can perform actions on behalf of the object owner. The authorization ID of the original user is traced for audit purposes.

Related concepts

Switching users of a trusted connection

When a trusted connection is established, Db2 enables the trusted connection to be reused by a different user on a transaction boundary.

Performing tasks on objects for other users

If you have DBADM authority, you can assume the identity of other users within a trusted context and perform tasks on their behalf.

About this task

After you successfully assume the identity of a view owner, you inherit all the privileges from the ID that owns the view and can therefore perform the CREATE, DROP, and GRANT actions on the view.

Procedure

To perform tasks on behalf of another user:

- 1. Define a trusted context.
 - Make sure that the SYSTEM AUTH ID is the primary authorization ID that you use in SPUFI.
- 2. Specify the primary authorization ID as the JOBNAME for the trusted connection.
- 3. Specify the primary authorization ID of the user whose identity you want to assume.
- 4. Log onto TSO with your primary authorization ID.
- 5. Set the ASUSER option on the DB2I DEFAULTS panel to the primary authorization ID of the user whose identity you want to assume.
- 6. Perform the actions that you want by using the privileges of the specified user.

Example

For example, assume that you have DBADM authority, your primary authorization ID is BOB, and you want to drop a view that is owned by user SALLY. You can issue the following statement to create and enable a trusted context called CTXLOCAL in which BOB can drop the selected view on SALLY's behalf:

CREATE TRUSTED CONTEXT CTXLOCAL BASED UPON CONNECTION USING SYSTEM AUTHID BOB ATTRIBUTES (JOBNAME 'BOB') ENABLE WITH USE FOR SALLY;

After logging onto TSO, you can set the ASUSER option to SALLY in the DB2I DEFAULTS panel and invoke SPUFI to process SQL statements. Db2 obtains the primary authorization ID BOB and JOBNAME BOB from the TSO logon session, authenticates BOB, searches for the matching trusted context (CTXLOCAL), and establishes a trusted connection. Db2 then authenticates the primary authorization ID SALLY and validates all privileges that are assigned to SALLY. After successful authentication and validation, you, BOB, can drop the view that is owned by SALLY.

Related concepts

Switching users of a trusted connection

When a trusted connection is established, Db2 enables the trusted connection to be reused by a different user on a transaction boundary.

Chapter 6. Managing access through data definition control

Data definition control is a Db2 security measure that provides additional constraints to existing authorization checks. You can use data definition control to manage access to your Db2 data.

Statements controlled by data definition control support

Data definition control support can control data definition statements.

Db2 data definition control support controls the following data definition statements.

Table 67. Data definition Statements					
Object	CREATE statement	ALTER statement	DROP statement		
Alias	CREATE ALIAS		DROP ALIAS		
Database	CREATE DATABASE	ALTER DATABASE	DROP DATABASE		
Index	CREATE INDEX	ALTER INDEX	DROP INDEX		
Storage group	CREATE STOGROUP	ALTER STOGROUP	DROP STOGROUP		
Synonym	CREATE SYNONYM ⁽¹⁾ on page 251		DROP SYNONYM		
Table	CREATE TABLE	ALTER TABLE	DROP TABLE		
Table space	CREATE TABLESPACE	ALTER TABLESPACE	DROP TABLESPACE		
View	CREATE VIEW		DROP VIEW		

Note:

1. FL 504 Beginning in Db2 12, packages bound with APPLCOMPAT(V12R1M504) or higher cannot issue CREATE SYNONYM statements.

The data definition control support also controls the COMMENT and LABEL statements.

Related concepts

Registration tables

If you use data definition control support, you must create and maintain an application registration table (ART) and an object registration table (ORT). You can register plans and package collections in the ART and objects that are associated with the plans and collections in the ORT.

Related reference

Data definition control support

If you want to use data definition statements for your plans and packages, you must install *data definition control support* on the Db2 DSNTIPZ installation panel.

Data definition control support

If you want to use data definition statements for your plans and packages, you must install *data definition control support* on the Db2 DSNTIPZ installation panel.

As shown in the following example, you can specify appropriate values for several installation options to install the data definition control support and to control data definition behaviors.

DSNTIPZ INSTALL DB2 - DATA DEFINITION CONTROL SUPPORT ===> Enter data below: YES - activate the support NO - omit DD control support 1 INSTALL DD CONTROL SUPT. ===> NO 2 CONTROL ALL APPLICATIONS ===> NO 3 REQUIRE FULL NAMES ===> YES YES or NO ===> YES YES or NO Action for unregistered DDL: ACCEPT - allow it REJECT - prohibit it 4 UNREGISTERED DDL DEFAULT ===> ACCEPT APPL - consult ART 5 ART/ORT ESCAPE CHARACTER ===> Used in ART/ORT Searches 6 REGISTRATION OWNER ===> DSNRGCOL 7 REGISTRATION DATABASE ===> DSNRGFDB Qualifier for ART and ORT Database name 8 APPL REGISTRATION TABLE ===> DSN_REGISTER_APPL Table name 9 OBJT REGISTRATION TABLE ===> DSN_REGISTER_OBJT Table name Note: ART = Application Registration Table ORT = Object Registration Table PRESS: ENTER to continue RETURN to exit HELP for more information

Figure 12. DSNTIPZ installation panel with default values

Related concepts

Registration tables

If you use data definition control support, you must create and maintain an application registration table (ART) and an object registration table (ORT). You can register plans and package collections in the ART and objects that are associated with the plans and collections in the ORT.

Related reference

Statements controlled by data definition control support Data definition control support can control data definition statements.

Data definition control support

If you want to use data definition statements for your plans and packages, you must install *data definition control support* on the Db2 DSNTIPZ installation panel.

Registration tables

If you use data definition control support, you must create and maintain an application registration table (ART) and an object registration table (ORT). You can register plans and package collections in the ART and objects that are associated with the plans and collections in the ORT.

Db2 consults these two registration tables before accepting a data definition statement from a process. It denies a request to create, alter, or drop a particular object if the registration tables indicate that the process is not allowed to do so.

Both ART and ORT contain the CREATOR and CHANGER columns. The CREATOR and CHANGER columns are CHAR(26) and large enough for a three-part authorization ID. You need to separate each 8-byte part of the ID with a period in byte 9 and in byte 18. If you enter only the primary authorization ID, consider entering it right-justified in the field (that is, preceded by 18 blanks).

In addition to the CREATOR and CHANGER columns, an ART also contains the following columns, some of which are optional and reserved for administrator use; Db2 does not use these columns.

Column name	Description
APPLIDENT	Indicates the collection-ID of the package that executes the data definition language. If no package exists, it indicates the name of the plan that executes the data definition language.
APPLIDENTTYPE	Indicates the type of application identifier.

Table 68. Columns of the ART

Table 68. Columns of the ART (continued)

Column name	Description
APPLICATIONDESC ¹	Optional data. Provides a more meaningful description of each application than the eight-byte APPLIDENT column can contain.
DEFAULTAPPL	Indicates whether all data definition language should be accepted from this application.
QUALIFIEROK	Indicates whether the application can supply a missing name part for objects that are named in the ORT. Applies only if REQUIRE FULL NAMES = NO.
CREATOR ^{1, 2}	Optional data. Indicates the authorization ID that created the row.
CREATETIMESTAMP ¹	Optional data. Indicates when a row was created. If you use CURRENT TIMESTAMP, Db2 automatically enters the value of CURRENT TIMESTAMP When you load or insert a row.
CHANGER ^{1, 2}	Optional data. Indicates the authorization ID that last changed the row.
CHANGETIMESTAMP ¹	Optional data. Indicates when a row was changed. If you use CURRENT TIMESTAMP, Db2 automatically enters the value of CURRENT TIMESTAMP When you update a row.

An ORT also contains the following columns, some of which are optional and reserved for administrator use; Db2 does not use these columns.

Table 69. Columns of the ORT

Column name	Description
QUALIFIER	Indicates the object name qualifier.
NAME	Indicates the unqualified object name.
ТҮРЕ	Indicates the type of object.
APPLMATCHREQ	Indicates whether an application that names this object must match the one that is named in the APPLIDENT column.
APPLIDENT	Collection-ID of the plan or package that executes the data definition language.
APPLIDENTTYPE	Indicates the type of application identifier.
APPLICATIONDESC ¹	Optional data. Provides a more meaningful description of each application than the eight-byte APPLIDENT column can contain.
CREATOR ^{1, 2}	Optional data. Indicates the authorization ID that created the row.
CREATETIMESTAMP ¹	Optional data. Indicates when a row was created. If you use CURRENT TIMESTAMP, Db2 automatically enters the value of CURRENT TIMESTAMP When you load or insert a row.
CHANGER ^{1, 2}	Optional data. Indicates the authorization ID that last changed the row.
CHANGETIMESTAMP ¹	Optional data. Indicates when a row was changed. If you use CURRENT TIMESTAMP, Db2 automatically enters the value of CURRENT TIMESTAMP When you update a row.

Related reference

Statements controlled by data definition control support

Data definition control support can control data definition statements.

Data definition control support

If you want to use data definition statements for your plans and packages, you must install *data definition control support* on the Db2 DSNTIPZ installation panel.

Installing data definition control support

You can install data definition control support that is available through the Db2 DSNTIPZ installation panel.

Procedure

To install data definition control support:

1. Enter YES for option 1 on the DSNTIPZ installation panel, as shown in the following example.

```
1 INSTALL DD CONTROL SUPT. ===> YES
```

2. Enter the names and owners of the registration tables in your Db2 subsystem and the databases in which these tables reside for options 6, 7, 8, and 9 on the DSNTIPZ installation panel.

The default values for these options are as follows:

6	REGIS	STRATION OWNER	===>	DSNRGCOL
7	REGIS	STRATION DATABASE	===>	DSNRGFDB
8	APPL	REGISTRATION TABLE	===>	DSN_REGISTER_APPL
9	OBJT	REGISTRATION TABLE	===>	DSN_REGISTER_OBJT

You can accept the default names or assign names of your own. If you specify your own table names, each name can have a maximum of 17 characters.

3. Enter an escape character for option 5 on the DSNTIPZ installation panel if you want to use the percent character (%) or the underscore character (_) as a regular character in the ART or ORT.

You can use any special character other than underscore or percent as the escape character. For example, you can use the pound sign (#) as an escape character. If you do, the value for option looks like this:

```
5 ART/ORT ESCAPE CHARACTER ===> #
```

After you specify the pound sign as an escape character, the pound sign can be used in names in the same way that an escape character is used in an SQL LIKE predicate.

4. Register plans, packages, and objects in the ART and ORT.

Choose the plans, packages, and objects to register based on whether you want to control data definition by application name or object name.

5. Enter the values for the three other options on the DSNTIPZ installation panel as follows:

```
2 CONTROL ALL APPLICATIONS ===>
3 REQUIRE FULL NAMES ===>
4 UNREGISTERED DDL DEFAULT ===>
```

Related reference

Data definition control support

If you want to use data definition statements for your plans and packages, you must install *data definition control support* on the Db2 DSNTIPZ installation panel.

Enabling data definition control

You can use data definition control after you install the Db2 data definition control support and create the application registration table (ART) and the object registration table (ORT).

Procedure

You can use data definition control in the following four ways:

- · Controlling data definition by application name
- Controlling data definition by application name with exceptions
- · Controlling data definition by object name
- · Controlling data definition by object name with exceptions

Related tasks

Disabling data definition control

When data definition control is active, only IDs with the installation SYSADM or installation SYSOPR authority can stop a database, a table space, or an index space that contains a registration table or index.

Controlling data definition by application name

The simplest way to implement data definition control is to give one or more applications total control over the use of data definition statements in the subsystem.

Procedure

To control data definition by application name:

1. Enter YES for the first option on the DSNTIPZ installation panel, as shown:

2 CONTROL ALL APPLICATIONS ===> YES

When you specify YES, only package collections or plans that are registered in the ART are allowed to use data definition statements.

2. In the ART, register all package collections and plans that you will allow to issue DDL statements, and enter the value Y in the DEFAULTAPPL column for these package collections. You must supply values for the APPLIDENT, APPLIDENTTYPE, and DEFAULTAPPL columns of the ART. You can enter information in other columns for your own use.

Example

Suppose that you want all data definition language in your subsystem to be issued only through certain applications. The applications are identified by the following application plan names, collection-IDs, and patterns:

PLANA

The name of an application plan

PACKB

The collection-ID of a package

TRULY%

A pattern name for any plan name beginning with TRULY

TR%

A pattern name for any plan name beginning with TR

The following table shows the entries that you need in your ART.

Table 70. Table DSN_REGISTER_APPL for total subsystem control			
APPLIDENT APPLIDENTTYPE DEFAULTAPPL			
PLANA	Р	Υ	
РАСКВ	С	Υ	
TRULY%	Р	Υ	
TR%	Р	Y	

If the row with TR% for APPLIDENT contains the value Y for DEFAULTAPPL, any plan with a name beginning with TR can execute data definition language. If DEFAULTAPPL is later changed to N to disallow that use, the changed row does not prevent plans beginning with TR from using data definition language; the row merely fails to allow that specific use. In this case, the plan TRXYZ is not allowed to use data definition language. However, the plan TRULYXYZ is allowed to use data definition language, by the row with TRULY% specified for APPLIDENT.

Related tasks

Controlling data definition by application name with exceptions You can register an application name with exceptions in the application registration table (ART) as a way to control data definition.

Controlling data definition by object name

You can register object names in the object registration table (ORT) as a way to control data definition. You need to control data definition by object names if you want all objects in the subsystem to be registered and if you want some applications to control specific sets of objects.

Controlling data definition by object name with exceptions You can register an object name with exceptions in the object registration table (ORT) as a way to control data definition.

Controlling data definition by application name with exceptions

You can register an application name with exceptions in the application registration table (ART) as a way to control data definition.

Procedure

To control data definition by application name with exceptions:

1. Choose not to control all applications.

On the DSNTIPZ installation panel, specify the following value for option 2:

2 CONTROL ALL APPLICATIONS ===> NO

When you specify NO, you allow unregistered applications to use data definition statements on some objects.

2. On the DSNTIPZ installation panel, specify the following for option 4:

4 UNREGISTERED DDL DEFAULT ===> APPL

When you specify APPL, you restrict the use of data definition statements for objects that are **not** registered in the ORT. If an object is registered in the ORT, any applications that are not registered in the ART can use data definition language on the object. However, if an object is not registered in the ORT, only applications that are registered in the ART can use data definition language on the ART can use data definition language on the object.

3. In the ART, register package collections and plans that you will allow to issue data definition statements on any object. Enter the value Y in the DEFAULTAPPL column for these package collections. Applications that are registered in the ART retain almost total control over data definition. Objects that are registered in the ORT are the only exceptions.

4. In the ORT, register all objects that are exceptions to the subsystem data definition control that you defined in the ART. You must supply values for the QUALIFIER, NAME, TYPE, APPLMATCHREQ, APPLIDENT, and APPLIDENTTYPE columns of the ORT. You can enter information in other columns of the ORT for your own use.

Example

Suppose that you want almost all of the data definition language in your subsystem to be issued only through an application plan (PLANA) and a package collection (PACKB).

Table 71. Table DSN_REGISTER_APPL for total subsystem control with exceptions				
APPLIDENT APPLIDENTTYPE DEFAULTAPPL				
PLANA P Y				
PACKB C Y				

However, suppose that you also want the following specific exceptions:

- Object KIM.VIEW1 can be created, altered, or dropped by the application plan PLANC.
- Object BOB.ALIAS can be created, altered, or dropped only by the package collection PACKD.
- Object FENG.TABLE2 can be created, altered, or dropped by **any** plan or package collection.
- Objects with names that begin with SPIFFY.MSTR and exactly one following character can be created, altered, or dropped by any plan that matches the name pattern TRULY%. For example, the plan TRULYJKL can create, alter, or drop the object SPIFFY.MSTRA.

The following table shows the entries that are needed to register these exceptions in the ORT.

Table 72. Table DSN_REGISTER_OBJT for subsystem control with exceptions					
QUALIFIER	NAME	TYPE	APPLMATCHREQ	APPLIDENT	APPLIDENTTYPE
KIM	VIEW1	С	Υ	PLANC	Р
вов	ALIAS	С	Υ	PACKD	С
FENG	TABLE2	С	Ν		
SPIFFY	MSTR_	С	Υ	TRULY%	Р

You can register objects in the ORT individually, or you can register sets of objects.

Related tasks

Controlling data definition by application name

The simplest way to implement data definition control is to give one or more applications total control over the use of data definition statements in the subsystem.

Controlling data definition by object name

You can register object names in the object registration table (ORT) as a way to control data definition. You need to control data definition by object names if you want all objects in the subsystem to be registered and if you want some applications to control specific sets of objects.

Controlling data definition by object name with exceptions

You can register an object name with exceptions in the object registration table (ORT) as a way to control data definition.

Controlling data definition by object name

You can register object names in the object registration table (ORT) as a way to control data definition. You need to control data definition by object names if you want all objects in the subsystem to be registered and if you want some applications to control specific sets of objects.

About this task

When you control data definition by object name, all objects are registered regardless of whether they are controlled by specific applications.

Procedure

To control data definition by object name:

1. Choose not to control all applications. On the DSNTIPZ installation panel, specify the following value for option 2:

2 CONTROL ALL APPLICATIONS ===> NO

When you specify NO, you allow unregistered applications to use data definition statements on some objects.

2. On the DSNTIPZ installation panel, complete option 4 as follows:

4 UNREGISTERED DDL DEFAULT ===> REJECT

When you specify REJECT for option 4, you totally restrict the use of data definition statements for objects that are not registered in the ORT. Therefore, no application can use data definition statements for any unregistered object.

- 3. In the ORT, register all of the objects in the subsystem, and enter Y in the APPLMATCHREQ column. You must supply values for the QUALIFIER, NAME, TYPE, APPLMATCHREQ, APPLIDENT, and APPLIDENTTYPE columns of the ORT. You can enter information in other columns of the ORT for your own use.
- 4. In the ART, register any plan or package collection that can use a set of objects that you register in the ORT with an incomplete name. Enter the value Y in the QUALIFIEROK column. These plans or package collections can use data definition language on sets of objects regardless of whether a set of objects has a value of Y in the APPLMATCHREQ column.

Example

The following table shows entries in the ORT for a Db2 subsystem that contains the following objects that are controlled by object name:

- Two storage groups (STOG1 and STOG2) and a database (DATB1) that are not controlled by a specific application. These objects can be created, altered, or dropped by a user with the appropriate authority by using any application, such as SPUFI or QMF.
- Two table spaces (TBSP1 and TBSP2) that are not controlled by a specific application. Their names are qualified by the name of the database in which they reside (DATB1).
- Three objects (OBJ1, OBJ2, and OBJ3) whose names are qualified by the authorization IDs of their owners. Those objects might be tables, views, indexes, synonyms, or aliases. Data definition statements for OBJ1 and OBJ2 can be issued only through the application plan named PLANX. Data definition statements for OBJ3 can be issued only through the package collection named PACKX.
- Objects that match the qualifier pattern E%D and the name OBJ4 can be created, altered, or deleted by application plan SPUFI. For example, the objects EDWARD.OBJ4, ED.OBJ4, and EBHARD.OBJ4, can be created, altered, or deleted by application plan SPUFI. Entry E%D in the QUALIFIER column represents all three objects.

• Objects with names that begin with TRULY.MY_, where the underscore character is actually part of the name. Assuming that you specify # as the escape character, all of the objects with this name pattern can be created, altered, or dropped only by plans with names that begin with TRULY.

Table 73. Table DSN_REGISTER_OBJT for total control by object						
QUALIFIER	NAME	TYPE	APPLMATCHREQ	APPLIDENT	APPLIDENTTYPE	
	STOG1	S	Ν			
	STOG2	S	Ν			
	DATB1	D	Ν			
DATB1	TBSP1	Т	Ν			
DATB1	TBSP2	Т	Ν			
KIM	OBJ1	С	Υ	PLANX	Р	
FENG	OBJ2	С	Υ	PLANX	Р	
QUENTIN	OBJ3	С	Υ	PACKX	С	
E%D	OBJ4	С	Υ	SPUFI	Р	
TRULY	MY#_%	С	Υ	TRULY%	Р	

Assume the following installation option:

3 REQUIRE FULL NAMES ===> YES

The entries do not specify incomplete names. Hence, objects that are not represented in the table cannot be created in the subsystem, except by an ID with installation SYSADM authority.

Related tasks

Controlling data definition by application name

The simplest way to implement data definition control is to give one or more applications total control over the use of data definition statements in the subsystem.

Controlling data definition by application name with exceptions

You can register an application name with exceptions in the application registration table (ART) as a way to control data definition.

Controlling data definition by object name with exceptions

You can register an object name with exceptions in the object registration table (ORT) as a way to control data definition.

Controlling data definition by object name with exceptions

You can register an object name with exceptions in the object registration table (ORT) as a way to control data definition.

About this task

You can allow some applications to control specific sets of registered objects while allowing other applications to use data definition statements for unregistered objects.

Procedure

To control data definition by object name with exceptions:

1. Choose not to control all applications. On the DSNTIPZ installation panel, specify the following value for option 2:

```
2 CONTROL ALL APPLICATIONS ===> NO
```

When you specify NO, you allow unregistered applications to use data definition statements on some objects.

2. On the DSNTIPZ installation panel, complete option 4 as follows:

4 UNREGISTERED DDL DEFAULT ===> ACCEPT

This option **does not** restrict the use of data definition statements for objects that are not registered in the ORT. Therefore, **any** application can use data definition language for any unregistered object.

- 3. Register all controlled objects in the ORT. Use a name and qualifier to identify a single object. Use only one part of a two-part name to identify a set of objects that share just that part of the name. For each controlled object, use APPLMATCHREQ = Y. Enter the name of the plan or package collection that controls the object in the APPLIDENT column.
- 4. For each set of controlled objects (identified by only a simple name in the ORT), register the controlling application in the ART. You must supply values for the APPLIDENT, APPLIDENTTYPE, and OUALIFIEROK columns of the ART.

Example

The following two tables assume that the installation option REQUIRE FULL NAMES is set to NO. The following table shows entries in the ORT for the following controlled objects:

Table 74. Table DSN_REGISTER_OBJT for object control with exceptions						
QUALIFIER	NAME	TYPE	APPLMATCHREQ	APPLIDENT	APPLIDENTTYPE	
KIM	OBJ1	С	Υ	PLANX	Р	
FENG	OBJ2	С	Υ	PLANX	Р	
QUENTIN	OBJ3	С	Υ	PACKX	С	
EDWARD	OBJ4	С	Υ	PACKX	С	
	ТАВА	С	Υ	PLANA	Р	
	ТАВВ	С	Υ	РАСКВ	С	

• The objects KIM.OBJ1, FENG.OBJ2, QUENTIN.OBJ3, and EDWARD.OBJ4, all of which are controlled by PLANX or PACKX. Db2 cannot interpret the object names as incomplete names because the objects that control them, PLANX and PACKX, are registered, with QUALIFIEROK=N, in the corresponding ART as shown in the following table:

Table 75. Table DSN_REGISTER_APPL for object control with exceptions					
APPLIDENT	APPLIDENTTYPE	DEFAULTAPPL	QUALIFIEROK		
PLANX	Р	Ν	Ν		
PACKX	С	Ν	Ν		
PLANA	Р	Ν	Υ		
РАСКВ	С	Ν	Υ		

In this situation, with the combination of installation options shown previously, any application can use data definition language for objects that are not covered by entries in the ORT. For example, if HOWARD has the CREATETAB privilege, HOWARD can create the table HOWARD.TABLE10 through any application.

• Two sets of objects, *.TABA and *.TABB, are controlled by PLANA and PACKB, respectively.

Related tasks

Controlling data definition by application name

The simplest way to implement data definition control is to give one or more applications total control over the use of data definition statements in the subsystem.

Controlling data definition by application name with exceptions You can register an application name with exceptions in the application registration table (ART) as a way to control data definition.

Controlling data definition by object name

You can register object names in the object registration table (ORT) as a way to control data definition. You need to control data definition by object names if you want all objects in the subsystem to be registered and if you want some applications to control specific sets of objects.

Registering object sets

Registering object sets enables you to save time and to simplify object registration.

About this task

Registering object sets is not a data definition control method; you must install of the data definition control methods before you can register any object sets.

Because complete two-part names are not required for every object that is registered in the ORT, you can use incomplete names to register sets of objects. To use incomplete names and register sets of objects, enter option 3 on the DSNTIPZ installation panel as follows:

3 REQUIRE FULL NAMES ===> NO

The default value YES requires you to use both parts of the name for each registered object. If you specify the value NO, an incomplete name in the ORT represents a set of objects that all share the same value for one part of a two-part name. Objects that are represented by incomplete names in the ORT require an authorizing entry in the ART.

Example

If you specify NO for option 3, you can include entries with incomplete names in the ORT. The following table shows entries in the ORT for the following objects:

Table 76. Table DSN_REGISTER_OBJT for objects with incomplete names						
QUALIFIER	NAME	TYPE	APPLMATCHREQ	APPLIDENT	APPLIDENTTYPE	
	ТАВА	С	Υ	PLANX	Р	
	ТАВВ	С	Υ	PACKY	С	
SYSADM		С	Ν			
DBSYSADM		Т	Ν			
USER1	TABLEX	С	Ν			

• Two sets of objects, *.TABA and *.TABB, which are controlled by PLANX and PACKY, respectively. Only PLANX can create, alter, or drop any object whose name is *.TABA. Only PACKY can create, alter, or drop any object whose name is *.TABB. PLANX and PACKY must also be registered in the ART with QUALIFIEROK set to Y, as shown in the following table: That setting allows the applications to use sets of objects that are registered in the ORT with an incomplete name.

Table 77. Table DSN_REGISTER_APPL for plans that use sets of objects

APPLIDENT	APPLIDENTTYPE	DEFAULTAPPL	QUALIFIEROK
PLANA	Р	Ν	Υ
РАСКВ	С	Ν	Υ

- Tables, views, indexes, or aliases with names like SYSADM.*.
- Table spaces with names like DBSYSADM.*; that is, table spaces in database DBSYSADM.
- Tables with names like USER1.* and tables with names like *.TABLEX.

APPLMATCHREQ=N and objects SYSADM.*, DBSYSADM.*, USER1.*, and *.TABLEX can be created, altered, or dropped by any package collection or application plan. However, the collection or plan that creates, alters, or drops such an object must be registered in the ART with QUALIFIEROK=Y to allow it to use incomplete object names.

Related reference

REQUIRE FULL NAMES field (RGFFULLQ subsystem parameter) (Db2 Installation and Migration) DSNTIPZ: Data definition control support panel (Db2 Installation and Migration)

Disabling data definition control

When data definition control is active, only IDs with the installation SYSADM or installation SYSOPR authority can stop a database, a table space, or an index space that contains a registration table or index.

About this task

When the object is stopped, only an ID with one of those authorities can start it again.

An ID with the installation SYSADM authority can execute data definition statements regardless of whether data definition control is active and whether the ART or ORT is available.

Procedure

To bypass data definition control, an ID with the installation SYSADM authority can use the following methods:

- If the ID is the owner of the plan or package that contains the statement, the ID can bypass data definition control by using a static SQL statement.
- If the ID is the current SQL ID, the ID can bypass data definition control through a dynamic CREATE statement.
- If the ID is the current SQL ID, the primary ID, or any secondary ID of the executing process, the ID can bypass data definition control through a dynamic ALTER or DROP statement.

Related tasks

Enabling data definition control

You can use data definition control after you install the Db2 data definition control support and create the application registration table (ART) and the object registration table (ORT).

Managing registration tables and indexes

You can create, update, and drop registration tables and indexes. You can also create table spaces for or add columns to registration tables.

Creating registration tables and indexes

When you install data definition control support, you create the application registration table (ART), the object registration table (ORT), and the unique indexes that are required on the tables. You can re-create these objects if you drop any of them.

About this task

You can use the following CREATE statements to re-create ART, the ORT, or the required unique indexes:

CREATE statements for the ART and its index:

GUPI

CREATE TABLE DSNRGCOL	.DSN_REGISTER	APPL	_			
(APPLIDENT	CHAR(18)	NOT	NULL	WITH	DEFAULT,	
APPLIDENTTYPE	CHAR(1)	NOT	NULL	WITH	DEFAULT,	
APPLICATIONDESC	VARCHAR(30)	NOT	NULL	WITH	DEFAULT,	
DEFAULTAPPL	CHAR(1)	NOT	NULL	WITH	DEFAULT,	
QUALIFIEROK	CHAR(1)	NOT	NULL	WITH	DEFAULT,	
CREATOR	CHAR(26)	NOT	NULL	WITH	DEFAULT,	
CREATETIMESTAMP	TIMESTAMP	NOT	NULL	WITH	DEFAULT,	
CHANGER	CHAR(26)	NOT	NULL	WITH	DEFAULT,	
CHANGETIMESTAMP	TIMESTAMP	NOT	NULL	WITH	DEFAULT)	
IN DSNRGFDB.DSNRGFT	5;					

CREATE UNIQUE INDEX DSNRGCOL.DSN_REGISTER_APPLI ON DSNRGCOL.DSN_REGISTER_APPL (APPLIDENT, APPLIDENTTYPE, DEFAULTAPPL DESC, QUALIFIEROK DESC) CLUSTER;

GUPI

CREATE statements for the ORT and its index:

GUPI

С	REATE	TABLE	DSNRGCOL.	DSN REGISTER	OBJT	Г		
	(QUAI	LIFIER		CHAR(8)	NOT	NULL	WITH	DEFAULT,
	ŇAME	=		CHAR(18)	NOT	NULL	WITH	DEFAULT,
	TYPE	=		CHAR(1)	NOT	NULL	WITH	DEFAULT,
	APPI	LMATCH	REQ	CHAR(1)	NOT	NULL	WITH	DEFAULT,
	APPI	LIDENT		CHAR(18)	NOT	NULL	WITH	DEFAULT,
	APPI	LIDENT	ГҮРЕ	CHAR(1)	NOT	NULL	WITH	DEFAULT,
	APPI	LICATIO	DNDESC	VARCHAR(30)	NOT	NULL	WITH	DEFAULT,
	CRE/	ATOR		CHAR(26)	NOT	NULL	WITH	DEFAULT,
	CRE/	ATETIME	ESTAMP	TIMESTAMP	NOT	NULL	WITH	DEFAULT,
	CHAN	VGER		CHAR(26)	NOT	NULL	WITH	DEFAULT,
	CHAN	VGETIME	ESTAMP	TIMESTAMP	NOT	NULL	WITH	DEFAULT)
	IN DS	SNRGFD	B.DSNRGFTS	5;				

CREATE UNIQUE INDEX DSNRGCOL.DSN_REGISTER_OBJTI ON DSNRGCOL.DSN_REGISTER_OBJT (QUALIFIER, NAME, TYPE) CLUSTER;

GUPI

You can alter these CREATE statements in the following ways:

· Add columns to the ends of the tables

- Assign an auditing status
- · Choose buffer pool or storage options for indexes
- Declare table check constraints to limit the types of entries that are allowed

Related tasks

Naming registration tables and indexes

Every member of a data sharing group must have the same names for the application registration table (ART) and object registration tables (ORT) table. Avoid changing the names of the ART and ORT tables.

Dropping registration tables and indexes

If you drop any of the registration tables or their indexes, most data definition statements are rejected until the dropped objects are re-created.

Creating table spaces for registration tables

The DSNTIJSG installation job creates a segmented table space that holds the application registration table (ART) and the object registration table (ORT):

Adding columns to registration tables

You can use the ALTER TABLE statement to add columns to the application registration table (ART) or the object registration table (ORT) for your own use. If you add columns, the additional columns must come at the end of the table, after existing columns.

Updating registration tables

You can use the LOAD utility or the INSERT, UPDATE, or DELETE statements to update the application registration table (ART) and the object registration table (ORT).

Naming registration tables and indexes

Every member of a data sharing group must have the same names for the application registration table (ART) and object registration tables (ORT) table. Avoid changing the names of the ART and ORT tables.

About this task

If you change the names, owners, or residing database of your ART and ORT, you must reinstall Db2 in update mode and make the corresponding changes on the DSNTIPZ installation panel.

Name the required index by adding the letter I to the corresponding table name. For example, suppose that you are naming a required index for the ART named ABC. You should name the required index ABCI.

Related tasks

Creating registration tables and indexes

When you install data definition control support, you create the application registration table (ART), the object registration table (ORT), and the unique indexes that are required on the tables. You can re-create these objects if you drop any of them.

Dropping registration tables and indexes

If you drop any of the registration tables or their indexes, most data definition statements are rejected until the dropped objects are re-created.

Creating table spaces for registration tables

The DSNTIJSG installation job creates a segmented table space that holds the application registration table (ART) and the object registration table (ORT):

Adding columns to registration tables

You can use the ALTER TABLE statement to add columns to the application registration table (ART) or the object registration table (ORT) for your own use. If you add columns, the additional columns must come at the end of the table, after existing columns.

Updating registration tables

You can use the LOAD utility or the INSERT, UPDATE, or DELETE statements to update the application registration table (ART) and the object registration table (ORT).

Dropping registration tables and indexes

If you drop any of the registration tables or their indexes, most data definition statements are rejected until the dropped objects are re-created.

About this task

The only data definition statements that are allowed under such circumstances are those that create the following objects:

- Registration tables that are defined during installation
- · Indexes of the registration tables that are defined during installation
- Table spaces that contain the registration tables that are defined during installation
- The database that contains the registration tables that are defined during installation

Related tasks

Creating registration tables and indexes

When you install data definition control support, you create the application registration table (ART), the object registration table (ORT), and the unique indexes that are required on the tables. You can re-create these objects if you drop any of them.

Naming registration tables and indexes

Every member of a data sharing group must have the same names for the application registration table (ART) and object registration tables (ORT) table. Avoid changing the names of the ART and ORT tables.

Creating table spaces for registration tables

The DSNTIJSG installation job creates a segmented table space that holds the application registration table (ART) and the object registration table (ORT):

Adding columns to registration tables

You can use the ALTER TABLE statement to add columns to the application registration table (ART) or the object registration table (ORT) for your own use. If you add columns, the additional columns must come at the end of the table, after existing columns.

Updating registration tables

You can use the LOAD utility or the INSERT, UPDATE, or DELETE statements to update the application registration table (ART) and the object registration table (ORT).

Creating table spaces for registration tables

The DSNTIJSG installation job creates a segmented table space that holds the application registration table (ART) and the object registration table (ORT):

About this task

You can issue the following statement to create the table space:

CREATE TABLESPACE DSNRGFTS IN DSNRGFDB SEGSIZE 4 CLOSE NO;

If you want to use a table space with a different name or different attributes, you can modify the DSNTIJSG job before installing Db2. Alternatively, you can drop the table space and re-create it, the ART and ORT tables, and their indexes.

Related tasks

Creating registration tables and indexes

When you install data definition control support, you create the application registration table (ART), the object registration table (ORT), and the unique indexes that are required on the tables. You can re-create these objects if you drop any of them.

Naming registration tables and indexes

Every member of a data sharing group must have the same names for the application registration table (ART) and object registration tables (ORT) table. Avoid changing the names of the ART and ORT tables.

Dropping registration tables and indexes

If you drop any of the registration tables or their indexes, most data definition statements are rejected until the dropped objects are re-created.

Adding columns to registration tables

You can use the ALTER TABLE statement to add columns to the application registration table (ART) or the object registration table (ORT) for your own use. If you add columns, the additional columns must come at the end of the table, after existing columns.

Updating registration tables

You can use the LOAD utility or the INSERT, UPDATE, or DELETE statements to update the application registration table (ART) and the object registration table (ORT).

Adding columns to registration tables

You can use the ALTER TABLE statement to add columns to the application registration table (ART) or the object registration table (ORT) for your own use. If you add columns, the additional columns must come at the end of the table, after existing columns.

About this task

Use a special character, such as the plus sign (+), in your column names to avoid possible conflict. If IBM adds columns to the ART or the ORT in future releases, the column names will contain only letters and numbers.

Related tasks

Creating registration tables and indexes

When you install data definition control support, you create the application registration table (ART), the object registration table (ORT), and the unique indexes that are required on the tables. You can re-create these objects if you drop any of them.

Naming registration tables and indexes

Every member of a data sharing group must have the same names for the application registration table (ART) and object registration tables (ORT) table. Avoid changing the names of the ART and ORT tables.

Dropping registration tables and indexes

If you drop any of the registration tables or their indexes, most data definition statements are rejected until the dropped objects are re-created.

Creating table spaces for registration tables

The DSNTIJSG installation job creates a segmented table space that holds the application registration table (ART) and the object registration table (ORT):

Updating registration tables

You can use the LOAD utility or the INSERT, UPDATE, or DELETE statements to update the application registration table (ART) and the object registration table (ORT).

Updating registration tables

You can use the LOAD utility or the INSERT, UPDATE, or DELETE statements to update the application registration table (ART) and the object registration table (ORT).

About this task

Because security provisions are important, allow only a restricted set of authorization IDs, or perhaps only those with the SYSADM authority, to update the ART. Consider assigning a validation exit routine to the ORT, to allow applications to change only those rows that have the same application identifier in the APPLIDENT column.

A registration table cannot be updated until all jobs whose data definition statements are controlled by the table have completed.

Related tasks

Creating registration tables and indexes

When you install data definition control support, you create the application registration table (ART), the object registration table (ORT), and the unique indexes that are required on the tables. You can re-create these objects if you drop any of them.

Naming registration tables and indexes

Every member of a data sharing group must have the same names for the application registration table (ART) and object registration tables (ORT) table. Avoid changing the names of the ART and ORT tables.

Dropping registration tables and indexes

If you drop any of the registration tables or their indexes, most data definition statements are rejected until the dropped objects are re-created.

Creating table spaces for registration tables

The DSNTIJSG installation job creates a segmented table space that holds the application registration table (ART) and the object registration table (ORT):

Adding columns to registration tables

You can use the ALTER TABLE statement to add columns to the application registration table (ART) or the object registration table (ORT) for your own use. If you add columns, the additional columns must come at the end of the table, after existing columns.

268 Db2 12 for z/OS: Managing Security (Last updated: 2024-09-06)

Chapter 7. Managing access through exit routines

You can control access to Db2 by using a Db2-supplied exit routine or an exit routine that you write. Db2 provides installation-wide exit points to the connection, sign-on, and access control authorization routines.

Related concepts

General guidelines for writing exit routines (Db2 Administration Guide)

Related information

Exit routines (Db2 Administration Guide)

Connection routines and sign-on routines

Your Db2 subsystem has two exit points for authorization routines, one in connection processing and one in sign-on processing. Both exit points perform crucial steps in the assignment of values to primary IDs, secondary IDs, and SQL IDs.

PSPI You must have a routine for each exit. Default routines are provided for both. DSN3@ATH is the default exit routine for connections, and DSN3@SGN is the default exit routine for sign-ons.

If your installation has a connection exit routine and you plan to use CONNECT with the USER/USING clause, you should examine your exit routine. Db2 does not update the following information to reflect the user ID and password that are specified in the USER/USING clause of the CONNECT statement:

- The security-related control blocks that are normally associated with the thread
- The address space that your exit routine can access

If you want to use secondary authorization IDs, you must replace the default routines with the sample routines, or with routines of your own.

Related concepts

General guidelines for writing exit routines (Db2 Administration Guide)

Related tasks

Using sample connection and sign-on exit routines for CICS transactions For a CICS transaction to use the sample connection or sign-on exit routines, the external security system, such as RACF, must be defined to CICS.

Specifying connection and sign-on routines

Your connection routine must have a CSECT name and entry point of DSN3@ATH. The name of the load module for the connection routine can be the same name, or it can be a different name. Your sign-on routine must have a CSECT name and entry point of DSN3@SGN. The name of the load module for the sign-on routine can be the same, or it can be a different name.

Debugging connection and sign-on routines

The diagnostic aids can assist you in debugging connection exit routines and sign-on exit routines.

Related reference

Processing of connection requests

A connection request makes a new connection to Db2; it does not reuse an application plan that is already allocated. Therefore, an essential step in processing the request is to check that the ID is authorized to use Db2 resources.

Processing of sign-on requests

Requests can come from IMS-dependent regions, CICS transaction subtasks, or RRS connections. For each of these types of requests, the initial primary ID is obtained immediately before a plan for the transaction is allocated. A new sign-on request can run the same plan without de-allocating and reallocating the plan.

Sample connection and sign-on routines

The sample Db2 exit routines are provided in the source code as members of prefix.SDSNSAMP.

Exit parameter list for connection and sign-on routines

The parameter list of connection and sign-on routines contains pointers to other information, such as the authorization ID list.

Specifying connection and sign-on routines

Your connection routine must have a CSECT name and entry point of DSN3@ATH. The name of the load module for the connection routine can be the same name, or it can be a different name. Your sign-on routine must have a CSECT name and entry point of DSN3@SGN. The name of the load module for the sign-on routine can be the same, or it can be a different name.

About this task

PSPI You can use an ALIAS statement of the linkage editor to provide the entry-point name.

Default routines exist in library *prefix*.SDSNLOAD. To use your routines instead, place your routines in library *prefix*.SDSNEXIT. You can use the installation job DSNTIJEX to assemble and link-edit the routines and place them in the new library. If you use any other library, you might need to change the STEPLIB or JOBLIB concatenations in the Db2 start-up procedures.

You can combine both routines into one CSECT and load module, but the module must include both entry points, DSN3@ATH and DSN3@SGN. Use standard assembler and linkage editor control statements to define the entry points. Db2 loads the module twice at startup, by issuing the z/OS LOAD macro first for entry point DSN3@ATH and then for entry point DSN3@SGN. However, because the routines are

reentrant, only one copy of each remains in virtual storage.

Related concepts

Connection routines and sign-on routines

Your Db2 subsystem has two exit points for authorization routines, one in connection processing and one in sign-on processing. Both exit points perform crucial steps in the assignment of values to primary IDs, secondary IDs, and SQL IDs.

Related reference

Processing of connection requests

A connection request makes a new connection to Db2; it does not reuse an application plan that is already allocated. Therefore, an essential step in processing the request is to check that the ID is authorized to use Db2 resources.

Processing of sign-on requests

Requests can come from IMS-dependent regions, CICS transaction subtasks, or RRS connections. For each of these types of requests, the initial primary ID is obtained immediately before a plan for the transaction is allocated. A new sign-on request can run the same plan without de-allocating and reallocating the plan.

Sample connection and sign-on routines

The sample Db2 exit routines are provided in the source code as members of prefix.SDSNSAMP.

Exit parameter list for connection and sign-on routines

The parameter list of connection and sign-on routines contains pointers to other information, such as the authorization ID list.

Sample connection and sign-on routines

The sample Db2 exit routines are provided in the source code as members of prefix.SDSNSAMP.

PSPI To examine the sample connection routine, list or assemble member DSN3SATH. To examine the sample sign-on routine, list or assemble member DSN3SSGN. You must use the High Level Assembler to assemble them.

Change required for some CICS users: You must change the sample sign-on exit routine (DSN3SSGN) before assembling and using it, if the following conditions are true:

- You attach to Db2 with an AUTH parameter other than AUTH=GROUP.
- You have the RACF list-of-groups option active.
- · You have transactions whose initial primary authorization ID is not defined to RACF

To change the sample sign-on exit routine (DSN3SSGN), perform the following steps:

1. Locate the following statement in DSN3SSGN as a reference point:

SSGN035	DS	ОН	BLANK	BACKSCAN	LOOP	REENTRY

2. Locate the following statement, which comes after the reference point:

B SSGN037 ENTIRE NAME IS BLANK, LEAVE

3. Replace the statement with the following statement:

SSGN090 NO GROUP NAME... BYPASS RACF CHECK

By changing the statement, you avoid an abend with SQLCODE -922. The routine with the new statement provides no secondary IDs unless you use AUTH=GROUP.

Related concepts

Connection routines and sign-on routines

в

Your Db2 subsystem has two exit points for authorization routines, one in connection processing and one in sign-on processing. Both exit points perform crucial steps in the assignment of values to primary IDs, secondary IDs, and SQL IDs.

Related tasks

Using sample connection and sign-on exit routines for CICS transactions

For a CICS transaction to use the sample connection or sign-on exit routines, the external security system, such as RACF, must be defined to CICS.

Specifying connection and sign-on routines

Your connection routine must have a CSECT name and entry point of DSN3@ATH. The name of the load module for the connection routine can be the same name, or it can be a different name. Your sign-on routine must have a CSECT name and entry point of DSN3@SGN. The name of the load module for the sign-on routine can be the same, or it can be a different name.

Debugging connection and sign-on routines

The diagnostic aids can assist you in debugging connection exit routines and sign-on exit routines.

Related reference

Processing of sign-on requests

Requests can come from IMS-dependent regions, CICS transaction subtasks, or RRS connections. For each of these types of requests, the initial primary ID is obtained immediately before a plan for the transaction is allocated. A new sign-on request can run the same plan without de-allocating and reallocating the plan.

When connection and sign-on routines are taken

Different local processes enter the access control procedure at different points, depending on the environment from which they originate. Different criteria apply to remote requests.

PSPI The following processes go through connection processing only:

- Requests that originate in TSO foreground and background (including online utilities and requests through the call attachment facility)
- JES-initiated batch jobs
- Requests through started task control address spaces (from the MVS START command)

The following processes go through connection processing, and can later go through the sign-on exit:

- The IMS control region
- The CICS recovery coordination task
- DL/I batch
- Requests through the Resource Recovery Services attachment facility (RRSAF)

The following processes go through sign-on processing:

- Requests from IMS-dependent regions (including MPP, BMP, and Fast Path)
- CICS transaction subtasks
- Scheduled tasks that are executed by the Db2 administrative task scheduler
 PSPI

Exit parameter list for connection and sign-on routines

The parameter list of connection and sign-on routines contains pointers to other information, such as the authorization ID list.

Regist	er 1 🔶			EXPL	
				Address of work area	
		Address of authorization ID list		Length of work area	Work area (8192 bytes)
		Pointer to session		Access return code	
		variable structure		Db2 subsystem name	
		\downarrow		Connection name	
	S	ession variable structure		Connection type	
	i I	Maximum number of entries n session variable array	6	Location name	
	Actual number of entries in session variable array Pointer to session variable array		LU name		
		Pointer to session		Network name	
		variable array		Db2 version ID	
	Authorization ID list			Extended location name address	 Extended
	Prima	ry ID			location name
	Contro	ol block information			
	SQL II)			
	Maxim ID ent	um number of secondary ries			
	Reserv	ved			
	ACEE	address of zero			
	Space (= max	for secondary ID list kimum * 8 bytes)			

PSPI The following diagram shows how the parameter list points to other information.

Figure 13. How a connection or sign-on parameter list points to other information

Connection routines and sign-on routines use 28 more bytes of the exit parameter list EXPL than other routines. The following table shows the entire list of connection routines and sign-on routines. The exit parameter list is described by macro DSNDEXPL.

Name	Hex offset	Data type	Description
EXPLWA	0	Address	Address of a 8192-byte work area to be used by the routine.
EXPLWL	4	Signed 4-byte integer	Length of the work area, in bytes; value is 8192.

Table 78. Exit parameter list for connection routines and sign-on routines

Table 78. Exit parameter list for connection routines and sign-on routines (continued)					
Name	Hex offset	Data type	Description		
EXPLRSV1	8	Signed 2-byte integer	Reserved.		
EXPLRC1	A	Signed 2-byte integer	Not used.		
EXPLRC2	С	Signed 4-byte integer	Not used.		
EXPLARC	10	Signed 4-byte integer	Access return code. Values can be: Access allowed; Db2 continues processing. Access denied; Db2 terminates processing with an error.		
EXPLSSNM	14	Character, 8 bytes	Db2 subsystem name, left justified; for example, 'DSN '.		
EXPLCONN	1C	Character, 8 bytes	Connection name for requesting location.		
EXPLTYPE	24	Character, 8 bytes	Connection type for requesting location. For DDF/ REST threads, the connection type is 'REST '.		
EXPLSITE	2C	Character, 16 bytes	For SNA protocols, this is the location name of the requesting location or <i><luname></luname></i> . For TCP/IP protocols, this is the dotted decimal IP address of the requester. If the value of EXPLSITE_OFF is not 0, EXPLSITE is not used.		
EXPLLUNM	3C	Character, 8 bytes	For SNA protocols, this is the locally known LU name of the requesting location. For TCP/IP protocols, this is the character string 'TCPIP'.		
EXPLNTID	44	Character, 17 bytes	For SNA protocols, the fully qualified network name of the requesting location. For TCP/IP protocols, this field is reserved.		
EXPLVIDS	55	Character, 1 byte	Db2 version identifier		
EXPLSITE_OFF	56	Signed 2-byte integer	Offset from the beginning of the work area to the extended location name of the Db2 site that originated the work request. Use this value if the location name is greater than 16 bytes. The extended location name has the following format:		
			 Signed, 2-byte integer: Length of the extended location name Character, 128 bytes: Extended location name 		

Table 70 Fuit lict fo tic +: -d cic tir (0 tin

PSPI

Related concepts

Connection routines and sign-on routines

Your Db2 subsystem has two exit points for authorization routines, one in connection processing and one in sign-on processing. Both exit points perform crucial steps in the assignment of values to primary IDs, secondary IDs, and SQL IDs.

Related tasks

Using sample connection and sign-on exit routines for CICS transactions For a CICS transaction to use the sample connection or sign-on exit routines, the external security system, such as RACF, must be defined to CICS.

Specifying connection and sign-on routines

Your connection routine must have a CSECT name and entry point of DSN3@ATH. The name of the load module for the connection routine can be the same name, or it can be a different name. Your sign-on routine must have a CSECT name and entry point of DSN3@SGN. The name of the load module for the sign-on routine can be the same, or it can be a different name.

Debugging connection and sign-on routines

The diagnostic aids can assist you in debugging connection exit routines and sign-on exit routines.

Related reference

Processing of sign-on requests

Requests can come from IMS-dependent regions, CICS transaction subtasks, or RRS connections. For each of these types of requests, the initial primary ID is obtained immediately before a plan for the transaction is allocated. A new sign-on request can run the same plan without de-allocating and reallocating the plan.

Authorization ID parameter list for connection and sign-on routines

An authorization ID list contains information that is specific to connection routines and sign-on routines.

The following table includes the authorization ID list for a connection or sign-on exit routine.

Table 79. Authorization ID list for a connection or sign-on exit routine					
Name	Hex offset	Data type	Description		
AIDLPRIM	0	Character, 8 bytes	Primary authorization ID for input and output; see descriptions in the text.		
AIDLCODE	8	Character, 2 bytes	Control block identifier.		
AIDLTLEN	А	Signed 2-byte integer	Total length of control block.		
AIDLEYE	С	Character, 4 bytes	Eyecatcher for block, "AIDL".		
AIDLSQL	10	Character, 8 bytes	On output, the current SQL ID.		
AIDLSCNT	18	Signed 4-byte integer	Number of entries allocated to secondary authorization ID list. Always equal to 1012.		
AIDLSAPM	1C	Address	For a sign-on routine only, the address of an 8- character additional authorization ID. If RACF is active, the ID is the user ID's connected group name. If the address was not provided, the field contains zero.		
AIDLCKEY	20	Character, 1 byte	Storage key of the ID pointed to by AIDLSAPM. To move that ID, use the "move with key" (MVCK) instruction, specifying this key.		
AIDLRSV1	21	Character, 3 bytes	Reserved		

PSPI
Table 79. Authorization ID list for a connection or sign-on exit routine (continued)							
Name	Hex offset	Data type	Description				
AIDLRSV2	24	Signed 4-byte integer	Reserved				
AIDLACEE	28	Signed 4-byte integer	The address of the ACEE structure, if known; otherwise, zero				
AIDLRACL	2C	Signed 4-byte integer	Length of data area returned by RACF, plus 4 bytes				
AIDLRACR	30	26 bytes	Reserved				
AIDLSEC	4A	Character, maximum x 8 bytes	List of the secondary authorization IDs, 8 bytes each				

PSPI

Input values for connection routines

A connection routine can have different input values.

The input values for a connection routine include the following:

• **PSPI** The initial primary authorization ID for a local request can be obtained from the z/OS address space extension block (ASXB).

The ASXB contains at most only a seven-character value. That is always sufficient for a TSO user ID or a user ID from an z/OS JOB statement, and the ASXB is always used for those cases.

For CICS, IMS, or other started tasks, z/OS can also pass an eight-character ID. If an eight-character ID is available, and if its first seven characters agree with the ASXB value, then Db2 uses the eight-character ID. Otherwise it uses the ASXB value.

If RACF is active, the field used contains a verified RACF user ID; otherwise, it contains blanks.

- The primary ID for a remote request is the ID passed in the conversation attach request header (SNA FMH5) or in the DRDA SECCHK command.
- The SQL ID contains blanks.
- The list of secondary IDs contains blanks.

Input values for sign-on routines

A sign-on routine can have different input values.

The input values for a sign-on routine are as follows:

- **PSPI** The initial primary ID depends on the sign-on method.
- The SQL ID and all secondary IDs contain blanks.
- Field AIDLSAPM in the authorization ID list can contain the address of an 8-character additional authorization ID, obtained by the CICS attachment facility using the RACROUTE REQUEST=EXTRACT service with the requester's user ID. If RACF is active, this ID is the RACF-connected group name from the ACEE corresponding to the requester's user ID. Otherwise, this field contains blanks. IMS does not pass this parameter.
- Field AIDLCKEY contains the storage key of the identifier pointed to by AIDLSAPM. To move that ID, use the "move with key" (MVCK) instruction, specifying this key.
- Field AIDLACEE contains the ACEE address only for a sign-on through the CICS attachment facility and only when the CICS RCT uses AUTH=GROUP.

Expected output for connection and sign-on routines

Db2 uses the output values of the primary ID, the SQL ID, and the secondary IDs. Your routines can set these IDs to any value that is an SQL short identifier.

PSPL If your identifier does not meet the 8-character criteria, the request fails. Therefore, when necessary, add blanks to the end of short identifiers to ensure that they meet the criteria.

If the values that are returned are not blank, Db2 interprets them in the following ways:

- The primary ID becomes the primary authorization ID.
- The list of secondary IDs, down to the first blank entry or to a maximum of 1012 entries, becomes the list of secondary authorization IDs. The space allocated for the secondary ID list is only large enough to contain the maximum number of authorization IDs. This number is in field AIDLSCNT.

Important: If you allow more than 1012 secondary authorization IDs, abends and storage overlays can occur.

• The SQL ID is checked to see if it is the same as the primary or one of the secondary IDs. If it is not, the connection or sign-on process fails. Otherwise, the validated ID becomes the current SQL ID.

If the returned value of the primary ID is blank, Db2 takes the following steps:

- In connection processing, the default ID that is defined when Db2 is installed (UNKNOWN AUTHID on panel DSNTIPP) is substituted as the primary authorization ID and the current SQL ID. The list of secondary IDs is set to blanks.
- Sign-on processing abends. No default value exists for the primary ID.

If the returned value of the SQL ID is blank, Db2 makes it equal to the value of the primary ID. If the list of secondary IDs is blank, it remains blank. No default secondary IDs exist.

Your routine must also set a return code in word 5 of the exit parameter list to allow or deny access (field EXPLARC). By those means you can deny the connection altogether. The code must have one of the values that are shown in Table 80 on page 276.

Table 80. Required return code in EXPLARC					
Value	Meaning				
0	Access allowed; continue processing.				
12	Access denied; terminate.				

Any other value will cause an abend.

Processing in sample connection and sign-on routines

The sample routines that are provided by IBM can serve as models for the processing that is required in connection routines and sign-on routines.

PSPI Recommendation: Consider using the sample routines as a starting point when you write your own routines.

Both the sample connection routine (DSN3SATH) and the sample sign-on routine have similar sections for setup, constants, and storage areas. Both routines set values of the primary ID, the SQL ID, and the secondary IDs in three numbered sections.

In the sample connection routine (DSN3SATH): The three sections of the sample connection routine perform the following functions:

Section 1

Section 1 provides the same function as in the default connection routine. It determines whether the first character of the input primary ID has a value that is greater than blank (hex 40), and performs the following operations:

- If the first character is greater than hex 40, the value is not changed.
- If the first character is not greater than hex 40, the value is set according to the following rules:
 - If the request is from a TSO foreground address space, the primary ID is set to the logon ID.
 - If the request is not from a TSO foreground address space, the primary ID is set to the job user ID from the JES job control table.
 - If no primary ID is located, Section 2 is bypassed.

Section 2

At the beginning of Section 2, you can restore one commented-out instruction, which then truncates the primary authorization ID to 7 characters. (The instruction is identified by comments in the code.)

Section 2 next tests RACF options and makes the following changes in the list of secondary IDs, which is initially blank:

- If RACF is not active, the list remains blank.
- If the list of groups option is not active, but an ACEE exists, the connected group name is copied as the only secondary ID. The source of the ACEE is one of the following:
 - An ACEE that is passed by the caller
 - The address-space-level ACEE
 - The task-level ACEE if the connection is for batch utilities.
- If the list of groups option is active, the list of group names from the ICHPCGRP block is copied into AIDLSEC in the authorization ID list.

Section 3

Section 3 performs the following steps:

- 1. The SQL ID is set equal to the primary ID.
- 2. If the TSO data set name prefix is a valid primary or secondary ID, the SQL ID is replaced with the TSO data set name prefix. Otherwise, the SQL ID remains set to the primary ID.

In the sample sign-on routine (DSN3SSGN): The three sections of the sample sign-on routine perform the following functions:

Section 1

Section 1 does not change the primary ID.

Section 2

Section 2 sets the SQL ID to the value of the primary ID.

Section 3

Section 3 tests RACF options and makes the following changes in the list of secondary IDs, which is initially blank:

- If RACF is not active, the list remains blank.
- If the list of groups option is active, section 3 attempts to find an existing ACEE from which to copy the authorization ID list.
 - If AIDLACEE contains a valid ACEE, it is used.

Otherwise, look for a valid ACEE chained from the TCB or from the ASXB or, if no usable ACEE exists, issue RACROUTE to have RACF build an ACEE structure for the primary ID.

Copy the list of group names from the ACEE structure into the secondary authorization list.

- If the exit issued RACROUTE to build an ACEE, another RACROUTE macro is issued and the structure is deleted.
- If a list of secondary authorization IDs has not been built, and AIDLSAPM is not zero, the data that is pointed to by AIDLSAPM is copied into AIDLSEC.

Performance considerations for connection and sign-on routines

Your sign-on exit routine is part of the critical path for transaction processing in IMS and CICS. Therefore, try to execute as quickly as possible.

About this task

Avoid writing SVC calls like GETMAIN, FREEMAIN, and ATTACH. Also avoid I/O operations to any data set or database. To improve performance, you might be able to delete the list of groups that process in Section 3 of the sample sign-on exit routine.

The sample sign-on exit routine can issue the RACF RACROUTE macro with the default option SMC=YES. If another product issues RACROUTE with SMC=NO, a deadlock might occur.

Your routine can also enhance the performance of later authorization checking. Authorization for dynamic SQL statements is checked first for the CURRENT SQLID, then for the primary authorization ID, and then for the secondary authorization IDs. If you know that a user's privilege most often comes from a secondary authorization ID, then set the CURRENT SQLID to this secondary ID within your exit routine.

Related concepts

General guidelines for writing exit routines (Db2 Administration Guide)

Debugging connection and sign-on routines

The diagnostic aids can assist you in debugging connection exit routines and sign-on exit routines.

About this task

PSPI Subsystem support identify recovery: The identify ESTAE recovery routine, DSN3IDES, generates the following VRADATA entries. The last entry, key VRAIMO, is generated only if the abend occurred within the connection exit routine.

Table 81. VR	Table 81. VRADATA entries that are generated by DSN3IDES					
VRA keyname	Key hex value	Data length	Content			
VRAFPI	22	8	Constant 'IDESTRAK'			
VRAFP	23	24	 32-bit recovery tracking flags 32-bit integer AGNT block unique identifier AGNT block address AIDL block address Initial primary authorization ID as copied from ASXBUSER or ASXBUSR8 			
VRAIMO	7C	10	 Connection exit load module load point address Connection exit entry point address Offset of failing address in the PSW from the connection exit entry point address 			

Subsystem support sign-on recovery: The sign-on ESTAE recovery routine DSN3SIES generates the following VRADATA entries. The last entry, key VRAIMO, is generated only if the abend occurred within the sign-on exit routine.

Table 82. VRADATA entries that are generated by DSN3SIES

VRA keyname	Key hex value	Data length	Content
VRAFPI	22	8	Constant 'SIESTRAK'
VRAFP	23	20	 Primary authorization ID (CCBUSER) AGNT block address Identify-level CCB block address Sign-on-level CCB block address
VRAIMO	7C	10	 Sign-on exit load module load point address Sign-on exit entry point address Offset of failing address in the PSW from the sign-on exit entry point address

Diagnostics for connection exit routines and sign-on exit routines: The connection (identify) recovery routine and the sign-on recovery routine provide diagnostics for the corresponding exit routines. The diagnostics are produced only when the abend occurs in the exit routine. The following diagnostics are available:

Dump title

The component failing module name is "DSN3@ATH" for a connection exit or "DSN3@SGN" for a sign-on exit.

z/OS and RETAIN symptom data

SDWA symptom data fields SDWACSCT (CSECT/) and SDWAMODN (MOD/) are set to "DSN3@ATH" or "DSN3@SGN", as appropriate.

Summary dump additions

The AIDL, if addressable, and the SADL, if present, are included in the summary dump for the failing allied agent. If the failure occurred in connection or sign-on processing, the exit parameter list (EXPL) is also included. If the failure occurred in the system services address space, the entire SADL storage

pool is included in the summary dump.

Related concepts

Connection routines and sign-on routines

Your Db2 subsystem has two exit points for authorization routines, one in connection processing and one in sign-on processing. Both exit points perform crucial steps in the assignment of values to primary IDs, secondary IDs, and SQL IDs.

Related reference

Processing of connection requests

A connection request makes a new connection to Db2; it does not reuse an application plan that is already allocated. Therefore, an essential step in processing the request is to check that the ID is authorized to use Db2 resources.

Processing of sign-on requests

Requests can come from IMS-dependent regions, CICS transaction subtasks, or RRS connections. For each of these types of requests, the initial primary ID is obtained immediately before a plan for the transaction is allocated. A new sign-on request can run the same plan without de-allocating and reallocating the plan.

Sample connection and sign-on routines

The sample Db2 exit routines are provided in the source code as members of prefix.SDSNSAMP.

Exit parameter list for connection and sign-on routines

The parameter list of connection and sign-on routines contains pointers to other information, such as the authorization ID list.

Session variables in connection and sign-on routines

Db2 supplies default session variables and the connection exit routine and the sign-on exit routine support up to 10 more session variables.

PSPI You can define the additional session variables and use them to provide information to applications by using the GETVARIABLE function. For more information, see <u>GETVARIABLE scalar</u> function (Db2 SQL)

The session variable structure

The connection exit routine and the sign-on exit routine point to the session variable structure (DSNDSVS). DSNDSVS specifies the maximum number of entries in the session array, the actual number of entries in the session array, and a pointer to the session variable array. The default value for the actual number of session variables is zero.

Defining session variables

To define session variables, use the session variable array (DSNDSVA) to list up to 10 session variables as name and value pairs. The session variables that you establish in the connection exit routine and the sign-on exit routine are defined in the SESSION schema. The values that the exit routine supplies in the session variable array replace the previous values.

Example

For example, the following session variable array lists six session variables.

Table 83. Sample session variable array					
Name	Value				
default_database	DATAXM				
default_driver	PZN4Y7				
location	Kyoto				
member_of	GROUP_42				
filename	report.txt				
account_number	A1-X142783				

The unqualified names are defined as VARCHAR(128), and the values are defined as VARCHAR(255). The exit routines must provide these values in Unicode CCSID 1208.

Related concepts Session variables (Db2 SQL) Related reference Built-in session variables (Db2 SQL)

Access control authorization exit routine

You can provide your own access control authorization exit routine by using an exit point that Db2 provides. Alternatively, after you carefully consider several important factors, you might choose to let RACF perform Db2 authorization checking for you.

PSPI

Is the access control authorization exit routine right for you?

Using the RACF (Security Server for z/OS) to perform access control is not the best choice for every customer. Consider the following points before choosing RACF to perform access control:

- If you want the database administrators to manage security, integration with Db2 is very important. Using RACF access control provides less integration with Db2. In most of these cases, Db2 authorization provides advantages.
- If you want security administrators to manage security, integration with the security server is more important. In most of these cases, using RACF for access control provides advantages. Furthermore, if you want a security group to define authorization and a centralized security control point, RACF access control is an excellent match.

If you change from Db2 authorization to RACF access control, you must change to RACF methods for some authorization techniques, and you must understand how Db2 and RACF work together. Expect to make the following changes when you implement RACF access control:

- Plan to use RACF facilities (such as groups and patterns) more.
- Plan to use patterns instead of individual item access profiles and permissions.
- Plan to use Db2 roles, RACF groups, or both, instead of secondary authorization IDs, which are not implemented in RACF. OWNER generally must be a valid group or a Db2 role.
- Plan to use Db2 roles for BINDAGENT processing or set the AUTHEXIT_CHECK subsystem parameter DB2. BINDAGENT based on secondary authorizations IDs is not implemented in RACF.
- Understand how SET CURRENT SQLID works with RACF. SET CURRENT SQLID can set a qualifier, but does not change authorization.
- Know that authorizations are not dropped when objects are dropped or renamed.
- Be aware of the relationship between objects and revoked privileges. Packages are not invalidated when authorizations are revoked. Views are not dropped when authorizations are revoked.

An alternative is to set the AUTHEXIT_CHECK system parameter to DB2. With that setting in effect, Db2 provides the ACEE of the package or plan owner to perform authorization checking during the processing of the autobind, BIND, REBIND PACKAGE, and REBIND PLAN commands and, if needed, the execution of the package or plan. Db2 also provides the ACEE of the authorization ID as determined by the DYNAMICRULES option to perform dynamic SQL authorization checking at run time. The access control authorization exit uses the ACEE for XAPLUCHK for authorization checking. The XAPLUCHK authorization ID can be a user or a group in RACF. To ensure successful authorization checks with the owner ACEE, the owner authorization ID in XAPLUCHK must be permitted access to the resources in RACF.

How the access control authorization routine works

Your routine specifies whether the authorization checking should all be done by RACF only, or by both RACF and Db2. (Also, the routine can be called and still let all checking be performed by Db2.)

When Db2 invokes the routine, it passes three possible functions to the routine:

- Initialization (Db2 startup)
- Authorization check
- Termination (Db2 shutdown)

The bulk of the work in the routine is for authorization checking. When Db2 must determine the authorization for a privilege, it invokes your routine. The routine determines the authorization for the privilege and then indicates to Db2 whether the privilege is authorized or not authorized, or whether Db2 should do its own authorization check, instead.

When you write an access control authorization routine, use the general guidelines for writing exit routines, with the following exceptions to the environment description:

• The routine executes in non-cross-memory mode during initialization and termination (XAPLFUNC of 1 or 3).

• During authorization checking, the routine can execute under a TCB or SRB in cross-memory or noncross-memory mode.

Bypass of the access control authorization routine

In the following situations, the access control authorization routine is not called to check authorization:

• The authorization ID that Db2 uses to determine access has installation SYSADM or installation SYSOPR authority (where installation SYSOPR authority is sufficient to authorize the request). This authorization check is made strictly within Db2. For example, if the execute privilege is being checked on a package, Db2 performs the check on the plan owner that this package is in. If the plan owner has installation SYSADM, the routine is not called.

The RACF access control module is called for any additional authorization checks that are done as part of a process, if those checks are done on behalf of another user or role that does not have installation SYSADM or installation SYSOPR authority. An example of such a process is revoking of dependent privileges.

- Db2 security has been disabled. (You can disable Db2 security by specifying NO on the USE PROTECTION field of installation panel DSNTIPP).
- Authorization has been cached from a prior check.
- In a prior invocation of the exit routine, the routine indicated that it should not be called again.
- GRANT statements.

The routine executes in the database services address space (*ssnm*DBM1) of Db2.

PSPI

Related concepts

General guidelines for writing exit routines (Db2 Administration Guide)

Access control external to Db2

You can control access to Db2 by using a Db2-supplied exit routine or an exit routine that you write.

Introduction to the RACF access control module (RACF Access Control Module Guide)

Related reference

Parameter list for access control authorization routines

The parameter list of access control authorization routines contains pointers to other information, such as the work area and the authorization ID list.

Specifying the access control authorization routine

Your access control authorization routine must have a CSECT name and an entry point of DSNX@XAC. The load module name or alias name must also be DSNX@XAC. A default routine with this name and entry point exists in library *prefix*.SDSNLOAD.

About this task

PSPI To use your routine instead of the default routine, place it in the *prefix*.SDSNEXIT library. Use installation job DSNTIJEX to assemble and link-edit the routine and to place it in the *prefix*.SDSNEXIT library. If you use any other library, you might need to change the STEPLIB or JOBLIB concatenations in the Db2 start-up procedures.

The source code for the default routine is in *prefix*.SDSNSAMP as DSNXSXAC. You can use it to write your own exit routine. To assemble it, you must use the High Level Assembler.

RACF provides a sample exit routine DSNXRXAC, which is shipped with Db2. It can be found in *prefix*.SDSNSAMP.

The default access control authorization routine

The default exit routine returns a code to the Db2 authorization module. The code indicates that a userdefined access control authorization exit routine is not available. Db2 then performs normal authorization checking and does not attempt to invoke this exit routine again.

When access control authorization routine is taken

Db2 can take the access control authorization routine when it starts up, shuts down, or performs an authorization check on a privilege.

PSPI The access control authorization routine is taken in the following three instances:

At Db2 startup

This exit routine is taken when Db2 starts to allow the external authorization checking application to perform any required setup prior to authorization checking. For example, loading authorization profiles into storage is a required setup task. Db2 uses the reason code that the exit routine sets during startup to determine how to handle exception situations.

When an authorization check is to be performed on a privilege

This exit routine is taken when Db2 accesses security tables in the catalog to check authorization on a privilege. The exit routine is taken only if none of the prior invocations have indicated that the exit routine must not be called again.

At Db2 shutdown

This exit routine is taken when Db2 is stopping, to let the external authorization checking application perform its cleanup before Db2 stops.

PSPI

Considerations for the access control authorization routine

You need to take additional factors into consideration when you use the access control authorization exit routine.

After a privilege is granted, the authorization information is cached for faster re-checking. If the AUTHEXIT_CACHEREFRESH system parameter is specified and RACF commands are issued with generic character ** or * in the resource names, the entire authorization cache for the corresponding class being revoked might be refreshed. In this case, the performance of authorization checking might be impacted until the cache is successfully rebuilt.

Related reference

AUTH EXIT CACHE REFR (AUTHEXIT_CACHEREFRESH subsystem parameter) (Db2 Installation and Migration)

When Db2 cannot provide an ACEE

Sometimes Db2 cannot provide an ACEE. This happens, for example, when you do not use external security in CICS and CICS does not pass an ACEE to the CICS attachment facility.

PSPI When Db2 does not have an ACEE, it passes zeros in the XAPLACEE field. If this happens, your routine can return a 4 in the EXPLRC1 field, and let Db2 handle the authorization check.

Db2 does not pass the ACEE address for IMS transactions. The ACEE address is passed for CICS transactions, if available.

Db2 does pass the ACEE address when it is available for Db2 commands that are issued from a logged on z/OS console. Db2 does not pass the ACEE address for Db2 commands that are issued from a console that is not logged on, or for the START DB2 command, or commands issued automatically during Db2 startup.

An ACEE is available to Db2 for an IMS transaction if IMS is configured to use either APPC/OTMA security full or the IMS Build Security Environment exit (DFSBSEX0). You need to code DFSBSEX0 to return RC4 in

register 15, which will instruct IMS to create the ACEE in the dependent region.

Authorization IDs and ACEEs

XAPL has two authorization ID fields, XAPLUPRM (the primary authorization ID) and XAPLUCHK (the authorization ID that Db2 uses to perform the authorization). These two fields might have different values.

PSPI The ACEE passed in XAPLACEE is that of the primary authorization ID, XAPLUPRM. If XAPLOWAC is on, the ACEE passed in XAPLACEE is that of the authorization ID that Db2 uses to perform the authorization, XAPLUCHK.

The implications of the XAPLUPRM and XAPLUCHK relationship need to be clearly understood. XAPLUCHK, the authorization ID that Db2 uses to perform authorization may be the primary authorization ID (XAPLUPRM), a secondary authorization ID, or another authorization ID such as a package owner.

If the RACF access control module is used, the following rules apply:

• RACF uses the ACEE of the primary authorization ID (XAPLUPRM) or the owner ID (XAPLUCHK) to perform authorization. The ACEE of the XAPLUCHK ID is used when the AUTHEXIT_CHECK subsystem parameter is set to DB2.

To ensure successful authorization checks with the owner ACEE, the owner authorization ID in XAPLUCHK must be permitted access to the resources in RACF. If the owner is a group in RACF, you need to permit the group access to the resource associated with the connection in the RACF DSNR class. For example, if the group access is from a batch application, you can issue the following PERMIT command to grant a group access to subsystem.BATCH or subsystem.* in the DSNR class:

PERMIT DSN.BATCH CLASS(DSNR) ID(DB2GRP) ACCESS(READ)
PERMIT DSN.* CLASS(DSNR) ID(DB2GRP) ACCESS(READ)

• Secondary authorization IDs are not implemented in RACF. Db2 roles or RACF groups should be used instead.

Examples

The following examples show how the rules apply:

- A package may be bound successfully by using the privileges of the binder (XAPLUPRM). Then only the EXECUTE privilege on the package is needed to execute it. If at some point this package is marked invalid (for instance, if a table it depends upon is dropped and re-created), the next execution of it will cause an autobind, which will usually fail. In this case, autobind checks the runner for the necessary authorization, but the runner does not have the required privileges for a successful rebind. However, if the owner of the package is a Db2 role, and the role has the necessary authorization, autobind will succeed. Or, if the AUTHEXIT_CHECK subsystem parameter is set to DB2, RACF checks the owner of the package (XAPLUCHK) for the necessary privileges, and autobind will succeed.
- If the OWNER on the BIND command is based on secondary authorization IDs, RACF groups should be used instead. Secondary authorization IDs are not supported by RACF.
- SET CURRENT SQLID can set a qualifier, but it cannot change authorization.
- The DYNAMICRULES settings have a limited effect on which authorization ID is checked. Only the primary authorization ID and secondary IDs that are valid RACF groups for this user are considered. For dynamic statements with the DYNAMICRULES(BIND) option to work, for example, the package owner must be the primary authorization ID or one of the RACF groups of the user who executes the statements.

However, the DYNAMICRULES settings will have the effect that you want on which authorization is checked if the authorization is based on a Db2 role or if the AUTHEXIT_CHECK subsystem parameter is set to DB2. For example, using a Db2 role, the dynamic statements with the DYNAMICRULES(BIND) option will work if a Db2 role is the owner of a plan or package or the definer of a stored procedure. If the AUTHEXIT_CHECK subsystem parameter is set to DB2, the dynamic statements with the DYNAMICRULES(BIND) option will work.

• The PKLIST bind option, location-name, or collection-ID value of an asterisk (*) can defer the authorization check until run time. At runtime, the runner is checked for the necessary authorization.

If the AUTHEXIT_CHECK subsystem parameter is set to DB2, the owner of the package or plan (XAPLUCHK) is checked for the necessary privileges.

• User-defined function and stored procedure authorizations involve several authorization IDs, such as implementer, definer, invoker, and so forth. Only the primary authorization ID and secondary IDs that are Db2 roles or RACF groups are considered. If the AUTHEXIT_CHECK subsystem parameter is set to DB2, the user-defined function and stored procedure authorizations that involve various authorization IDs will work.

Db2 processing of ENF signals

When the AUTHEXIT_CACHEREFRESH system parameter is set to ALL and when Db2 and the access control authorization exit are active, Db2 listens to type 62, type 71, and type 79 ENF signals from RACF for any user profile or resource access changes. If Db2 receives ENF 62, 71, and 79 signals, it refreshes the cache entries of the package authorization, the routine authorization, the DDF user authentication, and the dynamic statement.

PSPI RACF issues the ENF 71 signal for any change to a RACF user or group profile. Db2 listens to the ENF 71 signal when you use the following RACF commands or macros:

- ALTUSER command with the REVOKE option
- CONNECT command with the REVOKE option
- DELUSER command (to delete a user from RACF)
- DELGROUP command (to delete a group and its relationship with its parent group from RACF)
- REMOVE command (to remove a user from a group)
- RACROUTE REQUEST=VERIFY macro (to revoke a user due to excessive invalid password attempts)

RACF issues the ENF 79 signal for any change to a RACF user's or group's authorization to resources. Db2 listens to the ENF 79 signal when you use the following RACF commands:

- PERMIT with the DELETE, ACCESS(NONE), RESET, or WHEN(CRITERIA(SQLROLE ...)) option
- RALTER with the UACC(NONE) or DELMEM option
- RDELETE

When the ENF 79 signal is issued, Db2 caches the resource changes first and refreshes the cache entries only after the SETROPTS RACLIST REFRESH command is issued. RACF issues the ENF 62 signal when the SETROPTS RACLIST REFRESH command is used. Upon receiving the ENF 62 signal, Db2 refreshes the cache entries for the resources that are cached during ENF 79 notification. However, Db2 does not refresh the cache entries when the RDELETE command is used to delete general resource profiles for DSNADM and MDSNSM/GDSNSM classes without a profile name.

The ENF 79 signal is issued only for resource classes that are defined in the RACF Class Descriptor Table with the SIGNAL=YES option. The SIGNAL=YES option is enabled, by default, for the following IBM-supplied RACF resource classes for Db2:

- MDSNPK / GDSNPK
- MDSNTB / GDSNTB
- MDSNSP / GDSNSP
- MDSNSQ / GDSNSQ
- DSNADM and MDSNSM / GDSNSM
- MDSNUF / GDSNUF
- MDSNGV / GDSNGV

If you define RACF classes for Db2 objects and administrative authorities without using IBM-supplied RACF resource classes, you need to enable the SIGNAL=YES option for these classes in the RACF Class Descriptor Table. Class names for Db2 objects in both single-subsystem scope and multiple-subsystem scope are supported.

Profile names with discrete and generic resource characters are supported with the following restrictions:

- Generic character ampersand (&) indicates that RACF uses a profile in the RACFVARS class to determine the actual values for that part of the profile name. Db2 ignores a RACF profile that contains the & character and does not perform cache refresh for the profile.
- Generic character % is not supported in the privilege part of the profile name for cache refresh. Db2 ignores a RACF profile that contains the % character in the privilege part and does not perform cache refresh for the profile.
- If a profile name for classes other than DSNADM contains generic character * or ** and has parts few than what the CLASS parameter supports, all objects or all privileges or both for the specified CLASS parameter may be considered for cache refresh. For example, if you issue the PERMIT SYS1.** ID(USER01) DELETE CLASS(MDSNPK) command, Db2 deletes the entries in the package authorization cache for user USER01. If you issue the PERMIT SYS1.**.GV* ID(*) DELETE CLASS(MDSNGV) command, Db2 deletes the entries in the dynamic statement cache for object type global variables where the schema name starts with GV. If you issue the PERMIT SYS1.TSCH.**.VNAM.* ID(USER03) DELETE CLASS(MDSNTB) command, Db2 deletes the entries in the dynamic statement cache for object type global variables where the schema is TSCH for user USER03. It also deletes the entries where the schema is VNAM for user USER03.
- The generic character * is not supported when it is specified as an authorization ID in ID(*) for revoking the DSNADM class authority or the MDSNSM class for the SQLADM authority. Db2 ignores the authorization ID and does not perform cache refresh for the authorization ID. When ID(*authorization-id*) is specified, Db2 deletes all the entries in the caches for the specified authorization ID.

Db2 caches the RACF group in the following cases, when subsystem parameter AUTHEXIT_CHECK is set to DB2:

- For dynamic SQL statements, when the package owner is a RACF group, and the DYNAMICRULES bind option is set to a value that results in bind behavior.
- When the plan owner for a package that has the EXECUTE privilege is a RACF group.

In all other cases, Db2 caches the primary authorization ID that is associated with the RACF group when access is allowed from the group. If a privilege is revoked from the group, Db2 might not delete the cache entries for all users that are associated with the group. You need to explicitly permit the required privilege to users that are associated with the group, and then delete the permissions in RACF.

PSPI

Related reference

Invalid and inoperative packages

In Db2, when a privilege that is required by a package is revoked, the package is invalidated. Db2 can automatically rebind an invalidated package if proper privileges are granted.

AUTH EXIT CACHE REFR (AUTHEXIT_CACHEREFRESH subsystem parameter) (Db2 Installation and Migration)

Invalid and inoperative packages

In Db2, when a privilege that is required by a package is revoked, the package is invalidated. Db2 can automatically rebind an invalidated package if proper privileges are granted.

PSPI If the revoked privilege is the EXECUTE privilege on a user-defined function, Db2 marks the package inoperative, instead of invalid; you will need to manually rebind the inoperative package.

If a privilege that the package depends on is revoked, and if you want to invalidate the package or make it inoperative, you must use the SQL GRANT statement to grant the revoked privilege and then use the SQL REVOKE statement to revoke it. If you remove any object privilege from a user that is used to bind a package, you also need to revoke the EXECUTE privilege that the user has on the associated package. This prevents the user from accessing the package.

If you use an authorization access control routine, the exit routine does not have the ability to tell Db2 that a privilege is revoked. In this case, Db2 does not know that it needs to invalidate the package.

If you set the AUTHEXIT_CACHEREFRESH subsystem parameter to ALL and when the user profile or resource access is changed in RACF, Db2 refreshes the cache entries of the package authorization, the routine authorization, and the dynamic statement. Db2 also checks for static package dependency and invalidates the package when one of the following resource class permissions is removed from the user:

- INSERT, UPDATE, DELETE, SELECT on a table
- USAGE on a sequence
- EXECUTE on a stored procedure
- EXECUTE on an UDF (Dependent packages are marked inoperative.)
- READ, WRITE on a global variable.

If EXECUTE on a package is revoked from the user, Db2 will check for plan dependency and invalidates the plan.

A package can be invalidated only when Db2 is active during ENF notification and if the name of the affected RACF profile contains discrete characters. ENF notification ignores a profile if it is associated with the DSNADM class or if its name contains any generic characters (*, **, &, %). If the package owner is a user (not a RACF group) and if the user is associated with a group that had the required privileges when the package was bound, you need to explicitly permit the user all the privileges required for invalidating the package and then delete the permissions in RACF.

PSPI

Related concepts

Changes that invalidate packages (Db2 Application programming and SQL)

Related tasks

Identifying packages with characteristics that affect performance, concurrency, or the ability to run (Db2 Performance)

Related reference

Explicit package privileges You can explicitly grant privileges on packages.

GRANT statement (Db2 SQL)

REVOKE statement (Db2 SQL)

Related information

00E30305 (Db2 Codes)

Automatic rebind authorization

If you execute a package that is marked invalid, Db2 attempts to rebind it. If the package contains static SQL statements, Db2 checks the owner for the required authorization for a successful rebind.

PSPI If RACF access control is used, the owner of the plan or package must be a Db2 role for the automatic rebind to complete successfully.

AUTHEXIT_CHECK subsystem parameter

An alternative is to set the AUTHEXIT_CHECK system parameter to DB2. With that setting in effect, Db2 provides the ACEE of the package owner to perform authorization checking when processing autobinds or BIND and REBIND commands. Db2 provides the ACEE of the authorization ID as determined by the DYNAMICRULES option to perform dynamic SQL authorization checking. The access control authorization exit uses the ACEE for XAPLUCHK for authorization checking. The XAPLUCHK authorization ID can be a user or a group in RACF. To ensure successful authorization checks with the owner ACEE, the owner

authorization ID in XAPLUCHK must be permitted access to the resources in RACF.

Related concepts

Automatic rebinds (Db2 Application programming and SQL)

Related reference

AUTH EXIT CHECK (AUTHEXIT_CHECK subsystem parameter) (Db2 Installation and Migration) DYNAMICRULES bind option (Db2 Commands)

DYNAMICRULES(BIND) option authorization

The DYNAMICRULES(BIND) option provides the flexibility for you to specify the owner of a plan or a package that Db2 checks for the required authorization for dynamic SQL statements.

PSPI Because RACF does not support secondary IDs, you can use Db2 roles to exploit this flexibility. To use Db2 roles with the DYNAMICRULES(BIND) option, the owner of the plan or package must be a Db2 role. Similarly, for the define and invoke behavior of the DYNAMICRULES BIND options, the definer or invoker must be a Db2 role. In order to make the owner of the plan, package, or stored procedure a Db2 role, you need to create the plan, package, or stored procedure in a trusted context that is defined with the ROLE AS OBJECT OWNER AND QUALIFIER clause.

AUTHEXIT_CHECK subsystem parameter

An alternative is to set the AUTHEXIT_CHECK system parameter to DB2. With that setting in effect, Db2 provides the ACEE of the package owner to perform authorization checking when processing the autobind, BIND and REBIND commands. Db2 provides the ACEE of the authorization ID as determined by the DYNAMICRULES option to perform dynamic SQL authorization checking. The access control authorization exit uses the ACEE for XAPLUCHK for authorization checking. The XAPLUCHK authorization ID can be a user or a group in RACF. To ensure successful authorization checks with the owner ACEE, the

owner authorization ID in XAPLUCHK must be permitted access to the resources in RACF.

Related reference

AUTH EXIT CHECK (AUTHEXIT_CHECK subsystem parameter) (Db2 Installation and Migration) DYNAMICRULES bind option (Db2 Commands)

Using Db2 roles for BINDAGENT

You can bind plans and packages on the behalf of the owner by using the RACF BINDAGENT privilege through a Db2 role.

Before you begin

PSPI

An alternative is to set the AUTHEXIT_CHECK system parameter to DB2. With that setting in effect, Db2 provides the ACEE of the package owner to perform authorization checking when processing autobinds or BIND and REBIND commands. Db2 provides the ACEE of the authorization ID as determined by the DYNAMICRULES option to perform dynamic SQL authorization checking. The access control authorization exit uses the ACEE for XAPLUCHK for authorization checking. The XAPLUCHK authorization ID can be a user or a group in RACF. To ensure successful authorization checks with the owner ACEE, the owner authorization ID in XAPLUCHK must be permitted access to the resources in RACF. See <u>AUTH EXIT CHECK</u>

(AUTHEXIT_CHECK subsystem parameter) (Db2 Installation and Migration).

About this task

RACF provides support for BINDAGENT through Db2 roles. To use BINDAGENT, you must specify a role, instead of a secondary ID, as the owner of a plan or package and perform the BIND task within a trusted context. If you set field 1 (RESTART or DEFER) to DEFER and set field 2 (objects to restart or defer) to ALL in installation panel DSNTIPS, you cannot use trusted connections.

For this task, suppose you want role ROLEOWNER to own package COLLECTION01.PACKAGE01, but will have role ROLEBINDAGENT perform the BIND on behalf of role ROLEOWNER.

Procedure

To have ROLEBINDAGENT perform the BIND on behalf of ROLEOWNER:

- 1. Create role ROLEOWNER and role ROLEBINDAGENT.
 - Make sure that the ROLEOWNER role is the owner of the package and that the binder is associated with the ROLEBINDAGENT role and will bind the package.
- 2. Create trusted context CTX1 with the WITH ROLE AS OBJECT OWNER AND QUALIFIER clause. Specify ROLEBINDAGENT as the default role and set JOB=BINDPKG (which is the bind job name) and SYSTEM AUTHID=UBINDER (which is the binder's userid).
- 3. Create a RACF profile V91A.ROLEOWNER.BINDAGENT to control BINDAGENT access
- 4. Permit role ROLEBINDAGENT access to profile V91A.ROLEOWNER.BINDAGENT by issuing a RACF **PERMIT** command:

```
PERMIT V91A.ROLEOWNER.BINDAGENT ID(*) +
    WHEN(CRITERIA(SQLROLE('ROLEBINDAGENT'))) CL(MDSNSM)
```

5. Set up appropriate RACF profiles and give role ROLEOWNER the BINDADD and CREATE IN privileges on the package collection:

```
PERMIT V91A.BINDADD ID(*) CL(MDSNSM) +
    WHEN(CRITERIA(SQLROLE('ROLEOWNER')))
```

```
PERMIT V91A.COLLECTION01.CREATEIN ID(*) CL(MDSNCL) +
    WHEN(CRITERIA(SQLROLE('ROLEOWNER')))
```

6. Permit role ROLEOWNER all the required privileges for executing SQL statements in the application as shown in the following example:

7. Have UBINDER submit bind job BINDPKG that will run in trusted context CTX1 with role ROLEBINDAGENT and perform the BIND on behalf of role ROLEOWNER:

BIND PACKAGE(COLLECTION01) MEMBER(PACKAGE01) ACTION(REP) OWNER(ROLEOWNER)

RACF performs the BINDAGENT check on binder UBINDER, its role ROLEBINDAGENT, and its RACF groups. It then perform all the remaining checks on role ROLEOWNER and allows the BIND command to complete.

View authorization

Db2 passes specific base table information to an access control authorization exit (ACAE) routine. This information helps the routine to effectively control data access through views.

PSPI For the DELETE and INSERT privileges, Db2 passes the schema and name of the base table in the XAPLBSCM and XAPLBSNAM fields, along with the information about the view itself. For the UPDATE privilege, Db2 additionally passes the name of the base table column in the XAPLBCOL field that is being updated.

For any view in a nested stack, Db2 passes the base table information in addition to that of the view itself. All the intermediate views between the base table and the view that is being processed are ignored.

In the cases when the view is not updatable, the view information will be repeated in the XAPLBSCM, XAPLBSNAM, and XAPLBCOL fields. For example, if the view is specified with the Instead of Trigger, the base table of the view is not being updated using the view because all processing is based on the content of the trigger package. The view information is repeated in the base table fields to facilitate any view authorization check.

When a view is created, Db2 checks whether the owner of the view has the INSERT, UPDATE and DELETE privileges on the underlying base table. Db2 performs this check to determine what privileges should be

granted to the view owner. This processing occurs whether or not an ACAE routine, like the RACF access control module, is in effect. If an ACAE routine is in effect, the result of the Db2 authorization check does not impact the creation of the view or the privileges that the view owner gets on the view. In the case when the view is created based on another view, the base view information will be repeated in the

XAPLBSCM, XAPLBSNAM, and XAPLBCOL fields.

Behavior of EXPLAIN STMTCACHE with the access control authorization routine

The behavior of EXPLAIN STMTCACHE changes because in some instances the primary authorization ID replaces the statement authorization ID.

PSPI

An EXPLAIN statement that specifies the STMTCACHE clause captures EXPLAIN records for the specified dynamic SQL statements and writes them to to EXPLAIN tables. Under this option, no new access path selection processing occurs. The EXPLAIN records are extracted from the existing access paths that were selected when the dynamic SQL statements were prepared and entered the statement cache.

Dynamic statements are cached in the dynamic statement cache by using the primary authorization ID that runs the plan or package regardless of the DYNAMICRULES value. Therefore, if the access control authorization routine is used for security, the EXPLAIN STMTCACHE statement must be issued with the same primary authorization ID that is used when inserting the dynamic statements into the cache.

PSPI

Related tasks

Capturing performance information for dynamic SQL statements (Db2 Performance) Capturing access path information in EXPLAIN tables (Db2 Performance)

Related reference

DYNAMICRULES(BIND) option authorization The DYNAMICRULES(BIND) option provides the flexibility for you to specify the owner of a plan or a package that Db2 checks for the required authorization for dynamic SQL statements.

Authorization checks for caching of dynamic SQL statements

Dynamic statements can be cached when they have passed the authorization checks if the dynamic statement caching is enabled on your system.

EXPLAIN statement (Db2 SQL) EXPLAIN tables (Db2 Performance)

Dropping views

A view is dropped when the privilege that is required to create it is revoked.

PSPI Revoking the privilege on a view is not communicated to Db2 by the authorization checking routine. If you want Db2 to drop the view when the privilege is revoked, you must issue the SQL REVOKE statement. **PSPI**

Caching of EXECUTE on plans, packages, and routines

The results of authorization checks on the EXECUTE privilege for plans are not cached when those checks are performed by the authorization access control exit routine. The results of authorization checks on the EXECUTE privilege for packages and routines are cached if package and routine authorization caching is enabled on your system.

PSPI If authorization checks on the EXECUTE privilege for packages and routines are performed by the authorization access control exit routine, the role in effect or the primary authorization ID is cached. Db2 authorization can cache roles or primary authorization IDs for handling packages and routines. Db2

checks and caches a role if it is in effect and authorized. If a role is not in effect or authorized, Db2 checks and caches the primary authorization ID.

If this privilege is revoked in the exit routine, the cached information is not updated to reflect the revoke. You must use the SQL GRANT statement and the REVOKE statements to refresh the specific entry in the cache and invalidate any dependent package. If the privilege is revoked from a RACF group, you must issue the GRANT and REVOKE statements to refresh the cache information for every user in the RACF group. If the privilege is revoked from a profile name that is specified with generic characters, you must issue the GRANT and REVOKE statements to refresh the cache information for every object in Db2 that matches the generic characters for that object type.

If the AUTHEXIT_CACHEREFRESH subsystem parameter is set to ALL, Db2 refreshes the cache entries of the package authorization, the routine authorization, and the dynamic statement when a user profile or resource access is changed in RACF and the access control authorization exit is active. Db2 refreshes the cache entries for DDF user authentication when the user profile is changed in RACF. The DDF user authentication cache is refreshed regardless of whether security is managed with Db2 facilities or with

the access control authorization exit.

Implicit ownership privileges supported by RACF

When a user is the owner of a Db2 object, that user has some, but not all, implicit privileges associated with the ownership of the object. This limitation applies when the RACF access control module is used for authorization, for example.

RACF supports certain implicit privileges of ownership. See <u>Implicit privileges of ownership (RACF Access</u> <u>Control Module Guide)</u> for details about Db2 objects and the implicit ownership privileges that RACF supports.

Related concepts

Implicit privileges of ownership (RACF Access Control Module Guide)

Authorization checks for caching of dynamic SQL statements

Dynamic statements can be cached when they have passed the authorization checks if the dynamic statement caching is enabled on your system.

PSPI If authorization checks for dynamic statements are performed by the authorization access control exit routine, the role in effect or the primary authorization ID is cached. Db2 authorization can cache roles or primary authorization IDs for handling dynamic statements. Db2 checks and caches a role if it is in effect and authorized. If a role is not in effect or authorized, Db2 checks and caches the primary authorization ID.

If the privileges that this statement requires are revoked from the authorization ID that is cached with the statement, this cached statement must be invalidated. If the privilege is revoked in the exit routine, you must use the SQL GRANT and REVOKE statements to refresh the specific entry in the cache and invalidate any dependent package. If the privilege is revoked from a RACF group, you must issue the GRANT and REVOKE statements to refresh the cache information for every user in the RACF group. If the privilege is revoked from a profile name that is specified with generic characters, you must issue the GRANT and REVOKE statements to refresh the cache information for every object in Db2 that matches the generic

characters for that object type. PSPI

Related tasks

Enabling the dynamic statement cache to improve dynamic SQL performance (Db2 Performance)

Resolution of user-defined functions

The create timestamp for a user-defined function must be older than the bind timestamp for the package or plan in which the user-defined function is invoked. If Db2 authorization checking is in effect, and Db2 performs an automatic rebind on a plan or package that invokes a user-defined function, any user-defined

functions that are created after the original BIND or REBIND of the invoking plan or package are not candidates for execution.

PSPI If you use an access control authorization exit routine, some user-defined functions that were not candidates for execution before the original BIND or REBIND of the invoking plan or package might become candidates for execution during the automatic rebind of the invoking plan or package. If a user-defined function is invoked during an automatic rebind, and that user-defined function is invoked from a trigger body and receives a transition table, the form of the invoked function that Db2 uses for function selection includes only the columns of the transition table that existed at the time of the original

BIND or REBIND of the package or plan for the invoking program.

Creating materialized query tables

When a materialized query table is created, a CRTVUAUTT authorization check is performed. The CRTVUAUTT check is used to determine whether the creator of a materialized query table can provide the required SELECT privileges on base tables to the owner of the materialized query table.

PSPI If the owner of the materialized query table has the required privileges, the CRTVUAUTT authorization check proves redundant. However, the check is performed before the owner of the materialized query table's privileges are determined. Therefore, if the materialized query table owner holds the necessary privileges and the creator of the materialized query table does not, the CRTVUAUTT check can produce unwanted error messages.

For an ACA exit routine to suppress unwanted error messages during the creation of materialized query tables, XAPLFSUP is turned on.

SNA connection and DSNR class check at the server

In some cases, an additional RACF DSNR class check for the DIST profile at the server might occur.

PSPI RACF is called to validate the incoming connection request when all of the following conditions exist:

- The connection to a Db2 for z/OS server uses SNA.
- The SYSIBM.LUNAMES catalog table at the server is set up to do inbound translation.
- The security option is already verified.

This situation can cause an additional RACF DSNR class check for the DIST profile at the server.

PSPI

Parameter list for access control authorization routines

The parameter list of access control authorization routines contains pointers to other information, such as the work area and the authorization ID list.

PSPI The following diagram shows how the parameter list points to other information.



Figure 14. How an authorization routine's parameter list points to other information

The work area (4096 bytes) is obtained once during the startup of Db2 and only released when Db2 is shut down. The work area is shared by all invocations to the exit routine.

At invocation, registers are set, and the authorization checking routine uses the standard exit parameter list (EXPL). The following is a list of the exit-specific parameters, described by macro DSNDXAPL. Field names indicated by an asterisk (*) apply to initialization, termination, and authorization checking. Field names indicated by double asterisks (**) apply to initialization only. Other fields apply to authorization checking only.

		-		
Name	Hex offset	Data type	Input or output	Description
XAPLCBID*	0	Character, 2 bytes	Input	Control block identifier; value X'216A'.
XAPLLEN *	2	Signed, 2- byte integer	Input	Length of XAPL; value X'100' (decimal 256).
XAPLEYE *	4	Character, 4 bytes	Input	Control block eye catcher; value "XAPL".
XAPLLVL *	8	Character, 8 bytes	Input	Db2 version and level; for example, "VxRxMx ".
XAPLSTCK *	10	Character, 8 bytes	Input	The store clock value when the exit is invoked. Use this to correlate information to this specific invocation.
XAPLSTKN *	18	Character, 8 bytes	Input	STOKEN of the address space in which XAPLACEE resides. Binary zeroes indicate that XAPLACEE is in the home address space.

Table 84. Parameter list for access control authorization routines

Table 84. Parameter list for access control authorization routines (continued)				
Name	Hex offset	Data type	Input or output	Description
XAPLACEE *	20	Address, 4	Input	ACEE address
		bytes		 Of the Db2 address space (ssnmDBM1) when XAPLFUNC is 1 or 3.
				 Of the primary authorization ID associated with this agent or XAPLUCHK ID when XAPLFUNC is 2.
				There might be cases where an ACEE address is not available for an agent. In such cases this field contains binary zeroes.
XAPLUPRM *	24	Character, 8	Input	One of the following IDs:
		bytes		• When XAPLFUNC is 1 or 3, it contains the User ID of the Db2 address space (<i>ssnm</i> DBM1)
				• When XAPLFUNC is 2, it contains the primary authorization ID associated with the agent. The primary authorization ID is set to XAPLUCHK ID when XAPLOWAC is on.
XAPLFUNC *	2C	Signed, 2- byte integer	Input	Function to be performed by exit routine:
		.,		Initialization
				2 Authorization Charle
				3
				Termination
XAPLGPAT *	2E	Character, 4 bytes	Input	Db2 group attachment name for data sharing. The Db2 subsystem name if not data sharing.
XAPLUCKT	32	Character, 1 byte	Input	Type of the authorization ID on which Db2 performs the check:
				An authorization 1D
				- A role
XAPLONRT	33	Character, 1 byte	Input	Type of the authorization ID that owns the object in XAPLOWNR:
				An authorization ID
				A role
XAPLSDEF	34	Character, 1	Input	System-defined object:
		byte		S
				A system-defined routine of package
				Not a system-defined object
XAPLRSV1	35	Character, 3 bytes		Reserved

Name	Hex offset	Data type	Input or output	Description
XAPLPRIV	38	Signed, 2- byte integer	Input	Db2 privilege being checked. Security administrator (SECADM) authority and secure object creation (CREATE_SECURE_OBJECT) privilege required for row and column access control
XAPLTYPE	ЗA	Character, 1	Input	Db2 object type:
				B Buffer pool
				C C
				Collection
				Database -
				E Distinct typeDistinct type
				F User-defined functionUser-defined function
				H Global variable
				JAR
				K Package
				L
				M
				Schema N
				Trusted context
				O Stored procedure
				P Application plan
				Q Sequence
				R Table space
			S	
				Storage group T
				Table
				System privilege
				View

Name	Hex offset	Data type	Input or output	Description
XAPLFLG1	3B	Character, 1 byte	Input	The highest-order bit, bit 8, (XAPLCHKS) is on if the secondary IDs associated with this authorization ID (XAPLUCHK) are included in the Db2 authorization check. If it is off, only this authorization ID is checked.
				Bit 7 (XAPLUTB) is on if this is a table or view privilege (SELECT, INSERT, and so on) and if SYSCTRL, SQLADM, System DBADM, ACCESSCTRL, DATAACCESS, or SECADM is not sufficient authority to perform the specified operation on a table or view. SYSCTRL, SQLADM, System DBADM, ACCESSCTRL, DATAACCESS, or SECADM does not have the privilege of accessing user data unless the privilege is specifically granted to it.
				Bit 6 (XAPLAUTO) is on if this is an autobind.
				Bit 5 (XAPLCRVW) is on if the installation parameter DBADM CREATE AUTH is set to YES.
				Bit 4 (XAPLRDWR) is on if the privilege is a write privilege. If the privilege is a read-only privilege, bit 4 is off.
				Bit 3 (XAPLFSUP) is on to suppress error messages. These error messages are caused by intermediate checks that do not affect the final result.
				Bit 2 (XAPLRAOO) is on if this operation is in a trusted context that is defined with the ROLE AS OBJECT OWNER clause.
				Bit 1 (XAPLIMPD) is on if authorization checking involves an implicitly created database.
XAPLUCHK	3C	Address, 4 bytes	Input	Address to the authorization ID on which Db2 performs the check. It could be the primary, secondary, or some other ID. This is a VARCHAR(128) field.

Table 84. Parameter list for access control authorization routines (continued)

Name	Hex offset	Data type	Input or output	Description		
XAPLOBJN	40	Address, 4 bytes	Input	Address to the unqualified name of the object with which the privilege is associated. This is a VARCHAR(128) field.It is one of the following names:		
				Name Length		
				Application plan 8		
				Buffer pool 8		
				Collection VARCHAR(128)		
				Database 8		
				Distinct type VARCHAR(128)		
				Variable name VARCHAR(128)		
						JAR VARCHAR(128)
				Package VARCHAR(128)		
			Role VARCHAR(128)			
				Schema VARCHAR(128)		
				Sequence VARCHAR(128)		
				Storage group VARCHAR(128)		
				Table VARCHAR(128)		
				Table space 8		
				Trusted context VARCHAR(128)		
				User-defined function VARCHAR(128)		
				View VARCHAR(128)		
				For special system privileges (SYSADM, SYSCTRL, and so on) this field might contain binary zeroes.		
XAPLOWNQ	44	Address, 4 bytes	Input	Address of the object owner (creator) or object qualifier. The contents of this parameter depends on either the privilege being checked or the object. This is a VARCHAR(128) field.		
				If this field is not applicable, it contains binary zeros.		

Name	Hex offset	Data type	Input or output	Description
XAPLREL1	48	Address, 4 bytes	Input	Address of other related information 1. The contents of this parameter depend on either the privilege being checked or the object. This is a VARCHAR(128) field.
				If this field is not applicable, it contains binary zeros.
XAPLREL2	4C	Address, 4 bytes	Input	Address of other related information 2. The contents of this parameter depends on the privilege being checked. This is a VARCHAR(128) field.
				If this field is not applicable, it contains binary zeros.
XAPLDBSP	50	Address, 4 bytes	Input	Address of database information. This information is passed for CREATE VIEW and CREATE ALIAS.
				If this field is not applicable, it contains binary zeros.
XAPLOWNR	54	Address, 4	Input	Address of the object owner. This is a VARCHAR(128) field.
		bytes		If this field is not applicable, it contains binary zeros.
XAPLROLE	58	Address, 4 bytes	Input	Address of the user's role when operating in a trusted context. If this field is not applicable, it contains binary zeros.
XAPLOONM	5C	Address, 4 bytes	Input	Address of other object name
XAPLOOON	60	Address, 4 bytes	Input	Address of other object owner
XAPLBSCM	64	Address, 4 bytes	Input	Address of base table qualifier of a view or repeated view qualifier
XAPLBNAM	68	Address, 4 bytes	Input	Address of base table name of a view or repeated view name
XAPLBCOL	6C	Address, 4 bytes	Input	Address of base table column name of a view or repeated view column name
XAPLCLST**	70	Address, 4 bytes	Output	Address to the RACLISTed class list
XAPLCLNM**	74	Signed, 2- byte integer	Output	Number of RACLISTed Db2 classes
XAPLFLG3**	76	Character, 1 byte	Output	Bit 8 (the highest order bit) is on if classes are defined in multi-subsystem scope (XAPLMSSC)
				The remaining 7 bits are reserved.
XAPLRSV2	77	Character, 42 bytes		Reserved.
XAPLOOTP	A1	Character, 1 byte	Input	Other object type or the owner of the base table of a view
XAPLOOOT	A2	Character, 1 byte	Input	Other object owner type or the owner type of the base table of a view
XAPLRSV3	A3	Character, 1 byte		Reserved

Table 84. Parameter list for access control authorization routines (continued)

Name	Hex offset	Data type	Input or output	Description
XAPLXBTS	A4	Timestamp, 10 bytes	Input	The function resolution timestamp. Authorizations received prior to this timestamp are valid.
				Applicable to functions and procedures.
XAPLONWT	AE	Character, 1 byte	Output	Information required by Db2 from the exit routine for the UPDATE and REFERENCES table privileges:
				Value Explanation
				 Requester has privilege on the entire table * Requester has privilege on just this column
XAPLFLG2	AF	Character, 1 byte	Input	Bit 8 (the highest-order bit) is on if an object is associated with the row and column access control (XAPLSOBJ)
				Bit 7 is on if the SEPARATE SECURITY system parameter is set to YES (XAPLSPSC)
				Bit 6 is on when a catalog table (XAPLSCTB) can be accessed only by the SECADM authority.
				Bit 5 (XAPLACAC) is on when authorization checking is done for statements that involve the package authorization, routine authorization, or dynamic statement cache.
				Bit 4 (XAPLOWAC) is on if ACEE FOR XAPLUCHK ID is set IN XAPLACEE
				Bit 3 is on if class names are defined in multi-subsystem scope (XAPLMSSC)
				The remaining 2 bits are reserved.
XAPLDIAG	В0	Character, 80 bytes	Output	Information returned by the exit routine to help diagnose problems.

Table 84. Parameter list for access control authorization routines (continued)

The following table includes database information for determining authorization for creating a view. The address to this parameter list is in XAPLREL2.

Table 85. Parameter list for access control authorization routines—database information

Name	Hex offset	Data type	Input or output	Description
XAPLDBNP	0	Address	Input	Address of information for the next database. X'00000000' indicates no next database exists.
XAPLDBNM	4	Character, 8 bytes	Input	Database name.

Name	Hex offset	Data type	Input or output	Description
XAPLDBDA	С	Character, 1 byte	Output	Required by Db2 from the exit routine for CREATE VIEW.
				A value of Y and EXPLRC1=0 indicate that the user ID in field XAPLUCHK has database administrator authority on the database in field XAPLDBNM.
				When the exit checks if XAPLUCHK can create a view for another authorization ID, it first checks for SYSADM or SYSCTRL authority. If the check is successful, no more checking is necessary because SYSCTRL authority (for non-user tables) or SYSADM authority satisfies the requirement that the view owner has the SELECT privilege for all tables and views that the view might be based on. This is indicated by a blank value and EXPLRC1=0.
				If the authorization ID does not have SYSADM or SYSCTRL authority, the exit checks if the view creator has DBADM on each database of the tables that the view is based on because the DBADM authority on the database of the base table satisfies the requirement that the view owner has the SELECT privilege for all base tables in that database.
XAPLDBIM	D	Character, 1 bytes	Input	A value of 'Y' indicates that the database is implicitly created.
XAPLRSV5	E	Character, 2 bytes	none	Reserved.
Table 96 Deverence	list for set	an another a state state state	- routines -	less list array information
Tuble 86. Parameter	ust for acce	ss control authorization	i routines-ci	

Table 85. Parameter list for access control authorization routines-database information (continued)

Hex Input or

Name	offset	Data type	output	Description
XAPLCMEM**	0	Character, 8 bytes	Output	Db2 class name

XAPLOWNQ, XAPLREL1 and XAPLREL2 might further qualify the object or may provide additional information that can be used in determining authorization for certain privileges. The following is a list of the privileges and the contents of XAPLOWNQ, XAPLREL1 and XAPLREL2.

Table 87.	Related	informatior	ı for certain	privileges
		,	,	, 0

Privilege	Object type (XAPLTYPE)	XAPLOWNQ	XAPLREL1	XAPLREL2	XAPLOWNR
0263 (USAGE)	E	Address of schema name	Address of distinct type owner	Contains binary zeroes	Address of distinct type owner

Privilege	Object type (XAPLTYPE)	XAPLOWNQ	XAPLREL1	XAPLREL2	XAPLOWNR
0291 (READ) 0292 (WRITE)	Н	Address of schema name	Address of global variable owner	Contains binary zeroes	Address of global variable owner
0064 (EXECUTE) 0265 (START) 0266 (STOP) 0267 (DISPLAY)	F	Address of schema name	Address of user-defined function owner	Contains binary zeroes	Address of user- defined function owner
0263 (USAGE)	J	Address of schema name	Address of JAR owner	Contains binary zeroes	Address of JAR owner
0064 (EXECUTE)	К	Address of collection ID	Contains binary zeroes	Contains binary zeroes	Contains binary zeroes
0065 (BIND)	К	Address of collection ID	Address of package owner	Contains binary zeroes	Address of package owner
0073 (DROP)	К	Address of collection ID	Contains binary zeroes	Address of version ID	Contains binary zeroes
0097 (COMMENT)	К	Address of collection ID	Address of package owner	Contains binary zeroes	Address of package owner
0225 (COPY ON PKG)	К	Address of collection ID	Address of package owner	Contains binary zeroes	Address of package owner
0228 (ALLPKAUT)	К	Address of collection ID	Contains binary zeroes	Contains binary zeroes	Contains binary zeroes
0229 (SUBPKAUT)	К	Address of collection ID	Contains binary zeroes	Contains binary zeroes	Contains binary zeroes
0252 (ALTERIN) 0097 (COMMENT) 0252 (DROPIN)	М	Address of schema name	Address of object owner	Contains binary zeroes	Address of object owner
0064 (EXECUTE) 0265 (START) 0266 (STOP) 0267 (DISPLAY)	0	Address of schema name	Address of procedure owner	Contains binary zeroes	Address of procedure owner
0065 (BIND)	Р	Address of plan owner	Contains binary zeroes	Contains binary zeroes	Address of plan owner
0097 (COMMENT)	Р	Address of plan owner	Contains binary zeroes	Contains binary zeroes	Address of plan owner
0061 (ALTER) 0263 (USAGE)	Q	Address of schema name	Address of sequence name	Contains binary zeroes	Contains binary zeroes
0061 (ALTER)	R	Address of database name	Contains binary zeroes	Contains binary zeroes	Contains binary zeroes
0073 (DROP)	R	Address of database name	Contains binary zeroes	Contains binary zeroes	Contains binary zeroes

Table 87. Related information for certain privileges (continued)

Privilege	Object type (XAPLTYPE)	XAPLOWNQ	XAPLREL1	XAPLREL2	XAPLOWNR
0087 (USE)	R	Address of database name	Contains binary zeroes	Contains binary zeroes	Contains binary zeroes
0053 (UPDATE) 0054 (REFERENCES)	Т	Address of table schema	Address of column name, if applicable	Address of database name	Address of table owner
0022 (CATMAINT CONVERT) 0050 (SELECT) 0051 (INSERT) 0052 (DELETE) 0055 (TRIGGER) 0056 (CREATE INDEX) 0061 (ALTER) 0073 (DROP) 0075 (LOAD) 0076 (CHANGE NAME QUALIFIER) 0097 (COMMENT) 0098 (LOCK) 0233 (ANY TABLE PRIVILEGE) 0251 (RENAME) 0275 (REFRESH)	Т	Address of table schema	Contains binary zeroes	Address of database name	Address of table owner
0020 (DROP ALIAS) 0104 (DROP SYNONYM)	Т	Address of table schema	Contains binary zeroes	Contains binary zeroes	Contains binary zeroes
0103 (ALTER INDEX) 0105 (DROP INDEX) 0274 (COMMENT ON INDEX) 0283 (RENAME INDEX)	Т	Address of table schema	Contains binary zeroes	Address of database name	Address of index owner
0227 (BIND AGENT)	U	Address of package owner	Contains binary zeroes	Contains binary zeroes	Address of package owner
0015 (CREATE ALIAS)	U	Contains binary zeroes	Contains binary zeroes	Address of database name, if the alias is on a table	Contains binary zeroes
0053 (UPDATE)	V	Address of view schema	Address of column name, if applicable	Address of the database name of the view's base table, if applicable	Address of view owner

	-		-			
Privil	ege	Object type (XAPLTYPE)	XAPLOWNQ	XAPLREL1	XAPLREL2	XAPLOWNR
0051 0052	(INSERT) (DELETE)	V	Address of view schema	Contains binary zeroes	Address of the database name of the view's base table, if applicable	Address of view owner
0050 0073 0097 0233 PRIV	(SELECT) (DROP) (COMMENT) (ANY TABLE ILEGE)	V	Address of view schema	Contains binary zeroes	Contains binary zeroes	Address of view owner
0055	(TRIGGER)	V	Address of view schema	Contains binary zeroes	Contains binary zeroes	Address of view owner
0061	(ALTER)	V	Address of view schema	Contains binary zeroes	Contains binary zeroes	Address of view owner
	The following is a list	t of data types a	nd field lengths.			
	Table 88. Data types	s and field length	S			
	Resource name or o	other	Туре		Length	
	Database name		Character		8	
	Global variable nam	е	Character		VARCHAR(128)	
	Table name qualifier	r	Character		VARCHAR(128)	
	Object name qualifie	er	Character		VARCHAR(128)	
	Column name		Character		VARCHAR(128)	
	Collection ID		Character		VARCHAR(128)	
	Plan owner		Character		VARCHAR(128)	
	Package owner		Character		VARCHAR(128)	
	Package version ID		Character		VARCHAR(64)	
	Schema name		Character		VARCHAR(128)	
	Distinct typeowner		Character		VARCHAR(128)	
	JAR owner		Character		VARCHAR(128)	
	User-defined function	on owner	Character		VARCHAR(128)	
	Procedure owner		Character		VARCHAR(128)	
	View name qualifier		Character		VARCHAR(128)	
	Sequence owner		Character		VARCHAR(128)	
	Sequence name		Character		VARCHAR(128)	

Table 87. Related information for certain privileges (continued)

PSPI

Expected output for access control authorization routines

Your authorization exit routine is expected to return certain fields when it is called. If an unexpected value is returned in any of these fields, an abend occurs.

PSPI

The following is a list of output fields for the access control authorization routine. Register 3 points to the field in error, and abend code 00E70009 is issued.

Table 89. Output fields for the access control authorization routine				
Field	Required or optional			
EXPLRC1	Required			
EXPLRC2	Optional			
XAPLONWT	Required only for UPDATE and REFERENCES table privileges			
XAPLDIAG	Optional			

PSPI

Handling return codes

You need to place the return codes from the access control authorization routine in the EXPL field named EXPLRC1. The EXPLRC1 value affects Db2 processing.

About this task

PSPI EXPLRC1 must have one of the following values during initialization.

Table 90. Required values in EXPLRC1 during initialization				
Value	e Meaning			
0	Initialization successful.			
12 Unable to service request; don't call exit again.				

Db2 does not check EXPLRC1 on return from the exit routine during termination. Make sure that EXPLRC1 has one of the following values during the authorization check.

Table 91. Required values in EXPLRC1 during authorization check

Value	Meaning
0	Access permitted.
4	Unable to determine; perform Db2 authorization checking.
8	Access denied.
12	Unable to service request; don't call exit routine again.

On authorization failures, the return code is included in the IFCID 140 trace record.

PSPI

Related concepts

General guidelines for writing exit routines (Db2 Administration Guide)

Related reference

Exception processing

During initialization or authorization checking, Db2 issues diagnostic message DSNX210I to the operator's console when an error condition occur.

Handling reason codes

After initialization, the access control authorization routine returns reason code EXPLRC2. EXPLRC2 determines how Db2 processes return code EXPLRC1 that is returned during authorization checking.

About this task

PSP1 The following is a list of reason codes during initialization.

Table 92. Red	Table 92. Reason codes during initialization				
Value	Meaning				
-1	Identifies the default exit routine shipped with Db2. If you replace or modify the default exit, you should not use this value.				
16	Indicates to Db2 that it should terminate if the exit routine returns EXPLRC1=12, an invalid EXPLRC1 or abnormally terminates during initialization or authorization checking. When the exit routine sets the reason code to 16, Db2 does an immediate shutdown, without waiting for tasks to end. For long-running tasks, an immediate shutdown can mean that recovery times are long.				
Other	Ignored by Db2.				

Field EXPLRC2 enables you to put in any code for authorization check. You can use EXPLRC2 to determine why the authorization check in the exit routine failed. On authorization failures, the reason code is included in the IFCID 140 trace record.

Related concepts

General guidelines for writing exit routines (Db2 Administration Guide)

Related reference

Exception processing

During initialization or authorization checking, Db2 issues diagnostic message DSNX210I to the operator's console when an error condition occur.

Exception processing

During initialization or authorization checking, Db2 issues diagnostic message DSNX210I to the operator's console when an error condition occur.

PSPI Db2 issues diagnostic message DSNX210I if one of the following conditions occur:

- The authorization exit returns a return code of 12 or an invalid return code.
- The authorization exit abnormally terminates.

Additional actions that Db2 performs depend on the reason code that the exit returns during initialization. The following is a list of these actions.

Table 93. How an error condition affects Db2 actions during initialization and authorization checking		
Exit result	Reason code of 16 returned by exit routine during initialization	Reason code other than 16 or -1 returned by exit routine during initialization ¹
Return code 12	 The task² abnormally terminates with reason code 00E70015 Db2 terminates 	 The task² abnormally terminates with reason code 00E70009 Db2 switches to Db2 authorization checking
Invalid return code	 The task² abnormally terminates with reason code 00E70015 Db2 terminates 	 The task² abnormally terminates with reason code 00E70009 Db2 switches to Db2 authorization checking
Abnormal termination during initialization	Db2 terminates	Db2 switches to Db2 authorization checking
Abnormal termination during authorization checking	You can use the subsystem parameter AEXITLIM ³ to control how Db2 and the exit behave.	You can use the subsystem parameter AEXITLIM to control how Db2 and the exit behave.
	Example: If you set AEXITLIM to 10, the exit routine continues to run after the first 10 abnormal terminations. On the eleventh abnormal termination, the exit stops and Db2 terminates.	Example: If you set AEXITLIM to 10, the exit routine continues to run after the first 10 abnormal terminations. On the eleventh abnormal termination, the exit routine stops and Db2 switches to Db2 authorization checking.

Note:

- 1. During initialization, Db2 sets a value of -1 to identify the default exit. The user exit routine should not set the reason code to -1.
- 2. During initialization, the task is Db2 startup. During authorization checking, the task is the application.

3. AEXITLIM (authorization exit limit) can be updated online.

PSPI

Debugging access control authorization routines

Use trace records to determine the parameters that were used when an access control authorization routine was called.

Procedure

- Start a performance class 22 trace to generate IFCID 0314 trace records. Those records contain the
 parameter list for the access control authorization exit routine, and are generated on return from that
 exit routine.
- You can generate IFCID 0314 trace records only for authorization checks that use Db2 security facilities. To do that, in addition to starting a performance class 22 trace, start a trace for IFCID 0410.

Determining whether the access control authorization routine is active

You can determine whether the exit routine or Db2 is performing authorization checks.

Procedure

PSPI To determine whether the exit routine or Db2 is performing authorization checks:

- 1. Start audit trace class 1.
- 2. Choose a Db2 table on which to issue a SELECT statement and an authorization ID to perform the SELECT. The authorization ID must not have the Db2 SELECT privilege or the external security system SELECT privilege on the table.
- 3. Use the authorization ID to issue a SELECT statement on the table. The SELECT statement should fail.
- 4. Format the trace data and examine the return code (QW0140RC) in the IFCID 0140 trace record.
 - QW0140RC = -1 indicates that Db2 performed the authorization check and denied access.
 - QW0140RC = 8 indicates that the external security system performed the authorization check and denied access. PSPI

RACF access control module

The RACF access control module allows you to use RACF as an alternative to Db2 authorization checking for Db2 objects, authorities, and utilities.

PSPI You can activate the RACF access control module at the Db2 access control authorization exit point (DSNX@XAC), where you can replace the default routine. The RACF access control module is provided as an assembler source module in the DSNXRXAC member of Db2.SDSNSAMP.

The RACF access control module (DSNXRXAC) does not provide full support of roles on z/OS 1.7.

Related concepts

Introduction to the RACF access control module (RACF Access Control Module Guide)

Db2 12 for z/OS: Managing Security (Last updated: 2024-09-06)

Chapter 8. Managing program authorization

Program authorization lets you control whether a Db2 application program is authorized to use a plan.

Before you begin

Table SYSIBM.DSNPROGAUTH and index SYSIBM.DSNPROGAUTH_IDX1 must exist on your Db2 subsystem. They are created by installation job DSNTIJSG.

About this task

Program authorization is a useful technique when you do not know all of the programs and packages that might use a plan. Program authorization is performed in addition to package authorization.

Restriction:

Programs that run in the following environments do not support program authorization:

- RRSAF applications that issue CREATE THREAD with a collection name, and therefore use the default plan name ?RRSAF
- Multicontext ODBC applications, which use the RRSAF attachment facility and the plan name DSNACLI
- · Programs that run in stored procedure address spaces

Procedure

To enable program authorization:

- 1. Bind or rebind plans for which you want to enable program authorization with the PROGAUTH(ENABLE) option.
- 2. Add a row in the SYSIBM.DSNPROGAUTH table for each program and plan combination for which the plan is bound with PROGAUTH(ENABLE). The ENABLED column needs to have the value Y.

The program name that you need to insert in the row depends on the attachment facility that the program uses to connect to Db2:

- If the program uses the TSO attachment facility, the program name is the name that you specify in the DSN RUN subcommand.
- If the program uses the IMS attachment, the program name is the name of the IMS transaction application program.
- If the program uses any other attachment facility, the program name is the name of the module that is executed first under the job step TCB.

Job DSNTIJSG contains a sample INSERT statement for a SYSIBM.DSNPROGAUTH row. You can modify the INSERT statement and execute it to add a row for a program and plan.

Db2 12 for z/OS: Managing Security (Last updated: 2024-09-06)
Chapter 9. Protecting data through encryption and RACF

You can use the Db2 Secure Socket Layer (SSL) support or built-in data encryption functions to protect your sensitive data. You can also use the security features of RACF, or an equivalent system, to protect your data sets.

Encrypting your data with z/OS DFSMS data set encryption

Db2 for z/OS uses z/OS DFSMS data set encryption to transparently encrypt Db2 data sets.

Requirements for using z/OS DFSMS data set encryption

Before you can use z/OS DFSMS data set encryption to encrypt Db2 data sets, make sure that your system meets the following requirements:

- The operating system is z/OS 2.2 or later. For z/OS 2.2, the PTFs for APAR OA50569 and APAR OA53951 must be applied.
- Required hardware is installed. For details, see <u>Using the z/OS data set encryption enhancements (z/OS</u> DFSMS Using the New Functions).
- ICSF and RACF or equivalent security products.
- The Db2 started task user ID and any user ID that is required to read or write to an encrypted data set is permitted to use any key labels that are used to protect Db2 data sets.
- Any key label that is used to protect Db2 data sets is defined on all the members of a data sharing group and on any backup systems that might read or write from an encrypted data set.
- Any user ID that is required to run any of the stand-alone utilities is authorized to use any key label that is used to protect Db2 data sets.
- The prerequisite upgrades for your security product to support of z/OS data set encryption

Considerations for using z/OS DFSMS data set encryption

- When Db2 compression is enabled, compression is performed before encryption.
- z/OS DFSMS data set encryption is supported for extended format linear data sets, extended format sequential data sets, and sequential basic and large format data sets. z/OS DFSMS APAR OA56622 must be applied for sequential basic and large format data set support.
- When Db2 is at function level 100, this function works in a co-existence environment with Db2 11.
- The Db2 address space ID access to the key label is checked by DFSMS only during data set opening.
- For a disaster recovery situation, if the data has to be accessed at another physical site then the ICSF keys and RACF profiles must be set up similar to the originating site. The same rule applies to Db2 source and proxy sites in GDPS Continuous Availability with zero data loss solution environment. Refer to the <u>"Sample procedure for setting up z/OS DFSMS data set encryption" on page 321</u> for procedure to configure ICSF and RACF.

Related concepts

"Encrypting your data through Db2 built-in functions" on page 334

Db2 provides built-in data encryption and decryption functions that you can use to encrypt sensitive data, such as credit card numbers and medical record numbers.

"Protecting data sets through RACF" on page 330

To fully protect the data in Db2, you must take steps to ensure that no other process has access to the data sets in which Db2 data resides.

Types of DB2 data sets that can be encrypted by using DFSMS data set encryption

You can use DFSMS to encrypt various types of Db2 data sets including Db2-managed table space and index space data sets, data sets that are used by Db2 utilities, and sequential input and output data sets.

z/OS DFSMS data set encryption is supported for extended format linear data sets, extended format sequential data sets, and sequential basic and large format data sets. z/OS DFSMS APAR OA56622 must be applied for sequential basic and large format data set support.

Db2-managed table space and index space data sets

After you set up DFSMS encryption, you can run certain Db2 utilities to encrypt and decrypt Db2-managed table space and index space data sets.

The following utilities encrypt or decrypt the data sets for table spaces or index spaces based on the current key label that is defined in RACF data set profile or the current key label specified at the table level or storage group level or SMS data class:

- REORG TABLESPACE or REORG INDEX
- LOAD REPLACE
- RECOVER from sequential image copies- point in time or full recovery
- REBUILD INDEX

The setting of the REUSE option affects the key label in the following ways:

- If REUSE is specified, the existing key label and encryption status remain unchanged.
- If REUSE is not specified, these utilities reallocate the underlying data sets with the current key label. The existing key label and encryption status change if a new key label is defined in the RACF data set profile (or equivalent product) or SMS data class. Removing the key label from the data set profile or data set class causes these utilities to reallocate the underlying data sets without a key label and unencrypt the data.

For REORG TABLESPACE, REORG INDEX or LOAD REPLACE with SHRLEVEL CHANGE or SHRLEVEL REFERENCE, the shadow data sets will be allocated as encrypted if a key label was provided throuh the RACF data set profile, CREATE TABLE, ALTER TABLE, CREATE STOGROUP, ALTER STOGROUP or SMS data class. If the shadow data sets are preallocated, the data sets can be allocated as encrypted by the user.

Partition and Piece Level Encryption or Decryption

The following utilities can be invoked with the PART or DSNUM option for partitioned table spaces or indexes to encrypt or decrypt at the partition level:

- REORG TABLESPACE or REORG INDEX
- LOAD REPLACE
- RECOVER from sequential image copies- point in time or full recovery
- REBUILD INDEX

When the PART option is specified for REORG TABLESPACE or LOAD REPLACE, any NPIs over the table space will keep its existing key label and encryption status.

Use REORG INDEX on NPIs to encrypt or decrypt the entire NPI using the current key label.

When the DSNUM n option is specified for RECOVER of a piece of a non partitioned table space or index space, the underlying VSAM data set for that piece will be reallocated with the current key label.

Data sets that are used by utilities

Among the data sets that are used by utilities are data files for loading or unloading, utility control statement files, temporary work files for index keys or rows, and image copy data sets.

To encrypt utility data sets, use the RACF data set profile, JCL, or the SMS data class.

For data sets allocated through TEMPLATEs, DFSMS uses its order of precedence to determine the key label.

- RACF Data set profile
- JCL, Dynamic Allocation, TSO Allocate
- SMS construct: data class

If you still use hard coded DD statements instead of TEMPLATEs for the allocation of utility sequential output data sets and want to encrypt a data set, the DSKEYLBL option should be added to DD statements in the batch utility jobs.

z/OS DFSMS data set encryption does not support sequential data sets on tape, DUMMY data sets, or sort work data sets.

Encrypted input and output data sets for stand-alone utilities

The stand-alone utilities DSN1COPY, DSN1PRNT, DSN1COMP, DSNJU003, DSNJU004, DSNJCNVT, DSNJCNVB, and DSN1LOGP support encryption.

DSN1COPY, DSN1PRNT, and DSN1COMP will support encrypted VSAM or sequential data sets as input (SYSUT1 DD) and output (SYSUT2 DD) if the data sets are allocated with a key label. Since these standalone utilities do not allocate data sets, the data sets must be allocated with a key label before the job is executed. DSN1LOGP will support encrypted log data sets as input.

The job user ID must be permitted to access any underlying encrypted data sets used to run the utility.

Related concepts

Encrypted FlashCopy image copies, copies made with DFSMSdss concurrent copy, and system-level backups

System-level backups, backups for FlashCopy image copies, and copies that are made by DFSMSdss concurrent copy are allocated with the same key label as the table space and index space data sets.

Related tasks

Encrypting log, catalog, and directory data sets with z/OS DFSMS data set encryption Db2 supports z/OS DFSMS data set encryption for log, catalog, and directory data sets using a key label for encryption and decryption.

Encrypting and decrypting user-managed data sets using z/OS DFSMS data set encryption To encrypt data sets for user-managed table spaces or index spaces, use IDCAMS to define the shadow data sets with the KEYLABEL option.

Encrypting all data sets using a storage group with z/OS DFSMS data set encryption Db2 supports z/OS DFSMS data set encryption for all of the data sets in a storage group using a key label for encryption and decryption.

Using z/OS DFSMS data set encryption to encrypt the data sets associated with a particular table Db2 for z/OS supports z/OS DFSMS data set encryption for the data sets associated with a particular table.

Changing Db2 data sets from encrypted to unencrypted

To allocate a data set as unencrypted, make sure the key label is not specified through the RACF data set profile or one of the DFSMS methods.

Sample procedure for setting up z/OS DFSMS data set encryption

When you use z/OS DFSMS data set encryption to encrypt Db2 data, Integrated Cryptographic Service Facility (ICSF) and Resource Access Control Facility (RACF) or an equivalent security product must be configured to set up the encryption key and the key label.

Related reference

TEMPLATE (Db2 Utilities)

Encrypting log, catalog, and directory data sets with z/OS DFSMS data set encryption

Db2 supports z/OS DFSMS data set encryption for log, catalog, and directory data sets using a key label for encryption and decryption.

Procedure

- 1. FL 502 Set the key label by choosing one of the following approaches:
 - Set the ENCRYPTION_KEYLABEL subsystem parameter value, then issue the **SET SYSPARM** command to cause the ENCRYPTION_KEYLABEL subsystem parameter to take effect. Db2 passes the ENCRYPTION_KEYLABEL value to DFSMS for allocation of new archive log data sets or catalog and directory data sets. If a key label is specified in the RACF data set profile, that key label overrides the Db2-provided key label.
 - Set a key label for the RACF data set profile or the DFSMS data class used to protect the log, catalog, and directory data sets. DFSMS encrypts the data set when Db2 allocates new data sets that match the RACF data set profile for the following types of data sets:
 - Archive log data sets on disk
 - Catalog data sets
 - Directory data sets
- 2. Run the REORG TABLESPACE utility against the catalog and directory table spaces.

DSNDB01.SYSUTILX cannot be encrypted by running the REORG TABLESPACE utility.

- 3. Encrypt the DSNDB01.SYSUTILX directory table space by running the RECOVER utility followed by REBUILD INDEX(ALL).
- 4. Allocate new active log data sets as encrypted.

The user who allocates the active log data sets must specify a key label that Db2 has permission to use. However, the user who allocates the active log data set is not required to have access to that key label. For details, see Data Set Encryption (z/OS DFSMS Using Data Sets).

- 5. Identify the encrypted data sets as the new active log using one of the following methods:
 - Issue the **-STOP DB2** command, run the DSNJU003 NEWLOG statement, and restart Db2 to enable the use of encrypted active log data sets.
 - Issue the **-SET LOG NEWLOG** command. The active log data set is immediately available for use without recycling Db2.

What to do next

To display the current key label information, you can:

- FL 502 Issue the **DISPLAY ARCHIVE** command for the updated archive log data sets.
- FL 502 Issue the **DISPLAY LOG** command for active log data sets.
- FL 502 Issue the **DISPLAY GROUP** command to display for current subsystem parameter.
- Run the REPORT TABLESPACESET utility on catalog and directory table spaces.

Related concepts

Types of DB2 data sets that can be encrypted by using DFSMS data set encryption

You can use DFSMS to encrypt various types of Db2 data sets including Db2-managed table space and index space data sets, data sets that are used by Db2 utilities, and sequential input and output data sets.

Encrypted FlashCopy image copies, copies made with DFSMSdss concurrent copy, and system-level backups

System-level backups, backups for FlashCopy image copies, and copies that are made by DFSMSdss concurrent copy are allocated with the same key label as the table space and index space data sets.

Making changes for active logs (Db2 Utilities)

Related tasks

Encrypting and decrypting user-managed data sets using z/OS DFSMS data set encryption To encrypt data sets for user-managed table spaces or index spaces, use IDCAMS to define the shadow data sets with the KEYLABEL option.

Encrypting all data sets using a storage group with z/OS DFSMS data set encryption Db2 supports z/OS DFSMS data set encryption for all of the data sets in a storage group using a key label for encryption and decryption.

Using z/OS DFSMS data set encryption to encrypt the data sets associated with a particular table Db2 for z/OS supports z/OS DFSMS data set encryption for the data sets associated with a particular table.

Changing Db2 data sets from encrypted to unencrypted

To allocate a data set as unencrypted, make sure the key label is not specified through the RACF data set profile or one of the DFSMS methods.

Sample procedure for setting up z/OS DFSMS data set encryption

When you use z/OS DFSMS data set encryption to encrypt Db2 data, Integrated Cryptographic Service Facility (ICSF) and Resource Access Control Facility (RACF) or an equivalent security product must be configured to set up the encryption key and the key label.

Sample procedure for setting up z/OS DFSMS data set encryption

When you use z/OS DFSMS data set encryption to encrypt Db2 data, Integrated Cryptographic Service Facility (ICSF) and Resource Access Control Facility (RACF) or an equivalent security product must be configured to set up the encryption key and the key label.

Related reference

-DISPLAY ARCHIVE command (Db2) (Db2 Commands) -DISPLAY LOG (Db2) (Db2 Commands)

-DISPLAY GROUP command (Db2) (Db2 Commands)

DSNJU003 (change log inventory) (Db2 Utilities)

Encrypting and decrypting user-managed data sets using z/OS DFSMS data set encryption

To encrypt data sets for user-managed table spaces or index spaces, use IDCAMS to define the shadow data sets with the KEYLABEL option.

Procedure

- 1. Use the DFSMS Access Method Services DEFINE CLUSTER command to define the shadow data sets for the table space and index spaces with the appropriate KEYLABEL option.
- 2. Run the REORG utility with the SHRLEVEL CHANGE option on the table space.

Related concepts

Types of DB2 data sets that can be encrypted by using DFSMS data set encryption You can use DFSMS to encrypt various types of Db2 data sets including Db2-managed table space and index space data sets, data sets that are used by Db2 utilities, and sequential input and output data sets.

Encrypted FlashCopy image copies, copies made with DFSMSdss concurrent copy, and system-level backups

System-level backups, backups for FlashCopy image copies, and copies that are made by DFSMSdss concurrent copy are allocated with the same key label as the table space and index space data sets.

Related tasks

Encrypting log, catalog, and directory data sets with z/OS DFSMS data set encryption Db2 supports z/OS DFSMS data set encryption for log, catalog, and directory data sets using a key label for encryption and decryption.

Encrypting all data sets using a storage group with z/OS DFSMS data set encryption Db2 supports z/OS DFSMS data set encryption for all of the data sets in a storage group using a key label for encryption and decryption.

Using z/OS DFSMS data set encryption to encrypt the data sets associated with a particular table Db2 for z/OS supports z/OS DFSMS data set encryption for the data sets associated with a particular table.

Changing Db2 data sets from encrypted to unencrypted To allocate a data set as unencrypted, make sure the key label is not specified through the RACF data set profile or one of the DFSMS methods.

Sample procedure for setting up z/OS DFSMS data set encryption

When you use z/OS DFSMS data set encryption to encrypt Db2 data, Integrated Cryptographic Service Facility (ICSF) and Resource Access Control Facility (RACF) or an equivalent security product must be configured to set up the encryption key and the key label.

Related reference

REORG INDEX (Db2 Utilities)

Encrypting all data sets using a storage group with z/OS DFSMS data set encryption

Db2 supports z/OS DFSMS data set encryption for all of the data sets in a storage group using a key label for encryption and decryption.

About this task

Use this procedure to encrypt all the Db2-managed data sets for a storage group or to encrypt simple or segmented table spaces. For user-managed data sets, you need to use DFSMS interfaces.

Procedure

1. Obtain a key label from the RACF/ICSF administrator and ensure the key label is defined on all the backup sites used in disaster recovery and all the subsystems in a data sharing group.

For information on key labels, see "Creating a key label naming convention" in <u>Getting Started with</u> z/OS Data Set Encryption (IBM Redbooks).

2. Issue a CREATE or ALTER STOGROUP statement to define a key label.

Db2 provides the specified key label to DFSMS when allocating new data sets within the storage group. To override the Db2-provided key label at a table level, use the CREATE TABLE or ALTER TABLE statement with the KEY LABEL clause. This table-level override is only available for tables in universal or partitioned table spaces. The key label specified at the RACF data set profile overrides any Db2 provided key label.

3. Issue the REORG TABLESPACE utility against each table space within the storage group.

The key label that is specified in the ALTER STOGROUP statement is provided to DFSMS when allocating new data sets for the table spaces. The key label specified at the RACF data set profile overrides the Db2 provided key label

What to do next

You can run the REPORT utility with the TABLESPACESET, SHOWDSNS, and SHOWKEYLABEL option to display the current key label information for the table spaces.

Related concepts

Types of DB2 data sets that can be encrypted by using DFSMS data set encryption You can use DFSMS to encrypt various types of Db2 data sets including Db2-managed table space and index space data sets, data sets that are used by Db2 utilities, and sequential input and output data sets.

Encrypted FlashCopy image copies, copies made with DFSMSdss concurrent copy, and system-level backups

System-level backups, backups for FlashCopy image copies, and copies that are made by DFSMSdss concurrent copy are allocated with the same key label as the table space and index space data sets.

Related tasks

Encrypting log, catalog, and directory data sets with z/OS DFSMS data set encryption Db2 supports z/OS DFSMS data set encryption for log, catalog, and directory data sets using a key label for encryption and decryption.

Encrypting and decrypting user-managed data sets using z/OS DFSMS data set encryption To encrypt data sets for user-managed table spaces or index spaces, use IDCAMS to define the shadow data sets with the KEYLABEL option.

Using z/OS DFSMS data set encryption to encrypt the data sets associated with a particular table Db2 for z/OS supports z/OS DFSMS data set encryption for the data sets associated with a particular table.

Changing Db2 data sets from encrypted to unencrypted

To allocate a data set as unencrypted, make sure the key label is not specified through the RACF data set profile or one of the DFSMS methods.

Sample procedure for setting up z/OS DFSMS data set encryption

When you use z/OS DFSMS data set encryption to encrypt Db2 data, Integrated Cryptographic Service Facility (ICSF) and Resource Access Control Facility (RACF) or an equivalent security product must be configured to set up the encryption key and the key label.

Related reference

CREATE STOGROUP statement (Db2 SQL) ALTER STOGROUP statement (Db2 SQL) REORG TABLESPACE (Db2 Utilities) REPORT (Db2 Utilities) Getting Started with z/OS Data Set Encryption (IBM Redbooks)

Using z/OS DFSMS data set encryption to encrypt the data sets associated with a particular table

Db2 for z/OS supports z/OS DFSMS data set encryption for the data sets associated with a particular table.

About this task

Use this procedure to encrypt Db2-managed data sets for the data sets associated with a particular table. For user-managed data sets, you need to use DFSMS interfaces.

Procedure

FL 502 To encrypt table spaces with z/OS DFSMS data set encryption, use the following steps:

1. Obtain a key label from the RACF/ICSF administrator and ensure the key label is defined on all the backup sites used in disaster recovery and all the subsystems in a data sharing group.

For information on key labels, see "Creating a key label naming convention" in <u>Getting Started with</u> z/OS Data Set Encryption (IBM Redbooks).

2. Issue a CREATE or ALTER TABLE statement to define a key label to encrypt Db2-managed data sets.

Use this procedure to encrypt DB2-managed data sets for universal table spaces or partitioned table spaces. For user-managed data sets, you need to use DFSMS interfaces. For table spaces that can contain multiple tables, use the CREATE STOGROUP or ALTER STOGROUP statement with the KEY LABEL clause.

3. Run the REORG TABLESPACE utility against the table spaces associated with the table.

The key label specified on the CREATE TABLE or ALTER TABLE statement is provided to DFSMS when data sets for the table space, auxiliary (XML or LOB) table spaces, or indexes associated with the table are allocated. If a key label is specified for the RACF data set profile, it overrides the Db2-provided key label.

What to do next

You can run the REPORT utility with TABLESPACESET, SHOWDSNS, and SHOWKEYLABEL keyword to display the current key label information for the table spaces.

Related concepts

Types of DB2 data sets that can be encrypted by using DFSMS data set encryption You can use DFSMS to encrypt various types of Db2 data sets including Db2-managed table space and

index space data sets, data sets that are used by Db2 utilities, and sequential input and output data sets.

Encrypted FlashCopy image copies, copies made with DFSMSdss concurrent copy, and system-level backups

System-level backups, backups for FlashCopy image copies, and copies that are made by DFSMSdss concurrent copy are allocated with the same key label as the table space and index space data sets.

Related tasks

Encrypting log, catalog, and directory data sets with z/OS DFSMS data set encryption Db2 supports z/OS DFSMS data set encryption for log, catalog, and directory data sets using a key label for encryption and decryption.

Encrypting and decrypting user-managed data sets using z/OS DFSMS data set encryption To encrypt data sets for user-managed table spaces or index spaces, use IDCAMS to define the shadow data sets with the KEYLABEL option.

Encrypting all data sets using a storage group with z/OS DFSMS data set encryption Db2 supports z/OS DFSMS data set encryption for all of the data sets in a storage group using a key label for encryption and decryption.

Changing Db2 data sets from encrypted to unencrypted

To allocate a data set as unencrypted, make sure the key label is not specified through the RACF data set profile or one of the DFSMS methods.

Sample procedure for setting up z/OS DFSMS data set encryption When you use z/OS DFSMS data set encryption to encrypt Db2 data, Integrated Cryptographic Service Facility (ICSF) and Resource Access Control Facility (RACF) or an equivalent security product must be configured to set up the encryption key and the key label.

Encrypting all data sets using a storage group with z/OS DFSMS data set encryption Db2 supports z/OS DFSMS data set encryption for all of the data sets in a storage group using a key label for encryption and decryption.

Related reference

CREATE TABLE statement (Db2 SQL) CREATE STOGROUP statement (Db2 SQL) ALTER TABLE statement (Db2 SQL) ALTER STOGROUP statement (Db2 SQL) REORG TABLESPACE (Db2 Utilities) REPORT (Db2 Utilities) Getting Started with z/OS Data Set Encryption (IBM Redbooks)

Changing Db2 data sets from encrypted to unencrypted

To allocate a data set as unencrypted, make sure the key label is not specified through the RACF data set profile or one of the DFSMS methods.

Procedure

FL 502 To change a Db2 data set from encrypted to unencrypted, choose one of the following options:

- 1. For log, catalog, or directory data sets, complete the following steps:
 - a) Set the subsystem parameter ENCRYPTION_KEYLABEL to blank.
 - b) Issue the SET SYSPARM command to cause the new ENCRYPTION_KEYLABEL value to take effect. Db2 does not pass the ENCRYPTION_KEYLABEL value to DFSMS for allocation of new data sets for archive logs.
 - c) Run the REORG TABLESPACE utility against the catalog and directory table spaces.
- 2. For user objects, complete the following steps:
 - a) Issue ALTER TABLE or ALTER STOGROUP with the NO KEYLABEL clause for both the table and containing storage group.
 - b) Run the REORG TABLESPACE utility against the table spaces associated with the table.

Related concepts

Types of DB2 data sets that can be encrypted by using DFSMS data set encryption You can use DFSMS to encrypt various types of Db2 data sets including Db2-managed table space and index space data sets, data sets that are used by Db2 utilities, and sequential input and output data sets.

Encrypted FlashCopy image copies, copies made with DFSMSdss concurrent copy, and system-level backups

System-level backups, backups for FlashCopy image copies, and copies that are made by DFSMSdss concurrent copy are allocated with the same key label as the table space and index space data sets.

Related tasks

Encrypting log, catalog, and directory data sets with z/OS DFSMS data set encryption Db2 supports z/OS DFSMS data set encryption for log, catalog, and directory data sets using a key label for encryption and decryption.

Encrypting and decrypting user-managed data sets using z/OS DFSMS data set encryption To encrypt data sets for user-managed table spaces or index spaces, use IDCAMS to define the shadow data sets with the KEYLABEL option.

Encrypting all data sets using a storage group with z/OS DFSMS data set encryption Db2 supports z/OS DFSMS data set encryption for all of the data sets in a storage group using a key label for encryption and decryption.

Using z/OS DFSMS data set encryption to encrypt the data sets associated with a particular table Db2 for z/OS supports z/OS DFSMS data set encryption for the data sets associated with a particular table.

Sample procedure for setting up z/OS DFSMS data set encryption When you use z/OS DFSMS data set encryption to encrypt Db2 data, Integrated Cryptographic Service Facility (ICSF) and Resource Access Control Facility (RACF) or an equivalent security product must be configured to set up the encryption key and the key label.

Related reference

-SET SYSPARM command (Db2) (Db2 Commands) REORG TABLESPACE (Db2 Utilities) ALTER TABLE statement (Db2 SQL) ALTER STOGROUP statement (Db2 SQL)

Encrypted FlashCopy image copies, copies made with DFSMSdss concurrent copy, and system-level backups

System-level backups, backups for FlashCopy image copies, and copies that are made by DFSMSdss concurrent copy are allocated with the same key label as the table space and index space data sets.

For replication and disaster recovery, the same key information must be available at the recovery system in order to subsequently access the data.

FlashCopy image copies and concurrent copies

For FlashCopy image copies, the COPY, REORG, LOAD, or REBUILD INDEX utilities invoke DFSMSdss with the COPY command to create backups. The FlashCopy image copies are allocated with the key label for the data sets of the table space or index space.

For concurrent image copies, the COPY utility invokes DFSMSdss with the DUMP command to create backups. The concurrent copy data sets will be allocated with the key label for the data sets of the table space or index space.

During recovery from a FlashCopy image copy or concurrent copy, the RECOVER utility invokes DFSMSdss with the COPY and RESTORE commands respectively to restore the backup. <u>FL 502</u> If the key label for the storage group was altered after the copies were created, the key label for table spaces and index spaces may be different after the recovery, and might not match the current key label specified for the table space or storage group.

FL 502 The DFSMSdss COPY or RESTORE command fails if the data set attributes of the FlashCopy image copy or concurrent copy are different than the data set attributes of the table space and index space. Data set attributes include the encryption status (encrypted versus non encrypted) and the format (extended format versus basic format). For the DB2 RECOVER utility, this DFSMSdss restriction means that point-in-time recovery of an object will fail with a DFSMSdss error during the restore of a FlashCopy image copy or concurrent copy, if the encryption status of the table space and index space data sets have changed since the backup was created. As a work around, use IDCAMS ALTER NEWNAME or IDCAMS DELETE on the table space and index space data sets then execute the RECOVER utility. During recovery, DFSMSdss will create and allocate the table space and index space data sets automatically with attributes that match the FCIC or concurrent copy.

System-level backups of encrypted data sets

The BACKUP SYSTEM and RESTORE SYSTEM utilities invoke DFSMShsm to backup and restore Db2 production disks with FlashCopy at the volume level. The background or physical copy copies encrypted data.

Related concepts

Types of DB2 data sets that can be encrypted by using DFSMS data set encryption You can use DFSMS to encrypt various types of Db2 data sets including Db2-managed table space and index space data sets, data sets that are used by Db2 utilities, and sequential input and output data sets.

Related tasks

Encrypting log, catalog, and directory data sets with z/OS DFSMS data set encryption Db2 supports z/OS DFSMS data set encryption for log, catalog, and directory data sets using a key label for encryption and decryption.

Encrypting and decrypting user-managed data sets using z/OS DFSMS data set encryption To encrypt data sets for user-managed table spaces or index spaces, use IDCAMS to define the shadow data sets with the KEYLABEL option.

Encrypting all data sets using a storage group with z/OS DFSMS data set encryption Db2 supports z/OS DFSMS data set encryption for all of the data sets in a storage group using a key label for encryption and decryption.

Using z/OS DFSMS data set encryption to encrypt the data sets associated with a particular table

Db2 for z/OS supports z/OS DFSMS data set encryption for the data sets associated with a particular table.

Changing Db2 data sets from encrypted to unencrypted

To allocate a data set as unencrypted, make sure the key label is not specified through the RACF data set profile or one of the DFSMS methods.

Sample procedure for setting up z/OS DFSMS data set encryption

When you use z/OS DFSMS data set encryption to encrypt Db2 data, Integrated Cryptographic Service Facility (ICSF) and Resource Access Control Facility (RACF) or an equivalent security product must be configured to set up the encryption key and the key label.

Sample procedure for setting up z/OS DFSMS data set encryption

When you use z/OS DFSMS data set encryption to encrypt Db2 data, Integrated Cryptographic Service Facility (ICSF) and Resource Access Control Facility (RACF) or an equivalent security product must be configured to set up the encryption key and the key label.

Procedure

The following sample procedure shows you how to set up ICSF and RACF for encryption using z/OS DFSMS data set encryption:

1. Use ICSF to define the encryption key.

The secure AES key can be defined in the ICSF Cryptographic Key Data set (CKDS) or Public Key Data Set (PKDS).

2. Define the required authorities on RACF or an equivalent security product. RACF is used in this example.

To allow the system to create encrypted data sets when the key label is specified by Db2, the Db2 address space ID or the utility user must have at least READ authority to the following resource in the FACILITY class: STGADMIN.SMS.ALLOW.DATASET.ENCRYPT

The system checks RACF for authority to this resource when the data set is first allocated and only when it is defined as extended format linear, extended format sequential, or basic or large format sequential. For basic and large format sequential data sets, z/OS DFSMS APAR OA56622 must be applied.

Exception: When the key label is specified in the DFP segment in the RACF data set profile. The system does not require the user to have authority to this resource.

When UACC(NONE) is specified for resource STGADMIN.SMS.FAIL.INVALID.DSNTYPE.ENC in the FACILITY class, and an encryption key label is specified for a data set that is not extended format linear, extended format sequential, basic format sequential, or large format sequential, the key label is ignored, and the data set is successfully created as a non-encrypted data set.

SETR CLASSACT(CSFKEYS CSFSERV CRYPTOZ) REFRESH SETR GENERIC(CSFKEYS CSFSERV CRYPTOZ) REFRESH SETR RACLIST(CSFKEYS CSFSERV CRYPTOZ) RDEFINE CSFKEYS * UACC(NONE) ICSF(SYMCPACFWRAP(YES) SYMCPACFRET(YES))

Allocation fails if you have at least READ authority to STGADMIN.SMS.FAIL.INVALID.DSNTYPE.ENC.

Allow the DB2SYS.KEY02 and STG01KLABEL key labels to used by the SYSDSP DB2 address space ID when the key labels are accessed by any application. Allow the DB2USR.KEY01 key label to be used by the UTILUSR Db2 utility user only when the key label is accessed by z/OS DFSMS. The following example shows how to define these permissions:

PERMIT DB2SYS.KEY02 CLASS(CSFKEYS) ID(SYSDSP) ACCESS(READ) PERMIT STG01KLABEL CLASS(CSFKEYS) ID(SYSDSP) ACCESS(READ) PERMIT DB2USR.KEY01 CLASS(CSFKEYS) ID(UTILUSR) ACCESS(READ) WHEN(CRITERIA(SMS(DSENCRYPTION))) SETR RACLIST(CSFKEYS CSFSERV CRYPTOZ) REFRESH If ICSF prefixed profiles feature is enabled for the CSFKEYS resource class, additional RACF setup is needed. The resource, CSF.PREFIX.CSFKEYS.ENABLE, has to be defined in the XFACILIT class. The following example shows the RACF setup:

SETR CLASSACT(RACFVARS) RACLIST(RACFVARS) RDEFINE RACFVARS &TESTSYS ADDMEM(TEST1) SETR RACLIST(RACFVARS) REFRESH

Where *TEST1* is the system name.

RDEFINE CSFKEYS &TESTSYS.DB2SYS.KEY01 UACC(NONE) ICSF(SYMCPACFWRAP(YES) SYMCPACFRET(YES)) PERMIT &TESTSYS.DB2SYS.KEY01 ID(SYSDSP) ACC(READ) CLASS(CSFKEYS) SETR RACLIST(CSFKEYS) REFRESH

For details, see Setting up profiles in the CSFKEYS general resource class (z/OS Integrated Cryptographic Services ICSF Administrator's Guide). In addition, for protected keys, see Enabling use of encrypted keys in Symmetric Key Encipher and Symmetric Key Decipher callable services (z/OS Integrated Cryptographic Services ICSF Administrator's Guide)

- 3. FL 502 Define a key label on the data sets using one of the following methods.
 - Define a key label on a Db2 object. For example, create a storage group with key label STG01KLABEL.

CREATE STOGROUP DSNCG100 VOLUMES (ABC001,DEF003) VCAT DSNCAT KEY LABEL STG01KLABEL;

After the key label for storage group DSNCG100 is defined, any table space or index space that is allocated using storage group DSNCG100 will use key label STG01KLABEL for encryption.

• Define a key label at the RACF data set profile level. For example, you can alter the RACF data set profile to define a key label. The RACF data set profile key label takes precedence over any key label specified.

The following examples shows how you can alter the data set profile for the DB2 catalog (DSNDB06) database to add key label, DB2SYS.KEY02:

```
ALTDSD 'DSNCC10.DSNDBC.DSNDB06.*' DFP(DATAKEY(DB2SYS.KEY02))
```

4. Encrypt the data sets by using JCL.

The following example shows the JCL you might use to encrypt data sets that are used by the REORG utility:

SYSUT1 DD DSN=DB2SMS.N035UN02.REORGW.SYSUT1, DATACLAS=DB2SMS10,DSKEYLBL=DB2SG.KEY01, DISP=(MOD,DELETE,CATLG),UNIT=SYSDA, SPACE=(8000,(200,20),,ROUND)

Related concepts

Types of DB2 data sets that can be encrypted by using DFSMS data set encryption You can use DFSMS to encrypt various types of Db2 data sets including Db2-managed table space and index space data sets, data sets that are used by Db2 utilities, and sequential input and output data sets.

Encrypted FlashCopy image copies, copies made with DFSMSdss concurrent copy, and system-level backups

System-level backups, backups for FlashCopy image copies, and copies that are made by DFSMSdss concurrent copy are allocated with the same key label as the table space and index space data sets.

Related tasks

Encrypting log, catalog, and directory data sets with z/OS DFSMS data set encryption

Db2 supports z/OS DFSMS data set encryption for log, catalog, and directory data sets using a key label for encryption and decryption.

Encrypting and decrypting user-managed data sets using z/OS DFSMS data set encryption To encrypt data sets for user-managed table spaces or index spaces, use IDCAMS to define the shadow data sets with the KEYLABEL option.

Encrypting all data sets using a storage group with z/OS DFSMS data set encryption Db2 supports z/OS DFSMS data set encryption for all of the data sets in a storage group using a key label for encryption and decryption.

Using z/OS DFSMS data set encryption to encrypt the data sets associated with a particular table Db2 for z/OS supports z/OS DFSMS data set encryption for the data sets associated with a particular table.

Changing Db2 data sets from encrypted to unencrypted

To allocate a data set as unencrypted, make sure the key label is not specified through the RACF data set profile or one of the DFSMS methods.

Encrypting your data with Secure Socket Layer (SSL) support

Db2 supports Secure Socket Layer (SSL) protocol by using the z/OS Communications Server IP Application Transparent Transport Layer Security (AT-TLS).

The z/OS Communications Server for TCP/IP supports the AT-TLS function in the TCP/IP stack for applications that require secure TCP/IP connections. AT-TLS performs TLS on behalf of the application, such as Db2, by invoking the z/OS system SSL in the TCP layer of the TCP/IP stack. The z/OS system SSL supports TLS V1.0, SSL V3.0, and SSL V2.0 protocols.

AT-TLS also uses policies that provide system SSL configurations for connections that use AT-TLS. An application continues to send and receive clear text data over the socket while the transmission is protected by the system SSL.

AT-TLS support is policy-driven and can be deployed transparently underneath many existing sockets applications.

Related concepts

Encrypting your data through Db2 built-in functions

Db2 provides built-in data encryption and decryption functions that you can use to encrypt sensitive data, such as credit card numbers and medical record numbers.

Protecting data sets through RACF

To fully protect the data in Db2, you must take steps to ensure that no other process has access to the data sets in which Db2 data resides.

Related information

Db2 for z/OS: Configuring TLS/SSL for Secure Client-Server Communications (IBM Redbooks)

AT-TLS configuration

You need to complete a set of configurations that are required for Db2 to take advantage of AT-TLS support.

You must complete the following configurations of your Db2 to use the AT-TLS support:

• PROFILE.TCPIP configuration

You can specify the TTLS or NOTTLS parameter on the TCPCONFIG statement in PROFILE.TCPIP to control whether you want to use the AT-TLS support.

• TCP/IP stack access control configuration

To protect TCP/IP connections, you can configure the RACF EZB.INITSTACK.sysname.tcpname resource in the SERVAUTH class to block all stack access except for the user IDs that are permitted to use the resource.

• Policy configuration

The policy agent provides AT-TLS policy rules to the TCP/IP stack. Each rule defines a set of security conditions that the policy agent compares to the conditions at the connection that it is checking. When the policy agent finds a match, it assigns the connection to the actions that are associated with the rule.

Related tasks

Configuring SSL authentication levels

The Secure Socket Layer (SSL) protocol supports server and client authentication during the handshake phase. You can specify to use either server authentication, client authentication, or both depending on your security need.

Configuring the Db2 server for SSL

To implement SSL support for a Db2 server, you need to make sure that the TCP/IP SQL Listener service task of DDF is capable of listening to a secondary secure port for inbound SSL connections.

Configuring the Db2 requester for SSL

A Db2 requester must be able to insist on an SSL-protected connection to certain servers. To ensure SSL-protected connections, you can make communications database (CDB) changes that indicate that SSL-protected connections are required to certain remote locations.

Related reference

SSL authentication levels

The Secure Socket Layer (SSL) protocol supports server and client authentication during the handshake phase.

SSL authentication levels

The Secure Socket Layer (SSL) protocol supports server and client authentication during the handshake phase.

The SSL provides server authentication as the minimum level of security. It uses the Server Authentication mechanism to secure communications between a server and its client and allows the client to validate the authenticity of the server.

Server authentication

The SSL provides client authentication as an additional level of authentication and access control. It enables a server to validates the certificates of a client at the server and thus prevents the client from obtaining a secure connection without an installation-approved certificate.

Client authentication

Client authentication is optional. If used, it can provide the following three levels of authentication:

Level 1

With *Level 1 authentication* uses system SSL. A client passes a digital certificate to a server as part of the SSL handshake. To successfully pass the required authentication, the Certificate Authority (CA) that signs the client certificate must be trusted by the server. That is, the certificate for the CA must be in the key ring that the server uses and designates as trusted.

Level 2

Level 2 authentication (addition to level 1) requires that a client certificate be registered with RACF (or other SAF-compliant security products) and mapped to a valid user ID. When AT-TLS receives the client certificate during the SSL handshake, it queries RACF to verify that the certificate maps to a valid user ID before allowing a secure connection to be established.

Level 2 client authentication provides additional access control at the server and ensures that the client is known to have a valid user ID on the server host.

Level 3

Level 3 authentication (addition to levels 1 and 2) provides the capability to restrict access to a server based on the user ID associated with a client certificate. A client can access a server only

if the client itself is valid to the server, its certificate is valid, and a user ID associated with the certificate is valid. Level 3 authentication uses the RACF SERVAUTH general resource class to restrict access to the server based on the user ID of the client. If the SERVAUTH general resource class is not active or the SERVAUTH profile for the server is not defined, AT-TLS assumes that this level of authentication is not requested. However, if the SERVAUTH general resource class is active and the server's SERVAUTH profile is defined, a remote secure connection is be established only if the user ID that is associated with the client certificate is permitted to the server's SERVAUTH profile. Otherwise, the secure connection is not established and the connection itself is dropped.

Related concepts

AT-TLS configuration

You need to complete a set of configurations that are required for Db2 to take advantage of AT-TLS support.

Related tasks

Configuring SSL authentication levels

The Secure Socket Layer (SSL) protocol supports server and client authentication during the handshake phase. You can specify to use either server authentication, client authentication, or both depending on your security need.

Configuring the Db2 server for SSL

To implement SSL support for a Db2 server, you need to make sure that the TCP/IP SQL Listener service task of DDF is capable of listening to a secondary secure port for inbound SSL connections.

Configuring the Db2 requester for SSL

A Db2 requester must be able to insist on an SSL-protected connection to certain servers. To ensure SSL-protected connections, you can make communications database (CDB) changes that indicate that SSL-protected connections are required to certain remote locations.

Related information

Db2 for z/OS: Configuring TLS/SSL for Secure Client-Server Communications (IBM Redbooks)

Configuring SSL authentication levels

The Secure Socket Layer (SSL) protocol supports server and client authentication during the handshake phase. You can specify to use either server authentication, client authentication, or both depending on your security need.

Procedure

To specify whether to use server authentication, client authentication, or both, use the following approaches:

• If you need only a minimum level of security to authenticate the communications between a server and its clients, consider using server authentication. To use server authentication, specify the HandshakeRole Server parameter for the TTLSEnvironmentAction statement in the AT-TLS policy, as shown in the following example:

```
TTLSEnvironmentAction DB2ServerSecureEnvAct
{
TTLSKeyRingParms
{
Keyring DB2ServerKeyring
}
HandshakeRole Server
}
```

With this configuration, AT-TLS sends the server certificate to the client during the handshake phase of a connection request. The client then validates the server by examining the server certificate that it receives.

- If you need additional security, consider using client authentication. To use client authentication:
 - a) Specify the HandshakeRole ServerWithClientAuth parameter for the TTLSEnvironmentAction statement in the AT-TLS policy, as shown in the following example:

```
TTLSEnvironmentAction DB2ServerSecureEnvAct
{
    TTLSKeyRingParms
    {
        Keyring DB2SERVERKEYRING
    }
    HandshakeRole ServerWithClientAuth
    TTLSEnvironmentAdvancedParms
    {
        ClientAuthType SAFCheck
    }
}
```

b) Determine the level of client authentication by specifying the ClientAuthType parameter for the TTLSEnvironmentAdvancedParms statement in the AT-TLS policy.

Table 94. Client authentication levels						
Client Authentication Level	ClientAuthTyp e	Client Certificate	SERVAUTH Class Active and Server SERVAUTH Profile Defined	Certificate Validation		
None	PassThru	Optional	N/A	None		
None	Full	Optional	N/A	Certificate is validated against key ring, if provided		
Level 1	Required (default)	Required	N/A	Certificate is validated against key ring		
Level 2	SAFCheck	Required	Optional	Certificate is validated against key ring and must be associated with a user ID in the security product		
Level 3	SAFCheck	Required	Required	Certificate is validated against key ring and must be associated to a user ID in the security product and must be permitted to access server's SERVAUTH profile		

Depending on the authentication type (ClientAuthType) you specify, AT-TLS may not require the client to present its certificate during the SSL handshake phase.

- c) The RACF security administrator can associate user IDs with the connection that was created with SSL authentication by taking one of the following actions:
 - Create a one-to-one association, as described in <u>Enabling client login using certificates (Security</u> Server RACF Security Administrator's Guide).
 - Create a certificate name filter, as described in <u>Certificate name filtering (Security Server RACF</u> Security Administrator's Guide).

It is not necessary to store the certificates that represent the client in RACF, unless a one-toone certificate to user ID association is used. However, certificates that represent the "trusted" certificate authority (CA) that signed the client certificates must be available to RACF. Specifically, the CA certificate must be connected to the RACF KEYRING associated to the Db2 server process via the Keyring specification of TTLSKeyRingParms of the TTLSEnvironmentAction statement in the AT/TLS policy.

Results

Db2 is now ready to accept secure connections from remote clients that use SSL client and server authentication.

Related concepts

AT-TLS configuration

You need to complete a set of configurations that are required for Db2 to take advantage of AT-TLS support.

Enabling client login using certificates (Security Server RACF Security Administrator's Guide)

Related tasks

Configuring the Db2 server for SSL

To implement SSL support for a Db2 server, you need to make sure that the TCP/IP SQL Listener service task of DDF is capable of listening to a secondary secure port for inbound SSL connections.

Configuring the Db2 requester for SSL

A Db2 requester must be able to insist on an SSL-protected connection to certain servers. To ensure SSL-protected connections, you can make communications database (CDB) changes that indicate that SSL-protected connections are required to certain remote locations.

Related reference

SSL authentication levels

The Secure Socket Layer (SSL) protocol supports server and client authentication during the handshake phase.

Related information

Db2 for z/OS: Configuring TLS/SSL for Secure Client-Server Communications (IBM Redbooks)

Configuring the Db2 server for SSL

To implement SSL support for a Db2 server, you need to make sure that the TCP/IP SQL Listener service task of DDF is capable of listening to a secondary secure port for inbound SSL connections.

About this task

The TCP/IP Listener accepts regular (non-SSL) connections on the DRDA port, whereas the secure port accepts only SSL connections to provide secure communications with a partner. Clients are assured of getting the SSL protocol connections that they require.

The secure port is used only for accepting secure connections that use the SSL protocol. When the TCP/IP Listener accepts an inbound connection on the secure port, DDF invokes the SIOCTTLSCTL IOCTL service with TTLSi_Req_Type set to TTLS_QUERY_ONLY. It also retrieves the following AT-TLS policy information:

- Status of the connection. The status of a connection is either SECURE or NOT SECURE.
- Policy status of the connection. The IOCTL returns one of the following policy status:
 - If the IOCTL returns a policy status of TTLS_POL_NO_POLICY, a matching policy rule is not found for the connection and subsequently the connection status is not secure.
 - If the IOCTL returns a policy status of TTLS_POL_NOT_ENABLED, a matching policy rule is found for the connection but the policy is not configured to allow a secure connection for that client.
 - If the IOCTL returns a policy status of TTLS_POL_ENABLED, a matching policy rule is found, and SSL is enabled for the connection.
- Security type for the connection. The security type is either server or server with client authentication (with ClientAuthType = SAFCheck)
- A RACF-defined user ID that is associated with a client certificate. If a client certificate is provided by the client and validated by AT-TLS, and if a user ID is mapped to the certificate, the user ID is returned. Otherwise, the user ID is not returned.

If a secure port is not properly configured, DDF rejects the inbound connection request on the secure port. You must change the client system to either use the non-secure port, or you can configure the secure port to access Db2 remotely.

Db2 uses the resync port only for transaction completion states after failures, so no user data or authentication protocols are ever exchanged on the resync port. You can enable SSL security for the resync port by defining a network policy on all Db2 requesters and Db2 servers.

Procedure

To specify a secure port to Db2, use one of the following approaches:

• Specify the TCP/IP port number in the SECURE PORT field of Distributed Data Facility Panel 1 (DSNTIPR) during Db2 installation.

The SECURE PORT field specifies the port number that is to be used for accepting TCP/IP connection requests from remote DRDA clients that want to establish a secure connection using the SSL protocol. The value of the secure port number is a decimal number in the range 1–65534, and it cannot have the same value as the value of the RESYNC PORT field. If the SECURE PORT field has the same value as the TCP/IP PORT field, the TCP/IP port accepts only secure TCP/IP connection requests. Any non-zero port numbers are verified to ensure that they are all unique port numbers. If an error is detected, installation is not allowed to proceed until you resolve the error condition. If the DRDA SECURE PORT field is blank, SSL verification support is disabled, and the Db2 TCP/IP SQL Listener does not accept any inbound SSL connections on the secure port.

• Update the SECPORT parameter of the DDF statement in the BSDS with the change log inventory (DSNJU003) stand-alone utility.

The SECPORT parameter specifies the port number for the Db2 TCP/IP SQL Listener to accept inbound SSL connections. The value of the port number is a decimal number between 0 to 65535. If the value of the SECPORT secure port is the same as the value of RESPORT, Db2 issues an error message. If you specify a value of 0 for the SECPORT parameter, SSL verification support is disabled, and the Db2 TCP/IP SQL Listener does not accept any inbound SSL connections on the secure port.

If the value of SECPORT is disabled, the client can still use the DRDA port and use SSL on it, but Db2 does not validate whether the connection uses SSL protocol.

What to do next

Data sharing environments: In a data sharing environment, each Db2 member with SSL support must specify a secure port. The secure port for each Db2 member of the group should be the same, just as the DRDA port for each member should also be the same. If each Db2 member specifies a unique secure port, unpredictable behaviors might occur. For example, Sysplex member workload balancing might not work correctly.

Similarly, for Db2 members that are defined as a subset of the data sharing group, each Db2 member that belongs to the subset needs to configure the secure port. You do not need to define a separate unique secure port for the location alias.

Related concepts

AT-TLS configuration

You need to complete a set of configurations that are required for Db2 to take advantage of AT-TLS support.

Related tasks

Configuring SSL authentication levels

The Secure Socket Layer (SSL) protocol supports server and client authentication during the handshake phase. You can specify to use either server authentication, client authentication, or both depending on your security need.

Configuring the Db2 requester for SSL

A Db2 requester must be able to insist on an SSL-protected connection to certain servers. To ensure SSL-protected connections, you can make communications database (CDB) changes that indicate that SSL-protected connections are required to certain remote locations.

Modifying the change log inventory job for using TCP/IP (Db2 Installation and Migration)

Related reference

<u>SSL authentication levels</u> The Secure Socket Layer (SSL) protocol supports server and client authentication during the handshake phase.

DSNTIPR: Distributed data facility panel 1 (Db2 Installation and Migration)

Related information

Db2 for z/OS: Configuring TLS/SSL for Secure Client-Server Communications (IBM Redbooks)

Configuring the Db2 requester for SSL

A Db2 requester must be able to insist on an SSL-protected connection to certain servers. To ensure SSL-protected connections, you can make communications database (CDB) changes that indicate that SSL-protected connections are required to certain remote locations.

About this task

If a secure connection is required, DDF must determine whether an AT-TLS policy rule is defined and whether AT-TLS is enabled for the connection. To obtain this AT-TLS information, DDF invokes SIOCTTLSCTL IOCTLwith TTLSi_Req_Type = TTLS_QUERY_ONLY. If the IOCTL returns a policy status of TTLS_POL_NO_POLICY, a matching policy rule is not found for the connection.

If the IOCTL returns a policy status of TTLS_POL_NOT_ENABLED, a policy rule is defined for the connection, but AT-TLS is not enabled, and a secure connection is not established with the remote server. DDF issues a message, and the connection is closed.

If the IOCTL returns a policy status of TTLS_POL_ENABLED, a matching policy rule is found, and SSL is enabled for the connection.

Procedure

To specify a secure connection to DB2, use one of the following approaches:

- Specify 'Y' for the SECURE column in the SYSIBM.LOCATIONS table.
- Specify a value for the PORT column in the SYSIBM.LOCATIONS table for SSL connections.

For SSL support, the PORT column must contain the value of the configured secure DRDA port at the remote server. However, if the value of the PORT column is blank and the value of the SECURE column is 'Y', Db2 uses the reserved secure DRDA port (448) as the default.

What to do next

Some Db2 applications might require SSL protection and accept the performance cost for this level of security. However, some applications might be satisfied with unprotected connections. This flexibility can be accomplished by the use of the LOCATION ALIAS name feature.

Consider a Db2 server that is configured to support both non-secure and secure connections. At the Db2 requester, you can define two rows in the SYSIBM.LOCATIONS table: one row that specifies the location name and the non-secure DRDA port of the server and another row that specifies a different location name and the secure DRDA port of the server and SECURE='Y'. At the Db2 server, you can define a LOCATION ALIAS name to provide alternative names for any Db2 requesters that need to access the server by using the SSL protocol.

Related concepts

AT-TLS configuration

You need to complete a set of configurations that are required for Db2 to take advantage of AT-TLS support.

Related tasks

Configuring SSL authentication levels

The Secure Socket Layer (SSL) protocol supports server and client authentication during the handshake phase. You can specify to use either server authentication, client authentication, or both depending on your security need.

Configuring the Db2 server for SSL

To implement SSL support for a Db2 server, you need to make sure that the TCP/IP SQL Listener service task of DDF is capable of listening to a secondary secure port for inbound SSL connections.

Related reference

SSL authentication levels

The Secure Socket Layer (SSL) protocol supports server and client authentication during the handshake phase.

Related information

Db2 for z/OS: Configuring TLS/SSL for Secure Client-Server Communications (IBM Redbooks)

Protecting data sets through RACF

To fully protect the data in Db2, you must take steps to ensure that no other process has access to the data sets in which Db2 data resides.

Use RACF, or a similar external security system, to control access to the data sets just as RACF controls access to the Db2 subsystem. This section explains how to create RACF profiles for data sets and allow their use through Db2.

Assume that the RACF groups Db2 and DB2USER, and the RACF user ID DB2OWNER, have been set up for Db2 IDs. Given that setting, the examples that follow show you how to:

- Add RACF groups to control data sets that use the default Db2 qualifiers.
- Create generic profiles for different types of Db2 data sets and permit their use by Db2 started tasks.
- · Permit use of the profiles by specific IDs.
- Allow certain IDs to create data sets.

Related concepts

Encrypting your data through Db2 built-in functions Db2 provides built-in data encryption and decryption functions that you can use to encrypt sensitive data, such as credit card numbers and medical record numbers.

Encrypting your data with Secure Socket Layer (SSL) support Db2 supports Secure Socket Layer (SSL) protocol by using the z/OS Communications Server IP Application Transparent Transport Layer Security (AT-TLS).

Adding groups to control Db2 data sets

The default high-level qualifier for data sets that contain Db2 databases and recovery logs is DSNC111. The default high-level qualifier for distribution, target, SMP, and other installation data sets is DSN1210.

About this task

The DB2OWNER user ID can create groups that control those data sets by issuing the following commands:

ADDGROUP DSNC111 SUPGROUP(DB2) OWNER(DB2OWNER) ADDGROUP DSN1210 SUPGROUP(DB2) OWNER(DB2OWNER)

Related tasks

Creating generic profiles for data sets Db2 uses specific names to identify data sets for special purposes.

Authorizing Db2 IDs to use data set profiles

Authorization IDs with the installation SYSADM or installation SYSOPR authority need access to most Db2 data sets.

Enabling Db2 IDs to create data sets

You can enable Db2 IDs to create data sets by connecting them to the DSNC111 group that has the CREATE authority.

Creating generic profiles for data sets

Db2 uses specific names to identify data sets for special purposes.

About this task

Suppose that SYSDSP is the RACF user ID for Db2 started tasks in the following examples. DB2OWNER can issue the following commands to create generic profiles for the data sets and give complete control over the data sets to Db2 started tasks:

• For active logs, issue the following commands:

ADDSD 'DSNC111.LOGCOPY*' UACC(NONE) PERMIT 'DSNC111.LOGCOPY*' ID(SYSDSP) ACCESS(ALTER)

• For archive logs, issue the following commands:

ADDSD 'DSNC111.ARCHLOG*' UACC(NONE) PERMIT 'DSNC111.ARCHLOG*' ID(SYSDSP) ACCESS(ALTER)

• For bootstrap data sets, issue the following commands:

ADDSD 'DSNC111.BSDS*' UACC(NONE) PERMIT 'DSNC111.BSDS*' ID(SYSDSP) ACCESS(ALTER)

• For table spaces and index spaces, issue the following commands:

ADDSD 'DSNC111.DSNDBC.*' UACC(NONE) PERMIT 'DSNC111.DSNDBC.*' ID(SYSDSP) ACCESS(ALTER)

• For installation libraries, issue the following command:

ADDSD 'DSN1210.*' UACC(READ)

Started tasks do not need control.

• For other general data sets, issue the following commands:

ADDSD	'DSNC111.*'	UACC(NONE)	
PERMIT	'DSNC111.*'	ID(SYSDSP)	ACCESS(ALTER)

Although all of those commands are not absolutely necessary, the sample shows how you can create generic profiles for different types of data sets. Some parameters, such as universal access, could vary among the types. In the example, installation data sets (DSN1210.*) are universally available for read access.

If you use generic profiles, specify NO on installation panel DSNTIPP for ARCHIVE LOG RACF, or you might get a z/OS error when Db2 tries to create the archive log data set. If you specify YES, Db2 asks RACF to create a separate profile for each archive log that is created, which means that you cannot use generic profiles for these data sets.

To protect VSAM data sets, use the cluster name. You do not need to protect the data component names, because the cluster name is used for RACF checking.

The VSAM resource that is used to store the administrative scheduler task list must be protected in RACF against unauthorized access. Only the administrative scheduler started task user has the UPDATE authority on VSAM resources.

Access by stand-alone Db2 utilities: The following Db2 utilities access objects that are outside of Db2 control:

- DSN1COPY and DSN1PRNT: table space and index space data sets
- DSN1LOGP: active logs, archive logs, and bootstrap data sets
- Change Log Inventory (DSNJU003) and Print Log Map (DSNJU004): bootstrap data sets

The Change Log Inventory and Print Log Map utilities run as batch jobs that are protected by the USER and PASSWORD options on the JOB statement. To provide a value for the USER option, for example SVCAID, issue the following commands:

• For DSN1COPY:

PERMIT 'DSNC111.*' ID(SVCAID) ACCESS(CONTROL)

• For DSN1PRNT:

PERMIT 'DSNC111.*' ID(SVCAID) ACCESS(READ)

• For DSN1LOGP:

PERMIT'DSNC111.LOGCOPY*'ID(SVCAID)ACCESS(READ)PERMIT'DSNC111.ARCHLOG*'ID(SVCAID)ACCESS(READ)PERMIT'DSNC111.BSDS*'ID(SVCAID)ACCESS(READ)

• For Change Log Inventory:

PERMIT 'DSNC111.BSDS*' ID(SVCAID) ACCESS(CONTROL)

• For Print Log Map:

PERMIT 'DSNC111.BSDS*' ID(SVCAID) ACCESS(READ)

The level of access depends on the intended use, not on the type of data set (VSAM KSDS, VSAM linear, or sequential). For update operations, ACCESS(CONTROL) is required; for read-only operations, ACCESS(READ) is sufficient.

You can use RACF to permit programs, rather than user IDs, to access objects. When you use RACF in this manner, IDs that are not authorized to access the log data sets might be able to do so by running the DSN1LOGP utility. Permit access to database data sets through DSN1PRNT or DSN1COPY.

Related tasks

Adding groups to control Db2 data sets

The default high-level qualifier for data sets that contain Db2 databases and recovery logs is DSNC111. The default high-level qualifier for distribution, target, SMP, and other installation data sets is DSN1210.

Authorizing Db2 IDs to use data set profiles

Authorization IDs with the installation SYSADM or installation SYSOPR authority need access to most Db2 data sets.

Enabling Db2 IDs to create data sets

You can enable Db2 IDs to create data sets by connecting them to the DSNC111 group that has the CREATE authority.

Authorizing Db2 IDs to use data set profiles

Authorization IDs with the installation SYSADM or installation SYSOPR authority need access to most Db2 data sets.

About this task

The following command adds the two default IDs that have the SYSADM and SYSOPR authorities if no other IDs are named when Db2 is installed:

ADDUSER (SYSADM SYSOPR)

The next two commands connect those IDs to the groups that control data sets, with the authority to create new RACF database profiles. The ID that has the installation SYSOPR authority (SYSOPR) does not need that authority for the installation data sets.

CONNECT (SYSADM SYSOPR) GROUP(DSNC111) AUTHORITY(CREATE) UACC(NONE) CONNECT (SYSADM) GROUP(DSN1210) AUTHORITY(CREATE) UACC(NONE)

The following set of commands gives the IDs complete control over DSNC111 data sets. The system administrator IDs also have complete control over the installation libraries. Additionally, you can give the system programmer IDs the same control.

PERMIT	'DSNC111.LOGCOPY*'	ID(SYSADM	SYSOPR)	ACCESS(ALTER)
PERMIT	'DSNC111.ARCHLOG*'	ID(SYSADM	SYSOPR)	ACCESS(ALTER)
PERMIT	'DSNC111.BSDS*'	ID(SYSADM	SYSOPR)	ACCESS(ALTER)
PERMIT	'DSNC111.DSNDBC.*'	ID(SYSADM	SYSOPR)	ACCESS(ALTER)
PERMIT	'DSNC111.*'	ID(SYSADM	SYSOPR)	ACCESS(ALTER)
PERMIT	'DSN1210.*'	ID(SYSADM	I)	ACCESS(ALTER)

Related tasks

Adding groups to control Db2 data sets

The default high-level qualifier for data sets that contain Db2 databases and recovery logs is DSNC111. The default high-level qualifier for distribution, target, SMP, and other installation data sets is DSN1210.

Creating generic profiles for data sets

Db2 uses specific names to identify data sets for special purposes.

Enabling Db2 IDs to create data sets

You can enable Db2 IDs to create data sets by connecting them to the DSNC111 group that has the CREATE authority.

Enabling Db2 IDs to create data sets

You can enable Db2 IDs to create data sets by connecting them to the DSNC111 group that has the CREATE authority.

About this task

You can issue the following command to connect several IDs to the DSNC111 group:

```
CONNECT (USER1 USER2 USER3 USER4 USER5)
GROUP(DSNC111) AUTHORITY(CREATE) UACC(NONE)
```

Those IDs can now explicitly create data sets whose names have DSNC111 as the high-level qualifier. Any such data sets that are created by Db2 or by these RACF user IDs are protected by RACF. Other RACF user IDs are prevented by RACF from creating such data sets.

If no option is supplied for PASSWORD on the ADDUSER command that adds those IDs, the first password for the new IDs is the name of the default group, DB2USER. The first time that the IDs sign on, they all use that password, but they must change the password during their first session.

Related tasks

Adding groups to control Db2 data sets

The default high-level qualifier for data sets that contain Db2 databases and recovery logs is DSNC111. The default high-level qualifier for distribution, target, SMP, and other installation data sets is DSN1210.

Creating generic profiles for data sets

Db2 uses specific names to identify data sets for special purposes.

Authorizing Db2 IDs to use data set profiles

Authorization IDs with the installation SYSADM or installation SYSOPR authority need access to most Db2 data sets.

Encrypting your data through Db2 built-in functions

Db2 provides built-in data encryption and decryption functions that you can use to encrypt sensitive data, such as credit card numbers and medical record numbers.

You can encrypt data at the column or value level. You must install the Integrated Cryptographic Service Facility (ICSF) to use the built-in functions for data encryption.

When you use most data encryption, Db2 requires the correct password to retrieve the data in a decrypted format. If an incorrect password is provided, Db2 does not decrypt the data. If the ENCRYPT_DATAKEY built-in function is used to encrypt data, you must have access to the key label stored with the

Db2 for z/OS offers two different sets of built-in functions for encrypting and decrypting data:

- Data encryption using the TDES algorithm: The ENCRYPT_TDES built-in function encrypts data using a password, and the DECRYPT_BIT, DECRYPT_CHAR and DECRYPT_DB built-in functions decrypt data using a password. The DECRYPT_BIT, DECRYPT_CHAR and DECRYPT_DB built-in functions decrypt data that was encrypted with the ENCRYPT_TDES built-in function. The user provides the password when invoking a decryption function
- Data encryption data using the 256-bit AES CBC algorithm: The ENCRYPT_DATAKEY built-in function encrypts data using the 256-bit AES CBC algorithm with either a random initialization vector (IV) or fixed initialization vector (IV) and a key label. The DECRYPT_DATAKEY_INTEGER, DECRYPT_DATAKEY_BIGINT, DECRYPT_DATAKEY_DECIMAL, DECRYPT_DATAKEY_VARCHAR, DECRYPT_DATAKEY_CLOB, DECRYPT_DATAKEY_VARGRAPHIC, DECRYPT_DATAKEY_DBCLOB, AND DECRYPT_DATAKEY_BIT built-in functions decrypt data that was encrypted using the ENCRYPT_DATA KEY built-in function. The decryption process uses the key label stored with the encrypted data to decrypt the data.

Built-in encryption functions work for data that is stored within Db2 subsystem and is retrieved from within that same Db2 subsystem. The encryption functions do not work for data that is passed into and out of a Db2 subsystem. Application Transparent - Transport Layer Security (AT-TLS) is used to encrypt data between Db2 and applications or other data servers.

Attention: When the TDES encryption algorithm is used for encryption, Db2cannot decrypt data without the encryption password. If you forget the encryption password you cannot decrypt the data, and the data might become unusable.

Related concepts

Encrypting your data with Secure Socket Layer (SSL) support Db2 supports Secure Socket Layer (SSL) protocol by using the z/OS Communications Server IP Application Transparent Transport Layer Security (AT-TLS).

Protecting data sets through RACF

To fully protect the data in Db2, you must take steps to ensure that no other process has access to the data sets in which Db2 data resides.

Defining columns for data encrypted using the ENCRYPT_TDES built-in function.

When data is encrypted using the ENCRYPT_TDES built-in function, it is returned as a binary data string. Therefore, encrypted data should be stored in columns that are defined as VARCHAR FOR BIT DATA.

About this task

Columns that hold encrypted data also require additional bytes to hold a header and to reach a multiple of 8 bytes.

Suppose that you have non-encrypted data in a column that is defined as VARCHAR(6). Use the following calculation to determine the column definition for storing the data in encrypted format:

Maximum length of non-encrypted data Number of bytes to the next multiple of 8	6 bytes 2 bytes
24 bytes for encryption key	24 bytes
Encrypted data column length	32 bytes

Therefore, define the column for encrypted data as VARCHAR(32) FOR BIT DATA.

When encrypting data using the ENCRYPT_TDES built-in functions, you can use a password hint. If you use a password hint, Db2 requires an additional 32 bytes to store the hint. Suppose that you have nonencrypted data in a column that is defined as VARCHAR(10). Use the following calculation to determine the column definition for storing the data in encrypted format with a password hint:

Maximum length of non-encrypted data	10 bytes
Number of bytes to the next multiple of 8	6 bytes
24 bytes for encryption key	24 bytes
32 bytes for password hint	32 bytes
Encrypted data column length	72 bytes

Therefore, define the column for encrypted data as VARCHAR(72) FOR BIT DATA when using ENCRYPT_TDES to encrypt your data.

Related tasks

Defining column-level encryption for the ENCRYPT_TDES built-in function For column-level encryption using the ENCRYPT_TDES built-in function, all encrypted values in a column are encrypted with the same password.

Defining the ENCRYPT_TDES function for value-level encryption When you use the ENCRYPT_TDES built-in function for value-level encryption, each value in a given column can be encrypted with a different password. You set the password for each value by using the ENCRYPT keyword with the password.

Optimizing performance of data encrypted with the ENCRYPT_TDES function Encryption using the ENCRYPT_TDES function typically degrades the performance of most SQL statements. Decryption requires extra processing, and encrypted data requires more space in Db2.

Defining columns for data encrypted using the ENCRYPT_DATAKEY built-in function.

When data is encrypted using the ENCRYPT_DATAKEY built-in function, it is returned as a binary data string. Therefore, encrypted data should be stored in columns that are defined as VARBINARY or BLOB.

About this task FL 505 The resulting data type of the ENCRYPT_DATAKEY function is determined by the data type of the first argument. If the data type of the *expression* argument is BIGINT, INTEGER, DECIMAL, CHAR, VARCHAR, GRAPHIC, or VARGRAPHIC, the resulting data type is VARBINARY. If the data type of the *expression* argument is CLOB or DBCLOB, the resulting data type is BLOB.

Columns that hold encrypted data also require additional bytes to hold a header.

The length attribute and the actual length of the result are determined as follows:

- Length attribute of result in byes = (((length attribute of source data in bytes +16-1)/16)*16)+15- byte fixed header +64 bytes for length attribute of key label.
- Actual length of result in bytes = (((actual length of source data in bytes +16-1)/16)*16)+15-byte fixed header + variable length key label in bytes.

The actual length of the result can be longer than the length of *expression*. Therefore, when assigning a resulting encrypted value, the target must be defined with a length attribute that can contain the entire encrypted value.

The result can be null; if *expression* is null, the result is the null value.

Related reference

ENCRYPT_DATAKEY scalar function (Db2 SQL)

Defining column-level encryption for the ENCRYPT_TDES built-in function

For column-level encryption using the ENCRYPT_TDES built-in function, all encrypted values in a column are encrypted with the same password.

Procedure

To define column-level encryption:

1. Create the EMP table with the EMPNO column. The EMPNO column must be defined with the VARCHAR data type, must be defined FOR BIT DATA, and must be long enough to hold the encrypted data. The following statement creates the EMP table:

GUPI

CREATE TABLE EMP (EMPNO VARCHAR(32) FOR BIT DATA);

GUPI

2. Set the encryption password. The following statement sets the encryption password to the host variable :hv_pass:

GUPI

SET ENCRYPTION PASSWORD = :hv_pass;

GUPI

3. Use the ENCRYPT_TDES built-in function to insert encrypted data into the EMP table by issuing the following statements:

GUPI

INSERT INTO EMP (EMPNO) VALUES(ENCRYPT_TDES('47138')); INSERT INTO EMP (EMPNO) VALUES(ENCRYPT_TDES('99514')); INSERT INTO EMP (EMPNO) VALUES(ENCRYPT_TDES('67391'));

GUPI

4. Select the employee ID numbers in decrypted format:

```
GUPI
```

SELECT DECRYPT_CHAR(EMPNO) FROM EMP;

GUPI

If you provide the correct password, Db2 returns the employee ID numbers in decrypted format.

Related tasks

Defining columns for data encrypted using the ENCRYPT_TDES built-in function. When data is encrypted using the ENCRYPT_TDES built-in function, it is returned as a binary data string. Therefore, encrypted data should be stored in columns that are defined as VARCHAR FOR BIT DATA.

Defining the ENCRYPT_TDES function for value-level encryption When you use the ENCRYPT_TDES built-in function for value-level encryption, each value in a given column can be encrypted with a different password. You set the password for each value by using the ENCRYPT keyword with the password.

Optimizing performance of data encrypted with the ENCRYPT_TDES function Encryption using the ENCRYPT_TDES function typically degrades the performance of most SQL statements. Decryption requires extra processing, and encrypted data requires more space in Db2.

Creating views with column-level encryption

You can create a view that uses column-level encryption and selects decrypted data from a table.

About this task

You can define the view with a decryption function in the defining fullselect. If the correct password is provided when the view is queried, Db2 will return decrypted data. Suppose that you want to create a view that contains decrypted employee ID numbers from the EMP table.

Procedure

To create a view that uses column-level encryption and selects decrypted data:

1. Create a view on the EMP table by using the following statement:

GUPI

CREATE VIEW CLR_EMP (EMPNO) AS SELECT DECRYPT_CHAR(EMPNO) FROM EMP;

GUPI

2. Set the encryption password so that the fullselect in the view definition can retrieve decrypted data.

Use the following statement:

GUPI

```
SET ENCRYPTION PASSWORD = :hv_pass;
```

GUPI

3. Select data from the view by using the following statement:

GUPI

SELECT EMPNO FROM CLR_EMP;

GUPI

Related tasks

Using password hints with column-level encryption

Db2 can store encryption password hints to help with forgotten encryption passwords. Each password hint uses 32 bytes in the encrypted column.

Using password hints with column-level encryption

Db2 can store encryption password hints to help with forgotten encryption passwords. Each password hint uses 32 bytes in the encrypted column.

Procedure

To use password hints with column-level encryption, choose one of the following options:

• Issue the SET ENCRYPTION PASSWORD statement to set the password hint.

Use the following statement to set the password hint to the host variable hv_hint: GUPI

SET ENCRYPTION PASSWORD = :hv_pass WITH HINT = :hv_hint;

GUPI

• Use the GETHINT function to return the password hint.

Suppose that the EMPNO column in the EMP table contains encrypted data and that you submitted a password hint when you inserted the data. Suppose that you cannot remember the encryption password for the data. Use the following statement to return the password hint: **GUPT**

SELECT GETHINT (EMPNO) FROM EMP;

GUPI

Related tasks

<u>Creating views with column-level encryption</u> You can create a view that uses column-level encryption and selects decrypted data from a table.

Defining the ENCRYPT_TDES function for value-level encryption

When you use the ENCRYPT_TDES built-in function for value-level encryption, each value in a given column can be encrypted with a different password. You set the password for each value by using the ENCRYPT keyword with the password.

About this task

The following keywords are used with value-level encryption:

ENCRYPT_TDES

Indicates which data requires encryption. Also, encryption passwords, and optionally password hints, are indicated as part of the ENCRYPT_TDES keyword for value-level encryption.

Recommendation: Use host variables instead of literal values for all passwords and password hints. If statements contain literal values for passwords and password hints, the security of the encrypted data can be compromised in the Db2 catalog and in a trace report.

DECRYPT_BIT, DECRYPT_CHAR, DECRYPT_DB

Checks for the correct password and decrypts data when the data is selected.

Example

Suppose that a web application collects user information about a customer. This information includes the customer name, which is stored in host variable custname; the credit card number, which is stored in a host variable cardnum; and the password for the card number value, which is stored in a host variable userpswd. The application uses the following statement to insert the customer information: **GUPT**

INSERT INTO CUSTOMER (CCN, NAME)
VALUES(ENCRYPT(:cardnum, :userpswd), :custname);

GUPI

Before the application displays the credit card number for a customer, the customer must enter the password. The application retrieves the credit card number by using the following statement:

GUPI

SELECT DECRYPT_CHAR(CCN, :userpswd) FROM CUSTOMER WHERE NAME = :custname;

GUPI

Related tasks

Defining columns for data encrypted using the ENCRYPT_TDES built-in function. When data is encrypted using the ENCRYPT_TDES built-in function, it is returned as a binary data string. Therefore, encrypted data should be stored in columns that are defined as VARCHAR FOR BIT DATA.

Defining column-level encryption for the ENCRYPT_TDES built-in function For column-level encryption using the ENCRYPT_TDES built-in function, all encrypted values in a column are encrypted with the same password.

Optimizing performance of data encrypted with the ENCRYPT_TDES function Encryption using the ENCRYPT_TDES function typically degrades the performance of most SQL statements. Decryption requires extra processing, and encrypted data requires more space in Db2.

Using password hints with value-level encryption

Db2 can store encryption password hints to help with forgotten encryption passwords. Each password hint uses 32 bytes in the encrypted column.

About this task

For value-level encryption, the password hint is set with the ENCRYPT keyword. The GETHINT function returns the password hint.

Recommendation: Use host variables instead of literal values for all passwords and password hints. If the statements contain literal values for passwords and password hints, the security of the encrypted data can be compromised in the Db2 catalog and in a trace report.

Example

Suppose that you want the application from the previous example to use a hint to help customers remember their passwords. The application stores the hint in the host variable pswdhint. For this example, assume the values 'Tahoe' for userpswd and 'Ski Holiday' for pswdhint. The application uses the following statement to insert the customer information: **GUPI**

INSERT INTO CUSTOMER (CCN, NAME)
VALUES(ENCRYPT(:cardnum, :userpswd, :pswdhint), :custname);

GUPI

If the customer requests a hint about the password, the following query is used:

GUPI

SELECT GETHINT(CCN) INTO :pswdhint FROM CUSTOMER WHERE NAME = :custname;

GUPI

The value for pswdhint is set to 'Ski Holiday' and returned to the customer. Hopefully the customer can remember the password 'Tahoe' from this hint.

Related tasks

Encrypting non-character values

Db2 supports encryption for numeric and datetime data types indirectly through casting. If non-character data is cast as VARCHAR or CHAR, the data can be encrypted.

Encrypting non-character values

Db2 supports encryption for numeric and datetime data types indirectly through casting. If non-character data is cast as VARCHAR or CHAR, the data can be encrypted.

Example

Suppose that you need to encrypt timestamp data and retrieve it in decrypted format. Perform the following steps:

1. Create a table to store the encrypted values and set the column-level encryption password by using the following statements:

```
CREATE TABLE ETEMP (C1 VARCHAR(124) FOR BIT DATA);
SET ENCRYPTION PASSWORD :hv_pass;
```

2. Cast, encrypt, and insert the timestamp data by using the following statement:

INSERT INTO ETEMP VALUES ENCRYPT(CHAR(CURRENT TIMESTAMP));

3. Recast, decrypt, and select the timestamp data by using the following statement:

SELECT TIMESTAMP(DECRYPT_CHAR(C1)) FROM ETEMP;

Related tasks

Using password hints with value-level encryption

Db2 can store encryption password hints to help with forgotten encryption passwords. Each password hint uses 32 bytes in the encrypted column.

Using predicates for encrypted data

When data is encrypted, only = and <> predicates provide accurate results. Predicates such as >, <, and LIKE return inaccurate results for encrypted data.

About this task

Suppose that the value 1234 is encrypted as H71G. Also suppose that the value 5678 is encrypted as BF62. If you use a <> predicate to compare these two values in encrypted format, you receive the same result as you will if you compare these two values in decrypted format:

Decrypted: 1234 <> 5678 True Encrypted: H71G <> BF62 True

In both case, they are not equal. However, if you use a < predicate to compare these values in encrypted format, you receive a different result than you will if you compare these two values in decrypted format:

Decrypted: 1234 < 5678 True Encrypted: H71G < BF62 False

To ensure that predicates such as >, <, and LIKE return accurate results, you must first decrypt the data.

Optimizing performance of data encrypted with the ENCRYPT_TDES function

Encryption using the ENCRYPT_TDES function typically degrades the performance of most SQL statements. Decryption requires extra processing, and encrypted data requires more space in Db2.

About this task

If a predicate requires decryption, the predicate is a stage 2 predicate, which can degrade performance. Encrypted data can also impact your database design, which can indirectly impact performance. To minimize performance degradation, use encryption only in cases that require encryption.

Recommendation: Encrypt only a few highly sensitive data elements, such credit card numbers and medical record numbers.

Some data values are poor candidates for encryption. For example, boolean values and other small value sets, such as the integers 1 through 10, are poor candidates for encryption. Because few values are possible, these types of data can be easy to guess even when they are encrypted. In most cases, encryption is not a good security option for this type of data.

Creating indexes on encrypted data can improve performance in some cases. Exact matches and joins of encrypted data (if both tables use the same encryption key to encrypt the same data) can use the indexes that you create. Because encrypted data is binary data, range checking of encrypted data requires table space scans. Range checking requires all the row values for a column to be decrypted. Therefore, range checking should be avoided, or at least tuned appropriately.

Examples: Encryption performance scenario

The following scenario contains a series of examples that demonstrate how to improve performance while working with encrypted data.

Example

Suppose that you must store EMPNO in encrypted form in the EMP table and in the EMPPROJ table. To define tables and indexes for the encrypted data, use the following statements:

GUPI

CREATE TABLE EMP (EMPNO VARCHAR(48) FOR BIT DATA, NAME VARCHAR(48)); CREATE TABLE EMPPROJ(EMPNO VARCHAR(48) FOR BIT DATA, PROJECTNAME VARCHAR(48)); CREATE INDEX IXEMPPRJ ON EMPPROJ(EMPNO);

GUPI

Example

Next, suppose that one employee can work on multiple projects, and that you want to insert employee and project data into the table. To set the encryption password and insert data into the tables, use the following statements: **GUPT**

```
SET ENCRYPTION PASSWORD = :hv_pass;
SELECT INTO :hv_enc_val FROM FINAL TABLE
 (INSERT INTO EMP VALUES (ENCRYPT('A7513'),'Super Prog'));
INSERT INTO EMPPROJ VALUES (:hv_enc_val,'UDDI Project');
INSERT INTO EMPPROJ VALUES (:hv_enc_val,'DB2 10 ');
SELECT INTO :hv_enc_val FROM FINAL TABLE
 (INSERT INTO EMP VALUES (ENCRYPT('4NF18'),'Novice Prog'));
INSERT INTO EMPPROJ VALUES (:hv_enc_val,'UDDI Project');
```

GUPI

You can improve the performance of INSERT statements by avoiding unnecessary repetition of encryption processing. Note how the host variable hv_enc_val is defined in the SELECT INTO statement and then used in subsequent INSERT statements. If you need to insert a large number of rows that contain the same encrypted value, you might find that the repetitive encryption processing degrades performance. However, you can dramatically improve performance by encrypting the data, storing the encrypted data in a host variable, and inserting the host variable.

Example

Next, suppose that you want to find the programmers who are working on the UDDI Project. Consider the following pair of SELECT statements:

Poor performance

The following query shows how not to write the query for good performance:

GUPI

```
SELECT A.NAME, DECRYPT_CHAR(A.EMPNO) FROM EMP A, EMPPROJECT B
WHERE DECRYPT_CHAR(A.EMPNO) = DECRYPT_CHAR(B.EMPNO) AND
B.PROJECT ='UDDI Project';
```

GUPI Although the preceding query returns the correct results, it decrypts every EMPNO value in the EMP table and every EMPNO value in the EMPPROJ table where PROJECT = 'UDDI Project' to perform the join. For large tables, this unnecessary decryption is a significant performance problem

Good performance

The following query produces the same result as the preceding query, but with significantly better performance. To find the programmers who are working on the UDDI Project, use the following statement:

GUPI

SELECT A.NAME, DECRYPT_CHAR(A.EMPNO) FROM EMP A, EMPPROJ B
WHERE A.EMPNO = B.EMPNO AND B.PROJECT ='UDDI Project';

GUPI

Example

Next, suppose that you want to find the projects that the programmer with employee ID A7513 is working on. Consider the following pair of SELECT statements:

Poor performance

The following query requires Db2 to decrypt every EMPNO value in the EMPPROJ table to perform the join:

GUPI

```
SELECT PROJECTNAME FROM EMPPROJ WHERE DECRYPT_CHAR(EMPNO) = 'A7513';
```

GUPI

Good performance

The following query encrypts the literal value in the predicate so that Db2 can compare it to encrypted values that are stored in the EMPNO column without decrypting the whole column. To find the projects that the programmer with employee ID A7513 is working on, use the following statement:

GUPI

SELECT PROJECTNAME FROM EMPPROJ WHERE EMPNO = ENCRYPT('A7513');

GUPI

Related tasks

Defining columns for data encrypted using the ENCRYPT_TDES built-in function. When data is encrypted using the ENCRYPT_TDES built-in function, it is returned as a binary data string. Therefore, encrypted data should be stored in columns that are defined as VARCHAR FOR BIT DATA.

Defining column-level encryption for the ENCRYPT_TDES built-in function

For column-level encryption using the ENCRYPT_TDES built-in function, all encrypted values in a column are encrypted with the same password.

Defining the ENCRYPT_TDES function for value-level encryption

When you use the ENCRYPT_TDES built-in function for value-level encryption, each value in a given column can be encrypted with a different password. You set the password for each value by using the ENCRYPT keyword with the password.

Db2 12 for z/OS: Managing Security (Last updated: 2024-09-06)

Chapter 10. Auditing access to Db2

Security auditing allows you to inspect and examine the adequacy and effectiveness of the policies and procedures that you put in place to secure your data.

Db2 provides the ability for you to monitor if your security plan is adequately designed based on your security objectives and determine if your implementation techniques and procedures are effectively carried out to protect your data access and consistency. It enables you to address the following fundamental questions about your data security.

- · What sensitive data requires authorized access?
- Who is privileged to access the data?
- Who has actually accessed the data?
- What attempts are made to gain unauthorized access?

The Db2 catalog contains critical authorization and authentication information. This information provides the primary audit trail for the Db2 subsystem. You can retrieve the information from the catalog tables by issuing SQL queries.

Most of the catalog tables describe the Db2 objects, such as tables, views, table spaces, packages, and plans. Other tables, particularly those with the "AUTH" character string in their names, hold records of every granted privilege and authority. Each catalog record of a grant contains the following information:

- · Name of the object
- Type of privilege
- IDs that receive the privilege
- IDs that grant the privilege
- Time of the grant

The Db2 audit trace can help you monitor and track all the accesses to your protected data. The audit trace records provide another important trail for the Db2 subsystem. You can use the the audit trace to record the following access information:

- · Changes in authorization IDs
- · Changes to the structure of data, such as dropping a table
- · Changes to data values, such as updating or inserting records
- Access attempts by unauthorized IDs
- Results of GRANT statements and REVOKE statements
- · Mapping of Kerberos security tickets to IDs
- · Other activities that are of interest to auditors

Related tasks

Auditing manager access

The Spiffy payroll data is extremely sensitive. The security plan requires the audit trace to be automatically started for all classes whenever Db2 is started.

Auditing payroll operations and management

You can create an audit policy for the payroll update table to audit payroll operation and management activities.

Determining active security measures

If you are a security auditor, you must know the security measures that are enabled on the Db2 subsystem.

About this task

You can determine whether Db2 authorization checking, the audit trace, and data definition control are enabled in the following ways:

Audit trace

To see whether the trace is running, display the status of the trace by the command DISPLAY TRACE(AUDIT).

Db2 authorization checking

Without changing anything, look at panel DSNTIPP. If the value of the USE PROTECTION field is YES, Db2 checks privileges and authorities before permitting any activity.

Data definition control

Data definition control is a security measure that provides additional constraints to existing authorization checks. With it, you control how specific plans or collections of packages can use data definition statements. To determine whether data definition control is active, look at option 1 on the DSNTIPZ installation panel.

Db2 audit trace

The audit trace enables you to trace different events or categories of events by authorization IDs, object ownership, and so on.

When started, the audit trace records certain types of actions and sends the report to a named destination. The trace reports can indicate who has accessed data.

As with other types of Db2 traces, you can choose the following options for the audit trace:

- · Categories of events
- Particular authorization IDs or plan IDs
- · Methods to start and stop the audit trace
- · Destinations for audit records

You can choose whether to audit the activity on a table by specifying an option of the CREATE and ALTER statements.

Audit trace classes

The following table shows the IFCIDs that are activated for each audit trace class.

Tip: IFCID numbers are often presented in Db2 and its documentation with three or four digits and leading zeros. For example, you might find: "IFCID 1," "IFCID 001," or "IFCID 0001." However, you can assume that these references each have the same meaning.
Table 95. Classes for Db2 audit trace

Class	Description of class	Activated IFCIDs
1	Access attempts denied due to inadequate authorization. Class 1 is also activated when you omit the CLASS keyword from the START TRACE command when you start the audit trace.	140
2	Explicit GRANT and REVOKE.	141
3	CREATE, ALTER, and DROP operations against audited tables.	142
4	First change of audited object.	143
5	First read of audited object.	144
6	Bind time information about SQL statements that involve audited objects.	145
7	Assignment or change of authorization ID.	55, 83, 87, 169, 319
8	Utilities.	23, 24, 25, 219, 220
9	Installation-defined audit record.	146, 392
10	Trusted context information.	269, 270
11	Audits of successful access.	361 ^{"1" on page 347}
12-29	Reserved.	
30-32	Available for local use.	

Notes:

1. If IFCID 361 is started through START TRACE, all successful access is traced. If IFCID 361 is started because audit policy category SYSADMIN is on, only successful access using the SYSADMIN administrative authority is traced. If IFCID 361 is started because audit policy category DBADMIN is on, only successful access using the DBADMIN administrative authority is traced.

Audit trace field (IFCID) descriptions

You can find descriptions of trace records in the IFCID flat file (DSNWMSGS). The most current version of DSNWMSGS is available only for clients who have Db2 12 for z/OS licenses. The information is in a PDF file. To locate this information, see Db2 12 for z/OS IFCID flat file (DSNWMSGS).

Related concepts

Audit trace records

An audit trace record contains the information about the authorization ID that initiated the activity that is traced.

Audit trace reports

If you regularly start the audit trace for all classes, you can generate audit reports based on the data that you accumulate.

Related tasks

Starting the audit trace You can start an audit trace at any time or specify that an audit trace starts automatically whenever Db2 is started.

Stopping the audit trace

You can have multiple traces that run at the same time, including more than one audit trace. You can stop a particular trace by issuing the STOP TRACE command with the same options that you use for START TRACE.

Related reference

-START TRACE command (Db2) (Db2 Commands)

Authorization IDs traced by auditing

An audit trace generally identifies a process by its primary authorization ID. It records the primary ID before and after the invocation of an authorization exit routine. Therefore, you can identify the primary ID that is associated with a data change.

Exception: If a primary ID has been translated many times, you might not be able to identify the primary ID that is associated with a change. Suppose that the server does not recognize the translated ID from the requesting site. In this case, you cannot use the primary ID to gather all audit records for a user that accesses remote data.

The AUTHCHG record shows the values of all secondary authorization IDs that are established by an exit routine.

With the audit trace, you can also determine which primary ID is responsible for the action of a secondary ID or a current SQL ID. Suppose that the user with primary ID SMITHJ sets the current SQL ID to TESTGRP to grant privileges over the table TESTGRP.TABLE01 to another user. The Db2 catalog records the grantor of the privileges as TESTGRP. However, the audit trace shows that SMITHJ issued the grant statement.

Recommendation: Consider carefully the consequences of altering that ID by using an exit routine because the trace identifies a process by its primary ID. If the primary ID identifies a unique user, individual accountability is possible. However, if several users share the same primary ID, you cannot tell which user issues a particular GRANT statement or runs a particular application plan.

Audit classes

When you start the trace, you choose the events to audit by specifying one or more audit classes.

PSPI

The trace records are limited to 5000 bytes; the descriptions that contain long SQL statements might be truncated. The following table describes the available classes and the events that they include.

	Fronts that are traced
Audit class	Events that are traced
1	Access attempts that Db2 denies because of inadequate authorization. This class is the default.
2	Explicit GRANT and REVOKE statements and their results. This class does not trace implicit grants and revokes.
3	Traces CREATE, DROP, and ALTER operations against an audited table or a table that is enabled with multilevel security with row-level granularity. For example, it traces the updates to a table created with the AUDIT CHANGES or AUDIT ALL clause. It also traces the deletion of a table as the result of a DROP TABLESPACE or DROP DATABASE statement.

Table 96. Audit classes and the events that they trace

Table 96. Audit classes and the events that they trace (continued)		
Audit class	Events that are traced	
4	Changes to audited tables. Only the first attempt to change a table, within a unit of recovery, is recorded. (If the agent or the transaction issues more than one COMMIT statement, the number of audit records increases accordingly.) The changed data is not recorded; only the attempt to make a change is recorded. If the change is not successful and is rolled back, the audit record remains; it is not deleted. This class includes access by the LOAD utility. Accesses to a dependent table that are caused by attempted deletions from a parent table are also audited. The audit record is written even if the delete rule is RESTRICT, which prevents the deletion from the parent table. The audit record is also written when the rule is CASCADE or SET NULL, which can result in deletions that cascade to the dependent table.	
5	All read accesses to tables that are identified with the AUDIT ALL clause. As in class 4, only the first access within a Db2 unit of recovery is recorded. References to a parent table are also audited.	
6	The bind of static and dynamic SQL statements of the following types:	
	 INSERT, UPDATE, DELETE, CREATE VIEW, and LOCK TABLE statements for audited tables. Except for the values of host variables, the audit record contains the entire SQL statement. SELECT statements on tables that are identified with the AUDIT ALL clause. Except for the values of host variables, the audit record contains the entire SQL statement. 	
7	Assignment or shange of an authorization ID because of the following research	
1	Assignment or change of an authorization 1D because of the following reasons:	
	Changes through an exit routine (default or user-written) Changes through a SET CURRENT SOLID statement	
	An outbound or inbound authorization ID translation	
	 An ID that is being mapped to a RACF ID from a Kerberos security ticket 	
8	The start of a utility job, and the end of each phase of the utility	
9	Various types of records that are written to IFCID 0146 or IFCID 0392 by the IFI WRITE function	
10	CREATE and ALTER TRUSTED CONTEXT statements, establish trusted connection information and switch user information	
11	Audit the use of any administrative authority and the successful execution of any authorization ID	

PSPI

Audit trace reports

If you regularly start the audit trace for all classes, you can generate audit reports based on the data that you accumulate.

Consider producing audit trace reports that focus on the following important security events:

Use of sensitive data

You should define tables that contain sensitive data, such as employee salary records, with the AUDIT ALL option. You can report use by table and by authorization ID to look for access by unusual IDs, at unusual times, or of unexpected types. You should also record any ALTER or DROP operations that affect the data. Use audit classes 3, 4, and 5.

Grants of critical privileges

Carefully monitor IDs with special authorities, such as SYSADM and DBADM. Also carefully monitor IDs with privileges over sensitive data, such as an update privilege on records of accounts payable. You can query the Db2 catalog to determine which IDs hold privileges and authorities at a particular time. To determine which IDs received privileges and then had them revoked, use audit class 2 and consult the audit records.

Unsuccessful access attempts

Investigate all unsuccessful access attempts. Although some access failures are only user errors, others can be attempts to violate security. If you have sensitive data, always use trace audit class 1. You can report by table or by authorization ID.

Related concepts

Db2 audit trace

The audit trace enables you to trace different events or categories of events by authorization IDs, object ownership, and so on.

Audit trace records

An audit trace record contains the information about the authorization ID that initiated the activity that is traced.

Audit trace records

An audit trace record contains the information about the authorization ID that initiated the activity that is traced.

In addition, it contains the following information:

- The LOCATION of the ID that initiated the activity (if the access was initiated from a remote location)
- · The type of activity and the time that the activity occurred
- · The Db2 objects that were affected
- Whether access was denied
- The owner of a particular plan and package
- The database alias (DBALIAS) that was used to access a remote location or a location alias that was accepted from a remote application.

Related concepts

Db2 audit trace

The audit trace enables you to trace different events or categories of events by authorization IDs, object ownership, and so on.

Audit trace reports

If you regularly start the audit trace for all classes, you can generate audit reports based on the data that you accumulate.

Related tasks

Collecting audit trace records

You can prepare the System Management Facility (SMF) or Generalized Trace Facility (GTF) to accept audit trace records the same way as you prepare performance trace records. The records are of SMF type 102, as are performance trace records.

Formatting audit trace records

You can extract, format, and print Db2 trace records.

Limitations of the audit trace

The audit trace has certain limitations, including that it does not automatically record everything.

The audit trace has the following additional limitations:

• The audit trace must be turned on; it is not on by default.

- The trace does not record old data after it is changed.
- If an agent or transaction accesses a table more than once in a single unit of recovery, the audit trace records only the first access.
- The audit trace does not record accesses if you do not start the audit trace for the appropriate class of events.
- Except class 8, the audit trace does not audit certain utilities. For example, the trace audits the first access of a table with the LOAD utility, but it does not audit access by the COPY, RECOVER, and REPAIR utilities. The audit trace does not audit access by stand-alone utilities, such as DSN1PRNT.
- The trace audits only the tables that you specifically choose to audit.
- You cannot audit access to auxiliary tables.
- You cannot audit the catalog tables because you cannot create or alter catalog tables.

This auditing coverage is consistent with the goal of providing a moderate volume of audit data with a low impact on performance. However, when you choose classes of events to audit, consider that you might ask for more data than you are willing to process.

Starting the audit trace

You can start an audit trace at any time or specify that an audit trace starts automatically whenever Db2 is started.

About this task

The default option for the AUDITST subsystem parameter is NO. When NO is specified, audit traces do not start automatically.

Procedure

To start an audit trace, choose one of the following options:

• Set the AUDITST subsystem parameter to * (an asterisk).

This will cause a complete audit trace to start automatically whenever Db2 is started.

• Set the AUDITST subsystem parameter to YES.

This will cause an audit trace for the default class (class 1: access denials) and the default destination (the SMF data set) to start automatically whenever Db2 is started.

• Set the AUDITST subsystem parameter to a list of those classes (for example, 1,3,5).

This will cause an audit trace for specific audit trace classes to start automatically whenever Db2 is started.

• Issue the START TRACE command at any time.

This will cause an audit trace to start. You can choose the audit classes to trace and the destination for trace records. You can also include an identifying comment.

The following command starts an audit trace for classes 4 and 6 with distributed activity: GUPI

```
-START TRACE (AUDIT) CLASS (4,6) DEST (GTF) LOCATION (*)
COMMENT ('Trace data changes; include text of dynamic DML statements.')
```

GUPI

Related concepts

Db2 audit trace

The audit trace enables you to trace different events or categories of events by authorization IDs, object ownership, and so on.

Related tasks

Stopping the audit trace

You can have multiple traces that run at the same time, including more than one audit trace. You can stop a particular trace by issuing the STOP TRACE command with the same options that you use for START TRACE.

Related reference

AUDIT TRACE field (AUDITST subsystem parameter) (Db2 Installation and Migration) DSNTIPN: Tracing parameters panel (Db2 Installation and Migration) -START TRACE command (Db2) (Db2 Commands)

Stopping the audit trace

You can have multiple traces that run at the same time, including more than one audit trace. You can stop a particular trace by issuing the STOP TRACE command with the same options that you use for START TRACE.

Procedure

GUPI To stop a specific trace, use the following approaches:

• Issue the STOP TRACE command and included the options to uniquely identify a particular trace.

-STOP TRACE (AUDIT) CLASS (4,6) DEST (GTF)

• If you did not save the START command, use DISPLAY TRACE to determine the trace number to stop. For example, dISPLAY TRACE (AUDIT) might return a message like the following output:

TNO	TYPE	CLASS	DEST	QUAL
01	AUDIT	01	SMF	ŇO
02	AUDIT	04,06	GTF	YES

The message indicates that two audit traces are active. Trace 1 traces events in class 1 and sends records to the SMF data set. Trace 1 can be a trace that starts automatically whenever Db2 starts. Trace 2 traces events in classes 4 and 6 and sends records to GTF.

You can stop either trace by using its identifying number (TNO). For example, the following command stops trace 1:

-STOP TRACE AUDIT TNO(1)

GUPI

Related concepts

Db2 audit trace

The audit trace enables you to trace different events or categories of events by authorization IDs, object ownership, and so on.

Related tasks

Starting the audit trace

You can start an audit trace at any time or specify that an audit trace starts automatically whenever Db2 is started.

Collecting audit trace records

You can prepare the System Management Facility (SMF) or Generalized Trace Facility (GTF) to accept audit trace records the same way as you prepare performance trace records. The records are of SMF type 102, as are performance trace records.

About this task

If you send trace records to SMF (the default), data might be lost in the following circumstances:

• SMF fails while Db2 continues to run.

• An unexpected abend (such as a TSO interrupt) occurs while Db2 is transferring records to SMF.

In those circumstances, SMF records the number of records that are lost. z/OS provides an option to stop the system rather than to lose SMF data.

Related concepts

Audit trace records

An audit trace record contains the information about the authorization ID that initiated the activity that is traced.

Related tasks

Formatting audit trace records You can extract, format, and print Db2 trace records.

Formatting audit trace records

You can extract, format, and print Db2 trace records.

About this task

You can use any of the following methods to extract, format, and print the trace records:

- Db2 Audit Management Expert for z/OS
- IBM Tivoli® zSecure Audit
- IBM Tivoli OMEGAMON[®] XE on z/OS
- · Your own application program to access the SMF data
- The instrumentation facility interface (IFI) as an online resource to retrieve audit records.

Related concepts

Audit trace records

An audit trace record contains the information about the authorization ID that initiated the activity that is traced.

Related tasks

Collecting audit trace records

You can prepare the System Management Facility (SMF) or Generalized Trace Facility (GTF) to accept audit trace records the same way as you prepare performance trace records. The records are of SMF type 102, as are performance trace records.

Auditing in a distributed data environment

The Db2 audit trace records any access to your data, whether the request is from a remote location or from your local Db2 subsystem.

The trace record for a remote request reports the authorization ID as the final result of one of the following conditions:

- An outbound translation
- An inbound translation
- · Activity of an authorization exit routine

Essentially, the ID on a trace record for a remote request is the same as the ID to which you grant access privileges for your data. Requests from your location to a remote Db2 are audited only if an audit trace is active at the remote location. The output from the trace appears only in the records at that location.

Db2 audit policies

An *audit policy* is a set of criteria that determines the categories to be audited. It helps you configure and control the audit requirements of your security policies and to monitor data access by applications and individual users (authorization IDs or roles), including administrative authorities.

GUPT You create Db2 audit policies by inserting rows in the SYSIBM.SYSAUDITPOLICIES table. Users with appropriate authorities can modify the audit policies by issuing UPDATE or DELETE statements.

Db2 supports several types of audit policies, including audit policies that you start manually, audit policies that start automatically when Db2 starts, secure audit policies, and tamper-proof audit policies. The DB2START column in the SYSIBM.SYSAUDIPOLICIES table specifies the type of audit policy.

After a Db2 audit policy is created, users with the required authorities can start and manage the policies by issuing **START TRACE**, **STOP TRACE**, and **DISPLAY TRACE** commands with the AUDTPLCY option to start and manage audit polices.

Authorization for Db2 audit policies

If the SEPARATE_SECURITY subsystem parameter is set to YES, only the SECADM authority has implicit INSERT, UPDATE, and DELETE privileges on the SYSIBM.SYSAUDITPOLICIES table. If SEPARATE_SECURITY is set to NO, SYSADM authority also has these implicit privileges. For more information, see "Separating the SYSADM authority" on page 63.

Any user with authority to start traces can start any audit policy. However, some types of audit policies can only be modified or stopped with specific authorities.

With *secure audit policies*, SECADM authority is always required to stop the audit policy, regardless of the SEPARATE_SECURITY subsystem parameter value. Secure audit policies are created with DB2START='S' in the SYSIBM.SYSAUDITPOLICIES table.

<u>FL 509</u>With *tamper proof audit polices*, external authorities are required to either modify or stop the audit policy. Tamper-proof audit policies are created with DB2START='T' in the SYSIBM.SYSAUDITPOLICIES table. For more information, see <u>"Updating or stopping tamper-proof audit policies</u>" on page 360.

For any type of audit policy, each of following authorities has implicit SELECT privilege on the SYSIBM.SYSAUDITPOLICIES table: SECADM, SYSADM, ACCESSCTRL, DATAACCESS, system DBADM, SQLADM, and SYSCRTL.

If a view is created on the SYSIBM.SYSAUDITPOLICIES table, the DATAACCESS authority can perform INSERT, UPDATE, and DELETE on the view to indirectly INSERT, UPDATE, and DELETE on the SYSIBM.SYSAUDITPOLICIES table.

GUPI

Related reference

SYSAUDITPOLICIES catalog table (Db2 SQL) -START TRACE command (Db2) (Db2 Commands) -STOP TRACE command (Db2) (Db2 Commands) -DISPLAY TRACE command (Db2) (Db2 Commands) Administrative authorities in Db2 for z/OS Each administrative authority in Db2 for z/OS is vested with a specific set of privileges.

Audit category

Db2 audit policies are created and stored in the SYSIBM.SYSAUDITPOLICIES table. Each policy is specified with specific audit categories.

PSPI Db2 supports the following audit categories:

Table 97. Db2 audit policy categories		
Category	Description	
CHECKING	Generates IFCID 140 trace records for denied access attempts due to inadequate Db2 authorization and IFCID 83 trace records for RACF authentication failures	
VALIDATE	Generates IFCID 55, 83, 87, 169, and 319 trace records for new or changed assignments of authorization IDs and IFCID 269 trace records for the establishment of trusted connections or the switch of users in existing trusted connections	
OBJMAINT	Generates IFCID 142 trace records when tables are altered or dropped. When an audit policy is defined, it specifies the tables to be audited. The same audit policy can be used to audit different tables in a schema by specifying the table names with the SQL LIKE predicate.	
	Only tables that are defined in the following types of table spaces can be audited:	
	 Universal table space (UTS), including UTS that contains implicitly created tables, such as XML tables 	
	Traditional partitioned table space	
	 Segmented table space. 	
	In addition to tables, an audit policy can also be used to audit clone tables and tables that are implicitly created for XML columns.	
	The type of the object to be audited can be specified by using the OBJECTTYPE column. The default OBJECTTYPE column value of blank indicates that all of the supported object types are audited.	
EXECUTE	Generates IFCID 143, 144 and 145 trace records for every SQL statement with a unique statement ID that changes or reads against tables that are identified in the audit policy. IFCID 145 records SQL bind time information that includes the text and the unique ID of a SQL statement. The SQL statement ID is used in the IFCID 143 and 144 trace records to record any change or reading by the SQL statement identified in the IFCID 145 trace records.	
	When an audit policy is defined, it specifies the tables to be audited. The same audit policy can be used to audit different tables in a schema by specifying the table names with the SQL LIKE predicate.	
	Only tables that are defined in the following types of table spaces can be audited:	
	 Universal table space (UTS), including UTS that contains implicitly created tables, such as XML tables 	
	Traditional partitioned table space	
	 Segmented table space. 	
	In addition to tables, an audit policy can also be used to audit clone tables and tables that are implicitly created for XML columns.	
	The type of the object to be audited can be specified by using the OBJECTTYPE column. The default OBJECTTYPE column value of blank indicates that all of the supported object types are audited.	
	If the audit policy is started after the SQL statement is started, access to the table is not be audited.	
CONTEXT	Generates IFCID 23, 24, and 25 records.	

Table 97. Db2 audit policy categories (continued)		
Category	Description	
SECMAINT	Generates IFCID 141 trace records for granting and revoking privileges or administrative authorities, IFCID 270 trace records for creating and altering trusted contexts, and IFCID 271 trace records for creating, altering, and dropping row permissions or column masks.	
SYSADMIN	Generates IFCID 361 trace records when an administrative authority, in the order of installation SYSADM, installation SYSOPR, SYSOPR, SYSCTRL, or SYSADM, satisfies the required privilege for performing an operation	
	If the Access Control Authorization Exit (ACAE) is active, only the operations that are performed by the installation SYSADM and installation SYSOPR authorities are audited.	
DBADMIN	Generates IFCID 361 trace records when an administrative authority, in the order of DBMAINT, DBCTRL, DBADM, PACKADM, SQLADM, system DBADM, DATAACCESS, ACCESSCTRL, or SECADM, satisfies the required privilege for performing an operation	
	The database name can be specified for auditing the DBADM, DBCTRL and DBMAINT authorities. If the database name is not specified, all the databases, including implicit databases, are audited.	
	The collection ID can be specified for auditing the PACKADM authority. If the collection ID is specified, all packages in that collection are audited. If the collection ID is not specified, the packages in all collections are audited.	
	If the Access Control Authorization Exit (ACAE) is active, only the operations that are performed by the SECADM authority are audited.	

For the SYSADMIN and DBADMIN categories, Db2 checks a set of rules for each operation to determine the required authorization. In general, the rules are checked in the order of installation SYSADM, installation SYSOPR (if applicable), specific privileges required for the operation (i.e., SELECT, UPDATE), database authorities (i.e., DBMAINT, DBCTRL, DBADM), system database authorities (i.e., SQLADM, system DBADM, DATAACCESS, and ACCESSCTRL), and system authorities (i.e., SYSCTRL, SYSADM, and SECADM).

For example, to determine whether a user can alter a table, Db2 checks the required privilege in the following order:

- 1. Installation SYSADM
- 2. ALTER table privilege
- 3. DBADM authority on the database that the table is in
- 4. System DBADM
- 5. SYSCTRL
- 6. SYSADM

If the user has only the ALTER privilege on the table and if the audit policy is activated to audit the SYSADM authority, Db2 does not generate an IFCID 361 audit record on the ALTER operation. If the user also has the SYSADM authority, Db2 still does not generate an IFCID 361 record because the lowest (ALTER) privilege permits the operation.

In general, Db2 always checks the installation SYSADM and installation SYSOPR authorities prior to the lowest (ALTER) privilege. If the user has the installation SYSADM authority and the audit policy is

activated to audit the installation SYSADM authority, Db2 generates an IFCID 361 record.

Related tasks

Creating and activating audit policies

With the SECADM authority, you can create, display, activate, or inactivate Db2 audit policies.

Updating or stopping tamper-proof audit policies

<u>FL 509A</u> *tamper-proof audit policy* cannot be modified or stopped unless the user is authorized to access the Db2 audit policy profile by a z/OS security product that is external to Db2, such as RACF.

Auditing the use of an administrative authority You can create and activate an audit policy to audit how a Db2 administrative authority is used.

Auditing tables without specifying the AUDIT clause

With the SECADM authority, you can set up audit policies and dynamically enable auditing of tables that do not have the AUDIT clause specified.

Creating and activating audit policies

With the SECADM authority, you can create, display, activate, or inactivate Db2 audit policies.

Before you begin

Obtain the SECADM authority if you do not have it. Alternately, you can have the SECADM authority grant you the required privileges to create an audit policy. A user with the SYSOPR authority can activate the policy.

<u>FL 509</u> If the SEPARATE_SECURITY subsystem parameter is set to NO, most steps in this task, other stopping a secure audit policy, can also be completed with SYSADM authority. For more information, see "Separating the SYSADM authority" on page 63.

Procedure

To create and activate an audit policy:

1. Create a new audit policy by issuing the INSERT statement.

You need to specify a name for the new audit policy. An audit policy name is an identifier that is 1–128 letters or digits in length and begins with a letter.

You also need to specify proper audit categories in the new audit policy. If you specify the OBJMAINT or EXECUTE category, you must also specify the OBJECTSCHEMA, OBJECTNAME, and OBJECTTYPE columns in the SYSIBM.SYSAUDITPOLICIES table that identify the table to be audited.

For example, if you want to create a new AUDITADMIN1 policy to audit the SYSADM authority, you can specify SYSADMIN as the category:

GUPI

GUPI

You can also use the SQL LIKE predicate to audit tables of the same characteristics. For example, you can audit all tables that start with EMP in schema TSCHEMA by issuing the following INSERT statement:

GUPI

```
INSERT INTO SYSIBM.SYSAUDITPOLICIES
        (AUDITPOLICYNAME, OBJECTSCHEMA, OBJECTNAME, OBJECTTYPE, EXECUTE)
        VALUES('TEST2','TSCHEMA','''E_P%''','T','C');
```

GUPI

FL 509 To create a tamper-proof audit policy, which requires special authorization to modify or stop, set the DB2START column to T:

INSERT INTO SYSIBM.SYSAUDITPOLICIES
 (AUDITPOLICYNAME, CHECKING, SECMAINT, SYSADMIN, DB2START)
 VALUES('TAMPERPRFPOLICY01','A','A','I','T')

For more information on tamper-proof audit policies, see <u>"Updating or stopping tamper-proof audit</u> policies" on page 360.

2. Activate the audit policy by issuing the **START TRACE** command with the AUDTPLCY option.

You need to specify the AUDTPLCY option on the command to enable a specific audit policy:

GUPI

-STA TRACE (AUDIT) DEST (GTF) AUDTPLCY(AUDITADMIN1)

GUPI

Recommendation: <u>FL 509</u> Start all tamper-proof audit policies in one START TRACE command, which assigns them to one trace number. Doing so helps avoid the possibility of mismatching trace numbers among data sharing members if the SCOPE(GROUP) option is used to stop a tamper-proof audit policy.

This command starts a trace for IFCID 361 to audit the use of the SYSADM authority. Db2 also starts an IFCID 362 trace record to trace the audit policy information as defined in the catalog. If multiple audit policies are specified to start at the same time, the IFCID 362 record is written for every audit policy specified and contains the information about whether the policies successfully started or failed.

Up to 32 audit policies can be active concurrently.

Depending on the categories in the audit policy, Db2 starts the associated audit trace records, one for each IFCID that is related to the specified audit category.

Db2 runs against the audit policies that are already defined in the SYSIBM.SYSAUDITPOLICIES table when you issue the **START TRACE** command; it ignores any change you make to a specific audit policy after you start the START TRACE command. If you want Db2 to run against the updated audit policy, you need to stop and then start the audit policy trace. In addition, you cannot specify the CLASS or IFCID option when you specify the AUDTPLCY option on the **START TRACE** command.

<u>FL 509</u> If you prefer the audit policy to be automatically started, you need to set the DB2START column to Y, S, or T in the SYSIBM.SYSAUDITPOLICIES table. The audit policy will be started during Db2 startup. When you specify DB2START='S', only users (authorization IDs or roles) with the SECADM authority can stop the policy. When you specify DB2START='T', only users with additional authorization in RACF can modify or stop the policy. If you set DB2START = 'S' or 'T' to an audit policy that is already started, you must stop and restart the policy for the new setting to take effect.

You can automatically start up to 8 audit policies during Db2 startup. If you specify to automatically start multiple audit policies with different DB2START column settings, Db2 will start two traces, one for policies with DB2START = 'Y' and the other for policies with DB2START = 'S'. If you need to stop any audit policy that is automatically started, you must simultaneously stop all the policies that are assigned the same trace number.

3. If necessary, display the audit policy by issuing the **DISPLAY TRACE** command.

You need to specify the AUDTPLCY option on the command to show the name and other details about the AUDITADMIN1 audit policy:

GUPI

-DISPLAY TRACE (AUDIT) DETAIL(2) DEST (GTF) AUDTPLCY(AUDITADMIN1)

GUPI

The command returns an output like the following sample:

GUPI

```
15.49.46
                               -DIS TRACE(AUDIT) DETAIL(2)
           STC00125
                              DSNW143I - CURRENT TRACE QUALIFICATIONS ARE -
DSNW152I - BEGIN TNO 04 QUALIFICATIONS:
15.49.47
15.49.47
               STC00125
NO QUALIFICATIONS
END TNO 04 QUALIFICATIONS
15.49.47 STC00125 D
                              DSNW185I - BEGIN TNO 04 AUDIT POLICIES:
ACTIVE AUDIT POLICY: AUDITADMIN1
ACTIVE AUDIT POLICY: AUDITTABLE1
END TNO 04 AUDIT POLICIES
15.49.47 STC00125 D
                              DSNW148I - *****END OF DISPLAY TRACE QUALIFICATION
      DATA*****
              STC00125
15.49.47
                              DSN9022I - DSNWVCM1 '-DIS TRACE' NORMAL COMPLETION
```

GUPI

4. If necessary, disable the audit policy by issuing the STOP TRACE command.

Specify the AUDTPLCY option on the command to stop all the trace activities that are started by a specific audit policy:

GUPI

-STO TRACE (AUDIT) DEST (GTF) AUDTPLCY(AUDITADMIN1)

GUPI

Only the **STOP TRACE** command can stop all the trace activities that are started by a specific audit policy; deleting the active policy row from the SYSIBM.SYSAUDITPOLICIES table does not stop the tracing.

Tip: Additional authorities are required to stop certain audit policy types:

- Stopping a secure audit policy requires SECADM authority.
- Stopping a tamper-proof audit policy requires external authorizations.

Related tasks

Updating or stopping tamper-proof audit policies

FL 509A *tamper-proof audit policy* cannot be modified or stopped unless the user is authorized to access the Db2 audit policy profile by a z/OS security product that is external to Db2, such as RACF.

Auditing the use of an administrative authority

You can create and activate an audit policy to audit how a Db2 administrative authority is used.

Auditing tables without specifying the AUDIT clause

With the SECADM authority, you can set up audit policies and dynamically enable auditing of tables that do not have the AUDIT clause specified.

Related reference

Audit category

Db2 audit policies are created and stored in the SYSIBM.SYSAUDITPOLICIES table. Each policy is specified with specific audit categories.

SYSAUDITPOLICIES catalog table (Db2 SQL)

-START TRACE command (Db2) (Db2 Commands)

-STOP TRACE command (Db2) (Db2 Commands)

SECADM administrative authority

The SECADM authority enables you to manage security-related objects in Db2 and control access to all database resources. It does not have any inherent privilege to access data stored in the objects, such as tables.

Updating or stopping tamper-proof audit policies

FL 509A *tamper-proof audit policy* cannot be modified or stopped unless the user is authorized to access the Db2 audit policy profile by a z/OS security product that is external to Db2, such as RACF.

Before you begin

Your system security administrator must activate and RACLIST the RACF DSNR class if they have not already done so.

```
SETR CLASSACT(DSNR) GENERIC(DSNR)
SETR RACLIST(DSNR)
```

About this task

You can create a new tamper-proof audit policy by inserting an audit policy record into the SYSIBM.SYSAUDITPOLICIES catalog table with a DB2START value of 'T'. For more information, see <u>"Creating and activating audit policies" on page 357</u>. Any UPDATE or DELETE statements or STOP TRACE commands on this record require additional RACF authorization.

Procedure

To update a tamper-proof audit policy:

- 1. Ask your system security administrator to complete the following steps:
 - a) Optional: Define a default profile, DSNAUDIT.*, in the RACF DSNR class that prevents any tamperproof audit policy records from being modified or stopped.

```
RDEFINE DSNR DSNAUDIT.* UACC(NONE) OWNER(DB2OWNER)
SETR RACLIST(DSNR) REFRESH
```

b) Create a profile in the RACF DSNR class for the tamper-proof audit policy and permit you access to the profile.

The profile name must have the following format:

DSNAUDIT.policy-name

where *policy-name* is the name of the tamper-proof audit policy.

Note: In addition to access to the tamper-proof audit policy profile, you must also have the privileges that are required for the statements and commands that you will use to update and possibly restart the tamper-proof audit policy.

- 2. Update the tamper-proof audit policy record in the SYSIBM.SYSAUDITPOLICIES table.
- 3. If the tamper-proof audit policy is already started, restart the modified tamper-proof audit policy record by issuing the STOP TRACE and START TRACE commands.
- 4. Ask your system security administrator to remove your access to the audit policy profile in RACF.

Examples

Example: Updating a tamper-proof audit policy that is already started

Update the tamper-proof audit policy TAMPERPRFPOLICY01, which is already started, as a user with user ID SARA.

1. Ask your system security administrator to complete the following steps:

a. Activate and RACLIST the DSNR class.

SETR CLASSACT(DSNR) GENERIC(DSNR)
SETR RACLIST(DSNR)

b. Create a RACF profile, DSNAUDIT.TAMPERPRFPOLICY01, for the audit policy that is to be modified. Permit your user ID access to the profile.

RDEFINE DSNR DSNAUDIT.TAMPERPRFPOLICY01 UACC(NONE) OWNER(DB2OWNER) PE DSNAUDIT.TAMPERPRFPOLICY01 ID(SARA) ACCESS(READ) CLASS(DSNR) SETR RACLIST(DSNR) REFRESH

2. Update the tamper-proof audit policy record in the SYSIBM.SYSAUDITPOLICIES table.

UPDATE SYSIBM.SYSAUDITPOLICIES SET SYSADMIN='IR' WHERE AUDITPOLICYNAME='TAMPERPRFPOLICY01';

3. Issue the STOP TRACE command to stop the tamper-proof audit policy record.

STO TRACE(AUDIT) AUDTPLCY(TAMPERPRFPOLICY01)

4. Issue the START TRACE command to restart the modified tamper-proof audit policy record.

STA TRACE(AUDIT) AUDTPLCY(TAMPERPRFPOLICY01)

5. Ask your system security administrator to remove access to the audit policy profile in RACF for your user ID.

PE DSNAUDIT.TAMPERPRFPOLICY01 ID(SARA) DELETE CLASS(DSNR) SETR RACLIST(DSNR) REFRESH

Example: Updating a tamper-proof audit policy that is not started

Update the tamper-proof audit policy TAMPERPRFPOLICY02, which is not started, as a user that is associated with RACF group DBSECA.

- 1. Ask your system security administrator to complete the following steps:
 - a. Activate and RACLIST the DSNR class.

SETR CLASSACT(DSNR) GENERIC(DSNR)
SETR RACLIST(DSNR)

b. Create a RACF profile, DSNAUDIT.TAMPERPRFPOLICY02, for the audit policy to be modified. Permit the RACF group DBSECA access to the profile.

RDEFINE DSNR DSNAUDIT.TAMPERPRFPOLICY02 UACC(NONE) OWNER(DB2OWNER) PE DSNAUDIT.TAMPERPRFPOLICY02 ID(DBSECA) ACCESS(READ) CLASS(DSNR) SETR RACLIST(DSNR) REFRESH

2. Update the tamper-proof audit policy record in the SYSIBM.SYSAUDITPOLICIES table.

UPDATE SYSIBM.SYSAUDITPOLICIES SET DBADMIN='BGT' WHERE AUDITPOLICYNAME = 'TAMPERPRFPOLICY02';

3. Ask your system security administrator to remove access to the audit policy profile in RACF for DBSECA.

```
PE DSNAUDIT.TAMPERPRFPOLICY02 ID(DBSECA) DELETE CLASS(DSNR)
SETR RACLIST(DSNR) REFRESH
```

Related tasks

<u>Creating and activating audit policies</u> With the SECADM authority, you can create, display, activate, or inactivate Db2 audit policies.

Auditing the use of an administrative authority

You can create and activate an audit policy to audit how a Db2 administrative authority is used.

Auditing tables without specifying the AUDIT clause

With the SECADM authority, you can set up audit policies and dynamically enable auditing of tables that do not have the AUDIT clause specified.

Related reference

Audit category

Db2 audit policies are created and stored in the SYSIBM.SYSAUDITPOLICIES table. Each policy is specified with specific audit categories.

Auditing the use of an administrative authority

You can create and activate an audit policy to audit how a Db2 administrative authority is used.

About this task

Suppose that you have the SECADM authority and are responsible for making sure that all security policies, including audit policies, work as designed. You want to audit the use of the SYSADM authority by user SYSADMIN1.

Procedure

To audit the use of the SYSADM authority by SYSADMIN1:

1. Create audit policy AUDITADMN1 by issuing the following INSERT statement:

GUPI

GUPI

Db2 checks to make sure that you have the required privilege to issue the INSERT statement. Upon successful verification, it inserts a row in SYSIBM.SYSAUDITPOLICIES to include the new policy.

2. Activate the audit policy by issuing the **START TRACE** command:

GUPI

-STA TRACE (AUDIT) DEST (GTF) AUDTPLCY(AUDITADMN1)

GUPI

Db2 checks to make sure that you have the required privilege to run the **START TRACE** command. Upon successful verification, it starts an IFCID 0361 trace record.

For example, if SYSADM1 issues the ALTER BUFFERPOOL command to alter the attributes for active

buffer pools, Db2 records the ALTER activity in the IFCID 0361 trace record.

Related tasks

Creating and activating audit policies

With the SECADM authority, you can create, display, activate, or inactivate Db2 audit policies.

Updating or stopping tamper-proof audit policies

FL 509A *tamper-proof audit policy* cannot be modified or stopped unless the user is authorized to access the Db2 audit policy profile by a z/OS security product that is external to Db2, such as RACF.

Auditing tables without specifying the AUDIT clause

With the SECADM authority, you can set up audit policies and dynamically enable auditing of tables that do not have the AUDIT clause specified.

Related reference

Audit category

Db2 audit policies are created and stored in the SYSIBM.SYSAUDITPOLICIES table. Each policy is specified with specific audit categories.

Administrative authorities in Db2 for z/OS Each administrative authority in Db2 for z/OS is vested with a specific set of privileges. -START TRACE command (Db2) (Db2 Commands)

Auditing tables without specifying the AUDIT clause

With the SECADM authority, you can set up audit policies and dynamically enable auditing of tables that do not have the AUDIT clause specified.

Procedure

To audit the activities on table EMPLOYEE.SALARY without having to specify the AUDIT clause:

1. Obtain the SECADM authority if you do not have it.

Alternately, you can have the SECADM authority grant you the required privileges to create an audit policy. A user with the SYSOPR authority can activate the policy.

2. Create audit policy TABADT1 by issuing the following INSERT statement:

GUPI

```
INSERT INTO SYSIBM.SYSAUDITPOLICIES(AUDITPOLICYNAME, OBJECTSCHEMA,
OBJECTNAME, OBJECTTYPE, EXECUTE)
VALUES('TABADT1','EMPLOYEE','SALARY','T','A');
```

GUPI

Db2 checks to make sure that you have the required privilege to issue the INSERT statement. Upon successful verification, it inserts a row in SYSIBM.SYSAUDITPOLICIES to include the new policy.

3. Activate the audit policy by issuing the **START TRACE** command:

GUPI

-STA TRACE (AUDIT) DEST (GTF) AUDTPLCY(TABADT1);

GUPI

PSPI Db2 checks to make sure that you have the required privilege to run the **START TRACE** command. Upon successful verification, it starts the IFCID 0143, 0144, and 0145 trace records.

For example, if a user issues the SELECT statement to select from the EMPLOYEE.SALARY table, Db2

records the query activity in the IFCID 0144 trace record.

Related tasks

Creating and activating audit policies

With the SECADM authority, you can create, display, activate, or inactivate Db2 audit policies.

Updating or stopping tamper-proof audit policies

FL 509A *tamper-proof audit policy* cannot be modified or stopped unless the user is authorized to access the Db2 audit policy profile by a z/OS security product that is external to Db2, such as RACF.

Auditing the use of an administrative authority

You can create and activate an audit policy to audit how a Db2 administrative authority is used.

Related reference

Audit category

Db2 audit policies are created and stored in the SYSIBM.SYSAUDITPOLICIES table. Each policy is specified with specific audit categories.

-START TRACE command (Db2) (Db2 Commands) SYSAUDITPOLICIES catalog table (Db2 SQL)

SECADM administrative authority

The SECADM authority enables you to manage security-related objects in Db2 and control access to all database resources. It does not have any inherent privilege to access data stored in the objects, such as tables.

Additional sources of audit information

In addition to the audit trace, Db2 offers other sources of audit information for you to use.

Additional Db2 traces

Db2 accounting, statistics, and performance traces are also available. You can also use Db2 Performance Expert to print reports of these traces.

Recovery log

Although the recovery log is not an all-purpose log, it can be useful for auditing. You can print information from the log by using the DSN1LOGP utility. For example, the summary report can show which table spaces have been updated within the range of the log that you scan. The REPORT utility can indicate what log information is available and where it is located.

Image copies of table spaces

Typical recovery procedures generate image copies of table spaces. You can inspect these copies, or use them with the RECOVER utility to recover a table space to a particular point in time. If you recover to a point in time, you narrow the time period during which a particular change could have been made.

z/OS console log

The z/OS console log contains messages about exceptional conditions that are encountered during Db2 operation. Inspect this log for symptoms of problems.

Determining ID privileges and authorities

As an auditor, you must be aware of the privileges and authorities that are associated with the IDs or roles in the Db2 subsystem.

About this task

You can use the following methods to determine the privileges and authorities that a specific ID or role holds:

- Query the Db2 catalog to determine which IDs or roles hold particular privileges.
- Check on individual IDs that are associated with group IDs or roles. Some authorization IDs that you encounter are probably group IDs, to which many individual IDs can be connected. To see which IDs are connected to a group, obtain a report from RACF or from whatever external security system you are using. These reports can tell you which IDs have the required privileges to use Db2 data sets and other resources.

Auditing specific IDs or roles

As with other types of Db2 traces, you can start an audit trace for a particular plan name, a primary authorization ID, a role, or all of the above.

About this task

You might consider having audit traces on at all times for IDs with the SYSADM authority because they have complete access to every table. If you have a network of Db2 subsystems, you might need to trace multiple authorization IDs if the primary authorization IDs are translated several times. For embedded SQL, the audited ID is the primary authorization ID of the plan or package owner. For dynamic SQL, the audited ID is the primary authorization ID.

You can also start an audit trace for a particular role in a trusted context by using the ROLE and XROLE filters. For example, you can issue the following command to write accounting records for threads with a ROLE = abc:

GUPI

```
-start trace(acctg) dest(smf) role(abc)
```

GUPI

You can also issue the following command to write accounting records for threads with a ROLE= abc:

GUPI

-start trace(acctg) dest(smf) xrole(abc)

GUPI

In addition, you can use the asterisk (*) wildcard character (as in "abc*") or the underscore (_) wildcard character (as in "a_c") for more flexibility in audit tracing.

Related tasks

Auditing specific tables You can issue the CREATE TABLE or ALTER TABLE statement to audit a specific table.

Auditing specific tables

You can issue the CREATE TABLE or ALTER TABLE statement to audit a specific table.

About this task

GUPI

For the CREATE TABLE statement, the default audit option is NONE. For the ALTER TABLE statement, no default option exists. If you do not use the AUDIT clause in an ALTER TABLE statement, the audit option for the table is unchanged.

When CREATE TABLE statements or ALTER TABLE statements affect the audit of a table, you can audit those statements. However, the results of those audits are in audit class 3, not in class 4 or class 5. Use audit class 3 to determine whether auditing was turned off for a table for an interval of time.

If an ALTER TABLE statement turns auditing on or off for a specific table, any packages that use the table are invalidated and must be rebound. If you change the auditing status, the change does not affect packages, or dynamic SQL statements that are currently running. The change is effective only for packages or dynamic SQL statements that begin running after the ALTER TABLE statement has completed.

Procedure

To audit your table, choose any of the following options:

 To audit a table whenever the audit trace is on, include the AUDIT CHANGES option when you create the table.

CREATE TABLE DSN	8C10.DEPT		
(DEPTNO	CHAR(3)	NOT	NULL
DEPTNAME	VARCHAR(36)	NOT	NULL
MGRNO	CHAR(6)		
ADMRDEPT	CHAR(3)	NOT	NULL
LOCATION	CHAR(16)		
PRIMARY K	EY (DÉPTNO)		
IN DSN8D12A.DS	N8S12D		
AUDIT CHANGES;			

Because this statement includes the AUDIT CHANGES option, Db2 audits the table for each access that inserts, updates, or deletes data (trace class 4).

• To also audit the table for read accesses (class 5), issue the following statement:

ALTER TABLE DSN8C10.DEPT AUDIT ALL;

The statement is effective regardless of whether the table was previously chosen for auditing.

Related tasks

Auditing specific IDs or roles

As with other types of Db2 traces, you can start an audit trace for a particular plan name, a primary authorization ID, a role, or all of the above.

Preventing audits of tables

You can use the AUDIT NONE clause in the ALTER TABLE statement to prevent auditing of a table.

About this task

GUPI

For the CREATE TABLE statement, the default audit option is NONE. For the ALTER TABLE statement, no default option exists. If you do not use the AUDIT clause in an ALTER TABLE statement, the audit option for the table is unchanged.

If an ALTER TABLE statement turns auditing on or off for a specific table, any packages that use the table are invalidated and must be rebound. If you change the auditing status, the change does not affect packages, or dynamic SQL statements that are currently running. The change is effective only for packages or dynamic SQL statements that begin running after the ALTER TABLE statement has completed.

Procedure

Issue the following statement:

ALTER TABLE DSN8C10.DEPT AUDIT NONE;

GUPI

Ensuring data accuracy and integrity

Db2 provides many controls that you can apply to data entry and update.

Some of the controls are automatic; some are optional. All of the controls prohibit certain operations and provide error or warning messages if those operations are attempted. You can use these controls as a set auditing techniques to ensure data accuracy and integrity.

The set of techniques is not intended to be exhaustive. Other combinations of techniques are possible. For example, you can use table check constraints or a view with the check option to ensure that data values are members of a certain set. Or you can set up a master table and define referential constraints. You can also enforce the controls through application programs, and restrict the INSERT and UPDATE privileges only to those programs.

Related tasks

Ensuring data consistency

When you control data entry, you perform only part of a complete security and auditing policy. You must also verify the results when data is accessed and changed. In addition, you need to make sure that your data is consistent.

Ensuring data presence and uniqueness

You can ensure data presence with the NOT NULL clause and control the type of data by assigning data types and lengths to column data.

About this task

You can define columns with the NOT NULL clause to ensure that the required data is present. You can also control the type of data by assigning data types and lengths to column data. For example, you can specify that alphabetic data cannot be entered into a column with one of the numeric data types. You can also specify that the data for a DATE or TIME column must use a specific format.

You must ensure that the data in a column or a set of columns is unique. You can do so by creating a unique index on a column or set of columns.

Related tasks

<u>Protecting data integrity</u> Triggers and table check constraints enhance the ability to control data integrity.

Tracking data changes

Triggers offer an efficient means of maintaining an audit trail. You can define a trigger to activate in response to certain DELETE, INSERT, or UPDATE statements that change data.

Checking for lost and incomplete transactions

You can use the database balancing technique to alert you about lost and incomplete transactions. For each set of data, database balancing determines whether the opening balance and control totals equal the closing balance and control totals of processed transactions.

Protecting data integrity

Triggers and table check constraints enhance the ability to control data integrity.

About this task

Triggers are very useful for defining and enforcing rules that involve different states of Db2 data. For example, a rule can prevent a salary column from more than a ten percent increase. A trigger can enforce this rule and provide the value of the salary before and after the increase for comparison.

Table check constraints designate the values that specific columns of a base table can contain. A check constraint can express simple constraints, such as a required pattern or a specific range, and rules that refer to other columns of the same table.

As an auditor, you can verify that the table definitions express the required constraints on column values as table check constraints. You can also create a view with the check option and insert or update values only through that view.

Example

GUPT Suppose that, in table T, data in column C1 must be a number between 10 and 20. Suppose also that data in column C2 is an alphanumeric code that must begin with A or B. Create view V1 with the following statement:

```
CREATE VIEW V1 AS
SELECT * FROM T
WHERE C1 BETWEEN 10 AND 20
AND (C2 LIKE 'A%' OR C2 LIKE 'B%')
WITH CHECK OPTION;
```

Because of the CHECK OPTION, view V1 allows only data that satisfies the WHERE clause.

You cannot use the LOAD utility with a view, but that restriction does not apply to user-written exit routines; you can consider using the following types of user-written routines:

Validation routines

You can use validation routines to validate data values. Validation routines access an entire row of data, check the current plan name, and return a nonzero code to Db2 to indicate an invalid row.

Edit routines

Edit routines have the same access as validation routines, and can also change the row that is to be inserted. Auditors typically use edit routines to encrypt data and to substitute codes for lengthy fields. However, edit routines can also validate data and return nonzero codes.

Field procedures

Field procedures access data that is intended for a single column; they apply only to short-string columns. However, they accept input parameters, so generalized procedures are possible. A column that is defined with a field procedure can be compared only to another column that uses the same procedure.

Related tasks

Ensuring data presence and uniqueness

You can ensure data presence with the NOT NULL clause and control the type of data by assigning data types and lengths to column data.

Tracking data changes

Triggers offer an efficient means of maintaining an audit trail. You can define a trigger to activate in response to certain DELETE, INSERT, or UPDATE statements that change data.

Checking for lost and incomplete transactions

You can use the database balancing technique to alert you about lost and incomplete transactions. For each set of data, database balancing determines whether the opening balance and control totals equal the closing balance and control totals of processed transactions.

Tracking data changes

Triggers offer an efficient means of maintaining an audit trail. You can define a trigger to activate in response to certain DELETE, INSERT, or UPDATE statements that change data.

About this task

You can qualify a trigger by providing a list of column names when you define the trigger. The qualified trigger is activated only when one of the named columns is changed. A trigger that performs validation for changes that are made in an UPDATE operation must access column values both before and after the update. Transition variables (available only to row triggers) contain the column values of the row change that activated the trigger. The old column values and the column values from after the triggering operation are both available.

Related tasks

Ensuring data presence and uniqueness

You can ensure data presence with the NOT NULL clause and control the type of data by assigning data types and lengths to column data.

Protecting data integrity

Triggers and table check constraints enhance the ability to control data integrity.

Checking for lost and incomplete transactions

You can use the database balancing technique to alert you about lost and incomplete transactions. For each set of data, database balancing determines whether the opening balance and control totals equal the closing balance and control totals of processed transactions.

Checking for lost and incomplete transactions

You can use the database balancing technique to alert you about lost and incomplete transactions. For each set of data, database balancing determines whether the opening balance and control totals equal the closing balance and control totals of processed transactions.

About this task

Db2 has no automatic mechanism to calculate control totals and column balances and compare them with transaction counts and field totals. Therefore, to use database balancing, you must design these mechanisms into the application program.

Example

Use your application program to maintain a control table. The control table contains information to balance the control totals and field balances for update transactions against a user's view. The control table might contain these columns:

- View name
- Authorization ID
- Number of logical rows in the view (not the same as the number of physical rows in the table)
- · Number of insert transactions and update transactions
- Opening balances
- · Totals of insert transaction amounts and update transaction amounts
- Relevant audit trail information such as date, time, workstation ID, and job name

The program updates the transaction counts and amounts in the control table each time it completes an insert or update to the view. To maintain coordination during recovery, the program commits the work only after it updates the control table. After the application processes all transactions, the application writes a report that verifies the control total and balancing information.

Related tasks

Ensuring data presence and uniqueness

You can ensure data presence with the NOT NULL clause and control the type of data by assigning data types and lengths to column data.

Protecting data integrity

Triggers and table check constraints enhance the ability to control data integrity.

Tracking data changes

Triggers offer an efficient means of maintaining an audit trail. You can define a trigger to activate in response to certain DELETE, INSERT, or UPDATE statements that change data.

Ensuring data consistency

When you control data entry, you perform only part of a complete security and auditing policy. You must also verify the results when data is accessed and changed. In addition, you need to make sure that your data is consistent.

Related concepts

Ensuring data accuracy and integrity

Db2 provides many controls that you can apply to data entry and update.

Using referential integrity for data consistency

Referential integrity ensures that data is consistent across tables.

About this task

When you define primary and foreign keys, Db2 automatically enforces referential integrity.

Introductory concepts

Creation of relationships with referential constraints (Introduction to Db2 for z/OS)

As a result, every value of a foreign key in a dependent table must be a value of a primary key in the appropriate parent table. However, Db2 does not enforce informational referential constraints across subsystems.

Recommendation: Use referential integrity to ensure that a column allows only specific values. Set up a master table of allowable values, and define its primary key. Define foreign keys in other tables that must have matching values in their columns. In most cases, you should use the SET NULL delete rule.

Related tasks

Using locks for data consistency

Locks can ensure that data remains consistent even when multiple users try to access the same data at the same time. You can use locks to ensure that only one user is privileged to change data at a given time and that no user is privileged to access uncommitted data.

Checking data consistency

Whenever an operation changes the contents of a data page or an index page, Db2 verifies that the modifications do not produce inconsistent data.

<u>Creating tables for data integrity (Db2 Application programming and SQL)</u> Altering a table for referential integrity (Db2 Administration Guide)

Using locks for data consistency

Locks can ensure that data remains consistent even when multiple users try to access the same data at the same time. You can use locks to ensure that only one user is privileged to change data at a given time and that no user is privileged to access uncommitted data.

About this task

If you use repeatable read (RR), read stability (RS), or cursor stability (CS) as your isolation level, Db2 automatically controls access to data by using locks. However, if you use uncommitted read (UR) as your isolation level, users can access uncommitted data and introduce inconsistent data. As an auditor, you must know the applications that use UR isolation and that can introduce inconsistent data or create security risks.

GUPT For static SQL, you can determine the plans and packages that use UR isolation by querying the catalog.

For dynamic SQL statements, turn on performance trace class 3 to determine which plans and packages use UR isolation.

Consistency between systems: When an application program writes data to both Db2 and IMS, or to both Db2 and CICS, the subsystems prevent concurrent use of data until the program declares a point of consistency.

Examples

Example

For static SQL statements, use the following query to determine which plans use UR isolation:

```
SELECT DISTINCT Y.PLNAME
FROM SYSIBM.SYSPLAN X, SYSIBM.SYSSTMT Y
WHERE (X.NAME = Y.PLNAME AND X.ISOLATION = 'U')
OR Y.ISOLATION = 'U'
ORDER BY Y.PLNAME;
```

Example

For static SQL statements, use the following query to determine which packages use UR isolation:

```
SELECT DISTINCT Y.COLLID, Y.NAME, Y.VERSION
FROM SYSIBM.SYSPACKAGE X, SYSIBM.SYSPACKSTMT Y
WHERE (X.LOCATION = Y.LOCATION AND
X.LOCATION = ' ' AND
X.COLLID = Y.COLLID AND
X.NAME = Y.NAME AND
X.VERSION = Y.VERSION AND
X.ISOLATION = 'U'
ORDER BY Y.COLLID, Y.NAME, Y.VERSION;
```

Related tasks

Using referential integrity for data consistency Referential integrity ensures that data is consistent across tables.

Checking data consistency

Whenever an operation changes the contents of a data page or an index page, Db2 verifies that the modifications do not produce inconsistent data.

Checking data consistency

Whenever an operation changes the contents of a data page or an index page, Db2 verifies that the modifications do not produce inconsistent data.

About this task

You can use a variety of SQL queries, commands, and utilities to check data consistency.

Related tasks

Using referential integrity for data consistency Referential integrity ensures that data is consistent across tables.

Using locks for data consistency

Locks can ensure that data remains consistent even when multiple users try to access the same data at the same time. You can use locks to ensure that only one user is privileged to change data at a given time and that no user is privileged to access uncommitted data.

Checking data consistency with SQL queries

If you suspect that a table contains inconsistent data, you can submit an SQL query to search for a specific type of error.

About this task

Consider the view that is created by the following statement as an example of submitting an SQL query to search for an error:

```
CREATE VIEW V1 AS
SELECT * FROM T
WHERE C1 BETWEEN 10 AND 20
AND (C2 LIKE 'A%' OR C2 LIKE 'B%')
WITH CHECK OPTION;
```

The view allows an insert or update to table T1 only if the value in column C1 is in the range 10–20 and if the value in C2 begins with A or B. To check that the control has not been bypassed, issue the following statement:

```
SELECT * FROM T1
WHERE NOT (C1 BETWEEN 10 AND 20)
AND (C2 LIKE 'A%' OR C2 LIKE 'B%');
```

If the control has not been bypassed, Db2 returns no rows and thereby confirms that the contents of the view are valid. You can also use SQL statements to get information from the Db2 catalog about referential constraints that exist.

Checking data consistency with the CHECK utilities

One way to check data consistency is to use the CHECK DATA, CHECK INDEX, and CHECK LOB online utilities. You might want to use these utilities when you do a conditional restart or a point-in-time recovery or repair data.

Before you begin

Before you run CHECK DATA or CHECK LOB, you can find out all of the related tables spaces by using the REPORT utility with the TABLESPACESET option.

Procedure

Run one of the following utilities as needed:

CHECK DATA

The CHECK DATA utility checks referential constraints (but not informational referential constraints). It determines whether each foreign key value in each row is a value of the primary key in the appropriate parent table.

The CHECK DATA utility also checks table check constraints and checks the consistency between a base table space and any associated LOB or XML table spaces. It determines whether each value in a row is within the range that was specified for that column when the table was created.

The CHECK DATA utility also performs consistency checks on XML table spaces and related NodeID indexes. It verifies the consistency of XML documents that are stored in an XML table space and validates the documents against one or more XML schemas that are specified in the XML type modifier.

CHECK INDEX

The CHECK INDEX utility checks the consistency of indexes with the data to which the indexes point. It determines whether each index pointer points to a data row with the same value as the index key. If an index key points to a LOB, the CHECK INDEX utility determines whether the index key points to the correct LOB. If an index key points to an XML, the CHECK INDEX utility determines whether the index key points to the correct XML.

CHECK LOB

The CHECK LOB utility checks the consistency of a LOB table space. It determines whether any LOBs in the LOB table space are invalid.

Related reference

Syntax and options of the REPORT control statement (Db2 Utilities) CHECK DATA (Db2 Utilities) CHECK INDEX (Db2 Utilities) CHECK LOB (Db2 Utilities)

Checking data consistency with the DISPLAY DATABASE command

If you allow a table to be loaded without enforcing referential constraints on its foreign key columns, the table might contain data that violates the constraints. In this case, Db2 places the table space that contains the table in the CHECK-pending status.

About this task

You can determine the table spaces with the CHECK-pending status by using the DISPLAY DATABASE command with the RESTRICT option. You can also use the DISPLAY DATABASE command to display table spaces with invalid LOBs.

Checking data consistency with the operation log

You can use the operation log to verify that Db2 is operated reliably and to reveal unauthorized operations and overrides. The operation log consists of an automated log of Db2 operator commands, such as those for starting and stopping the subsystem, and Db2 abends.

About this task

The operation log records the following information:

- Command or condition type
- Date and time when the command was issued
- · Authorization ID that issued the command
- Database connection code

You can obtain this information from the system log (SYSLOG), the SMF data set, or the automated job scheduling system. To obtain the information, use SMF reporting, job-scheduler reporting, or a user-developed program. As a good practice, review the log report daily and keep a history file for comparison. Because abnormal Db2 termination can indicate integrity problems, implement an immediate notification procedure to alert the appropriate personnel (DBA, systems supervisor, and so on) of abnormal Db2 terminations.

Checking data consistency with internal integrity reports

You can generate internal integrity reports for application programs and utilities.

About this task

For application programs, you can record any Db2 return codes that indicate possible data integrity problems, such as inconsistency between index and table information, physical errors on database disk, and so on. All programs must check the SQLCODE or the SQLSTATE for the return code that is issued after an SQL statement is run. Db2 records, on SMF, the occurrence (but not the cause) of physical disk errors and application program abends. The program can retrieve and report this information; the system log (SYSLOG) and the Db2 job output also have this information. However, in some cases, only the program can provide enough detail to identify the exact nature of problem.

You can incorporate these integrity reports into application programs, or you can use them separately as part of an interface. The integrity report records the incident in a history file and writes a message to the operator's console, a database administrator's TSO terminal, or a dedicated printer for certain codes. The recorded information includes the following:

- Date
- Time
- Authorization ID
- Terminal ID or job name
- Application

- Affected view or affected table
- Error code
- Error description

When a Db2 utility reorganizes or reconstructs data in the database, it produces statistics to verify record counts and to report errors. The LOAD and REORG utilities produce data record counts and index counts to verify that no records were lost. In addition to that, keep a history log of any Db2 utility that updates data, particularly REPAIR. Regularly produce and review these reports, which you can obtain through SMF customized reporting or a user-developed program.

Information resources for Db2 for z/OS and related products

You can find the online product documentation for Db2 12 for z/OS and related products in IBM Documentation.

For all online product documentation for Db2 12 for z/OS, see IBM Documentation (https://www.ibm.com/docs/en/db2-for-zos/12).

For other PDF manuals, see PDF format manuals for Db2 12 for z/OS (https://www.ibm.com/docs/en/db2-for-zos/12?topic=zos-pdf-format-manuals-db2-12).

Db2 12 for z/OS: Managing Security (Last updated: 2024-09-06)

Notices

This information was developed for products and services offered in the US. This material might be available from IBM in other languages. However, you may be required to own a copy of the product or product version in that language in order to access it.

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

IBM Director of Licensing IBM Corporation North Castle Drive, MD-NC119 Armonk, NY 10504-1785 US

For license inquiries regarding double-byte (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

Intellectual Property Licensing Legal and Intellectual Property Law IBM Japan Ltd. 19-21, Nihonbashi-Hakozakicho, Chuo-ku Tokyo 103-8510, Japan

INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM websites are provided for convenience only and do not in any manner serve as an endorsement of those websites. The materials at those websites are not part of the materials for this IBM product and use of those websites is at your own risk.

IBM may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

IBM Director of Licensing IBM Corporation North Castle Drive, MD-NC119 Armonk, NY 10504-1785 US

Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement or any equivalent agreement between us.

The performance data and client examples cited are presented for illustrative purposes only. Actual performance results may vary depending on specific configurations and operating conditions.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to actual people or business enterprises is entirely coincidental.

COPYRIGHT LICENSE:

This information contains sample application programs in source language, which illustrate programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to IBM, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating platform for which the sample programs are written. These examples have not been thoroughly tested under all conditions. IBM, therefore, cannot guarantee or imply reliability, serviceability, or function of these programs. The sample programs are provided "AS IS", without warranty of any kind. IBM shall not be liable for any damages arising out of your use of the sample programs.

Each copy or any portion of these sample programs or any derivative work must include a copyright notice as shown below:

[©] (your company name) (year). Portions of this code are derived from IBM Corp. Sample Programs. [©] Copyright IBM Corp. (enter the year or years).

If you are viewing this information softcopy, the photographs and color illustrations may not appear.

Programming interface information

This information is intended to help you to plan for and administer Db2 12 for z/OS. This information also documents General-use Programming Interface and Associated Guidance Information and Product-sensitive Programming Interface and Associated Guidance Information provided by Db2 12 for z/OS.

General-use Programming Interface and Associated Guidance Information

General-use Programming Interfaces allow the customer to write programs that obtain the services of Db2 12 for z/OS.

General-use Programming Interface and Associated Guidance Information is identified where it occurs by the following markings:

GUPI General-use Programming Interface and Associated Guidance Information...

Product-sensitive Programming Interface and Associated Guidance Information

Product-sensitive Programming Interfaces allow the customer installation to perform tasks such as diagnosing, modifying, monitoring, repairing, tailoring, or tuning of this IBM software product. Use of such interfaces creates dependencies on the detailed design or implementation of the IBM software product. Product-sensitive Programming Interfaces should be used only for these specialized purposes. Because of their dependencies on detailed design and implementation, it is to be expected that programs written to such interfaces may need to be changed in order to run with new product releases or versions, or as a result of service.

Product-sensitive Programming Interface and Associated Guidance Information is identified where it occurs by the following markings:

PSPI Product-sensitive Programming Interface and Associated Guidance Information...

Trademarks

IBM, the IBM logo, and ibm.com[®] are trademarks or registered marks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the web at "Copyright and trademark information" at: http://www.ibm.com/legal/copytrade.shtml.

Linux is a registered trademark of Linus Torvalds in the United States, other countries, or both.

Microsoft, Windows, Windows NT, and the Windows logo are trademarks of Microsoft Corporation in the United States, other countries, or both.

UNIX is a registered trademark of The Open Group in the United States and other countries.

Java and all Java-based trademarks and logos are trademarks or registered trademarks of Oracle and/or its affiliates.

Terms and conditions for product documentation

Permissions for the use of these publications are granted subject to the following terms and conditions:

Applicability: These terms and conditions are in addition to any terms of use for the IBM website.

Personal use: You may reproduce these publications for your personal, noncommercial use provided that all proprietary notices are preserved. You may not distribute, display or make derivative work of these publications, or any portion thereof, without the express consent of IBM.

Commercial use: You may reproduce, distribute and display these publications solely within your enterprise provided that all proprietary notices are preserved. You may not make derivative works of these publications, or reproduce, distribute or display these publications or any portion thereof outside your enterprise, without the express consent of IBM.

Rights: Except as expressly granted in this permission, no other permissions, licenses or rights are granted, either express or implied, to the publications or any information, data, software or other intellectual property contained therein.

IBM reserves the right to withdraw the permissions granted herein whenever, in its discretion, the use of the publications is detrimental to its interest or, as determined by IBM, the above instructions are not being properly followed.

You may not download, export or re-export this information except in full compliance with all applicable laws and regulations, including all United States export laws and regulations.

IBM MAKES NO GUARANTEE ABOUT THE CONTENT OF THESE PUBLICATIONS. THE PUBLICATIONS ARE PROVIDED "AS-IS" AND WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY, NON-INFRINGEMENT, AND FITNESS FOR A PARTICULAR PURPOSE.

Privacy policy considerations

IBM Software products, including software as a service solutions, ("Software Offerings") may use cookies or other technologies to collect product usage information, to help improve the end user experience, to tailor interactions with the end user, or for other purposes. In many cases no personally identifiable information is collected by the Software Offerings. Some of our Software Offerings can help enable you to collect personally identifiable information. If this Software Offering uses cookies to collect personally identifiable information about this offering's use of cookies is set forth below.

This Software Offering does not use cookies or other technologies to collect personally identifiable information.

If the configurations deployed for this Software Offering provide you as customer the ability to collect personally identifiable information from end users via cookies and other technologies, you should seek

your own legal advice about any laws applicable to such data collection, including any requirements for notice and consent.

For more information about the use of various technologies, including cookies, for these purposes, see IBM's Privacy Statement at http://www.ibm.com/privacy.

Glossary

The glossary is available in IBM Documentation For definitions of Db2 for z/OS terms, see Db2 glossary (Db2 Glossary).

Db2 12 for z/OS: Managing Security (Last updated: 2024-09-06)
Index

A

access checking mandatory 123, 124 object security labels 123 user security labels 123 access control applications 98 auditing 345 authorities 2, 15, 20 authorization IDs 19, 20 authorizing 98, 99 catalog tables 113 **CICS 139** columns 221 data definition control overview 251 Db2 subsystem RACF 4 exit routines 4, 269 external overview 139 external Db2 data sets 6 IMS 139 internal overview 19 internal Db2 data 1 managing 98 multilevel security 4 object ownership 3 privileges <u>2</u>, <u>15</u>, <u>20</u> RACF 4, 139 restricting 98 roles 3, 19, 20 rows 221 subsystems local 5, 170 remote 5, 177 trusted connections 237 trusted contexts overview 237 access control authorization routine ACEE 283, 284 active 307 authorization IDs 284 debugging 306 default 283 expected output 304 EXPLAIN STMTCACHE 290 invoking 283 overview 280 packages inoperative 286 parameter list 292 processing exceptions 305 reason codes 305 return codes 304

access control authorization routine (continued) specifying 282 access profile defining 140 RACF 140 access requests remote permitting 151 ACCESSCTRL authority granting privileges 71 revoking privileges 71 accessibility keyboard xi shortcut keys xi accessing data 70 adding RACF groups 149 SAF user mapping plug-in 169 address spaces started-task 146 WLM-established 154 altering tables 70 application registration tables (ART) ART columns 252 applications authorization validating 95 executing 95 RRSAF 95 AT-TLS configuring 323 data protection 323 attachment requests remote 185 audit classes 348 audit policies audit categories 354 creating 357 displaying 357 overview 354 tamper-proof updating 360 audit trace records collecting 352 formatting 353 audit trace reports 349 audit traces audit classes 348 limitations 350 starting 351 stopping 352 auditing access overview 345 administrative authorities 362

auditing (continued) AUDIT ALL option 14 audit categories 354 audit policies 354 authorization IDs 348, 364 distributed environment 353 security measures 364 tables AUDIT clause 363 authentication cache global 199 authentication level configuring 325 Secure Socket Layer (SSL) 324, 325 authorities access control 2 ACCESSCTRL authority 30, 45, 51, 71 administrative auditing 362 DATAACCESS authority 30, 48, 51, 70 DB2 catalogs 53 DBADM authority 30, 49, 51, 115 DBCTRL authority 30, 50 DBMAINT authority 30, 50 directories 53 installation SYSADM authority 30, 37 installation SYSOPR authority 30, 42 managing 63 migrating 66 PACKADM authority 30, 51 **REVOKE statement 85** revoking 85 SECADM authority 30, 43, 51, 69 security 43 separating 63 SQLADM authority 30, 49, 51 SYSADM authority 30, 38, 51, 81, 85 SYSCTRL authority 30, 40 SYSOPR authority 30, 43 system DBADM authority 30, 45, 51, 70, 115 utilities 53 authorization access control 57 failure code 182 views 289 authorization IDs access control 19 audit traces 348 auditing 348, 364 caching 95–97 determining 108 dynamic SQL 104, 108 managing access 19 packages 96 plans 95 primary 20, 54 RACF 20 routines 97 secondary connection processing 173 sign-on processing 175 sign-on processing 174 SQL 20, 54 translating

authorization IDs (continued) translating (continued) inbound IDs <u>187</u> outbound IDs <u>212</u> automatic rebind roles 287

В

bind behavior attributes <u>105</u> BINDAGENT RACF <u>288</u> roles 288

С

caching authorization IDs plans 95 routines 97 **EXECUTE** privilege packages 290 plans 290 routines 290 roles 96 security labels 129 SQL statements 291 catalog tables privilege records 113 catalogs 53 CICS connection routines samples 176 sign-on routines samples 176 client certificate 324, 325 collecting audit trace records 352 collection privileges **CREATE IN privilege 23** column access control activating 230, 232 column masks 221, 223, 230, 232 deactivating 230, 232 column masks creating 230 modifying 232 column-level encryption password hints 338 views 337 commands Db2 **DISPLAY DATABASE command 373** DISPLAY TRACE command 351, 352 required authorization 151 START TRACE command 351 STOP TRACE command 352 DISPLAY DATABASE command 373 RACF ADDGROUP command 149 WLM REFRESH command 156 communications databases (CDB)

communications databases (CDB) (continued) requesters 202 servers 180 configuring AT-TLS 323 enterprise identity mapping (EIM) domain controller 168 IMS 153 LDAP server 166 RACF LDAP server 167 Secure Socket Layer (SSL) 323 SNA 138 SSL authentication level 325 TCP/IP 137 connection requests connection processing 170 local 170 managing 170 connection processing attachment requests 182, 209 BATCH 171 **CICS 171** IMS 171 **RACF 171** secondary authorization IDs 173 TSO 171 connection requests inbound 189, 197 managing 182, 189, 201 outbound 201 processing 171, 197 SNA-based 182 TCP/IP-based 189, 197 connection routines debugging 278 expected output 276 input values 275 invoking 271 overview 269 parameter list 272, 274 processing 276 samples 270 session variables 280 specifying 270 connections **VTAM 142** creating audit policies 357 materialized query tables 292 table spaces 265 trusted connections local 240

D

data access control <u>1</u> accessing <u>79</u> changes tracking <u>368</u> consistency data (continued) consistency (continued) SQL queries 371 verifying 369 distributed 79 integrity 366, 367 internal integrity reports 373 operation logs 373 transactions database balancing 369 uniqueness 367 data consistency locks 370 referential integrity 370 data definition control access control 251 application registration tables (ART) 255 controlling application name 255 application name with exceptions 256 object name with exceptions 259 object names 258 data definition statements 251 Db2 support DSNTIPZ panel 251 installing 254 disabling 262 managing 251 object registration tables (ORT) 255 restarting 262 stopping 262 data definition statements data definition control 251 data protection Db2 built-in functions 334 encryption overview 311 RACF overview 311 Secure Socket Layer (SSL) Db2 support 311 data sets adding groups 330 creating 333 generic profiles adding authorization IDs 333 creating 331 protecting 330 DATAACCESS authority accessing data 70 database balancing incomplete transactions 369 lost transactions 369 database privileges **CREATETAB** privilege 23 **CREATETS** privilege 23 DISPLAYDB privilege 23 DROP privilege 23 IMAGCOPY privilege 23 LOAD privilege 23 **RECOVERDB** privilege 23 REORG privilege 23 REPAIR privilege 23 STARTDB privilege 23

database privileges (continued) STATS privilege 23 STOPDB privilege 23 Db2 directories 53 Db2 support enterprise identity mapping (EIM) 165 z/OS identity filter 169 DB2I 244 DBADM authority managing access 15 DBCTRL authority 30, 50 DBMAINT authority 30, 50, 51 decryption Db2 built-in functions 334 define behavior attributes 106 definer, description 100 defining column-level encryption 336 Db2 resources **RACF 139** external security profiles 247 trusted contexts 239 DELETE statement 135, 224 denial-of-service attack managing 200 dependent privileges 81 disability xi disabling data definition control 262 DISPLAY TRACE command 351, 352 displaying audit policies 357 distinct types stored procedures 158 distributed access implementing 9, 10 planning 9 servers central 9 remote 10 views 9 distributed environment auditing 353 DRDA access security mechanisms 177-179 **DROP statement 84** dropping views 290 DSN command processor 244 DSNDB01 database 53 DSNDB06 database 53 DSNR class check SNA connection 292 dynamic SQL authorization 104 DYNAMICRULES 104, 108 DYNAMICRULES(BIND) roles 288

encrypted data (continued) defining columns 335 performance optimization 341 predicates 340 encrypting AES 216, 217 DES 216, 217 non-character values 340 passwords 213, 216, 217 encryption AT-TLS 323 column level defining 336 column-level encryption 337, 338 data protection 311 Db2 built-in functions 334 DFSMS 311 encrypted data 335, 340, 341 non-character values 340 password hints 338 performance optimization 341 predicates 340 Secure Socket Layer (SSL) 323, 327, 329 value-level encryption 338, 339 ENF signal processing 285 enterprise identity mapping (EIM) configuring 168 DB2 support 165 domain controller 168 implementing 165 establishing trusted connections remote 241, 243 executing stored procedure 161 exit routines access control 4, 269 managing access 269 EXPLAIN STMTCACHE SQL statements 290 explicit privileges collection privileges 22, 23 database privileges 22, 23 distinct type privileges 22 function privileges 22 granting 72 JAR privileges 22 managing 72 package privileges 22, 24 plan privileges 22, 24 procedure privileges 22 routine privileges 22, 25 schema privileges 22, 25 sequence privileges 22 system privileges 22, 25 table privileges 22, 27 usage privileges 22, 27 use privileges 22, 28 view privileges 22, 27 explicit view privileges ALTER privilege 27

DELETE privilege 27

GRANT ALL privilege 27

E

edit procedures <u>122</u> encrypted data explicit view privileges (continued) INDEX privilege <u>27</u> INSERT privilege <u>27</u> REFERENCES privilege <u>27</u> SELECT privilege <u>27</u> TRIGGER privilege <u>27</u> UPDATE privilege <u>27</u>

F

field procedures <u>122</u> formatting audit trace records <u>353</u>

G

general-use programming information, described <u>378</u> global authentication cache <u>199</u> global temporary tables <u>120</u> GRANT statement authorities <u>75</u> PUBLIC clause <u>72</u>, <u>73</u> ROLE AS OBJECT OWNER clause <u>72</u> granting privileges <u>71</u> write-down privileges <u>125</u> group access RACF PassTickets <u>143</u> GUPI symbols <u>378</u>

Ι

image copies 364 implementing column access control 221 enterprise identity mapping (EIM) 165 multilevel security 118 row access control 221 z/OS identity filter 169 implementor, description 100 implicit privilege ownership 291 implicit privileges granting object ownership 91 managing object ownership 89 object ownership changing 91 trusted contexts 90 routines 100 inbound IDs associating secondary IDs 189 managing 185 translating 187 indexes creating 263 dropping 265 managing 263 naming 264 **INSERT** statement column access control 234

INSERT statement (continued) row access control 234 installation SYSADM authority 30, 37 installation SYSOPR authority 30, 42 installing Db2 support data definition control 254 invoke behavior attributes 106 invoker, description 100

J

JAR files 159

Κ

Kerberos authenticating <u>187</u> authentication RACF <u>164</u>

L

LDAP configuring RACF <u>167</u> z/OS <u>166</u> links non-IBM Web sites 379

Μ

managing authorities 63 connection requests outbound 201 SNA-based 182 data multilevel-secure environment 130 denial-of-service attack 200 materialized query tables dropping 84 member-specific access **RACF PassTickets 143** MERGE statement 134, 224 migrating ACCESSCTRL authority 66 authorities 66 DATAACCESS authority 66 SECADM authority 66 SYSADM authority 66 SYSCTRL authority 66 system DBADM authority 66 multi-factor authentication) enabling for sysplex group authentication 193 multilevel security access control 4 advantages 118 constraints 121 discretionary access checking 123 distributed environment 137

multilevel security (continued) edit procedures 122 field procedures 122 global temporary tables 120 implementing 125, 127 mandatory access checking 123 materialized query tables 121 objects 125 rows 127 security categories 118 security labels 118 security levels 118 SNA configuring 138 tables adding 128 columns 128, 129 creating 128 removing 129 TCP/IP configuring 137 triggers 122 validation procedures 122 views 129

0

object owners managing access 17 object ownership access control 3 aliases 28 changing 91 databases 28 distinct types 28 global variables 28 implicit privileges granting 91 indexes 28 **JAR 28** packages 28, 92 plans 28, 92 privileges implicit 28 gualified names 90 roles 28 sequences 28 storage groups 28 stored procedures 28 synonyms 28 table spaces 28 tables 28 trusted contexts 28, 90 ungualified names 89 user-defined functions 28 views 28 object registration tables (ORT) ORT columns 252 object sets registering 261 objectives 7 outbound IDs translating 212 ownership

ownership (continued) implicit privilege 291

Ρ

PACKADM authority 30, 51 package ownership changing 92 creating 92 trusted contexts 92 package privileges BIND privilege 24 COPY privilege 24 EXECUTE privilege 24 **GRANT ALL privilege 24** packages access authorization 98 authorization validating 93, 94 binding 79 executing 93, 94 inoperative 85 invalidating 85 rebinding 79 unqualified names 93 parameters **REVOKE DEP PRIV parameter 81** SEPARATE SECURITY parameter 40, 70, 71, 221, 234 SEPARATE_SECURITY parameter 30, 63, 66, 69, 222, 223, 227, 230, 232, 235 system 30, 40, 63, 66, 69-71, 81, 221-223, 227, 230, 232, 234, 235 PassTickets configuring 215 generating 215 RACF 186 receiving 191 PassTickets) enabling for sysplex group authentication 193 enabling for use with RACF-protected user IDs 192 passwords changing 182 encrypting 186, 216, 217 RACF-encrypted 214 sending 213, 214 performance optimization encrypted data 341 plan ownership changing 92 creating 92 trusted contexts 92 plan privileges **BIND** privilege 24 **EXECUTE** privilege 24 plans access authorization 98, 99 authorization validating 93 binding 78, 79 executing remotely 99 rebinding 79 unqualified names 93 port of entry

port of entry (continued) **RACF APPCPORT class 151** RACF SERVAUTH class 151 predicates encrypted data 340 preventing SQL injection attacks 200 primary authorization ID 20 privileges access control 2 application programmers 55 authorization IDs 54, 113 catalog tables 114 composite using 112 CREATE DATABASE statement 61 **CREATE INDEX statement 61 CREATE STOGROUP statement 61 CREATE TABLE statement 61 CREATE TABLESPACE statement 61 CREATE VIEW statement 61 CREATEIN** privilege granting 157 data distributed 79 data definition statements 57 database administrators 55 dependent 81 **DROP statement 84** dynamic SQL 61 EXECUTE privilege caching 290 executing routines 100 explicit 22-25, 27, 28, 72 GRANT statement 61, 75, 77-79 granted 113 granting distinct types 158 JAR files 159 stored procedure packages 160 stored procedures 160 implicit 22, 28, 89-93, 100, 249 information center consultants 55 multiple grants 114 object ownership 28 package administrators 55 packages 58, 79, 112 plans 58, 78, 79, 112 production binders 55 PUBLIC ID 73 query users 55 restrictions 86 REVOKE statement 61, 80-85 revoking 80-86 roles 54, 113 routines 101 security administrators 55 static SQL 61 system administrators 55 system operators 55 system programmers 55 trusted contexts 249 user analysts 55

privileges (continued) users group 77 remote 73 views 74 processing ENF signals 285 product-sensitive programming information, described 378 program authorization 309 programming interface information, described 378 PSPI symbols 378 PUBLIC clause GRANT statement 72, 73 PUBLIC ID 73

R

RACF access authorization protected resources 145 SERVER resource class 154 access checking DSNR class 141 SERVER class 141 access control non-Db2 resources 157 authorization 6, 153 authorizing group access 150 **BINDAGENT 288** data protection 311, 330 Db2 resources defining 139 defining access profiles 140 Db2 resources 162 user IDs 146 encrypted passwords 214 groups adding 149 Kerberos authentication 164 managing access Db2 139 PassTickets 142, 191, 215 roles 288 RACF access control module 307 **RACF** groups creating 14 **RACF** PassTickets group and member-specific access 143 RACF-protected user IDs receiving 192 recovery logs 364 registering object sets 261 registration tables adding columns 266 application registration tables (ART) 252 creating 263 dropping 265 managing 263 naming 264 object registration tables (ORT) 252 updating 267

Resource Recovery Services attachment facility (RRSAF) RACF profiles 154 stored procedures 154 retrieving authorization IDs 113, 115, 116 multiple grants 114 packages 117 plans 117 privilege records 117 roles 113, 115, 116 reusing trusted connections 244-247 **REVOKE statement** ROLE AS OBJECT OWNER clause 83 revoking privileges 71 ROLE AS OBJECT OWNER clause **GRANT statement 72** roles access control 3, 19 automatic rebind 287 **BINDAGENT 288** caching 96 dropping 83, 84 DYNAMICRULES(BIND) 288 managing 19 packages 96 privileges 72 **RACF 288** ROLE AS OBJECT OWNER clause 72 SECADM authority 69 trusted connection 21 trusted contexts 21, 69 routine privileges **EXECUTE ON FUNCTION privilege 25 EXECUTE ON PROCEDURE privilege 25** routines access authorization simplifying 111 access control authorization routine 280, 282-284, 286, 290, 292, 304-307 authorization IDs 116 connection routines 269-272, 274-276, 278, 280 executing 100 implicit privileges 100 privileges granting 101 roles 116 sign-on routines 269-272, 274-276, 278, 280 stored procedures 100 user-defined functions (UDF) 100 row access control activating 227 deactivating 227 row permissions 221, 222, 227 row and column access control access types 224 column masks 224 implementing 221 row permissions 224 rules 224 row permissions creating 227 RRSAF 95, 246

run behavior attributes 105

S

SAF user mapping plug-in adding 169 scenarios security plans 6 schema privileges ALTERIN privilege 25 **CREATEIN** privilege 25 **DROPIN** privilege 25 schemas stored procedures 157 SECADM authority roles 69 trusted contexts 69 secondary authorization ID RACF ID 20 SOL ID 20 secondary IDs privileges 77 secondary role trusted connection 248 Secure Socket Layer (SSL) authentication level configuring 325 configuring 323 data protection 311, 323 Db2 requesters configuring 329 Db2 servers configuring 327 security active security measures 346 column access control 221 Db2 1 Db2 solutions overview 1 getting started 1 mechanisms DRDA access 177 multilevel implementing 118 managing 130 profiles defining 247 row access control 221 security measures 364 security categories 118 security labels caching 129 columns 128 determining 120 objects 123 RACF resource classes 125 relationships dominance 123 users 123 security levels 118 security plans access control 15, 17

security plans (continued) access restrictions 7, 11 auditing access 11, 14 distributed access 9, 10 privileges granting 13 **RACF** groups creating 14 scenarios 6 SELECT privilege 8 tables keys 13 triggers 13 updating 12 views creating 7, 12 SELECT statement 130, 224 separating ACCESSCTRL authority 63 authorities 63 DATAACCESS authority 63 SECADM authority 63 SYSADM authority 63 SYSCTRL authority 63 SYSOPR authority 63 system DBADM authority 63 server certificate 324, 325 shortcut keys keyboard xi sign-on processing requests 170 usage 170 sign-on requests authorization IDs 174 secondary authorization IDs 175 sign-on routines debugging 278 expected output 276 input values 275 invoking 271 overview 269 parameter list 272, 274 processing 276 samples 270 session variables 280 specifying 270 simplifying access authorization routines 111 SNA access protocols 182 security mechanisms 177-179 SNA connection DSNR class check 292 SOL attributes 107 **CONNECT statement 247 CREATE statement 263** dynamic 61, 104-108 static 61 SQL injection attacks preventing 200 SOL statements caching 291

SOLADM authority 30, 49, 51 START TRACE command 351 starting audit traces 351 STOP TRACE command 352 stopping audit traces 352 data definition control 262 stored procedure packages 160 stored procedures access control non-DB2 resources 157 creating 155 distinct types 158 executing remote 161 privileges granting 101 required authorization managing 153 trusted contexts 161 WLM 154-156 subsystems access control 5, 139 managing 139 syntax diagram how to read xii SYSADM authority managing access 16 SYSCTRL authority 30, 40, 63, 66 SYSIBM.IPNAMES columns 203 SYSIBM.LOCATIONS columns 207 SYSIBM.LUNAMES columns 180, 202 SYSIBM.USERNAMES columns 181, 206 SYSOPR authority 30, 43, 63 sysplex group authentication enabling 193 system administrator privileges 75 system DBADM authority altering tables 70 System Management Facility (SMF) 348 system privileges **ARCHIVE** privilege 25 **BINDADD** privilege 25 BINDAGENT privilege 25 BSDS privilege 25 CREATE_SECURE_OBJECT privilege 25 **CREATEALIAS** privilege 25 CREATEDBA privilege 25 CREATEDBC privilege 25 **CREATESG** privilege 25 **CREATETMTAB** privilege 25 **DEBUGSESSION** privilege 25 **DISPLAY** privilege 25 **EXPLAIN** privilege 25 MONITOR1 privilege 25 MONITOR2 privilege 25 **RECOVER** privilege 25 STOPALL privilege 25 STOSPACE privilege 25 TRACE privilege 25 system programmer 56

Т

table privileges ALTER privilege 27 **DELETE** privilege 27 **GRANT ALL privilege 27 INDEX** privilege 27 **INSERT** privilege 27 **REFERENCES** privilege 27 SELECT privilege 27 **TRIGGER** privilege 27 UPDATE privilege 27 table spaces registration tables 265 tables auditing 365 catalogs access control 113 privileges 113 creating 292 packages 117 plans 117 updating 12 tablesMoved authorization IDs 115 roles 115 tasks Db2-started 146 TCP/IP connection requests protecting 162 protocols 189, 197 tracking data changes 368 translating inbound IDs 187 outbound IDs 212 triggers creating 235 **TRUNCATE statement 136** trusted connections local creating 240 reusing 244, 246, 247 remote establishing 241, 243 reusing 245 reusing 244 roles 21 trusted contexts 238 trusted contexts access control 237 ASUSER 249 **BINDAGENT 288** defining 239 managing 237 object ownership 90 package ownership 92 plan ownership 92 **RACF 288** roles 21, 69, 288 stored procedure 161 trusted connections 237, 238, 247

U

UDFs privileges granting 101 UPDATE statement 132, 224 updating registration tables 267 usage privileges **USAGE ON DISTINCT TYPE privilege 27** USAGE ON JAR privilege 27 USAGE ON SEQUENCE privilege 27 use privileges USE OF BUFFERPOOL privilege 28 USE OF STOGROUP privilege 28 USE OF TABLESPACE privilege 28 user-defined functions (UDF) invoking 291 users group 77 utilities CHECK DATA utility 372 CHECK INDEX utility 372 CHECK LOB utility 372

V

validation procedures 122 value-level encryption defining 338 using passwords hints 339 verifying VTAM partner LUs 184 views authorization 289 creating 7, 12 dropping 84, 290 privileges records 117 VTAM APPL statement 185 connection control 142, 184 conversation-level security 185 partner LU verification 184 passwords choosing 184 VTAM partner LUs authenticating 185 VTAM partner LUsC verifying 184

W

WLM refreshing <u>156</u> stored procedures creating <u>155</u> write-down control mandatory access checking <u>124</u> write-down privileges <u>124</u> write-down privileges granting <u>125</u>

Ζ

z/OS console logs <u>364</u> z/OS identity filter DB2 support <u>169</u> implementing <u>169</u>

Db2 12 for z/OS: Managing Security (Last updated: 2024-09-06)



Product Number: 5650-DB2 5770-AF3



