

IBM Maximo Asset Management
Version 7 Release 6

Installation Guide
(Oracle WebLogic Server)



Note

Before using this information and the product it supports, read the information in "Notices" on page 63.

This edition applies to version 7, release 6, modification 0, fix pack 9 of IBM Maximo Asset Management and to all subsequent releases and modifications until otherwise indicated in new editions.

© **Copyright IBM Corporation 2007, 2017.**

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Contents

Chapter 1. Running the Maximo Asset Management 7.6.0.9 installation program 1

Chapter 2. Configuring Maximo Asset Management version 7.6.0.9 using the Maximo Asset Management version 7.6.0.9 configuration program 3

Chapter 3. Update the application database with the UpdateDB Lite command 5

Chapter 4. Installation and configuration programs log information 7

Chapter 5. Post installation tasks 9

Installing help locally	9
Installing help	9
IBM Knowledge Center configuration	10
Help components	11
Maximo Asset Management documentation library	12
Configuring initial data	14
Synchronizing users and groups	17
Adding sample data to the Maximo Asset Management database post configuration	17

Chapter 6. Maintaining EAR files 21

Building EAR files	21
Manually deploying Work Center WAR files	21
Manually uninstalling applications from Oracle WebLogic Server.	22
Manually uninstalling applications from Oracle WebLogic Server.	22

Chapter 7. Command line configuration 23

Configuration parameter validation	23
--	----

Input properties files	24
Command line interface parameters	25
Command line configuration program actions	32
action updateDatabaseConfiguration	32
action validateDatabaseConfiguration.	32
action validateAndUpdateDatabaseConfiguration	32
action deployDatabaseConfiguration	33
action removeDatabaseConfiguration.	33
action enableDB2TextSearch	33
action updateJ2eeConfiguration.	34
action validateJ2eeConfiguration	34
action validateAndUpdateJ2eeConfiguration	34
action deployJ2eeConfiguration.	34
action removeJ2EEConfiguration	35
action deployConfiguration	35
action removeConfiguration	35
action reapplyAppServerTuning	35
action enableAppSecurity.	36
action disableAppSecurity	36
action updateApplication.	36
action addLanguages	36
action configureProducts	37
action deployMiddlewareConfiguration	37
action upgrade75Configuration	38
action updateApplicationDBLite	38
action configureProductsDBLite	39
Configuration program properties	39

Chapter 8. Backup and restoration. 61

Backing up the administrative workstation	61
Restoring the administrative workstation	62

Notices 63

Trademarks	65
Terms and conditions for product documentation.	65
IBM Online Privacy Statement	66

Index 67

Chapter 1. Running the Maximo Asset Management 7.6.0.9 installation program

Use the Maximo® Asset Management version 7.6.0.9 installation program to install Maximo Asset Management version 7.6.0.9.

About this task

In order to install Maximo Asset Management version 7.6.0.9, run the Maximo Asset Management version 7.6.0.9 installation program on the Maximo Asset Management administrative system.

Procedure

1. Download the feature pack compressed file and copy it to the Administrative Workstation machine.
2. Run the Installation Manager from the following directory:

Option	Description
Windows	Start > All Programs > IBM Installation Manager > IBM Installation Manager
UNIX	In the /opt/IBM/InstallationManager/eclipse directory, run the IBMIM command.

3. In the Installation Manager main window, click **File > Preferences**.
4. Click **Add Repository**.
5. Add the repository for Maximo Asset Management version 7.6.0.9, click **OK**.
6. In the Preferences dialog box, click **OK**.
7. Click the Update icon.
8. In the Update Packages dialog box, select the IBM Tivoli's process automation suite package group, and click **Next**.
9. To complete the installation, follow the on screen instructions.
10. After the installation is complete, select the option to start the Maximo Asset Management version 7.6.0.9 configuration program, and then click **Finish**. The Maximo Asset Management version 7.6.0.9 installation program exits and the Maximo Asset Management version 7.6.0.9 configuration program is started automatically.

What to do next

Use the Maximo Asset Management version 7.6.0.9 configuration program to configure Maximo Asset Management version 7.6.0.9.

Chapter 2. Configuring Maximo Asset Management version 7.6.0.9 using the Maximo Asset Management version 7.6.0.9 configuration program

Use the Maximo Asset Management version 7.6.0.9 configuration program to configure Maximo Asset Management version 7.6.0.9.

Procedure

1. Start the configuration program:

Option	Description
Windows systems before Windows 7	Start > Programs > Tivoli's process automation suite > Configuration Program
Windows 7 and above	C:\IBM\SMP\ConfigTool\ConfigUI.exe or <i>InstallLocation</i> \ConfigTool\ConfigUI.exe
UNIX	<i>InstallLocation</i> /ConfigTool/ConfigUI. For example, /opt/IBM/SMP/ConfigTool/ConfigUI.

2. In the Deployment Operations pane, select **Update Database** and **Build and Deploy Application EAR Files**.
3. To complete the configuration, follow the on-screen instructions.

Results

Maximo Asset Management version 7.6.0.9 is installed and configured to use WebSphere® Application Server Network Deployment WebLogic Server.

Chapter 3. Update the application database with the UpdateDB Lite command

UpdateDB Lite splits the tasks of preparing class files and updating the database in Maximo Asset Management.

Starting with the v7.6.0.5 fix pack, you can minimize downtime by using new programs to manually perform configuration steps. Tasks that are performed by the UpdateDB Lite program, preparation of product class files and database updates, are split into two separate commands. These commands include pre-processing and post-processing.

Pre-processing tasks prepare class files before they are built into the application EAR files without stopping the application server. The UpdateDB Lite command can also perform this work, but it stops the application server.

In post-processing, UpdateDB Lite can perform updates to the database, but the application server must be stopped before you run the command. UpdateDB and UpdateDB Lite use the exact same parameters.

The Maximo Asset Management 7.6 configuration tool uses the UpdateDB to complete configuration.

Chapter 4. Installation and configuration programs log information

Log files generated by the Maximo Asset Management and configuration programs can provide details on completed and configuration tasks and any errors that might occur.

Maximo Asset Management installation and configuration programs log locations

Maximo Asset Management and associated middleware is installed through Installation Manager. The log files of Installation Manager are common to any installation, regardless of which components you choose to install. Log files for the Maximo Asset Management installation program are found on the system where it is run.

Table 1. Log file directories

Log file directory
C:\ProgramData\IBM\Installation Manager\logs
/var/ibm/InstallationManager/logs
C:\IBM\SMP\ConfigTool\logs
opt/IBM/SMP/ConfigTool/logs

When engaging IBM® product support services, be prepared to provide these log files in an archive file. The LogZipper utility provided in the *install_home*\configtool\scripts directory can be used for this task. If you use the LogZipper utility, all relevant log files are archived in *install_home*/configtool/debug/YYYYMMDD_hhmmss.zip.

Chapter 5. Post installation tasks

There are several post installation tasks required in order to complete the Maximo Asset Management deployment.

Installing help locally

Product help for Maximo Asset Management is provided online in IBM Knowledge Center. If you want to install help locally, you can download IBM Knowledge Center and help packages from Fix Central.

Installing help

You can download help packages from Fix Central that contain the same documentation packages that are available online in IBM Knowledge Center. You add the help packages and configuration files to a local installation of IBM Knowledge Center

Procedure

1. To download a locally-installable version of IBM Knowledge Center and help packages from Fix Central, follow the instructions at <http://www-01.ibm.com/support/docview.wss?uid=swg24041962>.
2. Extract the IBM Knowledge Center package to the location where you want to install it. The default installation location is C:\KnowledgeCenter. If you install IBM Knowledge Center to a different location, you must update the path value in the *taxonomy.properties* file for each help package that you install.
3. Extract a help package to a temporary location. The extracted files include one or more plugin folders, a properties file and a taxonomy file.
4. Copy all com.ibm.prod.doc plugin folders from the help package to the *install_home/KnowledgeCenter/usr/content/KCXhtml* directory.
5. Copy the properties file to the configuration directory, for example to *install_home/KnowledgeCenter/usr/conf/SSLKT6_7.6.0.5.properties*.
6. Open the *taxonomy.properties* file in a text editor and update the path value, if necessary, to point to the installed location. For example, change the value of the Path property from C:/KnowledgeCenter/usr/content/KCXhtml to E:/IBM/SMP/KnowledgeCenter/usr/content/KCXhtml, where IBM Knowledge Center is installed at E:/IBM/SMP/KnowledgeCenter.
7. Replace the *install_home/KnowledgeCenter/usr/taxonomy/KC_taxonomy.ditamap* with the version of the *KC_taxonomy.ditamap* file that is included in the help package.
8. In the *install_home/KnowledgeCenter/bin* directory, click **startKC.bat** on Windows or **startKC.sh** on Linux or AIX to start IBM Knowledge Center.
9. In a browser, open http://install_home:port/kc to view the product help, for example <http://127.0.0.1:9090/kc>.
10. In Maximo Asset Management, redirect the application help links to point to your local installation of IBM Knowledge Center:
 - a. In the System Properties application, filter for mxe.help properties.
 - b. Change the mxe.help.host and mxe.help.port properties to the host and port values for your local installation of IBM Knowledge Center, such as the default host value of 127.0.0.1 and default port value of 9090.

- c. Change the `mxe.help.path` property value from `/support/knowledgecenter/` to `/kc/`.
 - d. Save the changes and click **Live Refresh** to update the values in the product database.
11. To stop IBM Knowledge Center, in the `install_home/KnowledgeCenter/bin` directory, click **stopKC.bat** on Windows or **stopKC.sh** on Linux or AIX.

IBM Knowledge Center configuration

IBM Knowledge Center requires minimal configuration to run help packages for IBM products in your local environment. You can also configure it to provide different content in separate instances of IBM Knowledge Center or to run existing Eclipse help plugins in IBM Knowledge Center.

Changing the IBM Knowledge Center URL

If you install IBM Knowledge Center on your local computer, when you start the server, the help is available in a browser at the default URL of `http://localhost:9090/kc`. The host value changes, depending on where you install IBM Knowledge Center. If the default port is already in use, you can change the port value in the `kc_ant.properties` file in the `etc` directory.

If you want to provide different help to different audiences or if you want to host help for product versions that are not compatible with each other, you can install multiple instances of IBM Knowledge Center on the same computer. You rename the additional instances to unique directory names, such as `KnowledgeCenter2` and `KnowledgeCenter3`, and you configure the `kc_ant.properties` file in the `etc` directory so that each instance runs on a different port.

Maintaining taxonomy files

Each product version in the IBM software catalog has a unique taxonomy value that forms part of the URL for the product help on `www.ibm.com`. For example, the taxonomy value for Maximo Asset Management, version 7.6.0.5, is `SSLKT6_7.6.0.5`, and the URL for the product welcome page is `http://www.ibm.com/support/knowledgecenter/SSLKT6_7.6.0.5/com.ibm.mam.doc/welcome.html`. The `taxonomy.properties` file and the `KC_taxonomy.ditamap` file control the taxonomy values in IBM Knowledge Center.

Each help package includes a `taxonomy.properties` file that is specific to the product version. You must add this file to the `usr/conf` directory in IBM Knowledge Center. If you add help packages for multiple products to IBM Knowledge Center, the `usr/conf` directory must contain a separate `taxonomy.properties` file for each help package.

The `KC_taxonomy.ditamap` file lists each product version in the IBM software catalog, and the file is frequently updated as new products and new versions of products are released. A basic version of the `KC_taxonomy.ditamap` file is provided as a placeholder in the `usr/taxonomy` directory in IBM Knowledge Center but it does not contain a comprehensive list of product taxonomy values. You must replace this placeholder file with the version of the `KC_taxonomy.ditamap` that is included in the help package.

When you add multiple help packages to IBM Knowledge Center, each help package includes a `KC_taxonomy.ditamap` file. Because of the dynamic nature of this file, the included `KC_taxonomy.ditamap` files might be at different versions. Always

use the most recent version of the file because taxonomy values are added to the file incrementally.

Troubleshooting

When you start IBM Knowledge Center after adding a new help package, index and cache files are created to enable faster search and retrieval of help topics. If the new help topics do not show in a browser, check if subdirectories were created for the product version in the `runtime/diskcache` and `runtime/index` directories. If these subdirectories were not created, check that the `taxonomy.properties` file exists in the `usr/conf` directory and that it contains the correct path to the main help plugin in the `usr/content/KCXhtml` directory. If the `taxonomy.properties` is in the correct location and contains the correct path to the help plugin, it is likely that you forgot to add the latest version of the `KC_taxonomy.ditamap` to the `usr/taxonomy` directory.

After troubleshooting, before you start IBM Knowledge Center, you can delete the product version subdirectories in the `runtime/diskcache` and `runtime/index` directories, to ensure that the content is fully refreshed.

Help components

Help components include a locally installable version of IBM Knowledge Center and help packages that contain content plug-ins for product versions. You can download a locally installable version of IBM Knowledge Center to deploy help packages in your local environment.

IBM Knowledge Center

A stand-alone help system that includes a WebSphere Application Server Liberty, version 8.5.5.x, embedded server. IBM Knowledge Center is distributed to Maximo customers on <https://www-933.ibm.com/support/fixcentral/>. IBM Knowledge Center is available for Windows, Linux, or AIX® operating systems and you can run IBM Knowledge Center on a local computer, server, or read-only media.

After you extract the IBM Knowledge Center package, you add product help packages to it to deploy help in your local environment. You can use IBM Knowledge Center to host help packages for several products at the same time, if the products are on compatible release versions. If you want to host help packages that are not compatible with one another, you can run more instances of IBM Knowledge Center that you configure to run on different ports.

Help packages

Contain the same documentation that is available on <http://www.ibm.com/support/knowledgecenter> and include one or more content plug-ins. Help packages also include the following files that are required by IBM Knowledge Center:

- A `taxonomy.properties` file contains the taxonomy value for the product version and the path to the main `toc.ditamap` file for the plug-in or plug-ins in the help package.
- The `KC_taxonomy.ditamap` file lists the taxonomy values for all products in the IBM software catalog. A basic version of this file is included in IBM Knowledge Center but this version of the file is not up-to-date. The `KC_taxonomy.ditamap` file that is included in the help package is the current version of the file when the help package is created.

Help packages include instructions for where to add the plug-ins and the additional files to IBM Knowledge Center.

IBM Knowledge Center versions

The locally installable versions of IBM Knowledge Center are based on IBM Knowledge Center, version 1.5. This version has a different appearance to IBM Knowledge Center, version 2.0, which is on <http://www.ibm.com/support/knowledgecenter>. The functions are similar but some differences in navigation and search exist. PDF creation is not supported on the locally installable version.

When a locally installable IBM Knowledge Center, version 2.0, is available, it will be distributed to customers who want to update their local version.

Maximo Asset Management documentation library

The help packages in the documentation library mirror the product catalog and installation environment. Either the Maximo Asset Management help package or the Maximo Asset Management Multitenancy help package must be installed in the same IBM Knowledge Center environment where you install help packages for industry solutions and add-on products.

The Maximo Asset Management and Maximo Asset Management Multitenancy help packages contain multiple plugins. Most industry solution and add-on help packages contain just one plugin but some contain multiple plugins. When a help package contains multiple plugins, one plugin acts as the navigation plugin and contains the main *toc.ditamap* file that controls the table of contents for all plugins in the help package. In IBM Knowledge Center, the *taxonomy.properties* file in the help package specifies the path to the main *toc.ditamap* file in the navigation plugin.

Maximo Asset Management help package

This help package includes the following plugins:

com.ibm.mam.doc

Navigation plugin that manages the table of contents and sets the product taxonomy values for all plugins in the help package. Content includes the welcome page and product overview, planning, getting started, and managing financial processes topics.

com.ibm.mam.inswas.doc

Help for installing Maximo Asset Management on WebSphere Application Server.

com.ibm.mam.inswl.doc

Help for installing Maximo Asset Management on Oracle WebLogic Server.

com.ibm.mbs.doc

Help for administering Maximo Asset Management, application design, workflow design, working with Migration Manager, implementing high availability, and using applications. This plugin is a content reuse plugin that provides topics for use by other plugins but does not have a table of contents or a taxonomy value of its own. The content is used extensively by most help packages and you must include this plugin in IBM Knowledge Center to ensure that content is coherent and that links resolve for all help packages.

com.ibm.mif.doc

Help for integrating Maximo Asset Management data with external

applications. Similar to `com.ibm.mbs.doc`, this plugin is a content reuse plugin and must be included in IBM Knowledge Center.

`com.ibm.support.mbs.doc`

Troubleshooting and support information for Maximo Asset Management and for industry solutions and add-on products. Industry solution and add-on product troubleshooting topics are managed conditionally and are visible only if that help plugin is also available in IBM Knowledge Center.

Maximo Asset Management Multitenancy help package

This help package contains a subset of the plugins in the Maximo Asset Management help package and the content is specifically aimed at tenants in a multitenancy environment. You cannot install Maximo Asset Management plugins and Maximo Asset Management Multitenancy plugins in the same instance of IBM Knowledge Center environment. If you want to support both libraries, you must configure separate instances of IBM Knowledge Center to support them.

This help package includes the following plugins:

`com.ibm.mt.doc`

Navigation plugin that manages the table of contents and sets the product taxonomy values for all plugins in the help package. Content includes the welcome page and product overview, planning, getting started, and managing financial processes topics. Content also includes topics that are specific to a tenant in a multitenancy environment.

`com.ibm.mbs.doc`

Content reuse plugin and content is filtered to exclude information that is not relevant to tenants in a multitenancy environment.

`com.ibm.mif.doc`

Content reuse plugin and content is filtered to exclude information that is not relevant to tenants in a multitenancy environment.

Industry solution and add-on help packages

Most industry solution and add-on help packages contain just one plugin, but some contain multiple plugins. If there are multiple plugins in a help package, one plugin acts as the navigation plugin and controls the table of contents for all of the plugins in the help package. You must ensure that you add all of the plugins that are included in a help package to IBM Knowledge Center so that links resolve and content is complete.

The help packages for industry solutions and add-on products are designed to be used with the associated version of the Maximo Asset Management help package. You can check which version of Maximo Asset Management or Maximo Asset Management is a prerequisite for an industry solution or add-on product version at <https://www.ibm.com/developerworks/community/wikis/home?lang=en#!/wiki/IBM%20Maximo%20Asset%20Management/page/Other%20Maximo%20products%20system%20requirements>. You can install non-recommended versions of help packages together but some links might not resolve or some of the functionality described in topics might not be available to users.

Configuring initial data

After you successfully install and configure Maximo Asset Management components, you must complete several data configuration tasks before you use Maximo Asset Management.

Before you begin

- Create security groups and add users to the security groups.
- If you are using a directory server as part of your deployment, ensure that the user names are created in your LDAP repository.
- To ensure that you have the accounting information that you need, consult the Financial department of your organization.

Procedure

1. Log in to Maximo Asset Management by entering the user name `maxadmin` and the password that you specified during the installation.
2. If you didn't set the SMTP server by using the Configuration tool, configure the SMTP server to send users email notifications of system events. To learn about the range of system properties in Maximo Asset Management, see the System properties information.
 - a. From the **Go To** menu, select **System Configuration > Platform Configuration > System Properties**.
 - b. In the Global Properties table window, use the filter feature to search for and expand the `mail.smtp.host` property.
 - c. In the **Global Value** field, specify the SMTP host name.
 - d. Select the `mail.smtp.host` check box.
 - e. From the **Common Actions** menu, click **Live Refresh**.
 - f. In the Live Refresh window, click **OK**.
 - g. In the Global Properties table window, use the filter feature to search for the `mx.adminEmail` property.
 - h. Expand the `mx.adminEmail` property and in the **Global Value** field, specify your email address.
 - i. Select the `mx.adminEmail` record check box.
 - j. From the **Common Actions** menu, click **Live Refresh**.
 - k. In the Live Refresh window, click **OK**.
3. Define a currency code.
 - a. From the **Go To** menu, select **Financial > Currency Codes**
 - b. Click **New Row** and specify a currency code and a description. For example, enter USD for United States of America Dollar.
 - c. Click **Save Currency**.
4. Define item sets and company sets.
 - a. From the **Go To** menu, select **Administration > Sets**.
 - b. Click **New Row**.
 - c. Specify an item set name. For example, enter IT Items.
 - d. In the **Type** field, specify ITEM.
 - e. Click **New Row**.
 - f. Specify a company set name. For example, enter IT Comps.
 - g. In the **Type** field, specify COMPANY.
 - h. Click **Save Sets**.

5. Create an organization.
 - a. From the **Go To** menu, select **Administration > Organizations**.
 - b. From the toolbar, click **New Organization**.
 - c. Specify an organization name. For example, enter EAGLENA, and enter a long description.
 - d. Specify the base currency that you defined in step 3.
 - e. Specify the item set and the company set that you defined in step 4.
 - f. In the **Default Item Status** field, set the status to PENDING.
 - g. Click the **Sites** tab and select **New Row** under the Sites table window.
 - h. Specify a site name. For example, enter Factory01 and enter a long description.
 - i. Click **Save Organization**.
6. Create a general ledger account component.
 - a. From the **Go To** menu, select **System Configuration > Platform Configuration > Database Configuration**.
 - b. From the **More Actions** menu, select **GL Account Configuration**.
 - c. Click **New Row**.
 - d. Specify a component name. For example, enter MYCOMPONENT.
 - e. Specify a length for the component. For example, enter 5.
 - f. Specify a type for the component. For example, select Alphanumeric.
 - g. Click **OK**.
7. Apply changes to the database.
 - a. From the **More Actions** menu, select **Manage Admin Mode**.
 - b. Select **Turn Admin Mode ON** and click **OK**. This task takes several minutes to complete. You can click **Refresh Status** to view the progress.
 - c. From the **More Actions** menu, select **Apply Configuration Changes**. Ensure that the status To Be Changed does not appear in the status column of the listed objects.
 - d. From the **More Actions** menu, select **Manage Admin Mode**.
 - e. Select **Turn Admin Mode OFF** and click **OK**. If you do not turn off Admin Mode, cron tasks fail.
8. Create a general ledger account.
 - a. From the **Go To** menu, select **Financial > Chart of Accounts**.
 - b. In the Organizations table window, select your organization.
 - c. From the **More Actions** menu, select **GL Component Maintenance**.
 - d. In the Components table window, select the component that you entered in step 6 and click **New Row**.
 - e. Specify a GL Component value and a description, and then click **OK**.
 - f. In the GL Accounts table window, click **New Row**.
 - g. Specify a General Ledger Account and click **Save GL Account**.
 - h. From the **Go To** menu, select **Administration > Organizations**.
 - i. Find your organization and select the record.
 - j. In the **Clearing Account** field, specify the general ledger account that you created.
 - k. Select **Active**.
 - l. Click **Save Organization**.
9. Authorize a security group to modify a general ledger component type.

- a. From the **Go To** menu, select **Security > Security Groups**.
 - b. Select the group that provides authorization. For example, select **FINANCE**.
 - c. Click the **GL Components** tab.
 - d. For each GL Component that is listed, select the **Authorized** check box. As a shortcut, you can select **Authorize Group to Change All GL Component Types**.
 - e. Click **Save Group**.
10. Update the company-related accounts.
- a. From the **Go To** menu, select **Financials > Chart of Accounts**.
 - b. Select your organization and from the **More Actions** menu, select **Company-Related Accounts**.
 - c. Click **New Row** and specify the company type **Courier**.
 - d. Enter an account number in the **RBNI Account**, **AP Suspense Account**, and **AP Control Account** fields. You can specify the same account number in each field.
 - e. Click **OK**.
 - f. From the **More Actions** menu, select **Update Database** and click **OK**.
11. Create a default insert site.
- a. From the **Go To** menu, select **Security > Users**.
 - b. Find **maxadmin** and select the record.
 - c. In the **Default Insert Site** field, specify the site name that you created in step 5.
 - d. In the **Storeroom Site for Self-Service Requisitions** field, specify the same site name.
 - e. Click **Save User**.
12. Define work types. Work types denote the importance of the work task.
- a. From the **Go To** menu, select **Administration > Organizations**.
 - b. Find your organization and select the record.
 - c. From the **More Actions** menu, select **Work Order Options > Work Type**.
 - d. Click **New Row**.
 - e. In the **Work Order Class** field, select **WORKORDER**.
 - f. Specify a **Work Type**. For example, enter **MAJOR**.
 - g. Set the **Start Status** to **In Progress**.
 - h. Set the **Complete Status** to **Completed**.
 - i. Click **New Row** and repeat steps f-i to create another work order class with a different work type. For example, enter **MINOR**.
 - j. Click **New Row** and repeat steps f-i to create a **CHANGE** work order class with a different work type. For example, enter **SIG** to represent a significant change.
 - k. Click **OK** and click **Save Organization**.

Related information:

Integrating data with external applications

System properties

Synchronizing users and groups

When you select application server security, the scheduled synchronization of users and groups that occurs between LDAP repositories and Maximo Asset Management is governed by the federated repositories.

Before you begin

View the cron task configuration information in the Administering section of the Knowledge Center.

About this task

LDAP repositories are synchronized with Oracle WebLogic Server using the LDAP cron task.

To configure the synchronization schedule between LDAP repositories and Maximo Asset Management, complete the following steps:

Procedure

1. Open a web browser and point to `http://host name:port/maximo`.
2. Log in to Maximo Asset Management using the `maxadmin` user ID.
3. From the Maximo Asset Management interface, navigate to **Go To > System Configuration > Platform Configuration > Cron Task Setup**.
4. Search for the appropriate cron task in the **Cron Task** field and configure it.
5. Set the task to **active**.

What to do next

By default, the cron task performs its task every 5 minutes. Change the **Schedule** field of the cron task if you want to change the interval.

Adding sample data to the Maximo Asset Management database post configuration

Using the `maxinst` command, you can add sample data to the Maximo Asset Management database after the initial installation and configuration of Maximo Asset Management.

Before you begin

The `maxinst` command does not provide default values for table space parameters. You must specify the data table space name and the index table space name that you specified during the installation. The `maxinst` command replaces the current database schema and data. Do not add sample data to the Maximo Asset Management database if you want to preserve records currently stored in the database.

About this task

If you created a database either automatically or manually during the installation, you can use the `maxinst` command to create a sample data in that database instance.

Procedure

1. Back up the existing database.
2. Unzip the `install_home\IBM\SMP\Maximo\tools\maximo\en\maxdemo.dbtype.zip` file. Replace the `dbtype` variable with the extension that is appropriate for the type of database you used for the Maximo Asset Management deployment. Available options are `ora`, `sqs`, or `db2`.
3. Change the `install_home\IBM\SMP\Maximo\tools\maximo\en\maxdemo.dbtype` file to the name of the Maximo Asset Management database you configured during the initial deployment. For example, rename the file to `max76db.db2`
4. Open a command prompt and change to the `install_home\IBM\SMP\Maximo\tools\maximo` directory.
5. Populate the database with sample data. You must specify the table space name parameters when you run the `maxinst` command.
`maxinst -stablespace -ttablespace -imax76db` For example, for Oracle Database or for DB2®, enter `maxinst -sMAXDATA -tMAXDATA -imax76db`. For SQL Server, enter `maxinst -tPRIMARY -sPRIMARY -imax76db`. The system reads the `maximo.properties` file for database connectivity information. The `maximo.properties` file is in the `install_home\IBM\SMP\Maximo\Applications\Maximo\Properties` directory.
6. Populate the database by running commands with specific parameter values. Use the following **maxinst** database parameters:

Parameter	Description
-a	Database alias. If not specified, the alias <code>mxe.db.url.property</code> is used.
-d	Log file directory. If you are using the <code>-l</code> parameter, the log file is sent to the specified directory. Otherwise, the log file is sent to the log directory, for example <code>install_home\IBM\SMP\Maximo\tools\maximo\logs</code> .
-e	Runs the SQL. This parameter is required and already present in the <code>maxinst.bat</code> file.
-f	File name for the properties file. If not specified, <code>maximo.properties</code> is used.
-i	File name of the input file (without path or extension).
-k	Directory of the properties file.
-l	Creates a detailed log file. This parameter is already present in the <code>maxinst.bat</code> file.
-m2	Optional value for SQL Server: Multiplies the column width for strings by 2. This value is required for double-byte character sets.
-o	If you are using the <code>-l</code> parameter, the <code>-o</code> parameter specifies the file name for the log file.
-p	Password for the database connection. If not specified, the <code>mxe.db.password</code> property or <code>MAXIMO</code> is used. If <code>MAXIMO</code> is used, it must be entered in uppercase letters.

Parameter	Description
-s	Required value: Table space for index storage.
-t	Required value: Table space for table storage.
-u	User name for database connection. If not specified, the <code>mxe.db.user</code> property or MAXIMO is used. If MAXIMO is used, it must be entered in uppercase letters.
-x	Required value for UNIX: Fixes the doclink file separators in UNIX environments. Note: If a UNIX environment is deployed without using this parameter, the attached documents do not function properly.
-y	Multiplies the column width for strings by 2. This value is required for double-byte character sets.

- From the `install_home\IBM\SMP\ETC` directory, open the `install.properties` file and specify the installation-related properties. You can add these properties to the database from the System Properties application.

Results

The Maximo Asset Management database is populated with sample data.

If an error occurs when you run the `maxinst` command, check the log file in the `install_home\IBM\SMP\Maximo\tools\maximo\logs` directory. If the `maxinst` command fails, you must correct the error and rerun the `maxinst` command to complete the Maximo database schema deployment before you can start the application.

Chapter 6. Maintaining EAR files

This section contains information about maintaining Maximo Asset Management EAR files.

The following instructions are used to manually build or uninstall the Maximo Asset Management `maximo.ear` file on Oracle WebLogic Server.

- If you modify any database connection parameters in the `maximo.properties` file after the initial installation, you must rebuild of the `maximo.ear` file, and then redeploy it in Oracle WebLogic Server. In this scenario, you would likely only rebuild and redeploy the `maximo.ear` file.
- If you have installed Maximo Asset Management into a development environment, you might at some point like to migrate the deployment into a test or production environment. In this scenario, you must deploy both the `maximo` and `maximo help` applications into the new environment.

Building EAR files

You can manually build Maximo Asset Management EAR files if, for example, you modify a database connection parameter in the `maximo.properties` file after the initial installation.

About this task

To manually build Maximo Asset Management EAR files, use the `buildmaximoear` command.

Windows

```
install_home\maximo\deployment\buildmaximoear.cmd
```

Linux and UNIX

```
install_home/maximo/deployment/buildmaximoear.sh
```

Manually deploying Work Center WAR files

The Work Center WAR file, `maximo-x.war`, is automatically built and deployed during the installation and configuration process. However, you can manually build the Work Center WAR file by using the `buildmaximo-xwar` command.

Procedure

1. Log on to the administrative workstation, open a command line, and change to the `maximo-root\deployment` directory.
2. Run the `buildmaximo-xwar` command. The `maximo-x.war` file is created in `maximo-root\deployment\default` directory.
3. Deploy the `maximo-x.war` file on the Maximo Asset Management application server.

Configuration	Action
Simple	Deploy the <code>maximo-x.war</code> file on the Maximo Asset Management application server or UI cluster.

Configuration	Action
Proxy server that communicates with Maximo Asset Management by using a single hostname and port	Deploy the maximo-x.war file on a separate application server.
Cross origin requests to the Maximo Asset Management server.	Configure the CORS settings by using servlet filters that set access control headers on the application server that hosts the maximo-x application.

Results

After you build and deploy the maximo-x.war file, use the default context path /maximo-x to access the Work Centers.

Manually uninstalling applications from Oracle WebLogic Server

This section contains information about uninstalling Maximo Asset Management applications from Oracle WebLogic Server.

Manually uninstalling applications from Oracle WebLogic Server

Procedure

1. Log into the Administration Console. For example, `http://<server>:<port>/console`
2. Click **Lock & Edit**.
3. Click **Deployments**.
4. Select the application for the EAR to uninstall.
5. Click **Delete**.

Chapter 7. Command line configuration

Maximo Asset Management includes a configuration program, **reconfigurePae**, located in the *Install_Home \ConfigTool\scripts* directory, that is accessed from the command line. This command line configuration program performs the same duties as the Maximo Asset Management configuration program user interface. Command line configuration is used to quickly update configuration values when you choose to not use the configuration tool user interface.

When you install a fix pack or upgrade Maximo Asset Management, the configuration program uses values that are recorded from the previous deployment. These values are stored on the administrative system in the *install.properties* and *maximo.properties* files that are located under the *install_home\etc* and *install_home\maximo\applications\maximo\properties* directories.

If you make any environmental changes to any of the systems that are used for the original deployment, they must be recorded in the *install.properties* and *maximo.properties* files. Typically, these types of changes would include changing a host name or updating a password, for example.

You can update these values manually, or you can use the configuration command line interface tool to update configuration values for your existing deployment when they change. Properties that are specified for the configuration command line interface tool, either as parameters, or in an input properties file, replace existing properties in the *maximo.properties* and *install.properties* files. Properties are encrypted when they are saved.

You can complete the following tasks with the configuration command line interface tool:

- Change the security model for the original deployment. For example, you can migrate from Maximo Asset Management-based security to WebSphere Application Server security. This option is not available for Oracle WebLogic Server.
- Confirm that updated property values conform to required input domains. Validate credentials, host names, and available ports.
- Update database or application server configuration settings without the server available. These values cannot be validated in this scenario.
- Clone an existing environment and use the configuration command line interface tool to reconfigure the administrative workstation to use the new servers. The cloned environment must use the same directory structure as the original.
- Create an environment (non-cloned) and use the configuration command line interface tool to create all required artifacts database, table spaces, and application server objects, for example.
- Remove configuration from a previously configured database.

Configuration parameter validation

Use the Maximo Asset Management command line configuration program to validate input in the same way the Maximo Asset Management configuration program validates input in the user interface.

You can validate the following items with the Maximo Asset Management command line configuration program.

- Host names or IP addresses are correctly formatted and are reachable.
- User IDs and passwords meet length and character set criteria.
- Specified credentials are used to authenticate to WebSphere Application Server.
- Specified port values are listening on the corresponding host. Port values contain numbers only and are within a valid range.
- Middleware installation directories that are supplied exist.
- Preconfigured middleware can authenticate to the product database.
- Required objects such as JMS queues, SIB destinations, databases, and table spaces exist.
- Required WebSphere Application Server virtual member manager users exist.
- Sufficient authority is available to create WebSphere Application Server virtual member manager users.
- Remote login credentials are valid.
- There is enough space in the supplied directories to create database objects.

Input properties files

You can use property files as input for the Maximo Asset Management command-line configuration program.

The following sample input property files are provided with the Maximo Asset Management command-line configuration program.

- `DB2_Sample_input.properties`
- `Oracle_Sample_input.properties`
- `SQLServer_Sample_input.properties`
- `WebSphere_App_Server_Sample_input.properties`

These sample files are in the `ibm\smp\configtools\samples` directory. Each of these sample files contains properties that are associated with a specific database or application server type. They contain comments and properties you can update with values from your environment. You can then use the updated file as input for the configuration command line interface tool with the `-input` parameter.

All input properties, introduced from either the command line or in the input properties file, are validated before they are used. After validation is successful, the `maximo.properties` and `install.properties` files are updated with the values you provided.

Command line interface parameters

The following parameters can be used with the configuration command line program to configure your environment.

Table 2. Maximo Asset Management command line configuration program parameters

Parameter name	Description
-action	<p>Configuration action.</p> <ul style="list-style-type: none"> • addLanguages – Adds additional languages to a current deployment. • configureProducts - Configures more products after an initial installation and configuration. This action should be used to configure multiple products after they are installed and should also be used in an upgrade scenario. • configureProductsDBLite - Configures more products after an initial installation and configuration using the DB Lite feature. This action can configure multiple products after they are installed and can also be used in an upgrade scenario. • deployConfiguration - Configures initial installation. This action can configure multiple products after they are installed. This action is used for new installations only. • deployDatabaseConfiguration - Validates command input and defines configuration property values for a new database for the current product. • deployJ2eeConfiguration - Validates command input and defines configuration property values for a new application server for the current product. • deployMiddlewareConfiguration – Configures initial middleware installation. • disableAppSecurity - Disables application security for the application. Security is handled entirely through Maximo Asset Management. This action sets the mxe.useAppServerSecurity property to a value of 0. This value is written to the database when updated. • disableDB2TextSearch - Disable the full text search feature on a Db2 database. • enableAppSecurity – Enables application security for the application. This action sets the mxe.useAppServerSecurity property to a value of 1, and updates the mxe.ldapUserManagement flag. This value is written to the database when the database is updated. • enableDB2TextSearch – Enables the full text search feature on a Db2 database. • reapplyAppServerTuning – Reapplies tuning configuration to an application server. • removeDatabaseConfiguration – Removes product configuration information from a previously configured database. • removeJ2EEConfiguration – Removes application server configuration that was added by the configuration tool. • updateApplication – Updates the Maximo Asset Management application by updating the database and redeploying application EAR files. This action should not be used in an upgrade scenario or when a new product is installed in an existing product.

Table 2. Maximo Asset Management command line configuration program parameters (continued)

Parameter name	Description
	<ul style="list-style-type: none"> • updateApplicationDBLite – Update the database using the DB Lite feature and then rebuild and redeploy the EARs. • updateDatabaseConfiguration – Updates existing database configuration values. • updateJ2eeConfiguration - Updates existing application server configuration values. • upgrade75Configuration - Performs database properties validation for your Maximo Asset Management 7.5 deployment to ensure a valid connection to the database, and also configures WebSphere Application Server for Maximo Asset Management 7.6. When you upgrade from Maximo Asset Management 7.5, you must configure a new instance of WebSphere Application Server. • validateAndUpdateDatabaseConfiguration – Validates reconfiguration command line interface tool input and then updates existing database configuration property values. • validateAndUpdateJ2eeConfiguration - Validates reconfiguration command line interface tool input and then updates existing database configuration property values. • validateDatabaseConfiguration - Validates database configuration values specified as input for the reconfiguration command line interface tool. • validateJ2eeConfiguration - Validates application server configuration values that are specified as input for the reconfiguration command line interface tool. • removeConfiguration - Removes database and application configuration performed by the configuration tool. <p>The actions that modify the security setting for Maximo Asset Management also updates Maximo Asset Managementweb.xml files.</p>
-additionalLangs	<p>Adds one or more additional languages to the deployment.</p> <p>This parameter requires one or more locale abbreviations for input. For example, ES for Spanish.</p>
-allowUpdateDB	<p>The database update task is run to add the languages that are specified to the database.</p>
-applicationServerName	<p>Name of the application server.</p>
-applicationServerNode	<p>Name of the application server node.</p>
-automatedbconfig	<p>Automates the configuration of the database. Use this parameter to create the database instance, database users, the database, table spaces, and creates database schema.</p>
-automatej2eeconfig	<p>Automates the configuration of WebSphere Application Server. Using this parameter creates, for example, JMS queues and profiles.</p>
-buildAndDeployEAR	<p>Rebuilds and deploys application EAR files. Application EAR files must be rebuilt and redeployed for configuration changes to take effect in the application.</p>
-buildears	<p>Rebuilds application EAR files.</p>

Table 2. Maximo Asset Management command line configuration program parameters (continued)

Parameter name	Description
-bypassJ2eeValidation	<p>Skips the validation and configuration of the application server.</p> <p>If you use this parameter, then you must manually configure the application server before you can deploy Maximo Asset Management.</p> <p>Validation of a manually configured application server requires logging in to the application server with application server administrative credentials. If you do not want to provide those credentials to the configuration program, you can skip the validation task.</p> <p>If you use the bypassJ2eeValidation parameter, you cannot also use the following parameters:</p> <ul style="list-style-type: none"> • applicationServerName • applicationServerNode • automatej2eeconfig • buildAndDeployEAR • createResourcesIfMissing • deploymaximoear • enableappsecurity • enableEnhancedNavigation • enableSkin • inputfile • j2eeserverport • usermanagement • wasuser • waspwd
-bypassUpdateDB	<p>Specifies that the database update task is not run and the installation program does not update the database.</p> <p>Languages files for the locales that are specified are built into the application EAR file.</p> <p>Use this parameter if you have run the database update task and included the language files in the database through another method.</p>
-createResourcesIfMissing	Creates any resources that are not found during configuration.
-db2_english_only	<p>Specifies that alphanumeric data is stored as a varchar data type. Using this parameter limits you to using English in the user interface.</p> <p>If you do not use this parameter, alphanumeric data is stored as a vargraphic data type.</p>
-db2textsearchport	Port that is used by the Db2 server for full text search.
-dbname	Name of the database.
-dbpwd	Password for the user ID that accesses the database.
-dbrxapwd	Password for the user ID used to access a remote middleware server.
-dbrxuser	User ID used to access a remote middleware server.
-dbserverhost	Host name of the database server.

Table 2. Maximo Asset Management command line configuration program parameters (continued)

Parameter name	Description
-dbserverport	Port name of the database server.
-dbuser	User ID that accesses the database.
-dbvendor	Database software name. <ul style="list-style-type: none"> • DB2 • Oracle • SQLServer
-deleteInstanceUsersAndGroups	Removes the instance owner and database user IDs and associated groups from the Db2 server. This parameter has cannot be used with and Microsoft SQL Server. The deleteInstanceUsersAndGroups parameter requires the dbrxuser and dbrxpwd and the dbuser and dbpwd parameters.
-deleteWASprofiles	Deletes the WebSphere Application Server profiles that are created for the application.
-deployDemoData	Includes sample data.
-deploymaximoear	Deploys Maximo application EAR file.
-enableappsecurity	Enables application security for the application. This parameter works the same as the enableAppSecurity action. This action sets the mxo.useAppServerSecurity property to a value of 1, and updates the mxo.IdapUserManagement flag. This value is written to the database when updated.
-enableEnhancedNavigation	Enables enhanced navigational elements in the user interface, including enhancements for switching between applications and viewing record lists. The enableEnhancedNavigation parameter must be used with the enableSkin parameter. If you enable enhanced navigation, and then you enable a different user interface skin with the -enableSkin parameter, you must re-enable enhanced navigation.
-enableMultiTenancy	Enables the multitenancy feature. Multitenancy refers to software or services that can be configured to serve multiple groups of clients referred to as tenants. Each group of tenants is served by an instance of the software that uses data that only they can access.

Table 2. Maximo Asset Management command line configuration program parameters (continued)

Parameter name	Description
<p>-enableRestrictivePasswordPolicy</p>	<p>Enables a more restrictive password policy for Maximo Asset Management users.</p> <ul style="list-style-type: none"> • Login attempts <p>Standard policy allows 10 login attempts before the account is locked.</p> <p>Restrictive policy allows 3 login attempts before the account is locked.</p> • Number of times that the forgotten password link can be used <p>Standard policy allows 5 uses of the forgotten password link before locking the account.</p> <p>Restrictive policy allows 3 uses of the forgotten password link before locking the account.</p> • Password duration (days) <p>Standard policy passwords never expire.</p> <p>Restrictive policy passwords expire after 90 days.</p> • Password expiration warning (days) <p>Standard policy does not warn the user that the account password is about to expire.</p> <p>Restrictive policy warns the user that the account password is about to expire seven days before it expires.</p> • Password threshold <p>Standard policy does not enforce a password threshold.</p> <p>Restrictive policy enforces a password threshold of 270 characters.</p>
	<ul style="list-style-type: none"> • Password minimum character length <p>Standard policy passwords must be at least six characters.</p> <p>Restrictive policy passwords must be at least eight characters.</p> • Limit of allowed consecutive characters <p>Standard policy has no restrictions to the amount of times a character can be repeated consecutively in a password.</p> <p>Restrictive policy allows a character to be repeated two times consecutively in a password value.</p> • Password can be same value as user name <p>Standard policy allows you to use the same value for the user name and password.</p> <p>Restrictive policy does not allow you to use the same value for the user name and password.</p> • Number of numeric characters required in the password <p>Standard policy does not require numeric characters in a password value.</p> <p>Restrictive policy requires one or more numeric characters in a password value.</p> • Number of alphabetic characters required in the password <p>Standard policy does not require alphabetic characters in a password value.</p> <p>Restrictive policy requires one or more alphabetic characters in a password value.</p>

Table 2. Maximo Asset Management command line configuration program parameters (continued)

Parameter name	Description
-enableSkin	<p>Change the appearance of the user interface.</p> <ul style="list-style-type: none"> • Classic <p>Removes settings for the following properties:</p> <ul style="list-style-type: none"> – mxe.webclient.homeButtonHeaders – mxe.webclient.systemNavBar – mxe.webclient.tabBreadCrumbs – mxe.webclient.verticalLabels – mxe.webclient.skin • tivoli09 <p>Removes settings for the following properties:</p> <ul style="list-style-type: none"> – mxe.webclient.homeButtonHeaders – mxe.webclient.systemNavBar – mxe.webclient.tabBreadCrumbs – mxe.webclient.verticalLabels <p>Sets the following property:</p> <ul style="list-style-type: none"> – mxe.webclient.skin=tivoli09 • tivoli13 <p>Sets the following properties to a value of 1:</p> <ul style="list-style-type: none"> – mxe.webclient.homeButtonHeaders – mxe.webclient.systemNavBar – mxe.webclient.tabBreadCrumbs – mxe.webclient.verticalLabels <p>Sets the following property:</p> <ul style="list-style-type: none"> – mxe.webclient.skin=tivoli13
-force	<p>Indicates that an input property file updates the properties file and skips the validation of parameters input to the command line tool through an input properties file.</p> <p>When you use this parameter, you are not prompted for confirmation of the property update task.</p>
-inputfile	<p>Fully qualified path to the properties file that is used to set properties in an environment.</p> <p>Values that are specified as command line parameters for the configuration command line interface tool supersede values from the input file.</p>
-j2eeserverhost	<p>Host name of the domain manager of the application server.</p> <p>If deployment manager host name or server port is specified the thinwsadmin scripts are updated accordingly.</p>
-j2eeserverport	<p>Port name of the application server domain manager server.</p> <p>If deployment manager host name or server port is specified the thinwsadmin scripts are updated accordingly.</p>
-j2eevendor	<p>Application server software.</p> <ul style="list-style-type: none"> • WebSphere • WebLogic

Table 2. Maximo Asset Management command line configuration program parameters (continued)

Parameter name	Description
-removeCreatedArtifacts	Removes any artifacts that are created by the configuration tool. Examples include directories that are created by the configuration program, JMS objects, and the application server.
-removeInstance	Removes the database instance for Db2 and Oracle. This parameter cannot be used with Microsoft SQL Server. The removeInstance parameter requires the dbxouser and dbxapwd , and the dbuser and dbpwd parameters.
-setjdbcurl	Sets the JDBC connection URL string.
-stopAppServer	The application server must be stopped when you add languages. If you do not use the stopAppServer parameter with the addLanguages action, you must stop the application server manually before you use the addLanguages action. This parameter is used for WebSphere Application Server only.
-unsetjdbcurl	Removes the currently used JDBC connection URL string.
-updatedb	Runs the updatedb configuration task.
-usermanagement	Changes the security configuration of the existing Maximo deployment. <ul style="list-style-type: none"> • j2ee Change the security setting in Maximo so that both Maximo users and Maximo groups are managed through application server security mechanisms. • mixed Manage users through application server security mechanisms, and manage groups using Maximo.
-validateForNewDeploy	Validate middleware configuration. When this parameter is specified, validation is performed as if the tool was configuring the middleware. Additional configuration details are checked, including disk space availability and remote access credentials. If this parameter is not specified, validation is performed in the context of a component that is already established in the environment.
-validateUsers	Used with the enableAppSecurity action to validate users exist in the LDAP repository. If the users do not exist, the existing security model is not modified.
-waspwd	WebSphere Application Server administrator user ID password.
-wasrxapwd	Password for user ID to access remote WebSphere Application Server server host.
-wasrxouser	Operating system user ID used to access remote WebSphere Application Server host. Typically this user ID is defined either as Administrator or root.
-wasuser	WebSphere Application Server administrator user ID. This is the user ID that is used to log in to the WebSphere Application Server administrative client application. Typically, this user ID is defined as wasadmin.

Command line configuration program actions

Use the command line configuration program to configure new or existing deployments of Maximo Asset Management.

action updateDatabaseConfiguration

The **updateDatabaseConfiguration** action is used to update existing database configuration values.

```
-action updateDatabaseConfiguration [-force] [-buildAndDeployEAR]
[-dbserverhost hostname] [-dbserverport port number]
[-dbname database name] [-dbuser userid]
[-dbpwd password] [-dbrxauser userid]
[-dbrxapwd password] [-setjdbcurl jdbcurl]
[-unsetjdbcurl] [-inputfile path to input properties file]
```

action validateDatabaseConfiguration

Use the **validateDatabaseConfiguration** action to validate current database configuration properties. This action can be used to verify database properties before they are updated, or following an update action.

```
-action validateDatabaseConfiguration [-validateForNewDeploy]
[-dbserverhost hostname]
[-dbserverport port number]
[-dbname database name]
[-dbuser userid] [-dbpwd password]
[-dbrxauser userid]
[-dbrxapwd password] [-setjdbcurl jdbcurl]
[-unsetjdbcurl] [-enableMultiTenancy]
[-inputfile path to input properties file]
```

The following properties are required if the **-validateForNewDeploy** parameter is used.

- **Database.DB2.InstanceAdminGroup**
- **Database.DB2.InstanceAdminUserName** (Windows only)
- **Database.DB2.InstanceAdminPassword** (Windows only)
- **Database.DB2.FencedUser**
- **Database.DB2.FencedUserPassword**
- **Database.DB2.FencedGroupName**
- **Database.DB2.InstanceUserPassword**

These properties must be added manually to the `install.properties` file.

action validateAndUpdateDatabaseConfiguration

The **validateAndUpdateDatabaseConfiguration** action is used to both validate reconfiguration command-line interface tool input and then update existing database configuration property values.

```
-action validateAndUpdateDatabaseConfiguration [-validateForNewDeploy] [-force]
[-buildAndDeployEAR] [-dbserverhost hostname]
[-dbserverport port number] [-dbname database name]
[-dbuser userid] [-dbpwd password]
[-dbrxauser userid] [-dbrxapwd password]
[-setjdbcurl jdbcurl] [-unsetjdbcurl] [-enableMultiTenancy]
[-inputfile path to input properties file]
```

The following properties are required if the **-validateForNewDeploy** parameter is used.

- **Database.DB2.InstanceAdminGroup**
- **Database.DB2.InstanceAdminUserName** (Windows only)
- **Database.DB2.InstanceAdminPassword** (Windows only)
- **Database.DB2.FencedUser**
- **Database.DB2.FencedUserPassword**
- **Database.DB2.FencedGroupName**
- **Database.DB2.InstanceUserPassword**

These properties that must be added manually to the `install.properties` file.

The `-enableMultiTenancy` parameter must be used with the `-validateForNewDeploy` parameter.

action deployDatabaseConfiguration

The `deployDatabaseConfiguration` action is used to validate command-line configuration program input and define configuration property values for a new database for the currently deployed product. This action can be run after a successful `deployConfiguration` action.

```
-action deployDatabaseConfiguration [-buildAndDeployEAR] [-createResourcesIfMissing]
[-dbserverhost hostname] [-dbserverport port number]
\[-dbname database name] [-dbuser userid]
[-dbpwd password] [-dbrxouser userid] [-dbrxapwd password]
[-setjdbcurl jdbcurl] [-unsetjdbcurl] [-enableMultiTenancy]
[-deployDemoData]
[-inputfile path to input properties file] [-enableRestrictivePasswordPolicy]
```

The following properties are required if the `-createResourcesIfMissing` parameter is used.

- **Database.DB2.InstanceAdminGroup**
- **Database.DB2.InstanceAdminUserName** (Windows only)
- **Database.DB2.InstanceAdminPassword** (Windows only)
- **Database.DB2.FencedUser**
- **Database.DB2.FencedUserPassword**
- **Database.DB2.FencedGroupName**
- **Database.DB2.InstanceUserPassword**

These properties that must be added manually to the `install.properties` file.

action removeDatabaseConfiguration

The `removeDatabaseConfiguration` action is used to remove configuration settings from a previously configured database.

```
-action removeDatabaseConfiguration [-removeInstance] [-dbrxouser userid]
[-dbrxapwd password] [-dbuser userid]
[-dbpwd password] [-deleteInstanceUsersAndGroups]
```

action enableDB2TextSearch

The `enableDB2TextSearch` action is used to enable the full text search feature for a Db2 database.

```
-action enableDB2TextSearch [-db2textsearchport port number]
```

action updateJ2eeConfiguration

The **updateJ2eeConfiguration** action is used to update existing application server configuration values.

```
-action updateJ2eeConfiguration [-force] [-buildAndDeployEAR]
[-j2eeserverhost hostname] [-j2eeserverport port number]
[-wasuser userid] [-waspwd password]
[-applicationServerNode nodeName] [-applicationServerName appServerName]
[-inputfile path to input properties file]
```

action validateJ2eeConfiguration

The **validateJ2eeConfiguration** action is used to validate application server configuration values specified as input for the reconfiguration command-line interface tool.

```
-action validateJ2eeConfiguration [-validateForNewDeploy] [-j2eeserverhost hostname]
[-j2eeserverport port number] [-wasuser userid]
[-waspwd password] [-applicationServerNode nodeName]
[-applicationServerName appServerName] [-inputfile path to input properties file]
```

The following properties are required if the **-validateForNewDeploy** parameter is used and the **WAS.SibPersistMessages** property is set to true.

- **Database.DB2.FencedUser**
- **Database.DB2.FencedUserPassword**
- **Database.DB2.InstanceUserPassword**

These properties that must be added manually to the `install.properties` file.

action validateAndUpdateJ2eeConfiguration

The **validateAndUpdateJ2eeConfiguration** action is used to both validate reconfiguration command-line interface tool input and then update existing application server configuration property values.

```
-action validateAndUpdateJ2eeConfiguration [-force] [-validateForNewDeploy]
[-buildAndDeployEAR] [-j2eeserverhost hostname]
[-j2eeserverport port number] [-wasuser userid]
[-waspwd password] [-applicationServerNode nodeName]
[-applicationServerName appServerName]
[-inputfile path to input properties file]
```

The following properties are required if the **-validateForNewDeploy** parameter is used and the **WAS.SibPersistMessages** property is set to true.

- **Database.DB2.FencedUser**
- **Database.DB2.FencedUserPassword**
- **Database.DB2.InstanceUserPassword**

These properties must be added manually to the `install.properties` file.

action deployJ2eeConfiguration

The **deployJ2eeConfiguration** action is used to validate command line configuration program input and define configuration property values for a new application server for the currently deployed product. This action can be run after a successful **deployConfiguration** action.

```
-action deployJ2eeConfiguration [-bypassJ2eeValidation] [-buildAndDeployEAR]
[-createResourcesIfMissing] [-j2eeserverhost hostname]
[-j2eeserverport port number] [-wasuser userid]
[-waspwd password] [-applicationServerNode nodeName]
```

```
[-applicationServerName appServerName]  
[-inputfile path to input properties file]  
[-enableSkin Classic|tivoli09|tivoli13] [-enableEnhancedNavigation]
```

The following properties are required if the **-validateForNewDeploy** parameter is used and the **WAS.SibPersistMessages** property is set to true.

- **Database.DB2.FencedUser**
- **Database.DB2.FencedUserPassword**
- **Database.DB2.InstanceUserPassword**

These properties that must be added manually to the `install.properties` file.

action removeJ2EEConfiguration

The **removeJ2EEConfiguration** action is used to remove configuration settings from a previously configured application server. Items removed include domain manager and application server profiles, and JMS objects.

```
-action removeJ2EEConfiguration [-wasuser userid] [-waspwd password]  
[-wasrxuser userid] [-wasrxapwd password]  
[-removeCreatedArtifacts] [-deleteWasProfiles]
```

action deployConfiguration

Use the **deployConfiguration** action to configure the initial installation. This action is used for new Maximo Asset Management installation scenarios only. This action can configure multiple middleware products after they are installed. The **deployConfiguration** action requires the **inputfile** parameter and an input properties file populated with the configuration values you want to use.

```
-action deployConfiguration [-inputfile path to input properties file]  
[-dbvendor Oracle|DB2|SQLServer] [-j2eevendor WebSphere|WebLogic]  
[-bypassJ2eeValidation] [-automatedbconfig] [-automatej2eeconfig]  
[-usermanagement j2ee|mixed] [-buildears] [-deploymaximoear]  
[-enableappsecurity] [-deployDemoData] [-enableMultiTenancy] [-db2_english_only]  
[-enableSkin Classic|tivoli09|tivoli13] [-enableEnhancedNavigation]  
[-enableRestrictivePasswordPolicy]
```

action removeConfiguration

The **removeConfiguration** action is used to removes database and application configuration that is performed by the configuration tool. This action is equivalent to running the **removeJ2EEConfiguration** and **removeDatabaseConfiguration** actions together

```
-action removeConfiguration -dbuser userid  
-dbpwd password -wasuser userid  
-waspwd password [-wasrxuser userid]  
[-wasrxapwd password] [-dbrxuser userid]  
[-dbrxapwd password] [-removeInstance] [-deleteInstanceUsersAndGroups]  
[-removeCreatedArtifacts] [-deleteWasProfiles]  
[-inputfile path to input properties file]
```

action reapplyAppServerTuning

The **reapplyAppServerTuning** action is used to reapply best practices application server tuning settings.

```
-action reapplyAppServerTuning [-wasuser userid]  
[-waspwd password] [-applicationServerNode nodeName]  
[-applicationServerName appServerName]
```

You must restart the application server after the settings are applied.

action enableAppSecurity

The **enableAppSecurity** action is used to enable application security for the application. This action sets the **mx.e.useAppServerSecurity** property to a value of 1, and updates the **mx.e.ldapUserManagement** property according to the setting of the **-usermanagement** parameter. This value is written to the database when updated. The **maximouiweb**, **maxrestweb**, **meaweb**, and **mboweb** **web.xml** files are updated during this action.

```
-action enableAppSecurity -usermanagement {j2ee,mixed}
[-buildAndDeployEAR] [-validateUsers] [-force]
```

action disableAppSecurity

The **disableAppSecurity** action is used to disable application security for the application. This action sets the **mx.e.useAppServerSecurity** property to a value of 0. This value is written to the database when updated. Using this action reverts the security implementation to Maximo security for users and groups. The **maximouiweb**, **maxrestweb**, **meaweb**, and **mboweb** **web.xml** files are updated during this action.

```
-action disableAppSecurity [-buildAndDeployEar] [-force]
```

action updateApplication

The **updateApplication** action is used to update the application by updating the database and redeploying application EAR files. This action should not be used in an upgrade scenario or when a new product is installed in an existing product.

```
-action updateApplication [-updatedb] [-deploymaximoear]
[-enableSkin Classic|tivoli09|tivoli13] [-enableEnhancedNavigation]
[-enableRestrictivePasswordPolicy]
```

action addLanguages

Use the **addLanguages** action to configure additional languages for a deployment.

```
-action addLanguages [-additionalLangs locale1,locale2,locale3]
[-buildAndDeployEAR] [-allowUpdateDB | -bypassUpdatedDB] [-stopAppServer]
[-inputfile path to input properties file]
```

The application server must be stopped when you add languages. If you do not use the **stopAppServer** parameter with the **addLanguages** action, you must stop the application server manually before you use the **addLanguages** action.

The following locale values are supported.

Table 3. Locales supported by the configuration program

Language	Locale
Arabic	ar
Brazilian Portuguese	pt_BR
Croatian	hr
Czech	cs
Danish	da
Dutch	nl
Finnish	fi
French	fr
German	de

Table 3. Locales supported by the configuration program (continued)

Language	Locale
Hebrew	he
Hungarian	hu
Italian	it
Japanese	ja
Korean	ko
Norwegian	no
Polish	pl
Russian	ru
Simplified Chinese	zh_CN
Slovak	sk
Slovenian	sl
Spanish	es
Swedish	sv
Traditional Chinese	zh_TW
Turkish	tr

action configureProducts

The **configureProducts** action should be used to configure more products that are installed after an initial installation and configuration. This action verifies a full installation and configuration of an existing product was completed successfully before it continues. This action can configure multiple products after they are installed. This action should be used in an upgrade scenario.

```
-action configureProducts [-updatedb] [-buildears] [-deploymaximoear]
```

action deployMiddlewareConfiguration

The **deployMiddlewareConfiguration** action is used to configures middleware after it is installed.

```
-action deployMiddlewareConfiguration [-inputfile path to input properties file]
```

The following properties can be included in the input properties file used with the **deployMiddlewareConfiguration** action.

Table 4. Properties that can be used in the *deployMiddlewareConfiguration* action input file

Category	Property
HTTP Server properties	IHS.HTTPPort
	IHS.InstallLocation
	IHS.WebserverName
LDAP server properties	LDAP.AdminDN
	LDAP.AdminPassword
	LDAP.BaseEntry
	LDAP.GroupSuffix
	LDAP.OrgContainerSuffix
	LDAP.ServerHostName

Table 4. Properties that can be used in the `deployMiddlewareConfiguration` action input file (continued)

Category	Property
	LDAP.ServerPort
	LDAP.UserSuffix
	LDAP.Vendor
General middleware configuration properties	MW.Operation
WebSphere properties	PLG.InstallLocation
	WAS.AdminPassword
	WAS.AdminUserName
	WAS.ApplicationServerName
	WAS.CellName
	WAS.DeploymentManagerNodeName
\	WAS.DeploymentManagerProfileName
	WAS.InstallLocation
	WAS.LDAPAutomatedConfig
	WAS.ND.AutomateConfig
	WAS.NodeName
	WAS.ServerProfileName
	WAS.SOAPConnectorPort
	WCT.InstallLocation

action upgrade75Configuration

The **upgrade75Configuration** action performs database properties validation for your Maximo Asset Management 7.5 deployment to ensure a valid connection to the database, and also configures WebSphere Application Server for Maximo Asset Management 7.6. When you upgrade from Maximo Asset Management 7.5, you must configure a new instance of WebSphere Application Server.

```
-action upgrade75Configuration [-inputfile path to input properties file]
[-dbvendor <Oracle|DB2|SQLServer>] [-j2eevendor <WebSphere|WebLogic>]
[-automatej2eeconfig] [-usermanagement <j2ee|mixed>]
[-enableappsecurity] [-bypassJ2eeValidation]
```

action updateApplicationDBLite

The **updateApplicationDBLite** action is used to update the database using the DB Lite feature and then rebuild and redeploy the EARs. This action should not be used in an upgrade scenario or when a new product is installed in an existing product.

```
-action updateApplicationDBLite [-preprocessor] [-updatedb]
[-buildears] [-deploymaximoeear] [-enableSkin tivoli09|tivoli13|classic]
[-enableEnhancedNavigation] [-disableEnhancedNavigation]
[-enableRestrictivePasswordPolicy]
```

The `-preprocessor` attribute can be used to prepare class files before they are built into the application EAR files. The non-lite version of the `updatedb` command can also perform this work, however, it requires that you stop the application server. If

you use the `-preprocessor` attribute, you are not required to stop the application server while class files are prepared, decreasing the amount of downtime for your environment.

The `-updatedb` attribute can be used to update the database independently. When you use this attribute, the application server must be stopped. The `updatedb` process does not include preparing class files, which shortens the amount of time that your application server is down.

The `-preprocessor` and `-updatedb` attributes are mutually exclusive. You cannot use them together. The `-buildears` attribute can only be used with the `-preprocessor` attribute. The `-deploymaximoear` attribute can only be used in conjunction with the `-updatedb` attribute.

action `configureProductsDBLite`

The `configureProductsDBLite` action should be used to configure products after an initial installation and configuration using the DB Lite feature. This action can configure multiple products after they are installed and should be used in an upgrade scenario.

```
-action configureProductsDBLite [-preprocessor] [-updatedb]
[-buildears] [-deploymaximoear]
```

The `-preprocessor` attribute can be used to prepare class files before they are built into the application EAR files. The non-lite version of the `updatedb` command can also perform this work, however, it requires that you stop the application server. If you use the `-preprocessor` attribute, you are not required to stop the application server while class files are prepared, decreasing the amount of downtime for your environment.

The `-updatedb` attribute can be used to update the database independently. When you use this attribute, the application server must be stopped. The `updatedb` process does not include preparing class files, which shortens the amount of time that your application server is down.

The `-preprocessor` and `-updatedb` attributes are mutually exclusive. You cannot use them together. The `-buildears` attribute can only be used with the `-preprocessor` attribute. The `-deploymaximoear` attribute can only be used in conjunction with the `-updatedb` attribute.

Configuration program properties

Maximo Asset Management properties can be modified with the command line configuration program by using an `input.properties` file. When you set a property value to a Windows path, you must use two consecutive backslashes, for example, `C:\\IBM\\WebSphere\\AppServer`. When you set property values to a Linux or UNIX path, use single forward slashes. For example, `/opt/IBM/db2/V10.5`.

Table 5. Maximo Asset Management properties

Category	Property	Definition
Shared database properties	<code>mxe.db.schemaowner</code>	Owner of the database schema. For example, <code>maximo</code> . This value is written to the database when updated.

Table 5. Maximo Asset Management properties (continued)

Category	Property	Definition
	mxe.db.user	User ID that accesses the database.
	mxe.db.password	Password for the user ID that accesses the database.
	Database.RemoteAccessUserName	Database server system user ID that is used for configure the database remotely. This property is only required if the createResourcesIfMissing , validatefornewdeploy , or automatedbconfig parameters are specified.
	Database.RemoteAccessPassword	Password for user ID named in Database.RemoteAccessUserName . This property is only required if the createResourcesIfMissing , validatefornewdeploy , or automatedbconfig parameters are specified.
Db2 Properties	Database.DB2.ServerHostName	Fully qualified host name of the Db2 server. For example, mymachine.mydomain.com. This value is written to the database when updated.
	Database.DB2.ServerPort	Database server port. For example, 50005. This value is written to the database when updated.
	Database.DB2.InstanceName	Name of the database instance. For example, ctginst1. This value is written to the database when updated. This property is only required if the createResourcesIfMissing , validatefornewdeploy , or automatedbconfig parameters are specified.
	Database.DB2.InstanceUserPassword	Password for the database instance owner This property is only required if the createResourcesIfMissing , validatefornewdeploy , or automatedbconfig parameters are specified.

Table 5. Maximo Asset Management properties (continued)

Category	Property	Definition
	Database.DB2.InstanceAdminGroup	<p>Group for the instance administrator.</p> <p>For example, ctgiadm1.</p> <p>This property is only required if the createResourcesIfMissing, validatefornewdeploy, or automatedbconfig parameters are specified.</p>
	Database.DB2.DatabaseName	<p>Name of the database.</p> <p>For example, maxdb76.</p> <p>This value is written to the database when updated.</p>
	Database.DB2.InstallLocation	<p>Install location of the database.</p> <p>For example, /opt/IBM/db2/V10.5.</p> <p>This property is only required if the createResourcesIfMissing, validatefornewdeploy, or automatedbconfig parameters are specified.</p>
	Database.DB2.LogFileSize	<p>Set the size for transaction logs.</p> <p>For example, 8192.</p> <p>This property is only required if the createResourcesIfMissing, validatefornewdeploy, or automatedbconfig parameters are specified.</p>
	Database.DB2.AppCtlHeapSize	<p>Application control heap size.</p> <p>For example, 1024.</p> <p>This property is only required if the createResourcesIfMissing, validatefornewdeploy, or automatedbconfig parameters are specified.</p>
	Database.DB2.ApplHeapSize	<p>Application heap size.</p> <p>For example, 1024.</p> <p>This property is only required if the createResourcesIfMissing, validatefornewdeploy, or automatedbconfig parameters are specified.</p>

Table 5. Maximo Asset Management properties (continued)

Category	Property	Definition
	Database.DB2.LockListSize	<p>Size that is allocated to the lock list.</p> <p>For example, AUTOMATIC.</p> <p>This property is only required if the createResourcesIfMissing, validatefornewdeploy, or automatedbconfig parameters are specified.</p>
	Database.DB2.LogSecond	<p>Number of secondary log files allowed.</p> <p>For example, 100.</p> <p>This property is only required if the createResourcesIfMissing, validatefornewdeploy, or automatedbconfig parameters are specified.</p>
	Database.DB2.ServiceUser	<p>User ID used to autostart.</p> <p>This property is only required if the createResourcesIfMissing, validatefornewdeploy, or automatedbconfig parameters are specified.</p> <p>This property is only required if Db2 is installed on a Windows system.</p>
	Database.DB2.ServicePassword	<p>Password for Database.DB2.ServiceUser.</p> <p>This property is only required if the createResourcesIfMissing, validatefornewdeploy, or automatedbconfig parameters are specified.</p> <p>This property is only required if Db2 is installed on a Windows system.</p>
	Database.DB2.ExtentSize	<p>Number of pages per extent (group of pages).</p> <p>For example, 32.</p> <p>This property is only required if the createResourcesIfMissing, validatefornewdeploy, or automatedbconfig parameters are specified.</p>

Table 5. Maximo Asset Management properties (continued)

Category	Property	Definition
	Database.DB2.FencedUser	<p>Fenced user ID for Db2 on Linux or UNIX systems.</p> <p>For example, db2fenc1.</p> <p>This property is only required if the createResourcesIfMissing, validatefornewdeploy, or automatedbconfig parameters are specified.</p>
	Database.DB2.FencedUserPassword	<p>Password for the fenced user ID for Db2 on Linux or UNIX systems.</p> <p>This property is only required if the createResourcesIfMissing, validatefornewdeploy, or automatedbconfig parameters are specified.</p>
	Database.DB2.FencedGroupName	<p>Default group for database fenced user.</p> <p>For example, ctgfgrp1.</p> <p>This property is only required if the createResourcesIfMissing, validatefornewdeploy, or automatedbconfig parameters are specified.</p> <p>This property is only required if Db2 is installed on a Linux or UNIX system.</p>
	Database.DB2.AuthType	<p>Method Db2 uses to authenticate users.</p> <p>For example, server.</p> <p>This property is only required if the createResourcesIfMissing, validatefornewdeploy, or automatedbconfig parameters are specified.</p>
	Database.DB2.DataTablespaceName	<p>Db2 table space name for the product database.</p> <p>For example, maxdata.</p>
	Database.DB2.BufferPoolName	<p>Db2 buffer pool name.</p> <p>For example, MAXBUFPOOL.</p> <p>This property is only required if the createResourcesIfMissing, validatefornewdeploy, or automatedbconfig parameters are specified.</p>

Table 5. Maximo Asset Management properties (continued)

Category	Property	Definition
	Database.DB2.BufferPoolSize	<p>Size of the buffer pool.</p> <p>For example, 4096.</p> <p>This property is only required if the createResourcesIfMissing, validatefornewdeploy, or automatedbconfig parameters are specified.</p>
	Database.DB2.DataTablespaceLocation	<p>Location of Db2 database table space data files.</p> <p>For example, CTGDAT.</p> <p>This property is only required if the createResourcesIfMissing, validatefornewdeploy, or automatedbconfig parameters are specified.</p>
	Database.DB2.DataTablespaceSize	<p>Table space size, which is measured in Mb.</p> <p>For example, 5000.</p> <p>This property is only required if the createResourcesIfMissing, validatefornewdeploy, or automatedbconfig parameters are specified.</p>
	Database.DB2.TempTablespaceName	<p>Temporary table space name.</p> <p>For example, maxtemp.</p> <p>This property is only required if the createResourcesIfMissing, validatefornewdeploy, or automatedbconfig parameters are specified.</p>
	Database.DB2.TempTablespaceLocation	<p>Location of temporary table space.</p> <p>For example, CTGTMP.</p> <p>This property is only required if the createResourcesIfMissing, validatefornewdeploy, or automatedbconfig parameters are specified.</p>
	Database.DB2.TempTablespaceSize	<p>Temporary table space size, which is measured in Mb.</p> <p>For example, 1000.</p> <p>This property is only required if the createResourcesIfMissing, validatefornewdeploy, or automatedbconfig parameters are specified.</p>

Table 5. Maximo Asset Management properties (continued)

Category	Property	Definition
	Database.DB2.IndexTablespaceName	Index table space name. For example, maxdata.
	Database.DB2.IndexTablespaceLocation	Location of index table space. For example, CTGDAT. This property is only required if the createResourcesIfMissing , validatefornewdeploy , or automatedbconfig parameters are specified.
	Database.DB2.IndexTablespaceSize	Index table space size, which is measured in Mb. For example, 5000. This property is only required if the createResourcesIfMissing , validatefornewdeploy , or automatedbconfig parameters are specified.
	Database.DB2.InstanceAdminUserName	Administrative user or the database instance. For example, db2admin. This property is only required if the createResourcesIfMissing , validatefornewdeploy , or automatedbconfig parameters are specified. For Unix and Linux platforms, this value must be the same as the instance owner.
	Database.DB2.InstanceAdminPassword	Password for the user ID specified for Database.DB2.InstanceAdminUserName . This property is only required if the createResourcesIfMissing , validatefornewdeploy , or automatedbconfig parameters are specified. createResourcesIfMissing
Oracle	Database.Oracle.SchemaPassword	Password for the schema owner.
	Database.Oracle.InstanceName	Oracle instance name. This value is written to the database when updated.

Table 5. Maximo Asset Management properties (continued)

Category	Property	Definition
	Database.Oracle.SoftwareOwner	<p>Owner of the software installation.</p> <p>For example, oracle.</p> <p>This property is only required if the createResourcesIfMissing, validatefornewdeploy, or automatedbconfig parameters are specified.</p>
	Database.Oracle.SoftwareOwnerPassword	<p>Password for the user ID listed in Database.Oracle.SoftwareOwner.</p> <p>This property is only required if the createResourcesIfMissing, validatefornewdeploy, or automatedbconfig parameters are specified.</p>
	Database.Oracle.InstallLocation	<p>Oracle installation location. For example, /opt/app/oracle/product/10.2.0/db_1.</p> <p>This property is only required if the createResourcesIfMissing, validatefornewdeploy, or automatedbconfig parameters are specified.</p>
	Database.Oracle.DataTablespaceName	<p>Oracle table space name for the product database.</p> <p>For example, maxdata.</p>
	Database.Oracle.InstanceLocation	<p>Oracle instance location.</p> <p>For example, /opt/app/oracle/product/10.2.0/db_1.</p> <p>This property is only required if the createResourcesIfMissing, validatefornewdeploy, or automatedbconfig parameters are specified.</p>
	Database.Oracle.DataTablespaceSize	<p>Table space size, which is measured in Mb.</p> <p>For example, 5000.</p> <p>This property is only required if the createResourcesIfMissing, validatefornewdeploy, or automatedbconfig parameters are specified.</p>

Table 5. Maximo Asset Management properties (continued)

Category	Property	Definition
	Database.Oracle.TempTablespaceName	<p>Temporary table space name.</p> <p>For example, maxtemp.</p> <p>This property is only required if the createResourcesIfMissing, validatefornewdeploy, or automatedbconfig parameters are specified.</p>
	Database.Oracle.TempTablespaceSize	<p>Temporary table space size, which is measured in Mb.</p> <p>For example, 1000.</p> <p>This property is only required if the createResourcesIfMissing, validatefornewdeploy, or automatedbconfig parameters are specified.</p>
	Database.Oracle.IndexTablespaceName	<p>Index table space name.</p> <p>For example, maxdata.</p>
	Database.Oracle.IndexTablespaceSize	<p>Index table space size, which is measured in Mb.</p> <p>For example, 1000.</p> <p>This property is only required if the createResourcesIfMissing, validatefornewdeploy, or automatedbconfig parameters are specified.</p>
	Database.Oracle.ServerHostName	Fully qualified host name of the Oracle server.
	Database.Oracle.ServerPort	<p>Port number that is used by Oracle.</p> <p>For example, 1521.</p> <p>This value is written to the database when updated.</p>
	Database.DBUserName	<p>Oracle DBA user name.</p> <p>For example, sys.</p> <p>This property is only required if the createResourcesIfMissing, validatefornewdeploy, or automatedbconfig parameters are specified.</p>
	Database.DBAPassword	<p>Password for user ID listed for Database.DBUserName.</p> <p>This property is only required if the createResourcesIfMissing, validatefornewdeploy, or automatedbconfig parameters are specified.</p>

Table 5. Maximo Asset Management properties (continued)

Category	Property	Definition
Microsoft SQL Server	Database.SQL.DatabaseName	Name of the database. For example, maxdb76. This value is written to the database when updated.
	Database.SQL.DataFileName	A way to specify the name of the data file used for the database. For example, maxdb76_dat. This property is only required if the createResourcesIfMissing , validatefornewdeploy , or automatedbconfig parameters are specified.
	Database.SQL.DataFileMaxSize	Maximum size for data file for the database.
	Database.SQL.DataFileSize	Initial size for data file for the database in kb. For example, 5000. This property is only required if the createResourcesIfMissing , validatefornewdeploy , or automatedbconfig parameters are specified.
	Database.SQL.LogFileName	A way to specify the name for the database transaction log file. For example, maxdb76_log. This property is only required if the createResourcesIfMissing , validatefornewdeploy , or automatedbconfig parameters are specified.
	Database.SQL.LogFileSize	Microsoft SQL Server transaction log file size. This property is only required if the createResourcesIfMissing , validatefornewdeploy , or automatedbconfig parameters are specified.
	Database.SQL.DataFilegroupName	Database logical name file group. For example, PRIMARY. This property is only required if the createResourcesIfMissing , validatefornewdeploy , or automatedbconfig parameters are specified.

Table 5. Maximo Asset Management properties (continued)

Category	Property	Definition
	Database.SQL.ServerHostName	Host name of the database server. For example, myhost.mydomain.com.
	Database.SQL.ServerPort	Database server port. For example, 1433. This value is written to the database when updated.
	Database.SQL.InstanceAdminUserName	Administrative user for the Microsoft SQL Server instance. Used during installation for creating and modifying the database and database user. For example, sa. This property is only required if the createResourcesIfMissing , validatefornewdeploy , or automatedbconfig parameters are specified.
	Database.SQL.InstanceAdminPassword	Administrative user password. This property is only required if the createResourcesIfMissing , validatefornewdeploy , or automatedbconfig parameters are specified.
WebSphere Application Server Network Deployment	WAS.InstallLocation	Installation location for WebSphere Application Server Network Deployment. For example, C:\IBM\WebSphere\AppServer. This property is required if the WAS.SibPersistMessages property is set to true. This property is required in the properties file that is specified in one of the following properties. <ul style="list-style-type: none"> • WAS.MIFSIBPropertiesFile • WAS.CronSIBPropertiesFile • WAS.UISIBPropertiesFile
	WAS.DeploymentManagerHostName	Host name of the WebSphere Application Server Network Deployment deployment manager. This value is written to the database when updated.

Table 5. Maximo Asset Management properties (continued)

Category	Property	Definition
	WAS.DeploymentManagerProfileName	<p>WebSphere Application Server Network Deployment profile name.</p> <p>For example, ctgDmgr01.</p> <p>This property is required if the WAS.SibPersistMessages property is set to true.</p> <p>This property is required in the properties file that is specified in one of the following properties.</p> <ul style="list-style-type: none"> • WAS.MIFSIBPropertiesFile • WAS.CronSIBPropertiesFile • WAS.UISIBPropertiesFile
	WAS.DeploymentManagerProfileRoot	<p>Location of the WebSphere Application Server Network Deployment profile.</p> <p>For example, C:\IBM\WebSphere\AppServer\profiles\ctgDmgr01</p> <p>This property is only required if the WAS.SibPersistMessages property is set to true.</p> <p>This property is required in the properties file that is specified in one of the following properties.</p> <ul style="list-style-type: none"> • WAS.MIFSIBPropertiesFile • WAS.CronSIBPropertiesFile • WAS.UISIBPropertiesFile
	WAS.NodeName	<p>WebSphere Application Server Network Deployment node name.</p> <p>For example, ctgNode01</p>
	WAS.ApplicationServerName	<p>WebSphere Application Server Network Deployment application server name.</p> <p>For example, MXServer.</p> <p>This value is written to the database when updated.</p>
	WAS.CellName	<p>WebSphere Application Server Network Deployment cell name.</p> <p>For example, ctgCell01.</p>
	WAS.AdminUserName	<p>WebSphere Application Server Network Deployment administrator name.</p> <p>For example, wasadmin.</p>

Table 5. Maximo Asset Management properties (continued)

Category	Property	Definition
	WAS.AdminPassword	WebSphere Application Server Network Deployment administrator password.
	WAS.RemoteAccessUserName	<p>WebSphere Application Server Network Deployment deployment manager system user ID used for tasks such as copying Integrated Solutions Console web archive files and fetching the keystore.</p> <p>This property is required if the WAS.SibPersistMessages property is set to true.</p> <p>This property is required in the properties file that is specified in one of the following properties.</p> <ul style="list-style-type: none"> • WAS.MIFSIBPropertiesFile • WAS.CronSIBPropertiesFile • WAS.UISIBPropertiesFile
	WAS.RemoteAccessPassword	<p>WebSphere Application Server Network Deployment deployment manager system user password.</p> <p>This property is required if the WAS.SibPersistMessages property is set to true.</p> <p>This property is required in the properties file that is specified in one of the following properties.</p> <ul style="list-style-type: none"> • WAS.MIFSIBPropertiesFile • WAS.CronSIBPropertiesFile • WAS.UISIBPropertiesFile
	WAS.SOAPConnectorPort	<p>SOAP port for WebSphere Application Server Network Deployment deployment manager.</p> <p>For example, 8879.</p>
	WAS.VirtualHost	<p>Name of the WebSphere Application Server Network Deployment virtual host.</p> <p>For example, maximo_host.</p>
	WAS.WebServerHostName	Host name where the HTTP server is located.
	WAS.SibName	<p>Name of the service integration bus.</p> <p>For example, intjmsbus.</p>

Table 5. Maximo Asset Management properties (continued)

Category	Property	Definition
	WAS.SibHiMsg	<p>Service integration bus high message count.</p> <p>For example, 500000.</p> <p>This property is only required if the createResourcesIfMissing, validatefornewdeploy, or automatej2eeconfig parameters are specified.</p> <p>This property is required in the properties file that is specified in one of the following properties.</p> <ul style="list-style-type: none"> • WAS.MIFSIBPropertiesFile • WAS.CronSIBPropertiesFile • WAS.UISIBPropertiesFile
	WAS.WebServerName	<p>Name of the WebSphere Application Server Network Deployment web server. Used to manage HTTP server from within WebSphere Application Server Network Deployment.</p> <p>For example, webserver1.</p>
	WAS.SibPersistMessages	<p>Binary value that indicates if service integration bus messages are persisted in either the product database or a local derby database.</p> <p>A value of true indicates that the messages are persisted.</p> <p>This property is only required if the createResourcesIfMissing, validatefornewdeploy, or automatej2eeconfig parameters are specified.</p> <p>This property is required in the properties file that is specified in one of the following properties.</p> <ul style="list-style-type: none"> • WAS.MIFSIBPropertiesFile • WAS.CronSIBPropertiesFile • WAS.UISIBPropertiesFile

Table 5. Maximo Asset Management properties (continued)

Category	Property	Definition
	WAS.SibDSName	<p>Service integration bus data source name that is created to access the service integration bus persistence store.</p> <p>For example, intjmsds.</p> <p>This property is only required if the WAS.SibPersistMessages property is set to true.</p> <p>This property is required in the properties file that is specified in one of the following properties.</p> <ul style="list-style-type: none"> • WAS.MIFSIBPropertiesFile • WAS.CronSIBPropertiesFile • WAS.UISIBPropertiesFile
	WAS.SibDBName	<p>Name of the service integration bus messages database.</p> <p>This property is required in the properties file that is specified in one of the following properties.</p> <ul style="list-style-type: none"> • WAS.MIFSIBPropertiesFile • WAS.CronSIBPropertiesFile • WAS.UISIBPropertiesFile
	WAS.SibDBInstance	<p>Instance name of the service integration bus database.</p> <p>This property is required if the WAS.SibPersistMessages property is set to true.</p> <p>This property is required in the properties file that is specified in one of the following properties.</p> <ul style="list-style-type: none"> • WAS.MIFSIBPropertiesFile • WAS.CronSIBPropertiesFile • WAS.UISIBPropertiesFile
	WAS.SibDBInstancePassword	<p>IBM Db2 instance users password for the SIB IBM Db2 data store.</p> <p>This property is required if the WAS.SibPersistMessages property is set to true.</p> <p>This property is required in the properties file that is specified in one of the following properties.</p> <ul style="list-style-type: none"> • WAS.MIFSIBPropertiesFile • WAS.CronSIBPropertiesFile • WAS.UISIBPropertiesFile

Table 5. Maximo Asset Management properties (continued)

Category	Property	Definition
	WAS.SibDBServerName	<p>Server name of the system that is hosting the service integration bus message database.</p> <p>This property is required if the WAS.SibPersistMessages property is set to true.</p> <p>This property is required in the properties file that is specified in one of the following properties.</p> <ul style="list-style-type: none"> • WAS.MIFSIBPropertiesFile • WAS.CronSIBPropertiesFile • WAS.UISIBPropertiesFile
	WAS.SibDBServerPort	<p>Database server port for the database that contains the service integration bus messages.</p> <p>For example, 50005.</p> <p>This property is required if the WAS.SibPersistMessages property is set to true.</p> <p>This property is required in the properties file that is specified in one of the following properties.</p> <ul style="list-style-type: none"> • WAS.MIFSIBPropertiesFile • WAS.CronSIBPropertiesFile • WAS.UISIBPropertiesFile
	WAS.SibDBUserName	<p>User ID used to access the persistence data store database for service integration bus messages.</p> <p>This property is required if the WAS.SibPersistMessages property is set to true.</p> <p>This property is required in the properties file that is specified in one of the following properties.</p> <ul style="list-style-type: none"> • WAS.MIFSIBPropertiesFile • WAS.CronSIBPropertiesFile • WAS.UISIBPropertiesFile

Table 5. Maximo Asset Management properties (continued)

Category	Property	Definition
	WAS.SibDBUserPass	<p>Password for user ID named in WAS.SibDBUserName.</p> <p>This property is only required if the WAS.SibPersistMessages property is set to true.</p> <p>This property is required in the properties file that is specified in one of the following properties.</p> <ul style="list-style-type: none"> • WAS.MIFSIBPropertiesFile • WAS.CronSIBPropertiesFile • WAS.UISIBPropertiesFile
	WAS.SibDBInstallDir	<p>Where the service integration bus database is installed.</p> <p>For example, c:\program files\ibm\sqllib.</p> <p>This property is required if the WAS.SibPersistMessages property is set to true.</p> <p>This property is required in the properties file that is specified in one of the following properties.</p> <ul style="list-style-type: none"> • WAS.MIFSIBPropertiesFile • WAS.CronSIBPropertiesFile • WAS.UISIBPropertiesFile
	WAS.SibDbFencedUser	<p>Fenced user ID for the service integration bus database. This property is only used for databases that are hosted on Linux and UNIX systems.</p> <p>For example, db2fenc1.</p> <p>This property is required if the WAS.SibPersistMessages property is set to true.</p> <p>This property is required if the database is hosted on a Linux or UNIX system.</p> <p>This property is required in the properties file that is specified in one of the following properties.</p> <ul style="list-style-type: none"> • WAS.MIFSIBPropertiesFile • WAS.CronSIBPropertiesFile • WAS.UISIBPropertiesFile

Table 5. Maximo Asset Management properties (continued)

Category	Property	Definition
	WAS.SibDbFencedPassword	<p>Password for the fenced user ID for the service integration bus database.</p> <p>This property is required if the WAS.SibPersistMessages property is set to true.</p> <p>This property is required if the database is hosted on a Linux or UNIX system.</p> <p>This property is required in the properties file that is specified in one of the following properties.</p> <ul style="list-style-type: none"> • WAS.MIFSIBPropertiesFile • WAS.CronSIBPropertiesFile • WAS.UISIBPropertiesFile
	WAS.SibDbInstanceAdminUser	<p>Instance owner for the service integration bus database.</p> <p>This property is required if the WAS.SibPersistMessages property is set to true.</p> <p>This property is required if the database is hosted on a Windows system.</p> <p>This property is required in the properties file that is specified in one of the following properties.</p> <ul style="list-style-type: none"> • WAS.MIFSIBPropertiesFile • WAS.CronSIBPropertiesFile • WAS.UISIBPropertiesFile
	WAS.SibDbInstanceAdminPassword	<p>Password for the instance owner of the service integration bus database.</p> <p>This property is required if the WAS.SibPersistMessages property is set to true.</p> <p>This property is required if the database is hosted on a Windows system.</p> <p>This property is required in the properties file that is specified in one of the following properties.</p> <ul style="list-style-type: none"> • WAS.MIFSIBPropertiesFile • WAS.CronSIBPropertiesFile • WAS.UISIBPropertiesFile

Table 5. Maximo Asset Management properties (continued)

Category	Property	Definition
	WAS.SibDbRemoteAccessUser	<p>Database server system user that is used to configure the service integration bus remotely.</p> <p>This property is required if the WAS.SibPersistMessages property is set to true.</p> <p>This property is required in the properties file that is specified in one of the following properties.</p> <ul style="list-style-type: none"> • WAS.MIFSIBPropertiesFile • WAS.CronSIBPropertiesFile • WAS.UISIBPropertiesFile
	WAS.SibDbRemoteAccessPassword	<p>Password for user ID named in WAS.SibDbRemoteAccessUser.</p> <p>This property is required if the WAS.SibPersistMessages property is set to true.</p> <p>This property is required in the properties file that is specified in one of the following properties.</p> <ul style="list-style-type: none"> • WAS.MIFSIBPropertiesFile • WAS.CronSIBPropertiesFile • WAS.UISIBPropertiesFile
	WAS.VmmGroupRDN	<p>Relative Distinguished Name of the location of virtual member manager groups.</p> <p>For example, ou=groups,ou=SWG,o=IBM,c=US.</p>
	WAS.VmmUserRDN	<p>Relative Distinguished Name of the location of virtual member manager users.</p> <p>For example, ou=users,ou=SWG,o=IBM,c=US.</p>
	WAS.UseClustersForDeploy	<p>Deploy the application EAR to a cluster.</p> <p>For example, true.</p>
	WAS.UIClusterName	<p>Name of the cluster that manages UI tasks.</p> <p>Set a value for this parameter if WAS.UseClustersForDeploy is set to true.</p>

Table 5. Maximo Asset Management properties (continued)

Category	Property	Definition
	WAS.WAS.UIEnableJMS	<p>Enable or disable JMS for Maximo Enterprise Adapter for the UI cluster.</p> <p>For example, true.</p> <p>Set a value for this parameter if WAS.UseClustersForDeploy is set to true.</p>
	WAS.UISIBPropertiesFile	<p>File that contains SIB persistence properties if you are persisting messages in the UI clusters bus.</p> <p>For example, c:\sibdb_ui.properties.</p> <p>Set a value for this parameter if WAS.UseClustersForDeploy is set to true.</p>
	WAS.CronClusterName	<p>Name of the cluster that manages cron tasks.</p> <p>For example, maximocron.</p> <p>Set a value for this parameter if WAS.UseClustersForDeploy is set to true.</p>
	WAS.CronEnableJMS	<p>Enable JMS for Maximo Enterprise Adapter for the cron task cluster.</p> <p>For example, true.</p> <p>Set a value for this parameter if WAS.UseClustersForDeploy is set to true.</p>
	WAS.CronSIBPropertiesFile	<p>File that contains SIB persistence properties if you are persisting messages in the cron clusters bus.</p> <p>For example, c:\sibdb_cr.properties.</p> <p>Set a value for this parameter if WAS.UseClustersForDeploy is set to true.</p>
	WAS.ReportingClusterName	<p>Name of the cluster that manages reporting tasks.</p> <p>For example, maximorpt.</p> <p>Set a value for this parameter if WAS.UseClustersForDeploy is set to true.</p>

Table 5. Maximo Asset Management properties (continued)

Category	Property	Definition
	WAS.MIFClusterName	Name of the cluster that manages Maximo Integration Framework tasks. For example, maximomea. Set a value for this parameter if WAS.UseClustersForDeploy is set to true.
	WAS.MIFEnableJMS	Enable JMS for Maximo Enterprise Adapter for the Maximo Integration Framework task cluster. For example, true. Set a value for this parameter if WAS.UseClustersForDeploy is set to true.
	WAS.MIFSIBPropertiesFile	File that contains SIB persistence properties if you are persisting messages in the Maximo Integration Framework clusters bus. For example, c:\sibdb_mif.properties. Set a value for this parameter if WAS.UseClustersForDeploy is set to true.
Multi-tenancy	mt.sysprovider.tenantcode	Tenant code identifier for the multi-tenancy system provider. For example, MTM. This property is required to enable multi-tenancy.
	mt.sysprovider.desc	Description of the multi-tenancy manager.
	mt.configmanager.adminuserid	User ID of the multi-tenancy configuration manager. For example, maxadmin. This property is required to enable multi-tenancy. This value can be the same value used for the mtadminuser user.
	mt.configmanager.adminpassword	Password for the User ID of the multi-tenancy configuration manager. This property is required to enable multi-tenancy. This value can be the same value used for the mtadminpwd value.

Table 5. Maximo Asset Management properties (continued)

Category	Property	Definition
	mt.configmanager.tenantcode	<p>Tenant code identifier for the multi-tenancy configuration manager.</p> <p>For example, GA.</p> <p>This is property is required to enable multi-tenancy.</p>
	mt.configmanager.desc	<p>Description of the multi-tenancy global administrator.</p>
	mt.configmanager.dbuser	<p>User ID of the multi-tenancy configuration manager used to connect to the database.</p> <p>For example, ADMIN.</p> <p>This property is required to enable multi-tenancy.</p> <p>This value can be the same value used for the mtddbuser user.</p>
	mt.configmanager.dbpassword	<p>Password for the user ID of the multi-tenancy configuration manager that is used to connect to the database.</p> <p>This property is required to enable multi-tenancy.</p> <p>This value can be the same value used for the mtddbpwd value.</p>
	mxe.mt.enabled	<p>Value that indicates whether multi-tenancy is enabled.</p> <p>For example, a value of 1 indicates that multi-tenancy is enabled. A value of 0 indicates that multi-tenancy is not enabled for the product.</p>
	mxe.mt.db.adminuser	<p>THIS PROPERTY IS NO LONGER USED.</p>
	mxe.mt.db.adminrole	<p>Admin role that has permission to access template data when tenants are initially provisioned. The default value is MXTMPLT. However, users can create a different role and specify that value for the property.</p>
	mxe.mt.demo.extratnants	<p>Number of sample tenants to create when you enable multi-tenancy.</p> <p>For example, 10.</p> <p>This property is set in the <code>maximo.properties</code> file during the maxinst operation.</p>

Chapter 8. Backup and restoration

Like all important business data, it is a good idea to establish a process and schedule for backing up Maximo Asset Management data.

Back up and restore middleware application data using the methods described in the documentation for that product is important. Also, establish a process for backing up data contained on the Maximo Asset Management administrative workstation.

The default installation directory on the Maximo Asset Management administrative workstation is C:\ibm. This directory contains the critical files for your Maximo Asset Management deployment, which includes all class files and customizations that have been performed in your environment, the current Enterprise Archive (EAR) file, and the properties files and installation tools used for your environment. Plan to back up Maximo Asset Management administrative workstation data just after initial deployment and schedule periodic backups on an ongoing basis.

Backing up the administrative workstation

It is recommended that you back up all Maximo Asset Management middleware applications and Maximo Asset Management administrative workstation on a regular basis.

About this task

The default installation directory on the administrative workstation is \ibm. This directory contains the critical files for your Maximo Asset Management deployment.

Specifically, the administrative workstation contains the following items:

- Class files and customizations performed in your environment.
- The current Enterprise Archive (EAR) file.
- The properties files and installation tools used for your environment.

It is important to make a back up of the database at the same time that you back up the administrative workstation. During restoration, you restore the database back up at the same time you restore the administrative workstation back up it was paired with.

To back up critical Maximo Asset Management information, complete the following steps:

Procedure

1. Back up the Maximo Asset Management database, J2EE server, and authentication server information using the instructions provided by your middleware vendors.
2. Create a backup of the installation directory. By default, this directory is \IBM\SMP. Ensure that all file permissions are preserved.

3. Back up IBM Installation Manager agent data and shared files for recovery with IBM Business Process Manager (BPM). Refer to the IBM Support site for more information (<http://www-01.ibm.com/support/docview.wss?uid=swg21665878>).

Restoring the administrative workstation

This section details how to restore previously backed up Maximo Asset Management administrative workstation information. This information can be used to return an existing Maximo Asset Management administrative workstation to a previous state.

Before you begin

It is important to restore the back up of the database that was made when you backed up the administrative workstation. A database back up should be restored with the administrative workstation back up it was paired with.

About this task

To restore Maximo Asset Management information to an administrative workstation, complete the following steps:

Procedure

1. Restore the database back up that was paired with the administrative workstation back up you are restoring.
2. Log on to the target administrative system with the same user ID that was used to install the product on the existing administrative workstation.
3. Copy the Maximo Asset Management installation files and directories to the file system of the target administrative system. You must maintain the directory structure of the original installation. For example, if the Maximo Asset Management installation directory on the existing administrative system is `\IBM\SMP`, you cannot copy those files to a `\NewAdminWS\IBM\SMP` directory on the target administrative workstation.

Notices

This information was developed for products and services offered in the US. This material might be available from IBM in other languages. However, you may be required to own a copy of the product or product version in that language in order to access it.

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not grant you any license to these patents. You can send license inquiries, in writing, to:

*IBM Director of Licensing
IBM Corporation
North Castle Drive, MD-NC119
Armonk, NY 10504-1785
US*

For license inquiries regarding double-byte character set (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

*Intellectual Property Licensing
Legal and Intellectual Property Law
IBM Japan Ltd.
19-21, Nihonbashi-Hakozakicho, Chuo-ku
Tokyo 103-8510, Japan*

INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM websites are provided for convenience only and do not in any manner serve as an endorsement of those

websites. The materials at those websites are not part of the materials for this IBM product and use of those websites is at your own risk.

IBM may use or distribute any of the information you provide in any way it believes appropriate without incurring any obligation to you.

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

*IBM Director of Licensing
IBM Corporation
North Castle Drive, MD-NC119
Armonk, NY 10504-1785
US*

Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement or any equivalent agreement between us.

The performance data and client examples cited are presented for illustrative purposes only. Actual performance results may vary depending on specific configurations and operating conditions.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

This information is for planning purposes only. The information herein is subject to change before the products described become available.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to actual people or business enterprises is entirely coincidental.

COPYRIGHT LICENSE:

This information contains sample application programs in source language, which illustrate programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to IBM, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating platform for which the sample programs are written. These examples have not been thoroughly tested under all conditions. IBM, therefore, cannot guarantee or imply reliability, serviceability, or function of these programs. The sample

programs are provided "AS IS", without warranty of any kind. IBM shall not be liable for any damages arising out of your use of the sample programs.

Trademarks

IBM, the IBM logo, and ibm.com are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the web at "Copyright and trademark information" at www.ibm.com/legal/copytrade.shtml.

Java and all Java-based trademarks and logos are trademarks or registered trademarks of Oracle and/or its affiliates.

Linux is a trademark of Linus Torvalds in the United States, other countries, or both.

Microsoft, Windows, Windows NT, and the Windows logo are trademarks of Microsoft Corporation in the United States, other countries, or both.

UNIX is a registered trademark of The Open Group in the United States and other countries.

Terms and conditions for product documentation

Permissions for the use of these publications are granted subject to the following terms and conditions.

Applicability

These terms and conditions are in addition to any terms of use for the IBM website.

Personal use

You may reproduce these publications for your personal, noncommercial use provided that all proprietary notices are preserved. You may not distribute, display or make derivative work of these publications, or any portion thereof, without the express consent of IBM.

Commercial use

You may reproduce, distribute and display these publications solely within your enterprise provided that all proprietary notices are preserved. You may not make derivative works of these publications, or reproduce, distribute or display these publications or any portion thereof outside your enterprise, without the express consent of IBM.

Rights

Except as expressly granted in this permission, no other permissions, licenses or rights are granted, either express or implied, to the publications or any information, data, software or other intellectual property contained therein.

IBM reserves the right to withdraw the permissions granted herein whenever, in its discretion, the use of the publications is detrimental to its interest or, as determined by IBM, the above instructions are not being properly followed.

You may not download, export or re-export this information except in full compliance with all applicable laws and regulations, including all United States export laws and regulations.

IBM MAKES NO GUARANTEE ABOUT THE CONTENT OF THESE PUBLICATIONS. THE PUBLICATIONS ARE PROVIDED "AS-IS" AND WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY, NON-INFRINGEMENT, AND FITNESS FOR A PARTICULAR PURPOSE.

IBM Online Privacy Statement

IBM Software products, including software as service solutions, ("Software Offerings") may use cookies or other technologies to collect product usage information, to help improve the end user experience, to tailor interactions with the end user or for other purposes. In many cases no personally identifiable information is collected by the Software Offerings. Some of our Software Offerings can help enable you to collect personally identifiable information. If this Software Offering uses cookies to collect personally identifiable information, specific information about this offering's use of cookies is set forth below.

Depending upon the configurations deployed, this Software Offering may use session and persistent cookies that collect each user's name, user name, password, or other personally identifiable information for purposes of session management, authentication, single sign-on configuration or other usage tracking or functional purposes. These cookies can be disabled, but disabling them will also likely eliminate the functionality they enable.

If the configurations deployed for this Software Offering provide you as customer the ability to collect personally identifiable information from end users via cookies and other technologies, you should seek your own legal advice about any laws applicable to such data collection, including any requirements for notice and consent.

For more information about the use of various technologies, including cookies, for these purposes, see IBM's Privacy Policy at <http://www.ibm.com/privacy> and IBM's Online Privacy Statement at <http://www.ibm.com/privacy/details> in the section entitled "Cookies, Web Beacons and Other Technologies" and the "IBM Software Products and Software-as-a-Service Privacy Statement" at <http://www.ibm.com/software/info/product-privacy>.

Index

A

- action addLanguages 36
- action configureProducts 37
- action configureProductsDBLite 39
- action deployConfiguration 35
- action deployDatabaseConfiguration 33
- action deployJ2eeConfiguration 34
- action
 - deployMiddlewareConfiguration 37
- action disableAppSecurity 36
- action enableAppSecurity 36
- action enableDB2TextSearch 33
- action reapplyAppServerTuning 35
- action removeConfiguration 35
- action removeDatabaseConfiguration 33
- action removeJ2EEConfiguration 35
- action updateApplication 36
- action updateApplicationDBLite 38
- action updateDatabaseConfiguration 32
- action updateJ2eeConfiguration 34
- action upgrade75Configuration 38
- action validate And Update Database Configuration 32
- action validate And Update J2ee Configuration 34
- action validateDatabaseConfiguration 32
- action validateJ2eeConfiguration 34
- administrative workstation
 - backing up 61
 - restoring 62

B

- backup 61

C

- command line configuration program
 - input properties files 24
 - parameters 25
- Command line configuration program actions 32
- configuration 14
- configuration actions
 - addLanguages 36
 - configureProducts 37
 - configureProductsDBLite 39
 - deployConfiguration 35
 - deployDatabaseConfiguration 33
 - deployJ2eeConfiguration 34
 - deployMiddlewareConfiguration 37
 - disableAppSecurity 36
 - enableAppSecurity 36
 - enableDB2TextSearch 33
 - reapplyAppServerTuning 35
 - removeConfiguration 35
 - removeDatabaseConfiguration 33
 - removeJ2EEConfiguration 35
 - updateApplication 36
 - updateApplicationDBLite 38

- configuration actions (*continued*)
 - updateDatabaseConfiguration 32
 - updateJ2eeConfiguration 34
 - upgrade75Configuration 38
 - validate And Update Database Configuration 32
 - validate And Update J2ee Configuration 34
 - validateDatabaseConfiguration 32
 - validateJ2eeConfiguration 34
- configuring Maximo Asset Management
 - command line configuration program 23
 - validate configuration parameters from the command line 24

E

- EAR files
 - building manually 21
 - maintaining 21

I

- installation
 - program logs 7
- Installation
 - post-installation tasks 14
- installation program
 - logs 7

M

- Maximo Asset Management
 - configuring with the Maximo Asset Management configuration program 3
 - installing version 7.6 1

O

- Oracle WebLogic Server
 - manually uninstalling 22

P

- post installation 9
- properties
 - Maximo Asset Management 39

R

- restoration 61

U

- users
 - groups
 - synchronizing 17
 - synchronizing 17

W

- Work Center
 - manually building WAR file 21



Printed in USA