

Print Services Facility for z/OS
Version 4, Release 6.0

Messages and Codes



Note

Before using this information and the product it supports, read the information in [“Notices” on page 781.](#)

This edition applies to the IBM® Print Services Facility™ Version 4 Release 6 Modification 0 for z/OS®, Program Number 5655-M32, and to all subsequent releases and modifications until otherwise indicated in new editions.

This edition replaces G550-0432-04.

© **Copyright International Business Machines Corporation 1983, 2017.**

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Contents

About this publication.....	xlvi
Who should read this publication.....	xlvi
How this publication is organized.....	xlvi
Understanding message and code notation.....	xlvi
Related information.....	xlvi
How to send your comments to IBM.....	xlvii
If you have a technical problem.....	xlvii
Summary of changes.....	xlviii
Chapter 1. PSF for z/OS messages.....	1
Message destinations.....	1
Format of the messages.....	1
Responding to a message.....	3
APS000 to APS099.....	3
APS000I.....	3
APS001I.....	3
APS002A.....	3
APS003A.....	3
APS004I.....	4
APS005I.....	4
APS006I.....	5
APS018I.....	5
APS020I.....	5
APS021I.....	5
APS022I.....	5
APS023I.....	6
APS024I.....	6
APS025I.....	6
APS026I.....	6
APS030I.....	7
APS031I.....	7
APS032I.....	7
APS033I.....	8
APS034I.....	8
APS035I.....	8
APS036I.....	9
APS037I.....	9
APS038I.....	9
APS039I.....	9
APS040I.....	10
APS041I.....	10
APS042I.....	10
APS043I.....	10
APS044I.....	11
APS045I.....	11
APS047I.....	11
APS049I.....	12
APS050I.....	12
APS051I.....	12
APS052I.....	12
APS053I.....	13

APS054I.....	13
APS055I.....	13
APS056I.....	13
APS057I.....	14
APS058I.....	14
APS060I.....	14
APS061I.....	14
APS062I.....	15
APS063I.....	15
APS064I.....	15
APS065I.....	16
APS066I.....	16
APS067I.....	16
APS068I.....	16
APS069I.....	17
APS070I.....	17
APS071I.....	17
APS072I.....	18
APS073I.....	18
APS074I.....	18
APS075I.....	19
APS076I.....	19
APS077I.....	19
APS078I.....	19
APS079I.....	20
APS080I.....	20
APS081I.....	20
APS082I.....	21
APS083I.....	21
APS084I.....	21
APS085I.....	21
APS086I.....	22
APS087I.....	22
APS088I.....	22
APS089I.....	23
APS095I.....	23
APS096I.....	23
APS097I.....	24
APS098I.....	24
APS099I.....	25
APS100 to APS199.....	25
APS100I.....	25
APS101I.....	25
APS102I.....	26
APS103I.....	26
APS104I.....	27
APS105I.....	27
APS106I.....	28
APS107I.....	28
APS108I.....	29
APS109I.....	29
APS110I.....	29
APS111I.....	30
APS112I.....	31
APS113I.....	31
APS114I.....	32
APS115I.....	32
APS116I.....	33

APS117I	33
APS118I	34
APS120I	34
APS121I	35
APS122I	35
APS123I	36
APS124I	36
APS125I	37
APS126I	37
APS127I	37
APS128I	38
APS129I	38
APS130I	39
APS131I	39
APS132I	40
APS133I	40
APS134I	40
APS135I	41
APS136I	41
APS138I	42
APS139I	42
APS140I	43
APS141I	43
APS143I	44
APS145I	45
APS146I	45
APS147I	46
APS149I	46
APS151I	47
APS152I	47
APS153I	48
APS154I	49
APS155I	49
APS156I	50
APS157I	50
APS158I	50
APS159I	51
APS162I	51
APS163I	52
APS165I	52
APS166I	53
APS167I	53
APS169I	54
APS170I	54
APS171I	55
APS172I	55
APS178I	56
APS179I	56
APS181I	57
APS186I	57
APS188I	58
APS190I	58
APS191I	59
APS192I	59
APS193I	60
APS194I	60
APS195I	61
APS196I	61

APS197I	62
APS199I	62
APS200 to APS299.....	63
APS206I.....	63
APS207I.....	63
APS209I.....	63
APS210I.....	64
APS212I.....	64
APS213I.....	65
APS214I.....	65
APS215I.....	66
APS217I.....	66
APS218I.....	66
APS219I.....	67
APS220I.....	67
APS221I.....	67
APS222I.....	68
APS223I.....	68
APS225I.....	69
APS226I.....	69
APS227I.....	69
APS228I.....	70
APS229I.....	70
APS230I.....	71
APS231I.....	71
APS232I.....	71
APS233I.....	72
APS234I.....	72
APS235I.....	72
APS236I.....	73
APS237I.....	73
APS239I.....	73
APS240I.....	74
APS241I.....	74
APS242I.....	74
APS244I.....	75
APS245I.....	75
APS246I.....	76
APS247I.....	77
APS248I.....	77
APS249I.....	77
APS250I.....	78
APS251I.....	78
APS252I.....	79
APS253I.....	79
APS254I.....	80
APS255I.....	80
APS256I.....	81
APS258I.....	81
APS259I.....	81
APS260I.....	82
APS261I.....	82
APS262I.....	83
APS263I.....	83
APS264I.....	84
APS265I.....	84
APS267I.....	85
APS268I.....	85

APS269I.....	85
APS270I.....	86
APS271I.....	86
APS272I.....	87
APS273I.....	87
APS274I.....	88
APS275I.....	88
APS276I.....	89
APS278I.....	90
APS279I.....	90
APS280I.....	91
APS281I.....	92
APS282I.....	92
APS283I.....	93
APS284I.....	93
APS285I.....	94
APS286I.....	94
APS287I.....	95
APS288I.....	95
APS289I.....	95
APS290I.....	96
APS291I.....	96
APS292I.....	97
APS293I.....	98
APS294I.....	98
APS295I.....	99
APS296I.....	99
APS297I.....	100
APS298I.....	101
APS299I.....	101
APS300 to APS399.....	102
APS300I.....	102
APS301I.....	102
APS303I.....	103
APS304I.....	103
APS307I.....	104
APS308I.....	104
APS309I.....	105
APS310I.....	105
APS312I.....	105
APS314I.....	106
APS315I.....	106
APS316I.....	107
APS317I.....	107
APS319I.....	108
APS320I.....	108
APS321I.....	109
APS322I.....	109
APS323I.....	109
APS324I.....	110
APS326I.....	110
APS327I.....	111
APS328I.....	111
APS329I.....	112
APS330I.....	112
APS331I.....	113
APS334I.....	113
APS335I.....	114

APS337I.....	114
APS339I.....	115
APS340I.....	115
APS342I.....	116
APS343I.....	116
APS344I.....	117
APS345I.....	117
APS346I.....	117
APS347I.....	118
APS350I.....	118
APS352I.....	119
APS353I.....	119
APS355I.....	120
APS360I.....	120
APS361I.....	121
APS362I.....	121
APS363I.....	121
APS364I.....	122
APS365I.....	122
APS366I.....	123
APS367I.....	123
APS368I.....	124
APS369I.....	124
APS370I.....	125
APS371I.....	125
APS372I.....	126
APS373I.....	126
APS374I.....	126
APS375I.....	127
APS376I.....	128
APS377I.....	128
APS378I.....	129
APS380I.....	129
APS381I.....	130
APS383I.....	130
APS384I.....	131
APS385I.....	131
APS386I.....	132
APS387I.....	133
APS388I.....	133
APS389I.....	134
APS390I.....	134
APS391I.....	135
APS392I.....	135
APS393I.....	136
APS394I.....	136
APS395I.....	136
APS396I.....	137
APS397I.....	137
APS398I.....	138
APS399I.....	138
APS400 to APS499.....	139
APS400I.....	139
APS401I.....	140
APS402I.....	141
APS403I.....	141
APS404I.....	142
APS405I.....	142

APS406I.....	143
APS407I.....	143
APS408I.....	144
APS409I.....	144
APS410I.....	145
APS411I.....	145
APS412I.....	146
APS413I.....	146
APS414I.....	147
APS415I.....	147
APS416I.....	148
APS417I.....	148
APS418I.....	149
APS419I.....	149
APS420I.....	150
APS421I.....	151
APS422I.....	151
APS423I.....	152
APS424I.....	152
APS425I.....	153
APS426I.....	153
APS427I.....	154
APS428I.....	155
APS429I.....	155
APS430I.....	156
APS431I.....	156
APS432I.....	157
APS433I.....	158
APS434I.....	158
APS435I.....	159
APS436I.....	160
APS437I.....	160
APS438I.....	161
APS439I.....	161
APS440I.....	162
APS441I.....	162
APS442I.....	163
APS443I.....	163
APS444I.....	164
APS445I.....	164
APS446I.....	164
APS447I.....	165
APS448I.....	165
APS449I.....	166
APS450I.....	166
APS451I.....	167
APS452I.....	167
APS453I.....	168
APS454I.....	168
APS455I.....	169
APS456I.....	169
APS457I.....	170
APS458I.....	170
APS459I.....	171
APS460I.....	171
APS461I.....	172
APS462I.....	172
APS463I.....	173

APS464I.....	173
APS465I.....	174
APS466I.....	174
APS467I.....	175
APS468I.....	175
APS469I.....	176
APS470I.....	176
APS471I.....	177
APS473I.....	177
APS474I.....	178
APS475I.....	179
APS476I.....	179
APS477I.....	180
APS478I.....	180
APS479I.....	181
APS480I.....	181
APS481I.....	182
APS482I.....	182
APS483I.....	183
APS484I.....	183
APS485I.....	184
APS486I.....	184
APS487I.....	185
APS488I.....	185
APS489I.....	186
APS490I.....	186
APS491I.....	187
APS492I.....	187
APS493I.....	188
APS494I.....	188
APS495I.....	189
APS496I.....	189
APS497I.....	190
APS498I.....	190
APS499I.....	191
APS500 to APS599.....	191
APS500I.....	191
APS501I.....	192
APS502I.....	192
APS503I.....	193
APS504I.....	193
APS505I.....	194
APS506I.....	194
APS507I.....	194
APS508I.....	194
APS509I.....	195
APS510I.....	195
APS511I.....	196
APS512I.....	196
APS513I.....	197
APS514I.....	197
APS515I.....	197
APS516I.....	198
APS517I.....	198
APS518I.....	198
APS519I.....	198
APS520I.....	199
APS522I.....	199

APS523I	199
APS524I	200
APS525I	200
APS527I	201
APS532I	201
APS534I	201
APS535I	202
APS536I	202
APS537I	203
APS538I	203
APS539I	204
APS540I	204
APS547I	204
APS548I	204
APS549I	205
APS550I	206
APS551I	206
APS553I	206
APS554I	207
APS555I	207
APS556I	207
APS557I	208
APS560I	208
APS561I	209
APS562I	209
APS563I	210
APS564I	210
APS565I	210
APS566I	211
APS568I	212
APS569I	212
APS570I	213
APS571I	213
APS573I	213
APS574I	214
APS575I	214
APS576I	214
APS577I	215
APS579I	215
APS580I	216
APS581I	216
APS582I	216
APS583I	216
APS584I	217
APS585I	217
APS586I	217
APS587I	217
APS588I	218
APS589I	218
APS590I	218
APS591I	218
APS592I	219
APS593I	219
APS594I	219
APS595I	219
APS596I	219
APS597I	220
APS598I	220

APS599I	220
APS600 to APS699	221
APS600I	221
APS601I	221
APS602I	221
APS603I	222
APS604I	222
APS605I	222
APS606I	222
APS607I	223
APS608I	223
APS609I	223
APS610I	223
APS611I	224
APS612I	224
APS613I	224
APS614I	225
APS615I	225
APS616I	225
APS617I	225
APS618I	226
APS619I	226
APS620A	226
APS621I	227
APS622I	227
APS623I	227
APS624I	227
APS625I	227
APS626I	228
APS627I	228
APS628I	228
APS629I	228
APS630I	229
APS631I	229
APS632I	229
APS633I	230
APS634I	231
APS635I	232
APS636I	232
APS637I	232
APS638I	233
APS639I	233
APS640I	233
APS641I	233
APS642I	234
APS643I	235
APS644I	236
APS645I	236
APS646I	236
APS647I	237
APS648I	237
APS649I	237
APS650I	237
APS651I	238
APS652I	238
APS653I	238
APS654I	238
APS655I	239

APS656I.....	239
APS661I.....	239
APS664I.....	239
APS667I.....	240
APS668I.....	240
APS669I.....	240
APS670I.....	240
APS671I.....	241
APS672I.....	241
APS683I.....	241
APS684I.....	241
APS685I.....	242
APS686I.....	242
APS687I.....	242
APS690I.....	242
APS691I.....	242
APS692I.....	243
APS693I.....	243
APS694I.....	243
APS695I.....	243
APS696I.....	244
APS697I.....	244
APS698I.....	244
APS699I.....	244
APS700 to APS799.....	245
APS700I.....	245
APS701I.....	246
APS702I.....	247
APS703I.....	248
APS704I.....	248
APS705I.....	248
APS706I.....	249
APS707I.....	250
APS708I.....	250
APS709I.....	251
APS710I.....	252
APS711I.....	252
APS712I.....	253
APS713I.....	253
APS714I.....	253
APS715I.....	254
APS716I.....	254
APS717I.....	255
APS718I.....	255
APS719I.....	256
APS720I.....	256
APS721A.....	257
APS722I.....	257
APS723I.....	258
APS724I.....	258
APS725I.....	259
APS726I.....	259
APS727I.....	259
APS728I.....	260
APS729I.....	260
APS730I.....	261
APS731I.....	261
APS732I.....	262

APS733I.....	263
APS734I.....	263
APS735I.....	264
APS736I.....	264
APS737I.....	265
APS738I.....	266
APS739I.....	266
APS740I.....	267
APS741I.....	267
APS742I.....	268
APS743I.....	268
APS746I.....	269
APS747I.....	269
APS748I.....	270
APS749I.....	271
APS750I.....	271
APS751I.....	272
APS753I.....	272
APS754I.....	273
APS755I.....	274
APS756I.....	274
APS757I.....	275
APS758I.....	275
APS759I.....	276
APS760I.....	277
APS761I.....	277
APS762I.....	278
APS763I.....	279
APS764I.....	279
APS765I.....	280
APS766I.....	281
APS767I.....	281
APS768I.....	282
APS769I.....	283
APS770I.....	283
APS771I.....	284
APS772I.....	285
APS773I.....	285
APS774I.....	286
APS775I.....	286
APS776I.....	287
APS777I.....	288
APS778I.....	288
APS779I.....	289
APS780I.....	289
APS781I.....	290
APS782I.....	290
APS783I.....	291
APS784I.....	291
APS785I.....	291
APS786I.....	292
APS787I.....	292
APS788I.....	293
APS790I.....	293
APS791I.....	294
APS792I.....	294
APS793I.....	295
APS794I.....	296

APS796I.....	296
APS797I.....	296
APS798I.....	297
APS799I.....	297
APS800 to APS899.....	298
APS800I.....	298
APS801I.....	298
APS802I.....	299
APS803I.....	299
APS804I.....	300
APS805I.....	300
APS806I.....	301
APS807I.....	301
APS808I.....	302
APS809I.....	302
APS810I.....	303
APS811I.....	303
APS812I.....	304
APS813I.....	304
APS814I.....	305
APS815I.....	306
APS816I.....	306
APS817A.....	307
APS818I.....	308
APS819I.....	308
APS820I.....	309
APS821I.....	310
APS822I.....	310
APS823I.....	311
APS824I.....	311
APS825I.....	312
APS826I.....	313
APS827I.....	313
APS828I.....	313
APS829I.....	314
APS830I.....	314
APS831I.....	316
APS832I.....	316
APS833I.....	317
APS834I.....	317
APS835I.....	318
APS836I.....	319
APS837I.....	319
APS838I.....	319
APS839I.....	320
APS840I.....	321
APS841I.....	322
APS842I.....	322
APS843I.....	323
APS844I.....	323
APS845I.....	323
APS846I.....	324
APS847I.....	324
APS848I.....	324
APS849I.....	325
APS850I.....	325
APS851I.....	326
APS852I.....	326

APS853I.....	326
APS854I.....	327
APS855I.....	327
APS856I.....	328
APS857I.....	328
APS858I.....	329
APS859I.....	330
APS860I.....	330
APS861I.....	330
APS862I.....	331
APS863I.....	332
APS864I.....	333
APS865I.....	334
APS866I.....	334
APS867I.....	335
APS868I.....	335
APS869I.....	335
APS870I.....	336
APS871I.....	336
APS872I.....	337
APS873I.....	337
APS874I.....	338
APS875I.....	338
APS876I.....	339
APS877I.....	340
APS878I.....	340
APS879I.....	341
APS880I.....	341
APS881I.....	341
APS882I.....	342
APS883I.....	342
APS884I.....	343
APS885I.....	343
APS886I.....	344
APS887I.....	345
APS888I.....	346
APS889I.....	346
APS890I.....	347
APS891I.....	347
APS892I.....	348
APS893I.....	348
APS894I.....	349
APS895I.....	349
APS896I.....	349
APS897I.....	350
APS898I.....	350
APS899I.....	351
APS900 to APS999.....	352
APS920I.....	352
APS921I.....	352
APS922I.....	352
APS923I.....	355
APS924I.....	355
APS925I.....	356
APS926I.....	357
APS927I.....	357
APS928I.....	357
APS929I.....	357

APS930I.....	358
APS931I.....	358
APS932I.....	358
APS933I.....	359
APS934I.....	359
APS935I.....	361
APS936I.....	362
APS937I.....	363
APS938I.....	363
APS939I.....	363
APS940I.....	363
APS941I.....	364
APS942I.....	364
APS943I.....	364
APS944I.....	364
APS945I.....	365
APS946I.....	365
APS947I.....	365
APS948I.....	366
APS949I.....	366
APS950I.....	366
APS951I.....	366
APS952I.....	367
APS953I.....	367
APS954I.....	367
APS955I.....	367
APS956I.....	368
APS957I.....	368
APS958I.....	368
APS959I.....	369
APS960I.....	369
APS961I.....	369
APS962I.....	370
APS963I.....	370
APS964I.....	370
APS965I.....	370
APS966I.....	371
APS967I.....	371
APS970I.....	371
APS971I.....	372
APS972I.....	372
APS973I.....	373
APS974I.....	373
APS975I.....	374
APS976I.....	374
APS977I.....	375
APS978I.....	375
APS979I.....	375
APS980I.....	376
APS981I.....	376
APS982I.....	376
APS983I.....	377
APS984I.....	377
APS986I.....	378
APS987I.....	378
APS988I.....	378
APS989I.....	379
APS990I.....	379

APS991I.....	379
APS992I.....	380
APS993I.....	380
APS994I.....	380
APS995I.....	381
APS996I.....	381
APS997I.....	381
APS998I.....	382
APS999I.....	382
APS1000 to APS2499.....	382
APS1001I.....	382
APS1002I.....	383
APS1003I.....	383
APS1005I.....	383
APS1006I.....	384
APS1007I.....	384
APS1008I.....	384
APS1009I.....	384
APS1010I.....	385
APS1011A.....	385
APS1012A.....	385
APS1018I.....	386
APS1020I.....	386
APS1021I.....	386
APS1022I.....	386
APS1023I.....	387
APS1024I.....	387
APS1025I.....	388
APS1026I.....	388
APS1027I.....	388
APS1028I.....	388
APS1029I.....	389
APS1030I.....	389
APS1031I.....	389
APS1032I.....	389
APS1033I.....	390
APS1034I.....	390
APS1035I.....	390
APS1036I.....	390
APS1037I.....	391
APS1500I.....	391
APS1501I.....	391
APS1700I.....	391
APS1701I.....	392
APS1702I.....	392
APS1703I.....	392
APS1704I.....	392
APS1705I.....	393
APS1706I.....	393
APS1707I.....	393
APS1708I.....	393
APS1709I.....	393
APS1710I.....	394
APS1711I.....	394
APS2000I.....	394
APS2001I.....	395
APS2002I.....	395
APS2003I.....	395

APS2004I.....	396
APS2005I.....	396
APS2006I.....	396
APS2007I.....	397
APS2008I.....	397
APS2009I.....	397
APS2010I.....	398
APS2011I.....	398
APS2012I.....	398
APS2013I.....	399
APS2014I.....	399
APS2015I.....	400
APS2016I.....	400
APS2017I.....	401
APS2018I.....	401
APS2019I.....	402
APS2020I.....	402
APS2021I.....	402
APS2022I.....	403
APS2023I.....	404
APS2024I.....	404
APS2025I.....	405
APS2026I.....	405
APS2027I.....	406
APS2028I.....	406
APS2030I.....	407
APS2032I.....	407
APS2035I.....	408
APS2038I.....	408
APS2039I.....	408
APS2040I.....	409
APS2041I.....	409
APS2042I.....	409
APS2044I.....	410
APS2045I.....	410
APS2046I.....	411
APS2047I.....	411
APS2048I.....	412
APS2049I.....	412
APS2050I.....	412
APS2051I.....	413
APS2052I.....	413
APS2053I.....	414
APS2054I.....	414
APS2055I.....	414
APS2056I.....	415
APS2057I.....	415
APS2058I.....	416
APS2059I.....	416
APS2061I.....	417
APS2062I.....	417
APS2063I.....	418
APS2064I.....	418
APS2065I.....	419
APS2066I.....	419
APS2067I.....	420
APS2068I.....	420
APS2069I.....	421

APS2071I.....	422
APS2072I.....	422
APS2073I.....	422
APS2074I.....	423
APS2075I.....	423
APS2077I.....	424
APS2078I.....	424
APS2079I.....	425
APS2080I.....	425
APS2081I.....	426
APS2082I.....	426
APS2083I.....	427
APS2084I.....	427
APS2085I.....	428
APS2086I.....	428
APS2087I.....	429
APS2088I.....	430
APS2089I.....	430
APS2090I.....	431
APS2091I.....	431
APS2092I.....	432
APS2093I.....	432
APS2094I.....	433
APS2095I.....	433
APS2096I.....	434
APS2097I.....	434
APS2098I.....	435
APS2099I.....	435
APS2100I.....	436
APS2101I.....	436
APS2103I.....	437
APS2104I.....	437
APS2106I.....	438
APS2107I.....	438
APS2108I.....	439
APS2109I.....	439
APS2110I.....	440
APS2111I.....	440
APS2112I.....	440
APS2113I.....	441
APS2114I.....	441
APS2116I.....	441
APS2119I.....	442
APS2120I.....	442
APS2121I.....	443
APS2122I.....	443
APS2123I.....	444
APS2124I.....	444
APS2500 to APS2599.....	445
APS2500I.....	445
APS2501I.....	445
APS2502I.....	445
APS2503I.....	446
APS2504I.....	446
APS2505I.....	446
APS2506I.....	446
APS2507I.....	446
APS2508I.....	447

APS2509I.....	447
APS2510I.....	447
APS2511I.....	447
APS2512I.....	447
APS2513I.....	447
APS2514I.....	448
APS2515I.....	448
APS2516I.....	448
APS2517I.....	448
APS2518I.....	448
APS2519I.....	449
APS2520I.....	449
APS2521I.....	449
APS2522I.....	449
APS2523I.....	449
APS2524I.....	450
APS2525I.....	450
APS2526I.....	450
APS2527I.....	450
APS2528I.....	450
APS2529I.....	451
APS2530I.....	451
APS2531I.....	451
APS2532I.....	451
APS2533I.....	451
APS2534I.....	452
APS2535I.....	452
APS2536I.....	452
APS2537I.....	452
APS2538I.....	452
APS2539I.....	452
APS2540I.....	453
APS2541I.....	453
APS2542I.....	453
APS2543I.....	454
APS2544I.....	454
APS2545I.....	454
APS2546I.....	455
APS2547I.....	455
APS2548I.....	455
APS2549I.....	456
APS2550I.....	456
APS2551I.....	456
APS2552I.....	457
APS2553I.....	457
APS2554I.....	458
APS2555I.....	459
APS2556I.....	459
APS2557I.....	460
APS2558I.....	460
APS2559I.....	461
APS2560I.....	461
APS2561I.....	462
APS2562I.....	462
APS2563I.....	462
APS2564I.....	463
APS2565I.....	464
APS2566I.....	465

APS2567I.....	466
APS2568I.....	467
APS2569I.....	467
APS2570I.....	468
APS2571I.....	468
APS2572I.....	469
APS2573I.....	470
APS2574I.....	470
APS2575I.....	471
APS2576I.....	472
APS2577I.....	472
APS2578I.....	473
APS2579I.....	473
APS2580I.....	474
APS2581I.....	475
APS2582I.....	475
APS2583I.....	476
APS2584I.....	477
APS2585I.....	478
APS2586I.....	478
APS2587I.....	479
APS2588I.....	480
APS2589I.....	481
APS2590I.....	481
APS2591I.....	482
APS2592I.....	482
APS2593I.....	482
APS2594I.....	483
APS2595I.....	483
APS2596I.....	483
APS2597I.....	484
APS2598I.....	484
APS2599I.....	485
APS2600 to APS5999.....	485
APS2600I.....	485
APS2601I.....	486
APS2602I.....	486
APS2603I.....	487
APS2604I.....	488
APS2605I.....	488
APS2606I.....	489
APS2607A.....	489
APS2608I.....	490
APS2609I.....	490
APS2610I.....	491
APS2611I.....	491
APS2612I.....	491
APS2613I.....	492
APS2614I.....	492
APS2615I.....	493
APS2616I.....	493
APS2617I.....	493
APS2618I.....	494
APS2619I.....	494
APS2620I.....	495
APS2621I.....	496
APS2622I.....	497
APS2623I.....	497

APS2624I.....	498
APS2625I.....	498
APS2626I.....	499
APS2627I.....	499
APS2628I.....	500
APS2629I.....	500
APS2630I.....	501
APS2631I.....	501
APS2632I.....	502
APS2633I.....	503
APS2634I.....	504
APS2635I.....	504
APS2636I.....	505
APS2637I.....	506
APS2638I.....	507
APS2639I.....	507
APS2640I.....	508
APS2641I.....	509
APS2644I.....	510
APS2645I.....	511
APS2646I.....	512
APS2647I.....	512
APS2648I.....	513
APS2649I.....	514
APS2650I.....	515
APS2661I.....	516
APS2662I.....	516
APS2663I.....	517
APS2664I.....	517
APS2665I.....	518
APS2666I.....	519
APS2667I.....	519
APS2668I.....	520
APS2669I.....	521
APS2670I.....	522
APS2671I.....	522
APS2672I.....	523
APS2673I.....	524
APS2674I.....	524
APS2675I.....	525
APS2676I.....	525
APS2677I.....	525
APS2678I.....	526
APS2679I.....	526
APS2681I.....	526
APS2682I.....	527
APS2691I.....	528
APS2692I.....	528
APS2693I.....	529
APS2694I.....	529
APS2695I.....	530
APS2696I.....	530
APS2697I.....	531
APS2698I.....	531
APS2699I.....	532
APS2700I.....	532
APS2701I.....	533
APS2702I.....	533

APS2703I.....	534
APS2707I.....	534
APS2708I.....	535
APS2709I.....	535
APS2710I.....	536
APS2711I.....	536
APS2712I.....	537
APS2713I.....	537
APS2714I.....	538
APS2715I.....	539
APS2716I.....	539
APS2717I.....	540
APS2718I.....	540
APS2719I.....	541
APS2720I.....	541
APS2721I.....	542
APS2722I.....	542
APS2723I.....	543
APS3000I.....	543
APS3001I.....	543
APS3002I.....	544
APS3003I.....	544
APS3004I.....	544
APS3005I.....	545
APS3006I.....	545
APS3500I.....	545
APS3501I.....	546
APS3502I.....	546
APS3503I.....	547
APS3504I.....	547
APS3506I.....	548
APS3507I.....	548
APS3508I.....	548
APS3509I.....	549
APS3510I.....	549
APS3513I.....	550
APS3514I.....	550
APS3515I.....	551
APS3516I.....	551
APS3517I.....	551
APS3518I.....	552
APS3519I.....	552
APS3520I.....	553
APS3521I.....	553
APS3522I.....	553
APS3523I.....	554
APS3524I.....	554
APS4000I.....	555
APS4001I.....	556
APS4002I.....	557
APS4003I.....	557
APS4004I.....	558
APS4400I.....	558
APS4401I.....	559
APS4402I.....	559
APS4403I.....	560
APS4500I.....	560
APS4501I.....	561

APS4502I.....	561
APS4506I.....	561
APS6000 to APS8600.....	561
APS6500I	561
APS6501A and APS6501I	562
APS6502I	562
APS6503I	563
APS6504I	563
APS6505I	563
APS6506I	564
APS6507I	564
APS6508I	565
APS6509I	565
APS6510I	565
APS6511I	566
APS6512I	566
APS6513I	566
APS6514I	567
APS6515I	568
APS6516I	569
APS6517I	569
APS6518I	569
APS7000I	569
APS7001I	570
APS7002I	570
APS7003I	571
APS7004I	571
APS7005I	571
APS8000I	571
APS8001I	572
APS8002I	572
APS8003I	572
APS8004I	573
APS8005I	573
APS8006I	573
APS8007I	574
APS8008I	574
APS8009I	574
APS8010I	575
APS8012I	575
APS8013I	575
APS8014I	575
APS8015I	576
APS8016I	577
APS8017I	578
APS8018I	578
APS8019I	579
APS8020I	579
APS8200I	579
APS8201I	580
APS8202I	580
APS8203I	580
APS8204I	580
APS8205I	581
APS8206I	581
APS8207I	582
APS8208I	582
APS8209I	582

APS8210I	583
APS8211I	583
APS8212I	583
APS8215I	584
APS8216I	584
APS8217I	584
APS8218I	585
APS8219I	585
APS8220I	585
APS8221I	586
APS8222I	586
APS8223I	586
APS8225I	587
APS8226I	587
APS8227I	587
APS8228I	587
APS8229I	588
APS8230I	588
APS8231I	588
APS8232I	589
APS8233I	589
APS8234I	589
APS8235I	590
APS8236I	590
APS8237I	590
APS8238I	590
APS8239I	591
APS8240I	591
APS8241I	591
APS8242I	592
APS8243I	592
APS8244I	592
APS8245I	593
APS8246I	593
APS8247I	593
APS8248I	593
APS8249I	594
APS8250I	594
APS8251I	594
APS8252I	595
APS8253I	595
APS8254I	595
APS8255I	596
APS8256I	596
APS8257I	596
APS8258I	596
APS8259I	597
APS8260I	597
APS8300I	597
APS8500I	598
APS8501I	598
APS8550I	598
APS8551I	599
APS8552I	599
APS8553I	600
APS8554I	600
APS8555I	600
APS8556I	601

APS8557I	601
APS8558I	602
APS8559I	602
APS8560I	603
APS8562I	603
APS8563I	604
APS8564I	604
APS8565I	604
APS8566I	605
APS8600I	605
APSH0001 to APSH0064.....	605
APSH0001.....	605
APSH0002.....	605
APSH0003.....	606
APSH0004.....	606
APSH0005.....	606
APSH0006.....	606
APSH0007.....	606
APSH0008.....	606
APSH0009.....	606
APSH0010.....	607
APSH0011.....	607
APSH0012.....	607
APSH0013.....	607
APSH0014.....	607
APSH0015.....	607
APSH0016.....	608
APSH0017.....	608
APSH0018.....	608
APSH0019.....	608
APSH0020.....	608
APSH0021.....	609
APSH0022.....	609
APSH0049.....	609
APSH0050.....	609
APSH0051.....	609
APSH0052.....	609
APSH0053.....	609
APSH0054.....	610
APSH0055.....	610
APSH0056.....	610
APSH0057.....	610
APSH0058.....	610
APSH0059.....	610
APSH0060.....	610
APSH0061.....	611
APSH0062.....	611
APSH0063.....	611
APSH0064.....	611
APSH0065.....	611
APSH0066.....	612

Chapter 2. System completion codes and PSF abend reason codes.....613

Abend processing and restart.....	613
System completion codes.....	613
024 [PSF].....	613
027 [PSF].....	613

0A6 [PPCC].....	613
PSF abend reason codes.....	613
0004.....	614
0005.....	614
0006.....	614
0007.....	614
0008.....	614
0009.....	614
000A.....	615
000B.....	615
000C.....	615
000D.....	615
000E.....	615
000F.....	616
0010.....	616
0012.....	616
0014.....	616
0018.....	616
0019.....	616
001A.....	616
001C.....	617
0020.....	617
0024.....	617
0025.....	617
0026.....	617
0027.....	617
0028.....	617
0029.....	618
002A.....	618
002C.....	618
0030.....	618
0032.....	618
0034.....	618
0038.....	618
003C.....	619
0044.....	619
0048.....	619
004C.....	619
0050.....	619
0054.....	619
0058.....	619
005C.....	620
0060.....	620
0064.....	620
0068.....	620
0072.....	620
0073.....	620
0074.....	620
0075.....	621
0076.....	621
0078.....	621
0079.....	621
007A.....	621
007B.....	621
007F.....	621
0080.....	621
0081.....	622
0082.....	622

00C0.....	622
00C1.....	622
00C2.....	622
00C3.....	623
00D2.....	623
00D3.....	623
00D4.....	623
00D5.....	623
00D6.....	623
00D7.....	623
00D8.....	623
00D9.....	624
00DA.....	624
00DB.....	624
00DC.....	624
00DD.....	624
0100.....	624
0102.....	624
0103.....	625
0104.....	625
0106.....	625
0107.....	625
0108.....	625
0109.....	625
010A.....	625
010B.....	626
010C.....	626
010D.....	626
010E.....	626
010F.....	626
0110.....	626
0111.....	627
0112.....	627
0113.....	627
0114.....	627
0115.....	627
0116.....	627
0117.....	627
0118.....	628
0119.....	628
011A.....	628
011B.....	628
011C.....	628
011D.....	628
011E.....	629
0120.....	629
0122.....	629
0124.....	629
0128.....	629
012C.....	629
0130.....	629
0134.....	630
0138.....	630
013C.....	630
0140.....	630
0144.....	630
0146.....	630
0148.....	630

014C.....	630
0150.....	631
0154.....	631
0158.....	631
015C.....	631
0160.....	631
0164.....	631
0168.....	631
016C.....	631
0170.....	632
0174.....	632
0178.....	632
017C.....	632
0180.....	632
0184.....	632
0188.....	632
018C.....	633
0190.....	633
0194.....	633
0198.....	633
019C.....	633
01A0.....	633
01A4.....	633
01A8.....	633
01AC.....	634
01B0.....	634
01B4.....	634
01B8.....	634
01BA.....	634
01BB.....	634
01BC.....	635
01C0.....	635
01C4.....	635
01C8.....	635
01CC.....	635
01D0.....	635
01D4.....	635
01D8.....	636
01DC.....	636
01F0.....	636
01F4.....	636
01F8.....	636
01F9.....	636
01FA.....	637
01FD.....	637
01FF.....	637
0200.....	637
0201.....	637
0202.....	637
0203.....	638
0204.....	638
0205.....	638
0206.....	638
0207.....	638
0208.....	639
0209.....	639
020A.....	639
020B.....	639

020C.....	639
020D.....	640
0211.....	640
0212.....	640
0213.....	640
0214.....	640
0216.....	640
0218.....	641
0219.....	641
021A.....	641
021B.....	641
0220.....	641
0222.....	641
0223.....	642
0224.....	642
0225.....	642
0226.....	642
0227.....	642
0228.....	642
0230.....	643
0231.....	643
0232.....	643
0233.....	643
0234.....	643
0235.....	644
0236.....	644
0237.....	644
0238.....	644
0239.....	644
023A.....	645
023B.....	645
023C.....	645
023D.....	645
023E.....	645
023F.....	645
0240.....	645
0241.....	645
0242.....	646
0243.....	646
0244.....	646
0245.....	646
0246.....	646
0247.....	646
0248.....	647
0249.....	647
024A.....	647
0250.....	647
025A.....	648
0260.....	648
0261.....	648
0262.....	648
0263.....	648
0264.....	648
0270.....	649
0271.....	649
0272.....	649
0273.....	649
0274.....	649

0275.....	649
0276.....	650
0277.....	650
0278.....	650
0279.....	650
027A.....	650
027B.....	650
027C.....	650
027D.....	651
027E.....	651
027F.....	651
0280.....	651
0281.....	651
0282.....	652
0283.....	652
0284.....	652
0285.....	652
0287.....	652
028A.....	652
028C.....	653
028D.....	653
0291.....	653
02A0.....	653
02A1.....	653
02A2.....	653
02A3.....	654
02A4.....	654
02A5.....	654
02A6.....	654
02A7.....	654
02A8.....	654
02A9.....	655
02AA.....	655
02AB.....	655
02AC.....	655
02AE.....	655
02AF.....	655
02B0.....	655
02B1.....	656
02B2.....	656
02B3.....	656
02B4.....	656
02B5.....	656
02B6.....	656
02B7.....	657
02B8.....	657
02B9.....	657
02BA.....	657
02BB.....	657
02BC.....	658
02BE.....	658
02BF.....	658
02C0.....	658
02C1.....	658
02C2.....	658
02C3.....	659
02D0.....	659
02D1.....	659

02D2.....	659
02D3.....	659
02E0.....	659
02E1.....	659
02E2.....	660
02E3.....	660
02E5.....	660
02E6.....	660
02E7.....	660
02E9.....	661
02EA.....	661
02EB.....	661
02EC.....	661
02ED.....	661
02EE.....	661
02EF.....	662
02F0.....	662
02F1.....	662
02F2.....	662
02F3.....	662
02F4.....	663
02F5.....	663
02F6.....	663
02F7.....	663
02F8.....	663
02F9.....	664
02FA.....	664
02FF.....	664
0300.....	664
0301.....	664
0310.....	665
0311.....	665
0320.....	665
0321.....	665
0322.....	665
0323.....	666
0324.....	666
0325.....	666
0331.....	666
0332.....	666
0333.....	666
0334.....	666
0335.....	667
0340.....	667
03D0.....	667
03D1.....	667
03D2.....	667
03D3.....	668
03D4.....	668
03D5.....	668
03D6.....	668
03D7.....	668
03D8.....	668
03D9.....	668
03DA.....	669
03DB.....	669
03DC.....	669
03DD.....	669

03DE.....	669
03E0.....	670
03E1.....	670
03E3.....	670
03E4.....	670
03E5.....	670
03E6.....	670
03E7.....	671
03E8.....	671
03E9.....	671
03EA.....	671
03EB.....	671
03EC.....	672
03ED.....	672
03EE.....	672
03EF.....	672
03F0.....	672
03F1.....	672
03F2.....	673
03F3.....	673
03F4.....	673
03F5.....	673
03F6.....	673
03F7.....	673
03F8.....	674
03F9.....	674
03FA.....	674
03FC.....	674
03FD.....	674
03FE.....	674
0400.....	675
0401.....	675
0402.....	675
0403.....	675
0404.....	675
0405.....	675
0406.....	676
0407.....	676
0408.....	676
0409.....	676
040A.....	676
040B.....	676
040C.....	676
0410.....	677
0411.....	677
0412.....	677
0413.....	677
0414.....	677
0415.....	678
0416.....	678
0417.....	678
0418.....	678
0419.....	678
041A.....	678
041B.....	678
041C.....	679
041D.....	679
041E.....	679

041F.....	679
0420.....	679
0421.....	680
0422.....	680
0423.....	680
0435.....	680
0490.....	680
04A0.....	680
04A5.....	681
04B0.....	681
04B1.....	681
04B2.....	681
04B4.....	681
04B5.....	681
04B6.....	682
04B8.....	682
04B9.....	682
04F0.....	682
04F2.....	682
04F3.....	683
04F4.....	683
04F5.....	683
04F6.....	683
04F7.....	683
0502.....	684
0503.....	684
0504.....	684
0505.....	684
0506.....	684
0507.....	685
050B.....	685
0514.....	685
0515.....	685
0516.....	685
0518.....	685
0519.....	686
051A.....	686
051B.....	686
051D.....	686
051E.....	686
0520.....	687
0521.....	687
0523.....	687
0524.....	687
0525.....	687
0526.....	687
0551.....	688
0552.....	688
0553.....	688
0554.....	688
0555.....	689
0556.....	689
0557.....	689
0560.....	689
0570.....	689
0571.....	690
0601.....	690
0602.....	690

0604.....	690
0605.....	691
0606.....	691
0607.....	691
0608.....	691
0609.....	691
0615.....	691
0616.....	692
0617.....	692
0620.....	692
0621.....	692
0622.....	692
0623.....	693
0624.....	693
0625.....	693
0626.....	693
0627.....	693
0628.....	693
0629.....	694
0640.....	694
0643.....	694
0644.....	694
0648.....	694
0649.....	694
0650.....	695
0651.....	695
0652.....	695
0653.....	695
0654.....	695
0655.....	696
0656.....	696
0657.....	696
0658.....	696
0659.....	696
0660.....	696
0663.....	697
0701.....	697
0702.....	697
0703.....	697
0704.....	698
0705.....	698
0706.....	698
0707.....	698
0708.....	698
0709.....	698
070A.....	699
070B.....	699
070C.....	699
070D.....	699
070E.....	700
070F.....	700
0711.....	700
0712.....	700
0713.....	700
0714.....	700
0715.....	701
0716.....	701
0717.....	701

0722.....	701
0723.....	701
0725.....	702
0726.....	702
0728.....	702
0729.....	702
0730.....	703
0731.....	703
0734.....	703
0736.....	703
0738.....	703
0739.....	704
0740.....	704
0742.....	704
0743.....	704
0744.....	705
0751.....	705
0752.....	705
0771.....	705
0772.....	705
0773.....	705
0781.....	706
0782.....	706
0783.....	706
0791.....	706
07A1.....	706
07A2.....	706
07A4.....	707
07A8.....	707
07A9.....	707
07B0.....	707
07C0.....	707
07C1.....	708
07C2.....	708
07C3.....	708
07C4.....	708
07C5.....	708
07C6.....	709
0810.....	709
0811.....	709
0820.....	709
0821.....	709
0840.....	710
0841.....	710
0850.....	710
0851.....	710
0852.....	711
0860.....	711
0870.....	711
0880.....	711
0881.....	711
0882.....	711
0883.....	712
0891.....	712
0892.....	712
08A0.....	712
08A1.....	712
08A2.....	712

08A3.....	713
08A4.....	713
08A5.....	713
08A6.....	713
08A7.....	713
08A8.....	714
08A9.....	714
08AA.....	714
08AB.....	714
08AC.....	714
08AD.....	714
08AE.....	715
08AF.....	715
08B0.....	715
08B1.....	715
08C0.....	715
08D1.....	715
08D2.....	716
08D3.....	716
08D4.....	716
08D5.....	716
08D6.....	716
08D7.....	716
08D8.....	717
08D9.....	717
08DA.....	717
08E0.....	717
0900.....	717
0901.....	717
0902.....	718
0903.....	718
0904.....	718
0905.....	718
0906.....	718
090C.....	718
090D.....	719
090E.....	719
090F.....	719
0910.....	719
0911.....	719
0912.....	719
0913.....	719
0919.....	720
0920.....	720
0921.....	720
0922.....	720
0923.....	720
0924.....	720
0926.....	721
0928.....	721
0930.....	721
0931.....	721
0933.....	721
0936.....	721
0937.....	722
0938.....	722
0939.....	722
0940.....	722

0942.....	722
0944.....	722
0945.....	723
0946.....	723
0947.....	723
0948.....	723
0949.....	723
094A.....	723
094B.....	723
094C.....	724
094D.....	724
094E.....	724
094F.....	724
0950.....	724
0951.....	724
0952.....	725
0953.....	725
0954.....	725
0955.....	725
0956.....	725
0957.....	726
0958.....	726
0959.....	726
0963.....	726
0964.....	726
0965.....	727
0968.....	727
0969.....	727
0973.....	727
0974.....	727
0975.....	728
0976.....	728
0977.....	728
0978.....	728
0979.....	728
0980.....	728
0981.....	729
0982.....	729
0983.....	729
0987.....	729
0988.....	729
0990.....	729
0992.....	730
0993.....	730
0994.....	730
0996.....	730
0998.....	730
099A.....	730
099C.....	731
099E.....	731
09A1.....	731
09A3.....	731
09A4.....	731
09A5.....	732
09A6.....	732
09A7.....	732
09A8.....	732
09A9.....	732

09AA.....	732
09AB.....	733
09AC.....	733
09AD.....	733
09AE.....	733
09AF.....	733
09B1.....	733
09B2.....	734
09B3.....	734
09B4.....	734
09B8.....	734
09B9.....	734
09BB.....	734
09BC.....	735
09C0.....	735
09C1.....	735
09C2.....	735
09C4.....	735
09C5.....	735
09C6.....	735
09C7.....	736
09C9.....	736
09CA.....	736
09D5.....	736
09D6.....	736
09D7.....	736
09E0.....	737
09F0.....	737
09F1.....	737
09F2.....	737
09FE.....	737
09FF.....	737
0A00.....	737
0A10.....	738
0A11.....	738
0A12.....	738
0A20.....	738
0A21.....	738
0A30.....	739
0A31.....	739
0A40.....	739
0A41.....	739
0A50.....	739
0A51.....	739
0A52.....	739
0A53.....	740
0A54.....	740
0A55.....	740
0A58.....	740
0A59.....	740
0A5A.....	741
0A5B.....	741
0A5C.....	741
0A5D.....	741
0A5E.....	741
0A5F.....	741
0A60.....	742
0B00.....	742

0B01.....	742
0B02.....	742
0B04.....	742
0B05.....	742
0B10.....	743
0B11.....	743
0B12.....	743
0B13.....	743
0C00.....	743
0C01.....	743
0C02.....	744
0C03.....	744
0C04.....	744
0C20.....	744
0C22.....	744
0C30.....	744
0C31.....	745
0D00.....	745
0D01.....	745
0D03.....	745
0D04.....	745
0D05.....	745
0D06.....	746
0D07.....	746
0D08.....	746
0D09.....	746
0D0A.....	746
0D0B.....	746
0D0C.....	747
0D0E.....	747
0D0F.....	747
0D10.....	747
0D11.....	747
0D12.....	747
0D13.....	748
0D14.....	748
0D15.....	748
0D16.....	748
0D17.....	748
0D18.....	748
0D19.....	749
0D1A.....	749
0D20.....	749
0D21.....	749
0D31.....	749
0D32.....	749
0D33.....	750
0D41.....	750
0D54.....	750
0D56.....	750
0D57.....	750
0D58.....	751
0D60.....	751
0D70.....	751
0D71.....	751
0D77.....	752
0D78.....	752
0D79.....	752

0D80.....	752
0D81.....	752
0D82.....	752
0D83.....	753
0D84.....	753
0D85.....	753
0D86.....	753
0D87.....	753
0D88.....	754
0D89.....	754
0D90.....	754
0D91.....	754
0D92.....	754
0D93.....	755
0D95.....	755
0D96.....	755
0D98.....	755
0DA0.....	755
0DA1.....	756
0DA2.....	756
0DA3.....	756
0DA4.....	756
0DA5.....	756
0DA6.....	757
0DA7.....	757
0DA8.....	757
0DA9.....	757
0DAA.....	757
0DAB.....	757
0DAC.....	758
0DAD.....	758
0DAE.....	758
0DB0.....	758
0DB1.....	758
0DB2.....	759
0DB3.....	759
0DB4.....	759
0DB7.....	759
0DB8.....	759
0DB9.....	759
0E00.....	760
0E01.....	760
0E02.....	760
0E03.....	760
0E04.....	760
0E05.....	760
0E08.....	761
0E09.....	761
0E0A.....	761
0E0C.....	761
0E0E.....	761
0E10.....	761
0E11.....	762
0E12.....	762
0E13.....	762
0E14.....	762
0E19.....	762
0E20.....	762

0E21.....	762
0E22.....	763
0E23.....	763
0E24.....	763
0E30.....	763
0E31.....	763
0E32.....	763
0E33.....	764
0E34.....	764
0E35.....	764
0E36.....	764
0E50.....	764
0E51.....	764
0E60.....	765
0E61.....	765
0E80.....	765
0E82.....	765
0E83.....	765
0E84.....	766
0E85.....	766
0E90.....	766
0E91.....	766
0E92.....	766
0E93.....	766
0E94.....	767
0E96.....	767
0E97.....	767
0E98.....	767
0E9A.....	767
0E9C.....	767
0EA0.....	768
0EA1.....	768
0EA2.....	768
0EA3.....	768
0EA4.....	768
0EA5.....	768
0EA7.....	769
0EA8.....	769
0EA9.....	769
0F00.....	769
0F01.....	769
0F02.....	769
0F03.....	770
0F04.....	770
0F05.....	770
0F06.....	770
0F07.....	770
0F09.....	771
0F0A.....	771
0F0B.....	771
0F0C.....	771
0F0D.....	772
0F0E.....	772
0F0F.....	772
0F10.....	772
0F11.....	772
0F12.....	773
0F14.....	773

OF15.....	773
OF16.....	773
OF17.....	773
OF18.....	774
Appendix A. Valid scope values for the CMR Descriptor triplet.....	775
Appendix B. Accessibility.....	777
Accessibility features.....	777
Consult assistive technologies.....	777
Keyboard navigation of the user interface.....	777
Dotted decimal syntax diagrams.....	777
Notices.....	781
Terms and conditions for product documentation.....	782
IBM Online Privacy Statement.....	783
Policy for unsupported hardware.....	783
Minimum supported hardware.....	784
Trademarks.....	784
Bibliography.....	785
Advanced Function Presentation (AFP).....	785

About this publication

This publication describes the messages and codes that are issued by Print Services Facility (PSF) Version 4, Release 6.0 for z/OS (Program Number 5655-M32), including message and codes for the optional AFP Download Plus and Download for z/OS features.

The return reason codes that are contained in PSF memory dumps are described in [*PSF for z/OS: Diagnosis*](#). The program completion codes for the APSRCF30 utility are described in [*PSF for z/OS: Customization*](#).

In this publication, the word *printing* refers to presentation on paper, foils, labels, or microfilm. (*Microfilm* can mean either microfiche or 16 mm film.)

Who should read this publication

This publication can be used by anyone who knows how to maintain and operate the printers that work with PSF for z/OS.

How this publication is organized

Chapter 1, “[PSF for z/OS messages](#),” on page 1, lists the PSF messages in ascending numerical order, describes what the system does after an error occurs, and suggests what you must do to correct the problem. The message entries provide:

Explanation

The explanation gives more information about the condition that caused PSF to issue the message.

System Action

The system action describes how the system responds to the condition.

User Response, System Programmer Response, and Operator Response

The user response, the system programmer response, and the operator response provide actions for recovering from the error condition. Often this part of the entry gives more than one recovery action, or a series of related recovery actions; this means that more than one problem might cause the error.

Chapter 2, “[System completion codes and PSF abend reason codes](#),” on page 613, lists all the PSF abend reason codes, in ascending numerical order. The code entries provide:

Explanation

The explanation gives more information about the condition that caused the PSF abend.

System Action

The system action specifies whether PSF is to attempt to restart automatically, or is to stop processing.

System Programmer Response

If present, the system programmer response provides a suggested action for recovering from the error condition.

Appendix A, “[Valid scope values for the CMR Descriptor triplet](#),” on page 775 lists the valid scope values for the Color Management Resource (CMR) Descriptor triplet.

Appendix B, “[Accessibility](#),” on page 777 describes the accessibility features available in z/OS.

Notices and a bibliography are included. The bibliography lists the publications that contain additional information about the system, hardware, or software used by PSF, or about installation and maintenance.

Understanding message and code notation

The following rules apply to coding illustrations throughout this publication:

- Uppercase or bold letters are to be coded as shown.
- Variable data is printed in italics. Enter specific data to replace the characters in italics.
- Do not enter these symbols as part of a parameter or option:

Braces

{ }

Brackets

[]

Underscore

—

Vertical bar

|

- Braces around a value mean that you must select one of the values.
- Brackets around a value mean that you do not have to select the value.
- An underscored value means that if an option is not specified, the underscored value, called the default, is used.
- A vertical bar between two values means that you select one of the values.

Related information

Publications that are referred to in this document or that contain more information about AFP and related products are listed in the “Bibliography” on page 785. For information about all z/OS product publications, see *z/OS Information Roadmap*.

For more information about z/OS and PSF for z/OS, see these web pages:

- [z/OS home page \(www.ibm.com/systems/z/os/zos\)](http://www.ibm.com/systems/z/os/zos)
- [z/OS Print Management Software \(www.ibm.com/systems/z/os/zos/printsoftware\)](http://www.ibm.com/systems/z/os/zos/printsoftware)

To obtain the latest documentation updates for z/OS base elements and optional features that result from DOC APARs and PTFs, go to [z/OS APAR book \(publibz.boulder.ibm.com/cgi-bin/bookmgr_OS390/Shelves/ZDOCAPAR\)](http://publibz.boulder.ibm.com/cgi-bin/bookmgr_OS390/Shelves/ZDOCAPAR).

To obtain the latest documentation updates for PSF for z/OS, see the appropriate SYS1.SAMPLIB members in [Table 1 on page xlvi](#).

Member	Publication
APSGADP6	<i>PSF for z/OS: AFP Download Plus</i>
APSGCUS6	<i>PSF for z/OS: Customization</i>
APSGDGN6	<i>PSF for z/OS: Diagnosis</i>
APSGDLG6	<i>PSF for z/OS: Download for z/OS</i>
APSGMAC6	<i>PSF for z/OS: Messages and Codes</i>
APSGSEC6	<i>PSF for z/OS: Security Guide</i>
APSGUSR6	<i>PSF for z/OS: User's Guide</i>

How to send your comments to IBM

We invite you to submit comments about the z/OS product documentation. Your valuable feedback helps to ensure accurate and high-quality information.

Important: If your comment regards a technical question or problem, see instead [“If you have a technical problem”](#) on page xlvii.

Submit your feedback by using the appropriate method for your type of comment or question:

Feedback on z/OS function

If your comment or question is about z/OS itself, submit a request through the [IBM RFE Community](#) (www.ibm.com/developerworks/rfe/).

Feedback on IBM Knowledge Center function

If your comment or question is about the IBM Knowledge Center functionality, for example search capabilities or how to arrange the browser view, send a detailed email to IBM Knowledge Center Support at ibmkc@us.ibm.com.

Feedback on the z/OS product documentation and content

If your comment is about the information that is provided in the z/OS product documentation library, send a detailed email to mhvrcfs@us.ibm.com. We welcome any feedback that you have, including comments on the clarity, accuracy, or completeness of the information.

To help us better process your submission, include the following information:

- Your name, company/university/institution name, and email address
- The following deliverable title and order number: PSF V4R6 for z/OS: Messages and Codes, G550-0432-05
- The section title of the specific information to which your comment relates
- The solution title: PSF V4R6 for z/OS: Messages and Codes
- The text of your comment.

When you send comments to IBM, you grant IBM a nonexclusive right to use or distribute the comments in any way appropriate without incurring any obligation to you.

IBM or any other organizations use the personal information that you supply to contact you only about the issues that you submit.

If you have a technical problem

If you have a technical problem or question, do not use the feedback methods that are provided for sending documentation comments. Instead, take one or more of the following actions:

- Go to the [IBM Support Portal](#) (support.ibm.com).
- Contact your IBM service representative.
- Call IBM technical support.

Summary of changes

This content includes terminology, maintenance, and editorial changes to information previously presented in *PSF for z/OS: Messages and Codes*, G550-0432-04. Technical additions or changes to the text and illustrations are indicated by a vertical line to the left of the change.

General changes

- References to PSF 4.3.0, PSF 4.4.0, and z/OS 1.13 are removed because they are no longer in service.
- References to the Ricoh product "InfoPrint Manager" is removed.
- "Distributed Print Function (DPF)", "PSF Direct", and "Workstation Print Manager (WPM)" are changed to "distributed print function (DPF)", "PSF direct", and "workstation print manager (WPM)".
- "InfoPrint AFP Resource Installer" is removed or changed to "AFP resource installer".
- The Problem Determination section for each message in [Chapter 1](#), "PSF for z/OS messages," on [page 1](#) is removed. Also, the appendix that lists problem determination instructions is removed.

New information

These messages are new:

<u>APS124I</u> " on page 36	"		
<u>APS2584I</u> " on page 477	"APS2700I" on page 532	"APS2717I" on page 540	
<u>APS133I</u> " on page 40	"APS2609I" on page 490	"APS2701I" on page 533	"APS2718I" on page 540
<u>APS134I</u> " on page 40	"APS2610I" on page 491	"APS2702I" on page 533	"APS2719I" on page 541
<u>APS136I</u> " on page 41	"APS2631I" on page 501	"APS2703I" on page 534	"APS2720I" on page 541
<u>APS149I</u> " on page 46	"		
<u>APS2632I</u> " on page 502	"APS2707I" on page 534	"APS2721I" on page 542	
<u>APS303I</u> " on page 103	"APS2691I" on page 528	"APS2708I" on page 535	"APS2722I" on page 542
<u>APS304I</u> " on page 103	"APS2692I" on page 528	"APS2709I" on page 535	"APS2723I" on page 543
<u>APS536I</u> " on page 202	"APS2693I" on page 529	"APS2710I" on page 536	"
<u>APS6517I</u> " on page 569			
<u>APS549I</u> " on page 205	"APS2694I" on page 529	"APS2711I" on page 536	"
<u>APS6518I</u> " on page 569			
<u>APS550I</u> " on page 206	"APS2695I" on page 530	"APS2712I" on page 537	"
<u>APS8020I</u> " on page 579			
"APS945I" on page 365	"APS2696I" on page 530	"APS2713I" on page 537	"
<u>APS8259I</u> " on page 597			
"APS2061I" on page 417	"APS2697I" on page 531	"APS2714I" on page 538	"
<u>APS8260I</u> " on page 597			
"APS2123I" on page 444	"APS2698I" on page 531	"APS2715I" on page 539	"
<u>APS8557I</u>			

" on page 601
"APS2124I" on page 444 "APS2699I" on page 532 "APS2716I" on page 539

These abend reason codes are new:

"
00DD
" on page 624 "
0526
" on page 687
"
0207
" on page 638 "
0607
" on page 691
"
02FA
" on page 664 "
0608
" on page 691
"
03DC
" on page 669 "
0609
" on page 691
"
03E9
" on page 671

Changed information

These messages are changed:

<u>"APS037I" on page 9</u>	<u>"APS626I" on page 228</u>	<u>"APS2100I" on page 436</u>	"
<u>APS8005I</u> <u>" on page 573</u>			
<u>"APS061I" on page 14</u>	<u>"APS770I" on page 283</u>	<u>"APS2119I" on page 442</u>	"
<u>APS8006I</u> <u>" on page 573</u>			
<u>"APS068I" on page 16</u>	<u>"APS806I" on page 301</u>	<u>"APS4000I" on page 555</u>	"
<u>APS8007I</u> <u>" on page 574</u> "			
<u>APS100I</u> <u>" on page 25</u>	<u>"APS814I" on page 305</u>	<u>"APS4003I" on page 557</u>	"
<u>APS8008I</u> <u>" on page 574</u> "			
<u>APS101I</u> <u>" on page 25</u>	<u>"APS838I" on page 319</u>	<u>"APS4004I" on page 558</u>	"
<u>APS8009I</u> <u>" on page 574</u> "			
<u>APS110I</u> <u>" on page 29</u>	<u>"APS851I" on page 326</u>	"	
<u>APS6512I</u> <u>" on page 566</u>	"		
<u>APS8010I</u> <u>" on page 575</u>			
<u>"APS225I" on page 69</u>	<u>"APS933I" on page 359</u>	"	
<u>APS6513I</u> <u>" on page 566</u>	"		
<u>APS8012I</u> <u>" on page 575</u>			
<u>"APS280I" on page 91</u>	<u>"APS934I" on page 359</u>	"	
<u>APS6516I</u> <u>" on page 569</u>	"		
<u>APS8013I</u> <u>" on page 575</u>			
<u>"APS370I" on page 125</u>	<u>"APS935I" on page 361</u>	"	
<u>APS8000I</u> <u>" on page 571</u>	"		
<u>APS8014I</u> <u>" on page 575</u>			
<u>"APS386I" on page 132</u>	<u>"APS1021I" on page 386</u>	"	
<u>APS8001I</u> <u>" on page 572</u>	"		
<u>APS8015I</u>			

" on page 576
"APS437I" on page 160 "APS2062I" on page 417 "
APS8002I
" on page 572 "
APS8016I
" on page 577
"APS440I" on page 162 "APS2087I" on page 429 "
APS8003I
" on page 572 "
APS8018I
" on page 578
"APS471I" on page 177 "APS2097I" on page 434 "
APS8004I
" on page 573 "
APS8223I
" on page 586
"APS613I" on page 224

This abend reason code is changed:

- "0B05" on page 742

Deleted information

This message is deleted:

- APS3505I

Chapter 1. PSF for z/OS messages

Message destinations

PSF for z/OS (from now on referred to as PSF) issues messages to one or more of the following destinations, depending on which is most appropriate:

Operator's console

Messages that the operator or system programmer must address.

Security administrator's console

Messages reporting security violations or errors in the processing of security functions.

Job submitter's console

Messages reporting the completion or failure of a job to print.

In the printed output

Messages reporting the position from which data is retransmitted during a recovery.

Following the printed output

Messages describing errors in the data stream. Also, a duplicate copy of any message issued in the printed output.

SYSLOG data set

Issued if the NOTIFY parameter is specified on the JCL for the data set being transmitted.

stderr

Some messages issued by PSF running under z/OS UNIX System Services, from now on referred to as UNIX System Services.

Log file

Some messages issued by PSF running under UNIX System Services.

Format of the messages

Each PSF message has a 7 - 8 character message identifier followed by message text, such as:

APSnnnnt MESSAGE TEXT

or

APSHnnnn message text

where:

APS

Identifies PSF messages.

H

Indicates that PSF is running under UNIX System Services.

nnnn

Three- or four-digit message number.

t

One-character type code:

A

Message that requires operator action.

I

Information message.

MESSAGE TEXT

message text

PSF message text describes the condition that caused PSF to issue the message. For APShnnnn messages, the message text is in mixed case; otherwise, the text is in uppercase.

The message text can include these types of codes:

- Dynamic allocation error codes
- Event Control Block (ECB) completion codes
- Status codes
- PSF return reason codes
- PSF abend reason codes
- System completion codes
- SNA sense codes
- VTAM® codes
- In APShnnnn messages, error numbers issued by the C run-time library
- In APShnnnn messages, error explanations issued by the C run-time library

In system console messages, additional information is inserted between the message ID and the message text. This information identifies the specific functional subsystem application that issued the message. Most system console messages have the following format:

APSnnnt jobname jobstep procstep printer name attachment MESSAGE TEXT

where:

jobname

The job name of the startup procedure.

jobstep

The FSS name in the job.

procstep

The step name in a procedure. When PSF is managing a system output device for deferred printing under JES, this item is not entered.

printer name

The name of the printer.

attachment

(SNA)—For a Systems Network Architecture-attached printer.

(tcpname)—For a TCP/IP-attached printer. *tcpname* is the name of the TCP/IP startup procedure.

(nnn)—For a channel-attached printer with a three-digit device number. *nnn* is the device number.

(nnnn)—For a channel-attached printer with a four-digit device number. *nnnn* is the device number.

(***)—If the value cannot be determined.

For Download for z/OS messages, APS095I and APS986I through APS999I, the format is similar:

*APSnnnt jobname jobstep *** ** * MESSAGE TEXT*

jobname

The job name of the startup procedure.

jobstep

The FSS name within the job.

Responding to a message

When you get a message, use any codes in the message text, in addition to message description information, to determine a recovery procedure. This publication describes PSF abend reason codes and system completion codes. If an explanation does not exist in this publication for the code in your message, you are referred to another publication that contains the information you need.

If you need to determine the module that issued the message, see the message-to-module cross-reference table in *PSF for z/OS: Diagnosis*.

PSF often issues more than one message for an error condition. When this occurs, use all the messages to define and correct the error.

APS000 to APS099

APS000I *subsystem* **SUBSYSTEM ACTIVE.**

Explanation

The PSF Direct Printer Services Subsystem is active.

System action

This message is only for information.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

No response is necessary.

APS001I *subsystem* **SUBSYSTEM INITIALIZATION FAILED, RC = return code, [MODULE ACCESSED module].**

Explanation

The PSF Direct Printer Services Subsystem that is identified in this message failed to initialize. If you are using a 3800, until the problem is resolved, the 3800 can be directly allocated only if it is in compatibility mode.

System action

The PSF Direct Printer Services Subsystem is not active.

Operator response

Inform your system programmer that this error occurred.

System programmer response

The associated return code that is issued by the subsystem service routine is given in this message.

If the return code is 12, a GETMAIN failure occurred. For more information, see *PSF for z/OS: Diagnosis*.

If the return code is 20, the module that is accessed is not in SYS1.LINKLIB or a library concatenated to a SYS1.LINKLIB (in LNKLSTxx PARMLIB member). Link-edit the module to SYS1.LINKLIB or to a concatenated library.

User response

No response is necessary.

APS002A **INCORRECT REPLY – RE-SPECIFY.**

Explanation

An incorrect response was given to a previous load forms flash or to a thread-to-stacker message.

System action

Processing stops until the operator responds to this message.

Operator response

Enter the correct reply. See message APS003A for the correct reply.

System programmer response

No response is necessary.

User response

No response is necessary.

APS003A **SETUP *jobname procstep jobstep* *ddname (nnnn) O=forms flash***

**frame, B={Y | N} F=forms—REPLY
'U' OR 'CANCEL'.**

Explanation

(*nnnn*) is the 3 - 4 digit device number of the printer. The forms flash frame, which is identified by O= in this message, is the frame specified by the FORMS FLASH keyword on the JCL. B= indicates whether the BURST keyword on the JCL specified yes or no for the burster-trimmer-stacker feature. F= specifies the form used with the job. The setup must be consistent with the JCL specified for this print request.

This message identifies one or more of these parameters. If one of these parameters is not specified here, it was not specified on the JCL.

System action

Processing stops until the operator responds to this message.

Operator response

Enter one of the following replies, where *nn* is the number that the system specified when it issued this message:

- *Rnn,U*. This reply returns a hexadecimal code that verifies either that the requested setup is completed, or that the setup commands are ignored if the setup cannot be completed.
- *Rnn,CANCEL*. This reply causes a subsystem output block (SSOB) return code of X'04' to be passed back to the data management open routine. Return code X'04' indicates that the print request is canceled.

System programmer response

No response is necessary.

User response

No response is necessary.

APS004I ***subsystem* SUBSYSTEM
INITIALIZATION PARAMETER
INCORRECT, 1 ASSUMED.**

Explanation

The PSF Direct Printer Services Subsystem initialization parameter that is specified in the IEFSSNxx PARMLIB member is not valid. A parameter with more than 8 characters or non-numeric characters causes this message.

System action

The PSF Direct Printer Services Subsystem continues to initialize.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Correct the initialization parameter specified in the IEFSSNxx PARMLIB member. For information about correcting the initialization parameter in the IEFSSNxx PARMLIB member, see *PSF for z/OS: Customization*.

User response

No response is necessary.

APS005I **PSF INITIALIZATION FAILED,
REASON CODE *rc*.**

Explanation

PSF initialization failed, for the reason given in one of the following reason codes:

- 04** GETMAIN for DPSS control block failed.
- 08** SJFREQ FINDSWB failed.
- 0C** SJFREQ retrieve failed.
- 10** GETMAIN for SSXB failed.
- 14** APSAFSA attach failed.
- 18** PSF abend occurred.
- 1C** Operator specified cancel in response to message APS003A.

System action

The print job is not started or is discontinued at its current location.

Operator response

For an operator cancel, have the user resubmit the print request, and do not cancel it.

System programmer response

If the problem is a GETMAIN failure, increase the REGION size parameter. If the problem is an SJFREQ

failure, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center. If the problem is an attach failure, check to see that PSF is accessible to DPSS. For an operator cancel, no response is necessary.

User response

No response is necessary.

APS006I	PSF INITIALIZATION FAILED; MAXIMUM DIRECT ATTACH FSA'S EXCEEDED.
----------------	---

Explanation

PSF initialization failed because a request was made to attach more FSAs than the maximum specified in SYS1.PARMLIB.

System action

The print job is not started.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Either raise the maximum FSA number in SYS1.PARMLIB, or have the user resubmit the job when Direct Attach is not at capacity.

User response

No response is necessary.

APS018I	JOB TERMINATED AS REQUESTED BY THE PSF MESSAGE EXIT
----------------	--

Explanation

The Message Exit requested ending the job.

System action

The job stops processing.

Operator response

No response is necessary.

System programmer response

Evaluate why the Message Exit ended the job and take any appropriate action.

User response

Notify your system programmer of this error.

APS020I	PRINTING TERMINATED BECAUSE RECOVERY IS INHIBITED.
----------------	---

Explanation

An exception occurred for which the typical PSF recovery is to resend pages to the printer that might have already printed. The Printer Inventory or Exit 7 specified that this recovery cannot be done.

System action

PSF ends the current print job.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Resubmit the print job to reprint the incomplete portion of the print data, if needed.

APS021I	AN INCORRECT REQUEST FROM THE LOGICAL RECORD EXIT WAS DETECTED FOR LOGICAL RECORD <i>logical record</i>. PLEASE INFORM YOUR SYSTEM PROGRAMMER.
----------------	---

Explanation

An incorrect request was returned by the logical record processing exit 04 or 14.

System action

The original record is processed.

Operator response

No response is necessary.

System programmer response

Verify that recent changes did not cause an error in the logical record processing exit.

User response

Inform your system programmer that this error occurred.

APS022I	INCORRECT PSF INVOCATION.
----------------	----------------------------------

Explanation

PSF was incorrectly started with an MVS™ START command entered from a system console.

System action

PSF ends without establishing communication with the Job Entry Subsystem (JES).

Operator response

Use the appropriate JES command to start the device or writer. For the appropriate JES command, see the JES commands publication for the level of JES you are using.

System programmer response

No response is necessary.

User response

No response is necessary.

APS023I **FSA INITIALIZATION WAS
TERMINATED BY PSF
subcomponent.**

Explanation

The PSF Functional Subsystem Application (FSA) initialization was stopped by the PSF subcomponent identified in this message.

System action

The device does not start.

Operator response

To determine an appropriate response, see the specific console message that is issued by the PSF subcomponent that failed to initialize.

System programmer response

To determine an appropriate response, see the specific console message that is issued by the PSF subcomponent that failed to initialize.

User response

No response is necessary.

APS024I **STOP FSA WITH ABEND
REQUESTED.**

Explanation

PSF received the functional subsystem interface (FSI) abend request to stop the functional subsystem application (FSA).

System action

PSF abends the FSA.

Operator response

Inform your system programmer that this error occurred.

System programmer response

To determine an appropriate action, check the MVS console for any JES commands that are issued to the FSS that might cause JES to request a dump of the FSS. Save the memory dump for IBM Support Center use.

User response

No response is necessary.

APS025I **STOP FSS WITH ABEND
REQUESTED.**

Explanation

PSF received the functional subsystem interface (FSI) abend request to stop the functional subsystem (FSS).

System action

PSF abends the PSF FSS address space.

Operator response

Inform your system programmer that this error occurred.

System programmer response

To determine an appropriate action, check the MVS console for any JES commands that are issued to the FSS that might cause JES to request a dump of the FSS. Save the memory dump for IBM Support Center use.

User response

No response is necessary.

APS026I **{HASPxxxx (JES2 message text) |
IATxxxx (JES3 message text)}**

Explanation

This message is a null message. It contains no text that is generated by PSF; it is only a carrier for a JES2 message or a JES3 message. If the operator entered a Forward Space command, processing of the data set might be stopped while forward spacing, in which case no end messages are printed.

System action

This message is only for information.

Operator response

Inform your system programmer that this error occurred.

System programmer response

For more information, see the JES messages publication for the level of JES you are using.

User response

The printed output might be acceptable. If any pages were duplicated or skipped, you might want to resubmit the print request. If the error persists, consult your system programmer.

APS030I PRINT DATA SET DISPOSITION NOT CHANGED AS REQUESTED BY PRERROR BECAUSE *reason*.

Explanation

Processing of the output data set was stopped because of an error, but the disposition of the data set was not changed for one of the following reasons:

- HONOR PRERROR IS NOT INITIALIZED. The Error disposition supported option in the Printer Inventory does not specify Yes or the PRINTDEV initialization statement for this printer does not specify PRERROR=HONOR.
- A PSF EXIT REQUESTED THE DATA SET BE HELD. PSF installation exit 6 or 7 specified that the data set is to be held.
- MANDATORY PRINT LABELING IS IN EFFECT. The RACF® (Resource Access Control Facility) class PSFMPL is active on the system.

System action

The default disposition for the error is taken, or, if an exit requested it, the data set is held.

Operator response

No response is necessary.

System programmer response

If users are to be allowed to set the error disposition, set Error disposition support to Yes in the Printer Inventory or add PRERROR=HONOR on the PSF PRINTDEV statement for the printer.

User response

If honor PRERROR is not initialized, ask your system programmer to initialize it.

APS031I AN I/O ERROR WAS DETECTED WHILE READING THE DATA SET FROM THE JES SPOOL. RESUBMIT THE JOB.

Explanation

An I/O error was detected while the data set was being read from the Job Entry Subsystem (JES) spool.

System action

Processing of the data set ends.

Operator response

Request that the user resubmit the job.

System programmer response

To determine an appropriate action, see the JES I/O error message.

User response

Resubmit the print request.

APS032I A SPANNED RECORD LONGER THAN THE MAXIMUM ALLOWABLE RECORD LENGTH WAS DETECTED. PLEASE INFORM YOUR SYSTEM PROGRAMMER.

Explanation

PSF detected a Job Entry Subsystem (JES) record too long to process. The maximum length for a PSF record is 32,768 bytes.

System action

The partial record is processed, and processing for the current data set ends. The data set is requeued and held.

Operator response

After the error is corrected, release the data set. For the appropriate command to release the data set, see

the JES commands publication for the level of JES you are using.

System programmer response

Ensure that the maximum record length for JES does not exceed the maximum record length for PSF.

User response

Inform your system programmer that this error occurred.

APS033I A NONSPANNED RECORD OR THE START OF ANOTHER SPANNED RECORD WAS DETECTED WHILE A SPANNED RECORD WAS BEING COMPOSED. PLEASE INFORM YOUR SYSTEM PROGRAMMER.

Explanation

While PSF was composing a spanned record, it detected the start of another spanned or nonspanned record. The error is caused by the Job Entry Subsystem (JES).

System action

The partial record is processed, and processing for the current data set ends. The data set is requeued and held.

Operator response

After the error is corrected, release the data set. For the appropriate command to release the data set, see the JES commands publication for the level of JES you are using.

System programmer response

To determine an appropriate action, see the JES I/O error message.

User response

Inform your system programmer that this error occurred.

APS034I THE END OF THE DATA SET WAS REACHED BEFORE THE END OF A SPANNED RECORD WAS FOUND. PLEASE INFORM YOUR SYSTEM PROGRAMMER.

Explanation

PSF reached the end of the data set without finding the end of a spanned record. The error is caused by the Job Entry Subsystem (JES).

System action

The partial record is processed. The data set is requeued and held.

Operator response

After the error is corrected, release the data set. For the appropriate command to release the data set, see the JES commands publication for the level of JES you are using.

System programmer response

To determine an appropriate action, see the JES I/O error message.

User response

Inform your system programmer that this error occurred.

APS035I THE FIRST SPANNED RECORD PROCESSED WAS NOT THE BEGINNING OF A SPANNED RECORD. PLEASE INFORM YOUR SYSTEM PROGRAMMER.

Explanation

The first spanned record in the data set is not the beginning of a spanned record.

System action

The partial spanned record is processed. Processing of the current data set ends. The data set is requeued and held.

Operator response

After the error is corrected, release the data set. For the appropriate command to release the data set, see the JES commands publication for the level of JES you are using.

System programmer response

To determine an appropriate action, see the Job Entry Subsystem (JES) I/O error message.

User response

Inform your system programmer that this error occurred.

APS036I **END OF THE DATA SET WAS REACHED BEFORE A NON-RESOURCE RECORD WAS FOUND.**

Explanation

PSF reached the end of a data set before it found a nonresource record that contains data rather than a resource. A nonresource record is a record from a line-data or Mixed Object Document Content Architecture (MO:DCA) data file.

System action

Processing for the current data set is ended.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Ensure that the data set contains line-data records or MO:DCA data, and then resubmit the job.

APS037I **RESTARTED DATA SET IS EMPTY.**

Explanation

PSF attempted to restart a data set from a Job Entry Subsystem (JES) checkpoint, but the data set was empty.

System action

Processing for the data set is ended.

Operator response

Inform your system programmer that this error occurred.

System programmer response

If you feel this message was issued in error, create a PSF dump on this message, and ensure that an internal PSF trace is in the dump (TRACE=YES) (DUMP=,APSXXXXI).

User response

No response is necessary.

APS038I **RESTART PROCESSING IS BEGINNING FOR THE ABEND REPORTED ABOVE.**

Explanation

An abend occurred that PSF considers a candidate for restart processing. The abend condition is described in the preceding APS050I message.

System action

All active data sets are released, and PSF attempts to restart. PSF does not produce a memory dump unless the abend code was specified on the Dump: Message ID option in the Printer Inventory or the DUMP parameter of the PRINTDEV statement in the PSF startup procedure. If the restart is successful, message APS057I is issued, and PSF restarts by requesting a new data set from JES. If the restart is unsuccessful, PSF issues message APS053I and then ends.

Operator response

Inform your system programmer that this error occurred.

System programmer response

If the restart is successful, but the abend condition is frequently producing a restart, you can specify the abend reason code on the DUMP parameter in the PSF startup procedure to generate a conditional dump. For more information about the DUMP parameter, see [*PSF for z/OS: Diagnosis*](#).

User response

No response is necessary.

APS039I **DUE TO AN I/O ERROR ON THIS DATA SET OR AN OPERATOR COMMAND, REPOSITIONING OR AN INTERRUPT FUNCTION MAY HAVE CAUSED PAGE *nnn* TO BE DUPLICATED.**

Explanation

An I/O error occurred previously on this data set, or an operator command was entered at a time when insufficient information was available to reposition accurately. Repositioning was done, and either it was successful, or a page was duplicated.

Page *nnn* is a relative page number from the beginning of your data set. The relative page number includes header pages, message pages, and multiple transmissions of the data set.

System action

Processing of the data set continues. This message was issued to the JES operator console and was appended to the message data set.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Examine your output for duplicate pages.

**APS040I DATA SET RESTART PROCESSING
 WAS TERMINATED IN DIRECT-
 PRINTING MODE.**

Explanation

PSF attempted to restart the current data set while the printer was directly attached. Restart processing is not supported when a printer is being used in direct-printing mode.

System action

Processing for the current data set ends.

Operator response

Examine the accompanying PSF messages, if any, to determine why PSF attempted to restart the data set.

System programmer response

Examine the accompanying PSF messages, if any, to determine why PSF attempted to restart the data set.

User response

No response is necessary.

**APS041I STOP DEVICE WITH ABEND
 REQUESTED.**

Explanation

PSF received the functional subsystem interface (FSI) abend request to stop the PSF Functional Subsystem Application (FSA).

System action

PSF abends the FSA.

Operator response

Inform your system programmer that this error occurred.

System programmer response

To determine an appropriate action, check the MVS console for any JES commands that are issued to the FSA that might cause JES to request a dump of the FSA. Save the memory dump for IBM Support Center use.

User response

No response is necessary.

**APS042I SDUMP CREATED A PARTIAL
 DUMP.**

Explanation

The PSF ESTAE routine received a return code of X'04' after it returned from the system's SVC dump routine. This indicates that a partial memory dump was created.

System action

Abend processing continues.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Verify your SVC dump method, and then see [z/OS MVS Diagnosis: Tools and Service Aids](#).

User response

No response is necessary.

**APS043I DUMP WAS NOT TAKEN FOR STOP
 ORDER.**

Explanation

A Stop Device functional subsystem interface (FSI) order with the dump option was received. PSF received a return code of X'08' from the system's SVC dump routine.

System action

Device termination continues.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Verify your SVC dump method, and then see [z/OS MVS Diagnosis: Tools and Service Aids](#).

User response

No response is necessary.

APS044I **SDUMP WAS UNSUCCESSFUL.**
 REASON CODE=reason code.

Explanation

The PSF ESTAE routine received a return code of X'08' from the system's SVC dump routine. This indicates that an SVC dump was unsuccessful.

System action

Abend processing continues.

Operator response

Inform your system programmer that this error occurred.

System programmer response

If you receive reason code '0B'X, Dump Analysis Elimination (DAE) suppressed the memory dump because a dump of the same nature occurred earlier. Check your organization's DAE data set for a symptom string that matches the dump that was created.

If you receive reason code '05'X, verify your SVC dump method, and then see [z/OS MVS Diagnosis: Tools and Service Aids](#).

User response

No response is necessary.

APS045I **DEVICE device (address) COULD**
 NOT BE ALLOCATED. DYNALLOC
 ERROR CODE = error code AND
 INFORMATION REASON CODE =
 reason code.

Explanation

PSF attempted to dynamically allocate the device with the address identified in this message. PSF failed for one of the following reasons:

- The device was already allocated (DYNALLOC error code = X'0214').

- The operator denied the device allocation (DYNALLOC error code = X'0484').
- The specified ddname was already allocated (DYNALLOC error code = X'0410').

System action

The printer does not start.

Operator response

Before the device or writer is started, verify that the device is not allocated to another address space. If the allocation was denied by the operator, ensure that the device or writer that requires this device is not started. To interpret the DYNALLOC error code, see [z/OS MVS Programming: Authorized Assembler Services Guide](#).

System programmer response

No response is necessary.

User response

No response is necessary.

APS047I **device (address) SMF TYPE 6**
 RECORD WAS NOT WRITTEN,
 RETURN CODE 'nn' WAS RECEIVED
 FROM SMFWTM MACRO.

Explanation

PSF attempted to write a Systems Management Facility (SMF) Type 6 record by use of the SMFWTM macro. The SMFWTM macro return code indicated that the SMF Type 6 record was not written.

System action

If mandatory print labeling is active, PSF abends. Otherwise, processing continues.

Operator response

Inform your system programmer that this error occurred.

System programmer response

To interpret the SMFWTM macro return codes, see the System Management Facility publication for your operating system.

User response

No response is necessary.

**APS049I NO TIME-OF-DAY OR DATE
VALUES WERE INSERTED IN THE
SMF TYPE 6 RECORD.**

Explanation

During the processing of the SMF Type 6 record, a nonzero return code was received when the time of day and the date were being established (SVC 11).

System action

If mandatory print labeling is active, PSF abends. Otherwise, processing continues, and the record is written without these values.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Determine the cause of the SVC 11 failure.

User response

No response is necessary.

**APS050I SYSTEM COMPLETION CODE
system completion code, PSF
ABEND REASON CODE *reason
code*, HAS BEEN DETECTED BY
estae name, ISSUED BY MODULE
abending module name.**

Explanation

The PSF ESTAE routine detected a PSF abend condition.

System action

Depending on the error condition, PSF automatically restarts the printer, stops processing for the printer, or stops the PSF address space. A subsequent message from PSF tells the operator which action was taken.

An ESTAE routine creates an SVC dump, unless a dump was provided by an earlier routine or the functional subsystem interface (FSI) requested that no dump is created.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Examine the accompanying PSF message to determine the appropriate response.

To interpret system completion codes X'024', X'027', and X'0A6', see Chapter 2, "System completion codes and PSF abend reason codes," on page 613.

User response

Inform your system programmer that this error occurred.

APS051I PSF ABNORMAL TERMINATION.

Explanation

The PSF ESTAE issued this message as part of processing a PSF abend condition. Message APS050I or APS055I is also issued as part of the PSF abend processing. The ESTAE routine provided an SVC dump.

System action

Abend processing continues.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Use the information that is provided in message APS050I or APS055I to determine an appropriate response. Save the memory dump for IBM Support Center use.

User response

Inform your system programmer that this error occurred.

**APS052I MANDATORY PRINT LABELING IS
NOT SUPPORTED BY JES.**

Explanation

The installed version of the Job Entry Subsystem (JES) does not support mandatory print labeling.

System action

The data set that was processed at the time of the error was returned to the Job Entry Subsystem (JES) to place on the HOLD queue.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Install the correct release of JES if mandatory print labeling is required.

User response

No response is necessary.

APS053I ABEND RESTART PROCESSING HAS FAILED. ABEND PROCESSING FOR THE ORIGINAL ABEND WILL BEGIN.

Explanation

PSF was unable to restart following the abend reported in the previous APS050I message. The original abend is processed, and a memory dump is created.

System action

Abend processing continues.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Use the information in the APS050I message that reported the original abend to diagnose the problem.

User response

No response is necessary.

APS054I PSF HAS COMPLETED AN SDUMP.

Explanation

PSF successfully completed an SVC dump to a SYS1.DUMPnn data set.

System action

Abend processing continues.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Save the memory dump for IBM Support Center use.

User response

No response is necessary.

APS055I PSF ESTAE CANNOT EVALUATE SYSTEM COMPLETION CODE *system completion code* ISSUED BY MODULE *abending module name*. ABNORMAL TERMINATION PROCESSING WILL CONTINUE.

Explanation

The PSF ESTAE routine is unable to continue, for one of the following reasons:

- The abend reason code was not issued by PSF.
- The abend reason code was not stored in the function subsystem (FSB) control block.
- The FSB control-block address was incorrect.

System action

Abend processing continues.

Operator response

Inform your system programmer that this error occurred.

System programmer response

The contents of the registers at the time of the abend are provided in the SVC dump and register 15 might contain a PSF abend reason code. Save the dump for IBM Support Center use. To interpret the dump, see *PSF for z/OS: Diagnosis*. To interpret the system completion code, see the publication that contains system messages for your operating system.

User response

Inform your system programmer that this error occurred.

APS056I SYSTEM-DEFINED USER PRINTABLE AREA WAS REQUESTED ON A NONSECURE PRINTER.

Explanation

SYSAREA = YES was specified for a printer that does not support security functions. This JCL parameter was on the OUTPUT statement for the job.

System action

PSF releases the current data set back to JES and requests that it is held by the system.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

If security page labeling is required, submit the print request to a printer that supports security functions. If security labeling is not required, change the OUTPUT JCL statement to remove the SYSAREA keyword.

APS057I ABEND RESTART PROCESSING HAS COMPLETED.

Explanation

PSF successfully completed abend restart processing and continues processing. A new job is requested from JES.

System action

Processing continues.

Operator response

The output from the data set that was printing when the abend occurred might need to be discarded, because the entire data set might be printed again after the restart. However, the data set that was printing when the abend occurred is not necessarily the next one to print after PSF restarts.

System programmer response

No response is necessary.

User response

No response is necessary.

APS058I THE CURRENT JES STATUS OF PRINTER *printer name* IS 'NOT READY'. PSF IS ENDING THE IPDS SESSION WITH THE PRINTER. PRINTER STATUS MIGHT BE INACCURATE UNTIL A NEW IPDS SESSION IS STARTED. THE DEVICE MIGHT NEED TO BE MADE 'READY'.

Explanation

PSF received a "Not Ready" status from the printer as it was ending the IPDS session for one of these reasons:

- PSF received a STOP device order from JES.
- The disconnect interval (DISCINTV) expired.
- The release interval (RELINTV) expired.

Until the printer is made "Ready" and a new session is started with the printer, device status queries might not reflect the true status of the printer.

System action

PSF does one of these:

- Ends the session with the printer if JES issues a STOP device order.
- Waits for more work if the disconnect interval expired.
- Waits for the acquire interval to expire.

Operator response

The status of this printer might not be accurate until the device is made "Ready" and PSF starts a new session.

System programmer response

None.

User response

None.

APS060I MANDATORY PRINT LABELING IS NOT AVAILABLE UNDER DIRECT-PRINTING MODE.

Explanation

Mandatory Print Labeling is requested in direct-printing mode, but it is not allowed in that mode.

System action

PSF issues message APS005I and then abends.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Deactivate class PSFMPL by using the Resource Access Control Facility (RACF). For more information, see the RACF publications.

User response

Inform your system programmer that this error occurred.

APS061I SYSTEM ACTION TAKEN: THE ERRORS LISTED PREVENTED PROCESSING OF THE JOB. ALL

DATA SETS IN THE JOB WILL BE HELD.

Explanation

- While processing the job, PSF or AFP Download Plus detected an error that makes processing the job in a secure environment impossible.

System action

- PSF or AFP Download Plus releases the current data set back to JES and requests that it is held by the system.

Operator response

Inform your system programmer that this error occurred.

System programmer response

To determine an appropriate response, see the specific error conditions that are described in the accompanying messages.

User response

No response is necessary.

**APS062I NODE *nodeid* IS NOT VALID—
JOB=*jobname* STEP=*stepname*
ID=*jobid* ON *system-id*.**

Explanation

The message identifies a print request that contains a node that is specified with the NOTIFY keyword. However, the system does not recognize the node as valid.

System action

The print request was processed, but the user is not notified that processing is complete because the node is identified as not valid.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Notify the individuals directly that processing of the print request is completed. If the print request is to be resubmitted for printing, correct the incorrect node ID.

**APS063I PRINT REQUEST COMPLETED—
JOB=*jobname* STEP=*jobstep*
ID=*jobid* AT *system-id*.**

Explanation

Processing of the print request that is identified in the message completed successfully. The print-job submitter specified that this message is sent to the user IDs specified in the NOTIFY keyword in the JCL for the print request. When the printer is connected to PSF by use of the distributed print function (DPF) of PSF, this message indicates only that PSF completed its processing of the print request. The final disposition of the print request is controlled by DPF.

System action

PSF continues processing.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

The printed output is available at the printer, unless the printer is connected to PSF by use of DPF.

**APS064I PRINT REQUEST CANCELED—
JOB=*jobname* STEP=*jobstep*
ID=*jobid* AT *system-id*.**

Explanation

Processing of the print request that is identified in the message is canceled. The print-job submitter specified that this message is sent to the user IDs specified in the NOTIFY keyword in the JCL for the print request.

System action

PSF continues processing with the next print request.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Examine the PSF messages in the printed output to determine why the print request was canceled.

**APS065I PRINT REQUEST INTERRUPTED—
JOB=*jobname* STEP=*jobstep*
ID=*jobid* AT *system-id***

Explanation

Processing of the print request that is identified in the message is interrupted by the operator. The print-job submitter specified that this message is sent to the user IDs specified in the NOTIFY keyword in the JCL for the print request.

System action

The print request was returned to the Job Entry Subsystem (JES) and can be restarted by the operator.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Examine the PSF messages in the printed output to determine why the print request was interrupted, or consult your system operator.

**APS066I PRINT REQUEST UNSUCCESSFUL
— JOB=*jobname* STEP=*jobstep*
ID=*jobid* AT *system-id*.**

Explanation

Processing of the print request that is identified in the message completed unsuccessfully. The print-job submitter specified that this message is sent to the user IDs specified in the NOTIFY keyword in the JCL for the print request.

System action

See the accompanying messages for the system action that was taken.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Examine the PSF messages in the printed output to determine the cause of the error.

**APS067I PRINT REQUEST MARKED
UNPRINTABLE—JOB=*jobname*
STEP=*jobstep* ID=*jobid* AT *system-
id*.**

Explanation

PSF processing of the print request that is identified in the message determined that the data set is not printable. The print-job submitter specified that this message is sent to the user IDs specified in the NOTIFY keyword in the JCL for the print request.

System action

The print request was returned to the Job Entry Subsystem (JES) to be placed on the HOLD queue with a PSF message ID.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Examine the PSF messages in the printed output to determine why the print request was unprintable.

**APS068I SUBMITTER *submitter-id* NOT
AUTHORIZED TO SEND JOB
STATUS TO USERID=*user ID* ON
system-id.**

Explanation

The submitter of this job is not authorized to send the message to the user on the receiving system.

System action

PSF, Download for z/OS, or AFP Download Plus continues processing the notify request.

Operator response

No response is necessary.

System programmer response

Determine whether the user can be authorized to send the message (defined in the RACF SMESSEGE class). If the user can be authorized, use RACF to give the user the needed authorization. For information about using RACF, see *z/OS Security Server RACF Security Administrator's Guide* for your operating system.

User response

Inform your system programmer that this error occurred.

APS069I **NOTIFY ERROR *decimal-code* FOR
USER *user ID*— JOB=*jobname*
STEP=*stepname* ID=*jobid* AT
system-id.**

Explanation

A notify request was unsuccessful. The decimal code indicates the cause of the failure:

- 04** PSF logic error. Message truncated.
- 08** Exit canceled notify request. A system installation exit (not a PSF exit) canceled the notify request. Inform your system programmer that this error occurred.
- 12** PSF logic error. No user ID specified.
- 20** PSF logic error. Notify extension ID is not valid.
- 24** PSF logic error. Notify version is not valid.
- 28** No storage for request. The Job Entry Subsystem (JES) cannot obtain enough storage in subpool 231 to satisfy the request. The system programmer must determine why insufficient storage is available.
- 36** PSF logic error. Error in message specification.

System action

PSF continues processing the notify request.

Operator response

No response is necessary.

System programmer response

For codes “08” and “28”, see the explanation for the code. For all other codes, follow the procedures described in *PSF for z/OS: Diagnosis* before you consult with the IBM Support Center.

User response

Inform your system programmer that this error occurred.

APS070I **NOTIFY ERROR *decimal-code* FOR
USER *user ID*— JOB=*jobname***

**STEP=*stepname* ID=*jobid* AT
system-id.**

Explanation

A notify request was unsuccessful. The decimal code indicates the cause of the failure:

- 12** PSF logic error. No notify extension was found.

System action

PSF continues processing the notify request.

Operator response

No response is necessary.

System programmer response

Follow the procedures described in *PSF for z/OS: Diagnosis* before you consult with the IBM Support Center.

User response

Inform your system programmer that this error occurred.

APS071I **NOTIFY ERROR *decimal-code* FOR
USER *user ID*— JOB=*jobname*
STEP=*stepname* ID=*jobid* AT
system-id.**

Explanation

A notify request was unsuccessful. The decimal code indicates the cause of the failure:

- 04** PSF logic error. Subsystem does not support this function.
- 08** Subsystem exists, but is not up. Restart the Job Entry Subsystem (JES).
- 12** PSF logic error. Subsystem does not exist.
- 16** Function not completed; disastrous error. Determine cause of error from dump.
- 20** PSF logic error. Logical error (incorrect subsystem option block [SSOB] format, incorrect length, or some other logical error).

System action

PSF continues processing the notify request.

Operator response

No response is necessary.

System programmer response

For codes “08” and “16”, see the explanation for the code. For all other codes, follow the procedures described in *PSF for z/OS: Diagnosis* before you consult with the IBM Support Center.

User response

Inform your system programmer that this error occurred.

**APS072I CONSULT YOUR SYSTEM
PROGRAMMER FOR ASSISTANCE.**

Explanation

Resolving the error that is described by the preceding message requires the assistance of your system programmer.

System action

PSF continues processing the notify request.

Operator response

No response is necessary.

System programmer response

See the error codes in the preceding message.

User response

Consult your system programmer for assistance. Inform your system programmer that this error occurred.

**APS073I THE CHECKPOINT AREA FOR THE
DATA SET THAT WAS TO RESTART
FROM A CHECKPOINT DID NOT
CONTAIN THE REQUIRED
CONDITIONAL PROCESSING
INFORMATION. THE DATA SET
WAS RESTARTED FROM THE
BEGINNING.**

Explanation

The conditional processing information that is used in printing this data set was too large to fit into the checkpoint record that PSF previously wrote to JES. This can happen when the page definition specifies CONDITION commands by use of the WHEN CHANGE parameter, which causes large amounts of data to be tested. If too many of the WHEN CHANGE type of

conditions are specified, the checkpoint record becomes too large to write to JES. PSF must then write the checkpoint record to JES without any of the conditional processing information.

Because this data set needs the conditional processing information to restart from a checkpoint, but the JES checkpoint record that is given back to PSF does not contain this information, PSF must restart this data set from the beginning. This allows the conditional processing information to be rebuilt, and the data set prints correctly.

System action

PSF issues this message to the operator console and the message data set, and continues processing from the beginning of the data set.

Operator response

If you know which page the printing must restart on, issue a forward space command.

System programmer response

No response is necessary.

User response

Examine your output for duplicate pages.

**APS074I AN INTERRUPT MESSAGE PAGE
WOULD HAVE BEEN GENERATED
BUT IT HAS BEEN SUPPRESSED.**

Explanation

The interrupt message page that PSF inserts in your printed output was suppressed because the Printer Inventory or Exit 7 requested that no interrupt message page be printed.

System action

Processing continues without printing the interrupt message page.

Operator response

No response is necessary.

System programmer response

Ensure that the target device is appropriate. For microfilm devices, interrupt message pages are suppressed regardless of what functions were requested in PSF Exit 7 or the Printer Inventory.

For non-microfilm devices, ensure that the Interrupt message page value is set correctly in the Printer Inventory or XTP7IPSU is set correctly by Exit 7.

User response

If you feel that this message was issued incorrectly, ask your system programmer to check the target device, the Printer Inventory and Exit 7 for correctness.

**APS075I UNABLE TO ALLOCATE STORAGE
FOR MESSAGE DATASET RE-
DIRECTION.**

Explanation

Virtual storage cannot be acquired above the line for all required message data set redirection control blocks.

System action

The user data set completed printing, but the associated message data set was lost. The data set was released as incomplete for future reprinting. The FSA printing the data set was stopped with abend reason code 0335.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Increase the REGION parameter on the procedure that is used to start PSF.

User response

Inform your system programmer that this error occurred.

**APS076I DYNAMIC ALLOCATION FUNCTION
FOR THE SYSOUT MESSAGE
DATASET WAS UNSUCCESSFUL—
RETURN CODE xxxx, REASON
CODE xxxx.**

Explanation

An unsuccessful attempt was made to use an SVC 99 instruction to do the dynamic allocation of the redirected message data set.

System action

The user data set completed printing, but the associated message data set was lost. The data set

was released as incomplete for future reprinting. The FSA printing the data set was stopped with abend reason code 0335.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Use the return code and reason code to determine the cause of the error and an appropriate response. For information about the SVC 99 return and reason codes, see *z/OS MVS Diagnosis: Tools and Service Aids*.

User response

Inform your system programmer that this error occurred.

**APS077I OPENING OF THE SYSOUT
MESSAGE DATASET WAS
UNSUCCESSFUL.**

Explanation

An OPEN macro, which results in an SVC 19, was issued to open the redirected message data set for output. After PSF returned from the OPEN macro, it discovered that the data control block (DCB) was not opened.

System action

The user data set completed printing, but the associated message data set was lost. The data set was released as incomplete for future reprinting. The FSA printing the data set was stopped with abend reason code 0335.

Operator response

Inform your system programmer that this error occurred.

System programmer response

See the additional console messages associated with this error.

User response

Inform your system programmer that this error occurred.

**APS078I CLOSING OF THE SYSOUT
MESSAGE DATASET WAS
UNSUCCESSFUL.**

Explanation

A CLOSE macro, which results in an SVC 20, was issued to close the redirected message data set. After PSF returned from the CLOSE macro, it discovered that the data control block (DCB) was not closed.

System action

The user data set completed printing, but the associated message data set was lost. The data set was released as incomplete for future reprinting. The FSA printing the data set was stopped with abend reason code 0335.

Operator response

Inform your system programmer that this error occurred.

System programmer response

See the additional console messages associated with this error.

User response

Inform your system programmer that this error occurred.

APS079I	MESSAGE DATASET REDIRECTION WAS REQUESTED BUT ALL REQUIRED PREREQUISITES WERE NOT MET. THE REQUEST WAS SUPPRESSED.
----------------	---

Explanation

Message data set redirection was requested by specifying PIMSG=NO on the OUTPUT statement for the message data set in the startup procedure, but one of these occurred:

- The operating system does not support the functions required for message data set redirection.
- Message data set redirection was requested while using direct-printing mode.

System action

The request for message data redirection was ignored. Any error messages were printed with the associated user data set.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Either correct the problem that is described by the Explanation section, or do not request message data set redirection (do not specify PIMSG on the message data set OUTPUT statement in the startup procedure or specify PIMSG=YES).

User response

No response is necessary.

APS080I	INHIBIT RECOVERY WAS IGNORED BECAUSE IT WAS NOT SPECIFIED FOR THE FIRST DATA SET OF THE JOB.
----------------	---

Explanation

XTP7IHIB was set to off for the first data set of the job, but PSF Exit 7 set it on for a subsequent step of the job. PSF must do the same level of recovery for the entire job.

System action

Recovery is allowed for the entire job.

Operator response

No response is necessary.

System programmer response

Change PSF Exit 7 so that it sets XTP7IHIB the same way for each data set of a job.

User response

Notify your system programmer.

APS081I	RECOVERY IS INHIBITED BECAUSE IT WAS SPECIFIED FOR THE FIRST DATA SET OF THE JOB.
----------------	--

Explanation

PSF Exit 7 set XTP7IHIB to on for the first data set of the job but not for a subsequent step of the job. PSF must do the same level of recovery for the entire job.

System action

Recovery is inhibited for the entire job.

Operator response

No response is necessary.

System programmer response

Change PSF Exit 7 so that it sets XTP7IHIB the same way for each data set of a job.

User response

Notify your system programmer.

APS082I	FSI GETREC FAILED. GLRFLGS1= flags.
----------------	--

Explanation

A get record request on the Functional Subsystem Interface (FSI) was rejected.

System action

PSF ends with system completion code 024 and an abend reason code 0130.

Operator response

Notify your system programmer.

System programmer response

Contact IBM service and supply the GLRFLGS1 indicated.

User response

Notify your system programmer.

APS083I	THE CHECKPOINT AREA FOR THE DATA SET THAT WAS TO RESTART FROM A CHECKPOINT DID NOT CONTAIN THE REQUIRED SHEET COLLECTION FINISHING INFORMATION AT THE COPY GROUP LEVEL. THE DATA SET WAS RESTARTED FROM THE BEGINNING.
----------------	---

Explanation

The information for the sheet collection finishing at the copy group level, which is used in printing this data set, was too large to fit into the checkpoint record that PSF previously wrote to JES. This can happen when too many finishing operations are nested inside a copy group and the checkpoint record becomes too large to write to JES. PSF must then write the checkpoint record to JES without any of this finishing information.

Because this data set needs the sheet collection finishing information at the copy group level to restart from a checkpoint, but the JES checkpoint record that is given back to PSF does not contain this information, PSF must restart this data set from the beginning. The

finishing information is then rebuilt, and the data set prints correctly.

System action

PSF issues this message to the operator console and the message data set, and continues processing from the beginning of the data set.

Operator response

If you know which page the printing must restart on, issue a forward space command.

System programmer response

No response is necessary.

User response

Examine your output for unfinished and duplicate pages.

APS084I	THE UNICODE VALUE IN THE PARM= KEYWORD OF THE EXEC JCL STATEMENT IS NOT VALID. IT MUST BE THE CHARACTERS UNICODE OR BE OMITTED. PROCESSING CONTINUES WITH UNICODE SUPPORT.
----------------	---

Explanation

The UNICODE value in the PARM keyword of the EXEC JCL statement is no longer used; however, if it is specified, it must be UNICODE. If not specified, PSF or AFP Download Plus is always started with Unicode support.

System action

PSF or AFP Download Plus continues processing with Unicode support.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Correct the PARM information in the JCL. For the correct format of the EXEC statement, see *PSF for z/OS: Diagnosis* or *PSF for z/OS: AFP Download Plus*.

User response

No response is necessary.

APS085I	THE trace_type VALUE IN THE PARM= KEYWORD OF THE EXEC
----------------	--

JCL STATEMENT IS NOT VALID. IT MUST BE FULL, SYNC, INTR, LIMIT, OR IPDS. PROCESSING CONTINUES USING THE INTR VALUE.

Explanation

A value in the PARM keyword of the EXEC JCL statement specifies the type of tracing to be done. The value can be FULL, INTR, IPDS, LIMIT, or SYNC.

System action

PSF or one of its features continues processing and uses the default value of INTR to produce an internal trace.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Correct the PARM information in the JCL. For the correct format of the EXEC statement, see *PSF for z/OS: Diagnosis*, *PSF for z/OS: AFP Download Plus*, or *PSF for z/OS: Download for z/OS*.

User response

No response is necessary.

APS086I THE prompt VALUE IN THE PARM= KEYWORD OF THE EXEC JCL STATEMENT IS NOT VALID. IT MUST BE PROMPT OR NOPROMPT. PROCESSING CONTINUES USING THE NOPROMPT VALUE.

Explanation

A value in the PARM keyword of the EXEC JCL statement indicates whether an operator response is required to initialize the operator interface for PSF or a PSF feature. The value can be PROMPT or NOPROMPT.

System action

PSF or one of its features continues processing and uses the default value of NOPROMPT.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Correct the PARM information in the JCL. For the correct format of the EXEC statement, see *PSF for z/OS: Diagnosis*, *PSF for z/OS: AFP Download Plus*, or *PSF for z/OS: Download for z/OS*.

User response

No response is necessary.

APS087I THE trace_size VALUE IN THE PARM= KEYWORD OF THE EXEC JCL STATEMENT IS NOT VALID. IT MUST BE AN INTEGER IN THE RANGE OF 1 TO 999. A VALUE OF nnn WILL BE USED.

Explanation

A value in the PARM keyword of the EXEC JCL statement indicates how much memory is allocated for an internal trace. Valid values are 1 - 999.

System action

PSF or one of its features continues processing and uses one of these values to determine how much memory is allocated:

- If the value is not an integer or is less than 1, the default value of 32 is used.
- If the value is an integer greater than 999, the value of 999 is used.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Correct the PARM information in the JCL. For the correct format of the EXEC statement, see *PSF for z/OS: Diagnosis*, *PSF for z/OS: AFP Download Plus*, or *PSF for z/OS: Download for z/OS*.

User response

No response is necessary.

APS088I THE tcpip_name VALUE IN THE PARM= KEYWORD OF THE EXEC JCL STATEMENT IS NOT VALID. IT MUST BE 1 TO 8 CHARACTERS IN LENGTH. A VALUE OF TCPIP WILL BE USED.

Explanation

A value in the PARM keyword of the EXEC JCL statement specifies the name of a TCP/IP address space; however, it was greater than 8 characters in length.

System action

PSF or AFP Download Plus continues processing and uses the default name of TCPIP.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Correct the PARM information in the JCL. For the correct format of the EXEC statement, see [PSF for z/OS: Diagnosis](#) or [PSF for z/OS: AFP Download Plus](#).

User response

No response is necessary.

APS089I	THE NSTddname VALUE IN THE PARM= KEYWORD OF THE EXEC JCL STATEMENT IS NOT VALID. IT MUST BE 1 TO 8 CHARACTERS IN LENGTH. PSF HAS BEEN STARTED WITHOUT NST SUBTASK TRACING.
----------------	---

Explanation

A value in the PARM keyword of the EXEC JCL statement specifies the PSF Notify Subtask Trace (NST) data set name or Download for z/OS FSS trace output data set name (*FSSddname*) that is defined in a DD statement. The value must be 1 - 8 characters for PSF or AFP Download Plus to be started with NST tracing, or Download for z/OS to be started with FSS tracing.

System action

PSF, AFP Download Plus, or Download for z/OS continues processing without activating tracing.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Correct the PARM information in the JCL. For the correct format of the EXEC statement, see [PSF for](#)

[z/OS: Diagnosis, PSF for z/OS: AFP Download Plus](#), or [PSF for z/OS: Download for z/OS](#).

User response

No response is necessary.

APS095I	INSTALLATION EXIT 15 WILL NOT BE INVOKED.
----------------	--

Explanation

The initialization of the Download for z/OS exit routine failed because insufficient length was specified in the APSUCOM table, the APSUCOM module cannot be located, or a BLDL macro failed. Download for z/OS detected this error. See [PSF for z/OS: Download for z/OS](#) for more information about this feature.

System action

Processing continues without the installation exit.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Evaluate any changes that are made to the APSUCOM module (static table), to the exit routine, or to the methods used to establish the tables or routines in the system. Other messages might contain BLDL macro return and reason codes.

User response

No response is necessary.

APS096I	THE INVOCATION OF CEEPIPI TO INITIALIZE THE C ENVIRONMENT FAILED WITH RETURN CODE (return code).
----------------	---

Explanation

A nonzero return code was received from the invocation of CEEPIPI to initialize for subroutines. Return codes that are associated with this message are:

04

The function code is not valid.

08

Some of the addresses in the table were not resolved. This can occur if a LOAD failure was encountered, a routine within the table was not generated by a Language Environment[®] conforming

HLL, or a C or PL/I routine within the table was not retrievable.

12

Storage for the preinitialization environment cannot be obtained.

16

CEEPIPI was called from an active environment.

For more information about this invocation of CEEPIPI and its return codes, see [z/OS Language Environment Programming Guide](#).

System action

PSF processing ends abnormally with a system completion code 024 and abend reason code 0A57 or 0A5D.

Operator response

Inform your system programmer that this error occurred.

System programmer response

If the problem cannot be diagnosed from the return code, contact the IBM Support Center.

User response

No response is necessary.

APS097I THE INVOCATION OF CEEPIPI TO ADD A C EXIT FAILED WITH RETURN CODE (return code).

Explanation

A nonzero return code was received from the invocation of CEEPIPI to add an entry. Return codes that are associated with this message are:

04

The function code is not valid.

08

CEEPIPI was called from a Language Environment conforming routine.

12

The routine did not contain a common runtime environment PPA style prologue. The PIP table was not updated, and the *routine_entry* is set to the address of the loaded routine. This might occur for one of these reasons:

- An installation exit in assembler is given a C exit name and link-edited like an installation exit in C.
- An installation exit in assembler is named with a C exit name and is link-edited like an installation exit in assembler.

- The main function name in the C exit is not the same as the load module name.

16

The *token* is not valid.

20

The *routine_name* contains only blanks and the *routine_entry* was zero. The PIP table was not updated.

24

The *routine_name* was not found or a load failure existed. The PIP table was not updated.

28

The PIP table is full. No routine was added to the table, nor was any routine loaded by Language Environment.

For more information about this invocation of CEEPIPI and its return codes, see [z/OS Language Environment Programming Guide](#).

System action

PSF processing stops abnormally with a system completion code 024 and abend reason code 0A58 or 0A5E.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Make sure that any assembler installation exits are named correctly and are link-edited as assembler exits. Make sure that the main function name of any C installation exit is the same as the load module name. If the exits are correct and the problem cannot be diagnosed from the return code, contact the IBM Support Center.

User response

No response is necessary.

APS098I PSF INSTALLATION EXIT *exit routine* WILL NOT BE INVOKED BECAUSE THE C VERSION EXISTS AND WILL BE USED INSTEAD.

Explanation

PSF is trying to load an assembler installation exit but its C version is already loaded.

System action

Processing continues without the assembler version of the installation exit.

Operator response

Inform your system programmer that this error occurred.

System programmer response

You have both a C version and an assembler version of the same exit. If you would like to use the assembler version, delete the C version of the exit.

User response

No response is necessary.

APS099I **PSF INSTALLATION EXITS
WRITTEN IN C ARE NOT
SUPPORTED.**

Explanation

An installation exit in C is found, but the operating system version you are using does not support installation exits in C.

System action

Processing continues without the installation exits that are written in C. All assembler exits are used.

Operator response

Inform your system programmer that this error occurred.

System programmer response

If you want to use installation exits written in C, install the current version of z/OS.

User response

No response is necessary.

APS100 to APS199

APS100I **SYSTEM ACTION TAKEN:
PROCESSING OF THE CURRENT
PAGE (*current page*) WAS
STOPPED BECAUSE OF THE
ERRORS LISTED. IF *feature* WAS
UNABLE TO PROCESS THIS PAGE,
SUBSEQUENT REPOSITIONING
MAY BE INACCURATE.**

Explanation

An error was encountered that prevents further processing of the current page. Other error messages that are issued by PSF or AFP Download Plus describe the precise error condition and give additional information about the processing environment in which the error occurred.

System action

Processing of the current page ends. If the error occurred on the front side of a duplex sheet, and the front side was skipped, data that belongs on the back side of the page might be processed on the front of the sheet.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in

the PSF startup procedure. Inform your system programmer.

System programmer response

To determine an appropriate response, see the specific error conditions described in the accompanying messages.

User response

To determine an appropriate response, see the specific error conditions described in the accompanying messages.

APS101I **SYSTEM ACTION TAKEN: THE
ERRORS LISTED PREVENTED
PROCESSING OF THE *document*
type FOR JOB *print request*, STEP
step, OUTGROUP *outgroup*.**

Explanation

An error was encountered that prevents further processing of the current document that is part of the *outgroup* and *step* for the print request that is identified in this message.

If a series of asterisks (*****) is inserted in any of these identifying fields, the system cannot provide the information for that field.

Previous error messages describe the precise error condition and give additional information about the processing environment in which the error occurred.

If *document type* is DATA SET, this message is the last in a series of messages that describe the errors that stopped the processing of a user document. If *document type* is MESSAGES, this message is the last in a series at the operator's console. MESSAGES indicates that errors prevented the system from processing the error messages that were generated while the user document was being processed. If *document type* is JOB HEADER, DATA SET HEADER, or JOB TRAILER, this console message indicates that errors occurred during deferred processing of the indicated separator pages.

System action

Processing of the indicated document stops. PSF or AFP Download Plus attempts to process any data that is accumulated for the current page. If the error is in a job header or a data set header, PSF or AFP Download Plus tries to process the associated user document.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user data sets in the PSF or AFP Download Plus startup procedure. Inform your system programmer.

System programmer response

To determine an appropriate response, see the specific error conditions described in the accompanying messages.

User response

To determine an appropriate response, see the specific error conditions described in the accompanying messages.

APS102I	AN END OF FILE WAS FOUND BEFORE THE LOGICAL END OF A RESOURCE OR THE RESOURCE CONTAINED NO DATA. THE MEMBER NAME OF THE RESOURCE IS <i>member name</i>.
----------------	--

Explanation

One of these occurs:

- The end of file for a resource was found before the End-type structured field, with the result that the resource definition is incomplete.

- The resource existed as a member of a partitioned data set, but no data was found in the member.

System action

PSF stops processing the current page, and prints any data accumulated for the current page.

PSF attempts to find the end of the current page and to resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the resource, correct the error and resubmit the print request. If you created the empty partitioned member for the resource, correct the error by creating a resource that contains the structured fields for the resource type you want, and resubmit the print request. For more information about the structured fields, see *Mixed Object Document Content Architecture Reference*.

APS103I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: <i>structured field name1</i> STRUCTURED FIELD WAS FOUND WHERE <i>structured field name2</i> STRUCTURED FIELD WAS EXPECTED.
----------------	--

Explanation

structured field name1 is incorrect at the present point in the input data stream or resource. The structured field type that is expected is *structured field name2*. Either the required structured field is missing or out of sequence, or a line-data record is in the wrong place.

Subsequent error messages give additional information about the processing environment in which the error occurred.

System action

PSF stops processing the current page, and prints any data accumulated for the current page.

PSF attempts to find the end of the current page and to resume printing on the next page. If unable to find the end of the current page, PSF stops printing the data set. If the error is a result of incorrect structured fields within an inline page definition or form definition, PSF stops printing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information on the correct format of the referenced structured field. If the structured fields are in the correct order, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or resource, consult your system programmer.

APS104I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: structured field STRUCTURED FIELD IS NOT ALLOWED OR FORMS AN INCORRECT SEQUENCE.**

Explanation

The structured field that is identified in this message either is out of sequence or is not valid in an object. The record might be line data. If inline resources are used with data set header pages, multiple resource groups might be present.

System action

PSF stops processing the current page, and prints any data accumulated for the current page.

PSF attempts to find the end of the current page and to resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set. If the error is a result of incorrect structured fields within an inline resource, PSF stops printing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information on the correct format of the referenced structured field. If the structured fields are in the correct order, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or resource, consult your system programmer.

APS105I **THE ERROR REPORTED ABOVE OCCURRED IN LOGICAL RECORD NUMBER record number, WHOSE SEQUENCE NUMBER IS sequence number.**

Explanation

This message is given in addition to the message that describes the error. It identifies the specific incorrect input record. The object (if any) that contains the incorrect record is identified in either message APS108I or message APS109I, which is given after this message.

The record number that is specified is relative to the user data stream and is different for multiple transmissions of the data set. However, the record number might be inaccurate if the data set is using a page definition that does conditional processing.

The sequence number might print as NOT AVAILABLE in the message. For example, a line-data record does not have a sequence number.

System action

The printing disposition depends upon the error described in the accompanying messages.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

To determine an appropriate response, see the specific error conditions described in the accompanying messages.

User response

To determine an appropriate response, see the specific error conditions described in the accompanying messages.

APS106I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: NAME 'token name' IN Begin-type structured field DOES NOT MATCH NAME 'token name' IN End-type structured field.**

Explanation

The Token Name parameters in the Begin-type and End-type structured fields that are identified in this message do not correlate. The structured fields might be out of sequence in the input data stream.

When token names are specified, the Token Name parameters in the associated Begin-type and End-type structured fields must correlate.

System action

Processing continues, and PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APS107I **THE ERROR REPORTED ABOVE OCCURRED ON PAGE *page number* OF TRANSMISSION *transmission number*.**

Explanation

This message is issued in addition to a message that describes an error that occurred during the processing of a page or data that relates to a page.

This message identifies the page that contains the error by indicating the number of that page in the transmission. The number is not taken from any data that might be on the input page.

System action

The printing disposition depends on the error described in the accompanying messages.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

To determine an appropriate response, see the specific error conditions described in the accompanying messages.

User response

To determine an appropriate response, see the specific error conditions described in the accompanying messages.

APS108I	THE ERROR REPORTED ABOVE WAS DETECTED WITHIN OBJECT TYPE <i>object type</i> WITH TOKEN NAME <i>token name</i>.
----------------	---

Explanation

This message is issued in addition to the message that describes the error. The objects that were being processed are listed to identify the location of the error in the input data stream or in a resource.

System action

The printing disposition depends on the error described in the accompanying messages.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

To determine an appropriate response, see the specific error conditions described in the accompanying messages.

User response

To determine an appropriate response, see the specific error conditions described in the accompanying messages.

APS109I	THE ERROR REPORTED ABOVE WAS CAUSED BY THE RESOURCE <i>resource name</i> IN AN EXTERNAL LIBRARY OR AN INLINE RESOURCE.
----------------	---

Explanation

This message is issued in addition to the message that describes the error. The object identified in the accompanying message was either a resource that is processed from an external library or an inline resource. Error message, APS108I, identified the member with a resource type. The combined information from these two messages can be used to identify the library defined to PSF in the Printer Inventory or on the PRINTDEV statement if appropriate. If the resource is an inline form definition or page definition, the resource is not a member of an external library, but it is included at the beginning of the user's data set.

System action

The printing disposition depends on the error described in the accompanying messages.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

To determine an appropriate response, see the specific error conditions described in the accompanying messages.

User response

To determine an appropriate response, see the specific error conditions described in the accompanying messages.

APS110I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE LENGTH SPECIFIED IN THE SELF-DEFINING PARAMETER OR TRIPLET <i>identifier</i> OF THE
----------------	--

**structured field STRUCTURED
FIELD IS INCORRECT.**

Explanation

Insufficient data was present in the structured field for the length given in the self-defining parameter or triplet. If the self-defining parameter or triplet ID is 0, the length of the self-defining parameter or triplet might be 0 or 1, which means that no ID was available for use in this message.

System action

If the error occurred in a structured field in a page or resource, PSF attempts to find the end of the page or resource. If PSF can find the end of the page, it prints any data accumulated for the current page. If PSF cannot find the end of the page, it stops processing the data set. If the error occurred in a form definition, a page definition, or a non-presentation object container resource (for example, COMSETUP), the form definition, page definition, or non-presentation object container resource is not used, and one of these occurs:

- PSF is not started for any of these:
 - The default form definition
 - A form definition specified for printing messages or separator pages
 - A page definition specified for printing messages or separator pages
- PSF cannot begin printing the data set for a form definition or non-presentation object container resource (or page definition if printing line data) specified on a user's JCL OUTPUT statement; PSF tries to print the next data set.

If PSF is processing an inline resource, it stops processing the data set.

If PSF is processing a print data set and the current structured field is a Begin Print File (BPF) or a Begin Document (BDT), PSF stops processing the data set.

PSF issues a message that identifies the position of the structured field in the data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the object, contact your system programmer.

APS111I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE REQUESTED CHARACTER ROTATION IS NOT AVAILABLE IN THE CURRENT FONT.

Explanation

The Font Orientation (FNO) structured field does not include a repeating group for the requested character rotation. The FNO structured field is contained in the font character set. The font, its character rotation, and its print direction were specified in the Map Coded Font (MCF) structured field in the MO:DCA data, overlay, or page definition. If the font that is used was specified with a JCL CHARS or UCS keyword, then PSF constructed the MCF structured field.

System action

PSF cannot print the current page, but it attempts to find the end of that page and to resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF prints more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

Ensure that the correct font was specified. If it was, and if you used a program to create the MCF structured field, consult your system programmer. If the correct font was specified and you used bytes 28 and 29 to identify the character rotation for the font while you are creating the MCF structured field, ensure that the values in these bytes identify an available character rotation in the requested font.

If the correct font was specified, and if you created the structured fields for the font, ensure that an FNO repeating group is available for the character rotation you want, and resubmit the print request.

If the correct font was specified, and if you used a program to create the structured fields for the font, consult your system programmer.

APS112I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: RECORD CONTAINS NO DATA, EVEN THOUGH AT LEAST A CONTROL CHARACTER IS EXPECTED.**

Explanation

PSF read an input record without a control character that follows the record descriptor word (RDW). A minimum of 1 byte of control-character data is needed to make the record valid.

System action

PSF prints any data that accumulated for the page, and then stops printing the current data set. PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. For more information about the construction and placement of RDWs, see *z/OS DFSMS Using Data Sets*.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APS113I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: STRUCTURED FIELD LENGTH IS LESS THAN THE INTRODUCER LENGTH.**

Explanation

A structured field must have at least 8 bytes of data, the minimum length necessary for a structured field introducer. The Extension Indicator flag in the structured field introducer indicates whether the minimum length of the structured field can be greater than 8 bytes.

System action

PSF stops processing the current page, and prints any data accumulated for the current page. PSF attempts to find the end of the current page and to resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see [PSF for z/OS: Diagnosis](#) for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APS114I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: RDW LENGTH DOES NOT AGREE WITH LENGTH IN STRUCTURED FIELD INTRODUCER.
----------------	--

Explanation

Every structured field is preceded by a record descriptor word (RDW) that specifies the length of that record, including the RDW. The record length in the RDW for the current record is less than the sum of the Length parameter in the structured field introducer and the number of bytes for both the RDW (4 bytes) and the control character (1 byte).

System action

PSF stops processing the current page, and prints any data accumulated for the current page. PSF attempts to find the end of the current page and to resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see [PSF for z/OS: Diagnosis](#) for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or resource, ensure that the RDW for the incorrect structured field contains a valid record length, and resubmit the print request. If you used a program to create the structured fields for the print data set or resource, consult your system programmer.

APS115I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: STRUCTURED FIELD INTRODUCER FLAG BITS ARE NOT ACCEPTABLE.
----------------	--

Explanation

Bits 1–3 or 5–7 in the structured field introducer Flag Byte parameter are not all zeros.

System action

PSF stops processing the current page and prints any data accumulated for the current page. PSF attempts to find the end of the current page and resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF issues a message that identifies the position of the structured field in the input record or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see [PSF for z/OS: Diagnosis](#) for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is

provided in the User Response section to correct the error.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APS116I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: PADDING LENGTH OR EXTENSION LENGTH IS INCORRECT FOR STRUCTURED FIELD.
----------------	--

Explanation

The length of padding, extension, or both specified in the Length or Extension parameter in the structured field introducer indicates more data than was found in the structured field.

System action

PSF stops processing the current page, and prints any data accumulated for the current page. PSF attempts to find the end of the current page and to resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF issues a message that identifies the position of the structured field in the input record or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or resource, ensure that the Extension Indicator flag is set correctly and that the Length parameter in the structured field introducer specifies the actual length of padding for the incorrect structured field. See *Mixed Object Document Content Architecture Reference* for more information about the structured field introducer. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or resource, consult your system programmer.

APS117I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: LENGTH INDICATED IN THE STRUCTURED FIELD INTRODUCER IS INCORRECT FOR <i>structured field name</i> STRUCTURED FIELD.
----------------	--

Explanation

The length that is indicated by the structured field introducer specifies an incorrect number of bytes for the structured field identified in this message. This error is caused by one of these:

- The Extension or Padding Indicator flags in the structured field introducer are set incorrectly.
- One or more of the parameters in the structured field contain an incorrect number of bytes.

In some cases, the length of a structured field is specified in a parameter that is in another structured field. For example, the length of Fixed Data Text (FDX) structured fields is specified in the Size parameter of the Fixed Data Size (FDS) structured field.

System action

PSF stops processing the current page, and prints any data accumulated for the current page. PSF attempts to find the end of the current page and to resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF issues a message that identifies the position of the data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or resource, ensure that the Length parameter in the structured field introducer specifies a valid length for the structured field. Also, ensure that the number of bytes in the structured field parameter matches the length specified in the structured field introducer. See *Mixed Object Document Content Architecture Reference* for more information about the structured field introducer.

If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or resource, consult your system programmer.

APS118I	UNSUPPORTED STRUCTURED FIELD <i>structured field code</i> WAS IGNORED, AND, IF IT BEGAN AN OBJECT, THE OBJECT WAS IGNORED. THE PRINTED OUTPUT MAY BE ACCEPTABLE.
----------------	---

Explanation

The Identifier parameter in the structured field introducer for the incorrect structured field specified a structured field code that was not recognized as a valid structured field code.

System action

If the structured field began an object, the object was ignored. Otherwise, only the structured field was ignored, and processing of the rest of the data set continues as usual.

PSF issues a message that identifies the position of the structured field in the input data stream or containing resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If the printed output was unacceptable and you created the structured fields for the print data set or resource, give the incorrect structured field a code that is valid for its structured field type. See *Mixed Object Document Content Architecture Reference* for a list of valid structured field types.

If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured field for the print data set or resource, consult your system programmer.

APS120I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: <i>structured field name1</i> STRUCTURED FIELD CONTAINS AN INCORRECT VALUE FOR THE SIZE OF THE <i>structured field name2</i> REPEATING GROUP.
----------------	--

Explanation

Structured field name1 specifies the length of each repeating group found in *structured field name2*. Either the value that is specified in *structured field name1* for the size of the repeating group is too small, or the actual length of the repeating-group data is not a multiple of the size specified.

System action

PSF stops processing the current page and prints any data accumulated for the current page. PSF tries to find the end of the current page and resume printing on the next page. If PSF cannot find the end of the page, it stops printing the data set. If this error occurred in a Resource Environment Group (REG), PSF stops processing the REG and continues processing the data set.

PSF issues a message that identifies the position of the structured field in the data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is

defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see [PSF for z/OS: Diagnosis](#) for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APS121I	FORMDEF KEYWORD MUST BE SPECIFIED ON THE JCL OUTPUT STATEMENT IN ORDER TO PRINT THIS DATA SET. DETERMINE THE PERMISSIBLE VALUES USED IN YOUR INSTALLATION FOR THE FORMDEF KEYWORD.
----------------	---

Explanation

This data set cannot be printed without an active form definition. No FORMDEF keyword was provided on the JCL OUTPUT statement for this job, and no default form definition was defined in the Printer Inventory or the PSF startup procedure.

System action

PSF cannot print the current data set. If unable to find the end of the page, PSF stops printing the data set. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

Specify a default form definition for the FSA in the Printer Inventory or on the JCL PRINTDEV statement in the procedure that is used to start PSF. For information on how to specify a default form definition for the FSA in the Printer Inventory on the PRINTDEV statement, see [PSF for z/OS: Customization](#).

User response

To specify a form definition, do one of these:

- Code the FORMDEF keyword on the OUTPUT JCL statement. For information on how to code the OUTPUT statement, see [PSF for z/OS: User's Guide](#).
- Request that your system programmer code a default form definition name in the PSF initialization procedure.

APS122I	DATA IN A FONT CHARACTER SET RESOURCE IS NOT VALID: THE PATTERN-TECHNOLOGY VALUE IN THE FNC STRUCTURED FIELD IS INCORRECT.
----------------	---

Explanation

The pattern-technology value in Byte 1 of the Font Control (FNC) structured field is not valid. The FNC structured field is contained in the font character set.

System action

PSF cannot print the current page, but it attempts to find the end of that page and to resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF prints more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and [PSF for z/OS: Customization](#) for assistance in determining the source of the problem.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

APS123I	GROUP LEVEL MEDIUM FINISHING REQUESTED BUT THE PRINTER DOES NOT SUPPORT GROUP LEVEL MEDIUM FINISHING. THE PROCESSING OF THE DATA SET CONTINUES WITHOUT GROUP LEVEL MEDIUM FINISHING.
----------------	---

Explanation

A Document Environment Group in the current form definition contains a Medium Finishing Control (MFC) structured field but the printer does not support group level MFCs.

System action

The MFC is ignored and processing continues. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to

create the structured fields for the form definition, contact your system programmer.

APS124I	DATA IN A FONT CHARACTER SET RESOURCE IS NOT VALID: THE X SHAPE RESOLUTION <i>resolution</i> AND Y SHAPE RESOLUTION <i>resolution</i> OF THE FONT DO NOT MATCH.
----------------	--

Explanation

The X shape resolution (bytes 24-25) and the Y shape resolution (bytes 26-27) are specified incorrectly in the Font Control (FNC) structured field. The X and Y shape resolutions are optional for raster fonts; however, if they are specified, the resolutions must match.

System action

PSF cannot print the current page. PSF attempts to locate the end of the current page and resume printing on the next page. If the end of the current page cannot be located, PSF stops printing the data set. PSF issues a message identifying the position of the structured field in the input data stream or resource. PSF issues additional messages identifying the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource containing the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

APS125I**DATA IN A FONT CHARACTER SET RESOURCE IS NOT VALID: THE BASELINE EXTENT VALUE IN THE FNO STRUCTURED FIELD IS NOT ACCEPTABLE.****Explanation**

The Baseline Extent parameter in the Font Orientation (FNO) structured field does not contain a value in the correct range. The FNO structured field is contained in the font character set.

System action

PSF stops processing the current page. PSF attempts to find the end of the current page and to resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

APS126I**DATA IN A FONT CHARACTER SET RESOURCE IS NOT VALID: THE COMPRESSION ALGORITHM PARAMETER IN THE FNC STRUCTURED FIELD CONTAINS AN UNACCEPTABLE VALUE.****Explanation**

The Compression Algorithm Identifier was specified incorrectly in the Font Control (FNC) structured field. The FNC structured field is in the font character set.

System action

PSF stops processing the current page. PSF attempts to find the end of the current page and to resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

APS127I**MISMATCH BETWEEN CODE PAGE AND FONT CHARACTER SET RESOURCES: CPC STRUCTURED FIELD SPECIFIED A DEFAULT GRAPHIC CHARACTER 'default graphic character name' WHICH WAS NOT FOUND IN THE FNI STRUCTURED FIELD.****Explanation**

The value in the Default Graphic Character Name parameter in the Code Page Control (CPC) structured field does not match any of the values of the Graphic

Character Identifier parameters in the repeating groups of the associated Font Index (FNI) structured field. The CPC structured field is in the code page. The FNI structured field is contained in the font character set.

The repeating groups in the FNI structured field should be sorted in ascending numeric order. This error might be caused by incorrect sorting of the repeating groups.

System action

PSF stops processing the current page. PSF attempts to find the end of the current page and to resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

APS128I	SHEET LEVEL MEDIUM FINISHING REQUESTED BUT THE PRINTER DOES NOT SUPPORT SHEET LEVEL MEDIUM FINISHING. THE PROCESSING OF THE DATA SET CONTINUES WITHOUT SHEET LEVEL MEDIUM FINISHING.
----------------	---

Explanation

A medium map in the current form definition contains a Medium Finishing Control (MFC) structured field but the printer does not support sheet level MFCs.

System action

The MFC is ignored and processing continues. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS129I	DATA IN A FONT CHARACTER SET RESOURCE IS NOT VALID: THE FLAG BYTE VALUE IN THE FNC STRUCTURED FIELD IS NOT ACCEPTABLE.
----------------	---

Explanation

The Flag byte in the Font Control (FNC) structured field contains incorrect data. For the 3800 printer, the incorrect value might be in the Kerning flag or in the Uniform Character Box Size flag. For the other printers, the incorrect value is in the Uniform Character Box Size flag. The FNC structured field is contained in the font character set.

System action

PSF stops processing the current page. PSF attempts to find the end of the current page and to resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

APS130I **DATA IN AN INPUT RECORD IS NOT VALID: *structured field name* STRUCTURED FIELD IS NOT ACCEPTABLE AT THE START OF A DATA STREAM.**

Explanation

The structured field type that is identified in this message is not valid at the start of the data stream. Subsequent error messages give additional information about the processing environment in which the error occurred.

System action

PSF cannot print the current data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set, contact your system programmer.

APS131I **THE SEPARATOR PAGE EXIT GENERATED AN ERROR: *structured field type* IS NOT ACCEPTABLE AT THE START OF *separator page type* SEPARATOR PAGE. PLEASE INFORM YOUR SYSTEM PROGRAMMER.**

Explanation

The first structured field of the separator-page type that is identified in this message is not a valid structured field type or a line-data record. Line data is valid in this position. Any of the structured field types that can begin a document is also valid.

System action

The page is not printed.

Operator response

Inform your system programmer that this error occurred.

System programmer response

See *Mixed Object Document Content Architecture Reference* to construct one of the structured fields that can begin a document and to determine the correct sequence of structured fields within a data set or resource.

Correct the process that is used to create the separator page that contains the error, and replace the exit before resubmitting print requests.

User response

Inform your system programmer that this error occurred.

APS132I **DATA IN AN INPUT RECORD IS NOT VALID: *structured field name* STRUCTURED FIELD IS NOT ACCEPTABLE.**

Explanation

The structured field that begins a transmission is not an acceptable structured field type or a line-data record. Subsequent error messages give additional information about the processing environment in which the error occurred. If inline resources are used, multiple resource groups might be present.

System action

PSF stops printing the current data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set, contact your system programmer.

APS133I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE *structured field name* STRUCTURED FIELD HAS TOO MANY *identifier* TRIPLETS.**

Explanation

The triplet specified in the message was found multiple times in the indicated structured field. However, this triplet can occur only once.

System action

PSF stops printing the current data set.

PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

No response is necessary.

System programmer response

If an IBM licensed program was used to create the structured fields with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields, contact your system programmer.

APS134I **DATA IN AN INPUT RECORD IS NOT VALID: THE INTERCHANGE SET IDENTIFIER *isid* IN THE INTERCHANGE SET X'18' TRIPLET ON A *structured field name* STRUCTURED FIELD IS NOT VALID.**

Explanation

The interchange set (ISid) field in a X'18' triplet with Presentation type (X'01') is not valid for one of these reasons:

- The value is not valid according to Mixed Object Document Content Architecture.
- A Function Set triplet (X'8F') is specified on the structured field, but the ISid value in the associated X'18' triplet does not indicate that one is expected.

System action

PSF stops printing the current data set.

PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

No response is necessary.

System programmer response

If an IBM licensed program was used to create the structured fields with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields, contact your system programmer.

APS135I DATA IN A RESOURCE IS NOT VALID: DUPLICATE OVERLAY LOCAL IDENTIFIER WAS FOUND IN THE *structured field* STRUCTURED FIELD.

Explanation

The same local identifier was found assigned to more than one Overlay Local Identifier parameter in the Map Medium Overlay (MMO) or Map Page Overlay (MPO) structured field repeating groups. The MMO structured field is in the form definition. The MPO is in the page definition or the print data set.

System action

If the error is in a resource, the resource is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in the default page definition, or a page definition that is specified for printing messages or separator pages, PSF is not started.

- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.
- If the error is in a page definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

If the error is in the print data set, PSF cannot print the current page. PSF attempts to find the end of the current page and resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS136I THE REGISTERED OBJECT-TYPE OID *oid* OF AN OBJECT CONTAINER RESOURCE NAMED *name* IS NOT SUPPORTED WITH THE OBJECT CLASS *object class* IN THE OBJECT CLASSIFICATION TRIPLET (X'10') ON THE *structured field name* STRUCTURED FIELD.

Explanation

The registered object-type OID (*oid*) is not valid with the object class (*object class*) specified on the X'10' Object Classification triplet located on the specified structured field. Object containers and their registered object-type OID identifiers are only supported with certain object classes. For more information about the structured field and triplet, see *Mixed Object Document Content Architecture Reference*.

System action

The resource is skipped and processing of the data set continues.

Operator response

No response is necessary.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

If you created the structured field, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If you used a program to create the structured field, contact your system programmer.

APS138I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: OVERLAY LOCAL IDENTIFIER VALUE IS NOT ACCEPTABLE IN THE *structured field* STRUCTURED FIELD.

Explanation

An incorrect Overlay Local Identifier was encountered in one of the structured field repeating groups: Map Medium Overlay (MMO), Map Page Overlay (MPO), or Medium Modification Control (MMC). The MMO and MMC structured fields are in the form definition. The MPO is in the page definition or the print data set.

System action

If the error is in a resource, the resource is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

If the error is in the print data set, PSF cannot print the current page. PSF attempts to find the end of the current page and resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS139I DATA IN A FORMDEF RESOURCE IS NOT VALID: SUPPRESSION LOCAL IDENTIFIER VALUE IS NOT ACCEPTABLE IN THE MSU STRUCTURED FIELD.

Explanation

The Suppression Local Identifier parameter in the Map Suppression (MSU) structured field is not valid. The MSU structured field is in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS140I **DATA IN A FORMDEF RESOURCE IS NOT VALID: TWO structured fields STRUCTURED FIELDS ARE DEFINED WITH THE SAME IDENTIFIER, identifier.**

Explanation

Two Medium Modification Control (MMC) or two Page Modification Control (PMC) structured fields in a single Form Environment Group have the same value in their Identifier parameters. The MMC and PMC structured fields are in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the MMC structured field and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the MMC has no errors, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS141I **DATA IN A FORMDEF RESOURCE IS NOT VALID: MEDIUM SUPPRESSION TOKEN NAME IS**

REPEATED IN MSU STRUCTURED FIELD.

Explanation

The Token Name parameters in two repeating groups in a Map Suppression (MSU) structured field have the same value. The MSU structured field is in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS143I DATA IN A FORMDEF RESOURCE IS NOT VALID: COPY

SPECIFICATIONS IN THE MCC STRUCTURED FIELD ARE NOT ACCEPTABLE.

Explanation

Either the Starting and Stopping Copy Numbers contain a gap or an overlap, or the maximum number of copies for one set of modifications is exceeded. The Copy Number parameters are specified in the Medium Copy Count (MCC) structured field. The MCC structured field is contained in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, ensure that the Starting Copy Number and the Stopping Copy Number parameters in a repeating group in an MCC structured field have valid values that correlate. Also, verify that fewer than 255 copies are requested. If 255 or more copies with the same modifications are needed, define two or more MCC structured fields. For more information about the MCC structured field, see *Mixed Object Document Content*

Architecture Reference. If the MCC has no errors, the error might be a PSF logic error.

If you used a program to create the structured fields for the form definition, consult your system programmer.

APS145I DATA IN A FORMDEF RESOURCE IS NOT VALID: THE FORMS-FLASH VALUE IN MMC STRUCTURED FIELD, ID *identifier*, IS NOT ACCEPTABLE.

Explanation

The Medium Modification Control (MMC) structured field contains an incorrect value for the repeating group that contains forms-flash modification. The MMC structured field is contained in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the MMC structured field and

resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the MMC has no errors, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS146I DATA IN A FORMDEF RESOURCE IS NOT VALID: MORE THAN 8 OVERLAYS ARE SPECIFIED IN MMC STRUCTURED FIELD, ID *identifier*.

Explanation

In a Medium Modification Control (MMC) structured field, eight normal overlays can be specified (this count does not include one medium preprinted form overlay that can be specified); however, the maximum number of normal overlays that are allowed in one set of modifications is exceeded. The MMC structured field is contained in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the MMC structured field and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the MMC has no errors, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS147I DATA IN A FORMDEF RESOURCE IS NOT VALID: MORE THAN 8 SUPPRESSIONS ARE SPECIFIED IN MMC STRUCTURED FIELD, ID identifier.

Explanation

In a Medium Modification Control (MMC) structured field, the maximum number of suppressions that are allowed in one set of modifications is exceeded. The MMC structured field is contained in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the

input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the MMC structured field and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the MMC has no errors, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS149I RESOURCE DELETION CALL SETTINGS IN INSTALLATION EXIT 7 CONFLICT WITH THE RESOURCE DELETION RATIO PARAMETER IN THE AFPPARMS CONTROL STATEMENT.

Explanation

An installation Exit 7 requested a resource-deletion call for coded fonts, medium overlays, page segment/OCA, or object containers. The request was set during the INIT call to Exit 7. Either the Resource deletion ratio parameter in the Printer Inventory or the AFPPARMS control statement resource-deletion-ratio parameter is greater than zero. A value greater than zero conflicts with the PSF installation Exit 7 settings. You cannot specify both algorithms to control resource deletion.

Exit 7 requests a resource-deletion call for resources by setting flags on XTP7RDEL in the XTP7 parameter area (DSECT).

System action

PSF processing stops abnormally with a system completion code 024 and an abend reason code 0526.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Either correct the installation Exit 7 to remove the requests for resource-deletion calls or set the Resource deletion ratio parameter in the Printer Inventory or the AFPPARMS control statement resource-deletion-ratio parameter to zero.

For more information about Exit 7 or the resource deletion ratio, see *PSF for z/OS: Customization*.

User response

No response is necessary.

APS151I THE PRINTABLE AREA LENGTH OF inches INCHES IS TOO SMALL TO PRINT MESSAGES. PSF HAS USED THE SMALLEST LENGTH FROM THE LOGICAL PAGE inches OR THE PHYSICAL PRINTABLE AREA inches OR THE USER PRINTABLE AREA inches. PRINTING OF MESSAGES IS TERMINATED.

Explanation

A check was made to determine whether the message would fit in the printable area when printed on the paper currently in the printer. It was determined that not enough space existed for even one message line. The page length that is specified is too small.

System action

The message data set or interrupt message page is not printed.

Operator response

If the physical printable area length (forms length) might be configured by the operator and it is determined that this is the problem, increase the printable area length (forms length) and resubmit the job. See the printer hardware manual for details on configuring forms length. Otherwise, inform your system programmer that this error occurred.

System programmer response

If messages are to be printed, select a form, a logical page size, and a font size that allows messages to fit on the page. The form definition or page definition that is selected to process messages might be incorrect, or the font that is selected might be too large for the page size specified in the form definition or the page definition. In addition, the physical printable area length (form length) as returned in the XOH Obtain Printer Characteristics reply might be too small.

PSF uses the smallest of the following values to determine the printable area:

- The User Printable Area length plus its vertical offset
- The physical printable area length
- The current logical page length plus its vertical offset

The preceding printable area lengths are further reduced by any vertical offset from the medium origin (specified in the form definition) and by an extra 0.36 inches for all printers except the 3800. On the 3800,

the lengths are reduced by any vertical offset from the medium origin and by an extra 0.67 inches.

To correct the printable area length, do these:

1. Use the smallest length as specified in the message and:
 - If the logical page length is too small, correct the length in the page definition for the message data set. See *Page Printer Formatting Aid: User's Guide* for assistance.
 - If the physical page length (forms length) is too small and the forms length might be configured from the printer's operator panel, do the action that is specified in the Operator Response.
 - If the User Printable Area (UPA) is too small, see the *PSF for z/OS: Security Guide* for assistance.
- Note:** Note: All values that are too small are affected by the offset from the medium origin as specified in the form definition for the message data set. Check this value to ensure that the offset is not too large. See *Page Printer Formatting Aid: User's Guide* for assistance.
2. See the User Response section if it can be determined that the job submitter specified the FOMLEN keyword and the FORMLEN value is too small.
 3. If the specified page length is not too small, it might be because PSF calculated an incorrect maximum page length.

User response

If the FORMLEN keyword is specified in the user's OUTPUT JCL statement and this value is too small, increase the FORMLEN value and resubmit the job. The FORMLEN value is used for both the message data set and the interrupt message page. See the *PSF for z/OS: User's Guide* for details on the FORMLEN keyword. If this does not fix the problem, inform your system programmer.

APS152I DATA IN A FORMDEF RESOURCE IS NOT VALID: MMC STRUCTURED FIELD WAS NOT FOUND TO COMPARE WITH IDENTIFIER identifier value IN MCC STRUCTURED FIELD.

Explanation

The Medium Modification Control Identifier parameter in the Medium Copy Count (MCC) structured field contains a value that did not match the Medium Modification Control Identifier parameter in any Medium Modification Control (MMC) structured field in

the Form Environment Group. The MCC and MMC structured fields are in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the MCC or MMC structured field. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the MCC and MMC have no errors, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS153I

**A FORM DEFINITION REQUESTED
A PREPRINTED FORM OVERLAY,
BUT PREPRINTED FORM
OVERLAYS ARE NOT SUPPORTED
BY THIS PRINTER.**

Explanation

A form definition specifies a preprinted form overlay; however, this form definition cannot be used because the printer does not support preprinted form overlays.

System action

One of these occurs:

- PSF is not started if the default form definition or a form definition for printing messages or separator pages is specified.
- PSF does not print the data set if a form definition is specified on the user's JCL OUTPUT statement. PSF releases the current data set to Job Entry Subsystem (JES) and requests the system to hold it.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If you are running under JES, use JES commands to release the data set to a printer that supports preprinted form overlays. See *z/OS JES2 Commands* or *z/OS JES3 Commands* for information about the JES commands that release the data set for printing. If this message displays on the operator's console, it indicates that the form definition that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If a form definition is specified for printing messages or separator pages, do one of these:

- Modify the JCL OUTPUT statement for the message or separator data set to specify a form definition that does not request a preprinted form overlay.
- Edit the form definition that is used by the message or separator data set so it does not request a preprinted form overlay.

User response

To receive the printed output with the requested preprinted form overlay, ask your print operator to reroute the data set to a printer that supports preprinted form overlays. If you do not want to use a preprinted form overlay, do one of these:

- Ask your print operator to use a different form definition for the data set and then release the data set for printing.

- Specify a different form definition and resubmit the print request; then, ask your print operator to purge your previous held print request.

APS154I **DATA IN A FORMDEF RESOURCE IS NOT VALID: OVERLAY LOCAL IDENTIFIER IN MMC STRUCTURED FIELD, ID *identifier*, WAS NOT FOUND IN MMO STRUCTURED FIELD.**

Explanation

The overlay modification in the Medium Modification Control (MMC) structured field was not present in the Map Medium Overlay (MMO). The MMC and MMO structured fields are in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to

create the structured fields for the form definition, contact your system programmer.

APS155I **DATA IN A FORMDEF RESOURCE IS NOT VALID: TOO MANY COPY CONTROLS WERE SPECIFIED FOR THE CURRENT FORM ENVIRONMENT GROUP.**

Explanation

For a given physical page, up to 256 bytes of data can be specified for the printer command that describes the copies and modifications to be made. The current Form Environment Group causes the data for the command to exceed 256 bytes. PSF builds the printer command from data in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, either reduce the number of copy groups in the Medium Copy Count (MCC) structured field or reduce the number of modifications specified in the Medium Modification Control (MMC) structured field. Otherwise, split these functions between two or more Form Environment Groups in two or more medium maps. Then, include in your input two or more copies of the same page that are identical except that for

each of them you select an appropriate code page by use of an Invoke Medium Map (IMM) structured field. For more information about the MMC and MMO structured fields, see *Mixed Object Document Content Architecture Reference*.

If you used a program to create the structured fields for the form definition, consult your system programmer.

APS156I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: NULL NAME IS NOT ACCEPTABLE IN structured field name STRUCTURED FIELD.**

Explanation

Every Begin-type and End-type structured field can include an 8-byte token name. A null token name is not allowed for the listed structured field.

System action

PSF stops processing the current page. PSF attempts to find the end of the current page and resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program

to create the structured fields for the print data set or the resource, contact your system programmer.

APS157I **MISMATCH BETWEEN PRINT DATA SET AND FORMDEF RESOURCE: MEDIUM MAP 'medium map' SPECIFIED IN IMM STRUCTURED FIELD WAS NOT FOUND IN FORMDEF 'form definition name.'**

Explanation

The Token Name parameter in the Invoke Medium Map (IMM) structured field specifies the token name that is used to find a medium map in the form definition. This parameter must match the Token Name parameter specified in bytes 0–7 in one of the Begin Medium Map (BMM) structured fields in the current form definition. The IMM structured field is in the print data set.

System action

PSF stops processing the current data set, releases the data set back to JES, and requests that it is held by the system.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Ensure that the correct form definition was specified. If it was, and if you added the Invoke Medium Map structured field to the print data set, change the Token Name in the IMM structured field and resubmit the print request. For more information about the BMM and IMM structured fields, see *Mixed Object Document Content Architecture Reference*. If the correct form definition was specified, and if you used a program to embed the IMM structured field in the print data set, verify that the copy group name that you gave the program is valid for the form definition you specified.

APS158I **PAGEDEF KEYWORD MUST BE SPECIFIED IN ORDER TO PRINT THIS DATA SET. DETERMINE THE PERMISSIBLE VALUES USED IN YOUR INSTALLATION FOR THE PAGEDEF KEYWORD.**

Explanation

The current data set contains line data, XML data, or structured fields that do not form a MO:DCA page. This kind of data set cannot be printed without an active

page definition. No PAGEDEF keyword was provided on the JCL OUTPUT statements for this job, and no default page definition was defined in the PSF initialization procedure.

This error can also occur if MO:DCA data in the print data set contains a record without the required X'5A' control character that precedes the structured-field introducer. The missing control character makes the record appear to be line data. A page definition is necessary to process line data. Therefore, PSF detects an error.

System action

PSF stops processing the current page, and prints any data accumulated for the current page. PSF attempts to find the end of the current page and resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If the problem is with either a separator page or a message, modify the JCL OUTPUT statement for the separator or message data set.

Specify a default page definition in the Printer Inventory or on the JCL PRINTDEV statement in the procedure that is used to start PSF. For information about how to specify a default page definition in Printer Inventory on the PRINTDEV statement, see [PSF for z/OS: Customization](#).

User response

If you intended to print line data or XML data, do one of these to specify a page definition:

- Code the PAGEDEF parameter on the JCL OUTPUT statement. For information about how to code the OUTPUT statement, see [PSF for z/OS: User's Guide](#).
- Code the FCB parameter on the JCL DD statement.
- Request that your system programmer code a default page definition name in the PSF initialization procedure.

If you did not intend to print line data or XML data, and you used a program to create the structured fields for the print data set, consult your system programmer.

APS159I THE END OF THE DATA STREAM WAS ENCOUNTERED BEFORE THE LOGICAL END OF AN OBJECT WITHIN THE DATA STREAM.

Explanation

The object that PSF was processing began with a Begin-type structured field, but the input data stream ended before a corresponding End-type structured field was found. This message can also occur if the system operator prematurely interrupts or ends a print request by issuing an INTERRUPT, RESTART, or CANCEL Job Entry Subsystem (JES) command.

System action

PSF stops printing the current data set, and prints any data accumulated for the current page. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see [PSF for z/OS: Diagnosis](#) for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set, correct the error and resubmit the print request. See [Mixed Object Document Content Architecture Reference](#) for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set, contact your system programmer.

APS162I MISMATCH BETWEEN PRINT DATA SET AND PAGEDEF RESOURCE: DATA MAP 'data map' SPECIFIED IN IDM STRUCTURED FIELD WAS

NOT FOUND IN PAGEDEF 'page definition'.

Explanation

The Token Name parameter in the Invoke Data Map (IDM) structured field specifies the token name that is used to find a data map in the page definition. The name must match the value specified in the Token Name parameter in the Begin Data Map (BDM) structured field in the current page definition. The IDM structured field is in the print data set.

System action

PSF stops processing the current page and issues more messages that identify the processing environment in which the error occurred.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Ensure that the correct page definition was specified. If it was, and if you added the Invoke Data Map structured field to the print data set, change the Token Name in the IDM structured field and resubmit the print request. For more information about the BDM and IDM structured fields, see *Advanced Function Presentation: Programming Guide and Line Data Reference*. If the correct page definition was specified, and if you used a program to embed the IDM structured field in the print data set, verify that the data map name you supplied to the program is valid for the page definition you specified.

APS163I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE SCALE FACTOR VALUE IN THE IOC STRUCTURED FIELD IS NOT ACCEPTABLE.

Explanation

The Image Block Scale Factor parameter in the Image Output Control (IOC) structured field is not valid. The image block or image cell might be contained in an overlay, a page segment, or a MO:DCA document. It might also be embedded in a data set containing line data by using a Begin Image (BIM) structured field.

System action

PSF stops processing the current page, and prints any data accumulated for the current page. PSF attempts to find the end of the current page and resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If the structured fields are not valid and you created the structured fields for the resource or print data set containing the image, correct the error in the referenced structured field and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the resource or print data set containing the image, contact your system programmer.

APS165I DATA IN A CODE PAGE RESOURCE IS NOT VALID: GRAPHIC CHARACTER IDENTIFIER MUST NOT BE NULL IN THE CPI STRUCTURED FIELD.

Explanation

The Graphic Character Identifier parameter in a Code Page Index (CPI) structured field cannot be null. The CPI structured field is in the code page.

System action

PSF stops processing the current page. PSF attempts to find the end of the current page and continue

printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF issues a message that identifies the position of the structured field in the code page resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the code page with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the code page, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the code page, contact your system programmer.

APS166I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN ENTRY IN A MCF STRUCTURED FIELD CONTAINS AMBIGUOUS IDENTIFICATION.**

Explanation

A font in the Map Coded Font (MCF) structured field might be identified with a Coded Font Name parameter, with a combination of the Font Character Set Name parameter and the Code Page Name parameter, or with a Coded Font (also known as a GRID) parameter. One of the repeating groups in an MCF structured field specified more than one of these ways to specify a font, or specified a Coded Font (GRID) and a section number other than 0. The MCF structured field is in the MO:DCA data, an overlay, or a page definition.

System action

If the error is contained in a page definition, PSF stops processing of the data set and continues processing

with the next data set. Otherwise, PSF stops processing the page or overlay that contains the structured field in error. PSF attempts to locate the end of the current page and resume processing on the next page. If unable to find the end of the page, PSF stops printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APS167I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN ENTRY IN AN MCF STRUCTURED FIELD CONTAINS INCOMPLETE IDENTIFICATION.**

Explanation

One of the repeating groups in a Map Coded Font (MCF) structured field does not contain enough information to identify a coded font. A font in the Map Coded Font (MCF) structured field might be identified either with a Coded Font Name parameter, or with a combination of the Font Character Set Name parameter and the Code Page Name parameter. An entry contains only a Font Character Set Name parameter or a Code Page Name parameter. The MCF structured field is contained in a MO:DCA document, an overlay, or a page definition.

System action

PSF cannot print the current page. PSF attempts to find the end of the current page and resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APS169I	INSUFFICIENT VIRTUAL STORAGE PREVENTED FURTHER PROCESSING. INCREASE REGION SIZE, AND RESUBMIT THE PRINT REQUEST.
----------------	---

Explanation

The storage available in the PSF address space is insufficient to contain the internal control block that is needed to read an object.

System action

PSF stops processing the current page, and prints any data accumulated for the current page. PSF attempts to find the end of the current page and resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

Increase the size of the REGION parameter that is used for the print request. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the data set that contains the error was spooled, increase the REGION parameter on the startup procedure.

User response

Inform your system programmer that this error occurred.

APS170I	DATA IN A FORMDEF RESOURCE IS NOT VALID: THE SIMPLEX/ DUPLEX VALUE IN MMC STRUCTURED FIELD, ID <i>identifier</i>, IS NOT ACCEPTABLE.
----------------	---

Explanation

In the Medium Modification Control (MMC) structured field with the specified identifier, the value for either the SIMPLEX keyword parameter value or the DUPLEX keyword parameter value is not valid. The MMC structured field is contained in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the MMC structured field and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the MMC has no errors, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS171I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: FONT LOCAL IDENTIFIER VALUE IS NOT ACCEPTABLE IN THE *structured field* STRUCTURED FIELD.**

Explanation

The Map Coded Font (MCF) structured field consists of repeating groups. In one of the groups, the value of the Coded Font Local Identifier parameter for the font (section) being mapped is not valid. The MCF structured field is contained in a MO:DCA document, an overlay, or a page definition.

System action

PSF cannot print the current page. PSF attempts to find the end of the current page and resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APS172I **DATA IN A FORMDEF RESOURCE IS NOT VALID: THE SET OF MODIFICATIONS SPECIFIED IN THE MCC STRUCTURED FIELD INCLUDES BOTH NORMAL AND TUMBLE DUPLEX.**

Explanation

The Medium Copy Count (MCC) structured field refers to one or more Medium Modification Control (MMC) structured fields, which include requests for both normal duplex and tumble duplex. You cannot request both normal duplex and tumble duplex within the same medium map. The MCC and MMC structured fields are in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the MCC or MMC structured field. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the MCC and MMC have no errors, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS178I DATA IN A FORMDEF RESOURCE IS NOT VALID: THE MCC STRUCTURED FIELD HAS AN ODD NUMBER OF COPY GROUPS, BUT SPECIFIES DUPLEX.

Explanation

The Medium Copy Count (MCC) structured field specifies an odd number of copy groups, but the copy group modifications that are specified in the Medium Modification Control (MMC) structured field include duplex, which requires an even number of copy groups. The MCC and MMC structured fields are in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- PSF is not started, either for the default form definition or for a form definition that is specified for printing messages or separator pages.

- PSF cannot begin printing the data set for a form definition that is specified on a user's JCL OUTPUT statement; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the MCC or MMC structured field. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the MCC and MMC have no errors, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS179I DATA IN A FORMDEF RESOURCE IS NOT VALID: THE SET OF MODIFICATIONS SPECIFIED IN THE MCC STRUCTURED FIELD INCLUDES BOTH SIMPLEX AND DUPLEX.

Explanation

The Medium Copy Count (MCC) structured field refers to two or more Medium Modification Control (MMC) structured fields, which include requests for both simplex and duplex printing. You cannot specify both simplex and duplex printing within the same medium map. The MCC and MMC structured fields are in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the MCC or MMC structured field. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the MCC and MMC have no errors, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS181I DATA IN A FORMDEF RESOURCE IS NOT VALID: UNEQUAL COPY COUNTS FOR DUPLEX SHEETS ARE SPECIFIED IN THE MCC STRUCTURED FIELD.

Explanation

The set of modifications that are referred to by the Medium Copy Count (MCC) structured field includes duplexing, but the numbers of copies in two corresponding repeating groups are not equal. The repeating groups are defined in the Medium Map Control structured field (MMC). The MCC and MMC structured fields are in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- PSF is not started either for the default form definition or for a form definition that is specified for printing messages or separator pages.
- PSF cannot begin printing the data set for a form definition that is specified on a user's JCL OUTPUT statement; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the MCC or MMC structured field. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the MCC and MMC have no errors, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS186I DATA IN A CODE PAGE RESOURCE IS NOT VALID: THE DEFAULT GRAPHIC CHARACTER NAME MUST NOT BE NULL IN A CPC STRUCTURED FIELD.

Explanation

The Default Graphic Character parameter in a Code Page Control (CPC) structured field specifies the name of the graphic character raster pattern that is used when a pattern is not assigned to a code point in a Code Page Index (CPI) structured field. This parameter

cannot have a null value. A null value is any value that contains X'FFFF' in the first 2 bytes. The CPC and CPI structured fields are in the code page.

System action

PSF stops processing the current page. PSF attempts to find the end of the current page and resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set. PSF issues a message that identifies the position of the structured field in the code page resource.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the code page with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the code page, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the code page, contact your system programmer.

APS188I	THE SET OF MODIFICATIONS SPECIFIED IN THE MCC STRUCTURED FIELD SELECTS MORE THAN ONE INPUT SOURCE, AND THE DEVICE DOES NOT SUPPORT MORE THAN ONE INPUT SOURCE.
----------------	---

Explanation

The Medium Copy Count (MCC) structured field refers to one or more Medium Modification Control (MMC) structured fields, which include requests for more than one input source or media-type local ID. You cannot specify more than one input source or media-type local ID for multiple copy groups, because the printer you are using does not support it. The MCC and MMC structured fields are in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

Request that the job is printed on a printer that supports the specification of input source in the Load Copy Control (LCC) command. If you created the structured fields for the form definition, correct the MMC structured field and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the MMC has no errors, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS190I	DATA IN A FORMDEF RESOURCE IS NOT VALID: THE BIN SELECTION VALUE IN MMC STRUCTURED FIELD, ID <i>identifier</i>, IS NOT ACCEPTABLE.
----------------	---

Explanation

In the Medium Modification Control (MMC) structured field whose identifier is specified in the message text, the bin-selection parameter value was not valid. The

MMC structured field is contained in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the MMC structured field and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the MMC has no errors, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS191I **DATA IN A FORMDEF RESOURCE IS NOT VALID: THE SUPPRESSION LOCAL IDENTIFIER VALUE IN MMC STRUCTURED FIELD, ID identifier, IS NOT ACCEPTABLE.**

Explanation

The Medium Modification Control Identifier parameter in a Medium Modification Control (MMC) structured field is not valid. The MMC structured field is contained in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the MMC structured field and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the MMC has no errors, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS192I **DATA IN A FONT CHARACTER SET RESOURCE IS NOT VALID: THE PATTERN DATA ALIGNMENT PARAMETER IN THE FNC**

STRUCTURED FIELD CONTAINS AN UNACCEPTABLE VALUE.

Explanation

The pattern data alignment value in the Font Control (FNC) structured field is not valid. The FNC structured field is contained in the font character set.

System action

PSF cannot print the current page, but attempts to find the end of that page and to resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF prints more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

APS193I	DATA IN A FONT CHARACTER SET RESOURCE IS NOT VALID: BYTES 4-9 OF THE FNC STRUCTURED FIELD SPECIFY METRICS THAT ARE EITHER INCORRECT OR UNSUPPORTED BY THIS PRINTER.
----------------	--

Explanation

Bytes 4-9 were specified incorrectly in a Font Control (FNC) structured field. The FNC structured field is contained in the font character set.

System action

PSF cannot print the current page. PSF attempts to find the end of the current page and resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

APS194I	DATA IN A FONT CHARACTER SET RESOURCE IS NOT VALID: THE CHARACTER INCREMENT VALUE IN THE FNI STRUCTURED FIELD IS NOT ACCEPTABLE.
----------------	---

Explanation

The Character Increment parameter in a repeating group in the Font Index (FNI) structured field has an incorrect value. The FNI structured field is contained in the font character set.

System action

PSF cannot print the current page. PSF attempts to find the end of the current page and resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

APS195I	DATA IN A FONT CHARACTER SET RESOURCE IS NOT VALID: THE CHARACTER BOX SIZE VALUE IN THE FNI STRUCTURED FIELD IS NOT ACCEPTABLE.
----------------	--

Explanation

The Character Box Size parameter in a repeating group in a Font Index (FNI) structured field has an incorrect value. The FNI structured field is contained in the font character set.

System action

PSF cannot print the current page. PSF attempts to find the end of the current page and resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

APS196I	DATA IN A FONT CHARACTER SET RESOURCE IS NOT VALID: THE PATTERN DATA ADDRESS VALUE IN THE FNI STRUCTURED FIELD IS NOT ACCEPTABLE.
----------------	--

Explanation

A Pattern Data Address parameter in a repeating group of a Font Index (FNI) structured field has an incorrect value. The FNI structured field is contained in the font character set.

System action

PSF cannot print the current page. PSF attempts to find the end of the current page and resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

APS197I	DATA IN A FONT CHARACTER SET RESOURCE IS NOT VALID: NO FNI STRUCTURED FIELD WAS FOUND CORRESPONDING TO THE FONT INDEX NUMBER SPECIFIED IN AN FNO DATA GROUP.
----------------	---

Explanation

The FNO data group for the character rotation that is required by the font contains a font index number as part of the Flags byte. The index number specifies which Font Index (FNI) structured field in the font character set to use. The required FNI structured field was not found. The FNI and FNO structured fields are in the font character set.

System action

PSF cannot print the current page, but attempts to find the end of that page and to resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF prints more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that

the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

APS199I	AN ATTEMPT IS BEING MADE TO LOAD A REQUESTED DOUBLE-BYTE FONT INTO A PRINTER MODEL OR CONFIGURATION THAT MAY NOT BE ABLE TO ACCEPT IT.
----------------	---

Explanation

A request was made to use a double-byte font on a printer that is not configured for double-byte fonts.

System action

In addition to this message, PSF issues messages that identify the current record and the processing environment. PSF tries to load the font into the printer. If that loading fails, subsequent messages identify the font in question, and tell where that font is referenced.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

Ensure that documents that require double-byte fonts are routed to a printer model or configuration that can process them. Otherwise, do not use double-byte fonts.

APS200 to APS299

APS206I THE DATA SET WAS TERMINATED; THE MESSAGE THRESHOLD SPECIFIED ON PIMSG WAS REACHED. *document_type* FOR JOB *print_request*, STEP *step*, OUTGROUP *outgroup* WAS PRINTING WHEN THRESHOLD OCCURRED.

Explanation

The number of message groups that are specified in the PIMSG JCL keyword was reached while printing the current document that is part of the print request job, step, and outgroup identified in this message. The message limit was specified either in the JCL for the data set, or in the procedure that is used to start PSF. If a number for PIMSG was not specified, the PSF default of 16 was used.

System action

PSF stops processing the current data set, releases it to JES, and requests that it is held by the system unless PRTEROR=QUIT is specified on the OUTPUT statement. Pages that were being processed when the message group limit was reached might also print. Processing continues with the next data set.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Fix the errors reported in accompanying messages or raise the PIMSG limit and resubmit the print request. If you did not set the value of PIMSG to this limit and you do not want the limit enforced on the next print request, specify your own PIMSG value on the JCL for the next print request. For information on how to code the PIMSG keyword, see *PSF for z/OS: User's Guide*.

APS207I A DOUBLE-BYTE FONT WAS SPECIFIED FOR A PRINTER THAT DOES NOT SUPPORT DOUBLE-BYTE FONTS.

Explanation

A request to use a double-byte font was made to a printer that does not support double-byte fonts.

System action

PSF cannot print the current page. PSF attempts to find the end of the current page and resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

Ensure that documents that require double-byte fonts are routed to a printer model or configuration that can process them. Otherwise, do not use double-byte fonts.

APS209I DATA IN FORMDEF RESOURCE *formdef name* IS NOT ACCEPTABLE FOR MEDIA ORIGIN OVERRIDE AS REQUESTED. THIS MESSAGE IS ONLY ISSUED ONCE PER PRINT DATA SET.

Explanation

The Infoprint Server Printer Inventory or PSF Exit 7 requested that the media origin is changed to match the 3800 media origin, but the form definition specified capabilities that are not supported by the 3800, such as N_UP or Presentation System Setup IDs. These functions are not acceptable when the media origin is being overridden.

System action

The media origin override request is ignored, PSF continues processing, and the current form definition and the requested functions are used.

Operator response

No response is necessary.

System programmer response

See *PSF for z/OS: Customization* for a list of functions that are not available with the media origin override.

User response

No response is necessary.

APS210I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A REQUIRED TRIPLET OR SELF-DEFINING PARAMETER WITH ID <i>id</i> WAS MISSING FROM A <i>structured field name</i> STRUCTURED FIELD.
----------------	--

Explanation

The triplet or self-defining parameter specified in the message was not found in the indicated structured field. This is a required triplet or self-defining parameter.

System action

The system action depends on where the error is located:

- If the structured field is included in an object that is embedded in a page or overlay, or if the structured field is in a resource included in a page or overlay, PSF stops processing the page or overlay. PSF tries to find the end of the current page and resume processing on the next page. If PSF cannot find the end of the current page, it stops printing the data set.

If PSF is processing an inline resource, it stops processing the data set.

- For non-presentation object containers, PSF stops printing the data set.
- If the error is contained in a page definition or form definition, PSF stops processing the current data set and continues processing with the next data set.
- If this error occurs in a Resource Environment Group (REG), PSF stops processing the REG and continues processing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response:

User response:

APS212I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE UNIT BASE PARAMETER IN THE <i>structured field name</i> STRUCTURED FIELD IS NOT VALID.
----------------	---

Explanation

An incorrect Unit Base value was encountered in the structured field identified in this message.

System action

PSF cannot print the current page. PSF tries to find the end of the current page and resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

If this error occurs in a Resource Environment Group (REG), PSF stops processing the REG and continues processing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the image object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the image object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the image object, contact your system programmer.

APS213I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE L-UNITS PER UNIT BASE PARAMETER IN THE *structured field name* STRUCTURED FIELD IS NOT VALID.**

Explanation

An incorrect L-Units value was encountered in the structured field identified in this message. The structured field is in the Object Environment Group of an image object. The image object can be contained in a MO:DCA document, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

PSF stops processing the current page or overlay. Processing continues with the next page or overlay. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the image object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the image object, correct the error and resubmit the print request. See *Mixed Object Document Content*

Architecture Reference for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the image object, contact your system programmer.

APS214I **DATA IN A FORMDEF RESOURCE IS NOT VALID: CONSTANT FORMS CONTROL, SPECIFIED IN MEDIUM MAP *medium map name*, IS NOT ALLOWED WITH ENHANCED N_UP. THE CONSTANT FORMS CONTROL IS IGNORED.**

Explanation

Both enhanced N_UP and Constant Forms Control were requested in the form definition, but Constant Forms Control is not allowed when Enhanced N_UP is being used. Function similar to Constant Forms Control might be specified in the *PgFlgs* and *PMCID* parameters of the Page Position (PGP) Format 2 structured field. To request enhanced N_UP, specify explicit page placement in the PGP structured field and specify N_UP in the Medium Modification Control (MMC) structured field. The Constant Forms Control is in the MMC structured field. The MMC and PGP structured fields are in the form definition.

System action

The Constant Forms Control is ignored, and processing continues. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. For more information about the structured field, see *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation*:

Programming Guide and Line Data Reference. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, consult your system programmer.

APS215I DATA IN A FORMDEF RESOURCE IS NOT VALID: THE PAGE MODIFICATION CONTROL IDENTIFIER IN THE structured field STRUCTURED FIELD IS NOT ACCEPTABLE.

Explanation

An incorrect Page Modification Control identifier was encountered either in the Page Modification Control (PMC) structured field or in a Page Position (PGP) Format 2 structured field repeating group. The PMC and PGP structured fields are in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print

request. For more information about the structured field, see *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference*. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, consult your system programmer.

APS217I DATA IN AN INPUT RECORD IS NOT VALID: PARAMETER IN A BR STRUCTURED FIELD CONTAINS UNACCEPTABLE DATA.

Explanation

One of the parameters in the Begin Resource (BRS, also called BR) structured field is not valid. The BRS structured field is in the print data set.

System action

PSF stops printing the current data set and issues a message that identifies the processing environment in which the error occurred.

Operator response

No response is necessary.

System programmer response

If an IBM licensed program was used to place the BR structured field in the print data set, verify that the input to that program was valid. If it was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you placed the BR structured field in the print data set, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If you used a program to place the BR structured field in the print data set, consult your system programmer.

APS218I DUPLEXING WAS REQUESTED, BUT IS NOT SUPPORTED BY THIS PRINTER OR BY ALL OF THE INPUT BINS THAT WERE USED. THE OUTPUT IS PRINTED SIMPLEX.

Explanation

Duplexing was requested but is not supported by the printer or by the input bins that were being used. If multiple copies of a page are being printed from

different input bins and not all input bins support duplex, output for the page is printed simplex.

System action

PSF issues this message and continues processing, printing in simplex.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

If you do not want simplex output, submit the print request to a printer that supports duplex printing, or specify an input bin that supports duplex printing, if your installation has one. If you are printing multiple copies of a page from different input bins, ensure that all input bins that are requested for all copies support duplex printing.

APS219I **THE INPUT BIN WITH COMPONENT ID *component ID*, MEDIA NAME *media name*, BIN NUMBER *bin number* WAS DISABLED. AN ALTERNATE BIN WAS SUBSTITUTED.**

Explanation

The Medium Modification Control (MMC) structured field requested an input bin that is supported by the printer but was disabled. A value of *** for any of the three values means that piece of information was not provided by the MMC structured field. The input bin is selected by a media source selector keyword, media type local ID keywords, or both in the MMC structured field. The media type local ID keywords specify the ID of a Map Media Type (MMT) structured field that contains an Object Identifier (IOD), Media Name, or both. The MMC and MMT structured fields are contained in the form definition.

System action

PSF continues processing, selecting paper from an alternative bin.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

If the output is not acceptable, submit the print request to a printer that has the specified bin available, or ensure that the bin is enabled on the original printer before you resubmit the print request.

APS220I **OFFSET STACKING WAS SPECIFIED IN THE MMC STRUCTURED FIELD BUT IS NOT SUPPORTED BY THIS PRINTER. THE OUTPUT IS NOT OFFSET.**

Explanation

Offset stacking is not supported by this printer.

System action

PSF issues this message and continues processing without offsetting the output.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

If you want offset stacking, submit the print request to a printer that supports offset stacking.

APS221I **DATA IN A FORMDEF RESOURCE IS NOT VALID: THE ORIENTATION VALUE *value* IN THE MDD STRUCTURED FIELD IS UNACCEPTABLE.**

Explanation

The Medium Descriptor (MDD) structured field has an incorrect orientation value. The MDD structured field is in the form definition for the job.

System action

If the form definition was specified by the job, PSF stops processing the data set and issues an accompanying APS101I message. If the form definition is the default or is a form definition that is specified for printing messages or separator pages, PSF is not started. PSF issues a message that identifies the position of the structured field in the FORMDEF. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS222I DATA IN A FONT CHARACTER SET RESOURCE IS NOT VALID: THE FNM INDEX IN THE FNI STRUCTURED FIELD CONTAINS AN UNACCEPTABLE VALUE.

Explanation

The FNM index value is not valid in the Font Index (FNI) structured field. The FNI structured field is in the font character set.

System action

PSF cannot print the current page, but attempts to find the end of that page and to resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF prints more messages that identify the processing environment in which the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Advanced Function Presentation: Programming Guide and Line Data Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

APS223I A FORMDEF RESOURCE REQUESTED ENHANCED N_UP AND A CONFLICTING VALUE FOR DUPLEX WAS SPECIFIED ON THE OUTPUT STATEMENT.

Explanation

When enhanced N_UP is requested, the DUPLEX keyword on the OUTPUT statement cannot be used to change from duplex (specified in the form definition) to simplex or vice versa. The reason is that with enhanced N_UP, the Page Position (PGP) Format 2 structured field specified the partition number and sheet side for each page placed on a sheet. If the duplex value is changed from duplex to simplex or vice versa, PSF does not have the information that it needs to place the pages.

The only valid options for the DUPLEX keyword when enhanced N_UP is specified in the form definition are:

- If the form definition requests normal or tumble duplex, you can specify either DUPLEX=NORMAL or DUPLEX=TUMBLE on the output statement.
- If the form definition requests simplex, you can specify DUPLEX=NO on the output statement.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Advanced Function Presentation: Programming Guide and Line Data Reference*.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Resubmit the job without requesting the DUPLEX keyword on the output statement.

APS225I **SYSTEM ACTION TAKEN: THE ERRORS LISTED PREVENTED PROCESSING OF THE DATA SET. THE DATA SET WILL BE HELD.**

Explanation

Errors were detected while PSF, Download for z/OS, or AFP Download Plus was processing a data set. These might be I/O errors or errors that are encountered while a required resource is mapped. Mapping is the procedure that is used to process these resources when they are selected for use in printing a data set. The resource errors consist of structured field sequence problems, data value errors, or loading errors. The product marked the data set unprintable, and returned the data set to the Job Entry Subsystem (JES) to be marked as held for release by the operator. Informational messages that precede this message explain why the data set was not processed.

System action

Processing continues with the next data set.

Operator response

Requeue the data set as requested. Use JES commands to release the data set.

System programmer response

No response is necessary.

User response

The accompanying error messages determine what corrections must be made before you can release the data set and try the request again. Only attempt to try the request again if the error was corrected by replacing a resource. Otherwise, the current request must be canceled and a new one created.

APS226I **THE ASSOCIATED DATASET WAS PRINTED WITH *psf_version* ON *name*, WHICH IS A *type*.**

Explanation

The listed printer type identifies the device that is selected for printing the data set associated with the specified PSF version and printer name and type.

psf_version is the current version of PSF; *name* is the printer name if the printer is a JES printer, or the printer control statement name if the printer is being used in direct-printing mode; *type* is the printer device type.

System action

This message is issued only if other messages are issued for the data set, and if the PIMSG parameter is set to YES either in the JCL for the print job or in the PSF startup procedure.

Operator response

No response is necessary.

System programmer response

Ensure that the type of the device is what you expected. Output that is formatted for one type of page printer might print with errors on another type of printer.

User response

Ensure that the type of the device is what you expected. Output that is formatted for one type of page printer might print with errors on another type of printer.

APS227I **THE SUM OF THE NUMBER OF SECURITY OVERLAYS AND USER OVERLAYS FOR ONE PAGE IS MORE THAN 8.**

Explanation

When the number of overlays that are specified in the Medium Modification Control (MMC) structured field on the user's output statement and the number of security overlays is added, the total is more than eight. A maximum of eight overlays per page is permitted on this printer. The MMC structured field is contained in the form definition.

The limit for the total number of overlays depends on the printer you use. For more information, see the documentation provided with the printer.

System action

If the error occurred in a page, PSF attempts to find the end of the page. If PSF finds the end of the page, PSF prints any accumulated data for the current page. If unable to find the end of the page, PSF stops processing the data set. If the error occurred on a separator page or a message data set, PSF cannot print the separator page or the message data set, and an error message is issued to the operator's console.

PSF issues a message that identifies the position of the MMC structured field that caused the error. PSF issues more messages that identify the environment in which the error is found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the form definition that contains the MMC structured field, you must remove one or more of the overlays, depending on how many security overlays are printed on your class of job. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. Resubmit the print request. If the total number of user overlays and security overlays is less than or equal to 8, the error might be a PSF logic error. To find out how many security overlays are placed on your pages, consult your system programmer.

APS228I	PAGE LABELING WAS IN EFFECT, BUT NO SECURITY OVERLAYS WERE FOUND IN THE <i>security label</i> MEMBER OF THE SECURITY DEFINITIONS LIBRARY FOR THE CURRENT PAGE SIZE AND PAGE TOP.
----------------	---

Explanation

When page labeling is in effect (SPAGELBL = YES or DPAGELBL = yes), at least one security overlay must be listed in the appropriate entry of the security definitions library member that is used to print this page. The appropriate entry is based on the page size and top specification. The name of the member in the security definitions library is the security label of the print job.

System action

PSF releases the current data set back to JES and requests that it is held by the system.

Operator response

Notify the security administrator or the system programmer responsible for the security definitions library that this error occurred. See the publication that contains JES operator commands for your operating system for a command to release the data set for printing after the problem is corrected.

System programmer response

Ensure that at least one overlay for the page top, page size, and security label is listed in the security definitions library member referenced in the message. See *PSF for z/OS: Security Guide* for information about the format of the security definitions library.

User response

Inform your system programmer that this error occurred.

APS229I	SYSTEM ACTION TAKEN: THE ERRORS LISTED OCCURRED DURING THE PROCESSING OF THE SECURITY DEFINITIONS LIBRARY. PROCESSING OF THE DATA SET WAS TERMINATED.
----------------	--

Explanation

This message is issued in addition to a message that describes an error that occurred during processing of a member of the security definitions library. Other error messages that are issued by PSF describe the precise error condition.

System action

PSF releases the current data set back to JES and requests that it is held by the system.

Operator response

Notify the security administrator or the system programmer responsible for the security definitions library that this error occurred. See the publication that contains JES operator commands for your operating system for a command to release the data set for printing after the problem is corrected.

System programmer response

See the specific error conditions that are described in the accompanying messages to determine an appropriate response.

User response

Inform your system programmer that this error occurred.

APS230I **THE KEYWORD *value* IN THE *security label* MEMBER OF THE SECURITY DEFINITIONS LIBRARY IS NOT VALID.**

Explanation

A keyword that is not valid for entry in the security definitions library was found during the processing of the member for the specified security label. The name of the member in the security definitions library is the security label of the print job.

System action

PSF releases the current data set back to JES and requests that it is held by the system.

Operator response

Notify the security administrator or the system programmer responsible for the security definitions library that this error occurred. See the publication that contains JES operator commands for your operating system for a command to release the data set for printing after the problem is corrected.

System programmer response

Correct the keyword in the appropriate member of the security definitions library. See *PSF for z/OS: Security Guide* for information about the format of the security definitions library.

User response

Inform your system programmer that this error occurred.

APS231I **REQUIRED KEYWORD SECOVLY, UPADIM, OR UPAORG IS MISSING FROM AN ENTRY IN THE *security label* MEMBER OF THE SECURITY DEFINITIONS LIBRARY.**

Explanation

While PSF was processing an entry in a security definitions library member, PSF did not find a required keyword. The name of the member in the security definitions library is the security label of the print job.

System action

PSF releases the current data set back to JES and requests that it is held by the system.

Operator response

Notify the security administrator or the system programmer responsible for the security definitions library that this error occurred. See the publication that contains JES operator commands for your operating system for a command to release the data set for printing after the problem is corrected.

System programmer response

Add the required keyword to correct the entry in the appropriate member of the security definitions library. Cancel and restart the PSF startup procedure; then, release the job that is held. See *PSF for z/OS: Security Guide* for information about the format of the security definitions library.

User response

Inform your system programmer that this error occurred.

APS232I **PAPERNAME *value* IS NOT A SYSTEM-DEFINED PAPER NAME. IT WAS ENCOUNTERED WHILE PROCESSING THE *security label* MEMBER OF THE SECURITY DEFINITIONS LIBRARY.**

Explanation

While PSF was processing an entry in a security definitions library member, the PAPERNAME keyword was found. The paper name that is specified for this keyword is not a valid, system-defined paper name. The name of the member in the security definitions library is the security label of the print job.

System action

PSF releases the current data set back to JES and requests that it is held by the system.

Operator response

Notify the security administrator or the system programmer responsible for the security definitions library that this error occurred. See the publication that contains JES operator commands for your operating system for a command to release the data set for printing after the problem is corrected.

System programmer response

Correct the entry in the appropriate member of the security definitions library. See *PSF for z/OS: Security Guide* for information about the format of the security definitions library.

User response

Inform your system programmer that this error occurred.

APS233I **THE *value* KEYWORD IS OUT OF SEQUENCE IN THE *security label* MEMBER OF THE SECURITY DEFINITIONS LIBRARY.**

Explanation

While PSF was processing an entry in a member of the security definitions library, the specified keyword was found when a different keyword was expected. The name of the member in the security definitions library is the security label of the print job.

System action

PSF releases the current data set back to JES and requests that it is held by the system.

Operator response

Notify the security administrator or the system programmer responsible for the security definitions library that this error occurred. See the publication that contains JES operator commands for your operating system for a command to release the data set for printing after the problem is corrected.

System programmer response

Correct the entry in the appropriate member of the security definitions library. See *PSF for z/OS: Security Guide* for information about the format of the security definitions library.

User response

Inform your system programmer that this error occurred.

APS234I **THE SECOVLY KEYWORD WAS FOUND BUT NO OVERLAYS WERE SPECIFIED IN THE *security label* MEMBER OF THE SECURITY DEFINITIONS LIBRARY.**

Explanation

While PSF was processing an entry in a security definitions library member, the SECOVLY keyword was found, followed by another keyword. An overlay name was expected. At least one overlay name is required to do either data page labeling or separator page labeling for the job. The name of the member in the security definitions library is the security label of the print job.

System action

PSF releases the current data set back to JES and requests that it is held by the system.

Operator response

Notify the security administrator or the system programmer responsible for the security definitions library that this error occurred. See the publication that contains JES operator commands for your operating system for a command to release the data set for printing after the problem is corrected.

System programmer response

Correct the entry in the appropriate member of the security definitions library. See *PSF for z/OS: Security Guide* for information about the format of the security definitions library.

User response

Inform your system programmer that this error occurred.

APS235I **THE UNIT *unit* IN THE *security label* MEMBER OF THE SECURITY DEFINITIONS LIBRARY IS NOT VALID.**

Explanation

While PSF was processing an entry in a security definitions library member, an incorrect unit of measurement was processed. The name of the member in the security definitions library is the security label of the print job.

System action

PSF releases the current data set back to JES and requests that it is held by the system.

Operator response

Notify the security administrator or the system programmer responsible for the security definitions library that this error occurred. See the publication that contains JES operator commands for your operating system for a command to release the data set for printing after the problem is corrected.

System programmer response

Correct the entry in the appropriate member of the security definitions library. See *PSF for z/OS: Security Guide* for information about the format of the security definitions library.

User response

Inform your system programmer that this error occurred.

APS236I **THE NUMBER *number* IN THE security label MEMBER OF THE SECURITY DEFINITIONS LIBRARY IS NOT VALID.**

Explanation

While PSF was processing an entry in a security definitions library member, a number was processed that either is not numeric or is outside the valid range. The name of the member in the security definitions library is the security label of the print job.

System action

PSF releases the current data set back to JES and requests that it is held by the system.

Operator response

Notify the security administrator or the system programmer responsible for the security definitions library that this error occurred. See the publication that contains JES operator commands for your operating system for a command to release the data set for printing after the problem is corrected.

System programmer response

Correct the entry in the appropriate member of the security definitions library. See *PSF for z/OS: Security Guide* for information about the format of the security definitions library.

User response

Inform your system programmer that this error occurred.

APS237I **A PAPER SIZE MATCHING THE LOADED PAPER WAS NOT FOUND IN THE security label MEMBER OF THE SECURITY DEFINITIONS LIBRARY.**

Explanation

No entry was found in the security definitions library member to match the size of the paper loaded in one of the printer bins. The name of the member in the security definitions library is the security label of the print job.

System action

PSF releases the current data set back to JES and requests that it is held by the system.

Operator response

An unusual paper size might be inadvertently left in the specified bin. If so, replace the bin contents with paper of the correct size.

System programmer response

Make sure that the paper loaded in every bin of the printer has a corresponding PAPERNAME or PAPERSIZE specification in the security definitions library member listed in the message. Also, ensure that the PAPERSIZE specified is within plus or minus 0.04 inches of the actual form size loaded in the printer. See *PSF for z/OS: Security Guide* for information about the format of the security definitions library.

User response

Inform your system programmer that this error occurred.

APS239I **SYSTEM ACTION TAKEN: THE ERRORS LISTED OCCURRED DURING PROCESSING OF A SECURE RESOURCE. PROCESSING OF THE DATA SET WAS TERMINATED.**

Explanation

An error occurred during processing of a secure resource. The objects that are processed are provided to other PSF messages to identify the location of the error in the resource.

System action

PSF releases the current data set back to JES and requests that it is held by the system.

Operator response

Notify the security administrator or the system programmer responsible for the security definitions library that this error occurred. See the publication that contains JES operator commands for your operating system for a command to release the data set for printing after the problem is corrected.

System programmer response

To determine an appropriate response, see the specific error conditions described in the accompanying messages.

User response

To determine an appropriate response, see the specific error conditions described in the accompanying messages.

APS240I **THE OVERLAY NAME *name* IN THE security label MEMBER OF THE SECURITY DEFINITIONS LIBRARY IS NOT VALID.**

Explanation

While PSF was processing an entry in a security definitions library member, an overlay name was processed that is too long. The name of the member in the security definitions library is the security label of the print job.

System action

PSF releases the current data set back to JES and requests that it is held by the system.

Operator response

Notify the security administrator or the system programmer responsible for the security definitions library that this error occurred. See the publication that contains JES operator commands for your operating system for a command to release the data set for printing after the problem is corrected.

System programmer response

Correct the entry in the appropriate member of the security definitions library. See *PSF for z/OS: Security Guide* for information about the format of the security definitions library.

User response

Inform your system programmer that this error occurred.

APS241I **SYSTEM ACTION TAKEN: THE ERRORS OCCURRED DURING PROCESSING OF FINISHING OPERATION TRIPLETS. THESE FINISHING OPERATION TRIPLETS WILL NOT BE USED IN THE PROCESSING OF THE DATA SET. THE PROCESSING OF THE DATA SET CONTINUES.**

Explanation

A Finishing Operation triplet is not valid or forms an incorrect request because it is not compatible with other triplets in the same request. The triplet is not

used to process this data set. Informational messages that precede this message explain why the Finishing Operation triplet cannot be used.

System action

The triplet is ignored and processing continues. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS242I **CUT-SHEET EMULATION CAUSED TOO MANY COPY CONTROLS TO BE GENERATED FOR THE CURRENT FORM ENVIRONMENT GROUP.**

Explanation

For a given physical page, up to 256 bytes of data can be specified for the printer command that describes the copies and modifications to be made. When Cut-Sheet Emulation is being used, PSF must modify the printer command. The modifications for Cut-Sheet Emulation caused data for the printer command to exceed 256 bytes. PSF builds the printer command from data contained in the form definition.

System action

The form definition that causes the error for Cut-Sheet Emulation is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

Use the information that is provided in the User Response section to correct this error.

User response

Either reduce the number of copies that are specified, or reduce the number of modifications (such as suppressions or overlays) specified. Otherwise, split these functions between two or more Form Environment Groups in two or more medium maps (COPYGROUPS). Then, include in your input two or more identical copies of the same page, each of which selects an appropriate copy group by use of the Invoke Medium Map (IMM) structured field.

If you created the structured fields for the form definition, the number of copies or copy groups is specified in the Medium Copy Count structured field, and the medium modifications are specified in the Medium Modification Control (MMC) structured field. For more information about the MCC, MMC, and IMM structured fields, see *Mixed Object Document Content Architecture Reference*.

APS244I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE <i>structured field name</i> STRUCTURED FIELD CONTAINS TOO MANY REPEATING GROUPS.
----------------	--

Explanation

The structured field name contains more repeating groups than are allowed. The structured field in which the error appears can be in a Resource Environment

Group (REG), a composed text page, an overlay, or a page definition.

System action

If this error occurs in a resource, PSF stops processing the data set. If this error occurs in a REG, PSF stops processing the REG and continues processing the data set. If this error occurs in a composed text page, PSF stops processing the current page. PSF attempts to find the end of the current page and resume printing on the next page. If unable to find the end of the current page, PSF stops printing the data set. PSF issues more messages that identify the processing environment in which the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. For more information about the structured field, see *Mixed Object Document Content Architecture Reference*. If the structured field contains no error, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or the resource, consult your system programmer.

APS245I	A COMPLEX IM IMAGE OBJECT CONTAINS DATA WHICH IS NOT VALID OR IS INCORRECT. THE COMPLEX IM IMAGE OBJECT CANNOT BE CONVERTED TO AN IO IMAGE OBJECT.
----------------	---

Explanation

This message is issued when PSF converts a complex IM image object to an IO image object and the image size is not large enough to contain the image raster data from the IRD structured fields. This message is

issued only when PSF Exit 7 or the Printer Inventory requested that PSF convert a complex IM image object to a single IO image object.

This message is issued if any of these is true:

- The XCSIZE parameter value of the ICP structured field is larger than the calculated image X size.
- The YCSIZE parameter value of the ICP structured field is larger than the calculated image Y size.
- The XCOSET plus XFILSIZE parameter values of the ICP structured field are larger than the calculated image X size.
- The YCOSET plus YFILSIZE parameter values of the ICP structured field are larger than the calculated Y size.

When PSF converts a complex IM image object to an IO image object, PSF calculates the image size by subtracting the X and Y image origins from the X and Y page sizes.

The X and Y image origins are from the XOAOSSET and YOAOSSET parameter values of the IOC structured field.

The X and Y page sizes are from the XPGSIZE and YPGSIZE parameter values of the PGD structured field, if the image object is in a MO:DCA data set or in an overlay, or is embedded in a data set containing line data. For an image object in a page segment, the X and Y page sizes that are used by PSF are from the X and Y paper sizes of the current media source (media bin).

The IOC and ICP structured fields are in a MO:DCA data set, in an overlay, or in a page segment, or are embedded in a data set containing line data. The PGD structured field is in a MO:DCA data set, in an overlay, or in a page definition.

System action

PSF stops processing the image object and issues more messages that identify the processing environment in which the error occurred. PSF sends the part of the image that was successfully processed, if any, to the printer. PSF then continues processing the current data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer that this error occurred.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource

with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the resource or print data set containing the image, correct the error in the referenced structured field, and resubmit the print request. For more information about the MMC structured field, see *Mixed Object Document Content Architecture Reference*. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the resource or print data set containing the image, consult your system programmer.

APS246I

THE UPADIM VALUE IN THE security label MEMBER OF THE SECURITY DEFINITIONS LIBRARY WAS EITHER MISSING OR NOT VALID FOR THE CURRENT PAGE SIZE AND PAGE TOP.

Explanation

Either the UPADIM parameter was not specified in the appropriate entry in a security definitions library member, or one or both of the values were not valid. The appropriate entry is based on the page size and top specification. The name of the member in the security definitions library is the security label of the print job.

System action

PSF releases the current data set back to JES and requests that it is held by the system.

Operator response

Notify the security administrator or the system programmer responsible for the security definitions library that this error occurred. See the publication that contains JES operator commands for your operating system for a command to release the data set for printing after the problem is corrected.

System programmer response

Ensure that valid values are specified for the UPADIM parameter in the member of the security definitions library referenced in the message. See *PSF for z/OS: Security Guide* for information about the format of the security definitions library.

User response

Inform your system programmer that this error occurred.

APS247I THE TOP KEYWORD VALUE *value* IN THE *security label* MEMBER OF THE SECURITY DEFINITIONS LIBRARY IS NOT VALID.

Explanation

While PSF was processing the member for the specified security label in a security definitions library, an incorrect value for the TOP keyword was found. The name of the member in the security definitions library is the security label of the print job.

System action

PSF releases the current data set back to JES and requests that it is held by the system.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Correct the parameter in the appropriate member of the security definitions library. See *PSF for z/OS: Security Guide* for information about the format of the security definitions library.

User response

Inform your system programmer that this error occurred.

APS248I MULTIPLE COPIES FROM DIFFERENT INPUT BINS WERE REQUESTED WHILE PAGE LABELING WAS IN EFFECT, BUT THE BIN ATTRIBUTES DID NOT MATCH.

Explanation

Multiple copies from different input bins were requested in the form definition, but the two bins are loaded with paper of different sizes. Because page labeling is in effect, if multiple copies are requested from different input bins, the input bins must be configured the same.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment in which the error occurred. If the error

occurred on a separator page or the message data set, PSF releases the current data set back to JES and requests that the system hold it.

Operator response

If the form definition is correct, and copies are needed from the specified input bins, load both bins with paper of the same size. If the message displays on the operator's console, it indicates that the error occurred for a separator page or for the message data set. Check that the input bins are loaded with paper of the correct size. If yes, notify your system programmer of the problem.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

Change the form definition to request multiple copies from input bins that have the same paper size configuration, and resubmit the print request.

APS249I MICR FONT *micr font name* WAS SPECIFIED FOR A PRINTER THAT EITHER DOES NOT SUPPORT MICR FONTS OR HAS THE MICR FONT SUPPORT DISABLED.

Explanation

The specified font supports magnetic ink character recognition (MICR), but either the device does not support MICR fonts or the support is disabled.

In Advanced Function Presentation (AFP) fonts, the Font Control (FNC) structured field indicates that the font supports MICR.

When mapping TrueType and OpenType fonts, the Data Object Font Descriptor triplet (X'8B') indicates that the font supports MICR.

System action

PSF cannot print the current data set. PSF stops processing and printing the data set. PSF issues more messages that identify the processing environment in which the error occurred. PSF releases the current data set back to JES and requests that it is held by the system, unless PRERROR=QUIT was specified on the OUTPUT statement.

Operator response

If the printer is disabled, enable it, if appropriate.

System programmer response

No response is necessary.

User response

If you do not want MICR fonts, select a non-MICR font for the data set. If you do want MICR fonts, verify that the printer supports MICR. If the printer does support MICR, verify that the support is enabled; otherwise, choose a printer that supports MICR.

APS250I DATA IN A PAGE OR RESOURCE IS MISSING: THE REQUIRED STRUCTURED FIELD *structured field name* COULD NOT BE FOUND TO COMPLETE THE PROCESSING OF A PAGE OR RESOURCE.

Explanation

The structured field that is identified in this message is required to complete the processing of a page or a resource. This structured field was not found before the end of the page or resource was encountered.

System action

PSF stops processing the current page, and any accumulated data for the current page is printed.

PSF attempts to find the end of the current page and resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set. If the error occurs as a result of a missing structured field within an inline resource, PSF stops printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the

print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APS251I DATA IN A FORMDEF RESOURCE IS MISSING: THE FORMDEF DOES NOT CONTAIN ANY MEDIUM MAPS.

Explanation

The form definition did not specify any medium maps; however, a medium map is required in order to print a page.

System action

The form definition is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error

might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS252I THE FORM DEFINITION OR THE JCL COPIES PARAMETER SPECIFIED MULTIPLE COPIES OF A PAGE, BUT THE PRINTER DOES NOT SUPPORT THIS FUNCTION.

Explanation

More than one uncollated copy of a page was requested for this print request, but the printer that is selected to print the job does not support this function. The multiple copies were requested either by the JCL COPIES parameter or by the Medium Copy Count (MCC) structured field in the form definition.

System action

PSF prints only one copy of the page, and processing continues.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involved separator pages or the message data set, change the form definition that is named in the PRINTDEV statement that is used for that type of output so that it does not request multiple copies.

User response

If you require multiple copies of a page, resubmit the print request to a printer that supports the function.

If you do not require multiple copies of a page, and if you specified the form definition or the COPIES parameter in the JCL for the print job, do one of these:

- Specify a form definition that does not request multiple copies of a page, and resubmit the print request.
- Remove the request for multiple copies of a page from the form definition, and resubmit the print request with the same form definition specified in your JCL.
- Change the COPIES parameter specification in your JCL, and resubmit the print request.

If you do not require multiple copies of a page, and if you did not specify the form definition or the COPIES

parameter in the JCL for the print job, resubmit the print request, specifying either a COPIES parameter of one or a form definition that does not request multiple copies of a page in the JCL for your print job.

APS253I DATA IN A FORMDEF RESOURCE IS NOT VALID: THE PRINT QUALITY VALUE IN MMC STRUCTURED FIELD, ID *identifier*, IS NOT ACCEPTABLE.

Explanation

The Medium Modification Control (MMC) structured field specified a print quality value of 0, which is outside the valid range. The MMC structured field is contained in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the MMC structured field and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data*

Reference for more information about the structured field. If the MMC has no errors, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS254I DATA IN A FORMDEF RESOURCE IS NOT VALID: THE OFFSET STACKING VALUE IN MMC STRUCTURED FIELD, ID *identifier*, IS NOT ACCEPTABLE.

Explanation

The Medium Modification Control (MMC) structured field specified an offset stacking value other than 0 or 1. The MMC structured field is in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the MMC structured field and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data*

Reference for more information about the structured field. If the MMC has no errors, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS255I THE INPUT BIN WITH COMPONENT ID *component ID*, MEDIA NAME *media name*, BIN NUMBER *bin number* WAS NOT SUPPORTED ON THE PRINTER. AN ALTERNATE BIN WAS SUBSTITUTED.

Explanation

The Medium Modification Control (MMC) structured field specified a media selection that does not exist on the selected printer. A value of *** for any of the three values means that piece of information was not provided by the MMC structured field. The input bin is selected by a media source selector keyword, media type local ID keywords, or both in the MMC structured field. The media type local ID keywords specify the ID of a Map Media Type (MMT) structured field that contains an Object Identifier (OID), Media Name, or both. The MMC and MMT structured fields are in the form definition.

System action

PSF issues this message and continues processing, selecting paper from an alternative bin.

Operator response

No response is necessary.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If the output is not acceptable, submit the print request to a printer that supports the specified media selection. If you want to use the original printer, and if you created the structured fields for the form definition, specify a supported bin in the MMC structured field. For more information about the MMC structured field, see *Mixed Object Document Content Architecture Reference*. If the structured field contains the component ID, media name, or number of a supported bin, the error might be a PSF logic error. If you used a program to create the structured fields for

the form definition, ensure that the input to that program specified a supported bin. If it did, consult your system programmer.

APS256I **DUPLEXING WAS SPECIFIED IN THE MMC STRUCTURED FIELD, BUT THE DUPLEX PAPER PATH IS DISABLED AT THE PRINTER. THE OUTPUT IS PRINTED SIMPLEX.**

Explanation

The Medium Modification Control (MMC) structured field requested duplexing, but the duplex paper path is disabled at the printer. The MMC structured field is contained in the form definition.

System action

PSF continues processing, printing the data set simplex.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

If simplex output is not acceptable, submit the print request to a printer that has duplexing available, or ensure that the duplex paper path is enabled on the original printer before you resubmit the print request.

APS258I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: *structured field* STRUCTURED FIELD IS NOT ALLOWED BETWEEN OBJECTS.**

Explanation

The structured field that is identified in this message is not allowed at the point in the input data stream or resource at which it was found.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set,

or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: [Diagnosis](#)* for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured fields are in the correct order, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or resource, consult your system programmer.

APS259I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE X-DIRECTION AND Y-DIRECTION L-UNITS PER UNIT BASE VALUES SPECIFIED IN THE *structured field* STRUCTURED FIELD DO NOT MATCH.**

Explanation

The X-direction and Y-direction L-units per Unit Base values in the structured field that is identified in the message are not identical.

System action

PSF cannot print the current page. PSF tries to find the end of the current page and resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

If this error occurs in a Resource Environment Group (REG), PSF stops processing the REG and continues processing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set,

or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APS260I	THE OBJECT SPECIFIED WITH THE <i>structured field</i> STRUCTURED FIELD IS NOT SUPPORTED ON THIS PRINTER. THIS MESSAGE IS ONLY ISSUED ONCE PER PRINT DATA SET FOR A GIVEN STRUCTURED FIELD OR ONCE PER RESOURCE.
----------------	--

Explanation

PSF encountered a valid Advanced Function Presentation (AFP) object that is not supported by the printer. The object is identified either by its Begin structured field, or by an Invoke structured field such as Include Page Overlay (IPO), or by an OTH record (object container without MO:DCA structured fields that are wrapping the data).

System action

If the Begin or Include structured field is embedded in a page or overlay OR the Begin or Include structured field or the OTH record is in a resource included by a page or overlay, PSF stops processing the page or overlay. PSF attempts to locate the end of the current page and resume processing on the next page. If the end of the current page cannot be located, PSF stops printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the separator page data set contained

the unsupported object type. Inform your system programmer that this error occurred.

System programmer response

Delete the unsupported object type from the separator page data set for this printer.

User response

To print the object type that is indicated in the message, submit the print job to a printer that supports the object type. For more information about what object types are supported by your printer, see your printer documentation.

APS261I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: STRUCTURED FIELD <i>structured field</i> CONTAINED A FONT LOCAL IDENTIFIER VALUE THAT WAS USED IN A PREVIOUS FONT MAPPING STRUCTURED FIELD.
----------------	--

Explanation

One or more font-mapping structured fields in the same Active Environment Group or Object Environment Group used the same font local identifier for different fonts. Fonts can be mapped in a Map Coded Font (MCF) and a Map Data Resource (MDR) structured field. Each font that is mapped must have a unique font local identifier. The MCF and MDR structured fields can be in the MO:DCA print data set, an overlay, a graphics object, a bar code object, or a page definition.

System action

If you created the structured fields in the object that contains the error, check the font local identifiers in the MCF and MDR structured fields for duplicates. If the MCF and MDR structured fields have no error, the error might be a PSF logic error. If you used a program to create the structured fields in the object that contains the error, consult your system programmer.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see [PSF for z/OS: *Diagnosis*](#) for assistance in determining the source of the problem.

User response

If you created the structured fields in the object that contains the error, check the font local identifiers in the MCF and MDR structured fields for duplicates. If the MCF and MDR structured fields have no error, the error might be a PSF logic error. If you used a program to create the structured fields in the object that contains the error, consult your system programmer.

See *Mixed Object Document Content Architecture Reference* for more information about the structured field.

APS262I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: STRUCTURED FIELD <i>structured field</i> CONTAINS AN INCORRECT ROTATION VALUE.
----------------	---

Explanation

The rotation value specified in the named structured field was not valid.

System action

PSF stops processing the current page. PSF attempts to find the end of the current page and resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set. PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see [PSF for z/OS: *Diagnosis*](#) for assistance in determining the source of the problem.

Diagnosis for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APS263I	AN ATTEMPT WAS MADE TO INCLUDE PAGE OVERLAY 01xxxxxx BUT EITHER THIS PAGE OVERLAY IS NOT NAMED IN AN MPO STRUCTURED FIELD OR THE MPO INDICATES THAT THIS OVERLAY IS FOR ANNOTATION ONLY.
----------------	---

Explanation

An Include Page Overlay (IPO) structured field names a page overlay, but the overlay was not previously defined in the Map Page Overlay (MPO) structured field, or the MPO indicates that the overlay is for annotation only, and is not to be used for printing. The MPO structured field is in the Active Environment Group (AEG) of the page that contains the IPO. The MPO might be in the AEG of the MO:DCA data or a page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see [PSF for z/OS: *Diagnosis*](#) for assistance in determining the source of the problem.

User response

If the MPO indicates that this overlay is for annotation only, another MPO structured field must be created in the AEG that defines the page overlay. If you are using the input data to define the name of your page overlay and your input data is ASCII, this error can occur because the resource name in the MPO would be in EBCDIC.

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APS264I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A RESOURCE MAPPED BY AN <i>structured field</i> STRUCTURED FIELD IN AN OBJECT ENVIRONMENT GROUP IS NOT NAMED IN THE ACTIVE ENVIRONMENT GROUP OF THE PAGE OR RESOURCE.
----------------	--

Explanation

A *structured field* structured field in an Object Environment Group names a resource, but that resource is not defined in the *structured field* structured field in the Active Environment Group of the page or resource that contains the Object Environment Group.

System action

If the object is in a page, PSF stops processing the page and continues processing the data set. If the object is in a resource, PSF stops processing and printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APS265I	THE FORMS DEFINITION OR THE JCL COPIES PARAMETER SPECIFIED MULTIPLE COPY SUBGROUPS, BUT THE PRINTER DOES NOT SUPPORT THIS FUNCTION.
----------------	--

Explanation

More than one copy subgroup was requested for this print job, but the printer that was selected to print the job does not support this function. The multiple copy subgroups were requested either by the JCL COPIES parameter or by the repeating groups referenced by the Medium Copy Count (MCC) structured field in the form definition.

System action

PSF stops processing and printing the data set. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involved separator pages or the message data set, change the form definition that is named in the PRINTDEV statement that is used for that type of output so that it does not request multiple copy subgroups.

User response

If you require multiple copy subgroups, resubmit the print request to a printer that supports the function.

If you do not require multiple copy subgroups and if you specified the form definition or the COPIES parameter in the print job for the JCL, do one of these:

- Specify a form definition that does not request multiple copy subgroups, and resubmit the print request.

- Remove the request for multiple copy subgroups from the form definition, and resubmit the print request with the same form definition specified in your JCL.
- Change the COPIES copy group parameter specification in your JCL, and resubmit the print request.

If you do not require multiple copy subgroups, and if you did not specify the form definition or the COPIES parameter in the JCL for the print job, resubmit the print request, specifying either a COPIES subgroup parameter or a form definition that does not request multiple copy subgroups in the JCL for your print job.

APS267I **EITHER NO ENVIRONMENT GROUP WAS SPECIFIED FOR THE PAGE OR AN ERROR OCCURRED IN THE ENVIRONMENT GROUP.**

Explanation

Either no environment group was specified, or an error occurred in one of the structured fields in the environment group. If an environment group was present but contained an error, a previous PSF message identifies the error. The environment group that caused this error might be in an overlay, a page definition, or the MO:DCA data.

System action

PSF stops processing the current page. PSF attempts to find the end of the current page and resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APS268I **AN ENTRY IN AN MCF STRUCTURED FIELD DOES NOT CONTAIN A FONT CHARACTER SET REFERENCE.**

Explanation

One of the repeating groups in a Map Coded Font Format 2 (MCF-2) structured field specifies the code page information but not the font character set. This error was detected during the processing of a GOCA object within a page or overlay resource.

System action

PSF continues processing. The repeating group that contains the error is ignored.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

No response is necessary.

APS269I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN INCORRECT VALUE WAS SPECIFIED AS THE L-UNITS PER UNIT BASE IN THE *structured field name* STRUCTURED FIELD.**

Explanation

Several structured fields specify an L-units per Unit Base value: Medium Descriptor (MDD), Page Descriptor (PGD), Presentation Text Descriptor (PTD-2), Object Area Descriptor (OBD), Graphics Data Descriptor (GDD), Image Data Descriptor (IDD), Bar Code Data Descriptor (BDD), Image Input Descriptor (IID), Include Object (IOB), and Preprocess Presentation Object (PPO). The value specified was outside the range of acceptable values

System action

PSF cannot print the current page. PSF tries to find the end of the current page and resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

If this error occurs in a Resource Environment Group (REG), PSF stops processing the REG and continues processing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APS270I	DATA IN A PAGEDEF RESOURCE IS MISSING: THE PAGEDEF DOES NOT CONTAIN ANY DATA MAPS.
----------------	---

Explanation

The page definition did not specify any data maps, but a data map is required to print a data set that contains line data.

System action

The page definition is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS271I	DATA IN A FORMDEF RESOURCE IS NOT VALID: THE DUPLEX SPECIFICATION IN THE PGP STRUCTURED FIELD IS NOT ACCEPTABLE.
----------------	---

Explanation

The duplex specification value in the Page Position (PGP) structured field is not acceptable. The PGP structured field is in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.

- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS272I DATA IN A FORMDEF RESOURCE IS NOT VALID: THE PGP STRUCTURED FIELD DOES NOT CONTAIN A PAGE ORIGIN POSITION FOR THE FRONT SIDE OF A SHEET.

Explanation

The Page Position format-2 (PGP) structured field must contain a repeating group that defines the Page Origin Position for the front side. This value is also used for the back side of a duplex sheet, unless the PGP structured field contains a repeating group that specifies the Page Origin Position for the back side of the sheet. The PGP structured field is in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS273I DATA IN A FORMDEF RESOURCE IS NOT VALID: THE CONSTANT FORMS CONTROL VALUE IN THE MMC STRUCTURED FIELD ID *identifier* IS NOT ACCEPTABLE.

Explanation

The Constant Forms Control modification in the Medium Modification Control (MMC) structured field contained an unsupported value. The MMC structured field is in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS274I	DATA IN A FORMDEF RESOURCE IS NOT VALID: THE MODIFICATIONS SPECIFIED IN THE MCC STRUCTURED FIELD INCLUDE CONFLICTING CONSTANT FORMS CONTROL VALUES FOR THE SAME SIDE OF THE SHEET.
----------------	---

Explanation

All Medium Modification Control (MMC) structured fields that are referenced by the Medium Copy Count (MCC) structured field must use the same Constant Forms Control value for the same side of a sheet. The MMC and MCC structured fields are in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS275I	DATA IN A FORMDEF RESOURCE IS NOT VALID: MEDIUM MAP <i>medium map name</i> SPECIFIES
----------------	---

ONLY CONSTANT DATA FOR A PAGE.

Explanation

An attempt was made to process a page by use of a medium map that does not place any data on the sheet. The following combinations of controls can cause this message to be issued:

- Constant Forms Control for both the front and back sides of a duplexed sheet.
- Constant Forms Control for the front side of a simplex sheet.
- Basic N_UP requested, Constant Forms Control for the front side of a duplexed sheet, and the repeating group of the Page Position (PGP) Format 2 structured field for the back side of the sheet specifies a *PgFlgs* parameter value that requests no variable page data.
- Basic N_UP requested, Constant Forms Control for the back side of a duplexed sheet, and the repeating group of the PGP structured field for the front side of the sheet specifies a *PgFlgs* parameter value that requests no variable page data.
- Enhanced N_UP requested and all of the repeating groups of the PGP structured field specify a *PgFlgs* parameter value that requests no variable page data.

Another Medium Map must be invoked so that the remaining line or page data can be processed. The Constant Forms Control and the simplex/duplex requests are in the Medium Modification Control (MMC) structured field. To request basic N_UP, specify default page placement in the PGP structured field and specify N_UP in the MMC structured field. To request enhanced N_UP, specify explicit page placement in the PGP structured field and specify N_UP in the MMC structured field. The MMC and PGP structured fields are in the form definition.

System action

PSF cannot print the current data set. If unable to find the end of the page, PSF stops printing the data set. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

AP276I

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE BEGIN SEGMENT INTRODUCER IS MISSING IN THE FIRST GAD STRUCTURED FIELD IN A GRAPHICS OBJECT.

Explanation

The first Graphics Data (GAD) structured field in a graphics object does not contain a Begin Segment Introducer. PSF examines the Begin Segment Introducer of the first GAD structured field in a graphics object because some graphics applications add a comment record that must be removed before the graphics data is passed to the printer. The graphics object can be contained in a MO:DCA document, or an overlay, or it can be embedded in a data set containing line data.

System action

The printer you were using might attempt to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. If the graphics object is part of another resource, PSF stops processing and printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set

in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS278I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE MAPPING OPTION SPECIFIED IN THE *structured field name* STRUCTURED FIELD IS INCORRECT OR UNSUPPORTED.

Explanation

The structured field in error contained an incorrect Mapping Option value or the printer does not support the Mapping Option value. The structured field might be contained in a bar code object, graphics object, image object, presentation text object with an OEG, or object container object. Alternatively, it might be an Include Object (IOB) structured field or a Preprocess Presentation Object (PPO) structured field with an incorrect mapping option triplet.

System action

PSF stops processing the current page; then, tries to find the end of the current page and resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set. If this error occurs in a resource, PSF stops processing the data set. If this error occurs in a Resource Environment Group (REG), PSF stops processing the REG and continues processing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the print data set or resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the correct format of the referenced structured field. If the structured field is correct, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or resource, consult your system programmer.

APS279I A REQUESTED FONT RESOURCE IS NOT CURRENTLY RESIDENT IN THE PRINTER, OR THE CORRECT PRINTER FONT CARD IS NOT INSTALLED. THE HOST VERSION OF THE FONT IS NOT DOWNLOADABLE SINCE IT DOES NOT CONTAIN RASTER DATA.

Explanation

Some printers might have user-installable fonts on cards or some other media. To support formatting output on the host system for printing with these restructured fonts, the host font libraries might contain font resources with only formatting reference information, but no downloadable font patterns. This message might indicate that the referenced fonts were not installed in the printer when this data set was printed.

Bytes 17-19 of the Font Control (FNC) structured field contain a Pattern Data Count of 0. This value represents the total number of data bytes in the font character set. The FNC structured field is in the font character set.

System action

PSF cannot print the current page, but it attempts to find the end of that page and to resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF prints more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem. Run APSRMARK and mark the font as PUBLIC, so that the data set can be printed with the printer-resident font. If the font is marked as PUBLIC, verify that the marking is correct.

Ensure that both the code page and character set of the font are marked PUBLIC. In the font data definition referenced by the FONTDD parameter in the PSF PRINTDEV statement, ensure that the font libraries that contain marked resources are specified first in the library concatenation order.

Ensure that requested font or symbol set is mapped to a valid GRID. If the current entry seems to be valid, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

If the print request was submitted to a 4028 Printer, verify that the correct font cartridge was loaded in the printer when the job was processed. If it was not, resubmit the print request when the correct cartridge is loaded.

If the correct cartridge was loaded, or if you were printing on any other type of AFP printer, notify your system programmer.

APS280I THE RESOLUTION *resolution* PELS PER UNIT BASE OF THE RASTER FONT DOES NOT AGREE WITH THE RESOLUTION *resolution* PELS PER UNIT BASE OF THE DEVICE.

Explanation

The font resolution, which is specified in bytes 4-9 of the Font Control (FNC) structured field in the font character set, is incompatible with the device resolution. The device resolution is reported in the XOH Obtain Printer Characteristics (OPC) reply under IM-IMAGE AND CODED-FONT RESOLUTION SELF-DEFINING FIELD in the Printer Information report. See

PSF for z/OS: Diagnosis for information about the report.

System action

PSF cannot print the current page. PSF attempts to find the end of the current page and resume printing on the next page. If PSF is unable to find the end of the page or is printing an interrupt message page or message data set, it stops printing the data set. If PSF is printing an interrupt message page or message data set, it releases the current data set back to JES and requests that it is held by the system.

PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

Ensure that the font resolution of the fonts in the system font library is compatible with the device resolution. If not, update the PRINTDEV statement for the printer to specify the correct resolution font libraries. If the printer supports multiple resolutions, see *PSF for z/OS: Customization* to set up multiple resolution resource libraries.

If XTP7FMT is specified in Exit 7 or the resolution is specified in the Printer Inventory for this printer, ensure that the value matches the resolution that is supported by the device. Otherwise, determine whether the font requires any preprocessing to match the resolution of the device; if so, ensure that the preprocessing was done. For more information about converting 240-pel fonts to 300-pel fonts, see *PSF for z/OS: Customization*.

User response

Correct the mismatch between the font resolution and the device resolution:

- Send the print job to a device that matches the resolution of your font. Your system programmer might be able to help you find a matching device. If you do not have access to a device that matches the font resolution, you might be able to update the configuration of the printer to accept the resolution for the font. Some printers can be configured to accept multiple resolutions, also called automatic

resolution mode. Ask your printer operator if you can change the printer configuration.

- Change the font that you are using:
 1. Determine the library location of the font in error:
 - Look for the library location of the font in the job's Resource Summary by Name section of an AFP Statistics (AFPSTATS) report. See *PSF for z/OS: User's Guide* for information about how to create the AFPSTATS report.
 - Browse the input data set to see whether the font is located inline in the data set.
 - Browse the JCL for the print job to see whether user libraries are specified. If they are, browse the libraries for the font in error.
 2. Correct the library location, depending on where the font in error is located:

Located inline

Edit the input data stream and remove the inline font in error so that a system library font is used with the matching resolution of the device.

Located in a user library

- Delete the font in error from the user library so that a system library font is used with the matching resolution of the device.
- Edit your JCL OUTPUT statement and remove the user library that contains the font in error so that a system library font is used with the matching resolution of the device. If the user library specifies other resources, they must also be located in the system libraries that you are using.

Located in a system library

If you specified RESFMT on the JCL OUTPUT statement, ensure that it matches the resolution of the resource objects that are used by the job and the resolution of your device. If you are unable to correct the mismatch, inform your system programmer.

If you created the structured fields for the font and the resolution was specified incorrectly, correct the error and replace the font in the library. See *Font Object Content Architecture Reference* for more information about the structured field. If you used a program to create the structured fields for the font, contact your system programmer.

APS281I THE VERTICAL POINT SIZE VALUE IN THE FND STRUCTURED FIELD IS NOT ACCEPTABLE.

Explanation

The vertical point size value in the FND structured field is either not valid or not supported by this printer. PSF supports only values 40 - 720 inclusive. The FND structured field is in the font character set.

System action

PSF cannot print the current page. PSF attempts to find the end of the current page and resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

APS282I INCORRECT CHARACTER PATTERN ADDRESSES IN THE FNM REPEATING GROUPS.

Explanation

Bytes 4–7 of the Font Patterns Map (FNM) structured field contain the pattern data address. This value represents the offset in bytes of the start of the raster pattern for a character.

System action

PSF cannot print the current page. PSF attempts to find the end of the current page and resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF prints more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem. Run APSRMARK and mark the font as PUBLIC, to allow printing with the printer-resident font. If the font has been marked as PUBLIC, verify that the marking is correct.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer. If the font is a metric-only font that is supplied by IBM, consult your system programmer.

APS283I	MEDIUM MAP <i>medium map name</i> IN A FORMDEF RESOURCE REQUESTED N_UP <i>n</i>, BUT IT IS NOT SUPPORTED BY THIS PRINTER. THE OUTPUT IS PRINTED N_UP <i>m</i>.
----------------	---

Explanation

The Medium Modification Control (MMC) structured field requested N_UP *n*, but the device does not support N_UP printing or it does not support *n* pages on a sheet side.

System action

PSF continues printing the output in the highest N_UP supported by the printer.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. Verify that the printer microcode level supports N_UP printing. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If the output is not acceptable, submit the print request to a printer that supports N_UP printing with *n* pages per sheet side. If you created the structured fields for the form definition, correct the MMC structured field and resubmit the print request. For more information about the structured field, see *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference*. If the MMC structured field has no errors, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, consult your system programmer.

APS284I	A FORMDEF RESOURCE REQUESTED DUPLEX N_UP <i>n</i>, BUT THE COMBINATION IS NOT SUPPORTED BY THIS PRINTER. THE OUTPUT IS PRINTED SIMPLEX N_UP <i>n</i>.
----------------	--

Explanation

The Medium Modification Control (MMC) structured field requested N_UP *n* and duplexing, but the combination is not supported by this printer.

System action

PSF continues printing the output in simplex and the highest N_UP supported by the printer.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. Verify that the printer microcode level supports N_UP printing. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If the output is not acceptable, submit the print request to a printer that supports N_UP printing and duplex. If the printer supports duplexing and N_UP, and if you created the structured fields for the form definition, correct the MMC structured field and resubmit the print request. For more information about the structured field, see *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference*. If the MMC has no errors, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, consult your system programmer.

APS285I	DATA IN A FORMDEF RESOURCE IS NOT VALID: THE N_UP VALUE IN THE MMC STRUCTURED FIELD, ID <i>identifier</i>, IS NOT ACCEPTABLE.
----------------	--

Explanation

The Medium Modification Control (MMC) structured field specifies an N_UP value of zero.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the MMC with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the form definition, correct the MMC structured field and resubmit the print request. For more information about the structured field, see *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference*. If the MMC has no errors, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, consult your system programmer.

APS286I	DATA IN A FORMDEF RESOURCE IS NOT VALID: THE SET OF MODIFICATIONS SPECIFIED IN THE MCC STRUCTURED FIELD INCLUDES CONFLICTING N_UP VALUES.
----------------	--

Explanation

The Medium Copy Count (MCC) structured field refers to one or more Medium Modification Control (MMC) structured fields, which include requests for different N_UP values. You cannot request different N_UP values within the same medium map. The MCC and MMC structured fields are in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the MMC structured field and resubmit the print request. For more information about the structured field, see *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference*. If the MMC has no errors, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, consult your system programmer.

APS287I DATA IN A FORMDEF RESOURCE IS NOT VALID: THE MEDIUM MAP CONTAINS A PMC STRUCTURED FIELD, BUT THE PRINTER DOES NOT SUPPORT PAGE OVERLAYS.

Explanation

The Page Modification Control (PMC) structured field specifies page overlays to be used with N_UP processing. This error occurs when PSF finds a PMC structured field in a medium map, and the device does not support page overlays. PSF detected this error while it is processing a page.

System action

PSF ignores the page overlays and continues processing.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Redirect the output to a printer that supports page overlays.

APS288I PRINT LABELING WAS SPECIFIED WITH EITHER N_UP OR CUT-SHEET EMULATION. THIS COMBINATION IS NOT SUPPORTED.

Explanation

The print labeling function was requested, and either medium map specifies an N_UP value greater than one, or the Cut-Sheet Emulation function is being used with the current medium map. Print labeling cannot be used with a function that requests placing multiple logical pages on a side of a sheet. PSF detected this error while it is processing a page.

System action

PSF stops processing and printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

Do not request print labeling in combination with either N_UP printing or Cut-Sheet Emulation printing in the same job. Submit the print job again.

APS289I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE

FONT SCALING SIZE VALUE SPECIFIED IN AN MCF STRUCTURED FIELD IS NOT ACCEPTABLE.

Explanation

The value that is specified for either the font vertical scale factor, the horizontal scale factor, or the font width is not within the acceptable range of 0 - 32767.

System action

PSF cannot print the current page. PSF attempts to locate the end of the current page and resume printing on the next page. If the end of the current page cannot be located, PSF stops printing the data set. PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. For more information about the structured field, see *Mixed Object Document Content Architecture Reference*. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or the resource, consult your system programmer.

APS290I THE SELECTABLE MEDIUM MODIFICATION (*identifier*) SPECIFIED IN THE MMC STRUCTURED FIELD IS NOT CURRENTLY AVAILABLE AT THE DEVICE.

Explanation

The Selectable Medium Modification ID in the Medium Modification Control (MMC) structured field contains a Modification ID not currently available at the printer, or the printer does not support medium modifications. The MMC structured field is in the form definition.

System action

PSF stops processing and printing the data set. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the Medium Modification ID is defined for a separator page or the message data set in the PSF startup procedure. If the Medium Modification ID cannot always be available on the printer, consult with your system programmer.

To determine how to make the determined Medium Modification ID available for use, see the operator's manual for your printer or your post-processing device.

System programmer response

If this message displays on the operator's console, use the information provided in the Operator Response section. If the Medium Modification is not what you wanted, modify the PSF startup procedure as described in the User Response section.

User response

To receive the printed output with the medium modification identified, take any one of these actions:

- Specify the FORMS keyword on the OUTPUT statement of the JCL with a parameter as determined by local procedures.
- Request to the operator that the identified medium modifications be made available on the printer.
- Submit the job to a printer that contains the identified medium modification.

If the medium modification identified is not what you wanted, take either of these actions:

- Specify a form definition that contains a different medium modification, or none at all.
- Modify the form definition to require a different medium modification ID, or remove the use of the medium modification ID.

APS291I DATA IN A FORMDEF RESOURCE IS NOT VALID: THE SET OF MODIFICATIONS SPECIFIED IN

THE MCC STRUCTURED FIELD INCLUDES CONFLICTING SELECTABLE MEDIUM MODIFICATION CONTROL VALUES.

Explanation

Multiple MMC structured fields that are referenced by the MCC structured field do not use the exact same set of Selectable Medium Modification values.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. For more information about the structured field, see *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference*. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, consult your system programmer.

APS292I

A FORMDEF RESOURCE REQUESTED ENHANCED N_UP, BUT IT IS NOT SUPPORTED BY THIS PRINTER.

Explanation

Enhanced N_UP is not supported because of one of these:

- The Page Position (PGP) Format 2 structured field requested enhanced N_UP, but N_UP is not supported by this printer.
- The printer supports enhanced N_UP, and the printer was attached through distributed print function (DPF). However, enhanced N_UP is not supported through DPF.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set. PSF releases the current data set to JES and requests the system to hold it unless PRTEROR=QUIT is specified on the OUTPUT statement.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. Verify that the printer microcode level supports enhanced N_UP printing and that the printer is not attached through DPF. If the resource that contains the error is defined for the separator pages or the message data set, or as the default resource for user print data

sets in the PSF startup procedure, use the information that is provided in the User Response section to correct the error.

User response

Resubmit the job to a printer that supports enhanced N_UP and that is not attached through DPF; or, if you created the structured fields for the form definition, correct the error and resubmit the print request. For more information about the structured field, see *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference*. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, consult your system programmer.

APS293I **DATA IN A FORMDEF RESOURCE IS NOT VALID: ENHANCED N_UP WAS REQUESTED, BUT THE NUMBER OF REPEATING GROUPS IN THE PGP STRUCTURED FIELD DOES NOT MATCH THE N_UP VALUE SPECIFIED IN MEDIUM MAP *medium map name*.**

Explanation

When enhanced N_UP is requested, the number of repeating groups in the Page Position (PGP) Format 2 structured field must match the N_UP value that is multiplied by the number of sides of the sheet to be printed. If simplex is requested, the number of repeating groups in the PGP structured field must be equal to the value specified in the N_UP request. If duplex is requested, the number of repeating groups in the PGP structured field must be equal to twice the value specified in the N_UP request. To request enhanced N_UP, specify explicit page placement in the PGP structured field and specify N_UP in the Medium Modification Control (MMC) structured field. The simplex/duplex request is in the MMC structured field. The MMC and PGP structured fields are in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. For more information about the structured field, see *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference*. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, consult your system programmer.

APS294I **DATA IN A FORMDEF RESOURCE IS NOT VALID: THE SHEET SIDE PARAMETER VALUE *value* SPECIFIED IN THE PGP STRUCTURED FIELD IS NOT ACCEPTABLE.**

Explanation

A medium map or Document Environment Group in the current form definition contains a Page Position (PGP) Format 2 structured field with a repeating group that contains an incorrect value in the sheet side (*SHside*) parameter. For example:

- The *SHside* parameter specifies a value other than zero or one for the sheet side.
- The *SHside* parameter specifies a value greater than four for the partition number.

The PGP structured field is in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

SF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. For more information about the structured field, see *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference*. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, consult your system programmer.

APS295I	DATA IN A FORMDEF RESOURCE IS NOT VALID: THE PGP STRUCTURED FIELD SPECIFIES BOTH DEFAULT AND EXPLICIT PAGE PLACEMENT.
----------------	--

Explanation

A medium map or Document Environment Group in the current form definition contains a Page Position (PGP) Format 2 structured field that requests both default page placement and explicit page placement in

separate, repeating groups. Default page placement and explicit page placement are requested in the sheet side (*SHside*) parameter of the PGP structured field. The PGP structured field is in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. For more information about the structured field, see *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference*. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, consult your system programmer.

APS296I	DATA IN A FORMDEF RESOURCE IS NOT VALID: THE PGP STRUCTURED FIELD CONTAINS AN INCORRECT ROTATION, rotation.
----------------	--

Explanation

A medium map or Document Environment Group in the current form definition contains a Page Position (PGP) Format 2 structured field with a repeating group that contains an incorrect value in the page rotation (*PGorient*) parameter. The PGP structured field is in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. For more information about the structured field, see *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference*. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, consult your system programmer.

APS297I

**DATA IN A FORMDEF RESOURCE
IS NOT VALID: THE SHEET SIDE
PARAMETER VALUE OF THE PGP**

**STRUCTURED FIELD DOES NOT
MATCH THE SIMPLEX/DUPLEX OR
N_UP SPECIFICATION IN MEDIUM
MAP *medium map name*.**

Explanation

A medium map or Document Environment Group in the current form definition contains a Page Position (PGP) Format 2 structured field with a repeating group that contains an incorrect value in the sheet side (*SHside*) parameter. For example:

- The *SHside* parameter value specifies that a page is placed on the back side of the sheet, but the Medium Modification Control (MMC) structured field specifies simplex.
- The *SHside* parameter value specifies that a page is placed in partition number 3, but the MMC specifies 2-up format.

The MMC and PGP structured fields are in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource containing the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. For more information about the structured field, see *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference*. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, consult your system programmer.

APS298I **A FORMDEF RESOURCE REQUESTED ENHANCED N_UP AND DUPLEXING, BUT DUPLEXING IS NOT SUPPORTED BY THIS PRINTER OR BY THE INPUT BIN THAT WAS BEING USED.**

Explanation

When enhanced N_UP and duplex are requested, but the printer or the selected input bin does not support duplex, PSF cannot process the data set. The reason is that with enhanced N_UP, the Page Position (PGP) Format 2 structured field specifies the partition number and sheet side for each page placed on a sheet. If duplex is requested, PSF is not able to place pages in the requested partitions on the back side of the sheets. To request enhanced N_UP, specify explicit page placement in the PGP structured field and specify N_UP in the Medium Modification Control (MMC) structured field. The duplex request is in the MMC structured field. The MMC and PGP structured fields are in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set. PSF releases the current data set to JES and requests the system to hold it.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If you are running under Job Entry Subsystem (JES), use JES commands to release the data set to a printer

that supports enhanced N_UP and duplex functions. See *z/OS JES2 Commands* or *z/OS JES3 Commands* for information about the JES commands that release the data set for printing.

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

To receive the printed output with the requested enhanced N_UP and duplex, ask your print operator to reroute the data set to a printer that supports both.

If the enhanced N_UP and duplex request is not what you wanted, do one of these:

- Ask your print operator to use a different form definition for the data set and then release the data set for printing.
- Specify a different form definition and resubmit the print request; then, ask your print operator to purge your previous print request, which was held.

APS299I **AN IM IMAGE OBJECT CONTAINS DATA THAT IS NOT VALID OR IS INCORRECT. THE IM IMAGE OBJECT CANNOT BE CONVERTED TO AN IO IMAGE OBJECT.**

Explanation

This message is issued when PSF converts an IM image object to an IO image object and one of the image size values is zero or greater than X'7FFF'.

For a simple IM image object, this message is issued if either the XSize or the YSize parameter value of the IID structured field is zero or greater than X'7FFF'.

For a complex IM image object, this message is issued if one of the XCSize, YCSize, SFilSize, or YFilSize parameter values of the ICP structured field is zero or greater than X'7FFF'.

System action

PSF stops processing the image object and issues more messages that identify the processing environment in which the error occurred. PSF sends

the part of the image that was successfully processed, if any, to the printer. PSF then continues processing the current data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer that this error occurred.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was

valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the resource or print data set containing the image, correct the error in the referenced structured field and resubmit the print request. For more information about the structured field, see *Mixed Object Document Content Architecture Reference*. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the resource or print data set containing the image, consult your system programmer.

APS300 to APS399

APS300I **DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE NEXT LINE DESCRIPTOR IF SKIPPING PARAMETER VALUE IN LND STRUCTURED FIELD NUMBER *structured field number* IS 0.**

Explanation

The current record contains a control character that indicates a skip to a Line Descriptor (LND) structured field with a specific channel control. However, the LND structured field identified in this message had a value of 0 in its Next Line Descriptor IF SKIPPING parameter. The LND structured field is in the page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the object container that contains the error, verify that the input to that program was

valid. If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS301I **DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE NEXT LINE DESCRIPTOR IF SKIPPING PARAMETER VALUE IN LND STRUCTURED FIELD NUMBER *structured field number* IS *parameter value*. THIS EXCEEDS THE LNC STRUCTURED FIELD COUNT VALUE OF *parameter value*.**

Explanation

In the Line Descriptor (LND) structured field that is identified in this message, the value of the next LND IF SKIPPING parameter is greater than the total number of LND structured fields in the page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS303I	A METADATA OBJECT NAMED <i>name</i> IS OUT OF SEQUENCE IN THE DATA SET. THE METADATA OBJECT IS IGNORED, BUT PSF PROCESSING AND PRINTING IS NOT AFFECTED.
----------------	---

Explanation

An out of sequence metadata object is ignored in the data stream. Because metadata objects are not sent to the printer, the printed output is not affected. However, if this data stream is processed by transforms or transmitted by AFP Download Plus, this error might affect the output.

System action

PSF records this condition and continues processing.

Operator response

No response is necessary.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

Correct the out of sequence metadata object in the data stream so that problems do not occur if this data stream is processed by transforms or transmitted by AFP Download Plus. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If you used a program to create the structured field, contact your system programmer.

APS304I	A METADATA OBJECT NAMED <i>name</i> IS OUT OF SEQUENCE IN THE DATA STREAM. THE METADATA OBJECT IS IGNORED AND NOT TRANSMITTED WITH THE DATA SET. TO TRANSMIT THE METADATA, CORRECT THE DATA STREAM AND RESUBMIT THE JOB.
----------------	---

Explanation

An out of sequence metadata object is ignored in the data stream. However, because metadata objects might be used by transforms or other applications, this error might affect the output.

System action

AFP Download Plus records this condition, does not write the metadata object to the output file, and continues processing.

Operator response

No response is necessary.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is

provided in the User Response section to correct the error.

User response

Correct the out of sequence metadata object in the data stream so that problems do not occur if this data stream is processed by transforms or other applications that use the metadata object. If you created the structured field, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If you used a program to create the structured field, contact your system programmer.

APS307I DATA IN A PAGEDEF RESOURCE IS NOT VALID: IN LND STRUCTURED FIELD NUMBER *structured field number*, THE REUSE RECORD FLAG WAS SET BUT THE NEXT LINE DESCRIPTOR IF REUSING DATA PARAMETER WAS 0.

Explanation

In the Line Descriptor (LND) structured field that is identified in this message, the Reuse Record flag had a value of B'1', which indicates that the line data that is processed in this LND structured field must be reused and processed. The Next Line Descriptor If Reusing Data parameter must point to the LND structured field used to continue processing. However, the value for the Reusing Data parameter was X'0000', indicating the end of the chain. The LND structured field is contained in the page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the

input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS308I THE PRINTABLE AREA IS TOO SMALL TO PRINT MESSAGES WITH THE FONT SPECIFIED.

Explanation

A check was made to determine whether the messages would fit in the printable area when printed in the specified font on the paper size currently in the printer. Either fewer than 10 characters would fit on a line, or PSF calculated an incorrect value for the maximum baseline position. The values for the maximum baseline position are obtained from the printer; an incorrect value might indicate a microcode error that would cause PSF not to print messages. A value of fewer than 10 characters per line is too small and would also cause PSF not to print messages.

System action

The messages were not printed.

Operator response

Inform your system programmer that this error occurred.

System programmer response

If messages are to be printed, select a form, a logical page size, and a font with a character increment that allows messages to fit in the printable area. The form definition or page definition that is selected to process messages might be incorrect, or the font that is selected might be too large for the page size specified in the form definition or the page definition.

To determine the number of characters that fit on a line, determine the minimum width of either the logical page or the printable area on the physical page. From it, subtract the maximum inline position of the Line Descriptor (LND) structured field, and the form definition offset, plus twice the horizontal adjustment.

Divide the result by the character increment for the font.

User response

Inform your system programmer that this error occurred.

APS309I DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE REPEATING GROUP LENGTH PARAMETER VALUE IN CCP STRUCTURED FIELD CCP identifier IS NOT VALID.

Explanation

The Conditional Processing Control (CCP) structured field has an incorrect value. Either the Length of Repeating Groups parameter is zero, or the length of the repeating group data is not a multiple of the size specified in that parameter. The CCP structured field is in the page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot be initialized or cannot print a separator page or error messages. Inform your system programmer that this error occurred.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

Determine whether the structured field is correct. For more information about the structured field, see *Advanced Function Presentation: Programming Guide and Line Data Reference*. If the structured field is incorrect and was not created by an IBM licensed program, correct the error and resubmit the print request. If the structured field is incorrect and was created by an IBM licensed program, notify your system programmer. If the structured field is correct, the error might be a PSF logic error. In this case, notify your system programmer of this error.

APS310I DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE COUNT PARAMETER VALUE IN THE LNC STRUCTURED FIELD WAS 0.

Explanation

The Count parameter in the Line Descriptor Count (LNC) structured field in the data map of the page definition had a value of zero.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS312I DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE SIZE PARAMETER VALUE IN THE FDS STRUCTURED FIELD WAS 0.

Explanation

The Size parameter in the Fixed Data Size (FDS) structured field has a value of 0. The FDS structured field is in the page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS314I	DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE NUMBER OF REPEATING GROUPS PARAMETER VALUE IN CCP STRUCTURED FIELD <i>CCP identifier</i> IS NOT VALID.
----------------	--

Explanation

The Conditional Processing Control (CCP) structured field has an incorrect value. Either the Number of Repeating Groups parameter in the CCP structured field is zero, or the number of repeating groups does not match the number specified in the parameter. The CCP structured field is in the page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot be initialized or cannot print a separator page or error messages. Inform your system programmer that this error occurred.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS315I	DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE NEXT LINE DESCRIPTOR IF SPACING PARAMETER VALUE IN LND STRUCTURED FIELD NUMBER <i>structured field number</i> IS 0.
----------------	---

Explanation

The logical-record control character indicates that the Next Line Descriptor If Spacing parameter must be followed. However, in the Line Descriptor (LND) structured field identified in this message, the Next Line Descriptor If Spacing parameter value was zero. The LND structured field is contained in the page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. Refer *Mixed Object Document Content Architecture Reference*.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS316I	DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE NEXT LINE DESCRIPTOR IF SPACING PARAMETER IN LND STRUCTURED FIELD NUMBER <i>structured field number</i> IS <i>parameter value</i>. THIS VALUE IS TOO LARGE.
----------------	---

Explanation

The logical record control character indicates that the Next Line Descriptor If Spacing parameter in the Line Descriptor (LND) structured field must be followed. However, in the Line Descriptor (LND) structured field identified in this message, the Next Line Descriptor If Spacing parameter value was greater than the total number of line descriptors in the data map. The LND structured field is contained in the page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error,

verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS317I	DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE LENGTH OF COMPARISON STRING PARAMETER VALUE IN CCP STRUCTURED FIELD <i>CCP identifier</i> IS NOT VALID.
----------------	---

Explanation

The Conditional Processing Control (CCP) structured field has an incorrect value. Either the Length of Comparison String parameter is zero, or the length of the comparison string data does not match the length of a repeating group minus the fixed lengths of the remaining fields of the repeating group. The CCP structured field is in the page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot be initialized or cannot print a separator page or error messages. Inform your system programmer that this error occurred.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS319I DATA IN A PAGEDEF RESOURCE IS NOT VALID: LND, RCD, OR XMD STRUCTURED FIELD NUMBER *structured field number* HAS A NULL VALUE SPECIFIED IN THE SUPPRESSION TOKEN NAME PARAMETER. A NULL VALUE IS NOT VALID.

Explanation

The Suppression Token Name parameter in the Line Descriptor (LND), Record Descriptor (RCD), or XML Descriptor (XMD) structured field in the page definition has a null value. A null value is any value that contains 'X'FFFF' in the first 2 bytes.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS320I DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE IDENTIFIER *identifier1* SPECIFIED IN THE NEXT CCP IDENTIFIER PARAMETER IN CCP STRUCTURED FIELD *identifier2* WAS NOT FOUND.

Explanation

The Conditional Processing Control (CCP) structured field has an incorrect value. The Next Conditional Processing Control Identifier parameter in the CCP structured field specifies the identifier that is used to find a CCP if the CCP structured fields are chained. The identifier must match a value specified in the CCP Identifier parameter of another CCP in the same page definition. The identifier that is specified in the Next CCP Identifier parameter did not match the CCP Identifier of any CCPs in the page definition. The CCP structured field is in the page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot be initialized or cannot print a separator page or error messages. Inform your system programmer that this error occurred.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS321I **DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE TIMING OF ACTION PARAMETER VALUE *value* IN CCP STRUCTURED FIELD CCP *identifier* IS NOT VALID.**

Explanation

The Conditional Processing Control (CCP) structured field has an incorrect value. The Timing of Action parameter in one of the repeating groups of the CCP structured field contains an incorrect value. The CCP structured field is in the page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot be initialized or cannot print a separator page or error messages. Inform your system programmer that this error occurred.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the

structured fields for the page definition, contact your system programmer.

APS322I **DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE MEDIUM MAP ACTION PARAMETER VALUE *value* IN CCP STRUCTURED FIELD CCP *identifier* IS NOT VALID.**

Explanation

The Conditional Processing Control (CCP) structured field has an incorrect value. The Medium Map Action parameter in one of the repeating groups of the CCP structured field contains an incorrect value. The CCP structured field is in the page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot be initialized or cannot print a separator page or error messages. Inform your system programmer that this error occurred.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS323I **DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE DATA MAP ACTION PARAMETER VALUE *value* IN CCP STRUCTURED FIELD CCP *identifier* IS NOT VALID.**

Explanation

The Conditional Processing Control (CCP) structured field has an incorrect value. The Data Map Action parameter in one of the repeating groups of the CCP structured field contains an incorrect value. The CCP structured field is in the page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot be initialized or cannot print a separator page or error messages. Inform your system programmer that this error occurred.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS324I	DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE COMPARISON PARAMETER VALUE <i>value</i> IN CCP STRUCTURED FIELD <i>CCP identifier</i> IS NOT VALID.
----------------	---

Explanation

The Conditional Processing Control (CCP) structured field has an incorrect value. The Comparison parameter in one of the repeating groups of the CCP structured field contains an incorrect value. The CCP structured field is in the page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot be initialized or cannot print a separator page or error messages. Inform your system programmer that this error occurred.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS326I	DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE DATA MAP ' <i>data map name</i> ' SPECIFIED IN THE DATA MAP NAME PARAMETER OF CCP STRUCTURED FIELD <i>CCP identifier</i> WAS NOT FOUND.
----------------	---

Explanation

The Conditional Processing Control (CCP) structured field has an incorrect value. The Data Map Name parameter in one of the repeating groups of the CCP structured field specifies the token name of a data map that is used to find a data map in the page definition. The name must match the value specified in the Token Name parameter in one of the Begin Data Map (BDM) structured fields in the current page definition. No data map with name *data map name* was found in the page definition. The CCP structured field is in the page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing

environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot be initialized. Inform your system programmer that this error occurred.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS327I **DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE NEXT LINE DESCRIPTOR IF REUSING DATA PARAMETER VALUE IN LND STRUCTURED FIELD NUMBER *structured field number* WILL CAUSE AN INFINITE LOOP.**

Explanation

The Next Line Descriptor If Reusing Data parameter in the Line Descriptor (LND) structured field that is identified in this message caused an infinite-loop condition. The LND structured field is contained in the page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in

the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS328I **DATA IN A FORMDEF RESOURCE IS NOT VALID: MEDIUM MAP *medium map name* SPECIFIES A CONDITIONAL EJECT TO A PARTITION, BUT THE PARTITION DOES NOT EXIST.**

Explanation

The Begin Medium Map (BMM) structured field specified a conditional eject to a partition that does not exist in the Page Position (PGP) Format 2 structured field. The BMM structured field specified either a conditional eject to the next front side partition or a conditional eject to the next back side partition, but the PGP structured field does not contain a repeating group that specifies a partition on the requested side. The BMM and PGP structured fields are in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more

messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS329I **DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE NEXT LINE DESCRIPTOR IF REUSING DATA PARAMETER VALUE IN LND STRUCTURED FIELD NUMBER *structured field number* IS *parameter value1*. THIS EXCEEDS THE LNC STRUCTURED FIELD COUNT VALUE OF *parameter value2*.**

Explanation

The Next Line Descriptor If Reusing Data parameter in the Line Descriptor (LND) structured field that is identified in this message has an incorrect value. The value is greater than the Count parameter in the Line Descriptor Count (LNC) structured field in the current data map. The LNC and LND structured fields are in the page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing

environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS330I **DATA IN A PAGEDEF RESOURCE IS NOT VALID: WHEN THE DATA START POSITION VALUE IS ADDED TO THE DATA LENGTH VALUE IN LND, RCD, OR XMD STRUCTURED FIELD NUMBER *structured field number*, IT EXCEEDS THE FDS STRUCTURED FIELD SIZE VALUE OF *parameter value*.**

Explanation

The Use Fixed Data flag in byte 0 in the Line Descriptor (LND) structured field, in byte 11 in the Record Descriptor (RCD) structured field, or in byte 1 in the XML Descriptor (XMD) was set to B'1'. This indicates that data from Fixed Data Text (FDX) structured fields is to be added to the data placed within the page by the LND, RCD, or XMD structured field. The FDX, XMD, RCD, and LND structured fields are in the page definition.

The Data Start Position parameter in the LND, RCD, or XMD structured field indicates the offset of the first byte of data. The Data Length parameter specifies how many bytes of FDX are to be placed within the page.

This error was caused when these two parameters specified more data than the FDX structured fields contain. The number of bytes of data in the FDX structured fields can be found in the Size parameter of the Fixed Data Size (FDS) structured field.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS331I	A FORMDEF RESOURCE SPECIFIES PAGE ROTATION IN THE PGP STRUCTURED FIELD, BUT PAGE ROTATION IS NOT SUPPORTED BY THE PRINTER. THE PAGE ROTATION IS IGNORED. THIS MESSAGE IS ONLY ISSUED ONCE PER PRINT DATA SET.
----------------	--

Explanation

A medium map or Document Environment Group in the current form definition contains a Page Position (PGP) Format 2 structured field with a repeating group that requests page rotation in the *PGorient* parameter, but the printer does not support page rotation.

System action

The page rotation is ignored, and processing continues. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

Submit the job to a printer that supports page rotation; or, if you created the structured fields for the form definition, correct the error and resubmit the print request. For more information about the structured field, see *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference*. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, consult your system programmer.

APS334I	DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE AMOUNT OF FIXED DATA RECEIVED DID NOT AGREE WITH THE VALUE SPECIFIED IN THE FDS STRUCTURED FIELD SIZE PARAMETER.
----------------	--

Explanation

The Fixed Data Text (FDX) structured field more bytes of data than was specified in the Size parameter of the Fixed Data Size (FDS) structured field. The FDS and FDX structured fields are in the page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS335I DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE MEDIUM MAP 'medium map name' SPECIFIED IN THE MEDIUM MAP NAME PARAMETER OF CCP STRUCTURED FIELD CCP identifier WAS NOT FOUND.

Explanation

The Conditional Processing Control (CCP) structured field has an incorrect value. The Medium Map Name parameter in one of the repeating groups of the CCP structured field specifies the token name of a medium map that is used to find a medium map in the form definition. The name must match the value specified in the Token Name parameter in one of the Begin Medium Map (BMM) structured fields in the current form definition. No medium map with name *medium map name* was found in the form definition. The CCP structured field is in the page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. PSF releases the current data set back to JES and requests that it be

held by the system. See *Mixed Object Document Content Architecture Reference*.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot be initialized. Inform your system programmer that this error occurred.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS337I DATA IN A PAGEDEF RESOURCE IS NOT VALID: IN LND, RCD, OR XMD STRUCTURED FIELD NUMBER *structured field number*, THE CONDITIONAL PROCESSING FLAG WAS SET BUT THE CONDITIONAL PROCESSING CONTROL IDENTIFIER WAS ZERO.

Explanation

In the Line Descriptor (LND), Record Descriptor (RCD), or XML Descriptor (XMD) structured field, the Conditional Processing flag had a value of B'1', indicating that the line data to be processed by this LND, RCD, or XMD structured field is to be compared with a value specified in a Conditional Processing Control (CCP) structured field. The CCP Identifier parameter in the LND, RCD, or XMD structured field is used to find one of the CCP structured fields in the current page definition. This parameter was set to 0, which is not a valid value if the Conditional Processing flag is on. The LND, RCD, XMD, and CCP structured fields are in the page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing

environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot be initialized or cannot print a separator page or error messages. Inform your system programmer that this error occurred.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS339I **DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE IDENTIFIER *identifier* SPECIFIED IN THE CONDITIONAL PROCESSING CONTROL IDENTIFIER PARAMETER IN LND, RCD, OR XMD STRUCTURED FIELD NUMBER *structured field number* WAS NOT FOUND.**

Explanation

In the Line Descriptor (LND), Record Descriptor (RCD), or XML Descriptor (XMD) structured field, the Conditional Processing flag had a value of B'1', indicating that the line data to be processed by this LND, RCD, or XMD structured field is to be compared with a value specified in a Conditional Processing Control (CCP) structured field. The CCP Identifier parameter in the LND, RCD, or XMD structured field is used to find one of the CCP structured fields in the current page definition. However, the identifier specified in *identifier* does not match the value specified in the CCP Identifier parameter in any of the CCP structured fields in the current page definition. The LND, RCD, XMD, and CCP structured fields are in the page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot be initialized or cannot print a separator page or error messages. Inform your system programmer that this error occurred.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS340I **DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE NEXT LINE DESCRIPTOR IF CONDITIONAL PROCESSING PARAMETER VALUE IN LND, RCD, OR XMD STRUCTURED FIELD NUMBER *structured field number* IS *value1*. THIS EXCEEDS THE LNC STRUCTURED FIELD COUNT VALUE OF *value2*.**

Explanation

The Next Line Descriptor If Conditional Processing parameter in the Line Descriptor (LND), Record Format Descriptor (RCD), or XML Descriptor (XMD) structured field has an incorrect value. The value is greater than the Count parameter in the Line Descriptor Count (LNC) structured field in the current data map. The LNC, LND, RCD, and XMD structured fields are in the page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot be initialized. Inform your system programmer that this error occurred.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS342I	DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE NEXT LINE DESCRIPTOR IF CONDITIONAL PROCESSING PARAMETER VALUE IN LND, RCD, OR XMD STRUCTURED FIELD NUMBER <i>structured field number</i> WILL CAUSE AN INFINITE LOOP.
----------------	--

Explanation

The Next Line Descriptor If Conditional Processing parameter in the Line Descriptor (LND), Record Format Descriptor (RCD), or XML Descriptor (XMD) structured field caused an infinite-loop condition. The LND, RCD, and XMD structured fields are in the page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot be initialized. Inform your system programmer that this error occurred.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS343I	DATA IN AN INPUT RECORD OR PAGEDEF RESOURCE IS NOT VALID: RELATIVE POSITIONING PLACED DATA OUTSIDE THE LOGICAL PAGE IN THE NEGATIVE Y DIRECTION. THE PRIOR AND CURRENT LND, RCD, OR XMD STRUCTURED FIELD NUMBERS ARE: <i>structured field number1</i> AND <i>structured field number2</i>.
----------------	---

Explanation

When relative positioning is being used on a Line Descriptor (LND), Record Descriptor (RCD), or XML Descriptor (XMD) structured field, the relative position that is specified for the Y direction can be a negative value. The current LND, RCD, or XMD (*structured field number2*) is trying to position data outside of the logical page by using a negative value. The prior LND, RCD, or XMD position (*structured field number1*) defines the baseline position from which the relative offset of the current LND, RCD, or XMD is measured.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS344I	DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE NUMBER OF LND OR RCD STRUCTURED FIELDS DOES NOT MATCH THE VALUE SPECIFIED IN THE LNC STRUCTURED FIELD.
----------------	--

Explanation

The number of Line Descriptor (LND) or Record Descriptor (RCD) structured fields that are found in a page definition is either greater than or less than the value specified in the Line Descriptor Count (LNC) structured field. The LND, RCD, and LNC structured fields are in the page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS345I	MESSAGE ID = <i>message identifier</i> EXCEEDS MAXIMUM LENGTH. RECORD SEQUENCE NUMBER = <i>sequence number</i>.
----------------	--

Explanation

The length of the message text for the message ID is greater than the maximum message length of 1000 bytes.

System action

The message is printed to the length limit. Processing of the data set continues.

Operator response

Inform your system programmer that this error occurred.

System programmer response

If you suspect a PSF logic error, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

No response is necessary.

APS346I	DATA IN AN INPUT RECORD OR PAGEDEF RESOURCE IS NOT VALID: A SKIP TO A NONEXISTENT CHANNEL = <i>channel</i> ON RECORD NUMBER = <i>record number</i> WAS DETECTED WITHIN THE LND STRUCTURED FIELDS. OUTPUT WAS FORCED TO
----------------	---

SINGLE SPACING, WHICH MAY CAUSE BLANK PAGES.

Explanation

An attempt was made to skip to a channel not defined in the current data map. The Line Descriptor (LND) structured fields in the page definition are not valid. During scanning, the entire Next Line Descriptor If Skipping parameter cannot be followed because the End Page If Skipping flag was set in an LND structured field. This created an infinite loop on the same input record. The LND structured field is in the page definition.

System action

The record that contains the error was forced to single spacing. When forced single spacing occurs, the carriage control character on the record is ignored. The record is treated as if a X'09' machine control character or a X'40' (blank) ANSI control character was specified in the record that caused the error. The record number specified is relative to the input data stream and can be different for multiple transmissions of the data set.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot be initialized or cannot print error messages. Notify your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

If the error involves separator pages, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS347I DATA IN A PAGEDEF RESOURCE IS NOT VALID: A DXD STRUCTURED

FIELD CONTAINS AN INCORRECT PARAMETER VALUE.

Explanation

The Data Map Transmission Subcase Descriptor (DXD) structured field does not contain a value of X'000100FF'. The DXD structured field is in the page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot be initialized. Inform your system programmer that this error occurred.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS350I DATA IN A PAGEDEF RESOURCE IS NOT VALID: IN LND OR RCD STRUCTURED FIELD NUMBER *structured field number*, THE SHIFT-OUT CODED FONT LOCAL IDENTIFIER WAS NON-ZERO BUT THE GENERATE FONT CHANGE FLAG WAS NOT SET.

Explanation

In the Line Descriptor (LND) or Record Descriptor (RCD) structured field identified in this message, the Shift-out Coded Font Identifier was nonzero. The Generate Font Change flag must be set to indicate that

the Primary Coded Font Local Identifier is used whenever a shift-in code is processed. However, the Generate Font Change flag had a value of B'O'. The LND or RCD structured field is in the page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS352I	DATA IN A PAGEDEF RESOURCE IS NOT VALID: BAR CODE GENERATION WAS REQUESTED ON LND, RCD, OR XMD STRUCTURED FIELD NUMBER <i>structured field number</i>, BUT THE PRINTER DOES NOT SUPPORT BAR CODE OBJECTS. THIS MESSAGE IS ONLY ISSUED ONCE PER PRINT DATA SET.
----------------	---

Explanation

A Line Descriptor (LND), Record Descriptor (RCD), or XML Descriptor (XMD) structured field in a page definition requested PSF to generate a bar code object

from the line data, but the printer does not support bar code objects.

System action

PSF ignores the request and continues processing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Notify your system programmer.

System programmer response

If the page definition is for a separator page, the message data set, or the default page definition for the user print data sets defined in the PSF startup procedure, delete the option from the page definition that requests that a bar code is generated.

User response

To print the data set and have PSF generate bar code objects, submit the print job to a printer that supports bar code objects. For more information about a printer's support for bar code objects, see the documentation provided with the printer.

APS353I	DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE DATA LENGTH PARAMETER VALUE IN LND STRUCTURED FIELD NUMBER <i>structured field number</i> DOES NOT MATCH THE LENGTH OF COMPARISON STRING PARAMETER VALUE IN CCP STRUCTURED FIELD <i>CCP identifier</i>.
----------------	---

Explanation

In the Line Descriptor (LND) structured field, the value of the Data Length parameter is used in identifying the field of the current input record for which Conditional Processing is to be done. This field is to be compared with the Comparison String specified in the Conditional Processing Control (CCP) structured field. However, in the data set you submitted, the length that is specified in the Data Length parameter in the LND structured field does not match the length specified in the Length of Comparison String parameter of the CCP structured field. The LND and CCP structured fields are in the page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot be initialized. Inform your system programmer that this error occurred.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS355I	DATA IN PAGEDEF RESOURCE IS NOT VALID: A PAGE OVERLAY WAS REQUESTED IN LND OR RCD STRUCTURED FIELD NUMBER <i>structured field number</i>, BUT THE PRINTER DOES NOT SUPPORT PAGE OVERLAYS. THIS MESSAGE IS ONLY ISSUED ONCE PER PRINT DATA SET.
----------------	---

Explanation

An overlay was requested by a Line Descriptor (LND) or Record Descriptor (RCD) structured field within the page definition, but the printer does not support page overlays.

System action

PSF stops processing the page and continues processing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is

defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If the page definition is for a separator page, the message data set, or the default page definition for the user print data sets defined in the PSF startup procedure, delete the page overlay from the page definition.

User response

To print the data set containing the page overlay, submit the print job to a printer that supports page overlays. For more information about a printer's support for page overlays, see the documentation provided with the printer.

APS360I	AN OUTPUT BIN WAS REQUESTED FOR THE JOB, BUT EITHER THE PRINTER DOES NOT SUPPORT BIN SPECIFICATION OR THE BIN SPECIFIED WAS NOT AVAILABLE. THE PRINTER DEFAULT BIN WAS USED.
----------------	---

Explanation

The output bin that is specified by the OUTBIN keyword on the JCL OUTPUT statement or in the form definition is not available, or the device does not support the specification of an output bin.

System action

PSF continues processing, sending paper to the printer default output bin.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Inform your system programmer that this error occurred.

User response

If the output is not acceptable, submit the print request to a printer that supports the specification of an output bin and has the output bin available, or ensure that the bin is enabled on the original printer before you resubmit the print request.

APS361I **THE INPUT BIN WITH COMPONENT ID *component_id*, MEDIA NAME *media_name*, BIN NUMBER *bin_number* IS NOT SUPPORTED OR NOT ENABLED ON THE PRINTER. MEDIA FIDELITY REQUESTED THE JOB TO BE TERMINATED WITH NO ALTERNATE BIN SUBSTITUTION.**

Explanation

The Medium Modification Control (MMC) structured field specified a media selection that does not exist on the selected printer or is not enabled. A value of *** for any of the three values means that piece of information was not provided by the MMC structured field. The input bin is selected by a media-source selector keyword with or without media-type local ID keywords in the MMC structured field. The media-type local ID keywords specify the ID of a Map Media Type (MMT) structured field that contains an Object Identifier (OID) with or without a Media Name. The MMC and MMT structured fields are in the form definition.

System action

Processing of the current data set is ended.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

Submit the print request to a printer that supports the specified media selection. If you want to use the original printer, and if you created the structured fields for the form definition, specify a supported bin in the MMC structured field. For more information about the MMC structured field, see *Mixed Object Document Content Architecture Reference*. If the structured field contains the component ID, media name, or number of a supported bin, the error might be a PSF logic error. If you used a program to create the structured fields for

the form definition, ensure that the input to that program specified a supported bin. If it did, consult your system programmer.

APS362I **SYSTEM ACTION TAKEN: THE ERRORS LISTED OCCURRED DURING THE PROCESSING OF INLINE RESOURCES. PROCESSING OF THE DATA SET WAS TERMINATED.**

Explanation

This message is issued in addition to a message that describes an error that occurred during the processing of an inline resource. Other error messages that are issued by PSF describe the precise error condition.

System action

PSF stops processing and printing the data set.

Operator response

To determine an appropriate response, see the specific error conditions described in the accompanying messages.

System programmer response

To determine an appropriate response, see the specific error conditions described in the accompanying messages.

User response

To determine an appropriate response, see the specific error conditions described in the accompanying messages.

APS363I **MULTIPLE COPIES OF THE MESSAGE DATA SET WERE REQUESTED FROM DIFFERENT INPUT BINS BUT THE BIN ATTRIBUTES DID NOT MATCH.**

Explanation

PSF guarantees that at least the first 10 characters of each message are printed on the message page through a special message formatting routine. If multiple copies of message pages are printed from different input bins, and each input bin that is used has different attributes such as paper length, paper width, x-extent, y-extent, x-offset, y-offset, or media type (envelope, manual, or normal), PSF cannot guarantee that the first 10 characters of each message are printed on all copies of the message page.

System action

The messages were not printed.

Operator response

Inform your system programmer that this error occurred.

System programmer response

If messages are to be printed, specify a form definition that specifies only a single copy of the message page, or copies from bins with attributes that are the same.

User response

Inform your system programmer that this error occurred.

APS364I	THE SET OF MODIFICATIONS SPECIFIED IN THE MCC STRUCTURED FIELD INDICATES DIFFERENT SELECT INPUT SOURCE VALUES FOR THE FRONT AND BACK SIDES OF A DUPLEX SHEET.
----------------	--

Explanation

The Medium Modification Control (MMC) structured fields that are referenced by the Medium Copy Count (MCC) structured field repeating groups specify different input-source values or media-type local ID values along with either tumble or normal duplex. This results in an attempt to print the front and back sides of a sheet from different input bins.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition, or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set,

or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. For more information about the structured field, see *Mixed Object Document Content Architecture Reference*. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, consult your system programmer.

APS365I	AN ENVELOPE OR MANUAL FEED INPUT BIN WITH COMPONENT ID <i>componentID</i>, MEDIA NAME <i>media name</i>, BIN NUMBER <i>bin number</i> WAS REQUESTED, BUT IS NOT AVAILABLE ON THE PRINTER.
----------------	--

Explanation

The Medium Modification Control (MMC) structured field requested an envelope or manual feed bin, but no bins that are installed on the printer support the requested bin type. A value of *** for any of the three values means that piece of information was not provided by the MMC structured field. The input bin is selected by a media-source selector keyword with or without media-type local ID keywords in the MMC structured field. The media-type local ID keywords specify the ID of a Map Media Type (MMT) structured field that contains an Object Identifier (OID) with or without a Media Name. The MMC and MMT structured fields are in the form definition.

System action

Processing of the current data set is ended.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you want an envelope or manual feed bin, submit the print request to a printer that supports the requested bin type. If you want to use the original printer without an envelope or manual feed bin, and if you created the structured fields for the form definition, do not specify an envelope or manual feed bin type. For more information about the MMC structured field, see *Mixed Object Document Content Architecture Reference*.

If you used a program to create the structured field for the form definition, ensure that the input to that program specifies that you do not want an envelope or manual bin. If you did not request an envelope or manual bin in your form definition, the error might be a PSF logic error; consult your system programmer.

APS366I **DATA IN AN INPUT RECORD OR PAGEDEF RESOURCE IS NOT VALID: THE ORIENTATION USED WITH RELATIVE POSITIONING IS DIFFERENT THAN THE LAST ORIENTATION USED FOR PRINTING. THE PRIOR AND CURRENT LND, RCD, OR XMD STRUCTURED FIELD NUMBERS ARE: *structured field number1* AND *structured field number2*.**

Explanation

When relative positioning is being used on a Line Descriptor (LND), Record Descriptor (RCD), or XML Descriptor (XMD) structured field, the text orientation field of the current LND, RCD, or XMD (*structured field number2*) must match the text orientation of the LND, RCD, or XMD (*structured field number1*) that was last used for positioning data. The prior LND, RCD, or XMD position defines the baseline position from which the relative offset of the current LND, RCD, or XMD is measured.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS367I **DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE OUTPUT OPTION SPECIFIED IN AN IOB STRUCTURED FIELD WITH RESOURCE LOCAL ID *identifier* IS NOT VALID OR IS UNSUPPORTED. THE IOB IS INCLUDED WITH LND, RCD, OR XMD STRUCTURED FIELD NUMBER *structured field number*.**

Explanation

The Include Object (IOB) structured field in error contained an Output Option value that is not valid, or the printer does not support the Output Option value. The IOB is included by using the Line Descriptor (LND), Record Descriptor (RCD), or XML Descriptor (XMD) structured field identified in this message. The IOB, LND, RCD, and XMD structured fields are contained in the page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or for the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the resource, contact your system programmer.

APS368I **DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE RESOURCE LOCAL ID *identifier* SPECIFIED IN THE EXTENDED RESOURCE LOCAL ID TRIPLET ON LND OR RCD STRUCTURED FIELD NUMBER *structured field number* WAS NOT FOUND.**

Explanation

In the Line Descriptor (LND) or Record Descriptor (RCD) structured field, an Extended Resource Local Identifier triplet specifies a local identifier of an Include Object (IOB) structured field. This IOB structured field includes an object when the LND or RCD is used for printing. However, the local identifier that is specified on the LND or RCD does not match any of the IOB structured fields in the page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or for the message data

set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the resource, contact your system programmer.

APS369I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: STRUCTURED FIELD *structured field* HAS AN INCORRECT OBJECT CLASS VALUE IN AN OBJECT CLASSIFICATION TRIPLET.**

Explanation

The Object Classification (X'10') triplet in the structured field that is specified in the message has an incorrect object class value. Possible incorrect class values for each structured field are:

- Map Data Resource (MDR)
 - Non-presentation object container is included in a repeating group.
 - Object container or IOCA embedded in a page or overlay contains a data object font that is mapped in the Object Environment Group.
- Include Object (IOB) or Preprocess Presentation Object (PPO)
 - Non-presentation object container, data object font (DOF), or non-DOF secondary resource is specified.

System action

PSF stops processing the current page, attempts to find the end of the current page, and then tries to resume printing on the next page. If PSF cannot find the end of the page, it stops printing the data set.

If this error occurs in a resource or a page definition, PSF stops processing the data set.

If this error occurs in a Resource Environment Group (REG), PSF stops processing the REG and continues processing the data set.

Operator response

No response is necessary.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured field, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If you used a program to create the structured field, contact your system programmer. If the object class is valid for the structured field, this release of PSF does not support this function.

APS370I AN OUTLINE FONT WAS SPECIFIED FOR A PRINTER THAT DOES NOT SUPPORT OUTLINE FONTS.

Explanation

A request to use an outline font code page or font character set was made to a printer that does not support outline fonts. PSF detected this error while it was processing a code page or a font character set.

System action

PSF cannot print the current page. PSF attempts to locate the end of the current page and resume printing on the next page. If the end of the current page cannot be located, PSF stops printing the data set. PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is

defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

Ensure that data sets requiring outline fonts are routed to a printer model or configuration that can process them. Otherwise, do not use outline fonts.

APS371I A DOUBLE-BYTE OUTLINE FONT WAS SPECIFIED FOR A PRINTER THAT DOES NOT SUPPORT DOUBLE-BYTE OUTLINE FONTS.

Explanation

A request to use a double-byte outline font code page or a font character set was made to a printer that does not support double-byte outline fonts. PSF detected this error while it was processing a code page or a font character set.

System action

PSF cannot print the current page. PSF attempts to locate the end of the current page and resume printing on the next page. If the end of the current page cannot be located, PSF stops printing the data set. PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

Ensure that documents that require double-byte outline fonts are sent to a printer that can process them. Otherwise, do not use double-byte outline fonts.

APS372I**DATA IN A FONT RESOURCE IS NOT VALID: A FONT CHARACTER SET EXTENSION HAS BEEN SPECIFIED FOR A FONT THAT IS NOT A DOUBLE-BYTE OUTLINE FONT.****RESOLUTION SPECIFIED IN THE FNC STRUCTURED FIELD IS NOT VALID.****Explanation**

Bit 1 of byte 3 in the Font Control (FNC) structured field indicates that this font character set is an extension of an existing resident double-byte outline font, but the font technology identifier (byte 1 in the FNC structured field) is not X'1E'. PSF detected this error while it was processing a font character set.

System action

PSF cannot print the current page. PSF attempts to locate the end of the current page and resume printing on the next page. If the end of the current page cannot be located, PSF stops printing the data set. PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

Explanation

The font resolution specified in bytes 22-27 of the Font Control (FNC) structured field was specified incorrectly. For an outline font, these fields must be zeros. PSF detected this error while it was processing a font character set.

System action

PSF cannot print the current page. PSF attempts to locate the end of the current page and resume printing on the next page. If the end of the current page cannot be located, PSF stops printing the data set. PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

APS374I**THE HOST VERSION OF THE REQUESTED OUTLINE FONT CHARACTER SET IS NOT DOWNLOADABLE BECAUSE IT DOES NOT CONTAIN ANY FONT PATTERN DATA. IT MAY BE A**

APS373I**DATA IN A FONT RESOURCE IS NOT VALID: THE FONT**

METRIC-ONLY OUTLINE FONT CHARACTER SET.

Explanation

Some printers have optional font features or user-installable fonts on cards or other media. This message might indicate that the referenced font was not installed in the printer when this data set was printed.

To support printing with printer-resident fonts, the host font libraries might contain font resources with formatting information but no downloadable font pattern data. These metric-only font character sets (MOF) are used only to activate printer-resident fonts. Because of missing font data, the character set cannot be downloaded.

The pattern technology that is specified in byte 1 in the Font Control structured field is X'1E' or X'1F'. Bytes 28-31 in the FNC structured field contain the total number of bytes in the Font Patterns (FNG) structured field.

System action

PSF cannot print the current page. PSF attempts to locate the end of the current page and resume printing on the next page. If the end of the current page cannot be located, PSF stops printing the data set. PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the font character set is a standard IBM supplied font, it might be a metric-only font. If so, that specific font must be resident in the printer. Verify that the font is resident in the printer that is used. For example, double-byte outline (scalable) fonts generally have metric-only fonts on the host system. Double-byte outline resident fonts might be a separate printer feature. See the printer publications for information on resident fonts.

If the font is resident in the printer, ensure that the character set is marked PUBLIC (by APSRMARK). In the Data Definition that is referenced by the FONTDD parameter in the PSF PRINTDEV statement, ensure

that the font libraries that contain marked resources are specified first in the library concatenation order. If you use fonts as INLINE or USERLIB resources, verify that they are marked PUBLIC.

If an IBM licensed program was used to create the structured fields for the font that contains the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

Install the font on the printer, change to a font that is either installed or downloadable, or notify your system programmer of this error.

APS375I DATA IN A FONT RESOURCE IS NOT VALID: THE FNN DATA COUNT IN THE FNC STRUCTURED FIELD IS NOT VALID.

Explanation

The Font Name Map (FNN) Data Count in bytes 36-39 of the Font Control (FNC) structured field is specified incorrectly. PSF detected that this value is less than X'00000002', which is outside of the valid range X'00000002'–X'FFFFFFFF'. PSF detected this error while it was processing a font character set.

System action

PSF cannot print the current page. PSF attempts to locate the end of the current page and resume printing on the next page. If the end of the current page cannot be located, PSF stops printing the data set. PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error

involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

APS376I	DATA IN A FONT RESOURCE IS NOT VALID: THE SPECIFIED FONT DOES NOT CONTAIN REQUIRED OUTLINE FONT EXTENSION INFORMATION.
----------------	---

Explanation

When bit 1 of byte 3 in a Font Control (FNC) structured field indicates that the font character set is an extension of an existing resident double-byte outline font, the font character extension triplet (triplet ID X'6D') must specify the GCSGID of the corresponding resident double-byte outline font. PSF detected this error while it was processing a font character set.

System action

PSF cannot print the current page. PSF attempts to locate the end of the current page and resume printing on the next page. If the end of the current page cannot be located, PSF stops printing the data set. PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use

the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

APS377I	DATA IN A FONT RESOURCE IS NOT VALID: THE SPECIFIED OUTLINE FONT CHARACTER SET DOES NOT CONTAIN ANY FNN STRUCTURED FIELDS.
----------------	---

Explanation

No Font Name Map (FNN) structured fields exist for the specified outline font. PSF requires that at least one FNN structured field exist for an outline font. PSF detected this error while it was processing a font character set.

System action

PSF cannot print the current page. PSF attempts to locate the end of the current page and resume printing on the next page. If the end of the current page cannot be located, PSF stops printing the data set. PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

APS378I **THE ENCODING SCHEME SPECIFIED IN THE CPD STRUCTURED FIELD DOES NOT MATCH THE ENCODING SCHEME SPECIFIED IN THE MCF STRUCTURED FIELD FOR THE FONT.**

Explanation

The font encoding scheme that is specified in the encoding scheme ID triplet (triplet ID X'27') of the Map Coded Font (MCF) structured field does not match the encoding scheme specified in bytes 42-43 in the Code Page Descriptor (CPD) structured field for the code page. PSF detected this error while it was processing a code page.

System action

PSF cannot print the current page. PSF attempts to locate the end of the current page and resume printing on the next page. If the end of the current page cannot be located, PSF stops printing the data set. PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

The mismatch can be caused by an error in the MCF structured field that referenced the requested font, or by an error in the code page for the requested font. If you created the structured fields for the code page, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the code page, contact your system programmer. If you created the MCF structured field for the page definition or the MO:DCA data, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition or the MO:DCA data, consult your system programmer.

APS380I **THE REGISTRATION ID (*object-type OID*) OF AN OBJECT CONTAINER RESOURCE, NAME *resource name*, DOES NOT MATCH THE CORRESPONDING REGISTRATION ID FOR THE INVOKING JCL KEYWORD OR INCLUDING STRUCTURED FIELD.**

Explanation

An object container resource was requested through a JCL keyword or an IOB or MDR structured field, but the object classification triplet in the Begin Object Container structured field did not match the corresponding registration ID. For a list of registration IDs and their assumed functions, see *Mixed Object Document Content Architecture Reference*.

System action

If the object container was called out by JCL, PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found.

If the object container was included by an IOB or MDR structured field, PSF stops processing the page or overlay. PSF attempts to locate the end of the current page and resume processing on the next page. If the end of the current page cannot be located, PSF stops printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set,

or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the object container that contains the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the object container resource, ensure that the registration ID corresponds to the keyword used to call the resource or to the registration ID specified in the object classification triplet specified on the IOB or MDR structured field.

APS381I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE REGISTERED OBJECT ID IN THE OBJECT CLASSIFICATION TRIPLET ON A <i>structured field name</i> STRUCTURED FIELD IS NOT SPECIFIED.
----------------	---

Explanation

The registered object ID is 0 in the object classification triplet. Object containers require a registered ID to be specified.

System action

The system action depends on where the error is located:

- If the structured field is included in an object that is embedded in a page or overlay, or if the structured field is in a resource included by a page or overlay, PSF stops processing the page or overlay. PSF tries to find the end of the current page and resume processing on the next page. If it cannot find the end of the current page, PSF stops printing the data set.

If PSF is processing an inline resource, it stops processing the data set.

- For non-presentation object containers, PSF stops printing the data set.
- If the error is contained in a page definition, PSF stops processing the data set and continues processing with the next data set.

- If this error occurs in a Resource Environment Group (REG), PSF stops processing the REG and continues processing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response:

System programmer response:

User response:

APS383I	THE PRESENTATION SYSTEM SETUP ID (<i>identifier</i>) SPECIFIED IN THE MMC STRUCTURED FIELD IS NOT CURRENTLY AVAILABLE AT THE DEVICE. THE DATA SET WILL BE HELD BY THE SYSTEM.
----------------	--

Explanation

The Presentation System Setup ID in the Medium Modification Control (MMC) structured field contains a setup ID that is not currently available at the printer, or the printer does not support setup IDs. The MMC structured field is contained in the form definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*. PSF releases the current data set back to JES and requests that it be held by the system.

Operator response

If this message appears on the operator's console, it indicates that the resource that contains the setup ID is defined for a separator page or the message data set in the PSF startup procedure. If the setup ID cannot always be made available on your printer, then contact your system programmer.

See the operator's manual for your printer or your post-processing device to determine how to make the determined setup ID available for use.

System programmer response

If this message appears on the operator's console, use the information provided in the Operator Response section. If the setup ID is not what you wanted, modify the PSF startup procedure as described in the User Response section.

User response

To receive the printed output with the setup ID identified, do one of these:

- Specify the FORMS keyword on the OUTPUT statement of the JCL with a parameter as determined by local procedures.
- Ask the operator to make available on the printer the identified setup IDs.
- Submit the job to a printer that contains the identified setup ID.

If the setup ID identified is not what you wanted, do one of these:

- Specify a form definition that contains a different setup ID or no setup ID.
- Modify the form definition to require a different presentation system setup ID or remove the use of the presentation system setup ID.

APS384I **DATA IN A FORMDEF RESOURCE IS NOT VALID: THE SET OF MODIFICATIONS SPECIFIED IN THE MCC STRUCTURED FIELD INCLUDES CONFLICTING PRESENTATION SYSTEM SETUP ID VALUES.**

Explanation

Multiple MMC structured fields that are referenced by the MCC structured field do not use the exact same set of Presentation System Setup ID values.

System action

The form definition that contains the error is not used, and one of these occurs:

- PSF is not started if the form definition that contains the error is defined in the PSF startup procedure. The form definition resources that are defined in the PSF startup procedure are for separator pages, for the message data set, and for the default form definition resource for user print data sets.
- If the error is in a form definition that is specified on a user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS385I **DATA IN A FORMDEF RESOURCE IS NOT VALID: THE MODIFICATIONS SPECIFIED IN THE MMC STRUCTURED FIELD (structured field) INCLUDE UNPAIRED keyword1 AND keyword2 KEYWORDS.**

Explanation

The keywords must be paired in the Medium Modification Control (MMC) structured field. This form definition has one or the other keyword but not both, or the keyword pairs are not adjacent. The MMC structured field is contained in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- PSF is not started if the form definition that contains the error is defined in the PSF startup procedure. The form definition resources that are defined in the PSF startup procedure are for separator pages, for the message data set, and for the default form definition resource for user print data sets.
- If the error is in a form definition that is specified on a user's JCL OUTPUT statement, PSF cannot begin

printing the data set; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS386I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A REQUIRED TRIPLET WITH ID identifier WAS MISSING FROM A structured field STRUCTURED FIELD.

Explanation

When the message specifies a triplet identifier of X'18', the structured field contains at least one Function Set triplet (X'8F'), but does not contain an X'18' interchange triplet with a Presentation Type of X'01'.

When the message specifies a triplet identifier of X'22', the Extended Resource Local Identifier (X'22') triplet is required on an IOB structured field in a page definition. The structured field is contained in a print data set if it is a PPO.

When the message specifies a triplet identifier of X'4B', the x- or y-axis origin for the object content or an object area size is specified on the Include Object (IOB) or Preprocess Presentation Object (PPO) structured field, but no measurement unit (X'4B') triplet is specified. A PPO structured field is contained in a print data set. An IOB structured field is contained in a print data set, overlay, or page definition.

When the triplet identifier is X'8F', the Function Set (X'8F') triplet is missing when the Interchange Set (X'18') triplet specifies function set support on the structured field in a print data set.

System action

The system action depends on where the error is located:

- If the error is contained in a page definition, PSF stops processing the data set and continues processing with the next data set.
- If the error is in a page or overlay and the structured field is an IOB, PSF stops processing the page or overlay that contains the structured field in error. PSF tries to find the end of the current page and resume processing on the next page. If PSF cannot find the end of the current page, it stops printing the data set.
- If the error is in the print data set and the structured field is a PPO, PSF stops processing the Resource Environment Group and continues processing the data set.
- If the error is in the print data set and the structured field is a Begin Print File (BPF) or a Begin Document (BDT), PSF stops processing the print data set.

PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment when the error was found.

Operator response

No response is necessary.

System programmer response

If an IBM licensed program was used to place the IOB structured field in the print data set or overlay, verify that the input to that program was valid. If it was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and

Advanced Function Presentation: Programming Guide and Line Data Reference for more information about the structured field. If you used a program to create the structured fields, contact your system programmer.

APS387I **DATA IN AN INPUT RECORD IS NOT VALID: PARAMETER IN AN structured field STRUCTURED FIELD CONTAINS UNACCEPTABLE DATA.**

Explanation

One of the parameters in the structured field is not valid. If *structured field* is an IOB structured field, one of these caused the problem:

- The object type that is specified is not supported or is not valid.
- The x or y offset of the object area or the rotation value are not explicitly specified when the reference coordinate system is set to 'X'00'.

If *structured field* is a PPO structured field, one of these caused the problem:

- The object type that is specified is not supported or is not valid.
- The x or y offset of the object area is not valid.

If *structured field* is a PTD structured field, the x or y text presentation extent is not valid.

System action

PSF stops processing the page or overlay that contains the structured field in error. PSF tries to find the end of the current page and resume processing on the next page. If it cannot find the end of the current page, PSF stops printing the data set.

If this error occurs in a Resource Environment Group (REG), PSF stops processing the REG and continues processing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If you used a program to create the structured fields, contact your system programmer.

APS388I **DATA IN A PAGE SEGMENT IS NOT VALID: structured field STRUCTURED FIELD IS NOT ALLOWED IN A PAGE SEGMENT INCLUDED WITH AN IOB.**

Explanation

Only MO:DCA page segments are allowed to be included with an IOB structured field. MO:DCA page segments cannot contain IM1 images or PTOCA data.

System action

PSF stops processing the page or overlay that contains the structured field in error. PSF attempts to locate the end of the current page and resume processing on the next page. If the end of the current page cannot be located, PSF stops printing the data set. PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment when the error was found.

Operator response

No response is necessary.

System programmer response

If an IBM licensed program was used to place the IOB structured field in the print data set or overlay, verify that the input to that program was valid. If it was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you placed the IOB structured field in the print data set or overlay, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If you used a program to place the IOB structured field in the print data set or overlay, contact your system programmer.

APS389I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE METRIC-TECHNOLOGY, THE UNIT BASE OR THE UNITS PER UNIT BASE FIELD IS NOT VALID IN THE X'84' TRIPLET ON THE MCF2.

Explanation

The metric-technology, the unit base, or the units per unit base value in the X'84' triplet on the MCF2 structured field is not valid.

System action

PSF cannot print the current page. PSF attempts to locate the end of the current page and resume printing on the next page. If the end of the current page cannot be located, PSF stops printing the data set. PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program

to create the structured fields for the print data set or the resource, contact your system programmer.

APS390I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE structured field STRUCTURED FIELD CONTAINS A triplet TRIPLET THAT HAS AN INCORRECT VALUE. THE INCORRECT VALUE STARTS IN BYTE offset OF THE TRIPLET.

Explanation

A value that is not valid was specified for a field that starts in the byte offset of the triplet identified in this message. The triplet is specified on the structured field identified in this message.

System action

If the error occurred in a form definition, a page definition, or a non-presentation object container resource (for example, COMSETUP), the form definition, page definition, or non-presentation object container resource is not used, and one of these occurs:

- PSF is not started for any of these:
 - The default form definition
 - A form definition specified for printing messages or separator pages
 - A page definition specified for printing messages or separator pages
- PSF cannot begin printing the data set for a form definition or non-presentation object container resource (or page definition, if printing line data) specified on a user's JCL OUTPUT statement; PSF tries to print the next data set.

If the error occurred in a structured field in a page or another type of resource, PSF attempts to find the end of the page or resource. If PSF can find the end of the page or resource, it prints any data accumulated for the current page. If PSF cannot find the end of the page or resource, it stops processing the data set.

PSF issues a message that identifies the position of the structured field in the data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the resource, contact your system programmer.

APS391I THE METRIC-TECHNOLOGY AND RESOLUTION IN THE FONT DO NOT MATCH THE SPECIFIED VALUES.

Explanation

One of these occurred:

- The metric-technology and resolution values that are specified in the X'84' triplet on the MCF2 structured field do not match the values in the Font Control (FNC) structured field.
- The RESFMT keyword on the OUTPUT statement or the Resolution value from the Printer Inventory or the XTP7FMT field from the Resource-Management Exit 7 do not match the values in the Font Control (FNC) structured field.

The FNC structured field is in the font character set. These fields are required to match the specified values when the Presentation Fidelity Control (PFC) has the Font Fidelity triplet continuation rule set to "stop presentation". The PFC structured field is specified in the form definition.

System action

PSF cannot print the current page. PSF attempts to locate the end of the current page and resume printing on the next page. If the end of the current page cannot be located, PSF stops printing the data set. PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If the Printer Inventory or PRINTDEV JCL statement in the PSF startup procedure does not specify the correct font library for the resolution of the printer, correct it.

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

Determine whether the font required any preprocessing to match the resolution of the device; if so, ensure that this preprocessing was done. For more information about converting 240-pel fonts to 300-pel fonts, see *PSF for z/OS: Customization*. If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

APS392I DATA IN A FORMDEF RESOURCE IS NOT VALID: THE SCOPE VALUE IN THE MFC IS NOT VALID. EITHER DOCUMENT LEVEL OR PRINT FILE LEVEL FINISHING WAS SPECIFIED IN THE MEDIUM MAP OR MEDIUM LEVEL FINISHING WAS SPECIFIED IN THE DEG.

Explanation

Either a Document Environment Group or a medium map in the current form definition contains a Medium Finishing Control (MFC) structured field with an incorrect value specified for the scope.

System action

The MFC is ignored and processing continues. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS393I THE INPUT BIN SPECIFIED IN THE MMC STRUCTURED FIELD OR ON THE OUTPUT STATEMENT IS AN INSERTER BIN AND IS DISABLED. AN ALTERNATIVE BIN WAS SUBSTITUTED.

Explanation

The Medium Modification Control (MMC) structured field or the output statement requested an input bin that is supported by the printer but is disabled. This bin is an inserter bin. The MMC structured field is contained in a medium map in the form definition. The output statement is in the JCL.

System action

PSF continues processing, selecting paper from an alternative bin that is not an inserter bin.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

If the output is not acceptable, submit the print request to a printer that has the specified bin available, or ensure that the bin is enabled on the original printer before you resubmit the print request.

APS394I THE PSF OBJECT STACK IS ABOUT TO OVERFLOW DUE TO MISSING END STRUCTURED FIELDS.

Explanation

Common conversion machine (CCM) ran out of its object stack area. The cause might be a data stream error. A begin structured field must be followed by a matching end structured field in the data stream. If this requirement is not met, the CCM can run out of its object stack area. A common cause of this problem is missing EDT structured fields.

System action

PSF stops the processing and printing of this data set.

System programmer response

If an IBM licensed program was used to create the data stream with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the data stream, each begin structured field in the data stream must be followed by a matching end structured field. Check the data stream to ensure that it meets this requirement. If it does not meet the requirement, correct the data stream. If it does meet the requirement, this error code indicates a logic error. If you believe that the error is a logic error, consult your service representative in the IBM Support Center for assistance, or use your electronic link with IBM services.

APS395I A FORMDEF RESOURCE REQUESTED A MEDIA EJECT CONTROL TO THE NEXT BACK SIDE AND DUPLEX=NO WAS SPECIFIED ON THE OUTPUT STATEMENT.

Explanation

When a media eject control to the next back side is specified in a FORMDEF, the DUPLEX=NO keyword on

the OUTPUT statement cannot be used to change from duplex (specified in the FORMDEF) to simplex. The reason is that an incompatible request is being made—you cannot eject to the next back side when simplex is specified.

The only valid options for the DUPLEX keyword when a media eject control to the next back side is specified in the FORMDEF are:

- If the FORMDEF requests normal or tumble duplex, you can specify either duplex=normal or duplex=tumble on the output statement.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response

None.

System programmer response

None.

User response

Resubmit the job without requesting the DUPLEX keyword on the OUTPUT statement.

APS396I **DATA IN A FORMDEF RESOURCE IS NOT VALID: THE OUTPUT BIN SELECTION VALUE IN MMC STRUCTURED FIELD, ID *identifier*, IS NOT ACCEPTABLE.**

Explanation

The Medium Modification Control (MMC) structured field specified an output bin selection value of 0. Values 1 - 65535 are valid. The MMC structured field is in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- PSF is not started if the form definition that contains the error is defined in the PSF startup procedure. The form definition resources that are defined in the PSF startup procedure are for separator pages, for the message data set, and for the default form definition resource for user print data sets.
- If the error is in a form definition that is specified on a user's JCL OUTPUT statement, PSF cannot begin

printing the data set; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the MMC structured field and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the MMC has no errors, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS397I **DATA IN A FORMDEF RESOURCE IS NOT VALID: DIFFERENT OUTPUT BIN VALUES ARE SPECIFIED FOR THE FRONT AND BACK SIDES OF A SHEET IN MEDIUM MAP *medium map*.**

Explanation

The Medium Modification Control (MMC) structured fields that are referenced by the Medium Copy Count (MCC) structured field repeating groups specify different output bin values along with either tumble or normal duplex. The settings attempt to place the front and back sides of a sheet into different output bins. The MMC structured field is in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- PSF is not started if the form definition that contains the error is defined in the PSF startup procedure. The form definition resources that are defined in the PSF startup procedure are for separator pages, for the message data set, and for the default form definition resource for user print data sets.
- If the error is in a form definition that is specified on a user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the form definition. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS398I DATA IN A FORMDEF RESOURCE IS NOT VALID: THE SET OF MODIFICATIONS SPECIFIED IN THE MMC STRUCTURED FIELD, ID *identifier*, INCLUDES DUPLICATE CONFLICTING VALUES FOR THE *identifier* KEYWORD.

Explanation

The Medium Modification Control (MMC) structured field contains duplicate conflicting values for the MMC

keyword identified in the message text. The MMC structured field is in the form definition.

System action

PSF issues this message and continues processing, ignoring the duplicate keyword.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the MMC structured field and resubmit the print request. For more information about the structured field, see *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference*. If the MMC has no errors, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, consult your system programmer.

APS399I AN OUTPUT BIN *bin number* WAS REQUESTED FOR THE JOB, BUT IT WAS NOT AVAILABLE OR THE PRINTER DOES NOT SUPPORT OUTPUT BIN SELECTION.

Explanation

The OUTBIN keyword on the JCL OUTPUT statement or the output bin selection parameter value in the form definition specified an output bin. Either that bin is not available or the printer does not support output bin specification. Since mandatory print labeling is enabled, the data set cannot be processed.

System action

PSF cannot print the current data set. PSF stops processing and printing the data set. PSF issues more messages that identify the processing environment in which the error occurred. PSF releases the current

data set back to JES and requests that it is held by the system, unless PRTEROR=QUIT was specified on the OUTPUT statement.

Operator response

Inform your system programmer that this error occurred.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

Users have several options to correct or avoid this error:

- Resubmit the print request to a printer that supports the requested bin number.
- If the bin number was specified on the JCL OUTPUT statement, change the OUTBIN keyword to a bin

number that is supported by the printer and resubmit the print request. If the bin number that is specified by the OUTBIN keyword is supported by the printer, the error might be a PSF logic error.

- If you created the structured fields for the form definition, change the MMC structured field, specifying the correct output bin selection parameter value that is supported by the printer and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the MMC output bin selection parameter is supported by the printer, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.
- Disable mandatory print labeling and resubmit the print request.
- If you print to a printer that does not support output bin specification, remove the output bin specification.

APS400 to APS499

APS400I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: BYTE 0 OF A SELF-DEFINING FIELD IS NOT VALID OR IS UNSUPPORTED IN AN IPD STRUCTURED FIELD.

Explanation

The Image Picture Data (IPD) structured field is made up of self-defining fields. Byte 0 in each self-defining field identifies the type of self-defining field that follows it. The value of byte 0 in this self-defining field is not one of the supported values. The hex code for the self-defining field is provided in the formatted sense message (APS830I) in the Element Identifier (bytes 16-17). IOCA self-defining fields include:

- 0—no self-defining field ID provided
- 70—Begin Segment
- 71—End Segment
- 8C—Begin Tile Parameter
- 8D—End Tile Parameter
- 8E—Begin Transparency Mask Parameter
- 8F—End Transparency Mask Parameter
- 91—Begin Image Content
- 93—End Image Content
- 94—Image Size Parameter
- 95—Image Encoding Parameter
- 96—Image Data Element Size Parameter
- 97—Image Look Up Table ID Parameter

- 98—Band Image Parameter
- 9B—Image Data Element Structure Parameter
- 9F—External Algorithm Specification Parameter
- B5—Tile Position Parameter
- B6—Tile Size Parameter
- B7—Tile Set Color Parameter
- F4—Set Extended Bi-level Image Color
- F6—Set Bi-level Image Color
- F8—Set Presentation Space Size
- FE92—Image Data
- FE9C—Band Image Data
- FEB8—Include Tile Parameter
- FEBB—Tile TOC Parameter
- FECE—Image Subsampling Parameter
- FEDE—Color Palette Parameter
- nnnn—unrecognized self-defining field

The IPD structured field is contained in an image object. The image object might be contained in a MO:DCA document, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any position errors, exception highlighting might be included on the printed page.

PSF continues processing of the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the image object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the image object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the image object, contact your system programmer.

APS401I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE LENGTH PARAMETER OF AN IMAGE FIELD IS NOT VALID OR IS UNSUPPORTED IN AN IPD STRUCTURED FIELD.**

Explanation

The value that is specified in the Length parameter of a self-defining field is not valid or is unsupported. The self-defining field is in an Image Picture (IPD) structured field. The hex code for the self-defining field is provided in the formatted sense message (APS830I) in the Element Identifier (bytes 16-17). IOCA self-defining fields include:

- 0—self-defining field ID not provided
- 70—Begin Segment
- 71—End Segment
- 8C—Begin Tile Parameter
- 8D—End Tile Parameter
- 8E—Begin Transparency Mask Parameter
- 8F—End Transparency Mask Parameter

- 91—Begin Image Content
- 93—End Image Content
- 94—Image Size Parameter
- 95—Image Encoding Parameter
- 96—Image Data Element Size Parameter
- 97—Image Look Up Table ID Parameter
- 98—Band Image Parameter
- 9B—Image Data Element Structure Parameter
- 9F—External Algorithm Specification Parameter
- B5—Tile Position Parameter
- B6—Tile Size Parameter
- B7—Tile Set Color Parameter
- F4—Set Extended Bi-level Image Color
- F6—Set Bi-level Image Color
- F8—Set Presentation Space Size
- FE92—Image Data
- FE9C—Band Image Data
- FEB8—Include Tile Parameter
- FEBB—Tile TOC Parameter
- FECE—Image Subsampling Parameter
- FEDE—Color Palette Parameter
- nnnn—unrecognized self-defining field

The IPD structured field is contained in an image object. The image object might be contained in a MO:DCA document, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any position errors, exception highlighting might be included on the printed page. PSF continues processing of the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the image object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data

set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the image object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the image object, contact your system programmer.

APS402I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A BEGIN SEGMENT FIELD IS OUT OF SEQUENCE IN AN IPD STRUCTURED FIELD.
----------------	---

Explanation

A Begin Segment field is out of sequence in an Image Picture Data (IPD) structured field. The IPD structured field is contained in an image object. The image object might be contained in a MO:DCA document, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any position errors, exception highlighting might be included on the printed page. PSF continues processing of the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the image object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the image object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the image object, contact your system programmer.

APS403I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN END SEGMENT FIELD IS OUT OF SEQUENCE IN AN IPD STRUCTURED FIELD.
----------------	--

Explanation

An End Segment field is out of sequence in an Image Picture Data (IPD) structured field. The IPD structured field is contained in an image object. The image object can be contained in a MO:DCA document, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any position errors, exception highlighting might be included on the printed page. PSF continues processing of the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the image object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the image object, correct the error and resubmit the print

request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the image object, contact your system programmer.

APS404I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A BEGIN IMAGE CONTENT FIELD IS OUT OF SEQUENCE IN AN IPD STRUCTURED FIELD.

Explanation

A Begin Image Content field is missing, was encountered out of sequence, or (for a printer that does not support multiple image contents) appeared more than once. A Begin Image Content field is contained in an Image Picture Data (IPD) structured field. The IPD structured field is contained in an image object. The image object can be contained in a MO:DCA document, an overlay, an object container, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any position errors, exception highlighting might be included on the printed page. PSF continues processing of the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the image object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the image object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the image object, contact your system programmer.

APS405I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN END IMAGE CONTENT FIELD IS OUT OF SEQUENCE IN AN IPD STRUCTURED FIELD.

Explanation

An End Image Content field is missing, was encountered out of sequence in an Image Picture Data (IPD) structured field or (for a printer that does not support multiple image contents) appeared more than once. An End Image Content field must follow an Image Data self-defining field, a Band Image Data self-defining field, or an End Tile self-defining field. The IPD structured field is contained in an image object. The image object might be contained in a MO:DCA document, an overlay, an object container, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any position errors, exception highlighting might be included on the printed page. PSF continues processing of the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the image object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data

set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the image object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the image object, contact your system programmer.

APS406I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN IMAGE SIZE PARAMETER IS MISSING OR OUT OF SEQUENCE IN AN IPD STRUCTURED FIELD.
----------------	--

Explanation

An Image Size Parameter value is missing or out of sequence in an Image Picture Data (IPD) structured field. The IPD structured field is contained in an image object. The image object might be contained in a MO:DCA document, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any position errors, exception highlighting might be included on the printed page. PSF continues processing of the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the image object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the image object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the image object, contact your system programmer.

APS407I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE IMAGE SIZE CANNOT BE DETERMINED.
----------------	---

Explanation

An X- or Y-extent value in the Image Size Parameter is 0, but the size of the image in that direction cannot be detected from the image data. The Image Size Parameter is in an Image Picture Data (IPD) structured field.

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The horizontal size or the vertical size of the Image Size Parameter is zero, but the size of the image in that direction is not detectable from the image data.
2. An Image Size Parameter within a transparency mask does not match the dimensions of the containing tile.

If the IM1 image resolution within the IID structured field does not match the printer resolution, PSF attempts to convert the IM1 image to Image Object Content Architecture (IOCA), if the printer supports IOCA. During this conversion process, IM1 structured fields are converted to IOCA Intelligent Printer Data Stream (IPDS) commands. If the size of the image that is specified in the IID structured field is 0, this error might occur.

The IPD structured field is contained in an image object. The image object might be contained in a MO:DCA document, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any position errors, exception highlighting might be included on the printed page. PSF continues processing of the current data set with the page that follows the page in error, unless the

printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the image object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the image object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the image object, contact your system programmer.

APS408I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN UNSUPPORTED VALUE WAS FOUND IN AN IMAGE ENCODING PARAMETER IN AN IPD STRUCTURED FIELD.**

Explanation

A value in the Image Encoding Parameter is unsupported. The parameter is in an Image Picture Data (IPD) structured field. The IPD structured field is contained in an image object. The image object might be contained in a MO:DCA document, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any position errors, exception highlighting might be included on the printed page. PSF continues processing of the current data set with the page that follows the page in error, unless the

printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the image object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the image object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the image object, contact your system programmer.

APS409I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN UNSUPPORTED VALUE WAS FOUND IN AN IMAGE DATA ELEMENT SIZE PARAMETER IN AN IPD STRUCTURED FIELD.**

Explanation

A value in an Image Data Element Size Parameter is not valid. The parameter is in an Image Picture Data (IPD) structured field. The IPD structured field is contained in an image object. The image object might be contained in a MO:DCA document, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any position errors, exception highlighting might be included on the printed page. PSF continues processing of the current data set with the page that follows the page in error, unless the

printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the image object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the image object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the image object, contact your system programmer.

APS410I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE IDE SIZE IN AN IMAGE DATA ELEMENT SIZE PARAMETER DOES NOT MATCH THE COMPRESSION VALUE IN THE IMAGE ENCODING PARAMETER IN AN IPD STRUCTURED FIELD.

Explanation

The Image Data Element (IDE) Size in an Image Data Element Size Parameter is inconsistent with the Compression Identifier in the Image Encoding Parameter. The parameters are in an Image Picture Data (IPD) structured field. The IPD structured field is contained in an image object. The image object might be contained in a MO:DCA document, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any position errors, exception

highlighting might be included on the printed page. PSF continues processing of the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the image object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the image object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the image object, contact your system programmer.

APS411I AN ATTEMPT WAS MADE TO PLACE IMAGE DATA OUTSIDE OF THE IMAGE PRESENTATION SPACE.

Explanation

An attempt was made to place image data outside of the image presentation space. The image presentation space is a two-dimensional conceptual space in which an image is generated. The space is then mapped onto an output medium. The size of the image presentation space is defined in the Image Data Descriptor (IDD) structured field. The size of the image data is defined in the Image Size Parameter in an Image Picture Data (IPD) structured field. The size of the image data that is specified in the IPD structured field is too large to fit in the image presentation space specified in the IDD structured field. The IDD and IPD structured fields are in an image object. The image object might be contained in a MO:DCA document, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any position errors, exception highlighting might be included on the printed page. PSF continues processing of the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the image object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the image object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the image object, contact your system programmer.

APS412I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN INCORRECT VALUE WAS FOUND IN A SELF-DEFINING FIELD IN AN IPD STRUCTURED FIELD.

Explanation

An incorrect value was found in one of these image self-defining fields:

- 91 - Begin Image Content
- 94 - Image size Parameter
- 96 - Image Data Element Size Parameter
- FE9C - Band Image Data

The self-defining fields are in an Image Picture Data (IPD) structured field. The IPD structured field is contained in an image object. The image object might

be contained in a MO:DCA document, an overlay, or a page segment; or it might be embedded in a data set containing line data. The hex code for the self-defining field is provided in the formatted sense message (APS830I) in the Element Identifier (bytes 16-17).

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any position errors, exception highlighting might be included on the printed page. PSF continues processing of the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the image object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the image object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the image object, contact your system programmer.

APS413I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN IMAGE ENCODING PARAMETER IS OUT OF SEQUENCE IN AN IPD STRUCTURED FIELD.

Explanation

An Image Encoding Parameter is out of sequence in an Image Picture Data (IPD) structured field. The IPD structured field is contained in an image object. The image object might be contained in a MO:DCA

document, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any position errors, exception highlighting might be included on the printed page. PSF continues processing of the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the image object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the image object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the image object, contact your system programmer.

APS414I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN IMAGE DATA ELEMENT SIZE PARAMETER IS OUT OF SEQUENCE IN AN IPD STRUCTURED FIELD.**

Explanation

An Image Data Element Size Parameter is out of sequence in an Image Picture Data (IPD) structured field. The IPD structured field is contained in an image object. The image object might be contained in a MO:DCA document, an overlay, or a page segment; or

it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any position errors, exception highlighting might be included on the printed page. PSF continues processing of the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the image object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the image object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the image object, contact your system programmer.

APS415I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN IMAGE LOOK-UP TABLE ID PARAMETER VALUE IS OUT OF SEQUENCE IN AN IPD STRUCTURED FIELD.**

Explanation

An Image Look Up Table ID Parameter is out of sequence in an Image Picture Data (IPD) structured field. The IPD structured field is contained in an image object. The image object might be contained in a MO:DCA document, an overlay, or a page segment; or

it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any position errors, exception highlighting might be included on the printed page. PSF continues processing of the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the image object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the image object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the image object, contact your system programmer.

APS416I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN UNSUPPORTED LUT IDENTIFIER WAS FOUND IN AN IMAGE LOOK-UP TABLE ID PARAMETER IN AN IPD STRUCTURED FIELD.

Explanation

The value for the Look-Up Table (LUT) Identifier in the Look-Up Table ID Parameter is unsupported. The parameter is in an Image Picture Data (IPD) structured field. The IPD structured field is contained in an image object. The image object might be contained in a MO:DCA document, an overlay, or a page segment; or

it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any position errors, exception highlighting might be included on the printed page. PSF continues processing of the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the image object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the image object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the image object, contact your system programmer.

APS417I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN IMAGE DATA SELF-DEFINING FIELD IS OUT OF SEQUENCE IN AN IPD STRUCTURED FIELD.

Explanation

An Image Data self-defining field is out of sequence in an Image Picture Data (IPD) structured field. The IPD structured field is contained in an image object. The image object might be contained in a MO:DCA document, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any position errors, exception highlighting might be included on the printed page. PSF continues processing of the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the image object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the image object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the image object, contact your system programmer.

APS418I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE IMAGE SIZE SPECIFIED IN THE IMAGE SIZE PARAMETER DOES NOT MATCH THE SIZE OF THE IMAGE DATA IN AN IPD STRUCTURED FIELD.
----------------	---

Explanation

The Image Size value that is specified in the Image Size Parameter does not match the size of the image data in an Image Data self-defining field. The Image Data field and the Image Size Parameter are both in an Image Picture Data (IPD) structured field. The IPD structured field is contained in an image object. The image object might be contained in a MO:DCA

document, an overlay, or a page segment; or it might be embedded in a data set containing line data.

If the IM1 image resolution in the IID structured field does not match the printer resolution, PSF attempts to convert the IM1 image to Image Object Content Architecture (IOCA) (if the printer supports IOCA). During this conversion process, IM1 structured fields are converted to IOCA Intelligent Printer Data Stream (IPDS) commands. If the size of the image that is specified in the IID structured field does not match the amount of image data within the IRD structured fields, this error might occur.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any position errors, exception highlighting might be included on the printed page. PSF continues processing of the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the image object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the image object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the image object, contact your system programmer.

APS419I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN UNSUPPORTED UNIT BASE VALUE WAS FOUND IN AN IMAGE SIZE
----------------	--

PARAMETER IN AN IPD STRUCTURED FIELD.

Explanation

The Unit Base value in an Image Size Parameter is not valid. The parameter is in an Image Picture Data (IPD) structured field. The IPD structured field is contained in an image object. The image object might be contained in a MO:DCA document, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any position errors, exception highlighting might be included on the printed page. PSF continues processing of the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the image object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the image object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the image object, contact your system programmer.

APS420I

AN ATTEMPT WAS MADE TO PRINT AN HRI CHARACTER OUTSIDE OF THE BAR CODE PRESENTATION SPACE.

Explanation

An attempt was made to print a human readable interpretation (HRI) character outside of the bar code presentation space. The bar code presentation space is a two-dimensional conceptual space in which a bar code is generated. The space is then mapped onto an output medium. The size of the bar code presentation space is defined in the Bar Code Data Descriptor (BDD) structured field.

The position of the HRI characters is defined in the Flags byte of the Bar Code Data (BDA) structured field. The position for the placement of the HRI characters caused an HRI character to be located outside of the bar code presentation space. The BDA and BDD structured fields are in a bar code object. The bar code object might be contained in an overlay or a MO:DCA document or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a

program to create the structured fields for the bar code object, contact your system programmer.

APS421I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE BAR CODE TYPE IN A BAR CODE IS NOT VALID OR IS UNSUPPORTED.

Explanation

If the bar code is specified as a bar code object, the Bar Code Type specified in a Bar Code Data Descriptor (BDD) structured field is not valid or is unsupported.

If the bar code is specified with the BARCODE subcommand in a page definition, the type name that is specified by the TYPE parameter on the BARCODE subcommand is not valid.

The bar code object might be contained in a MO:DCA document or in an overlay, or might be associated with a data set that contains line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page following the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object or the page definition, correct the error and resubmit the print request. See *Bar Code Object Content Architecture Reference* for more information

about bar code objects. See *Page Printer Formatting Aid: User's Guide* for more information about creating page definitions. If the structured field or page definition has no error, the error might be a PSF or printer logic error.

If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS422I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE LOCAL FONT IDENTIFIER IN A BAR CODE IS UNSUPPORTED OR REFERS TO A FONT THAT IS NOT AVAILABLE IN THE PRINTER.

Explanation

If the bar code is specified as a bar code object, the Local Font Identifier that is specified in a Bar Code Data Descriptor (BDD) structured field is not valid or is unsupported.

If the bar code is specified with the BARCODE subcommand in a page definition, the name that is specified by the FONT subcommand on the FIELD command that contains the BARCODE subcommand is not valid or is unsupported.

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The font ID is unsupported.
2. The font ID is not mapped to a font.
3. The font ID is mapped to a font, but the font is not loaded in the printer.
4. The font type style or code page cannot be determined, but it is required by this symbology for human readable interpretation (HRI).

The bar code object might be contained in a MO:DCA document or in an overlay, or might be associated with a data set that contains line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object or the page definition, correct the error and resubmit the print request. See *Bar Code Object Content Architecture Reference* for more information about bar code objects. See *Page Printer Formatting Aid: User's Guide* for more information about creating page definitions. If the structured field or page definition has no error, the error might be a PSF or printer logic error.

If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS423I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE COLOR IDENTIFIER IN A BAR CODE IS UNSUPPORTED.
----------------	---

Explanation

If the bar code is specified as a bar code object, the Color Identifier that is specified in a Bar Code Data Descriptor (BDD) structured field is not valid or is unsupported.

If the bar code is specified with the BARCODE subcommand in a page definition, the color name that is specified by the BCCOLOR parameter on the BARCODE subcommand is not valid.

The bar code object might be contained in a MO:DCA document or in an overlay, or might be associated with a data set that contains line data.

System action:

Operator response:

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object or the page definition, correct the error and resubmit the print request. See *Bar Code Object Content Architecture Reference* for more information about bar code objects. See *Page Printer Formatting Aid: User's Guide* for more information about creating page definitions. If the structured field or page definition has no error, the error might be a PSF or printer logic error.

If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS424I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE MODULE WIDTH IN A BAR CODE IS NOT VALID OR IS UNSUPPORTED.
----------------	---

Explanation

If the bar code is specified as a bar code object, the Module Width that is specified in a Bar Code Data Descriptor (BDD) structured field is not valid or is unsupported.

If the bar code is specified with the BARCODE subcommand in a page definition, the value that is specified by the MODWIDTH parameter on the BARCODE subcommand is not valid.

The bar code object might be contained in a MO:DCA document or in an overlay, or might be associated with a data set that contains line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object or the page definition, correct the error and resubmit the print request. See *Bar Code Object Content Architecture Reference* for more information about bar code objects. See *Page Printer Formatting Aid: User's Guide* for more information about creating page definitions. If the structured field or page definition has no error, the error might be a PSF or printer logic error.

If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS425I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE ELEMENT HEIGHT IN A BAR CODE IS NOT VALID OR IS UNSUPPORTED.

Explanation

If the bar code is specified as a bar code object, the Element Height that is specified in a Bar Code Data Descriptor (BDD) structured field is not valid or is unsupported.

If the bar code is specified with the BARCODE subcommand in a page definition, the value that is specified by the HEIGHT parameter on the BARCODE subcommand is not valid.

The bar code object might be contained in a MO:DCA document or in an overlay, or might be associated with a data set that contains line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the

page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object or the page definition, correct the error and resubmit the print request. See *Bar Code Object Content Architecture Reference* for more information about bar code objects. See *Page Printer Formatting Aid: User's Guide* for more information about creating page definitions. If the structured field or page definition has no error, the error might be a PSF or printer logic error.

If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS426I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE HEIGHT MULTIPLIER IN A BAR CODE IS NOT VALID.

Explanation

If the bar code is specified as a bar code object, the Height Multiplier that is specified in a Bar Code Data Descriptor (BDD) structured field is not valid or is unsupported.

If the bar code is specified with the Bar Code Symbol Descriptor (X'69') triplet in a page definition, the Height Multiplier is not valid.

The bar code object might be contained in a MO:DCA document or in an overlay, or might be associated with a data set that contains line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object or the page definition, correct the error and resubmit the print request. See *Bar Code Object Content Architecture Reference* for more information about bar code objects. See *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the X'69' triplet.

If the structured field or page definition has no error, the error might be a PSF or printer logic error.

If you used a program to create the structured fields for the bar code object or page definition, contact your system programmer.

Explanation

If the bar code is specified as a bar code object, the Wide-to-Narrow Ratio that is specified in a Bar Code Data Descriptor (BDD) structured field is not valid or is unsupported.

If the bar code is specified with the BARCODE subcommand in a page definition, the value that is specified by the RATIO parameter on the BARCODE subcommand is not valid.

The bar code object might be contained in a MO:DCA document or in an overlay, or might be associated with a data set that contains line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object or the page definition, correct the error and resubmit the print request. See *Bar Code Object Content Architecture Reference* for more information about bar code objects. See *Page Printer Formatting Aid: User's Guide* for more information about creating page definitions. If the structured field or page definition has no error, the error might be a PSF or printer logic error.

If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS427I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE WIDE-TO-NARROW RATIO IN A BAR CODE IS NOT VALID OR IS UNSUPPORTED.

APS428I**DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE SYMBOL ORIGIN FOR A BAR CODE SYMBOL IS NOT VALID OR IS UNSUPPORTED.****Explanation**

If the bar code is specified as a bar code object, the Symbol Origin that is specified in a Bar Code Data Descriptor (BDD) structured field is not valid or is unsupported.

If the bar code is specified with the BARCODE subcommand in a page definition, the x-pos and y-pos values that are specified by the POSITION subcommand on the FIELD command that contains the BARCODE subcommand are not valid or are unsupported.

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The horizontal (Xoffset) value is not valid or is unsupported.
2. The vertical (Yoffset) value is not valid or is unsupported.

The bar code object might be contained in a MO:DCA document or in an overlay, or might be associated with a data set that contains line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If

the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object or the page definition, correct the error and resubmit the print request. See *Bar Code Object Content Architecture Reference* for more information about bar code objects. See *Page Printer Formatting Aid: User's Guide* for more information about creating page definitions. If the structured field or page definition has no error, the error might be a PSF or printer logic error.

If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS429I**DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE BAR CODE MODIFIER IN A BAR CODE IS NOT VALID OR IS UNSUPPORTED.****Explanation**

If the bar code is specified as a bar code object, the Bar Code Modifier that is specified in a Bar Code Data Descriptor (BDD) structured field is not valid or is unsupported.

If the bar code is specified with the BARCODE subcommand in a page definition, the MOD parameter on the BARCODE subcommand is not valid or is unsupported for the type-name specified by the TYPE parameter on the BARCODE subcommand.

The bar code object might be contained in a MO:DCA document or in an overlay, or might be associated with a data set that contains line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set

in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object or the page definition, correct the error and resubmit the print request. See *Bar Code Object Content Architecture Reference* for more information about bar code objects. See *Page Printer Formatting Aid: User's Guide* for more information about creating page definitions. If the structured field or page definition has no error, the error might be a PSF or printer logic error.

If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS430I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE BAR CODE DATA LENGTH IN A BAR CODE IS NOT VALID OR IS UNSUPPORTED.

Explanation

If the bar code is specified as a bar code object, the length of the bar code data that is specified in a Bar Code Data Descriptor (BDD) structured field is not valid or is unsupported.

If the bar code is specified with the BARCODE subcommand in a page definition, the value that is specified by the LENGTH subcommand on the FIELD command that contains the BARCODE subcommand is not valid or is unsupported.

The bar code object might be contained in a MO:DCA document or in an overlay, or might be associated with a data set that contains line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set

with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object or the page definition, correct the error and resubmit the print request. See *Bar Code Object Content Architecture Reference* for more information about bar code objects. See *Page Printer Formatting Aid: User's Guide* for more information about creating page definitions. If the structured field or page definition has no error, the error might be a PSF or printer logic error.

If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS431I THE OBJECT AREA ORIGIN IN AN OBP STRUCTURED FIELD FOR A BAR CODE BLOCK IS OUTSIDE OF THE LOGICAL PAGE.

Explanation

The bar code block origin is specified in the Object Area Origin parameter of an Object Area Position (OBP) structured field. The origin that is specified lies outside of the logical page. The origin of the logical page is specified in the Page Position (PGP) structured field. The dimensions of the logical page are specified in the Page Descriptor (PGD) structured field.

The OBP structured field is in a bar code object. The bar code object might be contained in an overlay or a MO:DCA document or it might be embedded in a data set containing line data. The PGD structured field is in the MO:DCA data set, an overlay, or a page definition. The PGP structured field is in a form definition.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

Change one of these specifications:

- The logical page origin, by correcting the form definition.
- The logical page size, by correcting the MO:DCA data, the overlay, or the page definition.
- The bar code block origin, by correcting the bar code object.

If any of the specifications seem to be correct, this error might be a PSF or printer logic error. Notify your system programmer.

APS432I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A CHECK DIGIT VALUE OF 10 WAS CALCULATED, WHICH IS AN ERROR AS DEFINED BY THE BAR CODE MODIFIER FOR THIS BAR CODE TYPE.

Explanation

The Bar Code Modifier that is associated with the Bar Code Type of MSI specified that a check digit value of 10 must be treated as an error condition. A check digit value of 10 was calculated, which means that the bar code data is incorrect.

If the bar code is specified as a bar code object, the bar code data is in a Bar Code Data (BDA) structured field.

If the bar code is specified with the BARCODE subcommand in a page definition, the data is specified by the START and LENGTH subcommands on the FIELD command that contains the BARCODE subcommand.

The bar code object might be contained in a MO:DCA document or in an overlay, or might be associated with a data set that contains line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object or the page definition, correct the error and resubmit the print request. See *Bar Code Object Content Architecture Reference* for more information about bar code objects. See *Page Printer Formatting Aid: User's Guide* for more information about creating page definitions. If the structured field or page definition has no error, the error might be a PSF or printer logic error.

If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS433I**THE HRI LOCATION FOR A BAR CODE IS NOT VALID OR IS UNSUPPORTED.****Explanation**

If the bar code is specified as a bar code object, Human Readable Interpretation (HRI) location that is specified in the Flag byte in a Bar Code Data Descriptor (BDD) structured field is not valid or is unsupported.

If the bar code is specified with the BARCODE subcommand in a page definition, the value that is specified by the HRI parameter on the BARCODE subcommand is not valid or is unsupported.

The bar code object might be contained in a MO:DCA document or in an overlay, or might be associated with a data set that contains line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object or the page definition, correct the error and resubmit the print request. See *Bar Code Object Content Architecture Reference* for more information about bar code objects. See *Page Printer Formatting Aid: User's Guide* for more information about creating page definitions. If the structured field or page

definition has no error, the error might be a PSF or printer logic error.

If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS434I**AN ATTEMPT WAS MADE TO PLACE BAR CODE DATA OR THE BAR CODE PRESENTATION SPACE OUTSIDE OF THE DEFINED OUTPUT AREA FOR BAR CODE DATA.****Explanation**

The meaning of this exception depends on the printer that detected it. See your printer publications to determine which of these possibilities applies:

- Part of a bar code symbol extends beyond the output area for bar code data. This output area is the intersection of the mapped bar code presentation space with the bar code block.
- Part of the bar code presentation space extends beyond the boundaries of the bar code block.
- Part of the bar code symbol extends outside the valid printable area.

If the bar code is specified as a bar code object, the size of the bar code presentation space is defined in the Bar Code Data Descriptor (BDD) structured field. The size of the bar code block is defined in the Object Area Descriptor (OBD) structured field. The placement of the bar code symbol is defined in the Bar Code Data (BDA) structured field.

If the bar code is specified with the BARCODE subcommand in a page definition, the START and LENGTH subcommands on the FIELD command that contains the BARCODE subcommand determine the data used for the bar code. If the bar code is specified in a page definition, the only possible error is the bar code symbol exceeds the valid printable area.

The bar code object might be contained in a MO:DCA document or in an overlay, or might be associated with a data set that contains line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object or the page definition, correct the error and resubmit the print request. See *Bar Code Object Content Architecture Reference* for more information about bar code objects. See *Page Printer Formatting Aid: User's Guide* for more information about creating page definitions. If the structured field or page definition has no error, the error might be a PSF or printer logic error.

If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS435I AN ATTEMPT WAS MADE TO PLACE BAR CODE DATA OR THE BAR CODE PRESENTATION SPACE OUTSIDE OF THE DEFINED OUTPUT AREA FOR BAR CODE DATA.

Explanation

The meaning of this exception depends on the printer that detected it. See your printer publications to determine which of these possibilities applies:

- Part of a bar code symbol extends beyond the output area for bar code data. This output area is the intersection of the mapped bar code presentation space and the bar code block.
- Part of the bar code presentation space extends beyond the bar code block boundaries.
- Part of the bar code symbol extends outside the valid printable area.

If the bar code is specified as a bar code object, the size of the bar code presentation space is defined in the Bar Code Data Descriptor (BDD) structured field.

The size of the bar code block is defined in the Object Area Descriptor (OBD) structured field. The placement of the bar code symbol is defined in the Bar Code Data (BDA) structured field.

If the bar code is specified with the BARCODE subcommand in a page definition, the START and LENGTH subcommands on the FIELD command that contains the BARCODE subcommand determine the data used for the bar code. If the bar code is specified in a page definition, the only possible error is the bar code symbol exceeds the valid printable area.

The bar code object might be contained in a MO:DCA document or in an overlay, or might be associated with a data set that contains line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object or the page definition, correct the error and resubmit the print request. See *Bar Code Object Content Architecture Reference* for more information about bar code objects. See *Page Printer Formatting Aid: User's Guide* for more information about creating page definitions.

If the structured field or page definition has no error, the error might be a PSF or printer logic error.

If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS436I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: GRAPHICS DATA CONTAINS AN UNSUPPORTED DRAWING ORDER OR COMMAND CODE.

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. An unsupported drawing order was specified in a Graphics Data (GAD) structured field.
2. A Begin Segment Introducer was not found in a GAD structured field.
3. The Parameter Type value in the Drawing Order self-identifying parameter of the Graphics Data Descriptor (GDD) structured field is not valid.

The GAD and GDD structured fields are in a graphics object. The graphics object might be contained in a MO:DCA document, or an overlay, or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS437I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A GRAPHICS OBJECT CONTAINS AN INCORRECT VALUE.

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. A reserved byte in a graphics drawing order is not set to 0. Drawing orders are in a Graphics Data (GAD) structured field. This condition is retired by the AFP GOCA architecture.
2. The Parameter Type value in the Set Current Defaults self-identifying parameter of the Graphics Data Descriptor (GDD) structured field is not valid.
3. The Parameter Length in the Set Current Defaults self-identifying parameter of the GDD structured field is X'04', but the Flag byte is not X'0F'.
4. The Parameter Length in the Set Current Defaults self-identifying parameter of the GDD structured field is greater than X'04', but the Flag byte is not X'8F'.
5. A Mask attribute value in the Set Current Defaults self-identifying parameter of the GDD structured field is not valid or is unsupported.

The GAD and GDD structured fields are in a graphics object. The graphics object might be contained in a MO:DCA document, or an overlay, or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS438I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE LENGTH OF A GRAPHICS DRAWING ORDER IS INCORRECT.

Explanation

A drawing order in a graphics object has an incorrect length. When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The Flags byte in the Set Current Defaults self-identifying parameter of a Graphics Data Descriptor (GDD) structured field, is X'8F', but the Length field does not contain the value implied by the Mask field.
2. The Segment Length in a Begin Segment Introducer in a Graphics Data (GAD) structured field is X'0000' for a new segment.
3. A drawing order in a GAD structured field specifies an incorrect length.
4. The Flag byte in the Set Current Defaults self-identifying parameter of a GDD structured field is X'0F', but the Length field is not X'04'.

5. The Flag byte in the Set Current Defaults self-identifying parameter of a GDD structured field is X'8F', and the Length field contains the value that is implied by the Mask field, but the number of Data bytes does not match the value in the Length field.

The GAD and GDD structured fields are in a graphics object. The graphics object might be contained in a MO:DCA document, or an overlay, or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS439I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A GRAPHICS DRAWING ORDER IN A GAD STRUCTURED FIELD CONTAINS AN INCORRECT ATTRIBUTE VALUE.

Explanation

A drawing order in a Graphics Data (GAD) structured field contains an incorrect value for an attribute. The drawing order is contained in a Graphics Data (GAD) structured field. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay or it might be embedded in a data set containing line data.

System action:

Operator response:

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response:

APS440I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A GRAPHICS DRAWING ORDER IN A GAD STRUCTURED FIELD IS INCOMPLETE.

Explanation

An incomplete drawing order was specified in a Graphics Data (GAD) structured field. When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The order is a fixed 2-byte order and the second byte is not in the segment.
2. The order is a long format order and the length byte is not in the segment.
3. The order is a long or extended format order and the number of bytes following the field that contains the length count to the end of the segment is less than the value of the length count.
4. The order is an extended format order and the qualifier byte is not in the segment.
5. The order is an extended format order and one or both of the length bytes are not in the segment.

The GAD structured field is in a graphics object. The graphics object might be contained in a MO:DCA document, or an overlay, or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS441I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE PROLOG IN A GAD STRUCTURED FIELD CONTAINS INCORRECT DATA.

Explanation

A Graphics Data (GAD) structured field contains a Begin Segment Introducer that defines a prolog for a graphics segment. When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. A supported drawing order is encountered that is not valid in a prolog.

2. The end of the segment was reached and no End Prolog was encountered.

The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS442I AN ATTEMPT WAS MADE TO PLACE GRAPHICS DATA OUTSIDE OF THE GRAPHICS PRESENTATION SPACE.

Explanation

A drawing order attempted to place graphics data outside of the graphics presentation space. The graphics presentation space is a two-dimensional conceptual space in which the graphics data is

generated. The space is then mapped onto an output medium. The extent of the graphics presentation space is -32 K to +32 K units. The size of the graphics data is defined in the Begin Image drawing order in the Graphics Data (GAD) structured field. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS443I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A GRAPHICS DRAWING ORDER IN A GAD STRUCTURED FIELD CONTAINS AN UNSUPPORTED ATTRIBUTE VALUE, SUCH AS AN UNSUPPORTED COLOR VALUE.

Explanation

A drawing order in a Graphics Data (GAD) structured field contains an unsupported value for an attribute. The drawing order is contained in a Graphics Data (GAD) structured field. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay or it might be embedded in a data set containing line data.

This message is sometimes issued because an unsupported color value is specified in a Set Color or Set External Color drawing order.

System action:

Operator response:

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response:

APS444I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A DEFAULT VALUE SET IN A GDD STRUCTURED FIELD IS NOT VALID OR IS UNSUPPORTED.
----------------	--

Explanation

The Set Current Defaults self-identifying parameter of a Graphics Data Descriptor (GDD) structured field sets a default in the Data bytes that is not valid or is unsupported. The GDD structured field is in a graphics object. The graphics object might be contained in a MO:DCA document, or an overlay, or it might be embedded in a data set containing line data.

System action:

Operator response:

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response:

APS445I	PRINTER (prtnnnn) IS UNUSABLE —ASSIGNED TO ANOTHER SYSTEM.
----------------	---

Explanation

PSF attempted to issue I/O to the printer, but the printer was assigned (reserved) to another system. The printer multi-host feature was enabled, which causes the printer to enforce that only one system can use the printer at a time. The printer detected and reported the error with an action code X'25' (sense byte 2). For more information about this error, see the printer publications for the printer that reported this error.

System action

PSF issues this message and ends with a system completion code 024 and abend reason code 0E33 or 0E35.

Operator response

Determine which system the printer is assigned to and, when appropriate, vary the printer offline from that system and vary the printer online to the system you want. Restart PSF.

System programmer response

If you do not need to share the printer among multiple PSF hosts, disable the multi-host feature at the printer console. For more information about sharing a printer among multiple PSFs, see *PSF for z/OS: Customization*.

APS446I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE SET CHARACTER ANGLE DRAWING ORDER IN A GAD STRUCTURED FIELD SPECIFIES AN UNSUPPORTED CHARACTER ANGLE VALUE.
----------------	--

Explanation

The Character Angle value that is specified in a Set Character Angle drawing order is not supported. The drawing order is contained in a Graphics Data (GAD) structured field. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the

page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS447I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE END PROLOG DRAWING ORDER IS OUT OF SEQUENCE IN A GAD STRUCTURED FIELD.
----------------	---

Explanation

PSF found an End Prolog drawing order outside of the prolog section of a graphics segment. The drawing order is contained in a Graphics Data (GAD) structured field. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed

page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS448I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN END AREA DRAWING ORDER IS OUT OF SEQUENCE IN A GAD STRUCTURED FIELD.
----------------	--

Explanation

An End Area drawing order was encountered without a Begin Area drawing order that precedes it. The drawing order is contained in a Graphics Data (GAD) structured field. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the

printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS449I	INSUFFICIENT PRINTER STORAGE WAS AVAILABLE TO PROCESS A GRAPHICS OBJECT.
----------------	---

Explanation

Some areas that are defined in graphics segments require temporary printer storage for processing. Insufficient temporary printer storage was available to process a graphics segment in a graphics object. The graphics object might be contained in a MO:DCA document, or an overlay, or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

Simplify the area that is defined in the graphics segment, and submit the print request again.

APS450I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A BEGIN AREA DRAWING ORDER IS OUT OF SEQUENCE IN A GAD STRUCTURED FIELD.
----------------	---

Explanation

A Begin Area drawing order was encountered at a time when another Begin Area drawing order was in effect. The drawing orders are contained in a Graphics Data (GAD) structured field. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the

input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS451I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN END AREA DRAWING ORDER IS MISSING FROM A GAD STRUCTURED FIELD.

Explanation

A Begin Area drawing order was processed in a graphics segment, and the end of the segment was reached before an End Area drawing order was encountered. The drawing orders are contained in a Graphics Data (GAD) structured field. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the

input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS452I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN UNEXPECTED DRAWING ORDER WAS ENCOUNTERED IN A GAD STRUCTURED FIELD.

Explanation

A drawing order was encountered within an area defined by a Begin Area drawing order. This drawing order is supported, but is not valid inside an area. The drawing order is contained in a Graphics Data (GAD) structured field. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for

assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS453I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE SET PATTERN SET DRAWING ORDER IN A GAD STRUCTURED FIELD CONTAINS AN UNSUPPORTED VALUE.
----------------	---

Explanation

The Pattern Set Identifier that is specified in a Set Pattern Set drawing order is not supported. The drawing order is contained in a Graphics Data (GAD) structured field. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If

the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS454I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE PATTERN TYPE SPECIFIED IN A SET PATTERN SYMBOL DRAWING ORDER IN A GAD STRUCTURED FIELD IS UNDEFINED.
----------------	---

Explanation

The Pattern Type specified in a Set Pattern Symbol drawing order is not defined in the pattern symbol set specified in a Set Pattern Set drawing order. The drawing orders are contained in a Graphics Data (GAD) structured field. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If

the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS455I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE SEGMENT FLAGS IN THE BEGIN SEGMENT INTRODUCER OF A GAD STRUCTURED FIELD ARE NOT VALID.
----------------	---

Explanation

The Segment Flags in the Begin Segment Introducer of a Graphics Data (GAD) structured field are set to B'10', which is an incorrect value. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data

set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS456I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE SEGMENT FLAGS IN THE BEGIN SEGMENT INTRODUCER OF A GAD STRUCTURED FIELD ARE NOT VALID.
----------------	---

Explanation

The Segment Flags in the Begin Segment Introducer of a Graphics Data (GAD) structured field are set to B'01', which is an incorrect value. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data

set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS457I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: BYTE 1 OF THE BEGIN SEGMENT INTRODUCER IS NOT VALID IN A GAD STRUCTURED FIELD.
----------------	---

Explanation

The Begin Segment Introducer Length parameter (byte 1) is not valid in a Graphics Data (GAD) structured field. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS458I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: LESS DATA WAS FOUND IN THE DRAWING ORDERS FOR A GRAPHICS SEGMENT THAN WAS SPECIFIED IN THE BEGIN SEGMENT INTRODUCER SEGMENT LENGTH PARAMETER IN A GAD STRUCTURED FIELD.
----------------	--

Explanation

The amount of data in the drawing orders for a graphics segment is less than the segment length specified in the Begin Segment Introducer of a Graphics Data (GAD) structured field. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data

set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS459I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN IMAGE DATA DRAWING ORDER IS OUT OF SEQUENCE IN A GAD STRUCTURED FIELD.
----------------	--

Explanation

An Image Data drawing order was encountered without a preceding Begin Image drawing order. The drawing order is contained in a Graphics Data (GAD) structured field. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS460I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE AMOUNT OF IMAGE DATA FOUND IN AN IMAGE DATA DRAWING ORDER IN A GAD STRUCTURED FIELD DOES NOT MATCH THE SPECIFIED LENGTH.
----------------	---

Explanation

The amount of image data that is found in an Image Data drawing order does not match the Length parameter specified in that drawing order. The drawing order is contained in a Graphics Data (GAD) structured field. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS461I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN END IMAGE DRAWING ORDER IS OUT OF SEQUENCE IN A GAD STRUCTURED FIELD.
----------------	---

Explanation

An End Image drawing order was encountered that is not preceded by a Begin Image drawing order. The drawing order is contained in a Graphics Data (GAD) structured field. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS462I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE NUMBER OF DRAWING ORDERS IN A GAD STRUCTURED FIELD IS INCORRECT.
----------------	---

Explanation

The number of drawing orders between the Begin Image and End Image drawing orders is not equal to the value specified in the Image Height parameter in the Begin Image drawing order. The drawing orders are contained in a Graphics Data (GAD) structured field. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS463I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE SET MARKER SET DRAWING ORDER IN A GAD STRUCTURED FIELD CONTAINS AN UNSUPPORTED VALUE.

Explanation

The Local Marker Set Identifier that is specified in a Set Marker Set drawing order is not supported. The drawing order is contained in a Graphics Data (GAD) structured field. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS464I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE MARKER SYMBOL SPECIFIED IN A SET MARKER SYMBOL DRAWING ORDER IN A GAD STRUCTURED FIELD IS UNDEFINED.

Explanation

The Marker Symbol that is specified in a Set Marker Symbol drawing order is not defined in the marker symbol set specified in the Set Marker Set drawing order. The drawing orders are contained in a Graphics Data (GAD) structured field. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS465I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE MARKER SYMBOL SPECIFIED IN A SET MARKER SYMBOL DRAWING ORDER IN A GAD STRUCTURED FIELD IS NOT SUPPORTED IN THE CURRENT MARKER SYMBOL SET.

Explanation

The Marker Symbol that is specified in a Set Marker Symbol drawing order is not supported in the marker symbol set specified in the Set Marker Set drawing order. The drawing orders are contained in a Graphics Data (GAD) structured field. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS466I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE CHARACTER SET SPECIFIED IN A SET CHARACTER SET DRAWING ORDER IN A GAD STRUCTURED FIELD IS NOT AVAILABLE IN THE PRINTER OR CANNOT BE USED WITH THE CURRENT PRINT QUALITY LEVEL.

Explanation

The Local Character Set Identifier that is specified in a Set Character Set drawing order or as a current default, and then is later used by a Character String drawing order, contains an error. When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The Local Character Set Identifier is not mapped to a font or symbol set.
2. The Local Character Set Identifier was mapped to a font or symbol set that is not loaded in the printer.
3. The Local Character Set Identifier was mapped to a font or symbol set, but is not supported at the current print quality level.

The print quality level is specified in the Medium Modification Control (MMC) structured field in the form definition. The drawing order is contained in a Graphics Data (GAD) structured field. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error. If you suspect a PSF logic error, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

Change one of these specifications:

- The print quality level in the form definition
- The character set identifier in the graphics object

If the character set that is originally specified needs to be supported at the specified print quality level, this error might be a PSF or printer logic error. Notify your system programmer.

APS467I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A GRAPHICS CHARACTER CODE IN A GAD STRUCTURED FIELD IS UNDEFINED OR UNAVAILABLE IN THE CURRENT CHARACTER SET.

Explanation

A graphics character code in a Character String drawing order is undefined or points to a character pattern that is not available in the character set specified in the Set Character Set drawing order. The drawing orders are contained in a Graphics Data (GAD) structured field. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS468I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A GRAPHICS CHARACTER CODE IN A GAD STRUCTURED FIELD IS UNDEFINED OR UNAVAILABLE IN THE CURRENT CHARACTER SET.

Explanation

A graphics character code in a Character String drawing order is undefined or points to a character pattern that is not available in the character set specified in the Set Character Set drawing order. The drawing orders are contained in a Graphics Data (GAD) structured field. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS469I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE SYMBOL SET SPECIFIED IN A SET CHARACTER SET DRAWING ORDER IN A GAD STRUCTURED FIELD DOES NOT HAVE THE CHARACTER ATTRIBUTES SPECIFIED IN THE GDD STRUCTURED FIELD.
----------------	--

Explanation

The symbol set specified in a Set Character Set drawing order cannot support the functions of the character attributes specified in the corresponding Graphics Data Descriptor (GDD) structured field. The drawing order is in a Graphics Data (GAD) structured field. The GAD and GDD structured fields are in a graphics object. The graphics object might be contained in a MO:DCA document, or an overlay, or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set

with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS470I	THE OVERLAY NESTING LIMIT OF THE PRINTER WAS EXCEEDED.
----------------	---

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. While processing an overlay, the printer is unable to include a nested overlay because the nesting limit of the printer is exceeded (possible logic error).
2. While processing an overlay, the printer is unable to include a page segment because the nesting limit of the printer is exceeded. The excessive page segment nesting in a page prevented the processing of an overlay or page segment.

System action

The printer you were using might try to print the page in error, or might print only part of the page. If the page that contains the error contains any positioning errors,

print-error markers might be included on the printed page. PSF stops processing and printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If the printed output is not acceptable, use smaller or fewer page segments in the overlay.

APS471I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE OBJECT AREA ORIENTATION IN AN OBP OR IOB STRUCTURED FIELD PARAMETER IS NOT VALID OR IS NOT SUPPORTED BY THE PRINTER.
----------------	---

Explanation

If you are printing bar code objects, graphics objects, image objects, object container objects, or presentation text objects, the Object Area Orientation parameter in an Object Area Position (OBP) or Include Object (IOB) structured field contains an incorrect value that is not supported by the printer. The OBP structured field is in the Object Environment Group (OEG) of the bar code, graphics, image, object container, or presentation text object. The IOB structured field is in a print data set, overlay, or page definition.

If the bar code is specified with a BARCODE subcommand in a page definition, the text orientation on the Line Descriptor (LND), Record Descriptor (RCD), or XML Descriptor (XMD) is not valid. The bar code object, graphics object, image object, object container object, or presentation text object might be contained or referenced in a MO:DCA document or an overlay, or might be associated with a data set that contains line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed

page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information provided in the User Response section to correct the error.

User response

If you created the structured fields for the object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured fields.

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the LND, RCD, or XMD structured field.

If the structured field has no error, the error might be a PSF or printer logic error.

If you used a program to create the structured fields for the object, contact your system programmer.

APS473I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE OBJECT CONTENT ORIGIN PARAMETER IS INCORRECT OR IS UNSUPPORTED IN AN OBP STRUCTURED FIELD.
----------------	---

Explanation

The Object Content Origin parameter in an Object Area Position (OBP) structured field contains an incorrect or unsupported value. The OBP structured field is in the Object Environment Group of a bar code, graphics, image, or presentation text object, or an object container. The bar code, graphics, image, or presentation text object, or the object container might

be contained or referenced in a MO:DCA document or a resource, or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the object, contact your system programmer.

APS474I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE UNITS PER UNIT BASE SPECIFIED FOR THE OBJECT ARE INCORRECT.

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The Units per Unit Base parameter in the IOB that included the object or in a Graphics Data Descriptor

(GDD), Image Data Descriptor (IDD), Bar Code Data Descriptor (BDD), Container Data Descriptor (CDD), or Object Area Descriptor (OBD) structured field is not valid or is unsupported.

2. The units per unit base that are specified for the Y coordinate in the GDD or BDD structured field is not equal to the units per unit base specified for the X coordinate.
3. The value that is specified in the IMXYRES field in the GDD structured field is not valid.

If the IM1 image resolution within the IID structured field does not match the printer resolution, PSF attempts to convert the IM1 image to IOCA, if the printer supports IOCA. During this conversion process, IM1 structured fields are converted to IOCA IPDS commands. Because IM1 structured fields do not contain L-Units per Unit Base parameters, the L-Units are determined from the PGD used for the page. The bar code, graphics, image, or presentation text object might be contained or referenced in a MO:DCA document, an overlay, or a page segment, or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the object, correct the error and resubmit the print request. See

Mixed Object Document Content Architecture Reference for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the object, contact your system programmer.

APS475I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE X OR Y EXTENT SPECIFIED FOR THE OBJECT IS NOT VALID.

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The Xg and Yg coordinates for a Graphics Data Descriptor (GDD), the X, Y sizes for an Image Data Descriptor (IDD), the X, Y extents for a Bar Code Data Descriptor (BDD), or the size for a Container Data Descriptor (CDD), Object Area Descriptor (OBD), or Include Object (IOB) that included the object are not valid or are unsupported.
2. The graphics presentation space window that is specified in the GDD structured field is defined incorrectly (the Xg left limit is equal to or to the right of the Xg right limit, or the Yg bottom limit is equal to or above the Yg top limit).

The bar code, graphics, image, or presentation text object might be contained or referenced in a MO:DCA document, an overlay, or a page segment, or it might be embedded in a data set containing line data.

If the bar code is specified with the BARCODE subcommand in a page definition, the values that are specified for the WIDTH parameter, the HEIGHT parameter, or both on the active PAGEFORMAT command or PAGEDEF command are not valid or are unsupported.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set

in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the object or you created the page definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. See *Page Printer Formatting Aid: User's Guide* for more information about creating page definitions.

If the structured field has no error, the error might be a PSF or printer logic error.

If you used a program to create the structured fields for the object, contact your system programmer.

APS476I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE HORIZONTAL COORDINATE FOR THE IMAGE BLOCK ORIGIN PARAMETER IS OUT OF RANGE IN AN IOC STRUCTURED FIELD.

Explanation

The Horizontal Coordinate for the Image Block Origin parameter is out of range in an Image Output Control (IOC) structured field. The value is specified in absolute X-units. The image block or image cell might be contained in an overlay, a page segment, or a MO:DCA document. It might also be embedded in a data set containing line data by using a Begin Image (BIM) structured field.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the resource or print data set containing the image, correct the error in the referenced structured field and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the resource or print data set containing the image, contact your system programmer.

APS477I AN ATTEMPT WAS MADE TO PRINT AN OBJECT OUTSIDE OF THE VALID PRINTABLE AREA.

Explanation

An attempt was made to print a bar code, graphics, or image object outside of the valid printable area. The valid printable area is the intersection (common space) of the physical page with one of these:

- The logical page
- The overlay
- The user-printable area defined within the logical page

Data in an image, graphics, or bar code object falls at least partly outside of the valid printable area.

The logical page size is defined in the Page Descriptor (PGD) structured field. The logical page origin is defined in the Page Position (PGP) structured field. The PGD structured field can be in the MO:DCA data, in an overlay, or in a page definition. The PGP structured field is in a form definition.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the

page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

Ensure that the correct form was loaded in the printer. If it was, change one of these specifications:

- The logical page size in the MO:DCA data, overlay, or page definition
- The logical page origin in the form definition
- The object origin in the Object Area Position (OBP) structured field in the object
- The object size in the Object Area Descriptor (OBD) structured field in the object

If all of the specifications seem correct, the error might be a PSF or printer logic error. Notify your system programmer.

APS478I AN ATTEMPT WAS MADE TO PRINT AN OBJECT OUTSIDE OF THE VALID PRINTABLE AREA.

Explanation

An attempt was made to print a bar code, graphics, or image object outside of the valid printable area. The valid printable area is the intersection (common space) of the physical page with one of these:

- The logical page
- The overlay
- The user-printable area defined in the logical page

Data in an image, graphics, or bar code object falls at least partly outside of the valid printable area.

The logical page size is defined in the Page Descriptor (PGD) structured field. The logical page origin is defined in the Page Position (PGP) structured field. The PGD structured field can be in the MO:DCA data, in an overlay, or in a page definition. The PGP structured field is in a form definition.

If the IM1 image resolution within the IID structured field does not match the printer resolution, PSF attempts to convert the IM1 image to Image Object Content Architecture (IOCA) (if the printer supports IOCA). During this conversion process, IM1 structured fields are converted to IOCA Intelligent Printer Data Stream (IPDS) commands. IM1 images that fall outside of the logical page would cause this error.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see [PSF for z/OS: Diagnosis](#) for assistance in determining the source of the problem.

User response

Ensure that the correct form was loaded in the printer. If it was, change one of these specifications:

- The logical page size in the MO:DCA data, overlay, or page definition
- The logical page origin in the form definition
- The object origin in the Object Area Position (OBP) structured field in the object
- The object size in the Object Area Descriptor (OBD) structured field in the object

If all of the specifications seem correct, the error might be a PSF or printer logic error. Notify your system programmer.

**APS479I PRINTER (*prtnnnn*) IS UNUSABLE
—NOT ASSIGNED TO THIS
SYSTEM.**

Explanation

PSF attempted to issue I/O to the printer, but the printer was not assigned (reserved) to this system. The printer multi-host feature was enabled, which causes the printer to enforce that only one system can use the printer at a time. The printer detected and reported the error with an action code X'24' (sense byte 2). For more information about this error, see the printer publications for the printer that reported this error.

System action

PSF issues this message and ends with a system completion code 024 and abend reason code 0E34 or 0E36.

Operator response

Determine which system the printer must be assigned to and, when available, vary the printer online to the system. This action might require the printer be varied offline from another system. Restart PSF.

System programmer response

If you do not need to share the printer among multiple PSF for z/OS hosts, disable the multi-host feature at the printer console. For more information about the sharing of a printer among multiple PSFs, see [PSF for z/OS: Customization](#).

**APS480I THE ERROR SENSE BYTES 0–7 =
error sense bytes 0–7, SENSE
BYTES 8–18 = *error sense bytes 8–
18*, SPECIFICATION GROUP =
specification group, PAGE
IDENTIFIER = *page identifier*.**

Explanation

This message formats and presents the 24 printer sense bytes that were reported to PSF at the time of an I/O error. A message that describes the specific I/O error accompanies this message.

- *error sense bytes 0–7* are the first 8 bytes in the sense data, reported in hexadecimal.
- *error sense bytes 8–18* are the next 11 bytes in the sense data, reported in hexadecimal.

- *specification group* is byte 19 of the sense data (reported in hexadecimal), which identifies the group number for specification check exceptions.
- *page identifier* is the last 4 bytes in the sense data (reported in hexadecimal), which identify the page that contains the error.

System action

See the accompanying messages for the system action that was taken.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the accompanying messages are not sufficient to identify the problem, use the sense data to analyze the problem. For more information about printer sense bytes and the specific error, see the printer publications for the printer that reported this error.

User response

See the specific error conditions that are described in the accompanying messages to determine an appropriate response.

APS481I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN ARC DRAWING ORDER IN A GAD STRUCTURED FIELD CAUSED AN ARC ENDING ERROR.

Explanation

A Full Arc or Full Arc at Current Position drawing order has an error in its coordinate values so that the starting and ending points of the arc are identical. The drawing order is contained in a Graphics Data (GAD) structured field. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the

printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS482I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN ARC DRAWING ORDER IN A GAD STRUCTURED FIELD CONTAINS ERRORS.

Explanation

A Full Arc or Full Arc at Current Position drawing order has an error in its coordinate values so that it might not be possible to draw the arc within the normal limits of pel accuracy. The drawing order is contained in a Graphics Data (GAD) structured field. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the

printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS483I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN END IMAGE DRAWING ORDER IS MISSING FROM A GAD STRUCTURED FIELD.

Explanation

A Begin Image drawing order was processed in a graphics segment, and the end of the segment was reached before an End Image drawing order was encountered. The drawing order is contained in a Graphics Data (GAD) structured field. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the

printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS484I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A DRAWING ORDER IS OUT OF SEQUENCE IN A GAD STRUCTURED FIELD.

Explanation

A Begin Image drawing order was processed in a graphics segment, and a drawing order that is not allowed to follow that drawing order was encountered. The drawing orders are contained in a Graphics Data (GAD) structured field. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the

printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS485I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE IMAGE FORMAT SPECIFIED IN A BEGIN IMAGE DRAWING ORDER IN A GAD STRUCTURED FIELD IS NOT SUPPORTED.**

Explanation

The Image Format value that is specified in a Begin Image drawing order is not supported. The drawing order is contained in a Graphics Data (GAD) structured field. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the

printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS486I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE IMAGE WIDTH SPECIFIED IN A BEGIN IMAGE DRAWING ORDER IN A GAD STRUCTURED FIELD IS TOO LARGE.**

Explanation

The Image Width value that is specified in a Begin Image drawing order exceeds the maximum supported image width. The drawing order is contained in a Graphics Data (GAD) structured field. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the

printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS487I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE IMAGE HEIGHT SPECIFIED IN A BEGIN IMAGE DRAWING ORDER IN A GAD STRUCTURED FIELD IS TOO LARGE.**

Explanation

The Image Height value that is specified in a Begin Image drawing order exceeds the maximum supported image height. The drawing order is contained in a Graphics Data (GAD) structured field. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the

printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS488I **AN ATTEMPT WAS MADE TO DRAW A LINE OUTSIDE OF THE GRAPHICS PRESENTATION SPACE.**

Explanation

A Relative Line or Relative Line at Current Position drawing order attempted to draw a line outside of the graphics presentation space. The graphics presentation space is a two-dimensional conceptual space in which the graphics data is generated. The space is then mapped onto an output medium. The extent of the graphics presentation space is -32 K to +32 K units. The end points of the line are defined in the drawing order. The drawing order is contained in a Graphics Data (GAD) structured field. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the

page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS489I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A SEGMENT CHARACTERISTICS DRAWING ORDER IS OUT OF SEQUENCE IN A GAD STRUCTURED FIELD.

Explanation

A Segment Characteristics drawing order was encountered outside of a segment prolog. The drawing order is contained in a Graphics Data (GAD) structured field. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then

print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS490I THE ERROR SENSE BYTES 0-2 = error sense bytes 0-2.

Explanation

This message presents the three printer sense bytes that were reported to PSF at the time of an I/O error.

System action

See the accompanying messages for the system action that was taken.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot be initialized or cannot print a separator page or error messages. Inform your system programmer that this error occurred.

System programmer response

To determine an appropriate response, see the specific error conditions described in the accompanying

messages. If the accompanying messages are not sufficient to identify the problem, use the sense data to analyze the problem. For more information about printer sense bytes and the specific error, see the printer publications for the printer that reported this error. If the error condition persists, follow the procedures described in *PSF for z/OS: Diagnosis* before you consult with the IBM Support Center.

User response

To determine an appropriate response, see the specific error conditions described in the accompanying messages. If the accompanying messages are not sufficient to identify the problem, consult your system programmer.

APS491I THE PRINT QUALITY LEVEL SPECIFIED IN THE FORMDEF CANNOT BE PROVIDED BY THE SELECTED FONT.

Explanation

The font that is selected to print the data cannot provide the print quality level specified in the Medium Modification Control (MMC) structured field. When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The combination of parameters that are specified for a font is unsupported when used with the specified print quality level.
2. A requested character set for a font that is mapped on the page is not valid or is unsupported, or is not valid with the other font parameters.

The MMC structured field is in the form definition. The selected font is specified in the MO:DCA data, page definition, or overlay, or with the JCL CHARS option. If no font was explicitly specified, the default printer font was being used.

System action

PSF stops processing and printing the page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If the print quality and font that are used by the printer are acceptable, no response is necessary. If the specified print quality level is required, select a font that can be printed at that print quality level, and resubmit the print request. If the selected font is required, specify a print quality level in the form definition that is supported by that font, and resubmit the print request. To determine the print quality level that each font supports, see the documentation provided with the printer.

APS492I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE SPECIFIED FONT CANNOT BE PRINTED IN THE SPECIFIED ORIENTATION.

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. A Set Coded Font Local (SCFL) text control in a Presentation Text Data (PTX) structured field named a font that was not available in the printer in the orientation specified in a Set Text Orientation (STO) text control.
2. An STO text control, when combined with the current print direction, results in a print direction that the printer does not support.
3. The current print direction is not valid, is unsupported, or is unsupported within the current text orientation.

The STO text control is embedded in a PTX structured field or was generated by PSF from a page definition. The Presentation Text Data (PTX) structured field might be contained in a MO:DCA document, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

PSF stops the processing and printing of the page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set

in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APS493I	AN ATTEMPT WAS MADE TO USE A RESIDENT SYMBOL SET OR RESIDENT FONT THAT IS NOT VALID OR IS NOT SUPPORTED BY THIS PRINTER.
----------------	---

Explanation

A resident symbol set or resident font that is specified for this print data set is not valid, or is not supported by this printer. The name of the symbol set or font might be specified in the JCL CHARS parameter or in a Map Coded Font (MCF) structured field. The MCF structured field is contained in a MO:DCA document, an overlay, or a page definition.

PSF uses the PSF Resident Font Table (APSRFTBL) to map the font or symbol set name to a Global Resource Identifier (GRID), which is then used to identify the font or symbol set in the printer. The symbol set or font was defined in APSRFTBL, but was not recognized by the printer.

System action

PSF stops the processing and printing of the page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If necessary, modify the entry in the APSRFTBL for the symbol set or font named by the print-job submitter. Ensure that the requested font or symbol set is mapped to a valid GRID. If the current entry seems to be valid, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

Inform your system programmer that this error occurred.

APS494I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE IMAGE BLOCK ORIGIN IS INCORRECT OR IS UNSUPPORTED.
----------------	---

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The reference coordinate system for the image object is not valid or is unsupported.
2. The X-axis origin for object content in an Include Object (IOB) or Object Area Position (OBP) structured field is not valid or is unsupported.
3. The Y-axis origin for object content in an Include Object (IOB) or Object Area Position (OBP) structured field is not valid or is unsupported.

The IOB structured field is contained in a print data set, overlay, or page definition. The OBP structured field is in the Object Environment Group of an image or the Active Environment Group (AEG) for the page. The image block or image cell might be embedded in a data set containing line data by using a Begin Image (BIM) structured field.

If the printer does not support Image Object Content Architecture (IOCA), PSF might convert your IOCA image to an IM1 image. In this case, the incorrect value is in the OBP structured field.

System action

If the image is in a page, the printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues the processing of the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF

recovery action. If the image is in a resource, PSF stops processing the data set that uses the resource in error.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the resource or print data set containing the image, correct the error in the referenced structured field and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the resource or print data set containing the image, contact your system programmer.

APS495I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE VERTICAL COORDINATE FOR THE IMAGE BLOCK ORIGIN PARAMETER IS OUT OF RANGE IN AN IOC STRUCTURED FIELD.**

Explanation

The Vertical Coordinate for the Image Block Origin parameter is out of range in an Image Output Control (IOC) structured field. The value is specified in absolute Y-units. The image block or image cell might be contained in an overlay, a page segment, or a MO:DCA document. It can also be embedded in a data set containing line data by using a Begin Image (BIM) structured field.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set

with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the resource or print data set containing the image, correct the error in the referenced structured field and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the resource or print data set containing the image, contact your system programmer.

APS496I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE COMPRESSION ALGORITHM SPECIFIED IN AN IPD STRUCTURED FIELD WAS UNSUCCESSFUL IN DECOMPRESSING THE IMAGE DATA.**

Explanation

The Compression Identifier that is specified in the Image Encoding parameter of an Image Picture Data (IPD) structured field cannot be successfully used to extract the image data. When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The image data was not encoded according to the compression or recording algorithm specified in the Image Encoding parameter.
2. The image data cannot be decoded successfully by using the size values specified in the Image Size

parameter. This condition applies to compression or recording algorithms that do not permit the image size to be encoded in the image data.

3. The image data was not in complete accordance with the compression algorithm specified in the Image Encoding parameter.
4. The image data is encoded by using the algorithm that is specified in the Image Encoding parameter, but uses a function of the algorithm that is unsupported by the receiver.

The IPD structured field is contained in an image object. The image object might be contained in a MO:DCA document, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the image object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the image object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the image object, contact your system programmer.

APS497I

DATA IN A FONT RESOURCE IS NOT VALID: THE DOUBLE-BYTE FONT SPECIFIED MICR PRINTING IN SOME, BUT NOT ALL, FONT SECTIONS.

Explanation

MICR printing was specified for one section of a double-byte font, but not all sections of that font. If the intended-use flags for one section of a double-byte font specify MICR printing, MICR printing must be specified for all sections of that font.

System action

PSF stops processing and printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the MICR font was supplied by IBM, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center. If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

APS498I

ORDERED DATA WAS SPECIFIED FOR THE PAGE, BUT UNORDERED DATA WAS RECEIVED.

Explanation

PSF indicated that the data on the page was ordered, but the data received by the printer was not ordered. Ordered data is defined to PSF by specifying PRMODE=LINE on the OUTPUT statement JCL when

you submit the job. This error can occur only on printers that support ordered data. For more information, see the documentation provided with the printer. This error occurs if ordered data was indicated to PSF and a structured field other than IDM or IMM was included with the line-data records on a page.

System action

The APS858I message that follows this message defines the system action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Notify your system programmer.

System programmer response

If the error involves the separator page or the message data set, this might be a PSF or printer logic error.

User response

If you specified PRMODE=LINE on the OUTPUT statement JCL when you submitted the job, resubmit the job without specifying PRMODE=LINE, or remove all structured fields other than IDM and IMM from the line-data records and resubmit it. If you did not specify PRMODE=LINE, or if you do not have structured fields included with your line-data records, the error might be a PSF or printer logic error; consult your system programmer.

APS499I	DATA IN AN INPUT RECORD IS NOT VALID: THE ORIENTATION FIELD IN AN INCLUDE PAGE OVERLAY COMMAND CONTAINS AN INCORRECT ID VALUE.
----------------	---

Explanation

The OvlyOrent field in the Include Page Overlay (IPO) command has an incorrect value. The IPO structured field is contained in a MO:DCA document.

APS500 to APS599

APS500I	THE <i>library resource type</i> SYSTEM LIBRARY WAS NOT SPECIFIED.
----------------	---

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the code page with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields, contact your system programmer.

Explanation

The ddname on the DD statement in the PSF startup procedure did not specify a library type for the resources specified in the current print request.

Library resource type can be:

FONT
 FONTPATH
 FORMDEF
 OBJECT CONTAINER/OCA
 OBJECT CONTAINER PATH
 OVERLAY
 PAGEDEF
 SECURITY DEFINITIONS
 SECURITY FONT
 SECURITY OVERLAY
 SECURITY SEGMENT/OCA
 SEGMENT/OCA

System action

For the system action taken, see the accompanying messages.

Operator response

Inform your system programmer that this error occurred.

System programmer response

The keyword for referencing a library type is not specified on the PRINTDEV statement—for example, FONTDD=ddname, PSEGDD=ddname. Specify all library types needed for this print request. For information on how to code a PRINTDEV statement, see *PSF for z/OS: Customization*. If the installation procedure for this writer indicates that these messages are expected, no action is necessary.

User response

Inform your system programmer that this error occurred.

APS501I THE DYNAMIC ALLOCATION FUNCTION WAS UNSUCCESSFUL – RETURN CODE xxxx, REASON CODE xxxx.

Explanation

An attempt was made to use an SVC 99 instruction to do the dynamic allocation of the user libraries associated with this data set, but the attempt was unsuccessful.

System action

PSF cannot print the current data set. PSF releases the current data set back to JES and requests that it is held by the system unless PRERROR=QUIT is specified on the OUTPUT statement.

Operator response

No response is necessary.

System programmer response

Use the return code and reason code to determine the cause of the error and an appropriate response. For information about the SVC 99 return and reason codes, see *z/OS MVS Diagnosis: Tools and Service Aids*.

User response

Verify that the data sets specified in the USERLIB keyword of the print job JCL are correctly specified and cataloged on the system. If the data sets are correctly specified, notify your system programmer of this error.

APS502I resource type IN THE SYSTEM LIBRARY CANNOT BE ACCESSED BECAUSE THE library resource type LIBRARY WAS NOT SPECIFIED ON THE PRINTDEV STATEMENT. PLEASE INFORM YOUR SYSTEM PROGRAMMER.

Explanation

The ddname on the DD statement in the procedure to start PSF did not specify a library for the resources specified in the current print request. The error might be caused by one of these:

- A library that is required for the PSF startup procedure is not specified on the PRINTDEV statement.
- The incorrect PSF startup procedure was started.
- The PSF startup procedure was modified to accept an incorrect job class.
- The print request specified an incorrect job class.
- When you use multiple resolution, a FONTDD, PSEGDD, or OVLYDD default was not included on the PRINTDEV statement.
- A FONTDD, PSEGDD, or OVLYDD default was not included on the PRINTDEV statement when you use multiple resolutions.

The *resource type* identifies one of these libraries that contains the error:

CODED FONT RESOURCE
 CODE PAGE RESOURCE
 COLOR MANAGEMENT RESOURCE
 DATA OBJECT FONT RESOURCE
 FONT CHARACTER SET RESOURCE
 FORM DEFINITION RESOURCE
 OBJECT CONTAINER/OCA RESOURCE
 OVERLAY RESOURCE
 PAGE DEFINITION RESOURCE

PAGE SEGMENT/OCA RESOURCE
SECURITY DEFINITIONS RESOURCE

The *library resource type* can be:

FONT
FONTPATH
FORMDEF
OBJECT CONTAINER/OCA
OBJECT CONTAINER PATH
OVERLAY
PAGEDEF
SECURITY DEFINITIONS
SECURITY FONT
SECURITY OVERLAY
SECURITY SEGMENT/OCA
SEGMENT/OCA

System action

For the system action taken, see the accompanying messages.

Operator response

Inform your system programmer that this error occurred.

System programmer response

The library that is indicated in this message must be specified on the PRINTDEV statement in the procedure that is used to start PSF. If the installation procedure for this writer indicates that these messages are expected, no action is necessary. For information on how to code a PRINTDEV statement, see [PSF for z/OS: Customization](#).

User response

Ensure that the resource name is spelled correctly. Also, ensure that the print request was routed to the correct output class. If the resource name and print class are correct, notify your system programmer.

**APS503I THE DYNAMIC CONCATENATION
FUNCTION WAS UNSUCCESSFUL
— RETURN CODE *xxxx*, REASON
CODE *xxxx*.**

Explanation

An attempt was made to use an SVC 99 instruction to do the dynamic concatenation of the user libraries associated with this data set, but the attempt was unsuccessful.

System action

PSF cannot print the current data set. PSF releases the current data set back to JES and requests that it is held by the system unless PRTEROR=QUIT is specified on the OUTPUT statement.

Operator response

No response is necessary.

System programmer response

Use the return code and the reason code to determine the cause of the error and an appropriate response. For information about the SVC 99 return and reason codes. See [z/OS MVS Diagnosis: Tools and Service Aids](#).

User response

Inform your system programmer that this error occurred.

**APS504I YOU ARE NOT AUTHORIZED BY
RACF TO ACCESS USERLIB
userlibname.**

Explanation

The authority that is required in order for you to access the specified user library is not present. Access to USERLIB is denied.

System action

PSF cannot print the current data set. PSF releases the current data set back to JES and requests that it is held by the system unless PRTEROR=QUIT is specified on the OUTPUT statement.

Operator response

Notify the security administrator of this error. For a command to release the data set for printing after the problem is corrected, see the publication that contains JES operator commands for your operating system.

System programmer response

Determine whether the user must be authorized to access the indicated library. If so, use RACF to give the user the appropriate authorization. For more information, see the RACF publications for your operating system.

User response

Ask the security administrator to arrange permission for you to access the indicated library.

APS505I **A VIRTUAL STORAGE REQUEST WAS UNSUCCESSFUL – REQUEST SIZE (*storage request size*), GETMAIN RETURN CODE *return code*. PLEASE NOTIFY YOUR SYSTEM PROGRAMMER.**

Explanation

A GETMAIN macro attempted to obtain virtual storage, but was unsuccessful. After returning from the GETMAIN macros, register 15 contained a nonzero return code. This message indicates the storage size requested and the return code from the system GETMAIN macro.

System action

For the system action taken, see the other messages associated with this error.

Operator response

If the error occurs during PSF initialization, inform your system programmer.

System programmer response

Increase the REGION parameter on the PSF startup procedure, and restart PSF. To interpret the GETMAIN return code, see [z/OS MVS Diagnosis: Tools and Service Aids](#).

User response

If the error occurs when PSF tries to print your print request, resubmit the print request. If the error persists, contact your system programmer.

APS506I **THE LIBRARY DATA SET ORGANIZATION IS NOT VALID. IT MUST BE SPECIFIED AS A PARTITIONED DATA SET.**

Explanation

The data set organization that is specified in a library is not valid because it is not defined as a partitioned data set.

System action

For the system action taken, see the other messages associated with this error.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Specify the organization in the Data Set Organization (DSORG) field of the data control block as partitioned, PO; or partitioned with location-dependent information, POU. For more information about defining a library, see [PSF for z/OS: Customization](#).

User response

Inform your system programmer that this error occurred.

APS507I **THE LIBRARY RECORD FORMAT IS NOT VALID. PLEASE INFORM YOUR SYSTEM PROGRAMMER.**

Explanation

The library has an incorrect record format. In the security definitions library, the record format (RECFM) field of the data control block (DCB) must be set to fixed F, or fixed-block FB. Control characters and track overflow must not be specified. The LRECL must be 80. For the Object container library, the RECFM field of the (DCB) must be set to variable V, or variable-blocked VB, with or without control characters. For all other library data sets, the RECFM must be specified with control characters as variable-unblocked V, or variable-blocked VB. The other messages that are associated with this error identify the library.

System action

See the accompanying messages that explain the error.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Change the format of the library to the appropriate format for this library and restart PSF. For more information about defining a library, see [PSF for z/OS: Customization](#).

User response

Inform your system programmer that this error occurred.

APS508I **THE CONVERSION FOR THE *device* FROM EBCDIC TO UTF-16 FAILED.**

Explanation

PSF encountered an error while converting the *device* from EBCDIC to UTF-16, where *device* is the device

type or device model. PSF uses the device type and device model to match to device-specific CMRs. PSF cannot obtain and download the device-specific CMRs to the printer. The printer might try to find a device-specific CMR, which degrades performance.

System action

PSF continues processing the print file.

Operator response

If this message is accompanied by Unicode conversion failure messages, APS4400I – APS4403I, inform your system programmer that these errors occurred.

System programmer response

Make sure that the z/OS system is properly enabled for Unicode data transforms and that the correct transforms, both to and from, are initialized. See *z/OS Unicode Services User's Guide and Reference* for more information about setting up Unicode Services.

If an IBM licensed program was used to create the structured fields for the print data set with the error, verify that the input to that program was correct. If the input was correct, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If this message is accompanied by Unicode conversion failure messages, APS4400I – APS4403I, inform your system programmer that these errors occurred.

APS509I THE INVOCATION OF CEEPIPI TO INVOKE A RAU FUNCTION FAILED WITH RETURN CODE *return code*.

Explanation

A nonzero return code was received from this invocation of CEEPIPI to start a RAU function as a subroutine. Return codes that are associated with this message are:

- 04** The function code is not valid.
- 08** CEEPIPI was called from a Language Environment conforming HLL.
- 12** The indicated environment was initialized for main routines. No routine was run.
- 16** The token is not valid.

- 20** The index points to an entry that is not valid or is empty.
- 24** The index that is passed is outside the range of the table.
- 28** This value indicates that the enclave was stopped while the process was retained. This can occur if a STOP statement is issued or if an unhandled condition exists. The *sub_ret_code*, *sub_reason_code*, and *sub_feedback_code* indicate this action.

For more information about this invocation of CEEPIPI and its return codes, see *z/OS Language Environment Programming Guide*.

System action

If the error occurred on a system library, PSF processing stops abnormally with a system completion code 024 and abend reason code 094F. If the error occurs on a user library, PSF continues processing.

Operator response

Inform your system programmer that this error occurred.

System programmer response

If the problem cannot be diagnosed from the return code, contact the IBM Support Center.

User response

No response is necessary.

APS510I THE INITIALIZATION OF THE RAU FAILED WITH RETURN CODE *return code*.

Explanation

The Resource Access Utility failed to initialize. The return codes that are associated with this message are:

- 10** The storage allocation failed.
- 90** The handle parameter is null.

System action

If the error occurred on a system library, PSF processing stops abnormally with a system completion code 024 and abend reason code 094D. If the error occurs on a user library, PSF continues processing.

Operator response

Inform your system programmer that this error occurred.

System programmer response

If the problem cannot be diagnosed from the return code, contact the IBM Support Center.

User response

No response necessary.

APS511I **THE RAU FAILED TO ADD PATH NAME *path name* TO THE PATH NAME SEARCH ORDER – RETURN CODE = *return code*.**

Explanation

The Resource Access Utility (RAU) failed to add the specified path name to the PSF path name search order. The return codes that are associated with this message are:

- 5** Resource access table (RAT) reached end-of-file (EOF).
- 10** The storage allocation failed.
- 15** Entry in the RAT is not valid.
- 20** The specified path name does not have a RAT.
- 25** The RAT is empty.
- 30** The RAU handle parameter is not valid.
- 111** Permission is denied to access the file or directory.
- 200** The RAT is not in a valid format.

System action

If the error occurred on a system library, PSF processing stops abnormally with a system completion code 024 and abend reason code 0950. If the error occurs on a user library, PSF continues processing.

Operator response

Inform your system programmer that this error occurred.

System programmer response

If the problem cannot be diagnosed from the return code, contact the IBM Support Center.

User response

If this error occurs for a USERPATH library and you get return code of 20, then you have an incorrect path name, the path name is misspelled, or the path name specified does not have a RAT. If you get return code of 200, the RAT might be sent in text format instead of binary.

APS512I ***resource type* WITH RESOURCE NAME *resource name* WAS NOT FOUND.**

Explanation

A request to the Resource Access Utility to find the specified resource was unsuccessful or the BPX1ACC (z/OS UNIX System Services Access Function) failed to access the resource file. The resource type is COLOR MANAGEMENT RESOURCE, DATA OBJECT FONT RESOURCE, or OBJECT CONTAINER/OCA RESOURCE.

System action

If the error occurs during initialization, PSF ends. PSF issues other messages that identify the processing environment in which the error was found. More system action messages are also issued.

If the error occurs during processing, see the system action messages to determine whether PSF stops processing the page (MSGAPS100I), or whether PSF stops printing the data set (MSGAPS101I).

Operator response

Inform your system programmer that this error occurred.

System programmer response

Verify that the resource with the name identified exists in a FONTPATH or USERPATH library and that PSF has permission to access the file.

User response

You might have sent your job to the wrong printer, or you might have sent it to the right printer but used the wrong resource name. You might not have set the permissions correctly on the file name, so PSF cannot access the file. If the resource must exist with the name identified in the message, contact your system programmer.

APS513I **resource type WITH PATH NAME path name AND RESOURCE NAME resource name COULD NOT BE OPENED. THE OPEN REQUEST FAILED WITH RETURN CODE return code AND REASON CODE reason code.**

Explanation

A BPX1OPN request was issued to open the identified file. BPX1OPN returned the return code and reason code in the message. The resource type is COLOR MANAGEMENT RESOURCE, CODE PAGE RESOURCE, DATA OBJECT FONT RESOURCE, or OBJECT CONTAINER/OCA RESOURCE.

Common return codes that are associated with this message are:

- 111** Permission is denied to access the file or directory.
- 129** The file or directory you are trying to access does not exist.
- 133** The UNIX file system is out of storage.

System action

If the error occurs during initialization, PSF ends. PSF issues other messages that identify the processing environment in which the error was found. More System Action messages are also issued.

If the error occurs during processing, see the System Action messages to determine whether PSF stops processing the page (MSGAPS100I), or whether PSF stops printing the data set (MSGAPS101I).

Operator response

Inform your system programmer that this error occurred.

System programmer response

Determine the appropriate response by interpreting the return code and the reason code. Verify that PSF has permission to access the file and that the system Conversion Facility is set up. To interpret the return code and the reason code, see *z/OS UNIX System Services Programming: Assembler Callable Services Reference*.

User response

You might have sent your job to the wrong printer, you might have sent it to the right printer but used the wrong resource name, or you might not have set the

permissions correctly so PSF cannot access the file. If the resource exists with the name identified in the message, contact your system programmer.

APS514I **THE GETDSAB SYSTEM MACRO HAS NOT BEEN INSTALLED ON THE SYSTEM.**

Explanation

PSF tried to use the GETDSAB macro to process the system path libraries, but the GETDSAB macro is not installed on the system.

System action

PSF processing stops abnormally with a system completion code 024 and abend reason code 0939.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Verify that the GETDSAB system macro is installed on the system where the printer was started.

User response

Inform your system programmer that this error occurred.

APS515I **INSUFFICIENT VIRTUAL STORAGE WAS AVAILABLE FOR BUFFERING OF INLINE RESOURCES.**

Explanation

The GETMAIN MACRO attempted to obtain space for the inline resource buffers, but was unsuccessful; or an inline resource approached 1 GB (a gigabyte is 1,073,741,824 bytes).

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response

Inform your system programmer that this error occurred.

System programmer response

The size of the REGION parameter for the print request must be increased. If the print request is processing in

direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

User response

Determine whether unnecessary inline resources might be deleted from the input data stream, or if you have an inline resource that approaches 1 GB (maximum size supported by PSF). If no resources can be deleted or none are near 1 GB, contact your system programmer.

APS516I **MESSAGES WERE LOST BECAUSE NOT ENOUGH VIRTUAL STORAGE WAS AVAILABLE.**

Explanation

PSF cannot obtain enough virtual storage for its control blocks or buffers. The REGION parameter on the startup procedure might be too small.

System action

If no other unrecoverable errors are encountered, the print request is processed. The message that was being processed when the error occurred is lost.

Operator response

Inform your system programmer that this error occurred.

System programmer response

If necessary, the size of the REGION parameter for the print request must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

User response

Correct the print request in response to the accompanying messages. If the error persists, notify your system programmer.

APS517I **MESSAGES WERE LOST BECAUSE THE BUFFER LIMIT WAS EXCEEDED.**

Explanation

The maximum number of buffers allocated for writing messages was exceeded. The message that was being processed when the error occurred is lost.

System action

Processing of the data set continues.

Operator response

Inform your system programmer that this error occurred.

System programmer response

No response is necessary.

User response

Correct the print request in response to the other messages associated with this error. Resubmit the print request.

APS518I **RECOVERY IS {IN PROGRESS | SUCCESSFUL | UNSUCCESSFUL} FOR A LIBRARY EXTENT ERROR.**

Explanation

A recovery from an extent error that occurred for a library either is in progress, or is successfully or unsuccessfully completed. PSF recovers from this error by closing and then opening the library to obtain the new extents. This error occurs when the library is updated. The update causes more extents to be added after PSF opened the library for processing.

System action

If the recovery was unsuccessful, PSF produces an abend. If the recovery was successful, processing continues. No response is necessary.

Operator response

If the recovery was unsuccessful, notify your system programmer.

System programmer response

If recovery was unsuccessful, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center. See the other error messages for the PSF abend reason codes and system completion codes associated with this error.

User response

If the recovery was unsuccessful, notify your system programmer.

APS519I **THE PRINTER DID NOT PROVIDE A DEVICE TYPE AND MODEL IN THE XOH OPC RESPONSE. THE DEVICE**

TYPE AND MODEL ARE REQUIRED FOR CMR SUPPORT.

Explanation

The printer did not provide a device type and model in the XOH Obtain Printer Characteristics (OPC) response. PSF uses the device type and device model to match to device-specific CMRs. PSF cannot obtain and download the device-specific CMRs to the printer. The printer might try to find a device-specific CMR, which degrades performance.

System action

PSF continues processing the print file.

Operator response

Inform your system programmer that this error occurred.

System programmer response

See your printer documentation for information about setting the device type and model.

User response

Inform your system programmer that this error occurred.

APS520I **SYSTEM FUNCTION *system function* WAS UNSUCCESSFUL – RETURN CODE *return code*. PLEASE INFORM YOUR SYSTEM PROGRAMMER.**

Explanation

The system function initiated by the *system function* macro was unsuccessful. After returning from the *system function* macro, register 15 contained a nonzero return code. The *system function* can be BPX1RED.

Common return codes that are associated with this message are:

111 Permission is denied to access the file or directory.

129 The file or directory you are trying to access does not exist.

133 The UNIX file system is out of storage.

System action

For the system action taken, see the other messages associated with this error.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Correct the problem in response to the system return code identified in this message. The return code is from the system function that was used. See *z/OS UNIX System Services Programming: Assembler Callable Services Reference* to interpret the return code.

User response

Inform your system programmer that this error occurred.

APS522I **A READ ERROR WAS DETECTED. SYNADAF TEXT = *text name*. PLEASE INFORM YOUR SYSTEM PROGRAMMER.**

Explanation

A physical error occurred on a READ macro request. The text of this message is in the format produced by the SYNADAF macro.

System action

For the system action taken, see the other messages associated with this error.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Determine the cause of the error by using the SYNADAF text provided in this message. For information about the format of the SYNADAF text, see *z/OS DFSMS Macro Instructions for Data Sets*.

User response

Inform your system programmer that this error occurred.

APS523I **AN OBJECT CONTAINS ADDITIONAL RECORDS IN BLOCK *block*, RECORD *record*, THAT WERE**

NOT PROCESSED. THE PRINTED OUTPUT MAY BE ACCEPTABLE.

Explanation

The last record of the resource is processed; however, the objects contained more records, which were not processed.

The *block* identified in this message contains the record identified in this message. The *record* contains the additional data. If the resource is stored in variable-unblocked format, the record number is always 1.

System action

Processing of the data set continues. The additional data in the identified record is not processed.

Operator response

Inform your system programmer that this error occurred.

System programmer response

If an IBM licensed program was used to create the structured fields for the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the resource, contact your system programmer.

APS524I THE RAU TERMINATION FUNCTION FAILED FOR THE USERPATH LIBRARY. RETURN CODE = *return code*.

Explanation

PSF tried to end the RAU session for a print data set, but the end call failed with *return code*. PSF had a successful dialog with the RAU to locate the required TrueType and OpenType fonts, data object resources, or color management resources for this document. However, when PSF tried to end the RAU session, an error occurred. This might be caused by one of these:

- An error during an `fclose` of an open file. The valid return codes are:
 - EAGAIN (112)—File currently in use.
 - EBADF (113)—File does not identify a valid opened file.
 - EINTR (120)—Service was interrupted by a signal while processing the `fclose` request.
- A PSF or RAU logic error. The valid return code is:
 - 50—The RAU handle is not valid.

System action

PSF continues processing.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Ensure that the z/OS UNIX System Services path specified in `USERPATH` were stable during PSF processing of this print data set. If the problem cannot be diagnosed from the return code, contact the IBM Support Center.

User response

Inspect the resulting print data set carefully for correctness, completeness, and other PSF messages. This condition is associated with z/OS UNIX System Services files (`USERPATH` parameter on the `OUTPUT JCL` statement) private to your print data set. If results are unsatisfactory, inform your system programmer.

APS525I THE RAU FAILED TO GET TRUETYPE COLLECTION INFORMATION. RETURN CODE = *return code*.

Explanation

The Resource Access Utility (RAU) cannot acquire TrueType Collection information. The return codes that are associated with this message are:

10

The storage allocation failed.

30

The RAU handle parameter is not valid.

System action

The AFP Download Plus FSA stops with system completion code 024 and abend reason code 09AE.

Operator response

Notify your system programmer.

System programmer response

Do one of these, depending on the return code:

- When *return code* is 10, increase the REGION parameter in the AFP Download Plus startup procedure.
- When *return code* is 30, this message indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance.

User response

No response is necessary.

APS527I THE LIBRARY MEMBER CANNOT BE PROCESSED BECAUSE IT WAS UPDATED DURING THIS ATTEMPT TO ACCESS IT. RESUBMIT THE JOB.

Explanation

An attempt was made to obtain the remainder of a library member contained in an extent that was added after PSF was started. PSF determined that the library member was updated after it was processed as a part of the current print request. Library members must not be updated while PSF is actively processing print requests, as this can cause errors.

System action

Processing of the library member ends. For further system action, see the other messages associated with this error.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Ensure that library members are not updated while PSF is processing.

User response

Resubmit the print request.

APS532I *resource type* WITH MEMBER NAME (*library member*) WAS NOT FOUND — RETURN CODE *return code*, REASON CODE *reason code*

RETURNED FROM SYSTEM (*system function*) FUNCTION.

Explanation

A BLDL request (SVC 18) was issued to position to the requested library member. BLDL returned the return code and reason code that display in the message. *Resource type* can be:

CODED FONT RESOURCE
CODE PAGE RESOURCE
FONT CHARACTER SET RESOURCE
FORM DEFINITION RESOURCE
PAGE DEFINITION RESOURCE
PAGE SEGMENT/OCA RESOURCE
OVERLAY RESOURCE
OBJECT CONTAINER/OCA RESOURCE
SECURITY DEFINITIONS RESOURCE

System action

If the error occurs during initialization, PSF ends. PSF issues other messages that identify the processing environment in which the error was found. More System Action messages are also issued.

If the error occurs during processing, see the System Action messages to determine whether PSF stops processing the page (MSGAPS100I), or whether PSF stops printing the data set (MSGAPS101I).

Operator response

Inform your system programmer that this error occurred.

System programmer response

Determine the appropriate response by interpreting the return code and the reason code. To interpret the return code and the reason code, see [z/OS DFSMS Using Data Sets](#).

User response

You might have sent your job to the wrong printer, or you might have sent it to the right printer but used the wrong resource-naming convention. For example, you might have used the coded font prefix X0 when you submitted a print request to the 3800 Model 3, 6, or 8. If you specified your resource inline, you might have placed the resource group definition out of sequence in the data stream.

If the member must exist with the name identified in the message, contact your system programmer.

APS534I *path* PATH COULD NOT BE OPENED. RETURN CODE (*return*

code). REASON CODE (reason code). PATHNAME=path name.

Explanation

The BPX10PD system function macro failed to open the specified path. After returning from the BPX10PD macro, register 15 contained a nonzero return code.

Common return codes that are associated with this message are:

111

Permission is denied to access the file or directory.

129

The file or directory you are trying to access does not exist.

133

The UNIX file system is out of storage.

System action

If the error occurred on a system library, PSF processing stops abnormally with an abend 024 and abend reason code 09AF. If the error occurs on a user library, PSF continues processing.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Determine the appropriate response by interpreting the return code and the reason code. Verify that PSF has permission to access the path. To interpret the return code and the reason code, see *z/OS UNIX System Services Programming: Assembler Callable Services Reference*.

User response

Inform your system programmer that this error occurred.

APS535I AN INCORRECT MEMBER NAME WAS SPECIFIED FOR A LIBRARY MEMBER.

Explanation

A structured field contained a member name for an overlay or a page segment that either is null or is not a valid PSF member name. An overlay name might be specified in one of these places:

- A Map Medium Overlay (MMO) structured field in a form definition

- A Map Page Overlay (MPO) structured field in a page definition or in the MO:DCA data set

A page segment name can be specified in one of these places:

- Map Page Segment (MPS) structured field in a page definition
- Overlay
- MO:DCA data

System action

See accompanying messages for the action done.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APS536I DATA OBJECT FONT WITH RESOURCE NAME *fontname* IS SPECIFIED TO BE IN THE RESOURCE GROUP FOR THE PRINT FILE, BUT THE FONT WAS NOT FOUND.

Explanation

A Data Object Font Descriptor triplet (X'8B') on the Map Data Resource (MDR) structured field specifies that the font must be in the resource group for the print file. However, the font was not found inline.

System action

If the error occurs during initialization, PSF ends. PSF issues other messages that identify the processing environment in which the error was found. More system action messages are also issued. If the error occurs during processing, see the System Action messages to determine whether PSF stops processing the page (MSGAPS100I) or stops printing the data set (MSGAPS101I).

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

If you are processing complex text with glyph runs, make sure that the data object font resource is in the resource group for the print file. Otherwise, determine whether you want the triplet flag set to specify that the font must be in the print file resource group.

APS537I **SYSTEM FUNCTION *system function* WAS UNSUCCESSFUL. PLEASE INFORM YOUR SYSTEM PROGRAMMER.**

Explanation

An OPEN or CLOSE macro was unsuccessful. One of these conditions caused this error:

- An OPEN macro request, which results in an SVC 19, was issued to open a library. After returning from the OPEN macro, PSF discovered that the data control block (DCB) was not opened.
- A CLOSE macro request, which results in an SVC 20, was issued to close a library. After returning from the CLOSE macro, PSF discovered that the DCB was not closed.

System action

If either the OPEN or CLOSE macro is unsuccessful, PSF ends.

Operator response

Inform your system programmer that this error occurred.

System programmer response

See the other messages for the PSF abend reason codes and system completion codes associated with this error.

User response

Inform your system programmer that this error occurred.

APS538I **AN EXTENT ERROR WAS DETECTED: MEMBER (*member*) IS NOT WITHIN KNOWN EXTENTS: EXTENT (*extent*), BIN (*bin*), CYLINDER (*cylinder*), HEAD (*head*), RECORD (*record name*), ACCESS-METHOD (*access method*).**

Explanation

An extent error occurred while PSF was preparing to process a member or read a member from a library. When this occurs, the library is closed and then reopened to obtain any extents that were added after PSF was started. Another attempt is then made to process the member.

The extent error was caused by one of these:

- An incorrect seek address caused the wrong block of data to be read from the direct access storage device (DASD).
- The relative track address was converted to a seek address that is not within the extents of this library as defined in the data extent block (DEB).
- The read address was not within the extents of this library, as defined in the DEB, when PSF attempted to read a block of data from a DASD.

The extent, bin, cylinder, head, and record fields that are identified in this message are given in hexadecimal and indicate either the seek or the read DASD address that is not valid.

System action

For the system action taken, see the other messages associated with this error.

Operator response

To determine the appropriate response, see the other messages associated with this error.

System programmer response

To determine the appropriate response, see the other messages associated with this error.

User response

Inform your system programmer that this error occurred.

APS539I AN EXTENT ERROR WAS DETECTED: MEMBER (*member*) IS NOT WITHIN KNOWN EXTENTS.

Explanation

An extent error occurred while PSF was reading a member from a library. The error was reported to PSF by the BPAM access method. A CHECK macro was posted with a X'42', and an end-of-file was indicated.

System action

The library is closed and then reopened to obtain any extents added after PSF was started. Another attempt is then made to process the member.

Operator response

Inform your system programmer that this error occurred.

System programmer response

See the other messages associated with this response. To obtain a memory dump at the time of failure, specify Dump: Message ID APS539I in the Printer Inventory or DUMP=(,APS539I,1) in the PRINTDEV statement.

User response

Inform your system programmer that this error occurred.

APS540I SAVED AUXILIARY FILE WAS SUCCESSFULLY CREATED: *filename*.

Explanation

AFP Download Plus successfully created and saved an auxiliary file because the parameter for saving auxiliary files was set to YES in the AFPPARMS control statement or the Printer Inventory. This message is issued for each auxiliary file that is saved for an active separator page and a message data set.

System action

AFP Download Plus saved the auxiliary file.

Operator response

Inform your system programmer that this message displayed on the operator's console.

System programmer response

You can run the MO:DCA validation tool of your choice on the saved auxiliary file to determine whether the file is MO:DCA IS/3 compliant and prints correctly. See *PSF for z/OS: AFP Download Plus* for more information about checking that files are MO:DCA IS/3 compliant.

User response

No response necessary.

APS547I SYSTEM FUNCTION *system function* TERMINATED WITH AN ABEND – RETURN CODE *return code*, SYSTEM COMPLETION CODE *system completion code*. PLEASE INFORM YOUR SYSTEM PROGRAMMER.

Explanation

An error was detected when either the OPEN or the CLOSE macro was processing a data control block (DCB). This caused the DCB abend exit routine to receive control. The return code and the system completion code are issued by the data management problem-determination routines.

This message identified either the OPEN or CLOSE macro request as the system function that was unsuccessful.

System action

PSF processing continues. If the abend cannot be ignored, the system returns to the problem-determination routine to continue the abend.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Use the return code and the system completion code to determine the cause of the error and an appropriate response. To interpret the return code and system completion code, see *z/OS MVS System Codes*.

User response

Inform your system programmer that this error occurred.

APS548I WHEN THE ERROR REPORTED ABOVE OCCURRED, THE *item* BEING PROCESSED WAS *resource type* | *library type* | *NOT AVAILABLE***.**

Explanation

This message gives information about the processing environment in which the error occurred. *Item* can be:

CONCATENATION NUMBER
DDNAME
DEFINITION TYPE
DSNAME
FILE NAME
LIBRARY TYPE
MEMBER NAME
MEMBER/TOKEN NAME
PATH NAME
RESOURCE TYPE
TOKEN NAME

Resource type is the resource library that is processed when the error occurred. It can be:

CODED FONT RESOURCE
CODE PAGE RESOURCE
COLOR MANAGEMENT RESOURCE
DATA OBJECT FONT RESOURCE.
file name
FONT CHARACTER SET RESOURCE
FORM DEFINITION RESOURCE
member name
OBJECT CONTAINER/OCA RESOURCE
OVERLAY RESOURCE
PAGE DEFINITION RESOURCE
PAGE SEGMENT/OCA RESOURCE
SECURITY DEFINITIONS RESOURCE
NOT VALID

Library type is the type of resource library that is being processed when the error occurred. It can be:

concatenation number
ddname
dsname
FONT
FONTPATH
FORMDEF
INLINE CMR
INLINE DATA OBJECT FONT
INLINE FONT
INLINE FORMDEF
INLINE OBJECT CONTAINER
INLINE OVERLAY
INLINE PAGEDEF
INLINE SEGMENT/OCA
OBJECT CONTAINER/OCA
OBJECT CONTAINER PATH
OVERLAY
PAGEDEF
SECURITY DEFINITIONS
SECURITY FONT
SECURITY OVERLAY
SECURITY SEGMENT/OCA

SEGMENT/OCA
SYSTEM LIBRARY
USERLIB
USERPATH
NOT VALID

NOT AVAILABLE means that one of these is not available to this function: the ddname, the dsname, the member name, the definition type, the resource type, the library resource type, or the token name. ***ddname for a USERLIB*** is a system-generated name that consists of the characters 'SYS' followed by 5 digits.

System action

For the system action taken, see the other messages associated with this error.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot be initialized or cannot print a separator page or error messages. Inform your system programmer that this error occurred.

System programmer response

To determine an appropriate response, see the specific error conditions described in the accompanying messages.

User response

To determine an appropriate response, see the specific error conditions described in the accompanying messages.

APS549I

**AN INLINE RESOURCE GROUP
WAS FOUND OUT OF SEQUENCE
IN THIS DATA SET AND IGNORED.
IF THE RESOURCE NAMED IN THE
PRECEDING MESSAGE WAS IN
THIS RESOURCE GROUP, FIX THE
DATA STREAM AND RESUBMIT
THE JOB.**

Explanation

This message is issued to alert you that an out of sequence inline resource group was encountered in the data stream and ignored. An inline resource group is only supported at the beginning of a data set before any pages. This message is issued because an APS512I, APS532I, or APS536I message was previously issued that indicates that a resource was not found. This resource might be located in this ignored inline resource group.

System action

See the other messages that are associated with this error.

Operator response

Inform your system programmer that this error occurred.

System programmer response

To diagnose the problem, see the User Response or use message APS512I or APS532I, depending on which one preceded this message.

User response

If you expected the resource to be found inline, confirm whether it is located in the ignored inline resource group. If it is, fix your data stream by consolidating all inline resources into a single inline resource group. Ensure that this single inline resource group is at the beginning of the data set, and then resubmit the print request.

If you do not expect to find this resource inline, see the explanation in the APS512I or APS532I message for information about how to proceed.

APS550I THE RESOURCE DELETION RATIO PARAMETER IN THE AFPPARMS CONTROL STATEMENT IS IGNORED DUE TO CONFLICTS WITH THE RESOURCE DELETION CALL SETTINGS IN INSTALLATION EXIT 7—JOB= *jobname* STEP= *stepname* ID= *jobid*.

Explanation

An installation Exit 7 requested a resource-deletion call for coded fonts, medium overlays, page segment/OCA, or object containers. The request was set by a call to Exit 7 after the Exit 7 INIT call. Either the Resource deletion ratio parameter in the Printer Inventory or the AFPPARMS control statement resource-deletion-ratio parameter is greater than zero. A value greater than zero conflicts with the PSF installation Exit 7 settings. You cannot specify both algorithms to control resource deletion.

Exit 7 requests a resource-deletion call for resources by setting flags on XTP7RDEL in the XTP7 parameter area (DSECT).

System action

PSF ignores the resource deletion ratio setting during data set end processing but does all other actions that are requested in the installation Exit 7.

Operator response

Inform your system programmer that this error occurred.

System programmer response

If you do not want to see this message, either correct the installation Exit 7 to remove the requests for resource-deletion calls or set the Resource deletion ratio parameter in the Printer Inventory or the AFPPARMS control statement resource-deletion-ratio parameter to zero.

For more information about Exit 7 or the resource deletion ratio, see [*PSF for z/OS: Customization*](#).

User response

No response is necessary.

APS551I THE RESOURCE EXIT REQUESTED THE SELECTIVE DELETION OF {PAGE SEGMENT | OVERLAY}. SELECTIVE DELETION OF THIS RESOURCE TYPE IS NOT SUPPORTED BY THE ATTACHED PRINTER.

Explanation

The resource exit requested a selective deletion for a printer that does not support selective deletion of this resource type.

System action

All resources of this type are deleted from the printer.

Operator response

Contact your system programmer.

System programmer response

Modify the exit code so that selective deletion of resources is not requested for a printer that does not support selective deletion of this resource type.

User response

No response is necessary.

APS553I A RASTER OVERLAY (*raster overlay*) WAS SPECIFIED BUT NO ACCUMULATOR FEATURE EXISTS. THE OVERLAY WAS PROCESSED AS A CODED OVERLAY.

Explanation

The error occurred because a request was made to load an overlay as a raster overlay. The 3800 printer has no accumulator feature to load the raster overlay.

System action

The overlay is processed and loaded into the printer not as a raster overlay but as a coded overlay. Printed output is acceptable.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

If a raster overlay is wanted for this data set, ensure that the data set is routed to an output class for a printer with the accumulator feature. If the data set was being processed in direct-printing mode, ensure that the allocated printer has the accumulator feature.

APS554I **A RASTER OVERLAY *raster overlay* WAS SPECIFIED WHEN ONE ALREADY HAS BEEN LOADED. THE OVERLAY WAS PROCESSED AS A CODED OVERLAY.**

Explanation

This error occurred because a request was made to load an overlay as a raster overlay. A raster overlay already occupies the accumulator.

System action

The overlay is processed and loaded into the printer not as a raster overlay but as coded overlay. Printed output is acceptable.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Ensure that multiple raster overlays are not required by the same data set. If the data set is spooled, ensure that the data set and the PSF startup procedure do not conflict in their raster-overlay requirements.

APS555I

THE RESOURCE EXIT REQUESTED A RELOADING OF {PAGE SEGMENT/OCA OBJECT | OVERLAY} *member name*. RELOADING OF THIS RESOURCE TYPE IS NOT SUPPORTED BY THE ATTACHED PRINTER.

Explanation

The resource exit requested a reloading of a resource. The selective-deletion required operation for this resource type is not supported by the attached printer.

System action

The resource was not reloaded. Processing of the data set continues with the original copy of the resource.

Operator response

Contact your system programmer.

System programmer response

Modify the exit code so that selective deletion of resources is not requested for a printer that does not support selective deletion of this resource type.

User response

No response is necessary.

APS556I

THE REQUESTED CHARACTER ROTATION FOR {CODED FONT | CP/FN PAIR} *member name* IS NOT SUPPORTED BY THE PRINTER.

Explanation

The font and its character rotation were specified in the Map Coded Font (MCF) structured field. The printer does not support the requested character rotation for resident fonts or resident symbol sets. If the CHARS or UCSJCL keywords were used in specifying the font that is used, PSF constructed the MCF structured field.

System action

PSF stops processing the current page, and prints any accumulated data for the current page. PSF attempts to find the end of current page and to resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream that contains the resource. PSF issues other messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error. If an IBM licensed program was used to create the structured fields for the print data set with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. For information on supported character rotations for resident fonts or resident symbol sets, see the publications for your printer. For more information about the MCF structured field, see *Mixed Object Document Content Architecture Reference*.

If you used a program to create the structured fields for the print data set or the resource, verify that a supported character rotation was specified for the resident font or resident symbol set. For information on supported character rotations for resident fonts or resident symbol sets, see the publications for your printer. If the specified character rotation is supported by the printer, contact your system programmer.

APS557I **REGION WAS TOO SMALL FOR PROCESSING {CODED FONT | FONT CHARACTER SET | CODE PAGE | PAGE SEGMENT | OVERLAY | FORMDEF | PAGEDEF | OBJECT CONTAINER } (member name).**

Explanation

The GETMAIN macro attempted to obtain space for the resources identified in this message, but was unsuccessful because of a lack of storage.

System action

PSF stops processing the current page, and prints any accumulated data for the current page. PSF attempts to find the end of the current page and resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or the containing resource. PSF issues other messages that identify the processing environment in which the error occurred.

Operator response

Inform your system programmer that this error occurred.

System programmer response

The size of the REGION parameter for the print request must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

User response

Determine whether any of the resources that are specified can be deleted from the input data stream. If no resources can be deleted, contact your system programmer.

APS560I **A DOUBLE-BYTE FONT WAS SPECIFIED FOR A PRINTER THAT DOES NOT SUPPORT DOUBLE-BYTE FONTS.**

Explanation

A request to use a double-byte font was made to a printer that does not support double-byte fonts.

System action

PSF cannot print the current page. PSF attempts to find the end of the current page and resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or containing resource. PSF issues other messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If double-byte fonts are required, resubmit the print request to a printer that supports double-byte fonts. If double-byte fonts are not required, remove the reference to them from the print data set, resource, or JCL CHARS parameter, and resubmit the print request to the original printer.

APS561I **REGION WAS TOO SMALL FOR PROCESSING {FORMDEF | PAGEDEF | CODED FONT | PAGE SEGMENT/OCA OBJECT | OVERLAY | OBJECT CONTAINER } (*member name*).**

Explanation

The GETMAIN macro attempted to obtain space for the resource identified in this message, but was unsuccessful because of a lack of storage.

System action

PSF stops processing the current page, and prints any accumulated data for the current page. PSF attempts to find the end of the current page and to resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or the containing resource. PSF issues other messages that identify the processing environment in which the error occurred.

Operator response

Inform your system programmer that this error occurred.

System programmer response

The size of the REGION parameter for the print request must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

User response

Determine whether any of the resources that are specified can be deleted from the input data stream. If

no resources can be deleted, contact your system programmer.

APS562I **CODED FONT MEMBER NAME *member name* SPECIFIED IN AN MCF STRUCTURED FIELD COULD NOT BE MAPPED TO CODE PAGE AND FONT CHARACTER SET MEMBER NAMES.**

Explanation

Coded font member names that are specified in a Map Coded Font (MCF) format 2 structured field contain an 8-byte Global Resource ID (GRID) that PSF maps to code page and font character set member names. The GRID specified in the message text was not mapped correctly to a code page, to a font character set, or to both of those objects. The MCF structured field is contained in a MO:DCA document, an overlay, or a page definition.

System action

PSF stops processing the current page, and prints any accumulated data for the current page. PSF attempts to find the end of the current page and to resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or containing resource. PSF issues other messages that identify the processing environment in which the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error. If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. See *Mixed Object Document Content*

Architecture Reference for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APS563I {CODED FONT | CP/FN PAIR | PAGE SEGMENT/OCA OBJECT | OVERLAY | PAGEDEF | FORMDEF | OBJECT CONTAINER} *member name* WAS REPLACED BY {CODED FONT | CP/FN PAIR | PAGE SEGMENT/OCA OBJECT | OVERLAY | PAGEDEF | FORMDEF | OBJECT CONTAINER} *member name* (*optional text*).

Explanation

The resource exit requested substitution of a CODED FONT (a code page/character set pair, abbreviated CP/FN PAIR), a PAGE SEGMENT/OCA OBJECT, an OVERLAY, a PAGEDEF, a FORMDEF, or an OBJECT CONTAINER. The member name of the resource that is originally specified, and the member name of the resource to be substituted, are provided. Optional message text might also be provided.

System action

PSF replaces the substitution resource for all references of the resource requested by the user.

Operator response

No response is necessary.

System programmer response

You might use the *optional text* field of the message to provide further explanation for the user as to why this resource was replaced. For more information about how to provide optional message text, see [PSF for z/OS: Customization](#).

User response

If the printed output is not acceptable, contact your system programmer.

APS564I {CODE PAGE | FONT CHARACTER SET} *member name* SPECIFIED IN A CFI OR AN MCF STRUCTURED FIELD IS NOT MAPPED TO A RESIDENT SYMBOL SET IN THE PSF RESIDENT FONT TABLE (APSRFTBL).

Explanation

PSF cannot find the code page or font character set member name in the PSF Resident Font Table (APSRFTBL). The code page and font character set were specified in a Coded Font Index (CFI) or a Map Coded Font (MCF) structured field. The CFI structured field is in a coded font. The MCF structured field might be in the MO:DCA data set, an overlay, or a page definition.

System action

PSF stops processing the current page, and prints any accumulated data for the current page. PSF attempts to find the end of the current page and to resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or the containing resource. PSF issues other messages that identify the processing environment in which the error occurred.

Operator response

No response is necessary.

System programmer response

Verify that the combination of requested font character set and code page member names is a valid symbol set that is resident in the printer. See your printer publications and to [PSF for z/OS: Customization](#). If the symbol set is valid, add the missing code page or font character set entry to the APSRFTBL. For information on how to modify APSRFTBL, see [PSF for z/OS: Customization](#).

User response

Verify that the font character set name and the code page name are specified correctly. If the names contain an error, correct the error and resubmit the print request. If the names are correct, contact your system programmer.

APS565I AN ATTEMPT WAS MADE TO ACTIVATE A PRINTER RESIDENT FONT USING GLOBAL RESOURCE ID *grid*. THE ATTEMPT WAS NOT SUCCESSFUL.

Explanation

The Global Resource Identifier (GRID) is used to identify a printer-resident font. The GRID is composed of four 2-byte numeric identifiers:

- Graphic Character Set Global Identifier (GCSGID)

- Code Page Global Identifier (CPGID)
- Font Global Identifier (FGID)
- Font Width (FW)

PSF attempts to activate a printer-resident font through the GRID because:

- The font character set and code page names cannot be mapped from the GRID by use of either the system mapping tables or the APSRNTGM or APSRGTNM user-modifiable tables.

The GRID provided in the message text did not identify a printer-resident font; therefore, it cannot be activated.

System action

If the error occurs during initialization, PSF ends. PSF issues other messages that identify the processing environment in which the error was found. More System Action messages are also issued.

If the error occurs during processing, see the System Action messages to determine whether PSF stops processing the page (MSGAPS100I) or stops printing the data set (MSGAPS101I).

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you wanted to use a printer-resident font, ensure that the GRID identified in the message is specified correctly. See the documentation for your printer. If the GRID contains an error, correct the error and resubmit the print request.

If you wanted to use a code page and font character set pair from the library, ensure that the APSRNTGM and APSRGTNM tables correctly map the GRID to a pair of code page and font character set names that exist in the system font library. If the tables do not correctly map the GRID to existing library members, follow the procedures to modify the tables and relink them with PSF, and resubmit the print request.

name USING FONT CHARACTER SET member name, CODE PAGE member name, VERTICAL FONT SIZE size, HORIZONTAL FONT SIZE size, AND HORIZONTAL SCALE FACTOR scale factor. THE ATTEMPT WAS NOT SUCCESSFUL.

Explanation

PSF was attempting to activate a coded font but was not successful. To activate the coded font, the code page and the font character set must already be loaded in the printer or activated. The message contains the member names of the coded font, the code page, and the character set that were involved in this error. Also included in the message are the vertical and horizontal font sizes and the horizontal scale factor.

Some possible causes of this error are:

- A coded font with the same HAID was already active. This would be a PSF logic error.
- The printer found something wrong with the values specified in the Active Resource command. This would be a PSF logic error.
- The font character set or the code page was not activated or loaded in the printer before the coded font was activated. This would be a PSF logic error.
- The character set and the code page are not compatible. A user can create a coded font resource that specifies a font character set and a code page that cannot be used together.

System action

PSF was unable to activate all the resources in the printer that were required for printing this page. As a result, PSF does not print the page that contains the error.

PSF issues a message that identifies the page that contains the resource that had the error. PSF issues other messages that identify the processing environment in which the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer that this error occurred.

System programmer response

If an IBM licensed program was used to create the structured fields for the resource with the error, verify

APS566I

**AN ATTEMPT WAS MADE TO
ACTIVATE A CODED FONT *member***

that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

Ensure that the code page and the font character set for the coded font that contains the error are compatible. For information about how to select compatible code pages and font character sets, see *Font Object Content Architecture Reference*. If the code page and the font character set are compatible, this might be a PSF logic error.

APS568I	A BEGIN STRUCTURED FIELD FOR {CODE PAGE PAGE SEGMENT FONT CHARACTER SET UNKNOWN OVERLAY } (<i>member name</i>) WAS NOT MARKED BY THE APSRMARK UTILITY OR WAS MARKED INCORRECTLY FOR USE WITH REMOTE PRINT MANAGER OR DISTRIBUTED PRINT FUNCTION. LINE UTILIZATION MAY BE EXCESSIVE.
----------------	--

Explanation

This failure is caused by an unsuccessful attempt to interrogate the Begin structured field for the identified resource. The Begin structured field either contains an error or is not marked by the APSRMARK utility for use with the distributed print function (DPF).

System action

Because PSF is unable to obtain information to determine the presence of this resource in the printer, processing is performed as if the resource in question were a private resource. The resource is sent to the printer rather than any remote resource that might be equivalent. PSF continues processing data, and the printed output is acceptable; however, printer performance is degraded.

PSF issues a message that identifies the position of the structured field in the input data stream or in the containing resource. PSF issues other messages that identify the processing environment in which the error was found.

Operator response

Inform your system programmer that this error occurred. For information about how to use

APSRMARK to mark a resource, see *PSF for z/OS: Customization*.

System programmer response

If DPF was supposed to process the resource, ensure that the resource was marked by the APSRMARK utility. If it was, the error might be a PSF logic error. If DPF was not to process the resource, no response is necessary. For information about how to mark a resource by use of APSRMARK, see *PSF for z/OS: Customization*.

User response

If you wanted DPF to process the resource, contact your system programmer. If you did not want DPF to process the resource, no response is necessary.

APS569I	AN ATTEMPT WAS MADE TO PRINT WITH DOUBLE BYTE FONT CHARACTER SET EXTENSION <i>childfont</i>, BUT THE ASSOCIATED PRINTER RESIDENT FONT COULD NOT BE ACTIVATED.
----------------	--

Explanation

The double-byte font that you selected has some characters defined in the double-byte character extension in the message as *childfont*. These are intended to be additions to a printer-resident double-byte font. However, the printer does not have the required double-byte font as a resident font. Therefore, PSF cannot activate (build) the combined font.

System action

PSF cannot print the current page. PSF attempts to locate the end of the current page and resume printing on the next page. If the end of the current page cannot be located, PSF stops printing the data set. PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If the double-byte font is required, resubmit the print request to a printer that has the required resident double-byte font. If the double-byte font is not required, remove the reference to it from the print data set, resource, or JCL CHARS parameter, and resubmit the print request to the original printer.

APS570I **A BLDL FAILURE OCCURRED DURING RESOURCE MANAGER INITIALIZATION, BLDL RETURN CODE *return code*, BLDL REASON CODE *reason code*.**

Explanation

While PSF was locating the APSRNTGM and APSRGTNM tables, the BLDL macro failed.

System action

Processing continues without the APSRNTGM and APSRGTNM tables.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Evaluate the BLDL macro return and reason codes to determine the cause of this failure. For more information, see [z/OS DFSMS Macro Instructions for Data Sets](#).

User response

Inform your system programmer that this error occurred.

APS571I **CODE PAGE *member name* AND FONT CHARACTER SET *member name* ARE ASSOCIATED WITH THE REPORTED FONT ERROR.**

Explanation

The code page and font character set identified in the message text were used to activate the font that caused the reported error. These resources might be used to activate a printer-resident font, in which case the printer-resident font might contain the error.

System action

See the accompanying messages for the system action that was taken.

Operator response

No response is necessary.

System programmer response

If the accompanying messages are not sufficient to identify the problem, use the sense data to analyze the problem. For more information about printer sense bytes and the specific error, see the printer publications for the printer that reported this error.

User response

If the accompanying messages are not sufficient to identify the problem, contact your system programmer.

APS573I **OVERLAY *member name* CONTAINS AN ERROR THAT MAY PREVENT THE PRINTER FROM PRINTING THE PAGE. IF THE PAGE IS PRINTED THE RESULTING OUTPUT MAY BE UNACCEPTABLE.**

Explanation

The specified resource contains a data-stream exception (such as a position error). For details on the type of data-stream exception, look at the environmental messages issued with the first APS573I message. One of the environmental messages states the page number on which the error was first detected. Scan past all other APS573I messages in the message data set, and search for the next message group that contains the same page number; it contains the message for the error in the resource.

System action

The printer you were using might attempt to print the page that contains the error or might print only part of the page. If the page that contains the error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page that contains the error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

No response is necessary.

System programmer response

No response is necessary. No response is necessary.

User response

Find the detailed error message for the resource by following the directions given in the Explanation. Correct the problem by following the User Response for that message.

APS574I **REGION WAS TOO SMALL FOR PROCESSING {CP/FN PAIR | CODED FONT | PAGE SEGMENT} member name.**

Explanation

The GETMAIN macro attempted to obtain space for the resource identified in this message but was unsuccessful because of lack of storage.

System action

PSF stops processing the current page, and prints any accumulated data for the current page. PSF attempts to find the end of the current page and to resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or containing resource. PSF issues other messages that identify the processing environment in which the error was found.

Operator response

Inform your system programmer that this error occurred.

System programmer response

The size of the REGION parameter for the print request must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

User response

Determine whether any of the resources that are specified can be deleted from the input data stream. If no resources can be deleted, contact your system programmer.

APS575I **REGION WAS TOO SMALL FOR PROCESSING OVERLAY member name.**

Explanation

The GETMAIN macro attempted to obtain space for the resource identified in this message, but was unsuccessful because of a lack of storage.

System action

PSF stops processing the current page, and prints any accumulated data for the current page. PSF attempts to find the end of the current page and to resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or the containing resource. PSF issues other messages that identify the processing environment in which the error was found.

Operator response

Inform your system programmer that this error occurred.

System programmer response

The size of the REGION parameter for the print request must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

User response

Determine whether any of the resources that are specified can be deleted from the input data stream. If no resources can be deleted, contact your system programmer.

APS576I **REGION WAS TOO SMALL FOR PROCESSING APSRMARK DATA IN THE BEGIN STRUCTURED FIELD OF {FONT CHARACTER SET | CODE PAGE | PAGE SEGMENT | OVERLAY} member name.**

Explanation

PSF attempted to obtain storage for a work area necessary to process APSRMARK data that was in the specified resource, but PSF was unsuccessful because of a lack of storage. The resource can be a code page, a font character set, a page segment, or an overlay. PSF needs this space to determine the presence of remote or resident resources.

System action

Because PSF has insufficient storage to determine the presence of these resources (resident either in the printer or in the Distributed Print Function resource library), processing is performed as if these resources did not exist as remote or resident resources.

Resources are sent to the printer instead of using any remote or resident resources that might be equivalent. PSF continues processing data, and the printed output is acceptable; however, performance of the printer is degraded.

PSF issues a message that identifies the position of the structured field in the input data stream or containing resource. PSF issues other messages that identify the processing environment in which the error was found.

Operator response

Inform your system programmer that this error occurred.

System programmer response

The size of the REGION parameter for the print request must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

User response

Determine whether any of the resources that are specified can be deleted from the input data stream. If no resources can be deleted, contact your system programmer.

APS577I **REGION WAS TOO SMALL FOR PROCESSING {PAGEDEF | FORMDEF | CODED FONT | CODE PAGE | FONT CHARACTER SET | PAGE SEGMENT | OVERLAY | OBJECT CONTAINER} *member name*.**

Explanation

The GETMAIN macro attempted to obtain space for the resource identified in this message, but was unsuccessful because of a lack of storage.

System action

PSF stops processing the current page, and prints any accumulated data for the current page. PSF attempts to find the end of the current page and resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or the containing resource. PSF issues other messages that identify the processing environment in which the error was found.

Operator response

Inform your system programmer that this error occurred.

System programmer response

The size of the REGION parameter for the print request must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

APS579I **WHILE PROCESSING A CODED FONT *member name* USING FONT CHARACTER SET *member name* AND CODE PAGE *member name*, CONFLICTING FONT TECHNOLOGIES WERE DISCOVERED IN THESE OBJECTS. PROCESSING FOR THIS FONT WAS NOT SUCCESSFUL.**

Explanation

PSF was attempting to load or activate a font when it discovered that the font technology (either raster or outline) of the font character set and the font technology of the code page were different. The font technology of the font character set and code page must be identical.

Some possible causes of this error might be:

- The coded font object specifies the name of a font character set with raster font technology and a code page with outline font technology.
- After mapping font names, the new font character set name and code page name specified font parts of different font technologies.

System action

PSF was unable to activate all the resources in the printer that were required for printing this page. As a result, PSF does not print the page that contains the error.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is specified for use with a separator page or message

data set in the PSF startup procedure. Inform your system programmer that this error occurred.

System programmer response

If an IBM licensed program was used to create the data stream structured fields for the resource with the error, verify that the input to the program was valid. If the input is valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section of this message to correct the error.

User response

Ensure that the code page and the font character set for the coded font are compatible. The coded font members must both be the same technology. For more information about how to select compatible code pages and font character sets, see *Font Object Content Architecture Reference*. If you think the code page and font character set are of the same font technology, PSF might have a logic error that caused the problem.

APS580I **APSRMARK control statement**

Explanation

This message echoes each APSRMARK control statement after it is processed.

System action

This message is only for information.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

No response is necessary.

APS581I **UNABLE TO OPEN INPUT
RESOURCE DATA SET. CHECK
INDD FOR ERRORS.**

Explanation

The data set defined by the JCL statement referred to by the INDD control parameter (as shown in the listing) cannot be opened for input. The reason is probably that a JCL statement is not valid or is missing.

System action

PSF stops processing this control statement.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Correct the JCL and resubmit the print request.

APS582I **INPUT RECFM IS INCORRECT FOR
RESOURCE DATA. CHECK INDD
FOR ERRORS.**

Explanation

The data set defined by the JCL statement referred to by the INDD control parameter (as shown in the listing) has a fixed-record format. The resource data is expected to be in variable-record format. The reason for the failure is probably that a data set is defined incorrectly in the JCL statement referred to by the INDD control parameter.

System action

PSF stops processing this control statement.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Change the JCL to see a valid resource data set, and resubmit the print request.

APS583I **INPUT LRECL IS INCORRECT FOR
RESOURCE DATA. CHECK INDD
FOR ERRORS.**

Explanation

The data set defined by the JCL statement referred to by the INDD control parameter (as shown in the listing) has a logical record length greater than 32,767. The resource data is expected to have a logical record length less than 32,768. The reason for the failure is probably that a data set is defined incorrectly in the JCL statement referred to by the INDD control parameter.

System action

PSF stops processing this control statement.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Change the JCL to see a valid resource data set, and resubmit the print request.

APS584I UNABLE TO OPEN OUTPUT DATA SET. CHECK OUTDD FOR ERRORS.

Explanation

The data set defined by the JCL statement referred to by the OUTDD control parameter (as shown in the listing) cannot be opened for output, probably because a JCL statement is not valid or is missing.

System action

PSF stops processing this control statement.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Correct the JCL and resubmit the print request.

APS585I RESOURCE DATA COPIED TO OUTPUT BUT WAS UNMARKED.

Explanation

Coded fonts, form definitions, page definitions, object containers, and unrecognized resources are not marked by the APSRMARK utility. They are copied to the output without modification. Only code pages, font character sets, overlays, and page segments can be marked by the APSRMARK utility.

System action

The processing of this control statement continues.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

No response is necessary.

APS586I PREMATURE END-OF-FILE DETECTED ON INPUT. INPUT MAY NOT BE VALID DATA FORMAT.

Explanation

The input data set is scanned for a valid Begin structured field and its corresponding End structured field. One or the other of these structured fields cannot be found in the input data set. Either the resource was missing a Begin or End structured field, or nonresource data was input to the APSRMARK utility. Only page segments, overlays, code pages, and font character sets are valid input.

System action

PSF stops processing this control statement.

Operator response

No response is necessary.

System programmer response

If an IBM licensed program was used to create the structured fields, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the resource and you did not intend to have the resource marked, correct your JCL and APSRMARK control statements and resubmit the APSRMARK job. If the resource's structured fields are correct, and you intended to mark the resource, contact your system programmer.

APS587I UNABLE TO OPEN CONTROL STATEMENT DATA SET. CHECK SYSIN FOR ERRORS.

Explanation

The data set defined by the SYSINDD statement cannot be opened for input, probably because a JCL statement is not valid or is missing.

System action

All processing is ended.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Correct the JCL and resubmit the print request.

**APS588I INPUT RECFM IS INCORRECT FOR
CONTROL STATEMENT DATA SET.
CHECK SYSIN FOR ERRORS.**

Explanation

The data set defined by the SYSINDD statement has an incorrect record format. The control statement data set must have a fixed record format. The reason for this failure is probably that a data set was defined incorrectly in the SYSINDD statement.

System action

All processing is ended.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Correct the SYSINDD statement, and resubmit the print request.

**APS589I INPUT LRECL IS INCORRECT FOR
CONTROL STATEMENT DATA SET.
CHECK SYSIN FOR ERRORS.**

Explanation

The data set defined by the SYSINDD statement has an incorrect logical record length. The control statement data set must have a logical record length of 80. The reason for this failure is probably that a data set was defined incorrectly in the SYSINDD statement.

System action

All processing is ended.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Correct the SYSINDD statement, and resubmit the print request.

**APS590I INCORRECT CONTROL
STATEMENT SYNTAX. STATEMENT
IGNORED.**

Explanation

The syntax of a control statement is not valid. This failure is probably caused by typing errors.

System action

PSF stops processing this control statement.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Correct the control statement syntax, and resubmit the print request.

**APS591I MPS STRUCTURED FIELD ADDED
TO OVERLAY.**

Explanation

In an overlay, a soft page segment that is identified with an Include Page Segment (IPS) structured field, was converted to a hard page segment by adding a Map Page Segment (MPS) structured field to the Active Environment Group of the overlay. This change was made during APSRMARK processing so that any updates to the page segment that are referenced in the overlay are detected by the distributed print function (DPF).

System action

PSF processing continues.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

No response is necessary.

**APS592I PROCESSING ABORTED FOR
MEMBER *member name*.**

Explanation

The input resource data cannot be processed successfully. Previous error messages describe the precise error condition.

System action

PSF stopped processing for this member.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

To determine an appropriate response, see the specific error condition described in the accompanying messages.

**APS593I BEGIN RECORD TRUNCATED
BECAUSE OF UNRECOGNIZED
EXTENSION.**

Explanation

The input resource data does not conform to the format expected for a valid Begin structured field. This message warns that the Begin structured field was changed to conform to the expected architecture and that information was dropped from the Begin structured field.

System action

The Begin structured field is changed, and processing continues.

Operator response

No response is necessary.

System programmer response

Ensure that no applications are affected by the changes to the Begin structured field.

User response

Inform your system programmer that this error occurred.

APS594I PROCESSING COMPLETED.

Explanation

The input resource data processed successfully.

System action

This message is only for information.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

No response is necessary.

**APS595I PROCESSING COMPLETED FOR
MEMBER *member name*.**

Explanation

The input resource data for the specified member processed successfully.

System action

This message is only for information.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

No response is necessary.

**APS596I OUTPUT RECFM IS INCORRECT
FOR RESOURCE DATA. CHECK
OUTDD FOR ERRORS.**

Explanation

The data set defined by the JCL statement referred to by the OUTDD control parameter (as shown in the listing) has a fixed-record format. The resource data is expected to be in variable-record format. The reason for this failure is probably that a data set is defined

incorrectly in the JCL statement referred to by the OUTDD control parameter.

System action

PSF stops processing this control statement.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Change the JCL to reference a valid resource data set, and resubmit the print request.

**APS597I OUTPUT LRECL IS INCORRECT
 FOR RESOURCE DATA. CHECK
 OUTDD FOR ERRORS.**

Explanation

The data set defined by the JCL statement referred to by the OUTDD control parameter (as shown in the listing) has a logical record length greater than 32,767. The resource data is expected to have a logical record length less than 32,768. The reason for this failure is probably that a data set was defined incorrectly in the JCL statement referred to by the OUTDD control parameter.

System action

PSF stops processing this control statement.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Change the JCL to see a valid resource data set, and resubmit the print request.

**APS598I INPUT DATA SET SPECIFIED BY
 INDD DOES NOT CONTAIN
 MEMBER *member name*.**

Explanation

The data set defined by the JCL statement referred to by the INDD control parameter (as shown in the listing) does not contain the referenced *member name*. This failure is probably caused by a typing error on the control statement.

System action

PSF stops processing this *member name*.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Correct the control statement to see a valid member name, and resubmit the print request.

**APS599I MEMBER ALREADY EXISTS IN
 DATA SET SPECIFIED BY OUTDD.
 USE REPLACE TO UPDATE
 MEMBER *member name*.**

Explanation

The data set defined by the JCL statement referred to by the OUTDD control parameter (as shown in the listing) already contains the referenced *member name*. To overwrite an existing member, the REPLACE parameter must be specified on the control statement.

System action

PSF stops processing this *member name*.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Correct the control statement to specify REPLACE, and resubmit the print request.

APS600 to APS699

APS600I USER IS NOT AUTHORIZED TO OVERRIDE DEFAULT VALUE.

Explanation

This message is issued when DPAGELBL or SYSAREA parameter is equal to YES on the PRINTDEV statement, and the user specifies NO without correct Resource Access Control Facility (RACF) authorization.

System action

PSF releases the current data set back to JES and requests that it is held by the system.

Operator response

Notify the security administrator of this error. For a command to release the data set for printing after the problem is corrected, see the publication that contains JES operator commands for your operating system.

System programmer response

Determine whether the user must be authorized to override SYSAREA or DPAGELBL. If the user must be authorized, use RACF to give the user the appropriate authorization. For information on how to do this, see the RACF publications for your operating system.

User response

Ask the system security administrator for permission to override the default values, or change the output so that it does not override the default.

APS601I USERLIB SPECIFICATION IS IGNORED.

Explanation

JES did not provide PSF the UTOKEN parameter that is required to do a RACF authorization check for a user library (USERLIB). This condition can arise if the correct prerequisite level of z/OS, RACF, or JES is not installed, or if any of those programs contains a logic error.

System action

Processing of the data set continues by using system libraries only.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Ensure that the correct levels of z/OS, RACF, and JES for this version of PSF are installed. If the correct levels are installed, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

Inform your system programmer that this error occurred.

APS602I PSF FAILED TO FIND CNTL STATEMENT *control statement* IN CURRENT STEP, REASON CODE = *reason code*.

Explanation

PSF started the Scheduler JCL Facility (SJF) to find the scheduler work block for the control statement in the current step specified by the CNTL keyword on the DD statement. The SJF FIND macro failed and returned the reason code identified in this message. The values of the reason codes and their meanings are:

- X'1': The FIND macro was successful.
- X'190': The specified SWB chain was not found.
- X'191': The STEP or PROC name was not found.
- X'192': The specified DD label was not found.
- X'193': No search bits were specified in the parameter list.
- X'194': Undefined bits were specified in the parameter list.
- X'195': The control group was not found.
- X'196': A step name was not specified in the parameter list.
- X'197': An incorrect starting address was specified in the parameter list.

System action

PSF fails to initialize.

Operator response

Inform your system programmer that this error occurred.

System programmer response

This error was probably caused by an error in specifying the JCL statements for the startup procedure. For information about specifying JCL

statements, see *PSF for z/OS: Customization*. Correct the error and restart the procedure. If you made any changes to the startup procedure, be sure to CANCEL the STARTED TASK before you try again.

User response

No response is necessary.

**APS603I PRINTDEV VERB NOT FOUND
WITHIN CNTL GROUP control
group.**

Explanation

PSF started the Scheduler JCL Facility (SJF) to find the scheduler work block chain for a PRINTDEV verb in the control group identified in this message. The PRINTDEV verb was not found.

System action

PSF fails to initialize.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Omission of the PRINTDEV JCL statements in the PSF startup procedure probably caused this error. For information about specifying JCL statements for the PSF startup procedure, see *PSF for z/OS: Customization*. Correct the error and restart the procedure.

User response

No response is necessary.

**APS604I ONE OR MORE KEYWORDS
REQUIRED TO INITIALIZE AN SNA
DEVICE WAS NOT SPECIFIED ON
THE PRINTDEV STATEMENT. ALL
REQUIRED KEYWORDS MUST BE
SPECIFIED BEFORE THE
PROCEDURE CAN BE STARTED.**

Explanation

To start an SNA-attached printer, all required keywords must be specified.

System action

PSF fails to initialize.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Ensure that all required keywords for the SNA-attached printer are specified in the PRINTDEV JCL statement in the PSF startup procedure. For more information, see *PSF for z/OS: Customization*. The required SNA-attached keywords are:

- LUNAME— VTAM node name for the printer
- APPLID— VTAM node name for the FSA

User response

No response is necessary.

**APS605I VIRTUAL STORAGE COULD NOT BE
ACQUIRED FOR TRACING. {ALL |
EXTERNAL} TRACING FOR
{prtname | fssname} HAS BEEN
CANCELED.**

Explanation

Virtual storage cannot be acquired for all the required trace control blocks. The indicated trace types are canceled.

System action

The indicated types of tracing were canceled.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Increase the REGION size specified in the PSF startup procedure.

User response

No response is necessary.

**APS606I PERMANENT I/O ERROR
OCCURRED ON TRACE DATA SET,
unit name, ddname, device type,
command, error.**

Explanation

The PSF SYNAD routine encountered a permanent I/O error on the trace data set.

System action

Tracing stops.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Correct the error based on the information provided by the message.

User response

Inform your system programmer that this error occurred.

APS607I **COMMAND (*command*) NOT PROCESSED - FSA (*fsa name*) IS NOT INITIALIZED.**

Explanation

The *fsa name* specified in a command was not initialized.

System action

AFP Download Plus continues processing.

Operator response

Enter the command again after the specified FSA is initialized by AFP Download Plus.

System programmer response

No response is necessary.

User response

No response is necessary.

APS608I **PSF GTF TRACING HAS BEEN {ACTIVATED | DEACTIVATED}.**

Explanation

PSF activated or deactivated tracing to Generalized Trace Facility (GTF). When activated, PSF Generalized Trace Facility issues the GTRACE macro request to write trace data to the GTF data set. When deactivated, PSF stops writing trace data to GTF.

System action

PSF continues processing the data.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

No response is necessary.

APS609I **MUTUALLY EXCLUSIVE KEYWORDS WERE SPECIFIED. SNA-REQUIRED KEYWORDS APPLID OR LUNAME WERE SPECIFIED WITH TCP/IP-REQUIRED KEYWORD IPADDR.**

Explanation

To start the printer, conflicting protocol keywords must be removed from the Printer Inventory or a PRINTDEV JCL statement in the PSF startup procedure.

System action

PSF fails to initialize.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Remove the keywords from the Printer Inventory or the PRINTDEV JCL statement for the protocol that is not used to communicate with the device. For more information about how to specify Printer Inventory options or a PRINTDEV statement, see *PSF for z/OS: Customization*. The keywords that are required for an SNA-attached printer are:

- LUNAME—VTAM node name for the printer
- APPLID—VTAM node name for the FSA

The keyword that is required for a TCP/IP-attached printer is:

- IPADDR—Internet Protocol (IP) address for the printer

User response

No response is necessary.

APS610I **GTF RETURN CODE = *rc*: *error text*.**

Explanation

Generalized Trace Facility (GTF) returned a nonzero return code from the GTRACE request. The return code *rc* and the *error text* explain the error. The return codes and error text are:

04 inactive MVS GTF
08 incorrect length = xxxx
0C incorrect data address = xxxx
10 incorrect FID = xx
14 incorrect EID = xx
18 no GTF buffer space
1C incorrect parameter address = xxxx
20 data paged out
xx unknown GTF return code

PSF issues this message when it attempts to start a PSF trace and direct its output to the GTF trace data set. If the message is received, GTF might not be started with the correct USR event IDs. If you use the command `MODIFY FSSname, TRACEON, PRTxxx, FORMAT=GTF` to start PSF tracing, you must specify `USR=(FD0,FD4)`. If you do not want both types of event, start GTF with the appropriate event ID. Then, if you want FD0, add `EID=PSF` to the `MODIFY` command; or, if you want only FD4 entries, add `EID=FSI` to the `MODIFY` command.

System action

The action depends on the return code; PSF might or might not continue tracing. For return codes 18 and 20, GTF tracing continues. For the other return codes listed, GTF tracing stops. For unknown return codes, GTF tracing stops.

Operator response

Inform your system programmer that this error occurred.

System programmer response

For more information about the return codes, see [z/OS MVS Diagnosis: Tools and Service Aids](#) or [z/OS MVS Diagnosis: Reference](#).

User response

No response is necessary.

APS611I	COMMAND (TRACEOFF) NOT PROCESSED – TRACING IS NOT ACTIVE.
----------------	--

Explanation

The TRACEOFF command was not processed because tracing was not active.

System action

PSF continues processing.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

No response is necessary.

APS612I	COMMAND (<i>command</i>) NOT PROCESSED – NO TRACE DATA SET ALLOCATED FOR (<i>printer-name</i> <i>notify task</i>).
----------------	---

Explanation

A trace request was received for a printer or notify task, but no trace data set was allocated for that printer or notify task.

System action

The entire command is ignored and processing continues with the next command entered.

Operator response

Ask your system programmer to identify the required trace data set, or start tracing with the GTF format.

System programmer response

If you are using the Printer Inventory, identify the trace data set by using the `FSA-trace-dsname` parameter or the `NST-trace-dsname` parameter. Otherwise, identify the trace data set with a `DD` statement in the startup procedure.

User response

No response is necessary.

APS613I	COMMAND (<i>command</i>) NOT PROCESSED – FSA (<i>name</i>) IS NOT ACTIVE.
----------------	--

Explanation

The Functional Subsystem Application (FSA) name specified in a command was not active.

System action

PSF continues processing.

Operator response

Enter the command again after you start the named FSA.

System programmer response

No response is necessary.

User response

No response is necessary.

APS614I THE VALUE SPECIFIED FOR THE keyword KEYWORD ON THE OUTPUT STATEMENT IS NOT VALID.

Explanation

The value that is given for the indicated keyword contained embedded blanks or too many decimal digits, or it specified an unrecognized unit.

System action

The data set is not printed.

Operator response

No response is necessary.

System programmer response

If the error is on an OUTPUT statement for a separator page or the message data set, correct the specification for the keyword in the PSF startup procedure and restart the FSA.

User response

Correct the specification for the keyword and resubmit the job.

APS615I RESPTIME OR NORESP KEYWORD SPECIFIED WITHOUT THE OTHER ON THE prtntnnn PRINTDEV STATEMENT.

Explanation

The NORESP keyword defines the action to be taken when the time that is specified by the RESPTIME keyword expires. If one of these keywords is specified, both must be given. Only one of them was specified.

System action

FSA startup for PRINTER *prtntnnn* is canceled.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Correct the PRINTDEV statement for *prtntnnn*.

User response

No response is necessary.

APS616I THE NORESP KEYWORD ON THE prtntnnn PRINTDEV STATEMENT CONTAINS AN INCORRECT ACTION PARAMETER.

Explanation

The NORESP keyword was specified on the PRINTDEV statement for printer *prtntnnn* with an incorrect action type.

System action

FSA startup for printer *prtntnnn* is canceled.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Correct the PRINTDEV statement for printer *prtntnnn*.

User response

No response is necessary.

APS617I THE FORMAT OF THE NOTIFY OPTION OF THE NORESP KEYWORD IS NOT VALID ON THE prtntnnn PRINTDEV STATEMENT.

Explanation

NORESP=NOTIFY was specified on the PRINTDEV statement for printer *prtntnnn*, but the format of the NOTIFY option was incorrect.

System action

FSA startup for printer *prtntnnn* is canceled.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Correct the PRINTDEV statement for *prtnnnn*.

User response

No response is necessary.

APS618I **RESPONSE TIMEOUT OR NO RESPONSE ACTION SPECIFIED WITHOUT THE OTHER IN THE PRINTER INVENTORY FOR *fsa_name*.**

Explanation

The no response action parameter defines the action to be taken when the time that is specified by the response timeout parameter expires. If one of these parameters is specified, both must be given. Only one of them was specified.

System action

FSA startup for PRINTER *fsa_name* is canceled.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Correct the printer definition in the Printer Inventory for *fsa_name*.

User response

No response is necessary.

APS619I **NOT ALL PARAMETERS REQUIRED TO INITIALIZE AN SNA DEVICE WERE SPECIFIED IN THE PRINTER INVENTORY FOR *fsaname*.**

Explanation

A parameter was specified which indicates that the printer is to be SNA-attached, but not all the parameters required for SNA attachment were given. To start an SNA-attached printer, all required parameters must be specified.

System action

PSF fails to initialize.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Ensure that all required keywords for the SNA-attached printer are specified in the printer definition in the Printer Inventory. For more information, see [z/OS Infoprint Server Operation and Administration](#). The required SNA-attached keywords are:

- *luname*— VTAM node name for the printer
- *applid*— VTAM node name for the FSA

User response

No response is necessary.

APS620A **ENTER PSF COMMAND OR U – USING THE MVS MODIFY COMMAND.**

Explanation

The PSF operator interface is not initialized.

System action

PSF initialization continues.

Operator response

You can do one of these:

- Enter MODIFY commands for only the FSS (commands cannot be entered that specify the printer name); then, initialize the PSF operator interface.
- Initialize the PSF operator interface.

To initialize the PSF operator interface, enter:

```
{MODIFY|F}  
fssname  
,U
```

fssname is the name of the PSF FSS as provided in the message. Do not enter a printer name, or the command is rejected. After the PSF operator interface is initialized, you can enter any PSF operator commands.

System programmer response

No response is necessary.

User response

No response is necessary.

APS621I **OPERATOR INTERFACE
INITIALIZED FOR *product* and
version.**

Explanation

The operator interface is initialized successfully. All operator commands can now be entered for the PSF version or Download version specified in the message text.

System action

Initialization continues.

Operator response

Operator commands can now be entered.

System programmer response

No response is necessary.

User response

No response is necessary.

APS622I **NOT ENOUGH STORAGE IS
AVAILABLE TO INITIALIZE THE
PSF OPERATOR INTERFACE –
STORAGE REQUESTED = *size*
RETURN CODE = *code*.**

Explanation

Not enough storage is available for control blocks or work areas. The message indicates the size of the storage that is requested, and the return code is from the MVS GETMAIN macro.

System action

The PSF operator interface is not initialized. PSF initialization continues.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Increase the REGION parameter on the procedure that is used to start PSF.

User response

No response is necessary.

APS623I **THE PSF OPERATOR INTERFACE
INITIALIZATION WAS**

**UNSUCCESSFUL – MODULE
(*module name*).**

Explanation

The PSF operator interface was not initialized successfully. A functional command initialization module returned a nonzero return code.

System action

The PSF operator interface is not initialized. PSF initialization continues.

Operator response

Inform your system programmer that this error occurred.

System programmer response

To determine an appropriate response, see the specific error conditions described in the accompanying messages.

User response

No response is necessary.

APS624I **THE PSF OPERATOR INTERFACE
IS BEING TERMINATED – MODULE
(*module name*) HAS TERMINATED.**

Explanation

An abend occurred in a module that has a previous abend condition. Because the previous abend and this abend involve the same module, no recovery of the operator interface is attempted.

System action

The PSF operator interface is ended.

Operator response

Inform your system programmer that this error occurred.

System programmer response

If you suspect a PSF logic error, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

No response is necessary.

APS625I **THE PSF OPERATOR INTERFACE
HAS BEEN TERMINATED.**

Explanation

The PSF operator interface has an unrecoverable error.

System action

The PSF operator interface is ended.

Operator response

PSF must be purged and restarted to activate the operator interface.

System programmer response

If you suspect a PSF logic error, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

No response is necessary.

APS626I	PSF OPERATOR INTERFACE RECOVERY IS {IN PROGRESS SUCCESSFUL UNSUCCESSFUL} – FOR MODULE (<i>module name</i>).
----------------	--

Explanation

The PSF operator interface has an error, and recovery is attempted. The error occurred in the named module.

System action

If recovery is successful, normal command processing is continued. If recovery is unsuccessful, the PSF operator interface is ended.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Contact the IBM Support Center or use your electronic link with IBM service for assistance.

User response

No response is necessary.

APS627I	PSF FSA <i>printer-name</i> HAS BEEN TERMINATED WITH THE FORCE COMMAND.
----------------	--

Explanation

The operator issued an MVS MODIFY FORCE command for the specified *printer-name*.

System action

The Functional Subsystem Application (FSA) for the indicated *printer-name* stopped.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

No response is necessary.

APS628I	SYSTEM COMPLETION CODE <i>system completion code</i>, PSF ABEND REASON CODE <i>reason code</i>, HAS BEEN DETECTED BY <i>estae routine</i>.
----------------	---

Explanation

The PSF ESTAE routine detected a PSF abend condition.

System action

Depending on the error condition, PSF attempts either to recover or to end the operator interface. A subsequent PSF message notifies the operator which action was taken.

An ESTAE routine creates an SVC dump unless a dump was provided by an earlier routine.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Examine the subsequent PSF messages to determine the appropriate response. To interpret the abend code, see [Chapter 2, “System completion codes and PSF abend reason codes,”](#) on page 613. For most abend reason codes, you must consult your IBM Support Center representative. However, for some abend reason codes you can recover by increasing the REGION parameter on the startup procedure.

User response

No response is necessary.

APS629I	PSF OPERATOR INTERFACE WAS TERMINATED ABNORMALLY.
----------------	--

Explanation

PSF detected an unrecoverable error while it evaluated the abend condition. The ESTAE routine provided an SVC dump.

System action

Abend processing continues.

Operator response

Inform your system programmer that this error occurred.

System programmer response

The contents of the registers at the time of the abend are provided in the SVC dump and register 15 might contain a PSF abend reason code. Save the dump for IBM Support Center use. To interpret the dump, see *PSF for z/OS: Diagnosis*. To interpret the system completion code, see the publication that contains system messages for your operating system.

User response

No response is necessary.

APS630I PSF ESTAE CANNOT EVALUATE SYSTEM COMPLETION CODE *system completion code*. ABNORMAL TERMINATION WILL CONTINUE.

Explanation

The PSF ESTAE routine is unable to continue because PSF did not issue the system completion code.

System action

Abend processing continues.

Operator response

Inform your system programmer that this error occurred.

System programmer response

To interpret the system completion code, see the MVS system codes publication for your operating system. To interpret the memory dump, see *PSF for z/OS: Diagnosis*. Save the dump for IBM Support Center use.

User response

No response is necessary.

APS631I

A STAPLE JAM HAS OCCURRED WHILE ACCUMULATING SHEETS FOR A FINISHING OPERATION. PARTIAL OR DUPLICATE PAGES MAY BE PRINTED.

Explanation

The staple mechanism on a printer or post processor jammed or caused a physical-media jam. The printer detected and reported an asynchronous intervention-required error with an action code of X'0A' (sense byte 2). For more information about this error, see the printer publications for the printer that reported this error.

System action

PSF resends pages to the printer, starting from the jam recovery page counter. Pages might be duplicated during recovery. If repositioning is not supported in the current environment, PSF stops processing the data set.

Operator response

See the operator's guide for the printer that reported this error and clear the paper from the printer and post processor. PSF assumes that pages between the jam recovery page counter and the stacked page counter are not damaged and do not need to be reprinted. If any pages between these two printer counters do need to be reprinted, use the JES BACKSPACE command.

System programmer response

If the error condition persists, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

The printed output might be acceptable. If any pages were duplicated, you might want to resubmit the print request. If the error condition persists, consult your system programmer.

APS632I

DATA IN A FORMDEF RESOURCE IS INCOMPATIBLE WITH THE PRINT REQUEST: THE OUTPUT CONTAINS TOO MANY SHEETS TO PERFORM THE FINISHING OPERATION SPECIFIED IN THE MEDIUM FINISHING CONTROL STRUCTURED FIELD.

Explanation

A finishing operation was requested for a collection of sheets, but the number of sheets was too large for the operation.

Finishing Operation triplets are specified in the Medium Finishing Control (MFC) structured field. The MFC is specified in the Document Environment Group of the form definition or in a Medium Map.

System action

PSF stops printing and processing the data set. The finishing operation is not applied or incompletely applied.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the MFC with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If the output is not acceptable:

- Verify that you requested the appropriate form definition for the finishing operation intended.
- Submit the print request to a printer that can do the finishing operation.
- If errors caused message pages to be added to the output or pages to be skipped, fix those errors so that the correct number of pages is printed.

APS633I

A PARAMETER VALUE IN A FORMDEF RESOURCE IS NOT VALID OR IS UNSUPPORTED: THE MEDIUM FINISHING CONTROL STRUCTURED FIELD SPECIFIES AN INCORRECT OR UNSUPPORTED FINISHING OPERATION TYPE FOR THE SELECTED MEDIA.

Explanation

The operation type field (byte 2) in a Finishing Operation triplet (X'85') contains an incorrect or unsupported value for the selected media.

Finishing Operation triplets are specified in the Medium Finishing Control (MFC) structured field. The MFC is specified in the Document Environment Group of the form definition or in a Medium Map.

System action

Reporting of this exception can be controlled by the Finishing Fidelity triplet in the Presentation Fidelity Control (PFC) command. The PFC command is contained in a form definition.

When the Finishing Fidelity triplet sets the continuation rule to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and the data set is marked unprintable. PSF releases the current data set back to JES and requests that it is held by the system unless PRTEROR=QUIT is specified on the OUTPUT statement.

When the Finishing Fidelity triplet sets the continuation rule to DO NOT STOP (X'02'), one of these occurs:

- If the printer supports the PFC Finishing Fidelity triplet and if the REPORT field is set to REPORT (X'01'), the printer reports this exception. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.
- If the printer supports the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.
- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer reports this exception but PSF does not issue the error message. The printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to REPORT (X'01'), the printer reports this exception and PSF issues the error message. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the MFC with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If the output is not acceptable:

- Verify that you requested the appropriate form definition for the finishing operation intended.
- Verify that the selected media is the type intended for the finishing operation. If the wrong media was selected, either select a different input bin or load the correct media in this input bin.
- Submit the print request to a printer that can do the finishing operation.
- If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

MEDIUM FINISHING CONTROL STRUCTURED FIELD SPECIFIES AN INCORRECT OR UNSUPPORTED FINISHING OPERATION REFERENCE CORNER AND EDGE FOR THE MEDIA BEING FINISHED.

Explanation

The reference corner and edge field (byte 5) in a Finishing Operation triplet (X'85') contains an incorrect or unsupported value for the media that is finished. This can be caused when a supported media size has different supported reference corners and edges depending on which edge of the media is the leading edge.

Finishing Operation triplets are specified in the Medium Finishing Control (MFC) structured field. The MFC is specified in the Document Environment Group of the form definition or in a Medium Map.

System action

Reporting of this exception can be controlled by the Finishing Fidelity triplet in the Presentation Fidelity Control (PFC) command. The PFC command is contained in a form definition.

When the Finishing Fidelity triplet sets the continuation rule to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and the data set is marked unprintable. PSF releases the current data set back to JES and requests that it is held by the system unless PRERROR=QUIT is specified on the OUTPUT statement.

When the Finishing Fidelity triplet sets the continuation rule to DO NOT STOP (X'02'), one of these occurs:

- If the printer supports the PFC Finishing Fidelity triplet and if the REPORT field is set to REPORT (X'01'), the printer reports this exception. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.
- If the printer supports the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.

APS634I

A PARAMETER VALUE IN A FORMDEF RESOURCE IS NOT VALID OR IS UNSUPPORTED: THE

- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer reports this exception but PSF does not issue the error message. The printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.
- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to REPORT (X'01'), the printer reports this exception and PSF issues the error message. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the MFC with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If the output is not acceptable:

- Verify that you requested the appropriate form definition for the finishing operation intended.
- Ensure that the media is oriented properly in the input bin for the requested finishing operation.
- Submit the print request to a printer that can do the finishing operation.
- If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content*

Architecture Reference and Advanced Function Presentation: Programming Guide and Line Data Reference for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS635I THE COMMAND (*command*) IS NOT VALID.

Explanation

An incorrect command was entered with the MODIFY command. The command is not supported.

System action

The command is ignored and processing continues with the next command entered.

Operator response

Enter a valid command.

System programmer response

No response is necessary.

User response

No response is necessary.

APS636I INCORRECT KEYWORD (*keyword*) SPECIFIED FOR COMMAND (*command*).

Explanation

An incorrect keyword was entered with the MODIFY command. The keyword is not supported.

System action

The command is ignored and processing continues with the next command entered.

Operator response

Enter the command with a valid keyword.

System programmer response

No response is necessary.

User response

No response is necessary.

APS637I PROCESSING OF THE FORCE COMMAND FOR PSF FSA *printer*

***name* HAS BEEN TERMINATED.
THE FSA HAS ALREADY BEGUN
TERMINATING.**

Explanation

The operator issued an MVS MODIFY FORCE for a PSF printer that is already in the process of stopping.

System action

The MODIFY FORCE command for the indicated printer name is discarded by PSF. The stop processing already in progress is completed to attain the results wanted by the discarded MODIFY FORCE command.

Operator response

Enter the command with a valid keyword.

System programmer response

No response is necessary.

User response

No response is necessary.

APS638I **NO COMMAND SPECIFIED –
command-text.**

Explanation

No command is associated with the data entered. *Command-text* is the data that was entered. The last character of *command-text* was the last position checked before PSF determined that no correct command was present.

System action

The command is ignored and processing continues with the next command entered.

Operator response

Enter a valid PSF command.

System programmer response

No response is necessary.

User response

No response is necessary.

APS639I **COMMAND (*command*) {ACCEPTED
| QUEUED}.**

Explanation

The PSF command is accepted, or the command is queued for later processing. When the command is accepted, the functional processor is called to process the command. When the command is queued, the command is placed on either an FSS-level queue or an FSA-level queue. All queued commands in which the printer-name is specified are queued on the FSA-level queue. Commands that are issued without the printer-name are queued on the FSS-level queue.

System action

PSF continues processing the data.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

No response is necessary.

APS640I **PARAMETER *parameter* in
KEYWORD *keyword* REQUIRES A
PRINTER NAME.**

Explanation

A printer name is expected, but no printer is specified.

System action

The command is ignored and processing continues with the next command entered.

Operator response

Enter the command again, with a printer name.

System programmer response

No response is necessary.

User response

No response is necessary.

APS641I **A MECHANISM EXCEPTION
OCCURRED THAT PREVENTS A
FINISHING OPERATION FROM
BEING APPLIED.**

Explanation

The finishing mechanism on a printer or post processor has an intervention-required condition. The printer detected and reported an asynchronous intervention-required error with an action code of X'0A' (sense byte 2). For more information about this error, see the printer publications for the printer that reported this error.

System action

PSF resends pages to the printer, starting from the jam recovery page counter. Pages might be duplicated during recovery. If repositioning is not supported in the current environment, PSF stops processing the data set.

Operator response

See the operator's guide for the printer that reported this error and clear the paper from the printer and post processor. PSF assumes that pages between the jam recovery page counter and the stacked page counter are not damaged and do not need to be reprinted. If any pages between these two printer counters do need to be reprinted, use the JES BACKSPACE command.

System programmer response

If the error condition persists, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

The printed output might be acceptable. If any pages were duplicated, you might want to resubmit the print request. If the error condition persists, consult your system programmer.

APS642I THE MEDIUM FINISHING CONTROL (MFC) STRUCTURED FIELD IN THE DOCUMENT ENVIRONMENT GROUP SPECIFIES FINISHING OPERATION TRIPLETS THAT ARE INCOMPATIBLE WITH THE FINISHING OPERATION TRIPLETS SPECIFIED ON THE MFC STRUCTURED FIELD IN A MEDIUM MAP.

Explanation

The Medium Finishing Control (MFC) structured field is specified in both the Document Environment Group and in the Medium Map and contain Finishing Operation triplets that are incompatible. Compatible combinations of finishing operations are specific to a particular presentation device. When the element

identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. A Finishing Operation triplet that is specified on a sheet level MFC structured field is incompatible with a group finishing triplet specified on a higher-level MFC structured field.
2. A Finishing Operation triplet that is specified on a nested group level MFC structured field is incompatible with a Finishing Operation triplet specified on a sheet level MFC structured field for the same sheet.
3. An MFC structured field contains two or more Finishing Operation triplets that specify incompatible finishing operations.
4. A pair or more of MFC structured fields create nested Finishing Operation triplets that specify incompatible finishing operations.

The MFC is specified in the Document Environment Group of the form definition or in a Medium Map.

System action

Reporting of this exception can be controlled by the Finishing Fidelity triplet in the Presentation Fidelity Control (PFC) command. The PFC command is contained in a form definition.

When the Finishing Fidelity triplet sets the continuation rule to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and the data set is marked unprintable. PSF releases the current data set back to JES and requests that it is held by the system unless PRTEROR=QUIT is specified on the OUTPUT statement.

When the Finishing Fidelity triplet sets the continuation rule to DO NOT STOP (X'02'), one of these occurs:

- If the printer supports the PFC Finishing Fidelity triplet and if the REPORT field is set to REPORT (X'01'), the printer reports this exception. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.
- If the printer supports the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.

- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer reports this exception but PSF does not issue the error message. The printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.
- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to REPORT (X'01'), the printer reports this exception and PSF issues the error message. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the MFC with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If the output is not acceptable:

- Verify that you requested the appropriate form definition for the finishing operation intended.
- Submit the print request to a printer that can do the finishing operation.
- If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the MFC contains no triplets or no triplets that might be incompatible, the error

might be a printer configuration problem or a printer logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS643I DATA IN A FORMDEF RESOURCE IS INCOMPATIBLE WITH THE PRINT REQUEST: THE OUTPUT CONTAINS TOO MANY SHEETS TO PERFORM THE FINISHING OPERATION SPECIFIED IN THE MEDIUM FINISHING CONTROL STRUCTURED FIELD.

Explanation

A finishing operation was requested for a collection of sheets, but the number of sheets was too large for the operation.

Finishing Operation triplets are specified in the Medium Finishing Control (MFC) structured field. The MFC is specified in the Document Environment Group of the form definition or in a Medium Map.

System action

PSF stops processing the current data set, releases it back to JES, and requests that it is held by the system unless PRERROR=QUIT is specified on the OUTPUT statement.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

If you are running under JES, use the JES commands to release the data set to a printer that supports the finishing operation. For information about the command to use to release the data set, see the publication that contains JES commands for your operating system.

System programmer response

If an IBM licensed program was used to create the structured fields for the MFC with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If the output is not acceptable:

- Verify that you requested the appropriate form definition for the finishing operation intended.
- Submit the print request to a printer that can do the finishing operation.
- If errors caused message pages to be added to the output, fix those errors so that the correct number of pages is printed.

Either contact your operator to determine which printer the data set can be rerouted to or ask the operator to purge the job so you can resubmit the print request.

APS644I **MIXED SIZES OF PHYSICAL MEDIA WERE SELECTED TO BE FINISHED BUT THE PRINTER DOES NOT SUPPORT FINISHING ON A GROUP OF SHEETS OF DIFFERENT SIZES.**

Explanation

A finishing operation was requested for a collection of sheets of mixed sizes, but the device requires all of the sheets in the collection to be the same size.

Finishing Operation triplets are specified in the Medium Finishing Control (MFC) structured field. The MFC is specified in the Document Environment Group of the form definition or in a Medium Map.

System action

PSF stops printing and processing the data set. The finishing operation is not applied or is incompletely applied.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the MFC with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If the output is not acceptable:

- If you selected multiple input bins for a collection of sheets to be finished, make sure the media size in each is the same.
- Verify that you requested the appropriate form definition for the finishing operation intended.
- Submit the print request to a printer that can do the finishing operation.
- If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS645I **PARAMETER *parameter* IS NOT SUPPORTED.**

Explanation

A parameter is specified that PSF does not support.

System action

The command is ignored and processing continues with the next command entered.

Operator response

Enter the command again, without the unsupported parameter.

System programmer response

No response is necessary.

User response

No response is necessary.

APS646I **THE KEYWORD (*keyword*) IS MUTUALLY EXCLUSIVE WITH ANOTHER KEYWORD SPECIFIED IN COMMAND (*command*).**

Explanation

Of the keywords that are specified in this command, two of them cannot both be specified in the same command.

System action

The command is ignored and processing continues with the next command entered.

Operator response

Enter the command again, with the correct keywords specified.

System programmer response

No response is necessary.

User response

No response is necessary.

APS647I	keyword CANNOT BE SPECIFIED WITH keyword parameter – keyword IGNORED.
----------------	--

Explanation

The command contains (a) a keyword and (b) a particular combination of keyword and parameter. This particular keyword cannot be used in the same command with this combination of keyword and parameter.

System action

The keyword is ignored and defaults are used.

Operator response

If different keywords are required, enter the command again. For more information about the keywords, see [*PSF for z/OS: Diagnosis*](#).

System programmer response

No response is necessary.

User response

No response is necessary.

APS648I	DUPLICATE KEYWORD (keyword) ENTERED FOR COMMAND (command).
----------------	---

Explanation

A keyword was entered more than once for the same command.

System action

The command is ignored and processing continues with the next command entered.

Operator response

Enter the command in the correct format.

System programmer response

No response is necessary.

User response

No response is necessary.

APS649I	KEYWORD EXPECTED BUT NOT FOUND – command-text.
----------------	---

Explanation

A keyword was expected on a command, but *command-text* was found instead. *Command-text* is the data that was entered. The last character of *command-text* was the last position checked before PSF determined that no correct keyword was present.

System action

The command is ignored and processing continues with the next command entered.

Operator response

Enter the correct format of the command.

System programmer response

No response is necessary.

User response

No response is necessary.

APS650I	KEYWORDS ARE NOT ALLOWED WITH COMMAND (command).
----------------	---

Explanation

A command was specified with keywords. This command does not allow keywords.

System action

The command is ignored and processing continues with the next command entered.

Operator response

Enter the command again without the keywords.

System programmer response

No response is necessary.

User response

No response is necessary.

APS651I **KEYWORD REQUIRED FOR
COMMAND (*command*).**

Explanation

A command was entered without keywords. This command requires keywords.

System action

The command is ignored and processing continues with the next command entered.

Operator response

Enter the command again with the required keywords.

System programmer response

No response is necessary.

User response

No response is necessary.

APS652I **THE PARAMETER STATUS=TCPIP
AND THE KEYWORDS SCOPE,
EVENT, AND INTV ARE MUTUALLY
EXCLUSIVE IN THE COMMAND
DISPLAY.**

Explanation

Both the STATUS=TCPIP parameter and one or more of the keywords SCOPE, EVENT, and INTV are specified in the DISPLAY command. The keywords SCOPE, EVENT, and INTV can be specified only when STATUS=AFPDIST.

System action

The command is ignored and processing continues with the next command entered.

Operator response

Enter the command again, specifying either:

- STATUS=TCPIP without the keywords SCOPE, EVENT, and INTV
- STATUS=AFPDIST with any of the keywords SCOPE, EVENT, and INTV

System programmer response

No response is necessary.

User response

No response is necessary.

APS653I **THE DISPLAY REQUEST FOR
component display_type CANNOT
BE PERFORMED BECAUSE NO
TCP/IP DESTINATION IS ACTIVE.**

Explanation

The request for a DISPLAY command cannot be done because no TCP/IP printers are active. *component* is the component or function, such as TCPIP, used for the DISPLAY command. *display_type* is the type of display, such as STATUS, requested from the DISPLAY command.

System action

The command is ignored and processing continues with the next command entered.

Operator response

Make sure that the printer for which you want to issue the command is active and enter the command again.

System programmer response

No response is necessary.

User response

No response is necessary.

APS654I **THE DISPLAY REQUEST FOR
component display_type FOR FSA
NAME *fsa_name* IS NOT VALID.
THIS DESTINATION IS *attachment*
AND A TCP/IP-ATTACHED
DESTINATION IS REQUIRED.**

Explanation

The request for a DISPLAY command cannot be done because the destination for which it is requested is not TCP/IP-attached. The *component* is the component or function, such as TCPIP, used for the DISPLAY command. The *display_type* is the type of display, such as STATUS, requested from the DISPLAY command. The *attachment* is the type of attachment for the destination, which can be CHANNEL-ATTACHED, SNA-ATTACHED or UNKNOWN-ATTACHMENT.

System action

The command is ignored and processing continues with the next command entered.

Operator response

Enter the command for a destination that is TCP/IP-attached.

System programmer response

No response is necessary.

User response

No response is necessary.

APS655I THE KEYWORDS EVENT=, SCOPE=, and INTV= MUST BE SPECIFIED WITH KEYWORD STATUS=AFPDP.

Explanation

The keywords EVENT, SCOPE, and INTV can be used only on the MODIFY command with the DISPLAY parameter and the keyword STATUS=AFPDP.

System action

The command is ignored and processing continues with the next command entered.

Operator response

If you entered a command other than MODIFY DISPLAY STATUS=AFPDP, reenter the command without the SCOPE, EVENT, or INTV keywords. If you meant to enter the command MODIFY DISPLAY STATUS=AFPDP, reenter the command and ensure that the STATUS=AFPDP keyword is included in the command.

System programmer response

No response is necessary.

User response

No response is necessary.

APS656I THE COMMAND DISPLAY STATUS=AFPDP CANNOT BE PROCESSED BECAUSE THERE ARE NO JOBS ON THE SPOOL.

Explanation

The command MODIFY DISPLAY STATUS=AFPDP can be processed only while AFP Download Plus is processing a job.

System action

If the value of the SCOPE keyword is ONCE (the default), the command is ignored. Otherwise, the command is queued for the next available job.

Operator response

If the value of the SCOPE keyword is ONCE, reenter the command while AFP Download Plus is processing a job. Otherwise, no response is necessary.

System programmer response

No response is necessary.

User response

No response is necessary.

APS661I INCORRECT PARAMETER (*parameter*) SPECIFIED FOR KEYWORD (*keyword*) IN COMMAND (*command*).

Explanation

A parameter that is specified for a keyword is not valid.

System action

The command is ignored and processing continues with the next command entered.

Operator response

Enter the command again, with the correct parameter for the keyword.

System programmer response

No response is necessary.

User response

No response is necessary.

APS664I THE PARAMETER (*parameter*) IS MUTUALLY EXCLUSIVE WITH ANOTHER PARAMETER SPECIFIED IN KEYWORD (*keyword*) IN COMMAND (*command*).

Explanation

Two parameters are specified that cannot be specified in the same keyword.

System action

The command is ignored and processing continues with the next command entered.

Operator response

Enter the command again, with consistent keywords specified.

System programmer response

No response is necessary.

User response

No response is necessary.

APS667I	DUPLICATE PARAMETER (parameter) ENTERED FOR KEYWORD (keyword) IN COMMAND (command).
----------------	--

Explanation

A parameter was specified more than once in the keyword.

System action

The command is ignored and processing continues with the next command entered.

Operator response

Enter the command without a duplicate parameter for the keyword.

System programmer response

No response is necessary.

User response

No response is necessary.

APS668I	A DELIMITER (delimiter) WAS FOUND IN THE COMMAND WHERE A PARAMETER WAS EXPECTED - COMMAND TEXT (command-text).
----------------	---

Explanation

A delimiter was found where a parameter was expected. The last character of the *command-text* data is the incorrect delimiter.

System action

The command is ignored and processing continues with the next command entered.

Operator response

Enter the command again, in the correct format.

System programmer response

No response is necessary.

User response

No response is necessary.

APS669I	NO PARAMETERS SPECIFIED FOR KEYWORD (keyword) IN COMMAND (command).
----------------	--

Explanation

A keyword cannot be entered without its associated parameters.

System action

The command is ignored and processing continues with the next command entered.

Operator response

Enter the command again, with the correct keyword parameters.

System programmer response

No response is necessary.

User response

No response is necessary.

APS670I	UNBALANCED PARENTHESES – command-text.
----------------	---

Explanation

An ending parenthesis is missing from a command. *Command-text* was the data that was entered. The last character of *command-text* was the last position checked before PSF determined that a correct parameter list was not present.

System action

The command is ignored and processing continues with the next command entered.

Operator response

Enter the command and the keyword parameter list in the correct format.

System programmer response

No response is necessary.

User response

No response is necessary.

APS671I **PARAMETER FOUND WHERE
PRINTER NAME EXPECTED –
command-parameter.**

Explanation

A command was entered without the printer name. The command was entered as *command,parameter*, but it must be entered as *command,prtntnnn,parameters* if a printer name is to be specified. If a printer name is not to be specified, it must be entered as *command,,parameters*.

System action

The command is ignored and processing continues with the next command entered.

Operator response

Enter the command again, with a printer name or with a comma to occupy the position of the printer name.

System programmer response

No response is necessary.

User response

No response is necessary.

APS672I **PARAMETER *parameter* IS NOT
SUPPORTED BY THE AFP
DOWNLOAD PLUS FEATURE OF
PSF.**

Explanation

A parameter is specified that AFP Download Plus does not support.

System action

The command is ignored and processing continues with the next command entered.

Operator response

Enter the command again, without the unsupported parameter.

System programmer response

No response is necessary.

User response

No response is necessary.

APS683I **PRINTER NAME CANNOT BE
SPECIFIED FOR A PSF COMMAND
DURING INITIALIZATION.**

Explanation

The reply for message APS620A specified the printer name in the command. During initialization, the printer name cannot be specified with any command. These commands take effect for the entire FSS; therefore, the printer name is incorrect.

System action

The command is ignored and processing continues with the next command entered.

Operator response

Enter the command without the printer name.

System programmer response

No response is necessary.

User response

No response is necessary.

APS684I **PRINTER NAME (*printer-name*) IS
NOT VALID IN COMMAND
(*command*).**

Explanation

The printer name that is specified is not valid. The valid format of a printer name is *PRTntnnn*.

System action

The command is ignored and processing continues with the next command entered.

Operator response

Enter the correct format of the printer name.

System programmer response

No response is necessary.

User response

No response is necessary.

APS685I **PRINTER NAME CANNOT BE SPECIFIED FOR COMMAND (*command*).**

Explanation

A command was specified with a printer name, and the printer name parameter is not valid with this command.

System action

The command is ignored and processing continues with the next command entered.

Operator response

Enter the command again without a printer name.

System programmer response

No response is necessary.

User response

No response is necessary.

APS686I **PRINTER NAME IS REQUIRED FOR COMMAND (*command*).**

Explanation

A command was specified without a printer name, and a printer name is required with this command.

System action

The command is ignored and processing continues with the next command entered.

Operator response

Enter the command again, with a printer name.

System programmer response

No response is necessary.

User response

No response is necessary.

APS687I **PRINTER NAME CANNOT BE SPECIFIED FOR COMMAND (*command*) WITH PARAMETER (*parameter*).**

Explanation

The printer name was specified for a command, but the parameter that is specified with this command does not allow the printer name to be specified.

System action

The command is ignored and processing continues with the next command entered.

Operator response

Enter the command again without a printer name.

System programmer response

No response is necessary.

User response

No response is necessary.

APS690I **THE DISPLAY REQUEST FOR *component display_type* WAS NOT PERFORMED BECAUSE NO TCP/IP PRINTER WAS ACTIVE.**

Explanation

The request for a DISPLAY command cannot be done because no TCP/IP printers are active. *component* is the component or function, such as TCPIP, used for the DISPLAY command. *display_type* is the type of display, such as STATUS, requested from the DISPLAY command.

System action

The command is ignored and processing continues with the next command entered.

Operator response

Make sure that the printer for which you want to issue the command is active and enter the command again.

System programmer response

No response is necessary.

User response

No response is necessary.

APS691I **NOT ENOUGH STORAGE TO PROCESS COMMAND QUEUES – STORAGE REQUESTED = *storage requested*, RETURN CODE = *return code*.**

Explanation

More storage was required to process the command queues, but this storage was not available. The return code is from the GETMAIN macro.

System action

The command is ignored and processing continues with the next command entered.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Increase the REGION parameter on the startup procedure.

User response

No response is necessary.

APS692I	THE QEDIT REQUEST WAS UNSUCCESSFUL – RETURN CODE (<i>return code</i>).
----------------	---

Explanation

An MVS QEDIT request to change the number of requests that can be queued for this FSS was unsuccessful. The return code is the code returned by the QEDIT macro.

System action

The operator interface is ended with a memory dump.

Operator response

Inform your system programmer that this error occurred.

System programmer response

For more information about the return codes from the QEDIT macro, see [z/OS MVS Diagnosis: Tools and Service Aids](#).

User response

No response is necessary.

APS693I	THE MVS STOP COMMAND IS NOT VALID FOR THE PSF OPERATOR INTERFACE.
----------------	--

Explanation

An MVS STOP command was entered for the PSF operator interface. The PSF operator interface processes only the MVS MODIFY command.

System action

The command is ignored and processing continues with the next command entered.

Operator response

Use the MVS MODIFY command to enter PSF commands.

System programmer response

No response is necessary.

User response

No response is necessary.

APS694I	<i>system function</i> UNSUCCESSFUL FOR MODULE <i>module name</i>, RETURN CODE <i>return code</i> – MODULE (<i>issuing module</i>).
----------------	--

Explanation

A system function was used to do some task for the operator interface. The function returned a nonzero return code.

System action

Processing ends with an abend or error message. A subsequent PSF message notifies the operator of the action taken.

Operator response

Inform your system programmer that this error occurred.

System programmer response

For information about the return code, see [z/OS MVS Diagnosis: Tools and Service Aids](#). If a memory dump was provided, see Chapter 2, “System completion codes and PSF abend reason codes,” on page 613.

User response

No response is necessary.

APS695I	FREEMAIN UNSUCCESSFUL FOR SUBPOOL <i>subpool</i>, RETURN CODE <i>return code</i> – MODULE (<i>issuing module</i>).
----------------	---

Explanation

The FREEMAIN was unsuccessful. It returned a nonzero return code.

System action

Processing ends with an abend or an error message. A subsequent PSF message notifies the operator of the action taken.

Operator response

Inform your system programmer that this error occurred.

System programmer response

For information about the return code, see *z/OS MVS Diagnosis: Tools and Service Aids*. If a memory dump was provided, see Chapter 2, "System completion codes and PSF abend reason codes," on page 613.

User response

No response is necessary.

APS696I **PRINTER NAME CANNOT BE SPECIFIED FOR KEYWORD *keyword* IN COMMAND *command*.**

Explanation

The printer name was specified for command *command*, but keyword *keyword* specified with this command does not allow the printer name to be specified.

System action

The command is ignored and processing continues with the next command entered.

Operator response

Enter the command again without a printer name.

System programmer response

No response is necessary.

User response

No response is necessary.

APS697I **PRINTER NAME IS REQUIRED FOR KEYWORD *keyword* IN COMMAND *command*.**

Explanation

The printer name was not specified with the keyword *keyword* used in command *command*.

System action

The command is ignored and processing continues with the next command entered.

Operator response

Enter the command again, with the printer name.

System programmer response

No response is necessary.

User response

No response is necessary.

APS698I **THE DISPLAY REQUEST FOR *component display_type* FOR PRINTER *printer_name* IS NOT VALID – THIS PRINTER IS *attachment*, HOWEVER, A TCP/IP PRINTER IS REQUIRED.**

Explanation

The request for a DISPLAY command cannot be done because the printer for which it was requested was not TCP/IP-attached. The *component* is the component or function, such as TCPIP, used for the DISPLAY command. The *display_type* is the type of display, such as STATUS, requested from the DISPLAY command. The *attachment* is the type of attachment for the printer, which can be CHANNEL-ATTACHED, SNA-ATTACHED or UNKNOWN-ATTACHMENT.

System action

The command is ignored and processing continues with the next command entered.

Operator response

Enter the command for a printer that is TCP/IP attached.

System programmer response

No response is necessary.

User response

No response is necessary.

APS699I **TCP/IP DISPLAY STATUS**

Explanation

This message displays the TCP/IP status. To interpret the output, see *PSF for z/OS: Diagnosis*.

System action

This message is displayed when requested. PSF processing continues.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

No response is necessary.

APS700 to APS799

APS700I **THE ERROR SENSE BYTES 0–5 = error sense bytes 0–5, XP POSITION = xp position, YP POSITION = yp position, BUFFER OFFSET = printer buffer offset, PRINTER STATE = printer state, COMMAND= channel command, ERROR ID TYPE = error identification type, ERROR ID = error identification, COPY GROUP = code page, SENSE BYTES 18–23 = error sense bytes 18–23.**

Explanation

This message formats and presents the 24 printer-sense bytes that were reported to PSF by a 3800 printer for a non-position check I/O error. A primary message that describes the specific I/O error accompanies this message. The primary message is sufficient for diagnosing and resolving a user error. This detailed sense byte message is intended for use by the system programmer or the IBM Support Center in diagnosing hardware or PSF logic errors.

- *Error sense bytes 0–5* are the first 6 bytes in the sense data, reported in hexadecimal. These bytes are used to identify the specific I/O error:
 - Byte 0—Error group
 - Byte 1—Check code or status code
 - Byte 2—Recovery Action code for this error condition
 - Byte 3—Dynamic conditions
 - Byte 4—X'00', or same as sense byte 1 or X'DE'
 - Byte 5—Depends on format of sense that is issued
- *Xp position* is the print position on the X-axis at the time of the error, stated in pels. This information was obtained from bytes 6 and 7 of the sense data.

- *Yp position* is the print position on the Y-axis at the time of the error, stated in pels. This information was obtained from bytes 8 and 9 of the sense data.
- *Printer buffer offset* is the approximate number (in decimal) of the byte, in the data that is sent by the current channel command, that the printer was processing when it detected the error. This information was transformed from bytes 10 and 11 of the sense data.
- *Printer state* is the state of the printer at the time the error was detected. This information was formatted from byte 12 of the sense data.
 - X'00'—Home state
 - X'01'—Font index
 - X'02'—Font state
 - X'03'—Page state
 - X'04'—Page image state
 - X'05'—Reserved
 - X'06'—Reserved
 - X'07'—Overlay state
 - X'08'—Overlay image state
 - X'09'—Reserved
 - X'0A'—Reserved
 - X'0B'—Segment state
 - X'0C'—Segment image state
 - X'0D'—Reserved
 - X'0E'—Reserved
 - X'0F'—Compatibility mode
- *Channel command* is the channel command that was being processed at the time when the error was detected. This information was formatted from byte 13 of the sense data. If the reference manual for the 3800 printer is not available, these channel commands are also listed in *IBM System/370 Extended Architecture Reference Summary*,

GX20-0157, or in *IBM Enterprise Systems Architecture/390 Reference Summary*, SA22-7209.

- *Error identification type* identifies the type of ID entry that is displayed in bytes 15 and 16 (the error identification). This information was formatted from byte 14 of the sense data. The values are:
 - X'80'—Font-related error (bytes 15 and 16 contain font ID)
 - X'40'—Segment-related error (bytes 15 and 16 contain segment ID)
 - X'20'—Overlay-related error (bytes 15 and 16 contain overlay ID)
 - X'10'—Suppression-related error (bytes 15 and 16 contain a suppression ID)
- *Error identification* is the font ID, segment ID, overlay ID, or suppression ID, as identified by the contents of the *error identification type* value. This information was formatted from bytes 15 and 16 of the sense data.
- *Copy subgroup* is the number of the active copy group, in decimal. To determine which copy subgroup was being printed at the time of the error, find the active form definition and medium map named in the accompanying environmental messages. In the medium map is a Medium Modification Control (MMC), which specifies the medium modifications to be applied for the copy subgroup specified in the Medium Copy Count (MCC) structured field. If all the copy subgroups specify simplex printing, the value that is returned in these sense bytes refers to the nth copy subgroup listed in the MCC. Any copy subgroup that specifies duplex counts as two. This information was transformed from byte 17 of the sense data.
- *Error sense bytes 18–23*, in hexadecimal:
 - Byte 18: Last font number set from the font equivalence table.
 - Byte 19: Check group code ID used with bytes 0 and 1 to identify the error.
 - Bytes 20–23: Page ID sent with the Begin Page command.
Note: If the printer is not in Page or Page Image state, the page ID is zero.

System action

See the accompanying messages for the system action that was taken.

Operator response

No response is necessary.

System programmer response

If the accompanying messages are not sufficient to identify the problem, use the sense data to analyze the problem. For more information about printer sense bytes and the specific error, see the printer publications for the printer that reported this error.

User response

If the accompanying messages are not sufficient to identify the problem, contact your system programmer.

APS701I **WHEN THE ERROR(S) REPORTED ABOVE OCCURRED, THE ACTIVE {FORMDEF MEMBER NAME = *formdef membername* | MODIFIED-DEFAULT FORMDEF MEMBER NAME = *formdef membername* | FORMDEF TOKEN NAME = *formdef tokename* | FORMDEF DATA SET NAME = *formdef datasetname* | PAGEDEF MEMBER NAME = *pagedef membername* | MODIFIED-DEFAULT PAGEDEF MEMBER NAME = *pagedef membername* | PAGEDEF TOKEN NAME = *pagedef tokename* | PAGEDEF DATA SET NAME = *pagedef datasetname* | FORM ENVIRONMENT GROUP NAME = *form environment groupname* | ACTIVE ENVIRONMENT GROUP NAME = *active environment groupname* | MEDIUM MAP TOKEN NAME = *mediummap tokename* | DATAMAP TOKEN NAME = *datamap tokename* | DATAMAP TRANSMISSION SUBCASE TOKEN NAME = *subcase tokename* | CODE PAGE NAME = *codepage name* | FONT NAME = *font name* | TRANSMISSION NUMBER IN ERROR WAS = *transmission number* | PAGE NUMBER IN ERROR WAS = *page number* | PRESENTATION OBJECT RESOURCE NAME = *resource name*}.**

Explanation

The page information and object names that were active at the time of the error are presented in this message. A subset of the pages and names that are listed in the message is associated with each error.

System action

Printing of the page or data set containing the error ends. Processing continues.

Operator response

No response is necessary.

System programmer response

To determine an appropriate response, see the specific error conditions described in the accompanying messages.

User response

To determine an appropriate response, see the specific error conditions described in the accompanying messages.

APS702I THE PRINT POSITION EXTENDS OFF THE LOGICAL PAGE.

Explanation

The print position exceeded the boundaries of the logical page to the right, bottom, left, or top. The direction in which the print position was off the page is relative not to the logical page, but to the paper as it moves through the printer. For example, the top of the sheet is the perforated edge that leads through the printer.

This error was reported because DATAACK=UNBLOCK or BLKCHAR was specified in the OUTPUT JCL statement or the PRINTDEV JCL statement in the PSF initialization procedure or Print error reporting was specified as All or Character in the Printer Inventory. Print-error markers are printed on the page that contains the error to indicate the position and the direction in which this position error occurred.

The error was caused by one or more of these:

- More characters were transmitted than can fit on a line in the logical page.
- More lines were transmitted than can fit on the logical page.
- The font that is selected from the form definition or defined either in the page definition or in the table reference character (TRC) caused the data to exceed the logical page.
- A positioning text-control sequence (Absolute Move Inline [AMI], Absolute Move Baseline [AMB], Relative Move Inline [RMI], or Relative Move Baseline [RMB]) positioned the print position outside of the physical page. The text-control sequence is in a Presentation Text Data (PTX) structured field or was generated by PSF from a page definition. The PTX structured field

might be contained in a MO:DCA document, a presentation text object, an overlay, or a page segment; or it might be embedded in a data set containing line data.

The message that contains the sense data that accompanies this message identifies the Xp and Yp position at the time of the error.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. The page in error is printed with print-error markers to indicate the position and direction of the positioning errors. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If your printed output would be acceptable, you can resubmit the print request, specifying BLOCK or BLKPOS for the DATAACK keyword on the JCL OUTPUT statement. For more information about how to code this keyword, see *PSF for z/OS: User's Guide*.

If you want to correct the source of the problem, and if you were printing MO:DCA data, check the current print position and either the characters per line, the lines per page, or both. Use a different font, if necessary, so that the print position is inside the printable area. Correct the size of the logical page so that it contains the print position. If you created the structured fields for the MO:DCA data, check the PTX structured field for positioning outside of the page.

If you want to correct the source of the problem, and if you were printing a data set containing line data, you can change the font selected from the page definition or the CHARS keyword in the JCL statements to a smaller font. If you are using a page definition and you created its structured fields, check the print-positioning values in the Line Descriptor (LND) structured field, and correlate them with the number

of printable characters per line and the number of lines per page. You can also increase the logical page size by changing the Page Descriptor (PGD) structured field in the page definition.

If you want to correct the source of the problem, and if you were printing a data set containing line data with embedded structured fields, check the PTX structured field for positioning outside of the page.

APS703I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A CFI OR MCF STRUCTURED FIELD CONTAINS FONT SECTION IDENTIFIERS WHICH ARE NOT IN ASCENDING ORDER.**

Explanation

The coded font section identifiers in the Coded Font Index (CFI) structured field are not in ascending order. The CFI structured field is in the coded font.

System action

The printer you were using might try to print the page that contains the error, or might print only part of the page. If the page contains any positioning errors, print-error markers might be included on the printed page. PSF stops processing and printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured fields. If the structured field has no error, the error might be a printer logic error or a PSF error. If you used a program to create the structured fields for the font, contact your system programmer.

APS704I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE IMAGE COLOR VALUE SPECIFIED IS NOT VALID OR IS UNSUPPORTED.**

Explanation

The image color value that is specified is not valid or is unsupported by this printer. The image color value is specified on any of these structured fields:

- The IM Image Input Descriptor (IID).
- The Image Data Descriptor (IDD) for IOCA images.

The image or image cell might be contained in an overlay, a page segment, or MO:DCA data. It might also be embedded in a data set containing line data by using a Begin Image (BIM) structured field.

System action:

Operator response:

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response:

APS705I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE X- OR Y-COORDINATE FOR A PAGE OVERLAY IS NOT VALID OR IS UNSUPPORTED.**

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The X-coordinate or Y-coordinate for a page overlay is not valid or is unsupported.
2. The Overlay Type parameter in an Include Overlay (IO) command is not valid or is unsupported (possible logic error).

If the overlay that contains the error is a secure overlay, this condition was caused by a PSF logic error. If the overlay that contains the error is not a secure overlay, the coordinates are specified in the Include Page Overlay (IPO) structured field. The IPO structured field might be in the MO:DCA data or a page definition, or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves a secure overlay, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center. If the error does not involve a secure overlay, and if an IBM licensed program was used to create the structured fields for the print data set with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If the error involves a secure overlay, notify your system programmer of this error. If you created the structured fields for the print data set, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set, contact your system programmer.

AP5706I

A PARAMETER VALUE IN A FORMDEF RESOURCE IS NOT VALID OR UNSUPPORTED: THE MEDIUM FINISHING CONTROL STRUCTURED FIELD SPECIFIES AN INCORRECT OR UNSUPPORTED FINISHING OPERATION REFERENCE CORNER AND EDGE FOR THIS FINISHER.

Explanation

The reference corner and edge field (byte 5) in a Finishing Operation triplet (X'85') contains an incorrect or unsupported value for this finisher.

Finishing Operation triplets are specified in the Medium Finishing Control (MFC) structured field. The MFC is specified in the Document Environment Group of the form definition or in a Medium Map.

System action

Reporting of this exception can be controlled by the Finishing Fidelity triplet in the Presentation Fidelity Control (PFC) command. The PFC command is contained in a form definition.

When the Finishing Fidelity triplet sets the continuation rule to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and the data set is marked unprintable. PSF releases the current data set back to JES and requests that it is held by the system unless PRTEROR=QUIT was specified on the OUTPUT statement.

When the Finishing Fidelity triplet sets the continuation rule to DO NOT STOP (X'02'), one of these occurs:

- If the printer supports the PFC Finishing Fidelity triplet and if the REPORT field is set to REPORT (X'01'), the printer reports this exception. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.
- If the printer supports the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.
- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer reports this exception but PSF does not issue the error message. The printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to REPORT (X'01'), the printer reports this exception and PSF issues the error message. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the MFC with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If the output is not acceptable:

- Verify that you requested the appropriate form definition for the finishing operation intended.
- Submit the print request to a printer that can do the finishing operation.
- If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS707I A HARDWARE ERROR WAS DETECTED WHILE DATA WAS BEING TRANSFERRED TO THE PRINTER.

Explanation

While a data set was being processed, the printer presented a command reject I/O error that indicates that the data transmission came to an abnormal end during a fast-buffer-release operation. For more

information about this error, see the printer publications for the printer that reported this error.

System action

PSF stops processing the data set being processed at the time of the error and marks it unprintable. PSF releases the current data set back to JES and requests that it is held by the system unless PRTEROR=QUIT is specified on the OUTPUT statement.

Operator response

If the data set was held by the system, a JES message is displayed on the console. For a JES command to release the data set for printing, see the publication that contains JES commands for your operating system.

System programmer response

If the error condition persists, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

If the data set was held by the system, consult the system operator to release the data set for printing. If PSF stopped processing the data set but it was not held by the system, resubmit the data set for printing. If the error condition persists, consult your system programmer.

APS708I A CHARACTER IN THE PRINT DATA IS NOT DEFINED FOR THE FONT.

Explanation

One or more of these conditions occurred:

- An undefined character or a character that is not valid is detected in Write Bar Code (WBC) command bar code data.
- An undefined character is detected in the font specified for text, bar code human-readable interpretation (HRI), or graphics character-string data.
- An undefined character is detected in Presentation Text (PTX) command data at the quality level specified.

When a code page is used, the flag byte parameter in either the Code Page Control (CPC) or a repeating group of the Code Page Index (CPI) structured field had the undefined bit set for a code point in the text data that was to be printed. The CPC and CPI structured fields are in the code page. This error occurred because DATAACK=UNBLOCK or BLKPOS was specified in the OUTPUT JCL statement or the

PRINTDEV JCL statement in the PSF initialization procedure or Print error reporting was specified as All or Character in the Printer Inventory. One of these conditions occurred:

- The code page did not include the code point, and the default character, which is specified by the CPC, had the not valid flag on.
- The character that is assigned to this code point did not exist in the character set, and the default character, which is specified by the CPC, had the not valid flag on.
- The code point, which is specified by the CPI structured field, had the not valid flag on.

For a Data-Object font used without a code page, a character was not defined for a code point. In this case, a special default character, such as Glyph Index 0 for a TrueType or OpenType font, is substituted for the missing character.

Note: In the formatted sense message (APS830I), the Element Identifier (bytes 16-17) contains the code point that caused the error. For double-byte fonts, byte 16 contains the section ID and byte 17 contains the second byte of the code point. For single-byte fonts, byte 17 contains the code point.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the code page with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If bytes 12-13 in the formatted sense message (APS830I) are COMMAND= 'D681'x (WBC), the error must be corrected in the application data; not by setting a DATAACK value. Contact the data owner to correct this error. Otherwise, to eliminate this error message from your output, you can resubmit the print request by specifying BLOCK or BLKCHAR for the DATAACK keyword on the JCL OUTPUT statement. For more information about how to code this keyword, see *PSF for z/OS: User's Guide*.

If you want to correct the source of the problem, you first need to identify which character in which font contains the error. If the printer returned the information about the incorrect character, check these:

- Immediately following this message (APS708I) is a formatted sense message (APS830I). The Element Identifier field in this message contains the code point in which the error occurs, or zeros if the printer did not return the information.
- To determine which code page and font have this incorrect code point, check the APS701I messages. These are the environmental messages for this page. If the printer returned the information, one of the APS701I messages provides the *active code page name* and the *active character set name*.

Ensure that the code point in the print data is correct. If the code point is incorrect and you created the structured fields for the code page, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information on the correct format of the referenced structured field. If you used a program to create the structured fields for the code page, consult your system programmer.

APS709I

DATA IN A FONT RESOURCE IS NOT VALID: THE FONT PATTERN DATA COUNT PARAMETER VALUE IN THE FNC STRUCTURED FIELD IS NOT VALID.

Explanation

The Pattern Data Count parameter value in the Font Control (FNC) structured field is not valid. The FNC structured field is contained in the font character set.

System action

PSF stops processing and printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is

defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a printer logic error or a PSF error. If you used a program to create the structured fields for the font, contact your system programmer.

APS710I	DATA IN A FONT RESOURCE IS NOT VALID: THE DOUBLE-BYTE FONT CONTROL DATA WAS NOT THE SAME BETWEEN DOUBLE-BYTE FONT SECTIONS.
----------------	--

Explanation

The printer detected this error while it was processing the font sections of a specified double-byte font. Except for two parameters, font sections are required to have identical data. The control data was not the same for one or more of the sections specified for the font. The font-control parameters must have unique data, except for these:

- Pattern Data Count in the Font Control (FNC) structured field
- Flag Byte in the Font Orientation (FNO) structured field

System action

PSF stops processing and printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a printer logic error or a PSF error. If you used a program to create the structured fields for the font, contact your system programmer.

APS711I	A PAPER JAM OR A POST PROCESSOR RESYNCHRONIZATION OCCURRED ON THE PRINTER DURING THE TRANSMISSION OF THIS DATA SET. PARTIAL OR DUPLICATE PAGES MAY BE PRINTED.
----------------	---

Explanation

The paper in the printer was jammed, or a post processor was resynchronized. The printer detected and reported an asynchronous intervention-required error with an action code of 'X'08' (sense byte 2). For more information about this error, see the printer publications for the printer that reported the error.

System action

PSF resends pages to the printer, starting from the jam recovery page counter plus 1. PSF might print this message on a separate sheet in the data set to mark the position at which the recovery from this error was started. Pages might be duplicated during the recovery. If repositioning is not supported in the current environment, PSF stops processing the data set.

Operator response

No response is necessary.

System programmer response

If the error condition persists, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

The printed output might be acceptable. If any pages are duplicated, you might want to resubmit the print request. If the error condition persists, consult your system programmer.

APS712I **A PRINTER PROCESS POWER ERROR OCCURRED DURING THE TRANSMISSION OF THIS DATA SET. PARTIAL OR DUPLICATE PAGES MAY BE PRINTED.**

Explanation

An error occurred with the process power of the printer. The printer detected and reported an asynchronous equipment check with an action code of X'0B' (sense-byte 2). For more information about this error, see the printer publications for the printer that reported this error.

System action

PSF resends pages to the printer, starting from the jam recovery page counter plus 1. PSF prints this message on a separate sheet in the data set to mark the position where the recovery from this error was started. Pages might be duplicated during the recovery. If repositioning is not supported in the current environment, PSF stops processing the data set. PSF also prints this message at the end of the print data set to indicate that this message was printed within the print data set.

Operator response

No response is necessary.

System programmer response

If the error condition persists, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

The printed output might be acceptable. If any pages were duplicated, you might want to resubmit the print request. If the error condition persists, consult your system programmer.

APS713I **A PRINTER UNIT CHECK AFTER AN INITIAL MICROCODE LOAD OCCURRED DURING THE TRANSMISSION OF THIS DATA SET. PARTIAL OR DUPLICATE PAGES MAY BE PRINTED.**

Explanation

The printer presented a unit check to PSF with an action code of X'0D' (sense-byte 2) to indicate that an automatic or manual initial microcode load (IML) operation is successfully completed. For more information about this error, see the printer publications for the printer that reported this error.

System action

Pages in the printer's page buffer and all resources in the printer are lost. If the printer is in the middle of finishing a group of pages, that finishing operation is not done. The printer resets its page counters to zero. PSF resends pages to the printer, starting from the committed page counter. PSF prints this message on a separate sheet in the data set to mark the position where the recovery from this error was started. PSF also prints this message at the end of the data set to indicate that this message was printed within the data set. Pages might be duplicated during the recovery. If repositioning is not supported in the current environment, PSF stops processing the data set.

Operator response

No response is necessary.

System programmer response

If the error condition persists, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

The printed output might be acceptable. If any pages were duplicated, you might want to resubmit the print request. If the error condition persists, consult your system programmer.

APS714I **AN ERROR OCCURRED WHILE PROCESSING AN ELECTRONIC OVERLAY OR A BASE PAGE IN THE PRINTER ACCUMULATOR.**

Explanation

The printer detected and reported a data check with an action code of X'10' (sense byte 2). This message indicates one of these:

- The page or paper size is not compatible with accumulator data stored earlier.
- The base page was moved to accumulator storage and needs to be reloaded.
- The raster overlay in the accumulator storage needs to be reloaded.

System action

PSF causes the printer to discard the printer's buffered data and to delete all overlays, page segments, and fonts. On the first occurrence of this error, the message is printed on a separate sheet in the data set to mark the position before recovery starts. PSF recovers by resending pages to the printer, starting from the last known committed page counter plus 1. On the second occurrence of this error, the message is printed at the end of the message data set, and PSF stops processing the data set at the committed page counter plus 1.

Operator response

No response is necessary.

System programmer response

If the error condition persists, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

If the output is unacceptable, resubmit the print request. The overlay or page segment might need to be modified. If the error condition persists, consult your system programmer.

APS715I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A TEXT SUPPRESSION DID NOT END BEFORE THE PAGE ENDED.

Explanation

The printer detected a Begin Suppression (BSU) text control while it was processing the page. The corresponding End Suppression (ESU) text control was not received before the page was completed. The text-control sequence is in a Presentation Text Data (PTX) structured field or was generated by PSF from a page definition. The PTX structured field might be contained in a MO:DCA document, a presentation text object, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document, a presentation text object, an overlay, or a page segment and you created the structured fields in the object that contains the error, correct the text-control sequence in the Presentation Text Data (PTX) structured field. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the MO:DCA document, a presentation text object, overlay, or page segment, contact your system programmer. If you are printing a data set containing line data with embedded structured fields, correct the text-control sequence in the PTX structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you are printing a data set containing line data without embedded structured fields, the error might be a PSF or printer logic error.

APS716I FONT CONTAINS INCORRECT DATA: CHARACTER BOX SIZE X-EXTENT OR Y-EXTENT PARAMETER NOT VALID.

Explanation

The printer detected an incorrect value for the character-box size specified either in the Character Box X-Extent or in the Character Box Y-Extent parameter in the Font Control (FNC) structured field of the font that is processed.

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of an error condition that caused the exception to be reported. For error sense X'0226..02' (written as Byte 0 Byte1...Byte 19), one or both of these conditions occurred:

1. The character box X size that is specified in the Font Control (FNC) structured field of the font is not valid or is unsupported, or is incompatible with the specified font.
2. The character box X size that is specified in the FNC structured field of the font is greater than the maximum X-box size.

For error sense X'0227..02' (written as Byte 0 Byte1...Byte 19), one or both of these conditions occurred:

1. The character box Y size that is specified in the Font Control (FNC) structured field of the font is not valid or is unsupported, or is incompatible with the specified font.
2. The character box Y size that is specified in the FNC structured field of the font is greater than the maximum X-box size.

The FNC structured field is in the font character set.

System action

PSF stops processing and printing the data set that uses the font that contains the error.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a printer logic error or a PSF error. If you used a program to create the structured fields for the font, contact your system programmer.

APS717I THE ERROR SENSE BYTES 0-23 = error sense bytes 0-23.

Explanation

This message presents the 24 printer sense bytes that were reported to PSF at the time of an I/O error.

System action

See the accompanying messages for the system action that was taken.

Operator response

Inform your system programmer that this error occurred.

System programmer response

If the accompanying messages are not sufficient to identify the problem, use the sense data to analyze the problem. For more information about printer sense bytes and the specific error, see the printer publications for the printer that reported this error. If the error condition persists, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

If the accompanying messages are not sufficient to identify the problem, contact your system programmer.

APS718I	DATA IN A FONT RESOURCE IS NOT VALID: THE UNIFORM CHARACTER BOX SIZE X-EXTENT AND Y-EXTENT PARAMETER VALUES ARE NOT EQUAL IN THE FNC STRUCTURED FIELD.
----------------	---

Explanation

The printer detected that the width and length values for the character-box size for a font that is specified to be non-uniform were not equal (for example, the font has variable character-box sizes). The character box X-Extent and the character box Y-Extent, which is specified in the Font Control (FNC) structured field, must be equal for non-uniform fonts. The Uniform Character Box Size parameter in the FNC structured field indicates whether the character box size of a font is uniform or non-uniform. The FNC structured field is contained in the font character set.

System action

PSF stops processing and printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a printer logic error or a PSF error. If you used a program to create the structured fields for the font, contact your system programmer.

APS719I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE INPUT DATA SELECTED A DOUBLE-BYTE FONT SECTION IDENTIFIER THAT IS NOT WITHIN THE RANGE OF THE FONT SPECIFIED TO PRINT THE DATA.**

Explanation

While the printer was processing double-byte data, it detected a font section identifier that cannot be used. Either the coded font that was specified to print the data did not contain a section with that identifier, or the section identifier was not in the valid range. The font section identifier is the first byte of the 2-byte character code in a double-byte data stream.

Note: In the formatted sense message (APS830I), the Element Identifier (bytes 16-17) contains the code point that caused the error. For double-byte fonts, byte 16 contains the section ID and byte 17 contains the second byte of the code point.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set

with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

Verify that the appropriate font was selected and that the section identifier coded in the print data for the character is valid. Valid ranges for font section identifiers are described in *Advanced Function Presentation: Programming Guide and Line Data Reference*. If the font section identifier is valid, ensure that a font section with that identifier is included in the double-byte coded font that you want to use.

APS720I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE SET VARIABLE SPACE INCREMENT TEXT CONTROL IS OUTSIDE THE VALID RANGE.**

Explanation

The Set Variable Space Increment (SVI) text-control sequence is outside the valid range. The text-control sequence is in a Presentation Text Data (PTX) structured field or was generated by PSF from a page definition. The PTX structured field might be contained in a MO:DCA document, a presentation text object, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document, an overlay, or a page segment and you created the structured fields in the object that contains the error, correct the text-control sequence in the Presentation Text Data (PTX) structured field. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the MO:DCA document, presentation text object, overlay, or page segment, contact your system programmer. If you are printing a data set containing line data with embedded structured fields, correct the text-control sequence in the PTX structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you are printing a data set containing line data without embedded structured fields, the error might be a PSF or printer logic error.

APS721A **A PRINTER PROCESS POWER ERROR OCCURRED ON PRINTER DEVICE = prtnnnn. SENSE BYTES 0-23 = error sense bytes 0-23. PARTIAL OR DUPLICATE PAGES MAY BE PRINTED.**

Explanation

The printer detected and reported an equipment check error with an action code of X'0B' (sense-byte 2). The printer that is identified by the address reported in this message requires the operator to restore power to the printer process. For more information about this error, or to interpret the printer sense bytes, see the printer publications for the printer that reported this error.

System action

After the printer is readied, PSF resends pages to the printer, starting from the jam recovery page counter

plus 1. PSF prints a message on a separate sheet in the data set to mark the position where the recovery from this error was started. PSF also prints the same message at the end of the data set to indicate that the message was printed within the data set. Pages might be duplicated during the recovery. If repositioning is not supported in the current environment, PSF stops processing the data set.

Operator response

Restore power to the printer and press RESET or READY.

System programmer response

If the error condition persists, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

The printed output might be acceptable. If any pages were duplicated, you might want to resubmit the print request. If the error condition persists, consult your system programmer.

APS722I **A PRINTER SUBSYSTEM RUN RESET WITH A POSSIBLE PAPER JAM OCCURRED DURING THE TRANSMISSION OF THIS DATA SET. PARTIAL OR DUPLICATE PAGES MAY BE PRINTED.**

Explanation

The printer detected and reported an asynchronous intervention-required error with an action code of X'08' (sense-byte 2). An unexpected RESET command was received and might have caused the printer's paper path to jam. For more information about this error, see the printer publications for the printer that reported this error.

System action

PSF resends pages to the printer, starting from the jam recovery page counter plus 1. PSF prints this message on a separate sheet in the data set to mark the position where the recovery from this error was started. Pages might be duplicated during the recovery. If repositioning is not supported in the current environment, PSF stops processing the data set.

Operator response

See the operator's guide for the printer that reported this error, and clear the paper jam in the printer. PSF

assumes that pages between the jam recovery page counter and the stacked page counter are not damaged by the paper jam and do not need to be reprinted. If any pages between these two page counters need to be reprinted, use the JES BACKSPACE command.

System programmer response

If the error condition persists, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

The printed output might be acceptable. If any pages were duplicated, you might want to resubmit the print request. If the error condition persists, consult your system programmer.

APS723I	DATA IN A FONT RESOURCE IS NOT VALID: THE UNIFORM CHARACTER INCREMENT PARAMETER IN THE FNO STRUCTURED FIELD IS NOT VALID.
----------------	--

Explanation

The Uniform Character Increment parameter in the Font Orientation (FNO) structured field is not valid. The FNO structured field is contained in the font character set.

System action

PSF stops processing and printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* and *Mixed Object*

Document Content Architecture Reference for more information about the structured field. If the structured field has no error, the error might be a printer logic error or a PSF error. If you used a program to create the structured fields for the font, contact your system programmer.

APS724I	{RPS WCS CPS FONT} PRINTER STORAGE LIMIT WAS EXCEEDED WHILE LOADING OBJECTS FOR THE PAGE. THE PAGE RETRY ATTEMPT MAY CAUSE A PARTIAL OR BLANK PAGE TO APPEAR IN THE OUTPUT.
----------------	--

Explanation

The printer detected and reported an out-of-storage print error with an action code of X'0C' (sense-byte 2). The requirement for raster-pattern storage (RPS), writable-control storage (WCS), compressed-pattern storage (CPS), or font storage (FONT) exceeded the available storage resources of the printer.

This message is accompanied by a message that presents the printer sense bytes. These sense bytes are unique to each printer. See the printer publications for the printer that reported this error.

System action

PSF recovers from this out-of-storage print error by deleting all resources (for example, overlays, page segments, and fonts) that are not required for the current page that is sent to the printer. PSF then resends pages to the printer, starting from the Received Page ID. If the error condition persists, PSF issues message APS725I, skips the page that contains the error, and continues processing the current data set with the page after the page that contains the error. If repositioning is not supported in the current environment, PSF stops processing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If the printed output is not acceptable, make the page less complicated by deleting resources (for example, overlays, page segments, and fonts) or print the data set on a printer with more of the type of storage that was exceeded. For more information, see the documentation provided with the printer.

APS725I **{RPS | WCS | CPS | FONT}
PRINTER STORAGE LIMIT WAS
EXCEEDED WHILE LOADING
OBJECTS DURING A PAGE RETRY.
THE PAGE IS SKIPPED AND
PROCESSING CONTINUES ON THE
NEXT PAGE.**

Explanation

The printer detected and reported an out-of-storage error with an action code of X'0C' (sense-byte 2). The requirement for raster-pattern storage (RPS), writable-control storage (WCS), compressed-pattern storage (CPS), or font storage (FONT) exceeded the available storage resources of the printer. PSF detected that this was the second resource-constrained error for the page that contains the error. (See message APS724I.) This message is accompanied by a message that presents the printer sense bytes. These sense bytes are unique to each printer. See the printer publications for the printer that reported this error.

System action

PSF recovers from this out-of-storage printer error by skipping the page that contains the error because this is the second attempt to send it to the printer. PSF continues processing the current data set with the page after the page that contains the error. If repositioning is not supported in the current environment, PSF stops processing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If the data stream errors stopped processing of the page just before the page for which APS725I was

issued, correct the data stream errors first and resubmit the print request. The condition that caused message APS725I to be issued might be resolved after the other errors are corrected. If this situation does not apply, make the page less complicated by deleting resources (for example overlays, page segments, and fonts), or print the data set on a printer with more of the type of storage that was exceeded.

APS726I **DATA IN A FONT RESOURCE IS
NOT VALID: THE ORIENTATION
PARAMETER IN THE FNO
STRUCTURED FIELD IS NOT
VALID.**

Explanation

The Orientation parameter in the Font Orientation (FNO) structured field is not valid. The FNO structured field is contained in the font character set.

System action

PSF stops processing and printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a printer logic error or a PSF error. If you used a program to create the structured fields for the font, contact your system programmer.

APS727I **DATA IN A FONT RESOURCE IS
NOT VALID: THE UNIFORM
BASELINE OFFSET PARAMETER IN
THE FNO STRUCTURED FIELD IS
NOT VALID.**

Explanation

The Uniform Baseline Offset parameter in the Font Orientation (FNO) structured field is not valid. The FNO structured field is contained in the font character set.

System action

PSF stops processing and printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a printer logic error or a PSF error. If you used a program to create the structured fields for the font, contact your system programmer.

APS728I **DATA IN A FONT RESOURCE IS NOT VALID: THE FLAG BYTE PARAMETER IN THE FNO STRUCTURED FIELD IS NOT VALID.**

Explanation

The Font Index Number, bits 0–2 of the Flag Byte parameter, in the Font Orientation (FNO) structured field is not valid. The FNO structured field is contained in the font character set.

System action

PSF stops processing and printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is

defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a printer logic error or a PSF error. If you used a program to create the structured fields for the font, contact your system programmer.

APS729I **DATA IN A FONT RESOURCE IS NOT VALID: A PATTERN DATA ADDRESS IN AN FNM STRUCTURED FIELD IS NOT VALID.**

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The pattern data offsets in the repeating group entries in the Font Pattern Map (FNM) structured field are not in ascending order.
2. A pattern data offset in the repeating group entries in the FNM structured field points past the end of the raster data.
3. A pattern data offset in the repeating group entries in the FNM structured field points to a character pattern that extends beyond the end of the raster data.
4. A pattern data offset in the repeating group entries in the FNM structured field points into a previously defined character pattern.

The FNM structured field is in the font character set.

System action

PSF stops processing and printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a printer logic error or a PSF error. If you used a program to create the structured fields for the font, contact your system programmer.

APS730I **THE TOTAL NUMBER OF MEDIUM OVERLAYS SPECIFIED ON THE OUTPUT STATEMENT, PRINTDEV STATEMENT, IN THE PRINTER INVENTORY, AND/OR MEDIUM MAP EXCEEDS WHAT THE PRINTER CAN SUPPORT FOR ONE PHYSICAL PAGE.**

Explanation

When the number of overlays that are specified in the Medium Modification Control (MMC) structured field and the number of medium overlays that are specified on the OUTPUT, PRINTDEV, or both statements, or in the Printer Inventory are added, the total exceeds what this printer can support on a physical page (one side of a sheet). The MMC structured field is contained in the form definition.

The limit for the total number of overlays depends on the printer you use.

System action

PSF stops processing the data set that was being processed at the time of the error and marks it unprintable. PSF releases the current data set back to JES and requests that it is held by the system unless PRERROR=QUIT is specified on the OUTPUT statement.

Operator response

If you are running under Job Entry Subsystem (JES), use the JES data set release commands to release the data set to a printer that can handle a larger number of medium overlays. To find the JES command to release the data set for printing, see the publication that contains JES commands for your operating system.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

Change the output class for the next submission. Consult the system operator to release the print request to a printer that can print the total number of overlays on that page. If you do not have access to a printer that can support that number of overlays on a page, the number of overlays needs to be decreased. If you created the form definition that contains the MMC structured field, you must remove one or more of the overlays, depending on how many medium overlays were specified. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. Resubmit the print request. If the total number of user overlays and OUTPUT/PRINTDEV statement medium overlays is less than or equal to what this printer supports, the error might be a PSF logic error.

APS731I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN EMBEDDED TEXT CONTROL IS NOT VALID.**

Explanation

An incorrect text control code was found. The text control came from a Text Data (PTX) structured field or was generated by PSF from a page definition. The Presentation Text Data (PTX) structured field might be contained in a MO:DCA document, an overlay, a presentation text object, or a page segment; or it might be embedded in a data set containing line data.

Note: In the formatted sense message (APS830I), the Element Identifier (bytes 16-17) contains the unsupported or unrecognized PTOCA control sequence function type that causes this error. Byte 16 contains X'00' and byte 17 contains the function-type value.

System action

Reporting of this exception can be controlled by the Text Fidelity triplet in the Presentation Fidelity Control

(PFC) command. The PFC command is contained in a form definition.

When the Text Fidelity triplet sets the continuation rule to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and marks the data set unprintable. PSF releases the current data set back to JES and requests that it is held by the system unless PRERROR=QUIT is specified on the OUTPUT statement.

When the Text Fidelity triplet sets the continuation rule to DO NOT STOP (X'02'), one of these occurs:

- If the printer supports the PFC Text Fidelity triplet and if the REPORT field is set to REPORT (X'01'), the printer reports this exception. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.
- If the printer supports the PFC Text Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.
- If the printer does not support the PFC Text Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer reports this exception but PSF does not issue the error message. The printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.
- If the printer does not support the PFC Text Fidelity triplet and the REPORT field is set to REPORT (X'01'), the printer reports this exception and PSF issues the error message. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document, an overlay, or a page segment and you created the structured fields in the object that contains the error, correct the text-control sequence in the Presentation Text Data (PTX) structured field. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the MO:DCA document, overlay, or page segment, contact your system programmer. If you are printing a data set containing line data with embedded structured fields, correct the text-control sequence in the PTX structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you are printing a data set containing line data without embedded structured fields, the error might be a PSF or printer logic error.

AP5732I

DATA IN A FONT RESOURCE IS NOT VALID: NONMATCHING DOUBLE-BYTE FONT SECTIONS.

Explanation

For a double-byte font, many of the parameters that are specified in the Code Page Control (CPC), Font Control (FNC), and Font Orientation (FNO) must be identical for all sections with the same character rotation, or must be identical for those sections in the range X'45' through X'FE'. One or more parameters violated these rules:

1. These parameters must be the same for all sections:

- Default Graphic Character Global ID (CPC)
- Space character Section Number and Code Point (CPC)
- Variable space enable flag (CPC)
- X Unit Base (FNC)
- Y Unit Base (FNC)

2. This parameter must be the same for all sections with the same character rotation:

- Space Character Increment (FNO)

3. These parameters must be the same for all sections in the range X'45' through X'FE' with the same character rotation:

- Uniform Character Box Font flag must be set to B'1' (FNC)
- Maximum Character Box Size (FNC)
- Maximum Baseline Offset (FNO)
- Maximum Character Increment (FNO)
- Uniform baseline offset flag must be set to B'1' (FNO)
- Uniform character increment flag must be set to B'1' (FNO)
- Minimum A-space (FNO)
- Maximum baseline extent (FNO)
- Uniform A-space flag must be set to B'1' (FNO)

Note: The FNC and FNO structured fields are in the font character set. The CPC structured field is in the code page.

System action

PSF stops processing and printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a printer logic error or a PSF error. If you used a program to create the structured fields for the font, contact your system programmer.

Explanation

The X-coordinate value that is specified in the Image Block Origin parameter of an Image Output Control (IOC) structured field is outside of the valid range. The value is specified in absolute I-units. The image block or image cell might be contained in an overlay, a page segment, or a MO:DCA document. It might also be embedded in a data set containing line data by using a Begin Image (BIM) structured field.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the resource or print data set containing the image, correct the error in the referenced structured field and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the resource or print data set containing the image, contact your system programmer.

APS733I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE X COORDINATE FOR THE IMAGE BLOCK ORIGIN IS OUT OF RANGE IN AN IOC STRUCTURED FIELD.

APS734I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE Y COORDINATE FOR THE IMAGE BLOCK ORIGIN IS OUT OF RANGE IN AN IOC STRUCTURED FIELD.

Explanation

The Y-coordinate value that is specified in the Image Block Origin parameter of an Image Output Control (IOC) structured field is outside of the valid range. The value is specified in absolute B-units. The image block or image cell might be contained in an overlay, a page segment, or a MO:DCA document. It might also be embedded in a data set containing line data by using a Begin Image (BIM) structured field.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the resource or print data set containing the image, correct the error in the referenced structured field and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the resource or print data set containing the image, contact your system programmer.

APS735I **SELECTED PHYSICAL MEDIA TO BE FINISHED CANNOT BE SENT TO THE SELECTED MEDIA DESTINATION.**

Explanation

The physical media cannot be sent to the selected media destination. The printer cannot continue processing the data set.

System action

PSF stops processing and printing the data set.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Follow these steps:

1. Ensure that the input media source is valid and that it contains the appropriate media for the finishing operation that is done. The input media source can be selected in the form definition, or PSF uses the default media source for the printer.
2. Ensure that the output media destination is valid for the finishing operation that is done. The media destination can be selected on the JCL OUTPUT statement with the OUTBIN keyword, or PSF uses the default media destination.
3. Verify that you requested the appropriate form definition for the finishing operation intended.

APS736I

PARAMETERS IN A FORMDEF RESOURCE ARE INCOMPATIBLE: THE MEDIUM FINISHING CONTROL STRUCTURED FIELD SPECIFIES INCOMPATIBLE FINISHING OPERATION TRIPLETS.

Explanation

The Medium Finishing Control (MFC) structured field contains Finishing Operation triplets that are incompatible. Compatible combinations of finishing operations are specific to a particular presentation device. When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. An MFC structured field contains two or more Finishing Operation triplets that specify incompatible finishing operations.

2. A pair or more of MFC structured fields create nested Finishing Operation triplets that specify incompatible finishing operations.

The MFC is specified in the Document Environment Group of the form definition or in a Medium Map.

System action

Reporting of this exception can be controlled by the Finishing Fidelity triplet in the Presentation Fidelity Control (PFC) command. The PFC command is contained in a form definition.

When the Finishing Fidelity triplet sets the continuation rule to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and the data set is marked unprintable. PSF releases the current data set back to JES and requests that it is held by the system unless PRERROR=QUIT was specified on the OUTPUT statement.

When the Finishing Fidelity triplet sets the continuation rule to DO NOT STOP (X'02'), one of these occurs:

- If the printer supports the PFC Finishing Fidelity triplet and if the REPORT field is set to REPORT (X'01'), the printer reports this exception. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.
- If the printer supports the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.
- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'021'), the printer reports this exception but PSF does not issue the error message. The printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.
- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to REPORT (X'01'), the printer reports this exception and PSF issues the error message. PSF continues processing the current data set with the page that

follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the MFC with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If the output is not acceptable:

- Verify that you requested the appropriate form definition for the finishing operation intended.
- Submit the print request to a printer that can do the finishing operation.
- If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS737I

DATA IN A FORMDEF RESOURCE IS NOT VALID: THE X COORDINATE SPECIFIED IN THE PAGE ORIGIN PARAMETER IN A PGP STRUCTURED FIELD IS OUT OF RANGE.

Explanation

The X-coordinate value in the Page Origin parameter in the Page Position (PGP) structured field is outside of the valid range. The PGP structured field is in the form definition.

System action

PSF stops processing and printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS738I	DATA IN A FORMDEF RESOURCE IS NOT VALID: THE Y COORDINATE SPECIFIED IN THE PAGE ORIGIN PARAMETER IN A PGP STRUCTURED FIELD IS OUT OF RANGE.
----------------	--

Explanation

The Y-coordinate value in the Page Origin parameter in the Page Position (PGP) structured field is outside of the valid range. The PGP structured field is in the form definition.

System action

PSF stops processing and printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS739I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: ADDITIONAL DATA IS NEEDED TO COMPLETE EITHER AN EMBEDDED TEXT CONTROL CHAINED SEQUENCE OR A DOUBLE-BYTE FONT CHARACTER CODE.
----------------	---

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. More data is required to complete a partial control sequence or double-byte code point. The text-control sequences came from a Presentation Text Data (PTX) structured field or were generated by PSF from a page definition.
2. More Image Picture Data (IPD) structured field data is required to complete a partial image. If the original image was an IM1 image and the resolution in the IID structured field does not match the printer resolution, PSF attempts to convert the IM1 image to Image Object Content Architecture (IOCA) (if the printer supports IOCA). During this conversion process, IM1 structured fields are converted to IOCA Intelligent Printer Data Stream (IPDS) commands. This error occurs in either of these conditions:
 - A Set Home State command occurs before the entire image data is sent to the printer.
 - An error is detected while outputting image data that causes PSF to stop processing the page.

3. More Graphics Data (GAD) structured field data is required to complete a partial graphics Begin Segment Introducer or drawing order.
4. More Object container Data (OCD) structured field data is required to complete a partial object container.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing MO:DCA data, an overlay, or a page segment, and you created the structured fields in the object that contains the error, correct the appropriate structured field. For more information, see *Mixed Object Document Content Architecture Reference*. If you used a program to create the structured fields for the MO:DCA print data set, overlay, or page segment, consult your system programmer.

If you are printing a data set containing line data with embedded structured fields, correct the appropriate structured field. If the structured field has no errors, consult your system programmer.

If you are printing a data set containing line data without embedded structured fields, the error might be a PSF or printer logic error. Consult your system programmer.

APS740I DATA IN A FONT RESOURCE IS NOT VALID: THE MAXIMUM BASELINE EXTENT PARAMETER

IN THE FNO STRUCTURED FIELD IS NOT VALID.

Explanation

The Maximum Baseline Extent parameter in the Font Orientation (FNO) structured field parameter is not valid. The FNO structured field is contained in the font character set.

System action

PSF stops processing and printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a printer logic error or a PSF error. If you used a program to create the structured fields for the font, contact your system programmer.

APS741I THE UPA DIMENSIONS SPECIFIED EXCEEDED THE MAXIMUM ALLOWED.

Explanation

The sum of the Xm (or Ym) coordinate of the User Printable Area (UPA) origin and the Xm extent of the User Printable Area that is specified in the security definitions library member exceeds the maximum value that can be represented in the printer. The UPA dimensions are specified in the security definitions library.

System action

PSF stops processing and printing the data set.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot print a separator page or print error messages. Inform your system programmer that this error occurred.

System programmer response

Decrease the size of the UPA dimensions in the security definitions library member. See *PSF for z/OS: Security Guide* for information about the format of the security definitions library.

User response

Inform your system programmer that this error occurred.

APS742I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE HORIZONTAL PRINT LIMIT FOR THE LOGICAL PAGE OR MEDIUM IS NOT VALID.
----------------	--

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The X axis extent in a Page Descriptor (PGD) or Presentation Text Data Descriptor (PTD) structured field is not valid or is unsupported.
2. The X axis extent in a Medium Descriptor (MDD) structured field is not valid or is unsupported.

The PGD structured field is in the MO:DCA data, an overlay, or a page definition. The PTD might be specified in either the Object Environment Group (OEG) for the presentation text object or the Active Environment Group (AEG) for the page or overlay. The MDD structured field is in the form definition.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is

defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing MO:DCA data, an overlay, or a form definition, and you created the structured fields in the object that contains the error, change the page size in the print data set, overlay, or form definition. If you are printing MO:DCA data, an overlay, or a form definition, and you used a program to create the structured fields in the object that contains the error, change your input to that program to change the paper size. If you are printing a data set containing line data, change the page size in the page definition.

APS743I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE VERTICAL PRINT LIMIT FOR THE LOGICAL PAGE OR MEDIUM IS NOT VALID.
----------------	--

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The Y axis extent in a Page Descriptor (PGD) or Presentation Text Data Descriptor (PTD) structured field is not valid or is unsupported.
2. The Y axis extent in a Medium Descriptor (MDD) structured field is not valid or is unsupported.

The PGD structured field is in the MO:DCA data, an overlay, or a page definition. The PTD might be specified in either the Object Environment Group (OEG) for the presentation text object or the Active Environment Group (AEG) for the page or overlay. The MDD structured field is in the form definition.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the

printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing MO:DCA data, an overlay, or a form definition, and you created the structured fields in the object that contains the error, change the page size in the print data set, overlay, or form definition. If you are printing MO:DCA data, an overlay, or a form definition, and you used a program to create the structured fields in the object that contains the error, change your input to that program to change the paper size. If you are printing a data set containing line data, change the page size in the page definition.

APS746I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE WIDTH PARAMETER OF A DRAW INLINE RULE OR DRAW BASELINE RULE TEXT CONTROL IN A PTX STRUCTURED FIELD IS NOT VALID.**

Explanation

The Width parameter in the Draw Inline Rule (DIR) or Draw Baseline Rule (DBR) text-control sequence either is greater than the maximum width or is less than the minimum width. The text-control sequence is in a Presentation Text Data (PTX) structured field. The structured field might be contained in a MO:DCA document, an overlay, or a page segment; or it might be embedded in a data set containing line data.

This message is accompanied by a message that presents the printer sense bytes. These sense bytes are unique to each printer. See the printer publications for the printer that reported this error.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document, an overlay, or a page segment and you created the structured fields in the object that contains the error, correct the text-control sequence in the Presentation Text Data (PTX) structured field. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the MO:DCA document, overlay, or page segment, contact your system programmer. If you are printing a data set containing line data with embedded structured fields, correct the text-control sequence in the PTX structured field. If the PTX has no errors, the error might be a PSF or printer logic error.

APS747I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE WIDTH PARAMETER OF A DRAW INLINE RULE TEXT CONTROL IN A PTX STRUCTURED FIELD IS LESS THAN THE MINIMUM WIDTH.**

Explanation

The Width parameter in the Draw Inline Rule (DIR) text-control sequence is less than the minimum width. The text-control sequence is in a Presentation Text Data (PTX) structured field. The structured field might

be contained in a MO:DCA document, an overlay, or a page segment; or it might be embedded in a data set containing line data.

This message is accompanied by a message that presents the printer sense bytes. These sense bytes are unique to each printer. See the printer publications for the printer that reported this error.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see [PSF for z/OS: Diagnosis](#) for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document, an overlay, or a page segment and you created the structured fields in the object that contains the error, correct the text-control sequence in the Presentation Text Data (PTX) structured field. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the MO:DCA document, overlay, or page segment, contact your system programmer. If you are printing a data set containing line data with embedded structured fields, correct the text-control sequence in the PTX structured field. If the PTX has no errors, the error might be a PSF or printer logic error.

APS748I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE LENGTH PARAMETER OF A DRAW INLINE RULE TEXT CONTROL IN A

PTX STRUCTURED FIELD IS OUTSIDE THE VALID RANGE.

Explanation

The Length parameter in the Draw Inline Rule (DIR) text control is outside the valid range. The text-control sequence is in a Presentation Text Data (PTX) structured field. The PTX structured field might be in the MO:DCA data, an overlay, or a page segment; or it might be embedded in a data set containing line data.

This message is accompanied by a message that presents the printer sense bytes. These sense bytes are unique to each printer. See the printer publications for the printer that reported this error.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see [PSF for z/OS: Diagnosis](#) for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document, an overlay, or a page segment and you created the structured fields in the object that contains the error, correct the text-control sequence in the Presentation Text Data (PTX) structured field. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the MO:DCA document, overlay, or page segment, contact your system programmer. If you are printing a data set containing line data with embedded structured fields,

correct the text-control sequence in the PTX structured field. If the PTX has no errors, the error might be a PSF or printer logic error.

APS749I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE WIDTH PARAMETER OF A DRAW BASELINE RULE TEXT CONTROL IN A PTX STRUCTURED FIELD EXCEEDS THE MAXIMUM WIDTH.

Explanation

The Width parameter in the Draw Baseline Rule (DBR) text control exceeds the maximum width. The text-control sequence is in a Presentation Text Data (PTX) structured field. The structured field might be contained in a MO:DCA document, an overlay, or a page segment; or it might be embedded in a data set containing line data.

This message is accompanied by a message that presents the printer sense bytes. These sense bytes are unique to each printer. See the printer publications for the printer that reported this error.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document, an overlay, or a page segment and you created the structured fields in the object that contains the error, correct the text-control sequence in the Presentation Text Data (PTX)

structured field. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the MO:DCA document, overlay, or page segment, contact your system programmer. If you are printing a data set containing line data with embedded structured fields, correct the text-control sequence in the PTX structured field. If the PTX has no errors, the error might be a PSF or printer logic error.

APS750I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE WIDTH PARAMETER OF A DRAW BASELINE RULE TEXT CONTROL IN A PTX STRUCTURED FIELD IS LESS THAN THE MINIMUM WIDTH.

Explanation

The Width parameter in the Draw Baseline Rule (DBR) text control is less than the minimum width. The text-control sequence is located in a Presentation Text Data (PTX) structured field. The structured field might be contained in a MO:DCA document, an overlay, or a page segment; or it might be embedded in a data set containing line data.

This message is accompanied by a message that presents the printer sense bytes. These sense bytes are unique to each printer. See the printer publications for the printer that reported this error.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS:*

Diagnosis for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document, an overlay, or a page segment and you created the structured fields in the object that contains the error, correct the text-control sequence in the Presentation Text Data (PTX) structured field. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the MO:DCA document, overlay, or page segment, contact your system programmer. If you are printing a data set containing line data with embedded structured fields, correct the text-control sequence in the PTX structured field. If the PTX has no errors, the error might be a PSF or printer logic error.

APS751I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE LENGTH PARAMETER OF A DRAW BASELINE RULE TEXT CONTROL IN A PTX STRUCTURED FIELD IS OUTSIDE THE VALID RANGE.

Explanation

The Length parameter in the Draw Baseline Rule (DBR) text control is outside the acceptable range. The text-control sequence is in a Presentation Text Data (PTX) structured field. The structured field might be contained in a MO:DCA document, an overlay, or a page segment; or it might be embedded in a data set containing line data.

This message is accompanied by a message that presents the printer sense bytes. These sense bytes are unique to each printer. See the printer publications for the printer that reported this error.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set

in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document, an overlay, or a page segment and you created the structured fields in the object that contains the error, correct the text-control sequence in the Presentation Text Data (PTX) structured field. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the MO:DCA document, overlay, or page segment, contact your system programmer. If you are printing a data set containing line data with embedded structured fields, correct the text-control sequence in the PTX structured field. If the PTX has no errors, the error might be a PSF or printer logic error.

APS753I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN ATTEMPT WAS MADE TO PRINT WITH A FONT THAT DID NOT MATCH THE CURRENT TEXT ORIENTATION.

Explanation

The Set Coded Font Local (SCFL) text-control sequence was not specified after the text orientation was changed. When the text orientation changes, the SCFL text-control sequence is specified after the Set Text Orientation (STO) text control sequence, unless the current font is usable in the new orientation. The text-control sequence is in a Presentation Text Data (PTX) structured field or was generated by PSF from a page definition. The PTX structured field might be contained in a MO:DCA document, a presentation text object, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set

with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing MO:DCA data, a presentation text object, an overlay, or a page segment, and you created the structured fields in the object that contains the error, correct the text-control sequence in the PTX structured field. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you are printing MO:DCA data, a presentation text object, an overlay, or a page segment, and you used a program to create the structured fields in the object that contains the error, consult your system programmer.

If you are printing a data set containing line data with embedded structured fields, correct the text-control sequence in the PTX structured field. If the PTX has no errors, the error might be a PSF or printer logic error.

If you are using a page definition to print a data set containing line data, and you created the structured fields for the page definition, specify a valid value for the text orientation parameter in the Line Descriptor (LND) structured field, or specify a font that can be printed in the original text orientation. If you used a program to create the structured fields for the page definition, consult your system programmer.

APS754I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE BEGIN AND END SUPPRESSION IDENTIFIERS IN A BEGIN/END SUPPRESSION TEXT CONTROL DID NOT MATCH.

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. An End Suppression (ESU) text-control sequence that identifies the end of a passage of suppressible text does not specify the print-suppression number used in the Begin Suppression (BSU) text control.
2. An ESU text-control sequence was encountered without a prior BSU text-control sequence.

The text-control sequence is in a Presentation Text Data (PTX) structured field or was generated by PSF from a page definition. The PTX structured field might be contained in a MO:DCA document, a presentation text object, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document, a presentation text object, an overlay, or a page segment and you created the structured fields in the object that contains the error, correct the text-control sequence in the Presentation Text Data (PTX) structured field. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you used a program to create the

structured fields for the MO:DCA document, a presentation text object, overlay, or page segment, contact your system programmer. If you are printing a data set containing line data with embedded structured fields, correct the text-control sequence in the PTX structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you are printing a data set containing line data without embedded structured fields, the error might be a PSF or printer logic error.

APS755I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: NESTING OF SUPPRESSION TEXT CONTROLS IS NOT ALLOWED.

Explanation

A Begin Suppression (BSU) text control was received before the preceding Begin Suppression (BSU) text control was ended by an accompanying End Suppression (ESU) text control. The printer you were using when the error occurred does not allow this. The text-control sequence is in a Presentation Text Data (PTX) structured field or was generated by PSF from a page definition. The PTX structured field might be contained in a MO:DCA document, a presentation text object, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document, a presentation text object, an overlay, or a page segment and you created the structured fields in the object that contains the error, correct the text-control sequence in the Presentation Text Data (PTX) structured field. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the MO:DCA document, a presentation text object, overlay, or page segment, contact your system programmer. If you are printing a data set containing line data with embedded structured fields, correct the text-control sequence in the PTX structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you are printing a data set containing line data without embedded structured fields, the error might be a PSF or printer logic error.

APS756I DATA IN AN OVERLAY RESOURCE IS NOT VALID: BEGIN/END SUPPRESSION TEXT CONTROLS ARE NOT ALLOWED INSIDE AN OVERLAY.

Explanation

A Begin Suppression (BSU) and an End Suppression (ESU) text-control sequence was specified within an overlay. The printer you were using when the error occurred does not allow this. The text-control sequence is in a Presentation Text Data (PTX) structured field.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the overlay, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the overlay, consult your system programmer.

APS757I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE ORIENTATION OF THE FONT IS INCOMPATIBLE WITH THE CURRENT TEXT ORIENTATION.**

Explanation

The orientation of the font that is selected to print the text does not match the current text orientation. The current text orientation is defined in a Set Text Orientation (STO) text control in a Presentation Text Data (PTX) structured field or, if you were printing a data set containing line data, in a Line Descriptor (LND) structured field in the page definition. The PTX structured field might be in MO:DCA data, an overlay, or a page segment; or it might be embedded in a data set containing line data. The font is named in a Map Coded Font (MCF) structured field, in the page definition or in the CHARS option of the JCL. The MCF structured field is in the MO:DCA data, an overlay, or a page definition.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set

in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If the orientation was correct but the font was wrong, specify a different font that is compatible with the text orientation you want.

If the orientation was incorrect and if you were printing MO:DCA data, an overlay, or a page segment, and you created the structured fields in the object that contains the error, change the text orientation value in the STO text control. See *Mixed Object Document Content Architecture Reference* for more information about specifying text orientation. If you are printing MO:DCA data, an overlay, or a page segment, and you used a program to create the structured fields in the object that contains the error, consult your system programmer.

If the orientation was incorrect and you are printing a data set containing line data with a page definition that you created, change the Text Orientation value in the LND structured field. If you are printing a data set that contains line data, and are using a page definition that is created by a program, consult your system programmer.

If the orientation was incorrect and you are printing a data set containing line data with embedded structured fields, change the text orientation value in the STO text control. See *Mixed Object Document Content Architecture Reference* for more information about specifying text orientation.

APS758I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE CODED FONT LOCAL IDENTIFIER OF A SET CODED FONT LOCAL TEXT CONTROL IS NOT VALID.**

Explanation

The Coded Font Local Identifier parameter in the Set Coded Font Local (SCFL) text control in a Presentation Text Data (PTX) structured field or in the Line Descriptor (LND) structured field in the page definition is outside the valid range. The Presentation Text Data (PTX) structured field might be contained in a MO:DCA

document, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing MO:DCA data, an overlay, or a page segment, and you created the structured fields in the object that contains the error, correct the identifier in the SCFL text control. If the SCFL text control has no errors, the error might be a PSF or printer logic error. If you are printing MO:DCA data, an overlay, or a page segment, and you used a program to create the structured fields in the object that contains the error, consult your system programmer.

If you are printing a data set containing line data, and you were using a page definition that you created, correct the identifier in the LND structured field. If the LND structured field has no errors, the error might be a PSF or printer logic error. If you are printing a data set containing line data, and you were using a page definition that you created by use of a program, consult your system programmer.

If you are printing a data set containing line data with embedded structured fields, correct the identifier in the SCFL text control. If the SCFL text control has no errors, the error might be a PSF or printer logic error.

For the valid values of the Coded Font Local Identifier in the appropriate structured field, see *Mixed Object Document Content Architecture Reference*.

APS759I

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE TEXT ORIENTATION PARAMETER VALUE OF A SET TEXT ORIENTATION TEXT CONTROL IS NOT VALID.

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The inline or baseline orientation value that is specified in a Set Text Orientation (STO) text control sequence in a Presentation Text Data (PTX) structured field or in a Line Descriptor (LND) structured field in a page definition, is not valid or is unsupported.
2. The combination of the baseline and inline orientations is not valid or is unsupported.

The Presentation Text Data (PTX) structured field might be contained in a MO:DCA document, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing MO:DCA data, an overlay, or a page segment, and you created the structured fields in the object that contains the error, correct the value in the STO text control.

If the STO text control has no errors, the error might be a PSF or printer logic error. If you are printing MO:DCA data, an overlay, or a page segment, and you used a program to create the structured fields in the object that contains the error, consult your system programmer.

If you are printing a data set containing line data by using a page that contains line data and by using a page definition that you created, correct the value in the LND structured field. If the LND structured field has no errors, the error might be a PSF or printer logic error. If you are printing a data set containing line data by using a page definition that you created with a program, consult your system programmer.

If you are printing a data set containing line data with embedded structured fields, correct the identifier in the STO text control. If the STO text control has no errors, the error might be a PSF or printer logic error.

See *Mixed Object Document Content Architecture Reference* for the acceptable values of the Text Orientation parameter in the appropriate structured field.

APS760I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE INLINE COORDINATE PARAMETER VALUE OF A SET INLINE MARGIN TEXT CONTROL IS NOT VALID.**

Explanation

The Inline Coordinate parameter in the Set Inline Margin (SIM) text-control sequence is not valid. The text-control sequence is in a Presentation Text Data (PTX) structured field or was generated by PSF from a page definition. The PTX structured field might be in MO:DCA data, an overlay, or a page segment; or it might be embedded in a data set containing line data. If the error occurred while PSF was processing line data, the Inline Position parameter in a Line Descriptor (LND) structured field in the page definition might be incorrect.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the

printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document, an overlay, or a page segment and you created the structured fields in the object that contains the error, correct the text-control sequence in the Presentation Text Data (PTX) structured field. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the MO:DCA document, overlay, or page segment, contact your system programmer. If you are printing a data set containing line data with embedded structured fields, correct the text-control sequence in the PTX structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you are printing a data set containing line data without embedded structured fields, the error might be a PSF or printer logic error.

APS761I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE BASELINE INCREMENT PARAMETER VALUE OF A SET BASELINE INCREMENT TEXT CONTROL IS NOT VALID.**

Explanation

The Baseline Increment parameter in the Set Baseline Increment (SBI) text-control sequence is not valid. The text-control sequence is in a Presentation Text Data (PTX) structured field or was generated by the PSF from a page definition. The PTX structured field might be in MO:DCA data, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document, an overlay, or a page segment and you created the structured fields in the object that contains the error, correct the text-control sequence in the Presentation Text Data (PTX) structured field. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the MO:DCA document, overlay, or page segment, contact your system programmer. If you are printing a data set containing line data with embedded structured fields, correct the text-control sequence in the PTX structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you are printing a data set containing line data without embedded structured fields, the error might be a PSF or printer logic error.

Explanation

The Intercharacter Increment parameter or the optional Intercharacter Adjustment Direction parameter in the Set Intercharacter Increment (SII) text control is not valid. The text-control sequence is in a Presentation Text Data (PTX) structured field or was generated by PSF from a page definition. The PTX structured field might be contained in a MO:DCA document, a presentation text object, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document, a presentation text object, an overlay, or a page segment and you created the structured fields in the object that contains the error, correct the text-control sequence in the Presentation Text Data (PTX) structured field. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the MO:DCA document, a presentation text object, overlay, or page segment, contact your system programmer. If you are printing a data set containing line data with embedded structured fields, correct the text-control sequence in the PTX structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you are

APS762I

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE INTERCHARACTER INCREMENT PARAMETER VALUE OF A SET INTERCHARACTER INCREMENT TEXT CONTROL IS NOT VALID.

printing a data set containing line data without embedded structured fields, the error might be a PSF or printer logic error.

APS763I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE BASELINE POSITION IS NOT VALID.

Explanation

The Baseline Print Position parameter is not valid. It might be specified in any of three places:

- The Absolute Move Baseline (AMB) text-control sequence in a Presentation Text Data (PTX) structured field
- The Page Segment Origin in an Include Page Segment (IPS) structured field
- The Baseline Position parameter in a Line Descriptor (LND) structured field

The PTX or IPS structured field might be in MO:DCA data, an overlay, or a page segment; or it might be embedded in a data set containing line data. The LND structured field is in the page definition.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing MO:DCA data, an overlay, or a page segment, and you created the structured fields in the object that contains the error, correct the position

parameter in the appropriate structured field. If the structured field has no errors, the error might be a PSF or printer logic error. If you are printing MO:DCA data, an overlay, or a page segment, and you used a program to create the structured fields in the object that contains the error, consult your system programmer.

If you are printing a data set containing line data by using a page definition that you created, correct the position parameter in the LND structured field. If the LND structured field has no errors, the error might be a PSF or printer logic error. If you are printing a data set containing line data by using a page definition that you created with a program, consult your system programmer.

If you are printing a data set containing line data with embedded structured fields, correct the position parameter in the appropriate structured field. If the structured field has no errors, the error might be a PSF or printer logic error.

For the valid values of the Baseline Position parameter in the appropriate structured field, see *Advanced Function Presentation: Programming Guide and Line Data Reference*. Ensure that the AMB (Absolute Move Baseline) text control fits within the logical page size as defined by the Load Page Descriptor (LPD) command in the page definition.

APS764I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE INLINE POSITION IS NOT VALID.

Explanation

The Inline Position parameter is not valid. It might be specified in any of three places:

- The Absolute Move Inline (AMI) text-control sequence in a Presentation Text Data (PTX) structured field
- The Page Segment Origin in an Include Page Segment (IPS) structured field
- The Inline Position parameter in a Line Descriptor (LND) structured field

The PTX or IPS structured field might be in MO:DCA data, an overlay, or a page segment; or it might be embedded in a data set containing line data. The LND structured field is in the page definition.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the

printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing MO:DCA data, an overlay, or a page segment, and you created the structured fields in the object that contains the error, correct the position parameter in the appropriate structured field. If the structured field has no errors, the error might be a PSF or printer logic error. If you are printing MO:DCA data, an overlay, or a page segment, and you used a program to create the structured fields in the object that contains the error, consult your system programmer.

If you are printing a data set containing line data by using a page definition that you created, correct the position parameter in the LND structured field. If the LND structured field has no errors, the error might be a PSF or printer logic error. If you are printing a data set containing line data by using a page definition that you created with a program, consult your system programmer.

If you are printing a data set containing line data with embedded structured fields, correct the position parameter in the appropriate structured field. If the structured field has no errors, the error might be a PSF or printer logic error.

For the valid values of the Inline Position parameter in the appropriate structured field. See *Advanced Function Presentation: Programming Guide and Line Data Reference*. Ensure that the AMI (Absolute Move Inline) text control fits within the logical page size as defined by the Load Page Descriptor (LPD) command in the page definition.

CONTROL IN A PTX STRUCTURED FIELD IS NOT VALID.

Explanation

The Inline Print Position Move parameter value is not valid in the Relative Move Inline (RMI) text control. The text-control sequence is in a Presentation Text Data (PTX) structured field. The structured field might be contained in a MO:DCA document, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document, an overlay, or a page segment and you created the structured fields in the object that contains the error, correct the text-control sequence in the Presentation Text Data (PTX) structured field. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the MO:DCA document, overlay, or page segment, contact your system programmer. If you are printing a data set containing line data with embedded structured fields, correct the text-control sequence in the PTX structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you are printing a data set containing line data without embedded

APS765I

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE INLINE PRINT POSITION MOVE PARAMETER VALUE OF A RELATIVE MOVE INLINE TEXT

structured fields, the error might be a PSF or printer logic error.

APS766I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE BASELINE PRINT POSITION MOVE PARAMETER VALUE OF A RELATIVE MOVE BASELINE TEXT CONTROL IN A PTX STRUCTURED FIELD IS NOT VALID.

Explanation

The Baseline Print Position Move parameter in the Relative Move Baseline (RMB) text-control sequence is not valid. The text-control sequence is located in a Presentation Text Data (PTX) structured field. The structured field might be contained in a MO:DCA document, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing MO:DCA data, an overlay, or a page segment, and you created the structured fields in the object that contains the error, correct the text-control sequence in the PTX structured field. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you used a program to create the structured

fields for the MO:DCA data set, an overlay, or a page segment, consult your system programmer.

If you are printing a data set containing line data with embedded structured fields, correct the text-control sequence in the PTX structured field. If the PTX has no errors, the error might be a PSF or printer logic error.

If you are printing a data set containing line data by using a page definition, and you created the structured fields for the page definition, specify a valid value for the text orientation parameter in the Line Descriptor (LND) structured field, or specify a font that can be printed in the original text orientation. If you used a program to create the structured fields for the page definition, consult your system programmer.

APS767I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE TEXT STRING PARAMETER'S LENGTH OF A REPEAT STRING TEXT CONTROL IN A PTX STRUCTURED FIELD IS OUTSIDE THE VALID RANGE.

Explanation

The length of the Text String parameter in the Repeat String (RPS) text control is outside the valid range. The text-control sequence is in a Presentation Text Data (PTX) structured field. The structured field might be contained in a MO:DCA document, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS*:

Diagnosis for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document, an overlay, or a page segment and you created the structured fields in the object that contains the error, correct the text-control sequence in the Presentation Text Data (PTX) structured field. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the MO:DCA document, overlay, or page segment, contact your system programmer. If you are printing a data set containing line data with embedded structured fields, correct the text-control sequence in the PTX structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you are printing a data set containing line data without embedded structured fields, the error might be a PSF or printer logic error.

APS768I DATA IN A FONT RESOURCE IS NOT VALID: A VALID LOAD FONT INDEX COMMAND CANNOT BE BUILT.

Explanation

While an index for the font was being loaded into the printer, incorrect data was detected. When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The uniform or maximum baseline offset value in a Font Orientation (FNO) structured field is not valid or is unsupported.
2. The uniform or maximum character increment value in an FNO structured field is not valid or is unsupported.
3. The maximum baseline extent value in an FNO structured field is not valid or is unsupported.
4. The uniform or minimum A-space value in an FNO structured field is not valid or is unsupported.
5. The space character increment value in an FNO structured field is not valid or is unsupported.
6. A pattern index value (FNMCnt) in a Font Index (FNI) structured field refers to a nonexistent pattern.
7. A character increment value in an FNI structured field is not valid or is unsupported.
8. An A-space value in an FNI structured field is not valid or is unsupported.

9. A baseline-offset value in an FNI structured field is not valid or is unsupported.
10. A parameter value that is specified for an individual character is greater than or less than the respective maximum or minimum value specified for that parameter.
11. The combination of baseline offset (FNI) and pattern size for a character is incompatible with the baseline-extent value (FNO) specified.
12. The underscore width value in a Font Position (FNP) structured field is not valid.
13. One or more orientation flags in an FNO structured field for a section from X'45' to X'FE' is not uniform. These sections must have a uniform A-space, uniform baseline offset, and uniform character increment.

The CPC and CPI structured fields are in the code page, but the FNI and FNO structured fields are in the font character set. This message is accompanied by a message that presents the printer sense bytes. These sense bytes are unique to each printer. See the printer publications for the printer that reported this error.

System action

PSF stops processing and printing the data set that uses the font that contains the error.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured field for the font or the code page with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the font or code page, check each of the parameters in each of the structured fields. For more information about the correct format of the referenced structured fields, see *Font Object Content Architecture Reference*. If the structured fields have no errors, the error might be a PSF or printer logic error. If you used a program to

create the structured fields for the font or code page, consult your system programmer.

APS769I **DATA IN A CODED FONT RESOURCE IS NOT VALID: THE FONT SECTION IDENTIFIER IS NOT ACCEPTABLE OR IS NOT IN SEQUENCE IN THE CFI STRUCTURED FIELD.**

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The section identifier value in the Coded Font Index (CFI) structured field is nonzero for a single-byte coded font.
2. The section identifier value in a repeating group in the CFI structured field is not in the range X'41' through X'FE' for a double-byte coded font.
3. The section identifier value in a repeating group in the CFI structured field does not match that of any previously loaded section for that font (possible logic error).

The CFI structured field is in the coded font.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a printer logic error or a PSF error. If you used a program to create the structured fields for the font, contact your system programmer.

APS770I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE COLOR SPACE FIELD VALUE IN A X'4E' TRIPLET, SET EXTENDED TEXT COLOR CONTROL SEQUENCE, OR GOCA OBJECT IS NOT VALID OR IS UNSUPPORTED.**

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The color space field value in a Color Specification (X'4E') triplet is not valid or is unsupported.
2. The color space field value in a PTOCA Set Extended Text Color (SEC) control sequence is not valid or is unsupported.
3. The color space field value in a GOCA Set Process Color (GSPCOL), Linear Gradient (GLGD), or Radial Gradient (GRGD) drawing order is not valid or is unsupported.

The X'4E' triplet might occur on these structured fields:

- A Page Descriptor (PGD).
- An Object Area Descriptor (OBD).
- Include Object (IOB)

The PGD is contained in an Active Environment Group (AEG) for a page or an overlay, and the OBD is contained in an Object Environment Group (OEG) for a graphics, image, bar code, or presentation text object, or an object container. The IOB structured field can be contained in a page definition, overlay, or MO:DCA page, or it can be embedded in line data.

The Set Extended Color control sequence is in a Presentation Text Data (PTX) structured field. The structured field might be contained in MO:DCA data, an overlay, or a page segment; or it might be embedded in a data set containing line data.

The Set Process Color, Linear Gradient, or Radial Gradient drawing order is in a Graphics Data (GAD)

structured field. The structured field might be contained in MO:DCA data, an overlay, or a page segment; or, it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

If the object is in a resource, PSF stops processing the data set that uses the resource in error.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see [PSF for z/OS: Diagnosis](#) for assistance in determining the source of the problem.

User response

If the structured fields are not valid and you created the structured fields for the resource or print data set containing the image, correct the error in the referenced structured field and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the resource or print data set containing the image, contact your system programmer.

If the color value is unsupported by this printer, resubmit the print request to a printer that does support this color value.

Explanation

The size of an image cell or image block in the X-dimension is less than the minimum allowed. The size might be specified in the X-dimension subparameter of these:

- The Image Cell Size parameter in the Image Cell Position (ICP) structured field
- The Image Size parameter in the Image Input Descriptor (IID) structured field

The image block or image cell might be contained in an overlay, a page segment, or a MO:DCA document. It might also be embedded in a data set containing line data by using a Begin Image (BIM) structured field.

System action

If the image is in a page, the printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues the processing of the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. If the image is in a resource, PSF stops processing the data set that uses the resource in error.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see [PSF for z/OS: Diagnosis](#) for assistance in determining the source of the problem.

User response

If you created the structured fields for the resource or print data set containing the image, correct the error in the referenced structured field and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the resource or print data set containing the image, contact your system programmer.

APS771I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE IMAGE HORIZONTAL PEL COUNT VALUE IS LESS THAN 1 PEL IN AN ICP OR IID STRUCTURED FIELD.
----------------	---

APS772I

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE IMAGE HORIZONTAL PEL COUNT VALUE IS GREATER THAN THE MAXIMUM ALLOWED IN AN ICP OR IID STRUCTURED FIELD.

Explanation

The size of an image block or image cell in the X-dimension is greater than the maximum allowed. The size might be specified in the X-dimension subparameter of these:

- The Image Cell Size parameter in the Image Cell Position (ICP) structured field
- The Image Size parameter in the Image Input Descriptor (IID) structured field

The image block or image cell might be contained in an overlay, a page segment, or a MO:DCA document. It might also be embedded in a data set containing line data by using a Begin Image (BIM) structured field.

If the printer does not support Image Object Content Architecture (IOCA), PSF might convert your IOCA image to an IM1 image. In this case, the IDD structured field contains an image X-dimension that is larger than the maximum allowed.

System action

If the image is in a page, the printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues the processing of the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. If the image is in a resource, PSF stops processing the data set that uses the resource in error.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the resource or print data set containing the image, correct the error in the referenced structured field and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the resource or print data set containing the image, contact your system programmer.

APS773I

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE IMAGE VERTICAL PEL COUNT VALUE IS LESS THAN 1 PEL IN AN ICP OR IID STRUCTURED FIELD.

Explanation

The size of an image cell or image block in the Y-dimension is less than the minimum allowed. The size might be specified in the Y-dimension subparameter of these:

- The Image Cell Size parameter in the Image Cell Position (ICP) structured field
- The Image Size parameter in the Image Input Descriptor (IID) structured field
- The Fill Rectangle Size parameter in the Image Cell Position (ICP) structured field

The image block or image cell might be contained in an overlay, a page segment, or a MO:DCA document. It might also be embedded in a data set containing line data by using a Begin Image (BIM) structured field.

If the printer does not support Image Object Content Architecture (IOCA), PSF might convert your IOCA image to an IM1 image. In this case, the IOCA image size is specified in the IDD structured field. This value is less than the minimum allowed.

System action

If the image is in a page, the printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues the processing of the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. If the image is in a resource, PSF stops processing the data set that uses the resource in error.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the resource or print data set containing the image, correct the error in the referenced structured field and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the resource or print data set containing the image, contact your system programmer.

APS774I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE IMAGE VERTICAL PEL COUNT VALUE IS GREATER THAN THE MAXIMUM ALLOWED IN AN ICP OR IID STRUCTURED FIELD.

Explanation

The size of an image cell or image block in the Y-dimension is greater than the maximum allowed. The size might be specified in the Y-dimension subparameter of these:

- The Image Cell Size parameter in the Image Cell Position (ICP) structured field
- The Image Size parameter in the Image Input Descriptor (IID) structured field

The image block or image cell might be contained in an overlay, a page segment, or a MO:DCA document. It might also be embedded in a data set containing line data by using a Begin Image (BIM) structured field.

If the printer does not support Image Object Content Architecture (IOCA), PSF might convert your IOCA image to an IM1 image. In this case, the IDD structured field contains an image Y-dimension that is larger than the maximum allowed.

System action

If the image is in a page, the printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues the processing of the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. If the image is in a resource, PSF stops processing the data set that uses the resource in error.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the resource or print data set containing the image, correct the error in the referenced structured field and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the resource or print data set containing the image, contact your system programmer.

APS775I DATA IN A FORMDEF RESOURCE IS INCOMPATIBLE WITH THE PRINT REQUEST: THE OUTPUT CONTAINS TOO MANY OR TOO FEW SHEETS TO PERFORM THE FINISHING OPERATION SPECIFIED IN THE MEDIUM FINISHING CONTROL STRUCTURED FIELD.

Explanation

A finishing operation was requested for a collection of sheets, but the number of sheets was too large or too small for the operation.

Finishing Operation triplets are specified in the Medium Finishing Control (MFC) structured field. The MFC is specified in the Document Environment Group of the form definition or in a Medium Map.

System action

Reporting of this exception can be controlled by the Finishing Fidelity triplet in the Presentation Fidelity Control (PFC) command. The PFC command is contained in a form definition.

When the Finishing Fidelity triplet sets the continuation rule to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and marks the data set. PSF releases the current data set back to JES and requests that it is held by the system unless PRTEROR=QUIT was specified on the OUTPUT statement.

When the Finishing Fidelity triplet sets the continuation rule to DO NOT STOP (X'02'), one of these occurs:

- If the printer supports the PFC Finishing Fidelity triplet and if the REPORT field is set to REPORT (X'01'), the printer reports this exception. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.
- If the printer supports the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.
- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer reports this exception but PSF does not issue the error message. The printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.
- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to REPORT (X'01'), the printer reports this exception and PSF issues the error message. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF

recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the MFC with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If the output is not acceptable:

- Verify that you requested the appropriate form definition for the finishing operation intended.
- Submit the print request to a printer that can do the finishing operation.
- If errors caused message pages to be added to the output or caused pages to be skipped, fix those errors so the correct number of pages is printed.

AP5776I

THE POST PROCESSOR HAS DETECTED A CONDITION THAT CAUSES PAGES TO BE DISCARDED.

Explanation

Paper in the post processor was discarded. The printer detected and reported an asynchronous intervention-required error with an action code of X'0A' (sense byte 2). For more information about this error, see the printer publications for the printer than reported this error.

System action

PSF resends pages to the printer, starting from the jam recovery page counter. Pages might be duplicated during recovery. If repositioning is not supported in the current environment, PSF stops processing the data set.

Operator response

See the operator's guide for the printer that reported this error and clear the paper from the printer and post processor. PSF assumes that pages between the jam recovery page counter and the stacked page counter are not damaged and do not need to be reprinted. If any pages between these two page counters do need to be reprinted, use the JES BACKSPACE command.

System programmer response

If the error condition persists, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

The printed output might be acceptable. If any pages were duplicated, you might want to resubmit the print request. If the error condition persists, consult your system programmer.

APS777I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE INLINE DIRECTION COMPONENT OF THE ORIENTATION PARAMETER IN AN IOC STRUCTURED FIELD IS NOT VALID.

Explanation

The Inline Direction Component of the Orientation parameter in an Input Output Control (IOC) structured field is not valid. The image block or image cell might be contained in an overlay, a page segment, or a MO:DCA document. It might also be embedded in a data set containing line data by using a Begin Image (BIM) structured field.

If the printer does not support Image Object Content Architecture (IOCA), PSF might convert your IOCA image to an IM1 image. In this case, the incorrect value is in the OBP structured field.

System action

If the image is in a page, the printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues the processing of the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. If the image is in a resource, PSF stops processing the data set that uses the resource in error.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the resource or print data set containing the image, correct the error in the referenced structured field and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the resource or print data set containing the image, contact your system programmer.

APS778I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE BASELINE DIRECTION COMPONENT OF THE ORIENTATION PARAMETER IN AN IOC STRUCTURED FIELD IS NOT VALID.

Explanation

The Baseline Direction Component of the Orientation parameter in an Input Output Control (IOC) structured field is not valid. The image block or image cell might be contained in an overlay, a page segment, or a MO:DCA document. It might also be embedded in a data set containing line data by using a Begin Image (BIM) structured field.

If the printer does not support Image Object Content Architecture (IOCA), PSF might convert your IOCA image to an IM1 image. In this case, the incorrect value is in the OBP structured field.

System action

If the image is in a page, the printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues the

processing of the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. If the image is in a resource, PSF stops processing the data set that uses the resource in error.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the resource or print data set containing the image, correct the error in the referenced structured field and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the resource or print data set containing the image, contact your system programmer.

APS779I THE STARTING PEL COORDINATES SPECIFIED FOR THE IMAGE WOULD PLACE ALL OR PART OF THE IMAGE TO THE RIGHT OF THE LOGICAL PAGE.

Explanation

Either the X-Position parameter in the Image Cell Position (ICP) structured field or the Horizontal Coordinate parameter in the Image Output Control (IOC) structured field is within the valid range, but is greater than the Horizontal Page Size parameter in the Page Descriptor (PGD) structured field. The image block or image cell might be contained in an overlay, a page segment, or a MO:DCA document. It might also be embedded in a data set containing line data by using a Begin Image (BIM) structured field. The PGD structured field is in the MO:DCA data, the overlay, or a page definition.

For a Begin Image Block (BIM) structured field in a line-data page, the offset is relative to the current print position before the image. For a BIM structured field in the MO:DCA data, the offset is relative to the page origin. For a BIM structured field included in a page segment, the offset is relative to the page segment origin.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you are printing MO:DCA data or an overlay, and you created the structured fields in the object that contains the error, change the page size in the print data set or an overlay. If you are printing MO:DCA data or an overlay, and you used a program to create the structured fields in the object that contains the error, change your input to that program to increase the page size in the print data set or the overlay. If you are printing a data set containing line data, change the page size in the page definition.

APS780I THE STARTING PEL COORDINATES SPECIFIED FOR THE IMAGE WOULD PLACE ALL OR PART OF THE IMAGE BEYOND THE BOTTOM OF THE LOGICAL PAGE.

Explanation

Either the Y-Position parameter in an Image Cell Position (ICP) structured field or the Vertical Coordinate parameter in an Image Output Control (IOC) structured field is within the valid range, but is greater than the Vertical Page Size parameter in the

Page Descriptor (PGD) structured field. The image block or image cell might be contained in an overlay, a page segment, or a MO:DCA document. It might also be embedded in a data set containing line data by using a Begin Image (BIM) structured field. The PGD structured field is in MO:DCA data, an overlay, or a page definition.

For a Begin Image Block (BIM) structured field in a line-data page, the offset is relative to the current print position before the image. For a BIM structured field in the MO:DCA data, the offset is relative to the page origin. For a BIM structured field included in a page segment, the offset is relative to the page segment origin.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you are printing MO:DCA data or an overlay, and you created the structured fields in the object that contains the error, change the page size in the print data set or the overlay. If you are printing MO:DCA data or an overlay, and you used a program to create the structured fields in the object that contains the error, change your input to that program to increase the page size in the print data set or an overlay. If you are printing a data set containing line data, change the page size in the page definition.

APS781I **THE CANCEL BUTTON ON THE
PRINTER CONTROL PANEL WAS
PRESSED WHILE THE PRINTER
WAS PROCESSING A DATA SET.**

Explanation

The printer detected and reported that the cancel button on the printer control panel was pressed while the printer was processing a data set.

System action

PSF causes the printer to discard the printer's buffered data. Then, if the stacked page counter is greater than zero, PSF cancels the data set at the stacked page counter plus 1. Otherwise, PSF cancels the data set at the stacked page counter.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

If wanted, resubmit the print request that was canceled. If the error condition persists, consult the operator to see why the cancel button is being pressed.

APS782I **THE PAGE BEING PROCESSED
WAS TOO COMPLEX TO PRINT.
ONE OR MORE OBJECTS MAY
HAVE TO BE REMOVED FROM THE
PAGE IN ORDER TO PRINT IT.**

Explanation

This error is a result of either too many items (for example, images) being placed on a page, or too many overstrikes being requested. The printer detected and reported an I/O error with an action code of X'09' (sense byte 2). This message is accompanied by a message that presents the printer sense bytes.

System action

When the print error is detected, the printer attempts to print at least part of the page that contains the error. PSF causes the printer to discard the printer's buffered data. PSF then stops processing the data set at the stacked page counter plus 1.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Remove one or more resources from the page, and resubmit the print request.

APS783I THE MAGNET SETTINGS OF THE CASSETTE WERE CHANGED AFTER THE PAGE WAS PROCESSED BUT BEFORE THE PAGE WAS PRINTED.

Explanation

The magnet settings of the cassette were not the same at the time the page was printed as they were when the page was formatted on the printer. The printer detected and reported an asynchronous error with an action code of X'23' (sense byte 2).

System action

PSF causes the printer to discard the printer's buffered data. PSF resends pages to the printer, starting from the stacked page counter plus 1. PSF prints this message on a separate sheet in the data set to mark the position where the recovery from this error was started. PSF also prints this message at the end of the data set to indicate that this message was printed within the data set.

Operator response

No response is necessary.

System programmer response

If the error condition persists, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

Check your output for duplicate pages. If the error condition persists, consult your system programmer.

APS784I A SERIALIZER PARITY ERROR OCCURRED DURING THE PRINTING OF THIS DATA SET.

Explanation

The serializer card in the printer generated an incorrect parity. The printer detected and reported an asynchronous error with an action code of X'23' (sense byte 2). This is a temporary hardware error.

System action

PSF causes the printer to discard the printer's buffered data. PSF resends pages to the printer, starting from the stacked page counter plus 1. PSF prints this

message on a separate sheet in the data set to mark the position where the recovery from this error was started. PSF also prints this message at the end of the data set to indicate that this message was printed within the data set.

Operator response

No response is necessary.

System programmer response

If the error condition persists, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

Check your output for duplicate pages. If the error condition persists, consult your system programmer.

APS785I AN IMAGE EXTENDS OFF THE RIGHT OF THE LOGICAL PAGE.

Explanation

Either the X-Position parameter in an Image Cell Position (ICP) structured field or a Horizontal Coordinate parameter in an Image Output Control (IOC) structured field is outside the valid range. The image block or image cell might be contained in an overlay, a page segment, or a MO:DCA document. It might also be embedded in a data set containing line data by using a Begin Image (BIM) structured field. If the image is part of a page segment, an overlay, or MO:DCA data, the image block origin is described as a displacement from the origin of the page segment, overlay, or MO:DCA data page. If the image is part of a line-data page, the image block origin is described as a displacement from the current Line Descriptor (LND) structured field. The LND structured field is contained in the page definition.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set

in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see [PSF for z/OS: Diagnosis](#) for assistance in determining the source of the problem.

User response

If you created the structured fields for the resource or print data set containing the image, correct the error in the referenced structured field and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the resource or print data set containing the image, contact your system programmer.

APS786I **AN IMAGE EXTENDS OFF THE
BOTTOM OF THE LOGICAL PAGE.**

Explanation

Either the Y-Position parameter in an Image Cell Position (ICP) structured field or a Vertical Coordinate parameter in an Image Output Control (IOC) structured field is outside the valid range. The image block or image cell might be contained in an overlay, a page segment, or a MO:DCA document. It might also be embedded in a data set containing line data by using a Begin Image (BIM) structured field. If the image is part of a page segment, an overlay, or a MO:DCA data page, the image block origin is described as a displacement from the origin of the page segment, overlay, or MO:DCA data page. If the image is part of a line-data page, the image block origin is described as a displacement from the current Line Descriptor (LND) structured field. The LND structured field is contained in the page definition.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see [PSF for z/OS: Diagnosis](#) for assistance in determining the source of the problem.

User response

If you created the structured fields for the resource or print data set containing the image, correct the error in the referenced structured field and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the resource or print data set containing the image, contact your system programmer.

APS787I **AN IMAGE GENERATOR ERROR
OCCURRED DURING THE
PRINTING OF THIS DATA SET.**

Explanation

The printer detected and reported an asynchronous error with an action code of X'23' (sense byte 2). This is a temporary hardware error. For more information about this error, see the printer publications for the printer that reported this error.

System action

PSF causes the printer to discard the printer's buffered data. PSF resends pages to the printer, starting from the stacked page counter plus 1. PSF prints this message on a separate sheet in the data set to mark the position where the recovery from this error was started. PSF also prints this message at the end of the data set to indicate that this message was printed within the data set.

Operator response

No response is necessary.

System programmer response

If the error condition persists, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

Check your output for duplicate pages. If the error condition persists, consult your system programmer.

APS788I **ONE OR MORE CHARACTERS, RULES, IMAGES, OR IMAGE CELLS WERE SPECIFIED TO PRINT OUTSIDE OF THE VALID PRINTABLE AREA.**

Explanation

An attempt was made to print outside the valid printable area. This area is the intersection (common space) of the physical page with the logical page or with an overlay. Characters, rules, or image cells fall at least partially outside of the valid printable area. Note that a data-stream image might consist of a number of image cells, and each cell is sent to the printer as one image.

System action

Characters and images that were not defined completely within the valid printable area are not printed. Rules are printed up to the area boundary. The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

Ensure that the correct form was loaded in the printer. If it was, and if your printed output would be

acceptable without the print-error markers, you can resubmit the print request, specifying BLOCK or BLKPOS for the DATAKEY keyword on the OUTPUT JCL statement.

If you want to correct the source of the problem, you can change the size of the logical page. If you want the logical page size to remain the same and if you were printing MO:DCA data, an overlay, or a page segment, and you created the structured fields in the object that contains the error, check the print positioning values in the text-control sequence in the Presentation Text Data (PTX) structured field for positioning outside of the page.

If you are printing an image, coordinate the image dimensions with the logical page size.

If you are printing a data set containing line data, and you were using a page definition that you created, check the print-positioning values in the Line Descriptor (LND) structured field.

If you are printing a data set containing line data with embedded structured fields, check the PTX structured field for positioning outside of the page.

APS790I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE BEGIN/END SUPPRESSION TEXT CONTROL PARAMETER VALUE IS OUTSIDE THE VALID RANGE.**

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The suppression ID in a Load Copy Control (LCC) command is not valid or is unsupported (possible logic error).
2. The Begin Suppression (BSU) suppression ID in a text-control sequence is not valid or is unsupported.

The text-control sequence is in a Presentation Text Data (PTX) structured field or was generated by PSF from a page definition. The PTX structured field might be contained in a MO:DCA document, a presentation text object, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set

with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document, a presentation text object, an overlay, or a page segment and you created the structured fields in the object that contains the error, correct the text-control sequence in the Presentation Text Data (PTX) structured field. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the MO:DCA document, a presentation text object, overlay, or page segment, contact your system programmer. If you are printing a data set containing line data with embedded structured fields, correct the text-control sequence in the PTX structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you are printing a data set containing line data without embedded structured fields, the error might be a PSF or printer logic error.

APS791I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE REPEAT STRING TEXT CONTROL LENGTH VALUE IN A PTX STRUCTURED FIELD IS NOT VALID.**

Explanation

The Length parameter in a Repeat String (RPS) text control was nonzero, but the Text String parameter had zero length. The RPS text control is in a Presentation Text Data (PTX) structured field. The Presentation Text Data (PTX) structured field might be contained in a MO:DCA document, an overlay, or a

page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document or an overlay, and you created the structured fields in the object that contains the error, correct the text-control sequence in the Presentation Text Data (PTX) structured field. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you are printing a MO:DCA document or an overlay, and you used a program to create its structured fields, contact your system programmer. If you are printing a MO:DCA document that contains line data with embedded structured fields, correct the text-control sequence in the PTX structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you are printing a data set containing line data without embedded structured fields, the error might be a PSF or printer logic error.

APS792I **DATA IN A CODE PAGE RESOURCE IS NOT VALID: DOUBLE-BYTE CHARACTER FLAGS ARE NOT VALID.**

Explanation

In the Code Page Index (CPI) or Code Page Control (CPC) structured fields, an incorrect flag combination was specified for a character of a double-byte font. The CPC and CPI structured fields are in the code page.

System action

PSF stops processing and printing the data set that uses the font that contains the error.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the code page with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the code page, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the code page, contact your system programmer.

APS793I THE PAGE DIMENSIONS SPECIFIED WERE LARGER THAN THE MAXIMUM ALLOWABLE DIMENSIONS.

Explanation

The meaning of this message depends on the printer. For all printers except the 3800 printers, the sum of the Y-Origin parameter in the Page Position (PGP) structured field and the Vertical Page Size parameter in the Page Descriptor (PGD) structured field must not exceed the addressability limit of the printer. Also, the sum of the X-Origin parameter in the PGP structured field and the Horizontal Page Size parameter in the PGD structured field must not exceed the addressability limit of the printer. The PGD structured field is in the MO:DCA data, an overlay, or a page

definition. The PGP structured field is in the form definition.

For the 3800 printers, the sum of the Y-Origin parameter in the Page Position (PGP) structured field and the Vertical Page Size parameter in the Page Descriptor (PGD) structured field must not exceed the maximum Y values of the following paper sizes. Also, the sum of the X-Origin parameter in the PGP structured field and the Horizontal Page Size parameter in the PGD structured field must not exceed the maximum X values of the following paper sizes. The PGD structured field is in the MO:DCA data, an overlay, or a page definition. The PGP structured field is in the form definition.

Common paper sizes:

X-dimension

3330

Y-dimension

2640

ISO paper sizes:

X-dimension

3330

Y-dimension

2880

More ISO paper sizes:

X-dimension

3330

Y-dimension

3000

These values represent the maximum common and maximum ISO paper sizes. For more information about the maximum X- and Y-dimensions of other paper sizes, see *IBM 3800 Printing Subsystem Models 3, 6, and 8 Operator's Guide*.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

Ensure that the correct form was loaded in the printer. If it was, and you were printing MO:DCA data or an overlay and you created the structured fields in the object that contains the error, change the page size in the print data set or an overlay. You can also change the page origin in the form definition.

If you are printing MO:DCA data or an overlay, and you used a program to create the structured fields in the object that contains the error, change your input to that program to reduce the page size in the print data set or overlay. You can also change the page origin in the form definition.

If you are printing a data set containing line data, change the page position in the page definition, or change the page origin in the form definition.

APS794I **THE PAGE OR PAPER SIZE IS GREATER THAN THE PRINTER ACCUMULATOR STORAGE CAPACITY.**

Explanation

The physical page requires the accumulator. The page size of the form that is loaded in the printer is too large for the accumulator.

System action

PSF causes the printer to discard the printer's buffered data and to delete all overlays, page segments, and fonts. On the first occurrence of this error, the message is printed on a separate sheet in the data set to mark the position before recovery starts. PSF recovers by resending pages to the printer, starting from the last known committed page counter plus 1. On the second occurrence of this error, the message is printed at the end of the message data set, and PSF stops processing the data set at the committed page counter plus 1.

System programmer response

If the error condition persists, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

Request a smaller page size, and ensure that the print request is routed to the appropriate output class. Otherwise, run the print request on a printer with a

different size accumulator, if available. If the error condition persists, consult your system programmer.

APS796I **A PAPER JAM OR A POST PROCESSOR RESYNCHRONIZATION OCCURRED DURING THE TRANSMISSION OF THIS DATA SET. PARTIAL OR DUPLICATE PAGES MAY BE PRINTED.**

Explanation

The paper in the printer was jammed. The printer detected and reported an asynchronous intervention-required error with an action code of X'08' (sense byte 2). For more information about this error, see the printer publications for the printer that reported this error.

System action

PSF resends pages to the printer, starting from the jam recovery page counter plus 1. PSF might print message APS711I on a separate sheet in the data set to mark the position where the recovery from this error was started. Pages might be duplicated during the recovery. If repositioning is not supported in the current environment, PSF stops processing the data set.

Operator response

See the operator's guide for the printer that reported this error and clear the paper jam in the printer. PSF assumes that pages between the jam recovery page counter and the stacked page counter are not damaged by the paper jam and do not need to be reprinted. If any pages between these two page counters do need to be reprinted, use the JES BACKSPACE command.

System programmer response

If the error condition persists, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

The printed output might be acceptable. If any pages were duplicated, you might want to resubmit the print request. If the error condition persists, consult your system programmer.

APS797I **THE PAGE BEING PROCESSED WAS TOO COMPLEX TO BE PRINTED AND WAS SKIPPED. ONE OR MORE OBJECTS MAY HAVE TO**

BE REMOVED FROM THE PAGE IN ORDER TO PRINT IT.

Explanation

An equipment check at print time indicated that either a strip-buffer overrun or an insufficient accumulator storage condition (includes the condition of no accumulator installed) occurred. The page at the committed page counter was too complex to print; therefore, the page was skipped. The printer detected and reported an asynchronous error with an action code of X'09' (sense-byte 2).

System action

PSF resends pages to the printer, starting from the committed page counter plus 2 to skip the page that was too complex to print. PSF prints this message on a separate sheet in the data set to mark the position at which the recovery from this error was started. PSF also prints this message at the end of the data set to indicate that this message was printed within the data set. If repositioning is not supported in the current environment, PSF stops processing the data set.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Remove some of the resources on the page (for example, overlays, images, fonts, or page segments), or remove some of the data from the page, and resubmit the print request.

APS798I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE LENGTH PARAMETER VALUE OF A REPEAT STRING TEXT CONTROL IN A PTX STRUCTURED FIELD IS NOT VALID

Explanation

The Length parameter in a Repeat String (RPS) text control is not valid. The text-control sequence is in a Presentation Text Data (PTX) structured field. The structured field might be contained in a MO:DCA document, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document, an overlay, or a page segment and you created the structured fields in the object that contains the error, correct the text-control sequence in the Presentation Text Data (PTX) structured field. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the MO:DCA document, overlay, or page segment, contact your system programmer. If you are printing a data set containing line data with embedded structured fields, correct the text-control sequence in the PTX structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you are printing a data set containing line data without embedded structured fields, the error might be a PSF or printer logic error.

APS799I THE DEMANDS FOR PRINTER {WCS | RPS} STORAGE ARE ADVERSELY AFFECTING PRINTER THROUGHPUT. THE PRINTED OUTPUT SHOULD BE ACCEPTABLE.

Explanation

Not enough writable-control storage (WCS) or raster-pattern storage (RPS) was available to complete the page. This message was issued to indicate that multiple resources in the printer used all of the WCS or RPS storage, and the data set was printed with the accumulator feature. The complexity of the page or resources from previous pages or data sets might be causing the printer to run slower than usual.

System action

The printer prints the page that contains the error by using the accumulator. If the page contains any position errors, the print-error markers are printed on the page that contains the error. PSF attempts to free some of the printer storage by deleting all overlays in the printer, all page segments in the printer, or all resources in the printer. The page that caused this error to be reported is already printed; so PSF continues processing the current data set with the page after the page that contains the error.

If repositioning is not supported in the current environment, the channel program is redriven on the next channel command.

Operator response

If the problem persists, notify your system programmer of this error.

System programmer response

If the printer throughput is unacceptable, consider acquiring more printer storage, if possible.

User response

If the printed output is not acceptable, make the page less complicated by deleting resources (for example overlays, page segments, and fonts), or print the data set on a printer with more of the type of storage that was exceeded. If greater throughput is wanted, you can remove some of the resources that are used for the data set to reduce the page complexity. If the problem persists, notify your system programmer.

APS800 to APS899

APS800I AN ERROR OCCURRED WHILE PSF WAS PROCESSING A SECURE OVERLAY.

Explanation

The printer detected and reported a data stream error in a secure overlay.

System action

The page that contains the secure overlay cannot be printed. Processing of the data set stops. PSF releases the current data set back to JES and requests that it is held by the system.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

See the specific error conditions that are described in the accompanying messages to determine an appropriate response.

APS801I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: DOUBLE-BYTE FONT TEXT DATA LENGTH MUST BE A MULTIPLE OF 2.

Explanation

While processing text data that uses a double-byte font, the printer detected that the Length of the Text parameter in a Repeat String (RPS) text control, a Transparent Data (TRN) text control, or a Unicode Complex Text (UCT) control sequence was not a multiple of two. Either an even number of bytes of source data was not specified on the text control, or a double-byte font was selected when the user intended for the data to be printed with a single-byte font. The text-control sequence is in a Presentation Text Data (PTX) structured field or was generated by PSF from a page definition. The PTX structured field might be contained in a MO:DCA document, a presentation text object, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using might attempt to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you did not intend to use a double-byte font, correct the font specification to name a single-byte font.

If you did intend to use a double-byte font in printing the MO:DCA data, and you created the structured fields for the print data set, a presentation text object, overlay, or page segment, correct the RPS or TRN text control. If the RPS or the TRN text control has no errors, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the print data set, a presentation text object, overlay, or page segment, consult your system programmer.

If you intended to use a double-byte font in printing a data set containing line data with embedded structured fields, correct the RPS or TRN text control. If the RPS or TRN text control has no errors, the error might be a PSF or printer logic error.

If you intended to print a data set containing line data by using a double-byte font, the error might be a PSF or printer logic error.

See *Mixed Object Document Content Architecture Reference* for the acceptable format of RPS and TRN text controls.

APS802I THE PRINTER ENCOUNTERED AN ACCUMULATOR READ CHECK. PARTIAL OR DUPLICATE PAGES MAY BE PRINTED.

Explanation

A read-check error was sensed by the accumulator feature circuits. The printer detected and reported an equipment check error with an action code of X'OF' (sense-byte 2). For more information about this error, see the printer publications for the printer that reported this error.

System action

PSF causes the printer to discard the printer's buffered data and to delete all the overlays in the printer. PSF resends pages to the printer, starting from the committed page counter plus 1. PSF prints this message on a separate sheet in the data set to mark the position where the recovery from this error was started. Pages might be duplicated during the recovery. If repositioning is not supported in the current environment, PSF stops processing the data set.

Operator response

No response is necessary.

System programmer response

If the error condition persists, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

Check the printed output for duplicate pages. If the problem persists, consult your system programmer.

APS803I AN UNEXPECTED I/O ECB COMPLETION CODE (completion code) WAS DETECTED.

Explanation

The PSF I/O Error Manager subcomponent detected the Event Control Block (ECB) that was reported in this message. Valid ECB completion codes are X'41', X'44', X'48', and X'7E'.

System action

PSF ends with a memory dump. JES queues the print request again.

Operator response

Inform your system programmer that this error occurred.

System programmer response

To interpret the ECB completion code, see *z/OS DFSMS Using Data Sets*. If the error condition persists, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

Inform your system programmer that this error occurred.

APS804I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE LENGTH PARAMETER OF A REPEAT STRING TEXT CONTROL IN A PTX STRUCTURED FIELD MUST BE A MULTIPLE OF 2 FOR A DOUBLE-BYTE FONT.

Explanation

While processing text data that uses a double-byte font, the printer detected that the target length of the data to be printed was not a multiple of two. Either the Length parameter in a Repeat String (RPS) text control is not valid, or a double-byte font was selected when a single-byte font was intended to print the data. The text-control sequence is in a Presentation Text Data (PTX) structured field. The structured field might be contained in a MO:DCA document, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using might attempt to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS:*

Diagnosis for assistance in determining the source of the problem.

User response

If you did not intend to use a double-byte font, correct the font specification to name a single-byte font.

If you intended to print the MO:DCA data with a double-byte font, and you created the structured fields for the print data set, overlay, or page segment, correct the RPS text control. If the RPS text control has no errors, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the print data set, overlay, or page segment, consult your system programmer.

If you intended to use a double-byte font to print a data set containing line data with embedded structured fields, correct the RPS text control.

If the RPS text control has no errors, the error might be a PSF or printer logic error. For the valid format of the RPS text control, see *Mixed Object Document Content Architecture Reference*.

APS805I DATA IN A FORMDEF RESOURCE IS NOT VALID: THE MAXIMUM HORIZONTAL ADJUSTMENT VALUE SPECIFIED IN THE MMC STRUCTURED FIELD IS GREATER THAN THE MAXIMUM ALLOWED BY THE PRINTER.

Explanation

The horizontal adjustment range that is specified in the Medium Modification Control (MMC) structured field Modification parameter is not valid. The value is greater than the maximum allowed. The operator can make an adjustment that ranges from zero to twice the value of this parameter. If more than one MMC structured field reports a value, the maximum value is specified to the operator. The MMC structured field is contained in the form definition.

System action

PSF stops processing and printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the MMC structured field and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the MMC has no errors, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS806I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE COLOR FIELD VALUE IN A X'4E' TRIPLET, SET EXTENDED TEXT COLOR CONTROL SEQUENCE, GOCA OBJECT, OR HIGHLIGHT COLOR IS NOT VALID OR IS UNSUPPORTED.

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The color field value in a Color Specification (X'4E') triplet is not valid or is unsupported.
2. The color field value in a PTOCA Set Extended Text Color (SEC) control sequence is not valid or is unsupported.
3. The color field value in a GOCA Set Process Color (GSPCOL), Linear Gradient (GLGD), or Radial Gradient (GRGD) drawing order is not valid or is unsupported.
4. A specified highlight color number is in the range X'0100'–X'FFFF', but a host-invoked indexed CMR is not found.
5. An indexed CMR is selected for use with a highlight color value, but the color value is not found in the indexed CMR.

Note: Only the selected indexed CMR is searched for this color value.

The X'4E' might occur on these structured fields:

- Page Descriptor (PGD)

- Object Area Descriptor (OBD)
- Include Object (IOB)

The PGD is contained in an Active Environment Group (AEG) for a page or an overlay, and the OBD is contained in an Object Environment Group (OEG) for a graphics, image, or bar code, or presentation text object, or an object container. The IOB structured field can be contained in a page definition, overlay, or MO:DCA page, or it can be embedded in line data.

The Set Extended Color control sequence is in a Presentation Text Data (PTX) structured field. The structured field might be contained in MO:DCA data, an overlay, or a page segment; or it might be embedded in a data set containing line data.

The Set Process Color, Linear Gradient, or Radial Gradient drawing order is in a Graphics Data (GAD) structured field. The structured field might be contained in MO:DCA data, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action:

Operator response:

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response:

APS807I THERE IS INSUFFICIENT PRINTER WCS STORAGE TO PRINT THE PAGE. ONE OR MORE OBJECTS MAY HAVE TO BE REMOVED FROM THE PAGE IN ORDER TO PRINT IT.

Explanation

Either the page is too complex for the Writable Control Storage (WCS), or both sides of a duplexed sheet are collectively too complex for the available WCS. This is caused by too much text or too many images or draw rules. This message is accompanied by a message that presents the printer sense bytes.

System action

PSF causes the printer to discard the printer's buffered data. PSF then stops processing the data set at the stacked page counter plus 1.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Simplify the page that was too complex to print. You might need to remove one or more resources from the page to print it. Resubmit the print request.

APS808I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: LESS IMAGE DATA WAS PROVIDED IN THE IRD STRUCTURED FIELD THAN WAS NEEDED FOR THE SIZE OF THE IMAGE SPECIFIED IN THE IID OR ICP STRUCTURED FIELDS.**

Explanation

The amount of raster data that is sent in one or more Image Raster Data (IRD) structured fields was not sufficient to complete the image. The number of bytes of source image data that is sent in one or more IRD structured fields must equal the product of the source-pel count and the source-scan count.

If the printer does not support Image Object Content Architecture (IOCA), PSF might have converted your IOCA image to an IM1 image. In this case, the image size is also specified in the IDD structured field.

The values for the source-pel count and source-scan count can be specified in three separate parameter combinations in the Image Input Descriptor (IID) structured field or the Image Cell Position (ICP) structured field:

- The X-dimension and Y-dimension of the Image Size parameter in the IID structured field.
- The Cell Size X-dimension and Cell Size Y-dimension of the Default Image Cell Size parameter in the IID structured field.
- The X-dimension and Y-dimension of the Image Cell Size parameter in the ICP structured field.

The image block or image cell might be contained in an overlay, a page segment, or a MO:DCA document. It might also be embedded in a data set containing line data by using a Begin Image (BIM) structured field.

System action

If the image is in a page, the printer you were using might attempt to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might

be included on the printed page. PSF continues the processing of the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. If the image is in a resource, PSF stops processing the data set that uses the resource in error.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the resource or print data set containing the image, correct the error in the referenced structured field and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the resource or print data set containing the image, contact your system programmer.

APS809I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: MORE IMAGE DATA WAS PROVIDED IN THE IRD STRUCTURED FIELD THAN WAS NEEDED FOR THE SIZE OF THE IMAGE SPECIFIED IN THE IID OR ICP STRUCTURED FIELDS.**

Explanation

The amount of raster data that is sent in one or more Image Raster Data (IRD) structured fields was more than was specified to complete the image. The number of bytes of source image data that is sent in one or more IRD structured fields must equal the product of the source-pel count and the source scan-count. More raster data was received in the Raster Pattern parameter in one or more IRD structured fields than was specified by this number.

If the printer does not support Image Object Content Architecture (IOCA), PSF might have converted your

IOCA image to an IM1 image. In this case, the image size is also specified in the IDD structured field.

The values for the source-pel count and source-scan count can be specified in three separate parameter combinations in the Image Input Descriptor (IID) structured field or the Image Cell Position (ICP) structured field:

- The X-dimension and Y-dimension of the Image Size parameter in the IID structured field
- The Cell Size X-dimension and Cell Size Y-dimension of the Default Image Cell Size parameter in the IID structured field
- The X-dimension and Y-dimension of the Image Cell Size parameter in the ICP structured field

System action

If the image is in a page, the printer you were using might attempt to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues the processing of the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. If the image is in a resource, PSF stops processing the data set that uses the resource in error.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the resource or print data set containing the image, correct the error in the referenced structured field and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the resource or print data set containing the image, contact your system programmer.

APS810I

DATA IN A FONT RESOURCE IS NOT VALID: THE PATTERN DATA COUNT PARAMETER IN THE FNC STRUCTURED FIELD MUST BE A MULTIPLE OF 4 FOR A DOUBLE-BYTE FONT

Explanation

The Pattern Data Count parameter of the Font Control (FNC) structured field is not valid. The FNC structured field is contained in the font character set.

System action

PSF stops processing and printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a printer logic error or a PSF error. If you used a program to create the structured fields for the font, contact your system programmer.

APS811I

DATA IN A FONT RESOURCE IS NOT VALID: MORE FONT DATA WAS RECEIVED THAN WAS DEFINED IN THE PATTERN DATA COUNT PARAMETER OF THE FNC STRUCTURED FIELD.

Explanation

The Pattern Data Count parameter in the Font Control (FNC) structured field specified fewer bytes of data than were sent in one or more Font Pattern (FNG)

structured fields. The FNC and FNG structured fields are in the font character set.

System action

PSF stops processing and printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a printer logic error or a PSF error. If you used a program to create the structured fields for the font, contact your system programmer.

APS812I **DATA IN A FONT RESOURCE IS NOT VALID: LESS FONT DATA WAS RECEIVED THAN WAS DEFINED IN THE PATTERN DATA COUNT PARAMETER OF THE FNC STRUCTURED FIELD.**

Explanation

The Pattern Data Count parameter of the Font Control (FNC) structured field specified more bytes of data than were sent in one or more Font Pattern (FNG) structured fields. The FNC and FNG structured fields are in the font character set.

System action

PSF stops processing and printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set

in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a printer logic error or a PSF error. If you used a program to create the structured fields for the font, contact your system programmer.

APS813I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE TEXT CONTROL ESCAPE SEQUENCE MUST BE X'2BD3'.**

Explanation

While processing text, the printer detected an escape character X'2B' that was not immediately followed by X'D3'. The escape sequence is in a Presentation Text Data (PTX) structured field or was generated by PSF from a page definition. The Presentation Text Data (PTX) structured field might be contained in a MO:DCA document, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using might attempt to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see [PSF for z/OS: Diagnosis](#) for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document, an overlay, or a page segment and you created the structured fields in the object that contains the error, correct the text-control sequence in the Presentation Text Data (PTX) structured field. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the MO:DCA document, overlay, or page segment, contact your system programmer. If you are printing a data set containing line data with embedded structured fields, correct the text-control sequence in the PTX structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you are printing a data set containing line data without embedded structured fields, the error might be a PSF or printer logic error.

APS814I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE SHADING OR COVERAGE VALUE IN A X'4E' TRIPLET, SET EXTENDED TEXT COLOR CONTROL SEQUENCE, OR GOCA OBJECT IS NOT VALID.

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The coverage field value, the shading field value, or both are not valid in a Color Specification (X'4E') triplet for a highlight color.
2. The coverage field value, the shading field value, or both are not valid in a PTOCA Set Extended Text Color (SEC) control sequence for a highlight color.
3. The coverage field value, the shading field value, or both are not valid in a GOCA Set Process Color (GSPCOL), Linear Gradient (GLGD), or Radial Gradient (GRGD) drawing order for a highlight color.

The X'4E' triplet might occur on these structured fields:

- A Page Descriptor (PGD).

- An Object Area Descriptor (OBD).
- Include Object (IOB)

The PGD is contained in an Active Environment Group (AEG) for a page or an overlay, and the OBD is contained in an Object Environment Group (OEG) for a graphics, image, or bar code, or presentation text object, or an object container. The IOB structured field can be contained in a page definition, overlay, or MO:DCA page, or it can be embedded in line data.

The Set Extended Color control sequence is in a Presentation Text Data (PTX) structured field. The structured field might be contained in MO:DCA data, an overlay, or a page segment; or it might be embedded in a data set containing line data.

The Set Process Color, Linear Gradient, or Radial Gradient drawing order is in a Graphics Data (GAD) structured field. The structured field might be contained in MO:DCA data, an overlay, or a page segment; or, it might be embedded in a data set containing line data.

System action

Reporting of this exception can be controlled by the Color Fidelity triplet in the Presentation Fidelity Control (PFC) command. The PFC command is contained in a form definition.

When the Color Fidelity triplet sets the continuation rule to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and marks the data set unprintable. PSF releases the current data set back to JES and requests that it is held by the system unless PRTEROR=QUIT is specified on the OUTPUT statement.

When the Color Fidelity triplet sets the continuation rule to DO NOT STOP (X'02'), one of these occurs:

- If the printer supports the PFC Color Fidelity triplet and if the REPORT field is set to REPORT (X'01'), the printer reports this exception. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.
- If the printer supports the PFC Color Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.
- If the printer does not support the PFC Color Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer reports this exception but PSF does not issue the error message. The

printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

- If the printer does not support the PFC Color Fidelity triplet and the REPORT field is set to REPORT (X'01'), the printer reports this exception and PSF issues the error message. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

Operator response:

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response:

APS815I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN IMBEDDED TEXT CONTROL LENGTH FIELD VALUE IS OUT OF RANGE.

Explanation

While processing an embedded text control, the printer detected that the value of a text control length byte was outside the valid range for the specified text control. The text-control sequence is in a Presentation Text Data (PTX) structured field or was generated by PSF from a page definition. The PTX structured field might be contained in a MO:DCA document, a presentation text object, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using might attempt to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document, a presentation text object, an overlay, or a page segment and you created the structured fields in the object that contains the error, correct the text-control sequence in the Presentation Text Data (PTX) structured field. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the MO:DCA document, a presentation text object, overlay, or page segment, contact your system programmer. If you are printing a data set containing line data with embedded structured fields, correct the text-control sequence in the PTX structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you are printing a data set containing line data without embedded structured fields, the error might be a PSF or printer logic error.

APS816I AN INCORRECT DATA TRANSFER COUNT OR AN INCORRECT PRINTER COMMAND LENGTH WAS DETECTED WHILE TRANSMITTING THIS DATA SET TO THE PRINTER. PLEASE NOTIFY YOUR SYSTEM PROGRAMMER.

Explanation

While processing a printer command, the printer detected a printer command with a length that was outside the valid range for the specific printer command (except the 3800 Models 3, 6, and 8).

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of an error condition that caused the exception to be reported. For error sense X'80E0..00' (written as Byte 0 Byte1...Byte 19), one or both of these conditions occurred:

1. The length of an IPDS command was not within the allowed range.
2. The length of the data in an Intelligent Printer Data Stream (IPDS) Write Graphics Control (WGC), Write Image Control 2 (WIC2), or Write Bar Code Control (WBCC) command is not equal to the sum of the lengths of the self-defining fields (Area Position, Output Control, and Data Descriptor) that are in the command.

For error sense X'0202..02' (written as Byte 0 Byte1...Byte 19), one or more of these conditions occurred:

1. The length value of a command is less than X'05' (or less than X'07' if a correlation ID is included).
2. The length of a command is greater than X'7FFF'.
3. The command length is not valid or is unsupported for the particular command.
4. The length of the data in an IPDS WGC, WIC2, WBCC, Write Object Container Control (WOCC), or Include Data Object (IDO) command is not equal to the sum of the lengths of the self-defining fields within it.

While processing a 3800 printer command, the printer detected that the channel data transfer count was not valid.

The formatted printer sense byte message that accompanies this message identifies the command that contains the error.

System action

The printer you were using might attempt to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

Verify the printer command length or data count, and examine the 24 bytes of sense data in the formatted printer sense byte message. For more information about printer sense bytes and this error, see the

printer publications for the printer that reported this error.

User response

Inform your system programmer that this error occurred.

APS817A

AN INTERFACE CONTROL CHECK WAS RECEIVED. SOFTWARE RECOVERY IS IN PROGRESS. IF THE DEVICE *prtnnnn* INDICATES A SUCCESSFUL INITIAL MICROCODE LOAD (IML) THEN MAKE THE DEVICE READY.

Explanation

This message indicates that an interface-control check occurred. This condition occurred because the channel detected errors on the interface between the control unit and the channel. A hardware problem might exist. Because of these errors, the channel does a system reset, a selective reset, or an interface disconnect sequence. A system reset or selective reset causes the printer to restart the initial microcode load (IML) facility that is built into that device. When an IML is completed successfully, the printer presents a unit check to PSF with an action code of X'0D' (sense byte 2). The printer display panel informs the operator of the successful IML and the condition of the printer. To determine what is displayed on the printer's display panel for a successful IML, see the printer publications for the printer that reported this error. An interface disconnect sequence is transparent to PSF.

System action

PSF attempts to resynchronize with the printer by doing I/O until the interface control check is either cleared or determined to be permanent. PSF then does its error recovery.

Operator response

If necessary, press RESET, READY, or START on the printer. For more information about IMLs and the appropriate response, see the reference publication or the operator's guide for the printer that reported the error. If the error persists or the recovery was unsuccessful, stop PSF and consult your system programmer.

System programmer response

If the error condition persists, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

APS818I

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE FONT IDENTIFIER SPECIFIED IN A SET CODED FONT LOCAL TEXT CONTROL WAS NOT MAPPED IN THE PRINTER.

APSRMARK utility to mark the font PRIVATE so that the system version is sent to the printer. Alternatively, you can supply a new font that is equivalent to the requested font but not marked for use as a resident font, and provide the name of the new font to the print-job submitter whose application requested the font orientation that was not available in the printer.

Explanation

The Coded Font Local identifier in a Set Coded Font Local (SCFL) text control contains an incorrect value. The value is not valid, for one of these reasons:

- It is outside the valid range.
- It was not specified in the Map Coded Font (MCF) structured field.
- An attempt was made to use a printer-resident font in an orientation that is not available.

The SCFL text control is in a Presentation Text Data (PTX) structured field or was generated by PSF from a page definition. The Presentation Text Data (PTX) structured field might be contained in a MO:DCA document, an overlay, or a page segment; or it might be embedded in a data set containing line data. The MCF structured field might be in MO:DCA data, an overlay, or a page definition.

System action

The printer you were using might attempt to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see [PSF for z/OS: Diagnosis](#) for assistance in determining the source of the problem.

If the error involves a font that is marked for use as a resident font, and if an orientation of the font is required that is not resident in the printer, use the

User response

If the error was caused by the unavailability of a printer-resident font orientation, select a different font if possible. If you cannot use a different font, consult your system programmer.

If you are printing MO:DCA data, an overlay, or a page segment, and you created the structured fields in the object that contains the error, check the SCFL identifier with the MCF structured field. If the structured fields have no errors, the error might be a PSF or printer logic error, or the result of an attempt to use a printer-resident font in an orientation that is not available. If you are printing MO:DCA data, an overlay, or a page segment, and you used a program to create the structured fields in the object that contains the error, consult your system programmer.

If you are printing a data set containing line data, and you were using a page definition that you created, ensure that the MCF structured field contains all the fonts you want to use in this data set. If the MCF structured field has no errors, the error might be a PSF or printer logic error, or the result of an attempt to use a printer-resident font in an orientation that is not available. If you are printing a data set containing line data, and you were using a page definition that you created by use of a program, consult your system programmer.

If you are printing a data set containing line data with embedded structured fields, check the SCFL identifier with the MCF structured field. If the structured field has no errors, the error might be a PSF logic error, a printer logic error, or the result of an attempt to use a printer-resident font in an orientation that is not available.

For more information about the correct format of the referenced structured fields, see *Mixed Object Document Content Architecture Reference*.

APS819I

DOUBLE-BYTE FONT CHARACTER SETS ARE NOT SUPPORTED ON PRINTER *printer number*. ROUTE THE JOB TO A PRINTER THAT DOES SUPPORT DOUBLE-BYTE FONTS.

Explanation

The printer that is named does not support double-byte fonts.

System action

PSF stops processing the data set that was being processed at the time of the error and marks it unprintable. PSF releases the current data set back to JES and requests that it be held by the system unless PRTEROR=QUIT is specified on the OUTPUT statement.

Operator response

Release the print request as requested. If you are running under JES, use the JES data set release commands to release the data set to a printer that allows double-byte fonts. For a JES command to release the data set for printing, see the publication that contains JES commands for your operating system.

System programmer response

No response is necessary.

User response

Change the output class for the next submission. Consult the system operator to release the print request to a printer that can process double-byte fonts.

**APS820I A PARAMETER VALUE IN A
FORMDEF RESOURCE IS
UNSUPPORTED: THE MEDIUM
FINISHING CONTROL
STRUCTURED FIELD SPECIFIES
AN UNSUPPORTED FINISHING
OPERATION COUNT VALUE.**

Explanation

The finishing operation count field (byte 6) in a Finishing Operation triplet (X'85') contains an unsupported value.

Finishing Operation triplets are specified in the Medium Finishing Control (MFC) structured field. The MFC is specified in the Document Environment Group of the form definition or in a Medium Map.

System action

Reporting of this exception can be controlled by the Finishing Fidelity triplet in the Presentation Fidelity Control (PFC) command. The PFC command is contained in a form definition.

When the Finishing Fidelity triplet sets the continuation rule to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and marks the data set unprintable. PSF releases the current data set back to JES and requests that it is held by the system unless PRTEROR=QUIT is specified on the OUTPUT statement.

When the Finishing Fidelity triplet sets the continuation rule to DO NOT STOP (X'02'), one of these occurs:

- If the printer supports the PFC Finishing Fidelity triplet and if the REPORT field is set to REPORT (X'01'), the printer reports this exception. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.
- If the printer supports the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.
- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer reports this exception but PSF does not issue the error message. The printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.
- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to REPORT (X'01'), the printer reports this exception and PSF issues the error message. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in

the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the MFC with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If the output is not acceptable:

- Verify that you requested the appropriate form definition for the finishing operation intended.
- Submit the print request to a printer that can do the finishing operation.
- If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

**APS821I INSUFFICIENT [WCS | FONT | CPS
| RPS | PST | PBS | INTERNAL |
MAIN] PRINTER STORAGE IS
AVAILABLE TO CONTINUE
PROCESSING THE DATA SET.**

Explanation

The printer detected and reported an out-of-storage error with an action code of X'0C' (sense byte 2). A request for raster-pattern storage (RPS), writable-control storage (WCS), compressed-pattern storage (CPS), pattern storage (PST), or page-buffer storage (PBS) exceeded the available storage resources of the printer. If the word FONT is included in the message, the printer has insufficient RPS storage or WCS (3820 only) storage to load the font. If the word INTERNAL or MAIN is included in the message, the printer does not differentiate between different subpools of storage. Therefore, the printer only indicates that its storage is exceeded. This message is accompanied by a message that presents the printer sense bytes.

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of an error condition that caused the exception to be reported. For error sense X'0212..02' (written as Byte 0 Byte1...Byte 19), one or more of these conditions occurred:

1. Either pattern storage or auxiliary storage is insufficient to store a raster or outline font.
2. Insufficient storage exists to load the data for a symbol set font.
3. Insufficient storage exists to activate a symbol set font.

System action

PSF issues this message only after it attempted to resolve the out-of-storage error condition by deleting all resources in the printer that the current page at the received page counter does not require, and then resending the page. If PSF receives a second action code X'0C' error for the same page at the received page counter, PSF issues this message and stops processing the data set. If repositioning is not supported in the current environment, PSF stops processing the data set when it receives the first resource-constraint error.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If data stream errors stopped the processing of the page just before the page for which APS821I was issued, correct the data stream errors first and resubmit the print request. The condition that caused message APS821I to be issued might be resolved after the other errors are corrected. If the error is not because of data stream errors, this error occurred either because a page or a resource is too complex, or because the combination of two sides of a duplexed sheet is too complex. Make the page or resource less complex by deleting resources (for example, text, images, page segments, overlays, or fonts). Resubmit the print request.

**APS822I A PRINTER UNIT CHECK AFTER
AN INITIAL MICROCODE LOAD
HAS OCCURRED. PARTIAL OR
DUPLICATE PAGES MAY BE
PRINTED.**

Explanation

The printer presented a unit check with an action code of X'0D' (sense byte 2) to indicate that one of these occurred:

- The printer was IMLed in a typical manner.
- The printer was switched from an Offline state to an Online state.
- The printer IMLed because of a printer-detected error.
- The channel issued a System Reset (this applies only to channel-attached printers).
- The channel issued a Selective Reset (this applies only to channel-attached printers).

This message is accompanied by a message that presents the printer sense bytes. These sense bytes are unique to each printer. See the printer publications for the printer that reported this error. These sense bytes are unique to each printer. See the printer publications for the printer that reported this error.

System action

Pages in the printer's page buffer and all resources in the printer are lost. The printer resets its counters to zero. PSF resends pages to the printer, starting from the last known committed page counter or jam recovery page counter. PSF prints a message on a separate sheet in the data set to mark the position at which the recovery from this error was started. PSF also prints the same message at the end of the data set to indicate that the message was printed within the data set. Pages might be duplicated during the recovery. If repositioning is not supported in the current environment, PSF stops processing the data set.

Operator response

If necessary, press RESET and READY on the printer.

System programmer response

If the printer does an excessive number of automatic IMLs, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

The printed output might be acceptable. If any pages were duplicated, you might want to resubmit the print request. If the error persists, consult your system programmer.

APS823I AN ERROR OCCURRED WHILE PROCESSING AN ELECTRONIC

OVERLAY OR A BASE PAGE IN THE PRINTER ACCUMULATOR.

Explanation

The printer detected and reported a data check with an action code of X'10' (sense byte 2). This message is accompanied by a message that presents the printer sense bytes. These sense bytes are unique to each printer. See the printer publications for the printer that reported this error.

System action

PSF causes the printer to discard the printer's buffered data and to delete all overlays, page segments, and fonts. On the first occurrence of this error, the message is printed on a separate sheet in the data set to mark the position before recovery starts. PSF recovers by resending pages to the printer, starting from the last known committed page counter plus 1. On the second occurrence of this error, PSF prints the message at the end of the message data set, and stops processing the data set at the committed page counter plus 1.

Operator response

No response is necessary.

System programmer response

If the error condition persists, follow the procedures described in *PSF for z/OS: Diagnosis* before that contacts the IBM Support Center.

User response

If the output is not acceptable, resubmit the print request. If the error persists, the overlay or page might need to be modified.

APS824I THE MAXIMUM NUMBER OF FONTS IS ALREADY LOADED.

Explanation

While PSF was loading fonts, either the maximum number of fonts allowed on a single sheet was reached or a possible logic error exists.

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of an error condition that caused the exception to be reported. For error sense X'0218..02' (written as Byte 0 Byte1...Byte 19), one of these conditions occurred:

1. The font Host-Assigned ID for a raster, outline, or symbol set font is not valid or is unsupported. If the

printer indicates this reason for the error in bytes 16-17, too many fonts are specified for the sheet.

2. The font Host-Assigned ID for an additional orientation of a raster, outline, or symbol set font does not match that of any previously loaded font (possible logic error).
3. The font local ID in a Map Coded Font (MCF) or in a Fully Qualified Name triplet (FQN X'02') with an FQNTYPE of X'DE' on a Map Data Resource (MDR) structured field is not valid or is unsupported (possible logic error).
4. A font local ID is referenced in a Set Coded-Font Local (SCFL) control sequence or in the Presentation Text Data Descriptor (PTD) for the page, for a Symbol Set font, or for a Bar Code object in the Bar Code Data Descriptor, but the font is not mapped in the Active Environment Group (AEG) for the page (possible user or application generator error).
5. A font local ID referenced in a Presentation Text Data Descriptor (PTD) for the page, a Presentation Text Data (PTX) structured field, or a Bar Code object in the Bar Code Data Descriptor was mapped in the Active Environment Group (AEG) for the page, but is not activated (possible logic error).

For error sense X'028F..01' (written as Byte 0 Byte1...Byte 19), one of these conditions occurred:

1. The length of an activation command is not valid or is unsupported (possible logic error).
2. The font Host-Assigned ID for a raster or outline font is not valid or is unsupported. If the printer indicates this reason for the error in bytes 16-17, too many fonts are specified for the sheet.
3. The section ID in an activation command is not valid (possible logic error).
4. The font inline sequence in an activation command is not valid (possible logic error).
5. The resource type in an activation command is not valid (possible logic error).
6. The resource ID format in an activation command is not valid (possible logic error).
7. The resource type in an activation command is not valid with or is unsupported with the resource ID format specified (possible logic error).
8. The resource ID in an activation command is not valid (possible logic error).

System action

PSF recovers from the error by deleting any fonts that are not needed for the current page and then resending pages from the received page counter plus 1. If the error persists, PSF stops processing and

printing the data set that contains this error. If repositioning is not supported in the current environment, PSF stops processing the data set.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

If data stream errors stopped the processing of the page just before the page for which APS824I was issued, correct the data stream errors first and resubmit the print request. The condition that caused message APS824I to be issued might be resolved after the other errors are corrected. If the error is not because of data stream errors, remove some of the fonts that are called for by the sheet or resource, and resubmit the print request.

APS825I

A CHARACTER-RESIDUE CHECK WAS DETECTED DURING THE LOADING OF A DOUBLE-BYTE FONT. PLEASE INFORM YOUR SYSTEM PROGRAMMER.

Explanation

While printing with a double-byte font, the printer detected a character-residue check for the double-byte font requested. This error occurred either because the font raster data for a double-byte font was not valid, or because the printer malfunctioned while it was retrieving the font from compressed-pattern (CPS) storage. Sense information can be obtained from the record in SYS1.LOGREC. For an explanation of the sense bytes, see the printer publications for the printer that reported this error.

System action

PSF stops processing the data set at the committed page counter plus 1.

Operator response

If the error occurred because the printer malfunctioned while it was retrieving the font from CPS storage, suspend processing for all data sets that use double-byte fonts, and notify your system programmer.

System programmer response

If you suspect that the problem is caused by incorrect double-byte font data, check to see whether the

compression algorithm was correctly applied to the raster pattern data from one or more Font Pattern (FNG) structured fields. The FNG structured fields are in the font character set. If you suspect the problem is caused by a malfunction of the printer, you might want to suspend the processing of all print data sets that use double-byte fonts. If the error condition persists, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

Inform your system programmer that this error occurred.

APS826I DATA IN A FONT RESOURCE IS NOT VALID: THE UNIFORM INLINE OFFSET PARAMETER VALUE OF A FNC STRUCTURED FIELD MUST BE 0 FOR A DOUBLE-BYTE CODED FONT.

Explanation

While PSF was attempting to load a font, the printer detected an error in the Font Control (FNC) structured field. The Uniform Inline Offset parameter reports an incorrect value for what is identified as a double-byte font. The FNC structured field is contained in the font character set.

System action

PSF stops processing and printing the data set that uses the font that contains the error.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* and *Mixed Object Document Content Architecture Reference* for more

information about the structured field. If the structured field has no error, the error might be a printer logic error or a PSF error. If you used a program to create the structured fields for the font, contact your system programmer.

APS827I DATA IN A FONT RESOURCE IS NOT VALID: THE UNIFORM INLINE OFFSET PARAMETER VALUE OF A FNC STRUCTURED FIELD IS NOT VALID.

Explanation

The Uniform Inline Offset parameter in the Font Control (FNC) structured field is outside the valid range for a single-byte font. The FNC structured field is contained in the font character set.

System action

PSF stops processing and printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a printer logic error or a PSF error. If you used a program to create the structured fields for the font, contact your system programmer.

APS828I THE HORIZONTAL ADJUSTMENT VALUE FOR THE RASTER OVERLAY IS GREATER THAN THE HORIZONTAL ADJUSTMENT VALUE FOR THE PAGE IT IS INCLUDED ON.

Explanation

When a raster overlay is received by the printer, the active horizontal adjustment value is used to format the overlay for storage. If the operator adjusts a page to the left, and the page includes the stored overlay, the horizontal adjustment value that is associated with the overlay exceeds that for the page.

System action

PSF causes the printer to discard the printer's buffered data and to delete all overlays, page segments, and fonts. On the first occurrence of this error, the message is printed on a separate sheet in the data set to mark the position before recovery starts. PSF recovers by resending pages to the printer, starting from the last known committed page counter plus 1. On the second occurrence of this error, PSF prints the message at the end of the message data set and stops processing the data set at the committed page counter plus 1. If the error persists, ask your system operator not to attempt horizontal adjustment for this job.

Operator response

Pages that include a raster overlay must not be adjusted to the left by the operator.

System programmer response

No response is necessary.

APS829I	A PAPER JAM HAS OCCURRED WHILE ACCUMULATING SHEETS FOR A FINISHING OPERATION. PARTIAL OR DUPLICATE PAGES MAY BE PRINTED.
----------------	---

Explanation

Paper in the post processor was discarded. The printer detected and reported an asynchronous intervention-required error with an action code of X'0A' (sense byte 2). For more information about this error, see the printer publications for the printer that reported this error.

System action

PSF resends pages to the printer, starting from the jam recovery page counter. Pages might be duplicated during recovery. If repositioning is not supported in the current environment, PSF stops processing the data set.

Operator response

See the operator's guide for the printer that reported this error and clear the paper from the printer and post

processor. PSF assumes that pages between the jam recovery page counter and the stacked page counter are not damaged and do not need to be reprinted. If any pages between these two page counters do need to be reprinted, use the Job Entry Subsystem (JES) BACKSPACE command.

System programmer response

If the error condition persists, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

The printed output might be acceptable. If any pages were duplicated, you might want to resubmit the print request. If the error condition persists, consult your system programmer.

APS830I	THE ERROR SENSE BYTES 0-7 = error sense bytes 0-7, OVERLAY IDENTIFIER = overlay identifier, SEGMENT IDENTIFIER = segment identifier, COMMAND = command, OBJECT IDENTIFIER(14-15) = object identifier, ELEMENT IDENTIFIER(16-17) = element identifier, OBJECT TYPE(18) = object type, SENSE BYTE 19 = error sense byte 19, PAGE IDENTIFIER(20-23) = page identifier.
----------------	--

Explanation

This message formats and presents the 24 printer sense bytes that were reported to PSF at the time of an I/O error. A message that describes the specific I/O error accompanies this message.

- *Error sense bytes 0-7* are the first 8 bytes in the sense data, reported in hexadecimal.
- *Overlay identifier* is the identifier from the Begin Overlay or Include Overlay command in which the error occurred. This information was formatted from bytes 8 and 9 of the sense data.
- *Segment identifier* is the identifier from the Begin Page or Include Page Segment command in which the error occurred. This information was formatted from bytes 10 and 11 of the sense data.
- *Command* is the printer command that was being processed at the time the error was detected. This information was formatted from bytes 12 and 13 of the sense data.
- *Object identifier* is the identifier of the object (other than segment or overlay) in which the error occurred.

This information was formatted from bytes 14 and 15 of the sense data. The *object identifier* is:

- For a font object, the HAID from an AR, DF, LCPC, LFC, LFCSC, LFI, or LSS command.
- For a data-object-font component, the HAID from an AR DDOFC, or WOCC command.
- For a data object resource, the HAID from AR, DDOR, DORE, ICMR, IDO, LPD, RPO, WBCC, WGC, WIC2, or WOCC command.
- *Element identifier* is the identifier of an element within the object type reported in object identifier. This information was formatted from bytes 16 and 17 of the sense data. For I/O errors with explanations that list multiple causes in the PSF primary message or the *Intelligent Printer Data Stream Reference*, bytes 16 and 17 might contain the number of the specific cause. The *element identifier* contains information that is specific to the error sense (see Note on page “#unique_830/unique_830_Connect_42_note830” on page 315) that was reported:
 - For sense X'0821..00', X'0829..00', and X'028F..50', bytes 16–17 contain the code point that caused the error. For double-byte fonts, byte 16 contains the section ID and byte 17 contains the code point. For single-byte fonts, byte 17 contains the code point.
 - For sense X'0500..01' and X'0500..03', bytes 16–17 contain the IO-image self-defining field code that caused the error. For 1-byte codes, byte 16 contains X'00' and byte 17 contains the code.
 - For sense X'0412..00', bytes 16–17 contain the IO-image self-defining field code that caused the error. For 1-byte codes, byte 16 contains X'00' and byte 17 contains the code.
 - For sense X'0406..11', bytes 16–17 contain the size of the smallest valid symbol width in twips. A twip is a unit of measure that equals 1/20 of a point. 1440 twips are in 1 inch.
 - For sense X'03C3..03' and X'021A..03', bytes 16–17 contain the Unicode value in error:
 - When a high-order surrogate code value was not immediately followed by a low-order surrogate code value, bytes 16–17 contain the high-order surrogate value.
 - When a low-order surrogate code value was not immediately preceded by a high-order surrogate code value, bytes 16–17 contain the low-order surrogate code value.
 - When an UTF-8 code value sequence was specified that was not valid, bytes 16–17 contain the first 2 bytes of the UTF-8 code value sequence.

- For sense X'029C..02', bytes 16–17 contain the failing glyph ID.
- For sense X'0237..04', bytes 16–17 contain the inconsistent media destination ID.
- For sense X'025D..ee', where *ee* is a hex value, bytes 16–17 contain a CMR TagID value as defined in *Color Management Object Content Architecture Reference*.
- For sense X'020D..01', X'020D..05' and X'0115..00', bytes 16–17 contain an object-specific error code. See the primary message explanation for a list of object specific error codes.
- For sense X'0200..01', bytes 16–17 contain the unsupported or unrecognized PTOCA control sequence function type that caused this error. Byte 16 contains X'00' and byte 17 contains the function-type value.

Note: The error sense is written as Byte 0 Byte 1...Byte 19.

- *Object type* indicates the type of object identified by the ID in sense bytes 14–15 and 20–23:

Bits 0–3 Resource identified in bytes 14–15

- B'0000' Font object
- B'0001' Data object resource

Bits 4–7 Page identified in bytes 20–23

- B'0000' Page identifier from Begin Page command
- B'0001' Page sequence number associated with a saved page

- *Error sense byte 19* is byte 19 of the error sense.
- *Page identifier* identifies the page if the error was associated with a particular page.

System action

See the accompanying messages for the system action taken.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot be initialized or cannot print a separator page or an error message. Notify your system programmer.

System programmer response

To determine an appropriate response, see the specific error conditions described in the accompanying messages. For more information about printer sense bytes and the specific error, see the printer publications for the printer that reported this error.

User response

To determine an appropriate response, see the specific error conditions described in the accompanying messages.

APS831I **THE COMBINATION OF A CHANNEL CONTROL CHECK AND AN INTERFACE CONTROL CHECK WAS DETECTED IN THE CHANNEL STATUS WORD. THE MISSING INTERRUPT HANDLER TIMER HAS EXPIRED. SOFTWARE RECOVERY IS IN PROGRESS.**

Explanation

The I/O Supervisor sets both the channel control check bit and the interface control check bit in the channel status word to indicate that the Missing Interrupt-Handler (MIH) timer expired.

System action

PSF continues its attempts to do I/O to the printer until the MIH condition is cleared or is determined to be permanent. If permanent, PSF ends with an abend.

Operator response

Restart PSF. If the error persists, consult your system programmer.

System programmer response

Reset the limit for the MIH timer. For the MIH value that pertains to the device type, see informational APAR II02083, section "C." If the error condition persists, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

No response is necessary.

APS832I **THE ERROR SENSE BYTES 0–7 = error sense bytes 0–7, OVERLAY ID = overlay identifier, SEGMENT ID = segment identifier, COMMAND = command, TEXT, IMAGE OR IMAGE CELL, AND RULE POSITION ERROR COUNTS = number of text position errors, number of image position errors, AND number of rule position errors, SENSE BYTES 17–23 = error sense bytes 17–23.**

Explanation

This message formats and presents the 24 printer sense bytes that were reported to PSF at the time of an I/O error. A message that describes the specific I/O error accompanies this message.

- *Error sense bytes 0–7* are the first 8 bytes in the sense data, reported in hexadecimal.
- *Overlay identifier* is the identifier from the Begin Overlay or Include Overlay command in which the error occurred. This information was formatted from bytes 8 and 9 of the sense data.
- *Segment identifier* is the identifier from the Begin Page or Include Page Segment command in which the error occurred. This information was formatted from bytes 10 and 11 of the sense data.
- *Command* is the printer command that was being processed at the time the error was detected. This information was formatted from bytes 12 and 13 of the sense data.
- *Number of text position errors* is the number of times an attempt was made to print text characters outside of the valid printable area on this page. A value of 255 means 255 or more such errors were detected. This information was transformed to decimal from byte 14 of the sense data.
- *Number of image position errors* is the number of attempts that were made to print image cells outside of the valid printable area on this page. A value of 255 means 255 or more such errors were detected. Note that a data-stream image might consist of a number of image cells, and each image cell is sent to the printer as one image. This information was transformed to decimal from byte 15 of the sense data.
- *Number of rule position errors* is the number of attempts that were made to print rules outside of the valid printable area on this page. A value of 255 means 255 or more such errors were detected. This information was transformed to decimal from byte 16 of the sense data.
- *Error sense bytes 17–23* are the last 7 bytes in the sense data, reported in hexadecimal.

System action

See the accompanying messages for the system action that was taken.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot be initialized or cannot print a separator page or error messages. Notify your system programmer.

System programmer response

To determine an appropriate response, see the specific error conditions described in the accompanying messages. For more information about printer sense bytes and the specific error, see the printer publications for the printer that reported this error.

User response

To determine an appropriate response, see the specific error conditions described in the accompanying messages.

APS833I **THE ERROR SENSE BYTES 0–5 = error sense bytes 0–5, TEXT, IMAGE OR IMAGE CELL, AND RULE POSITION ERROR COUNTS = number of text position errors, number of image position errors AND number of rule position errors, SENSE BYTE 9 = sense byte 9, BUFFER OFFSET = printer buffer offset, PRINTER STATE = printer state, COMMAND = command, SENSE BYTES 14–23 = sense bytes 14–23.**

Explanation

This message formats and presents the 24 printer sense bytes that were reported to PSF at the time of an I/O error. A message that describes the specific I/O error accompanies this message.

- *Error sense bytes 0–5* are the first 6 bytes in the sense data, reported in hexadecimal.
- *Number of text position errors* is the number of attempts that were made to print text characters outside of the valid printable area on this page. A value of 255 means 255 or more such errors were detected. This information was transformed to decimal from byte 6 of the sense data.
- *Number of image position errors* is the number of attempts that were made to print image cells outside of the valid printable area on this page. A value of 255 means that 255 or more such errors were detected. Note that a data-stream image might consist of a number of image cells, and each image cell is sent to the printer as one image. This information was transformed to decimal from byte 7 of the sense data.
- *Number of rule position errors* is the number of attempts that were made to print rules outside of the valid printable area on this page. A value of 255 means 255 or more such errors were detected. This information was transformed to decimal from byte 8 of the sense data.

- *Sense byte 9* is the 10th byte in the sense data, reported in hexadecimal.
- *Printer buffer offset* is the approximate byte number (in decimal) in the data that is sent by the channel command that the printer was processing when it detected the error. This information was transformed from bytes 10 and 11 of the sense data.
- *Printer state* is the state of the printer at the time the error was detected. This information was formatted from byte 12 of the sense data.
- *Channel command* is the channel command that was being processed at the time the error was detected. This information was formatted from byte 13 of the sense data.
- *Sense bytes 14–23* are the last 10 bytes in the sense data, reported in hexadecimal.

System action

See the accompanying messages for the system action that was taken.

Operator response

No response is necessary.

System programmer response

If the accompanying messages are not sufficient to identify the problem, use the sense data to analyze the problem. For more information about printer sense bytes and the specific error, see the printer publications for the printer that reported this error.

User response

If the accompanying messages are not sufficient to identify the problem, contact your system programmer.

APS834I **ONE OR MORE CHARACTERS, RULES, IMAGES, OR IMAGE CELLS WERE SPECIFIED TO PRINT OUTSIDE OF THE VALID PRINTABLE AREA, AND THE ADDRESSABILITY LIMIT OF THE PRINTER WAS EXCEEDED.**

Explanation

An attempt was made to print outside of the valid printable area. This area is the intersection (common space) of the physical page with the logical page or with an overlay. One or more characters, rules, or images fall at least partially outside of the valid printable area.

In addition, the print position that is specified for one of the items exceeded the addressability limit of the printer; that is, it was considerably outside of the printable area boundary. This message is accompanied by a message that presents the printer sense bytes. These sense bytes are unique to each printer. See the printer publications for the printer that reported this error.

System action

A partial page is printed with print-error markers up to this addressability error. The print-error markers are printed at the perimeter of the valid printable area, where attempts were made to cross the boundary. Characters, rules, and images that were not defined completely within the valid printable area are not printed. PSF continues processing the current data set with the page that follows the page that contains the error.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot be initialized or cannot print a separator page or error messages. Notify your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing MO:DCA data, an overlay, or a page segment, and you created the structured fields in the object that contains the error, check the print positioning values in the text-control sequence in the Presentation Text Data (PTX) structured field for positioning outside of the page. If you are printing MO:DCA data, an overlay, or a page segment, and you used a program to create the structured fields in the object that contains the error, consult your system programmer.

If you are printing an image, coordinate the image dimensions with the logical page size.

If you are printing a data set containing line data by using a page segment that you created, check the print-positioning values in the Line Descriptor (LND) structured field.

If you are printing a data set containing line data with embedded structured fields, check the PTX structured field for positioning outside of the page.

APS835I **ONE OR MORE CHARACTERS, RULES, IMAGES, OR IMAGE CELLS WERE SPECIFIED TO PRINT OUTSIDE OF THE VALID PRINTABLE AREA, AND SOME PRINT-ERROR MARKERS WERE NOT PRINTED BECAUSE OF THE COMPLEXITY OF THE PAGE.**

Explanation

An attempt was made to print outside of the valid printable area. This area is the intersection (common space) of the physical page with the logical page or with an overlay. One or more characters, rules, or images fall at least partially outside of the valid printable area.

In addition, the complexity of the page prevented the printing of all the print-error markers that would otherwise be presented to show where attempts were made to print outside the valid printable area. Such a complex page is handled by using an optional accumulator when available, but this message is issued when the accumulator feature is not installed in the printer.

System action

The entire page is printed. Some print-error markers might be printed at the perimeter of the valid printable area, where attempts were made to cross the boundary. One or more print-error markers were not printed because of the lack of printer storage to handle the complexity of the page when markers are included. Characters, rules, and images that were not defined completely within the valid printable area are not printed. The processing of the data set continues.

Operator response

No response is necessary.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing MO:DCA data, an overlay, or a page segment, and you created the structured fields in the

object that contains the error, check the print positioning values in the text-control sequence in the Presentation Text Data (PTX) structured field for positioning outside of the page. If you are printing MO:DCA data, an overlay, or a page segment, and you used a program to create the structured fields in the object that contains the error, consult your system programmer.

If you are printing an image, coordinate the image dimensions with the logical page size.

If you are printing a data set containing line data by using a page segment that you created, check the print-positioning values in the Line Descriptor (LND) structured field.

If you are printing a data set containing line data with embedded structured fields, check the PTX structured field for positioning outside of the page.

APS836I DUE TO AN I/O ERROR ON THIS DATA SET, A DUPLICATE PAGE MAY BE PRINTED.

Explanation

The printer reported an error in the data stream to PSF while the printer was processing this data set. The data stream error is reported in a previous PSF error message in the message data set.

System action

This message is printed both on a separate sheet in the data set to mark the position at which the recovery from this error was started and in the message data set at the end of the print data set. Pages might be duplicated during the recovery. PSF continues processing the current data set with the page after the page that contains the error.

Operator response

No response is necessary.

System programmer response

If the error condition persists, follow the procedures in *PSF for z/OS: Diagnosis* before you consult the IBM Support Center.

User response

The printed output might be acceptable. If pages are duplicated, resubmit the print request. If the error condition persists, consult your system programmer.

APS837I AN INTERVENTION-REQUIRED CONDITION AT THE PRINTER MAY

HAVE CAUSED PARTIAL, MISSING, OR DUPLICATE PAGES.

Explanation

An intervention-required condition (paper jam, out of paper, or printer not ready for 10 minutes) occurred while the data set was being printed on a 4224 printer or a 4234 printer. As a result, the output might contain partial, missing, or duplicate pages

System action

PSF prints this message at the end of the print data set. The processing of the print data set continues.

Operator response

No response is necessary.

System programmer response

If the error condition persists, follow the procedures described in *PSF for z/OS: Diagnosis* before you consult the IBM Support Center.

User response

The output might be acceptable. If any pages are duplicated, resubmit the print request. If the error condition persists, consult your system programmer.

APS838I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE NUMBER OF BITS SPECIFIED FOR A COLOR COMPONENT IN A X'4E' TRIPLET, SET EXTENDED TEXT COLOR CONTROL SEQUENCE, OR GOCA OBJECT IS NOT VALID OR IS UNSUPPORTED.

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. A value that is specified in the Colsize1, Colsize2, Colsize3, or Colsize4 field of a Color Specification (X'4E') triplet is not valid or is unsupported.
2. The Colsize fields in a Color Specification (X'4E') triplet specify length values that are inconsistent with the triplet length value.
3. A value that is specified in the Colsize1, Colsize2, Colsize3, or Colsize4 field of a PTOCA Set Extended Text Color (SEC) control sequence is not valid or is unsupported.

4. The Colsize fields in a PTOCA Set Extended Text Color (SEC) control sequence specify length values that are inconsistent with the control sequence length value.
5. A value that is specified in the Colsize1, Colsize2, Colsize3, or Colsize4 field of a GOCA Set Process Color (GSPCOL), Linear Gradient (GLGD), or Radial Gradient (GRGD) drawing order is not valid or is unsupported.
6. The Colsize fields in a GOCA Set Process Color (GSPCOL) drawing order specify length values that are inconsistent with the drawing order length value.
7. The Colsize fields in a GOCA Linear Gradient (GLGD) or Radial Gradient (GRGD) drawing order specify length values that are inconsistent with the length value in the start color specification.

The X'4E' triplet might occur on these structured fields:

- A Page Descriptor (PGD).
- An Object Area Descriptor (OBD).
- Include Object (IOB)

The PGD is contained in an Active Environment Group (AEG) for a page or an overlay, and the OBD is contained in an Object Environment Group (OEG) for a graphics, image, or bar code, or presentation text object, or an object container. The IOB structured field can be contained in a page definition, overlay, or MO:DCA page, or it can be embedded in line data.

The Set Extended Color control sequence is in a Presentation Text Data (PTX) structured field. The structured field might be contained in MO:DCA data, an overlay, or a page segment; or it might be embedded in a data set containing line data.

The Set Process Color, Linear Gradient, or Radial Gradient drawing order is in a Graphics Data (GAD) structured field. The structured field might be contained in MO:DCA data, an overlay, or a page segment; or, it might be embedded in a data set containing line data.

System action

The printer you were using might attempt to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

If the object is in a resource, PSF stops processing the data set that uses the resource in error.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If the structured fields are not valid and you created the structured fields for the resource or print data set containing the image, correct the error in the referenced structured field and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the resource or print data set containing the image, contact your system programmer.

If the color value is unsupported by this printer, resubmit the print request to a printer that does support this color value.

AP5839I

A PARAMETER VALUE IN A FORMDEF RESOURCE IS NOT VALID OR IS UNSUPPORTED: THE MEDIUM FINISHING CONTROL STRUCTURED FIELD SPECIFIES AN INCORRECT OR UNSUPPORTED FINISHING OPERATION AXIS OFFSET VALUE.

Explanation

The axis offset field (bytes 7–8) in a Finishing Operation triplet (X'85') contains an incorrect or unsupported value.

Finishing Operation triplets are specified in the Medium Finishing Control (MFC) structured field. The MFC is specified in the Document Environment Group of the form definition or in a Medium Map.

System action

Reporting of this exception can be controlled by the Finishing Fidelity triplet in the Presentation Fidelity

Control (PFC) command. The PFC command is contained in a form definition.

When the Finishing Fidelity triplet sets the continuation rule to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and marks the data set unprintable. PSF releases the current data set back to JES and requests that it is held by the system unless PRERROR=QUIT is specified on the OUTPUT statement.

When the Finishing Fidelity triplet sets the continuation rule to DO NOT STOP (X'02'), one of these occurs:

- If the printer supports the PFC Finishing Fidelity triplet and if the REPORT field is set to REPORT (X'01'), the printer reports this exception. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.
- If the printer supports the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.
- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer reports this exception but PSF does not issue the error message. The printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.
- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to REPORT (X'01'), the printer reports this exception and PSF issues the error message. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the MFC with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If the output is not acceptable:

- Verify that you requested the appropriate form definition for the finishing operation intended.
- Submit the print request to a printer that can do the finishing operation.
- If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS840I	THE MAXIMUM NUMBER OF PAGE SEGMENTS THE PRINTER WILL ACCEPT MAY HAVE BEEN EXCEEDED BY A SIMPLEX PAGE OR BY THE FRONT AND BACK OF A DUPLEX SHEET.
----------------	---

Explanation

While loading page segments in the printer, the printer detected and reported that a page segment number was out of the valid range. This error might be caused by a simplex page or by the front and back of a duplex sheet that contains more page segments than the printer can accept.

System action

PSF recovers from the error by deleting any page segments that are not needed for the current sheet at the received page counter, and then resending the page. If PSF receives a second occurrence of this error, PSF issues this message and ends. If repositioning is

not supported in the current environment, PSF stops processing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If data stream errors stopped the processing of the page that precedes the page for which APS840I was issued, correct the data stream errors first, and resubmit the print request. The condition that caused message APS840I to be issued might be resolved after the other errors are corrected. If the error is not because of data stream errors, delete some of the page segments on the simplex page or duplex sheet at the received page counter plus 1. If the simplex page or duplex sheet at the received page counter plus 1 does not exceed the number of page segments that the printer can accept, a PSF or printer logic error might have occurred.

APS841I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE RELATIVE METRIC MULTIPLYING FACTOR IN THE LOAD FONT CONTROL IS NOT VALID OR IS UNSUPPORTED.**

Explanation

The font contains incorrect data. The character set FNC structured field has an incorrect vertical point size or host-font resolution.

System action

The printer you were using might attempt to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Consult your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

APS842I **THE CANCEL BUTTON ON THE PRINTER CONTROL PANEL WAS PRESSED WHILE THE PRINTER WAS PROCESSING A DATA SET.**

Explanation

The printer detected and reported to PSF that the cancel button on the printer control panel was pressed while the printer was processing a data set. For more information about this condition, see the printer publications for the printer that reported this error.

System action

If the committed copy counter is greater than zero, PSF cancels the data set at the committed page counter plus 1; otherwise, PSF cancels the data set at the committed page counter.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

If wanted, resubmit the data set that was canceled. If the error persists, consult the operator to see why the cancel button is being pressed.

APS843I THE PAGE BEING PROCESSED WAS TOO COMPLEX TO PRINT. ONE OR MORE OBJECTS MAY HAVE TO BE REMOVED FROM THE PAGE IN ORDER TO PRINT IT.

Explanation

An equipment check during printing indicated a print overrun. The page at the committed page counter plus 1 was too complex to print. The printer detected and reported an asynchronous error with an action code of X'09' (sense byte 2). This error occurs either because too many items (for example, images) were placed on a page or because too many overstrikes were requested. Sense information can be obtained from the record in SYS1.LOGREC. For an explanation of the sense bytes, see the printer publications for the printer that reported this error.

System action

When the print error was detected, the printer was attempting to print a page that was too complex. PSF stops processing the data set at the committed page counter plus 1.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Remove some of the resources on the page (for example, overlays, images, or page segments), or remove some of the data from the page, and resubmit the print request. See Performance Considerations in the printer publications for the specific printer that reported the error.

APS844I A HARDWARE-RELATED PRINT ERROR OCCURRED DURING THE PRINTING OF THIS DATA SET. PARTIAL OR DUPLICATE PAGES MAY BE PRINTED.

Explanation

A temporary hardware-related print error (for example, an image-generator error) occurred in the printer, and

caused the printer to require recovery. The printer detected and reported an asynchronous error with an action code of X'16' (sense byte 2). For more information about this error, see the printer publications for the printer that reported this error.

System action

PSF resends pages to the printer, starting from the committed page counter plus 1. PSF might print this message on a separate sheet in the data set to mark the position at which the recovery from this error was started. Pages might be duplicated during the recovery.

Operator response

If the error condition persists, consult your system programmer.

System programmer response

If the error condition persists, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

The printed output might be acceptable. If any pages were duplicated, you might want to resubmit the print request. If the error persists, consult your system programmer.

APS845I A PERMANENT HARDWARE ERROR WAS DETECTED BY THE PRINTER.

Explanation

A permanent hardware error was reported by the printer to indicate that the printer cannot be used. The printer detected and reported an asynchronous error with an action code of X'17' (sense byte 2). For more information about this error, see the printer publications for the printer that reported this error.

System action

PSF issues this message and ends with an abend.

Operator response

PSF can be restarted, if you use an operational printer.

System programmer response

If the error condition persists, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

Inform your system programmer that this error occurred.

APS846I AN INTERFACE CONTROL CHECK OR MIH TIMER EXPIRATION OCCURRED DURING THE PRINTING OF THIS DATA SET. PARTIAL OR DUPLICATE PAGES MAY BE PRINTED.

Explanation

While PSF is communicating with the channel, it detected an interface control check or a missing interrupt-handler expiration. After the interface control check or missing interrupt-handler timer expiration, PSF issued more I/O commands. The interface control check or missing interrupt-handler condition was reported to PSF in the Channel Status Word Channel Status byte.

System action

PSF resynchronizes with the printer and resends pages to the printer, starting from the committed page counter. If repositioning is not supported in the current environment, PSF stops processing the data set.

Operator response

No response is necessary.

System programmer response

For more information about this error, see the Principles of Operation publication for your operating system. If the error condition persists, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

The printed output might be acceptable. If any pages were duplicated, you might want to resubmit the print request. If the error persists, consult your system programmer.

APS847I THE PRINTER SETUP WAS CHANGED WHILE THE PRINTER WAS PROCESSING A DATA SET. PARTIAL OR DUPLICATE PAGES MAY BE PRINTED.

Explanation

The printer characteristics were changed in the printer, and the printer discarded its buffered pages. The printer reports an action code X'1D' to instruct PSF to

obtain the new printer characteristics and redrive buffered pages. For more information about this condition, see the printer publications for the printer that reported this error.

System action

PSF obtains the new printer characteristics, and then resends pages to the printer, starting from the committed page counter plus 1. PSF might print this message on a separate sheet in the data set to mark the position at which the recovery from this error was started. Pages might be duplicated during the recovery.

If repositioning is not supported in the current environment, PSF stops processing the data set.

Operator response

Inform your system programmer that this error occurred.

System programmer response

If the printer characteristics were not changed at the printer and the error condition persists, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

The printed output might be acceptable. If any pages were duplicated, you might want to resubmit the print request. If the error persists, consult your system programmer.

APS848I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE SET TEXT COLOR CONTROL SEQUENCE CONTAINS AN INCORRECT OR UNSUPPORTED TEXT COLOR OR PRECISION.

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The color field in the Set Text Color (STC) control sequence is not valid or is unsupported.
2. The text color in the Initial Text Condition parameters of the Presentation Text Data Descriptor (PTD) structured field is not valid or is unsupported.
3. The precision field in the Set Text Color (STC) control sequence is not valid or is unsupported.

The control sequence is in a Presentation Text Data (PTX) structured field or was generated by PSF from a page definition. The PTX structured field might be contained in a MO:DCA document, a presentation text object, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action:

Operator response:

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response:

APS849I **ONE OR MORE CHARACTERS, RULES, IMAGES, OR IMAGE CELLS WERE SPECIFIED TO PRINT OUTSIDE OF THE VALID PRINTABLE AREA, AND THE PRINT POSITION COULD NOT BE REPRESENTED IN THE PRINTER.**

Explanation

An attempt was made to print outside of the valid printable area. This area is the intersection (common space) of the physical page with the logical page or with an overlay. One or more characters, rules, or images fall at least partially outside of the valid printable area. In addition, the print position that is specified for one of the items exceeds the addressable-memory limit of the printer. During the computation of the current print position, an overflow or underflow of the -32,768 to +32,768 range was detected.

System action

A partial page is printed with print-error markers at the perimeter of the valid printable area where attempts were made to cross the boundary. PSF continues processing the current data set with the page after the page that contains the error.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing MO:DCA data, an overlay, or a page segment, and you created the structured fields in the object that contains the error, check the print-positioning values in the text-control sequence in the Presentation Text Data (PTX) structured field for positioning outside of the page. If you are printing a MO:DCA print data set, an overlay, or a page segment, and you used a program to create the structured fields in the object that contains the error, consult your system programmer.

If you are printing an image, coordinate the image dimensions with the logical page size.

If you are printing a data set containing line data, and you were using a page segment that you created, check the print-positioning values in the Line Descriptor (LND) structured field.

If you are printing a data set containing line data with embedded structured fields, check the PTX structured field for positioning outside of the page.

APS850I **A CONDITION OCCURRED IN THE PRINTER OR A FUNCTION WAS SELECTED ON THE PRINTER CONTROL PANEL WHILE THE PRINTER WAS PROCESSING A DATA SET. PARTIAL OR DUPLICATE PAGES MAY BE PRINTED.**

Explanation

An error condition in the printer, or a function that was selected on the printer control panel, caused the printer to discard its buffered pages. The printer reports an action code X'1A' to instruct PSF to redrive buffered pages. For more information about this condition, see the printer publications for the printer that reported this error.

System action

PSF resends pages to the printer, starting from the committed page counter plus 1. Pages might be duplicated during the recovery.

If repositioning is not supported in the current environment, PSF stops processing the data set.

Operator response

Inform your system programmer that this error occurred.

System programmer response

If a function was not selected at the printer, and the error condition persists, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

The printed output might be acceptable. If any pages were duplicated, you might want to resubmit the print request. If the error persists, consult your system programmer.

APS851I THE PRINTER REPORTED A DATA STREAM ERROR THAT PSF DOES NOT RECOGNIZE. THE DATA SET IS TERMINATED.

Explanation

- The printer reported a data stream error that PSF does not recognize. This message is accompanied by a message that presents the printer sense bytes.

System action

PSF releases the current data set back to JES and requests that it is held by the system unless PRTEROR=QUIT is specified on the OUTPUT statement.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error condition persists, follow the procedures described in *PSF for z/OS: Diagnosis* before you contacts the IBM Support Center.

User response

Inform your system programmer that this error occurred.

APS852I AN UNEXPECTED VALUE WAS DETECTED IN THE CHANNEL STATUS WORD (CSW): THE CSW UNIT STATUS BYTE = X' unit status byte' AND THE CSW CHANNEL

STATUS BYTE = X' channel status byte'.

Explanation

The PSF I/O Error Manager subcomponent detected an unexpected condition in the Channel Status and Unit Status bytes of the Channel Status Word (CSW). I/O Error Manager expects the device-dependent Error Recovery Procedures (ERPs) and the PSF Device Manager subcomponent to handle certain conditions represented by CSW bit settings, without passing control to I/O Error Manager.

System action

PSF issues this message and ends with an abend.

Operator response

Restart PSF. If the error persists, notify your system programmer.

System programmer response

For more information about the Channel Status Word and this CSW bit setting, see the Principles of Operation publication for your operating system. If the error condition persists, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

No response is necessary.

APS853I mechanism name IS DISABLED. THE PRINTER REPORTED AN ATTEMPT TO USE THE DISABLED MECHANISM.

Explanation

PSF attempted to use a mechanism in the printer that is disabled. Because PSF was initialized for the printer, the status of the mechanism that is listed in the message text changed from "installed and available" to "installed but not available" (disabled).

System action

PSF issues this message and ends with an abend.

Operator response

If the disabled mechanism in the printer is not required for the print data set being processed, restart PSF.

System programmer response

If the mechanism that is indicated in the message is not disabled in the printer, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

No response is necessary.

APS854I THE PRINTER DID NOT REPORT ALL DATA STREAM ERRORS DUE TO THE EXCESSIVE NUMBER OF DATA STREAM ERRORS ON THE PAGE IN ERROR.

Explanation

The printer detected so many data stream errors for the current page at the received page counter plus 1, that the printer cannot report all of them to PSF. The printer reported the data stream errors that it was able to store in its error queue. This message is accompanied by a message that presents the printer sense bytes. These sense bytes are unique to each printer. See the printer publications for the printer that reported this error.

System action

PSF prints error messages for the errors that the printer reported, and bases its error recovery on the error with the highest priority.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

Correct the errors that were reported. Resubmit the corrected print request to receive the additional errors that were not reported because of this constraint on printer storage.

APS855I TEXT EXTENDS BEYOND THE VALID PRINTABLE AREA.

Explanation

The printer detected and reported that one or more attempts were made to print text outside of the valid printable area. This message is accompanied by a message that presents the printer sense bytes. These sense bytes are unique to each printer. See the printer publications for the printer that reported this error. The error was caused by one or more of these:

- The positioning of characters on the line placed the first character outside of the physical page.
- The characters are placed incorrectly.
- The combination of the placement of the baseline and the font that is used to print the data causes the first pel for the graphic character raster pattern to be placed outside the valid printable area.
- The selected font causes the character to be placed outside of the page boundary.
- A character pattern was placed outside the valid printable area because the characters in the font have "on pels" that precede the character reference point.
- A positioning text-control sequence (Absolute Move Inline [AMI], Absolute Move Baseline [AMB], Relative Move Inline [RMI], or Relative Move Baseline [RMB]) placed the first pel for the graphic character raster pattern outside of the physical page. The text-control sequence is in a Presentation Text Data (PTX) structured field or was generated by PSF from a page definition. The PTX structured field might be contained in a MO:DCA document, a presentation text object, an overlay, or a page segment; or it might be embedded in a data set containing line data.
- The wrong paper size was mounted.
- An incorrect output class was specified.

System action

The printer you were using might attempt to print the page in error. The entire page might not be printed. The page in error is printed with print-error markers to indicate the position and direction of the positioning errors. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

Ensure that the correct paper size is mounted.

System programmer response

No response is necessary.

User response

Ensure that the correct form was loaded in the printer. If it was, and if your printed output would be acceptable without the print-error markers, you can resubmit the print request, specifying BLOCK or BLKPOS for the DATAKEY keyword of the OUTPUT JCL statement. If you want to correct the source of the problem, and if you were printing MO:DCA data, check the current print position relative to the edges of the physical page. Place the logical page so that it does not extend into the unprintable area of the physical page. Use a different font, if necessary, so that the print position is inside the printable area. If you created the structured fields for an overlay, a presentation text object, or MO:DCA data, check the PTX structured field for positioning outside of the page.

If you are printing a data set containing line data, you might change the font selected from the page definition or the CHARS keyword on the JCL to a smaller font. If you created the structured fields for the page definition, check the print-positioning values in the Line Descriptor (LND) structured field and correlate them with the edges of the physical page.

If you are printing a data set containing line data with embedded structured fields, check the PTX structured field for positioning outside of the page.

APS856I

ONE OR MORE RULES EXTEND BEYOND THE VALID PRINTABLE AREA.

Explanation

The printer detected and reported one or more attempts to print one or more rules outside of the valid printable area. This message is accompanied by a message that presents the printer sense bytes. The inline or baseline dimension of the Width or Length parameter, in either the Draw Inline Rule (DIR) or the Draw Baseline Rule (DBR) text-control sequence, caused the rule to exceed the right, bottom, left, or top of the logical page. The direction in which the rule was off the page is relative to the paper as it moves through the printer, rather than to the logical page; for example, the top of the sheet is the perforated edge that leads through the printer. The error was caused by one or more of these:

- The rule width or length that is specified in either the Draw Inline Rule (DIR) or the Draw Baseline Rule (DBR) text-control sequence caused the print position to be outside of the physical page.
- The Horizontal Page Size and Vertical Page Size subparameters in the Page Descriptor (PGD) structured field specified values that caused the width to extend off the logical page.

- The wrong paper size is mounted.
- The output class is incorrect.

The text-control sequence is in a Presentation Text Data (PTX) structured field. The structured field might be contained in a MO:DCA document, an overlay, or a page segment; or it might be embedded in a data set containing line data. The PGD structured field is in MO:DCA data, an overlay, or a page definition.

System action

The printer you were using might attempt to print the page in error. The entire page might not be printed. The page in error is printed with print-error markers to indicate the position and direction of the positioning errors. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

Ensure that the correct paper size is mounted.

System programmer response

No response is necessary.

User response

Ensure that the correct form was loaded in the printer. If it was, and if your printed output would be acceptable without the print-error markers, you can resubmit the print request, specifying BLOCK or BLKPOS for the DATAKEY keyword on the OUTPUT JCL statement. If you want to correct the source of the problem, you might change the size of the logical page. If you want the logical page size to remain the same, and if you were printing a page segment, an overlay, or MO:DCA data, and you created the structured fields for the object that contains the error, check the text-control sequence in the PTX structured field for positioning outside of the page.

If you are printing a data set containing line data, and you were using a page segment that you created, check the print-positioning values in the Line Descriptor (LND) structured field and correlate them with the edge of the page that was exceeded (logical or physical).

If you are printing a data set containing line data with embedded structured fields, check the PTX structured field for positioning outside of the page.

APS857I

ONE OR MORE IMAGES OR IMAGE CELLS EXTENDS BEYOND THE VALID PRINTABLE AREA.

Explanation

The printer detected and reported an image that extends outside of the valid printable area. This message is accompanied by a message that presents the printer sense bytes. The position or direction in which the image was off the page is relative to the paper as it moves through the printer, rather than to the logical page; for example, the top of the sheet is the perforated edge that leads through the printer. The error was caused by one or more of these:

- The horizontal or vertical coordinates of the image were outside of the logical page size specified in the Page Size parameter in the Page Descriptor (PGD) structured field. The PGD structured field is in MO:DCA data, an overlay, or a page definition.
- The Image Size parameter in the Image Input Descriptor (IID) structured field, when added either to the Horizontal Coordinate or to the Vertical Coordinate subparameter of the Image Output Control (IOC) structured field, placed the image outside of the logical page.
- Either the X-position or the Y-position subparameter of the Image Cell Position (ICP) structured field placed the image outside of the logical-page size.
- Within line data, the image can be placed relative to the current print position. Therefore, the font that is used to print the data determined the start of the image and caused the image to be outside of the logical page.
- The font that is used to print the data caused the image to be outside of the physical page.
- The wrong paper size is mounted.
- The output class is incorrect.

The image block or image cell might be contained in an overlay, a page segment, or a MO:DCA document. It might also be embedded in a data set containing line data by using a Begin Image (BIM) structured field.

System action

The printer you were using might attempt to print the page in error. The entire page might not be printed. The page in error is printed with print-error markers to indicate the position and direction of the positioning errors. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

Ensure that the correct paper size is mounted.

System programmer response

No response is necessary.

User response

Ensure that the correct form was loaded in the printer. If it was, and if your printed output would be acceptable without the print-error markers, you can resubmit the print request, specifying BLOCK or BLKPOS for the DATAKEY keyword on the OUTPUT JCL statement. If you want to correct the source of the problem, and if the image was positioned relative to the print position, you can use a different font so that the image origin falls inside the printable area. You can also change the size of the logical page. If you want the font and the logical page size to remain as defined, and you created the structured fields for the image, coordinate the IOC, ICP, or IID structured fields with the logical page size.

APS858I

SYSTEM ACTION TAKEN: PSF STOPPED PROCESSING THE PAGE IN ERROR AND CONTINUES TO PROCESS THE DATA SET STARTING WITH THE NEXT PAGE. THE PRINTER MIGHT STILL PRINT THE PAGE IN ERROR.

Explanation

This message indicates the recovery that PSF does when the printer reports an I/O error to PSF. This message accompanies a message that describes the I/O error and a message that displays the sense bytes reported from the printer.

System action

The printer you were using might attempt to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

To determine an appropriate response, see the specific error conditions described in the accompanying messages.

User response

To determine an appropriate response, see the specific error conditions described in the accompanying messages.

APS859I **SYSTEM ACTION TAKEN: PSF TERMINATED THE DATA SET THAT CONTAINED THE PAGE IN ERROR. PSF WILL PROCESS THE NEXT DATA SET.**

Explanation

This message indicates the recovery that PSF does when the printer reports an I/O error to PSF. This message accompanies a message that describes the I/O error and a message that displays the sense bytes reported from the printer.

System action

The printer you were using might attempt to print the page that contains the error, or might print only part of the page. If the page that contains the error contains any positioning errors, print-error markers might be included on the printed page. PSF stops processing and printing the data set that contains this error.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

To determine an appropriate response, see the specific error conditions described in the accompanying messages.

User response

To determine an appropriate response, see the specific error conditions described in the accompanying messages.

APS860I **THE SPECIFIED INPUT BIN CANNOT BE USED WITH THE SPECIFIED OUTPUT BIN.**

Explanation

The specified media source cannot be used with the specified media destination. One example of this type of error is using inserts that are on a post processor input bin and routing the data set to an output bin located back on the printer.

Note: In the formatted sense message (APS830I), the second byte of the Object Identifier (byte 15) contains a media-source ID, and the Element Identifier (bytes 16–17) contains the media-destination ID that is incompatible with the media-source ID.

System action

PSF releases the current data set back to JES and requests that it is held by the system unless PRTEROR=QUIT is specified on the OUTPUT statement.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

If you specified an output bin with the OUTBIN keyword and it is the wrong output bin, change the bin and resubmit the print job. Your data set might require a different printer configuration. For more information about your printer configuration, see the printer publications for the printer that reported this error.

APS861I **A CHARACTER IN THE PRINT DATA IS NOT VALID ACCORDING TO THE CODE PAGE ASSOCIATED WITH THE FONT.**

Explanation

The Flag Byte parameter in either the Code Page Control (CPC) or a repeating group of the Code Page Index (CPI) structured field had the undefined or unprintable bit set for a code point in the text data that was to be printed. The CPC and CPI structured fields are in the code page. This error occurred because DATAK=UNBLOCK or BLKPOS was specified in the OUTPUT JCL statement or the PRINTDEV JCL statement in the PSF initialization procedure, Print error reporting was specified as All, or Position was specified in the Printer Inventory and one of these conditions existed:

- The code page did not include the code point, and the default character, which is specified by the CPC, had the not valid flag on.

- The character that is assigned to this code point did not exist in the character set, and the default character, which is specified by the CPC, had the not valid flag on.
- The code point, which is specified by the CPI structured field, had the not valid flag on.

This page might contain other data stream errors that PSF did not report but that the printer highlighted.

System action

The printer you were using might attempt to print the page in error, or might print only part of the page. If the page that contains the error contains any position errors, print-error markers are included on the printed page. PSF continues processing the current data set with the page that follows the page that contains the error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages of the message data set, use the information that is provided in the User Response section to correct the error.

User response

To eliminate this error message from your output, you can resubmit the print request, specifying BLOCK or BLKCHAR for the DATAKEY keyword on the JCL OUTPUT statement. For more information about how to code this keyword, see *PSF for z/OS: User's Guide*.

If you want to correct the source of the problem, you first need to identify which character in which font contains the error.

If the printer returned the information about the incorrect character, check these:

- Immediately following this message (APS861I) is a formatted sense message (APS830I). The Element Identifier field in this message contains the code

point in which the error occurs, or zeros if the printer did not return the information.

- To determine which code page and character set pair have the incorrect code point, check messages APS701I. The APS701I messages are environmental messages for this page. If the printer returned the information, one of the APS701I messages provides the *active code page name* and the *active character set name*.

Ensure that the code point in the print data is correct. If the code point is incorrect, and you created the structured fields for the code page, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information on the correct format of the referenced structured field. If you used a program to create the structured fields for the code page, consult your system programmer.

APS862I **ONE OR MORE CHARACTERS, RULES, IMAGES, OR IMAGE CELLS WERE SPECIFIED TO PRINT OUTSIDE OF THE VALID PRINTABLE AREA.**

Explanation

An attempt was made to print outside of the valid printable area. This area is the intersection (common space) of the physical page with the logical page or with an overlay. Characters, rules, or image cells fall at least partially outside of the valid printable area. Note that a data stream image might consist of a number of image cells, and each cell is sent to the printer as one image. Other data stream errors might exist on this page that PSF did not report but that the printer highlighted.

System action

The printer you were using might attempt to print the page in error, or might print only part of the page. If the page that contains the error contains any position errors, print-error markers are included on the printed page. PSF continues processing the current data set with the page that follows the page that contains the error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

Ensure that the correct form was loaded in the printer. If it was, and if your printed output would be acceptable without the print-error markers, you can resubmit the print request, specifying BLOCK or BLKPOS for the DATAKEY keyword on the OUTPUT JCL statement. If you want to correct the source of the problem, you can change the size of the logical page. If you want the logical page size to remain the same and if you were printing MO:DCA data, an overlay, or a page segment, and you created the structured fields in the object that contains the error, check the print-positioning values in the text-control sequence in the Presentation Text Data (PTX) structured field for positioning outside of the page.

If you are printing an image, coordinate the image dimensions with the logical page size.

If you are printing a data set containing line data, and you were using a page definition that you created, check the print-positioning values in the Line Descriptor (LND) structured field.

If you are printing a data set containing line data with embedded structured fields, check the PTX structured field for positioning outside of the page.

APS863I A PARAMETER VALUE IN A FORMDEF RESOURCE IS NOT VALID OR IS UNSUPPORTED: THE MEDIUM FINISHING CONTROL STRUCTURED FIELD SPECIFIES AN INCORRECT OR UNSUPPORTED FINISHING OPERATION TYPE FOR THIS FINISHER.

Explanation

The operation type field (byte 2) in a Finishing Operation triplet (X'85') contains an incorrect or unsupported value for this finisher.

Finishing Operation triplets are specified in the Medium Finishing Control (MFC) structured field. The MFC is specified in the Document Environment Group of the form definition or in a Medium Map.

System action

Reporting of this exception can be controlled by the Finishing Fidelity triplet in the Presentation Fidelity

Control (PFC) command. The PFC command is contained in a form definition.

When the Finishing Fidelity triplet sets the continuation rule to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and marks the data set unprintable. PSF releases the current data set back to JES and requests that it is held by the system unless PRERROR=QUIT is specified on the OUTPUT statement.

When the Finishing Fidelity triplet sets the continuation rule to DO NOT STOP (X'02'), one of these occurs:

- If the printer supports the PFC Finishing Fidelity triplet and if the REPORT field is set to REPORT (X'01'), the printer reports this exception. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.
- If the printer supports the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.
- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer reports this exception but PSF does not issue the error message. The printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.
- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to REPORT (X'01'), the printer reports this exception and PSF issues the error message. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the MFC with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If the output is not acceptable:

- Verify that you requested the appropriate form definition for the finishing operation intended.
- Submit the print request to a printer that can do the finishing operation.
- If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS864I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A PARAMETER VALUE IN A TEMPORARY BASELINE MOVE TEXT CONTROL IN A PTX STRUCTURED FIELD IS NOT VALID.

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The Temporary Baseline Move (TBM) text-control increment, move direction, or precision value is not valid or is unsupported.
2. The printer does not support the use of multiple TBM text controls without an intervening termination TBM. This is also referred to as multi-offsetting.

3. The printer uses the substitution method to create the appearance of a temporary baseline move, but the substitution character that is used for the TBM text control is unsupported.
4. The printer is unable to support the TBM text control by printing full-size characters. Processing the TBM causes a portion of the character box on the current baseline to exceed the boundaries of the object space.

The text-control sequence is in a Presentation Text Data (PTX) structured field. The PTX structured field might be in MO:DCA data, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer you were using attempts to print the page that contains the error, or might print only part of the page. If the page that contains the error contains any position errors, print-error markers are included on the printed page. PSF continues processing the current data set with the page after the page containing the error, unless the printer reports another error that requires a more severe recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBMlicensed program was used to create the print file or resource with the error, verify that the input to that program was valid. If the input was valid, consult *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you are printing MO:DCA data, an overlay, or a page segment, and you created the structured fields in the object that contains the error, correct the text-control sequence in the PTX structured field. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you are printing MO:DCA data, an overlay, or a page segment, and you used a program to create the structured fields, consult your system programmer.

If you are printing a data set containing line data with embedded structured fields, correct the text-control sequence in the PTX structured field. If the PTX has no errors, the error might be a PSF or printer logic error.

If you are printing a data set containing line data without embedded structured fields, the error might be a PSF or printer logic error.

APS865I THE ACTUAL MEDIA LOADED DOES NOT MATCH THE FORM THAT WAS SELECTED AT THE PRINTER CONSOLE.

Explanation

The media that is currently loaded in the printer does not match the form that was selected at the printer console. The printer detected and reported an asynchronous intervention-required error with an action code of X'0A' (sense byte 2). Bytes 0, 1, and 19 of the error are 4035..00. For more information about this error, see the printer publications for the printer that reported the error.

System action

PSF resends pages to the printer, starting from the jam recovery page counter plus 1. PSF might print this message on a separate sheet in the data set to mark the position at which the recovery from this error was started. If repositioning is not supported in the current environment, the data set is ended.

Operator response

Clear the paper up to the jam recovery page counter. Perform these tasks to continue printing:

- Verify that the correct form for the job is selected at the printer console. If the correct form for the job is not selected, change it to the correct one.
- Load the paper that matches the selected form at the printer console. For a continuous forms printer, be sure to NPRO the correct paper up to the jam recovery page counter.
- If the correct paper for the job is not available, do one of these:
 - Cancel the job at the printer console. The job must be resubmitted when the correct paper is available.
 - Disable the verifier and continue printing with the paper that is available.

PSF assumes that pages between the jam recovery page counter and the stacked page counter are not damaged and do not need to be reprinted. If any pages between these two counters do need to be reprinted, use the JES BACKSPACE command.

System programmer response

If the error condition persists, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

The printed output might be acceptable. If the error condition persists, consult your system programmer.

APS866I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A PTD-2 INLINE DIRECTION IS NOT VALID.

Explanation

The inline direction value that is specified as the initial default for the Set Text Orientation (STO) text control in the Self Identifying Parameters field of the Presentation Text Descriptor Format 2 (PTD-2) structured field is not valid or is unsupported. The PTD-2 structured field might be in an overlay, the Object Environment Group (OEG) of a presentation text object, MO:DCA data, or a page definition.

System action

The printer you were using might attempt to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document or an overlay, and you created the structured fields in the object that contains the error, correct the text-control sequence in

the PTD-2 structured field. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the PDT-2 has no errors, the error might be a PSF or printer logic error. If you are printing a MO:DCA document or an overlay, and you used a program to create its structured fields, contact your system programmer.

APS867I DATA IN A FORMDEF RESOURCE IS NOT VALID: THE PAGE ORIGIN VALUE IN THE PGP STRUCTURED FIELD IS NOT ACCEPTABLE.

Explanation

The Page Origin parameter in the Page Position (PGP) structured field specifies, in pels, the displacement of the page from the origin of the physical page. This parameter has two subparameters, the X-origin and the Y-origin, and one of these has an incorrect value. The PGP structured field is in the form definition.

System action

PSF stops processing and printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS868I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A PTD-2 BASELINE DIRECTION IS NOT VALID.

Explanation

The baseline direction value that is specified as the initial default for the Set Text Orientation (STO) text control in the Self Identifying Parameters field of the Presentation Text Descriptor Format 2 (PTD-2) structured field is not valid or is unsupported. The PTD-2 structured field might be in an overlay, the Object Environment Group (OEG) of a presentation text object, MO:DCA data, or a page definition.

System action

The printer you were using might attempt to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document or an overlay, and you created the structured fields in the object that contains the error, correct the text-control sequence in the PTD-2 structured field. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the PDT-2 has no errors, the error might be a PSF or printer logic error. If you are printing a MO:DCA document or an overlay, and you used a program to create its structured fields, contact your system programmer.

APS869I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A PTD-2 INLINE COORDINATE IS NOT VALID.

Explanation

The inline coordinate position value that is specified as the initial default for the Absolute Move inline (AMI) text control in the Self Identifying Parameters field of the Presentation Text Descriptor Format 2 (PTD-2) structured field is not valid or is unsupported. The PTD-2 structured field might be in an overlay, the Object Environment Group (OEG) of a presentation text object, MO:DCA data, or a page definition.

System action

The printer you were using might attempt to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see [PSF for z/OS: Diagnosis](#) for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document or an overlay, and you created the structured fields in the object that contains the error, correct the text-control sequence in the PTD-2 structured field. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the PDT-2 has no errors, the error might be a PSF or printer logic error. If you are printing a MO:DCA document or an overlay, and you used a program to create its structured fields, contact your system programmer.

APS870I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A PTD-2 BASELINE COORDINATE IS NOT VALID.

Explanation

The baseline coordinate position value that is specified as the initial default for the Absolute Move Baseline (AMB) text control in the Self Identifying Parameters field of the Presentation Text Descriptor Format 2 (PTD-2) structured field is not valid or is unsupported. The PTD-2 structured field might be in an overlay, the Object Environment Group (OEG) of a presentation text object, MO:DCA data, or a page definition.

System action

The printer you were using might attempt to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see [PSF for z/OS: Diagnosis](#) for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document or an overlay, and you created the structured fields in the object that contains the error, correct the text-control sequence in the PTD-2 structured field. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the PDT-2 has no errors, the error might be a PSF or printer logic error. If you are printing a MO:DCA document or an overlay, and you used a program to create its structured fields, contact your system programmer.

APS871I A FORMDEF RESOURCE REQUESTED N_UP, BUT N_UP IS NOT SUPPORTED FOR ENVELOPES.

Explanation

The printer does not support N_UP printing on envelopes.

System action

PSF stops processing the current data set, releases the current data set to JES, and requests the system to hold it unless PRTEROR=QUIT is specified on the OUTPUT statement.

Operator response

No response is necessary.

System programmer response

Fix the form definition or replace it with one that does not request N_UP printing.

User response

Change the form definition to one that does not request N_UP on the next submission, or submit the job to a printer that does not have envelopes in the bin requested by the form definition.

APS872I THE SPECIFIED INPUT BIN CANNOT BE USED WITH THE SPECIFIED OUTPUT BIN.

Explanation

The paper size in the input bin that is selected is not compatible with the output bin selected for the data set. The input bin is either the printer default input bin, or the bin specified in the form definition for the data set. The output bin is either the printer default output bin, or the bin specified on the OUTBIN keyword on the JCL OUTPUT statement for the data set.

Note: In the formatted sense message (APS830I), the second byte of the Object Identifier (byte 15) contains a media-source ID, and the Element Identifier (bytes 16–17) contains the media-destination ID that is incompatible with the media-source ID.

System action

PSF releases the current data set back to JES and requests that it is held by the system unless PRTEROR=QUIT is specified on the OUTPUT statement.

Operator response

If you are running under JES, use the JES data set release commands to release the data set to a printer that supports this function. To find a JES command to release the data set for printing, see the JES

commands publication for the level of JES you are using. If this message is displayed on the operator console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

No response is necessary.

User response

If you specified an output bin with the OUTBIN keyword, and it is the wrong output bin, change the bin and resubmit the print job. Contact the operator to have your previous print request purged. If you submitted the job to the wrong printer, contact the operator and specify which printer to release your print request to.

APS873I DATA IN A FONT RESOURCE IS NOT VALID: TOO MUCH OR TOO LITTLE CODE PAGE DATA WAS RECEIVED.

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The amount of code page data that is received does not match the value specified.
2. The last entry in a code page is incomplete.

The amount of code page data in the Code Page Index (CPI) structured field does not match the value in bytes 34-37 in the Code Page Descriptor (CPD) structured field (if present), or is inconsistent with the CPI repeating group length (specified in byte 9 of the Code Page Control structured field).

System action

If the font that contains the error is a printer-resident font, PSF attempts to download the host version of the font and continue processing the current page; otherwise, PSF stops processing and printing the data set.

A System Action message is issued indicating which action was taken.

Operator response

No response is necessary.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

If the font is a printer-resident font, consult your IBM printer hardware service representative.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

If the font is a printer-resident font, consult your system programmer.

APS874I **OUTPUT BIN *bin number* WAS REQUESTED BUT CANNOT BE USED WITH INPUT BIN *bin number*.**

Explanation

The paper size in the input bin that is selected is not compatible with the output bin selected for the data set. The input bin is either the printer default input bin, or the bin specified in the form definition for the data set. The output bin is either the printer default output bin, or the bin specified on the OUTBIN keyword on the JCL OUTPUT statement for the data set.

System action

PSF releases the current data set back to JES and requests that it is held by the system unless PRERROR=QUIT is specified on the OUTPUT statement.

Operator response

If you are running under JES, use the JES data set release commands to release the data set to a printer with consistent bins. For a JES command to release the data set for printing, see the publication that contains JES commands for your operating system.

System programmer response

No response is necessary.

User response

If you specified an output bin with the OUTBIN keyword, and it is the wrong output bin, change the bin and resubmit the print job. If the bin values are correct, the data set was sent to a printer with a bin configuration that was not compatible with the bins requested for the data set. Consult your operator to determine which printer to reroute the data set to.

APS875I **DATA IN A FORMDEF RESOURCE IS INCOMPATIBLE: THE MEDIUM FINISHING CONTROL STRUCTURED FIELD SPECIFIES A FINISHING OPERATION THAT IS INCOMPATIBLE WITH THE SELECTED MEDIA OR THE SELECTED MEDIA DESTINATION.**

Explanation

A finishing operation that is specified in a Finishing Operation triplet (X'85' or X'8E') is incompatible with the selected physical media or with the media destination. Some printers do not support all sizes of media or mixed-size media when finishing. Also, some printers restrict the possible media destination of finished data sets to a subset of all media destinations available.

Finishing Operation triplets are specified in the Medium Finishing Control (MFC) structured field. The MFC is specified in the Document Environment Group of the form definition or in a Medium Map.

System action

Reporting of this exception can be controlled by the Finishing Fidelity triplet in the Presentation Fidelity Control (PFC) command. The PFC command is contained in a form definition.

When the Finishing Fidelity triplet sets the continuation rule to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and marks the data set unprintable. PSF releases the current data set back to JES and requests that it is held by the system unless PRERROR=QUIT is specified on the OUTPUT statement.

When the Finishing Fidelity triplet sets the continuation rule to DO NOT STOP (X'02'), one of these occurs:

- If the printer supports the PFC Finishing Fidelity triplet and if the REPORT field is set to REPORT (X'01'), the printer reports this exception. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe

PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

- If the printer supports the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.
- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer reports this exception but PSF does not issue the error message. The printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.
- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to REPORT (X'01'), the printer reports this exception and PSF issues the error message. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the MFC with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If the output is not acceptable:

- If you specified OUTBIN on your JCL OUTPUT statement, make sure that it selects a media destination that supports finished output.

- Verify that you requested the appropriate form definition for the finishing operation intended.
- Submit the print request to a printer that can do the finishing operation.
- If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

AP5876I

DATA IN A FONT RESOURCE IS NOT VALID: THE PATTERN TECHNOLOGY IDENTIFIER IN A FONT CHARACTER SET IS NOT VALID OR IS UNSUPPORTED.

Explanation

The pattern technology identifier that is specified in byte 1 in the Font Control (FNC) structured field is not valid or is unsupported.

System action

If the font that contains the error is a printer-resident font, PSF attempts to download the host version of the font and continue processing the current page; otherwise, PSF stops processing and printing the data set.

A System Action message is issued indicating which action was taken.

Operator response

No response is necessary.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

If the font is a printer-resident font, consult your IBM printer hardware service representative.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font*

Object Content Architecture Reference for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

If the font is a printer-resident font, consult your system programmer.

APS877I **DATA IN A FONT RESOURCE IS NOT VALID: THE NUMBER OF BYTES IN THE FNG OR FNN STRUCTURED FIELD IS NOT VALID OR IS UNSUPPORTED.**

Explanation

The Font Data Length that is specified in bytes 28-31 in the Font Control (FNC) structured field, or the Font Name Map Data Count that is specified in bytes 36-39 in the FNC structured field, was not valid or is unsupported.

System action

If the font that contains the error is a printer-resident font, PSF attempts to download the host version of the font and continue processing the current page; otherwise, PSF stops processing and printing the data set.

A System Action message is issued indicating which action was taken.

Operator response

No response is necessary.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

If the font is a printer-resident font, consult your IBM printer hardware service representative.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the

structured fields for the font, contact your system programmer.

If the font is a printer-resident font, consult your system programmer.

APS878I **DATA IN A FONT RESOURCE IS NOT VALID: THE FNN DATA COUNT IN THE FNC STRUCTURED FIELD IS NOT VALID OR IS UNSUPPORTED.**

Explanation

The Font Name Map (FNN) Data Count specified in bytes 36 - 39 of the Font Control (FNC) structured field is not valid or is unsupported.

System action

If the font that contains the error is a printer-resident font, PSF attempts to download the host version of the font and continue processing the current page; otherwise, PSF stops processing and printing the data set.

A System Action message is issued indicating which action was taken.

Operator response

No response is necessary.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

If the font is a printer-resident font, consult your IBM printer hardware service representative.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

If the font is a printer-resident font, consult your system programmer.

APS879I**DATA IN A FONT RESOURCE IS NOT VALID: THE ENCODING PARAMETERS IN THE FNN STRUCTURED FIELD ARE NOT VALID OR ARE UNSUPPORTED.****Explanation**

The value that is specified in byte 0 or byte 1 in the Font Name Map (FNN) structured field is not valid or is unsupported.

System action

If the font that contains the error is a printer-resident font, PSF attempts to download the host version of the font and continue processing the current page; otherwise, PSF stops processing and printing the data set.

A System Action message is issued indicating which action was taken.

Operator response

No response is necessary.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

If the font is a printer-resident font, consult your IBM printer hardware service representative.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

If the font is a printer-resident font, consult your system programmer.

Explanation

An incorrect technology-specific ID offset value was specified in the second section of an FNN structured field.

System action

If the font that contains the error is a printer-resident font, PSF attempts to download the host version of the font and continue processing the current page; otherwise, PSF stops processing and printing the data set.

A System Action message is issued indicating which action was taken.

Operator response

No response is necessary.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

If the font is a printer-resident font, consult your IBM printer hardware service representative.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

If the font is a printer-resident font, consult your system programmer.

APS881I**DATA IN A FONT RESOURCE IS NOT VALID: AN INCORRECT TECHNOLOGY-SPECIFIC ID LENGTH WAS SPECIFIED IN AN FNN STRUCTURED FIELD.****Explanation**

An incorrect technology-specific ID length value was specified in the third section of an FNN structured field.

APS880I**DATA IN A FONT RESOURCE IS NOT VALID: AN INCORRECT TECHNOLOGY-SPECIFIC ID OFFSET WAS SPECIFIED IN AN FNN STRUCTURED FIELD.**

System action

If the font that contains the error is a printer-resident font, PSF attempts to download the host version of the font and continue processing the current page; otherwise, PSF stops processing and printing the data set.

A System Action message is issued indicating which action was taken.

Operator response

No response is necessary.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

If the font is a printer-resident font, consult your IBM printer hardware service representative.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

If the font is a printer-resident font, consult your system programmer.

APS882I	DATA IN A FONT RESOURCE IS NOT VALID: AN INCORRECT TECHNOLOGY-SPECIFIC OBJECT LENGTH WAS SPECIFIED IN THE FNG STRUCTURED FIELD.
----------------	--

Explanation

The technology-specific object length that is specified in bytes 0–3 in the Font Patterns (FNG) structured field is not valid.

System action

If the font that contains the error is a printer-resident font, PSF attempts to download the host version of the font and continue processing the current page;

otherwise, PSF stops processing and printing the data set.

A System Action message is issued indicating which action was taken.

Operator response

No response is necessary.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

If the font is a printer-resident font, consult your IBM printer hardware service representative.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

If the font is a printer-resident font, consult your system programmer.

APS883I	DATA IN A FONT RESOURCE IS NOT VALID: THE CHECKSUM VALUE SPECIFIED IN THE FNG STRUCTURED FIELD DOES NOT MATCH THE CHECKSUM VALUE CALCULATED BY THE PRINTER.
----------------	--

Explanation

The checksum that is specified in bytes 4–7 of the Font Patterns (FNG) structured field does not match the checksum value that is calculated by the printer.

System action

If the font that contains the error is a printer-resident font, PSF attempts to download the host version of the font and continue processing the current page; otherwise, PSF stops processing and printing the data set.

A System Action message is issued indicating which action was taken.

Operator response

No response is necessary.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

If the font is a printer-resident font, consult your IBM printer hardware service representative.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

If the font is a printer-resident font, consult your system programmer.

APS884I	DATA IN A FONT RESOURCE IS NOT VALID: AN INCORRECT TECHNOLOGY-SPECIFIC OBJECT NAME LENGTH WAS SPECIFIED IN THE FNG STRUCTURED FIELD.
----------------	---

Explanation

The value that is specified for the technology-specific object name length in bytes 8-9 of the Font Patterns (FNG) structured field is not valid.

System action

If the font that contains the error is a printer-resident font, PSF attempts to download the host version of the font and continue processing the current page; otherwise, PSF stops processing and printing the data set.

A System Action message is issued indicating which action was taken.

Operator response

No response is necessary.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

If the font is a printer-resident font, consult your IBM printer hardware service representative.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

If the font is a printer-resident font, consult your system programmer.

APS885I	PARAMETERS IN A FORMDEF RESOURCE ARE NOT VALID OR ARE UNSUPPORTED: THE MEDIUM FINISHING CONTROL STRUCTURED FIELD SPECIFIES AN INCORRECT OR UNSUPPORTED NUMBER OF FINISHING POSITIONS.
----------------	--

Explanation

In a Finishing Operation triplet (X'85'), either the number of position values that are specified does not match the count (byte 6), or the number of supported positions is exceeded.

Finishing Operation triplets are specified in the Medium Finishing Control (MFC) structured field. The MFC is specified in the Document Environment Group of the form definition or in a Medium Map.

System action

Reporting of this exception can be controlled by the Finishing Fidelity triplet in the Presentation Fidelity Control (PFC) command. The PFC command is contained in a form definition.

When the Finishing Fidelity triplet sets the continuation rule to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and marks the data set unprintable. PSF releases the current data set back to

JES and requests that it is held by the system unless PRERROR=QUIT is specified on the OUTPUT statement.

When the Finishing Fidelity triplet sets the continuation rule to DO NOT STOP (X'02'), one of these occurs:

- If the printer supports the PFC Finishing Fidelity triplet and if the REPORT field is set to REPORT (X'01'), the printer reports this exception. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.
- If the printer supports the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.
- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer reports this exception but PSF does not issue the error message. The printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.
- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to REPORT (X'01'), the printer reports this exception and PSF issues the error message. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the MFC with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If the output is not acceptable:

- Verify that you requested the appropriate form definition for the finishing operation intended.
- Submit the print request to a printer that can do the finishing operation.
- If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

AP5886I

A PARAMETER VALUE IN A FORMDEF RESOURCE IS NOT VALID OR IS UNSUPPORTED: THE MEDIUM FINISHING CONTROL STRUCTURED FIELD SPECIFIES AN INCORRECT OR UNSUPPORTED FINISHING OPERATION POSITION VALUE.

Explanation

A finishing operation position field in a Finishing Operation triplet (X'85') contains an incorrect or unsupported value.

Finishing Operation triplets are specified in the Medium Finishing Control (MFC) structured field. The MFC is specified in the Document Environment Group of the form definition or in a Medium Map.

System action

Reporting of this exception can be controlled by the Finishing Fidelity triplet in the Presentation Fidelity Control (PFC) command. The PFC command is contained in a form definition.

When the Finishing Fidelity triplet sets the continuation rule to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and marks the data set unprintable. PSF releases the current data set back to JES and requests that it is held by the system unless

PRERROR=QUIT is specified on the OUTPUT statement.

When the Finishing Fidelity triplet sets the continuation rule to DO NOT STOP (X'02'), one of these occurs:

- If the printer supports the PFC Finishing Fidelity triplet and if the REPORT field is set to REPORT (X'01'), the printer reports this exception. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.
- If the printer supports the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.
- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer reports this exception but PSF does not issue the error message. The printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.
- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to REPORT (X'01'), the printer reports this exception and PSF issues the error message. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the MFC with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If the output is not acceptable:

- Verify that you requested the appropriate form definition for the finishing operation intended.
- Submit the print request to a printer that can do the finishing operation.
- If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

AP5887I

DATA IN A FONT RESOURCE IS NOT VALID: THE CHARACTER-ID ENCODING PARAMETER FOR A FONT CHARACTER SET EXTENSION DOES NOT MATCH THE CHARACTER-ID ENCODING PARAMETER FOR THE PARENT DOUBLE-BYTE OUTLINE FONT.

Explanation

Either the IBMcharacter-ID format value or the technology-specific character-ID map of a font character set extension does not match the equivalent value in the parent font character set.

System action

If the font that contains the error is a printer-resident font, PSF attempts to download the host version of the font and continue processing the current page; otherwise, PSF stops processing and printing the data set.

A System Action message is issued indicating which action was taken.

Operator response

No response is necessary.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

If the font is a printer-resident font, consult your IBM printer hardware service representative.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

If the font is a printer-resident font, consult your system programmer.

APS888I	DATA IN A FONT RESOURCE IS NOT VALID: ONE OR MORE GCGIDS IN AN FNN STRUCTURED FIELD IS OUT OF ORDER.
----------------	---

Explanation

Graphic Character Global Identifiers (GCGIDs) in the second section of a Font Name Map (FNN) structured field are not in ascending-EBCDIC order.

System action

If the font that contains the error is a printer-resident font, PSF attempts to download the host version of the font and continue processing the current page; otherwise, PSF stops processing and printing the data set.

A System Action message is issued indicating which action was taken.

Operator response

No response is necessary.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error

involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

If the font is a printer-resident font, consult your IBM printer hardware service representative.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

If the font is a printer-resident font, consult your system programmer.

APS889I	DATA IN A FONT RESOURCE IS NOT VALID: ONE OR MORE OF THE TECHNOLOGY-SPECIFIC OBJECTS IN AN FNG STRUCTURED FIELD CONTAINS INCORRECT OR MISSING DATA.
----------------	--

Explanation

The technology specific object that is provided in a Font Patterns (FNG) structured field contains incorrect data. The character set is unusable.

System action

If the font that contains the error is a printer-resident font, PSF attempts to download the host version of the font and continue processing the current page; otherwise, PSF stops processing and printing the data set.

A System Action message is issued indicating which action was taken.

Operator response

No response is necessary.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

If the font is a printer-resident font, consult your IBM printer hardware service representative.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

If the font is a printer-resident font, consult your system programmer.

APS890I **DATA IN A FONT RESOURCE IS NOT VALID: THE SETTING OF THE MICR BIT IN THE FNC STRUCTURED FIELD IS INCONSISTENT WITH THE BASE RESIDENT OUTLINE FONT.**

Explanation

Bit 1 in byte 3 of the Font Control (FNC) structured field indicates whether the font is intended for Magnetic Ink Character Recognition (MICR) printing. The setting of this bit is inconsistent with the intended-for-MICR setting of the base resident outline font.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response

No response is necessary.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more

information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

APS891I **DATA IN A FONT RESOURCE IS NOT VALID: THE ENCODING SCHEME IN A CODE PAGE IS NOT VALID OR UNSUPPORTED.**

Explanation

The encoding scheme that is specified in bytes 42–43 in the Code Page Descriptor (CPD) structured field is incorrect or is unsupported.

System action

If the font that contains the error is a printer-resident font, PSF attempts to download the host version of the font and continue processing the current page; otherwise, PSF stops processing and printing the data set.

A System Action message is issued indicating which action was taken.

Operator response

No response is necessary.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

If the font is a printer-resident font, consult your IBM printer hardware service representative.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

If the font is a printer-resident font, consult your system programmer.

APS892I DATA IN A FONT RESOURCE IS NOT VALID: THE AMOUNT OF CODE PAGE DATA SPECIFIED IN A CPD, CPI OR CPC STRUCTURED FIELD IS NOT VALID OR IS UNSUPPORTED.

Explanation

The amount of code page data in a Code Page Index (CPI) structured field is not valid or is unsupported; or the value that is specified in bytes 34–37 in a Code Page Descriptor (CPD) structured field is not valid or is unsupported; or the CPI repeating group length that is specified in byte 9 of the CPC structured field is not valid or is unsupported.

System action

If the font that contains the error is a printer-resident font, PSF attempts to download the host version of the font and continue processing the current page; otherwise, PSF stops processing and printing the data set.

A System Action message is issued indicating which action was taken.

Operator response

No response is necessary.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

If the font is a printer-resident font, consult your IBM printer hardware service representative.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

If the font is a printer-resident font, consult your system programmer.

APS893I DATA IN A FONT RESOURCE IS NOT VALID: THE CODE POINTS SPECIFIED IN A CPI STRUCTURED FIELD ARE OUT OF ORDER.

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported: Code points are specified in the Code Page Index (CPI) structured field.

1. The entries in a series of LCP commands or in a resident code page are not specified in ascending code-point order.
2. A code point appeared more than once.

System action

If the font that contains the error is a printer-resident font, PSF attempts to download the host version of the font and continue processing the current page; otherwise, PSF stops processing and printing the data set.

A System Action message is issued indicating which action was taken.

Operator response

No response is necessary.

System programmer response

If an IBM licensed program was used to create the structured fields for the code page that contains the error, verify that the input to that program was valid. If the input was valid, or if the code page is not a double-byte code page, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

If the font is a printer-resident font, consult your IBM printer hardware service representative.

User response

If you created the structured fields for the double-byte code page, correct the error and resubmit the print request. For more information about the structured field, see *Font Object Content Architecture Reference*. If the structured field has no error, or if the code page is not a double-byte code page, the error might be a PSF logic error. If you used a program to create the structured fields for the code page, consult your system programmer.

If the font is a printer-resident font, consult your system programmer.

APS894I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE CHARACTER INCREMENT FOR THE OVERSTRIKE CHARACTER IS NOT VALID.

Explanation

The character increment for the overstrike character that is specified in bytes 5–6 in a PTOCA Overstrike Control Sequence (OVS) must be greater than zero and equal to or greater than the character box for the font, but was not. When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The character increment of the selected overstrike character is less than or equal to zero.
2. The character increment of the selected overstrike character is less than the character-box X size.
3. The overstrike character is not a printable character.

The character increment for the character is specified in bytes 8-9 in the Font Index (FNI) structured field. The uniform box size for the font is specified in bytes 10–13 in the Font Control (FNC) structured field. Either the overstrike character that is specified in the OVS is not an appropriate overstrike character set or its character increment is inconsistent with the character box size for the font.

System action

The printer you were using might attempt to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

No response is necessary.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see [PSF for z/OS:](#)

Diagnosis for assistance in determining the source of the problem.

User response

If you created the structured fields for the font or the data set containing the OVS structured field, correct the error and resubmit the print request. For more information about the fields, see *Font Object Content Architecture Reference* or *Presentation Text Object Content Architecture Reference*. If the structured fields have no errors, the error might be a PSF logic error. If you used a program to create the structured field, consult your system programmer.

APS895I SYSTEM ACTION TAKEN: PSF WILL ATTEMPT TO DOWNLOAD A HOST VERSION OF THE PRINTER-RESIDENT FONT IN ERROR AND CONTINUE PROCESSING THE DATA SET.

Explanation

This message describes the recovery that is done by PSF when the printer reports an I/O error to PSF. This message accompanies a message that describes the I/O error.

System action

If the font that contains the error is a printer-resident font, PSF attempts to download the host version of the font and continue processing the current page; otherwise, PSF stops processing and printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

To determine an appropriate response, see the specific error conditions described in the accompanying messages.

User response

To determine an appropriate response, see the specific error conditions described in the accompanying messages.

APS896I THE DATA IN AN OBJECT CONTAINER RESOURCE WAS

CONSIDERED INCORRECT BY THE PRINTER. CODE = (code and brief description).

Explanation

The data in an object container resource was not considered valid by the printer, although the printer supports the resource type as identified by the Object Classification triplet on the Begin Object Container structured field.

For a complete list of the error codes and descriptions, see *Intelligent Printer Data Stream Reference*.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the data in the structured fields of the object container resource, correct the error and resubmit the print request. See the appropriate documentation for the data stream that is carried in the object container resource. If you used a program to create the structured fields and the data, consult your system programmer.

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The GRID contains a value that is not valid or is out of range in one or more of its components.
2. The printer requires a valid GRID, but one is not supplied.

The components of the GRID are in the code page and character set for the font.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

APS897I DATA IN A FONT RESOURCE IS NOT VALID: THE COMPONENTS OF A GRID ARE NOT PRESENT OR ARE NOT VALID IN THE COMBINATION OF THE FONT CHARACTER SET AND CODE PAGE. A VALID GRID IS REQUIRED IN ALL FONTS FOR THIS PRINTER.

APS898I DATA IN A CODE PAGE RESOURCE IS NOT VALID: THE CPGID IS NOT VALID OR IS NOT PRESENT. A VALID CPGID IS REQUIRED IN ALL FONTS FOR THIS PRINTER.

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The CPGID value that is specified for a code page is not valid (out of range).
2. The printer requires a valid CPGID, but one is not supplied.

The CPGID is specified in the Code Page Descriptor of the code page.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the code page, correct the error and resubmit the print request. For more information about the structured field, see *Font Object Content Architecture Reference*. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the code page, consult your system programmer.

APS899I

DATA IN A FONT CHARACTER SET RESOURCE IS NOT VALID: THE FGID IS NOT VALID OR IS NOT PRESENT. A VALID FGID IS

REQUIRED IN ALL FONTS FOR THIS PRINTER.

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The FGID value for a font character set is not valid (out of range).
2. The printer requires a valid FGID, but one is not supplied.

The FGID is specified in the Font Descriptor (FND) of the font character set.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the code page, correct the error and resubmit the print request. For more information about the structured field, see *Font Object Content Architecture Reference*. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the code page, consult your system programmer.

APS900 to APS999

**APS920I MICROCODE ERROR DETECTED
ON PRINTER *prtnnnn*. PRINTER
RESPONSE IS NOT VALID.**

Explanation

PSF requested a response from the printer, but the printer returned a response that is not valid. The incorrect response is one of these:

- Multiple acknowledgment records within a single SNA or TCP/IP response
- Type of IPDS acknowledgment is not expected
- A null IPDS acknowledgment
- Not an IPDS acknowledgment

System action

PSF processing is abnormally ended with a system completion code 024 and abend reason code 02E5, 02EB, 02F7, or 02F8 depending on the type of incorrect printer response. PSF begins restart processing. If this message is issued frequently, PSF might continue with abnormal ending and not do restart processing.

Operator response

If this message is displayed frequently or restart processing failed, contact your system programmer.

System programmer response

This error is most likely because of a printer microcode problem, but might be a PSF logic error. Consult your hardware service representative. If the printer is channel-attached to a channel extender, this is probably a channel extender microcode problem. Contact your channel extender hardware service representative.

To determine whether PSF began restart processing, check the operator console for message APS038I. To verify that it was successful, check the console for message APS057I. If restart processing fails, PSF issues message APS053I and continues to end abnormally. If message APS920I is issued frequently, PSF might continue to end abnormally and create an SVC dump. For more information about PSF restart processing, see *PSF for z/OS: Diagnosis*.

User response

No response is necessary.

**APS921I THE PAGE PRINTER
COMMUNICATION COMPONENT
COULD NOT BE LOADED.
COMMUNICATION WITH SNA-
ATTACHED PRINTER (*prtnnnn*)
CANNOT BE ESTABLISHED.**

Explanation

During PSF initialization, a LOAD error occurred while attempting to load the Page Printer Communication Component (PPCC) load module, DCKVTBL. DCKVTBL is required to communicate with the SNA-attached printer *prtnnn*. DCKVTBL is probably not in an authorized library.

System action

This message is issued during PSF initialization. PSF initialization is stopped.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Ensure that DCKVTBL is a member in an authorized library that is defined to the LNKLIST concatenation.

User response

No response is necessary.

**APS922I COMMUNICATION WITH SNA-
ATTACHED PRINTER (*prtnnnn*)
LUNAME (*luname*) WAS
TERMINATED, CAUSE (*cause*)
VTAM CODE (*'nnnn'X*) SNA SENSE
(*'mmmm'X*).**

Explanation

This message indicates a probable network or printer error. For more information, see the appropriate referenced publications and see message APS925I. Communication with PRINTER (*prtnnnn*) was ended for the reason specified by CAUSE (*cause*).

A VTAM CODE (*'nnnn'X*) and SNA SENSE (*'mmmm'X*) are provided. The communications session cannot be reestablished, for one of these reasons:

- The CAUSE is an error condition that cannot be tried again.

- The Printer Inventory specified Failure Action = Stop or PSF PRINTDEV specified FAILURE=STOP.
- The retry limit is reached.

Any previous retries caused corresponding APS925I messages. For information about VTAM codes (such as RTNCD-FDBK2), reason codes (such as LOSTERM), and return codes (such as TPEND or OPEN), see *z/OS Communications Server: IP and SNA Codes*. For information about the SNA SENSE in the error message, see *SNA Formats*, GA27-3136.

PRINTER (*prtnnnn*) specifies the name on the PRINTDEV statement. LUNAME (*luname*) specifies the SNA logical unit name of the SNA-attached printer. CAUSE can be one of these:

- ALLOCATION ERROR—HALT REQUESTED. The printer is not allocated because the VTAM network, or some subset of the network that includes this printer, is being shut down. No new communication is allowed.
- ALLOCATION ERROR—TRANSACTION PROGRAM NAME. The printer is not allocated because the remote transaction program name is not compatible with PSF.
- ALLOCATION ERROR—TRANSACTION PROGRAM RETRY. The printer is not allocated because the remote transaction program is temporarily not available. Either the program is not currently authorized to run, or the resources to run it are not currently available.
- DEALLOCATE—ABEND. The remote transaction program deallocated the communication with TYPE(ABEND_TIMER) because its Device Busy Timer expired.
- DEALLOCATE—TIMER. The remote transaction program deallocated the communication with TYPE(ABEND_TIMER) because its Device Busy Timer expired.
- DEALLOCATE—NORMAL. The remote transaction program deallocated the communication with TYPE(FLUSH).
- SESSION FAILURE—DEVICE ERROR. Communication with the printer ended because of a problem reported by the remote printer. SNA SENSE gives the SNA sense code sent by the printer.
- SESSION FAILURE—LOSTERM. Communication with the printer ended because a VTAM 'LOSTERM' exit was issued with the code given by VTAM CODE.
- SESSION FAILURE—NETWORK ERROR. Communication with the printer ended because a problem was encountered within the communications network. The RTNCD-FDBK2 from the VTAM RPL on entry to SYNAD/LERAD is given in the VTAM CODE field of the message.

- SESSION FAILURE—TPEND. Communication with the printer ended because a VTAM 'TPEND' exit was issued with the code given by VTAM CODE.
- SESSION FAILURE—UNBIND. The conversation with the printer ended because an 'UNBIND' was received with the code given by VTAM CODE. For UNBIND types, see *SNA Formats*.
- SESSION RETRY—DEVICE ERROR. Communication with the printer ended because of a problem reported by the remote printer. SNA SENSE gives the SNA sense code sent by the printer.
- SESSION RETRY—LOSTERM. Communication with the printer ended because a VTAM 'LOSTERM' exit was issued with the code given by VTAM CODE. If the VTAM CODE is zero, NSEXIT was issued with a CLEANUP RU. In either case, the session was disconnected.
- SESSION RETRY—UNBIND. Communication with the printer ended because an 'UNBIND' was received with the code given by VTAM CODE. For UNBIND types, see *SNA Formats*.
- SESSION RETRY—NETWORK ERROR. Communication with the printer ended because a problem was encountered within the communications network. The RTNCD-FDBK2 from the VTAM RPL on entry to SYNAD/LERAD is given in the VTAM CODE field of the message.
- NO VTAM. VTAM is not available to accept the request to connect PSF with VTAM. The VTAM CODE gives the return code from the VTAM OPEN macro.
- APPLID PROBLEM. A problem with the network definition of the APPLID (name of the local logical unit) is specified on the JCL procedure that is used to start PSF. The VTAM CODE gives the return code from the VTAM OPEN macro.
- ACTIVATE—LOGICAL UNIT BUSY. Activation of the communication session failed because the requested logical unit was busy or unavailable. The RTNCD-FDBK2 from the VTAM OPNDST or SIMLOGON RPL is given by VTAM CODE. Any SNA sense code information that is associated with the reason for the failure of session activation is given in SNA SENSE. If the printer is not in use, LOGAPPL must be removed from the LU statement in your VTAM network definition for the printer.
- ACTIVATE—LOGICAL UNIT NOT ACTIVE. Activation of the communication session failed because the requested logical unit was not active or not enabled. SNA SENSE of X'0809' might indicate that the LUNAME is incorrect in the PSF PRINTDEV and is unknown to VTAM. The RTNCD-FDBK2 from the VTAM OPNDST or SIMLOGON RPL is given by VTAM CODE. Any SNA sense code information that is associated with the reason for the failure of session activation is given in SNA SENSE.

- **ACTIVATE—PATH ERROR.** Activation of the communication session failed because of a physical problem in the network path. The RTNCD-FDBK2 from the VTAM OPNDST or SIMLOGON RPL is given by VTAM CODE. Any SNA sense code information that is associated with the reason for the failure of session activation is given in SNA SENSE.
- **ACTIVATE—VTAMHALT.** Activation of the communication session failed because the ACF/VTAM operator issued a HALT command or a VARY NET, INACT, I, or F for PSF. The RTNCD-FDBK2 from the VTAM OPNDST or SIMLOGON RPL is given by VTAM CODE. Any SNA sense code information that is associated with the reason for the failure of session activation is given in SNA SENSE.
- **ACTIVATE—ACB INACTIVE.** Activation of the communication session failed because the ACB is being closed. This might be because a VARY NET,INACT was issued for the application. The RTNCD-FDBK2 from the VTAM OPNDST or SIMLOGON RPL is given by VTAM CODE. Any SNA sense code information that is associated with the reason for the failure of session activation is given in SNA SENSE.
- **ACTIVATE—MODENAME.** Activation of the communication session failed because the mode name used to start PSF is not valid. The Logmode specified in the Printer Inventory or the LOGMODE specified in the PSF PRINTDEV was not found in the logon mode table for the LUNAME specified on the PSF PRINTDEV data statement. If Logmode was not specified in the Printer Inventory or LOGMODE was not specified on the PRINTDEV statement, the DLOGMODE that was specified in the LU statement in the VTAM network definition was not found in the logon mode table. The RTNCD-FDBK2 from the VTAM OPNDST or SIMLOGON is given by VTAM CODE. Any SNA sense code information that is associated with the reason for the failure of session activation is given in SNA SENSE.
- **ACTIVATE—LUNAME.** Activation of the communication session failed because the LU name in the Printer Inventory or the LUNAME specified in the JCL procedure that is used to start PSF is not valid. The RTNCD-FDBK2 from the VTAM OPNDST or SIMLOGON RPL is given by VTAM CODE. Any SNA sense code information that is associated with the reason for the failure of session activation is given in SNA SENSE.
- **ACTIVATE—NOT AUTHORIZED.** Activation of the communication session failed because the application program name specified was not authorized to acquire the logical unit. This might be a network definition problem. The RTNCD-FDBK2 from the VTAM OPNDST or SIMLOGON RPL is given by VTAM CODE. Any SNA sense code information that is associated with the reason for the failure of session activation is given in SNA SENSE.
- **ACTIVATE—PERMANENTLY NOT AVAIL.** Activation of the communication session failed because the logical unit or a required resource is permanently unavailable. The RTNCD-FDBK2 from the VTAM OPNDST or SIMLOGON RPL is given by VTAM CODE. Any SNA sense code information that is associated with the reason for the failure of session activation is given in SNA SENSE.
- **ACTIVATE—SESSION PARM INCORRECT.** Activation of the communication session failed because the session parameters specified by Logmode in the Printer Inventory or by LOGMODE in the PSF PRINTDEV were incorrect for PSF or were rejected by the printer. The RTNCD-FDBK2 from the VTAM OPNDST or SIMLOGON RPL is given by VTAM CODE. Any SNA sense code information that is associated with the reason for the failure of session activation is given in SNA SENSE.
- **ACTIVATE—NEGOTIATION.** Activation of the communication session failed because the negotiated session parameters were unacceptable to the host communications code.
- **ACTIVATE—DEACTIVATE.** Activation of the communication session failed because PSF requested deactivation before the activation was complete. This condition represents a logic error in PSF.
- **ACTIVATE—ABORT.** Activation of the communication session failed because VTAM or communications management detected session-outage conditions during the activation, or SNA sense data indicated that the activation cannot be completed for a reason that did not fit into the other categories. The RTNCD-FDBK2 from the VTAM OPNDST or SIMLOGON RPL is given by VTAM CODE. Any SNA sense code information that is associated with the reason for the failure of session activation is given in SNA SENSE.

System action

The PSF FSA is ended. This message is issued because of conditions that cannot be tried again or because the retry limit is reached. For most of the causes in the Explanation section, PSF follows the Failure action that is specified in the Printer Inventory or the FAILURE action that is specified on the PRINTDEV statement in the JCL procedure that is used to start PSF. However, PSF always ends for these causes:

- **ACTIVATE—ACB INACTIVE**
- **ACTIVATE—SESSPARM**
- **ACTIVATE—NOTAVAIL**
- **ACTIVATE—LUNAME**

- ACTIVATE—MODENAME
- ACTIVATE—NEGOTIATION
- ACTIVATE—NOT AUTHORIZED
- APPLID PROBLEM
- ACTIVATE—VTAMHALT
- NO VTAM

Operator response

If the CAUSE does not explain why the communication session with the printer was ended, notify your system programmer of this error. If CAUSE, VTAM CODE, or SNA SENSE explain why communication with the printer ended, fix the problem and restart the PSF FSA.

System programmer response

If the problem was caused by an incorrect network specification, incorrect values in the Printer Inventory, or an incorrect PSF PRINTDEV statement, correct the incorrect items. If the error condition persists, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

If the procedure used to start PSF is changed (such as for APPLID PROBLEM, ACTIVATE—MODENAME, or ACTIVATE—LUNAME), the PSF FSS must be restarted to use the changed PRINTDEV statements. If options are changed in the Printer Inventory, only the FSA for which options are changed must be restarted to use the new options.

User response

No response is necessary.

APS923I **COMMUNICATION WITH SNA-ATTACHED PRINTER (*prtnnnn*) LUNAME (*luname*) WAS TERMINATED DUE TO CONDITION (*condition*).**

Explanation

The printer detected a device-inoperative condition and timed out before the printer operator was able to clear the condition. PRINTER (*prtnnnn*) specifies the name of the PRINTDEV statement. LUNAME (*luname*) specifies the SNA logical unit name of the SNA-attached printer. CONDITION can be one of these:

- Data-related print error.
- Developer mix needs changing.
- Fine filter needs changing.
- Finishing mechanism exception.
- Fuser oil supply empty.
- Fuser requires corrective action.

- Image generator error.
- Improper media specified.
- Oiler felt needs changing.
- Out of paper (cassette) or no cassette.
- Out of paper (in primary bin), or bin cover open.
- Out of staples.
- Output bin full.
- Paper jam.
- Paper specification check.
- Permanent hardware error.
- Post processor attempted-off page printing.
- Post processing discarded pages.
- Post processor not ready.
- Printer not ready—open door.
- Punch waste bin full.
- Staple jam.
- Suppressed jam recovery.
- Toner collector full.
- Toner supply empty.
- Too many sheets for a finishing operation.
- Transport requires corrective action.

System action

Communication with the SNA-attached printer is ended. PSF follows the FAILURE action that is specified on the PRINTDEV statement in the JCL procedure that is used to start PSF.

For permanent hardware errors, PSF does not follow the Failure action specified in the Printer Inventory or the FAILURE action. In this case PSF stops the printer. A permanent hardware error must be corrected before PSF is restarted.

Operator response

Consult the person responsible for the remote printer.

System programmer response

No response is necessary.

User response

No response is necessary.

APS924I **COMMUNICATION WITH SNA-ATTACHED PRINTER (*prtnnnn*) LUNAME (*luname*) WAS TERMINATED DUE TO A DISCONNECT INTERVAL TIMEOUT.**

Explanation

Communication with PRINTER (*prtnnnn*) was ended because the printer had nothing to print for the amount of time specified by the Disconnect interval parameter in the Printer Inventory or the DISCINTV parameter on the PRINTDEV statement specified for this printer. PRINTER (*prtnnnn*) specifies the name of the PRINTDEV statement that defines this printer. LUNAME (*luname*) specifies the SNA logical unit name of the SNA-attached printer.

System action

Communication with the SNA-attached printer is ended. PSF follows the Disconnect action in the Printer Inventory or the TIMEOUT action that is specified on the PRINTDEV statement in the JCL procedure that is used to start PSF.

Operator response

If this message displays frequently for an SNA-attached printer that is not shared by multiple host systems, notify your system programmer.

System programmer response

If this message displays frequently for an SNA-attached printer that is not shared by multiple host systems, consider increasing the amount of time that is specified in the Disconnect interval in the Printer Inventory or the DISCINTV parameter on the PRINTDEV statement in the procedure that is used to start PSF. For information on how to specify Printer Inventory options or a PRINTDEV statement, see [PSF for z/OS: Customization](#).

User response

No response is necessary.

APS925I	SESSION ACTIVATION WITH SNA-ATTACHED PRINTER (<i>prtnnnn</i>) LUNAME (<i>luname</i>) IS BEING RETRIED BECAUSE OF A PREVIOUSLY DETECTED RETRIABLE CONDITION (<i>condition</i>) VTAM CODE ('<i>nnnn</i>'X) SNA SENSE ('<i>mmmm</i>'X).
----------------	---

Explanation

Communication with PRINTER (*prtnnnn*) was ended for the reason specified by CONDITION (*condition*). The condition is RETRIABLE, and session activation was tried again. A VTAM CODE ('*nnnn*'X) and SNA SENSE ('*mmmm*'X) are provided. For reference to the condition and VTAM code in the error message, see *Advanced Function Communication Function for VTAM*,

Version 2, Programming or the appropriate version of VTAM. For reference to the SNA sense in the error message, see *SNA Formats*, GA27-3136.

CONDITION can be one of these:

- PPCC—Allocerr TPRETRY
- PPCC—Sessrtry DEVERR
- PPCC—Sessrtry LOSTERM
- PPCC—Sessrtry NETERR
- PPCC—Sessrtry UNBIND
- ACTIVATE—LUBUSY
- ACTIVATE—LOGICAL UNIT NOT ACTIVE
- ACTIVATE—PATH ERROR
- ACTIVATE—ABORT
- ACTIVATE—DEACT

Note: See Message APS922I for a description of the conditions.

System action

Session activation was tried again, and PSF is waiting for the activation to complete.

Operator response

In some cases, the activation completes without operator intervention. However, if the printer does not appear to be initializing (that is, a JES \$DU command shows the printer STARTING), the operator might have to intervene.

For the condition ACTIVATE—LOGICAL UNIT BUSY, the LUNAME is not available and might be in use by another invocation of PSF. Ensure that the LUNAME is available for this printer.

For the condition ACTIVATE—LOGICAL UNIT NOT ACTIVE, the LUNAME must be varied active by issuing a VTAM 'VARY NET,ACT' command.

For all conditions, it might be necessary to take action at the printer.

- Reset the printer by turning the power switch off and then on.
- If you are using a switched line, reestablish the connection by redialing the host.

System programmer response

For the condition ACTIVATE—LOGICAL UNIT NOT ACTIVE, if the LU is not active because it does not exist, add LUNAME to the network definition.

User response

No response is necessary.

APS926I NO RESPONSE NOTIFY FAILED FOR *prtntnnn*, RETURN CODE= *rc*.**Explanation**

No response action = Notify was specified in the Printer Inventory or NORESP=NOTIFY was specified on the PRINTDEV statement for printer *prtntnnn*. When a no response timeout occurred for this printer, the notify was attempted but failed with the return code indicated.

System action

The notify messages are sent to the system operator.

Operator response

Notify your system programmer that this message was received.

System programmer response

Correct the Printer Inventory or the PRINTDEV statement for printer *prtntnnn*.

User response

No response is necessary.

APS927I *mechanism name* IS DISABLED ON PRINTER *prtntnnn*.**Explanation**

The mechanism that is listed in the message is disabled on printer *prtntnnn*.

System action

This message is issued during PSF initialization.

Operator response

Either allow the printer to start, which causes PSF to avoid the selection of the disabled mechanism, or cancel the PSF writer processor. If the mechanism that is indicated in the message is not disabled in the printer, notify your system programmer.

System programmer response

If the mechanism that is indicated in the message is not disabled in the printer, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

No response is necessary.

APS928I THE PAGE PRINTER COMMUNICATION COMPONENT HAS ABENDED, PPCC ABEND REASON CODE '*nnnnnnnn*'X, SNA SENSE ('*mmmmmmmm*'X).**Explanation**

A Page Printer Communications Component abend occurred. PSF detected a PPCC abend reason code '*nnnnnnnn*'X with accompanying SNA SENSE ('*mmmmmmmm*'X).

System action

The PSF FSA is ended. An ESTAE routine creates an SVC dump for some PPCC abends. A subsequent message indicates whether an SVC dump is available.

Operator response

Notify your system programmer of this error.

System programmer response

Examine the PPCC abend reason code and SNA sense value (if nonzero) to determine the appropriate response. For an explanation of the PPCC abend reason code, see Chapter 2, "System completion codes and PSF abend reason codes," on page 613.

User response

No response is necessary.

APS929I COMMUNICATION WITH TCP/IP- ATTACHED PRINTER (*prtntnnn*) IPADDR (*ip-address*) WAS TERMINATED DUE TO A DISCONNECT INTERVAL TIMEOUT.**Explanation**

Communication with PRINTER (*prtntnnn*) was ended because the printer had nothing to print for the amount of time specified by the Disconnect interval in the Printer Inventory or the DISCONTV parameter on the PRINTDEV statement specified for the printer. PRINTER(*prtntnnn*) specifies the name of the PRINTDEV statement that defines this printer. IPADDR(*ip-address*) specifies the Internet Protocol (IP) address of the TCP/IP-attached printer.

System action

Communication with the TCP/IP-attached printer is ended. PSF follows the Disconnect action in the Printer Inventory or the TIMEOUT action that is specified on the PRINTDEV statement in the JCL procedure that is used to start PSF.

Operator response

If this message is displayed frequently for a TCP/IP-attached printer that is not shared by multiple host systems, notify your system programmer.

System programmer response

If this message displays frequently for a TCP/IP-attached printer that is not shared by multiple host systems, consider increasing the amount of time that is specified in the Disconnect interval in the Printer Inventory or the DISCINTV parameter on the PRINTDEV statement in the procedure that is used to start PSF. For information on how to code a PRINTDEV statement, see [PSF for z/OS: Customization](#).

User response

If this message displays frequently for a TCP/IP-attached printer that is not shared by multiple host systems, notify your system programmer.

APS930I **PRINTER *prtnnnn*, SPECIFIED AN INCORRECT OUTPUT BIN ID RANGE OF *first bin ID* – *last bin ID*.**

Explanation

During the processing of the OPC response, an incorrect output bin range was detected. An incorrect output bin range means that the last ID in the range is incorrectly less than the first ID in the range.

System action

This message is issued during PSF initialization, and the incorrect output bin range is ignored. PSF initialization continues.

Operator response

PSF initialization continues without operator assistance. Some output bins on the printer might not be available for use. You might have to re-enable the bins or do a power-on-reset.

System programmer response

This indicates a possible logic error in the microcode of the printer. Consult your microcode service representative in the IBM Support Center for assistance.

User response

No response is necessary.

APS931I **PRINTER SPECIFIED AN INCORRECT LENGTH FIELD IN**

THE *typeof* RESPONSE AT OFFSET: '*offset*'X.

Explanation

PSF requested a response to the Sense Type and Model (STM) command or the XOH Obtain Printer Characteristics (OPC) command from the printer, but the printer returned a response that is not valid. The message values are:

- *typeof* specifies the type of response that was not valid.
- *offset* is the hexadecimal offset in the response where the incorrect length was detected.

System action

The PSF FSA stops with a completion code of 024 and abend reason code 24A.

Operator response

Inform your system programmer that this error occurred.

System programmer response

This error is most likely from a printer microcode problem, but might be a PSF logic error. Contact your IBM hardware service representative.

User response

No response is necessary.

APS932I **AN UNEXPECTED COMMUNICATION FAILURE OCCURRED DURING THE PRINTING OF THIS JOB. THE JOB WILL BE RESTARTED AT A PREVIOUS CHECKPOINT, AND PAGES MAY BE DUPLICATED.**

Explanation

PSF detected an unexpected failure in communication with the printer; for instance, the session was disconnected during page processing. Some pages might have printed, of which PSF was not informed. When TCP/IP is attached to the printer, this message might be caused by TCP/IP being recycled.

System action

The data set being processed at the time of the error is restarted from the most recent checkpoint before the interrupt.

Operator response

To determine an appropriate response, see the specific error conditions described in any accompanying console message.

System programmer response

No response is necessary.

User response

Examine your output for duplicate pages.

APS933I **PRINTER INFORMATION,**
DEV=pppp, printername,
ECLEVEL=eeeeeeee,
ADDR=address,
SYSNAME=sssssss,
CPUID=cccccccccc,
ATTACH=type, PORT=nnnn.

Explanation

A printer information message was issued, where these variables describe the printer:

- *pppp* is the printer device type—for example, 3900 or 3816.
- *printername* is the name of the printer—for example, IBM INFOPRINT 4100.
- *eeeeeeee* is the engineering change level of the printer. If this field is not sent by the printer in the Obtain Printer Characteristics (OPC) response, then ECLEVEL=UNKNOWN is placed in the message.
- *address* is one of these values:
 - The three- or four-digit device number of the channel-attached printer.
 - The SNA logical unit name of the SNA-attached printer.
 - The Internet Protocol address or the host name of the TCP/IP-attached printer.
- *sssssss* is the system name for the current system.
- *cccccccccc* is the CPU ID, which also contains the serial number.
- *type* indicates how the printer is attached:

DPF

Distributed print function

PSF

Print Services Facility

PSFDIRECT

PSF direct

RPM2

Remote Print Manager 2

RPM3

Remote Print Manager 3

WPM

Workstation print manager

- PORT is optional and is only displayed in this message for a TCP/IP-attached printer. *nnnn* is the four-digit port number of the TCP/IP-attached printer.

System action

This message is issued only to the operator console. PSF continues processing.

Operator response

Ensure that the correct printer device type was started and attached correctly.

System programmer response

No response is necessary.

User response

No response is necessary.

APS934I **COMMUNICATION WITH TCP/IP-**
ATTACHED PRINTER (prtnnnn)
IPADDR (ip-address) WAS ENDED,
CAUSE (reason) TCP/IP ERRNO =
errno.

Explanation

A network or printer error occurred, causing communication with the printer to end. The TCP/IP session with the printer cannot be established, for one of these reasons:

- The error condition cannot be tried again.
- The Printer Inventory specified Failure action = Stop or the PSF PRINTDEV specified FAILURE=STOP.
- Connect interval (CONNINTV) timer expired.

The APS934I message is issued from the PSF ESTAE and does not have complete information if the error is a network error or printer communication error. In some cases APS935I precedes APS934I and has more detailed CAUSE information. If the APS935I message is issued, always use APS935I to determine the cause.

If PSF tried the error again, you received corresponding APS935I messages.

TCP/IP ERRNO=*errno* indicates the TCP/IP error. To interpret the ERRNO, see [z/OS Communications Server: IP and SNA Codes](#).

Common ERRNOs associated with this message are:

49

Cannot reach destination, indicating a bad IP address.

60

- The printer is powered off.
- If the printer is attached with an i-data 7913 IPDS printer LAN Attachment, either the printer or the i-data 7913 IPDS Printer LAN Attachment is not powered on.
- The wrong IP address is specified in the Printer Inventory or in the PRINTDEV statement.
- The printer is not physically attached.
- The IP address that is specified is a duplicate of another IP address on the network.
- The port number (PORTNO) at the host and printer do not match.
- A firewall problem exists between the system and the printer.
- The printer has a bad IPDS card.
- The printer is attached on a different LPAR.

61

Connection was refused. This error might happen when the printer is accepting a connection with another partner and refuses other connections while it completes the current request. It also might happen when the IP address is valid but the target system is not a printer or host that has the IBM printer layer code. This error might also happen when the port number (PORTNO) at the host and printer do not match.

PRINTER(*prtnnnn*) specifies the name of the PRINTDEV statement. IP ADDRESS(*ip-address*) specifies the Internet Protocol (IP) address of the TCP/IP-attached printer. CAUSE can be any of these reasons:

- SOCKET CONNECT FAILED—PSF failed to establish a socket connection with the printer. PSF displays this reason when:
 - The printer is powered off.
 - If the printer is attached with an i-data 7913 IPDS printer LAN Attachment, either the printer or the i-data 7913 IPDS Printer LAN Attachment is not powered on.
 - The wrong IP address is specified in the Printer Inventory or in the PRINTDEV statement.
 - The printer is not physically attached.
 - The IP address that is specified is a duplicate of another IP address on the network.
 - The port number (PORTNO) at the host and printer do not match.

- OPEN SESSION FAILED—PSF failed to establish a session with the printer because of either a timeout that is waiting for a reply from the printer or a communication error. PSF displays this reason when:
 - The target system is not processing the IBM printer layer code.
 - The printer is being used by another PSF FSA on the same host.
- PRINTER ASSIGN FAILED—The host request to assign the printer failed. The printer can be reached, but it did not accept the assignment request.
- PRINTER ASSIGNED ELSEWHERE—The printer (*prtnnnn*) at IP address (*ip-address*) is being used by another host application. Only one task such as PSF can communicate with the printer at any time.
- PRINTER ASSIGN TIMEOUT—The printer did not reply to a host request for assignment of an IPDS conversation.
- INCORRECT MESSAGE VERSION—This cause indicates an incompatibility between PSF and the printer. If the communication failure occurs with a printer that is supported by PSF, notify your system programmer of this error.
- NONACK RETRY—Communication with the printer was ended, but a RETRY condition exists. PSF tries to reestablish communication with the printer.
- NONACK NORETRY—Communication with the printer was ended. PSF displays this reason when:
 - The printer has a hardware failure.
 - The connection with the printer is broken.
 - An unknown communication failure occurs.
- NONACK COMMERR—PSF communication with the printer failed because of either a timeout that is waiting on a reply from the printer or a communication error. PSF displays this reason when the physical connection with the printer is broken.

System action

The PSF FSA ends because the condition cannot be tried again or the connect interval (CONNINTV) timer expired.

Operator response

If CAUSE and ERRNO explain why communication with the printer ended, fix the problem and restart the PSF FSA. If the CAUSE does not explain why the communication session with the printer was ended, notify your system programmer of this error.

System programmer response

If the problem was caused by incorrect values in the Printer Inventory or an incorrect network specification or an incorrect PSF PRINTDEV statement, correct the incorrect items. If a communications-attachment failure occurred, use the PING command with the IP address in the message to ensure that the printer's TCP/IP socket connection to this address is active. For information on how to ping an IP address, see [PSF for z/OS: Customization](#).

If this printer is being shared by another host print application or by another PSF, see information about sharing a printer in [PSF for z/OS: Customization](#).

If you changed a PRINTDEV parameter on the PSF startup procedure, such as the IP address, the PSF FSS must be restarted to use the changes. If you changed a parameter in the Printer Inventory, the PSF FSA must be restarted to use the changes.

If the error condition persists, follow the procedures that are described in [PSF for z/OS: Customization](#) before you consult the IBM Support Center.

User response

No response is necessary.

APS935I CONNECTION WITH TCP/IP-ATTACHED PRINTER (*prtnnnn*) IPADDR (*ip-address*) IS BEING TRIED AGAIN BECAUSE OF A PREVIOUSLY DETECTED RETRIABLE CONDITION (*reason*), TCP/IP ERRNO = *errno*.

Explanation

Communication with the printer was ended for a condition that can be tried again. PSF tried to establish the session again.

TCP/IP ERRNO=*errno* indicates the TCP/IP error. To interpret the *errno*, see [z/OS Communications Server: IP and SNA Codes](#).

Common ERRNOs associated with this message are:

0

See the previous message for a description of the problem.

49

Cannot reach destination, indicating a bad IP address.

60

- The printer is powered off.
- If the printer is attached with an i-data 7913 IPDS printer LAN Attachment, either the printer

or the i-data 7913 IPDS Printer LAN Attachment is not powered on.

- The wrong IP address is specified in the Printer Inventory or in the PRINTDEV statement.
- The printer is not physically attached.
- The IP address that is specified is a duplicate of another IP address on the network.
- The port number (PORTNO) at the host and printer do not match.
- A firewall problem exists between the system and the printer.
- The printer has a bad IPDS card.
- The printer is attached on a different LPAR.

61

Connection was refused. This error might happen when the printer is accepting a connection with another partner and refuses other connections while it completes the current request. It also might happen when the IP address is valid but the target system is not a printer or host that has the IBM printer layer code. This error might also happen when the port number (PORTNO) at the host and printer do not match.

PRINTER (*prtnnnn*) specifies the name of the PRINTDEV statement. IPADDR (*ip-address*) specifies the Internet Protocol (IP) address of the TCP/IP-attached printer. CONDITION can be any of these reasons:

- SOCKET FAILED—PSF was not able to get a socket on the z/OS operating system.
- SOCKET CONNECT FAILED—PSF failed to establish a socket connection with the printer. PSF displays this reason when:
 - The printer is powered off.
 - If the printer is attached with an i-data 7913 IPDS printer LAN Attachment, either the printer or the i-data 7913 IPDS Printer LAN Attachment is not powered on.
 - The wrong IP address is specified in the Printer Inventory or in the PRINTDEV statement.
 - The printer is not physically attached.
 - The IP address that is specified is a duplicate of another IP address on the network.
 - The port number (PORTNO) at the host and printer do not match.
- IOCTL FAILED—The socket connection requires a non-blocking socket but the call to make the socket non-blocking failed.
- SETSOCKOPT FAILED—The call to set the KEEPALIVE option on for the socket connect failed.

- OPEN SESSION FAILED—PSF failed to establish a session with the printer because of either a timeout that is waiting for a reply from the printer or a communication error. PSF displays this reason when:
 - The target system is not processing the IBM printer layer code.
 - The printer is being used by another PSF FSA on the same host.
- PRINTER ASSIGN FAILED—The host request to assign the printer failed. The printer can be reached, but it did not accept the assignment request.
- PRINTER ASSIGNED ELSEWHERE—The printer (*prtnnnn*) at IP address (*ip-address*) is being used by another host application. Only one task such as PSF can communicate with the printer at any time.
- PRINTER ASSIGN TIMEOUT—The printer did not reply to a host request for assignment of an IPDS conversation.
- NONACK RETRY—Communication with the printer was ended.
- NONACK COMMERR—PSF communications with the printer failed because of either a timeout that is waiting for a reply from the printer or a communication error. PSF displays this message when the printer was attached but for some reason the connection is severed through a hardware or software problem.

System action

Start of the session is tried again, and PSF waits for the activation to complete. If Failure action = Wait for connect in the Printer Inventory or FAILURE=WCONNECT was specified on the PRINTDEV statement in the PSF startup procedure, PSF attempts to restart the session continuously, issuing the APS935I message only when the ERRNO or REASON code changes between attempts.

Operator response

If CONDITION and ERRNO explain why communication with the printer ended, fix the problem and restart the PSF FSA. If the CONDITION does not explain why the communication session with the printer ended, notify your system programmer of this error.

If the printer does not respond to PSF, you can stop the printer FSA by use of the MODIFY command:

```
MODIFY FSSname,FORCE,printer-name
```

System programmer response

If the problem was caused by an incorrect network specification, incorrect values in the Printer Inventory,

or an incorrect PSF PRINTDEV statement, correct the incorrect items.

If a communication-attachment failure occurred, use the PING command with the IP address in the message to ensure that this printer's TCP/IP socket connection to this address is active. For information on how to ping an IP address, see [PSF for z/OS: Customization](#).

If this printer is being shared by another host print application or by another PSF, see information about sharing printers in [PSF for z/OS: Customization](#).

User response

No response is necessary.

APS936I COMMUNICATION WITH SNA-ATTACHED PRINTER prtnnnn LUNAME luname WAS TERMINATED DUE TO A RELEASE REQUEST FROM VTAM.

Explanation

Communication with PRINTER (*prtnnnn*) was ended after VTAM indicated that another print driver queued a session request for the printer and the release interval (RELINTV) expired. PRINTER (*prtnnnn*) specifies the name of the PRINTDEV statement that defines this printer. LUNAME (*luname*) specifies the SNA logical unit name of the SNA-attached printer.

System action

Communication with the SNA-attached printer is ended. PSF attempts to restart the session with the printer according to the management mode specified in the Printer Inventory or on the PRINTDEV statement (MGMTMODE).

Operator response

If this message is displayed frequently, notify your system programmer.

System programmer response

If this message is displayed too frequently, consider increasing the amount of time that is specified in the Release interval in the Printer Inventory or the RELINTV parameter on the PRINTDEV statement in the procedure that is used to start PSF. For information on printer sharing, see [PSF for z/OS: Customization](#).

User response

No response is necessary.

APS937I**IPDS DIALOG WITH PRINTER
prtntnnn WAS ENDED DUE TO A
RELEASE REQUEST FROM THE
PRINTER.****Explanation**

The IPDS dialog with PRINTER (*prtntnnn*) was ended after a release request (NACK) was received from the printer and the release interval (RELINTV) expired. PRINTER (*prtntnnn*) specifies the name of the PRINTDEV statement that defines this printer.

System action

Communication with the printer is suspended temporarily. PSF attempts to restart the dialog with the printer according to the release mode specified in the Printer Inventory or on the PRINTDEV statement. When the release mode is IDLE, the dialog is restarted when another data set for the printer is on the JES spool. When the release mode is TIME, the dialog is restarted after the acquire interval (ACQINTV) expires.

Operator response

If this message occurs frequently, consult your system programmer.

System programmer response

If this message is displayed too frequently, consider increasing the amount of time specified for the release interval in the Printer Inventory or on the PRINTDEV statement. For information on printer sharing, see [PSF for z/OS: Customization](#).

User response

No response is necessary.

APS938I**IPDS DIALOG WITH PRINTER
prtntnnn WAS RESTARTED.****Explanation**

The IPDS dialog with PRINTER (*prtntnnn*) was suspended and is now restarted. PRINTER (*prtntnnn*) specifies the name of the PRINTDEV statement that defines this printer.

System action

Communication with the printer continues.

Operator response

No response is necessary.

System programmer response

No response is necessary. For information on printer sharing, see [PSF for z/OS: Customization](#).

User response

No response is necessary.

APS939I**STARTUP OF COMMUNICATION
WITH PRINTER *prtntnnn* WAS
ABORTED DUE TO A CONNECT
INTERVAL TIMEOUT.****Explanation**

PSF attempted to start a session or dialog with the printer for the time specified by the connect interval (CONNINTV). The printer was busy or unavailable for this period. PRINTER (*prtntnnn*) specifies the name of the PRINTDEV statement that defines this printer.

System action

The PSF FSA for the printer is stopped.

Operator response

If this message is displayed frequently, notify your system programmer.

System programmer response

If this message is displayed too frequently, consider increasing the amount of time that is specified in the Connect interval in the Printer Inventory or CONNINTV parameter on the PRINTDEV statement in the procedure that is used to start PSF.

User response

No response is necessary.

APS940I**REQUIRED RESPONSE NOT
RECEIVED FROM *prtntnnn*.****Explanation**

The time that is specified by the Response timeout in the Printer Inventory or the PRINTDEV RESPTIME keyword for printer or download receiver *prtntnnn* expired before PSF received a response from the printer.

System action

The action that is specified by the No response action in the Printer Inventory or the NORESP keyword on the PRINTDEV statement is taken.

Operator response

Have the responsible person check the printer or download receiver to determine why it is not responding to PSF and correct the condition.

System programmer response

Have the responsible person check the printer or download receiver to determine why it is not responding to PSF and correct the condition.

User response

Have the responsible person check the printer or download receiver to determine why it is not responding to PSF and correct the condition.

APS941I **MISSING RESPONSE RECEIVED FROM prtnnnn.**

Explanation

This message follows APS940I and indicates that the problem is corrected and the printer or download receiver is now responding to PSF.

System action

None.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

No response is necessary.

APS942I **AUTOMATIC RESOLUTION MODE NOT SUPPORTED WHEN ATTACHED TO EITHER DPF OR RPM3. SWITCH THE PRINTER OUT OF AUTOMATIC RESOLUTION MODE.**

Explanation

PSF is connected to the printer with an intermediate device of either DPF or RPM3, and the printer is in automatic resolution mode. This configuration is not supported.

System action

The PSF FSA for the printer is stopped with a system completion code 024 and abend reason code 0243.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Switch the printer out of automatic resolution mode.

User response

No response is necessary.

APS943I **PSF WAS UNABLE TO COMPLETE CHANNEL INITIALIZATION. THE REGION SIZE IS PROBABLY TOO SMALL.**

Explanation

More storage was required to complete channel initialization, but this storage was not available. This message is followed by PSF message APS050I.

System action

PSF processing ends abnormally with a system completion code 024 and abend reason code 0201.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Increase the Region Parameter on the startup procedure.

User response

No response is necessary.

APS944I **THE *data type* DATA SET MUST BE A PDSE. THE *data type* REPORT WILL NOT BE CREATED.**

Explanation

The *data type* data set, where *data type* is PRTINFO or AFPSTATS, was not allocated as a PDSE; therefore, PSF cannot create the PRTINFO or AFPSTATS report. The PRTINFO or AFPSTATS data set must be a partitioned data set allocated as a PDSE to reduce problems with insufficient directory blocks and storage space and to allow multiple FSAs to open the data set without a system abend.

System action

PSF continues processing but does not create the PRTINFO or AFPSTATS report.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Allocate the PRTINFO or AFPSTATS data set as a PDSE.

User response

Inform your system programmer that this error occurred.

APS945I **PRINTER *printer name* RESPONSE IS LONGER THAN THE MAXIMUM BUFFER ALLOCATED FOR THE *command name* COMMAND.**

Explanation

PSF requested a response from the printer, but the printer returned a command response that is longer than the maximum buffer size allocated for the command.

System action

PSF processing is abnormally ended with a system completion code of 024 and abend reason code 02FA.

Operator response

If this message is displayed, contact your system programmer.

System programmer response

Follow the procedures that are described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

No response is necessary.

APS946I **THE IPADDR (*ip_address*) SPECIFIED IN THE PRINTDEV OR IN THE PRINTER INVENTORY COULD NOT BE RESOLVED.**

Explanation

If a dotted decimal or colon hexadecimal address was provided, it was not in the correct format or was not

valid. If a host name was provided, it cannot be resolved by TCP/IP.

System action

The PSF FSA ends.

Operator response

Notify your system programmer.

System programmer response

If a dotted decimal or colon hexadecimal address was provided, correct the error.

If an installation exit that is written in the C language is being used, each FSA runs as a new "Process". Verify that the SYS1.PARMLIB member BPXPRMxx values for MAXPROCSYS and MAXPROCUSER are large enough for each PSF FSA and the FSS to have a PROC. The operator command "D OMVS, 0" displays the current values for these configuration parameters.

If a valid host name was provided, contact your TCP/IP administrator. PSF uses the same name resolver as the TSO LPR command.

User response

Inform your system programmer that this error occurred.

APS947I **COMMUNICATION WITH TCP/IP- ATTACHED PRINTER (*prtnnnn*) WAS TERMINATED DUE TO A PRINTER CONDITION FROM WHICH THE PRINTER COULD NOT RECOVER.**

Explanation

A printer condition occurred from which the printer cannot recover.

System action

The PSF FSA stops processing.

Operator response

Notify the person responsible for the remote printer. This printer condition must be corrected before PSF is restarted.

System programmer response

No response is necessary.

User response

No response is necessary.

APS948I **INITAPI FAILED FOR TCP/IP ADDRESS SPACE NAME OF (*tcpip_name*) FOR REASON (*reason*).**

Explanation

PSF detected that it did not issue a successful INITAPI request with the *tcpip_name* given. *Reason* might be: NO TCP/IP—The FSS was not able to find the TCP/IP module EZASOK03.

System action

The PSF FSA ends.

Operator response

Notify your system programmer.

System programmer response

Ensure that TCP/IP was installed in a library that is loadable by PSF.

User response

No response is necessary.

APS949I **INITAPI FAILED FOR TCP/IP ADDRESS SPACE NAME OF (*tcpip_name*) WITH A RETURN CODE OF (*nnnn*) AND AN ERRNO = *errno*.**

Explanation

The INITAPI call to TCP/IP failed. RETURN CODE has the return code from the call, and ERRNO has the TCP/IP error number. The *tcpip_name* has the TCP/IP address space name, either the default name, TCPIP, or the name specified as a parameter on the EXEC statement.

System action

The PSF FSA ends.

Operator response

Verify that the TCP/IP procedure with the *tcp_ip* name was started. If the TCP/IP task is not started, you must cancel the startup procedure. Then, start the TCP/IP task and restart the printer.

System programmer response

Verify that *tcpip_name* is the TCP/IP address space name. This is the TCP/IP started task name that is in the TCP/IP profile data set with the TCPIPJOBNAME keyword. Unless the TCP/IP address space name is specified on the EXEC statement in the PSF startup procedure, then PSF uses the default name, TCPIP. Check the ERRNO value in *z/OS Communications Server: IP and SNA Codes*.

User response

No response is necessary.

APS950I **EXIT PUT PROCESSING TERMINATED.**

Explanation

The Document Processor subcomponent of PSF detected an error while the installation exit routine, APSUPUT, had control. This message might be issued because of an I/O error.

System action

A separator page might be incomplete.

Operator response

If no I/O error occurred before this message, notify your system programmer.

System programmer response

Examine the installation exit processing routine in control to see whether it contains an incorrect APSUPUT record.

User response

No response is necessary.

APS951I **SEPARATOR PAGES WILL NOT BE GENERATED AND PSF INSTALLATION EXITS WILL NOT BE INVOKED.**

Explanation

Initialization of the PSF installation exit routine failed, for one of these reasons:

- An insufficient length was specified in the APSUCOM table.
- The APSUCOM module cannot be found.
- A BLDL macro or a LOAD macro failed.

System action

Processing continues without installation exits.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Evaluate any changes that are made to the APSUCOM module (static table), to the exit processor routines, or to the methods used to establish the table or routines in the system. Other messages might contain BLDL macro or LOAD macro return and reason codes.

User response

No response is necessary.

APS952I	BLDL FAILURE DURING INSTALLATION EXIT INITIALIZATION, BLDL RETURN CODE <i>return code</i>, BLDL REASON CODE <i>reason code</i>.
----------------	--

Explanation

While PSF was finding the installation exit processing modules, the BLDL macro failed.

System action

Processing continues without installation exits. Processing of separator pages is suspended.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Evaluate the BLDL macro return codes and reason codes to determine the cause of this failure. For more information, see [z/OS DFSMS Macro Instructions for Data Sets](#).

User response

No response is necessary.

APS953I	FAILURE DURING LOAD OF <i>exit routine</i>, SYSTEM COMPLETION CODE <i>system completion code</i>, SYSTEM REASON CODE <i>system reason code</i>.
----------------	--

Explanation

When you attempted to LOAD an installation exit routine, the LOAD macro failed.

System action

PSF does not initialize.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Use the system completion code and system reason code that is issued by the LOAD SVC to determine an appropriate response. To interpret the completion code and reason code, see [z/OS MVS System Codes](#). Also see [z/OS MVS Diagnosis: Tools and Service Aids](#) for a description of the LOAD macro.

After you resolve the problem, restart the printer.

User response

No response is necessary.

APS954I	TERMINATION OF THIS DATA SET WAS REQUESTED BY THE RESOURCE EXIT. (<i>optional text</i>).
----------------	---

Explanation

The Resource Exit requested ending the data set. Optional text might also be provided.

System action

PSF stops processing the data set.

Operator response

No response is necessary.

System programmer response

You might use the Resource Exit to insert data into the *optional text* field of the message, to provide a more detailed explanation for the user as to why this ending occurred. For more information about how to provide optional message text, see [PSF for z/OS: Customization](#).

User response

No response is necessary.

APS955I	BLDL FAILURE DURING INSTALLATION EXIT INITIALIZATION, BLDL RETURN
----------------	--

**CODE return code, BLDL REASON
CODE reason code.**

Explanation

During address space initialization, the BLDL macro failed while locating the installation exit processing modules.

System action

PSF tries to load the exits again when the printer is started. Because the exits cannot be found, PSF uses these assumptions:

- The exits run in 31-bit addressing mode (AMODE 31). PSF obtains the exit data areas above the 16 MB line.
- No C exits exist. PSF does not call BPX1SDD to dub all subtasks as new processes. Processing continues without the installation exits that are written in C.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Evaluate the BLDL macro return codes and reason codes to determine the cause of this failure. For more information, see [z/OS DFSMS Macro Instructions for Data Sets](#).

User response

No response is necessary.

APS956I	24-BIT ADDRESSING CANNOT BE USED BY THE INSTALLATION EXIT <i>exit routine</i> AT THIS TIME. THE EXIT WILL NOT BE INVOKED.
----------------	--

Explanation

At address space initialization, PSF determined that all of the exits ran in 31-bit addressing mode (AMODE 31). The addressing mode might not be changed to 24-bit (AMODE 24) without stopping all the printers in the address space, canceling the PSF address space, and restarting the printers. This problem might be caused in two ways:

- All of the exits ran in AMODE 31. At least one exit was added or was changed to AMODE 24 without canceling the PSF address space.
- During address space initialization, PSF was unable to load one or more of the installation exits because of a BLDL error. PSF assumed that the exits ran in

AMODE 31. When a printer was started, PSF loaded this exit, which was AMODE 24.

System action

Processing continues without this exit.

Operator response

Inform your system programmer that this error occurred.

System programmer response

To use the exit, do these steps:

1. Stop all printers in the address space.
2. Cancel the PSF address space.
3. Restart the printers.

User response

No response is necessary.

APS957I	FAILURE DURING LOAD OF <i>exit routine</i>, SYSTEM COMPLETION CODE <i>system completion code</i>, SYSTEM REASON CODE <i>system reason code</i>.
----------------	--

Explanation

When attempting to LOAD an installation exit routine, the LOAD macro failed.

System action

The PSF address space does not initialize.

Operator response

Inform your system programmer that this error occurred.

System programmer response

To determine an appropriate response, use the system completion code and the system reason code issued by the LOAD SVC routine. To interpret the completion code and reason code, see [z/OS MVS System Codes](#). Also see [z/OS MVS Diagnosis: Tools and Service Aids](#) for a description of the LOAD macro. After you resolve the problem, restart the printer.

User response

No response is necessary.

APS958I	PSF INSTALLATION EXITS WILL NOT BE INVOKED.
----------------	--

Explanation

The initialization of the PSF installation exit routine failed, for one of these reasons:

- Insufficient length was specified in the APSUCOM table.
- The APSUCOM module cannot be found.
- A BLDL macro failed.

System action

Processing continues without installation exits.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Evaluate any changes that are made to the APSUCOM module (static table), to the exit routines, or to the methods used to establish the tables or routines in the system. Other messages might contain BLDL macro return and reason codes.

User response

No response is necessary.

APS959I **SEPARATOR PAGES WILL NOT BE GENERATED. INSTALLATION EXIT exit routine IS NOT AVAILABLE.**

Explanation

Initialization of the PSF or AFP Download Plus installation exit routine failed because the APSUBTBL module cannot be found.

System action

Processing continues without this installation exit.

Operator response

Notify your system programmer of this error.

System programmer response

To use the installation exit, do these steps:

1. Stop all printers in the address space.
2. Cancel the PSF or AFP Download Plus address space.
3. Add load module APSUBTBL to the linklib.
4. Restart the printers.

User response

No response is necessary.

APS960I **UNABLE TO {OPEN | CLOSE} DD STATEMENT *ddname*. TRACE FORMATTING TERMINATED.**

Explanation

The indicated *ddname* cannot be opened or closed by the PSF Trace Formatter. Processing is ended because the data set is required.

System action

The Trace Formatter stops processing. If the error occurred during a CLOSE request, the output data set might or might not be created. The state of the input data set is not affected.

Operator response

No response is necessary.

System programmer response

Verify that the indicated data set is correctly allocated and that the DD statement is correct in the JCL for the trace formatter job.

User response

No response is necessary.

APS961I **INCORRECT SYSIN DATA SET ATTRIBUTES WERE SPECIFIED.**

Explanation

The DCB attributes of the SYSIN data set are not valid, in one of these ways:

- The record length of the SYSIN data set is not 80. A record length of 80 is required for the SYSIN data set.
- The SYSIN data set is not in fixed-record format. A fixed-record format is required for the SYSIN data set.

System action

Trace Formatter processing was stopped. No output data set is created.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Ensure that the SYSIN data set has a block size of 80 and is in fixed-record format.

APS962I **INSUFFICIENT VIRTUAL STORAGE WAS AVAILABLE TO ACQUIRE CONTROL BLOCKS REQUIRED FOR TRACE FORMATTING. TRACE FORMATTING WAS TERMINATED.**

Explanation

A GETMAIN error occurred during Trace Formatter initialization. Initialization cannot be completed.

System action

Trace Formatter processing is stopped. No output data set is created. The state of the input data set is not affected.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Increase the region size in the JCL for the trace formatter job.

APS963I **INCORRECT TRACE CONTROL OPTIONS SPECIFIED, TYPE=SHORT WAS ASSUMED.**

Explanation

The options specified in the SYSIN data set were not recognized by the Trace Formatter. For information on the format of the SYSIN control options, see [PSF for z/OS: Diagnosis](#).

System action

Tracing is done by using TYPE=SHORT.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Correct the options that are specified in the SYSIN data set.

APS964I **AN INCOMPLETE TRACE RECORD WAS FOUND AT THE END OF THE TRACE DATA SET.**

Explanation

An end of file was encountered before all the data associated with an input trace record was processed. Incomplete trace records can occur for many reasons, including these:

- The operator canceled PSF while it was tracing.
- End of Volume was encountered while PSF was tracing.
- An I/O error occurred while PSF was tracing.
- A part of the PSF trace is being formatted.

System action

Part or all of the incomplete trace record was not formatted. Formatting of the partial record was attempted. The partial record might be formatted in dump format.

Operator response

No response is necessary.

System programmer response

If the error condition persists, follow the procedures described in [PSF for z/OS: Diagnosis](#) before you contact the IBM Support Center.

User response

Inform your system programmer that this error occurred.

APS965I **NUMBER OF TRACE RECORDS PROCESSED = count.**

Explanation

The indicated number of input trace records were processed during the execution of the PSF Trace Formatter. The number of trace records might not match the number of trace entries. The message is printed every time the number of entries processed counter-wraps to 0. To obtain the total number of entries that are processed, add all the occurrences of this message.

System action

Trace Formatter processing continues.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

No response is necessary.

**APS966I NUMBER OF TRACE RECORDS IN
 ERROR = *count*.**

Explanation

The indicated number of input unformatted trace records contained errors. The unformatted trace records were in an unrecognizable format. This message is printed every time the trace entries in error counter wraps to 0. To get the total number of trace entries that contain errors, add all the occurrences of this message.

System action

The entries that contain errors were printed in dump format, and recovery was attempted.

Operator response

No response is necessary.

System programmer response

Errors in the unformatted trace data set can occur because:

- The unformatted trace data set was modified or copied to a data set that has incompatible DCB characteristics.
- The DCB characteristics that are used in generating the data set do not match the DCB characteristics specified to the Trace Formatter.

If the PSF generated unformatted trace data set was unaltered, consult your IBMservice representative.

User response

Inform your system programmer that this error occurred.

**APS967I SYSIN DATA SET COULD NOT BE
 OPENED. DEFAULT FORMATTING
 TYPE OF SHORT WAS USED.**

Explanation

The SYSIN data set cannot be opened; the default option (TYPE=SHORT) was assumed.

System action

The default control option, TYPE=SHORT, was assumed.

Operator response

No response is necessary.

System programmer response

If you suspect a PSF Trace Formatter logic error, follow the procedures described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

If a SYSIN data set was specified in the Trace Formatter JCL, verify that the data set exists. If the data set exists and was correctly specified in the Trace Formatter JCL, report the problem to your system programmer.

**APS970I NO FCB PARAMETER WAS
 SPECIFIED IN THE DATA SET JCL
 OR AS A JES DEFAULT.**

Explanation

The data set that is processed was identified as requiring 3800 Line-Mode Conversion or Line Mode Migration processing. However, no FCB parameter was found in the JCL for the data set; therefore, the processing cannot take place.

System action

PSF stops processing and printing the data set. In deferred printing mode PSF releases the current data set back to JES and requests that it is held by the system unless PRTEROR=QUIT was specified on the OUTPUT statement.

Operator response

No response is necessary.

System programmer response

If the 3800 Line-Mode Conversion function is being used, PSF Exit 4 or 14 requested that line-mode conversion is done for this data set. If conversion is required, PSF cannot determine the correct formatting of each page because no FCB is specified. Specify an FCB on the JCL, define an installation default FCB, or

request that the job is printed in JES 3800 compatibility mode or on a 3900 printer with the 3800 compatibility mode for 3900 RPQ 8B3997 installed.

If you do not want 3800 line-mode conversion for this data set, change PSF Exit 4 or 14 to specify no conversion.

If the Line Mode Migration function is being used, PSF Exit 8 requested that Line Mode Migration is done on this data set. If the migration is done, PSF cannot determine the page format because no FCB is specified on the data set JCL. Either specify an FCB on the JCL, define an installation default FCB, or request that the job is printed on a JES-controlled printer that supports the type of FCB being used by the job. For example, a 4245 uses an FCB2 and a 4248 uses an FCB4.

If you do not want Line Mode Migration processing for this data set, change Exit 8 so that it does not request the migration function for this data set.

User response

If the data set requires 3800 line-mode conversion, specify the correct FCB parameter in the JCL for the data set. If the data set JCL cannot be changed, request that the job is printed on a 3800 printer in compatibility mode or on a 3900 printer with the 3800 compatibility for 3900 RPQ 8B3997. If the data set does not require 3800 line-mode conversion, consult your system programmer, or change the JCL to specify a page definition or form definition that must be used to print this data set. Specifying a page definition or form definition overrides the request to do the conversion function.

If the data set requires Line Mode Migration processing, specify the correct FCB parameter in the JCL for the data set. If the data set JCL cannot be changed, request that the job is printed on a JES-controlled printer that supports the type of FCB being used by the job. For example, a 4245 uses an FCB2 and a 4248 uses an FCB4. If the data set does not require Line Mode Migration processing, consult your system programmer or change the JCL to specify a page definition that can be used to print this data set. Specifying a page definition overrides the request to do the migration function on the data set.

APS971I **MEMBER *member name* WAS NOT FOUND IN SYS1.IMAGELIB.**

Explanation

The data set being processed was identified as requiring 3800 Line-Mode Conversion or Line Mode Migration processing. However, the member was not

found in the resource library SYS1.IMAGELIB; therefore, the processing cannot take place.

System action

PSF stops processing and printing the data set. In deferred printing mode PSF releases the current data set back to JES and requests that it is held by the system unless PRTEROR=QUIT was specified on the OUTPUT statement.

Operator response

No response is necessary.

System programmer response

If the data set is not to be converted from 3800 line mode to PSF line mode, change PSF Exit 4 or 14 to request that this data set is not converted.

If the data set is not to be migrated from 4245 line mode or 4248 line mode to PSF line mode, change the PSF Exit 8 so migration processing is not done on this data set.

User response

If you want 3800 Line-Mode Conversion or Line Mode Migration processing for this data set, an FCB matching the FCB name in the user JCL must exist in SYS1.IMAGELIB. If the FCB name in the JCL is incorrect, change the name of the FCB in the JCL statements. If the FCB name in the JCL is correct, use IEBIMAGE to create an FCB that matches the FCB name specified in the JCL. If you do not want 3800 Line-Mode Conversion or Line Mode Migration processing for this data set, or you are using the FCB specified in the JCL as a page definition name to be accessed in a PSF resource library, consult your system programmer.

APS972I

A SYSTEM LOAD ERROR WAS DETECTED WHILE ATTEMPTING TO LOAD MEMBER *member name* FROM SYS1.IMAGELIB, SYSTEM COMPLETION CODE *system completion code*, SYSTEM REASON CODE *system reason code*.

Explanation

The data set being processed was identified as requiring 3800 Line-Mode Conversion or Line Mode Migration processing. However, a LOAD error occurred during the attempt to load the member from SYS1.IMAGELIB into virtual storage.

System action

PSF stops processing and printing the data set. In deferred printing mode PSF releases the current data set back to JES and requests that it is held by the system unless PRTEROR=QUIT was specified on the OUTPUT statement.

Operator response

Inform your system programmer that this error occurred.

System programmer response

To determine an appropriate response, use the system completion code and system reason code issued by the LOAD SVC routine. To interpret the completion code and reason code, see *z/OS MVS Programming: Authorized Assembler Services Reference LLA-SDU* for a description of the LOAD macro. After you resolve the problem, resubmit the data set.

User response

Inform your system programmer that this error occurred.

APS973I **THE PAGE LENGTH OF *fc**b*-paper-length INCHES DEFINED IN FCB *fc**b*-name DOES NOT MATCH THE physical-paper-length INCH LENGTH OF THE PAPER LOADED IN THE PRINTER.**

Explanation

The data set being processed was identified as requiring line mode conversion. However, the paper length in the FCB, as calculated by number of lines and lines per inch, must match:

- For PSF, the physical length of the paper loaded in the printer.
- For AFP Download Plus, the `paper-length` AFPPARMS control statement parameter or the `Paper length` Printer Inventory parameter.

System action

PSF stops processing and printing the data set. In deferred-printing mode, PSF releases the current data set back to JES and requests that it is held by the system unless PRTEROR=QUIT was specified on the OUTPUT data set.

AFP Download Plus stops processing the data set. AFP Download Plus releases the current data set back to JES and requests that it is held by the system unless

PRTEROR=QUIT was specified on the OUTPUT data set.

Operator response

For PSF, load the FORM that corresponds to the paper size specified in the FCB.

For AFP Download Plus, no response is necessary.

System programmer response

No response is necessary for PSF.

For AFP Download Plus, do one of these:

- Correct the AFPPARMS control statement `paper-length` parameter that was specified on the AFPPARMS DD statement in the AFP Download Plus startup procedure or the `paper length` parameter that was specified in the Printer Inventory.
- Set XTP7LMCM in installation Exit 7 to OFF or set `Report Line-Mode Conversion paper-length errors` in the Printer Inventory to NO.

User response

For PSF, if the correct FCB was specified in the data set JCL, request that the operator load the correct paper in the printer, or specify the correct installation-defined `FORM=` in the data set JCL. If the FCB specified is incorrect for the data set JCL, correct the FCB specified and resubmit the data set.

For AFP Download Plus, if the correct FCB was specified in the data set JCL, do one of these:

- Correct the AFPPARMS control statement `paper-length` parameter that was specified on the OUTPUT statement in the data set JCL or the `paper length` parameter that was specified in the Printer Inventory.
- Set XTP7LMCM in installation Exit 7 to OFF or set `Report Line-Mode Conversion paper-length errors` in the Printer Inventory to NO.

If the FCB specified is incorrect for the data set JCL, correct the FCB specified and resubmit the data set.

APS974I **THE DATA SET IS NOT A VALID CANDIDATE FOR 3800-1 COMPATIBILITY MODE PROCESSING. COPYMOD *copymod-name* WAS SPECIFIED IN THE DATA SET JCL, BUT COPYMOD PROCESSING IS NOT A SUPPORTED FUNCTION.**

Explanation

The data set being processed was identified as requiring 3800-1 compatibility mode (3800 line mode) conversion. However, a COPYMOD *copymod-name* was specified in the data set JCL; and COPYMOD conversion is not a supported function.

System action

PSF stops processing and printing the data set. In deferred printing mode PSF releases the current data set back to JES and requests that it is held by the system unless PRTEROR=QUIT was specified on the OUTPUT statement.

Operator response

Route the job to a 3800 printer that is running in JES 3800-1 compatibility mode or to a 3900 printer with the 3800 Compatibility for 3900 RPQ 8B3997 installed.

System programmer response

No response is necessary.

User response

Request that the job is printed in JES 3800-1 compatibility mode or on a 3900 printer with the 3800 Compatibility for 3900 RPQ 8B3997 installed.

APS975I	THE DATA SET IS NOT A VALID CANDIDATE FOR 3800-1 COMPATIBILITY MODE PROCESSING, BECAUSE A PAGEDEF OR FORMDEF WAS SPECIFIED IN THE DATA SET JCL. THE DATA SET WAS PRINTED USING THE PAGEDEF OR FORMDEF SPECIFIED IN THE JCL.
----------------	--

Explanation

The data set being processed was identified as requiring 3800-1 compatibility mode (3800 line mode) conversion. Because the PAGEDEF or FORMDEF parameter was specified in the data set JCL, no attempt was made to convert the job from 3800 line mode to PSF line mode. Instead, the data set was printed as if no conversion is requested. If an FCB was specified in the data set JCL, and no PAGEDEF was specified, the FCB name is used as the PAGEDEF. If both an FCB and a PAGEDEF parameter are specified in the JCL, the PAGEDEF parameter is used to print the data set.

System action

PSF continues processing the data set, but does not do the 3800 line-mode conversion to PSF line mode.

System programmer response

No response is necessary.

User response

Remove the PAGEDEF or FORMDEF parameters from the JCL, or notify your system programmer of this error.

APS976I	THE DYNAMIC ALLOCATION FUNCTION WAS UNSUCCESSFUL FOR SYS1.IMAGELIB—SYSTEM COMPLETION CODE <i>system completion code</i>, DYNALLOC ERROR CODE <i>error code</i>, INFORMATION REASON CODE <i>information code</i>.
----------------	---

Explanation

The data set being processed was identified as requiring 3800 Line-Mode Conversion or Line Mode Migration processing. However, an ALLOCATE error occurred during the attempt to allocate SYS1.IMAGELIB.

System action

PSF stops processing and printing the data set. In deferred printing mode PSF releases the current data set back to JES and requests that it is held by the system unless PRTEROR=QUIT was specified on the OUTPUT statement.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Use the system completion code, error code, and information code that is issued by the ALLOCATE routine to determine an appropriate response. To interpret the completion code, SVC99 error code, and SVC99 information code, see *z/OS MVS Programming: Authorized Assembler Services Guide*. After you resolve the problem, resubmit the print job.

User response

Inform your system programmer that this error occurred.

APS977I**SYSTEM FUNCTION *open | close*
FOR SYS1.IMAGELIB WAS
UNSUCCESSFUL. PLEASE INFORM
YOUR SYSTEM PROGRAMMER.****Explanation**

The data set being processed was identified as requiring 3800 Line-Mode Conversion or Line Mode Migration processing. However, an OPEN or CLOSE macro was unsuccessful. One of these conditions caused this error:

- An OPEN macro request, which results in an SVC 19, was issued to open SYS1.IMAGELIB. After returning from the OPEN macro, PSF discovered that the Data Control Block (DCB) was not opened.
- A CLOSE macro request, which results in an SVC 20, was issued to close SYS1.IMAGELIB. After returning from the CLOSE macro, PSF discovered that the Data Control Block (DCB) was not closed.

System action

PSF stops processing and printing the data set. In deferred printing mode PSF releases the current data set back to JES and requests that it is held by the system unless PRTEROR=QUIT was specified on the OUTPUT statement.

Operator response

Inform your system programmer that this error occurred.

System programmer response

For the system information associated with this error, see the additional console messages.

User response

Inform your system programmer that this error occurred.

APS978I**3800-1 COMPATIBILITY MODE
PROCESSING FUNCTION IS NOT
SUPPORTED FOR THIS PRINTER.****Explanation**

The data set being processed was identified as requiring 3800-1 compatibility mode (3800 line-mode) conversion. However, PSF does not support the 3800 line-mode conversion function for the 3800 printer.

System action

PSF stops processing and printing the data set. In deferred printing mode PSF releases the current data set back to JES and requests that it is held by the system unless PRTEROR=QUIT was specified on the OUTPUT statement.

Operator response

Notify your system programmer. If installation procedures allow it, print the data set in 3800-1 compatibility mode. Otherwise, no response is necessary.

System programmer response

Ensure that installation procedures are defined to print data sets requiring 3800 line-mode conversion on printers other than the 3800, or use JES in 3800-1 compatibility mode to print those data sets. If 3800 line-mode conversion is not wanted for the data set, modify PSF Exit 4 or 14 to request that no conversion is done for the data set.

User response

Ensure that data sets requiring 3800 line-mode conversion are routed to a printer other than the 3800. Otherwise, print the data set by using JES in 3800-1 compatibility mode, or route it to a 3900 printer with the 3800 Compatibility for 3900 RPQ 8B3997 installed; or change PSF Exit 4 or 14 so that conversion is never requested for print jobs that run to a 3800.

APS979I**AN INCORRECT REQUEST FROM
THE LOGICAL RECORD EXIT WAS
DETECTED FOR LOGICAL RECORD
*logical record number.*****Explanation**

An incorrect request was returned by the logical record processing exit 04 or 14 during 3800 line-mode conversion.

System action

PSF stops processing and printing the data set. In deferred printing mode PSF releases the current data set back to JES and requests that it is held by the system unless PRTEROR=QUIT was specified on the OUTPUT statement.

Operator response

No response is necessary.

System programmer response

Verify that recent changes did not cause an error in the logical record processing exit.

User response

Inform your system programmer that this error occurred.

APS980I **THERE WAS A PREVIOUS ERROR RETURNED FROM THE OPEN REQUEST ON SYS1.IMAGELIB. NO PROCESSING WILL BE DONE.**

Explanation

The data set being processed was identified as requiring 3800 Line-Mode Conversion or Line Mode Migration processing. However, the OPEN attempt on SYS1.IMAGELIB failed.

System action

PSF stops processing and printing the data set. In deferred printing mode PSF releases the current data set back to JES and requests that it is held by the system unless PRTEROR=QUIT was specified on the OUTPUT statement.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Examine the system codes and messages issued for the original OPEN error. APS977I was issued by PSF at the time of the original OPEN error. The system diagnostic messages are in the area of the APS977I message on the console or in the console log.

User response

Inform your system programmer that this error occurred.

APS981I **THE DATA SET IS NOT A VALID CANDIDATE FOR LINE MODE MIGRATION PROCESSING BECAUSE A PAGEDEF OR FORMLEN PARAMETER WAS SPECIFIED IN THE DATA SET JCL. THE DATA SET WAS PRINTED USING THE PAGEDEF OR FORMLEN SPECIFIED IN THE JCL.**

Explanation

The data set being processed required Line-Mode Migration processing. Because a PAGEDEF or FORMLEN parameter was specified in the data set JCL, the data set was not migrated from 4245 line mode or 4248 line mode to PSF line mode. The data set was printed by using the PAGEDEF or FORMLEN parameter specified in the JCL.

System action

If a PAGEDEF parameter was specified in the data set JCL, PSF used the page definition that is specified on the PAGEDEF parameter to print the data set even if an FCB parameter was specified in the data set JCL. If a FORMLEN parameter was specified in the data set JCL, PSF printed the data set by using the FORMLEN parameter in addition to the page definition or FCB that is specified in the data set JCL.

Operator response

No response is necessary.

System programmer response

If the data set is to be migrated, have the user remove the PAGEDEF or FORMLEN parameter from the data set JCL and instead use the FCB parameter to specify an FCB for PSF to use when it migrates the data set. Ensure that the data set is processed by using the correct type of Line Mode Migration processing: 4245 FCB or 4248 FCB. If the data set is not to be migrated, modify PSF Exit 8 so the data set is not selected for migration processing.

User response

If the data set is to be migrated, remove the PAGEDEF or FORMLEN parameter from the data set JCL. If the data set is not to be migrated, notify your system programmer of this error.

APS982I **LINE MODE MIGRATION PROCESSING FOR THIS DATA SET IS TERMINATED BECAUSE IT IS NOT USING A 4248 FCB.**

Explanation

The data set being processed was identified as requiring Line Mode Migration processing for a 4248 FCB (FCB4). However, the FCB specified in the FCB parameter in the JCL for the data set is not a 4248 FCB.

System action

PSF stops processing the data set and releases it back to JES. It requests that the data set is held by the system unless PRTEROR=QUIT was specified on the OUTPUT statement in the JCL for the data set.

Operator response

No response is necessary.

System programmer response

If the Line Mode Migration processing must be done on this data set, have the user specify a 4248 FCB on the data set JCL. If Line Mode Migration processing does not need to be done on this data set, modify PSF Exit 8 so processing is not done on this data set.

User response

If the data set requires Line Mode Migration processing for a 4248 FCB, specify the name of a 4248 FCB in the FCB parameter in the data set JCL. If the data set JCL cannot be changed, request that the job is printed on a JES-controlled 4248 printer.

If the data set does not require Line Mode Migration processing, change the JCL to specify a page definition for PSF to use to print this data set or have your system programmer modify PSF Exit 8 so Line Mode Migration processing is not done on this data set. Specifying a page definition overrides the request to do the Line Mode Migration processing on the data set. For more information about a 4248 FCB, see [z/OS DFSMSdfp Utilities](#).

APS983I	WHEN CONVERTED TO L-UNITS, THE VALUE SPECIFIED FOR THE PAPER-LENGTH CONTROL PARAMETER IS <i>paper-length</i> L-UNITS. THE VALUE CANNOT BE EITHER 0 L-UNITS OR GREATER THAN THE MAXIMUM L-UNITS.
----------------	--

Explanation

When the paper length value (specified in the `paper-length` AFPPARMS control statement parameter or in the `Paper length` Printer Inventory parameter) is converted to L-units, the value is either 0 or greater than 65535 L-units, which is not valid. The maximum values for the paper length parameter are:

- 273.066 inches
- 693.589 centimeters
- 6935.893 millimeters
- 65535 pels
- 19660 points

System action

The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 0E83.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Verify and correct the value of the `paper-length` AFPPARMS control parameter or the `Paper length` Printer Inventory parameter.

User response

No response is necessary.

APS984I	WHEN CONVERTED TO L-UNITS, THE VALUE SPECIFIED FOR THE PAPER-WIDTH CONTROL PARAMETER IS <i>paper-width</i> L-UNITS. THE VALUE CANNOT BE EITHER 0 L-UNITS OR GREATER THAN THE MAXIMUM L-UNITS.
----------------	--

Explanation

When the paper width value (specified in the `paper-width` AFPPARMS control statement parameter or in the `Paper width` Printer Inventory parameter) is converted to L-units, the value is either 0 or greater than 65535 L-units, which is not valid. The maximum values for the paper width parameter are:

- 273.066 inches
- 693.589 centimeters
- 6935.893 millimeters
- 65535 pels
- 19660 points

System action

The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 0E84.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Verify and correct the value of the `paper-width` AFPPARMS control parameter or the `Paper width` Printer Inventory parameter.

User response

No response is necessary.

APS986I **NO DOWNLOAD ROUTING RECORD
MATCHED FOR JOB (*jobname*),
DATASET (*data set name*).**

Explanation

The class, form name, or destination that is specified in the JCL for the data set does not match any of the routing records in the Download for z/OS routing-control data set. Download for z/OS cannot determine the remote system to which to route this data set. Download for z/OS detected this error. See [PSF for z/OS: Download for z/OS](#) for more information about this feature.

System action

Download for z/OS releases the data set back to JES and requests that it is held by the system.

Operator response

Release the held data set after the system programmer modifies the routing-control data set to add the class, destination, or form name of the data set. If the system programmer does not want to modify the routing-control data set, you can process the held data set by releasing it with a class, form name, or destination that matches an existing routing statement in the routing-control data set. For example, to release output group 2.1.1 of job 13 to class C:

```
$T 0 J13,OUTGRP=2.1.1,REL=SYS,Q=C
```

System programmer response

Consider adding a routing statement in the Download for z/OS routing-control data set to match the data set's class, form name, or destination. After you modify the routing-control data set, stop the FSS and restart the Download for z/OS FSAs to use the modified routing-control data set.

User response

No response is necessary.

APS987I **THE REMOTE SYSTEM DID NOT
SUCCESSFULLY PROCESS THE
RECEIVED DATA SET OR THE
TOTAL BYTES SENT DOES NOT
MATCH THE TOTAL BYTES
RECEIVED BY THE REMOTE
SYSTEM.**

Explanation

The remote system detected an error with the received data set. Either the script or exit that is called by the download receiver encountered an error, or a discrepancy exists between the number of bytes sent by Download for z/OS and the number of bytes received by the remote system.

Download for z/OS detected this error. See [PSF for z/OS: Download for z/OS](#) for more information about this feature.

System action

Download for z/OS attempts to resend the data set according to the retry interval and retry number specified in the matching routing record of the Download for z/OS routing-control data set. If retry is not requested or is not successful, Download for z/OS releases the data set back to JES and requests that it is held by the system.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Check the error logs on the remote system for messages that provide additional information about the cause of the error. Ensure that TCP/IP is functioning correctly. If the problem persists, contact your service representative in the IBM Support Center, or use your electronic link with IBM service for assistance.

User response

No response is necessary.

APS988I **DOWNLOAD SENT *number* (*base*)
BYTES TO *ip_address*-JOB=
jobname STEP= *jobstep* ID= *jobid*.**

Explanation

A data set with the indicated number of bytes was resent to the remote system with the IP address (*ip_address*) indicated in the message.

In the message, *number* has two possible forms.

- For files smaller than 4 gigabytes (GB), *number* is the decimal number of bytes sent and *base* is DECIMAL.
- For files larger than 4 GB, *number* is the hexadecimal number of bytes sent. The *base* is HEX and *number* is 16 hexadecimal digits, including leading zeros.

The job submitter requested that this message is sent to the user IDs specified in the NOTIFY keyword in the JCL for the data set. When the job submitter specifies the NOTIFY keyword, this message is sent also to the SYSLOG data set. Download for z/OS detected this error. See *PSF for z/OS: Download for z/OS* for more information about this feature.

System action

Download for z/OS verifies that all data was received by the server on the AIX® system before it purges the data set from the JES spool. No response is necessary.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

No response is necessary.

APS989I **DOWNLOAD SOCKET xxxxxx
COMMAND FAILED FOR IPADDR =
ip_address, PORTNUM = nnnn,
RETURN CODE = nn, ERRNO =
nnnn.**

Explanation

The named socket API call failed with the return code and error number indicated. The IP address and port number of the target remote system and server are indicated in the message.

If RETURN CODE = 0 and ERRNO = 0, the connection partner closed its end of the socket connection.

Download for z/OS detected this error. See *PSF for z/OS: Download for z/OS* for more information about this feature.

System action

Download for z/OS resends the data set according to the retry interval and retry number specified in the matching routing record of the Download for z/OS routing-control data set. If retry is not requested or is not successful, Download for z/OS releases the data set back to JES and requests that it is held.

Operator response

Inform your system programmer that this error occurred. Stop the Download for z/OS FSS, and restart the FSAs if necessary.

System programmer response

To interpret the ERRNO, see *z/OS Communications Server: IP and SNA Codes*. Ensure that the server with the IP address and port number that is indicated in the message is running. If the server is down, restart the server. You typically do not need to restart Download for z/OS. If the connection partner closed its end of the socket connection, determine why the connection closed.

When restarting the server, the administrator of the remote system specifies the same file systems to store files that are received from Download for z/OS. If the same file systems are not specified, transmission of the interrupted file restarts from the beginning of the file instead of from the checkpoint.

User response

No response is necessary.

APS990I **INCORRECT KEYWORD (xxxxxx)
SPECIFIED IN THE DOWNLOAD
ROUTING CONTROL DATASET. THE
KEYWORD IS IGNORED.**

Explanation

Download for z/OS detected an incorrect keyword in the Download for z/OS routing-control data set. Download for z/OS detected this error. See *PSF for z/OS: Download for z/OS* for more information about this feature.

System action

Download for z/OS ignores the incorrect keyword and continues processing the other keywords.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Correct the incorrect keyword in the routing-control data set. To use the modified routing-control data set, stop the Download for z/OS FSS and restart the FSAs.

User response

No response is necessary.

APS991I **DOWNLOAD ROUTING STATEMENT
NUMBER nn DOES NOT CONTAIN
ALL THE REQUIRED KEYWORDS.
THE STATEMENT IS IGNORED.**

Explanation

A routing statement in the Download for z/OS routing-control data set does not contain the required keywords. *nn* is the number of the statement in the routing-control data set; a statement consists of a series of keywords ending with a semicolon. Download for z/OS detected this error. See [PSF for z/OS: Download for z/OS](#) for more information about this feature.

System action

Download for z/OS ignores the routing statement and continues processing the other routing statements, if any.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Correct the incorrect routing statement. Then, stop the Download for z/OS FSS and restart the FSAs to use the modification.

User response

No response is necessary.

APS992I *download version* INITIALIZED.

Explanation

The Download for z/OS version specified was initialized successfully. See [PSF for z/OS: Download for z/OS](#) for more information about the Download for z/OS feature.

System action

The Download for z/OS FSA is ready to receive data sets from the JES spool and send them to servers on AIX systems.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

No response is necessary.

APS993I DOWNLOAD REQUEST CANCELLED —JOB= *jobname* STEP= *jobstep* ID= *jobid* AT *system-id*.

Explanation

The operator canceled processing of the data set indicated in the message. The job submitter requested that this message is sent to the user IDs specified in the NOTIFY keyword in the JCL for the data set. When the job submitter specifies the NOTIFY keyword, this message is sent also to the SYSLOG data set. Download for z/OS detected this error. See [PSF for z/OS: Download for z/OS](#) for more information about this feature.

System action

Download for z/OS continues processing the next data set.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Consult the system operator to determine why the operator canceled the data set.

APS994I DOWNLOAD REQUEST MARKED UNPRINTABLE—JOB= *jobname* STEP= *jobstep* ID= *jobid* AT *system- id*.

Explanation

Download for z/OS determined that the data set identified in the message cannot be sent. The job submitter requested that this message is sent to the user IDs. When the job submitter specifies the NOTIFY keyword, this message is sent also to the SYSLOG data set. Download for z/OS detected this error. See [PSF for z/OS: Download for z/OS](#) for more information about this feature.

System action

Download for z/OS releases the data set back to JES, and requests that the system hold it.

Operator response

See the associated messages to determine the correct action.

System programmer response

No response is necessary.

User response

Consult the system operator to determine why the data set is being held.

APS995I **DOWNLOAD SOCKET xxxxxx
COMMAND FAILED WITH RETURN
CODE= nn, ERRNO= nnnn.**

Explanation

The named socket API call failed with the return code and error number indicated. Download for z/OS detected this error. See *PSF for z/OS: Download for z/OS* for more information about this feature.

System action

- If xxxxxx is INITAPI, the Download FSA might stop. If the error occurs while Download for z/OS is sending a data set, Download for z/OS releases the data set back to JES and requests that it is held by the system.
- If xxxxxx is SOCKET, Download for z/OS resends the current data set according to the retry interval and retry number specified in the matching routing record of the Download for z/OS routing-control data set. If retry is not requested or is not successful, Download for z/OS releases the data set back to JES and requests that it is held by the system.

Operator response

Inform your system programmer that this error occurred.

- If xxxxxx is INITAPI, start TCP/IP and then start Download for z/OS again.
- If xxxxxx is SOCKET, stop the Download for z/OS FSS and then restart the FSAs. Before you restart the FSAs, ensure that TCP/IP is running and the communication controller between the z/OS system and the remote system is online.

System programmer response

To interpret the ERRNO, see *z/OS Communications Server: IP and SNA Codes*.

User response

No response is necessary.

APS996I **INCORRECT PARAMETER VALUE
(value) SPECIFIED FOR KEYWORD
(keyword) AT LINE NUMBER (nnn)**

**IN THE DOWNLOAD ROUTING
CONTROL DATA SET. THE
KEYWORD IS IGNORED.**

Explanation

Download for z/OS detected an incorrect parameter in the Download for z/OS routing-control data set.

value

Is the text that contains the error.

keyword

Is the keyword in the routing record that was being parsed when the error was detected.

nnn

Is the number of the line (80-character record) in the routing-control data set.

Download for z/OS detected this error. See *PSF for z/OS: Download for z/OS* for more information about this feature.

System action

Download for z/OS ignores the keyword that is associated with the incorrect parameter and continues processing the other keywords.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Correct the incorrect parameter in the routing-control data set. To use the modified routing control data set, stop the Download for z/OS FSS and restart the FSAs.

User response

No response is necessary.

APS997I **DOWNLOAD DID NOT TRANSMIT
THE DATASET BECAUSE IPADDR
(ip_address) COULD NOT BE
RESOLVED.**

Explanation

The IPADDR specified in the routing-control data set cannot be used, so the file was not sent. If a dotted decimal or colon hexadecimal address was provided, it was not in the correct format or was not valid. If a host name was provided, it cannot be resolved by TCP/IP.

System action

Download for z/OS attempts to resend the data set according to the retry interval and retry number that is

specified in the matching routing record of the routing-control data set. If retry is not requested or is not successful, Download for z/OS releases the data set back to JES and requests that it is held by the system.

Operator response

Inform your system programmer that this error occurred.

System programmer response

If a dotted decimal or colon hexadecimal address was provided, correct the IPADDR parameter in the routing-control data set. To use the modified routing control data set, stop the Download for z/OS FSS and restart the FSAs.

If a valid host name was provided, contact your TCP/IP administrator. Download for z/OS uses the same name resolver as the TSO LPR command.

User response

Inform your system programmer that this error occurred.

APS998I	THE LAST STATEMENT IN THE DOWNLOAD ROUTING CONTROL DATA SET WAS NOT PROPERLY TERMINATED.
----------------	---

Explanation

Download for z/OS detected that the last statement in the routing-control data set was not ended with a semicolon.

System action

Download for z/OS ignores the last statement and continues processing with the other valid statements.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Correct the incorrect statement by specifying a final semicolon. Ensure that all required keywords are specified. To use the modified routing-control data set, stop the Download FSS and restart the FSAs.

User response

No response is necessary.

APS999I	DOWNLOAD SENT A ZERO LENGTH DATA SET TO THE REMOTE SYSTEM. NULL DATA SETS ARE UNPRINTABLE.
----------------	---

Explanation

Download for z/OS sent a null data set to the remote system that cannot be printed. Additional information messages that precede this message, such as APS031I, might explain why the data set was not printed.

System action

The data set is marked as "unprintable" and returned to the Job Entry subsystem (JES) spool to be held for problem determination. Processing continues with the next data set.

Operator response

None.

System programmer response

This message indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance.

User response

Notify the system programmer about the possible logic error. Resubmit the print request.

APS1000 to APS2499

APS1001I	PRINTER INVENTORY NAME SPECIFIED FOR <i>fssname</i> IS NOT VALID.
-----------------	--

Explanation

The EXEC statement in the PSF startup procedure specifies PARM=(INV= *dbname*), which indicates that

the Infoprint Server Printer Inventory is to be used, but the name is not valid.

System action

The printer does not start.

Operator response

No response is necessary.

System programmer response

Correct the EXEC statement and restart PSF.

User response

No response is necessary.

APS1002I	THE CONNECTION TOKEN USED TO CONNECT TO THE PRINTER INVENTORY IS NOT VALID.
-----------------	--

Explanation

PSF or AFP Download Plus attempted to access the Infoprint Server Printer Inventory; however, the connection token that is used is not valid.

System action

Processing ends abnormally.

Operator response

No response is necessary.

System programmer response

Restart PSF or AFP Download Plus to correct the connection token.

User response

No response is necessary.

APS1003I	AN UNEXPECTED INFOPRINT SERVER INTERNAL ERROR OCCURRED WHILE PROCESSING A <i>object_type</i> OBJECT WITH A NAME OF <i>name</i>. INFOPRINT SERVER ERROR MESSAGE: <i>error_message</i>.
-----------------	--

Explanation

An error occurred in Infoprint Server while the Printer Inventory was processing an FSS or FSA object. An Infoprint Server error message that indicates the reason for the failure might be displayed in the message. For information about Infoprint Server messages, see [z/OS Infoprint Server Messages and Diagnosis](#).

System action

Processing ends abnormally.

Operator response

No response is necessary.

System programmer response

The error is an Infoprint Server logic error. See [z/OS Infoprint Server Messages and Diagnosis](#) for assistance in determining the source of the problem.

User response

No response is necessary.

APS1005I	AN UNEXPECTED INFOPRINT SERVER ERROR OCCURRED WHILE PROCESSING A <i>object_type</i> OBJECT WITH A NAME OF <i>name</i>. RETURN CODE (<i>return_code</i>) AND REASON CODE (<i>reason_code</i>).
-----------------	--

Explanation

An error occurred when the Infoprint Server Printer Inventory was processing an FSS or FSA object. These are the return code and reason code values:

Return Code 16

An API error occurred with one of these reason codes:

Reason Code 12

PSF or AFP Download Plus storage was unavailable.

Reason Code 16

The query token is not valid.

Reason Code 20

Data that PSF or AFP Download Plus supplied to the Printer Inventory was not valid.

Reason Code 24

The request type was not valid. The most likely cause is running different maintenance levels between PSF or AFP Download Plus and the Printer Inventory.

Reason Code 28

An abend occurred during extract.

Reason Code 32

Multiple asynchronous fetches were sent.

Reason Code 36

A service was requested that is not allowed.

Reason Code 40

The service call was interrupted.

Reason Code 44

A mismatched parameter list was coded.

Reason Code 48

PSF or AFP Download Plus is not authorized to do the specified action.

Reason Code 52

Infoprint Server storage is not available.

System action

Processing ends abnormally.

Operator response

No response is necessary.

System programmer response

Correct the error and then restart PSF or AFP Download Plus.

User response

No response is necessary.

APS1006I **THE *object_type* OBJECT WITH A NAME OF *name* WAS NOT OBTAINED FROM THE PRINTER INVENTORY BECAUSE THE BUFFER FOR ATTRIBUTE *attribute_number* WAS TOO SMALL.**

Explanation

PSF or AFP Download Plus attempted to access the Infoprint Server Printer Inventory. However, the buffer PSF or AFP Download Plus provided Infoprint Server is too small for the requested attribute.

System action

Processing ends abnormally.

Operator response

No response is necessary.

System programmer response

The error is a PSF or AFP Download Plus logic error. See *PSF for z/OS: Diagnosis* or *PSF for z/OS: AFP Download Plus* for assistance in determining the source of the problem.

User response

No response is necessary.

APS1007I **THE INFOPRINT SERVER CONNECTION HAS BEEN BROKEN.**

Explanation

While accessing the Printer Inventory, PSF or AFP Download Plus was disconnected from Infoprint Server.

System action

Processing ends abnormally.

Operator response

No response is necessary.

System programmer response

Restart Infoprint Server and then restart PSF or AFP Download Plus.

User response

No response is necessary.

APS1008I **THE *object_type* OBJECT WITH A NAME OF *name* WAS NOT FOUND IN THE PRINTER INVENTORY.**

Explanation

PSF or AFP Download Plus accessed the Infoprint Server Printer Inventory to obtain initialization parameters. However, the FSS or FSA object that PSF or AFP Download Plus was trying to obtain was not found in the Printer Inventory.

System action

Processing ends abnormally.

Operator response

No response is necessary.

System programmer response

Correct the FSS or FSA object definition and restart PSF or AFP Download Plus. For more information about FSS and FSA definitions in the Printer Inventory, see *z/OS Infoprint Server Operation and Administration*, *PSF for z/OS: Customization*, or *PSF for z/OS: AFP Download Plus*.

User response

No response is necessary.

APS1009I **SYSTEM ACTION TAKEN: THE ERRORS LISTED PREVENTED THE PRINTING OF THE DATA SET. THE DATA SET WILL BE TERMINATED.**

Explanation

This message indicates the recovery that PSF does when the printer reports an input/output (I/O) error to PSF. This message accompanies a message that

describes the I/O error and a message that displays the sense bytes reported from the printer.

System action

The printer you were using might try to print the page that contains the error, or might print only part of the page. If the page that contains the error contains any positioning errors, print-error markers might be included on the printed page. PSF stops processing and printing the data set that contains this error.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

To determine an appropriate response, see the specific error conditions described in the accompanying messages.

User response

To determine an appropriate response, see the specific error conditions described in the accompanying messages.

APS1010I	AFP DOWNLOAD PLUS DOES NOT HONOR THE <i>jescommand</i> JES COMMAND. THE COMMAND IS IGNORED.
-----------------	--

Explanation

AFP Download Plus does not support the JES FSI synch order that was entered. The only JES FSI synch orders that are supported are Cancel and Restart.

System action

AFP Download Plus ignores the command and continues processing.

Operator response

If you entered the wrong command, enter the correct one.

System programmer response

None.

User response

None.

APS1011A	DO YOU WANT TO <i>jescommand</i> SPOOL DATA SET <i>jobid</i>? ENTER CONT OR IGNORE.
-----------------	--

Explanation

You entered a supported JES FSI synch order. AFP Download Plus issues this message to confirm that you want to apply this command to the spool data set mentioned in the message. The only JES FSI synch orders that are supported are Cancel and Restart.

System action

AFP Download Plus waits for your response to the message. If you enter CONT or C, AFP Download Plus runs the JES command. If you enter IGNORE or I, AFP Download Plus ignores the command and continues processing.

Operator response

Reply to the message. Enter CONT or C to run the JES command. Enter IGNORE or I to ignore the JES command.

System programmer response

None.

User response

None.

APS1012A	YOU ENTERED AN INCORRECT VALUE. ENTER CONT OR IGNORE.
-----------------	--

Explanation

You entered an incorrect response to message APS1011A.

System action

AFP Download Plus waits for your response to the message. If you enter CONT or C, AFP Download Plus runs the JES command listed in message APS1011A. If you enter IGNORE or I, AFP Download Plus ignores the command that is listed in APS1011A and continues processing.

Operator response

Reply to the message. Enter CONT or C to run the JES command. Enter IGNORE or I to ignore the JES command.

System programmer response

None.

User response

None

APS1018I **AFP DOWNLOAD PLUS
ENCOUNTERED PROBLEMS
TRANSFORMING THE MO:DCA
MESSAGE DATA SET TO SEND TO
THE REMOTE SYSTEM. REFER TO
PREVIOUSLY ISSUED CONSOLE
MESSAGES FOR SPECIFIC
ERRORS.**

Explanation

AFP Download Plus encountered problems that prevented it from transforming the message data set to a MO:DCA-P file and sending it to the remote system. More messages were issued to the console for this problem.

System action

An empty message file was sent to the remote system instead of an AFP Download Plus created MO:DCA-P message file.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Fix any processing problems for the message data set as described in the previous messages issued to the console.

User response

No response is necessary.

APS1020I **INFOPRINT SERVER
CONFIGURATION INFORMATION
WAS NOT OBTAINED. MESSAGES
CANNOT BE LOGGED TO THE
INFOPRINT SERVER COMMON
MESSAGE LOG.**

Explanation

PSF or AFP Download Plus was unable to obtain Infoprint Server configuration information. Without this information, PSF or AFP Download Plus cannot activate the common message log function.

System action

PSF or AFP Download Plus continues processing without logging messages to the Infoprint Server common message log.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Previous messages contain details about this error. Use the information that is recorded in the previous messages to diagnose and fix the error condition.

User response

No response is necessary.

APS1021I **AN ERROR WAS RECEIVED AFTER
CALLING SYSTEM FUNCTION
IEANTRT TO OBTAIN PC NUMBER
FOR INFOPRINT SERVER.
RC='nnnnnnnn'.**

Explanation

PSF or AFP Download Plus was unable to obtain the program call (PC) number for Infoprint Server. Without this PC number, processing cannot continue. Return Code 4 indicates that either the Printer Inventory name in the EXEC statement does not match the Printer Inventory name that is specified in the Infoprint Server configuration file or Infoprint Server is not started.

System action

PSF or AFP Download Plus processing ends abnormally with a system completion code 027 and abend reason code 0005.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Use the return code from this message to diagnose the Infoprint Server installation problem and correct it. For more information, see *z/OS Infoprint Server Messages and Diagnosis*. For information about return codes from the IEANTRT system function, see *z/OS MVS Programming: Authorized Assembler Services Reference EDT-IXG*.

User response

No response is necessary.

APS1022I **THE CONNECTION TOKEN USED
TO CONNECT TO THE PRINTER
INVENTORY IS NOT VALID.**

Explanation

PSF or AFP Download Plus attempted to access the Infoprint Server Printer Inventory; however, the connection token used is not valid because Infoprint Server is not running. When Infoprint Server is restarted, PSF or AFP Download Plus sees a new connection token and reestablishes the connection to Infoprint Server.

System action

When the connection token is not valid, PSF or AFP Download Plus does not log any messages to the Infoprint Server common message log.

PSF or AFP Download Plus detects when Infoprint Server is running again. At the beginning of the next print job, PSF or AFP Download Plus turns on logging and issues message APS1032I to inform the user that logging is turned back on.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

No response is necessary.

APS1023I	AN UNEXPECTED INFOPRINT SERVER INTERNAL ERROR OCCURRED WHILE PROCESSING A <i>object_type</i> OBJECT WITH A NAME OF <i>name</i>. INFOPRINT SERVER ERROR MESSAGE: <i>error_message</i>.
-----------------	--

Explanation

An error occurred in Infoprint Server while the Printer Inventory was processing an FSA, configuration, print job, or document object. An Infoprint Server error message that indicates the reason for the failure might be displayed in the message. For information about Infoprint Server messages, see [z/OS Infoprint Server Messages and Diagnosis](#).

System action

PSF or AFP Download Plus does not log any messages to the Infoprint Server common message log.

Operator response

No response is necessary.

System programmer response

The error is an Infoprint Server logic error. See [z/OS Infoprint Server Messages and Diagnosis](#) for assistance in determining the source of the problem.

User response

No response is necessary.

APS1024I	AN UNEXPECTED INFOPRINT SERVER ERROR OCCURRED WHILE PROCESSING A <i>object_type</i> OBJECT WITH A NAME OF <i>name</i>. RETURN CODE (<i>return_code</i>) AND REASON CODE (<i>reason_code</i>).
-----------------	--

Explanation

An error occurred when the Infoprint Server Printer Inventory was processing an FSA, configuration, print job, or document object. These are the return code and reason code values:

Return Code 16

An API error occurred with one of these reason codes:

Reason Code 12

PSF or AFP Download Plus storage was unavailable.

Reason Code 16

The query token is not valid.

Reason Code 20

Data that PSF or AFP Download Plus supplied to the Printer Inventory was not valid.

Reason Code 24

The request type was not valid. The most likely cause is running different maintenance levels between PSF or AFP Download Plus and the Printer Inventory.

Reason Code 28

An abend occurred during extract.

Reason Code 32

Multiple asynchronous fetches were sent.

Reason Code 36

A service was requested that is not allowed.

Reason Code 40

The service call was interrupted.

Reason Code 44

A mismatched parameter list was coded.

Reason Code 48

PSF or AFP Download Plus is not authorized to do the specified action.

Reason Code 52

Infoprint Server storage is not available.

System action

PSF or AFP Download Plus does not log any messages to the Infoprint Server common message log.

Operator response

No response is necessary.

System programmer response

Correct the error.

User response

No response is necessary.

APS1025I **THE *object_type* OBJECT WITH A NAME OF *name* WAS NOT OBTAINED FROM THE PRINTER INVENTORY BECAUSE THE BUFFER FOR ATTRIBUTE *attribute_number* WAS TOO SMALL.**

Explanation

PSF or AFP Download Plus attempted to access the Infoprint Server Printer Inventory. However, the buffer PSF or AFP Download Plus provided Infoprint Server is too small for the requested attribute.

System action

PSF or AFP Download Plus does not log any messages to the Infoprint Server common message log.

Operator response

No response is necessary.

System programmer response

The error is a PSF or AFP Download Plus logic error. See *PSF for z/OS: Diagnosis* or *PSF for z/OS: AFP Download Plus* for assistance in determining the source of the problem.

User response

No response is necessary.

APS1026I **THE INFOPRINT SERVER CONNECTION HAS BEEN BROKEN.**

Explanation

While accessing the Printer Inventory, PSF or AFP Download Plus was disconnected from Infoprint Server. PSF or AFP Download Plus detects when

Infoprint Server is running again and reestablishes the connection.

System action

When Infoprint Server is not running, PSF or AFP Download Plus does not log any messages to the Infoprint Server common message log.

When it reconnects with Infoprint Server, PSF or AFP Download Plus turns on logging and issues message APS1032I to inform the user that logging is turned back on.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

No response is necessary.

APS1027I **THE *object_type* OBJECT WITH A NAME OF *name* WAS NOT FOUND IN THE PRINTER INVENTORY.**

Explanation

PSF or AFP Download Plus accessed the Infoprint Server Printer Inventory to obtain PSF initialization parameters. However, the configuration object that PSF or AFP Download Plus was trying to obtain was not found in the Printer Inventory.

System action

PSF or AFP Download Plus does not log any messages to the Infoprint Server common message log.

Operator response

No response is necessary.

System programmer response

The error is an Infoprint Server logic error. See *z/OS Infoprint Server Messages and Diagnosis* for assistance in determining the source of the problem.

User response

No response is necessary.

APS1028I **MESSAGES ARE NOT BEING LOGGED TO THE INFOPRINT SERVER COMMON MESSAGE LOG.**

Explanation

PSF or AFP Download Plus cannot log messages to the Infoprint Server common message log because the error in the previous message turned off the log messages function.

System action

PSF or AFP Download Plus does not log any messages to the Infoprint Server common message log.

Operator response

No response is necessary.

System programmer response

To correct the error, see the previous message.

User response

No response is necessary.

APS1029I THE PRINT JOB WAS COMPLETED SUCCESSFULLY.

Explanation

Processing of the print request completed successfully.

System action

PSF processes the next print request.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

No response is necessary.

APS1030I THE PRINT JOB WAS SENT SUCCESSFULLY.

Explanation

The print request was successfully processed and sent.

System action

AFP Download Plus processes the next print request.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

No response is necessary.

APS1031I JES DID NOT PROVIDE THE INFORMATION NEEDED TO LOG MESSAGES TO THE INFOPRINT SERVER COMMON MESSAGE LOG.

Explanation

PSF or AFP Download Plus cannot log messages to the Infoprint Server common message log because Job Entry Subsystem (JES) did not provide the required information.

System action

PSF or AFP Download Plus does not log any messages to the Infoprint Server common message log.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Install JES2 or JES3 at the supported z/OS level to log messages to the common message log.

User response

No response is necessary.

APS1032I MESSAGES ARE NOW BEING LOGGED TO THE INFOPRINT SERVER COMMON MESSAGE LOG.

Explanation

The log messages function is turned on, so PSF or AFP Download Plus can now log messages to the Infoprint Server common message log.

System action

PSF or AFP Download Plus logs any messages to the Infoprint Server common message log.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

No response is necessary.

APS1033I THE PRINTER INVENTORY QUERY WAS NOT FETCHED BECAUSE THE BUFFER FOR THE QUERY WAS TOO SMALL.

Explanation

PSF or AFP Download Plus attempted to query the Infoprint Server Printer Inventory. However, the buffer PSF or AFP Download Plus provided Infoprint Server is too small for the requested query.

System action

Processing ends abnormally.

Operator response

No response is necessary.

System programmer response

The error is a PSF or AFP Download Plus logic error. See *PSF for z/OS: Diagnosis* or *PSF for z/OS: AFP Download Plus* for assistance in determining the source of the problem.

User response

No response is necessary.

APS1034I AN UNEXPECTED INFOPRINT SERVER INTERNAL ERROR OCCURRED WHILE PROCESSING A PRINTER INVENTORY QUERY.

Explanation

An error occurred in Infoprint Server while the Printer Inventory was processing a query.

System action

Processing ends abnormally.

Operator response

No response is necessary.

System programmer response

The error is an Infoprint Server logic error. See *z/OS Infoprint Server Messages and Diagnosis* for assistance in determining the source of the problem.

User response

No response is necessary.

APS1035I AN UNEXPECTED INFOPRINT SERVER ERROR OCCURRED WHILE PROCESSING A PRINTER INVENTORY QUERY.

Explanation

An error occurred when the Infoprint Server Printer Inventory was processing a query.

System action

Processing ends abnormally.

Operator response

No response is necessary.

System programmer response

Correct the error.

User response

No response is necessary.

APS1036I NOT ENOUGH STORAGE IS AVAILABLE TO INITIALIZE THE PSF PRINTER INVENTORY NOTIFICATION TASK - STORAGE REQUESTED = *storage requested* RETURN CODE = *return code*.

Explanation

More storage was required to initialize the notification task, but this storage was not available. The return code is from the GETMAIN macro.

System action

The command is ignored and processing continues with the next command entered.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Increase the REGION parameter on the startup procedure.

User response

No response is necessary.

APS1037I **macro UNSUCCESSFUL FOR
MODULE *task module name*,
RETURN CODE *return code* -
MODULE(*module making call*).**

Explanation

The specified macroinstruction, such as ATTACH, was not successfully run for the task module name, such as APSPINST. The return code is the code that is returned by the module that made the call.

System action

The dynamic allocation function was not run.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Correct the problem in response to the return code identified in this message.

User response

No response is necessary.

APS1500I **A *bin_type* BIN NUMBER HAS NOT
BEEN SPECIFIED FOR INPUT BIN
NUMBER *bin_number* IN
INSTALLATION EXIT 7.**

Explanation

An installation Exit 7 requested side and edge sensitive paper handling for the input bin, but did not specify a *bin_type* bin number. *bin_type* can be simplex or duplex.

System action

PSF ignores the request for bin substitution for bin number *bin_number*, but does all other bin substitutions requested in this installation Exit 7.

Operator response

Inform your system programmer.

System programmer response

Correct the installation Exit 7 to specify both a simplex and a duplex bin for each input bin that requires substitution.

User response

If the printed output is not acceptable, contact your system programmer.

APS1501I **THE SIDE AND EDGE SENSITIVE
PAPER HANDLING FUNCTION HAS
BEEN DEACTIVATED BECAUSE NO
BINS WERE SPECIFIED FOR
SUBSTITUTION.**

Explanation

An installation Exit 7 requested side and edge sensitive paper handling, but did not specify a bin number that requires substitution.

System action

PSF ignores the request for side and edge sensitive paper handling and does not do bin substitution. PSF then generates this informational message and continues processing.

Operator response

Inform your system programmer.

System programmer response

Correct the installation Exit 7. Either turn off the XTP7SENS flag, which indicates that bins are to be substituted for side and edge sensitivity processing, or correctly specify bins that require substitution.

User response

If the printed output is not acceptable, contact your system programmer.

APS1700I **UNABLE TO LOAD USER MAPPING
TABLE APSRNTGM.**

Explanation

User mapping table APSRNTGM cannot be loaded by use of link list search order.

System action

The font library utility continues processing without a user mapping table.

Operator response

No response is necessary.

System programmer response

If no user mapping table is defined for your system, this message can be ignored. If a user mapping table is defined for your system, determine why the table is not in link list search order. The user mapping table must be installed in the same data set as PSF and the font library utility.

User response

Notify your system programmer.

**APS1701I NO DATA SETS TO PROCESS—
PROCESSING ENDED.**

Explanation

The JCL to run the font library utility does not contain any DD statements that start with *FONT*.

System action

The font library utility stops processing. No code pages or character sets are updated.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Identify all font libraries with DD names that start with *FONT*.

**APS1702I PROCESSING COMPLETED FOR
RESOURCE *resource name*.**

Explanation

The code page or character set specified in the message was updated by the font library utility with new valid GRID data.

System action

The font library utility continues processing.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

No response is necessary.

**APS1703I OLD GRID HEX VALUES: {FGID=
nnnn GCSGID= *nnnn* FONT
WIDTH= *nnnn* | CPGID= *nnnn*
GCSGID= *nnnn*}.**

Explanation

The code page or character set specified in the message contained the specified GRID data before processing by the font library utility.

System action

The font library utility continues processing.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

No response is necessary.

**APS1704I NEW GRID HEX VALUES: {FGID=
nnnn GCSGID= *nnnn* FONT
WIDTH= *nnnn* | CPGID= *nnnn*
GCSGID= *nnnn*}.**

Explanation

The code page or character set specified in the message was updated by the font library utility, and contains the specified GRID data.

System action

The font library utility continues processing.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

No response is necessary.

APS1705I PROCESSING COMPLETED FOR ALL DATA SETS.**Explanation**

The font library utility completed processing all the data sets specified in the JCL.

System action

The font library utility is complete with all processing.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

No response is necessary.

APS1706I NO AVAILABLE USER RANGE GRID VALUES FOR CODE PAGES.**Explanation**

All user range CPGIDs are already assigned to existing code pages. Insufficient user range CPGIDs are available to satisfy all the fonts on your system.

System action

The font library utility stops processing. Some code pages are not updated correctly.

Operator response

No response is necessary.

System programmer response

Notify your IBM Support Center.

User response

Inform your system programmer that this error occurred.

APS1707I USER MAPPING TABLE APSRNTGM IS LOADED AND MAY BE USED BY APSRFLU TO UPDATE FONT GRID DATA.**Explanation**

User mapping table APSRNTGM was loaded by using the link list search order.

System action

The font library utility continues processing by using the user mapping table.

Operator response

No response is necessary.

System programmer response

If a user mapping table is defined for your system, this message can be ignored. If a user mapping table is not intended to be used on your system, determine why the table is in link list search order.

User response

Notify your system programmer.

APS1708I A SPECIFIED FONT LIBRARY HAS INCORRECT DATA SET ATTRIBUTES. NO PROCESSING HAS BEEN PERFORMED.**Explanation**

The font library utility JCL contains a DD statement, starting with FONT, that has attributes not valid for a font data set. The data set either is not variable blocked, contains spanned records, does not contain carriage control, or is not a partitioned data set.

System action

The font library utility stops processing. No code pages or character sets are updated.

Operator response

No response is necessary.

System programmer response

Verify that all font data sets have the required font data set attributes. Change all data sets that do not have the correct attributes or do not use those data sets with PSF.

User response

Update your JCL to specify only DD names that start with FONT and that are font data sets, and resubmit your job. If all DD names that start with FONT are font data sets, notify your system programmer.

APS1709I THE USER MODIFIABLE NAME TO GRID TABLE IS UNUSABLE BECAUSE IT IS AMODE 31. NO PROCESSING HAS BEEN PERFORMED.

Explanation

The user-modifiable mapping table APSRNTGM is installed as AMODE 31, but the font library utility requires the table to be AMODE 24.

System action

The font library utility stops processing. No code pages or character sets are updated.

Operator response

No response is necessary.

System programmer response

Relink-edit the user-modifiable mapping table APSRNTGM in the PSF linklib as AMODE=24.

User response

Notify your system programmer.

APS1710I **PROCESSING ABORTED FOR
RESOURCE *membername* IN DD
ddname. CPD OR FND
STRUCTURED FIELD IS MISSING.**

Explanation

If the specified resource is a code page, the CPD structured field is not included in the code page data. If the specified resource is a character set, the FND structured field is not included in the character set. These structured fields are required for processing by the font library utility.

System action

The font library utility stops processing. Some code pages and character sets are not updated correctly.

Operator response

No response is necessary.

System programmer response

If you created the structured fields for the font, correct the error and resubmit the job. For more information about the structured field, see *Font Object Content Architecture Reference*. If an IBM licensed program was used to create the structured fields for the font that contains the error, verify that the input to the program was valid.

User response

Inform your system programmer that this error occurred.

APS1711I **NO AVAILABLE USER RANGE GRID
VALUES FOR CHARACTER SETS.**

Explanation

All user range FGIDs are already assigned to existing character sets. Insufficient user range FGIDs are available to satisfy all the fonts on your system.

System action

The font library utility stops processing. Some character sets are not updated correctly.

Operator response

No response is necessary.

System programmer response

Notify your IBM Support Center.

User response

Inform your system programmer that this error occurred.

APS2000I **THE REGISTERED OBJECT TYPE
ID ('*registration id*') OF AN OBJECT
CONTAINER RESOURCE, NAME
resource name OR OBJECT OID *oid*
IS NOT VALID OR IS NOT
SUPPORTED BY PSF OR THE
PRINTER.**

Explanation

The registration ID specified for an object container is not supported by the printer. The registration ID is specified in the object classification triplet on one of these structured fields:

- Include Object (IOB)
- Begin Object Container (BOC)
- Begin Resource (BRS, also called BR)
- Map Data Resource (MDR)

A value of *** for the name or object OID means that it was not specified.

System action

PSF stops processing the page or overlay. PSF tries to locate the end of the current page and resume processing on the next page. If the end of current page cannot be located, PSF stops printing the data set. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the object container resource, ensure that the registration ID is correct. If the registration ID is correct, submit the print job to a printer that supports this object type. For more information about what object types are supported by your printer, see your printer documentation.

APS2001I **COLOR FIDELITY WAS REQUESTED BUT COLOR FIDELITY IS NOT SUPPORTED BY THIS PRINTER. PROCESSING OF THE DATA SET IS TERMINATED.**

Explanation

User requested color fidelity with a continuation exception rule of stop. However, the printer does not support color fidelity.

System action

PSF ends processing on this data set and returns the data set to JES to have it held.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Submit the print job to a printer that supports color fidelity. Contact your operator to determine which printers support color fidelity.

APS2002I **COLOR FIDELITY WAS REQUESTED BUT COLOR FIDELITY IS NOT SUPPORTED BY THIS PRINTER. PROCESSING OF THE DATA SET CONTINUES.**

Explanation

User requested color fidelity with a continuation exception rule of continue. However, the printer does not support color fidelity and thus does not control the reporting of unsupported or incorrect color value.

System action

PSF processes this data set without color fidelity.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

No response is necessary.

APS2003I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: STRUCTURED FIELD *structured field* CONTAINED AN EXTENDED RESOURCE LOCAL IDENTIFIER VALUE THAT WAS USED IN A PREVIOUS STRUCTURED FIELD OF THE SAME TYPE.**

Explanation

More than one structured field used the same Extended Resource Local Identifier value for different resources of the same type. The Extended Resource Local Identifier is specified by using the Extended Resource Local Identifier (X'22') triplet on the structured field. The structured field that attempted to use the same Extended Resource Local Identifier value is identified in the message.

System action

PSF stops processing the current data set and issues messages that identify the position of the structured field and the processing environment when the error was found.

Operator response:

System programmer response:

User response:

APS2004I **DATA IN A FORMDEF RESOURCE IS NOT VALID: MEDIA TYPE LOCAL IDENTIFIER IN MMC STRUCTURED FIELD, ID *identifier*, WAS NOT FOUND IN THE MMT STRUCTURED FIELD.**

Explanation

The Media Type local ID in the Medium Modification Control (MMC) structured field was not present in the Map Media Type (MMT) structured field. The MMC and MMT structured fields are in the form definition.

System action

The form definition that contains the error is not used, and one of these occurs:

- If the error is in the default form definition or in a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

Operator response:

System programmer response:

User response:

APS2005I **DATA IN AN INPUT RECORD OR PAGEDEF RESOURCE IS NOT VALID: RECORD IDENTIFIER *record identifier* COULD NOT BE FOUND WITHIN THE RCD STRUCTURED FIELDS.**

Explanation

The record identifier that is specified in an input record cannot be matched to a Record Descriptor (RCD) structured field in the current data map. The RCD structured field is in the page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot be initialized or cannot print error messages. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

If the error involves separator pages, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS2006I **DATA IN A PAGEDEF RESOURCE IS NOT VALID: GRAPHICS GENERATION WAS SPECIFIED ON RCD STRUCTURED FIELD NUMBER *structured field number*, BUT THE PRINTER DOES NOT SUPPORT GRAPHICS OBJECTS. THIS MESSAGE IS ONLY ISSUED ONCE PER PRINT DATA SET.**

Explanation

A Record Descriptor (RCD) structured field in a page definition requested PSF to generate a graphics object from the line data, but the printer does not support graphics objects.

System action

PSF ignores the request and continues processing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If the page definition is for a separator page, the message data set, or the default page definition for the

user print data sets defined in the PSF startup procedure, delete the option from the page definition that requests that a graphics object is generated.

User response

To print the data set and have PSF generate graphics objects, submit the print job to a printer that supports graphics objects. For more information about a printer's support for graphics objects, see the documentation provided with the printer.

APS2007I **DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE FIELD RCD POINTER VALUE IN RCD STRUCTURED FIELD NUMBER *structured field number* WILL CAUSE AN INFINITE LOOP.**

Explanation

The Field Record Descriptor Pointer value in the Record Descriptor (RCD) structured field that is identified in this message caused an infinite loop condition. The RCD structured field is contained in the page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response:

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APS2008I **DATA IN A PAGEDEF RESOURCE IS NOT VALID: RCD OR XMD STRUCTURED FIELD NUMBER *structured field number* SPECIFIES A VALUE THAT IS NOT VALID AS A**

POINTER TO A FIELD RCD OR XMD. THE VALUE *parameter value1* EXCEEDS THE LNC STRUCTURED FIELD COUNT VALUE OF *parameter value2*.

Explanation

The Field Record Descriptor Pointer in the Record Descriptor (RCD) or XML Descriptor (XMD) structured field that is identified in this message has a value that is not valid. The value is greater than the Count value in the Line Descriptor Count (LNC) structured field in the current data map. The LNC, RCD, and XMD structured fields are in the page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response:

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS2009I **DATA IN A PAGEDEF RESOURCE IS NOT VALID: RIGHT ALIGNMENT WAS REQUESTED ON RCD STRUCTURED FIELD NUMBER *structured field number*, BUT THE PRINTER DOES NOT SUPPORT RIGHT ALIGNMENT.**

Explanation

A Record Descriptor (RCD) structured field in a page definition requested that PSF right align a field from the line data, but the printer does not support the controls necessary for PSF to do this function.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response:

System programmer response

If the page definition is for a separator page, the message data set, or the default page definition for the user print data set, or the default page definition for the user print data sets defined in the PSF startup procedure, delete the option from the page definition that requests that a field is right-aligned.

User response

To print the data set and have PSF right align fields, submit the print job to a printer that supports all four inline print directions and all four character rotations. For more information about inline print directions and character rotations that are supported by a printer, see the documentation provided with the printer.

APS2010I RECORD FORMATTING WAS REQUESTED BY THE PAGE DEFINITION BUT THAT FUNCTION IS NOT SUPPORTED BY THIS RELEASE OF PSF.

Explanation

The record formatting function is not supported by this release of PSF.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response:

System programmer response

If the page definition is for a separator page, the message data set, or the default page definition for the user print data set, or the default page definition for the user print data sets defined in the PSF startup procedure, remove this page definition and select one that does not use the record formatting function.

User response

To use the record formatting function, submit this job to a version of PSF that supports record formatting.

APS2011I DATA IN A PAGEDEF RESOURCE IS NOT VALID: DATA MAP *data map name1* AND DATA MAP *data map name2* ARE FOR PROCESSING DIFFERENT TYPES OF DATA. ALL DATA MAPS IN THE PAGE DEFINITION MUST SPECIFY THE SAME DATA FORMATTING.

Explanation

A page definition can be used only for one type of line data. A single page definition cannot be used to mix the processing of traditional, record-format, and XML line data.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response:

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS2012I DATA IN A PAGEDEF RESOURCE IS NOT VALID: A NON-ZERO RECORD IDENTIFIER VALUE *record identifier* WAS SPECIFIED IN RCD STRUCTURED FIELD NUMBER *structured field number*.

Explanation

For Record Descriptor (RCD) structured fields that are marked as either a field or a conditional processing

RCD, the record identifier value must be all zeros. The RCD structured fields are in the page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response:

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS2013I	DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE SAME RECORD IDENTIFIER VALUE <i>record identifier</i> WAS SPECIFIED IN RCD STRUCTURED FIELD NUMBERS <i>structured field number1</i> AND <i>structured field number2</i>. ALL RECORD IDENTIFIERS MUST BE UNIQUE IN THE SAME DATA MAP.
-----------------	--

Explanation

All Record Descriptor (RCD) structured fields in a data map must specify a unique record identifier; except for these RCD structured fields:

- Default Page Header
- Default Page Trailer
- Field
- Conditional Processing

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response:

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS2014I	DATA IN AN INPUT RECORD OR PAGEDEF RESOURCE IS NOT VALID: THE PAGE SIZE IS NOT LARGE ENOUGH TO PLACE THE FIRST RECORD OF THE PAGE BY USING RCD OR XMD STRUCTURED FIELD NUMBER <i>structured field number</i> AND ITS ASSOCIATED FIELD RCD OR XMD STRUCTURED FIELDS.
-----------------	--

Explanation

The Body Record Descriptor (RCD) or XML Descriptor (XMD) structured field that is selected for placing the first body record of the page does not fit within the area of the page defined by the bottom margin. If Field RCD or XMD structured fields are being used, one of the Field RCD or XMD structured fields might be positioning data beyond the bottom margin. This error prevents PSF from being able to place the record and continuing.

System action

PSF stops processing the current data set and issues more messages that identify the processing

environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response:

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS2015I DATA IN A PAGEDEF RESOURCE IS NOT VALID: AN RCD STRUCTURED FIELD SPECIFIED A GRAPHICS DESCRIPTOR TRIPLET TO END ALL STARTED GRAPHICS DESCRIPTOR TRIPLETS THAT HAVE A MATCHING GRAPH ID VALUE OF *graphics identifier*, BUT A MATCH COULD NOT BE FOUND.

Explanation

A graphics object can be started by one Record Descriptor (RCD) structured field and ended with another RCD structured field. When this is done, the Graphics Descriptor triplets that start and end a graphics object must have matching Graph ID parameter values specified and the RCD structured fields must have matching orientations. PSF cannot find a match between the start and end Graphics Descriptor triplets by using the Graphid parameter from the end Graphics Descriptor triplet and the Text Orientation parameter value from the RCD structured field.

System action

PSF stops processing the current data set and issues more messages that identify the processing

environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response:

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS2016I DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE USE RECORD IDENTIFIER FLAG WAS SET BUT THE SUM OF THE DATA START POSITION AND THE DATA LENGTH VALUES IN RCD STRUCTURED FIELD NUMBER *structured field number* SELECTS DATA BEYOND THE RECORD IDENTIFIER FIELD.

Explanation

For Record Descriptor (RCD) structured fields that are marked to use only the record identifier portion of an input record, only the record identifier can be accessed by the RCD. The Data Start value plus the Data Length value of this RCD accesses data beyond the 10-byte record identifier area of the input record.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response:

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS2017I **DATA IN A PAGEDEF RESOURCE IS NOT VALID: A FONT IS NEEDED FOR THE *structured field name* STRUCTURED FIELD IN DATA MAP *data map name* BUT NO FONTS WERE MAPPED IN THE DATA MAP.**

Explanation

Fonts that are needed for printing record format line data or XML data must be selected in the data map. The CHARS JCL parameter cannot be used to select fonts. The data map identified in this message contained a Record Descriptor (RCD) or an XML Descriptor (XMD) structured field that requires a font, but no fonts were specified in the data map.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response:

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS2018I **DATA IN A PAGEDEF RESOURCE IS NOT VALID: RCD STRUCTURED FIELD NUMBER *structured field number* REQUESTED THAT THE PAGE NUMBER BE RESET, BUT THE PAGE NUMBER PARAMETER CONTAINS ZERO.**

Explanation

The page number parameter in a Record Descriptor (RCD) structured field cannot be zero when the RCD requests that PSF reset the page number.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response:

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS2019I **DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE FONT SELECTED FOR PRINTING THE PAGE NUMBER ON RCD OR XMD STRUCTURED FIELD NUMBER *structured field number* CANNOT BE A DOUBLE-BYTE FONT WHEN USING THE ASCII ENCODING SCHEME.**

Explanation

PSF cannot determine the correct code points to generate when a double-byte font is used to print the page number in the ASCII encoding scheme. The structured field that is identified in this message selected a double-byte ASCII font for printing the page number. This is not allowed.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. See *Mixed Object Document Content Architecture Reference*.

Operator response:

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS2020I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE OBJECT OID SPECIFIED IN A FULLY QUALIFIED NAME TRIPLET ON AN *structured field* STRUCTURED FIELD IS INCORRECT.**

Explanation

An object OID specified in a Fully Qualified Name triplet must not contain all zeros and must be less than 130 bytes.

System action

PSF stops processing the current page, then tries to find the end of the current page and to resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set. If this error occurs in a resource, PSF stops processing the data set. If this error occurs in a Resource Environment Group (REG), PSF stops processing the REG and continues processing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the print data set or resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the correct format of the referenced structured field. If the structured field is correct, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or resource, contact your system programmer.

APS2021I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE *structured field* STRUCTURED FIELD CONTAINS UNPAIRED FQN X'BE' AND X'DE' TRIPLETS.**

Explanation

If the structured field is an Include Object (IOB) or Preprocess Presentation Object (PPO), the Fully

Qualified Name (FQN) triplet with an FQNType of Data Object Internal Resource Reference (X'BE') must immediately follow an FQN triplet with an FQNType of Data Object External Resource Reference (X'DE').

If the structured field is a Map Data Resource (MDR), a repeating group with an FQN triplet type X'BE' must also include an FQN triplet type X'DE'.

System action

PSF cannot print the current page. PSF tries to find the end of the current page and resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

If this error occurs in a Resource Environment Group (REG), PSF stops processing the REG and continues processing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or resource with the error, verify that the input to that program was valid. If the input was valid, see [PSF for z/OS: Diagnosis](#) for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or resource, contact your system programmer.

NAMED IN THE ENVIRONMENT GROUP.

Explanation

If the structured field in error is an Include Object (IOB), the secondary resource must be named in a Map Data Resource (MDR) structured field in the Active Environment Group (AEG) of the page, overlay, or page definition that contains the IOB structured field.

If the structured field in error is a Preprocess Presentation Object (PPO), the secondary resource must be named in an MDR structured field in the Resource Environment Group (REG) of the data set or page definition that contains the PPO structured field.

If the structured field in error is a Line Descriptor (LND), Record Descriptor (RCD), or XML Descriptor (XMD), the secondary resource must be named in an MDR structured field in the AEG of the data map.

System action

If the object is in a page, PSF stops processing the page and continues processing the data set. If the object is in a resource, PSF stops processing and printing the data set.

If this error occurred in a REG, PSF stops processing the REG and continues processing the data set.

If this error occurred in a page definition, PSF stops processing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error. If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see [PSF for z/OS: Diagnosis](#) for assistance in determining the source of the problem.

User response

If you created the structured fields, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide*

APS2022I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A SECONDARY RESOURCE IDENTIFIED ON STRUCTURED FIELD *structured field* IS NOT

and *Line Data Reference* for more information about the structured field. If the structured field does not have an error, the error might be a PSF logic error. If you used a program to create the structured fields, contact your system programmer.

APS2023I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE FORMAT SPECIFIED IN AN FQN TRIPLET IS NOT VALID. THE STRUCTURED FIELD *structured field* IS IN ERROR**

Explanation

FQNfmt specified in a Fully Qualified Name (FQN) triplet on the structured field that is specified in the message is not valid.

System action

PSF stops processing the current page, attempts to find the end of the current page, and then tries to resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

If this error occurs in a resource or page definition, PSF stops processing the data set.

If this error occurs in a Resource Environment Group (REG), PSF stops processing the REG and continues processing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide*

and *Line Data Reference* for more information about the structured field. If the structured field does not have an error, the error might be a PSF logic error. If you used a program to create the structured fields, contact your system programmer.

APS2024I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN FQN TRIPLET MAPPED AN OBJECT THAT IS NOT ALLOWED IN AN MDR STRUCTURED FIELD IN AN OBJECT ENVIRONMENT GROUP.**

Explanation

A Fully Qualified Name (FQN) triplet with an FQNType of Begin Resource Object Reference (X'84') or Other Object Data Reference (X'CE') is not allowed on a Map Data Resource (MDR) structured field in an Object Environment Group (OEG). In addition, an FQN triplet with an FQNType of Data Object External Resource Reference (X'DE') can map only a data object font or a color management resource (CMR) in a graphics object, a bar code object, or a presentation text object with an Object Environment Group (OEG).

System action

PSF stops processing the current page, then tries to find the end of the current page and to resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set. If this error occurs in a resource, PSF stops processing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the print data set or resource, correct the error and resubmit the

print request. See *Mixed Object Document Content Architecture Reference* for more information about the correct format of the referenced structured field. If the structured field is correct, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or resource, contact your system programmer.

APS2025I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN ERROR WAS FOUND IN A FULLY QUALIFIED NAME TRIPLET SPECIFIED IN A REPEATING GROUP ON AN *structured field* STRUCTURED FIELD.**

Explanation

One of these errors was found:

- More than one Fully Qualified Name triplet with one of these FQNTypes was found in a repeating group on an MDR structured field:
 - Begin Resource Object Reference (X'84')
 - Other Object Data Reference (X'CE')
 - Data Object External Resource Reference (X'DE')
 - Code Page Name Reference (X'85')

More than one Fully Qualified Name triplet with one of these FQNTypes was found in a repeating group on a PPO structured field:

- Begin Resource Object Reference (X'84')
- Other Object Data Reference (X'CE')
- An FQNTYPE that is not valid was specified on a Fully Qualified Name triplet on a Map Data Resource (MDR) structured field.

System action

PSF stops processing the current page, then tries to find the end of the current page and to resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set. If this error occurs in a resource, PSF stops processing the data set. If this error occurs in a Resource Environment Group (REG), PSF stops processing the REG and continues processing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the print data set or resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the correct format of the referenced structured field. If the structured field is correct, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or resource, contact your system programmer.

APS2026I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE OBJECT CLASS SPECIFIED IN AN OBJECT CLASSIFICATION TRIPLET ON AN MDR STRUCTURED FIELD IS NOT VALID.**

Explanation

If the Fully Qualified Name triplet type in the repeating group is a Data Object External Resource Reference (X'DE'), the ObjClass specified in an Object Classification triplet on a Map Data Resource (MDR) structured field must be X'40' or X'41'. If the Fully Qualified Name triplet type in the repeating group is an Other Object Data Reference (X'CE'), the ObjClass specified must be X'01'.

System action

PSF stops processing the current page, then tries to find the end of the current page and to resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set. If this error occurs in a resource, PSF stops processing the data set. If this error occurs in a Resource Environment Group (REG), PSF stops processing the REG and continues processing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set,

or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the print data set or resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the correct format of the referenced structured field. If the structured field is correct, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or resource, contact your system programmer.

APS2027I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN MDR STRUCTURED FIELD SPECIFIES THE SAME RESOURCE REFERENCE MORE THAN ONCE IN AN ENVIRONMENT GROUP.
-----------------	--

Explanation

The same resource reference cannot be made multiple times in a Map Data Resource (MDR) structured field in an environment group.

System action

PSF stops processing the current page, then tries to find the end of the current page and to resume printing on the next page. If unable to find the end of the page, PSF stops printing the data set. If this error occurs in a resource, PSF stops processing the data set. If this error occurs in a Resource Environment Group (REG), PSF stops processing the REG and continues processing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in

the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the print data set or resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the correct format of the referenced structured field. If the structured field is correct, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or resource, contact your system programmer.

APS2028I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE RESOURCE BEGINNING WITH THE <i>structured field</i> STRUCTURED FIELD CANNOT BE SENT TO THE PRINTER AS A HARD RESOURCE. THIS MESSAGE IS ONLY ISSUED ONCE PER PRINT DATA SET FOR A GIVEN RESOURCE TYPE.
-----------------	--

Explanation

Either the printer or your PSF does not support sending this resource to the printer before the page and treating it as a hard resource managed by PSF. A hard resource is sent to the printer once.

System action

PSF ignores this resource in the MDR and continues processing. The resource is treated as a soft resource by PSF each time it is included in a page or resource. A soft resource is sent to the printer each time it is included.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in

the PSF startup procedure. Inform your system programmer.

System programmer response

This message indicates that the print data set was created with a certain level of resource management function expected. Either PSF or the printer does not have this level of resource management. Confirm the resource management capability of PSF and the printer to decide which one is deficient of the management function for this resource. If it is PSF, determine whether an APAR or new release is available that provides the function and install it. If it is the printer, determine whether the job can be sent to a different printer that has the function or if an engineering change (EC) is available to upgrade the microcode on this printer.

User response

If the performance of the job is acceptable, do nothing. If the performance of the job is not acceptable, inform your system programmer.

APS2030I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A SECONDARY RESOURCE THAT IS NOT A CMR IS SPECIFIED ON AN IOB STRUCTURED FIELD THAT INCLUDES ONE OF THESE OBJECTS: BAR CODE, GRAPHICS, OR PRESENTATION TEXT WITH AN OEG.
-----------------	---

Explanation

A Fully Qualified Name (FQN) triplet of type Data Object External Resource Reference (X'DE') is specified in an Include Object (IOB) structured field that has one of these objects: bar code, graphics, or presentation text with an OEG. Only color management resources (CMRs) are allowed as secondary resources for these objects.

System action

The secondary resource reference that is not a CMR is ignored and processing continues.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the print data set or resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the correct format of the referenced structured field. If the structured field is correct, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or resource, contact your system programmer.

APS2032I	DATA IN PAGEDEF RESOURCE <i>pagedef name</i> IS NOT VALID: THE RESOURCE BEGINNING WITH THE <i>structured field</i> STRUCTURED FIELD CANNOT BE SENT TO THE PRINTER AS A HARD RESOURCE. THIS MESSAGE IS ONLY ISSUED ONCE PER PRINT DATA SET FOR A GIVEN RESOURCE TYPE.
-----------------	---

Explanation

Either the printer or your PSF does not support sending this resource to the printer before the page and treating it as a hard resource managed by PSF. A hard resource is sent to the printer once.

System action

PSF ignores this resource in the MDR and continues processing. The resource is treated as a soft resource by PSF each time it is included in a page or resource. A soft resource is sent to the printer each time it is included.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

None.

User response

None.

APS2035I TONER SAVER CONTROL WAS REQUESTED BUT TONER SAVER CONTROL IS NOT SUPPORTED BY THIS PRINTER. PROCESSING OF THE DATA SET CONTINUES.

Explanation

Toner saver control was requested but the printer does not support Toner saver control.

System action

The data set is processed without toner saver control.

Operator response

None.

System programmer response

None.

User response

If you want toner fidelity, send the data to a printer that supports Toner saver control.

APS2038I THE BAR CODE DATA OR THE BAR CODE DATA PLUS THE ADDITIONAL 2D BAR CODE PARAMETERS EXCEEDED THE OUTPUT COMMAND BUFFER.

Explanation

Either the bar code data itself or the bar code data plus the macro control block data that is specified for a 2D bar code exceeds the size of the output command buffer. The macro control block data is specified in your page definition as part of the BCXPARMS (more bar code parameters).

System action

PSF issues this message and continues processing.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Change the amount of data that is specified for your bar code or reduce the amount of data in the macro control block.

APS2039I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A DUPLICATE FINISHING OPERATION WAS FOUND IN THE (*medium map name*) MEDIUM MAP.

Explanation

The same finishing operation was specified more than once in a medium map. This nesting of the same finishing operation is not allowed. The Media Finishing Control (MFC) structured field is in a form definition or an internal medium map in the print data set.

System action

The error is in either the print data set or a resource. If the error is in the print data set, PSF stops processing the data set. If the error is in a resource, the resource is not used and one of these occurs:

- If the error is in the default form definition or a form definition that is specified for printing messages or separator pages, PSF is not started.
- If the error is in a form definition that is specified on the user's JCL OUTPUT statement, PSF cannot begin printing the data set; it tries to print the next data set.

PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS2040I THE NUMBER OF MEDIA COLLECTION FINISHING NESTING LEVELS IS MORE THAN 4.

Explanation

You exceeded the maximum levels of nesting allowed for media collection finishing. The Medium Finishing Control (MFC) structured field can be contained in a form definition or internal medium map in a page.

System action

PSF stops processing the data set.

Operator response

If this message displays on the operator's console, it indicates either that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the form definition or internal medium map, remove one or more levels of media collection finishing operations and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field.

If the total number of nesting levels is less than or equal to four, the error might be a PSF logic error.

APS2041I DATA IN AN INPUT RECORD OR PAGEDEF RESOURCE IS NOT VALID: INPUT DATA BEING USED FOR A VARIABLE RESOURCE NAME IN LND OR RCD STRUCTURED FIELD *structured****field number IS DOUBLE BYTE EBCDIC, UTF16, OR UTF8 DATA.***

Explanation

A Resource Object Include triplet or an Extended Resource Local ID triplet on a Line Descriptor (LND) or Record Descriptor (RCD) structured field requests that input data is used as the name of the resource to be included. This input data cannot be double-byte EBCDIC, UTF16, or UTF8 data.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates either that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the print data set or page definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field is correct, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the print data set or page definition, contact your system programmer.

APS2042I DATA IN A PAGEDEF RESOURCE IS NOT VALID: AN XML PAGE DEFINITION REQUESTED THAT THE INPUT DATA BE USED FOR A RESOURCE NAME ON XMD STRUCTURED FIELD NUMBER (*structured field number*).

Explanation

An Object Reference Qualifier (ORQ) triplet is specified on an XML Descriptor (XMD) structured field. This function is not supported when you are using an XML page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates either that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field is correct, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS2044I	DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE FIELD XMD POINTER VALUE IN XMD STRUCTURED FIELD NUMBER <i>structured field number</i> WILL CAUSE AN INFINITE LOOP.
-----------------	--

Explanation

The Field XML Descriptor Pointer value in the XML Descriptor (XMD) structured field that is identified in this message caused an infinite loop condition. The XMD structured field is contained in the page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field is correct, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS2045I	THE USER DATA ENCODING SCHEME SPECIFIED IN A PAGE DEFINITION IS NOT SUPPORTED BY PSF.
-----------------	--

Explanation

The encoding scheme that is specified is not supported by PSF.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in

the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

You need to use an encoding scheme that is supported by PSF. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS2046I XML DATA FORMATTING WAS REQUESTED BY THE PAGE DEFINITION BUT THAT FUNCTION IS NOT SUPPORTED BY THIS RELEASE OF PSF.

Explanation

The XML Data formatting function is not supported by this release of PSF.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If the page definition is for a separator page or the message data set, is the JES default page definition for the user print data set, or is the default page definition that is defined in the PSF startup procedure for the user print data set, remove this page definition and

select one that does not use the record formatting function.

User response

To use the XML Data formatting function, submit this job to a version of PSF that supports XML Data formatting.

APS2047I DATA IN A PAGEDEF RESOURCE IS NOT VALID: DATA MAP *data map name1* AND DATA MAP *data map name2* HAVE DIFFERENT ENCODING SCHEMES SPECIFIED FOR THE USER DATA. ALL DATA MAPS IN THE PAGE DEFINITION MUST SPECIFY THE SAME ENCODING SCHEME.

Explanation

All the data maps in a page definition must use the same encoding scheme for the user data.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field is correct, the error might be a PSF or printer logic error. If you used a

program to create the structured fields for the page definition, contact your system programmer.

APS2048I DATA IN AN INPUT RECORD IS NOT VALID: A DTD DECLARATION AT CHARACTER COUNT NUMBER *character count* IS SPECIFIED OUTSIDE OF A DTD.

Explanation

A document type definition (DTD) declaration is only allowed inside a DTD. The character count number that is specified in this message is relative to the start of the record.

System action

PSF stops processing the current data set and issues a message that identifies the position of the error in the input data stream. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot be initialized or cannot print error messages. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the XML data with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages, use the information that is provided in the User Response section to correct the error.

User response

If you created the XML data, correct the error and resubmit the print request. See the *Extensible Markup Language (XML)* specification on the [W3C \(www.w3.org\)](http://www.w3.org). If the XML data has no error, the error might be a PSF logic error. If you used a program to create the XML data, contact your system programmer.

APS2049I DATA IN AN INPUT RECORD IS NOT VALID: THE XML COMMENT SYNTAX AT CHARACTER COUNT NUMBER *character count* IS NOT VALID.

Explanation

When an XML comment is started, you can use only two dashes in a row when you end a comment. The

character count number that is specified in this message is relative to the start of the record.

System action

PSF stops processing the current data set and issues a message that identifies the position of the error in the input data stream. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot be initialized or cannot print error messages. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the XML data with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages, use the information that is provided in the User Response section to correct the error.

User response

If you created the XML data, correct the error and resubmit the print request. See the *Extensible Markup Language (XML)* specification on the [W3C \(www.w3.org\)](http://www.w3.org). If the XML data has no error, the error might be a PSF logic error. If you used a program to create the XML data, contact your system programmer.

APS2050I DATA IN AN INPUT RECORD IS NOT VALID: THE XML END TAG AT CHARACTER COUNT NUMBER *character count* DOES NOT MATCH THE LAST START TAG.

Explanation

An XML end tag must exactly match its start tag. The character count number that is specified in this message is relative to the start of the record.

System action

PSF stops processing the current data set and issues a message that identifies the position of the error in the input data stream. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot be initialized or cannot print error messages. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the XML data with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages, use the information that is provided in the User Response section to correct the error.

User response

If you created the XML data, correct the error and resubmit the print request. See the *Extensible Markup Language (XML)* specification on the [W3C \(www.w3.org\)](http://www.w3.org). If the XML data has no error, the error might be a PSF logic error. If you used a program to create the XML data, contact your system programmer.

APS2051I **DATA IN AN INPUT RECORD IS NOT VALID: THE END OF A DOCUMENT TYPE DECLARATION AT CHARACTER COUNT NUMBER *character count* IS NOT THE CORRECT SYNTAX.**

Explanation

The end of a document type declaration did not have the correct syntax. The character count number that is specified in this message is relative to the start of the record.

System action

PSF stops processing the current data set and issues a message that identifies the position of the error in the input data stream. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot be initialized or cannot print error messages. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the XML data with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator

pages, use the information that is provided in the User Response section to correct the error.

User response

If you created the XML data, correct the error and resubmit the print request. See the *Extensible Markup Language (XML)* specification on the [W3C \(www.w3.org\)](http://www.w3.org). If the XML data has no error, the error might be a PSF logic error. If you used a program to create the XML data, contact your system programmer.

APS2052I **DATA IN AN INPUT RECORD IS NOT VALID: THE CHARACTER CODE AT CHARACTER COUNT NUMBER *character count* IS NOT A VALID VALUE FOR A CHARACTER REFERENCE.**

Explanation

A character code inside a character reference is not one of the allowed values. The character count number that is specified in this message is relative to the start of the record.

System action

PSF stops processing the current data set and issues a message that identifies the position of the error in the input data stream. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot be initialized or cannot print error messages. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the XML data with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages, use the information that is provided in the User Response section to correct the error.

User response

If you created the XML data, correct the error and resubmit the print request. See the *Extensible Markup Language (XML)* specification on the [W3C \(www.w3.org\)](http://www.w3.org). If the XML data has no error, the error might be a PSF logic error. If you used a program to create the XML data, contact your system programmer.

APS2053I DATA IN AN INPUT RECORD IS NOT VALID: THE ENTITY AT CHARACTER COUNT NUMBER *character count* IS NOT DEFINED IN THE DOCUMENT TYPE DEFINITION.

Explanation

PSF allows only internal general entity references that must be defined in an internal document type definition (DTD). The character count number that is specified in this message is relative to the start of the record.

System action

PSF stops processing the current data set and issues a message that identifies the position of the error in the input data stream. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot be initialized or cannot print error messages. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the XML data with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages, use the information that is provided in the User Response section to correct the error.

User response

If you created the XML data, correct the error and resubmit the print request. See the *Extensible Markup Language (XML)* specification on the [W3C \(www.w3.org\)](http://www.w3.org). If the XML data has no error, the error might be a PSF logic error. If you used a program to create the XML data, contact your system programmer.

APS2054I DATA IN AN INPUT RECORD IS NOT VALID: THE CHARACTER IN A TAG NAME AT CHARACTER COUNT NUMBER *character count* IS NOT VALID.

Explanation

A character in an XML tag name is not valid. The character count number that is specified in this message is relative to the start of the record.

System action

PSF stops processing the current data set and issues a message that identifies the position of the error in the input data stream. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot be initialized or cannot print error messages. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the XML data with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages, use the information that is provided in the User Response section to correct the error.

User response

If you created the XML data, correct the error and resubmit the print request. See the *Extensible Markup Language (XML)* specification on the [W3C \(www.w3.org\)](http://www.w3.org). If the XML data has no error, the error might be a PSF logic error. If you used a program to create the XML data, contact your system programmer.

APS2055I DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE ENCODING SCHEME IDENTIFIER FOR THE USER DATA IS NOT SPECIFIED IN THE ENCODING SCHEME TRIPLET ON THE BDM STRUCTURED FIELD.

Explanation

The Encoding Scheme Identifier for User Data (ESidUD) is missing on the Encoding Scheme triplet (X'50') on a Begin Data Map (BDM) structured field. This information is required when you are processing an XML page definition.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in

the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

You need to provide the encoding scheme for the user data. See *Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS2056I DATA IN A PAGEDEF RESOURCE IS NOT VALID: THE SAME QUALIFIED TAG WAS SPECIFIED IN XMD STRUCTURED FIELD NUMBERS *structured field number1* AND *structured field number2*. ALL QUALIFIED TAGS MUST BE UNIQUE IN THE SAME DATA MAP.

Explanation

All XML Descriptor (XMD) structured fields in a data map must specify a unique qualified tag, except for these types of XMD structured fields:

- Default Page Header
- Default Page Trailer
- Field
- Conditional Processing
- Attribute

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set,

or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS2057I DATA IN A PAGEDEF RESOURCE IS NOT VALID: RELATIVE INLINE POSITIONING ON AN XMD STRUCTURED FIELD CAN ONLY BE USED TO PLACE TEXT DATA.

Explanation

A Resource Object Include, Extended Resource Local ID, Bar Code Symbol Descriptor, or Graphics Descriptor triplet that uses relative inline positioning is specified on an XML Descriptor (XMD) structured field. You must use absolute inline positioning when you include a page segment, overlay, or object with an XMD structured field. You must also use absolute inline positioning when you generate a bar code or graphics object with an XMD structured field.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in

the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

You need to change your inline positioning to an absolute value. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS2058I	YOU HAVE REQUESTED PSF'S SIDE AND EDGE SENSITIVE PAPER HANDLING BUT THE PRINTER OR INPUT BIN NUMBER <i>bin_number</i>, WHICH WAS SPECIFIED FOR DUPLEX PRINTING, CANNOT HANDLE DUPLEX.
-----------------	--

Explanation

Duplex printing was requested but is not supported by the printer or the input bin that was specified. The support for duplex might not be installed on this printer or it might be disabled. Since side and edge sensitive paper handling is specified, PSF does not try to do any bin substitution.

System action

PSF stops processing the current data set and issues a message that identifies the position of the error in the input data stream. PSF issues more messages that identify the processing environment when the error was found. It then releases the current data set back to JES and requests that it is held by the system.

Operator response

If you are running under JES, use the JES data set release commands to release the data set to a printer that supports this function. To find a JES command to

release the data set for printing, see the JES publication for the level of JES you are using.

System programmer response

If the bin number specified in installation Exit 7 for printing duplex is correct, submit this print request to a printer that can print duplex from the requested bin.

If the bin number specified in installation Exit 7 for printing duplex does not exist or is incorrect for the printer you are using, change your installation Exit 7 to specify the correct bin.

User response

If the printed output is not acceptable, contact your system programmer.

APS2059I	YOU HAVE REQUESTED PSF'S SIDE AND EDGE SENSITIVE PAPER HANDLING BUT INPUT BIN NUMBER <i>bin_number</i>, WHICH WAS SPECIFIED FOR SIMPLEX OR DUPLEX PRINTING, CANNOT BE FOUND OR IS DISABLED.
-----------------	--

Explanation

PSF was directed to use bin number *bin_number* instead of the one specified in the form definition or JCL, but PSF cannot find that bin on this printer or it is disabled. Because side and edge sensitive paper handling is specified, PSF does not try to do any bin substitution.

System action

PSF stops processing the current data set and issues a message that identifies the position of the error in the input data stream. PSF issues more messages that identify the processing environment when the error was found. It then releases the current data set back to JES and requests that it is held by the system.

Operator response

If you are running under JES, use the JES data set release commands to release the data set to a printer that supports this function. To find a JES command to release the data set for printing, see the JES commands publication for the level of JES you are using.

System programmer response

If the bin number specified in the installation Exit 7 for printing simplex or duplex is correct, submit this print request to a printer with this bin enabled or enable this bin on the printer that is used.

If the bin number specified in installation Exit 7 for printing simplex or duplex does not exist or is incorrect for the printer you are using, change installation Exit 7 to specify the correct bin.

User response

If the printed output is not acceptable, contact your system programmer.

APS2061I **THE RESOLUTION OF MAPPED PAGE SEGMENT *member name* DOES NOT MATCH THE RESOLUTION OF THE PAGE OR OVERLAY THAT INCLUDED IT. AFP DOWNLOAD PLUS MUST PLACE THE PAGE SEGMENT DATA IN THE PAGE OR OVERLAY AS A SOFT RESOURCE, WHICH MIGHT CREATE A VERY LARGE AFP FILE.**

Explanation

This job might require more processing time and create a larger output file because AFP Download Plus must reprocess one or more page segments and place them in the AFP file as soft resources.

When the page segment was first mapped, AFP Download Plus converted the IM1 images to IOCA by using the resolution of the page or overlay that mapped it, and then saved the IOCA inline as a hard resource. Later in the data set that same page segment was included by a page or overlay that specified a different resolution. Because the resolutions did not match, AFP Download Plus cannot use the saved page segment. Instead, AFP Download Plus had to add the page segment data to the page or overlay as a soft resource. If the page segment is included numerous times at a resolution that is different than the saved inline version, the replication of the page segment data in each of these pages or overlays causes the size of the AFP output file to be large.

System action

AFP Download Plus continues processing the data; however, the processing might require more time and file space.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Do one of these:

- If the job performance is not affected and the amount of space that is used is acceptable, you can continue to process this data as is. You continue to receive this message unless you suppress it by using PIMSG=NO on the OUTPUT JCL statement for this job. You can use PIMSG=NO to suppress message reporting for conditions other than errors that cause AFP Download Plus to stop printing the data.
- If the job performance is affected and the amount of file space use is unacceptable, you can do one of these:
 - Convert the IM1 images in this print file to IOCA images. The AFP Conversion and Indexing Facility (ACIF) can do this conversion for you.
 - Change the resolution of the pages and overlays that include the image so that they are consistent across the job.

APS2062I **THE ORIENTATION REQUIRED FOR THIS IPS STRUCTURED FIELD DOES NOT MATCH THAT OF THE PAGE SEGMENT LOADED IN THE PRINTER. PSF MUST REPROCESS *member name* PAGE SEGMENT IN THE NEW ORIENTATION AS A SOFT PAGE SEGMENT. THIS MIGHT REQUIRE MORE PROCESSING TIME.**

Explanation

This job might require more processing time because PSF must reprocess one or more page segments.

When PSF is processing page segments with IM1 images, PSF automatically converts the IM1 image into IOCA during Map Page Segment (MPS) structured field processing, and then loads it in the printer. PSF converts the image so it appears at the intended size. During this conversion, PSF does not know the orientation that is planned for the image and assumes the image is used at 0,90 degree orientation. When PSF is processing the Include Page Segment (IPS) structured field, if the image orientation for the page segment is not 0,90 degrees, PSF reprocesses the page segment as a soft page segment in the required orientations and issues this message. *member name* in the message indicates the name of the page segment that is processed when PSF encountered this condition.

System action

PSF continues processing the print data, but the processing might require more time because of the soft page segment processing.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Do one of these:

- If the print performance is not affected and is acceptable, you can continue to print this data as is. You continue to receive this message unless you suppress it by using PIMSG=NO on the OUTPUT JCL statement for this job. You can use PIMSG=NO to suppress message reporting for conditions other than errors that cause PSF to stop printing the data.
- If print performance is affected and is unacceptable, you can convert the IM1 images in this print file to IOCA images. The AFP Conversion and Indexing Facility (ACIF) can do this conversion for you.

**APS2063I GROUP-LEVEL MEDIUM
FINISHING WAS REQUESTED BUT
IS NOT SUPPORTED BY THE
PRINTER. PROCESSING OF THE
DATA SET IS TERMINATED.**

Explanation

A Document Environment Group or medium map in the current form definition contains a Medium Finishing Control (MFC) structured field but the printer does not support group-level MFCs.

System action

PSF stops processing the data set because the finishing fidelity specified in the form definition had a continuation rule of STOP (X'01'). Finishing fidelity is requested by specifying the Finishing Fidelity triplet (X'88') on the Presentation Fidelity Control (PFC) structured field.

PSF releases the current data set back to JES and requests that it is held by the system unless PRTEROR=QUIT is specified on the OUTPUT statement. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

No response is necessary.

User response

If you want the medium finishing applied to this data set, have the operator reroute the data set to a printer that supports group-level medium finishing. If the system does not hold the data set, resubmit it to a printer that supports group-level medium finishing.

If you want the data set to print without the medium finishing operations applied, update the form definition to specify a finishing fidelity continuation rule of DO NOT STOP (X'02'). If you used a program to create the structured fields for the form definition, see the documentation for that program for information about changing the finishing fidelity setting. If you created the structured fields for the form definition, see *Mixed Object Document Content Architecture Reference* for more information.

**APS2064I SHEET-LEVEL MEDIUM FINISHING
WAS REQUESTED BUT IS NOT
SUPPORTED BY THE PRINTER.
PROCESSING OF THE DATA SET IS
TERMINATED.**

Explanation

A medium map in the current form definition contains a Medium Finishing Control (MFC) structured field but the printer does not support sheet-level MFCs.

System action

PSF stops processing the data set because the finishing fidelity specified in the form definition had a continuation rule of STOP (X'01'). Finishing fidelity is requested by specifying the Finishing Fidelity triplet (X'88') on the Presentation Fidelity Control (PFC) structured field. PSF releases the current data set back to JES and requests that it is held by the system unless PRTEROR=QUIT is specified on the OUTPUT statement. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

No response is necessary.

User response

If you want the medium finishing applied to this data set, have the operator reroute the data set to a printer that supports sheet-level medium finishing. If the system does not hold the data set, resubmit it to a printer that supports sheet-level medium finishing.

If you want the data set to print without the medium finishing operations applied, update the form definition to specify a finishing fidelity continuation rule of DO NOT STOP (X'02'). If you used a program to create the structured fields for the form definition, see the documentation for that program for information about changing the finishing fidelity setting. If you created the structured fields for the form definition, see *Mixed Object Document Content Architecture Reference* for more information.

APS2065I DATA IN A FORM DEFINITION IS NOT SUPPORTED: UP3I FINISHING WAS REQUESTED BUT IS NOT SUPPORTED BY THE PRINTER. PROCESSING OF THE DATA SET CONTINUES.

Explanation

The form definition specified a Universal Printer Pre- and Postprocessing Interface (UP3I) finishing operation but the printer does not support UP3I finishing.

System action

The UP3I triplets are ignored and processing continues because of one of these:

- The form definition specified a finishing exception continuation rule of DO NOT STOP (X'02') and a finishing exception reporting rule of REPORT (X'01').
- The form definition did not specify any finishing fidelity.

PSF issues more messages that identify the processing environment in which the error occurred.

Finishing fidelity is requested by specifying the Finishing Fidelity triplet (X'88') on the Presentation Fidelity Control (PFC) structured field.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

No response is necessary.

User response

If you want to suppress error messages that are related to finishing, specify a finishing exception continuation rule of DO NOT STOP (X'02') and a finishing exception reporting rule of DO NOT REPORT (X'02') in the form definition. See *Mixed Object Document Content Architecture Reference* for more information about the PFC structured field and the Finishing Fidelity triplet (X'88').

If the output is unacceptable, do one of these:

- Submit the print job to a printer that supports UP3I and the specific finishing operations specified by the print job.
- Specify a finishing exception continuation rule of STOP (X'01') in the form definition for the print job to stop printing the job when finishing errors are reported.

APS2066I DATA IN A FORM DEFINITION IS NOT SUPPORTED: UP3I FINISHING WAS REQUESTED BUT IS NOT SUPPORTED BY THE PRINTER. PROCESSING OF THE DATA SET IS TERMINATED.

Explanation

The form definition specified a Universal Printer Pre- and Postprocessing Interface (UP3I) finishing operation but the printer does not support UP3I finishing.

System action

PSF stops processing the data set because the form definition specified a finishing exception continuation rule of STOP (X'01'). PSF issues more messages that identify the processing environment in which the error occurred, ends the print job, marks the data set unprintable, and returns the data set to JES to be

marked as held for release by the operator. Processing continues with the next data set.

Finishing fidelity is requested by specifying the Finishing Fidelity triplet (X'88') on the Presentation Fidelity Control (PFC) structured field.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

No response is necessary.

User response

If the output is unacceptable, do one of these:

- Submit the print job to a printer that supports UP3I and the specific finishing operations specified by the print job.
- Specify a finishing exception continuation rule of DO NOT STOP (X'02') with a finishing exception reporting rule of DO NOT REPORT (X'02') in the form definition for the print job. This tells PSF to print the job and not report any finishing errors.
- Specify a finishing exception continuation rule of DO NOT STOP (X'02') with a finishing exception reporting rule of REPORT (X'01') in the form definition for the print job. This tells PSF to print the job and report any finishing errors that occurred while printing.
- Do not specify the Finishing Fidelity triplet (X'88') in the form definition for the print job. This tells PSF to print the job and report any finishing errors that occurred while printing.

APS2067I DATA IN A FORM DEFINITION IS NOT SUPPORTED: AFP FINISHING WAS REQUESTED BUT IS NOT SUPPORTED BY THE PRINTER. PROCESSING OF THE DATA SET CONTINUES.

Explanation

The form definition specified an AFP finishing operation but the printer does not support AFP finishing.

System action

The AFP triplets are ignored and processing continues because of one of these:

- The form definition specified a finishing exception continuation rule of DO NOT STOP (X'02') and a finishing exception reporting rule of REPORT (X'01').
- The form definition did not specify any finishing fidelity.

PSF issues more messages that identify the processing environment in which the error occurred.

Finishing fidelity is requested by specifying the Finishing Fidelity triplet (X'88') on the Presentation Fidelity Control (PFC) structured field.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

No response is necessary.

User response

If you want to suppress error messages that are related to finishing, specify a finishing exception continuation rule of DO NOT STOP (X'02') and a finishing exception reporting rule of DO NOT REPORT (X'02') in the form definition. See *Mixed Object Document Content Architecture Reference* for more information about the PFC structured field and the Finishing Fidelity triplet (X'88').

If the output is unacceptable, do one of these:

- Submit the print job to a printer that supports UP3I and the specific finishing operations specified by the print job.
- Specify a finishing exception continuation rule of STOP (X'01') in the form definition for the print job to stop printing the job when finishing errors are reported.

APS2068I DATA IN A FORM DEFINITION IS NOT SUPPORTED: AFP FINISHING WAS REQUESTED BUT IS NOT SUPPORTED BY THE PRINTER. PROCESSING OF THE DATA SET IS TERMINATED.

Explanation

The form definition specified an AFP finishing operation but the printer does not support AFP finishing.

System action

PSF stops processing the data set because the form definition specified a finishing exception continuation rule of STOP (X'01'). PSF issues more messages that identify the processing environment in which the error occurred, stops the print job, marks the data set unprintable, and returns the data set to JES to be marked as held for release by the operator. Processing continues with the next data set.

Finishing fidelity is requested by specifying the Finishing Fidelity triplet (X'88') on the Presentation Fidelity Control (PFC) structured field.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

No response is necessary.

User response

If the output is unacceptable, do one of these:

- Submit the print job to a printer that supports AFP finishing and the specific finishing operations specified by the print job.
- Specify a finishing exception continuation rule of DO NOT STOP (X'02') with a finishing exception reporting rule of DO NOT REPORT (X'02') in the form definition for the print job. This tells PSF to print the job and not report any finishing errors.
- Specify a finishing exception continuation rule of DO NOT STOP (X'02') with a finishing exception reporting rule of REPORT (X'01') in the form definition for the print job. This tells PSF to print the job and report any finishing errors that occurred while printing.
- Do not specify the Finishing Fidelity triplet (X'88') in the form definition for the print job. This tells PSF to print the job and report any finishing errors that occurred while printing.

APS2069I

**SYSTEM ACTION TAKEN:
PRINTING HAS STOPPED AND**

**THE DATA SET IS BEING HELD
BECAUSE YOU SPECIFIED DO NOT
CONTINUE IN THE FORM
DEFINITION AND FINISHING
ERRORS WERE RECEIVED.**

Explanation

The form definition specifies a finishing operation that the printer does not support and a finishing exception continuation rule of STOP (X'01').

Finishing fidelity is requested by specifying the Finishing Fidelity triplet (X'88') on the Presentation Fidelity Control (PFC) structured field.

System action

PSF stops processing the data set because the form definition specified a finishing exception continuation rule of STOP (X'01'). PSF issues more messages that identify the processing environment in which the error occurred, stops the print job, marks the data set unprintable, and returns the data set to JES to be marked as held for release by the operator. Processing continues with the next data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

No response is necessary.

User response

If the output is unacceptable, do one of these:

- Submit the print job to a printer that supports UP3I and the specific finishing operations specified by the print job.
- Specify a finishing exception continuation rule of DO NOT STOP (X'02') with a finishing exception reporting rule of DO NOT REPORT (X'02') in the form definition for the print job. This tells PSF to print the job and not report any finishing errors.
- Specify a finishing exception continuation rule of DO NOT STOP (X'02') with a finishing exception reporting rule of REPORT (X'01') in the form definition for the print job. This tells PSF to print the job and report any finishing errors that occurred while printing.

- Do not specify the Finishing Fidelity triplet (X'88') in the form definition for the print job. This tells PSF to print the job and report any finishing errors that occurred while printing.

APS2071I A TRUETYPE OR OPENTYPE FONT WAS SPECIFIED BUT THESE FONTS ARE NOT SUPPORTED BY THE PRINTER.

Explanation

The printer does not support TrueType and OpenType fonts.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found. PSF releases the current data set back to JES and requests that it is held by the system, unless PRTEROR=QUIT is specified on the OUTPUT statement.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

This message indicates that the print data set contains TrueType or OpenType fonts. The printer does not support these types of fonts. Determine whether the job can be sent to a different printer or if an engineering change (EC) is available to upgrade the microcode on this printer. To determine a printer's level of support, use the display printer information function in PSF. If X'F204' (Data Object Font support) is returned in the Sense Type and Model (STM) reply, the printer supports TrueType or OpenType fonts.

User response

Submit this job to a printer that supports TrueType and OpenType fonts. For information about what object types your printer supports, use the display printer information function in PSF or see your printer's documentation.

APS2072I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN INCORRECT COMBINATION OF TRIPLETS WAS SPECIFIED WHEN MAPPING A DATA OBJECT FONT IN AN MDR STRUCTURED FIELD.

Explanation

When mapping a data object font (DOF) in a Map Data Resource (MDR) structured field, you must have Fully Qualified Name (FQN) type X'DE', FQN type X'BE', and DOF descriptor X'8B' triplets specified as well. In addition, the FQN type X'BE' triplet must specify a 1-byte local ID.

System action

PSF stops processing the current page, then tries to find the end of the current page and resume printing on the next page. If it cannot find the end of the page, PSF stops printing the data set. If this error occurs in a resource, PSF stops processing the data set. If this error occurred in a Resource Environment Group (REG), PSF stops processing the REG and continues processing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the print data set or resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the correct format of the referenced structured field. If the structured field is correct, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or resource, contact your system programmer.

APS2073I DATA IN AN INPUT RECORD IS NOT VALID. THE FULLY QUALIFIED NAME TRIPLET TYPE AND THE OBJECT TYPE SPECIFIED IN A REPEATING GROUP ON A PREPROCESS PRESENTATION

OBJECT STRUCTURED FIELD DO NOT AGREE.

Explanation

When a repeating group in a Preprocess Presentation Object (PPO) structured field is mapping an object container, you must use a Fully Qualified Name triplet of type X'CE'. When the repeating group is mapping an IOCA object or an overlay, you must use a Fully Qualified Name triplet of type X'84'.

System action

PSF stops processing the Resource Environment Group and continues processing the data set. As a result, the object is not to be rasterized until it is included in the page or overlay with an Include Object (IOB) or Include Page Overlay (IPO) structured field.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the print data set or resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the correct format of the referenced structured field. If the structured field is correct, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or resource, contact your system programmer.

Explanation

When mapping data object fonts, you can specify only the name of a TrueType or OpenType font. This font might reside in a collection, but the Map Data Resource (MDR) structured field needs the font name in the collection.

System action

PSF stops processing the current page, then tries to find the end of the current page and resume printing on the next page. If it cannot find the end of the page, PSF stops printing the data set. If this error occurs in a resource, PSF stops processing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the print data set or resource, correct the error and resubmit the print request. It is possible that the problem is the object type OID specified in the X'10' object classification triplet. It might specify that a TrueType or OpenType collection is being mapped when a font is really mapped. See *Mixed Object Document Content Architecture Reference* for more information about the correct format of the referenced structured field.

If the structured field is correct, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or resource, contact your system programmer.

APS2074I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN MDR STRUCTURED FIELD IS MAPPING THE NAME OF A TRUETYPE OR OPENTYPE COLLECTION.

APS2075I TRCS ARE NOT ALLOWED WITH A PAGE THAT HAS FONTS MAPPED IN BOTH AN MCF AND AN MDR. THE DATA MAP BEING PROCESSED IS *data map name*.

Explanation

You can use table reference characters (TRCs) with fonts mapped in a Map Coded Font (MCF) structured field (FOCA fonts) or with fonts mapped in a Map Data Resource (MDR) structured field (TrueType or OpenType fonts). However, you cannot have a mixture of both types of fonts in a data map and use TRCs.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

Change your page definition to use either all FOCA fonts or all TrueType or OpenType fonts.

APS2077I DATA IN AN INPUT RECORD IS NOT VALID: AN INLINE TRUETYPE OR OPENTYPE COLLECTION DOES NOT HAVE ANY BASE FONTS SPECIFIED.

Explanation

The Begin Resource (BRS, also called BR) structured field must have Fully Qualified Name type X'6E' triplets for each base font contained in the collection.

System action

PSF stops processing the data set.

Operator response

None.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was

valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the print data set or resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the correct format of the referenced structured field. If the structured field is correct, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or resource, contact your system programmer.

APS2078I DATA IN AN INPUT RECORD IS NOT VALID: AN INLINE RESOURCE HAS AN INCORRECT SPECIFICATION OF BASE FONTS, LINKED FONTS, OR MAPPED CMRS.

Explanation

A Begin Resource (BRS, also called BR) structured field has an error. Base fonts (Fully Qualified Name type X'6E' triplets) can be specified only for TrueType or OpenType collections. Linked fonts (Fully Qualified Name type X'7E' triplets) can be specified only for a TrueType or OpenType font or for a base font of a TrueType or OpenType collection. Mapped CMRs (Fully Qualified Name type X'41' triplets) can be specified only for color management resources (CMRs).

System action

PSF stops processing the data set.

Operator response

None.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the print data set, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the correct format of the referenced structured field. If the structured field is correct, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or resource, contact your system programmer.

APS2079I THE NUMBER OF LINKED FONTS FOR A TRUETYPE OR OPENTYPE FONT resource name CAUSES THE ACTIVATE RESOURCE REQUEST TO EXCEED THE OUTPUT COMMAND BUFFER.

Explanation

The number of linked fonts for a TrueType or OpenType font caused the activation request to exceed the size of the output command buffer.

System action

PSF stops processing the current page, then tries to find the end of the current page and resume printing on the next page. If it cannot find the end of the page, PSF stops printing the data set. If this error occurs in a resource, PSF stops processing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

Decrease the number of linked fonts for your TrueType or OpenType font to the minimum necessary to print your data.

APS2080I INPUT DATA (input data) CANNOT BE CONVERTED TO AN ENCODING of CCSID (ccsid). RETURN CODE return code AND REASON CODE reason code VALUES WERE RETURNED BY THE CONVERTER.

Explanation

PSF must convert the input data to the specified encoding to continue processing. An error occurred during this conversion.

If the input data is a resource name, the CCSID is 1200. Any other CCSID indicates that mixed single-byte or double-byte EBCDIC data is being converted to mixed single-byte or double-byte ASCII data for a QR Code bar code. If the error occurs on data for a bar code, the message shows only the first 50 bytes of the data.

The system's conversion services can return these return codes and reason codes:

Return Code 4

Reason Code 1

The converted name exceeded the maximum character size.

Reason Code 3 or 4

The SET UNI command is running, which changes the conversion environment.

Reason Code 6

A character was found that cannot be converted.

Reason Code 7

The string to be converted contains a multibyte character that is missing characters.

Reason Code 9

An indirect character conversion error was found.

Return Code 8

Reason Code 3

The specified conversion is not supported in the active conversion image.

Reason Code 5

The sub code page number is not in the valid range of numbers for the specified conversion.

Return Code 12

Reason Code 1

No conversion environment is set up. Issue a SET UNI command.

Reason Code 2

Conversion services are not available.

System action

PSF stops processing the current page, then tries to find the end of the current page and resume printing on the next page. If it cannot find the end of the page, PSF stops printing the data set. If this error occurs in a resource, PSF stops processing the data set.

If this error occurs in a Resource Environment Group (REG), PSF stops processing the REG and continues processing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

Look at the return and reason code to verify that no problem exists with the system's conversion services. If a problem exists with the conversion services, see *z/OS Unicode Services User's Guide and Reference* for instructions to correct the error.

User response

The user response varies, depending on the return and reason codes issued:

- For return code 4, reason codes 3 and 4, try processing your data set again. For other reason codes, check the encoding of the input data.
- For return code 8, check with your system operator for valid values for the conversion images available on your system.
- For return code 12, an IPL is required with the correct SET UNI command.

APS2081I	YOUR PRINTER DOES NOT SUPPORT PREPROCESSING AND CACHING A RESOURCE.
-----------------	--

Explanation

The print data set requested a resource be preprocessed and stored in a cache. This request is made with the Preprocess Presentation Object (PPO) structured field in a Resource Environment Group. The printer does not support this function.

System action

PSF ignores this preprocess request and continues processing. As a result, the object is not rasterized until it is included in the page or overlay with an Include Object (IOB) structured field.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

This message indicates that the print data set was created with a certain level of resource management function expected. The printer does not have this level of resource management. Determine whether the job can be sent to a different printer or if an engineering change (EC) is available to upgrade the microcode on this printer. To determine a printer's level of support, use the display printer information function in PSF. If X'707B' (Rasterize Presentation Object (RPO) command support) is returned in the Sense Type and Model (STM) reply, the printer supports this function.

User response

If the performance of the job is acceptable, do nothing. If the performance of the job is not acceptable, inform your system programmer.

APS2082I	DATA IN AN INPUT RECORD IS NOT VALID. RESOURCE NAME <i>resource name</i> IS SPECIFIED ON A PREPROCESS PRESENTATION OBJECT (PPO) STRUCTURED FIELD BUT IS NOT MAPPED IN THE RESOURCE ENVIRONMENT GROUP.
-----------------	--

Explanation

All resources that are specified on a PPO structured field must be mapped in the Resource Environment Group (REG). Overlays must be mapped with a Map Page Overlay (MPO) structured field. IOCA image and

object containers must be mapped with a Map Data Resource (MDR) structured field.

System action

PSF stops processing the REG and continues processing the data set. As a result, the object is not rasterized until it is included with an Include Object (IOB) or Include Page Overlay (IPO) structured field.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error. If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the print data set or the resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or the resource, contact your system programmer.

APS2083I DATA IN A PAGEDEF RESOURCE IS NOT VALID: DATA MAP *data map name* HAS RECORD FORMAT IDS THAT ARE NOT THE SAME LENGTH.

Explanation

All the record format IDs for a data map in a page definition must be the same length. Blanks can be used in the record format ID to make it the required length.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program is valid. If the input is valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information in the User Response section to correct the error.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field is correct, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS2084I THE LENGTH OF DATA IN RECORD NUMBER *record number* DOES NOT MATCH THE LENGTH REQUIRED FOR THE USER DATA TYPE SPECIFIED IN THE PAGE DEFINITION.

Explanation

The type of user data that is specified in the page definition determines the length required for an input record. For example, if you specified UTF16 data in the page definition, the record length must be a multiple of 2. If you specified UTF8 data, the length of each character can vary 1 - 4 bytes.

System action

PSF stops processing the current data set and issues a message that identifies the position of the error in the input data stream. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot be initialized or cannot print error messages. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the data with the error, verify that the input to that program is valid. If the input is valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages, use the information in the User Response section to correct the error.

User response

If you created the data, correct the data in the record so that it matches the length that is required for the specified data type and then resubmit the print request. If the data has no error, the error might be a PSF logic error. If you used a program to create the data, contact your system programmer.

APS2085I DATA IN A FORM DEFINITION IS NOT SUPPORTED: PRINT JOB FINISHING WAS REQUESTED BUT IS NOT SUPPORTED FOR THIS TYPE OF DATA. PROCESSING OF THE DATA SET CONTINUES.

Explanation

The form definition of a data set other than the job header specified a Medium Finishing Control (MFC) structured field with a scope value of PRINTJOB. The print job finishing scope is only supported when it is specified in the form definition used for the job header.

The MFC structured field is specified in the Document Environment Group of the form definition or in a copy group.

System action

The finishing triplets are ignored and processing continues when one of these happens:

- The form definition specifies a finishing fidelity exception continuation rule of DO NOT STOP (X'02') and a finishing exception reporting rule of REPORT (X'01').
- The form definition does not specify any finishing fidelity.

PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page (other than the job header), for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

None.

User response

If the output is unacceptable, do one of these:

- Update the MFC structured field in the form definition to specify a supported scope.
- Specify a different form definition for the data set that does not request print job finishing.
- Specify a finishing fidelity exception continuation rule of STOP (X'01') in the form definition for the print job. This tells PSF to stop printing the job when finishing errors are reported.
- Specify a finishing fidelity exception continuation rule of DO NOT STOP (X'02') with a finishing fidelity exception reporting rule of DO NOT REPORT (X'02') in the form definition for the print job. This tells PSF to print the job and not to report any finishing errors.

Finishing fidelity is requested by specifying the finishing fidelity triplet (X'88') on the Presentation Fidelity Control (PFC) structured field in the form definition.

If you want the job header finished with the rest of the job, contact your system programmer to find out whether a printer or class is set up with the print job finishing function.

APS2086I DATA IN A FORM DEFINITION IS NOT SUPPORTED: PRINT JOB FINISHING WAS REQUESTED BUT IS NOT SUPPORTED FOR THIS TYPE OF DATA. PROCESSING OF THE DATA SET IS STOPPED.

Explanation

The form definition of a data set other than the job header specified a Medium Finishing Control (MFC) structured field with a scope value of PRINTJOB. The print job finishing scope is only supported when it is specified in the form definition used for the job header.

The MFC structured field is specified in the Document Environment Group of the form definition or in a copy group.

System action

The finishing triplets are ignored and PSF stops processing the data set because the form definition specified a finishing fidelity exception continuation rule of STOP (X'01').

PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page (other than the job header), for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

User response

If the output is unacceptable, do one of these:

- Update the MFC structured field in the form definition to specify a supported scope.
- Specify a different form definition for the data set that does not request print job finishing.
- Specify a finishing fidelity exception continuation rule of DO NOT STOP (X'02') with a finishing fidelity exception reporting rule of DO NOT REPORT (X'02') in the form definition for the print job. This tells PSF to print the job and not to report any finishing errors.
- Specify a finishing fidelity exception continuation rule of DO NOT STOP (X'02') with a finishing fidelity exception reporting rule of REPORT (X'01') in the form definition for the print job. This tells PSF to print the job and report any finishing errors that occur while printing.
- Do not specify a finishing fidelity triplet (X'88') in the form definition for the print job. This tells PSF to print the job and report any finishing errors that occur while printing.

Finishing fidelity is requested by specifying the finishing fidelity triplet (X'88') on the Presentation Fidelity Control (PFC) structured field in the form definition.

If you want the job header finished with the rest of the job, contact your system programmer to find out whether a printer or class is set up with the print job finishing function.

Explanation

PSF must convert a resource name encoded with a graphic character set global identifier (GCSGID) and code page global identifier (CPGID) pair by first converting the pair into a coded character set identifier (CCSID). In this case, the conversion to a CCSID failed.

The GCSGID and CPGID pair is specified in a coded graphic character set global identifier triplet, X'01', at the time the resource is referenced.

The possible return codes from the system's conversion services are:

- X'00010001'—No entry was found in the CCSID resource repository for the specified GCSGID and CPGID pair.
- X'00020001'—A CPGID value is zero.
- X'00030001'—A CPGID value is 65,535.

System action

PSF stops processing the current page, then tries to find the end of the current page and resume printing on the next page. If it cannot find the end of the page, PSF stops printing the data set. If this error occurs in a resource, PSF stops processing the data set.

If this error occurs in a Resource Environment Group (REG), PSF stops processing the REG and continues processing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

Look at the return code to verify that no problem exists with the system's conversion services. If a problem exists with the conversion services, see *z/OS Unicode Services User's Guide and Reference* for instructions to correct the error.

APS2087I **A GCSGID *gcsgid* AND CPGID *cpgid* PAIR CANNOT BE CONVERTED TO A CCSID. RETURN CODE *return code* WAS RETURNED BY THE CONVERTER.**

User response

The user response varies, depending on the return code issued:

- For return code X'00010001', you must specify a GCSGID and CPGID value that has a supported CCSID.
- For all other return codes, fix your X'01' triplet to specify a valid value for the CPGID.

Consider changing the X'01' triplet to the CCSID form where just a CCSID value is specified. This removes the need to convert the GCSGID, CPGID pair to a CCSID.

If your resource name is in EBCDIC, change the X'01' triplet to specify CCSID 500.

APS2088I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: STRUCTURED FIELD <i>structured field</i> HAS AN INCORRECT SCOPE VALUE ON A CMR DESCRIPTOR TRIPLET.
-----------------	---

Explanation

The scope value is not correct on the Color Management Resource (CMR) Descriptor triplet, X'91', for the specified structured field. The valid scope values for each structured field are listed in [Appendix A, "Valid scope values for the CMR Descriptor triplet," on page 775.](#)

System action

- If processing a form definition, page definition, or resource, PSF stops processing the data set.
- If processing a Resource Environment Group (REG), PSF skips the remainder of the REG and continues processing the data set.
- If processing a page, PSF skips the remainder of the page and continues processing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or resource with the error, verify that the input to that program was valid. If the input was valid, see [PSF for z/OS:](#)

Diagnosis for assistance in determining the source of the problem.

User response

If you created the structured fields, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field does not have an error, the error might be a PSF logic error. If you used a program to create the structured fields, contact your system programmer.

APS2089I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE <i>structured field</i> STRUCTURED FIELD CONTAINS UNPAIRED FQN X'DE' AND CMR DESCRIPTOR TRIPLETS.
-----------------	--

Explanation

When specifying a color management resource (CMR), the CMR Descriptor triplet (X'91') must immediately follow a Fully Qualified Name (FQN) triplet with an FQNType of Data Object External Resource Reference (X'DE').

System action

If this error occurs in a page, PSF attempts to find the end of the current page, and then tries to resume printing on the next page. If PSF cannot find the end of the page, it stops printing the data set.

If this error occurs in a Resource Environment Group (REG), PSF stops processing the REG and continues processing the data set.

If this error occurs in a page definition or resource, PSF stops processing the data set.

PSF issues a message that identifies the position of the structured field in the input data stream or resource. PSF issues additional messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field does not have an error, the error might be a PSF logic error. If you used a program to create the structured fields, contact your system programmer.

APS2090I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: STRUCTURED FIELD *structured field* HAS AN INCORRECT PROCESSING MODE VALUE ON A CMR DESCRIPTOR TRIPLET.**

Explanation

The processing mode value is not correct on the Color Management Resource (CMR) Descriptor triplet, X'91', for the specified structured field. Only audit or instruction modes are valid.

System action

- If processing a form definition, page definition, or resource, PSF stops processing the data set.
- If processing a Resource Environment Group (REG), PSF skips the remainder of the REG and continues processing the data set.
- If processing a page, PSF skips the remainder of the page and continues processing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or resource with the error, verify that the input to that program was

valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field does not have an error, the error might be a PSF logic error. If you used a program to create the structured fields, contact your system programmer.

APS2091I **BASIC COLOR MANAGEMENT IS NOT SUPPORTED BY THIS PRINTER. THIS MESSAGE IS ONLY ISSUED ONCE PER DOCUMENT.**

Explanation

Your print job is requesting color management. However, your printer does not support Color Management Resource (CMR) Descriptor triplets (X'91'), Invoke CMR triplets (X'92'), Rendering Intent triplets (X'95'), or Fully Qualified Name (FQN) type X'41' triplets (X'02').

System action

- If the form definition indicates color fidelity stop, PSF stops processing the data set.
- If the form definition indicates color fidelity continue and report errors, PSF continues processing the data set and reports an error. No basic color management information is sent to the printer.
- If the form definition indicates color fidelity continue and do not report an error, PSF continues processing the data set and does not report an error. No basic color management information is sent to the printer.
- If the form definition does not indicate color fidelity, PSF continues processing the data set and reports an error. No basic color management information is sent to the printer.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

Delete the color management requests from the separator page data set for this printer.

User response

If you are satisfied with your output and do not want to see this message, change your form definition to indicate color fidelity continue and do not report an error.

If you are not satisfied with your output, submit the print job to a printer that supports color management.

APS2092I **A CMR WITH TYPE *cmr type* IS NOT SUPPORTED BY THIS PRINTER. THIS MESSAGE IS ONLY ISSUED ONCE PER DOCUMENT FOR A GIVEN CMR TYPE.**

Explanation

The print job or data object resource access table (RAT) specified a color management resource (CMR) with the CMR type listed in the message. However, your printer does not support the specified CMR type:

- If the CMR type is color conversion (CC), the printer does not support the most basic color management or a CMR that is referenced as pass-through.
- If the CMR type is halftone (HT) or tone transfer curve (TC), it might be a generic or device specific CMR that the printer does not support.
- If the CMR type is link (LK) or index (IX), the printer does not provide this support.

System action

- If the form definition indicates color fidelity stop, PSF stops processing the data set.
- If the form definition indicates color fidelity continue and report errors, PSF continues processing the data set and reports an error. The CMR is not sent to the printer.
- If the form definition indicates color fidelity continue and do not report an error, PSF continues processing the data set and does not report an error. The CMR is not sent to the printer.
- If the form definition does not indicate color fidelity, PSF continues processing the data set and reports an error. The CMR is not sent to the printer.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in

the PSF startup procedure. Inform your system programmer.

System programmer response

Delete the color management requests from the separator page data set for this printer.

User response

If you are satisfied with your output and do not want to see this message, change your form definition to indicate color fidelity continue and do not report an error.

If you are not satisfied with your output, submit the print job to a printer that supports the specified CMR type.

APS2093I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A REPEATING GROUP IN AN MDR STRUCTURED FIELD CONTAINS AN INCOMPLETE SPECIFICATION FOR A CMR.**

Explanation

A repeating group in a Map Data Resource (MDR) structured field for a color management resource (CMR) is missing a Fully Qualified Name (FQN) triplet (X'02') with an FQNType of Data Object External Resource Reference (X'DE'), a CMR Descriptor triplet (X'91'), or both.

System action

- If processing a form definition, page definition, or resource, PSF stops processing the data set.
- If processing a Resource Environment Group (REG), PSF skips the remainder of the REG and continues processing the data set.
- If processing a page, PSF skips the remainder of the page and continues processing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or resource with the error, verify that the input to that program was

valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field does not have an error, the error might be a PSF logic error. If you used a program to create the structured fields, contact your system programmer.

APS2094I	THE INVOKE CMR COMMAND IS NOT SUPPORTED BY THIS PRINTER. THIS MESSAGE IS ONLY ISSUED ONCE PER PRINT DATA SET.
-----------------	--

Explanation

Your print job has color management resources (CMRs) specified in the form definition, or it specified that an overlay is preripped with a CMR. However, your printer does not support the Invoke CMR (ICMR) command.

System action

- If the form definition indicates color fidelity stop, PSF stops processing the data set.
- If the form definition indicates color fidelity continue and report errors, PSF continues processing the data set and reports an error. The ICMR command is not sent to the printer.
- If the form definition indicates color fidelity continue and do not report an error, PSF continues processing the data set and does not report an error. The ICMR command is not sent to the printer.
- If the form definition does not indicate color fidelity, PSF continues processing the data set and reports an error. The ICMR command is not sent to the printer.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

Delete the color management requests from the separator page form definition for this printer.

User response

If you are satisfied with your output and do not want to see this message, change your form definition to indicate color fidelity continue and do not report an error.

If you are not satisfied with your output, submit the print job to a printer that supports the full color management function.

APS2095I	THE SPE COMMAND IS NOT SUPPORTED BY THIS PRINTER. THIS MESSAGE IS ONLY ISSUED ONCE PER PRINT DATA SET.
-----------------	---

Explanation

Your print job has rendering intent, device appearance, or both specified in the form definition, or it requested that an overlay is preripped with a rendering intent. However, your printer does not support the Set Presentation Environment (SPE) command.

System action

- If the form definition indicates color fidelity stop, PSF stops processing the data set.
- If the form definition indicates color fidelity continue and report errors, PSF continues processing the data set and reports an error. The SPE command is not sent to the printer.
- If the form definition indicates color fidelity continue and do not report an error, PSF continues processing the data set and does not report an error. The SPE command is not sent to the printer.
- If the form definition does not indicate color fidelity, PSF continues processing the data set and reports an error. The SPE command is not sent to the printer.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

Delete rendering intent and device appearance from the separator page form definition for this printer.

User response

If you are satisfied with your output and do not want to see this message, change your form definition to indicate color fidelity continue and do not report an error.

If you are not satisfied with your output, submit the print job to a printer that supports rendering intent and device appearance.

APS2096I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A CMR NAME HAS AN ERROR.

Explanation

A problem exists with the name of a color management resource (CMR) that is specified in a Map Data Resource (MDR) or a Begin Resource (BRS) structured field. The possible problems are:

- A link (LK) CMR cannot be specified in an MDR.
- A generic CMR must have a type of tone transfer curve (TTC) or halftone (HT).
- A pass-through CMR must have a type of color conversion (CC).
- The CMR name length must be 73 bytes in single-byte encoding or 146 bytes in double-byte encoding.

System action

- If processing a form definition, page definition, or resource, PSF stops processing the data set.
- If processing a Resource Environment Group (REG), PSF skips the remainder of the REG and continues processing the data set.
- If processing a page, PSF skips the remainder of the page and continues processing the data set.
- If processing an inline resource, PSF stops processing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or resource with the error, verify that the input to that program was valid. If the input was valid, see [PSF for z/OS](#):

Diagnosis for assistance in determining the source of the problem.

User response

If you created the structured fields, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field does not have an error, the error might be a PSF logic error. If you used a program to create the structured fields, contact your system programmer.

APS2097I OBJECT AREA COLORING IS NOT SUPPORTED BY THIS PRINTER. THIS MESSAGE IS ONLY ISSUED ONCE PER DOCUMENT.

Explanation

Your printer does not support object area coloring. The Color Specification triplet (X'4E') in the following structured fields determines from where the object area coloring is requested.

- Page Descriptor (PGD) - page or overlay
- Include Object (IOB) - override for the IOCA, GOCA, BCOCA, object container, or page segment object
- Object Area Descriptor (OBD) - IOCA, GOCA, BCOCA, or object container

System action

- If the form definition indicates color fidelity stop, PSF stops processing the data set.
- If the form definition indicates color fidelity continue and report errors, PSF continues processing the data set and reports an error. An object area coloring request is not sent to the printer.
- If the form definition indicates color fidelity continue and do not report an error, PSF continues processing the data set and does not report an error. An object area coloring request is not sent to the printer.
- If the form definition does not indicate color fidelity, PSF continues processing the data set and does not report an error. An object area coloring request is not sent to the printer.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

Delete object area coloring requests from the separator page data set for this printer.

User response

If you are satisfied with your output and do not want to see this message, change your form definition to indicate color fidelity continue and do not report an error.

If you are not satisfied with your output, submit the print job to a printer that supports object area coloring.

To find a printer that supports object area coloring, search for the IPDS Sense Type and Model (STM) X'6201' property pair in a printer information report. The PRTINFO DD statement in the PSF startup procedure specifies the data set name that contains the reports.

APS2098I EXTENDED BAR CODE COLORS ARE NOT SUPPORTED BY THIS PRINTER. THIS MESSAGE IS ONLY ISSUED ONCE PER DOCUMENT.

Explanation

The Color Specification triplet (X'4E') specifies the extended bar code color on the Bar Code Data Descriptor (BDD) structured field or for a bar code generated by a page definition. However, your printer does not support extended bar code colors.

System action

- If the form definition indicates color fidelity stop, PSF stops processing the data set.
- If the form definition indicates color fidelity continue and report errors, PSF continues processing the data set and reports an error. A bar code extended color request is not sent to the printer.
- If the form definition indicates color fidelity continue and do not report an error, PSF continues processing the data set and does not report an error. A bar code extended color request is not sent to the printer.
- If the form definition does not indicate color fidelity, PSF continues processing the data set and does not report an error. A bar code extended color request is not sent to the printer.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in

the PSF startup procedure. Inform your system programmer.

System programmer response

Delete extended bar code color requests from the separator page data set for this printer.

User response

If you are satisfied with your output and do not want to see this message, change your form definition to indicate color fidelity continue and do not report an error.

If you are not satisfied with your output, submit the print job to a printer that supports extended bar code colors.

APS2099I SET BILEVEL IMAGE COLOR IS NOT SUPPORTED BY THIS PRINTER. THIS MESSAGE IS ONLY ISSUED ONCE PER DOCUMENT.

Explanation

The Color Specification triplet (X'4E') requests a bi-level image color in an Include Object (IOB) structured field. A Set Bilevel Image Color self-defining parameter requests bi-level image color in an Image Data Descriptor (IDD) structured field. However, your printer does not support the Set Bilevel Image Color self-defining parameter for IOCA images.

System action

- If the form definition indicates color fidelity stop, PSF stops processing the data set.
- If the form definition indicates color fidelity continue and report errors, PSF continues processing the data set and reports an error. A bi-level image color request is not sent to the printer.
- If the form definition indicates color fidelity continue and do not report an error, PSF continues processing the data set and does not report an error. A bi-level image color request is not sent to the printer.
- If the form definition does not indicate color fidelity, PSF continues processing the data set and does not report an error. A bi-level image color request is not sent to the printer.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

Delete bi-level image color requests from the separator page data set for this printer.

User response

If you are satisfied with your output and do not want to see this message, change your form definition to indicate color fidelity continue and do not report an error.

If you are not satisfied with your output, submit the print job to a printer that supports bi-level image colors.

APS2100I SET EXTENDED BILEVEL IMAGE COLOR IS NOT SUPPORTED BY THIS PRINTER. THIS MESSAGE IS ONLY ISSUED ONCE PER DOCUMENT.

Explanation

A Set Extended Bilevel Image Color self-defining parameter in an Image Data Descriptor (IDD) structured field requests an extended bi-level image color. However, your printer does not support the Set Extended Bilevel Image Color self-defining parameter for IOCA images.

System action

- If the form definition indicates color fidelity stop, PSF stops processing the data set.
- If the form definition indicates color fidelity continue and report errors, PSF continues processing the data set and reports an error. An extended bi-level image color request is not sent to the printer.
- If the form definition indicates color fidelity continue and do not report an error, PSF continues processing the data set and does not report an error. An extended bi-level image color request is not sent to the printer.
- If the form definition does not indicate color fidelity, PSF continues processing the data set and does not report an error. An extended bi-level image color request is not sent to the printer.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

Delete extended bi-level image color requests from the separator page data set for this printer.

User response

If you are satisfied with your output and do not want to see this message, change your form definition to indicate color fidelity continue and do not report an error.

If you are not satisfied with your output, submit the print job to a printer that supports extended bi-level image colors.

To find a printer that supports extended bi-level image colors, search for the IPDS Sense Type and Model (STM) X'4401' property pair in a printer information report. The PRTINFO DD statement in the PSF startup procedure specifies the data set name that contains the reports.

APS2101I SET PROCESS COLOR DRAWING ORDER IS NOT SUPPORTED BY THIS PRINTER. THIS MESSAGE IS ONLY ISSUED ONCE PER DOCUMENT.

Explanation

The Color Specification triplet (X'4E') requests a Set Process Color drawing order for a graphics object that is generated by a page definition. However, your printer does not support the Set Process Color drawing order for GOCA graphics.

System action

- If the form definition indicates color fidelity stop, PSF stops processing the data set.
- If the form definition indicates color fidelity continue and report errors, PSF continues processing the data set and reports an error. A Set Process Color drawing order is not sent to the printer.
- If the form definition indicates color fidelity continue and do not report an error, PSF continues processing the data set and does not report an error. A Set Process Color drawing order is not sent to the printer.
- If the form definition does not indicate color fidelity, PSF continues processing the data set and does not report an error. A Set Process Color drawing order is not sent to the printer.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is

defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

Delete Set Process Color drawing order requests from the separator page's page definition.

User response

If you are satisfied with your output and do not want to see this message, change your form definition to indicate color fidelity continue and do not report an error.

If you are not satisfied with your output, submit the print job to a printer that supports Set Process Color drawing orders

APS2103I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE structured field STRUCTURED FIELD IN A PAGE DEFINITION IS MISSING A CMR DESCRIPTOR TRIPLET.

Explanation

When you specify a color management resource (CMR), a CMR Descriptor triplet (X'91') must immediately follow a Fully Qualified Name (FQN) triplet with an FQNTYPE of Data Object External Resource Reference (X'DE').

System action

PSF stops processing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field does not have an error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS2104I TOO MANY CMRS HAVE BEEN SPECIFIED.

Explanation

Too many color management resources (CMRs) were specified, which caused one of these conditions:

- On PSF for z/OS:
 - Too many specified in the Active Environment Group for a page to fit on the Logical Page Descriptor command.
 - Too many specified in a form definition to fit on the Invoke CMR command.
 - Too many specified for an IOCA, GOCA, BCOCA, or object container to fit on a WIC2, WGC, WBCC, or WOCC command.
 - Too many specified on an Include Object to fit on the IDO command.
 - Too many specified on a Preprocess Presentation Object (PPO) structured field to fit on the RPO command.
- On AFP Download Plus, too many specified in the data object resource access table (RAT) to fit on the IOB command or the PPO command.

System action

PSF stops processing the current page, attempts to find the end of the current page, and then tries to resume printing on the next page. If PSF cannot find the end of the page, it stops printing the data set. If this error occurs in a resource, PSF stops processing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

You must specify thousands of CMRs to create this condition. Contact the generator of your data stream to remove the extraneous CMRs.

APS2106I	DATA IN A FONT RESOURCE IS NOT VALID: THE RASTER PATTERN DATA COUNT IN THE FNC STRUCTURED FIELD IS NOT VALID.
-----------------	--

Explanation

While PSF was processing a font character set, it detected that bytes 17–19 of the Font Control (FNC) structured field contain a Raster Pattern Data Count that is specified incorrectly. The count is less than the total number of data bytes for all Font Patterns (FNG) structured fields; however, it must be the same.

System action

PSF cannot print the current page. PSF attempts to locate the end of the current page and resume printing on the next page. If the end of the current page cannot be located, PSF stops printing the data set. PSF issues a message identifying the position of the structured field in the input data stream or resource. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the font with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use

the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the font, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the font, contact your system programmer.

APS2107I	SET TEXT COLOR IS NOT SUPPORTED BY THIS PRINTER. THIS MESSAGE IS ONLY ISSUED ONCE PER PRINT DATA SET.
-----------------	--

Explanation

Text color is set by one of these:

- The Text Color Value in a page definition Line Descriptor (LND) structured field defines the color for text.
- An Include Object (IOB) structured field specifies a standard OCA color when it includes a PTOCA object with an OEG.

However, the printer you are using does not support the Set Text Color PTOCA control.

System action

- If the form definition indicates color fidelity stop, PSF stops processing the data set.
- If the form definition indicates color fidelity continue and report errors, PSF continues processing the data set and reports an error. A text color request is not sent to the printer.
- If the form definition indicates color fidelity continue and do not report an error, PSF continues processing the data set and does not report an error. A text color request is not sent to the printer.
- If the form definition does not indicate color fidelity, PSF continues processing the data set and does not report an error. A text color request is not sent to the printer.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

Delete text color requests from the separator page data set for this printer.

User response

If you are satisfied with your output and do not want to see this message, change your form definition to indicate color fidelity continue and do not report an error.

If you are not satisfied with your output, submit the print job to a printer that supports text colors.

APS2108I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A RESOURCE OTHER THAN A CMR HAS BEEN SPECIFIED IN AN MDR STRUCTURED FIELD FOR A FORM DEFINITION.

Explanation

Only color management resources (CMRs) can be specified in a Map Data Resource (MDR) structured field for a form definition.

System action

PSF stops processing the print job.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the form definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field does not have an error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS2109I SET EXTENDED TEXT COLOR IS NOT SUPPORTED BY THIS PRINTER. THIS MESSAGE IS ONLY ISSUED ONCE PER PRINT DATA SET.

Explanation

Extended text color is set by one of these:

- The Color Specification triplet (X'4E') in a page definition defines extended color for text.
- An Include Object (IOB) structured field specifies extended text color when it includes a PTOCA object with an OEG.

However, the printer you are using does not support the Set Extended Text Color PTOCA control.

System action

- If the form definition indicates color fidelity stop, PSF stops processing the data set.
- If the form definition indicates color fidelity continue and report errors, PSF continues processing the data set and reports an error. An extended text color request is not sent to the printer.
- If the form definition indicates color fidelity continue and do not report an error, PSF continues processing the data set and does not report an error. An extended text color request is not sent to the printer.
- If the form definition does not indicate color fidelity, PSF continues processing the data set and does not report an error. An extended text color request is not sent to the printer.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

Delete extended text color requests from the separator page data set for this printer.

User response

If you are satisfied with your output and do not want to see this message, change your form definition to indicate color fidelity continue and do not report an error.

If you are not satisfied with your output, submit the print job to a printer that supports extended text colors.

APS2110I THE SPECIFIED DEVICE APPEARANCE IS NOT SUPPORTED BY THIS PRINTER. THIS MESSAGE IS ONLY ISSUED ONCE PER PRINT DATA SET.

Explanation

Your printer either does not support the device appearance that was specified or it does not support the Device Appearance triplet (X'97'). Device appearance is specified in the form definition.

System action

- If the form definition indicates color fidelity stop, PSF stops processing the data set.
- If the form definition indicates color fidelity continue and report errors, PSF continues processing the data set and reports an error. The device appearance request is not sent to the printer.
- If the form definition indicates color fidelity continue and do not report an error, PSF continues processing the data set and does not report an error. The device appearance request is not sent to the printer.
- If the form definition does not indicate color fidelity, PSF continues processing the data set and reports an error. The device appearance request is not sent to the printer.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

Delete device appearance from the separator page form definition for this printer.

User response

If you are satisfied with your output and do not want to see this message, change your form definition to indicate color fidelity continue and do not report an error.

If you are not satisfied with your output, submit the print job to a printer that supports the device appearance specified.

APS2111I DATA IN A CODE PAGE RESOURCE IS NOT VALID: A CPI STRUCTURED FIELD IN CODE PAGE *code page* HAS AN INCORRECT REPEATING GROUP LENGTH.

Explanation

The Code Page Index (CPI) structured field has a repeating group with an incorrect length.

System action

PSF stops processing the current page. PSF attempts to find the end of the current page and continue printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF issues a message that identifies the position of the structured field in the code page resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the code page with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the code page, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field is correct, the error might be a PSF logic error. If you used a program to create the structured fields for the code page, contact your system programmer.

APS2112I CMR TAG FIDELITY WAS REQUESTED BUT CMR TAG FIDELITY IS NOT SUPPORTED BY THIS PRINTER. PROCESSING OF THE DATA SET HAS STOPPED.

Explanation

The user requested Color Management Resource (CMR) Tag fidelity with a continuation exception rule of

stop. However, the printer does not support CMR Tag fidelity so PSF stops processing the data set.

System action

PSF stops processing this data set and returns it to JES to be held.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Submit the print job to a printer that supports CMR Tag fidelity. Contact your operator to determine which printers support CMR Tag fidelity.

APS2113I CMR TAG FIDELITY WAS REQUESTED BUT CMR TAG FIDELITY IS NOT SUPPORTED BY THIS PRINTER. PROCESSING OF THE DATA SET CONTINUES.

Explanation

The user requested Color Management Resource (CMR) Tag fidelity with a continuation exception rule of continue; however, the printer does not support CMR Tag fidelity. Therefore, unsupported or incorrect CMR Tags cannot be reported, even though PSF continues to process the data set.

System action

PSF processes this data set without CMR Tag fidelity.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

No response is necessary.

APS2114I DATA IN A CODE PAGE RESOURCE IS NOT VALID: THE SORT ORDER FLAG IN THE CPC STRUCTURED FIELD IS INCORRECT.

Explanation

The sort order flag in the Code Page Control (CPC) structured field is incorrect for the code page resource. A single-byte code page must have the Code Page Index (CPI) repeating groups sorted in ascending character ID order. A double-byte code page must have the CPI repeating groups sorted in ascending code point order.

System action

PSF stops processing the current page. PSF attempts to find the end of the current page and continue printing on the next page. If unable to find the end of the page, PSF stops printing the data set.

PSF issues a message that identifies the position of the structured field in the code page resource. PSF issues more messages that identify the processing environment in which the error occurred.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the code page with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the code page, correct the error and resubmit the print request. See *Font Object Content Architecture Reference* for more information about the structured field. If the structured field is correct, the error might be a PSF logic error. If you used a program to create the structured fields for the code page, contact your system programmer.

APS2116I DATA IN A PAGEDEF RESOURCE IS NOT VALID: CONFLICTING SEQUENCE NUMBER TYPES HAVE BEEN SPECIFIED FOR A CONCATENATED BAR CODE ON A (structured field) STRUCTURED FIELD.

Explanation

All segments of a given concatenated bar code must specify the same type of sequence numbering. All segments must specify either sequence numbers or no sequence numbers. Concatenated bar code sequence numbers are part of the Concatenate Bar Code Data triplet (X'93'), which is specified on a Line Descriptor (LND), Record Descriptor (RCD), or XML Descriptor (XMD) structured field.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the page definition with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the page definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* and *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the page definition, contact your system programmer.

APS2119I	A PTOCA OBJECT WITH AN OEG IS NOT SUPPORTED BY THE PRINTER, PSF, OR BOTH. THIS MESSAGE IS ONLY ISSUED ONCE PER PRINT DATA SET OR RESOURCE.
-----------------	---

Explanation

The printer, PSF, or both do not support Presentation Text Object Content Architecture (PTOCA) objects with an Object Environment Group (OEG).

System action

PSF stops processing the current page, then tries to find the end of the current page and resume printing on the next page. If it cannot find the end of the page, PSF stops printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

This message indicates that the print data set contains PTOCA objects with an OEG. Either PSF, the printer, or both do not support these types of objects. Confirm the support of PSF and the printer to decide which one does not support these objects:

- If your release of PSF is 4.4 or earlier, install PSF 4.5 or later.
- If the printer does not support this function, determine whether the job can be sent to a different printer that has the function or if an engineering change (EC) is available to upgrade the microcode on the printer. To determine the printer's level of support, use the display printer information function in PSF. If X'2001' (Text Object support) is returned in the Sense Type and Model (STM) reply, the printer supports this function.

User response

Submit this job to a printer that supports PTOCA objects with an OEG. For information about what object types your printer supports, see your printer's documentation. To determine the release of PSF, contact your system programmer.

APS2120I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE INITIAL TEXT CONDITIONS IN THE PTD STRUCTURED FIELD ARE INCORRECT.
-----------------	---

Explanation

The Presentation Text Descriptor (PTD) structured field is in the Object Environment Group (OEG) of a PTOCA object with an OEG. This object can be in a page, overlay, or a resource.

System action

PSF stops processing the current page, then tries to find the end of the current page and resume printing on the next page. If it cannot find the end of the page, PSF stops printing the data set. If this error occurs in a resource, PSF stops processing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the print data set or resource, correct the error and resubmit the print request. See the *Presentation Text Object Content Architecture Reference* for more information about the correct format of the initial text conditions on the Presentation Text Data Descriptor (PTD) structured field. If the structured field is correct, the error might be a PSF logic error. If you used a program to create the structured fields for the print data set or resource, contact your system programmer.

APS2121I	DATA WAS FOUND AFTER AN END PRINT FILE (EPF) STRUCTURED FIELD WHEN AN END OF FILE (EOF) WAS EXPECTED.
-----------------	--

Explanation

A Begin Print File (BPF) and End Print File (EPF) structured field pair was used to encapsulate the MO:DCA data stream; however, data was found outside of the BPF-EPF pair before the End of File (EOF) was found. The BPF-EPF pair must encapsulate all the data in a MO:DCA print file.

System action

PSF stops processing and printing the data set.

Operator response

No response is necessary.

System programmer response

If an IBM licensed program was used to create the structured fields for the BPF-EPF pair with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the MO:DCA print file, remove any data that follows the EPF structured field and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for information about the MO:DCA print file. If the MO:DCA print file has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the MO:DCA print file, contact your system programmer.

APS2122I	AFP DOWNLOAD PLUS DOES NOT ALLOW AN OVERLAY OR PAGE SEGMENT TO BE SUBMITTED AS PRINT DATA.
-----------------	---

Explanation

The data set that AFP Download Plus is processing contains a stand-alone overlay or page segment. MO:DCA print data that is produced with a stand-alone overlay or page segment is not valid.

System action

AFP Download Plus stops processing the current data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the data for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

Do not attempt to process a data set with a stand-alone overlay or page segment. See *Mixed Object Document Content Architecture Reference* for information about valid objects for AFP Download Plus.

APS2123I BI-LEVEL IO IMAGE COLOR OVERRIDE ON THE PPO STRUCTURED FIELD IS NOT SUPPORTED BY THIS PRINTER. THIS MESSAGE IS ONLY ISSUED ONCE PER DOCUMENT.

Explanation

The Color Specification triplet (X'4E') requests an override of the bi-level IO image color on the Preprocess Presentation Object (PPO) structured field. However, your printer does not support bi-level IO image color override for IOCA images.

System action

- If the form definition indicates color fidelity stop, PSF stops processing the data set.
- If the form definition indicates color fidelity continue and report errors, PSF continues processing the data set and reports an error. A bi-level IO image color override request is not sent to the printer.
- If the form definition indicates color fidelity continue and do not report an error, PSF continues processing the data set and does not report an error. A bi-level IO image color override request is not sent to the printer.
- If the form definition does not indicate color fidelity, PSF continues processing the data set and does not report an error. A bi-level IO image color override request is not sent to the printer.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

Delete bi-level IO image color override requests from the separator page data set for this printer.

User response

If you are satisfied with your output and do not want to see this message, change your form definition to

indicate color fidelity continue and do not report an error.

If you are not satisfied with your output, submit the print job to a printer that supports bi-level IO image color override.

To find a printer that supports bi-level IO image color override requests, search for the IPDS Sense Type and Model (STM) X'4403' property pair in a printer information report. The PRTINFO DD statement in the PSF startup procedure specifies the data set name that contains the reports.

APS2124I BI-LEVEL AND GRAYSCALE IMAGE COLOR DEFAULT OR OVERRIDE IS NOT SUPPORTED BY THIS PRINTER. THIS MESSAGE IS ONLY ISSUED ONCE PER DOCUMENT.

Explanation

Your printer does not support the bi-level and grayscale image color default or override for object containers. The Color Specification triplet (X'4E') in the following structured fields determines from where the object area coloring is requested:

- Preprocess Presentation Object (PPO) - override for the object container.
- Include Object (IOB) - override for the object container.
- Container Data Descriptor (CDD) - default for the object container.

System action

- If the form definition indicates color fidelity stop, PSF stops processing the data set.
- If the form definition indicates color fidelity continue and report errors, PSF continues processing the data set and reports an error. A bi-level and grayscale image color default or override request is not sent to the printer.
- If the form definition indicates color fidelity continue and do not report an error, PSF continues processing the data set and does not report an error. A bi-level and grayscale image color default or override request is not sent to the printer.
- If the form definition does not indicate color fidelity, PSF continues processing the data set and does not report an error. A bi-level and grayscale image color default or override request is not sent to the printer.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set,

or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

Delete bi-level and grayscale image color default or override requests from the separator page data set for this printer.

User response

If you are satisfied with your output and do not want to see this message, change your form definition to

indicate color fidelity continue and do not report an error.

If you are not satisfied with your output, submit the print job to a printer that supports bi-level and grayscale image color default or override requests.

To find a printer that supports bi-level and grayscale image color default or override requests, search for the IPDS Sense Type and Model (STM) X'5801' property pair in a printer information report. The PRTINFO DD statement in the PSF startup procedure specifies the data set name that contains the reports.

APS2500 to APS2599

APS2500I DATA IN A FORMDEF RESOURCE OR USER'S JCL IS NOT VALID: THE Y EXTENT SPECIFIED FOR THE MEDIA PRESENTATION SPACE IS NOT VALID OR IS UNSUPPORTED.

Explanation

The medium extent for the Y axis of the medium presentation space is not valid or is unsupported for the current printer configuration. Either the medium that is loaded in the input bin is not the correct length, or the Y extent value is incorrect.

The Y axis extent is specified in the Medium Descriptor (MDD) structured field in the form definition, or on the JCL OUTPUT statement with the FORMLen keyword.

System action

Processing of the data set stops. PSF releases the current data set back to JES and requests that it is held by the system.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure or that the user specified an incorrect FORMLen value on the JCL OUTPUT statement. Inform the user if you suspect the FORMLen value is incorrect; otherwise, inform your system programmer.

System programmer response:

User response

Verify that the proper medium is loaded in the printer for this data set. If a different medium needs to be loaded in the printer, contact your operator.

If the correct medium is loaded in the printer, then verify the Y extent value that is specified. If you specified the FORMLen keyword on your JCL OUTPUT, correct the value and resubmit the print request.

APS2501I DATA IN A FORMDEF RESOURCE IS NOT VALID: THE UNITS PER UNIT BASE SPECIFIED IN THE MEDIUM DESCRIPTOR STRUCTURED FIELD IS NOT VALID OR UNSUPPORTED.

Explanation

The units per unit base is not valid or is unsupported for the current printer configuration. The units per unit base is specified in the Medium Descriptor (MDD) structured field in the form definition.

System action

Processing of the data set stops. PSF releases the current data set back to JES and requests that it is held by the system.

Operator response:

System programmer response:

User response:

APS2502I DATA IN A FONT RESOURCE IS NOT VALID: THE METRIC ADJUSTMENT TRIPLET CONTAINS AN INCORRECT OR UNSUPPORTED VALUE.

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The unit base field contained an incorrect value.
2. The XUPUB or YUPUB field contained an incorrect or unsupported value.
3. The XUPUB value was not equal to the YUPUB value.

A metric adjustment triplet (X'79') is contained in a Coded Font Control (CFC) structured field.

System action

PSF stops processing and printing the data set.

Operator response

No response is necessary.

System programmer response:

User response:

APS2503I DATA IN A FONT RESOURCE IS NOT VALID: THE BASELINE ADJUSTMENT VALUE IS TOO LARGE OR TOO SMALL.

Explanation

The combination of the baseline offset adjustment value and a character's baseline offset value is beyond the range that the printer can handle. The baseline offset adjustment value is contained in a Metric Adjustment triplet. A Metric Adjustment triplet (X'79') is contained in a Coded Font Control (CFC) structured field.

System action

PSF stops processing and printing the data set.

Operator response

No response is necessary.

System programmer response:

User response:

APS2504I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A BEGIN TRANSPARENCY MASK PARAMETER IS OUT OF SEQUENCE IN AN IPD STRUCTURED FIELD.

Explanation

A Begin Transparency Mask parameter is out of sequence or appears more than once in an image or tile. A Begin Transparency Mask parameter is contained in an Image Picture Data (IPD) structured field.

System action:

Operator response:

System programmer response:

User response:

APS2505I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN END TRANSPARENCY MASK PARAMETER IS MISSING OR OUT OF SEQUENCE IN AN IPD STRUCTURED FIELD.

Explanation

An End Transparency Mask parameter is missing after a Begin Transparency Mask is encountered or is out of sequence. An End Transparency Mask parameter is contained in an Image Picture Data (IPD) structured field.

System action:

Operator response:

System programmer response:

User response:

APS2506I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN IMAGE DATA SELF-DEFINING FIELD IS NOT VALID IN AN IPD STRUCTURED FIELD.

Explanation

An Image Data self-defining field was specified in an IOCA image object but cannot be present because the Band Image parameter was specified. An Image Data self-defining field and a Band Image parameter are contained in an Image Picture Data (IPD) structured field.

System action:

Operator response:

System programmer response:

User response:

APS2507I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: BOTH A BAND IMAGE PARAMETER AND AN IMAGE SUBSAMPLING PARAMETER WERE SPECIFIED IN AN IPD STRUCTURED FIELD. ONLY ONE IS ALLOWED.

Explanation

A Band Image parameter was specified in an IOCA image object and a subsequent Image Subsampling parameter was also found in the same image object. A Band Image parameter and an Image Subsampling parameter cannot coexist in the same image object. A Band Image parameter and an Image Subsampling parameter are contained in an Image Picture Data (IPD) structured field.

System action:**Operator response:****System programmer response:****User response:**

APS2508I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A BAND IMAGE PARAMETER IS OUT OF SEQUENCE IN AN IPD STRUCTURED FIELD.
-----------------	--

Explanation

A Band Image parameter was encountered out of sequence or appeared more than once in IOCA image object.

System action:**Operator response:****System programmer response:****User response:**

APS2509I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A BAND IMAGE PARAMETER VALUE IN AN IPD STRUCTURED FIELD IS NOT VALID OR IS UNSUPPORTED.
-----------------	--

Explanation

A Band Image parameter value in an Image Picture Data (IPD) structured field is not valid or is not supported.

System action:**Operator response:****System programmer response:****User response:**

APS2510I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: BAND IMAGE PARAMETER VALUES IN AN IPD STRUCTURED FIELD ARE INCONSISTENT.
-----------------	---

Explanation

The number of BITCNT parameters in a Band Image parameter is not equal to the BCOUNT value. A Band Image parameter is contained in an Image Picture Data (IPD) structured field.

System action:**Operator response:****System programmer response:****User response:**

APS2511I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A BAND IMAGE PARAMETER IN AN IPD STRUCTURED FIELD IS INCONSISTENT WITH THE IDE SIZE PARAMETER.
-----------------	---

Explanation

The IDE size that is determined by the Band Image parameter (after padding bits are subtracted) does not match the IDE Size parameter. A Band Image parameter is contained in an Image Picture Data (IPD) structured field.

System action:**Operator response:****System programmer response:****User response:**

APS2512I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN IDE STRUCTURE PARAMETER IN AN IPD STRUCTURED FIELD IS OUT OF SEQUENCE.
-----------------	--

Explanation

An IDE Structure parameter was encountered out of sequence or appears more than once. An IDE Structure parameter is contained in an Image Picture Data (IPD) structured field.

System action:**Operator response:****System programmer response:****User response:**

APS2513I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN IDE STRUCTURE PARAMETER IN AN IPD STRUCTURED FIELD IS NOT VALID OR IS UNSUPPORTED.
-----------------	--

Explanation

A value in an IDE Structure parameter is not valid or is not supported. An IDE Structure parameter is contained in an Image Picture Data (IPD) structured field.

System action:**Operator response:****System programmer response:****User response:**

APS2514I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE IDE STRUCTURE PARAMETER IN AN IPD STRUCTURED FIELD IS NOT VALID.

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The sum of the SIZE1 through SIZE4 values in an IDE Structure parameter does not match the IDE size specified in the IDE Size parameter.
2. The color space is CMYK and SIZE4 is missing.
3. SIZE4 is present and the color space is not CMYK.

An IDE Structure parameter and IDE Size parameter are contained in an Image Picture Data (IPD) structured field.

System action:**Operator response:****System programmer response:****User response:**

APS2515I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A BAND IMAGE DATA SELF-DEFINING FIELD WAS SPECIFIED WITHOUT A BAND IMAGE PARAMETER BEING SPECIFIED.

Explanation

A Band Image Data self-defining field was specified that cannot be present because the Band Image parameter was not specified. A Band Image Data self-defining field and a Band Image parameter are contained in an Image Picture Data (IPD) structured field.

System action:**Operator response:****System programmer response:****User response:**

APS2516I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A BAND IMAGE DATA SELF-DEFINING FIELD IS MISSING OR OUT OF SEQUENCE.

Explanation

A Band Image Data self-defining field was missing or encountered out of sequence. When a Band Image parameter is specified, one or more Band Image Data self-defining fields must appear after image data parameters and before End Image Content. A Band Image Data self-defining field is contained in an Image Picture Data (IPD) structured field.

System action:**Operator response:****System programmer response:****User response:**

APS2517I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN INCORRECT NUMBER OR SEQUENCE OF BAND IMAGE DATA SELF-DEFINING FIELDS WERE SPECIFIED IN AN IPD STRUCTURED FIELD.

Explanation

Either some of the bands specified in the Band Image parameter were missing in the Band Image Data or the Band Image Data self-defining fields were not in the sequential order of the band numbers. A Band Image Data self-defining field is contained in an Image Picture Data (IPD) structured field.

System action:**Operator response:****System programmer response:****User response:**

APS2518I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN INCONSISTENT EXTERNAL ALGORITHM SPECIFICATION PARAMETER AND IMAGE ENCODING PARAMETER WERE SPECIFIED IN AN IPD STRUCTURED FIELD.

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. An External Algorithm Specification parameter was specified in an IOCA image object, but a corresponding Image Encoding parameter was not found.
2. An Image Encoding Parameter was specified in an IOCA image object that requires an External Algorithm Specification Parameter, but no External Algorithm Parameter was found.

An External Algorithm Specification parameter and an Image Encoding parameter are contained in an Image Picture Data (IPD) structured field.

System action:

Operator response:

System programmer response:

User response:

APS2519I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN EXTERNAL ALGORITHM SPECIFICATION PARAMETER IN AN IPD STRUCTURED FIELD IS OUT OF SEQUENCE.
-----------------	---

Explanation

An External Algorithm Specification parameter was encountered out of sequence or appeared more than once. An External Algorithm Specification parameter is contained in an Image Picture Data (IPD) structured field.

System action:

Operator response:

System programmer response:

User response:

APS2520I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN EXTERNAL ALGORITHM SPECIFICATION PARAMETER VALUE IN AN IPD STRUCTURED FIELD IS NOT VALID OR IS UNSUPPORTED.
-----------------	---

Explanation

A value in an External Algorithm parameter is not valid or is unsupported. An External Algorithm Specification

parameter is contained in an Image Picture Data (IPD) structured field.

System action:

Operator response:

System programmer response:

User response:

APS2521I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN EXTERNAL ALGORITHM SPECIFICATION PARAMETER WAS SPECIFIED IN AN IPD STRUCTURED FIELD THAT IS NOT REQUIRED.
-----------------	---

Explanation

An External Algorithm parameter was specified in the image, but the Image Encoding parameter does not require it. An External Algorithm Specification parameter is contained in an Image Picture Data (IPD) structured field.

System action:

Operator response:

System programmer response:

User response:

APS2522I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A TILE POSITION PARAMETER IN AN IPD STRUCTURED FIELD IS MISSING OR OUT OF SEQUENCE.
-----------------	--

Explanation

A required Tile Position parameter is missing or was encountered out of sequence. A Tile Position parameter is contained in an Image Picture Data (IPD) structured field.

System action:

Operator response:

System programmer response:

User response:

APS2523I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A TILE POSITION PARAMETER VALUE IN AN IPD STRUCTURED FIELD IS NOT VALID.
-----------------	---

Explanation

An XOFFSET or YOFFSET value in a Tile Position parameter is not valid or is outside the image

presentation space. A Tile Position parameter is contained in an Image Picture Data (IPD) structured field.

System action:

Operator response:

System programmer response:

User response:

APS2524I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: TILE POSITION PARAMETER VALUES IN AN IPD STRUCTURED FIELD ARE INCONSISTENT.

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. Tiles are specified out of order. This exception can occur only if the Tile Table of Contents (TOC) parameter does not contain any TOC entries. If the Tile TOC parameter does contain TOC entries, the tiles themselves can be specified in any order.
2. The Tile TOC parameter does contain the table of contents, but the XOFFSET or YOFFSET given for this tile in the table of contents does not match the corresponding values specified in the Tile Position parameter.

A Tile Position parameter is contained in an Image Picture Data (IPD) structured field.

System action:

Operator response:

System programmer response:

User response:

APS2525I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A TILE SIZE PARAMETER IN AN IPD STRUCTURED FIELD IS MISSING OR OUT OF SEQUENCE.

Explanation

A required Tile Size parameter is missing or was encountered out of sequence. A Tile Size parameter is contained in an Image Picture Data (IPD) structured field.

System action:

Operator response:

System programmer response:

User response:

APS2526I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A TILE SIZE PARAMETER VALUE IN AN IPD STRUCTURED FIELD IS NOT VALID.

Explanation

A value in a Tile Size parameter is not valid. A Tile Size parameter is contained in an Image Picture Data (IPD) structured field.

System action:

Operator response:

System programmer response:

User response:

APS2527I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A TILE SIZE PARAMETER VALUE IN AN IPD STRUCTURED FIELD IS INCONSISTENT.

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The tile overlaps a previously specified tile.
2. The RELRES value that is specified in the table of contents does not match the corresponding RELRES value in the Tile Size parameter.
3. The THSIZE or TVSIZE specified in the table of contents does not match the corresponding value in the Tile Size parameter.

A Tile Size parameter and the Tile table of contents are contained in an Image Picture Data (IPD) structured field.

System action:

Operator response:

System programmer response:

User response:

APS2528I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A TILE SET COLOR PARAMETER IN AN IPD STRUCTURED FIELD IS OUT OF SEQUENCE.

Explanation

A Tile Set Color parameter was encountered out of sequence or appeared more than once. A Tile Set Color parameter is contained in an Image Picture Data (IPD) structured field.

System action:

Operator response:

System programmer response:

User response:

APS2529I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A TILE SET COLOR PARAMETER VALUE IN AN IPD STRUCTURED FIELD IS INCONSISTENT.

Explanation

A Tile Set Color parameter was specified once in the correct sequence, but the tile was not a bi-level tile. The IDE Size parameter, if specified, must specify an IDE size of 1 bit per IDE. The IDE Structured parameter, if specified, must specify a color space of either YCrCb or YCbCr. A Tile Set Color parameter is contained in an Image Picture Data (IPD) structured field.

System action:

Operator response:

System programmer response:

User response:

APS2530I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A TILE TOC PARAMETER IN AN IPD STRUCTURED FIELD IS OUT OF SEQUENCE.

Explanation

In a tiled image, the Tile Table of Contents (TOC) parameter did not appear immediately after a Begin Image Content self-defining field, or it appeared more than once. A Tile TOC parameter is contained in an Image Picture Data (IPD) structured field.

System action:

Operator response:

System programmer response:

User response:

APS2531I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A TILE TOC PARAMETER VALUE IN AN

IPD STRUCTURED FIELD IS NOT VALID.**Explanation**

A value in a Tile Table of Contents (TOC) parameter is not valid. A Tile TOC parameter is contained in an Image Picture Data (IPD) structured field.

System action:

Operator response:

System programmer response:

User response:

APS2532I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A TILE TOC PARAMETER VALUE IN AN IPD STRUCTURED FIELD IS INCONSISTENT.

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. Not all tiles are listed in the table of contents, even though the table of contents contains at least one tile.
2. The table of contents lists a non-existent tile.
3. An incorrect tile order was specified; two or more tiles in the table of contents have sort keys (primary: YOFFSET; secondary: XOFFSET) that are identical or are out of sequence.
4. The specified offset for one or more tiles does not point to a position where a Begin Tile parameter starts.

A Tile TOC parameter is contained in an Image Picture Data (IPD) structured field.

System action:

Operator response:

System programmer response:

User response:

APS2533I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN IMAGE SUBSAMPLING PARAMETER AND A BAND IMAGE PARAMETER IN AN IPD STRUCTURED FIELD ARE INCONSISTENT.

Explanation

An Image Subsampling parameter was specified in an IOCA image object and a subsequent Band Image parameter was also found. A Band Image parameter and an Image Subsampling parameter cannot coexist in the same image. An Image Subsampling parameter and Band Image parameter are contained in an Image Picture Data (IPD) structured field.

System action:**Operator response:****System programmer response:****User response:**

APS2534I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN IMAGE SUBSAMPLING PARAMETER IN AN IPD STRUCTURED FIELD IS OUT OF SEQUENCE.

Explanation

An Image Subsampling parameter was encountered out of sequence or appeared more than once. An Image Subsampling parameter and Begin Image Content parameter are contained in an Image Picture Data (IPD) structured field.

System action:**Operator response:****System programmer response:****User response:**

APS2535I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN IMAGE SUBSAMPLING PARAMETER VALUE IN AN IPD STRUCTURED FIELD IS NOT VALID OR IS UNSUPPORTED.

Explanation

A value in an Image Subsampling parameter is not valid or is not supported. An Image Subsampling parameter is contained in an Image Picture Data (IPD) structured field.

System action:**Operator response:****System programmer response:****User response:**

APS2536I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A COLOR PALETTE PARAMETER IN

AN IPD STRUCTURED FIELD IS OUT OF SEQUENCE.**Explanation**

A Color Palette parameter was encountered out of sequence or appeared more than once. A Color Palette parameter is contained in an Image Picture Data (IPD) structured field.

System action:**Operator response:****System programmer response:****User response:**

APS2537I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A COLOR PALETTE PARAMETER IN AN IPD STRUCTURED FIELD IS NOT VALID OR IS UNSUPPORTED.

Explanation

A value in a Color Palette parameter is not valid or is not supported. A Color Palette parameter is contained in an Image Picture Data (IPD) structured field.

System action:**Operator response:****System programmer response:****User response:**

APS2538I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A BEGIN TILE PARAMETER IS OUT OF SEQUENCE IN AN IPD STRUCTURED FIELD.

Explanation

A Begin Tile parameter was encountered out of sequence in a series of Image Picture Data (IPD) structured fields.

System action:**Operator response:****System programmer response:****User response:**

APS2539I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN END TILE PARAMETER IS MISSING OR OUT OF SEQUENCE IN AN IPD STRUCTURED FIELD.

Explanation

An End Tile parameter is missing after a Begin Tile parameter is encountered, or it is out of sequence in a series of Image Picture Data (IPD) structured fields.

System action:

Operator response:

System programmer response:

User response:

APS2540I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A TILE SET COLOR PARAMETER VALUE IN AN IPD STRUCTURED FIELD IS NOT VALID.

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The color space (CSPACE) value that is specified is not valid.
2. The size value that is specified is not valid.
3. The color value that is specified is not valid.

A Tile Set Color parameter is contained in an Image Picture Data (IPD) structured field.

System action:

Operator response:

System programmer response:

User response:

APS2541I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A MAPPING OPTION VALUE IS NOT VALID OR IS UNSUPPORTED.

Explanation

The Mapping Option specified was not valid, or the printer does not support the Mapping Option value. The Mapping Option was specified on an Include Object (IOB), a Map Graphics Object (MGO), a Map Bar Code (MBC), a Map Image Object (MIO), or a Map Presentation Text (MPT) structured field. The IOB, MGO, MIO, and MPT structured fields can be contained in a page definition, a resource object, an overlay, or a MO:DCA page, or they can be embedded in line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the

page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. If the structured field was part of a resource, PSF stops processing and printing the data set.

Operator response:

System programmer response

If an IBM licensed program was used to create the structured fields for the object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you created the structured fields for the object, correct the error and resubmit the print request. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the object, contact your system programmer.

APS2542I THE PRESENTATION DATA IN AN OBJECT CONTAINER RESOURCE EXTENDS OUTSIDE THE OBJECT AREA.

Explanation

A position mapping was used that caused some portion of the object data to extend outside of the object area. The presentation space is specified in the object data. The object area size can be specified in an Object Area Descriptor (OBD) in an Object Environment Group (OEG) for the object container or in an Include Object (IOB) structured field.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response:

System programmer response:

User response

Either increase the object area size or change the offset specified for the position mapping and resubmit the print request. Changing the mapping option to position and trim can show where the object data is hitting the object boundary. See the appropriate documentation for the data stream that is carried in the object container resource. If you used a program to create the structured fields and the data, contact your system programmer.

APS2543I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE HAXIS OR VAXIS PARAMETER OF A BOX OR BOX AT CURRENT POSITION DRAWING ORDER IS TOO LARGE.

Explanation

A Box or Box at Current Position drawing order in a Graphics Data (GAD) structured field contains an HAXIS or VAXIS parameter that is too large to fit the indicated corner into the size of the box.

The GAD structured field is contained in a graphics object. The graphics object can be contained in a MO:DCA document or an overlay or it might be embedded in a data set containing line data.

System action:

Operator response:

System programmer response:

User response

If the structured fields are not valid and you created the structured fields for the resource or print data set containing the graphics object, correct the error in the referenced structured field and resubmit the print request. See *Graphics Object Content Architecture for AFP Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the resource or print data set containing the image, contact your system programmer.

APS2544I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: EITHER THE HAXIS OR VAXIS PARAMETER OF A BOX OR BOX AT CURRENT POSITION DRAWING ORDER IS OUTSIDE THE VALID RANGE.

Explanation

A Box or Box at Current Position drawing order in a Graphics Data (GAD) structured field contains an

HAXIS or VAXIS parameter that is outside the valid range.

The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay or it might be embedded in a data set containing line data.

System action:

Operator response:

System programmer response:

User response

If the structured fields are not valid and you created the structured fields for the resource or print data set containing the graphics object, correct the error in the referenced structured field and resubmit the print request. See *Graphics Object Content Architecture for AFP Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the resource or print data set containing the image, contact your system programmer.

APS2545I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE POSITION FOR THE ENDPOINT OF THE ARC IN A PARTIAL ARC OR PARTIAL ARC AT CURRENT POSITION DRAWING ORDER IS OUTSIDE THE PRESENTATION SPACE.

Explanation

In a partial Arc or Partial Arc at Current Position drawing order, the calculated new current position for the endpoint of the arc is outside the limits of the graphic presentation space.

The Partial Arc and Partial Arc at Current Position drawing orders are contained in the Graphics Data (GAD) structured field. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay or it might be embedded in a data set containing line data.

System action:

Operator response:

System programmer response:

User response

If the structured fields are not valid and you created the structured fields for the resource or print data set containing the graphics object, correct the error in the

referenced structured field and resubmit the print request. See *Graphics Object Content Architecture for AFP Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the resource or print data set containing the image, contact your system programmer.

APS2546I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: IN A PARTIAL ARC OR PARTIAL ARC AT CURRENT POSITION DRAWING ORDER, THE SWEEP ANGLE IS NOT VALID.

Explanation

In a Partial Arc or Partial Arc at Current Position drawing order, the SWEEP angle is not valid (negative).

The Partial Arc and Partial Arc at Current Position drawing orders are contained in the Graphics Data (GAD) structured field. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay or it might be embedded in a data set containing line data.

System action:

Operator response:

System programmer response:

User response

If the structured fields are not valid and you created the structured fields for the resource or print data set containing the graphics object, correct the error in the referenced structured field and resubmit the print request. See *Graphics Object Content Architecture for AFP Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the resource or print data set containing the image, contact your system programmer.

APS2547I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: IN A PARTIAL ARC OR PARTIAL ARC AT CURRENT POSITION DRAWING ORDER, THE START ANGLE IS NOT VALID.

Explanation

In a Partial Arc or Partial Arc at Current Position drawing order, the START angle is not valid (negative).

The Partial Arc and Partial Arc at Current Position drawing orders are contained in the Graphics Data (GAD) structured field. The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay or it might be embedded in a data set containing line data.

System action:

Operator response:

System programmer response:

User response

If the structured fields are not valid and you created the structured fields for the resource or print data set containing the graphics object, correct the error in the referenced structured field and resubmit the print request. See *Graphics Object Content Architecture for AFP Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the resource or print data set containing the image, contact your system programmer.

APS2548I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A PORTION OF A CHARACTER WILL EXTEND BEYOND THE TEXT PRESENTATION SPACE BOUNDARY.

Explanation

A character is positioned so that a portion of its character box exceeds the Text Presentation Space boundary in either the i-direction or b-direction.

The text-control sequence is in a Presentation Text Data (PTX) structured field or was generated by PSF from a page definition. The size of the presentation text space is defined in the Presentation Text Descriptor (PTD) structured field.

The PTX structured field might be contained or referenced in a MO:DCA document, a resource, or it might be embedded in a data set containing line data. The PTD might be specified in either the Object Environment Group (OEG) for the presentation text object or the Active Environment Group (AEG) for the page or overlay.

System action:

Operator response:

System programmer response:

User response

If the structured fields are not valid and you created the structured fields for the resource or print data set, correct the error in the referenced structured field and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the resource or print data set containing the image, contact your system programmer.

APS2549I **A DATA-VALIDATION DEVICE CONNECTED TO THE PRINTER HAS DETECTED UNREADABLE OR INCORRECTLY PRINTED DATA. PARTIAL OR DUPLICATE PAGES MIGHT BE PRINTED.**

Explanation

A data-validation device that is connected to the printer detected unreadable or incorrectly printed data. This caused the printer to discard its buffered pages. The printer reports an action code X'1A' to instruct PSF to redrive buffered pages. For more information about this condition, see the publications for the printer that reported this error.

System action

PSF resends pages to the printer, starting from the committed page counter plus 1. Pages might be duplicated during the recovery.

If the current environment does not support repositioning, PSF stops processing the data set.

Operator response

Inform your system programmer that this error occurred.

System programmer response

If a function was not selected at the printer and the error condition persists, follow the procedures that are described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

The printed output might be acceptable. If any pages were duplicated, you might want to resubmit the print request. If the error persists, contact your system programmer.

APS2550I **THE PUNCH WASTE BIN ON A PRINTER THAT SUPPORTS THE PUNCH OPERATION HAS BECOME**

FULL. PARTIAL OR DUPLICATE PAGES MIGHT BE PRINTED.

Explanation

The punch waste bin on a printer that supports the punch operation is full. This caused the printer to discard its buffered pages. The printer reports an action code X'1A' to instruct PSF to redrive buffered pages. For more information about this condition, see the publications for the printer that reported this error.

System action

PSF resends pages to the printer, starting from the committed page counter plus 1. Pages might be duplicated during the recovery.

If the current environment does not support repositioning, PSF stops processing the data set.

Operator response

Inform your system programmer that this error occurred.

System programmer response

If a function was not selected at the printer and the error condition persists, follow the procedures that are described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

The printed output might be acceptable. If any pages were duplicated, you might want to resubmit the print request. If the error persists, contact your system programmer.

APS2551I **THE DATA IN A PRESENTATION OBJECT CONTAINER RESOURCE WAS CONSIDERED INCORRECT BY THE PRINTER. CODE = (code and brief description).**

Explanation

The data in an object container resource was not considered valid by the printer, although the printer supports the resource type as identified by the Object Classification triplet on the Begin Object Container structured field.

For a complete list of the error codes and descriptions, see *Intelligent Printer Data Stream Reference*.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the

page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the correct format of the referenced structured field. If the structured field is correct, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the resource, contact your system programmer.

APS2552I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN INCLUDE TILE PARAMETER IS SPECIFIED WITHIN AN IOCA TILE RESOURCE.

Explanation

An Include Tile Parameter was specified in an IOCA tile resource. Nested references are not allowed. The Include Tile Parameter is contained in an Image Picture Data (IPD) structured field. The IPD structured field is contained in an IOCA image object. The IOCA image data object might be included in a MO:DCA document, an overlay, a page segment, or an object container, or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the print data set or resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field is correct, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the print data set or resource, contact your system programmer.

APS2553I THE DATA IN AN OBJECT CONTAINER RESOURCE WAS CONSIDERED INCORRECT BY THE PRINTER. CODE = (code and brief description).

Explanation

The data in an object container resource was not considered valid by the printer, although the printer supports the resource type as identified by the Object Classification triplet on the Begin Object Container structured field.

For a complete list of the error codes and descriptions, see *Intelligent Printer Data Stream Reference*.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the data in the structured fields of the object container resource, correct the error and resubmit the print request. See the appropriate documentation for the data stream that is carried in the object container resource. If you used a program to create the structured fields and the data, contact your system programmer.

APS2554I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A SECONDARY DATA OBJECT RESOURCE WAS NOT FOUND.

Explanation

While printing a data object, an error occurred with a secondary resource. When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. A presentation data object referenced a data object resource by an internal name, but no X'DE', X'BE' pair existed on the Include Object (IOB) to identify the secondary resource's external name.

2. A presentation data object referenced a data object resource by an internal name. This internal name was mapped to an external name by a X'DE', X'BE' pair on the Include Object (IOB), but the resource identified by the external name was not mapped in the Active Environment Group (AEG) for the page.
3. A presentation data object referenced a data object resource by an external name, but this external name was not mapped in the Active Environment Group (AEG) for the page.

The data object might be included in a MO:DCA document, an overlay, or an object container or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the print data set or resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the correct format of the referenced structured field. If the structured field is correct, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the print data set or resource, contact your system programmer.

APS2555I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN INCLUDE TILE PARAMETER IS OUT OF SEQUENCE.**Explanation**

An Include Tile Parameter was encountered out of sequence or appeared more than once. An Include Tile Parameter must appear immediately after a Tile Position Parameter. The Include Tile Parameter is contained in an Image Picture Data (IPD) structured field. The IPD structured field is contained in an IOCA image object. The IOCA image object might be included in a MO:DCA document, an overlay, a page segment, or an object container or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the image object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the correct format of the referenced structured field. If the structured field is correct, the error might be a PSF or

printer logic error. If you used a program to create the structured fields for the image object, contact your system programmer.

APS2556I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: INAPPROPRIATE SECONDARY RESOURCE INVOKED FOR A DATA OBJECT.**Explanation**

A data object resource was called for a presentation data object, but it is not a valid object type for that data object. The data object might be included in a MO:DCA document, an overlay, or an object container, or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the print data set or resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the correct format of the referenced structured field. If the

structured field is correct, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the print data set or resource, contact your system programmer.

APS2557I THE PRINTER HAS DETECTED A DATA-RELATED DECOMPRESSION ERROR.

Explanation

The printer detected a data-related error on a page when it was extracting data. Incorrectly compressed JPEG image data in a data object or an IOCA image can cause this error.

The image object might be contained in a MO:DCA document, an overlay, or a page segment; or it might be embedded in a data set containing line data. The data object might be included in a MO:DCA document, an overlay, or an object container, or it might be embedded in a data set containing line data.

System action

PSF stops processing the current data set, releases it back to JES, and requests that it is held by the system unless PRTEROR=QUIT is specified on the OUTPUT statement

Operator response

See the operator's guide for the printer that reported this error, and clear any paper that is not stacked. If you are running under JES, use the JES commands to release the data set to a printer that supports the finishing operation. For information about the command to use to release the data set, see the publication that contains JES commands for your operating system.

System programmer response

If an IBM licensed program was used to create the structured fields for the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

Do one of these:

- If you created the structured fields of the object container or image object resource, correct the error and resubmit the print request. See the appropriate documentation for the data stream that is carried in

the object container or image object resource. If you used a program to create the structured fields and the data, contact your system programmer.

- Contact your operator to determine which printers the data set can be rerouted to. If no printers are available that can process the job, ask the operator to purge the job. Then, correct the error and resubmit the print request.

APS2558I THE PRINTER HAS DETECTED A DATA-RELATED DECOMPRESSION ERROR.

Explanation

The printer detected a data-related error on a page when it was extracting data. Incorrectly compressed JPEG image data in a data object or an IOCA image can cause this error.

The image object might be contained in a MO:DCA document, an overlay, or a page segment; or it might be embedded in a data set containing line data. The data object might be included in a MO:DCA document, an overlay, or an object container, or it might be embedded in a data set containing line data.

System action

PSF stops processing the current data set, releases it back to JES, and requests that it is held by the system unless PRTEROR=QUIT is specified on the OUTPUT statement

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

If you are running under JES, use the JES commands to release the data set to a printer that supports the finishing operation. For information about the command to use to release the data set, see the publication that contains JES commands for your operating system.

System programmer response

If an IBM licensed program was used to create the structured fields for the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

Do one of these:

- If you created the data in the structured fields of the object container or image object resource, correct the error and resubmit the print request. See the appropriate documentation for the data stream that is carried in the object container resource. If you used a program to create the structured fields and the data, contact your system programmer.
- Contact your operator to determine which printers the data set can be rerouted to. If no printers are available that can process the job, ask the operator to purge the job. Then, correct the error and resubmit the print request.

APS2559I THE DATA IN A PRESENTATION OBJECT CONTAINER RESOURCE WAS CONSIDERED INCORRECT BY THE PRINTER. CODE = (code and brief description).

Explanation

The data in an object container resource was not considered valid by the printer, although the printer supports the resource type as identified by the Object Classification triplet on the Begin Object Container structured field.

For a complete list of the error codes and descriptions, see *Intelligent Printer Data Stream Reference*.

N (rightmost 4 bits) in the error code, for example, X'016N', contains the collection index value plus one. A value of X'0' indicates either that the object was a font or indicates that the collection index is not provided because it is greater than 15 (X'F'). If message APS830I is issued along with this message, then the Element Identifier contains the error code with the collection index.

System action

PSF stops processing the current data set and issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the object container resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the object container resource, contact your system programmer.

APS2560I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE OBJECT-AREA-ORIGIN-OFFSET VALUE SPECIFIED FOR A DATA OBJECT IS UNSUPPORTED.

Explanation

The X or Y object-area-origin-offset value that is specified in the Object Area Position (OBP) of the data object resource or in the IOB that included the object is unsupported.

The data object might be included in a MO:DCA document, an overlay, or an object container, or it might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the data object resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the data object resource, contact your system programmer.

APS2561I **A PROBLEM WITH THE PRINTER RIBBON HAS OCCURRED THAT REQUIRES OPERATOR INTERVENTION.**

Explanation

A problem with the printer ribbon occurred. This caused the printer to discard its buffered pages. The printer reports an action code X'1A' to instruct PSF to redrive buffered pages. For more information about this condition, see the publications for the printer that reported this error.

System action

PSF resends pages to the printer, starting from the committed page counter plus 1. Pages might be duplicated during the recovery.

If the current environment does not support repositioning, PSF stops processing the data set.

Operator response

Inform your system programmer that this error occurred.

System programmer response

If a function was not selected at the printer and the error condition persists, follow the procedures that are described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

The printed output might be acceptable. If any pages were duplicated, you might want to resubmit the print request. If the error persists, contact your system programmer.

APS2562I **THE PRINTER HAS REPORTED A CONDITION IN A POSTPROCESSOR THAT PSF DOES NOT RECOGNIZE.**

Explanation

The printer reported an action code X'0A' I/O error that PSF does not recognize. This message is accompanied by a message that presents the printer sense bytes.

System action

PSF stops processing and printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF.

System programmer response

If the error condition persists, follow the procedures that are described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

Inform your system programmer that this error occurred.

APS2563I **A PARAMETER VALUE IN A FORMDEF RESOURCE IS UNSUPPORTED: THE MEDIUM FINISHING CONTROL STRUCTURED FIELD SPECIFIES AN UNSUPPORTED FINISHING OPERATION COUNT VALUE.**

Explanation

The finishing operation count field (byte 6) in a Finishing Operation triplet (X'85') contains an unsupported value.

Finishing Operation triplets are specified in the Medium Finishing Control (MFC) structured field. The MFC is specified in the Document Environment Group of the form definition or in a Medium Map.

System action

Reporting of this exception can be controlled by the Finishing Fidelity triplet in the Presentation Fidelity Control (PFC) command. The PFC command is contained in a form definition.

When the Finishing Fidelity triplet sets the continuation rule to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and marks the data set unprintable. PSF releases the current data set back to JES and requests that it is held by the system unless PRTEROR=QUIT is specified on the OUTPUT statement.

When the Finishing Fidelity triplet sets the continuation rule to DO NOT STOP (X'02'), one of these occurs:

- If the printer supports the PFC Finishing Fidelity triplet and if the REPORT field is set to REPORT (X'01'), the printer reports this exception. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.
- If the printer supports the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.
- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer reports this exception but PSF does not issue the error message. The printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.
- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to REPORT (X'01'), the printer reports this exception and PSF issues the error message. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the MFC with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If the output is not acceptable, do one of these:

- Verify that you requested the appropriate form definition for the finishing operation intended.
- Submit the print request to a printer that can do the finishing operation.
- If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS2564I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A SET PRESENTATION SPACE SIZE SELF-DEFINING FIELD WAS SPECIFIED INCORRECTLY.

Explanation

One or more of these occurred in the Set Presentation Space self-defining field:

- The Xsize or Ysize field in a Set Presentation Space Size self-defining field is incorrect.
- Both Xsize and Ysize can be specified with 2 bytes. The values were not specified in Image Data Description (IDD) bytes 11-14 or the Set Presentation Space Size self-defining field was not specified.
- One or both of the size parameters in a Set Presentation Space Size self-defining field are

greater than X'7FFF', but the corresponding value or values that are specified in IDD bytes 11–14 are not set to X'7FFF'.

A Set Presentation Space Size self-defining field is contained in an IDD structured field.

The IDD structured field is contained in an IOCA image object. The IOCA image object might be contained in a MO:DCA document, an overlay, an object container, a data set containing line data, or a page segment, or might be included by an Include Object (IOB) structured field. A page segment is included by using an Include Page Segment (IPS) structured field or an IOB structured field.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the image object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the image object, contact your system programmer.

APS2565I

A PARAMETER VALUE IN A FORMDEF RESOURCE IS NOT VALID OR IS UNSUPPORTED: THE MEDIUM FINISHING CONTROL STRUCTURED FIELD SPECIFIES AN INCORRECT OR UNSUPPORTED FINISHING OPERATION AXIS OFFSET VALUE.

Explanation

The axis offset field (bytes 7–8) in a Finishing Operation triplet (X'85') contains an incorrect or unsupported value.

Finishing Operation triplets are specified in the Medium Finishing Control (MFC) structured field. The MFC is specified in the Document Environment Group of the form definition or in a Medium Map.

System action

Reporting of this exception can be controlled by the Finishing Fidelity triplet in the Presentation Fidelity Control (PFC) command. The PFC command is contained in a form definition.

When the Finishing Fidelity triplet sets the continuation rule to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and marks the data set unprintable. PSF releases the current data set back to JES and requests that it is held by the system unless PRTEROR=QUIT is specified on the OUTPUT statement.

When the Finishing Fidelity triplet sets the continuation rule to DO NOT STOP (X'02'), one of these occurs:

- If the printer supports the PFC Finishing Fidelity triplet and if the REPORT field is set to REPORT (X'01'), the printer reports this exception. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.
- If the printer supports the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.
- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer reports this exception but PSF does not issue the error message. The

printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to REPORT (X'01'), the printer reports this exception and PSF issues the error message. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the MFC with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If the output is not acceptable:

- Verify that you requested the appropriate form definition for the finishing operation intended.
- Submit the print request to a printer that can do the finishing operation.
- If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS2566I

A PARAMETER VALUE IN A FORMDEF RESOURCE IS NOT VALID OR IS UNSUPPORTED: THE MEDIUM FINISHING CONTROL STRUCTURED FIELD SPECIFIES AN INCORRECT OR UNSUPPORTED FINISHING OPERATION POSITION VALUE.

Explanation

A finishing operation position field in a Finishing Operation triplet (X'85') contains an incorrect or unsupported value.

Finishing Operation triplets are specified in the Medium Finishing Control (MFC) structured field. The MFC is specified in the Document Environment Group of the form definition or in a Medium Map.

System action

Reporting of this exception can be controlled by the Finishing Fidelity triplet in the Presentation Fidelity Control (PFC) command. The PFC command is contained in a form definition.

When the Finishing Fidelity triplet sets the continuation rule to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and marks the data set unprintable. PSF releases the current data set back to JES and requests that it is held by the system unless PRTEROR=QUIT is specified on the OUTPUT statement.

When the Finishing Fidelity triplet sets the continuation rule to DO NOT STOP (X'02'), one of these occurs:

- If the printer supports the PFC Finishing Fidelity triplet and if the REPORT field is set to REPORT (X'01'), the printer reports this exception. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.
- If the printer supports the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.
- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer reports this exception but PSF does not issue the error message. The

printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to REPORT (X'01'), the printer reports this exception and PSF issues the error message. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the MFC with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If the output is not acceptable, do one of these:

- Verify that you requested the appropriate form definition for the finishing operation intended.
- Submit the print request to a printer that can do the finishing operation.
- If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS2567I

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE MATRIX ROW SIZE VALUE OR THE NUMBER OF ROWS VALUE FOR A BAR CODE IS UNSUPPORTED.

Explanation

If the bar code is specified as a bar code object, either the matrix row size value or the number of rows value that is specified in a Bar Code Data (BDA) structured field is unsupported.

If the bar code is specified with the BARCODE subcommand in a page definition, the values that are specified in the SIZE *rows* BY *cols* parameter on the BCXPARMS subcommand are not valid.

The BDA structured field is contained in a bar code object. The bar code object might be contained in a MO:DCA document, an overlay, or might be embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object or you created the page definition, correct the error and resubmit the print request. See *Bar Code Object Content Architecture Reference* for more

information about bar code objects. See *Page Printer Formatting Aid: User's Guide* for more information about creating page definitions.

If the structured field has no error, the error might be a PSF or printer logic error.

If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS2568I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE STRUCTURED APPEND SEQUENCE INDICATOR FOR A BAR CODE IS NOT VALID.

Explanation

If the bar code is specified as a bar code object, a structured append sequence indicator that is specified in the Bar Code Data (BDA) structured field is not valid.

If the bar code is specified with the BARCODE subcommand in a page definition, the value that is specified for *seq* in the SEQUENCE *seq* OF *tot* parameter on the BCXPARMS subcommand is not valid. For a Data Matrix or QR Code symbol, the sequence indicator must be 1 - 16, inclusive. For a MaxiCode symbol, the sequence indicator must be 1 - 8, inclusive.

The bar code object might be contained in a MO:DCA document or an overlay or might be associated with a data set that contains line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the

input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object or you created the page definition, correct the error and resubmit the print request. See *Bar Code Object Content Architecture Reference* for more information about bar code objects. See *Page Printer Formatting Aid: User's Guide* for more information about creating page definitions.

If the structured field has no error, the error might be a PSF or printer logic error.

If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS2569I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE STRUCTURED APPEND SEQUENCE INDICATOR FOR A BAR CODE IS TOO LARGE.

Explanation

If the bar code is specified as a bar code object, a structured append sequence indicator that is specified in the Bar Code Data (BDA) structured field is larger than the total number of structured append symbols.

If the bar code is specified with the BARCODE subcommand in a page definition, the value that is specified for *seq* in the SEQUENCE *seq* OF *tot* parameter is larger than the value specified for *tot*.

The bar code object might be contained in a MO:DCA document or an overlay or might be associated with a data set that contains line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set,

or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object or you created the page definition, correct the error and resubmit the print request. See *Bar Code Object Content Architecture Reference* for more information about bar code objects. See *Page Printer Formatting Aid: User's Guide* for more information about creating page definitions.

If the structured field has no error, the error might be a PSF or printer logic error.

If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS2570I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: MISMATCHED STRUCTURED APPEND INFORMATION IS SPECIFIED FOR A BAR CODE.

Explanation

If the bar code is specified as a bar code object, mismatched structured append information is specified in the Bar Code Data (BDA) structured field. One of the sequence-indicator or total-number-of-symbols parameters is X'00', but the other is not.

If the bar code is specified with the BARCODE subcommand in a page definition, the value that is specified for *seq* or *tot* in the SEQUENCE *seq* OF *tot* parameter is X'00' and the other is not.

The bar code object might be contained in a MO:DCA document or an overlay or might be associated with a data set that contains line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page.

PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object or you created the page definition, correct the error and resubmit the print request. See *Bar Code Object Content Architecture Reference* for more information about bar code objects. See *Page Printer Formatting Aid: User's Guide* for more information about creating page definitions.

If the structured field has no error, the error might be a PSF or printer logic error.

If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS2571I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE NUMBER OF STRUCTURED APPEND SYMBOLS SPECIFIED FOR A BAR CODE IS NOT VALID.

Explanation

If the bar code is specified as a bar code object, the number of structured append symbols that are specified in the Bar Code Data (BDA) structured field is not valid.

If the bar code is specified with the BARCODE subcommand in a page definition, the value that is specified for *tot* in the SEQUENCE *seq* OF *tot* parameter on the BCXPARMS subcommand is not valid. For a Data Matrix or QR Code symbol, the total

number of symbols must be 2 - 16. For a MaxiCode symbol, the total number of symbols must be 2 - 8.

The bar code object might be contained in a MO:DCA document or an overlay or might be associated with a data set that contains line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object or you created the page definition, correct the error and resubmit the print request. See *Bar Code Object Content Architecture Reference* for more information about bar code objects. See *Page Printer Formatting Aid: User's Guide* for more information about creating page definitions.

If the structured field has no error, the error might be a PSF or printer logic error.

If you used a program to create the structured fields for the bar code object, contact your system programmer.

Explanation

An incompatible combination of Data Matrix parameters is specified. When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. A structured append is specified, but either the reader programming flag is set to B'1', or a header and trailer macro is specified.
2. The GS1 FNC1 flag is set to B'1', but either the industry FNC1 flag is set to B'1', the reader programming flag is set to B'1', or a header and trailer macro is specified.
3. The industry FNC1 flag is set to B'1', but either the GS1 FNC1 flag is set to B'1', the reader programming flag is set to B'1', or a header and trailer macro is specified.
4. The reader programming flag is set to B'1', but either a structured append is specified, one of the FNC1 flags is set to B'1', or a header and trailer macro is specified.
5. A header and trailer macro is specified, but either a structured append is specified, one of the FNC1 flags is set to B'1', or the reader programming flag is set to B'1'.

If the bar code is specified as a bar code object, the error is in the Bar Code Data Descriptor (BDD) structured field.

If the bar code is specified with the BARCODE subcommand in a page definition, the error is in an Additional Bar Code Parameters triplet (X'7B') on a Line Descriptor (LND), Record Descriptor (RCD), or XML Descriptor (XMD) structured field.

The bar code object might be contained in a MO:DCA document, an overlay, or a page segment, or might be associated with a data set that contains line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set,

APS2572I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN INCOMPATIBLE COMBINATION OF DATA MATRIX PARAMETERS IS SPECIFIED FOR A BAR CODE.

or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object or the page definition, correct the error and resubmit the print request. See *Bar Code Object Content Architecture Reference* for more information about the BDA structured field. See *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the X'7B' triplet.

If the structured field has no error, the error might be a PSF or printer logic error.

If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS2573I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A SPECIFIED STRUCTURED APPEND FILE IDENTIFICATION VALUE FOR A BAR CODE IS NOT VALID.

Explanation

A structured append file identification value that is specified in a bar code is not valid. Each byte of the 2-byte file identification value must be in the range X'0A'–X'FE'.

If the bar code is specified as a bar code object, the error is in the Bar Code Data Descriptor (BDD) structured field.

If the bar code is specified with the BARCODE subcommand in a page definition, the values that are specified for *uidHi*, *uidLo*, or both in the SEQUENCE seq OF tot ID *uidHi uidLo* parameter on the BCXPARMS subcommand are not valid.

The bar code object might be contained in a MO:DCA document, an overlay, or might be associated with a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object or you created the page definition, correct the error and resubmit the print request. See *Bar Code Object Content Architecture Reference* for more information about bar code objects. See *Page Printer Formatting Aid: User's Guide* for more information about creating page definitions.

If the structured field has no error, the error might be a PSF or printer logic error.

If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS2574I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A SPECIFIED SYMBOL MODE VALUE FOR A BAR CODE IS NOT VALID.

Explanation

If the bar code is specified as a bar code object, a symbol mode value that is specified in the Bar Code Data (BDA) structured field is not valid.

If the bar code is specified with the BARCODE subcommand in a page definition, the value that is

specified for the MODE parameter on the BCXPARMS subcommand is not valid.

The bar code object might be contained in a MO:DCA document, an overlay, a page segment, or embedded in a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object or you created the page definition, correct the error and resubmit the print request. See *Bar Code Object Content Architecture Reference* for more information about bar code objects. See *Page Printer Formatting Aid: User's Guide* for more information about creating page definitions.

If the structured field has no error, the error might be a PSF or printer logic error.

If you used a program to create the structured fields for the bar code object, contact your system programmer.

FOR A PDF417 SYMBOL IS NOT VALID.

Explanation

The number of data symbol characters per row for a PDF417 bar code symbol is not valid.

If the bar code is specified as a bar code object, the error is in the Bar Code Data (BDA) structured field.

If the bar code is specified with the BARCODE subcommand in a page definition, the value that is specified for *cols* in the SIZE *rows* BY *cols* parameter on the BCXPARMS subcommand is not valid.

The bar code object might be contained in a MO:DCA document, an overlay, or a page segment, or might be associated with a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object or you created the page definition, correct the error and resubmit the print request. See *Bar Code Object Content Architecture Reference* for more information about bar code objects. See *Page Printer Formatting Aid: User's Guide* for more information about creating page definitions.

APS2575I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A SPECIFIED DATA SYMBOL CHARACTERS PER ROW VALUE

If the structured field has no error, the error might be a PSF or printer logic error.

If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS2576I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A DESIRED NUMBER OF ROWS VALUE FOR A BAR CODE IS NOT VALID.**

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of an error condition that caused the exception to be reported. For a PDF417 symbol, one of these conditions occurred:

1. A specified desired number of rows value is not valid.
2. The number of rows times the number of data symbol characters is greater than 928.

If the bar code is specified as a bar code object, the error is in the Bar Code Data (BDA) structured field.

If the bar code is specified with the BARCODE subcommand in a page definition, the value that is specified for *rows* in the SIZE *rows* BY *cols* parameter on the BCXPARMS subcommand is not valid.

The bar code object might be contained in a MO:DCA document, an overlay, or a page segment, or might be associated with a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object or you created the page definition, correct the error and resubmit the print request. See *Bar Code Object Content Architecture Reference* for more information about bar code objects. See *Page Printer Formatting Aid: User's Guide* for more information about creating page definitions.

If the structured field has no error, the error might be a PSF or printer logic error.

If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS2577I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: TOO MUCH DATA WAS SPECIFIED FOR A PDF417 SYMBOL.**

Explanation

If the bar code is specified as a bar code object, too much data is specified in a Bar Code Data (BDA) structured field for a PDF417 symbol.

If the bar code is specified with the BARCODE subcommand in a page definition, the length that is specified by the LENGTH subcommand on a FIELD command that contains the BARCODE subcommand picks up too much data for a PDF417 symbol.

The bar code object might be contained in a MO:DCA document, an overlay, or a page segment, or might be associated with a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object or you created the page definition, correct the error and resubmit the print request. See *Bar Code Object Content Architecture Reference* for more information about bar code objects. See *Page Printer Formatting Aid: User's Guide* for more information about creating page definitions.

If the structured field has no error, the error might be a PSF or printer logic error.

If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS2578I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A SPECIFIED SECURITY LEVEL VALUE FOR A PDF417 SYMBOL IS NOT VALID.

Explanation

If the bar code is specified as a bar code object, the security level that is specified in a Bar Code Data (BDA) structured field for a PDF417 symbol is not valid.

If the bar code is specified with the BARCODE subcommand in a page definition, the security level that is specified by the SECLEV parameter on a BCXPARMS subcommand is not valid.

The bar code object might be contained in a MO:DCA document, an overlay, or a page segment, or might be associated with a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object or you created the page definition, correct the error and resubmit the print request. See *Bar Code Object Content Architecture Reference* for more information about bar code objects. See *Page Printer Formatting Aid: User's Guide* for more information about creating page definitions.

If the structured field has no error, the error might be a PSF or printer logic error.

If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS2579I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A SPECIFIED LENGTH VALUE FOR A MACRO PDF417 CONTROL BLOCK IS NOT VALID.

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of an error condition that caused the exception to be reported. For a

PDF417 symbol, one or both of these conditions occurred:

1. A Macro PDF417 Control Block length value in a bar code is not valid.
2. The length of a Macro PDF417 Control Block is too large.

If the bar code is specified as a bar code object, the error is in the Bar Code Data (BDA) structured field.

If the bar code is specified with the BARCODE subcommand in a page definition, the *qstring* specified in the MACRO *qstring* parameter on the BCXPARMS subcommand is too long.

The bar code object might be contained in a MO:DCA document, an overlay, or a page segment, or might be associated with a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object or you created the page definition, correct the error and resubmit the print request. See *Bar Code Object Content Architecture Reference* for more information about bar code objects. See *Page Printer Formatting Aid: User's Guide* for more information about creating page definitions.

If the structured field has no error, the error might be a PSF or printer logic error.

If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS2580I

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: DATA SPECIFIED FOR A MACRO PDF417 CONTROL BLOCK IS NOT VALID.

Explanation

For a PDF417 symbol, an error occurred in the data for a PDF417 macro.

If the bar code is specified as a bar code object, the error is in the Bar Code Data (BDA) structured field.

If the bar code is specified with the BARCODE subcommand in a page definition, the *qstring* specified in the MACRO *qstring* parameter on the BCXPARMS subcommand is not valid.

The bar code object might be contained in a MO:DCA document, an overlay, or a page segment, or might be associated with a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object or you created the page definition, correct the error and resubmit the print request. See *Bar Code Object Content Architecture Reference* for more information about bar code objects. See *Page Printer Formatting Aid: User's Guide* for more information about creating page definitions.

If the structured field has no error, the error might be a PSF or printer logic error.

If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS2581I INSUFFICIENT [WCS | CPS | RPS | PST | PBS | INTERNAL] PRINTER STORAGE IS AVAILABLE TO LOAD ALL THE RESOURCES MAPPED IN A RESOURCE ENVIRONMENT GROUP.

Explanation

The printer detected and reported an out-of-storage error with an action code of X'0C' (sense byte2) while it was loading resources that are mapped in a Resource Environment Group (REG). A request for raster-pattern storage (RPS), writable-control storage (WCS), compressed-pattern storage (CPS), pattern storage (PST), or page-buffer storage (PBS) exceeded the available storage resources of the printer. If the word INTERNAL is included in the message, the printer does not differentiate between different subpools of storage. Therefore, the printer indicates that its storage is exceeded. This message is accompanied by a message that presents the printer sense bytes.

System action

PSF issues this message only after it attempted to resolve the out-of-storage error condition. Any remaining resources that are mapped in the REG are not loaded into the printer now. PSF issues this message and continues processing the data set. If the current environment does not support repositioning, PSF stops processing the data set when it receives the first resource-constraint error.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If data stream errors stopped the processing of the page just before the page for which this message was issued, correct the data stream errors then resubmit the print request. The condition that caused this message to be issued might be resolved after the other errors are corrected.

If the error is not a data stream error, this error occurred because of one of these reasons:

- The REG maps too many resources or the resources are too large.
- A page or a resource is too complex.
- The combination of two sides of a duplexed sheet is too complex.

If the performance of the print request is acceptable, do nothing. If the performance of the print request is not acceptable, either make the REG, page or resource less complex by deleting resources (for example, text, images, page segments, overlays, or fonts) or submit the print request to a printer with more storage.

APS2582I THE MAXIMUM NUMBER OF OVERLAYS THE PRINTER WILL ACCEPT MIGHT HAVE BEEN EXCEEDED BY A SIMPLEX PAGE OR BY THE FRONT AND BACK OF A DUPLEX SHEET.

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. Either an overlay ID or overlay HAID value that is used in downloading an overlay is not valid. This error might be caused by a simplex page, or by the front and back of a duplex sheet that contains more overlays than the printer can accept.
2. An overlay HAID value in an Include Overlay (IO) command is not valid or is unsupported (possible logic error).
3. An overlay ID or overlay HAID value in a Load Copy Control (LCC) command is not valid (possible logic error).

System action

PSF recovers from the error by deleting any overlays that are not needed for the current sheet at the received page counter and then resending the page. If PSF receives a second occurrence of this error, PSF issues this message and ends. If the current environment does not support repositioning, PSF stops processing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If data stream errors stopped the processing of the page that precedes the page for which this message was issued, correct the data stream errors and resubmit the print request. The condition that caused this message to be issued might be resolved after the other errors are corrected. If the error is not because of data stream errors, delete some of the overlays on the simplex page or duplex sheet at the received page counter plus 1. If the simplex page or duplex sheet at the received page counter plus 1 does not contain more overlays than the printer can accept, a PSF or printer logic error might have occurred.

APS2583I	AN INCOMPATIBLE CHANGE IN MEDIA DESTINATION WAS REQUESTED DURING A FINISHING OPERATION. THE FINISHING OPERATION IS TERMINATED. PROCESSING OF THE DATA SET CONTINUES.
-----------------	---

Explanation

A finishing operation that is specified in a Finishing Operation triplet (X'85') is incompatible with the change in the media destination. Because some printers restrict the possible media destination of finished data sets to a subset of all media destinations available, the finishing operation is stopped.

Finishing Operation triplets are specified in the Medium Finishing Control (MFC) structured field. The

MFC is specified in the Document Environment Group of the form definition or in a medium map.

Media destination is specified on the OUTPUT statement in the JCL and in a medium map in the form definition.

System action

Reporting of this exception can be controlled by the Finishing Fidelity triplet in the Presentation Fidelity Control (PFC) command. The PFC command is contained in a form definition.

When the Finishing Fidelity triplet sets the continuation rule to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and marks the data set unprintable. PSF releases the current data set back to JES and requests that it is held by the system unless PRTEROR=QUIT is specified on the OUTPUT statement.

When the Finishing Fidelity triplet sets the continuation rule to DO NOT STOP (X'02'), one of these occurs:

- If the printer supports the PFC Finishing Fidelity triplet and the REPORT field is set to REPORT (X'01'), the printer reports this exception. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, print-error markers might be included on the printed page.
- If the printer supports the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.
- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer reports this exception but PSF does not issue the error message. The printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.
- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to REPORT (X'01'), the printer reports this exception and PSF issues the error message. PSF continues processing the current data set with the page that

follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the MFC with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If the output is not acceptable:

- If you specified OUTBIN on any COPYGROUP commands in your form definition, make sure that it selects a media destination that supports finished output.
- Verify that you requested the appropriate form definition for the finishing operation intended.
- Submit the print request to a printer that can do the finishing operation.
- If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS2584I DATA IN A FORMDEF RESOURCE IS NOT VALID OR IS UNSUPPORTED: THE MEDIUM FINISHING CONTROL STRUCTURED FIELD SPECIFIES AN INCORRECT OR UNSUPPORTED FINISHING OPTION.

Explanation

The Finishing option field (byte 3) in a Finishing Operation triplet (X'85') contains an unsupported value for the specified group of pages for this finisher. The finisher is unable to do the finishing request on the group of pages that are specified by the MFC Scope field (byte 3) of the Medium Finishing Control (MFC) structured field.

Finishing Operation triplets are specified in the Medium Finishing Control (MFC) structured field. The MFC is specified in the Document Environment Group of the form definition or in a medium map.

System action

Reporting of this exception can be controlled by the Finishing Fidelity triplet in the Presentation Fidelity Control (PFC) command. The PFC command is contained in a form definition. When the Finishing Fidelity triplet sets the continuation rule to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and the data set is marked unprintable. PSF releases the current data set back to JES and requests that it is held by the system unless PRTEROR=QUIT was specified on the OUTPUT statement.

When the Finishing Fidelity triplet sets the continuation rule to DO NOT STOP (X'02'), one of these actions occurs:

- If the printer supports the PFC Finishing Fidelity triplet and the REPORT field is set to REPORT (X'01'), the printer reports this exception. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, print-error markers might be included on the printed page.
- If the printer supports the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.
- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer reports this exception but PSF does not issue the error message. The printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in

error contains any positioning errors, then print-error markers might be included on the printed page.

- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to REPORT (X'01'), the printer reports this exception and PSF issues the error message. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the MFC with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If the output is not acceptable:

- Verify that you requested the appropriate form definition for the finishing operation intended.
- Submit the print request to a printer that can do the finishing operation.
- If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS2585I

A UP3I-CONTROLLED DEVICE ATTACHED TO THE PRINTER HAS REPORTED AN INTERVENTION REQUIRED CONDITION.

Explanation

A Universal Printer Pre- and Postprocessing Interface (UP3I)-controlled device that is attached to the printer reported a condition that requires intervention, with an action code of X'0A' (sense byte 2). The specific error is identified in the accompanying message, APS2600I.

System action

PSF resends pages to the printer, starting from the jam recovery page counter. PSF might print this message on a separate sheet in the data set to mark the position at which it started the recovery from this error. Pages might be duplicated during the recovery.

If the current environment does not support repositioning, PSF stops processing the data set.

Operator response

No response is necessary.

System programmer response

If the error condition persists, follow the procedures that are described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

The printed output might be acceptable. If any pages were duplicated, you might want to resubmit the print request. If the error condition persists, contact your system programmer.

APS2586I

A UP3I-CONTROLLED DEVICE ATTACHED TO THE PRINTER HAS REPORTED AN INTERVENTION REQUIRED CONDITION.

Explanation

A Universal Printer Pre- and Postprocessing Interface (UP3I)-controlled device that is attached to the printer reported a condition that requires intervention, with an action code of X'1A' (sense byte 2). The specific error is identified in the accompanying message, APS2600I.

System action

PSF resends pages to the printer, starting from the committed page counter plus 1. PSF might print this message on a separate sheet in the data set to mark the position at which it started the recovery from this error. Pages might be duplicated during the recovery.

If the current environment does not support repositioning, PSF stops processing the data set.

Operator response

See the operator's guide for the printer that reported this error and clear the paper from the printer and post processor. PSF assumes that pages between the jam recovery page counter and the stacked page counter are not damaged and do not need to be reprinted. If any pages between these two page counters do need to be reprinted, use the JES BACKSPACE command.

System programmer response

If the error condition persists, follow the procedures that are described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

The printed output might be acceptable. If any pages were duplicated, you might want to resubmit the print request. If the error condition persists, contact your system programmer.

**APS2587I A PARAMETER VALUE IN A
FORMDEF RESOURCE IS NOT
VALID OR IS UNSUPPORTED: THE
MEDIUM FINISHING CONTROL
STRUCTURED FIELD SPECIFIES
UP3I FINISHING WITH AN
INCORRECT OR UNSUPPORTED
PARAMETER.**

Explanation

A specification error was detected for a Universal Printer Pre- and Postprocessing Interface (UP3I)-controlled device. The specific error code is identified in the accompanying message, APS2600I.

UP3I Finishing Operation triplets (X'8E') are specified in the Medium Finishing Control (MFC) structured field or were generated by the printer for AFP Finishing Operation triplets (X'85') specified in the MFC structured field. The MFC is specified in the Document Environment Group of the form definition or in a medium map.

System action

Reporting of this exception can be controlled by the Finishing Fidelity triplet in the Presentation Fidelity Control (PFC) structured field. The PFC structured field is contained in a form definition.

When the Finishing Fidelity triplet sets the continuation rule to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and marks the data set unprintable. PSF releases the current data set back to JES and requests that it is held by the system unless

PRTEROR=QUIT is specified on the OUTPUT statement.

When the Finishing Fidelity triplet sets the continuation rule to DO NOT STOP (X'02'), one of these occurs:

- If the printer supports the PFC Finishing Fidelity triplet and the REPORT field is set to REPORT (X'01'), the printer reports this exception. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, print-error markers might be included on the printed page.
- If the printer supports the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.
- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer reports this exception but PSF does not issue the error message. The printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.
- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to REPORT (X'01'), the printer reports this exception and PSF issues the error message. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the MFC with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If the output is not acceptable, do one of these:

- Verify that you requested the appropriate form definition for the finishing operation intended.
- Submit the print request to a printer that supports the finishing operation.
- If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS2588I A PARAMETER VALUE IN A FORMDEF RESOURCE IS NOT VALID OR IS UNSUPPORTED: THE MEDIUM FINISHING CONTROL STRUCTURED FIELD SPECIFIES UP3I FINISHING WITH AN INCORRECT OR UNSUPPORTED PARAMETER.

Explanation

A function no longer achievable error (action code X'06') was detected for a Universal Printer Pre- and Postprocessing Interface (UP3I)-controlled device. The specific error code is identified in the accompanying message, APS2600I.

UP3I Finishing Operation triplets (X'8E') are specified in the Medium Finishing Control (MFC) structured field or were generated by the printer for AFP Finishing Operation triplets (X'85') specified in the MFC structured field. The MFC is specified in the Document Environment Group of the form definition or in a medium map.

System action

Reporting of this exception can be controlled by the Finishing Fidelity triplet in the Presentation Fidelity Control (PFC) structured field. The PFC structured field is contained in a form definition.

When the Finishing Fidelity triplet sets the continuation rule to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and marks the data set unprintable. PSF releases the current data set back to JES and requests that it is held by the system unless PRTEROR=QUIT is specified on the OUTPUT statement.

When the Finishing Fidelity triplet sets the continuation rule to DO NOT STOP (X'02'), one of these occurs:

- If the printer supports the PFC Finishing Fidelity triplet and the REPORT field is set to REPORT (X'01'), the printer reports this exception. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, print-error markers might be included on the printed page.
- If the printer supports the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.
- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer reports this exception but PSF does not issue the error message. The printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.
- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to REPORT (X'01'), the printer reports this exception and PSF issues the error message. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in

the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the MFC with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If the output is not acceptable, do one of these:

- Verify that you requested the appropriate form definition for the finishing operation intended.
- Submit the print request to a printer that supports the finishing operation.
- If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.
- Ensure that the printer and post-processors are set up for the finishing operation and ensure that the operator does not change the setup while the job is printing.

APS2589I **A UP3I-CONTROLLED DEVICE ATTACHED TO THE PRINTER HAS REPORTED AN EQUIPMENT CHECK THAT IS ALSO AN INTERVENTION REQUIRED CONDITION.**

Explanation

A Universal Printer Pre- and Postprocessing Interface (UP3I)-controlled device that is attached to the printer reported an equipment check error that is also an intervention required condition with an action code of X'08' (sense byte 2). The specific error is identified in the accompanying message, APS2600I.

System action

PSF resends pages to the printer, starting from the jam recovery page counter plus 1. PSF might print this message on a separate sheet in the data set to mark the position at which it started the recovery from this error. Pages might be duplicated during the recovery.

If the current environment does not support repositioning, PSF stops processing the data set.

Operator response

No response is necessary.

System programmer response

If the error condition persists, follow the procedures that are described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

The printed output might be acceptable. If any pages were duplicated, you might want to resubmit the print request. If the error condition persists, contact your system programmer.

APS2590I **A UP3I-CONTROLLED DEVICE ATTACHED TO THE PRINTER HAS REPORTED AN EQUIPMENT CHECK THAT IS ALSO AN INTERVENTION REQUIRED CONDITION.**

Explanation

A Universal Printer Pre- and Postprocessing Interface (UP3I)-controlled device that is attached to the printer reported an equipment check error that is also an intervention required condition with an action code of X'09' (sense byte 2). The specific error is identified in the accompanying message, APS2600I.

For more information about this error, see the post processor publications for the printer that reported this error.

System action

PSF resends pages to the printer, starting from the jam recovery page counter plus 1. PSF might print this message on a separate sheet in the data set to mark the position at which it started the recovery from this error. Pages might be duplicated during the recovery.

If the current environment does not support repositioning, PSF stops processing the data set.

Operator response

No response is necessary.

System programmer response

If the error condition persists, follow the procedures that are described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

The printed output might be acceptable. If any pages were duplicated, you might want to resubmit the print request. If the error condition persists, contact your system programmer.

APS2591I **A UP3I-CONTROLLED DEVICE ATTACHED TO THE PRINTER HAS REPORTED AN EQUIPMENT CHECK THAT IS ALSO AN INTERVENTION REQUIRED CONDITION.**

Explanation

A Universal Printer Pre- and Postprocessing Interface (UP3I)-controlled device that is attached to the printer reported an equipment check error that is also an intervention required condition with an action code of X'16' (sense byte 2). The specific error is identified in the accompanying message, APS2600I.

For more information about this error, see the post processor publications for the printer that reported this error.

System action

PSF resends pages to the printer, starting from the jam recovery page counter plus 1. PSF might print this message on a separate sheet in the data set to mark the position at which it started the recovery from this error. Pages might be duplicated during the recovery.

If the current environment does not support repositioning, PSF stops processing the data set.

Operator response

No response is necessary.

System programmer response

If the error condition persists, follow the procedures that are described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

The printed output might be acceptable. If any pages were duplicated, you might want to resubmit the print request. If the error condition persists, contact your system programmer.

APS2592I **A UP3I-CONTROLLED DEVICE ATTACHED TO THE PRINTER HAS REPORTED A PAPER JAM AS AN INTERVENTION REQUIRED CONDITION.**

Explanation

A Universal Printer Pre- and Postprocessing Interface (UP3I)-controlled device that is attached to the printer reported a paper jam, which is an intervention required condition, with an action code of X'08' (sense byte 2). The specific error is identified in the accompanying message, APS2600I.

System action

PSF resends pages to the printer, starting from the committed page counter plus 1. PSF might print this message on a separate sheet in the data set to mark the position at which it started the recovery from this error. Pages might be duplicated during the recovery.

If the current environment does not support repositioning, PSF stops processing the data set.

Operator response

No response is necessary.

System programmer response

If the error condition persists, follow the procedures that are described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

The printed output might be acceptable. If any pages were duplicated, you might want to resubmit the print request. If the error condition persists, contact your system programmer.

APS2593I **A UP3I-CONTROLLED DEVICE ATTACHED TO THE PRINTER HAS REPORTED AN EQUIPMENT CHECK ERROR THAT CAN NOT BE CORRECTED BY AN OPERATOR.**

Explanation

A Universal Printer Pre- and Postprocessing Interface (UP3I)-controlled device that is attached to the printer reported an equipment check error that cannot be corrected by an operator, with an action code of X'09' (sense byte 2). The specific error is identified in the accompanying message, APS2600I.

For more information about this error, see the post processor publications for the printer that reported this error.

System action

PSF stops printing the data set at the committed page counter plus 1.

Operator response

Inform your system programmer that this error occurred.

System programmer response

If the error condition persists, follow the procedures that are described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

Inform your system programmer that this error occurred.

APS2594I **A UP3I-CONTROLLED DEVICE ATTACHED TO THE PRINTER HAS REPORTED AN EQUIPMENT CHECK ERROR THAT CAN NOT BE CORRECTED BY AN OPERATOR.**

Explanation

A Universal Printer Pre- and Postprocessing Interface (UP3I)-controlled device that is attached to the printer reported an equipment check error that cannot be corrected by an operator, with an action code of X'23' (sense byte 2). The specific error is identified in the accompanying message, APS2600I.

For more information about this error, see the post processor publications for the printer that reported this error.

System action

PSF resends pages to the printer, starting from the committed page counter plus 1. PSF might print this message on a separate sheet in the data set to mark the position at which it started the recovery from this error. Pages might be duplicated during the recovery.

If the current environment does not support repositioning, PSF stops processing the data set.

Operator response

No response is necessary.

System programmer response

If the error condition persists, follow the procedures that are described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

The printed output might be acceptable. If any pages were duplicated, you might want to resubmit the print

request. If the error condition persists, contact your system programmer.

APS2595I **A PARAMETER VALUE IN A FORMDEF RESOURCE IS NOT VALID OR IS UNSUPPORTED: THE MEDIUM FINISHING CONTROL STRUCTURED FIELD SPECIFIES UP3I FINISHING WITH AN INCORRECT OR UNSUPPORTED PARAMETER.**

Explanation

A Data-Related Print exception (action code X'09') was detected for a Universal Printer Pre- and Postprocessing Interface (UP3I)-controlled device. The specific error code is identified in the accompanying message, APS2600I.

UP3I Finishing Operation triplets (X'8E') are specified in the Medium Finishing Control (MFC) structured field or were generated by the printer for AFP Finishing Operation triplets (X'85') specified in the MFC structured field. The MFC is specified in the Document Environment Group of the form definition or in a medium map.

System action

PSF stops printing the data set at the committed page counter plus 1.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the MFC with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

If the error condition persists, follow the procedures that are described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

Inform your system programmer that this error occurred.

APS2596I **A UP3I-CONTROLLED DEVICE ATTACHED TO THE PRINTER HAS**

**REPORTED A CONDITION
REQUIRING HOST NOTIFICATION.**

Explanation

An error condition in a Universal Printer Pre- and Postprocessing Interface (UP3I)-controlled device that is attached to the printer caused the printer to discard its buffered pages. A sheet cannot be printed because of a problem within the data stream. The printer reports an action code X'09'. The specific error is identified in the accompanying message, APS2600I.

System action

PSF stops printing the data set at the committed page counter plus 1.

Operator response

Inform your system programmer that this error occurred.

System programmer response

If the error condition persists, follow the procedures that are described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

Inform your system programmer that this error occurred.

**APS2597I A UP3I-CONTROLLED DEVICE
ATTACHED TO THE PRINTER HAS
REPORTED A CONDITION
REQUIRING HOST NOTIFICATION.**

Explanation

An error condition in a Universal Printer Pre- and Postprocessing Interface (UP3I)-controlled device that is attached to the printer caused the printer to discard its buffered pages. The printer reports an action code X'1A' to instruct PSF to redrive buffered pages. The specific error is identified in the accompanying message, APS2600I.

System action

PSF resends pages to the printer, starting from the jam recovery page counter plus 1. PSF might print this message on a separate sheet in the data set to mark the position at which it started the recovery from this error. Pages might be duplicated during the recovery.

If the current environment does not support repositioning, PSF stops processing the data set.

Operator response

Inform your system programmer that this error occurred.

System programmer response

If the error condition persists, follow the procedures that are described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

The printed output might be acceptable. If any pages were duplicated, you might want to resubmit the print request. If the error condition persists, contact your system programmer.

**APS2598I A UP3I-CONTROLLED DEVICE
ATTACHED TO THE PRINTER HAS
REPORTED A CONDITION
REQUIRING HOST NOTIFICATION.**

Explanation

An error condition in a Universal Printer Pre- and Postprocessing Interface (UP3I)-controlled device that is attached to the printer caused the printer to discard its buffered pages. At least one of the printer characteristics was changed in the printer. The printer reports an action code X'1D' to instruct PSF to redrive buffered pages. The specific error is identified in the accompanying message, APS2600I.

System action

PSF obtains the new printer characteristics and then resends to the printer the pages that start from the committed page counter plus 1. PSF might print this message on a separate sheet in the data set to mark the position at which it started the recovery from this error. Pages might be duplicated during the recovery.

If the current environment does not support repositioning, PSF stops processing the data set.

Operator response

Inform your system programmer that this error occurred.

System programmer response

If the printer characteristics were not changed at the printer and the error condition persists, follow the procedures that are described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

The printed output might be acceptable. If any pages were duplicated, you might want to resubmit the print request. If the error condition persists, contact your system programmer.

APS2599I **A UP3I-CONTROLLED DEVICE ATTACHED TO THE PRINTER HAS REPORTED A CONDITION REQUIRING HOST NOTIFICATION.**

Explanation

An error condition in a Universal Printer Pre- and Postprocessing Interface (UP3I)-controlled device that is attached to the printer caused the printer to discard its buffered pages. The printer reports an action code X'1A' to instruct PSF to redrive buffered pages. The specific error is identified in the accompanying message, APS2600I.

System action

PSF resends pages to the printer, starting from the jam recovery page counter plus 1. PSF might print this message on a separate sheet in the data set to mark the position at which it started the recovery from this error. Pages might be duplicated during the recovery.

If the current environment does not support repositioning, PSF stops processing the data set.

Operator response

See the operator's guide for the printer that reported this error and clear the paper from the printer and postprocessor. PSF assumes that pages between the jam recovery page counter and the stacked page counter are not damaged and do not need to be reprinted. If any pages between these two page counters do need to be reprinted, use the JES BACKSPACE command.

System programmer response

If the error condition persists, follow the procedures that are described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

The printed output might be acceptable. If any pages were duplicated, you might want to resubmit the print request. If the error condition persists, contact your system programmer.

APS2600 to APS5999

APS2600I **THE ERROR SENSE BYTES 0–5 = error sense bytes 0–5, IPDS COMMAND IN PROCESS = ipds command, UP3I-SPECIFIC ERROR CODE = error code, UP3I PAPER SEQUENCE ID OF THE DEVICE = paper sequence id, UP3I-SPECIFIC INFORMATION = up3i-specific information, BYTE 19 = error sense byte 19, PAGE IDENTIFIER = page id.**

Explanation

This message formats and presents the 24 printer sense bytes that are reported to PSF at the time of an I/O error from a Universal Printer Pre- and Postprocessing Interface (UP3I)-controlled device that is attached to the printer. A message that describes the specific I/O error accompanies this message. The message contains this information:

- *Error sense bytes 0–5* are the first 6 bytes in the sense data, reported in hexadecimal.
- *IPDS command* is the 2-byte hexadecimal code for the IPDS command that was in process at the time

the error occurred. This information was formatted from bytes 6 and 7 of the sense data. A value of X'0000' indicates that the error was not associated with any particular IPDS command.

- *Error code* is the UP3I-specific error code. See the *UP3I Specification* at [AFP Consortium \(www.afpcinc.org\)](http://www.afpcinc.org) for a description of the error codes. This information was formatted from bytes 8 and 9 of the sense data.
- *Paper sequence id* is the UP3I paper sequence ID of the device that caused the error. This information was formatted from byte 10 of the sense data.
- *UP3I-specific information*; see the *UP3I Specification* at [AFP Consortium \(www.afpcinc.org\)](http://www.afpcinc.org) for a description of the content of these bytes. This information was formatted from bytes 11 - 18 of the sense data.
- *Error sense byte 19* is the third byte of the 3-byte exception ID; together with sense byte 1, it defines the specific exception within an exception class.

Note: The error sense is written as Byte 0 Byte 1... Byte 19.

- *Page id* is the page ID from the Begin Page command if the error is associated with a particular page. It is reported in hexadecimal.

System action

See the accompanying messages for the system action taken.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot be initialized or cannot print a separator page or an error message. Notify your system programmer.

System programmer response

To determine an appropriate response, see the specific error conditions that are described in the accompanying messages. For more information about printer sense bytes and the specific error, see the UP3I-controlled device publications for the printer that reported this error.

User response

To determine an appropriate response, see the specific error conditions that are described in the accompanying messages.

**APS2601I MICR PRINTING WAS
 REQUESTED, BUT IS NOT
 AVAILABLE.**

Explanation

Magnetic ink character recognition (MICR) printing is requested when the Presentation Text Data (PTX) structured field or the Graphics Data (GAD) structured field uses a font that supports MICR. When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. A string of text is encountered that is to be printed with a MICR font, but MICR printing is not available for this text string.
2. Some printers can print MICR text on one side of the media, but not on the other side; in this case, text data to be printed with a MICR font that is placed on the non-MICR side of the media causes this exception to occur.
3. Some printers can print MICR text only in specific colors, such as black or a specific highlight color.
4. Some printers allow MICR printing to be disabled (even after a MICR font is activated).

System action

PSF cannot print the current data set. PSF stops processing and printing the data set. PSF issues more messages that identify the processing environment in which the error occurred. PSF releases the current data set back to JES and requests that it is held by the system, unless PRTEROR=QUIT was specified on the OUTPUT statement.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

If you do not want MICR printing, change the PTX or GAD structured field to not use MICR fonts. If you do want MICR printing, change the data stream to request MICR printing on the supported side, send the job to a different printer that prints MICR on the requested side, or reconfigure this printer to print MICR on the requested side.

**APS2602I DATA IN AN INPUT RECORD OR
 RESOURCE IS NOT SUPPORTED:
 THE IMAGE RESOLUTION FOR A
 PRESENTATION OBJECT
 CONTAINER RESOURCE
 SPECIFIED A UNIT BASE THAT
 THE PRINTER DOES NOT
 SUPPORT.**

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The X unit base value in an Image Resolution (X'9A') triplet is not valid or is unsupported.
2. The Y unit base value in an Image Resolution (X'9A') triplet is not valid or is unsupported.
3. The Y unit base value in an Image Resolution (X'9A') triplet is not identical to the X unit base value.

Image resolution is specified with the X'9A' triplet on the Container Data Descriptor (CDD), Include Object (IOB), or Preprocess Presentation Object (PPO) structured fields.

The CDD structured field is specified inside the presentation object container resource. The IOB structured field can be contained in a page definition,

an overlay, or a MO:DCA page, or it can be embedded in line data. The PPO structured field is specified in the Resource Environment Group (REG) for the print data set.

System action

The printer you were using might try to print the page in error; however, the entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the data object resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the data object resource, contact your system programmer.

Explanation

The image resolution for a presentation object (such as a GIF, JPEG, PNG, or TIFF, image) is needed to process the object, but the resolution was not provided within the presentation object and was not provided by an Image Resolution (X'9A') triplet.

Image resolution is specified with the X'9A' triplet on the Container Data Descriptor (CDD), Include Object (IOB), or Preprocess Presentation Object (PPO) structured fields.

The CDD structured field is specified inside the presentation object container resource. The IOB structured field can be contained in a page definition, an overlay, or a MO:DCA page, or it can be embedded in line data. The PPO structured field is specified in the Resource Environment Group (REG) for the print data set.

System action

The printer uses the printer's resolution to print the image. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the data object resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error

APS2603I DATA FOR A RESOURCE IS NOT COMPLETE: THE IMAGE RESOLUTION FOR A PRESENTATION OBJECT IS NEEDED BUT IS NOT SPECIFIED. THE IMAGE IS PRINTED USING THE PRINTER'S RESOLUTION.

might be a PSF or printer logic error. If you used a program to create the structured fields for the data object resource, contact your system programmer.

APS2604I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE FONT LOCAL IDENTIFIER FOR A MAPPED FONT IS OUTSIDE THE SUPPORTED RANGE FOR THE PRINTER.

Explanation

A font local identifier is outside the supported range for the printer. The font local identifier is specified in:

- The Map Coded Font Format 2 (MCF-2) structured field in the Resource Local Identifier triplet (X'24').
- The Map Data Resource (MDR) structured field in the Fully Qualified Name triplet (X'02') with FQNTYPE 'X'BE' for Data Object fonts.

The MCF-2 and MDR structured fields might be contained in a MO:DCA document, an overlay, or a page definition.

System action

The printer you were using might try to print the page in error; however, the entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the structured field that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing MO:DCA data or an overlay and you created the structured field in error, make sure the font local identifier that you specified is supported by your printer. If you used a program to create the structured

fields in the object that contains the error, contact your system programmer.

If you are printing a data set that contains line data and you are using a page definition that you created, ensure that the font local identifier that is specified in the MCF-2 or MDR structured field is within the supported range for your printer. If the font local identifier is within the supported range for the printer, this error is a printer logic error. If the font local identifier is outside the supported range for the printer, either change the font local identifier so it is within the supported range or route your job to a printer that supports your font local identifier value.

See *Mixed Object Document Content Architecture Reference* for more information about the structured fields.

APS2605I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE SYMBOL WIDTH PARAMETER IN THE BAR CODE IS NOT VALID.

Explanation

A bar code is specified as a bar code object or in a page definition; however, the value of the symbol width parameter is not valid. The location of the parameter depends on how the bar code is specified:

- If the bar code is specified as a bar code object, the Symbol width parameter in a Bar Code Symbol Descriptor (BSD) structured field is not valid. The bar code object might be contained in a MO:DCA document or in an overlay.
- If the bar code is specified with the BARCODE subcommand in a page definition, the WIDTH parameter on the BARCODE subcommand is not valid. The bar code object might be associated with a data set that contains line data.

System action

The printer that you are using might try to print the page in error, but the entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see PSF for z/OS: Diagnosis for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object or the page definition, correct the error and resubmit the print request. See *Bar Code Object Content Architecture Reference* for more information about bar code objects. See *Page Printer Formatting Aid: User's Guide* for more information about creating page definitions. If the structured field or page definition has no error, the error might be a PSF or printer logic error.

If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS2606I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE SYMBOL WIDTH PARAMETER IN THE BAR CODE IS TOO SMALL.

Explanation

A bar code is specified as a bar code object or in a page definition; however, the value of the symbol width parameter is too small to generate a bar code symbol. The location of the parameter depends on how the bar code is specified:

- If the bar code is specified as a bar code object, the Symbol width parameter in a Bar Code Symbol Descriptor (BSD) structured field is too small. The bar code object might be contained in a MO:DCA document or in an overlay.
- If the bar code is specified with the BARCODE subcommand in a page definition, the WIDTH parameter on the BARCODE subcommand is too small. The bar code object might be associated with a data set that contains line data.

System action

The printer that you are using might try to print the page in error, but the entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the

printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see PSF for z/OS: Diagnosis for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

In the accompanying formatted sense message (APS830I), the Element Identifier (bytes 16-17) contains the smallest valid symbol size that is measured in twips. (A twip is a unit of measure equal to 1/20 of a point. 1440 twips exist in 1 inch.)

If you created the structured fields for the bar code object or the page definition, correct the error and resubmit the print request. See *Bar Code Object Content Architecture Reference* for more information about bar code objects. See *Page Printer Formatting Aid: User's Guide* for more information about creating page definitions. If the structured field or page definition has no error, the error might be a PSF or printer logic error.

If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS2607A THE PRINTER HAS RESPONDED WITH AN ACTION CODE X'4D' SENSE CODE. PSF CANNOT COMMUNICATE WITH THIS CHANNEL DEVICE UNTIL OPERATOR RECOVERY IS PERFORMED.

Explanation

The PSF error recovery procedure (ERP) was unable to recover from a channel error reported from the device. Communication with the device is not possible. See the accompanying APS717I message for the specific sense code that the printer reports.

System action

PSF processing ends abnormally.

Operator response

PSF ended processing because it cannot communicate with the device. For more information, check for the presence of an IOS permanent error message, such as IOS000I with Equipment Check (EQC). Try VARYING the device OFFLINE and back ONLINE. It might be necessary to turn the printer power off and then back on. You must restart the printer with regular JES commands after the device is successfully brought back ONLINE. If the device fails to become READY, contact your IBM service representative.

Use the MVS K E,*nn* command to delete this message from the console display. See [z/OS MVS System Commands](#).

System programmer response

See the information that is provided in the Operator Response section.

User response

No response is necessary.

APS2608I THE FULLY QUALIFIED NAME IN AN FQN (X'02') TRIPLET IS NOT VALID.

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The FQN Format value is X'00' and the FQN value is not a valid UTF-16BE-encoded string.
2. The FQN Format value is X'00' and the FQN value is not a valid character-encoded string. When the FQN is for a TrueType and OpenType font, the string must be encoded with UTF-16BE. When the FQN is for an object name, the string must be encoded with UTF-16BE unless a preceding Coded Graphic Character Set Global Identifier (X'01') triplet exists.

The Fully Qualified Name (FQName) in an FQN (X'02') triplet is specified on a Map Data Resource (MDR) structured field. The MDR can be found in a Resource Environment Group (REG) for a document or for a group of pages in a document or in the Active Environment Group (AEG) of the page or overlay.

System action

The printer might try to print the page with the error. The entire page might not be printed. If the page with the error contains any positioning errors, then print-error markers might be included on the printed page.

PSF continues processing the current data set with the page that follows the page in error unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the data for the FQN triplet with the error, verify that the input to that program was valid. If the input was valid, see [Mixed Object Document Content Architecture Reference](#) and [PSF for z/OS: Customization](#) for assistance in determining the source of the problem.

User response

If you created the data for the FQN triplet, correct the error and resubmit the print request. See [Mixed Object Document Content Architecture Reference](#) for more information about the contents of the FQN triplet. If the data has no error, the error might be a printer logic error or a PSF error. If you used a program to create the data for the FQN triplet, contact your system programmer.

APS2609I MORE INFORMATION RELATED TO THE PRECEDING ERROR MESSAGE IS FOUND IN APS2610I, WHICH FOLLOWS THIS MESSAGE.

Explanation

The printer reported more information that is related to the error that is described immediately preceding this message. This additional information is presented as reported by the printer in a series of APS2610I messages immediately following this message.

System action

See the accompanying messages for the system action that was taken.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot be initialized or cannot print a separator page or an error message. Notify your system programmer.

System programmer response

To determine an appropriate response, see the specific error conditions that are described in the accompanying messages. For more information about printer sense bytes and the specific error, see the printer publications for the printer that reported this error.

User response

To determine an appropriate response, see the specific error conditions that are described in the accompanying messages.

APS2610I *Variable text reported by the printer.*

Explanation

The printer reported more information that is related to the previous error that is described immediately preceding the APS2609I message. This additional information is reported by the printer in a series of APS2610I messages. If an APS2610I message is a hexadecimal string, it means that the UTF-16BE text that the printer returned is incorrect; PSF is unable to convert the text to printable characters.

System action

See the accompanying messages for the system action that was taken.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot be initialized or cannot print a separator page or an error message. Notify your system programmer.

System programmer response

To determine an appropriate response, see the specific error conditions that are described in this message and the accompanying messages. For more information about printer sense bytes and the specific error, see the printer publications for the printer that reported this error.

User response

To determine an appropriate response, see the specific error conditions that are described in this message and the accompanying messages.

APS2611I **THE TRUETYPE OR OPENTYPE COLLECTION FONT INDEX VALUE FOR A LINKED FONT IS NOT VALID.**

Explanation

An index value that is specified in a TrueType or OpenType Collection Font Index table vector (X'1A') does not correspond to any TrueType or OpenType font in the collection. The TrueType/OpenType Collection Font Index table vector (X'1A') is in the resource access table (RAT), which is installed on a system by an AFP resource installer.

System action

PSF stops processing and printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the table vectors for the RAT with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* for assistance in determining the source of the problem.

User response

If you created the table vectors for the RAT, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the RAT. If the table vector has no error, the error might be a printer logic error or a PSF error. If you used a program to create the table vector for the RAT, contact your system programmer.

APS2612I **A FULL FONT NAME USED TO IDENTIFY A PARTICULAR LINKED TRUETYPE OR OPENTYPE FONT WITHIN THE COLLECTION IS NOT VALID.**

Explanation

The fully qualified name in the Fully Qualified Name triplet (X'02') with FQNTYPE X'6E' in the Begin Resource (BRS, also called BR) structured field is not valid. No TrueType or OpenType font exists in the collection for this full font name. The BRS structured field is found in a print-file level resource group.

System action

PSF stops processing and printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the BRS with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the structured fields for the BRS, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a printer logic error or a PSF error. If you used a program to create the structured fields for the BRS, contact your system programmer.

APS2613I THE FONT TECHNOLOGY VALUE IN A DATA OBJECT FONT DESCRIPTOR TRIPLET (X'8B') IS NOT VALID.

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The font-technology value that is specified in a Data-Object Font Descriptor (X'8B') triplet is not valid.
2. The font technology that is specified in a Data-Object Font Descriptor (X'8B') triplet does not match the actual technology of the font.

The Data-Object Font Descriptor triplet is on a Map Data Resource (MDR) structured field. The MDR can be found in a Resource Environment Group (REG) for a document or for a group of pages in a document or in the Active Environment Group (AEG) of the page or overlay.

System action

PSF stops processing and printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the triplets for the MDR with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the triplets for the MDR, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the triplet. If the triplet has no error, the error might be a printer logic error or a PSF error. If you used a program to create the triplets for the MDR, contact your system programmer.

APS2614I THE VERTICAL FONT SIZE VALUE IN A DATA OBJECT FONT DESCRIPTOR TRIPLET (X'8B') IS NOT VALID.

Explanation

The vertical font size in a Data Object Font Descriptor triplet (X'8B') on a Map Data Resource (MDR) structured field is not valid. The MDR can be found in a Resource Environment Group (REG) for a document or for a group of pages in a document or in the Active Environment Group (AEG) of the page or overlay.

System action

PSF stops processing and printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is

defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the triplets for the MDR with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the triplets for the MDR, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the triplet. If the triplet has no error, the error might be a printer logic error or a PSF error. If you used a program to create the triplets for the MDR, contact your system programmer.

APS2615I THE HORIZONTAL SCALE FACTOR VALUE IN A DATA OBJECT FONT DESCRIPTOR TRIPLET (X'8B') IS NOT VALID.

Explanation

The horizontal scale factor in a Data Object Font Descriptor triplet (X'8B') on a Map Data Resource (MDR) structured field is not valid. The MDR can be found in a Resource Environment Group (REG) for a document or for a group of pages in a document or in the Active Environment Group (AEG) of the page or overlay.

System action

PSF stops processing and printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the triplets for the MDR with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the triplets for the MDR, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the triplet. If the triplet has no error, the error might be a printer logic error or a PSF error. If you used a program to create the triplets for the MDR, contact your system programmer.

APS2616I THE CHARACTER ROTATION VALUE IN A DATA OBJECT FONT DESCRIPTOR TRIPLET (X'8B') IS NOT VALID.

Explanation

The character rotation value in a Data Object Font Descriptor triplet (X'8B') on a Map Data Resource (MDR) structured field is not valid. The MDR can be found in a Resource Environment Group (REG) for a document or for a group of pages in a document or in the Active Environment Group (AEG) of the page or overlay.

System action

PSF stops processing and printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the triplets for the MDR with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the triplets for the MDR, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the triplet. If the triplet has no error, the error might be a printer logic error or a PSF error. If you used a program to create the triplets for the MDR, contact your system programmer.

APS2617I THE ENCODING ENVIRONMENT VALUE IN A DATA OBJECT FONT DESCRIPTOR TRIPLET (X'8B') IS NOT VALID.

Explanation

When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The encoding environment value that is specified in a Data-Object Font Descriptor (X'8B') triplet is not valid.
2. The encoding environment value that is specified in a Data-Object Font Descriptor (X'8B') triplet cannot be used with the specified font technology.

The Data-Object Font Descriptor triplet is on a Map Data Resource (MDR) structured field. The MDR can be found in a Resource Environment Group (REG) for a document or for a group of pages in a document or in the Active Environment Group (AEG) of the page or overlay.

System action

PSF stops processing and printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the triplets for the MDR with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the triplets for the MDR, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the triplet. If the triplet has no error, the error might be a printer logic error or a PSF error. If you used a program to create the triplets for the MDR, contact your system programmer.

APS2618I THE ENVIRONMENT-SPECIFIC ENCODING IDENTIFIER VALUE IN A DATA OBJECT FONT DESCRIPTOR TRIPLET (X'8B') IS NOT VALID.

Explanation

The environment-specific encoding identifier value in a Data Object Font Descriptor triplet (X'8B') on a Map Data Resource (MDR) structured field is not valid. The MDR can be found in a Resource Environment Group (REG) for a document or for a group of pages in a document or in the Active Environment Group (AEG) of the page or overlay.

System action

PSF stops processing and printing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the triplets for the MDR with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the triplets for the MDR, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the triplet. If the triplet has no error, the error might be a printer logic error or a PSF error. If you used a program to create the triplets for the MDR, contact your system programmer.

APS2619I THE UNICODE DATA IN A GRAPHICS OBJECT CHARACTER STRING IS NOT VALID.

Explanation

One of these errors occurred in the Graphics Data (GAD) structured field:

- A high-order surrogate code value was not immediately followed by a low-order surrogate code value. The high-order surrogate range is U+D800 through U+DBFF.
- A low-order surrogate code value was not immediately preceded by a high-order surrogate code value. The low-order surrogate range is U+DC00 through U+DFFF.
- An incorrect UTF-8 byte sequence, as defined in the Unicode specification, was specified.

The UTF-8 error cases are:

- The value in the first byte of the UTF-8 sequence was not in the valid UTF-8 range (X'00'-X'7F' and X'C2'-X'F4').
- The value in the second byte of the UTF-8 sequence was not in the valid UTF-8 range that is allowed by the first byte. The valid ranges for the second byte are:

First Byte	Second Byte
X'C2'-X'DF'	X'80'-X'BF'
X'E0'	X'A0'-X'BF'
X'E1'-X'EC'	X'80'-X'BF'
X'ED'	X'80'-X'9F'
X'EE'-X'EF'	X'80'-X'BF'
X'F0'	X'90'-X'BF'
X'F1'-X'F3'	X'80'-X'BF'
X'F4'	X'80'-X'8F'

- The value in the third or fourth byte of the UTF-8 sequence was not in the valid UTF-8 range for that byte (X'80'-X'BF').

For a formal definition of UTF-8, see the Unicode specification on [The Unicode Consortium \(www.unicode.org\)](http://www.unicode.org).

The GAD structured field is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay, or it might be embedded in a data set that contains line data.

Note: In the formatted sense message (APS830I), the Element Identifier (bytes 16–17) contains the Unicode code value in error, as follows:

- When a high-order surrogate code value was not immediately followed by a low-order surrogate code value, bytes 16–17 contain the high-order surrogate code value.
- When a low-order surrogate code value was not immediately preceded by a high-order surrogate code value, bytes 16–17 contain the low-order surrogate code value.
- When a UTF-8 code value sequence that is not valid was specified, bytes 16–17 contain the first 2 bytes of the UTF-8 code value sequence.

System action

The printer might try to print the page with the error. The entire page might not be printed. If the page with the error contains any positioning errors, then print-error markers might be included on the printed page.

PSF continues processing the current data set with the page that follows the page in error unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the data for the GAD with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the data for the GAD, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the contents of the GAD. If the data has no error, the error might be a printer logic error or a PSF error. If you used a program to create the data for the GAD, contact your system programmer.

APS2620I THE UNICODE DATA IN THE PRINT DATA IS NOT VALID.

Explanation

One of these errors occurred in the Presentation Text (PTX) command data or line data:

- A high-order surrogate code value was not immediately followed by a low-order surrogate code value. The high-order surrogate range is U+D800 through U+DBFF.
- A low-order surrogate code value was not immediately preceded by a high-order surrogate code value. The low-order surrogate range is U+DC00 through U+DFFF.
- An incorrect UTF-8 byte sequence, as defined in the Unicode specification, was specified.

The UTF-8 error cases are:

- The value in the first byte of the UTF-8 sequence was not in the valid UTF-8 range (X'00'-X'7F' and X'C2'-X'F4').
- The value in the second byte of the UTF-8 sequence was not in the valid UTF-8 range that is

allowed by the first byte. The valid ranges for the second byte follow:

First Byte	Second Byte
X'C2'-X'DF'	X'80'-X'BF'
X'E0'	X'A0'-X'BF'
X'E1'-X'EC'	X'80'-X'BF'
X'ED'	X'80'-X'9F'
X'EE'-X'EF'	X'80'-X'BF'
X'F0'	X'90'-X'BF'
X'F1'-X'F3'	X'80'-X'BF'
X'F4'	X'80'-X'8F'

- The value in the third or fourth byte of the UTF-8 sequence was not in the valid UTF-8 range for that byte (X'80'-X'BF').

For a formal definition of UTF-8, see the Unicode specification on [The Unicode Consortium \(www.unicode.org\)](http://www.unicode.org).

Note: In the formatted sense message (APS830I), the Element Identifier (bytes 16–17) contains the Unicode code value in error, as follows:

- When a high-order surrogate code value was not immediately followed by a low-order surrogate code value, bytes 16–17 contain the high-order surrogate code value.
- When a low-order surrogate code value was not immediately preceded by a high-order surrogate code value, bytes 16–17 contain the low-order surrogate code value.
- When a UTF-8 code value sequence that is not valid was specified, bytes 16–17 contain the first 2 bytes of the UTF-8 code value sequence.

System action

Your printer might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

PSF continues processing the current data set with the page that follows the page in error unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set

in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the data for the PTX with the error, verify that the input to that program was valid. If the input was valid, see *Presentation Text Object Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the data for the PTX, correct the error and resubmit the print request. See *Presentation Text Object Content Architecture Reference* for more information about the structured field. If the PTX data has no error, the error might be a printer logic error or a PSF error. If you used a program to create the data for the PTX, contact your system programmer.

APS2621I

AN UNKNOWN GRAPHIC CHARACTER GLOBAL ID (GCGID) VALUE WAS FOUND WITHIN A CODE PAGE USED WITH A DATA OBJECT FONT.

Explanation

The printer does not recognize the GCGID found in the code page that is used with a data object font. One of these conditions occurred:

- The GCGID was not mapped to a Unicode value by the printer's GCGID to Unicode mapping table or by the Unicode extended code page.
- The GCGID is defined in a Unicode extended code page that the printer does not support, so the Unicode mapping is not being used by the printer. To see whether your printer supports Unicode extended code pages, display the printer information report and see whether the Sense Type and Model (STM) Loaded-Font Command-Set Vector contains the X'B005' - Extended (Unicode mapping) code page support property pair.

Note: In the formatted sense message (APS830I), the Element Identifier (bytes 16–17) contains the unknown character's code point. For double-byte code pages, byte 16 contains the section ID and byte 17 contains the second byte of the code point. For single-byte code pages, byte 17 contains the code point.

System action

Your printer might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

PSF continues processing the current data set with the page that follows the page in error unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the data for the code page with the error, verify that the input to that program was valid. If the input was valid, see the *Font Object Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If the GCGID is not defined and you created the data for the code page, correct the error and resubmit the print request. If the GCGID is defined in a Unicode extended code page, verify which printer supports these code pages and submit the print request to a supporting printer. See the *Font Object Content Architecture Reference* for more information about the code page. If the code page has no error, the error might be a printer logic error or a PSF error. If you used a program to create the data for the code page, contact your system programmer.

APS2622I **RESOURCE *resource name* COULD NOT BE RASTERIZED BECAUSE AN X-AXIS ORIGIN OR Y-AXIS ORIGIN WAS SPECIFIED THAT THE PRINTER DOES NOT SUPPORT.**

Explanation

An X-axis origin for object content or Y-axis origin for object content that the printer does not support was specified in the Preprocess Presentation Object (PPO) structured field. When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. A negative XocaOset or YocaOset value was specified in a PPO structured field, but the printer does not support negative offsets.
2. A valid XocaOset or YocaOset value was specified in a PPO structured field, but the printer does not

support that value with the specified units of measure.

The PPO structured field can be specified in a Resource Environment Group (REG) following Map Data Resources (MDRs) and Map Page Overlays (MPOs).

System action

PSF stops processing the REG and continues processing the data set.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured field for the PPO with the error, verify that the input to that program was valid. If the input was valid, see *Mixed Object Document Content Architecture Reference* and *PSF for z/OS: Customization* for assistance in determining the source of the problem.

User response

If you created the structured fields for the PPO, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a printer logic error or a PSF error. If you used a program to create the structured fields for the PPO contact your system programmer.

APS2623I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: CONVERSION VALUE FOR A QR CODE BAR CODE SYMBOL IS NOT VALID OR IS UNSUPPORTED.**

Explanation

The conversion value that is specified in the Bar Code Symbol Data (BSA) structure in a Bar Code Data (BDA) structured field is not valid or is unsupported.

The BDA structured field is contained in a bar code object. The bar code object might be contained in a MO:DCA document, an overlay, or might be associated with a data set containing line data.

The printer you were using might try to print the page in error. The entire page might not be printed. If the

page in error contains any positioning errors, print-error markers might be included on the printed page.

PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS2624I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE VERSION VALUE FOR A QR CODE BAR CODE SYMBOL IS NOT VALID.

Explanation

The version parameter value that is specified in the Bar Code Symbol Data (BSA) data structure in a Bar Code Data (BDA) structured field is not valid.

The BDA structured field is contained in a bar code object. The bar code object might be contained in a MO:DCA document, an overlay, or might be associated with a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the

page in error contains any positioning errors, print-error markers might be included on the printed page.

PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS2625I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE ERROR-CORRECTION-LEVEL VALUE FOR A QR CODE BAR CODE SYMBOL IS NOT VALID.

Explanation

The error-correction-level parameter value that is specified in the Bar Code Symbol Data (BSA) data structure in a Bar Code Data (BDA) structured field is not valid.

The BDA structured field is contained in a bar code object. The bar code object might be contained in a MO:DCA document, an overlay, or might be associated with a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page.

PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS2626I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN INCOMPATIBLE COMBINATION OF SPECIAL-FUNCTION FLAGS WAS SPECIFIED FOR A QR CODE BAR CODE SYMBOL.
-----------------	---

Explanation

An incompatible combination of special-function flags was specified in the Bar Code Symbol Data (BSA) data structure in a Bar Code Data (BDA) structured field. Only one of the FNC1 flags can be B'1'.

The BDA structured field is contained in a bar code object. The bar code object might be contained in a

MO:DCA document, an overlay, or might be associated with a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page.

PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS2627I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE APPLICATION-INDICATOR VALUE FOR A QR CODE BAR CODE SYMBOL IS NOT VALID.
-----------------	--

Explanation

The application-indicator value that is specified in the Bar Code Symbol Data (BSA) data structure in a Bar Code Data (BDA) structured field is not valid.

The BDA structured field is contained in a bar code object. The bar code object might be contained in a MO:DCA document, an overlay, or might be associated with a data set containing line data.

System action

The printer you were using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page.

PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS2628I **INTERVENTION REQUIRED,**
 DEV=pppp, LUNAME=luname.

Explanation

A condition that requires intervention, such as a paper jam, occurred on an SNA-attached printer. The message uses these variables to describe the printer:

pppp

The printer device type; for example, 3816.

luname

The SNA logical unit name of the SNA-attached printer.

System action

PSF stops processing. When the intervention condition is cleared, this message is deleted and PSF continues processing.

Operator response

When this message is displayed on the console, it indicates that a condition exists that requires intervention at an SNA-attached printer. See the operator's guide for the printer that reported this condition, and clear the condition at the printer. If you do not want this message to be issued for this printer, contact your system programmer.

System programmer response

If you do not want this message to be issued for this printer, set the Exit 7 XTP7IMSG flag to B'0' or set the Issue intervention messages value in the Printer Inventory to NO.

User response

No response is necessary.

APS2629I **DATA IN AN INPUT RECORD OR**
 RESOURCE IS NOT VALID: DATA IN
 A UCC/EAN 128, GS1 DATABAR
 EXPANDED, OR GS1 DATABAR
 EXPANDED STACKED BAR CODE IS
 NOT VALID.

Explanation

If your bar code is specified as a bar code object, the data that is specified in the Bar Code Symbol Data (BSA) data structure in a Bar Code Data (BDA) structured field is not valid.

If your bar code is specified with the BARCODE subcommand in a page definition, the data that is selected by the START and LENGTH subcommands on the FIELD command is not valid.

One or more of these conditions exists:

- FNC1 is not the first data character.
- An application identifier (ai) value is not valid.
- Data for an ai does not match the ai definition.
- Insufficient data, or no data, follows an ai.
- Too much data exists for an ai.
- The FNC1 character is used incorrectly.

The bar code object might be contained in a MO:DCA document or an overlay, or might be associated with a data set that contains line data.

Note: In the formatted sense message (APS830I), the Element Identifier (bytes 16–17) contains the application ID (ai) value for the bad data. The ai value is read as four decimal digits, with leading zeros if necessary. For example, ai = 01 is shown as X'0001' and ai = 8005 is shown as X'8005' in bytes 16–17.

System action

The printer might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page.

PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program is valid. If the input is valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object or the page definition, correct the error and resubmit the print request. See the *Bar Code Object Content Architecture Reference* for more information. If the data has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the bar code object, contact your system programmer.

Explanation

If the bar code is specified as a bar code object, the combination of element height and height multiplier values that are specified in the Bar Code Symbol Data (BSA) data structure in a Bar Code Data (BDA) structured field is not valid for the modifier selected.

If the bar code is specified with the BARCODE subcommand in a page definition, the value that is specified for the HEIGHT subcommand on the FIELD command is not valid.

The bar code object might be contained in a MO:DCA document or an overlay, or might be associated with a data set that contains line data.

System action

The printer might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page.

PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program is valid. If the input is valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object or the page definition, correct the error and resubmit the print request. See the *Bar Code Object Content Architecture Reference* for more information. If the data has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS2630I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE COMBINATION OF ELEMENT HEIGHT AND HEIGHT MULTIPLIER VALUES FOR A GS1 DATABAR BAR CODE IS NOT VALID FOR THE MODIFIER SELECTED.

APS2631I THE INFORMATION PROVIDED BY THE PRINTER EXCEEDED THE PSF

BUFFER. THE LAST APS2610I MESSAGE IS INCOMPLETE.

Explanation

The printer reported more information than PSF can store. All the information up to the maximum limit is displayed in the preceding APS2610I messages. The last message is incomplete.

System action

See the accompanying messages for the system action that was taken.

Operator response

If this message displays on the operator's console, it indicates that PSF cannot be initialized or cannot print a separator page or an error message. Notify your system programmer.

System programmer response

No response is necessary.

User response

No response is necessary.

APS2632I DATA IN A FORMDEF RESOURCE IS NOT VALID OR IS UNSUPPORTED: THE MEDIUM FINISHING CONTROL STRUCTURED FIELD SPECIFIES A FINISHING OPTION THAT IS UNSUPPORTED FOR THIS GROUP OF PAGES.

Explanation

The Finishing option field (byte 3) in a Finishing Operation triplet (X'85') contains an unsupported value for the specified group of pages for this finisher. The finisher is unable to do the finishing request on the group of pages that are specified by the MFC Scope field (byte 3) of the Medium Finishing Control (MFC) structured field.

Finishing Operation triplets are specified in the MFC structured field. The MFC is specified in the Document Environment Group of the form definition or in a Medium Map.

System action

Reporting of this exception can be controlled by the Finishing Fidelity triplet in the Presentation Fidelity Control (PFC) command. The PFC command is contained in a form definition. When the Finishing

Fidelity triplet sets the continuation rule to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and the data set is marked unprintable. PSF releases the current data set back to JES and requests that it is held by the system unless PRTEROR=QUIT was specified on the OUTPUT statement.

When the Finishing Fidelity triplet sets the continuation rule to DO NOT STOP (X'02'), one of these actions occurs:

- If the printer supports the PFC Finishing Fidelity triplet and the REPORT field is set to REPORT (X'01'), the printer reports this exception. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, print-error markers might be included on the printed page.
- If the printer supports the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.
- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer reports this exception but PSF does not issue the error message. The printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.
- If the printer does not support the PFC Finishing Fidelity triplet and the REPORT field is set to REPORT (X'01'), the printer reports this exception and PSF issues the error message. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. The finishing operation is not applied or is applied incompletely. If the page in error contains any positioning errors, print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in

the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the MFC with the error, verify that the input to that program is valid. If the input is valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If the output is not acceptable:

- Verify that you requested the appropriate form definition for the finishing operation intended.
- Submit the print request to a printer that can do the finishing operation.
- If you created the structured fields for the form definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* and *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF logic error. If you used a program to create the structured fields for the form definition, contact your system programmer.

APS2633I DATA IN A COLOR MANAGEMENT RESOURCE IS NOT VALID: THE LENGTH VALUE IN THE CMR HEADER FOR A COLOR MANAGEMENT RESOURCE IS NOT VALID.

Explanation

The length field in the CMR header for a color management resource (CMR) is not valid.

Note: In the formatted sense message (APS830I), the Element Identifier (bytes 16–17) contains X'EFFa', where *a* identifies the specific field within the header.

System action

Reporting of this exception can be controlled by the Color Fidelity triplet in the Presentation Fidelity Control (PFC) command. The PFC command is contained in a form definition.

When the Color Fidelity triplet sets the CONTINUE field equal to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and marks the data set as unprintable. PSF releases the current data set back to JES and requests that the system hold the data set unless

PRTEROR=QUIT was specified on the OUTPUT statement.

When the Color Fidelity triplet sets the CONTINUE field equal to DO NOT STOP (X'02'), one of these actions occurs:

- If the printer supports the PFC Color Fidelity triplet, the printer reports this exception if the REPORT field is set to REPORT. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The printer that you are using might attempt to print the page in error, but the entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. If the REPORT field was set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.
- If the printer does not support the PFC Color Fidelity triplet, this exception might or might not be reported. In either case, the printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The printer that you are using might attempt to print the page in error, but the entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the tags for the CMR with the error, verify that the input to that program was valid. If the input is valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information in the User Response section to correct the error.

User response

If you created the tags for the CMR, correct the error and resubmit the print request. See *Color Management Object Content Architecture Reference* for more information about the tag. If the tag has no error, the

error might be a printer logic error. If you used a program to create the tags for the CMR, contact your system programmer.

APS2634I DATA IN A COLOR MANAGEMENT RESOURCE IS NOT VALID: UNSUPPORTED TAGID VALUE IN A CMR TAG.

Explanation

The CMR Data field for a color management resource (CMR) contains an unsupported TagID value.

Note: In the formatted sense message (APS830I), the Element Identifier (bytes 16–17) contains the CMR TagID value for the tag that caused the error.

System action

Reporting of this exception can be controlled by the CMR Tag Fidelity triplet in the Presentation Fidelity Control (PFC) command. The PFC command is contained in a form definition.

When the CMR Tag Fidelity triplet sets the CONTINUE field equal to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and marks the data set as unprintable. PSF releases the current data set back to JES and requests that the system hold the data set unless PRTEROR=QUIT was specified on the OUTPUT statement.

When the CMR Tag Fidelity triplet sets the CONTINUE field equal to DO NOT STOP (X'02'), one of these actions occurs:

- If the printer supports the PFC CMR Tag Fidelity triplet, the printer reports this exception if the REPORT field is set to REPORT. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The printer that you are using might attempt to print the page in error, but the entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. If the REPORT field was set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.
- If the printer does not support the PFC CMR Tag Fidelity triplet, this exception might or might not be reported. In either case, the printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery

action. The printer that you are using might attempt to print the page in error, but the entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the tags for the CMR with the error, verify that the input to that program was valid. If the input is valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information in the User Response section to correct the error.

User response

If you created the tags for the CMR, correct the error and resubmit the print request. See *Color Management Object Content Architecture Reference* for more information about the tag. If the tag has no error, the error might be a printer logic error. If you used a program to create the tags for the CMR, contact your system programmer.

APS2635I DATA IN A COLOR MANAGEMENT RESOURCE IS NOT VALID: THE COUNT VALUE IN A CMR TAG IS NOT VALID.

Explanation

The CMR Data field for a color management resource (CMR) contains a tag with a Count value that is not valid.

Note: In the formatted sense message (APS830I), the Element Identifier (bytes 16–17) contains the CMR TagID value for the tag that caused the error.

System action

Reporting of this exception can be controlled by the Color Fidelity triplet in the Presentation Fidelity Control (PFC) command. The PFC command is contained in a form definition.

When the Color Fidelity triplet sets the CONTINUE field equal to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the

error and marks the data set as unprintable. PSF releases the current data set back to JES and requests that the system hold the data set unless PRTEROR=QUIT was specified on the OUTPUT statement.

When the Color Fidelity triplet sets the CONTINUE field equal to DO NOT STOP (X'02'), one of these actions occurs:

- If the printer supports the PFC Color Fidelity triplet, the printer reports this exception if the REPORT field is set to REPORT. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The printer that you are using might attempt to print the page in error, but the entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. If the REPORT field was set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.
- If the printer does not support the PFC Color Fidelity triplet, this exception might or might not be reported. In either case, the printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The printer that you are using might attempt to print the page in error, but the entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the tags for the CMR with the error, verify that the input to that program was valid. If the input is valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information in the User Response section to correct the error.

User response

If you created the tags for the CMR, correct the error and resubmit the print request. See *Color Management Object Content Architecture Reference* for more information about the tag. If the tag has no error, the error might be a printer logic error. If you used a program to create the tags for the CMR, contact your system programmer.

APS2636I	DATA IN A COLOR MANAGEMENT RESOURCE IS NOT VALID: THE FIELDTYPE VALUE IN A CMR TAG IS NOT VALID.
-----------------	---

Explanation

The CMR Data field for a color management resource (CMR) contains a tag with a Fieldtype value that is not valid.

Note: In the formatted sense message (APS830I), the Element Identifier (bytes 16–17) contains the CMR TagID value for the tag that caused the error.

System action

Reporting of this exception can be controlled by the Color Fidelity triplet in the Presentation Fidelity Control (PFC) command. The PFC command is contained in a form definition.

When the Color Fidelity triplet sets the CONTINUE field equal to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and marks the data set as unprintable. PSF releases the current data set back to JES and requests that the system hold the data set unless PRTEROR=QUIT was specified on the OUTPUT statement.

When the Color Fidelity triplet sets the CONTINUE field equal to DO NOT STOP (X'02'), one of these actions occurs:

- If the printer supports the PFC Color Fidelity triplet, the printer reports this exception if the REPORT field is set to REPORT. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The printer that you are using might attempt to print the page in error, but the entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. If the REPORT field was set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.
- If the printer does not support the PFC Color Fidelity triplet, this exception might or might not be

reported. In either case, the printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The printer that you are using might attempt to print the page in error, but the entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the tags for the CMR with the error, verify that the input to that program was valid. If the input is valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information in the User Response section to correct the error.

User response

If you created the tags for the CMR, correct the error and resubmit the print request. See *Color Management Object Content Architecture Reference* for more information about the tag. If the tag has no error, the error might be a printer logic error. If you used a program to create the tags for the CMR, contact your system programmer.

APS2637I DATA IN A COLOR MANAGEMENT RESOURCE IS NOT VALID: THE CMR DATA FOR A CMR IS MISSING A REQUIRED TAG.

Explanation

The CMR Data field for a color management resource (CMR) is missing a required tag for its CMR type.

Note: The Element Identifier bytes 16–17 in the formatted sense message contain the CMR TagID value for the tag that caused the error.

System action

Reporting of this exception can be controlled by the Color Fidelity triplet in the Presentation Fidelity Control (PFC) command. The PFC command is contained in a form definition.

When the Color Fidelity triplet sets the CONTINUE field equal to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and marks the data set as unprintable. PSF releases the current data set back to JES and requests that the system hold the data set unless PRTEROR=QUIT was specified on the OUTPUT statement.

When the Color Fidelity triplet sets the CONTINUE field equal to DO NOT STOP (X'02'), one of these actions occurs:

- If the printer supports the PFC Color Fidelity triplet, the printer reports this exception if the REPORT field is set to REPORT. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The printer that you are using might attempt to print the page in error, but the entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. If the REPORT field was set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.
- If the printer does not support the PFC Color Fidelity triplet, this exception might or might not be reported. In either case, the printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The printer that you are using might attempt to print the page in error, but the entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the tags for the CMR with the error, verify that the input to that program was valid. If the input is valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information in the User Response section to correct the error.

User response

If you created the tags for the CMR, correct the error and resubmit the print request. See *Color Management Object Content Architecture Reference* for more information about the tag. If the tag has no error, the error might be a printer logic error. If you used a program to create the tags for the CMR, contact your system programmer.

APS2638I DATA IN A COLOR MANAGEMENT RESOURCE IS NOT VALID: THE SEQUENCE OF CMR TAGS SPECIFIED IS NOT VALID.

Explanation

The CMR Data field for a color management resource (CMR) contains tags out of sequence. Tags in a CMR must be specified in increasing order by their TagIDs.

Note: In the formatted sense message (APS830I), the Element Identifier (bytes 16–17) contains the CMR TagID value for the tag that caused the error.

System action

Reporting of this exception can be controlled by the Color Fidelity triplet in the Presentation Fidelity Control (PFC) command. The PFC command is contained in a form definition.

When the Color Fidelity triplet sets the CONTINUE field equal to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and marks the data set as unprintable. PSF releases the current data set back to JES and requests that the system hold the data set unless PRTEROR=QUIT was specified on the OUTPUT statement.

When the Color Fidelity triplet sets the CONTINUE field equal to DO NOT STOP (X'02'), one of these actions occurs:

- If the printer supports the PFC Color Fidelity triplet, the printer reports this exception if the REPORT field is set to REPORT. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The printer that you are using might attempt to print the page in error, but the entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. If the REPORT field was set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.
- If the printer does not support the PFC Color Fidelity triplet, this exception might or might not be

reported. In either case, the printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The printer that you are using might attempt to print the page in error, but the entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the tags for the CMR with the error, verify that the input to that program was valid. If the input is valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information in the User Response section to correct the error.

User response

If you created the tags for the CMR, correct the error and resubmit the print request. See *Color Management Object Content Architecture Reference* for more information about the tag. If the tag has no error, the error might be a printer logic error. If you used a program to create the tags for the CMR, contact your system programmer.

APS2639I DATA IN A COLOR MANAGEMENT RESOURCE IS NOT VALID: THE FIELD VALUE IN A CMR HEADER OR CMR TAG IS NOT VALID OR IS UNSUPPORTED.

Explanation

The CMR Data field for a color management resource (CMR) contains a tag with a field value that is not valid or is unsupported.

Note: In the formatted sense message (APS830I), the Element Identifier (bytes 16–17) contains the CMR TagID value for the tag that caused the error. For errors in the CMR header, the Element Identifier (bytes 16–17) contains X'EFFa' where *a* identifies the specific field within the header.

System action

Reporting of this exception can be controlled by the Color Fidelity triplet in the Presentation Fidelity Control (PFC) command. The PFC command is contained in a form definition.

When the Color Fidelity triplet sets the CONTINUE field equal to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and marks the data set as unprintable. PSF releases the current data set back to JES and requests that the system hold the data set unless PRTEROR=QUIT was specified on the OUTPUT statement.

When the Color Fidelity triplet sets the CONTINUE field equal to DO NOT STOP (X'02'), one of these actions occurs:

- If the printer supports the PFC Color Fidelity triplet, the printer reports this exception if the REPORT field is set to REPORT. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The printer that you are using might attempt to print the page in error, but the entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. If the REPORT field was set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.
- If the printer does not support the PFC Color Fidelity triplet, this exception might or might not be reported. In either case, the printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The printer that you are using might attempt to print the page in error, but the entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the tags for the CMR with the error, verify that the input to

that program was valid. If the input is valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information in the User Response section to correct the error.

User response

If you created the tags for the CMR, correct the error and resubmit the print request. See *Color Management Object Content Architecture Reference* for more information about the tag. If the tag has no error, the error might be a printer logic error. If you used a program to create the tags for the CMR, contact your system programmer.

APS2640I DATA IN A COLOR MANAGEMENT RESOURCE IS NOT VALID: INCONSISTENT CMR TAG CONTENTS.

Explanation

The CMR Data field for a color management resource (CMR) contains a tag with inconsistent or conflicting values. For example, the count field and the number of components in the tag do not match.

Note: In the formatted sense message (APS830I), the Element Identifier (bytes 16–17) contains the CMR TagID value for the tag that caused the error.

System action

Reporting of this exception can be controlled by the Color Fidelity triplet in the Presentation Fidelity Control (PFC) command. The PFC command is contained in a form definition.

When the Color Fidelity triplet sets the CONTINUE field equal to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and marks the data set as unprintable. PSF releases the current data set back to JES and requests that the system hold the data set unless PRTEROR=QUIT was specified on the OUTPUT statement.

When the Color Fidelity triplet sets the CONTINUE field equal to DO NOT STOP (X'02'), one of these actions occurs:

- If the printer supports the PFC Color Fidelity triplet, the printer reports this exception if the REPORT field is set to REPORT. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The printer that you are using might attempt to print the page in error, but the entire page might not be printed. If the page in error contains any positioning

errors, then print-error markers might be included on the printed page. If the REPORT field was set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.

- If the printer does not support the PFC Color Fidelity triplet, this exception might or might not be reported. In either case, the printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The printer that you are using might attempt to print the page in error, but the entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the tags for the CMR with the error, verify that the input to that program was valid. If the input is valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information in the User Response section to correct the error.

User response

If you created the tags for the CMR, correct the error and resubmit the print request. See *Color Management Object Content Architecture Reference* for more information about the tag. If the tag has no error, the error might be a printer logic error. If you used a program to create the tags for the CMR, contact your system programmer.

APS2641I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A COLOR MANAGEMENT RESOURCE IS NOT AVAILABLE.

Explanation

A color management resource (CMR) is needed to process specific print data. However, a CMR is unavailable because the printer does not have a default CMR for that type of color data and a host-called CMR is not supplied. The device default CMRs

defined in the *Color Management Object Content Architecture Reference* must be supported by the printer, but defaults for other color spaces are optional and a host-called CMR must be supplied.

System action

Reporting of this exception can be controlled by the Color Fidelity triplet in the Presentation Fidelity Control (PFC) command. The PFC command is contained in a form definition.

When the Color Fidelity triplet sets the CONTINUE field equal to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and marks the data set as unprintable. PSF releases the current data set back to JES and requests that the system hold the data set unless PRTEROR=QUIT was specified on the OUTPUT statement.

When the Color Fidelity triplet sets the CONTINUE field equal to DO NOT STOP (X'02'), one of these actions occurs:

- If the printer supports the PFC Color Fidelity triplet, the printer reports this exception if the REPORT field is set to REPORT. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The printer that you are using might attempt to print the page in error, but the entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. If the REPORT field was set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.
- If the printer does not support the PFC Color Fidelity triplet, this exception might or might not be reported. In either case, the printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The printer that you are using might attempt to print the page in error, but the entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in

the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the data set with the error, verify that the input to that program was valid. If the missing CMR is not installed in the RAT or is not correctly mapped to a data object resource, use an AFP resource installer to update the RAT. If the input is valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information in the User Response section to correct the error.

User response

See *Color Management Object Content Architecture Reference* for more information about device default CMRs. If a device default CMR must be supported by the printer, this error might be a printer logic error. If the device default CMR is optional for this color space, the required CMR must be specified on the host. The CMR can be mapped directly in the job or indirectly through the resource access table (RAT). If you used a program to create the structured fields for the job or to install the resources in a RAT, contact your system programmer.

APS2644I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE INVOKED, MEDIA-SPECIFIC INSTRUCTION CMR DOES NOT MATCH THE SELECTED MEDIA.

Explanation

An invoked instruction or device link (DL) color management resource (CMR) is requested, but the media-specific fields in the CMR header do not match the current media that is used by the printer for this sheet.

System action

Reporting of this exception can be controlled by the Color Fidelity triplet in the Presentation Fidelity Control (PFC) command. The PFC command is contained in a form definition.

When the Color Fidelity triplet sets the CONTINUE field equal to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and marks the data set as unprintable. PSF releases the current data set back to JES and requests that the system hold the data set unless

PRTEROR=QUIT was specified on the OUTPUT statement.

When the Color Fidelity triplet sets the CONTINUE field equal to DO NOT STOP (X'02'), one of these actions occurs:

- If the printer supports the PFC Color Fidelity triplet, the printer reports this exception if the REPORT field is set to REPORT. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The printer that you are using might attempt to print the page in error, but the entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. If the REPORT field was set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.
- If the printer does not support the PFC Color Fidelity triplet, this exception might or might not be reported. In either case, the printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The printer that you are using might attempt to print the page in error, but the entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the job with the error or the CMR in the RAT, verify that the input to that program was valid. If the correct media-specific instruction CMR is not installed or is not correctly mapped to a data object resource, use an AFP resource installer to update the RAT. If the input is valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information in the User Response section to correct the error.

User response

If the output is unacceptable, see *Color Management Object Content Architecture Reference* for more information about the rules for matching media-specific fields with media type on the printer:

- If the wrong media was loaded in the printer, correct the error and resubmit the job.
- If the loaded media is correct, but the media characteristics that are selected by the printer operator do not match the loaded media, contact your printer operator to correct the error and resubmit the job.
- If the media-specific instruction CMR is not what you intended, change the structured fields in the job that specify the incorrect CMR to specify the correct media-specific instruction CMR.
- If the job does not explicitly map the incorrect CMR, the incorrect CMR might be associated with the job through the resource access table (RAT). If you created the data object RAT or CMR RAT used by this job, make sure the correct media-specific instruction CMR is installed and mapped to the appropriate data object resources. Otherwise, contact your system programmer.
- If the media-specific CMR must match the media that is used by the printer, this error might be a printer logic error.

APS2645I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE REQUESTED GENERIC CMR IS NOT SUPPORTED.

Explanation

A generic color management resource (CMR) is selected, but the printer does not have the appropriate device-specific CMR to use in place of the generic CMR.

System action

Reporting of this exception can be controlled by the Color Fidelity triplet in the Presentation Fidelity Control (PFC) command. The PFC command is contained in a form definition.

When the Color Fidelity triplet sets the CONTINUE field equal to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and marks the data set as unprintable. PSF releases the current data set back to JES and requests that the system hold the data set unless PRTEROR=QUIT was specified on the OUTPUT statement.

When the Color Fidelity triplet sets the CONTINUE field equal to DO NOT STOP (X'02'), one of these actions occurs:

- If the printer supports the PFC Color Fidelity triplet, the printer reports this exception if the REPORT field is set to REPORT. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The printer that you are using might attempt to print the page in error, but the entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. If the REPORT field was set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.
- If the printer does not support the PFC Color Fidelity triplet, this exception might or might not be reported. In either case, the printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The printer that you are using might attempt to print the page in error, but the entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to install the CMRs, verify that the input to that program was valid. If the required device-specific CMR is not installed in the RAT or is not correctly mapped to a data object resource, use an AFP resource installer to update the RAT. If the input is valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information in the User Response section to correct the error.

User response

If you created the CMR resource access table (RAT) being used by this job, then install the required device-

specific CMR. Otherwise, contact your system programmer.

APS2646I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN INVOKED, SELECTED CMR WAS NOT USED. THE PRINTER USED AN APPROPRIATE DEFAULT CMR.

Explanation

A color management resource (CMR) is invoked, selected for use, and valid, but it cannot be used. When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. A printer-operator control is invoked to achieve a specific look that overrides a user-specified tone transfer curve CMR.
2. A selected halftone CMR is not appropriate for the printer; for example, a threshold-array halftone is invoked and selected for use with an ink jet printer, or an error-diffusion halftone is invoked and selected for use with a laser printer.
3. A halftone or tone transfer curve CMR is applied to a portion of a sheet. However, a subsequent halftone or tone transfer curve CMR is not supported because the printer can allow only one halftone or tone transfer curve CMR after a complete sheet is created.
4. A limited number of halftone or tone transfer curve CMRs are supported on a sheet; for example, when data overlaps, only one halftone can be applied to the overlapping area.

System action

Reporting of this exception can be controlled by the Color Fidelity triplet in the Presentation Fidelity Control (PFC) command. The PFC command is contained in a form definition.

When the Color Fidelity triplet sets the CONTINUE field equal to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and marks the data set as unprintable. PSF releases the current data set back to JES and requests that the system hold the data set unless PRERROR=QUIT was specified on the OUTPUT statement.

When the Color Fidelity triplet sets the CONTINUE field equal to DO NOT STOP (X'02'), one of these actions occurs:

- If the printer supports the PFC Color Fidelity triplet, the printer reports this exception if the REPORT field

is set to REPORT. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The printer that you are using might attempt to print the page in error, but the entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. If the REPORT field was set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.

- If the printer does not support the PFC Color Fidelity triplet, this exception might or might not be reported. In either case, the printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The printer that you are using might attempt to print the page in error, but the entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the tags for the CMR with the error, verify that the input to that program was valid. If the input is valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information in the User Response section to correct the error.

User response

If the output is unacceptable, do these actions:

- Verify that a print-operator control did not override your CMR.
- If you created the structured fields in your job that specify the CMR in error, verify that the appropriate CMR is being specified for the printer that is used.

APS2647I THE PRINTER DETECTED A COLOR RELATED ERROR WITHIN A PRESENTATION OBJECT CONTAINER. CODE = (code and brief description).

Explanation

The printer detected a color-related error in a data object resource. For a complete list of the error codes and descriptions, see *Intelligent Printer Data Stream Reference*.

System action

Reporting of this exception can be controlled by the Color Fidelity triplet in the Presentation Fidelity Control (PFC) command. The PFC command is contained in a form definition.

When the Color Fidelity triplet sets the CONTINUE field equal to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and marks the data set as unprintable. PSF releases the current data set back to JES and requests that the system hold the data set unless PRTEROR=QUIT was specified on the OUTPUT statement.

When the Color Fidelity triplet sets the CONTINUE field equal to DO NOT STOP (X'02'), one of these actions occurs:

- If the printer supports the PFC Color Fidelity triplet, the printer reports this exception if the REPORT field is set to REPORT. PSF stops processing the data set that was being processed at the time of the error and marks the data set as unprintable. PSF releases the current data set back to JES and requests that the system hold it unless PRTEROR=QUIT was specified on the OUTPUT statement. If the REPORT field was set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.
- If the printer does not support the PFC Color Fidelity triplet, this exception might or might not be reported. In either case, the printer takes its continuation action for the page and PSF reports this exception if the REPORT field is set to REPORT. PSF stops processing the data set that was being processed at the time of the error and marks the data set as unprintable. PSF releases the current data set back to JES and requests that the system hold it unless PRTEROR=QUIT was specified on the OUTPUT statement.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the resource with the error, verify that the input to that program was valid. If the input is valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information in the User Response section to correct the error.

User response

If you created the structured fields for the object container resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the object container resource, contact your system programmer.

APS2648I

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE SPECIFIED SET EXTENDED BILEVEL IMAGE COLOR VALUE IS NOT VALID.

Explanation

A Set Extended Bilevel Image Color value for an image object is not valid. When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. A specified color space value is not valid.
2. A specified size value is not valid.
3. A specified color value is not valid.

The Set Extended Bilevel Image Color self-defining field is in the Image Data Descriptor (IDD) structured field. The IDD structured field is in an image object. The image object might be contained in a MO:DCA document, overlay, or page segment; or embedded in a data set containing line data.

System action

Reporting of this exception can be controlled by the Color Fidelity triplet in the Presentation Fidelity Control (PFC) command. The PFC command is contained in a form definition.

When the Color Fidelity triplet sets the CONTINUE field equal to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the

error and marks the data set as unprintable. PSF releases the current data set back to JES and requests that the system hold the data set unless PRTEROR=QUIT was specified on the OUTPUT statement.

When the Color Fidelity triplet sets the CONTINUE field equal to DO NOT STOP (X'02'), one of these actions occurs:

- If the printer supports the PFC Color Fidelity triplet, the printer reports this exception if the REPORT field is set to REPORT. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The printer that you are using might attempt to print the page in error, but the entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. If the REPORT field was set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.
- If the printer does not support the PFC Color Fidelity triplet, this exception might or might not be reported. In either case, the printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The printer that you are using might attempt to print the page in error, but the entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the image object with the error, verify that the input to that program was valid. If the input is valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information in the User Response section to correct the error.

User response

If you created the structured fields for the image object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the image object, contact your system programmer.

APS2649I DATA IN A COLOR MANAGEMENT RESOURCE IS NOT VALID: INCORRECTLY ORDERED REPEATING GROUPS FOR AN INDEXED COLOR TAG.

Explanation

The tags that are used to translate 2-byte indexed color values to a specific color space are specified in repeating groups. These repeating groups must be sorted in ascending order of indexed color value.

Note: In the formatted sense message (APS830I), the Element Identifier (bytes 16-17) contains the color management resource (CMR) TagID value for the tag that caused the error.

System action

Reporting of this exception can be controlled by the Color Fidelity triplet in the Presentation Fidelity Control (PFC) command. The PFC command is contained in a form definition.

When the Color Fidelity triplet sets the CONTINUE field equal to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and marks the data set as unprintable. PSF releases the current data set back to JES and requests that the system hold the data set unless PRTEROR=QUIT was specified on the OUTPUT statement.

When the Color Fidelity triplet sets the CONTINUE field equal to DO NOT STOP (X'02'), one of these actions occurs:

- If the printer supports the PFC Color Fidelity triplet and the REPORT field is set to REPORT, the printer reports this exception. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The printer that you are using might attempt to print the page in error, but the entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. If the REPORT field was set to DO NOT REPORT (X'02'), the printer does not report this

error to PSF but takes its continuation action and continues processing the page.

- If the printer does not support the PFC Color Fidelity triplet, this exception might or might not be reported. In either case, the printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The printer that you are using might attempt to print the page in error, but the entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the tags for the CMR with the error, verify that the input to that program was valid. If the input is valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information in the User Response section to correct the error.

User response

If you created the tags for the CMR, correct the error and resubmit the print request. See *Color Management Object Content Architecture Reference* for more information about the tag. If the tag has no error, the error might be a printer logic error. If you used a program to create the tags for the CMR, contact your system programmer.

APS2650I	DATA IN A COLOR MANAGEMENT RESOURCE IS NOT VALID: A COLORANT NAME IS SPECIFIED IN MORE THAN ONE REPEATING GROUP IN A COLORANT IDENTIFICATION LIST TAG.
-----------------	---

Explanation

A colorant identification list consists of repeating groups of colorant names. Each of these names must be unique; no duplicates are allowed.

Note: In the formatted sense message (APS830I), the Element Identifier (bytes 16-17) contains the color

management resource (CMR) TagID value for the tag that caused the error.

System action

Reporting of this exception can be controlled by the Color Fidelity triplet in the Presentation Fidelity Control (PFC) command. The PFC command is contained in a form definition.

When the Color Fidelity triplet sets the CONTINUE field equal to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and marks the data set as unprintable. PSF releases the current data set back to JES and requests that the system hold the data set unless PRTEROR=QUIT was specified on the OUTPUT statement.

When the Color Fidelity triplet sets the CONTINUE field equal to DO NOT STOP (X'02'), one of these actions occurs:

- If the printer supports the PFC Color Fidelity triplet and the REPORT field is set to REPORT, the printer reports this exception. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The printer that you are using might attempt to print the page in error, but the entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. If the REPORT field was set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.
- If the printer does not support the PFC Color Fidelity triplet, this exception might or might not be reported. In either case, the printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action. The printer that you are using might attempt to print the page in error, but the entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the tags for the CMR with the error, verify that the input to that program was valid. If the input is valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information in the User Response section to correct the error.

User response

If you created the tags for the CMR, correct the error and resubmit the print request. See *Color Management Object Content Architecture Reference* for more information about the tag. If the tag has no error, the error might be a printer logic error. If you used a program to create the tags for the CMR, contact your system programmer.

APS2661I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: INCORRECT OR INSUFFICIENT DATA WAS ENCOUNTERED IN A ROYAL MAIL RED TAG BAR CODE OBJECT.

Explanation

Within a Royal Mail RED TAG bar code object, data is incorrect or insufficient. Exactly 21 numeric digits must be in the input data. The printer uses the BCOCA range to check that each field of the input data is valid.

System action

The printer that you are using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If

the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object or the page definition, correct the error and resubmit the print request. See *Bar Code Object Content Architecture Reference* for more information about bar code objects. See *Page Printer Formatting Aid: User's Guide* for more information about creating page definitions. If the structured field or page definition has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS2662I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE OBJECT OFFSET TRIPLET SPECIFIED FOR A PAGINATED DATA OBJECT RESOURCE SELECTED AN OBJECT THAT COULD NOT BE FOUND. THE PAGE IS PRINTED WITHOUT THE OBJECT.

Explanation

The object offset specified for a data object resource selected an object that does not exist. An object offset is specified with the X'5A' triplet on the Container Data Descriptor (CDD), the Include Object (IOB), or the Preprocess Presentation Object (PPO) structured field for a data object resource.

The CDD structured field is specified inside the presentation object container resource. The IOB structured field can be contained in a page definition, an overlay, or a MO:DCA page, or it can be embedded in line data. The PPO structured field is specified in the Resource Environment Group (REG) for the print data set.

System action

The printer that you are using might try to print the page in error; however, the entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the data object resource, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* or *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the data object resource, contact your system programmer.

APS2663I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A UNICODE COMPLEX TEXT PARAMETER VALUE IS NOT VALID.

Explanation

An incorrect PTOCA Unicode Complex Text (UCT) control sequence parameter value was found in a Presentation Text Data (PTX) structured field, which might be contained in a MO:DCA document, a PTOCA object, an overlay, or a page segment; or it might be embedded in a data set containing line data.

For printers that return the IPDS Sense Type and Model (STM) Text Command-Set vector X'4303' property pair, the error is with the UCT data length value (CTLNGTH).

System action

The printer that you are using might try to print the page in error; however, the entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error,

unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document, a PTOCA object, an overlay, or a page segment and you created the structured fields in the object that contains the error, correct the text-control sequence in the PTX structured field. See *Mixed Object Document Content Architecture Reference* and *Presentation Text Object Content Architecture Reference* for more information about the structured field and control sequence. If the PTX has no errors, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the MO:DCA document, PTOCA object, overlay, or page segment, contact your system programmer. If you are printing a data set containing line data with embedded structured fields, correct the text-control sequence in the PTX structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you are printing a data set containing line data without embedded structured fields, the error might be a PSF or printer logic error.

To determine whether your printer returns the STM property pair, see the printer information report for this printer (specified with the PRTINFO DD statement in the PSF startup procedure). Contact your system programmer for help locating this report.

APS2664I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE FONT OBJECT ID SPECIFIED IN A GLYPH LAYOUT CONTROL DOES NOT MATCH THE FONT OBJECT ID OF THE CURRENT FONT BEING USED TO RENDER THE TEXT.

Explanation

The font object ID (OID), specified in a Presentation Text Data (PTX) Glyph Layout Control (GLC) control sequence FONTOID parameter, does not match the font OID of the font that is used to render the text because of one of these:

- The font OID does not match the font OID of the current font or any font that is linked to the current font.
- The font OID matched the OID of a font collection, but the full font name (FFONTNME) specified in the GLC does not match any font in the collection.
- The printer does not have a font OID for the current font to compare against the GLC font OID.

The element identifier in the formatted sense byte message (APS830I) contains the number that identifies the specific cause of the error.

The text-control came from a PTX structured field, which might be contained in a MO:DCA document, a PTOCA object, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer that you are using might try to print the page in error; however, the entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document, a PTOCA object, an overlay, or a page segment and you created the structured fields in the object that contains the error, correct the text-control sequence in the PTX

structured field. See *Mixed Object Document Content Architecture Reference* and *Presentation Text Object Content Architecture Reference* for more information about the structured field and control sequence. If the PTX has no errors, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the MO:DCA document, PTOCA object, overlay, or page segment, contact your system programmer. If you are printing a data set containing line data with embedded structured fields, correct the text-control sequence in the PTX structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you are printing a data set containing line data without embedded structured fields, the error might be a PSF or printer logic error.

See the accompanying environmental messages for the name of the current font.

APS2665I

DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A PTOCA GLYPH LAYOUT CONTROL CHAIN WAS ENCOUNTERED, BUT THE CURRENT FONT IS NOT A TRUETYPE OR OPENTYPE FONT.

Explanation

The current font that is used to process the glyph runs in a PTOCA Glyph Layout Control (GLC) chain is not a TrueType or OpenType font. The current font is specified in a previous Presentation Text Data (PTX) Set Coded Font Local control sequence.

The text-control came from a PTX structured field, which might be contained in a MO:DCA document, a PTOCA object, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer that you are using might try to print the page in error; however, the entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document, a PTOCA object, an overlay, or a page segment and you created the structured fields in the object that contains the error, correct the text-control sequence in the PTX structured field. See *Mixed Object Document Content Architecture Reference* and *Presentation Text Object Content Architecture Reference* for more information about the structured field and control sequence. If the PTX has no errors, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the MO:DCA document, PTOCA object, overlay, or page segment, contact your system programmer. If you are printing a data set containing line data with embedded structured fields, correct the text-control sequence in the PTX structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you are printing a data set containing line data without embedded structured fields, the error might be a PSF or printer logic error.

See the accompanying environmental messages for the name of the current font.

APS2666I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A GLYPH ID SPECIFIED IN A GLYPH ID RUN CONTROL SEQUENCE WAS NOT FOUND IN THE CURRENT FONT.
-----------------	---

Explanation

A glyph ID specified in a PTOCA Glyph ID Run (GIR) was not found in the current font. The current font is specified in the FONTOID parameter of a Presentation Text Data (PTX) Glyph Layout Control (GLC) control sequence for this GLC chain or a previous one if none is specified for this one.

The text-control came from a PTX structured field, which might be contained in a MO:DCA document, a PTOCA object, an overlay, or a page segment; or it might be embedded in a data set containing line data.

Note: In the formatted sense message (APS830I), the Element Identifier (bytes 16-17) contains the failing glyph ID.

System action

The printer that you are using might try to print the page in error; however, the entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document, a PTOCA object, an overlay, or a page segment and you created the structured fields in the object that contains the error, correct the text-control sequence in the PTX structured field. See *Mixed Object Document Content Architecture Reference* and *Presentation Text Object Content Architecture Reference* for more information about the structured field and control sequence. If the PTX has no errors, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the MO:DCA document, PTOCA object, overlay, or page segment, contact your system programmer. If you are printing a data set containing line data with embedded structured fields, correct the text-control sequence in the PTX structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you are printing a data set containing line data without embedded structured fields, the error might be a PSF or printer logic error.

APS2667I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A MISSING OR INCORRECT CONTROL SEQUENCE WAS FOUND IN A GLYPH LAYOUT CONTROL CHAIN.
-----------------	---

Explanation

An unexpected PTOCA control sequence was encountered in a Glyph Layout Control (GLC) chain. A GLC chain consists of a GLC control sequence followed by one or more Glyph ID Run (GIR), Glyph Advance Run (GAR), and optional Glyph Offset Run (GOR) control sequences. The GLC chain can end with an optional Unicode Complex Text (UCT) control sequence. A chain must contain these control sequences in this order (brackets surround optional controls):

```
X'2BD3' GLC GIR GAR [GOR] [GIR  
GAR [GOR]]...[GIR GAR [GOR]]  
[UCT]
```

The text-control came from a Presentation Text Data (PTX) structured field, which might be contained in a MO:DCA document, a PTOCA object, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer that you are using might try to print the page in error; however, the entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document, a PTOCA object, an overlay, or a page segment and you created the structured fields in the object that contains the error, correct the text-control sequence in the PTX structured field. See *Mixed Object Document Content Architecture Reference* and *Presentation Text Object*

Content Architecture Reference for more information about the structured field and control sequence. If the PTX has no errors, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the MO:DCA document, PTOCA object, overlay, or page segment, contact your system programmer. If you are printing a data set containing line data with embedded structured fields, correct the text-control sequence in the PTX structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you are printing a data set containing line data without embedded structured fields, the error might be a PSF or printer logic error.

APS2668I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN UNSUPPORTED UNICODE COMPLEX TEXT CONTROL SEQUENCE WAS FOUND OUTSIDE OF A GLYPH LAYOUT CONTROL CHAIN.

Explanation

A PTOCA Unicode Complex Text (UCT) control sequence was found outside of a Glyph Layout Control (GLC) chain. If the printer supports glyph layout controls, it ignores UCTs that are chained to a GLC chain and recognizes, but does not support, other UCT control sequences.

The text-control came from a Presentation Text Data (PTX) structured field, which might be contained in a MO:DCA document, a PTOCA object, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

Reporting of this exception can be controlled by the Text Fidelity triplet in the Presentation Fidelity Control (PFC) command. The PFC command is contained in a form definition.

When the Text Fidelity triplet sets the continuation rule to STOP (X'01'), PSF stops processing the data set that was being processed at the time of the error and marks the data set unprintable. PSF releases the current data set back to JES and requests that it is held by the system unless PRTEROR=QUIT is specified on the OUTPUT statement.

When the Text Fidelity triplet sets the continuation rule to DO NOT STOP (X'02'), one of these actions occurs:

- If the printer supports the PFC Text Fidelity triplet and if the REPORT field is set to REPORT (X'01'), the printer reports this exception. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports

another error that requires a more severe PSF recovery action. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

- If the printer supports the PFC Text Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer does not report this error to PSF but takes its continuation action and continues processing the page.
- If the printer does not support the PFC Text Fidelity triplet and the REPORT field is set to DO NOT REPORT (X'02'), the printer reports this exception but PSF does not issue the error message. The printer takes its continuation action for the page and PSF continues processing the data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.
- If the printer does not support the PFC Text Fidelity triplet and the REPORT field is set to REPORT (X'01'), the printer reports this exception and PSF issues the error message. PSF continues processing the current data set with the page that follows the page in error, unless the printer reports another error that requires a more severe PSF recovery action. If the page in error contains any positioning errors, then print-error markers might be included on the printed page.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see [PSF for z/OS: Diagnosis](#) for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document, a PTOCA object, an overlay, or a page segment and you created the structured fields in the object that contains the error, correct the text-control sequence in the PTX structured field. See *Mixed Object Document Content Architecture Reference* and *Presentation Text Object Content Architecture Reference* for more information about the structured field and control sequence. If the

PTX has no errors, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the MO:DCA document, PTOCA object, overlay, or page segment, contact your system programmer. If you are printing a data set containing line data with embedded structured fields, correct the text-control sequence in the PTX structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you are printing a data set containing line data without embedded structured fields, the error might be a PSF or printer logic error.

APS2669I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A GLYPH ID RUN, GLYPH ADVANCE RUN, OR GLYPH OFFSET RUN CONTROL SEQUENCE WAS FOUND OUTSIDE A GLYPH LAYOUT CONTROL CHAIN.

Explanation

A PTOCA Glyph ID Run (GIR), Glyph Advance Run (GAR), or Glyph Offset Run (GOR) control sequence was found outside a Glyph Layout Control (GLC) chain. A GLC chain consists of a GLC control sequence followed by one or more GIR, GAR, and optional GOR control sequences. The GLC chain can end with an optional Unicode Complex Text (UCT) control sequence. A chain must contain these control sequences in this order (brackets surround optional controls):

```
X'2BD3' GLC GIR GAR [GOR] [GIR  
GAR [GOR]]...[GIR GAR [GOR]]  
[UCT]
```

The text-control came from a Presentation Text Data (PTX) structured field, which might be contained in a MO:DCA document, a PTOCA object, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer that you are using might try to print the page in error; however, the entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is

defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document, a PTOCA object, an overlay, or a page segment and you created the structured fields in the object that contains the error, correct the text-control sequence in the PTX structured field. See *Mixed Object Document Content Architecture Reference* and *Presentation Text Object Content Architecture Reference* for more information about the structured field and control sequence. If the PTX has no errors, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the MO:DCA document, PTOCA object, overlay, or page segment, contact your system programmer. If you are printing a data set containing line data with embedded structured fields, correct the text-control sequence in the PTX structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you are printing a data set containing line data without embedded structured fields, the error might be a PSF or printer logic error.

APS2670I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE NUMBER OF ENTRIES IN A GLYPH ADVANCE RUN OR GLYPH OFFSET RUN CONTROL SEQUENCE DOES NOT MATCH THE NUMBER OF ENTRIES IN THE GLYPH ID RUN CONTROL SEQUENCE IN A GLYPH LAYOUT CONTROL CHAIN.

Explanation

The number of entries in a PTOCA Glyph Advance Run (GAR) or Glyph Offset Run (GOR) control sequence must match the number of entries in the preceding Glyph ID Run (GIR) control sequence in the Glyph Layout Control (GLC) chain.

The text-control came from a Presentation Text Data (PTX) structured field, which might be contained in a MO:DCA document, a PTOCA object, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer that you are using might try to print the page in error; however, the entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document, a PTOCA object, an overlay, or a page segment and you created the structured fields in the object that contains the error, correct the text-control sequence in the PTX structured field. See *Mixed Object Document Content Architecture Reference* and *Presentation Text Object Content Architecture Reference* for more information about the structured field and control sequence. If the PTX has no errors, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the MO:DCA document, PTOCA object, overlay, or page segment, contact your system programmer. If you are printing a data set containing line data with embedded structured fields, correct the text-control sequence in the PTX structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you are printing a data set containing line data without embedded structured fields, the error might be a PSF or printer logic error.

APS2671I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A TRUETYPE OR OPENTYPE FONT OBJECT ID WAS NOT PROVIDED FOR A GLYPH LAYOUT CONTROL CHAIN.

Explanation

A PTOCA Glyph Layout Control (GLC) control sequence specified a font object ID length (OIDLGTH) of zero (indicating that the previously specified font object ID (FONTOID) is still in effect), but no previously specified FONTOID was found in the text object, page, or overlay.

The text-control came from a Presentation Text Data (PTX) structured field, which might be contained in a MO:DCA document, a PTOCA object, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer that you are using might try to print the page in error; however, the entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see [PSF for z/OS: Diagnosis](#) for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document, a PTOCA object, an overlay, or a page segment and you created the structured fields in the object that contains the error, correct the text-control sequence in the PTX structured field. See *Mixed Object Document Content Architecture Reference* and *Presentation Text Object Content Architecture Reference* for more information about the structured field and control sequence. If the PTX has no errors, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the MO:DCA document, PTOCA object, overlay, or page segment, contact your system programmer. If you are printing a data set containing line data with embedded structured fields, correct the text-control sequence in the PTX structured field. If

the PTX has no errors, the error might be a PSF or printer logic error. If you are printing a data set containing line data without embedded structured fields, the error might be a PSF or printer logic error.

APS2672I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A PTOCA GLYPH LAYOUT CONTROL (GLC) CONTROL SEQUENCE CONTAINS AN INCORRECT LENGTH FIELD.

Explanation

A PTOCA Glyph Layout Control (GLC) control sequence contains an incorrect length field. When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The font object ID length (OIDLGTH) field or the full font name length (FFNLGTH) field contains a value that is not consistent with the overall control sequence length.
2. The font OIDLGTH contains a value that is not valid.
3. The FFNLGTH field contains a value that is not valid.

The text-control came from a Presentation Text Data (PTX) structured field, which might be contained in a MO:DCA document, a PTOCA object, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer that you are using might try to print the page in error; however, the entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see [PSF for z/OS:](#)

Diagnosis for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document, a PTOCA object, an overlay, or a page segment and you created the structured fields in the object that contains the error, correct the text-control sequence in the PTX structured field. See *Mixed Object Document Content Architecture Reference* and *Presentation Text Object Content Architecture Reference* for more information about the structured field and control sequence. If the PTX has no errors, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the MO:DCA document, PTOCA object, overlay, or page segment, contact your system programmer. If you are printing a data set containing line data with embedded structured fields, correct the text-control sequence in the PTX structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you are printing a data set containing line data without embedded structured fields, the error might be a PSF or printer logic error.

APS2673I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A GLYPH LAYOUT CONTROL (GLC) CONTROL SEQUENCE SPECIFIED A FULL FONT NAME, BUT NO FONT OBJECT ID.

Explanation

A PTOCA Glyph Layout Control (GLC) control sequence specified a full font name (FFONTNME) and a nonzero value in the full font name length (FFNLGTH) field, but no font object ID (FONTOID) was specified. PTOCA requires a FONTOID when a full font name is specified.

The text-control came from a Presentation Text Data (PTX) structured field, which might be contained in a MO:DCA document, a PTOCA object, an overlay, or a page segment; or it might be embedded in a data set containing line data.

System action

The printer that you are using might try to print the page in error; however, the entire page might not be printed. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the print data set or the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

If you are printing a MO:DCA document, a PTOCA object, an overlay, or a page segment and you created the structured fields in the object that contains the error, correct the text-control sequence in the PTX structured field. See *Mixed Object Document Content Architecture Reference* and *Presentation Text Object Content Architecture Reference* for more information about the structured field and control sequence. If the PTX has no errors, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the MO:DCA document, PTOCA object, overlay, or page segment, contact your system programmer. If you are printing a data set containing line data with embedded structured fields, correct the text-control sequence in the PTX structured field. If the PTX has no errors, the error might be a PSF or printer logic error. If you are printing a data set containing line data without embedded structured fields, the error might be a PSF or printer logic error.

APS2674I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A CHARACTER ENCOUNTERED WITHIN THE BAR CODE DATA IS NOT VALID FOR THE SELECTED ENCODING SCHEME.

Explanation

Within a Data Matrix bar code object, a C40, Text, X12, or EDIFACT scheme was selected and a character was encountered that is not valid for that encoding scheme. The encoding schemes do not support all 256 possible input characters.

System action

The printer that you are using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then

print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object or the page definition, correct the error and resubmit the print request. See *Bar Code Object Content Architecture Reference* for more information about bar code objects. See *Page Printer Formatting Aid: User's Guide* for more information about creating page definitions. If the structured field or page definition has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS2675I **WHILE THE PRINTER WAS PROCESSING A DATA SET, THIS CONDITION OCCURRED: FUSER OIL SUPPLY IS EMPTY.**

Explanation

The fuser oil supply for the printer is empty. This error condition caused the printer to discard its buffered pages. The printer reports an action code X'1A' to instruct PSF to redrive buffered pages. For more information about this condition, see the printer publications for the printer that reported this error.

System action

After the printer is readied, PSF resends pages to the printer, starting from the committed page counter plus 1. If repositioning is not supported in the current environment, PSF stops processing the data set.

Operator response

Resolve the error condition at the printer and press RESET or READY.

System programmer response

If the error condition persists, follow the procedures that are described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

The printed output might be acceptable.

APS2676I **WHILE THE PRINTER WAS PROCESSING A DATA SET, THIS CONDITION OCCURRED: DEVELOPER MIX NEEDS CHANGING.**

Explanation

The developer mix for the printer needs changing. This error condition caused the printer to discard its buffered pages. The printer reports an action code X'1A' to instruct PSF to redrive buffered pages. For more information about this condition, see the printer publications for the printer that reported this error.

System action

After the printer is readied, PSF resends pages to the printer, starting from the committed page counter plus 1. If repositioning is not supported in the current environment, PSF stops processing the data set.

Operator response

Resolve the error condition at the printer and press RESET or READY.

System programmer response

If the error condition persists, follow the procedures that are described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

The printed output might be acceptable.

APS2677I **WHILE THE PRINTER WAS PROCESSING A DATA SET, THIS CONDITION OCCURRED: OILER FELT NEEDS CHANGING.**

Explanation

The oiler felt for the printer needs changing. This error condition caused the printer to discard its buffered

pages. The printer reports an action code X'1A' to instruct PSF to redrive buffered pages. For more information about this condition, see the printer publications for the printer that reported this error.

System action

After the printer is readied, PSF resends pages to the printer, starting from the committed page counter plus 1. If repositioning is not supported in the current environment, PSF stops processing the data set.

Operator response

Resolve the error condition at the printer and press RESET or READY.

System programmer response

If the error condition persists, follow the procedures that are described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

The printed output might be acceptable.

APS2678I	WHILE THE PRINTER WAS PROCESSING A DATA SET, THIS CONDITION OCCURRED: TONER COLLECTOR FULL.
-----------------	--

Explanation

The toner collector for the printer is full and needs to be replaced. This error condition caused the printer to discard its buffered pages. The printer reports an action code X'1A' to instruct PSF to redrive buffered pages. For more information about this condition, see the printer publications for the printer that reported this error.

System action

After the printer is readied, PSF resends pages to the printer, starting from the committed page counter plus 1. If repositioning is not supported in the current environment, PSF stops processing the data set.

Operator response

Resolve the error condition at the printer and press RESET or READY.

System programmer response

If the error condition persists, follow the procedures that are described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

The printed output might be acceptable.

APS2679I	WHILE THE PRINTER WAS PROCESSING A DATA SET, THIS CONDITION OCCURRED: FINE FILTER NEEDS CHANGING.
-----------------	--

Explanation

The fine filter for the printer needs changing. This error condition caused the printer to discard its buffered pages. The printer reports an action code X'1A' to instruct PSF to redrive buffered pages. For more information about this condition, see the printer publications for the printer that reported this error.

System action

After the printer is readied, PSF resends pages to the printer, starting from the committed page counter plus 1. If repositioning is not supported in the current environment, PSF stops processing the data set.

Operator response

Resolve the error condition at the printer and press RESET or READY.

System programmer response

If the error condition persists, follow the procedures that are described in *PSF for z/OS: Diagnosis* before you contact the IBM Support Center.

User response

The printed output might be acceptable.

APS2681I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: TEXT DATA EXTENDS OUTSIDE THE TEXT OBJECT AREA.
-----------------	--

Explanation

A character is positioned so that a portion of the PTOCA Presentation Text (PTX) data extends beyond the intersection of the mapped presentation text space and the text object area.

The size of the presentation text space is defined in the Presentation Text Descriptor (PTD). The position of the presentation text space is specified in the Map Presentation Text (MPT) structured field or the Object Area Position (OBP) structured field. The text object area is specified in the Object Area Descriptor (OBD) structured field. The position or size of the presentation text object did not fit into the specified object area.

The PTX structured field is contained in a presentation text object. The presentation text object might be contained or referenced in a MO:DCA document, a resource, or it might be embedded in a data set containing line data. The MPT, PTD, OBD, and OBP are specified in the Object Environment Group (OEG) for the presentation text object.

System action

The printer that you are using might try to print the page in error. The entire page might not be printed. If the page in error contains any position errors, exception highlighting might be included on the printed page. PSF continues processing of the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If the structured fields are not valid and you created the structured fields for the resource or print data set, correct the error in the referenced structured field and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the resource or print data set containing the image, contact your system programmer.

Explanation

Within an Intelligent Mail Container bar code object, data is incorrect or insufficient. When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. Too many or too few characters were specified; Exactly 22 characters must be in the input data.
2. A character was encountered in the data that is not valid; specific ranges are defined for each field that is defined for this symbology.
3. Data was encountered that would cause subset A to be used; only subsets B and C are allowed for this symbology.

System action

The printer that you are using might try to print the page in error. The entire page might not be printed. If the page in error contains any positioning errors, then print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object or the page definition, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about bar code objects. See *Advanced Function Presentation: Programming Guide and Line Data Reference* for more information about creating page definitions. If the structured field or page definition has no error, the error might be a PSF or printer logic

APS2682I	DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: INCORRECT OR INSUFFICIENT DATA WAS ENCOUNTERED IN AN INTELLIGENT MAIL CONTAINER BAR CODE OBJECT.
-----------------	---

error. If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS2691I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A GOCA END CUSTOM PATTERN DRAWING ORDER WAS RECEIVED WITHOUT A BEGIN CUSTOM PATTERN DRAWING ORDER.

Explanation

An End Custom Pattern drawing order was received without a Begin Custom Pattern drawing order. The drawing orders are contained in a Graphics Data (GAD) structured field, which is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay, or it might be embedded in a data set containing line data.

System action

The printer might try to print the page with the error. However, the entire page might not print. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. See *Graphics Object Content Architecture for AFP Reference* for more information

about the drawing orders. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS2692I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A GOCA BEGIN AREA DRAWING ORDER THAT IS SPECIFIED INSIDE THE DEFINITION OF A CUSTOM PATTERN USES THE CURRENT PATTERN SYMBOL, BUT THAT PATTERN SYMBOL IS A CUSTOM PATTERN.

Explanation

A Begin Area drawing order that was found in the definition of a Custom Pattern uses the current pattern symbol that identifies a custom pattern. However, custom patterns cannot be used in another custom pattern definition. The drawing order is contained in a Graphics Data (GAD) structured field, which is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay, or it might be embedded in a data set containing line data.

System action

The printer might try to print the page with the error. However, the entire page might not print. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. See *Graphics Object Content Architecture for AFP Reference* for more information about the drawing orders. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS2693I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A GOCA BEGIN CUSTOM PATTERN DRAWING ORDER WAS RECEIVED WHILE ANOTHER BEGIN CUSTOM PATTERN DRAWING ORDER WAS ALREADY IN PROGRESS.

Explanation

A Begin Custom Pattern drawing order was found in the middle of a custom pattern definition that was already in process. Either an End Custom Pattern drawing order is missing or custom pattern definitions are nested. Custom pattern definitions cannot be nested within another custom pattern. The drawing orders are contained in a Graphics Data (GAD) structured field, which is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay, or it might be embedded in a data set containing line data.

System action

The printer might try to print the page with the error. However, the entire page might not print. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the

input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. See *Graphics Object Content Architecture for AFP Reference* for more information about the drawing orders. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS2694I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE END OF A SEGMENT IN A GOCA CUSTOM PATTERN DEFINITION WAS REACHED BEFORE AN END CUSTOM PATTERN DRAWING ORDER WAS RECEIVED.

Explanation

A Begin Custom Pattern drawing order was processed in a segment. However, an End Custom Pattern drawing order was not received before the end of the segment was reached. The drawing orders are contained in a Graphics Data (GAD) structured field, which is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay, or it might be embedded in a data set containing line data.

System action

The printer might try to print the page with the error. However, the entire page might not print. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. See *Graphics Object Content Architecture for AFP Reference* for more information about the drawing orders. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS2695I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A GOCA BEGIN CUSTOM PATTERN DRAWING ORDER SPECIFIES A PATTERN SET THAT IS NOT VALID FOR A CUSTOM PATTERN SET.

Explanation

A Begin Custom Pattern drawing order specifies a pattern set that is not valid for custom pattern sets. The drawing order is contained in a Graphics Data (GAD) structured field, which is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay, or it might be embedded in a data set containing line data.

System action

The printer might try to print the page with the error. However, the entire page might not print. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. See *Graphics Object Content Architecture for AFP Reference* for more information about the drawing orders. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS2696I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A GOCA BEGIN CUSTOM PATTERN DRAWING ORDER SPECIFIES A PATTERN SYMBOL THAT IS NOT VALID FOR A CUSTOM PATTERN SET.

Explanation

A Begin Custom Pattern drawing order specifies a pattern symbol that is not valid for custom pattern sets. The drawing order is contained in a Graphics Data (GAD) structured field, which is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay, or it might be embedded in a data set containing line data.

System action

The printer might try to print the page with the error. However, the entire page might not print. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set

in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. See *Graphics Object Content Architecture for AFP Reference* for more information about the drawing orders. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS2697I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A GOCA BEGIN CUSTOM PATTERN DRAWING ORDER SPECIFIES AN INCORRECTLY DEFINED PATTERN WINDOW.

Explanation

A Begin Custom Pattern drawing order specifies an incorrectly defined pattern window. When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these conditions that caused the exception to be reported:

1. The X position of the left side of the pattern window is equal to or greater than the X position of the right side.
2. The Y position of the bottom side of the pattern window is equal to or greater than the Y position of the top side.

The drawing order is contained in a Graphics Data (GAD) structured field, which is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay, or it might be embedded in a data set containing line data.

System action

The printer might try to print the page with the error. However, the entire page might not print. If the page in

error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. See *Graphics Object Content Architecture for AFP Reference* for more information about the drawing orders. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS2698I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A GOCA BEGIN CUSTOM PATTERN DRAWING ORDER SPECIFIES PATTERN SET AND PATTERN SYMBOL VALUES THAT ALREADY EXIST.

Explanation: A Begin Custom Pattern drawing order specifies pattern set and pattern symbol values that correspond to an existing custom pattern. The drawing order is contained in a Graphics Data (GAD) structured field, which is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay, or it might be embedded in a data set containing line data.

System action

The printer might try to print the page with the error. However, the entire page might not print. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. See *Graphics Object Content Architecture for AFP Reference* for more information about the drawing orders. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS2699I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE TEMPORARY STORAGE OVERFLOWED WHILE DEFINING A GOCA CUSTOM PATTERN.

Explanation: Custom patterns within graphics segments require temporary storage to save the pattern until it is used. The drawing orders within the custom pattern require more temporary storage than is available. The drawing orders are contained in a Graphics Data (GAD) structured field, which is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay, or it might be embedded in a data set containing line data.

System action

The printer might try to print the page with the error. However, the entire page might not print. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

To free up temporary storage, delete unneeded patterns with the Delete Pattern drawing order. If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. See *Graphics Object Content Architecture for AFP Reference* for more information about the drawing orders. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS2700I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A SUPPORTED GOCA DRAWING ORDER IS NOT VALID WITHIN A CUSTOM PATTERN DEFINITION.

Explanation

Not all GOCA drawing orders are valid in a custom pattern definition. These examples are some of the orders that are not allowed between the Begin Custom Pattern and the End Custom Pattern drawing orders:

- Begin Custom Pattern
- Delete Pattern

- Linear Gradient
- Radial Gradient

See *Graphics Object Content Architecture for AFP Reference* for a complete list of orders that are not valid in a custom pattern definition. The drawing orders are contained in a Graphics Data (GAD) structured field, which is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay, or it might be embedded in a data set containing line data.

System action

The printer might try to print the page with the error. However, the entire page might not print. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. See *Graphics Object Content Architecture for AFP Reference* for more information about the drawing orders. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS2701I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A GOCA DELETE PATTERN DRAWING

ORDER SPECIFIES A PATTERN THAT DOES NOT EXIST.

Explanation: A Delete Pattern drawing order specifies a pattern set and pattern symbol that does not exist. The drawing order is contained in a Graphics Data (GAD) structured field, which is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay, or it might be embedded in a data set containing line data.

System action

The printer might try to print the page with the error. However, the entire page might not print. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. See *Graphics Object Content Architecture for AFP Reference* for more information about the drawing orders. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS2702I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A GOCA DELETE PATTERN DRAWING ORDER SPECIFIES A PATTERN SET THAT IS NOT VALID.

Explanation: A Delete Pattern drawing order specifies a pattern set that is not valid. For example, a pattern in the default pattern set cannot be deleted. The drawing order is contained in a Graphics Data (GAD) structured field, which is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay, or it might be embedded in a data set containing line data.

System action

The printer might try to print the page with the error. However, the entire page might not print. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. See *Graphics Object Content Architecture for AFP Reference* for more information about the drawing orders. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS2703I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A GOCA DELETE PATTERN DRAWING ORDER SPECIFIES A PATTERN SYMBOL THAT IS NOT VALID.

Explanation: A Delete Pattern drawing order specifies a pattern symbol that is not valid, such as X'00'. The drawing order is contained in a Graphics Data (GAD) structured field, which is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay, or it might be embedded in a data set containing line data.

System action

The printer might try to print the page with the error. However, the entire page might not print. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. See *Graphics Object Content Architecture for AFP Reference* for more information about the drawing orders. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS2707I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A GOCA LINEAR GRADIENT DRAWING ORDER SPECIFIES A PATTERN SET THAT IS NOT VALID.

Explanation: A Linear Gradient drawing order specifies a pattern set that is not valid as a gradient

pattern set. The drawing order is contained in a Graphics Data (GAD) structured field, which is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay, or it might be embedded in a data set containing line data.

System action

The printer might try to print the page with the error. However, the entire page might not print. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. See *Graphics Object Content Architecture for AFP Reference* for more information about the drawing orders. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS2708I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A GOCA LINEAR GRADIENT DRAWING ORDER SPECIFIES A PATTERN SYMBOL THAT IS NOT VALID.

Explanation: A Linear Gradient drawing order specifies a pattern symbol that is not valid as a gradient pattern symbol. The drawing order is

contained in a Graphics Data (GAD) structured field, which is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay, or it might be embedded in a data set containing line data.

System action

The printer might try to print the page with the error. However, the entire page might not print. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. See *Graphics Object Content Architecture for AFP Reference* for more information about the drawing orders. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS2709I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A GOCA LINEAR GRADIENT DRAWING ORDER SPECIFIES PATTERN SET AND PATTERN SYMBOL VALUES THAT ALREADY EXIST.

Explanation: A Linear Gradient drawing order specifies pattern set and pattern symbol values that correspond to an existing pattern. The drawing order is

contained in a Graphics Data (GAD) structured field, which is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay, or it might be embedded in a data set containing line data.

System action

The printer might try to print the page with the error. However, the entire page might not print. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. See *Graphics Object Content Architecture for AFP Reference* for more information about the drawing orders. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS2710I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE TEMPORARY STORAGE OVERFLOWED WHILE DEFINING A GOCA LINEAR GRADIENT.**

Explanation: A linear gradient might require temporary storage for processing and storage. A Linear Gradient drawing order requires more temporary storage than is available. The drawing order is

contained in a Graphics Data (GAD) structured field, which is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay, or it might be embedded in a data set containing line data.

System action

The printer might try to print the page with the error. However, the entire page might not print. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

To free up temporary storage, delete unneeded patterns with the Delete Pattern drawing order. If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. See *Graphics Object Content Architecture for AFP Reference* for more information about the drawing orders. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS2711I **DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN OUTSIDE PARAMETER SPECIFIED IN A GOCA LINEAR GRADIENT DRAWING ORDER IS NOT VALID.**

Explanation: A value for one or both of the OUTSIDE_S or OUTSIDE_E parameters in a Linear

Gradient drawing order is not valid. The drawing order is contained in a Graphics Data (GAD) structured field, which is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay, or it might be embedded in a data set containing line data.

System action

The printer might try to print the page with the error. However, the entire page might not print. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. See *Graphics Object Content Architecture for AFP Reference* for more information about the drawing orders. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS2712I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN OFFSET VALUE FOR A COLOR STOP SPECIFIED IN A GOCA LINEAR GRADIENT DRAWING ORDER IS NOT VALID.

Explanation: An offset value for a color stop in a Linear Gradient drawing order is not valid or is less

than a previous color stop offset. The drawing order is contained in a Graphics Data (GAD) structured field, which is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay, or it might be embedded in a data set containing line data.

System action

The printer might try to print the page with the error. However, the entire page might not print. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. See *Graphics Object Content Architecture for AFP Reference* for more information about the drawing orders. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS2713I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE LENGTH FIELD IN THE COLOR SPECIFICATION OF A GOCA LINEAR GRADIENT DRAWING ORDER IS NOT VALID.

Explanation: The color specification in a Linear Gradient order contains a length field that is not valid.

The drawing order is contained in a Graphics Data (GAD) structured field, which is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay, or it might be embedded in a data set containing line data.

System action

The printer might try to print the page with the error. However, the entire page might not print. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. See *Graphics Object Content Architecture for AFP Reference* for more information about the drawing orders. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS2714I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE COLOR SPACE OR COLOR VALUES SPECIFIED IN A GOCA LINEAR GRADIENT DRAWING ORDER DO NOT FOLLOW THE RULES FOR A GRADIENT.

Explanation

The color space or color values in the Linear Gradient drawing order are valid, but do not follow the rules for colors in a gradient. When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

1. The color space that is specified is the Standard OCA color space.
2. The color space that is specified is the Highlight color space, but the color values that are specified in the order do not all resolve to Indexed CMR Color Palette tags.

The drawing order is contained in a Graphics Data (GAD) structured field, which is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay, or it might be embedded in a data set containing line data.

System action

The printer might try to print the page with the error. However, the entire page might not print. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. See *Graphics Object Content*

Architecture for AFP Reference for more information about the drawing orders. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS2715I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A GOCA RADIAL GRADIENT DRAWING ORDER SPECIFIES A PATTERN SET THAT IS NOT VALID.

Explanation: A Radial Gradient drawing order specifies a pattern set that is not valid as a gradient pattern set. The drawing order is contained in a Graphics Data (GAD) structured field, which is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay, or it might be embedded in a data set containing line data.

System action

The printer might try to print the page with the error. However, the entire page might not print. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. See *Graphics Object Content Architecture for AFP Reference* for more information

about the drawing orders. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS2716I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A GOCA RADIAL GRADIENT DRAWING ORDER SPECIFIES A PATTERN SYMBOL THAT IS NOT VALID.

Explanation: A Radial Gradient drawing order specifies a pattern symbol that is not valid as a gradient pattern symbol. The drawing order is contained in a Graphics Data (GAD) structured field, which is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay, or it might be embedded in a data set containing line data.

System action

The printer might try to print the page with the error. However, the entire page might not print. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. See *Graphics Object Content Architecture for AFP Reference* for more information about the drawing orders. If the structured field has no

error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS2717I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: A GOCA RADIAL GRADIENT DRAWING ORDER SPECIFIES PATTERN SET AND PATTERN SYMBOL VALUES THAT ALREADY EXIST.

Explanation: A Radial Gradient drawing order specifies pattern set and pattern symbol values that correspond to an existing pattern. The drawing order is contained in a Graphics Data (GAD) structured field, which is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay, or it might be embedded in a data set containing line data.

System action

The printer might try to print the page with the error. However, the entire page might not print. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. See *Graphics Object Content Architecture for AFP Reference* for more information about the drawing orders. If the structured field has no

error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS2718I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE TEMPORARY STORAGE OVERFLOWED WHILE DEFINING A GOCA RADIAL GRADIENT.

Explanation: A radial gradient might require temporary storage for processing and storage. A Radial Gradient drawing order requires more temporary storage than is available. The drawing order is contained in a Graphics Data (GAD) structured field, which is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay, or it might be embedded in a data set containing line data.

System action

The printer might try to print the page with the error. However, the entire page might not print. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

To free up temporary storage delete unneeded patterns with the Delete Pattern drawing order. If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. See *Graphics Object Content Architecture for AFP Reference*

for more information about the drawing orders. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS2719I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN OUTSIDE PARAMETER SPECIFIED IN A GOCA RADIAL GRADIENT DRAWING ORDER IS NOT VALID.

Explanation: A value for one or both of the OUTSIDE_S or OUTSIDE_E parameters in a Radial Gradient drawing order is not valid. The drawing order is contained in a Graphics Data (GAD) structured field, which is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay, or it might be embedded in a data set containing line data.

System action

The printer might try to print the page with the error. However, the entire page might not print. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. See *Graphics Object Content Architecture for AFP Reference* for more information

about the drawing orders. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS2720I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: AN OFFSET VALUE FOR A COLOR STOP SPECIFIED IN A GOCA RADIAL GRADIENT DRAWING ORDER IS NOT VALID.

Explanation: An offset value for a color stop in a Radial Gradient drawing order is not valid or is less than a previous color stop offset. The drawing order is contained in a Graphics Data (GAD) structured field, which is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay, or it might be embedded in a data set containing line data.

System action

The printer might try to print the page with the error. However, the entire page might not print. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. See *Graphics Object Content Architecture for AFP Reference* for more information

about the drawing orders. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS2721I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE LENGTH FIELD IN THE COLOR SPECIFICATION OF A GOCA RADIAL GRADIENT DRAWING ORDER IS NOT VALID.

Explanation: The color specification in a Radial Gradient order contains a length field that is not valid. The drawing order is contained in a Graphics Data (GAD) structured field, which is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay, or it might be embedded in a data set containing line data.

System action

The printer might try to print the page with the error. However, the entire page might not print. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. See *Graphics Object Content Architecture for AFP Reference* for more information about the drawing orders. If the structured field has no

error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS2722I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: THE COLOR SPACE OR COLOR VALUES SPECIFIED IN A GOCA RADIAL GRADIENT DRAWING ORDER DO NOT FOLLOW THE RULES FOR A GRADIENT.

Explanation

The color space or color values in the Radial Gradient drawing order are valid, but do not follow the rules for colors in a gradient. When the element identifier (bytes 16-17) in the formatted sense message (APS830I) is not zero, the printer might provide the number of one of these error conditions that caused the exception to be reported:

- The color space that is specified is the Standard OCA color space.
- The color space that is specified is the Highlight color space, but the color values that are specified in the order do not all resolve to the same type of color.

The drawing order is contained in a Graphics Data (GAD) structured field, which is contained in a graphics object. The graphics object might be contained in a MO:DCA document or an overlay, or it might be embedded in a data set containing line data.

System action

The printer might try to print the page with the error. However, the entire page might not print. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the graphics object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If

the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the graphics object, correct the error and resubmit the print request. See *Mixed Object Document Content Architecture Reference* for more information about the structured field. See *Graphics Object Content Architecture for AFP Reference* for more information about the drawing orders. If the structured field has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the graphics object, contact your system programmer.

APS2723I DATA IN AN INPUT RECORD OR RESOURCE IS NOT VALID: INCORRECT, INSUFFICIENT, OR TOO MUCH DATA WAS ENCOUNTERED IN A ROYAL MAIL MAILMARK BAR CODE OBJECT.

Explanation: In a Royal Mail Mailmark bar code object, incorrect, insufficient, or too much data was encountered in a Bar Code Data (BDA) structured field. The valid data for the parameters of each modifier (X'00'-X'01') is defined in the Royal Mail Mailmark Definition Document. The BDA structured field is contained in a bar code object, which might be contained in a MO:DCA document, an overlay, or might be embedded in a data set containing line data.

System action

The printer might try to print the page with the error. However, the entire page might not print. If the page in error contains any positioning errors, print-error markers might be included on the printed page. PSF continues processing the current data set with the page that follows the page in error, unless the printer reported another error that required a more severe PSF recovery action.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page or the message data set in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the bar code object with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for

assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the bar code object or the page definition, correct the error and resubmit the print request. See *Bar Code Object Content Architecture Reference* for more information about bar code objects. See *Page Printer Formatting Aid: User's Guide* for more information about creating page definitions. If the structured field or page definition has no error, the error might be a PSF or printer logic error. If you used a program to create the structured fields for the bar code object, contact your system programmer.

APS3000I THE RDJFCB TYPE X'13' SYSTEM FUNCTION IS NOT SUPPORTED BY THIS SYSTEM AND PSF REQUIRES THIS SUPPORT. PLEASE NOTIFY YOUR SYSTEM PROGRAMMER.

Explanation

The RDJFCB type X'13' system function is not supported by this system. You are running with an earlier DFP or operating system or both. The minimum operating system level is MVS/XA 2.2.0, and the minimum MVS/DFP level is 2.3.0 for this RDJFCB support.

System action

The PSF initialization is stopped.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Ensure that PSF is installed on a system that supports the RDJFCB type X'13' system function with the appropriate level of DFP. See Explanation for minimum levels.

If you are on a system at the appropriate level, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

No response is necessary.

APS3001I THE RDJFCB TYPE X'13' SYSTEM FUNCTION WAS UNSUCCESSFUL

– RETURN CODE *return code*.
PLEASE NOTIFY YOUR SYSTEM PROGRAMMER.

Explanation

The RDJFCB type X'13' system function was unsuccessful. An RDJFCB macro request was issued to obtain the data set names of a library, and a nonzero code was returned.

System action

The PSF initialization is stopped.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Correct the problem in response to the system return code identified in this message. See *z/OS DFSMSdfp Advanced Services* for information on the hexadecimal return code. See information on the ARLRCODE field.

User response

No response is necessary.

APS3002I THE OBTAIN SYSTEM FUNCTION WAS UNSUCCESSFUL FOR DATA SET NAME *data set name* – RETURN CODE *return code*. PLEASE NOTIFY YOUR SYSTEM PROGRAMMER.

Explanation

The system OBTAIN(reading by Data Set Name) function was unsuccessful and the return code indicates the cause.

System action

PSF is ended.

Operator response

Notify your system programmer.

System programmer response

Correct the problem in response to the system return code identified in the message. See *z/OS DFSMSdfp Advanced Services* for the meaning of the OBTAIN hexadecimal return code.

User response

No response is necessary.

APS3003I SAVING THE AUXILIARY FILE WAS UNSUCCESSFUL: THERE IS A PROBLEM WITH OUTPUT FILE (*filename*). RETURN CODE (*return code*). REASON CODE (*reason code*).

Explanation

You specified the parameter for saving auxiliary files in the AFPPARMS control statement or the Printer Inventory; however, AFP Download Plus was unable to save the auxiliary file because it received an error from UNIX System Services when it tried to copy the resource group file and MO:DCA file to the output auxiliary file.

System action

The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 0D1A.

Operator response

Contact your system programmer.

System programmer response

Use the return code and reason code to determine the problem. See *z/OS UNIX System Services Programming: Assembler Callable Services Reference*.

User response

No response necessary.

APS3004I SAVING THE AUXILIARY FILE WAS UNSUCCESSFUL: THERE IS A PROBLEM WITH INPUT FILE (*filename*). RETURN CODE (*return code*). REASON CODE (*reason code*).

Explanation

You specified the parameter for saving auxiliary files in the AFPPARMS control statement or the Printer Inventory; however, AFP Download Plus was unable to save the auxiliary file because it received an error from UNIX System Services when it tried to copy the resource group input file or the MO:DCA input file to the output auxiliary file.

System action

The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 0D1A.

Operator response

Contact your system programmer.

System programmer response

Use the return code and reason code to determine the problem. See *z/OS UNIX System Services Programming: Assembler Callable Services Reference*.

User response

No response necessary.

APS3005I PSF CANNOT PROCESS THE (resource) LIBRARY FOR DD STATEMENT (ddname) BECAUSE PSF IS NOT UNICODE ENABLED. PROCESSING CONTINUES.

Explanation

The library that is specified in the PSF startup procedure cannot be processed because PSF is not Unicode-enabled. By default, PSF is enabled for Unicode processing; however, because of a UNIX System Services error, PSF cannot use conversion services to process this resource library request.

System action

PSF continues processing the data set.

Operator response

Inform your system programmer that this error occurred.

System programmer response

A UNIX System Services error occurred that prevented PSF from processing this resource request. See message APS7001I, which was issued with this message, for help correcting the UNIX System Services error.

User response

Inform your system programmer that this error occurred.

APS3006I PSF CANNOT PROCESS THE USERPATH PARAMETER FOR OUTPUT STATEMENT (outputname) BECAUSE PSF IS NOT UNICODE ENABLED. PROCESSING CONTINUES.

Explanation

The USERPATH parameter that is specified in the OUTPUT JCL statement cannot be processed because PSF is not Unicode-enabled. By default, PSF is enabled for Unicode processing; however, because of a UNIX System Services error, PSF cannot use conversion services to process this request.

System action

PSF continues processing the data set.

Operator response

None.

System programmer response

A UNIX System Services error occurred that prevented PSF from processing this resource request. See message APS7001I, which was issued with this message, for help correcting the UNIX System Services error.

User response

Inform your system programmer that this error occurred.

APS3500I THE FONT MENTIONED IN THE MESSAGE ABOVE HAS A GLOBAL RESOURCE IDENTIFIER (GRID) OF 'grid'. THE COMPONENTS OF THE GRID (SPECIFIED AS DECIMAL VALUES) ARE: GCSGID= gscgid, CPGID= cpgid, FGID= fgid, AND FONT WIDTH= font width.

Explanation

This message is issued in addition to the message that describes the error. It is intended as more diagnostic information. The font that is processed at the time of the error is listed in this message by its GRID and GRID components (GCSGID, CPGID, FGID, and font width). The GRID is presented as a hexadecimal value and the GRID components are specified as decimal values.

System action

The printing disposition depends on the error that is described in the accompanying messages.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is specified, in this case, for use with a separator page or

message data set in the PSF startup procedure. Inform your system programmer that this error occurred.

System programmer response

To determine an appropriate response, see the specific error conditions that are described in the accompanying messages.

User response

To determine an appropriate response, see the specific error conditions that are described in the accompanying messages.

APS3501I DATA OBJECT RESOURCE TYPE (type string), NAME (member) OR OBJECT ID (object oid), HAS AN UNSUPPORTED REGISTRATION ID (object-type oid).

Explanation

The registration ID (*object-type oid*) for the specified data object resource is not supported by either the printer or PSF. The registration ID is specified in the object classification triplet on one of these structured fields:

- Include Object (IOB)
- Begin Object Container (BOC)
- Begin Resource (BRS, also called BR)
- Map Data Resource (MDR)

Any message inserts (enclosed in parentheses) in this message that are not available or that do not apply to this instance of this message are specified as '(***>'. If the data object resource type in this message is '(***', PSF or the printer does not support the resource type. For more information about registration IDs and object types, see *Mixed Object Document Content Architecture Reference*.

System action

If this error was encountered when PSF is processing a Resource Environment Group (REG), PSF skips over this particular data object resource and tries to process any other resources that are specified in the REG. If this error was encountered while PSF is processing a page or overlay object, PSF stops processing the page or overlay object. PSF tries to locate the end of the current page and resume processing on the next page. If the end of the current page cannot be located, PSF stops printing the data set. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields for the resource with the error, verify that the input to that program was valid. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the data object resource, ensure that the registration ID is correct. If the registration ID is correct, submit the print job to a printer that supports this object type. For more information about what object types are supported by your printer, see your printer documentation.

APS3502I DATA OBJECT RESOURCE TYPE (type string), NAME (member) OR OBJECT ID (object oid), COULD NOT BE PROCESSED. THIS OBJECT IS NOT REQUIRED FOR THIS PRINTER AND IS SKIPPED.

Explanation

The registration ID (*object-type OID*) for the specified data object resource is not supported by the printer. The registration ID is specified in the object classification triplet on one of these structured fields:

- Include Object (IOB)
- Begin Object Container (BOC)
- Begin Resource (BRS, also called BR)
- Map Data Resource (MDR)

The printer does not support the registration ID; however, this object is not required for printing this document. It is likely that the print file was formatted for a color printer that supports color profiles but is being printed on a printer that does not support these color profile objects. Any message inserts (enclosed in parentheses) in this message that are not available or that do not apply to this instance of this message are specified as '(***'.

System action

PSF records this condition and then continues processing.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

Verify that the formatting options at the time the print file was produced are compatible with the printer on which this print file is printing. Correct any mismatches.

User response

If the printed output is not acceptable, choose a printer that supports the color profiles that are specified in this print file, or reformat this print file for the printer on which this print file is being printed.

APS3503I	DATA OBJECT RESOURCE TYPE (type string), NAME (member) OR OBJECT ID (object oid), WAS REPLACED BY DATA OBJECT RESOURCE NAME (member) OR OBJECT ID (object oid), (optional user text).
-----------------	--

Explanation

The resource exit requested substitution of this data object resource. The specific type of data object resource is identified in this message. This message also contains the original data object resource name or object ID and the new data object. Any message inserts (enclosed in parentheses) in this message that are not available or that do not apply to this instance of this message are specified as '(***)'.

System action

PSF replaces the original data object resource references (*name* or *object ID*) with the new data object resource references (*name* or *object ID*) specified by the resource exit. PSF then generates this informational message unless directed otherwise by the resource exit.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is

defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

You can use the optional user text field of this message to provide further information to the user about why this data object resource was replaced. For more information about providing optional user text in this message, see [PSF for z/OS: Customization](#).

User response

If the printed output is not acceptable, contact your system programmer.

APS3504I	THIS RESOURCE SUBSTITUTION REQUEST IS NOT ALLOWED. NAME (member) OR OBJECT ID (object OID) WAS NOT REPLACED BY NAME (member) OR OBJECT ID (object OID).
-----------------	--

Explanation

The resource exit requested substitution of this data object resource. This substitution was denied because the identification of the new data object resource (*name* or *object ID*) was not of the same identification type (*name* or *object ID*) as the original data object resource. The specific type of data object resource is identified in this message. This message also contains the original data object resource name or object ID and the new data object resource name or object ID. Any message inserts (enclosed in parentheses) in this message that are not available or that do not apply to this instance of this message are specified as '(***)'.

System action

PSF ignores the new data object resource name or object ID and uses the original data object resource name or object ID. PSF then generates this warning message and continues processing.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

To specify a new data object resource as a substitute for the original data object resource, the resource identification type must be identical. For example, if the original data object resource was identified with a name, the new data object resource must also be identified with a name and the object ID specifications must remain unchanged. For more information about resource substitution, see *PSF for z/OS: Customization*.

User response

If the printed output is not acceptable, contact your system programmer.

APS3506I DATA OBJECT RESOURCE TYPE (type string), OBJECT ID (object oid), COULD NOT BE ACTIVATED IN THE PRINTER.

Explanation

The printer cannot activate the data object resource with object ID *object oid*. If the data object resource type string (*type string*) in this message is '(***)' PSF does not support the object type. Any message inserts (enclosed in parentheses) in this message that are not available or that do not apply to this instance of this message are specified as '(***)'.

System action

PSF stops printing the current data set and issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

Verify that the formatting options when the print file is produced are compatible with the printer that is being used. Correct any mismatches.

User response

Choose a printer that can activate the data object resource with the object ID that is specified in the print file, correct the object ID, or reformat this print file for the printer on which it is being printed.

APS3507I DATA OBJECT RESOURCE TYPE (type string), OBJECT ID (object oid), COULD NOT BE ACTIVATED IN THE PRINTER. THIS OBJECT IS NOT REQUIRED FOR PRINTING AND IS SKIPPED.

Explanation

The data object resource with object ID (*object oid*) cannot be activated by the printer. The printer does not know of this data object resource; however, this object is not required for printing this document. PSF records this condition and continues. It is likely that the print file was formatted for a color printer that supports color profiles but is being printed on a printer that does not support these color profile objects. It is also possible that the object ID (*object oid*) was specified incorrectly. Any message inserts (enclosed in parentheses) in this message that are not available or that do not apply to this instance of this message are specified as '(***)'.

System action

PSF records this condition and then continues processing.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

Verify that the formatting options at the time the print file is produced are compatible with the printer on which this print file is printing. Correct any mismatches.

User response

If the printed output is not acceptable, choose a printer that knows the object IDs that are specified in the print file, correct the object ID, or reformat this print file for the printer on which it is being printed.

APS3508I RESOURCE TYPE (type string), NAME (member) OR OBJECT ID (object oid), SHOULD NOT BE SPECIFIED AS AN OBJECT CONTAINER RESOURCE.

Explanation

PSF encountered an object in an object container construct that must not be an object container. One example is an IOCA object that is placed in object container structured fields. The object in error was identified by name (*member*) or object ID (*object oid*). Any message inserts (enclosed in parentheses) in this message that are not available or that do not apply to this instance of this message are specified as '(***)'.

System action

If this error was encountered when PSF is processing a Resource Environment Group (REG), PSF skips over this particular data object resource and tries to process any other resources that are specified in the REG. If this error was encountered while PSF is processing a page or overlay object, PSF stops processing the page or overlay object. PSF tries to locate the end of the current page and resume processing on the next page. If the end of the current page cannot be located, PSF stops printing the data set. PSF issues more messages that identify the processing environment when the error was found.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

If an IBM licensed program was used to create the structured fields, verify that the input to that program was valid and the correct printer is being used. If the input was valid, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem. If the error involves separator pages or the message data set, use the information that is provided in the User Response section to correct the error.

User response

If you created the structured fields for the data object resource, ensure that the object type is appropriate for use as an object container or use this object type as intended. For more information about the proper usage of this object type, see *Mixed Object Document Content Architecture Reference*.

APS3509I THE ABOVE CONDITION WAS ENCOUNTERED WHILE PROCESSING OBJECTS SPECIFIED IN RESOURCE

ENVIRONMENT GROUP (*token name*). PROCESSING OF THE RESOURCE ENVIRONMENT GROUP CONTINUES.

Explanation

The previous condition or error was found while PSF was processing a Resource Environment Group (REG) for this document. Errors or conditions that are identified during REG processing are recorded and processing continues. This message is produced to help find the noted condition. The message insert (*token name*) identifies the REG being processed when the condition was encountered. If the REG does not have a token name, the message insert appears as '(***)'.

System action

PSF records the environment at the time the primary condition was encountered and continues processing.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

See the System Programmer Response for the primary message in this message set.

User response

See the User Response for the primary message in this message set.

APS3510I THE ABOVE CONDITION OCCURRED IN THE RESOURCE ENVIRONMENT GROUP JUST PRIOR TO PAGE (*page number*) OF TRANSMISSION (*transmission number*).

Explanation

The previous condition or error was found while PSF was processing a Resource Environment Group (REG) for this document. Errors or conditions that are identified during REG processing are recorded and processing continues. This message is produced to help find the noted condition. The condition occurred before PSF processed the page and transmission that is identified in this message.

System action

PSF records the environment at the time the primary condition was encountered and continues processing.

Operator response

If this message displays on the operator's console, it indicates that the resource that contains the error is defined for a separator page, for the message data set, or as the default resource for user print data sets in the PSF startup procedure. Inform your system programmer.

System programmer response

See the System Programmer Response for the primary message in this message set.

User response

See the User Response for the primary message in this message set.

APS3513I AN ATTEMPT WAS MADE TO ACTIVATE A PRINTER-RESIDENT CODE PAGE USING CPGID *cpgid* AND GCSGID *gcsgid*. THE ATTEMPT WAS NOT SUCCESSFUL.

Explanation

PSF received a request for a TrueType or OpenType font that asked that a code page is used to transform the print data. The code page was identified by a CPGID of *cpgid* and a GCSGID of *gcsgid*. However, the code page is not printer resident so PSF cannot complete the activation.

A TrueType or OpenType font is introduced in the print data set by using an MDR structured field. The MDR was generated by the print application, PPFA, or some data stream formatter. The MDR for this TrueType or OpenType font specified a code page (by CPGID and GCSGID) to be used by the printer to transform the data encoding to Unicode. The CPGID and GCSGID are identifiers that are used by PSF and the printer to communicate about a specific code page. In this case, the printer did not know the identified code page.

The CPGID or GCSGID might be incorrect. Since PSF was given only the CPGID and GCSGID for the code page, PSF can attempt to activate only the code page. When the code page activation fails for a code page that is identified by CPGID and GCSGID, PSF must return this error.

System action

PSF was unable to process the necessary resources to print the page. PSF prints this error message and associated environment messages.

The action that is taken by PSF depends on where in the data stream the font was specified. In the associated environment message that is produced for this error, PSF identifies the location of the error within the data stream and the disposition of the error.

Operator response

If this message displays on the operator's console, it indicates an error in the specification of a code page to be used with a TrueType or OpenType font for printing the separator pages, message pages, or a default resource specified with the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or message pages, use the information that is provided in the User Response section to correct the error. If an IBM licensed program was used to create the structured fields for the print data set with the error, verify that the input to that program was correct. If the input was correct, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

Do one of these actions to solve this problem:

- Verify that the CPGID and GCSGID used to identify this code page are correct.
- Specify the code page by name instead of by CPGID and GCSGID, which gives PSF a way to download the code page to the printer.

APS3514I PSF CANNOT PROCESS THE TRUETYPE FONT, OPENTYPE FONT, OR COLOR MANAGEMENT RESOURCE (*resource name*). PSF MUST BE UNICODE-ENABLED TO SUPPORT THIS RESOURCE.

Explanation

A TrueType or OpenType font or a color management resource was specified in the data stream with a name of *resource name*. By default, PSF is enabled for Unicode processing; however, because of a UNIX System Services error, PSF cannot use conversion services to process this resource request.

System action

PSF was unable to process the necessary resources to print the page. PSF prints this error message and associated environment messages.

The action that is taken by PSF depends on where in the data stream the resource was specified. In the associated environment message that is produced for this error, PSF identifies the location of the error within the data stream and the disposition of the error.

Operator response

Inform your system programmer that this error occurred.

System programmer response

A UNIX System Services error occurred that prevented PSF from processing this resource request. See message APS7001I, which was issued with this message, for help correcting the UNIX System Services error.

User response

Contact your system programmer.

APS3515I	THE (<i>structured field name</i>) STRUCTURED FIELD CONTAINS A DATA OBJECT OR OCA OBJECT RESOURCE (<i>resource name</i>) WITH A NAME LONGER THAN 8 CHARACTERS, BUT PSF IS NOT UNICODE-ENABLED. PSF WILL TRUNCATE THE NAME TO 8 CHARACTERS AND ATTEMPT TO PROCESS THIS RESOURCE.
-----------------	--

Explanation

A data object or OCA object resource was specified in the data stream with a *resource name* that is longer than 8 characters. By default, PSF is enabled for Unicode processing; however, because of a UNIX System Services error, PSF cannot use conversion services to process resource names longer than 8 characters.

System action

PSF truncates the resource name to 8 characters and tries to continue processing the resource.

Operator response

If this print data set was not successfully processed by PSF, inform your system programmer.

System programmer response

If this print data set was not successfully processed by PSF, see message APS7001I, which was issued with this message, for help correcting the UNIX System Services error.

User response

If this print data set was not successfully processed by PSF, contact your system programmer.

APS3516I	THE (<i>structured field name</i>) STRUCTURED FIELD CONTAINS A DATA OBJECT OR OCA OBJECT RESOURCE (<i>resource name</i>), GCSGID (<i>gcsgid</i>), CPGID (<i>cpgid</i>). PSF MUST BE UNICODE-ENABLED TO SUPPORT THIS RESOURCE.
-----------------	--

Explanation

A data object or OCA object resource with a hexadecimal *resource name* was specified in the data stream with a name encoding of *gcsgid* and *cpgid*. By default, PSF is enabled for Unicode processing; however, because of a UNIX System Services error, PSF cannot use conversion services to process this resource request.

System action

PSF was unable to process the necessary resources to print the page. PSF prints this error message and associated environment messages.

The action that is taken by PSF depends on where in the data stream the resource was specified. In the associated environment messages that are produced for this error, PSF identifies the location of the error within the data stream and the disposition of the error.

Operator response

Inform your system programmer that this error occurred.

System programmer response

A UNIX System Services error occurred that prevented PSF from processing this resource request. See message APS7001I, which was issued with this message, for help correcting the UNIX System Services error.

User response

Contact your system programmer.

APS3517I	PSF CANNOT PROCESS THE TRUETYPE FONT, OPENTYPE
-----------------	---

FONT, OR COLOR MANAGEMENT RESOURCE (*resource name*), GCSGID (*gcsgid*), CPGID (*cpgid*). PSF MUST BE UNICODE-ENABLED TO SUPPORT THIS RESOURCE.

Explanation

A TrueType or OpenType font or a color management resource with a hexadecimal *resource name* was specified in the data stream with a name encoding of *gcsgid* and *cpgid*. By default, PSF is enabled for Unicode processing; however, because of a UNIX System Services error, PSF cannot use conversion services to process this resource request.

System action

PSF was unable to process the necessary resources to print the page. PSF prints this error message and associated environment messages.

The action that is taken by PSF depends on where in the data stream the resource was specified. In the associated environment messages that are produced for this error, PSF identifies the location of the error within the data stream and the disposition of the error.

Operator response

Inform your system programmer that this error occurred.

System programmer response

A UNIX System Services error occurred that prevented PSF from processing this resource request. See message APS7001I, which was issued with this message, for help correcting the UNIX System Services error.

User response

Contact your system programmer.

APS3518I	PSF CANNOT PROCESS THE TRUETYPE FONT, OPENTYPE FONT, OR COLOR MANAGEMENT RESOURCE (<i>resource name</i>), CCSID (<i>ccsid</i>). PSF MUST BE UNICODE-ENABLED TO SUPPORT THIS RESOURCE.
-----------------	--

Explanation

A TrueType or OpenType font or a color management resource with a hexadecimal *resource name* was specified in the data stream with a name encoding of *ccsid*. By default, PSF is enabled for Unicode processing; however, because of a UNIX System

Services error, PSF cannot use conversion services to process this resource request.

System action

PSF was unable to process the necessary resources to print the page. PSF prints this error message and associated environment messages.

The action that is taken by PSF depends on where in the data stream the resource was specified. In the associated environment messages that are produced for this error, PSF identifies the location of the error within the data stream and the disposition of the error.

Operator response

Inform your system programmer that this error occurred.

System programmer response

A UNIX System Services error occurred that prevented PSF from processing this resource request. See message APS7001I, which was issued with this message, for help correcting the UNIX System Services error.

User response

Contact your system programmer.

APS3519I	THE (<i>structured field name</i>) STRUCTURED FIELD CONTAINS A DATA OBJECT OR OCA OBJECT RESOURCE (<i>resource name</i>), CCSID (<i>ccsid</i>). PSF MUST BE UNICODE-ENABLED TO SUPPORT THIS RESOURCE.
-----------------	--

Explanation

A data object or OCA object resource with a hexadecimal *resource name* was specified in the data stream with a name encoding of *ccsid*. By default, PSF is enabled for Unicode processing; however, because of a UNIX System Services error, PSF cannot use conversion services to process this resource request.

System action

PSF was unable to process the necessary resources to print the page. PSF prints this error message and associated environment messages.

The action that is taken by PSF depends on where in the data stream the resource was specified. In the associated environment messages that are produced for this error, PSF identifies the location of the error within the data stream and the disposition of the error.

Operator response

Inform your system programmer that this error occurred.

System programmer response

A UNIX System Services error occurred that prevented PSF from processing this resource request. See message APS7001I, which was issued with this message, for help correcting the UNIX System Services error.

User response

Contact your system programmer.

APS3520I **A RESOURCE HAS BEEN FOUND THAT CANNOT BE PLACED INLINE IN THE RESOURCE GROUP: PATH (*path*), FILENAME (*filename*).**

Explanation

AFP Download Plus received a request to process a resource that cannot be placed inline. Some resources, for example, TrueType and OpenType Fonts, have a setting that indicates whether embedding is allowed. If this setting forbids embedding, AFP Download Plus cannot place the resource inline.

System action

AFP Download Plus cannot process the necessary resources to print the page. AFP Download Plus issues this error message and associated environment messages. The action that is taken depends on where in the data stream the data object resource was specified. The associated environment messages for this error identify the location of the error within the data stream and the disposition of the error.

Operator response

If this message displays on the operator's console, it indicates that AFP Download Plus is processing a resource request for separator pages, message pages, or a default resource specified in the AFP Download Plus startup procedure. Inform your system programmer.

System programmer response

Use only resources that can be embedded in separator pages and message pages and as default resources specified in the AFP Download Plus startup procedure.

User response

Use only resources that can be embedded.

APS3521I **THE (*structured field name*) STRUCTURED FIELD CONTAINS A PAGE SEGMENT, BCOCA, OR GOCA RESOURCE (*resource name*) WITH A NAME LONGER THAN 8 CHARACTERS, PSF WILL TRUNCATE THE NAME TO 8 CHARACTERS AND ATTEMPT TO PROCESS THIS RESOURCE.**

Explanation

A page segment, BCOCA, or GOCA resource was specified in the data stream with a *resource name* longer than 8 characters. PSF supports only these resources with names of 8 characters or less.

System action

PSF truncates the resource name to 8 characters and tries to continue processing the resource.

Operator response

No response is necessary.

System programmer response

If this print data set was not successfully processed by PSF, ensure that the appropriate resource name is 8 characters or less in length.

User response

If PSF successfully printed your print data set, no response is necessary. If this print data set was not successfully processed by PSF, ensure that all references in the data stream to this resource are 8 characters or less in length.

APS3522I **THE (*structured field*) STRUCTURED FIELD CONTAINS A PAGE SEGMENT, BCOCA, OR GOCA RESOURCE (*resource name*), GCSGID (*gcsgid*), CPGID (*cpgid*). PSF ONLY SUPPORTS THIS RESOURCE WITH DEFAULT NAME ENCODING (CCSID=500).**

Explanation

A page segment, BCOCA, or GOCA resource with a hexadecimal resource name was specified in the data stream with a name encoding of *gcsgid* and *cpgid*. However, PSF supports only a name encoding of CCSID=500 for page segment, BCOCA, or GOCA resources.

System action

PSF cannot process the necessary resources to print the page. PSF prints this error message and its associated environment messages, which identify the location of the error within the data stream and the disposition of the page.

Operator response

If this message displays on the operator's console, it indicates that PSF is processing a resource request for separator pages, message pages, or a default resource specified in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or message pages, do the action in the User Response section to correct the error. If an IBM licensed program was used to create the structured fields for the print data set with the error, verify that the input to that program was correct. If the input was correct, see the *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

Change the name encoding of the resource to CCSID=500.

APS3523I	THE (structured field) STRUCTURED FIELD CONTAINS A PAGE SEGMENT, BCOCA, OR GOCA RESOURCE (resource name), CCSID (ccsid). PSF ONLY SUPPORTS THIS RESOURCE WITH DEFAULT NAME ENCODING (CCSID=500).
-----------------	---

Explanation

A page segment, BCOCA, or GOCA resource was specified in the data stream with a name encoding of *ccsid*. However, PSF supports only a name encoding of CCSID=500 for page segment, BCOCA, or GOCA resources.

System action

PSF cannot process the necessary resources to print the page. PSF prints this error message and its associated environment messages, which identify the location of the error within the data stream and the disposition of the page.

Operator response

If this message displays on the operator's console, it indicates that PSF is processing a resource request for separator pages, message pages, or a default resource specified in the PSF startup procedure. Inform your system programmer.

System programmer response

If the error involves separator pages or message pages, do the action in the User Response section to correct the error. If an IBM licensed program was used to create the structured fields for the print data set with the error, verify that the input to that program was correct. If the input was correct, see the *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

Change the name encoding of the resource to CCSID=500.

APS3524I	THE FONT USED IN AN AUXILIARY DATA SET IS NOT IS/3 COMPLIANT. ONLY TRUETYPE AND OPENTYPE FONTS CAN BE USED.
-----------------	--

Explanation

When the Printer Inventory or the AFPPARMS control statement parameter that specifies the MO:DCA level for auxiliary files is set to IS3, auxiliary pages in an output data stream must be MO:DCA IS/3 compliant. To be IS/3 compliant, auxiliary pages, such as separator pages and message files, must use only TrueType and OpenType fonts. An error occurred because the font that is used for the auxiliary pages is a FOCA font, not a TrueType and OpenType font.

System action

AFP Download Plus processing ends abnormally with a system completion code 024 and abend reason code 0E60. PSF stops processing the auxiliary data set that caused the error.

Operator response

If this message displays on the operator's console, it indicates that an auxiliary page was specified as IS/3, but the auxiliary file did not use only TrueType and OpenType fonts. Inform your system programmer.

System programmer response

Do one of these actions:

- To indicate that the auxiliary files are not IS/3 compliant, specify NONE for the Printer Inventory or the AFPPARMS control statement parameter that specifies the MO:DCA level for auxiliary files.
- Update the PRINTDEV statement in the startup procedure to specify separator page and message OUTPUT statements with page definitions that use only TrueType and OpenType fonts, not FOCA fonts.
- If you are using AFP separator pages instead of line data, update the AFP separator page files to specify only TrueType and OpenType fonts.

User response

Contact your system programmer.

APS4000I THE AFP STATISTICS REPORT FACILITY IN PSF HAS ENCOUNTERED A MEMORY SHORTAGE AND HAS SHUT DOWN. MEMORY WAS NOT AVAILABLE FOR (memory item). ALL OTHER PSF PROCESSING CONTINUES.

Explanation

While PSF was processing an AFP Statistics (AFPSTATS) report for this print data set, a shortage of virtual memory occurred that caused the AFPSTATS processing to end. The specific error is described by *memory item* in the message.

memory item can be any of these values:

- PRINT FILE INFORMATION SECTION, TITLE RECORD
- PRINT FILE INFORMATION SECTION, PAGEFOOTER RECORD
- PRINT FILE INFORMATION SECTION, HEADING RECORD
- PRINT FILE INFORMATION SECTION, PRINTFILE RECORD
- PRINT FILE INFORMATION SECTION, COMMENT RECORD
- PRINT FILE EXTENSION SECTION, TITLE RECORD
- PRINT FILE EXTENSION SECTION, PAGEFOOTER RECORD
- PRINT FILE EXTENSION SECTION, HEADING RECORD
- PRINT FILE EXTENSION SECTION, PRINTFILE RECORD
- PRINT FILE EXTENSION SECTION, COMMENT RECORD
- PROCESSING DETAIL SECTION, TITLE RECORD

- PROCESSING DETAIL SECTION, PAGEFOOTER RECORD
- PROCESSING DETAIL SECTION, HEADING RECORD
- PROCESSING DETAIL SECTION, RESOURCE RECORD
- PROCESSING DETAIL SECTION, EVENT RECORD
- PROCESSING DETAIL SECTION, NOTE RECORD
- PROCESSING DETAIL SECTION, COMMENT RECORD
- RESOURCE SUMMARY BY NAME SECTION, TITLE RECORD
- RESOURCE SUMMARY BY NAME SECTION, PAGEFOOTER RECORD
- RESOURCE SUMMARY BY NAME SECTION, HEADING RECORD
- RESOURCE SUMMARY BY NAME SECTION, SUMM-NAME RECORD
- RESOURCE SUMMARY BY NAME SECTION, COMMENT RECORD
- RESOURCE SUMMARY BY NAME SECTION, NOTE RECORD
- RESOURCE SUMMARY BY DATA SET SECTION, TITLE RECORD
- RESOURCE SUMMARY BY DATA SET SECTION, PAGEFOOTER RECORD
- RESOURCE SUMMARY BY DATA SET SECTION, SECTION RECORD
- RESOURCE SUMMARY BY DATA SET SECTION, SUMM-DSN RECORD
- RESOURCE SUMMARY BY DATA SET SECTION, SUMM-DSN-R RECORD
- RESOURCE SUMMARY BY DATA SET SECTION, COMMENT RECORD
- RESOURCE SUMMARY BY DATA SET SECTION, NOTE RECORD
- RESOURCE SUMMARY BY RESOURCE TYPE SECTION, TITLE RECORD
- RESOURCE SUMMARY BY RESOURCE TYPE SECTION, PAGEFOOTER RECORD
- RESOURCE SUMMARY BY RESOURCE TYPE SECTION, SECTION RECORD
- RESOURCE SUMMARY BY RESOURCE TYPE SECTION, HEADING RECORD
- RESOURCE SUMMARY BY RESOURCE TYPE SECTION, SUMM-REF RECORD
- RESOURCE SUMMARY BY RESOURCE TYPE SECTION, SUMM-LOC RECORD
- RESOURCE SUMMARY BY RESOURCE TYPE SECTION, SUMM-DISP RECORD
- RESOURCE SUMMARY BY RESOURCE TYPE SECTION, COMMENT RECORD

- RESOURCE SUMMARY BY RESOURCE TYPE SECTION, NOTE RECORD
- PROCESSING SUMMARY SECTION, TITLE RECORD
- PROCESSING SUMMARY SECTION, PAGEFOOTER RECORD
- PROCESSING SUMMARY SECTION, SECTION RECORD
- PROCESSING SUMMARY SECTION, HEADING RECORD
- PROCESSING SUMMARY SECTION, SUMM-PAGE RECORD
- PROCESSING SUMMARY SECTION, SUMM-EVENT RECORD
- PROCESSING SUMMARY SECTION, EVENT-LIST RECORD
- PROCESSING SUMMARY SECTION, COMMENT RECORD
- PROCESSING SUMMARY SECTION, NOTE RECORD
- PROCESSING SUMMARY SECTION, META-LIST RECORD
- INTERNAL CONTROL STRUCTURE, DATA SET LIST ITEM
- INTERNAL CONTROL STRUCTURE, RESOURCE LIST ITEM
- INTERNAL CONTROL STRUCTURE, EVENT LIST ITEM
- INTERNAL CONTROL STRUCTURE, RESOURCE NAME LIST ITEM
- INTERNAL CONTROL STRUCTURE, PROCESSING SUMMARY ANCHOR
- INTERNAL CONTROL STRUCTURE, DATA SET NAME ANCHOR
- INTERNAL CONTROL STRUCTURE, RESOURCE TYPE ANCHOR
- INTERNAL CONTROL STRUCTURE, RESOURCE NAME ANCHOR
- INTERNAL CONTROL STRUCTURE, META LIST ITEM

System action

The processing for the AFP Statistics facility is ended and PSF continues processing the print file.

Operator response

If this message displays on the operator's console, inform your system programmer. AFP Statistics are not gathered while separator pages or the PSF message data set are processed.

System programmer response

Not enough virtual memory exists for PSF to process the print file and produce an AFP Statistics report at the same time. Increase the amount of virtual memory that is specified on the REGION parameter of the PSF startup procedure.

User response

Inform your system programmer that this error occurred.

APS4001I THE AFP STATISTICS REPORT FOR THIS PRINT FILE WAS WRITTEN TO – *data set name(member name)*.

Explanation

When an AFP Statistics (AFPSTATS) report is requested, this informational message is produced to tell the requester where the report was placed. PSF gives the report a member name and writes it to the PDSE specified in the PSF startup procedure.

data set name

Specifies the name of the PDSE where PSF writes the AFPSTATS report. This data set is defined in the PSF startup procedure by the AFPSTATS DD statement.

member name

The name PSF gave the report when it was placed in the PDSE named *data set name*. This report can be viewed or printed. For information about printing the AFPSTATS report, see [PSF for z/OS: User's Guide](#).

System action

This message is placed in the message data set for the print data set when an AFPSTATS report is requested. PSF processing continues.

Operator response

If this message appears on the operator's console, inform your system programmer. AFP Statistics are not gathered or reported while separator pages or the PSF message data set are processed.

System programmer response

No response is necessary.

User response

Use the data set name and member name from this message to locate the requested AFPSTATS report for viewing or printing.

APS4002I THE AFP STATISTICS REPORT WAS REQUESTED BUT COULD NOT BE GENERATED BECAUSE THE AFPSTATS DD STATEMENT WAS NOT SPECIFIED ON THE PSF STARTUP PROCEDURE.

Explanation

An AFP Statistics (AFPSTATS) report was requested for this print file, but the required AFPSTATS DD statement was not specified in the PSF startup procedure.

System action

No AFPSTATS report was generated. PSF stops AFPSTATS report-related processing but continues all other processing.

Operator response

If this message appears on the operator's console, inform your system programmer. AFP Statistics are not gathered during processing of separator pages or the PSF message data set.

System programmer response

The AFPSTATS DD statement must be specified in the PSF startup procedure for PSF to produce the AFPSTATS report. For information about how to allocate the PDSE for AFP Statistics facility see [PSF for z/OS: Customization](#).

User response

Inform your system programmer of this condition. The system programmer must specify the AFPSTATS DD statement in the PSF startup procedure for PSF to produce the AFPSTATS report.

APS4003I THE AFP STATISTICS REPORT FACILITY IN PSF HAS ENCOUNTERED AN AFPSTATS FILE ACCESS PROBLEM AND HAS SHUT DOWN. THE DETAILS FOR THE FILE ACCESS FAILURE ARE (*file access failure*). ALL OTHER PSF PROCESSING CONTINUES.

Explanation

While PSF was processing an AFP Statistics (AFPSTATS) report for this print data set, an error occurred accessing the PDSE where PSF is trying to place the AFPSTATS report. This caused AFPSTATS report processing to be ended. The specific error is described by *file access failure*.

file access failure can be any of these values:

- OPEN FAILURE, AFPSTATS DD STATEMENT
- CREATING MEMBER, *member_name*
- NO UNIQUE MEMBER
- WRITE FAILURE, PRINT FILE INFORMATION SECTION
- WRITE FAILURE, PRINT FILE EXTENSION INFORMATION SECTION
- WRITE FAILURE, PROCESSING DETAIL SECTION — FRONT MATTER
- WRITE FAILURE, PROCESSING DETAIL SECTION — RESOURCE RECORD
- WRITE FAILURE, PROCESSING DETAIL SECTION — EVENT RECORD
- WRITE FAILURE, PROCESSING DETAIL SECTION — BACK MATTER
- WRITE FAILURE, RESOURCE SUMMARY BY NAME SECTION
- WRITE FAILURE, RESOURCE SUMMARY BY DATA SET SECTION
- WRITE FAILURE, RESOURCE SUMMARY BY RESOURCE TYPE SECTION
- WRITE FAILURE, PROCESSING SUMMARY SECTION

System action

The processing for the AFPSTATS report is stopped and PSF continues processing the print file.

Operator response

If this message displays on the operator's console, inform your system programmer. AFP Statistics are not gathered while separator pages or the PSF message data set are processed.

System programmer response

An error exists in the way the AFPSTATS DD statement was specified or in the PDSE specified by the AFPSTATS DD statement. This message might be the result of an error in the AFPSTATS repository. The error might be caused by one of these conditions:

1. The AFPSTATS repository is full.
2. The volume that contains the AFPSTATS repository is full.
3. An I/O error exists on the volume that contains the AFPSTATS repository.

To keep PSF running when an error occurs in the AFPSTATS data set, PSF traps the data set error, produces this message, ends any further AFPSTATS processing, and continues to process the print file.

Correct the AFPSTATS DD statement or the PDSE error and try again. See *PSF for z/OS: Customization* for information about allocating this PDSE.

User response

Inform your system programmer that this error occurred.

APS4004I THE AFP STATISTICS REPORT FACILITY IN PSF HAS ENCOUNTERED AN INTERNAL LOGIC ERROR AND HAS SHUT DOWN. THE SPECIFIC ERROR WAS (*logic error*). ALL OTHER PSF PROCESSING CONTINUES.

Explanation

While PSF was processing an AFP Statistics (AFPSTATS) report for this print data set, an internal logic error occurred that caused the AFPSTATS processing to be ended. The specific error is described by *logic error*.

logic error can be any of these values:

- PARAMETERS NOT VALID, APSGAACT
- PARAMETERS NOT VALID, APSGADEX
- PARAMETERS NOT VALID, APSGAEVR
- PARAMETERS NOT VALID, APSGAFEX
- PARAMETERS NOT VALID, APSGAFRF
- PARAMETERS NOT VALID, APSGAINC
- PARAMETERS NOT VALID, APSGAJCL
- PARAMETERS NOT VALID, APSGAMEX
- PARAMETERS NOT VALID, APSGAMLD
- PARAMETERS NOT VALID, APSGAMLR
- PARAMETERS NOT VALID, APSGARES
- PARAMETERS NOT VALID, APSGARLD
- PARAMETERS NOT VALID, APSGARSR
- PARAMETERS NOT VALID, APSGATRM
- PARAMETERS NOT VALID, APSRASFT
- PARAMETERS NOT VALID, APSRAUST
- INTERFACE ERROR, APSGAEND
- INTERFACE ERROR, APSGAEVR
- INTERFACE ERROR, APSGAPFR
- INTERFACE ERROR, APSGAPFX
- INTERFACE ERROR, APSGARSR
- INTERFACE ERROR, APSGASNM
- INTERFACE ERROR, APSGASPR
- INTERFACE ERROR, APSGASRT

System action

The processing for the AFP Statistics facility is stopped and PSF continues processing the print file.

Operator response

If this message displays on the operator's console, inform your system programmer. AFP Statistics are not gathered while separator pages or the PSF message data set are processed.

System programmer response

This error is most likely an internal PSF error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

User response

Inform your system programmer that this error occurred.

APS4400I UNICODE CONVERSION FAILURE: FACILITY RETURNED WITH RETURN CODE=*return code* AND REASON CODE=*reason code*. CONVERTING STRING FROM INPUT ENCODING=*from ccsid* TO OUTPUT ENCODING=*to ccsid*.

Explanation

PSF encountered an error when it is using the ZCONV Unicode data transform facility. PSF might have to change the Unicode encoding for resource names because various system facilities might require the name to be in a different Unicode encoding. For example, a TrueType font name might be specified in Unicode encoding UTF-16 (CCSID=1200) but PSF might be printing a message that wants to give the font name in EBCDIC (CCSID=500). In this case, PSF must change the encoding of the font name. For a list of return and reason codes, see *z/OS Unicode Services User's Guide and Reference*.

System action

PSF was unable to process the necessary resources to print the page. PSF prints this error message and associated environment messages.

The action that is taken by PSF depends on where in the data stream the data object resource was specified. In the associated environment messages that are produced for this error, PSF identifies the location of the error within the data stream and the disposition of the error.

Operator response

If this message displays on the operator's console, it indicates that PSF is processing a TrueType or OpenType font request for separator pages, message pages, or a default resource specified in the PSF startup procedure. Inform your system programmer.

System programmer response

Make sure that the z/OS system is properly enabled for Unicode data transforms and that the correct transforms, both to and from, are initialized. See *PSF for z/OS: Customization* for more information about setting up the ZCONV facility.

If the error involves separator pages or message pages, use the information that is provided in the User Response section to correct the error. If an IBM licensed program was used to create the structured fields for the print data set with the error, verify that the input to that program was correct. If the input was correct, see *PSF for z/OS: Diagnosis* for assistance in determining the source of the problem.

User response

This problem is generally caused by one of these conditions:

- The Unicode encoding of the font name was not correct. Either the *to ccsid*, the GCSGID and CPGID equivalent of the *to ccsid*, or the *from ccsid* were not specified correctly in the Map Data Resource (MDR) structured field.
- The font name was not encoded as indicated in the *to ccsid* or GCSGID and CPGID of the MDR. A mismatch existed between the actual name encoding and the specification of the name encoding.
- The z/OS system was not properly prepared to handle this particular name encoding transform. A transform from *from ccsid* to *to ccsid* is not currently enabled on the system. Contact your system programmer for assistance in correcting this condition.

APS4401I **CDRA CONVERSION FAILURE:
FACILITY RETURNED WITH
RETURN CODE = *return code*.**

Explanation

When PSF is using Character Data Representation Architecture (CDRA) services to convert a resource name, PSF must convert a graphic character set global identifier (GCSGID) and code page global identifier (CPGID) encoding pair into a coded character set identifier (CCSID). However, the conversion to a CCSID

failed. The possible return codes from the system's conversion services are:

X'00060001'—The CCSID resource repository was not found.

X'00060002'—The CCSID resource repository is unavailable.

X'00070001'—The system CCSID resource repository that is accessed by the function was found not to be valid in structure.

All other return codes—logic error.

System action

PSF produces this error message and then produces an abend with a system completion code 024 and abend reason code 0E51.

Operator response

If this message displays on the operator's console, it indicates that PSF is processing separator pages, message pages, or a default resource specified in the PSF startup procedure. Inform your system programmer.

System programmer response

If this error is deemed a logic error, contact your service representative in the IBM Support Center, or use your electronic link with IBM service for assistance.

User response

Inform your system programmer.

APS4402I **REQUESTED TRANSFORM OF
INPUT DATA FROM
GCSGID(*gcsgid*)-CPGID(*cpgid*) TO
CCSID(*ccsid*) CANNOT BE
PERFORMED.**

Explanation

PSF received a request to process a TrueType or OpenType font, data object resource, or color management resource with a Unicode name encoding GCSGID of *gcsgid*, and CPGID of *cpgid*. PSF needs to transform this name to a Unicode encoding of *ccsid*, and cannot process this request unless PSF is Unicode-enabled. By default, PSF is enabled for Unicode processing; however, because of a UNIX System Services error, PSF cannot use conversion services to process this request.

System action

PSF was unable to process the necessary resources to print the page. PSF prints this error message and associated environment messages.

The action that is taken by PSF depends on where in the data stream the data object was specified. In the associated environment message that is produced for this error, PSF identifies the location of the error within the data stream and the disposition of the error.

Operator response

If this message displays on the operator's console, it indicates that PSF is processing separator pages, message pages, or a default resource that is specified in the PSF startup procedure that requires TrueType and OpenType fonts, data object resources, or color management resources, but PSF is not Unicode-enabled. Inform your system programmer.

System programmer response

A UNIX System Services error occurred that prevented PSF from processing this resource request. See message APS7001I, which was issued with this message, for help correcting the UNIX System Services error.

User response

Contact your system programmer.

APS4403I	THE REQUESTED TRANSFORM OF INPUT DATA FROM CCSID(<i>ccsid</i>) TO CCSID(<i>ccsid</i>) CANNOT BE PERFORMED.
-----------------	---

Explanation

PSF must convert input data to the specified encoding to continue processing, but cannot do so because it is not enabled for Unicode processing. By default, PSF is enabled for Unicode processing; however, because of a UNIX System Services error, PSF cannot use conversion services to process this request.

If the output CCSID is 1200 or 500, the input data is a TrueType or OpenType font, data object resource, or color management resource name. If the output CCSID is anything else, mixed single-byte or double-byte EBCDIC data is being converted to mixed single-byte or double-byte ASCII data for a QR Code bar code.

System action

PSF is unable to continue processing the page. PSF prints this error message and associated environment messages.

The action that is taken by PSF depends on where in the data stream the conversion error occurred. In the associated environment message, PSF identifies the location of the error within the data stream and the disposition of the error.

Operator response

If this message displays on the operator's console, it indicates that PSF is processing separator pages, message pages, or a default resource specified in the PSF startup procedure. Inform your system programmer.

System programmer response

A UNIX System Services error occurred that prevented PSF from processing this resource request. See message APS7001I, which was issued with this message, for help correcting the UNIX System Services error.

User response

Contact your system programmer.

APS4500I	DYNAMIC ALLOCATION FAILED FOR TRACE DATASET <i>dsname</i>, RETURN CODE <i>retcode</i>, REASON CODE <i>reason code</i>.
-----------------	---

Explanation

PSF tried to allocate the requested trace data set, but received the error indicated. One possible cause for this message is that the PSF trace data set did not exist before the PSF FSA was started. Another possible cause is that the data set was not cataloged.

dsname is the PSF trace data set name that is specified in the Printer Inventory `fsa-trace-dsname` parameter. *retcode* and *reason code* are the values that are returned to PSF from the system dynamic allocation function and might help diagnose this problem.

System action

PSF initialization continues with no external tracing.

Operator response

No response is necessary.

System programmer response

Correct the error and restart PSF. For more information about tracing, see *PSF for z/OS: Diagnosis*.

User response

No response is necessary.

APS4501I **TRACING TO (*ddname* | *dsname*)
HAS STARTED.**

Explanation

This message indicates that the output trace for PSF is started. If you are tracing the FSA, *dsname* matches the name of the CNTL statement. If the Printer Inventory is being used for this FSS, the *dsname* was specified in the inventory. Otherwise, the *ddname* was specified in the PSF startup procedure.

System action

Processing of the data set continues.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

No response is necessary.

APS4502I **TRACING TO (*ddname* | *dsname*)
HAS STOPPED.**

Explanation

This message indicates that the output trace for PSF is stopped. If you are tracing the FSA, *dsname* matches the name of the CNTL statement. If the Printer Inventory is being used for this FSS, the *dsname* was specified in the inventory. Otherwise, the *ddname* was specified in the PSF startup procedure.

System action

Processing of the data set continues.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

No response is necessary.

APS4506I **THE ZFS TRACING FILE FAILED TO
OPEN. TRACING HAS STOPPED.**

Explanation

An error occurred that prevents PSF from opening the requested tracing file. The error might be because the PSF tracing file did not exist before the PSF FSA was started.

System action

PSF initialization continues with no external tracing.

Operator response

No response is necessary.

System programmer response

Correct the error and restart PSF. For more information about tracing, see *PSF for z/OS: Diagnosis*.

User response

No response is necessary.

APS6000 to APS8600

APS6500I **UNEXPECTED SESSION ENDING
RESPONSE RECEIVED FROM THE
PRINTER.**

Explanation

An unexpected response was received from the printer that ended the TCP/IP session prematurely.

System action

If a data set was being printed at the time the session ended, the data set might be restarted from the most recent checkpoint before the session was ended or

might be restarted from the beginning if no checkpoints were reached.

One of these actions occurs, depending on when the failure occurred and what type of failure it was.

- If connecting to the printer and FAILURE=WCONNECT is specified on the PRINTDEV statement or Failure action = Wait for connect is specified in the Printer Inventory, PSF issues message APS935I and tries to connect again until the connect interval timer (CONNINTV on the PRINTDEV statement or Connect interval in the Printer Inventory) expires.

- If connecting to the printer and FAILURE=STOP in the Printer Inventory, PSF stops the FSA and issues APS934I.
- If attempting to send data and FAILURE=STOP is specified on the PRINTDEV statement or Failure action = stop is specified in the Printer Inventory, PSF stops the FSA and issues APS934I.
- If attempting to send data and FAILURE=WCONNECT is specified on the PRINTDEV statement or Failure action = Wait for connect is specified in the Printer Inventory, PSF issues messages APS932I and APS6501I and attempts to reestablish the connection.

Operator response

No response is necessary.

System programmer response

This error indicates a possible logic error in the microcode of the printer or another problem with the printer. Contact your hardware service provider or the person responsible for the printer for assistance.

User response

Examine your output for duplicate pages.

APS6501A and APS6501I **AN UNEXPECTED COMMUNICATION FAILURE OCCURRED. PRINTING WILL BE RESTARTED AT A PREVIOUS CHECKPOINT, AND PAGES MIGHT BE DUPLICATED. ERRNO = *errno*.**

Explanation

PSF detected a communication failure with the printer; for example, the session was disconnected during page processing. Printing is restarted at the most recent checkpoint or the beginning of the data set; therefore, some pages might be reprinted. PSF might issue this message when TCP/IP is recycled. This message appears on the operator console.

ERRNO = *errno* indicates the TCP/IP error. To interpret the ERRNO, see [z/OS Communications Server: IP and SNA Codes](#).

A common ERRNO associated with this message is:

- 0** This error indicates that the partner closed its end of the socket connection. Determine why the remote partner closed the connection, which might involve a microcode trace at the printer.

System action

The data set that is printed at the time of the error is restarted from the most recent checkpoint before the interrupt. If no checkpoints were reached, the data set is reprinted from the beginning.

Operator response

To determine an appropriate response, see the specific error conditions that are described in any accompanying console messages.

Message APS6501A: The message must be removed manually from the operator console.

System programmer response

No response is necessary.

User response

Examine your output for duplicate pages.

APS6502I **PERMANENT HARDWARE ERROR DETECTED ON PRINTER *prtnnn*. PAPER SIZE FOR INPUT BIN *nn* IS NOT VALID. PSF INITIALIZATION IS TERMINATED**

Explanation

The Obtain Printer Characteristics response that is returned by the printer showed the physical paper width, physical paper length, logical page width, or the logical page length for the input bin is zero. For each input bin that is used, PSF requires a valid physical paper size and logical page size.

System action

PSF processing ends abnormally by issuing a system completion code 024 and abend reason code 0242. PSF does not create an SVC dump for this abend.

Operator response

Notify your system programmer that this error occurred.

System programmer response

This error indicates a logic error in the printer microcode, but is not a PSF logic error. Contact your hardware service representative. If an SVC dump is required, follow the procedure that is described in [PSF for z/OS: Diagnosis](#) for generating an SVC dump.

User response

No response is necessary.

**APS6503I PRINTER *prt*nnn RETURNED
UNEXPECTED PAGE COUNTERS.****Explanation**

The page counters that are returned in the printer response do not match the PSF internal page counters. The printer might not recognize that a page was sent by PSF. This message is only issued when you are using a SNA or TCP/IP attached printer.

System action

PSF processing ends abnormally by issuing a system completion code 024 and abend reason code 02BE. PSF begins restart processing. If this message is issued frequently, PSF might continue with abnormal ending and not do restart processing

Operator response

If this message is displayed frequently or restart processing failed, contact your system programmer.

System programmer response

This error is most likely a logic error in the printer microcode, but might be a PSF logic error. Contact your hardware service representative.

To determine whether PSF began restart processing, check the operator console for message APS038I and to verify it was successful, check the console for message APS057I. If restart processing fails, PSF issues message APS053I and continues with abnormal ending. If message APS6503I is issued frequently, PSF might continue to end abnormally and create an SVC dump. For more information about PSF restart processing, see [PSF for z/OS: Diagnosis](#).

User response

No response is necessary.

**APS6504I THE MESSAGE LENGTH IN THE
TCP/IP PREFIX IS GREATER THAN
THE MAXIMUM LENGTH ALLOWED.****Explanation**

The message length in the TCP/IP prefix is greater than the maximum message length allowed.

System action

If PSF is bringing up the session, it attempts to restart the session. If PSF already has a session, it brings down the session and then attempts to restart it.

Operator response

This error indicates a possible logic error in the microcode of the printer or another problem with the printer. Contact your hardware service provider or the person responsible for the printer for assistance.

System programmer response

This error indicates a possible logic error in the microcode of the printer or another problem with the printer. Contact your hardware service provider or the person responsible for the printer for assistance.

User response

No response is necessary.

**APS6505I INITAPI FAILED FOR TCP/IP
ADDRESS SPACE NAME OF (*tcpip*
name) WITH A RETURN CODE OF
(*nnnn*) AND AN ERRNO = *errno*.****Explanation**

The INITAPI call to TCP/IP failed. *nnnn* is the return code from the call, and *errno* is the TCP/IP error number. *tcpip name* is the TCP/IP address space name: either the default name, TCPIP, or the name specified as a parameter on the EXEC statement.

The INITAPI call failed for a condition that can be tried again. PSF is trying the INITAPI call again and continues retrying the call for the duration of the connect interval timer (CONNINTV).

To interpret the error number (ERRNO), see [z/OS Communications Server: IP and SNA Codes](#).

ERRNOs associated with this message are:

1036

TCP/IP is not installed or not active.

10218

Application programming interface (API) cannot locate the specified TCP/IP.

In either case, ensure that TCP/IP is active.

System action

The INITAPI call was tried again and continues to be tried until the call completes successfully or the connect interval timer expires. If FAILURE=WCONNECT on the PRINTDEV statement in the PSF startup procedure or Failure action = Wait for connect in the Printer Inventory, PSF tries to do the INITAPI call continuously, issuing the APS6505I message only when the ERRNO changes between attempts.

Operator response

The problem occurred because TCP/IP is not active. Start TCP/IP or ensure that TCP/IP is started before you start the printer.

System programmer response

The problem occurred because TCP/IP is not active. Start TCP/IP or ensure that TCP/IP is started before you start the printer.

User response

No response is necessary.

APS6506I **PRINTER INFORMATION FOR
prtnnnn COULD NOT BE WRITTEN
TO THE *location* DUE TO ERROR:
error**

Explanation

While PSF was attempting to write the printer information for printer *prtnnnn* to *location*, an error occurred and prevented PSF from writing the printer information.

location can be one of these values:

PRTINFO DATA SET

PSF was attempting to write the printer information to the printer information data set specified by the PRTINFO DD statement in the PSF startup procedure.

SYSTEM LOG

When using the PSF operator interface, the operator requested that PSF write the printer information to the system log.

error describes the error that occurred and can be one of these values:

STORAGE ALLOCATION FAILURE.

PSF was attempting to get storage required for processing, but a GETMAIN failed.

MEMBER COULD NOT BE WRITTEN TO THE PRTINFO DATA SET.

PSF was attempting to write the member for *prtnnnn* to the printer information data set, but an I/O error occurred.

PRTINFO DD STATEMENT WAS NOT SPECIFIED.

The PRTINFO DD statement, which specified the printer information data set, was not specified in the PSF startup procedure.

PRTINFO DATA SET COULD NOT BE OPENED.

PSF was attempting to open the data set defined by the PRTINFO DD statement, but the open failed.

ERROR WRITING TO SYSLOG.

PSF was writing the printer information data to the SYSLOG data set when it encountered an error.

INTERNAL PROGRAM ERROR.

PSF encountered a logic error while it was processing the PRTINFO request.

System action

PSF stops writing the printer information and continues processing. No data or partial data is written to the system log or printer information data set.

Operator response

Inform your system programmer that this error occurred. If the PSF operator interface was used to write the printer information to the system log, issue the command again.

System programmer response

If the error was caused because PSF cannot get storage, increase the REGION parameter in the PSF startup procedure. If the PRTINFO DD statement was not specified, add it to the PSF startup procedure. For more information about the PSF startup procedure, see *PSF for z/OS: Customization*. If the error was because of an I/O error, check the operator console for message IECxxxI to determine the cause of the I/O error. For more information about message IECxxxI, see *z/OS MVS System Messages, Vol 7 (IEB-IEE)*.

User response

No response is necessary.

APS6507I **PRINTER INFORMATION FOR
prtnnnn CANNOT BE DISPLAYED
BECAUSE THE INFORMATION IS
NOT PROVIDED BY A *pppp*
PRINTER.**

Explanation

Printer information was requested for a *pppp* printer that does not provide the Sense Type and Model (STM) and Obtain Printer Characteristics (OPC) command responses that PSF uses to generate the printer information. *pppp* is either 3800 or 3820.

System action

PSF does not write the printer information to the system log or the printer information data set.

Operator response

Printer information cannot be displayed for a 3800 or 3820 printer. If the PSF operator interface is being used to write the printer information to the system log, only request printer information for printers other than a 3800 or 3820. If the printer information was to be written to the printer information data set, inform your system programmer that this error occurred.

System programmer response

Remove the PRTINFO DD statement from the PSF startup procedure, which prevents this message from occurring again; however, message APS6506I might be issued for other printers.

User response

No response is necessary.

APS6508I PRTINFO DISPLAY DATA

Explanation

When using the PSF operator interface, the operator requested that PSF write the printer information to the system log. For more information, see [PSF for z/OS: Diagnosis](#).

System action

PSF displays the printer information to the system log and continues processing.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

No response is necessary.

APS6509I PRINTER INFORMATION FOR prtnnnn COULD NOT BE WRITTEN TO THE SYSTEM LOG BECAUSE THE PRINTER HAS NOT BEEN CONTACTED.

Explanation

The operator used the PSF operator interface to request that PSF write the printer information for printer *prtnnnn* to the system log. However, the information was not obtained from the printer because PSF was not connected to the printer. PSF was probably not connected to the printer because the

MGMTMODE parameter on the PRINTDEV statement was set to OUTAVAIL or, if the Printer Inventory is used, the Management mode parameter was set to Output available and PSF did not process the first job. After PSF processes the first job, the printer information can be displayed in the system log.

System action

PSF does not write the printer information to the system log.

Operator response

When PSF starts to process the first job, issue the MVS MODIFY command to display the printer information in the system log. Otherwise, inform your system programmer that this error occurred.

System programmer response

If you want PSF to display the printer information even if a job was not processed, specify MGMTMODE = IMMED on the PRINTDEV statement or Management Mode = Immediate in the Printer Inventory. See [PSF for z/OS: Customization](#) for more information.

User response

No response is necessary.

APS6510I AN UNEXPECTED COMMUNICATION FAILURE OCCURRED. PRINTING WILL BE RESTARTED AT A PREVIOUS CHECKPOINT, AND PAGES MIGHT BE DUPLICATED.

Explanation

PSF detected a communication failure with the printer; for example, the session was disconnected during page processing. Printing is restarted at the most recent checkpoint or the beginning of the data set; therefore, some pages might be reprinted. This message appears on the operator console.

System action

The data set being printed at the time of the error is restarted from the most recent checkpoint before the interrupt. If no checkpoints were reached, the data set is reprinted from the beginning.

Operator response

To determine an appropriate response, see the specific error conditions that are described in any accompanying console messages.

System programmer response

No response is necessary.

User response

Examine your output for duplicate pages.

APS6511I **INTERVENTION REQUIRED,
DEV=pppp, IPADDR=ipaddr.**

Explanation

A condition that requires intervention, such as a paper jam, occurred on a TCP/IP-attached printer. The message uses these variables to describe the printer:

pppp

The printer device type; for example, 4322.

ipaddr

The Internet Protocol address or host name of the TCP/IP-attached printer.

System action

PSF stops processing. When the intervention condition is cleared, this message is deleted and PSF continues processing.

Operator response

When this message displays on the console, it indicates that a condition exists that requires intervention at a TCP/IP-attached printer. See the operator's guide for the printer that reported this condition, and clear the condition at the printer. If you do not want this message to be issued for this printer, contact your system programmer.

System programmer response

If you do not want this message to be issued for this printer, set the Exit 7 XTP7IMSG flag to B'0' or set the Issue intervention messages value in the Printer Inventory to NO.

User response

No response is necessary.

APS6512I **AN UNEXPECTED
COMMUNICATION FAILURE
OCCURRED. THE JOB WILL BE
RESTARTED AT A PREVIOUS
CHECKPOINT. ERRNO = *errno*.**

Explanation

AFP Download Plus detected a communication failure with the remote system; for example, the session was disconnected. The job is restarted at the most recent

checkpoint or the beginning of the job. AFP Download Plus can issue this message when TCP/IP is recycled. This message appears on the operator console.

ERRNO (*errno*) specifies the TCP/IP error number. To interpret the error number, see *z/OS Communications Server: IP and SNA Codes*.

Common error numbers that are associated with this message are:

0

The remote system closed its end of the socket connection. Determine why the remote system closed the connection.

54

The connection to the destination host is not available. This error can happen when AFP Download Plus is connected to a Windows remote system that is configured with the `Provide exit program errors to z/OS error processing option` and a job was sent with a `DESTINATION` that was not defined to the print server. The print server stops the receiver, which causes the APS6512I message.

System action

The job is resent from the checkpoint before the interrupt. If no checkpoints were reached, the data set is resent from the beginning.

Operator response

To determine an appropriate response, see the specific error conditions that are described in any accompanying console messages.

System programmer response

No response is necessary.

User response

No response is necessary.

APS6513I **CONNECTION WITH TCP/IP-
ATTACHED REMOTE SYSTEM
(*fsaname*) IPADDR (*ip-address*)
PORT NUMBER (*portnumber*) IS
BEING TRIED AGAIN BECAUSE OF
A PREVIOUSLY DETECTED
CONDITION (*reason*), TCP/IP
ERRNO = *errno*.**

Explanation

Communication with the remote (receiver) system ended for a condition that can be tried again. AFP Download Plus is trying to reestablish the connection.

TCP/IP ERRNO=*errno* specifies the TCP/IP error number and PORT NUMBER (*port number*) specifies the port number of the TCP/IP-attached remote system. To interpret the error number, see [z/OS Communications Server: IP and SNA Codes](#).

Common error numbers that are associated with this message are:

0

See the previously displayed message for a description of the problem.

49

AFP Download Plus cannot reach the destination, indicating a bad IP address.

60

The connection timed out before it was completed. This error can happen when AFP Download Plus is connected to a Windows remote system that is configured with the "Provide extended error information to AFP Download Plus" error processing option and a job was sent with a DESTINATION that was not defined to the print server. The print server stops the receiver, which causes the APS6513I message.

61

The connection was refused. This error can happen when:

- The remote system is accepting a connection with another partner and refuses other connections while it completes the current request.
- The port numbers at the host (sender) system and the remote system do not match.

SYSTEM (*fsaname*) specifies the name of the PRINTDEV statement.

IPADDR (*ip-address*) specifies the IP address of the TCP/IP-attached remote system.

CONDITION (*reason*) can be any of these:

SOCKET FAILED

AFP Download Plus was not able to get a socket on the z/OS operating system.

SOCKET CONNECT FAILED

AFP Download Plus failed to establish a socket connection with the remote system. AFP Download Plus displays this reason when:

- The remote system is not started.
- The wrong IP address is specified in the Printer Inventory or in the PRINTDEV statement.
- The IP address that is specified is a duplicate of another IP address on the network.
- The port numbers at the host and the remote system do not match.

System action

AFP Download Plus tried to restart the connection and waits for activation to complete. AFP Download Plus continues to try to restart the connection, issuing message APS6513I only when the ERRNO or REASON code changes between attempts.

Operator response

If CONDITION and ERRNO explain why communication with the remote system ended, fix the problem and restart the FSA. If the CONDITION does not explain why the communication session with the remote system ended, notify your system programmer.

If the remote system does not respond to AFP Download Plus, stop the FSA with this command:

```
MODIFY fss-name,FORCE,fsa-name
```

System programmer response

If any values in the Printer Inventory or on the PRINTDEV statement are incorrect, correct the incorrect items.

If a communication-attachment failure occurred, use the PING command with the IP address in the message to ensure that this remote system's TCP/IP socket connection to this address is active. For information about how to ping an IP address, see [PSF for z/OS: Customization](#).

User response

No response is necessary.

APS6514I **COMMUNICATION WITH TCP/IP-
ATTACHED REMOTE SYSTEM
(*fsaname*) IPADDR (*ip-address*)
WAS ENDED, CAUSE (*reason*)
TCP/IP ERRNO = *errno*.**

Explanation

A network error caused communication with the remote system to end. The TCP/IP connection with the remote system cannot be established, for one of these reasons:

- The error condition cannot be tried again.
- The connect interval (CONNINTV) timer expired.

Message APS6514I is issued from the AFP Download Plus ESTAE. This message does not have complete information if the error is a network error or communication error. If AFP Download Plus tried the error again, APS6513I precedes APS6514I and has more detailed CAUSE information. If message APS6513I is issued, use it to determine the cause.

Common error numbers that are associated with this message are:

49

AFP Download Plus cannot reach the destination, indicating a bad IP address.

60

The remote system might not be active.

61

The connection was refused. This error can happen when:

- The remote system is accepting a connection with another partner and refuses other connections while it completes the current request.
- The port numbers at the host and the remote system do not match.

REMOTE SYSTEM (*fsaname*) specifies the name of the PRINTDEV statement.

IPADDR (*ip-address*) specifies the IP address of the TCP/IP-attached remote system.

CAUSE (*reason*) can be:

SOCKET CONNECT FAILED

AFP Download Plus failed to establish a socket connection with the remote system. PSF displays this reason when:

- The remote system is not started.
- The wrong IP address is specified in the Printer Inventory or in the PRINTDEV statement.
- The IP address that is specified is a duplicate of another IP address on the network.
- The port numbers at the host and the remote system do not match.

System action

The AFP Download Plus FSA ends because the condition cannot be tried again or the connect interval (CONNINTV) timer expired.

Operator response

If CAUSE and ERRNO explain why communication with the remote system ended, fix the problem and restart the FSA. Otherwise, notify your system programmer.

System programmer response

If any values in the Printer Inventory or on the PRINTDEV statement are incorrect, correct the incorrect items.

If a communication-attachment failure occurred, use the PING command with the IP address in the

message to ensure that this remote system's TCP/IP socket connection to this address is active. For information on how to ping an IP address, see [PSF for z/OS: Customization](#).

If you changed a PRINTDEV parameter on the AFP Download Plus startup procedure, such as the IP address, you must restart the AFP Download Plus FSS to use the changes.

If you changed a parameter in the Printer Inventory, you must restart the AFP Download Plus FSA to use the changes.

If the error condition persists, consult the IBM Support Center.

User response

No response is necessary.

APS6515I

THE REQUIRED RESPONSE WAS NOT RECEIVED FROM THE REMOTE SYSTEM.

Explanation

AFP Download Plus did not receive a required response from the remote system. This error might be caused by one of these conditions:

- Another FSA actively communicating with the same download receiver. This warning message can be ignored because the connection is completed when the other FSA finishes with its connection.
- An incorrect version of the download receiver is in use. Either an old version of the download receiver is being used or secure transmission is deactivated and a version of the download receiver is being used that does not support secure transmission deactivation.

System action

Processing continues while AFP Download Plus waits indefinitely for the required response.

Operator response

If multiple FSAs are using the same download receiver and the correct version of the download receiver is being used, no response is necessary. Otherwise, inform your system programmer that this error occurred.

System programmer response

If multiple FSAs are using the same download receiver and the correct version of the download receiver is being used, no response is necessary.

Verify that the correct version of the download receiver is being used. AFP Download Plus might require a newer version of the download receiver than Download for z/OS requires. Deactivating secure transmission requires a new version of the download receiver.

User response

No response is necessary.

APS6516I **PRINTER INFORMATION FOR
prtnnnn COULD NOT BE CREATED
DUE TO AN INTERNAL ERROR. PSF
PROCESSING CONTINUES.
RC('returncode'X)
RS('reasoncode'X)**

Explanation

PSF detected an internal processing error while it was processing the printer information for printer *prtnnnn*. The *returncode* and *reasoncode* values define the specific error.

System action

PSF processing continues. PSF either does not produce a printer information report or it produces a partial report.

Operator response

If the error persists, inform your system programmer.

System programmer response

This message indicates a possible PSF logic error. Follow the procedures that are described in *PSF for z/OS: Diagnosis*. If the error condition persists, contact the IBM Support Center.

User response

No response is necessary.

APS6517I **PSF ATTEMPTED TO CONNECT TO
A CHANNEL-ATTACHED PRINTER
BUT CONTROL BLOCK IHAASVT
WAS ABOVE THE LINE.**

Explanation

In z/OS V2R1 and later, you can specify a DIAGxx SYS1.PARMLIB member that contains a CBLOC statement (CBLOC VIRTUAL31(IHAASVT)) with the IHAASVT control block above the line. However, PSF requires the IHAASVT control block to be below the line when it is using a channel-attached printer.

System action

PSF processing ends abnormally with a system completion code 024 and abend reason code 0207.

Operator response

Inform your system programmer that this error occurred.

System programmer response

To use a channel-attached printer, remove IHAASVT from the CBLOC VIRTUAL31 statement in the DIAGxx SYS1.PARMLIB member. An IPL is required when you change the CBLOC statement in the DIAGxx member.

User response

No response is necessary.

APS6518I **THE PRINTER SUPPORTS
FINISHING OPTIONS BUT DOES
NOT SUPPORT ANY FINISHING
OPERATIONS.**

Explanation

While processing the Obtain Printer Characteristics (OPC) response, the Finishing Options self-defining field was detected; however, no Finishing Operations self-defining field exists.

System action

The PSF FSA for the printer is stopped with a system completion code 024 and abend reason code 02FB.

Operator response

Inform your system programmer that this error occurred.

System programmer response

This message indicates a logic error in the microcode of the printer. Consult your IBM hardware service representative. This error is not a PSF logic error.

User response

No response is necessary.

APS7000I **THE INVOCATION OF CEEPIPI TO
INVOKE A C EXIT FAILED WITH
RETURN CODE (return code).**

Explanation

A nonzero return code was received from this invocation of CEEPIPI to call the C exit as a subroutine.

Return codes that are associated with this message are:

- 04** The function code is not valid.
- 08** CEEPIPI was called from a Language Environment-conforming HLL.
- 12** The indicated environment was initialized for main routines. No routine was run.
- 16** The token is not valid.
- 20** The index points to an entry that is not valid or is empty.
- 24** The index that is passed is outside the range of the table.
- 28** The enclave was stopped while the process was retained. This error can occur if a STOP statement is issued or if an unhandled condition exists. The *sub_ret_code*, *sub_reason_code*, and *sub_feedback_code* indicate this action.

For more information on this invocation of CEEPIPI and its return codes, see [z/OS Language Environment Programming Guide](#).

System action

PSF processing ends abnormally with a system completion code 024 or 027 and abend reason code 0A59, 0A5A, or 0A5B.

Operator response

Inform your system programmer that this error occurred.

System programmer response

If the problem cannot be diagnosed from the return code, contact the IBM Support Center.

User response

No response is necessary.

APS7001I THE INVOCATION OF BPX1SDD FOR PROCESS DUBBING FAILED WITH RETURN CODE (*return code*) AND REASON CODE (*reason code*).

Explanation

A bad return code was received from the BPX1SDD UNIX System Services callable service. For more information about this invocation, see [z/OS UNIX System Services Programming: Assembler Callable Services Reference](#). For information about its return and reason codes, see [z/OS UNIX System Services Messages and Codes](#).

System action

Processing continues without the installation exits that are written in C. All assembler exits are used.

Operator response

Inform your system programmer that this error occurred.

System programmer response

If the problem cannot be diagnosed from the return code and reason code, contact the IBM Support Center.

User response

No response is necessary.

APS7002I ACTIVATING BOTH 3800 LINE MODE CONVERSION AND LINE MODE MIGRATION IS NOT ALLOWED.

Explanation

Both 3800 Line-Mode Conversion and Line Mode Migration were activated for the same data set. This combination is not allowed.

System action

PSF processing ends abnormally with a system completion code 024 and abend reason code 0A5F.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Either disable 3800 Line-Mode Conversion processing in PSF Exit 4 or 14, or disable Line Mode Migration processing in PSF Exit 8 for this data set.

User response

No response is necessary.

**APS7003I ACTIVATING BOTH LINE MODE
MIGRATION FOR A 4245 FCB AND
LINE MODE MIGRATION FOR A
4248 FCB IS NOT ALLOWED.**

Explanation

Both Line Mode Migration processing for a 4245 FCB and Line Mode Migration processing for a 4248 FCB were activated for the same data set. This combination is not allowed. Either 4245 FCB or 4248 FCB processing can be active for the data set, but not both.

System action

PSF processing ends abnormally with a system completion code 024 and abend reason code 0A60.

Operator response

Inform your system programmer that this error occurred.

System programmer response

In the PSF Exit 8, disable either 4245 FCB Line Mode Migration processing or 4248 FCB Line Mode Migration for this data set.

User response

No response is necessary.

**APS7004I INSTALLATION EXIT 7 HAS
CHANGED THE VALUE OF THE
AFPSTATS OUTPUT STATEMENT
PARAMETER TO *value*.**

Explanation

Exit 7 changed the value of the AFPSTATS Output statement parameter. It either changed it from yes to no or from no to yes.

System action

PSF places this message in the message data set and continues processing.

Operator response

No response is necessary.

System programmer response

If you want Exit 7 to control whether the AFP Statistics Report is written, no response is necessary. If not, remove or modify Exit 7.

User response

If this change is not acceptable, contact your system programmer.

**APS7005I THE INVOCATION OF BPX1SDD
FOR PROCESS DUBBING FAILED
WITH RETURN CODE (*return code*)
AND REASON CODE (*reason code*).**

Explanation

A bad return code was received from the BPX1SDD UNIX System Services callable service. For more information about this invocation, see *z/OS UNIX System Services Programming: Assembler Callable Services Reference*. For information about its return and reason codes, see *z/OS UNIX System Services Messages and Codes*.

System action

PSF processing ends abnormally with an abend 027 and abend reason code 0A50.

Operator response

Inform your system programmer that this error occurred.

System programmer response

If the problem cannot be diagnosed from the return code and reason code, contact the IBM Support Center.

User response

No response is necessary.

**APS8000I THE DATA SET NAME SPECIFIED
WITH THE AFPPARMS
PARAMETER CONTAINS AN
ERROR. THE CHARACTER
character IS NOT VALID IN THE
DATA SET NAME.**

Explanation

An error exists in the name of the control data set that is specified with the AFPPARMS parameter in the OUTPUT JCL statement. The name of this data set consists of 1 - 5 qualifiers that are separated by periods and optionally followed by a member name in parentheses. The qualifiers must contain only these characters:

- Alphabetic characters (A–Z)
- Numeric characters (0–9)
- United States national characters (@, #, and \$)

Incorrect:
JANE ' S . AFP . CONTROL . PARS (LDPARMS)
Correct: MY . AFP . CONTROL . PARS (LDPARMS)

System action

PSF stops processing the current print data set, releases it back to JES, and requests that it is held by the system.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

If necessary, rename the control data set. Correct the OUTPUT JCL statement.

APS8001I THE DATA SET NAME SPECIFIED WITH THE AFPPARMS PARAMETER CONTAINS AN ERROR. THE FIRST CHARACTER IN THE DATA SET NAME CANNOT BE A PERIOD.

Explanation

An error exists in the name of the control data set that is specified with the AFPPARMS parameter in the OUTPUT JCL statement. Periods are used to separate qualifiers in the data set name, but must not be used before the first qualifier.

Incorrect: .MY . AFP . CONTROL . PARS
Correct: MY . AFP . CONTROL . PARS

System action

PSF stops processing the current print data set, releases it back to JES, and requests that it is held by the system.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

If necessary, rename the control data set. Correct the OUTPUT JCL statement.

APS8002I THE DATA SET NAME SPECIFIED WITH THE AFPPARMS PARAMETER CONTAINS AN ERROR. THE LAST CHARACTER IN THE DATA SET NAME CANNOT BE A PERIOD.

Explanation

An error exists in the name of the control data set that is specified with the AFPPARMS parameter in the OUTPUT JCL statement. Periods are used to separate qualifiers in the data set name, but must not be used after the last qualifier.

Incorrect: MY . AFP . CONTROL . PARS .
Correct: MY . AFP . CONTROL . PARS

System action

PSF stops processing the current print data set, releases it back to JES, and requests that it is held by the system.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

If necessary, rename the control data set. Correct the OUTPUT JCL statement.

APS8003I THE DATA SET NAME SPECIFIED WITH THE AFPPARMS PARAMETER CONTAINS AN ERROR. THE DATA SET NAME CANNOT HAVE MORE THAN FIVE QUALIFIERS SEPARATED BY PERIODS.

Explanation

An error exists in the name of the control data set that is specified with the AFPPARMS parameter in the OUTPUT JCL statement. Although the z/OS operating system allows data set names to have as many as 22 qualifiers, this data set name cannot have more than five.

Incorrect:
MY . CONTROL . PARS . FOR . AFP . DOWNLOAD . PLUS
Correct: MY . AFP . CONTROL . PARS

System action

PSF stops processing the current print data set, releases it back to JES, and requests that it is held by the system.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

If necessary, rename the control data set. Correct the OUTPUT JCL statement.

APS8004I THE DATA SET NAME SPECIFIED WITH THE AFPPARMS PARAMETER CONTAINS AN ERROR. THE DATA SET NAME CANNOT HAVE MORE THAN ONE PERIOD SEPARATING TWO QUALIFIERS.

Explanation

An error exists in the name of the control data set that is specified with the AFPPARMS parameter in the OUTPUT JCL statement. Multiple periods exist between two qualifier names. Only one period is allowed.

Incorrect: MY . AFP . . CONTROL . PARMS
 Correct: MY . AFP . CONTROL . PARMS

System action

PSF stops processing the current print data set, releases it back to JES, and requests that it is held by the system.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

If necessary, rename the control data set. Correct the OUTPUT JCL statement.

APS8005I THE DATA SET NAME SPECIFIED WITH THE AFPPARMS PARAMETER CONTAINS AN ERROR. A DATA SET NAME

QUALIFIER CANNOT CONTAIN MORE THAN EIGHT CHARACTERS.**Explanation**

An error exists in the name of the control data set that is specified with the AFPPARMS parameter in the OUTPUT JCL statement. A qualifier name is longer than the limit of 8 characters.

Incorrect: MY . AFP . CONTROL . PARAMETERS
 Correct: MY . AFP . CONTROL . PARMS

System action

PSF stops processing the current print data set, releases it back to JES, and requests that it is held by the system.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

If necessary, rename the control data set. Correct the OUTPUT JCL statement.

APS8006I THE DATA SET NAME SPECIFIED WITH THE AFPPARMS PARAMETER CONTAINS AN ERROR. A DATA SET NAME CANNOT CONTAIN A NUMBER AS THE FIRST CHARACTER IN A QUALIFIER.

Explanation

An error exists in the name of the control data set that is specified with the AFPPARMS parameter in the OUTPUT JCL statement. Qualifiers can contain the numeric characters (0 - 9), but they must begin with one of these characters:

- Alphabetic characters (A - Z)
- United States national characters (@, #, and \$)

Incorrect: MY . AFP . CONTROL . 3PARMS
 Correct: MY . AFP . CONTROL . PARMS3

System action

PSF stops processing the current print data set, releases it back to JES, and requests that it is held by the system.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

If necessary, rename the control data set. Correct the OUTPUT JCL statement.

APS8007I THE DATA SET NAME SPECIFIED WITH THE AFPPARMS PARAMETER CONTAINS AN ERROR. THE DATA SET NAME IS MISSING A PARENTHESIS.

Explanation

An error exists in the name of the control data set that is specified with the AFPPARMS parameter in the OUTPUT JCL statement. One of the parentheses around the member name is missing.

Incorrect: MY . AFP . CONTROL . PARM (LDPARMS
 Incorrect: MY . AFP . CONTROL . PARMSLDPARMS)
 Correct: MY . AFP . CONTROL . PARM (LDPARMS)

System action

PSF stops processing the current print data set, releases it back to JES, and requests that it is held by the system.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Correct the OUTPUT JCL statement.

APS8008I THE DATA SET NAME SPECIFIED WITH THE AFPPARMS PARAMETER CONTAINS AN ERROR. THE MEMBER NAME ENCLOSED IN PARENTHESSES MUST BE AT THE END OF THE DATA SET NAME.

Explanation

An error exists in the name of the control data set that is specified with the AFPPARMS parameter in the

OUTPUT JCL statement. Characters must not be used after the closing parenthesis of the member name.

Incorrect:
 MY . AFP . CONTROL . PARM (LDPARMS) . SET1
 Correct:
 MY . AFP . CONTROL . PARM . SET1 (LDPARMS)

System action

PSF stops processing the current print data set, releases it back to JES, and requests that it is held by the system.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Correct the OUTPUT JCL statement.

APS8009I THE DATA SET NAME SPECIFIED WITH THE AFPPARMS PARAMETER CONTAINS AN ERROR. THE MEMBER NAME MUST CONTAIN ONE TO EIGHT CHARACTERS.

Explanation

An error exists in the name of the control data set that is specified with the AFPPARMS parameter in the OUTPUT JCL statement. Either the member name is longer than 8 characters or no member name exists in the parentheses.

Incorrect:
 MY . AFP . CONTROL . PARM (LDPARAMETERS)
 Correct: MY . AFP . CONTROL . PARM (LDPARMS)
 Incorrect: MY . AFP . CONTROL . PARM ()
 Correct: MY . AFP . CONTROL . PARM

System action

PSF stops processing the current print data set, releases it back to JES, and requests that it is held by the system.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

If necessary, rename the member in the control data set. Correct the OUTPUT JCL statement.

APS8010I THE DATA SET NAME SPECIFIED WITH THE AFPPARMS PARAMETER CONTAINS AN ERROR. THE FIRST CHARACTER IN A MEMBER NAME CANNOT BE A NUMBER.

Explanation

An error exists in the name of the control data set that is specified with the AFPPARMS parameter in the OUTPUT JCL statement. The member name can contain the numeric characters (0–9), but it must begin with one of these characters:

- Alphabetic characters (A–Z)
 - United States national characters (@, #, and \$)
- Incorrect: MY . AFP . CONTROL . PARM S (1PARMS)
Correct: MY . AFP . CONTROL . PARM S (PARMS1)

System action

PSF stops processing the current print data set, releases it back to JES, and requests that it is held by the system.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

If necessary, rename the member in the control data set. Correct the OUTPUT JCL statement.

APS8012I THE DATA SET NAME SPECIFIED WITH THE AFPPARMS PARAMETER CONTAINS AN ERROR. THE MEMBER NAME CANNOT BE IMMEDIATELY PRECEDED BY A PERIOD.

Explanation

An error exists in the name of the control data set that is specified with the AFPPARMS parameter in the OUTPUT JCL statement. Unlike qualifiers, the member name must not be preceded by a period.

Incorrect: MY . AFP . CONTROL . PARM S . (LDPARMS)
Correct: MY . AFP . CONTROL . PARM S (LDPARMS)

System action

PSF stops processing the current print data set, releases it back to JES, and requests that it is held by the system.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

If necessary, rename the member in the control data set. Correct the OUTPUT JCL statement.

APS8013I THE DATA SET NAME SPECIFIED WITH THE AFPPARMS PARAMETER CONTAINS AN ERROR. THE CHARACTER *character* IS NOT VALID IN THE MEMBER NAME.

Explanation

An error exists in the name of the control data set that is specified with the AFPPARMS parameter in the OUTPUT JCL statement. The member name must contain only these characters:

- Alphabetic characters (A–Z)
 - Numeric characters (0–9)
 - United States national characters (@, #, and \$)
- Incorrect: MY . AFP . CONTROL . PARM S (LD_PARM S)
Correct: MY . AFP . CONTROL . PARM S (LDPARMS)

System action

PSF stops processing the current print data set, releases it back to JES, and requests that it is held by the system.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

If necessary, rename the member in the control data set. Correct the OUTPUT JCL statement.

APS8014I AN ERROR OCCURRED WHILE PROCESSING THE *identifier* DATA

SET data set name. RETURN CODE return code. REASON CODE decimal reason code/hexadecimal reason code.

Explanation

An error occurred while a sequential data set or a partitioned data set member was opened or read. The identifier indicates how you specified the data set name and can have these values:

STARTUP PROCEDURE AFPPARMS

This identifier indicates that the data set name came from the AFPPARMS DD statement in the startup procedure.

OUTPUT STATEMENT AFPPARMS

This identifier indicates that the data set name came from the AFPPARMS parameter on the OUTPUT statement.

The return code indicates the underlying system function that failed. The reason code is from the corresponding system function:

- 1 The reason code is the value of S99ERROR from the DFSMS DYNALLOC macro.
- 2 The reason code is the value of S99EERR from the DFSMS DYNALLOC macro.
- 3 The reason code is the value of register 15 from the DFSMS OPEN macro.
- 4 The reason code is the return code from an abend that occurred with the DFSMS OPEN macro.
- 5 The reason code is the value of register 1 that was passed to the SYNAD routine by the DFSMS GET macro.

System action

For the OUTPUT statement AFPPARMS, processing of the current print data set stops, it is released back to JES, and then it is held by the system. For the startup procedure AFPPARMS, the error message is issued to the console and the FSA stops abnormally.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Verify the data set name that you specified. Verify that the data set exists and authorizations are set to read it.

User response

Verify the data set name that you specified. Verify that the data set exists and authorizations are set to read it.

AP58015I

AN ERROR OCCURRED WHILE CREATING A TOKEN FROM A CONTROL PARAMETER IN THE identifier DATA SET data set name. RECORD NUMBER number. RETURN CODE return code.

Explanation

A syntax error was detected while processing records from a sequential data set or a partitioned data set member. The identifier indicates how you specified the data set name and can have these values:

STARTUP PROCEDURE AFPPARMS

This identifier indicates that the data set name came from the AFPPARMS DD statement in the startup procedure.

OUTPUT STATEMENT AFPPARMS

This identifier indicates that the data set name came from the AFPPARMS parameter on the OUTPUT statement.

The record number indicates the location of the error in the data set. The return code indicates the type of error that occurred:

- 2 The last control parameter in the data set is not complete. One or more values are missing.
- 3 The keyword separator is missing.
Incorrect: color red
Correct: color = red
- 4 The group begin delimiter occurs within a group. A group end delimiter is missing.
Incorrect: color = (red,bright(
Correct: color = (red,bright)
- 5 The group end delimiter occurs outside a group. A group begin delimiter or a string delimiter is missing.
Incorrect: color = color = red)
Correct: color = (red)
- 6 The group separator occurs outside a group. A group begin delimiter or a string delimiter is missing.

Incorrect: color = red,bright)
Correct: color = (red,bright)

7

The string end delimiter is missing.

Incorrect: place = "Tony's Pizza

Correct: place = "Tony's Pizza"

8

A string delimiter occurs within a non-string value. A string begin delimiter is missing.

Incorrect: place = Tony's Pizza"

Correct: place = "Tony's Pizza"

9

A group begin delimiter occurs inside a non-string value. A string begin delimiter is missing.

Incorrect: parenthetical = (some phrase)"

Correct: parenthetical = "(some phrase)"

10

Extra text occurs outside a string or comment. A string delimiter or comment delimiter is missing.

Incorrect: color = red my favorite color

Correct: color = red # my favorite color

11

A hexadecimal string contains characters that are not valid, or a character is missing.

Incorrect: color = 'D9V5C4'x

Correct: color = 'D9C5C4'x

System action

For the OUTPUT statement AFPPARMS, processing of the current print data set stops, it is released back to JES, and then it is held by the system. For the startup procedure AFPPARMS, the error message is issued to the console, and the FSA stops abnormally.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Verify and correct the syntax of the control parameter.

User response

Verify and correct the syntax of the control parameter.

APS8016I

AN ERROR OCCURRED WHILE INTERPRETING A CONTROL PARAMETER IN THE *identifier* DATA SET *data set name*. RECORD

NUMBER *number*. KEYWORD *keyword*. RETURN CODE *return code*.

Explanation

A syntax error was detected while processing records from a sequential data set or a partitioned data set member. The identifier indicates how you specified the data set name and can have the following values:

STARTUP PROCEDURE AFPPARMS

This identifier indicates that the data set name came from the AFPPARMS DD statement in the startup procedure.

OUTPUT STATEMENT AFPPARMS

This identifier indicates that the data set name came from the AFPPARMS parameter on the OUTPUT statement.

The record number indicates the last record of the data set for the control parameter that is in error. The keyword precedes the equal sign in the control parameter. The return code indicates the type of error that occurred:

1

The keyword is not recognized.

Incorrect: number = 10

Correct: number = 10

Some keywords are only valid on the AFPPARMS statement in the startup procedure and not on the AFPPARMS parameter in the OUTPUT statement. You receive this return code if you try to use those keywords on the AFPPARMS parameter in the OUPUT statement.

2

The value is not valid.

Incorrect: number = ten

Correct: number = 10

3

The option is not valid for the keyword.

Incorrect: color = rainy

Correct: color = red

4

There are too many values for the keyword. The maximum number of values varies by keyword.

Incorrect: color = (red, green, blue)

Correct: color = red

5

There are too few values for the keyword. The minimum number of values varies by keyword.

Incorrect: time = hours

Correct: time =
(hours,minutes,seconds)

- 6 The keyword is specified more than once, when only one instance is allowed.

Incorrect: oldest = Mary, oldest = John
Correct: oldest = Mary

- 7 The string value is too short. The minimum string length varies by keyword.

Incorrect: jobname = ""
Correct: jobname = "CHECKS"

- 8 The string value is too long. The maximum string length varies by keyword.

Incorrect: jobname = "JULY_CHECKS"
Correct: jobname = "CHECKS"

- 9 The numeric value is less than the allowed range. The allowed range varies by keyword.

Incorrect: speed = -1
Correct: speed = 55

- 10 The numeric value is greater than the allowed range. The allowed range varies by keyword.

Incorrect: speed = 200
Correct: speed = 55

- 11 Two options cannot both be valid at the same time.

Incorrect: weather = (rainy,dry)
Correct: weather = (rainy,wet)

- 12 The number of values is not valid. It might not be clear whether you specified too many values or too few. The required number of values varies by keyword.

Incorrect: car-tires =
(tire1,tire2,tire3)
Correct: car-tires =
(tire1,tire2,tire3,tire4)

System action

For the OUTPUT statement AFPPARMS, processing of the current print data set stops, it is released back to JES, and then it is held by the system. For the startup procedure AFPPARMS, the error message is issued to the console and the FSA stops abnormally.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Verify and correct the syntax of the control parameter.

User response

Verify and correct the syntax of the control parameter.

APS8017I	AFP DOWNLOAD PLUS HAS REMOVED THE -o name ATTRIBUTE SPECIFIED BY EXIT 15. -o name WILL NOT BE SENT TO THE REMOTE SYSTEM.
-----------------	---

Explanation

A -o attribute, such as OUTGRP, is not supported by the AFP Download Plus remote system. Therefore, AFP Download Plus ignores the -o attribute specified by Exit 15.

System action

AFP Download Plus continues to process the job, but does not send the -o attribute to the remote system.

Operator response

Notify your system programmer that this error occurred.

System programmer response

To stop issuing this message, change Exit 15 so the -o attribute is not specified.

User response

No response is necessary.

APS8018I	AN ERROR OCCURRED WHILE INTERPRETING A CONTROL PARAMETER IN THE identifier. KEYWORD keyword. VALUE value
-----------------	---

Explanation

- A syntax error was detected while processing records from a sequential data set or a partitioned data set member. The *identifier* can have one of these values:

STARTUP PROCEDURE AFPPARMS

Indicates that the data set was specified on the AFPPARMS DD statement in the startup procedure.

OUTPUT STATEMENT AFPPARMS

Indicates that the data set was specified in the AFPPARMS parameter on the OUTPUT statement.

System action

For the STARTUP PROCEDURE AFPPARMS value, the FSA stops with a system completion code 024 and abend reason code 00DA. For the OUTPUT STATEMENT AFPPARMS value, the FSA stops processing the current print data set, releases it back to JES, and requests that it is held by the system.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Verify and correct the value of the control parameter.

User response

Verify and correct the value of the control parameter.

APS8019I TWO DEFAULT MEMBER NAMES, DEFAULTS AND AFDPDEF, EXIST IN THE STARTUP PROCEDURE AFPPARMS DATA SET *dsname*. ONLY ONE DEFAULT MEMBER NAME IS ALLOWED.

Explanation

AFP Download Plus detected an error while it was processing the AFPPARMS DD statement in the startup procedure. The AFPPARMS data set can contain only one defaults member, DEFAULTS or AFDPDEF, not both.

System action

The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 00DC.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Specify either the DEFAULTS or AFDPDEF member name, and remove or rename the other member.

User response

No response is necessary.

APS8020I AFPPARMS IS NOT SUPPORTED WHEN USING DIRECT-PRINTING MODE.

Explanation: AFPPARMS parameter processing was requested in direct-printing mode, but it is not supported in that mode.

System action

PSF stops with a system completion code 024 and abend reason code 00DD.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Remove the AFPPARMS DD statement from the JCL, and resubmit the print request.

User response

Remove the AFPPARMS DD statement from the JCL, and resubmit the print request.

APS8200I A POSSIBLE LOGIC ERROR OCCURRED WHILE AFP DOWNLOAD PLUS ATTEMPTED TO CONNECT TO THE REMOTE SYSTEM.

Explanation

AFP Download Plus attempted to connect to the remote system. An internal logic error occurred.

System action

The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 03ED.

Operator response

Notify your system programmer.

System programmer response

This message indicates a possible logic error. Contact your remote service representative, contact your service representative in the IBM Support Center, or use your electronic link with IBM service for assistance.

User response

No response is necessary.

APS8201I **A POSSIBLE LOGIC ERROR OCCURRED WHILE AFP DOWNLOAD PLUS ATTEMPTED TO DISCONNECT FROM THE REMOTE SYSTEM.**

Explanation

AFP Download Plus attempted to disconnect from the remote system. An internal logic error occurred.

System action

The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 03EE.

Operator response

Notify your system programmer.

System programmer response

This message indicates a possible logic error. Contact your remote service representative, contact your service representative in the IBM Support Center, or use your electronic link with IBM service for assistance.

User response

No response is necessary.

APS8202I **A POSSIBLE LOGIC ERROR OCCURRED AS AN INTERNAL OPERATION FAILED.**

Explanation

AFP Download Plus had an internal logic error.

System action

The AFP Download Plus FSA stops with a system completion code 024 and one of these PSF abend reason codes: 03D6, 03E1, 03E2, 03E6, 03F7, 03FA, or 03FC.

Operator response

Notify your system programmer.

System programmer response

This message indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance.

User response

No response is necessary.

APS8203I **AFP DOWNLOAD PLUS TRIED MULTIPLE TIMES TO TRANSMIT THIS DATA SET BUT HAS REACHED THE MAXIMUM NUMBER OF ATTEMPTS.**

Explanation

AFP Download Plus attempted to send the data set to the remote system. AFP Download Plus encountered multiple problems during the transmission and tried to send the data set multiple times. The maximum number of attempts was reached.

System action

The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 03EC.

Operator response

Notify your system programmer.

System programmer response

This message indicates that a possible problem exists with the Internet Protocol network, a possible logic error exists with the remote system, or a possible logic error exists with AFP Download Plus. Other messages might be issued that have more details about the problem. Ensure that TCP/IP is functioning correctly.

If the problem persists, contact your remote service representative, contact your service representative in the IBM Support Center, or use your electronic link with IBM service for assistance.

User response

No response is necessary.

APS8204I **FILE *filename* COULD NOT BE OPENED. RETURN CODE *return code*. REASON CODE *reason code*. AFP DOWNLOAD PLUS CONTINUES TO SEND THE DATA SET TO THE REMOTE SYSTEM WITHOUT CHECKPOINTS.**

Explanation

AFP Download Plus issued a BPX1OPN request to open the identified file. The BPX1OPN open request returned with the return code and reason code in the message.

Common return codes that are associated with this message are:

- 111** Permission to access the file or directory was denied.
- 129** The file or directory you are trying to access does not exist.
- 133** The UNIX file system is out of storage.

System action

AFP Download Plus continues sending the data set to the remote system without checkpoints.

Operator response

Notify your system programmer.

System programmer response

Verify that AFP Download Plus has permission to access the file. Determine the appropriate response by interpreting the return code and the reason code. To interpret the return code and reason code, see *z/OS UNIX System Services Programming: Assembler Callable Services Reference*.

User response

No response is necessary.

APS8205I	FILE <i>filename</i> COULD NOT BE WRITTEN. RETURN CODE <i>return code</i>. REASON CODE <i>reason code</i>. AFP DOWNLOAD PLUS CONTINUES TO SEND THE DATA SET TO THE REMOTE SYSTEM WITHOUT CHECKPOINTS.
-----------------	--

Explanation

AFP Download Plus issued a BPX1WRT request to write the identified file. The BPX1WRT write request returned with the return code and reason code in the message.

Common return codes that are associated with this message are:

- 111** Permission to access the file or directory was denied.
- 129** The file or directory you are trying to access does not exist.
- 133** The UNIX file system is out of storage.

System action

AFP Download Plus continues sending the data set to the remote system without checkpoints.

Operator response

Notify your system programmer.

System programmer response

Verify that AFP Download Plus has permission to access the file. Determine the appropriate response by interpreting the return code and the reason code. To interpret the return code and reason code, see *z/OS UNIX System Services Programming: Assembler Callable Services Reference*.

User response

No response is necessary.

APS8206I	FILE <i>filename</i> COULD NOT BE READ. RETURN CODE <i>return code</i>. REASON CODE <i>reason code</i>. AFP DOWNLOAD PLUS CONTINUES TO SEND THE DATA SET TO THE REMOTE SYSTEM WITHOUT CHECKPOINTS.
-----------------	---

Explanation

AFP Download Plus issued a BPX1RED request to read the identified file. The BPX1RED read request returned with the return code and reason code in the message.

Common return codes that are associated with this message are:

- 111** Permission to access the file or directory was denied.
- 129** The file or directory you are trying to access does not exist.
- 133** The UNIX file system is out of storage.

System action

AFP Download Plus continues sending the data set to the remote system without checkpoints.

Operator response

Notify your system programmer.

System programmer response

Verify that AFP Download Plus has permission to access the file. Determine the appropriate response by

interpreting the return code and the reason code. To interpret the return code and reason code, see [z/OS UNIX System Services Programming: Assembler Callable Services Reference](#).

User response

No response is necessary.

APS8207I **AFP DOWNLOAD PLUS ATTEMPTED TO CHANGE THE FILE OFFSET IN FILE *filename*, BUT THIS FUNCTION FAILED. RETURN CODE *return code*. REASON CODE *reason code*.**

Explanation

AFP Download Plus issued a BPX1LSK request to change the file offset. The file offset is the position in a file from which data is next read. The BPX1LSK request returned with the return code and reason code in the message.

Common return codes that are associated with this message are:

111

Permission to access the file or directory was denied.

129

The file or directory you are trying to access does not exist.

133

The UNIX file system is out of storage.

System action

The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 03EA.

Operator response

Notify your system programmer.

System programmer response

Verify that AFP Download Plus has permission to access the file. Determine the appropriate response by interpreting the return code and the reason code. To interpret the return code and reason code, see [z/OS UNIX System Services Programming: Assembler Callable Services Reference](#).

User response

No response is necessary.

APS8208I **A POSSIBLE LOGIC ERROR OCCURRED WHILE AFP**

DOWNLOAD PLUS ATTEMPTED TO SEND DATA TO THE REMOTE SYSTEM.

Explanation

AFP Download Plus attempted to send data to the remote system. An internal logic error occurred.

System action

The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 03E5.

Operator response

Notify your system programmer.

System programmer response

This message indicates a possible logic error. Contact your remote service representative, contact your service representative in the IBM Support Center, or use your electronic link with IBM service for assistance.

User response

No response is necessary.

APS8209I **FILE *filename* COULD NOT BE READ. RETURN CODE *return code*. REASON CODE *reason code*.**

Explanation

AFP Download Plus issued a BPX1RED request to read the identified file. The BPX1RED read request returned with the return code and reason code in the message.

Common return codes that are associated with this message are:

111

Permission to access the file or directory was denied.

129

The file or directory you are trying to access does not exist.

133

The UNIX file system is out of storage.

System action

The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 03EF.

Operator response

Notify your system programmer.

System programmer response

Verify that AFP Download Plus has permission to access the file. Determine the appropriate response by interpreting the return code and the reason code. To interpret the return code and reason code, see [z/OS UNIX System Services Programming: Assembler Callable Services Reference](#).

User response

No response is necessary.

APS8210I **FILE *filename* COULD NOT BE READ. RETURN CODE *return code*. REASON CODE *reason code*.**

Explanation

AFP Download Plus issued a BPX1RED request to read the identified file. The BPX1RED read request returned with the return code and reason code in the message.

Common return codes that are associated with this message are:

111

Permission to access the file or directory was denied.

129

The file or directory you are trying to access does not exist.

133

The UNIX file system is out of storage.

System action

The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 03E8.

Operator response

Notify your system programmer.

System programmer response

Verify that AFP Download Plus has permission to access the file. Determine the appropriate response by interpreting the return code and the reason code. To interpret the return code and reason code, see [z/OS UNIX System Services Programming: Assembler Callable Services Reference](#).

User response

No response is necessary.

APS8211I **FILE *filename* COULD NOT BE OPENED. RETURN CODE *return code*. REASON CODE *reason code*.**

Explanation

AFP Download Plus issued a BPX1OPN request to open the identified file. The BPX1OPN open request returned with the return code and reason code in the message.

Common return codes that are associated with this message are:

111

Permission to access the file or directory was denied.

129

The file or directory you are trying to access does not exist.

133

The UNIX file system is out of storage.

System action

The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 03E7.

Operator response

Notify your system programmer.

System programmer response

Verify that AFP Download Plus has permission to access the file. Determine the appropriate response by interpreting the return code and the reason code. To interpret the return code and reason code, see [z/OS UNIX System Services Programming: Assembler Callable Services Reference](#).

User response

No response is necessary.

APS8212I **THE HEADER EXCEEDED THE SIZE OF THE SEND BUFFER.**

Explanation

AFP Download Plus added the header to the send buffer. The length of the header exceeded the length of the send buffer.

System action

The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 03E0.

Operator response

Notify your system programmer.

System programmer response

This message indicates a possible logic error. Alternatively, the header might have grown in size until it exceeded the length of the send buffer.

Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance.

User response

No response is necessary.

APS8215I	A POSSIBLE LOGIC ERROR OCCURRED WHILE AFP DOWNLOAD PLUS ATTEMPTED TO RECEIVE DATA FROM THE REMOTE SYSTEM.
-----------------	--

Explanation

AFP Download Plus attempted to receive data from the remote system. An internal logic error occurred.

System action

The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 03E3.

Operator response

Notify your system programmer.

System programmer response

This message indicates a possible logic error. Contact your remote service representative, contact your service representative in the IBM Support Center, or use your electronic link with IBM service for assistance.

User response

No response is necessary.

APS8216I	A RESPONSE <i>response</i> THAT IS NOT SUPPORTED FOR THE <i>request</i> REQUEST WAS RECEIVED FROM THE REMOTE SYSTEM.
-----------------	---

Explanation

AFP Download Plus expected a response from the remote system to the request. However, the response that was received is not supported.

System action

The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 03E4 or 03F9.

Operator response

Notify your system programmer.

System programmer response

This message indicates a possible logic error with the remote system. Contact your remote system service representative for assistance.

User response

No response is necessary.

APS8217I	THE REMOTE SYSTEM DID NOT SUCCESSFULLY PROCESS THE RECEIVED DATA SET OR THE NUMBER OF BYTES SENT BY AFP DOWNLOAD PLUS DOES NOT MATCH THE NUMBER OF BYTES RECEIVED BY THE REMOTE SYSTEM.
-----------------	--

Explanation

The remote system indicated that an error occurred with the received data set. Either the script or exit that is called by the download receiver encountered an error, or the number of bytes sent by AFP Download Plus is not the same as the number of bytes received by the remote system.

System action

Depending on the error at the remote system, one of these actions occurs:

- AFP Download Plus attempts to resend the data set from the previous checkpoint. If no previous checkpoint exists, it resends the data set from the beginning.
- AFP Download Plus attempts to resend the data set from the beginning.
- AFP Download Plus stops processing the data set, releases it back to JES, and requests that the data set is held by the system.
- The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 03D2 or 03D3.

Operator response

Notify your system programmer.

System programmer response

Check the accompanying messages (if they exist) for information about the cause of the error, or check the error logs on the remote system for messages that provide additional information about the cause of the error. This message might indicate a possible logic error in AFP Download Plus or the remote system. If the problem persists, contact your remote system service representative, contact your service representative in the IBM Support Center, or use your electronic link with IBM service for assistance.

User response

No response is necessary.

APS8218I THE DATA SET WAS RESENT FROM THE LAST CHECKPOINT, BUT THE FILENAME WAS NOT FOUND BY THE REMOTE SYSTEM. THE DATA SET WILL BE RESENT FROM THE BEGINNING.

Explanation

Because of a problem, the data set was resent from the previous checkpoint; but the remote system cannot find the file name of the data set.

System action

AFP Download Plus attempts to resend the data set from the beginning.

Operator response

Notify your system programmer.

System programmer response

This message might indicate a possible logic error in AFP Download Plus or the remote system. If the problem persists, contact your remote system service representative, contact your service representative in the IBM Support Center, or use your electronic link with IBM service for assistance.

User response

No response is necessary.

APS8219I THE DATA SET WAS RESENT FROM THE LAST CHECKPOINT, BUT THE BYTE COUNT WAS NOT CORRECT. THE DATA SET WILL BE RESENT FROM THE BEGINNING.

Explanation

Because of a problem, the data set was resent from the previous checkpoint; but the remote system might not find the byte count of the data set.

System action

AFP Download Plus attempts to resend the data set from the beginning.

Operator response

Notify your system programmer.

System programmer response

This message might indicate a possible logic error in AFP Download Plus or the remote system. If the problem persists, contact your remote system service representative, contact your service representative in the IBM Support Center, or use your electronic link with IBM service for assistance.

User response

No response is necessary.

APS8220I COMPRESSION WAS REQUESTED FOR THIS FSA, BUT THE REMOTE SYSTEM CONNECTED TO AFP DOWNLOAD PLUS DOES NOT SUPPORT COMPRESSION. COMPRESSION IS DEACTIVATED.

Explanation

Compression support was requested by setting the compression parameter to LZW in the AFPPARMS DD statement data set for this FSA. However, the remote system that is attached to AFP Download Plus does not support the compression requests necessary for compression.

System action

AFP Download Plus does not use compression for this FSA.

Operator response

Notify your system programmer.

System programmer response

If compression is not needed for this FSA, set the compression parameter to NONE or ignore this message. If compression is needed for this FSA, find a remote system that supports compression.

User response

No response is necessary.

APS8221I **MULTIPLE DATA SET SUPPORT WAS REQUESTED FOR THIS FSA, BUT THE REMOTE SYSTEM CONNECTED TO AFP DOWNLOAD PLUS DOES NOT SUPPORT THE MULTIPLE DATA SET REQUESTS. MULTIPLE DATA SET SUPPORT IS NOT USED.**

Explanation

Multiple data set support was requested by setting the `dataset-grouping` parameter to YES in the AFPPARMS DD statement data set for this FSA. However, the remote system that is attached to AFP Download Plus does not support the multiple data set requests necessary for multiple data set mode.

System action

AFP Download Plus does not use multiple data set mode for this FSA.

Operator response

Notify your system programmer.

System programmer response

If multiple data set support is not required for this FSA, set the `dataset-grouping` parameter to NO. If multiple data set support is required for this FSA, find a remote system that supports multiple data set requests.

User response

No response is necessary.

APS8222I **AFP DOWNLOAD PLUS ATTEMPTED TO CANCEL A DATA SET AT THE REMOTE SYSTEM, BUT THE REMOTE SYSTEM DOES NOT SUPPORT THE CANCEL DATA SET REQUEST. AFP DOWNLOAD PLUS CONTINUES WITHOUT CANCELLING THE DATA SET.**

Explanation

AFP Download Plus attempted to cancel a data set on the remote system, but the remote system does not support the cancel data set request.

System action

AFP Download Plus continues processing.

Operator response

Notify your system programmer.

System programmer response

If AFP Download Plus needs to cancel a data set at the remote system, use a remote system that supports the cancel data set request. Orphaned files might be left on the remote system and must be manually cleaned up. Contact the person responsible for the remote system to clean up these files.

User response

No response is necessary.

APS8223I **AFP DOWNLOAD PLUS ESTABLISHED A CONNECTION WITH THE REMOTE SYSTEM. FSA = *fsa*. IPADDR = *ip-address*. PORT NUMBER = *port number*. REMOTE SYSTEM = *product name*. REMOTE SYSTEM OPERATING SYSTEM = *operating system*. REMOTE SYSTEM VERSION = *version*. REMOTE SYSTEM COMPILE DATE = *compile date*.**

Explanation

AFP Download Plus established a connection with the remote system where:

- FSA is the functional subsystem address; for example, PRT660.
- IPADDR specifies the Internet Protocol (IP) address of the TCP/IP-attached remote system.
- PORT NUMBER specifies the port number of the TCP/IP-attached remote system.
- REMOTE SYSTEM is the product name of the remote system. The default is UNKNOWN.
- REMOTE SYSTEM OPERATING SYSTEM is the operating system of the remote system; for example, Microsoft Windows 8 (Version 6.2.9200). The default is UNKNOWN.
- REMOTE SYSTEM VERSION is the version of the remote system; for example, 3.0. The default is UNKNOWN.
- REMOTE SYSTEM COMPILE DATE is the compile date of the remote system; for example, May 11 2013. The default is UNKNOWN.

System action

AFP Download Plus continues processing.

Operator response

Ensure that the correct remote system was started.

System programmer response

No response is necessary.

User response

No response is necessary.

APS8225I AN UNKNOWN COMMAND CODE WAS RECEIVED IN THE RESPONSE FROM THE REMOTE SYSTEM TO THE QUERY SUPPORTED COMMAND REQUEST SENT BY AFP DOWNLOAD PLUS. COMMAND CODE = *command code*.

Explanation

AFP Download Plus received an unknown command code in the response from the remote system to the Query Supported Command request.

System action

The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 03E2.

Operator response

Notify your system programmer.

System programmer response

This message might indicate a possible logic error with the remote system. If the problem persists, contact your remote system service representative for assistance.

User response

No response is necessary.

APS8226I A NEGATIVE RESPONSE WAS RECEIVED FROM THE REMOTE SYSTEM TO THE QUERY SUPPORTED COMMAND REQUEST SENT BY AFP DOWNLOAD PLUS.

Explanation

AFP Download Plus expected to receive a positive response, but received a negative response from the remote system in reply to the Query Supported Command request.

System action

The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 03F1.

Operator response

Notify your system programmer.

System programmer response

This message might indicate a possible logic error with the remote system. If the problem persists, contact your remote system service representative for assistance.

User response

No response is necessary.

APS8227I THE REMOTE SYSTEM DOES NOT SUPPORT CHECKPOINTS. AFP DOWNLOAD PLUS CONTINUES TO SEND DATA SETS TO THE REMOTE SYSTEM WITHOUT CHECKPOINTS.

Explanation

AFP Download Plus was using checkpoints. However, because the remote system does not support checkpoints, AFP Download Plus is sending data sets without checkpoints.

System action

AFP Download Plus continues and sends all jobs to the remote system without checkpoints.

Operator response

Notify your system programmer.

System programmer response

To use checkpoints, send data sets to a remote system that supports checkpoints.

User response

No response is necessary.

APS8228I THE FOUR BYTE END OF FILE REQUEST IS NOT SUPPORTED BY THE REMOTE SYSTEM.

Explanation

The remote system does not support the 4-byte end-of-file request as required by the download protocol.

System action

The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 03F2.

Operator response

Notify your system programmer.

System programmer response

This message might indicate a possible logic error with the remote system. If the problem persists, contact your remote system service representative for assistance.

User response

No response is necessary.

APS8229I THE QUERY SUPPORTED COMMAND REQUEST IS NOT SUPPORTED BY THE REMOTE SYSTEM.

Explanation

The remote system does not support the Query Supported Command request as required by the download protocol.

System action

The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 03F3.

Operator response

Notify your system programmer.

System programmer response

This message might indicate a possible logic error with the remote system. If the problem persists, contact your remote system service representative for assistance.

User response

No response is necessary.

APS8230I ONE OF THE MULTIPLE DATA SET REQUESTS IS SUPPORTED BY THE REMOTE SYSTEM AND THE OTHER MULTIPLE DATA SET REQUEST IS NOT SUPPORTED BY THE REMOTE SYSTEM.

Explanation

The remote system supports only one of the two multiple data set requests. The download protocol requires that either both requests be supported or both requests not be supported.

System action

The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 03F4.

Operator response

Notify your system programmer.

System programmer response

This message might indicate a possible logic error with the remote system. If the problem persists, contact your remote system service representative for assistance.

User response

No response is necessary.

APS8231I ONE OF THE COMPRESSION REQUESTS IS SUPPORTED BY THE REMOTE SYSTEM AND THE OTHER COMPRESSION REQUEST IS NOT SUPPORTED BY THE REMOTE SYSTEM.

Explanation

Two compression requests exist, the Start LZW Compression request and the End Compression request. The protocol requires that either both requests must be supported or both requests must not be supported.

System action

AFP Download Plus FSA stops with a system completion code 024 and abend reason code 03F5.

Operator response

Notify your system programmer.

System programmer response

This message might indicate a possible logic error with the remote system. If the problem persists, contact your remote system service representative for assistance.

User response

No response is necessary.

**APS8232I A PROCESSING
ACKNOWLEDGEMENT WAS
RECEIVED FROM THE REMOTE
SYSTEM, BUT THE REMOTE
SYSTEM DOES NOT SUPPORT
PROCESSING
ACKNOWLEDGEMENTS.**

Explanation

The remote system sent a processing acknowledgment to AFP Download Plus; however, the remote system does not support processing acknowledgements.

System action

The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 03F6.

Operator response

Notify your system programmer.

System programmer response

This message might indicate a possible logic error with the remote system. If the problem persists, contact your remote system service representative for assistance.

User response

No response is necessary.

**APS8233I A NEGATIVE RESPONSE WAS
RECEIVED FROM THE REMOTE
SYSTEM IN REPLY TO ONE OF THE
MULTIPLE DATA SET REQUESTS
SENT BY AFP DOWNLOAD PLUS.**

Explanation

AFP Download Plus expected to receive a positive response, but received a negative response from the remote system in reply to one of the multiple data set requests sent by AFP Download Plus.

System action

The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 03D0 or 03F8.

Operator response

Notify your system programmer.

System programmer response

This message might indicate a possible logic error in AFP Download Plus or the remote system. If the problem persists, contact your remote system service representative, contact your service representative in the IBM Support Center, or use your electronic link with IBM service for assistance.

User response

No response is necessary.

**APS8234I A DECOMPRESSION ERROR
OCCURRED WHILE THE REMOTE
SYSTEM WAS ATTEMPTING TO
DECOMPRESS A DATA SET SENT
BY AFP DOWNLOAD PLUS.**

Explanation

AFP Download Plus sent an End Compression request and received a negative response because an error occurred while the remote system was trying to extract the data.

System action

Depending on the error at the remote system, one of these actions occurs:

- AFP Download Plus attempts to resend the data set from the previous checkpoint. If no previous checkpoint exists, it resends the data set from the beginning.
- AFP Download Plus attempts to resend the data set from the beginning.
- AFP Download Plus stops processing the data set, releases it back to JES, and requests that the data set is held by the system.
- The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 03D1.

Operator response

Notify your system programmer.

System programmer response

This message might indicate a possible logic error in AFP Download Plus or the remote system. If the problem persists, contact your remote system service representative, contact your service representative in the IBM Support Center, or use your electronic link with IBM service for assistance.

User response

No response is necessary.

APS8235I THE REMOTE SYSTEM DOES NOT SUPPORT THE EIGHT BYTE CHECKPOINT REQUEST, BUT CHECKPOINTING IS ACTIVE AND THE DATA SET REQUIRES EIGHT BYTE CHECKPOINTING.

Explanation

AFP Download Plus needed to send the 8-byte checkpoint request to the remote system because of the size of the data set. However, the remote system does not support the 8-byte checkpoint request.

System action

The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 03FD.

Operator response

Notify your system programmer.

System programmer response

If data sets that are larger than 4 GB are required, use a remote system that supports 8-byte checkpoint requests.

User response

Do not send data sets that are larger than 4 gigabytes (GB). Data sets that are larger than 4 GB require the use of the 8-byte checkpoint request.

APS8236I THE REMOTE SYSTEM DOES NOT SUPPORT THE EIGHT BYTE END OF FILE REQUEST, BUT THE DATA SET REQUIRES THE EIGHT BYTE END OF FILE REQUEST.

Explanation

AFP Download Plus needed to send the 8-byte end-of-file request to the remote system because of the size of the data set. However, the remote system does not support the 8-byte end-of-file request.

System action

The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 03FE.

Operator response

Notify your system programmer.

System programmer response

If data sets that are larger than 4 GB are required, use a remote system that supports 8-byte end-of-file requests.

User response

Do not send data sets that are larger than 4 gigabytes (GB). Data sets that are larger than 4 GB require the use of the 8-byte end-of-file request.

APS8237I THE REMOTE SYSTEM IS BUSY PROCESSING THE DATA IT RECEIVED FROM AFP DOWNLOAD PLUS.

Explanation

The remote system is busy processing the data it received from AFP Download Plus. The remote system replies to the data when it is finished processing.

System action

AFP Download Plus stops processing. When the remote system replies to the data, this message is deleted and AFP Download Plus continues processing.

Operator response

Notify your system programmer if this error becomes a problem.

System programmer response

When this message displays on the console, it indicates that the remote system is busy processing the data from AFP Download Plus. If this error becomes a problem, contact the person responsible for the remote system to determine whether it is the typical operating procedure.

User response

No response is necessary.

APS8238I AFP DOWNLOAD PLUS ATTEMPTED TO CANCEL A JOB AT THE REMOTE SYSTEM, BUT THE REMOTE SYSTEM DOES NOT SUPPORT THE CANCEL DATA SET AND JOB REQUEST.

Explanation

AFP Download Plus encountered a situation where it needs to cancel the data set and job on the remote system; however, the remote system does not support the cancel data set and job request.

System action

AFP Download Plus continues processing.

Operator response

Notify your system programmer.

System programmer response

If AFP Download Plus needs to cancel a job on the remote system, use a remote system that supports the cancel data set and job request. Orphaned files might be left on the remote system and must be manually cleaned up. Contact the person responsible for the remote system to clean up these files.

User response

No response is necessary.

APS8239I AFP DOWNLOAD PLUS WAS NOT SUCCESSFUL IN PROCESSING THE DATA SET. THE SPECIFIC MESSAGES FOR THE FAILURE ARE IN THE MESSAGE FILE ON THE AFP DOWNLOAD PLUS SYSTEM.

Explanation

While transforming a data set in multiple data set mode (the dataset-grouping parameter set to YES in the AFPPARMS DD statement data set for this FSA), AFP Download Plus encountered an error that stopped processing of a data set in a multiple data set job.

System action

The system action is determined by the transform errors that occur.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Correct the transform errors and then resubmit the job.

APS8240I COMPRESSION WAS REQUESTED FOR THIS DATA SET, BUT THE REMOTE SYSTEM CONNECTED TO AFP DOWNLOAD PLUS DOES NOT SUPPORT COMPRESSION. COMPRESSION IS DEACTIVATED.

Explanation

Compression was requested on the AFPPARMS data set specified on the OUTPUT statement, but compression is not supported by the remote system that is connected to AFP Download Plus.

System action

AFP Download Plus deactivates compression, processes the data set without compressing the data, and sends the data set to the remote system.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

If you want to compress the data set, connect AFP Download Plus to a remote system that supports compression. If you do not want to compress the data set, ignore this message or remove the compression parameter from the AFPPARMS data set.

APS8241I THE ERROR CODE RECEIVED IN THE RESPONSE FROM THE REMOTE SYSTEM = *error code* - *error code description*.

Explanation

AFP Download Plus received a negative response from the remote system with an error code that describes the error that occurred at the remote system. These error codes and error code descriptions are supported:

- 0** Success
- 1** No information provided
- 2** Checkpoint file not found
- 3** Checkpoint restart point not found
- 4** Delta byte count mismatch
- 5** Script/exit failure
- 6** Decompression failure
- 7** Unrecognized MDS ID

- 8 No MDS IDs available
- 9 System error
- 10 Start compression or EOF request received while compression is active
- 11 Download protocol violation
- 12 Start MFT or End MFT request received when not allowed
- 13 Invalid Multi File Transfer file sequence or file name
- 14 Invalid Set File file number
- xx Unrecognized error code

System action

AFP Download Plus continues processing.

Operator response

Notify your system programmer.

System programmer response

The accompanying error messages describe the problem in more detail and indicate whether you need to take any action.

User response

No response is necessary.

APS8242I THE FOLLOWING MESSAGE WAS ISSUED BY THE REMOTE SYSTEM. IPADDR = *ip-address*. PORT NUMBER = *port number*.

Explanation

This message indicates that a problem occurred at the remote system. Message APS8243I is issued after this message and contains the error message from the remote system. *ip-address* specifies the IP address of the TCP/IP-attached remote system. *port number* specifies the port number of the TCP/IP-attached remote system.

System action

AFP Download Plus continues processing.

Operator response

Notify your system programmer.

System programmer response

The accompanying error messages describe the problem in more detail and indicate whether you need to take any action.

User response

No response is necessary.

APS8243I *message text*

Explanation

This message describes the problem that occurred at the remote system.

System action

AFP Download Plus continues processing.

Operator response

Notify your system programmer.

System programmer response

Do the action that is indicated in the message.

User response

No response is necessary.

APS8244I A NEGATIVE RESPONSE WAS RECEIVED FROM THE REMOTE SYSTEM TO THE CHECKPOINT RESTART HEADER SENT BY AFP DOWNLOAD PLUS.

Explanation

AFP Download Plus expected to receive a positive response from the remote system in reply to the checkpoint restart header request, but instead received a negative response.

System action

The AFP Download Plus FSA stops with a system completion code of 024 and abend reason code 03D4.

Operator response

Notify your system programmer.

System programmer response

This message indicates a possible logic error with the remote system. Contact your remote system service representative for assistance.

User response

No response is necessary.

APS8245I A NEGATIVE RESPONSE WAS RECEIVED FROM THE REMOTE SYSTEM TO THE CHECKPOINT RESTART BYTE COUNT SENT BY AFP DOWNLOAD PLUS.

Explanation

AFP Download Plus expected to receive a positive response from the remote system in reply to the checkpoint restart byte count, but instead received a negative response.

System action

The AFP Download Plus FSA stops with a system completion code of 024 and abend reason code 03D5.

Operator response

Notify your system programmer.

System programmer response

This message indicates a possible logic error with the remote system. Contact your remote system service representative for assistance.

User response

No response is necessary.

APS8246I THE REMOTE SYSTEM DOES NOT WANT THE CURRENT DATA SET TO BE TRIED AGAIN, BUT WILL STAY ACTIVE WAITING FOR ANOTHER DATA SET TO BE SENT.

Explanation

The remote system sent a negative response that indicates that it does not want this data set to be tried again, but it stays active so another data set can be sent.

System action

AFP Download Plus stops processing the data set, releases it back to JES, and requests that the data set is held by the system.

Operator response

Notify your system programmer.

System programmer response

This message indicates a possible logic error with the remote system or with AFP Download Plus. Other messages might be issued that have more details about the problem.

If the problem persists, contact your remote system service representative, contact your service representative in the IBM Support Center, or use your electronic link with IBM service for assistance.

User response

No response is necessary.

APS8247I A RECOVERY INDICATOR THAT WAS NOT SUPPORTED WAS RECEIVED FROM THE REMOTE SYSTEM IN THE EXTENDED RECEIVER INFORMATION RESPONSE.

Explanation

AFP Download Plus received a negative response from the remote system with a recovery indicator that is not supported.

System action

The AFP Download Plus FSA stops with a system completion code of 024 and abend reason code 03D7.

Operator response

Notify your system programmer.

System programmer response

This message indicates a possible logic error with the remote system. Contact your remote system service representative for assistance.

User response

No response is necessary.

APS8248I AN UNKNOWN RESPONSE *response* WAS RECEIVED FROM THE REMOTE SYSTEM.

Explanation

AFP Download Plus received an unknown response from the remote system. AFP Download Plus expected

a response, but it did not recognize the response that was received.

System action

The AFP Download Plus FSA stops with a system completion code of 024 and abend reason code 03D8.

Operator response

Notify your system programmer.

System programmer response

This message indicates a possible logic error with the remote system. Contact your remote system service representative for assistance.

User response

No response is necessary.

APS8249I **A RESPONSE *response* WAS RECEIVED FROM THE REMOTE SYSTEM THAT DID NOT SUPPORT ENCODING OF THE DATA WHEN ENCODING OF THE DATA WAS ACTIVE.**

Explanation

Data encoding was active; however, AFP Download Plus received a response from the remote system that did not support encoding of the data.

System action

The AFP Download Plus FSA stops with a system completion code of 024 and abend reason code 03D9.

Operator response

Notify your system programmer.

System programmer response

This message indicates a possible logic error with the remote system. Contact your remote system service representative for assistance.

User response

No response is necessary.

APS8250I **THE SENDING OF SEPARATOR PAGES WAS REQUESTED FOR THIS FSA BUT THE REMOTE SYSTEM CONNECTED TO AFP DOWNLOAD PLUS DOES NOT SUPPORT MULTIPLE DATA SET REQUESTS. MULTIPLE DATA SET**

SUPPORT IS REQUIRED FOR THE SENDING OF SEPARATOR PAGES.

Explanation

The FSA is set to send separator pages with the Send separator pages parameter in the Printer Inventory or the AFPPARMS control statement. However, the FSA cannot send the separator pages because multiple data set support is required, but the remote system that is attached to AFP Download Plus does not have this support.

System action

The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 3DA.

Operator response

Notify your system programmer.

System programmer response

If this FSA does not need to send separator pages, set the Send separator pages parameter to NO. Otherwise, send the job to a remote system that supports multiple data set requests.

User response

No response is necessary.

APS8251I **THE SENDING OF SEPARATOR PAGES WAS REQUESTED FOR THIS FSA BUT THE MULTIPLE DATA SET FUNCTION WAS NOT REQUESTED. MULTIPLE DATA SET SUPPORT IS REQUIRED FOR THE SENDING OF SEPARATOR PAGES.**

Explanation

The FSA is set to send separator pages with the Send separator pages parameter in the Printer Inventory or the AFPPARMS control statement. However, the data set grouping parameter for multiple data set support is not set for the FSA in the Printer Inventory or the AFPPARMS control statement, which is required to send separator pages.

System action

The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 3DB.

Operator response

Notify your system programmer.

System programmer response

If this FSA does not need to send separator pages, set the send separator pages parameter to NO. Otherwise, set the data set grouping parameter to YES.

User response

No response is necessary.

APS8252I **A NEGATIVE RESPONSE WAS RECEIVED FROM THE REMOTE SYSTEM IN REPLY TO THE END MULTI FILE TRANSFER REQUEST SENT BY AFP DOWNLOAD PLUS.**

Explanation

AFP Download Plus sent an End Multi File Transfer request and received a negative response from the remote system.

System action

Depending on the error at the remote system, one of these actions occurs:

- Because all of the data was successfully received by the remote system, AFP Download Plus sends another Start Multi File Transfer request and End Multi File Transfer request.
- AFP Download Plus stops processing the data set, releases it back to JES, and requests that the data is held by the system.
- The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 03DE.

Operator response

Notify your system programmer.

System programmer response

This message might indicate a possible logic error in AFP Download Plus or the remote system. If the problem persists, contact your remote system service representative, contact your service representative in the IBM Support Center, or use your electronic link with IBM service for assistance.

User response

No response is necessary.

APS8253I **AFP DOWNLOAD PLUS TRIED MULTIPLE TIMES TO COMMUNICATE WITH THE REMOTE SYSTEM BUT HAS REACHED THE MAXIMUM NUMBER OF ATTEMPTS.**

Explanation

AFP Download Plus attempted to send the data set to the remote system but encountered multiple problems during the transmission. AFP Download Plus tried to send the data set multiple times; however, the maximum number of attempts was reached.

System action

The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 3EC.

Operator response

Notify your system programmer.

System programmer response

This message indicates that a possible problem exists with the Internet Protocol network, a possible logic error exists with the remote system, or a possible logic error exists with AFP Download Plus. Other messages might be issued that have more details about the problem. Ensure that TCP/IP is functioning correctly.

If the problem persists, contact your remote service representative, contact your service representative in the IBM Support Center, or use your electronic link with IBM service for assistance.

User response

No response is necessary.

APS8254I **A NEGATIVE RESPONSE WAS RECEIVED FROM THE REMOTE SYSTEM IN REPLY TO THE START MULTI FILE TRANSFER REQUEST SENT BY AFP DOWNLOAD PLUS.**

Explanation

AFP Download Plus sent a Start Multi File Transfer request and received a negative response from the remote system.

System action

Depending on the error at the remote system, one of these actions occurs:

- AFP Download Plus sends another Start Multi File Transfer request and attempts to send the data from the beginning again.
- The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 03DD.

Operator response

Notify your system programmer.

System programmer response

This message might indicate a possible logic error in AFP Download Plus or the remote system. If the problem persists, contact your remote system service representative, contact your service representative in the IBM Support Center, or use your electronic link with IBM service for assistance.

User response

No response is necessary.

APS8255I **ONE OF THE MULTI FILE TRANSFER REQUESTS IS SUPPORTED BY THE REMOTE SYSTEM AND THE OTHER MULTI FILE TRANSFER REQUEST IS NOT SUPPORTED BY THE REMOTE SYSTEM.**

Explanation

The remote system supports only one of the two multi-file transfer requests. The download protocol requires that either both requests be supported or both requests not be supported.

System action

The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 040A.

Operator response

Notify your system programmer.

System programmer response

This message might indicate a possible logic error with the remote system. If the problem persists, contact your remote system service representative for assistance.

User response

No response is necessary.

APS8256I **DIRECT DOWNLOAD WAS REQUESTED FOR THIS FSA, BUT THE REMOTE SYSTEM CONNECTED TO AFP DOWNLOAD PLUS DOES NOT SUPPORT THE MULTI FILE TRANSFER REQUESTS. DIRECT DOWNLOAD IS NOT USED.**

Explanation

The direct download function for sending MO:DCA data directly to the receiver was requested by setting the `direct-download` parameter in the AFPPARMS DD

statement data set for this FSA. However, the remote system that is attached to AFP Download Plus does not support the multi-file transfer requests necessary for the direct download function.

System action

AFP Download Plus does not use the direct download function for this FSA.

Operator response

Notify your system programmer.

System programmer response

If direct download is not required for this FSA, set the `direct-download` parameter to NONE. If direct download is required for this FSA, find a remote system that supports the multi-file transfer requests.

User response

No response is necessary.

APS8257I **AFP DOWNLOAD PLUS ATTEMPTED TO CANCEL A FILE AT THE REMOTE SYSTEM, BUT THE REMOTE SYSTEM DOES NOT SUPPORT THE CANCEL FILE REQUEST.**

Explanation

AFP Download Plus encountered a situation where it needs to cancel the file on the remote system; however, the remote system does not support the cancel file request.

System action

The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 040C.

Operator response

Notify your system programmer.

System programmer response

Find a remote system that supports the cancel file request.

User response

No response is necessary.

APS8258I **AFP DOWNLOAD PLUS ATTEMPTED TO CANCEL A JOB AT THE REMOTE SYSTEM, BUT THE REMOTE SYSTEM DOES NOT**

SUPPORT THE CANCEL FILE AND JOB REQUEST.

Explanation

AFP Download Plus encountered a situation where it needs to cancel the job on the remote system; however, the remote system does not support the cancel file and job request.

System action

The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 040B.

Operator response

Notify your system programmer.

System programmer response

Find a remote system that supports the cancel file and job request.

User response

No response is necessary.

APS8259I AFP DOWNLOAD PLUS IS UNABLE TO SEND JOBS TO THE RECEIVING SYSTEM THAT HAVE BOTH MULTIPLE DATA SETS AND LINE DATA MESSAGES.

Explanation

The Data set grouping parameter in the Printer Inventory or the dataset-grouping parameter in the AFPPARMS control statement is set for multiple data set support and the Send messages on failure parameter in the Printer Inventory or the send-messages-on-failure parameter in the AFPPARMS control statement is set to `generic only`. However, this combination is not allowed because the receiving system cannot receive jobs with both MO:DCA-P data sets and line data messages.

System action

The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 03E9.

Operator response

Notify your system programmer.

System programmer response

If this FSA does not need to send multiple data set jobs, set the Data set grouping or the dataset-grouping

parameter to NO. Otherwise, set the Send messages on failure or the send-messages-on-failure parameter to ALL.

User response

No response is necessary.

APS8260I AFP DOWNLOAD PLUS IS UNABLE TO SEND JOBS TO THE RECEIVING SYSTEM WITH BOTH MULTIPLE DATA SETS AND FORM DEFINITION RESOURCES THAT ARE NOT INCLUDED INLINE.

Explanation

The Data set grouping parameter in the Printer Inventory or the dataset-grouping parameter in the AFPPARMS control statement is set for multiple data set support and the Resources Included Inline: Form definitions parameter in the Printer Inventory or the formdefs parameter in the AFPPARMS control statement is set to `not-inline`. However, this combination is not allowed because the receiving system cannot receive jobs with multiple data sets and form definitions that are not inline.

System action

The AFP Download Plus FSA stops with a system completion code 024 and abend reason code 03DC.

Operator response

Notify your system programmer.

System programmer response

If this FSA does not need to send multiple data set jobs, set the Data set grouping or the dataset-grouping parameter to NO. Otherwise, set the Resources Included Inline: Form definitions or the formdefs parameter to `INLINE`.

User response

No response is necessary.

APS8300I AN INCORRECT PORTNUM (*port_number*) IS SPECIFIED AT LINE NUMBER (*nnn*) IN THE DOWNLOAD ROUTING-CONTROL DATA SET. THE PORTNUM KEYWORD IS IGNORED.

Explanation

Download for z/OS detected an incorrect port number in the Download for z/OS routing-control data set. The values in the message are:

port_number

The specified port number. The valid range of port numbers is: 5002 - 64000, except 8251 and 8253, which are not allowed.

nnn

The line number of the 80-character record in the routing-control data set.

See *PSF for z/OS: Download for z/OS* for information about the Download for z/OS routing-control data set.

System action

Download for z/OS ignores the PORTNUM keyword and continues processing the other keywords in the routing-control data set.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Correct the value for the PORTNUM keyword in the routing-control data set. To use the corrected routing-control data set, stop the Download for z/OS FSS and restart the FSAs.

User response

No response is necessary.

APS8500I	NO GRID OR RRID INFORMATION IS AVAILABLE FOR MEMBER <i>member name</i>. RESOURCE IS NOT ENABLED FOR CAPTURE.
-----------------	---

Explanation

No value was specified for RRID on the APSRMARK control statement, and no corresponding GRID components were present inside the font.

System action

This resource is marked public by PSF, but is not enabled for resource capture by the printer.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Correct the control statement syntax by specifying a valid RRID value and resubmit the request. See *Font Object Content Architecture Reference* for more information about the GRID components of a font.

APS8501I	MEMBER <i>member name</i> HAS AN EXISTING X'63' TYPE 2 TRIPLET. THE RRID INFORMATION WAS NOT REPLACED IN THIS TRIPLET.
-----------------	---

Explanation

A X'63' type 2 font resource management triplet was found in the Begin structured field for the specified member. If this resource was already marked with a valid RRID, it is enabled for resident resource activation and resource capture. Because no RRID value was specified on the APSRMARK control statement, the existing X'63' type 2 triplet was updated with new date and time values, but the engineering change information was kept the same. The first time this resource is used, it is downloaded so that the printer can capture it.

System action

This resource is marked by PSF and is enabled for resident resource activation and for printer capture if a valid RRID was already present in the X'63' type 2 triplet.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

If the resource is not captured by the printer, correct the control statement syntax by specifying a valid RRID value and resubmit the request. See *Font Object Content Architecture Reference* for more information about the X'63' type 2 font resource management triplet.

APS8550I	FILE <i>filename</i> COULD NOT BE CREATED. RETURN CODE (<i>return code</i>).
-----------------	---

Explanation

AFP Download Plus failed to create the specified file.

System action

For the system action taken, see the other messages that are associated with this error.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Correct the problem in response to the system return code identified in this message. Possible return codes are:

- 10** The file name address is not valid.
- 15** Part of the full name is not a directory.
- 20** The path name address is not valid.
- 30** The file name is too short.
- 40** The file name or path name is too long.
- 50** The path name is too short.

User response

Inform your system programmer that this error occurred.

APS8551I FILE *filename* COULD NOT BE OPENED. RETURN CODE (*return code*). REASON CODE (*reason code*). PATHNAME=*pathname*.

Explanation

The BPX1OPN system function macro failed to open the specified file. After returning from the BPX1OPN macro, register 15 contained a nonzero return code.

Common return codes that are associated with this message are:

- 111** Permission to access the file or directory was denied.
- 129** The file or directory you are trying to access does not exist.
- 133** The UNIX file system is out of storage.

System action

For the system action taken, see the other messages that are associated with this error.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Correct the problem in response to the system return code identified in this message. The return code is from the system function that was used. See *z/OS UNIX System Services Programming: Assembler Callable Services Reference* to interpret the return code.

User response

Inform your system programmer that this error occurred.

APS8552I THE CHANGING OF OWNERSHIP FOR THE *directory name* DIRECTORY HAS FAILED WITH RETURN CODE(*return code*) AND REASON CODE(*reason code*).

Explanation

The BPX1CHO system function macro failed to change the ownership of the specified directory. After returning from the BPX1CHO macro, register 15 contained a nonzero return code.

Common return codes that are associated with this message are:

- 111** Permission to access the file or directory was denied.
- 129** The file or directory you are trying to access does not exist.
- 133** The UNIX file system is out of storage.

System action

None.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Correct the problem in response to the system return code identified in this message. The return code is from the system function that was used. See [z/OS UNIX System Services Programming: Assembler Callable Services Reference](#) to interpret the return code.

User response

Inform your system programmer that this error occurred.

APS8553I **THE CHANGING OF OWNERSHIP FOR THE *directory name* DIRECTORY HAS FAILED. BPX1GPN FAILED WITH RETURN CODE(*return code*) AND REASON CODE(*reason code*).**

Explanation

The BPX1GPN system function macro failed to change the ownership of the specified directory. After returning from the BPX1GPN macro, register 15 contained a nonzero return code.

Common return codes that are associated with this message are:

111

Permission to access the file or directory was denied.

129

The file or directory you are trying to access does not exist.

133

The UNIX file system is out of storage.

System action

None.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Correct the problem in response to the system return code identified in this message. The return code is from the system function that was used. See [z/OS UNIX System Services Programming: Assembler Callable Services Reference](#) to interpret the return code.

User response

Inform your system programmer that this error occurred.

APS8554I **THE CHANGING OF OWNERSHIP FOR THE *file name* FILE HAS FAILED. BPX1GPN FAILED WITH RETURN CODE(*return code*) AND REASON CODE(*reason code*).**

Explanation

The BPX1GPN system function macro failed to change the ownership of the specified file. After returning from the BPX1GPN macro, register 15 contained a nonzero return code.

Common return codes that are associated with this message are:

111

Permission to access the file or directory was denied.

129

The file or directory you are trying to access does not exist.

133

The UNIX file system is out of storage.

System action

None.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Correct the problem in response to the system return code identified in this message. The return code is from the system function that was used. See [z/OS UNIX System Services Programming: Assembler Callable Services Reference](#) to interpret the return code.

User response

Inform your system programmer that this error occurred.

APS8555I **THE CHANGING OF OWNERSHIP FOR THE *file name* FILE HAS FAILED WITH RETURN CODE(*return code*) AND REASON CODE(*reason code*).**

Explanation

The BPX1CHO system function macro failed to change the ownership of the specified file. After returning from the BPX1CHO macro, register 15 contained a nonzero return code.

Common return codes that are associated with this message are:

111

Permission to access the file or directory was denied.

129

The file or directory you are trying to access does not exist.

133

The UNIX file system is out of storage.

System action

None.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Correct the problem in response to the system return code identified in this message. The return code is from the system function that was used. See *z/OS UNIX System Services Programming: Assembler Callable Services Reference* to interpret the return code.

User response

Inform your system programmer that this error occurred.

APS8556I	FILE <i>filename</i> COULD NOT BE CLOSED. RETURN CODE (<i>return code</i>). REASON CODE (<i>reason code</i>). PATHNAME=<i>pathname</i>.
-----------------	--

Explanation

The BPX1CLO system function macro failed to close the specified file. After returning from the BPX1CLO macro, register 15 contained a nonzero return code.

Common return codes that are associated with this message are:

111

Permission to access the file or directory was denied.

129

The file or directory you are trying to access does not exist.

133

The UNIX file system is out of storage.

System action

For the system action taken, see the other messages that are associated with this error.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Correct the problem in response to the system return code identified in this message. The return code is from the system function that was used. See *z/OS UNIX System Services Programming: Assembler Callable Services Reference* to interpret the return code.

User response

Inform your system programmer that this error occurred.

APS8557I	THE ACCESS PERMISSIONS FOR THE <i>directory name</i> DIRECTORY CANNOT BE CHANGED. THE ACCESS REQUEST FAILED WITH RETURN CODE (<i>return code</i>) AND REASON CODE (<i>reason code</i>).
-----------------	--

Explanation

The BPX1CHM system function macro failed to change the permissions of the specified directory. After returning from the BPX1CHM macro, register 15 contained a nonzero return code.

Common return codes that are associated with this message are:

111

Permission to access the file or directory was denied.

129

The file or directory you are trying to access does not exist.

133

The UNIX file system is out of storage.

System action

None.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Use the return code and reason code that are identified in the message to correct the problem. See [z/OS UNIX System Services Programming: Assembler Callable Services Reference](#) to interpret the return code and reason code.

User response

Inform your system programmer that this error occurred.

APS8558I FILE *filename* COULD NOT BE WRITTEN. RETURN CODE (*return code*). REASON CODE (*reason code*). PATHNAME=*pathname*.

Explanation

The BPX1WRT system function macro failed to write to the specified file. After returning from the BPX1WRT macro, register 15 contained a nonzero return code.

Common return codes that are associated with this message are:

111

Permission to access the file or directory was denied.

129

The file or directory you are trying to access does not exist.

133

The UNIX file system is out of storage.

System action

For the system action taken, see the other messages that are associated with this error.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Correct the problem in response to the system return code identified in this message. The return code is from the system function that was used. See [z/OS UNIX System Services Programming: Assembler Callable Services Reference](#) to interpret the return code.

User response

Inform your system programmer that this error occurred.

APS8559I *jobname, jobid, stepname, ddname, jobpart, eventdata*.

Explanation

The status of processing for the current spool data set is displayed when the DISPLAY, STATUS=AFPD operator interface MODIFY command or the `display -afpd -status AFPPARMS` control statement parameter is used. The values are:

jobname

Name of the job currently being processed.

jobid

Job identifier of the spool data set being processed.

stepname

Step name of the job that is processed.

ddname

DD name for the step name that is processed.

jobpart

The part of the job that is being processed. Values are:

DS HDR

Data set header

JOB HDR

Job header

JOB TRL

Job trailer

MESSAGE

Messages that are produced from the user print data.

USER

User print data.

eventdata

The number of transformed and transmitted bytes, the percentage of transformed bytes that are transmitted, and the number of compressed bytes. The *eventdata* value depends on the mode that AFP Download Plus is in and how the status feature is activated:

- If activated with the `display -afpd -status AFPPARMS` control statement parameter, the processing status is reported for both the spool data set transformation to MO:DCA-P and transformed document transmission.
- If activated with the DISPLAY, STATUS=AFPD operator interface MODIFY command, the processing status is reported for the value that is specified with the EVENT parameter.

The values are:

Transformed bytes=nnnnnnn

Specifies the number of kilobytes (KB), megabytes (MB), or gigabytes (GB) that result from AFP Download Plus transforming data to MO:DCA-P format.

Transmitted=ppppp

Specifies the percentage (0% to 100%) of the total number of transformed bytes that AFP Download Plus transmitted to the receiving system.

Transmitted bytes=ggggggg

Specifies the number of bytes (KB, MB, or GB) that AFP Download Plus transmitted to the receiving system.

Compressed bytes=ccccccc

When compression is activated for the FSA or data set, specifies the number of bytes (KB, MB, or GB) that result from AFP Download Plus compressing the data.

See *PSF for z/OS: AFP Download Plus* for information about activating the status feature and how *eventdata* is displayed.

System action

None.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

No response is necessary.

APS8560I **AFP DOWNLOAD PLUS PRINT REQUEST CANCELED FOR JOB= *jobname* STEP= *jobstep* ID= *jobid* AT *system-id*. INFORMATIONAL MESSAGES ARE LOCATED IN FILE: *location*.**

Explanation

Processing of the print request is canceled. If the job submitter specified that this message be sent to the user IDs specified in the NOTIFY keyword in the JCL for the print request, the message is sent to those user IDs. Otherwise, this message is sent to the job submitter. This message is also recorded in the system log. The *location* values are:

filename

The name of the file that contains the messages.

MESSAGES REDIRECTED

Messages are redirected to a SYSOUT data set.

System action

AFP Download Plus continues processing with the next print request.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Examine the messages in *filename* or the redirected message data set for more information. For more information about the redirected message data set, contact your system programmer.

APS8562I **AFP DOWNLOAD PLUS HAS SUCCESSFULLY COMPLETED PROCESSING FOR JOB= *jobname* STEP= *jobstep* ID= *jobid* AT *system-id*. INFORMATIONAL MESSAGES ARE LOCATED IN FILE: *location*.**

Explanation

Processing of the print request completed successfully. If the job submitter specified that this message be sent to the user IDs specified in the NOTIFY keyword in the JCL for the print request, the message is sent to those user IDs. Otherwise, this message is sent to the job submitter. This message is also recorded in the system log. The *location* values are:

filename

The name of the file that contains the messages.

MESSAGES REDIRECTED

Messages are redirected to a SYSOUT data set.

System action

The job is transmitted to the receiver. AFP Download Plus continues processing with the next print request.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Examine the messages in *filename* or the redirected message data set for more information. For more information about the redirected message data set, contact your system programmer.

APS8563I **AFP DOWNLOAD PLUS STOPPED PROCESSING THE PRINT DATA SET DUE TO ERRORS: JOB= *jobname* STEP= *jobstep* ID= *jobid* AT *system-id*. ERROR EXPLANATIONS ARE LOCATED IN FILE: *location*.**

Explanation

Processing of the print request ended unsuccessfully. If the job submitter specified that this message be sent to the user IDs specified in the NOTIFY keyword in the JCL for the print request, the message is sent to those user IDs. Otherwise, this message is sent to the job submitter. This message is also recorded in the system log. The *location* values are:

filename

The name of the file that contains the messages.

MESSAGES REDIRECTED

Messages are redirected to a SYSOUT data set.

System action

The job is not transmitted to the receiver. AFP Download Plus continues processing with the next print request.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

Examine the messages in *filename* or the redirected message data set for more information. For more information about the redirected message data set, contact your system programmer.

APS8564I **AFP DOWNLOAD PLUS HAS SUCCESSFULLY COMPLETED PROCESSING FOR JOB= *jobname* STEP= *jobstep* ID= *jobid* AT *system-id*.**

Explanation

Processing of the print request completed successfully. The job submitter specified that this

message be sent to the user IDs specified in the NOTIFY keyword in the JCL for the print request. This message is also recorded in the system log.

System action

AFP Download Plus continues processing with the next print request.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

No response is necessary.

APS8565I **COULD NOT CREATE THE AFP DOWNLOAD PLUS *directory name* DIRECTORY. BPX1MKD FAILED WITH RETURN CODE = *return code* AND REASON CODE = *reason code*.**

Explanation

The BPX1MKD system function macro failed to create the specified file. After returning from the BPX1MKD macro, register 15 contained a nonzero return code.

Common return codes that are associated with this message are:

111

Permission to access the file or directory was denied.

129

The file or directory you are trying to access does not exist.

133

The UNIX file system is out of storage.

System action

For the system action taken, see the other messages that are associated with this error.

Operator response

Inform your system programmer that this error occurred.

System programmer response

Correct the problem in response to the system return code identified in this message. The return code is from the system function that was used. See [z/OS](#)

UNIX System Services Programming: Assembler Callable Services Reference to interpret the return code.

User response

Inform your system programmer that this error occurred.

APS8566I **AFP DOWNLOAD PLUS PRINT REQUEST INTERRUPTED FOR JOB= *jobname* STEP= *jobstep* ID= *jobid* AT *system-id*. INFORMATIONAL MESSAGES ARE LOCATED IN FILE: *location*.**

Explanation

Processing of the print request that is identified in the message was interrupted by the operator. If the job submitter specified that this message be sent to the user IDs specified in the NOTIFY keyword in the JCL for the print request, the message is sent to those user IDs. Otherwise, this message is sent to the job submitter. This message is also recorded in the system log. The *location* values are:

filename

The name of the file that contains the messages.

MESSAGES REDIRECTED

Messages are redirected to a SYSOUT data set.

System action

The print request is returned to JES and can be restarted by the operator.

Operator response

No response is necessary.

System programmer response

No response is necessary.

APSH0001 to APSH0064

APSH0001 **Usage: apshhsub Fname JCLOpts Queue " " Port Xparms**

Explanation

You invoked the apshhsub exit with the -? command option.

System action

None.

User response

Examine the messages in *filename* or the redirected message data set for more information. For more information about the redirected message data set, contact your system programmer.

APS8600I **JOB=*jobname* STEP=*jobstep* ID=*jobid* AT *system_id* WAS PROCESSED BY *afpdp_version* ON *fsa*, DESTINED FOR IPADDR=*ip_address*, PORT=*port_number*.**

Explanation

This message provides the associated job and system information. It also identifies the version of AFP Download Plus that processed this data set and indicates the receiver where the data set was sent. The IP address and port number identify the selected receiver for processing the data set associated with the specified AFP Download Plus version and FSA name.

System action

This message is issued only if other messages are issued for the data set, and if the PIMSG parameter is set to YES either in the JCL for the print job or in the AFP Download Plus startup procedure.

Operator response

No response is necessary.

System programmer response

No response is necessary.

User response

No response is necessary.

User response

None.

APSH0002 **The command option *—option* is not valid.**

Explanation

You issued the apshhsub exit and included a command option that is not valid.

System action

The command ends without processing.

User response

Review the command syntax and issue the command again.

APSH0003 **One or more required parameters are missing.**

Explanation

One or more required parameters are missing in the apshhsub exit.

System action

The command ends without processing.

User response

Review the command syntax and issue the command again.

APSH0004 **-option value 'text' is not valid.**

Explanation

You issued the apshhsub exit with a command option that was not in the correct format. For example, it specified an alphabetic value when a numeric value was required.

System action

The command ends without processing.

User response

Review the command syntax and issue the command again.

APSH0005 **Unable to allocate storage (error errno). ...system-explanation**

Explanation

The apshhsub exit cannot allocate the required storage. The message provides additional information on why the storage allocation attempt failed.

System action

The command stops processing.

User response

Use the information in the message to correct the problem and issue the command again.

APSH0006 **An error occurred while opening file-name (error errno). ...system-explanation**

Explanation

The apshhsub exit cannot open the specified file. The message provides additional information on why the storage allocation attempt failed.

System action

The command stops processing.

User response

Use the information in the message to correct the problem and issue the command again.

APSH0007 **time-stamp – submit started.**

Explanation

The apshhsub exit issues this message when it begins processing data that is received by apshhrcd. The message shows when the process began.

System action

The apshhsub exit begins processing the data.

User response

None.

APSH0008 **time-stamp – submit ended (rc return-code).**

Explanation

The apshhsub exit issues this message when it completes processing data that is received by apshhrcd. The message shows when the process was complete. It also shows the overall return code from the process.

System action

The apshhsub exit ends.

User response

None.

APSH0009 **Parameters:Input file: 'file-name'
Options: 'sender-options'
Queue: 'apshhrcd-q-value'
Port: 'apshhrcd-p-value'
Extra arguments: 'apshhrcd-X-value'**

Trace: '1-or-0'

Explanation

The apshhsub exit issues this message when it begins processing data that is received by apshhꠁcd. This message shows the parameters that were passed to apshhsub from apshhꠁcd.

System action

The apshhsub exit begins processing the data.

User response

None.

APSH0010 **Option 'name' is not valid.**

Explanation

The apshhsub exit encountered an option that it did not recognize.

System action

The apshhsub exit stops processing.

User response

If the option is from a sender (AFP Download Plus or Download for z/OS), report the problem to IBM. If the option is from an attribute mapping file, correct the attribute mapping file and issue the exit again.

APSH0011 **Options mapped from file-name:**

Explanation

The apshhsub exit is mapping options from an attribute mapping file. This message shows the name of the file. It is followed by one or more instances of message APSH0012.

User response

None.

APSH0012 **Line number: 'options-from-file'**

Explanation

The apshhsub exit is mapping options from an attribute mapping file. This message shows the options from the file that apply to the current job.

System action

The apshhsub exit continues processing.

User response

None.

APSH0013 **An error occurred while reading file-name (error errno). ...system-explanation**

Explanation

The apshhsub exit cannot read the specified file. The message provides additional information on why the storage allocation attempt failed.

System action

The command stops processing.

User response

Use the information in the message to correct the problem and issue the command again.

APSH0014 **An error occurred while activating the output descriptor. ...return code = return-code, reason code = reason-code, parameter = text-unit.**

Explanation

The apshhsub exit attempted to use text units to create an output descriptor to assign attributes to the SYSOUT data set. One of the text units is in error. The return code and reason code are from the OUTADD macro.

System action

The apshhsub exit stops processing.

User response

Review the option value that corresponds to the text unit reported in the message. If the option is from a sender (AFP Download Plus or Download for z/OS), report the problem to IBM. If the option is from an attribute mapping file, correct the attribute mapping file and issue the exit again.

APSH0015 **An error occurred while trying to create the SYSOUT data set.**

Explanation

The apshhsub exit cannot create a SYSOUT data set. This message is followed by another message that provides more detail about the problem.

System action

The apshhsub exit stops processing

User response

Use the information in the next message that is issued to correct the problem and issue the exit again.

APSH0016 **An error occurred while trying to open the SYSOUT data set.**

Explanation

The apshhsub exit cannot open a SYSOUT data set. This message is followed by another message that provides more detail about the problem.

System action

The apshhsub exit stops processing

User response

Use the information in the next message that is issued to correct the problem and issue the exit again.

APSH0017 **An error occurred while trying to write the SYSOUT data set.**

Explanation

The apshhsub exit cannot write to a SYSOUT data set. This message is followed by another message that provides more detail about the problem.

System action

The apshhsub exit stops processing

User response

Use the information in the next message that is issued to correct the problem and issue the exit again.

APSH0018 **The input data is not complete.**

Explanation

The apshhsub exit is copying records from the input data file to the SYSOUT data set. The last record in the input data file is not complete. It contains a length field that indicates that more data exists after the end of the file.

System action

The apshhsub exit stops processing

User response

If the sender is AFP Download Plus, report the problem to IBM. If the sender is Download for z/OS, ensure that SEND_REC_LENGTH=YES is specified in the routing control data set entry for this receiver. If SEND_REC_LENGTH=YES is specified, report the problem to IBM.

APSH0019 **The data set was spooled to SYSOUT:**
Bytes=byte_count (rounded_count)
Records=record_count (rounded_count)
Pages=page_count (rounded_count)

Explanation

The apshhsub exit completed writing the SYSOUT data set. This message reports the total number of bytes, records, and pages in that data set. For larger numbers, the message also reports the counts rounded up to the nearest kilobytes (KBs), megabytes (MBs), or gigabytes (GBs).

The number of bytes is an exact count of the bytes that comprise the data. This number can differ from the number of bytes that is reported by JES for the same job. JES includes in its byte count those bytes that it uses for its own internal functions.

The number of records is an exact count of the records that comprise the data.

The number of pages is based on the content of the data. For MO:DCA-P documents, apshhsub counts the number of BPG structured fields. For other documents, apshhsub analyzes the skip-to-channel-1 carriage controls within the data stream.

System action

The apshhsub exit continues processing.

User response

None.

APSH0020 **The final disposition is HOLD.**

Explanation

The apshhsub exit completed writing the SYSOUT data set. This message reports that the SYSOUT data set is placed in the held queue.

System action

The apshhsub exit continues processing.

User response

None.

APSH0021 The final disposition is NORMAL.

Explanation

The apshhsub exit completed writing the SYSOUT data set. This message reports that the SYSOUT data set is not held or deleted.

System action

The apshhsub exit continues processing.

User response

None.

APSH0022 The final disposition is DELETE.

Explanation

The apshhsub exit completed writing the SYSOUT data set. This message reports that the SYSOUT data set is deleted.

System action

The apshhsub exit continues processing.

User response

None.

APSH0049 *timestamp* - submit started.

Explanation

The apshhmds exit issues this message when it begins processing data that is received by apshhxcd. The message shows when the process started.

System action

The apshhmds exit begins processing the data.

User response

None.

**APSH0050 Not all data sets in the job are afp.
Either a data set in the job failed
or the job was submitted through
Download.**

Explanation

The apshhmds exit requires that all data sets in a multiple data set job are MO:DCA.

System action

The apshhmds exit rejects the job and no data is put on the spool.

User response

None.

APSH0051 afpconcat failed.

Explanation

The apshhmds exit received a nonzero return code from the afpconcat program.

System action

The apshhmds exit rejects the job and no data is put on the spool.

User response

None.

**APSH0052 APSHHSUB failed, see the
APSHHSUB.port.LOG file.**

Explanation

The apshhmds exit received a nonzero return code from the apshhsub exit. See the apshhsub message file, apshhsub.port.log, for more information.

System action

The apshhmds exit rejects the job and no data is put on the spool.

User response

None.

**APSH0053 There were no print files found to
print.**

Explanation

No print files were found in the working directory. apshhxcd might have problems storing the data sets for the job.

System action

The apshhmds exit rejects the job and no data is put on the spool.

User response

None.

APSH0054 **Read failed for *job name* job parameter file, the errno is *errno* and the error string is *errno string*.**

Explanation

The job parameter file read failed. Use the errno value and the errno string to determine the problem.

System action

The apshhmds exit rejects the job and no data is put on the spool.

User response

None.

APSH0055 **Close failed for *job name* job parameter file, the errno is *errno* and the error string is *errno string*.**

Explanation

The job parameter file close failed. Use the errno value and the errno string to determine the problem.

System action

The apshhmds exit rejects the job and no data is put on the spool.

User response

None.

APSH0056 **Open failed for *job name* job parameter file, the errno is *errno* and the error string is *errno string*.**

Explanation

The job parameter file open failed. Use the errno value and the errno string to determine the problem.

System action

The apshhmds exit rejects the job and no data is put on the spool.

User response

None.

APSH0057 **Open failed for *file name* afpconcat parameter file, the errno is *errno* and the error string is *errno string*.**

Explanation

The afpconcat parameter file open failed. Use the errno value and the errno string to determine the problem.

System action

The apshhmds exit rejects the job and no data is put on the spool.

User response

None.

APSH0058 **Write failed for *file name* afpconcat parameter file, the errno is *errno* and the error string is *errno string*.**

Explanation

The afpconcat parameter file write failed. Use the errno value and the errno string to determine the problem.

System action

The apshhmds exit rejects the job and no data is put on the spool.

User response

None.

APSH0059 **Open failed for *file name*.JCL file, the errno is *errno* and the error string is *errno string*.**

Explanation

The -o options file open failed. Use the errno value and the errno string to determine the problem.

System action

The apshhmds exit rejects the job and no data is put on the spool.

User response

None.

APSH0060 **Read failed for *file name*.JCL file, the errno is *errno* and the error string is *errno string*.**

Explanation

The -o options file read failed. Use the errno value and the errno string to determine the problem.

System action

The apshhmds exit rejects the job and no data is put on the spool.

User response

None.

APSH0061 **Close failed for file name.JCL file, the errno is *errno* and the error string is *errno string*.**

Explanation

The -o options file close failed. Use the errno value and the errno string to determine the problem.

System action

The apshhmds exit rejects the job and no data is put on the spool.

User response

None.

APSH0062 **Processing completed successfully for job *job name*.**

Explanation

The apshhmds exit issues this message when it successfully completes processing the data received by apshhrcd. The message shows when the process ended.

System action

The apshhmds exit ends.

User response

None.

APSH0063 **Processing failed for job *job name*.**

Explanation

The apshhmds exit issues this message when it unsuccessfully completes processing the data received by apshhrcd. The message shows when the process ended. Check the apshhmds .port number .log for other messages.

System action

The apshhmds exit ends.

User response

None.

APSH0064 **Parmlist: *parameter list***

Explanation

The apshhmds exit issues this message when debug=yes and logging is active (yes or error). The message shows the parameters passed to apshhmds from apshhrcd.

The parameters are:

Base: *directory*

The directory that contains the AFP Download Plus executable files.

Parm list file: *job name.JOB*

The file name built by apshhrcd that contains the list of data set names received by apshhrcd.

Queue: *null*

Always null.

Port: *port number*

The port number that apshhrcd is using.

-X arguments: *arguments*

The -X arguments specified on the apshhrcd startup command.

Trace:

The -t value specified on the apshhrcd startup command, where 1 = yes, 0 = no.

If the apshhsub exit is going to be issued, the message shows the apshhsub parameter list that apshhmds created just before the apshhsub exit is issued by apshhmds. See APSh0009 for the parameter definitions.

System action

The apshhmds exit begins processing the data.

User response

None.

APSH0065 **The stat function failed for file name *filename*; the errno is *errno* and the error string is *errno string*.**

Explanation

The stat function was unable to determine whether the file contains data and must be processed or ignored. Use the errno value and the errno string to determine the problem.

System action

The apshhmds exit rejects the job and no data is put on the spool.

User response

None.

multiple data set mode, only files that contain data can be included with the concatenated data set that is put on the JES spool.

APSH0066 **File name *filename* contains no data and cannot be included in the spooled data set.**

System action

The apshhmds exit continues processing the data.

Explanation

A PRD data file was found to contain no data and was not included in the spooled data set. When running in

User response

None.

Chapter 2. System completion codes and PSF abend reason codes

Abend processing and restart

PSF issues messages to the operator to indicate its status during an abnormal ending (abend). When an abend occurs, PSF issues either APS050I, if it recognizes the system completion code that is provided by z/OS, or APS055I, if it does not recognize that code. In either case, PSF also issues APS051I, indicating that it is undergoing an abnormal ending. PSF gives more diagnostic information on system completion codes it recognizes by listing a PSF abend reason code within the APS050I message. This information lists the system completion codes that PSF recognizes and describes the abend reason codes that can appear in the APS050I message.

If the abend reason code that is listed in the APS050I message represents a condition that can be corrected when the printer is started again, PSF automatically tries to restart, provided the operating system supports this function. On an automatic restart, PSF issues APS038I to indicate that it is attempting to restart. Subsequently, PSF issues APS057I or APS053I, depending on whether the restart was successful. For more information about the automatic abend restart function, see [PSF for z/OS: Diagnosis](#).

If PSF determines that a memory dump is to be generated, it requests a dump. Subsequently, PSF issues either APS042I, APS044I, or APS054I, depending on how successful it was in creating that dump.

System completion codes

The system completion code is used in combination with the PSF abend reason code to determine an appropriate response to the abend. PSF recognizes these system completion codes:

024 [PSF]

Explanation

The PSF FSA is stopped.

027 [PSF]

Explanation

The PSF FSS is stopped.

0A6 [PPCC]

Explanation

The Page Printer Communication Component is ended.

PSF abend reason codes

The PSF abend reason code entries in this information provide:

Explanation

The explanation gives more information about the condition that caused a PSF abend.

System Action

The system action specifies whether PSF attempts to restart itself automatically, or end.

System Programmer Response

If present, the system programmer response provides a suggested recovery action for the error condition.

Each abend reason code includes the PSF module that issued it. For a brief description of each module, see *PSF for z/OS: Diagnosis*.

0004**Explanation**

This abend is issued by module APSPPIEP or APSKAFPD— the ESTAE macro failed to establish the ESTAE routine.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0005**Explanation**

This abend is issued by module APSPPIEP— an error occurred accessing the Printer Inventory for FSS parameters.

System action:**System programmer response**

Correct the Printer Inventory error that is indicated by the preceding message, and restart PSF.

0006**Explanation**

This abend is issued by module APSOPIA— not enough storage exists for a PrinterInventoryAPI object.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Increase the REGION parameter in the PSF startup procedure.

0007**Explanation**

This abend is issued by module APSOFSS— not enough storage exists for a FunctionalSubSystem object.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Increase the REGION parameter in the PSF startup procedure.

0008**Explanation**

This abend is issued by module APSPPIEP or APSKAFPD— the GETMAIN macro for PSF FSS-related control blocks failed.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0009**Explanation**

This abend is issued by module APSOPIA— not enough memory exists for a PIA header.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Increase the REGION parameter in the PSF startup procedure.

000A**Explanation**

This abend is issued by module APSOCONF— not enough storage exists for a Configuration object.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Increase the REGION parameter in the PSF startup procedure.

000B**Explanation**

This abend is issued by module APSOBOOT— No memory for bootstrap object.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Increase the REGION parameter in the PSF startup procedure.

000C**Explanation**

This abend is issued by module APSPPIEP or APSKAFPD— an incorrect parameter was specified on the MVS START command.

System action

PSF processing ends abnormally.

000D**Explanation**

This abend is issued by module APSPPIEP or APSKAFPD— the GETMAIN macro for below the 16 MB line PSF FSS-related control blocks failed.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

000E**Explanation**

This abend is issued by module APSPCKEN— the PSF product or feature is not enabled on your system.

System action

PSF processing ends abnormally.

System programmer response

This abend reason code indicates that the PSF product or feature is not enabled in the IFAPRDxx member in SYS1.PARMLIB. If you have a license for the PSF product or feature, you might need to change the STATE value in the IFAPRDxx member from DISABLED to ENABLED, or you might need to add a PRODUCT entry in the IFAPRDxx member that sets the STATE value to ENABLED. If you need to add an entry for the product, follow the instructions in the appropriate PSF product or feature program directory.

If you do not have the appropriate PSF product or feature license, contact your IBM marketing representative to obtain a license.

000F**Explanation**

This abend is issued by module APSPCKEN— IFAEDREG failed on call to check enablement of the PSF product or feature.

System action

PSF processing ends abnormally.

System programmer response

This abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center, or use your electronic link with IBM service for assistance.

0010**Explanation**

This abend is issued by module APSPPIEP or APSKAFPD— the FSS-level FSI CONNECT request failed. A CONNECT request failure can occur if the JES timer expires.

System action

PSF processing ends abnormally.

System programmer response

To determine other reasons for the failure, check the system log for all related JES and system messages.

0012**Explanation**

This abend is issued by module APSPFCON— the parameter that specifies either FSS or FSA level was not passed to the module when APSPFCON was called.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0014**Explanation**

This abend is issued by module APSPASI— an incorrect parameter was specified on the MVS START command that was used to start the PSF address space.

System action

PSF processing ends abnormally.

0018**Explanation**

This abend is issued by module APSPPFSP— FREEMAIN for APSPPNST failed.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system determine why FREEMAIN failed or returned unexpected results. If FREEMAIN reported that the storage requested to be freed is not owned by PSF, it indicates a PSF logic error. If it is a logic error, contact your service representative in the IBM Support Center, or use your electronic link with IBM service for assistance.

0019**Explanation**

This abend is issued by module APSPPFSP— GETMAIN for SAE storage failed.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Increase the REGION parameter for the PSF startup procedure.

001A**Explanation**

This abend is issued by modules APSHPFSP, APSKFSP, and APSPPFSP — An FSS order was posted

(SAQORECB) but the order outstanding flag (SAQOROUT) is off. Communication between JES and PSF is out of sync.

System action

PSF processing ends abnormally.

001C

Explanation

This abend is issued by modules APSPASI and APSAFSA— the ATTACH for the Notify subtask, APSPNST, failed.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system macros to determine why the macro failed or returned unexpected results.

0020

Explanation

This abend is issued by module APSPFSP— APSPFSP was dispatched to process an order other than a Stop FSS or Start FSA FSS level-order.

System action

PSF processing ends abnormally.

0024

Explanation

This abend is issued by module APSPNST— the FSI RELDS request failed. The return code is in the NCBNSTRC field in the APSPNCB control block.

System action

PSF processing ends abnormally.

0025

Explanation

This abend is issued by module APSOPIP— no storage for PIP object.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to

do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Increase the REGION parameter in the PSF startup procedure.

0026

Explanation

This abend is issued by module APSOPIP— no storage for buffer.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Increase the REGION parameter in the PSF startup procedure.

0027

Explanation

This abend is issued by module APSOPIQ— no storage for PIQ object.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Increase the REGION parameter in the PSF startup procedure.

0028

Explanation

This abend is issued by module APSPNST— the FSI CHKPT request failed. The return code is in the NCBNSTRC field in the APSPNCB control block.

System action

PSF processing ends abnormally.

0029**Explanation**

This abend is issued by module APSOPIQ— bad query flag.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

002A**Explanation**

This abend is issued by module APSPINST— see accompanying message.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

002C**Explanation**

This abend is issued by module APSPNST— the SMFWTM macro failed. The return code is in the NCBNSTRC field in the APSPNCB control block.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system macros to determine why the macro failed or returned unexpected results.

0030**Explanation**

This abend is issued by module APSPPIEP or APSKAFPD— the FSS-level FSI DISCONNECT request failed.

System action

PSF processing ends abnormally.

0032**Explanation**

This abend is issued by module APSPDCON— the parameter that specifies either the FSS or FSA level was not passed to the module when APSPDCON was called.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0034**Explanation**

This abend is issued by module APSPPIEP or APSKAFPD— the FREEMAIN macro for the FSS-level PSF control blocks failed.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system determine why FREEMAIN failed or returned unexpected results. If FREEMAIN reported that the storage requested to be freed is not owned by PSF, it indicates a PSF logic error. If it is a logic error, contact your service representative in the IBM Support Center, or use your electronic link with IBM service for assistance.

0038**Explanation**

This abend is issued by module APSPPIEP or APSKAFPD— the ESTAE macro to cancel the PSF address space ESTAE routine failed.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system macros to determine why the macro failed or returned unexpected results.

003C**Explanation**

This abend is issued by module APSPDPDS— the APSPPNST subtask was dispatched for ending and ended with nonzero completion code.

System action

PSF processing ends abnormally.

0044**Explanation**

This abend is issued by modules APSPDPDS/APSAFSA — the DETACH macro to detach the Notify subtask (APSPPNST) failed.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system macros to determine why the macro failed or returned unexpected results.

0048**Explanation**

This abend is issued by module APSPPASI— an incorrect subsystem name was provided on the MVS START command that is used to start the PSF address space.

System action

PSF processing ends abnormally.

004C**Explanation**

This abend is issued by module APSPPNST— an incorrect APSPFSAQ control block was passed to the Notify subtask (APSPPNST).

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0050**Explanation**

This abend is issued by module APSPPNST— the first unprocessed stacked Page Pending Queue (PPQ) entry is not a Begin Data Set (BDS) structured field entry. For more information about the BDS structured field, see *Mixed Object Document Content Architecture Reference*.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0054**Explanation**

This abend is issued by module APSPPFSP— IDENTIFY issued for APSPPFSA entry failed.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system macros to determine why the macro failed or returned unexpected results.

0058**Explanation**

This abend is issued by module APSPPFSP or APSHPFSP— an abend occurred in the Notify subtask, APSPPNST.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

005C**Explanation**

This abend is issued by module APSPPNST— an End Data Set (EDS) structured field entry was not found for a Begin Data Set (BDS) structured field stacked Page Pending Queue (PPQ) entry. For more information about the BDS and EDS structured fields, see *Mixed Object Document Content Architecture Reference*.

System action

PSF processing ends abnormally.

0060**Explanation**

This abend is issued by module APSPPNST— the data set ID for the Begin Data Set (BDS) structured field Page Pending Queue (PPQ) entry does not match the data set ID for the corresponding End Data Set (EDS) structured field PPQ entry.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0064**Explanation**

This abend is issued by module APSPPNST— the stack-queue locking protocol was violated. The stacked Page Pending Queue (PPQ) was acquired while APSPPNST was holding the queue in a locked state.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM

Support Center or use your electronic link with IBM service for assistance with this error code.

0068**Explanation**

This abend is issued by module APSPPNST— an incorrect Page Pending Queue (PPQ) entry type was found in the stacked PPQ.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0072**Explanation**

This abend is issued by module APSPPFSP— APSPPFSP DETACH APSPPNST failed.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system macros to determine why the macro failed or returned unexpected results.

0073**Explanation**

This abend is issued by module APSPPFSP— APSPPFSP DETACH APSPPFSA failed, and the NODUMP option was specified.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system macros to determine why the macro failed or returned unexpected results.

0074

Explanation

This abend is issued by module APSPPNST— a TIME (SVC11) macro to get the time and date failed.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system macros to determine why the macro failed or returned unexpected results.

0075**Explanation**

This abend is issued by module APSPPFSP— the APSPPNST subtask ended abnormally.

System action

PSF processing ends abnormally.

0076**Explanation**

This abend is issued by module APSPPFSP— APSPPFSP ATTACH FSA failed.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system macros to determine why the macro failed or returned unexpected results.

0078**Explanation**

This abend is issued by module APSAFSA— the IDENTIFY macro for the APSPPNST entry point failed.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system macros to determine why the macro failed or returned unexpected results.

0079**Explanation**

This abend is issued by module APSPPFSP— the SDUMP macro issued an incorrect return code during the processing of the Stop FSS order with a DUMP option specified.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system macros to determine why the macro failed or returned unexpected results.

007A**Explanation**

This abend is issued by module APSPPFSP— a Stop FSS order with ABEND and DUMP options specified was received.

System action

PSF processing ends abnormally.

007B**Explanation**

This abend is issued by module APSPPFSP— a Stop FSS order with ABEND and NODUMP options specified was received.

System action

PSF processing ends abnormally.

007F**Explanation**

This abend is issued by module APSPPFSP— APSPPFSP ATTACH NST failed.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system macros to determine why the macro failed or returned unexpected results.

0080

Explanation

This abend is issued by module APSLINIT— the library access system interface (LASI) was called to initialize the LASI environment, but the LASI environment was already initialized. The CCBSOCP field in the common control block (CCB) was not zero.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0081**Explanation**

This abend is issued by module APSLINIT— the library access system interface (LASI) was called to initialize the LASI environment. However, the device control block (APSJDEVB) was not available; the CCBPJDPV field in the common control block (CCB) was zero.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0082**Explanation**

This abend is issued by module APSLINIT— the library access system interface (LASI) was called to initialize the LASI environment. The ID for control block APSJDEVB is not valid. The ID must be JDE.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

00C0**Explanation**

This abend is issued by module APSCTERM— APSCTERM encountered an error while it was attempting to use the PGFREE macro. An abend occurs if a nonzero return code is issued by the PGFREE macro. The PGFREE macro must be run against the Device Manager control block storage and the PCI appendage (APSCPCIA).

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system macros to determine why the macro failed or returned unexpected results.

00C1**Explanation**

This abend is issued by module APSCESTA— APSCESTA encountered an error while it was attempting to page free storage. An abend occurs if the PGFREE macro issues a nonzero return code. The PGFREE macro must be run against the Device Manager control block storage and the PCI appendage (APSCPCIA).

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system macros to determine why the macro failed or returned unexpected results.

00C2**Explanation**

This abend is issued by module APSCCDEV— the conversion of the printer type and model from EBCDIC to UTF16 failed.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible problem with z/OS conversion services. z/OS conversion services might not be set up correctly. See [*z/OS Unicode Services User's Guide and Reference*](#) for more information.

00C3**Explanation**

This abend is issued by module APSCSYNC— the Set Purge Job Done SNMP request was not successful.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error or a possible printer problem. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance.

00D2**Explanation**

This abend is issued by module APSJCL— an SJF FIND request failed while locating the default output statement.

System action

PSF processing ends abnormally.

00D3**Explanation**

This abend is issued by module APSJCL— an SJF FIND request failed while locating the default output statement.

System action

PSF processing ends abnormally.

00D4**Explanation**

This abend is issued by module APSJCL— an SJF RETRIEVE request occurred while obtaining the keyword parameters.

System action

PSF processing ends abnormally.

00D5**Explanation**

This abend is issued by module APSJCL— an incorrect matrix pointer was received as a parameter.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

00D6**Explanation**

This abend is issued by module APSJCL— the SJF parameter and the matrix lengths do not match.

System action

PSF processing ends abnormally.

00D7**Explanation**

This abend is issued by module APSJGSWB— a failure in an SJF GETSWB request occurred.

System action

PSF processing ends abnormally.

System programmer response

The DIA_GETSWB_REAS field contains the incorrect reason code. This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

00D8**Explanation**

This abend is issued by module APSJPI— an error occurred while obtaining FSA parameters from the Printer Inventory.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Correct the Printer Inventory error that is indicated by the preceding message, and restart PSF.

00D9**Explanation**

This abend is issued by module APSJCK— an error occurred during processing of the AFPPARMS parameters specified in the startup procedure.

System action

PSF stops processing abnormally.

System programmer response

Correct the error that is specified by the preceding message, and restart PSF.

00DA**Explanation**

This abend is issued by module APSJCL— an incorrect value was detected while processing an AFPPARMS parameter specified in the startup procedure.

System action

AFP Download Plus processing ends abnormally.

System programmer response

Correct the error that is specified by the preceding message, and restart AFP Download Plus.

00DB**Explanation**

This abend is issued by module APSOFSA— not enough storage exists for a FunctionalSubSysApplication object.

System action

PSF processing ends abnormally.

System programmer response

Increase the REGION parameter in the PSF startup procedure.

00DC**Explanation**

This abend is issued by module APSJCLF— AFP Download Plus detected an error while processing the

AFPPARMS DD statement in the startup procedure. The AFPPARMS data set can contain only one defaults member, DEFAULTS or AFPDPDEF, not both.

System action

AFP Download Plus processing ends abnormally.

System programmer response

Correct the error that is specified by the preceding message, and restart AFP Download Plus.

00DD**Explanation**

This abend is issued by module APSJCK— AFPPARMS parameter processing is not supported in direct-printing mode.

System action

PSF processing ends abnormally.

System programmer response

Correct the error that is specified by the preceding message, and resubmit the print request.

0100**Explanation**

This abend is issued by module APSPPFSA or APSKFSA— the GETMAIN macro for PSF FSA-related control blocks failed.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0102

Explanation

This abend is issued by module APSPFFSA or APSKFSA— the GETMAIN macro for below the 16 MB line PSF FSA-related control blocks failed.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0103**Explanation**

This abend is issued by module APSHRPO— APSHRPO was called with a function that is not valid.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0104**Explanation**

This abend is issued by module APSPFFSA— the dynamic allocation of the device to be managed by the FSA failed.

System action

PSF processing ends abnormally.

0106**Explanation**

This abend is issued by module APSPFFSA— the printer failed to initialize.

System action

PSF processing ends abnormally.

0107**Explanation**

This abend is issued by module APSPFFSA— the printer failed to initialize, either because device contact is broken, or because the device is inoperative as an IPDS printer. This error is detected when PSF is obtaining initial printer information.

System action

PSF processing ends abnormally.

0108**Explanation**

This abend is issued by module APSPFFSA or APSKFSA— the FSA-level FSI CONNECT request failed.

System action

PSF processing ends abnormally.

0109**Explanation**

This abend is issued by module APSHRPO— APSHRPO cannot find a beginning of the file Page Pending Queue (PPQ) entry.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

010A**Explanation**

This abend is issued by module APSPFFSA or APSKFSA— the GETMAIN macro for the FSI area failed.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

010B**Explanation**

This abend is issued by module APSHRPO— APSHRPO cannot find a recovery point or beginning of the file Page Pending Queue (PPQ) entry.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

010C**Explanation**

This abend is issued by module APSPFFSA— the FSI SEND request failed. The SEND request was to notify the Job Entry Subsystem (JES) that FSA initialization was not successful because the device was not available.

System action

PSF processing ends abnormally.

010D**Explanation**

This abend is issued by module APSPFFSA or APSKFSA— the GETMAIN macro for above the 16 MB line PSF FSA-related control blocks failed.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

010E**Explanation**

This abend is issued by module APSPSEND— the FSI SEND request failed. The SEND request was to notify the Job Entry Subsystem (JES) of either an intervention-required or an intervention-cleared condition.

System action

PSF processing ends abnormally.

010F**Explanation**

This abend is issued by module APSPFFSA or APSKFSA— FSA initialization failed during FSA restart processing.

System action

PSF processing ends abnormally.

0110**Explanation**

This abend is issued by module APSPFFSA— the device was not available, and the write-to-operator message that informs the operator of the situation failed.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0111**Explanation**

This abend is issued by module APShPUSR— unrecognized return code from DDSSendfiles call for user's data set.

System action

AFP Download Plus processing ends abnormally.

System programmer response

This AFP Download Plus abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0112**Explanation**

This abend is issued by module APSPFFSA or APSKFSA— the GETMAIN macro for below the 16 MB line PSF FSA-related control blocks failed.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0113**Explanation**

This abend is issued by module APShPDSP— the GETMAIN macro for the work area failed.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0114**Explanation**

This abend is issued by module APSPPIFA or APSKIFA — the APSIBLD macro to initialize the record resource block (RRB) interface for Page Printing Writer Document Processor failed.

System action

PSF processing ends abnormally.

0115**Explanation**

This abend is issued by module APShPDSC— the DDS@ variable still points to a DownloadDS (DDS) object in the POSObj control block when trying to create a new DDSObj control block.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0116**Explanation**

This abend is issued by module APSPDVP or APSKDVP— the FSI Release data set request failed.

System action

PSF processing ends abnormally.

0117**Explanation**

This abend is issued by module APSPDVP— the restart PPQ pointer (DCAPRSTQP) was not saved by

APSPDCM and APSPDVP is unable to restore the finishing environment.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0118

Explanation

This abend is issued by module APSPFSA or APSKFSA— the FSI SEND request failed. The FSI SEND request was to notify the Job Entry Subsystem (JES) that the PSF FSA initialization was not successful.

System action

PSF processing ends abnormally.

0119

Explanation

This abend is issued by module APSPUSR— return code set by the sender during direct-download=modca transmission is not valid.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

011A

Explanation

This abend is issued by module APSPJT— return code set by the sender during direct-download=modca transmission is not valid.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

011B

Explanation

This abend is issued by module APSPJH— return code set by the sender during direct-download=modca transmission is not valid.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

011C

Explanation

This abend is issued by module APSPFAC— module APSPORD dispatched the APSPFAC routine for an incorrect order.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

011D

Explanation

This abend is issued by module APSPDH— return code set by the sender during direct-download=modca transmission is not valid.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM

Support Center or use your electronic link with IBM service for assistance with this error code.

011E**Explanation**

This abend is issued by module APSHPDVP— the transmission reason code (DDSTransmitRS) is not recognized when a sync is required (SABSYNCH=ON).

System action

AFP Download Plus processing ends abnormally.

System programmer response

This AFP Download Plus abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0120**Explanation**

This abend is issued by module APSPSNDR— an FSI SEND request from PSF failed. The send request was a response to an FSI order from JES.

System action

PSF processing ends abnormally.

0122**Explanation**

This abend is issued by module APSPPFSA or APSKFSA— the FREEMAIN macro for the subpool kept across restarts failed.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system determine why FREEMAIN failed or returned unexpected results. If FREEMAIN reported that the storage requested to be freed is not owned by PSF, it indicates a PSF logic error. If it is a logic error, contact your service representative in the IBM Support Center, or use your electronic link with IBM service for assistance.

0124**Explanation**

This abend is issued by module APSPPGDS— the FSI GETDS request to acquire the data set failed.

System action

PSF processing ends abnormally.

0128**Explanation**

This abend is issued by module APSPPDVP— the APSIBLD macro to get a data set message record resource block (RRB) failed.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

012C**Explanation**

This abend is issued by module APSPIPER— APSPIPER sent a record to Document Processor in the APSIPUT macro for the current data set. Document Processor issued an incorrect return code. The return code is in the SABFSARC in the APSFSAB control block.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0130

Explanation

This abend is issued by module APSPDPS or APSKDSP— an FSI GETREC request failed for the reason indicated by GLRFLGS1 as given in message APS082I, which precedes this abend. This indicates a logic error in PSF or JES.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0134**Explanation**

This abend is issued by module APSPDPS or APSKDSP— an FSI FREEREC request failed. The return code is in the SABFSARC in the APSFSAB control block.

System action

PSF processing ends abnormally.

0138**Explanation**

This abend is issued by module APSPPODR or APSKODR— APSPPODR or APSKODR dispatched APPSPDVP to process an incorrect order.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

013C**Explanation**

This abend is issued by module APSPPODR or APSKODR— the SDUMP macro issued an incorrect return code.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system macros to determine why the macro failed or returned unexpected results.

0140**Explanation**

This abend is issued by module APSPPODR or APSKODR— a Stop Device order was received with ABEND and NODUMP options specified.

System action

PSF processing ends abnormally. No system dump is generated for the abend.

0144**Explanation**

This abend is issued by module APSPDCM— an incorrect order was detected by APPDCM.

System action

PSF processing ends abnormally.

0146**Explanation**

This abend is issued by module APSPDVP— dynamic allocation of storage failed.

System action

PSF processing ends abnormally.

0148**Explanation**

This abend is issued by module APSPDCM— the Page Pending Queue (PPQ) stacked queue was acquired while APSPDCM had exclusive use of it.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

014C

Explanation

This abend is issued by modules APSPDCM, APSPINTV, and APSPSET— the FSI SEND request failed. The return code is in the SABFSARC.

System action

PSF processing ends abnormally.

0150**Explanation**

This abend is issued by modules APSPPODR/APSKODR — the Stop Device order with ABEND and DUMP options was received.

System action

PSF processing ends abnormally.

0154**Explanation**

This abend is issued by module APSPDCM— an FSI RELDS request failed. The return code is in the SABFSARC field of the APSFSAB control block.

System action

PSF processing ends abnormally.

0158**Explanation**

This abend is issued by module APSPPFAC— a Stop Device order was received with ABEND and NODUMP options specified.

System action

PSF processing ends abnormally. No system dump is generated for the abend.

015C**Explanation**

This abend is issued by module APSPPFSA— the dynamic deallocation of the device that is managed by FSA failed.

System action

PSF processing ends abnormally.

0160**Explanation**

This abend is issued by module APSPPFSA or APSKFSA— the FSA-level FSI DISCONNECT request failed.

System action

PSF processing ends abnormally.

0164**Explanation**

This abend is issued by module APSPPFSA or APSKFSA— the FREEMAIN macro for the FSA-level PSF control blocks failed.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system determine why FREEMAIN failed or returned unexpected results. If FREEMAIN reported that the storage requested to be freed is not owned by PSF, it indicates a PSF logic error. If it is a logic error, contact your service representative in the IBM Support Center, or use your electronic link with IBM service for assistance.

0168**Explanation**

This abend is issued by module APSPTFA— an APSIDEQ macro to end the resource record block (RRB) interface for Page Printing Writer Document Processor failed.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

016C**Explanation**

This abend is issued by module APSPPFSA or APSKFSA— the write-to-operator message failed. The message was to notify the operator that the PSF FSA initialization was unsuccessful.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0170**Explanation**

This abend is issued by module APSPPGDS— the TIME (SVC11) macro to get the time and date failed.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system macros to determine why the macro failed or returned unexpected results.

0174**Explanation**

This abend is issued by modules APSPPODR/APSKODR — a Stop FSA order was received with ABEND and DUMP options specified.

System action

PSF processing ends abnormally.

0178**Explanation**

This abend is issued by module APSPPODR or APSKODR— a Stop FSA FSI order was received with ABEND and NODUMP options specified.

System action

PSF processing ends abnormally. No system dump is generated for the abend.

017C**Explanation**

This abend is issued by module APSPPCNP— the STIMERM CANCEL request failed.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system macros to determine why the macro failed or returned unexpected results.

0180**Explanation**

This abend is issued by module APSPNPR— the timer ID that was passed to the STIMERM exit routine when the timer expired did not match any timer ID returned when the STIMERM was issued.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible PSF or MVS logic error. For assistance related to this error code, consult your service representative in the IBM Support Center, or use your electronic link with IBM service.

0184**Explanation**

This abend is issued by module APSPPFAC— an FSI SEND request failed.

System action

PSF processing ends abnormally.

0188**Explanation**

This abend is issued by module APSPDCM— no repositioning entry was found for the data set that spans the committed page counter. The minimum entry of a Begin Data Set (BDS) entry must exist.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

018C**Explanation**

This abend is issued by modules APSPDPS/APSKDPS — an FSI GETREC request failed. The return code is in the SABFSARC in the APSPFSAB control block.

System action

PSF processing ends abnormally.

0190**Explanation**

This abend is issued by module APSRMSG— the APSIPUT macro to free message buffer record resource blocks (RRBs) failed.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0194**Explanation**

This abend is issued by module APSPDVP— Page Pending Queue (PPQ) entries still exist, even though the device was stopped.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0198**Explanation**

This abend is issued by module APSPFAC— the Stop Device order was received with ABEND and DUMP options specified.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

019C**Explanation**

This abend is issued by module APSPTFA— the first record resource block (RRB) on the RRB stack was not the Page Printing Writer Document Processor RRB.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

01A0**Explanation**

This abend is issued by module APSPTFA— the Page Printing Writer Document Processor record resource block (RRB) was not the only RRB on the RRB stack after the end of the PSF FSA.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

01A4**Explanation**

This abend is issued by module APSPPODR— an incorrect operator-intervention type was specified in the Operator Intervention FSA order.

System action

PSF processing ends abnormally.

01A8

Explanation

This abend is issued by module APSPPGDS— an AP SJCL logic error occurred during the processing of the COPIES JCL keyword. The copy count was not specified.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

01AC**Explanation**

This abend is issued by module APSPDPCM— a restart Page Pending Queue (PPQ) entry is not a valid PPQ entry type.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

01B0**Explanation**

This abend is issued by module APSPINTV— APSPDPCM was called by module APSPPFAC to process an Operator Intervention order. However, the device was not stopped.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

01B4**Explanation**

This abend is issued by module APSPINTV— an intervention type specified in the Operator Intervention order was not valid.

System action

PSF processing ends abnormally.

01B8**Explanation**

This abend is issued by module APSPDPCM— the Begin Data Set (BDS) entry for the data set that spans the committed page counter cannot be found in the stack queue.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

01BA**Explanation**

This abend is issued by module APSPDPCM— the Begin Transmission (BTM) entry for the data set that spans the committed page counter cannot be found in the stack queue.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

01BB**Explanation**

This abend is issued by module APSPDPCM— not enough storage available for triplet data.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to

do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

01BC

Explanation

This abend is issued by module APSPFFAC— the SDUMP macro issued an incorrect return code during the processing of the Stop Device order with the DUMP option specified.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system macros to determine why the macro failed or returned unexpected results.

01C0

Explanation

This abend is issued by module APSPDVP— the STIMER macro failed to set a timer.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system macros to determine why the macro failed or returned unexpected results.

01C4

Explanation

This abend is issued by module APSRMSG— the APSIDEQ macro to dequeue message record resource blocks (RRBs) failed.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

01C8

Explanation

This abend is issued by module APSPTFA— an APSIPUT call to dequeue the Job Entry Subsystem (JES) message record resource block (RRB) failed.

System action

PSF processing ends abnormally.

01CC

Explanation

This abend is issued by module APSPDOT— a SEND FSI request failed. The SEND was issued to notify the Job Entry Subsystem (JES) that a data set was at the committed page counter.

System action

PSF processing ends abnormally.

01D0

Explanation

This abend is issued by module APSPDOT— either the Page Pending Queue (PPQ) entry pointer that is passed by APSQDEQ does not point to a Begin Data Set (BDS), Begin Transmission (BTM), or End Data Set (EDS) entry, or the BDS that is pointed to must not be tracked.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

01D4

Explanation

This abend is issued by module APSPFFSA or APSKFSA— the input parameter does not point to the APSPFSAE control block.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

01D8**Explanation**

This abend is issued by module APSPFFAC— a Stop FSA order was received in which the ABEND and DUMP options were specified.

System action

PSF processing ends abnormally.

01DC**Explanation**

This abend is issued by module APSPFFAC— a Stop FSA order was received in which the ABEND and NODUMP options were specified.

System action

PSF processing ends abnormally.

01F0**Explanation**

This abend is issued by module APSPFFAC— during the processing of the Stop FSA order, the SDUMP macro issued an incorrect return code in which DUMP options were specified.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system macros to determine why the macro failed or returned unexpected results.

01F4**Explanation**

This abend is issued by module APSPPTFA— an APSIPUT macro to free the Job Entry Subsystem (JES) message buffers failed.

System action

PSF processing ends abnormally.

01F8**Explanation**

This abend is issued by module APSPPIFA or APSKIFA — initialization for the Job Entry Subsystem (JES) interrupt-message record resource block (RRB) build failed.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

01F9**Explanation**

This abend is issued by module APSPPDVP— the system function for OPEN of the PSF resource libraries did not succeed. The PSF resource libraries were closed and an attempt to reopen them occurred, but the reopen failed.

System action

PSF processing ends abnormally.

System programmer response

If Data Management messages preceded by IEC are received, use the information that is provided by these messages to recover from the open failure before you contact the IBM Support Center or use your electronic link with IBM service for assistance.

01FA**Explanation**

This abend is issued by module APSPDPV— the close request for the PSF resource libraries failed. PSF was trying to close the PSF resource libraries because no work is available for this printer and the close failed.

System action

PSF processing ends abnormally.

System programmer response

If Data Management messages preceded by IEC are received, use the information that is provided by these messages to recover from the open failure before you contact the IBM Support Center or use your electronic link with IBM service for assistance.

01FD**Explanation**

This abend is issued by module APSPDPSP— APSPDPSP was specifically waiting for an FSI order, and it was dispatched for work.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

01FF**Explanation**

This abend is issued by module APSPDPV— APSPDPV was in job trailer processing, but Document Processor set a flag that indicates otherwise.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0200**Explanation**

This abend is issued by module APSCINIT— APSCINIT was called to initialize Device Manager, but the page-fixed storage area was already assigned. APSCINIT interprets this as a redundant call to APSCINIT.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0201**Explanation**

This abend is issued by module APSCINIT— APSCINIT cannot get storage for the Device Manager page-fixed storage area. This error was detected for a channel-attached device, and the region is probably too small.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0202**Explanation**

This abend is issued by module APSCINIT— APSCINIT encountered an error while it was attempting to page-fix storage. An abend occurs if the PGFIX macro returns codes other than 0 or 8. An abend also occurs if a completion code is issued during the attempt to wait for the page fix, indicating that the attempt was unsuccessful.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system macros to determine why the macro failed or returned unexpected results.

0203**Explanation**

This abend is issued by module APSCINIT— APSCINIT cannot find the printer device DD name in the task I/O table (IEFTIOT1).

This abend occurs only when you are using a channel-attached printer; however, it might occur if you are using an SNA or TCP/IP attached printer. If the IPADDR, or APPLID and LUNAME parameters were not specified correctly in the PRINTDEV statement in the PSF startup procedure or in the Printer Inventory, this abend might occur.

This abend might occur for a printer that was added to the I/O configuration by use of the Dynamic Reconfiguration Management (DRM) function of MVS and JES2 or JES3 was not aware of the newly added device.

System action

PSF processing ends abnormally.

System programmer response

If DRM is being used to update the I/O configuration, ensure that the newly added device is defined to JES2 or JES3. If you are trying to use a TCP/IP printer, verify that the IPADDR parameter is set correctly and the LUNAME and APPLID parameters are not being used in the PRINTDEV statement or in the Printer Inventory. If you are trying to use an SNA printer, verify that the LUNAME and APPLID parameters are set correctly and the IPADDR parameter is not being used in the PRINTDEV statement or in the Printer Inventory.

For JES2, use the \$T or \$ADD command. For JES3, do a restart.

0204**Explanation**

This abend is issued by module APSCINIT— the SETLOCK macro issued a nonzero return code that notifies APSCINIT that it was unable to get or release the local lock while working with the task control block/data extent block (TCB/DEB) queue.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system macros to determine why the macro failed or returned unexpected results.

0205**Explanation**

This abend is issued by module APSCINIT— a DEBCHK macro failed while APSCINIT was attempting to add the data extent block (IEZDEB) to the data extent block (DEB) table.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system macros to determine why the macro failed or returned unexpected results.

0206**Explanation**

This abend is issued by module APSCINIT— a failure occurred while APSCINIT was trying to make the address space nonswappable. This is done only in direct-printing mode. A return code was issued while waiting for the SYSEVENT TRANSWAP macro, indicating that the attempt to make the address space nonswappable was unsuccessful.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system macros to determine why the macro failed or returned unexpected results.

0207**Explanation**

This abend is issued by module APSCINIT — Control block IHAASVT was above the line when attempting to start a channel-attached printer.

System action

PSF processing ends abnormally.

System programmer response

To use a channel-attached printer, remove IHAASVT from the CBLOC VIRTUAL31 statement in the DIAGxx SYS1.PARMLIB member. An IPL is required when you change the CBLOC statement in the DIAGxx member.

0208

Explanation

This abend is issued by module APSCINIT— For 3800 channel-attached devices, the GETMAIN for the OBR record failed. For an AFP1 channel-attached printer, the GETMAIN for the OBR record or the NACK buffer failed.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0209

Explanation

This abend is issued by module APSCINIT— APSCINIT encountered a GETMAIN failure for a Data Extent Block (DEB).

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is

for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

020A

Explanation

This abend is issued by module APSCINIT— APSCINIT was called to initialize Device Manager and detected an incorrect attachment type specification in the Common Control Block.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

020B

Explanation

This abend is issued by module APSCINIT— APSCINIT detected a UCB unit type value that is not supported by PSF. The value of UCBUNTYP or UCBDVCLS was not X'0E', X'0F', or X'08'. This abend reason code can also be issued when the PRINTDEV statement is missing the LUNAME parameter for an SNA-attached printer or the IPADDR parameter for a TCP/IP-attached printer.

System action

PSF processing ends abnormally.

020C

Explanation

This abend is issued by module APSCINIT— APSCINIT issued the sense ID CCW and it failed, or it issued the read configuration data CCW and it failed. This probably indicates that an I/O error was encountered when the sense ID or the read configuration data CCW was sent to the printer.

System action

PSF processing ends abnormally.

System programmer response

To determine the I/O error, check the MVS system console log or run the EREP report for the device.

Notify your system engineer that a hardware error might have occurred.

020D**Explanation**

This abend is issued by module APSCINIT— the TCP/IP port number is greater than 56,535.

System action

PSF processing ends abnormally.

System programmer response

Specify a value 5001 - 56,535 for the Port number parameter in the Printer Inventory or the PORTNO parameter on the PRINTDEV statement in the startup procedure for PSF.

0211**Explanation**

This abend is issued by module APSCTERM— APSCTERM detected an incorrect attachment type in the CCBCTYPE field of the common control block (CCB). The CCBCTYPE value must be C, S, or T.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0212**Explanation**

This abend is issued by module APSCTERM— the SETLOCK macro returned a nonzero return code that notifies APSCTERM that it was unable to get or release the local lock while working with the TCB/DEB (task control block — data extent block) queue.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system macros to determine why the macro failed or returned unexpected results.

0213**Explanation**

This abend is issued by module APSCTERM— DEBCHK failed while APSCTERM was attempting to delete the data extent block (DEB) from the DEB table.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains Data Management macros to determine why the macro failed or returned unexpected results.

0214**Explanation**

This abend is issued by module APSCTERM— APSCTERM encountered an error while it was attempting to make the address space swappable. This is done only in direct-printing mode. The SYSEVENT OKSWAP macro issued a return code while it was attempting to make the address space swappable; this indicates that the attempt was unsuccessful.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system macros to determine why the macro failed or returned unexpected results.

0216**Explanation**

This abend is issued by module APSCBMGR— APSCBMGR (the buffer manager module) detected a request that was inconsistent with the buffer state. One of these conditions might exist:

- An incorrect function was requested.
- An attempt was made to allocate a block larger than the buffer.
- An attempt was made to allocate a block in which the specified minimum was greater than the length requested.
- The specified minimum was greater than 0, and IDAWS were also provided.

- An attempted assign resulted in a set of IDAWS that referenced more than 8 KB.
- An attempt to free a block might cause the free-space size to exceed the buffer length.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0218

Explanation

This abend is issued by module APSCCDEV—APSCCDEV detected an incorrect attachment type in the CCBCTYPE field of the common control block (CCB). The CCBCTYPE value must be C, S, or T.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0219

Explanation

This abend is issued by module APSCSNIO—APSCSNIO detected a UCB unit type value that is not supported by PSF; the UCBUNTYP field had a value that was not X'0E' or X'0F'.

System action

PSF processing ends abnormally.

021A

Explanation

This abend is issued by module APSCCDEV— after multiple attempts, APSCCDEV was unable to refresh the printer characteristics. Failure was probably because of I/O errors encountered on the XOH-RPI, XOH-OPC, or STM command.

System action

PSF processing ends abnormally.

System programmer response

The printer is probably experiencing I/O errors. Check the printer to ensure that it is working correctly. If the printer is working correctly, restart PSF. If the printer has errors, correct them and restart PSF. If the printer errors persist, you might have to do an IML of the printer.

021B

Explanation

This abend is issued by module APSCCDEV—APSCCDEV was called before TCP/IP was initialized by APSNINIT. APSNINIT must be called before APSCIPRT.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. For assistance with this error code, consult your service representative in the IBMsupport Center, or use your electronic link with IBMservice.

0220

Explanation

This abend is issued by module APSCADJR— the DATALNG parameter that was passed to APSCADJR was not valid. The DATALNG parameter was too large. Valid values for this parameter range are 0 - 2048. If you are adding a Write Text, Write Image, or Load Font command, the value must be from 0 to X'7FFFFFFF'.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0222

Explanation

This abend is issued by module APSCADJR— a Transfer-in-Channel (TIC) command parameter was

passed to APSCADJR. An attempt was made to add the TIC command, but APSCADJR does not support TIC commands.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0223

Explanation

This abend is issued by module APSCADJR— the DATALNG parameter that was passed to APSCADJR was not valid. The DATALNG parameter in the channel command was negative. Valid values for this parameter range are 0 - 2048. If you are adding a Write Text, a Write Image, or a Load Font command, the value must be from 0 to X'7FFFFFFF'.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0224

Explanation

This abend is issued by module APSCADJR— APSCADJR detected two consecutive calls with different nonzero transaction IDs without an intervening call to APSCWRT.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0225

Explanation

This abend is issued by module APSCADJR— APSCADJR detected an incorrect printer family specification in the CCB; the field CCBCFMLY must have a valid value.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0226

Explanation

This abend is issued by module APSCADJR— APSCADJR requested buffer space from APSBMGR, but the request failed. APSCADJR then attempted to recover buffer space, but this request also failed, most likely because of a programming error.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0227

Explanation

This abend is issued by module APSCADJR— APSCADJR was called while in error state. This should not occur.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0228

Explanation

This abend is issued by module APSCADJR—APSCADJR requested buffer space from APSBMGR, but the request failed. APSCADJR then attempted to recover buffer space by using two recovery routines, but this request also failed, probably because of a storage shortage.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0230**Explanation**

This abend is issued by module APSCRDRV—APSCRDRV was called while I/O was still in progress. APSCRDRV must be called only during I/O error recovery to redrive an inactive channel program.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0231**Explanation**

This abend is issued by module APSCRDRV—APSCRDRV received an incorrect parameter that specifies the point at which to begin the redrive. The only valid parameters are 0, 1, and 2. APSCRDRV must be called only during an I/O error recovery to redrive an inactive channel program.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0232**Explanation**

This abend is issued by module APSCRDRV—APSCRDRV detected an incorrect printer family specification in the CCB. The field CCBCFMLY must have a valid value.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0233**Explanation**

This abend is issued by module APSCRDRV—APSCRDRV was called while not in error state. This is a program logic error.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0234**Explanation**

This abend is issued by module APSCOPCI— the 42x4 printer has an unsupported EC level.

System action

PSF processing ends abnormally.

System programmer response

Upgrade the 42x4 microcode to a supported level.

0235

Explanation

This abend is issued by module APSCOPCI—APSCOPCI cannot get storage for the multiple output bin array, the Setup ID area, the medium name string, or the medium OID string.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0236

Explanation

This abend is issued by module APSCINFO or APSCOPCI—APSCINFO or APSCOPCI cannot get storage for the Device Attribute Table input bin information entry.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode,

increase the REGION parameter used in the PSF startup procedure.

0237

Explanation

This abend is issued by module APSCINFO—APSCINFO detected a printer that does not support the define user area (DUA) printer command while the user printable area (UPA) is in effect. This abend can occur if the SYSAREA is enabled and you are attempting to use a nonguaranteed printer. For more information about these areas, see [PSF for z/OS: Security Guide](#).

System action

PSF processing ends abnormally.

0238

Explanation

This abend is issued by module APSCINFO—APSCINFO detected an incorrect printer family specification in the CCB.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0239

Explanation

This abend is issued by module APSCOPCI— at device initialization, APSCOPCI detected in the OPC record that the printer was unable to detect the media size loaded in the printer. This abend occurred because of a hardware failure in the printer's media-size sensors.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

If the printer has removable paper cassettes or bins, ensure that the cassettes or bins are fully inserted into the printer.

023A**Explanation**

This abend is issued by module APSCOPCI—APSCOPCI detected a two-channel switch configuration that is not supported by PSF. Any configuration that allows loosely coupled switching to actively occur causes this abend.

System action

PSF processing ends abnormally.

023B**Explanation**

This abend is issued by module APSCSTMI— the printer does not support the DC/1 function set required by IPDS.

System action

PSF processing ends abnormally.

023C**Explanation**

This abend is issued by module APSCOPCI— the Unit Base returned in the XOA Obtain Printer Characteristic acknowledge reply was not 'X'00'.

System action

PSF processing ends abnormally.

023D**Explanation**

This abend is issued by module APSCSTMI or APSCOPCI— APSCSTMI or APSCOPCI detected that coded fonts were not designated as supported in the Sense, Type, and Model acknowledge reply. Or, APSCOPCI detected that symbol sets were not designated as supported in the Obtain Printer Characteristics acknowledge reply.

System action

PSF processing ends abnormally.

023E**Explanation**

This abend is issued by module APSCSTMI—APSCSTMI detected that PT/1, PT/2, or PT/3 was not

designated as supported by the Sense, Type, and Model acknowledge reply.

System action

PSF processing ends abnormally.

023F**Explanation**

This abend is issued by module APSCOPCI—APSCOPCI cannot get storage for the Selectable Medium Modification information entry.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0240**Explanation**

This abend is issued by module APSCRSET—APSCRSET was called while I/O activity was still in progress.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0241**Explanation**

This abend is issued by module APSCRSET—APSCRSET detected an incorrect attachment type in

the CCBCTYPE field of the common control block (CCB). The CCBCTYPE value must be C, S, or T.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0242

Explanation

This abend is issued by module APSCOPCI— the actual medium presentation space width, actual medium presentation space length, Xm extent of the physical printable area in L-units, or Ym extent of the physical printable area in L-units returned on the X'0A' Obtain Printer Characteristics acknowledge reply was X'0000'.

System action

PSF issues message APS6502I and abnormally ends.

System programmer response

This PSF abend reason code indicates a logic error in the microcode of the printer. Consult your hardware service representative. This is not a PSF logic error. See message APS6502I for additional information.

0243

Explanation

This abend is issued by module APSCOPCI— the Printable-Area Self-Defining field was not in the XOA Obtain Printer Characteristics acknowledge reply. Thus no input bins were defined.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a logic error in the microcode of the printer. Consult your hardware service representative. This is not a PSF logic error.

0244

Explanation

This abend is issued by module APSCOPCI— no enabled non-inserter input bins were defined in the

Printable-Area Self-Defining field that was returned in the XOA Obtain Printer Characteristics acknowledge reply.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a configuration error at the printer. A non-inserter input bin must be enabled.

0245

Explanation

This abend is issued by module APSOCPCI— APSCOPCI detected that PSF was connected to the printer with an intermediate device of DPF or RPM3, and the printer was in automatic resolution mode.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates that the printer was in automatic resolution mode and that PSF was connected to the printer via DPF or RPM3. DPF and RPM3 do not support a printer in automatic resolution mode.

0246

Explanation

This abend is issued by module APSCOPCI— APSCOPSCI detected that the Obtain Printer Characteristics (OPC) response in the Printable Area Self-Defining field contained multiple media ID entries with the same media ID type value. The media ID type value MUST be different for each entry.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a logic error in the microcode of the printer. Consult your hardware service representative. This is NOT a PSF logic error.

0247

Explanation

This abend is issued by module APSCOCPI—APSCOPCI cannot get storage for the device appearance support list.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-mode, increase the REGION parameter used in the PSF startup procedure.

0248**Explanation**

This abend is issued by module APSCOPCI—APSCOPCI cannot get storage for a registration ID link list element.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0249**Explanation**

This abend is issued by module APSCOPCI or APSCRPII—APSCOPCI or APSCRPII cannot get

storage for a Group Operation Link List element or subelement.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

024A**Explanation**

This abend is issued by module APSCSTMI or APSCOPCI—APSCSTMI detected an incorrect length value in the Sense Type and Model acknowledge reply. Or, APSCOPCI detected an incorrect length value in the Obtain Printer Characteristics acknowledge reply.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible error in the printer microcode, but might be a PSF logic error. Contact your IBM hardware service representative.

0250**Explanation**

This abend is issued by module APSCCOMP— the last Channel Command Word (CCW) processed was not a NOP CCW, a SIB CCW, or a READ CCW.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM

Support Center or use your electronic link with IBM service for assistance with this error code.

025A**Explanation**

This abend is issued by module APSCNORS— the response timer expired before a response was received from the printer when No response action = Terminate was specified in the Printer Inventory or NORESP=TERMINATE was specified on the PRINTDEV statement.

System action

This abend is preceded by message APS940I with *prtnnnn* identifying the FSA for which the abend occurred. The FSA for the printer is stopped.

System programmer response

Determine why the printer is not responding and correct the problem. Then, restart the FSA.

0260**Explanation**

This abend is issued by module APSCCLR— APSCCLR printed too many blank pages during a nonprocess runout (NPRO). The failure might be because of an error in the microcode that updates the printer counters; or it might occur because the Forward Spacing flag was left on during the NPRO.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error in either the microcode of the printer or in PSF. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0261**Explanation**

This abend is issued by module APSCCLR— APSCCLR detected an incorrect input parameter for a channel-attached printer. The function parameter was not NPRO, PBD, or NOFUNCTION.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0262**Explanation**

This abend is issued by module APSCCLR— APSCCLR detected an incorrect attachment type in the CCBCTYPE field of the common control block (CCB). The value must be C, S, or T.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0263**Explanation**

This abend is issued by module APSCCLR— APSCCLR was called with an incorrect input parameter.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0264**Explanation**

This abend is issued by module APSCCLR— APSCCLR was called for a printer inoperative condition with an action code X'22' on a TCP/IP connection.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates that a printer condition occurred from which the printer cannot recover. Contact the person responsible for the remote printer.

0270**Explanation**

This abend is issued by module APSCSNA— APSCSNA was called while PSF was driving a channel-attached printer. APSCSNA is used only for Systems Network Architecture-attached printers. This is probably a Device Manager logic error.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0271**Explanation**

This abend is issued by module APSCSNA— APSCSNA STRTPPCC function was called at a time when the PSF state was not valid.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0272**Explanation**

This abend is issued by module APSCSNA— APSCSNA ENDPPCC function was called at a time when the PSF state was not valid.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0273**Explanation**

This abend is issued by module APSCSNA— APSCSNA ESTBSESS function was called at a time when the PSF state was not valid.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0274**Explanation**

This abend is issued by module APSCSNA— APSCSNA HALTSESS function was called at a time when the PSF state was not valid.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0275**Explanation**

This abend is issued by module APSCSNA— APSCSNA SEND function was called at a time when the PSF state was not valid.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM

Support Center or use your electronic link with IBM service for assistance with this error code.

0276**Explanation**

This abend is issued by module APSCSNA— APSCSNA RECEIVE function was called at a time when the PSF state was not valid.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0277**Explanation**

This abend is issued by module APSCSNA— APSCSNA SESSYNC function was called at a time when the PSF state was not valid.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0278**Explanation**

This abend is issued by module APSCSNA— the END PPCC function in the module APSCSNA detected a logic error after it issued the TERMINATE verb. The return code cannot be mapped.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0279**Explanation**

This abend is issued by module APSCSNA— the module APSCSNA detected a logic error when it was attempting to issue the TERMINATE TYPE (NORMAL) verb.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

027A**Explanation**

This abend is issued by module APSCSNA— the module APSCSNA detected a logic error after it issued the DEACTIVATE TYPE (NORMAL) verb to PPCC. The return code from DEACTIVATE cannot be mapped.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

027B**Explanation**

This abend is issued by module APSCSNA— the SEND_DATA function of the module APSCSNA detected that the length of data to be sent to the printer was greater than 32,765 bytes.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

027C

Explanation

This abend is issued by module APSCSNA— APSCSNA detected a logic error when it was attempting to issue the DEACTIVATE TYPE (NORMAL) verb. DEACTIVATE TYPE (NORMAL) must be issued after the DEALLOCATE TYPE (LOCAL) verb.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

027D**Explanation**

This abend is issued by module APSCSNA— the HALT_SESS function in APSCSNA detected a logic error after it issued the DEALLOCATE TYPE (FLUSH) verb to PPCC. The return code from DEALLOCATE cannot be mapped.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

027E**Explanation**

This abend is issued by module APSCSNA— APSCSNA detected an incorrect value for the internal state.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

027F**Explanation**

This abend is issued by module APSCSNA— APSCSNA detected a logic error after it issued the PRE_RECEIVE verb to PPCC. The return code cannot be mapped.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0280**Explanation**

This abend is issued by module APSCINIT— APSCINIT cannot get storage for the Device Manager control block for a Systems Network Architecture-attached printer. The region is probably too small, as this is one of the first requests for storage during device initialization.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0281**Explanation**

This abend is issued by module APSCSNA— the HALT_SESS function of the module APSCSNA detected a logic error while attempting to issue the DEACTIVATE TYPE (NORMAL) command. The DEALLOCATE TYPE (NORMAL) verb should be issued after the DEALLOCATE TYPE (ABEND) verb.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0282**Explanation**

This abend is issued by module APSCSNA— APSCSNA was called with an incorrect function. The valid values are defined in APSCSNA.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0283**Explanation**

This abend is issued by module APSCSNA— APSCSNA detected a logic error when it attempted to map the internal state it calculated to an external PSF state.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0284**Explanation**

This abend is issued by module APSCSNA— APSCSNA detected a logic error. An incorrect internal state was calculated by the RECDATA function.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0285**Explanation**

This abend is issued by module APSCSNA— APSCSNA detected a logic error. An incorrect internal state was calculated by the SESSYNC function.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0287**Explanation**

This abend is issued by module APSCSNA— APSCSNA detected a second PGMERR return code from PPCC after it issued the RECEIVE and WAIT verb when going to Send state.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

028A**Explanation**

This abend is issued by module APSCCDEV— APSCCDEV was issued before the Page Printer Communications Component was loaded (by APSCINIT). APSCINIT must be called before APSCIPRT.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

028C**Explanation**

This abend is issued by module APSCIPRT— APSCIPRT detected an incorrect printer family specification in the field CCBCFMLY of the CCB.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

028D**Explanation**

This abend is issued by module APSCIPRT— APSCIPRT detected an incorrect LU Type for a Systems Network Architecture-attached printer; the LU type must be LU 1 or LU 6.2. Or, APSCIPRT detected an incorrect attachment type in the CCBCTYPE field of the common control block (CCB); the CCBCTYPE value must be C, S, or T.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. For assistance related to this error code, consult your service representative in the IBMSupport Center.

0291**Explanation**

This abend is issued by module APSCTERM— APSCTERM detected that the DELETE macro failed to delete the Page Printer Communications Component load module.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system macros to determine why the macro failed or returned unexpected results.

02A0**Explanation**

This abend is issued by module APSCADJR— an incorrect parameter was passed to APSCADJR for a Systems Network Architecture-attached printer; the data length of the command was too large. The DATALNG parameter must be 0 - 32758 bytes (if correlation IDs are supported) or 0 - 32760.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02A1**Explanation**

This abend is issued by module APSCADJR— APSCADJR detected an incorrect attachment type in the CCBCTYPE field of the common control block (CCB). The CCBCTYPE value must be C, S, or T.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02A2**Explanation**

This abend is issued by module APSCADJR— the Systems Network Architecture session or the TCP/IP conversation was disconnected, or else the printer was not initialized upon entry to APSCADJR. APSCCDEV must be called and successfully completed before any module other than APSCIPRT can call APSCADJR.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02A3**Explanation**

This abend is issued by module APSCADJR— an incorrect combination of the PSF state and the APSCSNA return code resulted after APSCSNA returned to APSCADJR. Or, an incorrect combination of the PSF state and the APSTCP return code resulted after APSTCP returned to APSCADJR.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02A4**Explanation**

This abend is issued by module APSCADJR— APSCADJR called APSCCOMP to process an exception reported from a Systems Network Architecture printer. APSCCOMP cannot return to a zero return code unless PSF is in Synchronous Order processing. PSF ignores certain exceptions in Synchronous Order processing.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02A5**Explanation**

This abend is issued by module APSTCP— the attachment type is not valid. The attachment must be TCP/IP.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02A6**Explanation**

This abend is issued by module APSTCP— APSTCP was called with an incorrect external state.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02A7**Explanation**

This abend is issued by module APSTCP— APSTCP was called with an incorrect external state (not TCP_RESET) for TCPINIT (printer initialization).

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02A8**Explanation**

This abend is issued by module APSTCP— APSTCP was called with an incorrect external state (not TCP_CONVLOST) for TCPLINK (TCP/IP socket connection).

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02A9**Explanation**

This abend is issued by module APSTCP— APSTCP was called with an incorrect external state (not TCP_SEND, TCP_RECEIVE, or TCP_CONVLOST) for TCPSHUT (shutdown) or with an incorrect external state (not TCP_CONVLOST) for TCPTERM (terminate).

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02AA**Explanation**

This abend is issued by module APSTCP— APSTCP was called with an incorrect external state (not TCP_SEND) for TCPSND (sending data).

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02AB**Explanation**

This abend is issued by module APSTCP— APSTCP was called with an incorrect external state (not TCP_RECEIVE) for TCPRECV (receiving data).

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02AC**Explanation**

This abend is issued by module APSTCP— APSTCP was called with an incorrect function.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02AE**Explanation**

This abend is issued by module APSTCP— the IPDS data length is greater than 32,767.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02AF**Explanation**

This abend is issued by module APSTCP— no data is in the receive buffer.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02B0

Explanation

This abend is issued by module APSCCOMP— the Device Manager subcomponent of PSF was not in SEND or RECEIVE state when APSCCOMP was issued outside of initialization for a Systems Network Architecture- or TCP/IP-attached printer.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02B1**Explanation**

This abend is issued by module APSCSNA— APSCSNA detected a second program error return code from the PPCC after it issued a RECEIVE and WAIT verb to receive data.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02B2**Explanation**

This abend is issued by module APSCCOMP— APSERRM did not call APSCRSET or APSCRDRV before it returned to APSCCOMP. APSCCOMP probably has a logic error.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02B3**Explanation**

This abend is issued by module APSCCOMP— APSCCOMP detected an incorrect acknowledgment type. This is probably a Page Printer Communications Component logic error.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02B4**Explanation**

This abend is issued by module APSCCOMP— APSCCOMP detected an incorrect acknowledgment record (incorrect command code).

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02B5**Explanation**

This abend is issued by module APSCCOMP— APSCCOMP detected an incorrect attachment type specification in the CCB.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02B6**Explanation**

This abend is issued by module APSCCOMP— APSCCOMP detected a null acknowledgment from a

channel attached printer. The printer returned a null ACK record. A null ACK record means that no page counters were returned in the response from the device. PSF requires page counters to continue processing pages.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error within the microcode of the printer. Contact your IBM service representative to make sure that your printer is at the latest microcode level.

02B7

Explanation

This abend is issued by module APSCCOMP—APSCCOMP detected an incorrect printer family specification in the CCB.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02B8

Explanation

This abend is issued by module APSCCOMP— the Channel-End appendage received control. It detected Channel-End status without Device-End status in an otherwise normal channel program ending.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02B9

Explanation

This abend is issued by module APSCCOMP—APSCCOMP was called while the PSF Device Manager was in error state.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02BA

Explanation

This abend is issued by module APSCCOMP—APSCCOMP detected a protocol error. PPEC indicated that the printer or controller recovered incorrectly from an intervention-required condition at the printer. The SNA level recovery (sending -rsp 0802) was done without first sending the required IPDS NACK. The IPDS NACK is required in order for PSF to reposition correctly. Examples of intervention-required conditions include paper jams and running out of paper.

System action

PSF tries to recover from this abend by restarting. If PSF successfully restarts, message APS057I is issued.

System programmer response

This PSF abend reason code indicates a logic error in the microcode of either the printer or the SNA controller. Consult your hardware service representative. This is not a PSF logic error.

02BB

Explanation

This abend is issued by module APSCCOMP— after APSCSNA returned to APSCCOMP, APSCCOMP detected an incorrect combination of the PSF state and the APSCSNA return code. Or, APSCCOMP detected an incorrect combination of the PSF state and the APSCTCP return code after APSCTCP returned to APSCCOMP.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02BC**Explanation**

This abend is issued by module APSCCOMP—APSCCOMP detected multiple acknowledgment records returned in a single Systems Network Architecture response.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02BE**Explanation**

This abend is issued by module APSCCOMP—APSCCOMP detected that the PSF-simulated received page counter was not equal to the received page counter returned from the printer in a positive acknowledgment (ACK) record.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend is most likely caused by a logic error in the printer microcode, but might be a PSF logic error. Consult your hardware service representative. See message APS6503I for additional information.

02BF**Explanation**

This abend is issued by module APSCCOMP—APSCCOMP detected an incorrect negative acknowledgment record (incorrect sense byte or page counter format).

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error within the microcode of the printer. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02C0**Explanation**

This abend is issued by module APSCWRT— the Device Manager subcomponent of PSF was not in SEND or RECEIVE state when APSCWRT was issued outside of initialization for a Systems Network Architecture- or TCP/IP-attached printer. This is a logic error.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02C1**Explanation**

This abend is issued by module APSCWRT— APSCWRT detected an incorrect attachment type in the CCBCTYPE field of the common control block (CCB). The value must be C, S, or T.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02C2**Explanation**

This abend is issued by module APSCWRT— APSCWRT detected an incorrect printer family specification in the common control block (CCB) field CCBCFMLY.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02C3**Explanation**

This abend is issued by module APSCWRT— APSCWRT was called while in error state.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02D0**Explanation**

This abend is issued by module APSCSYNC— the Device Manager subcomponent of PSF was not in SEND or RECEIVE state when APSCSYNC was issued for a Systems Network Architecture- or TCP/IP- attached printer.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02D1**Explanation**

This abend is issued by module APSCSNIO— the Device Manager subcomponent of PSF issued a sense type and model command and discovered that the printer type changed while PSF was running.

System action

PSF processing ends abnormally.

02D2**Explanation**

This abend is issued by module APSCSYNC— APSCSYNC detected an incorrect attachment type in the CCBCTYPE field of the common control block (CCB). The CCBCTYPE value must be C, S, or T.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02D3**Explanation**

This abend is issued by module APSCSYNC— after APSCSNA returned to APSCSYNC, APSCSYNC detected an incorrect combination of the PSF state and the APSCSNA return code.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02E0**Explanation**

This abend is issued by module APSCPRCT— APSCPRCT was called to support a device with an attachment type other than channel attachment.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02E1

Explanation

This abend is issued by module APSCPRCT—APSCPRCT was called with an incorrect function requested.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02E2**Explanation**

This abend is issued by module APSCPRCT— an attempt failed to assign a CCW to end a transaction. APSCPRCT must always be able to assign one CCW before it fills the CCW buffer.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02E3**Explanation**

This abend is issued by module APSCPRCT—APSCPRCT detected an incorrect printer family specification in the CCB field CCBCFMLY.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02E5**Explanation**

This abend is issued by module APSCPRCT—APSCPRCT detected an incorrect response

(acknowledgment) from a local channel-attached printer or a channel extender to which the channel-attached printer is connected.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts. Message APS920I is issued when this abend occurs.

System programmer response

This PSF abend is most likely because of a printer microcode problem, but might be a PSF logic error. Consult your hardware service representative.

If the printer is channel-attached to a channel extender, this is probably a channel extender microcode problem. Contact your channel extender hardware service representative. See message APS920I for additional information

02E6**Explanation**

This abend is issued by module APSCPRCT—APSCPRCT detected that the page counter that is received from the printer does not match the PSF-simulated received page counter. Either the printer did not increment the page counter by 1 or it is a PSF logic error.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error in either the microcode of the printer or in PSF. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02E7**Explanation**

This abend is issued by module APSCCTIM— the STIMER macro failed to set a timer.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system macros to determine why the macro failed or returned unexpected results.

02E9**Explanation**

This abend is issued by module APSCSNIO—APSCSNIO was called with an incorrect function request.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02EA**Explanation**

This abend is issued by module APSCSNIO—APSCSNIO detected a request to do a READ request while not in I/O error state. Either an I/O error did not occur, or APSCRDRV or APSCRSET was called, and cleared the error, before APSCSNIO was called.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02EB**Explanation**

This abend is issued by module APSCSNIO—APSCSNIO detected a null ACK record on return from the printer.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts. Message APS920I is issued when this abend occurs.

System programmer response

This PSF abend is most likely because of a printer microcode problem, but might be a PSF logic error. Consult your hardware service representative.

If the printer is channel-attached to a channel extender, this is probably a channel extender microcode problem. Contact your channel extender hardware service representative. See message APS920I for additional information

02EC**Explanation**

This abend is issued by module APSCSNIO— the PSF state must be SEND when APSCSNIO is called to do the selected function.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02ED**Explanation**

This abend is issued by module APSCSNIO— the APSCSNIO SENSEID function detected an incorrect condition. These conditions must be true for PSF when APSCSNIO is called to do the SENSEID function:

- The device contact indicator is set OFF.
- The PSF Device Manager initialization indicator is set ON.
- The ignore residual errors indicator is set ON.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02EE

Explanation

This abend is issued by module APSCSNIO— the APSCSNIO SENSEID function was unable to complete its function successfully. The printer did not respond to the first PSF IPDS command (STM). The SNA or TCP/IP connection might have failed, or a printer hardware error might be the cause. No IPDS information on the reason for the failure is available.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This abend indicates a possible printer hardware error. Correct any problems indicated on the printer operator panel. Correct any outstanding intervention conditions at the printer. Verify that a good network path to the printer exists. Re-IML the printer. If the problem persists, consult your systems engineer for assistance in correcting this error.

02EF**Explanation**

This abend is issued by module APSCSNIO— the APSCSNIO READ function was unable to obtain a valid acknowledgment record from the printer.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error within the microcode of the printer. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02F0**Explanation**

This abend is issued by module APSCSNIO— the APSCSNIO ONECMD function was unable to obtain a valid acknowledgment record from the printer.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error within the microcode of the printer. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02F1**Explanation**

This abend is issued by module APSCSNIO— after APSCSNA returned to APSCSNIO, APSCSNIO detected an incorrect combination of the PSF state and the APSCSN return code. Or, APSCSNIO detected an incorrect combination of the PSF state and the APSCTCP return code after APSCTCP returned to APSCSNIO.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02F2**Explanation**

This abend is issued by module APSCSNIO— APSCSNIO detected a looping condition caused by consecutive PPCC RETRY return codes.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02F3**Explanation**

This abend is issued by module APSCSNIO— either APSCSNIO received an incorrect acknowledgment record type from the printer, or the device manager subcomponent of PSF issued a sense type and model command. Then, the device manager subcomponent discovered that the printer type changed to a printer

that was using a different acknowledgment format while PSF was running.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error within the microcode of the printer. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02F4

Explanation

This abend is issued by module APSCSNIO—APSCSNIO detected an incorrect printer family in the Common Control Block.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02F5

Explanation

This abend is issued by module APSCSNIO—APSCSNIO detected an incorrect attachment type in the Common Control Block (CCB) field CCBCFMLY.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02F6

Explanation

This abend is issued by module APSCSNIO— the APSCSNIO ONECMD function was called to send an IPDS command that the APSCSNIO ONECMD function does not support.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02F7

Explanation

This abend is issued by module APSCSNIO—APSCSNIO detected multiple acknowledgment records returned in a single Systems Network Architecture response or returned in a single TCP/IP response.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts. Message APS920I is issued when this abend occurs. This abend is issued only when you are using a SNA or TCP/IP attached printer.

System programmer response

This PSF abend reason code is most likely caused by a logic error in the printer microcode, but might be a PSF logic error. Consult your hardware service representative. See message APS920I for additional information.

02F8

Explanation

This abend is issued by module APSCSNIO—APSCSNIO detected an incorrect acknowledgment record (incorrect command code). If attached to a channel printer, the LMOD IGE0000E might not be found. IGE0000E is the PSF supplied ERP for non-3800-channel-attached printers.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts. Message APS920I is issued when this abend occurs.

System programmer response

This PSF abend is most likely caused by a logic error in the microcode of the printer, but might be a PSF logic error. Consult your hardware service representative. See message APS920I for additional information.

02F9**Explanation**

This abend is issued by module APSCSNIO—APSCSNIO is unable to determine and set the printer family based on the value that is returned in the acknowledgment record type field; or else the printer family field in the Common Control Block does not match the previously determined printer family.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code results from a possible logic error in either the microcode of the printer or in PSF. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

02FA**Explanation**

This abend is issued by module APSCSNIO—APSCSNIO detected that the command response length returned by the printer was greater than the maximum allocated buffer length.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend is most likely caused by a logic error in the microcode of the printer, but it might be a PSF logic error. Consult your hardware service representative. See message APS945I for additional information.

02FF**Explanation**

This abend is issued by module APSCCDEV—APSCCDEV was unable to establish contact with the printer after multiple attempts. Failure to make contact might be because of a permanent printer hardware error, an uncleared intervention-required condition at the printer, or a network problem.

System action

PSF processing ends abnormally.

System programmer response

The printer might require a hardware reset, or the printer might still be in the middle of printing pages of a previous job from a previous SNA session. Allow the printer time to complete processing the previous job before it attempts to establish contact again. Clear any intervention-required condition at the printer. Then, restart PSF to try to establish contact again. If these actions do not fix the problem, consult your service representative in the IBMSupport Center, or use your electronic link with IBMservice for assistance related to this error code.

0300**Explanation**

This abend is issued by module APSQINIT— APSQINIT was called to initialize Pending Page Queue (PPQ) manager. However, PPQ manager was already initialized, and the PPQ control block, APSQPPQ, already exists.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0301**Explanation**

This abend is issued by module APSQINIT— APSQINIT was unable to get space for the Pending Page Queue (PPQ) control block, APSQPPQ.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode,

increase the REGION parameter used in the PSF startup procedure.

0310**Explanation**

This abend is issued by module APSQDACT— APSQDACT cannot find the Pending Page Queue (PPQ) control block, APSQPPQ, for one of these reasons:

- APSQDACT was called before PPQ was initialized.
- An alteration caused the pointer to APSQPPQ to be incorrect.
- An alteration caused APSQPPQ to be incorrect.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0311**Explanation**

This abend is issued by module APSQDACT— APSQDACT received an incorrect input parameter. Either PPQPTR or COUNT equal zero, or PPQPTR is not pointing to a valid PPQ entry on the active queue.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0320**Explanation**

This abend is issued by module APSQENQ— APSQENQ cannot find the Pending Page Queue (PPQ) control block, APSQPPQ, for one of these reasons:

- APSQENQ was called before PPQ was initialized.
- An alteration caused the pointer to APSQPPQ to be incorrect.
- An alteration caused APSQPPQ to be incorrect.

PPQ must be initialized before the Device Manager (see APSPPIFA).

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0321**Explanation**

This abend is issued by module APSQENQ— APSQENQ was called to build and queue a Pending Page Queue (PPQ) entry on the active queue. However, the PPQ exceeded the maximum size of 65,535 entries.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0322**Explanation**

This abend is issued by module APSQENQ— APSQENQ was unable to get space for a Pending Page Queue (PPQ) entry.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode,

increase the REGION parameter used in the PSF startup procedure.

0323**Explanation**

This abend is issued by module APSQENQ— APSQENQ received an incorrect input parameter. The input to APSQENQ must be a positive transaction ID.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0324**Explanation**

This abend is issued by module APSQENQ— incorrect pointer data caused errors in repositioning in the message data set.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0325**Explanation**

This abend is issued by module APSQENQ— the block and record count of the last record written to the current message data set was not the same in both the DIA (DIAMREP) and the current message RRB (RRBREP).

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0331**Explanation**

This abend is issued by module APSQDEQ— an error was reported by APSIPUT in freeing the message data set buffers.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0332**Explanation**

This abend is issued by module APSQDEQ— an error was reported by APSQDEQ in dequeuing and freeing the message data set record resource block (RRB).

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0333**Explanation**

This abend is issued by module APSQDEQ— APSQDEQ received a transaction ID higher than that of the first incomplete PPQ entry. A routine called APSQDEQ after a previous required call was omitted.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0334

Explanation

This abend is issued by module APSQDEQ— APSQDEQ detected a form ID error: the printer incremented or decremented an ID erroneously.

System action

PSF processing ends abnormally.

System programmer response

Apply maintenance to the microcode for the 3800 printer to bring it up to current levels.

0335**Explanation**

This abend is issued by module APSQDEQ— routing of the message data set to a SYSOUT data set failed. To determine the reason for the failure, see the accompanying error message on the operator console.

System programmer response

To determine the appropriate action, see the System Programmer Response for the accompanying error message on the operator console.

0340**Explanation**

This abend is issued by module APSQIMPL— APSQIMPL cannot find the Pending Page Queue (PPQ) control block, APSQPPQ, for one of these reasons:

- APSQIMPL was called before PPQ was initialized.
- An alteration caused the pointer to APSQPPQ to be incorrect.
- An alteration caused APSQPPQ to be incorrect.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

03D0**Explanation**

This abend is issued by module APSHHERI— one of the multiple data set requests sent by AFP Download Plus

received a negative response with a recovery indicator that specifies that the remote system is shutting down.

System action

AFP Download Plus processing ends abnormally.

System programmer response

The AFP Download Plus abend reason code indicates a possible logic error with the remote system or with AFP Download Plus.

Contact your remote system service representative, contact your service representative in the IBM Support Center, or use your electronic link with IBM service.

03D1**Explanation**

This abend is issued by module APSHHERI— the End Compression request received a negative response with a recovery indicator that specifies that the remote system is shutting down.

System action

AFP Download Plus processing ends abnormally.

System programmer response

The AFP Download Plus abend reason code indicates a possible logic error with the remote system or with AFP Download Plus.

Contact your remote system service representative, contact your service representative in the IBM Support Center, or use your electronic link with IBM service.

03D2**Explanation**

This abend is issued by module APSHHERI— the Checkpoint request received a negative response with a recovery indicator that specifies that the remote system is shutting down.

System action

AFP Download Plus processing ends abnormally.

System programmer response

The AFP Download Plus abend reason code indicates a possible logic error with the remote system or with AFP Download Plus.

Contact your remote system service representative, contact your service representative in the IBM Support Center, or use your electronic link with IBM service.

03D3**Explanation**

This abend is issued by module APSHHERI— the EOF request received a negative response with a recovery indicator that specifies that the remote system is shutting down.

System action

AFP Download Plus processing ends abnormally.

System programmer response

The AFP Download Plus abend reason code indicates a possible logic error with the remote system or with AFP Download Plus.

Contact your remote system service representative, contact your service representative in the IBM Support Center, or use your electronic link with IBM service.

03D4**Explanation**

This abend is issued by module APSHHERI— the Checkpoint Restart header request received a negative response from the remote system.

System action

AFP Download Plus processing ends abnormally.

System programmer response

The AFP Download Plus abend reason code indicates a possible logic error with the remote system.

Contact your remote system service representative for assistance.

03D5**Explanation**

This abend is issued by module APSHHERI— the Checkpoint Restart byte count received a negative response from the remote system.

System action

AFP Download Plus processing ends abnormally.

System programmer response

The AFP Download Plus abend reason code indicates a possible logic error with the remote system.

Contact your remote system service representative for assistance.

03D6**Explanation**

This abend is issued by module APSHHERI— a bad request type was detected.

System action

AFP Download Plus processing ends abnormally.

System programmer response

The AFP Download Plus abend reason code indicates a possible logic error with AFP Download Plus.

Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance.

03D7**Explanation**

This abend is issued by module APSHHERI— the remote system issued an extended receiver information response with a recovery indicator that is not supported.

System action

AFP Download Plus processing ends abnormally.

System programmer response

The AFP Download Plus abend reason code indicates a possible logic error with the remote system.

Contact your remote system service representative for assistance.

03D8**Explanation**

This abend is issued by module APSHHRSP— an unknown response was received from the remote system.

System action

AFP Download Plus processing ends abnormally.

System programmer response

The AFP Download Plus abend reason code indicates a possible logic error with the remote system.

Contact your remote system service representative for assistance.

03D9

Explanation

This abend is issued by module APSHHDET— a response was received from the remote system that did not support encoding of the data when encoding of the data was active.

System action

AFP Download Plus processing ends abnormally.

System programmer response

The AFP Download Plus abend reason code indicates a possible logic error with the remote system.

Contact your remote system service representative for assistance.

03DA**Explanation**

This abend is issued by module APSHHDET or APSHHQSC— the FSA is set to send separator pages but the remote system connected to AFP Download Plus does not support multiple data set requests.

System action

AFP Download Plus processing ends abnormally.

System programmer response

If this FSA does not need to send separator pages, set the Send separator pages parameter to NO. Otherwise, send the job to a remote system that supports multiple data set requests.

03DB**Explanation**

This abend is issued by module APSHHQSC— the FSA is set to send separator pages; however, the parameter for multiple data set support, the Data set grouping parameter in the Printer Inventory or dataset-grouping parameter in the AFPPARMS control statement, is not set for the FSA, which is required to send separator pages.

System action

AFP Download Plus processing ends abnormally.

System programmer response

If this FSA does not need to send separator pages, set the Send separator pages parameter in the Printer Inventory or the send-separator-pages parameter in the AFPPARMS control statement to NO.

Otherwise, set the Data set grouping parameter in the Printer Inventory or the dataset-grouping parameter in the AFPPARMS control statement to YES.

03DC**Explanation**

This abend is issued by module APSHHQSC— the receiving system cannot receive jobs with multiple data sets and form definitions that are not inline. The FSA was set to send multiple data set jobs and to not include form definitions inline in the Printer Inventory or the AFPPARMS control statement.

System action

AFP Download Plus processing ends abnormally.

System programmer response

If the FSA does not need to send multiple data set jobs, set the Data set grouping parameter in the Printer Inventory or the dataset-grouping parameter in the AFPPARMS control statement to NO. Otherwise, set the Send messages on failure parameter in the Printer Inventory or the send-messages-on-failure parameter in the AFPPARMS control statement to ALL.

03DD**Explanation**

This abend is issued by module APSHHERI — the Start Multi File Transfer (SMFT) request received a negative response with a recovery indicator that specifies that the remote system is shutting down.

System action

AFP Download Plus processing ends abnormally.

System programmer response

This AFP Download Plus abend reason code indicates a possible logic error with the remote system or AFP Download Plus.

Contact your remote system service representative, contact your service representative in the IBM Support Center, or use your electronic link with IBM service.

03DE**Explanation**

This abend is issued by module APSHHERI — the End Multi File Transfer (EMFT) request received a negative response with a recovery indicator that specifies that the remote system is shutting down.

System action

AFP Download Plus processing ends abnormally

System programmer response

This AFP Download Plus abend reason code indicates a possible logic error with the remote system or AFP Download Plus.

Contact your remote system service representative, contact your service representative in the IBM Support Center, or use your electronic link with IBM service.

03E0**Explanation**

This abend is issued by module APSHHJOF— the header that was being built exceeded the size of the send buffer.

System action

AFP Download Plus processing ends abnormally.

System programmer response

This message indicates a possible logic error. Alternatively, the header might have grown in size until it exceeded the length of the send buffer.

Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance.

03E1**Explanation**

This abend is issued by module APSHHQSC— APSHHQSC encountered an incorrect counter value that it did not recognize.

System action

AFP Download Plus processing ends abnormally.

System programmer response

The AFP Download Plus abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance.

03E3**Explanation**

This abend is issued by module APSHHCKT, APSHHEOF, APSHHJOF, or APSHHMFT — APSHCTCP

was called with an incorrect external state (not TCP_RECEIVE) for TCPRECV (receiving data).

System action

AFP Download Plus processing ends abnormally.

System programmer response

This AFP Download Plus abend reason code indicates a possible logic error.

Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance.

03E4**Explanation**

This abend is issued by module APSHHCKT, APSHHEOF, APSHHJOF, or APSHHMFT — An unknown response was received from the remote system.

System action

AFP Download Plus processing ends abnormally.

System programmer response

The AFP Download Plus abend reason code indicates a possible logic error with the remote system. Contact your remote system service representative for assistance.

03E5**Explanation**

This abend is issued by module APSHHCKT, APSHHCMF, APSHHEOF, APSHHJOF, APSHHMDF, APSHHMFT, APSHHRGF, or APSHHSMD — APSHCTCP was called with an incorrect external state (not TCP_SEND) for TCPSEND (sending data).

System action

AFP Download Plus processing ends abnormally.

System programmer response

This AFP Download Plus abend reason code indicates a possible logic error.

Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance.

03E6

Explanation

This abend is issued by module APSHHFDB, APSHHHER, APSHHINI, APSHHLDB, APSHHMDB, APSHHRES, or APSHHSND — APSHHSND encountered an incorrect return code from one of the sender modules that it did not recognize.

System action

AFP Download Plus processing ends abnormally.

System programmer response

This AFP Download Plus abend reason code indicates a possible logic error.

Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance.

03E7**Explanation**

This abend is issued by module APSHHMDF, APSHHMFT, APSHHRGF, or APSHODDS— AFP Download Plus cannot open the file. See the return code and reason code in the accompanying message for more details.

System action

AFP Download Plus processing ends abnormally.

System programmer response

If Data Management messages preceded by IEC are received, follow the procedures for your operating system before you contact the IBM Support Center or use your electronic link with IBM service.

03E8**Explanation**

This abend is issued by module APSHHRGF or APSHHMDF— AFP Download Plus cannot read the file. See the return code and reason code in the accompanying message for more details.

System action

AFP Download Plus processing ends abnormally.

System programmer response

If Data Management messages preceded by IEC are received, follow the procedures for your operating system before you contact the IBM Support Center or use your electronic link with IBM service.

03E9**Explanation**

This abend is issued by module APSHHQSC— the receiving system cannot receive jobs with both MO:DCA-P data sets and line data. The FSA was set to send multiple data set jobs and generic line data messages on failure in the Printer Inventory or the AFPPARMS control statement.

System action

AFP Download Plus processing ends abnormally.

System programmer response

If the FSA does not need to send multiple data set jobs, set the Data set grouping parameter in the Printer Inventory or the dataset-grouping parameter in the AFPPARMS control statement to NO. Otherwise, set the Send messages on failure parameter in the Printer Inventory or the send-messages-on-failure parameter in the AFPPARMS control statement to ALL.

03EA**Explanation**

This abend is issued by module APSHHRGF or APSHHMDF — AFP Download Plus attempted to change the file offset. The file offset is the position in a file from which data is next read. See the return code and reason code in the accompanying message for more details.

System action

AFP Download Plus processing ends abnormally.

System programmer response

If Data Management messages preceded by IEC are received, follow the procedures for your operating system before you contact the IBM Support Center or use your electronic link with IBM service.

03EB**Explanation**

This abend is issued by module APSHHSND — not enough storage exists for the send buffer.

System action

AFP Download Plus processing ends abnormally. This abend might be accompanied by a system GETMAIN abend, such as 878, if AFP Download Plus does not have enough storage to do its termination functions.

Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Increase the REGION parameter in the AFP Download Plus startup procedure.

03EC

Explanation

This abend is issued by module APSHHFDB, APSHHHER, APSHHINI, APSHHLDB, APSHHMDB, APSHHRES, or APSHHSND – the maximum number of attempts is exceeded for this job.

System action

AFP Download Plus processing ends abnormally.

System programmer response

This AFP Download Plus abend reason code indicates a possible logic error.

Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance.

03ED

Explanation

This abend is issued by module APSHHFDB, APSHHHER, APSHHINI, APSHHRES, or APSHHSND – APSHCTCP was called with an incorrect external state (not TCP_CONVLOST) for TCPLINK (TCP/IP socket connection).

System action

AFP Download Plus processing ends abnormally.

System programmer response

This AFP Download Plus abend reason code indicates a possible logic error.

Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance.

03EE

Explanation

This abend is issued by module APSHHFDB, APSHHHER, APSHHINI, APSHHLDB, APSHHMDB, APSHHRES, or APSHHSND – APSHCTCP was called with an incorrect external state (not TCP_SEND,

TCP_RECEIVE, or TCP_CONVLOST) for TCPSHUT (shutdown).

System action

AFP Download Plus processing ends abnormally.

System programmer response

This AFP Download Plus abend reason code indicates a possible logic error.

Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance.

03EF

Explanation

This abend is issued by module APSHHRGF or APSHHMDF— AFP Download Plus cannot read the file. See the return code and reason code in the accompanying message for more details.

System action

AFP Download Plus processing ends abnormally.

System programmer response

If Data Management messages preceded by IEC are received, follow the procedures for your operating system before you contact the IBM Support Center or use your electronic link with IBM service.

03F0

Explanation

This abend is issued by module APSHHSND— not enough storage exists for APSHHSCB.

System action

AFP Download Plus processing ends abnormally. This abend might be accompanied by a system GETMAIN abend, such as 878, if AFP Download Plus does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Increase the REGION parameter in the AFP Download Plus startup procedure.

03F1

Explanation

This abend is issued by module APSHHQSC— A negative response to the Query Supported Command request was received from the remote system.

System action

AFP Download Plus processing ends abnormally.

System programmer response

The AFP Download Plus abend reason code indicates a possible logic error with the remote system. Contact your remote system service representative for assistance.

03F2**Explanation**

This abend is issued by module APSHHQSC— The 4-byte end-of-file request is not supported by the remote system.

System action

AFP Download Plus processing ends abnormally.

System programmer response

The AFP Download Plus abend reason code indicates a possible logic error with the remote system. Contact your remote system service representative for assistance.

03F3**Explanation**

This abend is issued by module APSHHQSC— The Query Supported Command request is not supported by the remote system.

System action

AFP Download Plus processing ends abnormally.

System programmer response

The AFP Download Plus abend reason code indicates a possible logic error with the remote system. Contact your remote system service representative for assistance.

03F4**Explanation**

This abend is issued by module APSHHQSC— The remote system supports only one of the two multiple data set requests.

System action

AFP Download Plus processing ends abnormally.

System programmer response

The AFP Download Plus abend reason code indicates a possible logic error with the remote system. Contact your remote system service representative for assistance.

03F5**Explanation**

This abend is issued by module APSHHQSC— One of the compression requests is supported by the remote system and the other compression request is not supported by the remote system.

System action

AFP Download Plus processing ends abnormally.

System programmer response

The AFP Download Plus abend reason code indicates a possible logic error with the remote system. Contact your remote system service representative for assistance.

03F6**Explanation**

This abend is issued by module APSHHRSP— A processing acknowledgment was received from the remote system, but the remote system does not support processing acknowledgements.

System action

AFP Download Plus processing ends abnormally.

System programmer response

The AFP Download Plus abend reason code indicates a possible logic error with the remote system. Contact your remote system service representative for assistance.

03F7**Explanation**

This abend is issued by module APSHHMDS— A select value was encountered that was not valid.

System action

AFP Download Plus processing ends abnormally.

System programmer response

This AFP Download Plus abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance.

03F8**Explanation**

This abend is issued by module APSHHMDS— A negative response to one of the multiple data set requests was received from the remote system.

System action

AFP Download Plus processing ends abnormally.

System programmer response

The AFP Download Plus abend reason code indicates a possible logic error with the remote system or AFP Download Plus. Contact your remote system service representative, contact your service representative in the IBM Support Center, or use your electronic link with IBM service for assistance.

03F9**Explanation**

This abend is issued by module APSHHMDS— An unknown response was received from the remote system.

System action

AFP Download Plus processing ends abnormally.

System programmer response

The AFP Download Plus abend reason code indicates a possible logic error with the remote system. Contact your remote system service representative for assistance.

03FA**Explanation**

This abend is issued by module APSHHCMP or APSHHMFT — A compression type or multi-file transfer type that is not valid was passed from the calling module.

System action

AFP Download Plus processing ends abnormally.

System programmer response

This AFP Download Plus abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance.

03FC**Explanation**

This abend is issued by module APSHHCMP— A response that was not valid was received from the remote system.

System action

AFP Download Plus processing ends abnormally.

System programmer response

The AFP Download Plus abend reason code indicates a possible logic error with the remote system. Contact your remote system service representative for assistance.

03FD**Explanation**

This abend is issued by module APSHHCKT— The remote system does not support the 8-byte checkpoint request.

System action

AFP Download Plus processing ends abnormally.

System programmer response

This AFP Download Plus abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance.

03FE**Explanation**

This abend is issued by module APSHHEOF— The remote system does not support the 8-byte end-of-file request.

System action

AFP Download Plus processing ends abnormally.

System programmer response

This AFP Download Plus abend reason code indicates a possible logic error. Contact your service

representative in the IBM Support Center or use your electronic link with IBM service for assistance.

0400**Explanation**

This abend is issued by module APSHOPOS— not enough storage exists for a PrintOutSource object.

System action

AFP Download Plus processing ends abnormally. This abend might be accompanied by a system GETMAIN abend, such as 878, if AFP Download Plus does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Increase the REGION parameter in the AFP Download Plus startup procedure.

0401**Explanation**

This abend is issued by module APSHOPOS— not enough storage exists for a DownloadDS object.

System action

AFP Download Plus processing ends abnormally. This abend might be accompanied by a system GETMAIN abend, such as 878, if AFP Download Plus does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Increase the REGION parameter in the AFP Download Plus startup procedure.

0402**Explanation**

This abend is issued by module APSHODES— not enough storage exists for the DES object.

System action

AFP Download Plus processing ends abnormally. This abend might be accompanied by a system GETMAIN abend, such as 878, if AFP Download Plus does not have enough storage to do its termination functions. Because of the lack of available storage, the System

Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Increase the REGION parameter in the AFP Download Plus startup procedure.

0403**Explanation**

This abend is issued by module APSHODES— DESRecvTCPIP returned in the wrong state. It must always return in TCP_SEND state.

System action

AFP Download Plus processing ends abnormally.

System programmer response

The AFP Download Plus abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance.

0404**Explanation**

This abend is issued by module APSHODES— DESSendTCPIP returned in the wrong state.

System action

AFP Download Plus processing ends abnormally.

System programmer response

The AFP Download Plus abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance.

0405**Explanation**

This abend is issued by module APSHODES— not enough storage exists for APSNTREC.

System action

AFP Download Plus processing ends abnormally. This abend might be accompanied by a system GETMAIN abend, such as 878, if AFP Download Plus does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Increase the REGION parameter in the AFP Download Plus startup procedure.

0406**Explanation**

This abend is issued by module APSHODES— not enough storage exists for APSNTPSR.

System action

AFP Download Plus processing ends abnormally. This abend might be accompanied by a system GETMAIN abend, such as 878, if AFP Download Plus does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Increase the REGION parameter in the AFP Download Plus startup procedure.

0407**Explanation**

This abend is issued by module APSHODES— the TCP/IP port number is greater than 56,535.

System action

AFP Download Plus processing ends abnormally.

System programmer response

Specify a value 5001 - 56,535 for the Port number parameter in the Printer Inventory or the PORTNO parameter on the PRINTDEV statement in the startup procedure for AFP Download Plus.

0408**Explanation**

This abend is issued by module APSHODES— TCP/IP was not initialized in state TCP_RESET before DESLinkTCPIP.

System action

AFP Download Plus processing ends abnormally.

System programmer response

The AFP Download Plus abend reason code indicates a possible logic error. Contact your service

representative in the IBM Support Center or use your electronic link with IBM service for assistance.

0409**Explanation**

This abend is issued by module APSHODES— DESLinkTCPIP returned in the wrong state. It must always return in TCP_SEND state.

System action

AFP Download Plus processing ends abnormally.

System programmer response

The AFP Download Plus abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance.

040A**Explanation**

This abend is issued by module APSHHQSC — the remote system supports only one of the two multi-file transfer requests.

System action

AFP Download Plus processing ends abnormally.

System programmer response

This AFP Download Plus abend reason code indicates a possible logic error with the remote system.

Contact your remote system service representative for assistance.

040B**Explanation**

This abend is issued by module APSHHCMF — the remote system does not support the cancel file and job request.

System action

AFP Download Plus processing ends abnormally.

System programmer response

Use a remote system that supports the cancel file and job request.

040C

Explanation

This abend is issued by module APSHHCMF — the remote system does not support the cancel file request.

System action

AFP Download Plus processing ends abnormally.

System programmer response

Use a remote system that supports the cancel file request.

0410**Explanation**

This abend is issued by module APSHODES— not enough storage exists for the TCP/IP send buffer.

System action

AFP Download Plus processing ends abnormally. This abend might be accompanied by a system GETMAIN abend, such as 878, if AFP Download Plus does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Increase the REGION parameter in the AFP Download Plus startup procedure.

0411**Explanation**

This abend is issued by module APSHMPMF— the structured field in the internal message data set is not a Message Variable (MSV) structured field. For more information about the MSV structured field, see *Mixed Object Document Content Architecture Reference*.

System action

AFP Download Plus processing ends abnormally.

System programmer response

This AFP Download Plus abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0412**Explanation**

This abend is issued by module APSHMPMF— APSDGET detected an error while it was accessing the messages by reading the first record from an internal record data set.

System action

AFP Download Plus processing ends abnormally.

System programmer response

This AFP Download Plus abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0413**Explanation**

This abend is issued by module APSHMPMF— an attempt to build a record resource block (RRB) to access the internal message data set was unsuccessful.

System action

AFP Download Plus processing ends abnormally.

System programmer response

This AFP Download Plus abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0414**Explanation**

This abend is issued by module APSHMPMF— an attempt to delete a record resource block (RRB) used to access the internal message data set was unsuccessful. The RRB for the message data set cannot be removed from the queue.

System action

AFP Download Plus processing ends abnormally.

System programmer response

This AFP Download Plus abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0415**Explanation**

This abend is issued by module APSHMPMF— the message file cannot be created.

System action

AFP Download Plus processing ends abnormally.

System programmer response

See message APS8550I on the operator console to determine the system response needed.

0416**Explanation**

This abend is issued by module APSHMPMF— the message file cannot be opened.

System action

AFP Download Plus processing ends abnormally.

System programmer response

See message APS8551I on the operator console to determine the system response needed.

0417**Explanation**

This abend is issued by module APSHMPMF— APSHMPMF cannot get storage for the full path and file name string for the message file.

System action

AFP Download Plus processing ends abnormally. This abend might be accompanied by a system GETMAIN abend, such as 878, if AFP Download Plus does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Increase the REGION parameter in the AFP Download Plus startup procedure.

0418**Explanation**

This abend is issued by APSHPCRT— the POS object cannot be created.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0419**Explanation**

This abend is issued by module APSJCKO— not enough virtual storage exists to build the interpreter rules.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

041A**Explanation**

This abend is issued by module APSHROCR— APSHROCR cannot get storage for the base font list.

System action

AFP Download Plus processing ends abnormally. This abend might be accompanied by a system GETMAIN abend, such as 878, if AFP Download Plus does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Increase the REGION parameter in the AFP Download Plus startup procedure.

041B

Explanation

This abend is issued by module APSHROCR—APSHROCR cannot get storage for converting the TrueType Font name to UTF-16 encoding.

System action

AFP Download Plus processing ends abnormally. This abend might be accompanied by a system GETMAIN abend, such as 878, if AFP Download Plus does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Increase the REGION parameter in the AFP Download Plus startup procedure.

041C**Explanation**

This abend is issued by module APSHROCR—APSHROCR cannot get storage for the linked font list.

System action

AFP Download Plus processing ends abnormally. This abend might be accompanied by a system GETMAIN abend, such as 878, if AFP Download Plus does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Increase the REGION parameter in the AFP Download Plus startup procedure.

041D**Explanation**

This abend is issued by module APSHROCR—APSHROCR cannot get storage for the multiple name list for the Data Object Font.

System action

AFP Download Plus processing ends abnormally. This abend might be accompanied by a system GETMAIN abend, such as 878, if AFP Download Plus does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Increase the REGION parameter in the AFP Download Plus startup procedure.

041E**Explanation**

This abend is issued by APSHPCRT— the system has insufficient memory for the directory read buffer.

System action

AFP Download Plus processing ends abnormally. This abend might be accompanied by a system GETMAIN abend, such as 878, if AFP Download Plus does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This AFP Download Plus abend reason code indicates that the REGION size must be increased. Increase the REGION size in the AFP Download Plus startup procedure.

041F**Explanation**

This abend is issued by APSHPCRT — the system has insufficient memory to store the file names.

System action

AFP Download Plus processing ends abnormally. This abend might be accompanied by a system GETMAIN abend, such as 878, if AFP Download Plus does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This AFP Download Plus abend reason code indicates that the REGION size must be increased. Increase the REGION size in the AFP Download Plus startup procedure.

0420**Explanation**

This abend is issued by module APSHDWPFF— the MO:DCA data file cannot be written.

System action

AFP Download Plus processing ends abnormally.

System programmer response

See message APS8558I on the operator console to determine the response needed.

0421**Explanation**

This abend is issued by module APSHDWPF— the resource group file cannot be written.

System action

AFP Download Plus processing ends abnormally.

System programmer response

See message APS8558I on the operator console to determine the response needed.

0422**Explanation**

This abend is issued by module APSHDCLS— the resource group file cannot be written.

System action

AFP Download Plus processing ends abnormally.

System programmer response

See message APS8558I on the operator console to determine the response needed.

0423**Explanation**

This abend is issued by module APSHDCLS— the MO:DCA data file cannot be written.

System action

AFP Download Plus processing ends abnormally.

System programmer response

See message APS8558I on the operator console to determine the response needed.

0435**Explanation**

This abend is issued by module APSSDOC— the carriage control type in the RRB control block was not recognized. It must be either None, ANSI, or Machine.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0490**Explanation**

This abend is issued by module APSDGETI— an incorrect combination of return and reason codes was issued from the invocation of the APSIGET macro.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

04A0**Explanation**

This abend is issued by module APSDINIT— control was passed to module APSGGGETM with the issuance of the APSXGETM macro. This abend indicates that the required storage cannot be obtained.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

04A5

Explanation

This abend is issued by module APSDINIT— a nonzero return code was received from the first APSIPUT macro against Page Printing Writer output spool APSIRRB.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

04B0

Explanation

This abend is issued by module APSDPROC— the first invocation of APSDGET issued a nonzero return code when it was getting the first record from Page Printing Writer.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

04B1

Explanation

This abend is issued by module APSDPROC— module APSCCLR issued an incorrect return code.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

04B2

Explanation

This abend is issued by module APSDPROC— module APSDDS issued an incorrect return code.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

04B4

Explanation

This abend is issued by module APSDPROC— APSDGET issued a nonzero return code while it was getting the next record from Page Printing Writer.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

04B5

Explanation

This abend is issued by module APSDPROC— after the invocation of APSCCLR, an I/O error was issued with an action code, sense-byte 2, indicating that the

current page was ending. The action code for an I/O error cannot end the current page after a call to APSCCLR.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

04B6

Explanation

This abend is issued by module APSPDPROC— after the invocation of APSCCLR, an I/O error was issued with an unrecognizable action code, sense-byte 2.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

04B8

Explanation

This abend is issued by module APSPDPROC— after the invocation of APSDDS, an I/O error was issued with an unrecognizable action code.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

04B9

Explanation

This abend is issued by module APSPDPROC— after the invocation of APSDDS, an I/O error was issued with an action code, sense-byte 2, indicating that the current page was ending. The action code for an I/O error cannot end the current page after a call to APSDDS.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

04F0

Explanation

This abend is issued by module APSDLOAD— the object type that is indicated in the Resource Control Block (RCB) that was passed to APSDLOAD is unrecognizable.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

04F2

Explanation

This abend is issued by module APSDLOAD— an I/O error occurred while a font was being loaded. Repeated tries were unsuccessfully made to delete the part of the font that was already loaded. APSDLOAD cannot delete the font because of repeated I/O errors.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

04F3**Explanation**

This abend is issued by module APSDLOAD— not enough virtual storage was available to build the Formdef Interface parameter area.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

04F4**Explanation**

This abend is issued by module APSDLOAD— insufficient virtual storage was available to build the PAGEDEF Interface parameter block.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

04F5**Explanation**

This abend is issued by module APSDLOAD— the library type that is indicated in the Resource Control Block (RCB) that was passed to APSDLOAD is unrecognizable.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

04F6**Explanation**

This abend is issued by module APSDLOAD— APSDLOAD cannot get storage for common conversion machine (CCM) Object Container Interface control block.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter in the PSF startup procedure.

04F7**Explanation**

This abend is issued by module APSDLOAD— APSDLOAD cannot get storage for common conversion machine (CCM) IO Image Interface parameter block.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to

do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter in the PSF startup procedure.

0502

Explanation

This abend is issued by module APSDDS— the current structured field is not an End Data Set (EDS). Structured fields other than EDS must be processed elsewhere. For more information about the EDS structured field, see *Mixed Object Document Content Architecture Reference*.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0503

Explanation

This abend is issued by module APSOPJ— not enough storage exists for a PrintJob object.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Increase the REGION parameter in the PSF startup procedure.

0504

Explanation

This abend is issued by module APSOPJ— not enough memory exists to parse FSSDATA.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Increase the REGION parameter in the PSF startup procedure.

0505

Explanation

This abend is issued by module APSOLOG— not enough storage exists for a LogName object.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Increase the REGION parameter in the PSF startup procedure.

0506

Explanation

This abend is issued by module APSOTIME— not enough memory exists for a time work area.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Increase the REGION parameter in the PSF startup procedure.

0507**Explanation**

This abend is issued by module APSODOC— not enough storage exists for a Document object.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Increase the REGION parameter in the PSF startup procedure.

050B**Explanation**

This abend is issued by module APSDDS— the current structured field is not an End Job Header (EJH). Structured fields other than EJH must be processed elsewhere. For more information about the EJH structured field, see *Mixed Object Document Content Architecture Reference*.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0514**Explanation**

This abend is issued by module APSDDS— the structured field that was encountered at the end of a transmission is not an End Transmission (ETM). Structured fields other than ETM must be processed elsewhere. For more information about the ETM structured field, see *Mixed Object Document Content Architecture Reference*.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0515**Explanation**

This abend is issued by module APSDDS— an incorrect field from Page Printing Writer was detected after an authorized End Transmission (ETM) structured field. For more information about the ETM structured field, see *Mixed Object Document Content Architecture Reference*.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0516**Explanation**

This abend is issued by module APSDDS— the structured field that was encountered at the end of a data set header is not an End Data Set Header (EDH). Structured fields other than EDH must be processed elsewhere. For more information about the EDH structured field, see *Mixed Object Document Content Architecture Reference*.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0518

Explanation

This abend is issued by module APSDDS— the structured field in the internal message data set is not a Message Variable (MSV) structured field. For more information about the MSV structured field, see *Mixed Object Document Content Architecture Reference*.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0519**Explanation**

This abend is issued by module APSDDS— APSDGET detected an error while it was trying to access the messages by reading the first record from an internal record data set.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

051A**Explanation**

This abend is issued by module APSDDS— an attempt to build a record resource block (RRB) to access the internal message data set was unsuccessful.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

051B**Explanation**

This abend is issued by module APSDDS— an attempt to delete a record resource block (RRB) used to access the internal message data set was unsuccessful. The RRB for the message data set cannot be dequeued.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

051D**Explanation**

This abend is issued by module APSDDS— the structured field encountered at the end of a job trailer was not an End Job Trailer (EJT). Structured fields other than EJT must be processed elsewhere. For more information about the EJT structured field, see *Mixed Object Document Content Architecture Reference*.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

051E**Explanation**

This abend is issued by module APSDDS— an incorrect reason code was issued with a return code that was set to INFORMATIONAL.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0520**Explanation**

This abend is issued by module APSDDS— the I/O Error Manager action code was not valid.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0521**Explanation**

This abend is issued by module APSDDS— an unrecognizable nonzero return code was issued to APSDDS.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0523**Explanation**

This abend is issued by module APSDDS— after APSDDS notified the Page Printing Writer either to reposition or to stop processing a data set, module APSDGET issued an incorrect combination of return code and reason code.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM

Support Center or use your electronic link with IBM service for assistance with this error code.

0524**Explanation**

This abend is issued by module APSDDS— APSQENQ issued a nonzero return code while it was building a Page Pending Queue (PPQ) entry.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0525**Explanation**

This abend is issued by module APSDDS— the system function for OPEN of the PSF resource libraries did not succeed. This is the initial attempt at opening the PSF resource libraries.

System action

PSF processing ends abnormally.

System programmer response

If Data Management messages preceded by IEC are received, use the information that is provided by these messages to recover from the open failure before you contact the IBM Support Center or use your electronic link with IBM service for assistance.

0526**Explanation**

This abend is issued by module APSDDS—User Exit 7 requested data set end processing for one or more coded fonts, medium overlays, page segments/OCA, and object containers. However, either the Resource deletion ratio parameter in the Printer Inventory or the AFPPARMS control statement resource-deletion-ratio parameter is greater than zero.

System action

PSF processing ends abnormally.

System programmer response

See message APS149I on the operator console to determine the response needed.

0551

Explanation

This abend is issued by module APSDSECD— not enough virtual storage was available to build the SECPAPR control block to represent the bin information for the security definitions library.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0552

Explanation

This abend is issued by module APSDSECD— not enough virtual storage was available to build the narrow SECADATA control block to represent the narrow security definitions library paper information.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the

print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0553

Explanation

This abend is issued by module APSDSECD— not enough virtual storage was available to build the wide SECADATA control block to represent the narrow security definitions library paper information.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0554

Explanation

This abend is issued by module APSDSECD— not enough virtual storage was available to build the paper table for security definitions library processing.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0555**Explanation**

This abend is issued by module APSDSECD— not enough virtual storage was available to build the match table for security definitions library processing.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0556**Explanation**

This abend is issued by module APSDSECD— an error occurred in the called module APSIBLD while PSF was trying to build the Record Resource Block (RRB) to facilitate access to the security definitions library.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0557**Explanation**

This abend is issued by module APSDSECD— an error occurred in the called module APSIDEQ while PSF was trying to delete the Record Resource Block (RRB). The RRB was built by APSIBDLD to facilitate access to the security definitions library.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0560**Explanation**

This abend is issued by module APSDMSGF— PSF expected the current structured field to be a message variable (MSV) structured field, but it was not.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0570**Explanation**

This abend is issued by module APSDECH— insufficient virtual storage was available to build the Translate Character String parameter area.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0571

Explanation

This abend is issued by module APSDECH—insufficient virtual storage was available to build the Message Insert area.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0601

Explanation

This abend is issued by module APSERRM— APSERRM detected unexpected values in sense bytes 0, 1, and 19 for an action code X'01' error (sense byte 2). This error is caused by a logic error in the I/O Error Manager, the Document Processor, or the Resource Manager subcomponent, or in the printer. For more information about the definition of specific action codes and sense bytes, see *Intelligent Printer Data Stream Reference*. If the sense byte is unique to a printer, see the reference publication for the specific printer that is used.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error in either the microcode of the printer or in PSF. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0602

Explanation

This abend is issued by module APSERRM— APSERRM detected unexpected values in sense bytes 0, 1, and 19 for an action code X'01' error (sense byte 2). The reason is probably that the data stream has extra or missing bytes, which cause the IPDS command boundaries to be lost. This error is caused by a data transmission problem or by a logic error in some piece of software or microcode in the data transmission path. For more information about the definition of specific action codes and sense bytes, see *Intelligent Printer Data Stream Reference*. If the sense byte is unique to a printer, see the reference publication for the specific printer that is used.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code results from a possible logic error in the printer microcode, the controller microcode, the NCP code, the VTAM code, or the PSF code. For assistance related to this error code, consult your service representative in the IBMSupport Center, or use your electronic link with IBMservice.

0604

Explanation

This abend is issued by module APSERRM— APSERRM detected an unrecoverable interface control check. Three tries to do printer I/O failed. The problem might be from the printer that is associated with the abend, or might be caused by another device on the same channel.

System action

PSF processing ends abnormally.

System programmer response

To determine what device is causing the error, run the EREP report for each device on the channel. Notify

your systems engineer that a hardware error might have occurred.

0605**Explanation**

This abend is issued by module APSERRM— it indicates that the printer is reporting a unit check-in response to the IPDS NOP command.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend might indicate a logic error in the printer microcode. However, most likely it is because of problems in communication between PSF and the printer. Such problems are typically caused by a mismatch between channel protocol and speed. Verify that the CNTLUNIT PROTOCL statement matches the protocol for which the printer is configured.

0606**Explanation**

This abend is issued by module APSERRM— APSERRM detected that the printer is reporting an excessive number of NACKs in response to the I/O issued for doing recovery.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code might indicate a logic error in the printer microcode. Contact your service representative for the printer involved.

0607**Explanation**

This abend is issued by module APSERRM— APSERRM cannot obtain storage for the printer AEI response buffer.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is

for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter that is used in the PSF startup procedure.

0608**Explanation**

This abend is issued by module APSERRM— APSERRM cannot obtain storage for the Error Queue element AEI text string.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter that is used in the PSF startup procedure.

0609**Explanation**

This abend is issued by module APSERRM— APSCSNIO returned a negative acknowledgment on the Execute Order Anystate - Obtain Additional Exception Information (XOA-OAEI) command instead of a positive acknowledgment with the Obtain Additional Exception Information reply data.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error in either the microcode of the printer or in PSF. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0615**Explanation**

This abend is issued by module APSERRM— APSERRM detected a channel control check in the channel status word (CSW). This I/O error is handled in an error recovery procedure (ERP), and APSERRM does not get control. The ERP makes five tries to restart the channel program on the failing channel control word (CCW)

before this type of error is considered a permanent error and is reported to PSF.

System action

PSF processing ends abnormally.

System programmer response

To determine what device is causing the error, run the EREP report for each device on the channel. Notify your systems engineer that a hardware error might have occurred.

0616

Explanation

This abend is issued by module APSERRM— APSERRM detected a channel data check in the channel status word (CSW). This I/O error is handled in an error recovery procedure (ERP), and APSERRM does not get control. The ERP makes five tries to restart the channel program on the failing channel control word (CCW) before this type of error is considered a permanent error and is reported to PSF.

System action

PSF processing ends abnormally.

System programmer response

To determine what device is causing the error, run the EREP report for each device on the channel. Notify your systems engineer that a hardware error might have occurred.

0617

Explanation

This abend is issued by module APSERRM— APSERRM detected that both the Channel Control bit and the Interface Control bit in the CSW set were set ON. The I/O Supervisor sets both of these bits ON to indicate that the Missing Interrupt Handler (MIH) timer expired.

System action

PSF processing ends abnormally.

System programmer response

IML the printer again if it is not printing. Correct any outstanding interventions at the printer. Correct any printer hardware problems. If necessary, increase the MIH timer interval.

0620

Explanation

This abend is issued by module APSEATCD— APSEATCD detected an unexpected action code in the printer sense byte 2. The cause is one of these:

- The printer returned an undocumented or incorrect value in sense byte 2.
- APSEATCD detected an action code that the error recovery procedure (ERP) returned because it was unable to recover the device.
- Check for the presence of an OIS permanent error message (such as IOS000I with EQC [Equipment Check]). If one is found, an abend occurred because the device is in a state such that PSF cannot communicate with it. If no IOS permanent error message is issued, this PSF abend reason code indicates a possible logic error.

System action

PSF processing ends abnormally.

System programmer response

For printer sense bytes 0 - 23, see PSF message APS717I on the operator console.

For more information about the definition of specific action codes and sense bytes, see *Intelligent Printer Data Stream Reference*. If the sense byte is unique to a printer, see the reference publication for the specific printer that is used. This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0621

Explanation

This abend is issued by module APSERRM— APSERRM detected at least one of these bits in the channel status word (CSW) set ON: Chaining Check, Program Check, or Protection Check.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0622

Explanation

This abend is issued by module APSEERRM— APSEERRM detected that an incorrect Length bit was set in the channel status word (CSW).

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0623**Explanation**

This abend is issued by module APSEERRM— APSEERRM detected that least one of these bits in the channel status word (CSW) was set ON: Attention, or Status Modifier, or Control Unit End, or Busy, or Channel End, or Program-Control Interruption.

System action

PSF processing ends abnormally.

0624**Explanation**

This abend is issued by module APSEMSG— APSEMSG detected an incorrect recovery code in the I/O Error Manager parameter area (PARMRCOD).

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0625**Explanation**

This abend is issued by module APSEATCD— APSEATCD detected that a hardware error occurred in the printer's media-size sensors.

System action

PSF processing ends abnormally.

System programmer response

For information on how to correct the problem, see the reference publication for your printer.

0626**Explanation**

This abend is issued by module APSEERRM— APSEERRM detected that the CSW Unit Status and Channel Status bytes were both equal to zero.

System action

PSF processing ends abnormally.

0627**Explanation**

This abend is issued by module APSEMSG— APSEMSG detected that the Transaction ID at the time of error does not match the Transaction ID in the I/O Error Information Element. A logic error exists in one of these:

- The PSF Document Processor subcomponent that builds the I/O Information elements
- The Device Manager subcomponent that passes the address of the I/O Information elements to I/O Error Manager subcomponent
- The PSF I/O Error Manager subcomponent

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0628**Explanation**

This abend is issued by module APSEERRM— APSEERRM detected an ECB completion code other than X'41', X'44', X'48', or X'7E'. APSEERRM continues processing only on the above ECB completion codes. To interpret the ECB completion code, see *z/OS DFSMS Using Data Sets* or the debugging handbook for your operating system.

System action

PSF processing ends abnormally.

0629**Explanation**

This abend is issued by module APSEATCD— an unrecognized recovery code was found during X'06' recovery.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBMSupport Center or use your electronic link with IBMservice for assistance with this error code.

0640**Explanation**

This abend is issued by module APSE3820— APSE3820 detected incorrect values in sense bytes 0 and 1 for an action code X'09' error (sense byte 2). This error occurs either because the printer returned undocumented or incorrect values in sense bytes 0, 1, and 2, or because the PSF I/O Error Manager subcomponent contains a logic error. For more information about the definition of specific action codes and sense bytes, see *Intelligent Printer Data Stream Reference*. If the sense byte is unique to a printer, consult the reference publication for the specific printer that is used.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error in either the microcode of the printer or in PSF. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0643**Explanation**

This abend is issued by module APSE3820— APSE3820 detected an unexpected action code in the printer sense byte 2. This error arises either because the printer returned an undocumented or incorrect value in sense byte 2, or because the PSF I/O Error Manager subcomponent contains a logic error. For more information about the definition of specific action codes and sense bytes, see *Intelligent Printer Data*

Stream Reference. If the sense byte is unique to a printer, see the reference publication for the specific printer that is used.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error in either the microcode of the printer or in PSF. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0644**Explanation**

This abend is issued by module APSE3820— APSE3820 received sense data with an action code of X'23', but with an undefined status code.

System action

PSF processing ends abnormally.

System programmer response

Re-IML the printer. If the problem persists, notify your systems engineer that a hardware error might have occurred.

0648**Explanation**

This abend is issued by module APSEMSG— APSEMSG detected an incorrect value (task) in the parameter MSGTASK.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0649**Explanation**

This abend is issued by module APSERRM— APSERRM cannot get enough storage for the PSF I/O error queue.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0650**Explanation**

This abend is issued by module APSERRM— APSERRM detected that either I/O Error Manager's I/O Error Queue was empty, or no error was recorded as having the highest priority when it was time to select the highest-priority error.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0651**Explanation**

This abend is issued by module APSEMSG— APSEMSG detected incorrect values in sense bytes 0 and 1 for an action code X'0C' error (sense byte 2). This error is caused by either of these:

1. The printer returned undocumented or incorrect values in sense bytes 0, 1, and 2.
2. The PSF I/O Error Manager subcomponent contains a logic error.

For more information about the definition of specific action codes and sense bytes, see *Intelligent Printer Data Stream Reference*. If the sense byte is unique to a printer, consult the reference publication for the specific printer that is used.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0652**Explanation**

This abend is issued by module APSEMSG— APSEMSG detected that the Device Manager or Document Processor did not provide an address to an I/O Error Information Element for a synchronous error. Either the Device Manager, the Document Processor, or the I/O Error Manager subcomponent contains a logic error.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0653**Explanation**

This abend is issued by module APSEATCD— APSEATCD detected an action code X'17' (printer sense byte 2) unit check I/O error. Action code X'17' indicates either a permanent hardware error or an attempt to use a disabled mechanism in the printer.

System action

PSF processing ends abnormally.

System programmer response

To use the disabled mechanism, you must fix the problem and reactivate the mechanism. If a permanent hardware error occurred, notify your systems engineer.

0654

Explanation

This abend is issued by module APSEERRM— APSEERRM detected the unit exception bit set in the channel status word (CSW). This I/O error must never occur while PSF is driving a printer in pagemode.

System action

PSF processing ends abnormally.

0655**Explanation**

This abend is issued by module APSEERRM— APSEERRM received a synchronous I/O error after an asynchronous I/O error with a negative acknowledgment record associated with it was received and placed in the I/O Error Manager's I/O Error Queue.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error in either the microcode of the printer or in PSF. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0656**Explanation**

This abend is issued by module APSEERRM— during SYNC order processing, APSEERRM detected an incorrect action code (sense byte 2) in I/O Error Manager's I/O Error Queue.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0657**Explanation**

This abend is issued by module APSEERRM— APSEERRM detected that the error transaction ID or the I/O Error

Information Element address was changed while APSCSNIO was called to do synchronous I/O.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0658**Explanation**

This abend is issued by module APSEERRM— APSEERRM detected a NACK after APSRROCK indicated a successful return. The PSF Resource Manager subcomponent contains a logic error.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0659**Explanation**

This abend is issued by module APSEERRM— APSEERRM received a zero return code from APSRROCK. APSRROCK is required to return either an informational return code, when successful, or an 8-or-higher return code, when unsuccessful. The PSF Resource Manager subcomponent contains a logic error.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0660

Explanation

This abend is issued by module APSECUR— APSECUR received an incorrect function in the I/O Error Manager work area. The PSF I/O Error Manager subcomponent contains a logic error.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0663**Explanation**

This abend is issued by module APSERRM— APSERRM called APSCPRCT to determine the transaction in error and APSCPRCT was unable to do so.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error in either the microcode of the printer or in PSF. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0701**Explanation**

This abend is issued by module APSRINIT— no space was available for the resource control table. PSF cannot proceed without sufficient storage space to build its basic control blocks.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is

processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0702**Explanation**

This abend is issued by module APSRINIT— APSRINIT cannot get storage for the REGD list.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0703**Explanation**

This ABEND is issued by module APSGGGETM on behalf of APSRADOR— not enough memory was available to build the APRACTPX interface structure to call APRACTEZ.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode,

increase the REGION parameter used in the PSF startup procedure.

0704**Explanation**

This abend is issued by module APSRTTCP— APSRTTCP did not understand the code page object identification response.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0705**Explanation**

This abend is issued by module APSORES— APSORES cannot get storage for a complete font resource object.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter in the PSF startup procedure.

0706**Explanation**

This abend is issued by module APSORES— APSORES cannot get storage for a code page resource object.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of

available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter in the PSF startup procedure.

0707**Explanation**

This abend is issued by module APSORES— APSORES cannot get storage for a data object font resource object.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter in the PSF startup procedure.

0708**Explanation**

This abend is issued by module APSRTTDF— APSRTTDF did not understand the data object font identification response.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0709

Explanation

This abend is issued by module APSORES— APSORES detected a failure from APSIBLD while it was building an RRB structure.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

070A**Explanation**

This abend is issued by module APSOCFM— APSOCFM cannot get storage for a coded font map object.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter in the PSF startup procedure.

070B**Explanation**

This abend is issued by module APSORES— APSORES cannot get storage for an APRACTPX structure.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter in the PSF startup procedure.

070C**Explanation**

This abend is issued by module APSOCFT— APSOCFT cannot get storage for a copy of the X'8B' triplet structure.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter in the PSF startup procedure.

070D**Explanation**

This abend is issued by module APSOCFT— APSOCFT cannot get storage for an APRACTPX linked font structure.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is

processing in deferred-printing mode, increase the REGION parameter in the PSF startup procedure.

070E**Explanation**

This abend is issued by module APSRTTCF— APSRTTCF detected a coded font activation failure.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

070F**Explanation**

This abend is issued by module APSORES— APSORES cannot get storage for an APSIRRB structure.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter in the PSF startup procedure.

0711**Explanation**

This abend is issued by module APSRNAME— APSRNAME received an incorrect resource type as an input parameter. This parameter was not recognized as a coded font, a page segment, an overlay, a form definition, a page definition, or a code page-font character set resource type.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0712**Explanation**

This abend is issued by module APSRNAME— insufficient storage was available for an RLST entry.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0713**Explanation**

This abend is issued by module APSRNAME— an Object Container is missing a required parameter REGD@.

System action:

0714**Explanation**

This abend is issued by module APSODOF— APSODOF cannot get storage for an APROC RPX structure.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter in the PSF startup procedure.

0715

Explanation

This abend is issued by module APSOCPG— APSOCPG cannot get storage for an APRCPGPX structure.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter in the PSF startup procedure.

0716

Explanation

This abend is issued by module APSORES— APSORES cannot get storage for an APSGRIT structure.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter in the PSF startup procedure.

0717

Explanation

This ABEND is issued by module APSGGTM on behalf of a PSF module that is using the ESTRCreat method — not enough memory was available to build an instance of the APSOESTR (EncodingString) class for Unicode encoding conversion.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0722

Explanation

This abend is issued by module APSRLOAD— the resource control block (RCB) contained a resource type other than a font, a code page or font character set, a page segment, an overlay, a form definition, or a page definition.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0723

Explanation

This abend is issued by module APSRLOAD— the module was unable to GETMAIN storage for a control block. PSF cannot proceed without sufficient storage space to build its basic control blocks.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0725

Explanation

This abend is issued by module APSODOR— a nested data object resource is being deleted when a dependent resource still exists.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0726

Explanation

This abend is issued by module APSRDEL— an object container has a dependent data object resource in the dependent chain.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend,

such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0728

Explanation

This abend is issued by module APSRMPSG— this module was unable to GETMAIN storage for a control block. PSF cannot proceed without sufficient storage space to build its basic control blocks.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0729

Explanation

This abend is issued by module APSRMPSG— APSRMPSG was called to process a Map Page Segment (MPS) structured field, but the printer does not support page segments.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0730

Explanation

This abend is issued by module APSRMPSG— the module was unable to GETMAIN storage for the APSRSWRK control block. PSF cannot proceed without sufficient storage space to build its basic control blocks.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0731

Explanation

This abend is issued by module APSRMFNT— insufficient storage was available for an RLST entry.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the

print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0734

Explanation

This abend is issued by module APSRMFNT— APSRMFNT was called to process a Map Coded Font (MCF) structured field, but the printer does not support coded fonts.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0736

Explanation

This abend was issued by module APSRMFNT— the module was unable to GETMAIN storage for the APSRSWRK control block. PSF cannot proceed without sufficient storage space to build its basic control blocks.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0738

Explanation

This abend is issued by module APSRMOVL— the module was unable to GETMAIN storage for a control

block. PSF cannot proceed without sufficient storage space to build its basic control blocks.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0739

Explanation

This abend is issued by module APSRMOVL—APSRMOVL was called to process a Map Medium Overlay (MMO) or Map Page Overlay (MPO) structured field, but the printer does not support overlays.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0740

Explanation

This abend was issued by module APSRMOVL— the module was unable to GETMAIN storage for the APSRSWRK control block. PSF cannot proceed without sufficient storage space to build its basic control blocks.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities

(SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0742

Explanation

This abend is issued by module APSRLRT— this failure occurs when APSRLRT calls the LOAD macro to load the PSF Resident Font Table (APSRFTBL) and the return code from the LOAD macro is not equal to zero.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0743

Explanation

This abend is issued by module APSRLRT— the module was unable to GETMAIN storage for a control block. PSF cannot proceed without sufficient storage space to build its basic control blocks.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode,

increase the REGION parameter used in the PSF startup procedure.

0744**Explanation**

This abend is issued by module APSRLRT— this failure occurs when APSRLRT calls the LOAD macro to load the optional user mapping table APSRNTGM and APSRGTM. The return code from the LOAD is not equal to zero.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0751**Explanation**

This abend is issued by module APRGRNEX— this failure occurs when APRGRNEX is called with an input pointer that does not point to storage that contains a valid Resource Control Block.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0752**Explanation**

This abend is issued by module APRGRNEX— the failure occurs when APRGRNEX detects that the attached printer supports the distributed print function and printer-resident fonts.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0771**Explanation**

This abend is issued by module APSRDEL— APSRDEL received an incorrect input parameter. Valid input parameters are X'01' or X'02'.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0772**Explanation**

This abend is issued by module APSRDEL— the reasonable resource-loading value (RRLV) for overlays was not set to zero.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0773**Explanation**

This abend is issued by module APSRDEL— APSRDEL is called to specifically delete the RCB for a resource that is still loaded in the printer. This is a logic error in PSF because the RCB is used to track resources in the printer. The resource must be deleted first.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0781**Explanation**

This abend is issued by module APSRROCK— the input parameter pointer does not address a valid RCB.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0782**Explanation**

This abend is issued by module APSRROCK— Resource Manager delete flags indicate that two or more operations are in error.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0783**Explanation**

This abend is issued by module APSRROCK— printer support of an RRL printer order is insufficient to allow recovery from a printer error.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0791**Explanation**

This abend is issued by module APSRSRT— APSRSRT detected that the pointer to the resident code page section or resident font character set section of PSF Resident Font Table (APSRFTBL) does not point to valid storage that contains the required font information.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

07A1**Explanation**

This abend is issued by module APROAEEX— this failure occurs when APROAEEX is called with an input pointer that does not point to storage that contains a valid resource control block.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

07A2**Explanation**

This ABEND is issued by module APSGGTM on behalf of a PSF module that is using the HIDCreate method— not enough memory was available to build an instance of the APSOHID (HAID) class for managing Host Assigned Printer IDs.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities

(SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

07A4

Explanation

This ABEND is issued by a module that is using the HIDFreeHAID method— a HAID was being freed for a resource that was still loaded in the printer.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

07A8

Explanation

This abend is issued by module APSRMFNX— fonts that are mapped in a Map Coded Font (MCF) structured field for an Object Environment Group must also be mapped in an MCF in the Active Environment Group for the same page or overlay. This error must be detected before APSRMFNT is called, but was not.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

07A9

Explanation

This abend is issued by module APSRMFNX— the module was unable to GETMAIN storage for a control block. PSF cannot proceed without sufficient storage space to build its basic control blocks.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

07B0

Explanation

This abend is issued by module APSRFIOM— an incorrect font code page or character set was processed. The code page or character set did not contain a X'5A' carriage control, or else a logic error exists in the font library utility.

System action

The font library utility ends abnormally.

System programmer response

Verify that the code page or character set is valid. Register 5 points to the member name, and register 6 points to the DD name. If the font member contains X'5A' carriage control, consult your service representative in the IBMSupport Center, or use your electronic link with IBMservice for assistance related to this error code.

07C0

Explanation

This abend is issued by module APSRMDOR— APSRMDOR cannot get storage for an RCB.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter in the PSF startup procedure.

07C1**Explanation**

This abend is issued by module APSORES— APSORES cannot get storage for an RLST entry.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter in the PSF startup procedure.

07C2**Explanation**

This abend is issued by module APSRHAID— the module was unable to obtain a HAID for the current font because 127 fonts are already required for the current page.

System action

AFP Download Plus processing ends abnormally.

System programmer response

Reduce the number of fonts required for the current page to less than 127.

07C3**Explanation**

This abend is issued by module APSORES— APSORES cannot get storage for an RRL entry.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter in the PSF startup procedure.

07C4**Explanation**

This abend is issued by module APSODOR— not enough memory for OCRPX.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter in the PSF startup procedure.

07C5

Explanation

This abend is issued by module APSODOR— not enough memory for STGPZ.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter in the PSF startup procedure.

07C6**Explanation**

This abend is issued by module APSODOR— not enough memory for IOBSR LL item.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter in the PSF startup procedure.

0810**Explanation**

This abend is issued by module APRIPSEX— the library type that is indicated in the library parameter from APSRNAME is unrecognizable.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0811**Explanation**

This abend is issued by module APRIPSEX— not enough memory was available to build a PSCB entry.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0820**Explanation**

This abend is issued by module APRIOBEX— the library type that is indicated in the library parameter from APSRNAME is unrecognizable.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0821**Explanation**

This abend is issued by module APRIOBEX— not enough memory was available to build the Object Container parameter areas.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0840**Explanation**

This ABEND is issued by module APSGGETM on behalf of APRBRSEX— not enough memory was available to build the local buffer for APRBRSEX.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0841**Explanation**

This ABEND is issued by module APSGGETM on behalf of APRIOBEX— not enough memory was available to build the APROC RPX, APROC APX, or APSPGPX interface structure for calling the common conversion machine (CCM).

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0850**Explanation**

This abend is issued by module APRINPEX— aPRINPEX detected an authorized structured field. All authorized structured fields were recognized and processed elsewhere. This is a logic error.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0851**Explanation**

This abend is issued by module APRINPEX— APSDMSGF was called to retrieve records from the Message Data Set, but no record pointer was returned.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM

Support Center or use your electronic link with IBM service for assistance with this error code.

0852**Explanation**

This abend is issued by module APRINPEX— an incorrect carriage control type was specified in the record resource block, APSIRRB. The only valid carriage control types are None, ANSI, and Machine. This is a logic error.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0860**Explanation**

This abend is issued by modules APRDOCEX, APSHDCLS, and APSHDWPF— data set type was not found.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0870**Explanation**

This abend is issued by module APRSTGEX— the AFPCCM requested that space is allowed, but none was allowed successfully. The APSGGETM or APSXGETM macro might contain a problem.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities

(SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0880**Explanation**

This abend is issued by module APRBPGEX— the bin number supplied by the caller was not found in APRDATDX.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

0881**Explanation**

This abend is issued by module APRBPGEX— the bin number supplied by the caller was not found in APSDYSEC.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0882**Explanation**

This abend is issued by module APRBPGEX— the value of DCAERCID (number of copies printed) was odd, but the page was on a duplex sheet.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0883

Explanation

This abend is issued by module APRBPGEX— not enough storage available for triplet data.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0891

Explanation

This abend is issued by module APREPGEX— the duplex indicator in the parameter block is not valid.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0892

Explanation

This abend is issued by module APREPGEX— the location of the last input record for the page is not valid because it contains blanks.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

08A0

Explanation

This abend is issued by module APRMSGEX— no DAT pointer was passed to the common conversion machine (CCM). This is a logic error.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

08A1

Explanation

This abend is issued by module APRMSGEX— no FORMDEF pointer was passed to the common conversion machine (CCM). This is a logic error.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

08A2

Explanation

This abend is issued by module APRMSGEX— no PAGEDEF pointer was passed to the common conversion machine (CCM). This is a logic error.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

08A3**Explanation**

This abend is issued by module APRMSGEX— no Object Stack pointer was passed to the common conversion machine (CCM). This is a logic error.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

08A4**Explanation**

This abend is issued by module APRMSGEX— no code page pointer was passed to the common conversion machine (CCM). This is a logic error.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

08A5**Explanation**

This abend is issued by module APRMSGEX— no Font Metric pointer was passed to the common conversion machine (CCM). This is a logic error.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

08A6**Explanation**

This abend is issued by module APRMSGEX— the common conversion machine (CCM) encountered an unexpected parameter. This is a logic error.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

08A7**Explanation**

This abend is issued by module APRMSGEX— the common conversion machine (CCM) cannot find the requested medium map. This is a logic error.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

08A8**Explanation**

This abend is issued by module APRMSGEX— the common conversion machine (CCM) cannot find the requested data map. This is a logic error.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

08A9**Explanation**

This abend is issued by module APRMSGEX— the common conversion machine (CCM) cannot find the requested environment group.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

08AA**Explanation**

This abend is issued by module APRMSGEX— an incorrect message identifier was passed by the common conversion machine (CCM). This is a logic error.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support

Center or use your electronic link with IBM service for assistance with this error code.

08AB**Explanation**

This abend is issued by module APRMSGEX— an incorrect logic error identifier was passed by the common conversion machine (CCM). This is a logic error.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

08AC**Explanation**

This abend is issued by module APRMSGEX— after the common conversion machine (CCM) called the shell to load a list of overlays, it looks at the overlay local IDs and matches them with the overlay IDs in the MMC structured field. If a match cannot be found, the error is a logic error because the shell must not change the overlay local ID field.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

08AD**Explanation**

This abend is issued by module APRMSGEX— the starting copy count that is provided by the shell to the common conversion machine (CCM) exceeds the total number of copies in the current medium map. This error would happen after PSF had to reposition for some reason.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

08AE**Explanation**

This abend is issued by module APRMSGEX— the common conversion machine (CCM) passed an incorrect message ID to APRMSGEX.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

08AF**Explanation**

This abend is issued by module APRMSGEX— the common conversion machine (CCM) passed an incorrect logic error ID to APRMSGEX.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

08B0**Explanation**

This abend is issued by module APRMSGEX— the common conversion machine (CCM) was requested to use conditional processing information, but the page definition is not a conditional processing page definition.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

08B1**Explanation**

This abend is issued by module APRMSGEX— insufficient virtual storage was available to build the Translate Character String parameter area.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

08C0**Explanation**

This abend is issued by module APRIPOEX— the overlay specified in the Include Page Overlay (IPO) structured field was not loaded in the printer.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

08D1

Explanation

This abend is issued by module APRMSGEX— common conversion machine (CCM) was requested to activate an outline font character set or code page, but the printer does not support outline fonts. This is a logic error.

System action:**System programmer response:**

08D2**Explanation**

This abend is issued by module APRMSGEX— common conversion machine (CCM) was requested to activate a font resource, but the global name was not provided or an incorrect length was specified. This is a logic error.

System action:**System programmer response:**

08D3**Explanation**

This abend is issued by module APRMSGEX— no Frequent Font table or FGID Lookaside table pointer was passed to common conversion machine (CCM). This is a logic error.

System action:**System programmer response:**

08D4**Explanation**

This abend is issued by module APRMSGEX— common conversion machine (CCM) ran out of its object stack area. This might be a data stream error or a logic error. A begin structured field must be followed by a matching end structured field in the data stream. If this requirement is not met, the CCM can run out of its object stack area.

System action

PSF processing ends abnormally.

System programmer response

Each begin structured field in the data stream must be followed by a matching end structured field. Check the data stream to ensure that this requirement is met. If it is not met, correct the data stream. If it is met, this error code indicates a logic error. If you believe that the error is a logic error, consult your service representative in the IBMSupport Center for assistance, or use your electronic link with IBMservice.

System programmer response

This PSF abend reason code indicates a logic error. For assistance with this error code, consult your service representative in the IBMSupport Center, or use your electronic link with IBMservice.

08D5**Explanation**

This abend is issued by module APRMSGEX— all bins reported back from the printer are either disabled or are inserter bins. As a result, no bins are available for printing and the current data set cannot be printed.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

08D6**Explanation**

This abend is issued by module APRMSGEX— no record length was passed to common conversion machine (CCM) when processing an object container resource. This is a logic error.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBMSupport Center or use your electronic link with IBMservice for assistance with this error code.

08D7**Explanation**

This abend is issued by module APRMSGEX— no Data Object Font (DOF) Descriptor triplet information was provided for a data object font activation request.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a PSF logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

08D8**Explanation**

This abend is issued by module APRMSGEX— no OID was specified for a data object resource or data object font component activation request.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a PSF logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

08D9**Explanation**

This abend is issued by module APRMSGEX— no processing mode or scope information was provided for a color management resource (CMR) activation request.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a PSF logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error.

08DA**Explanation**

This abend is issued by module APRMSGEX— color management resource (CMR) activation request was received, but the printer does not support CMRs.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a PSF logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error.

08E0**Explanation**

This abend is issued by module APRTNEX— an incorrect or missing parameter was passed by the module that called APRTNEX.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0900**Explanation**

Any LASI module— not enough storage was available for the interface data block (APSLIDB) for the message data set.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0901

Explanation

This abend is issued by module APLWIDS— not enough storage to add an element to a linked list.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0902**Explanation**

Any LASI module— the record resource block (RRB) was not valid. The first 4 bytes must be RRB followed by a space.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0903**Explanation**

Any LASI module— the record resource block (RRB) is not a message data set or an inline library.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0904**Explanation**

Any LASI module— the record resource block (RRB) does not specify a FIRSTCALL or GET.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0905**Explanation**

Any LASI module— an incorrect reason code was issued to LASI. The reason code is in register 2.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0906**Explanation**

Any LASI module— an incorrect return code was issued to LASI. The return code is in register 2.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

090C**Explanation**

Any LASI module— the record resource block (RRB) was not valid. The first 4 bytes must be RRB followed by a space.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

090D**Explanation**

Any LASI module— the record resource block (RRB) does not specify a message data set or an inline library data set.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

090E**Explanation**

Any LASI module— a request was received to process an output message data set or inline library. The record resource block (RRB) that was specified was not an output message data set or an inline library RRB.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

090F**Explanation**

Any LASI module— the producer issued an incorrect reason code to LASI.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0910**Explanation**

Any LASI module— the producer issued an incorrect return code to LASI.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0911**Explanation**

Any LASI module— the length of the logical record is greater than the maximum allowed.

System action

PSF processing ends abnormally.

System programmer response

The resource that contains the error must be re-created following the Data Management guidelines for logical records. The logical record minimum is 5 bytes, and the logical record maximum is 32 760 bytes.

0912**Explanation**

Any LASI module— the length of the logical record is less than the minimum allowed.

System action

PSF processing ends abnormally.

System programmer response

The resource that contains the error must be re-created following the Data Management guidelines for logical records. The logical record minimum is 5 bytes, and the logical record maximum is 32 760 bytes.

0913

Explanation

Any LASI module— an incorrect request was received.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0919**Explanation**

Any LASI module— the control block is not a record resource block (RRB). The first 4 bytes must be RRB followed by a space.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0920**Explanation**

Any LASI module— the record resource block (RRB) is not type LIB.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0921**Explanation**

Any LASI module— an incorrect reason code was returned to LASI.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0922**Explanation**

Any LASI module— an incorrect return code was returned to LASI.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0923**Explanation**

This abend is issued by module APLRPNM— not enough storage for the CRL entry.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0924**Explanation**

This abend is issued by module APSLRIDS— while an inline resource was being read from its buffers, the buffered inline resource was modified.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0926**Explanation**

This abend is issued by module APSLRBS— the SYNADRLS macro discovered an incorrect save area chain.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0928**Explanation**

This abend is issued by module APSLRBS— the function that is requested is not known by this module.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0930**Explanation**

This abend is issued by module APSLRBS— the closing of a system library that had an extent error was unsuccessful.

System action

PSF processing ends abnormally.

System programmer response

If Data Management messages preceded by IEC are received, follow the procedures for your operating system before you contact the IBM Support Center or use your electronic link with IBM service.

0931**Explanation**

This abend is issued by module APSLRBS— the reopening of a system library that had an extent error was unsuccessful.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

If Data Management messages preceded by IEC are received, follow the procedures for your operating system before you contact the IBM Support Center or use your electronic link with IBM service.

0933**Explanation**

This abend is issued by module APSLRBS— an unknown type of extent error occurred. The error cannot be processed.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

If Data Management messages preceded by IEC are received, follow the procedures for your operating system before you contact the IBM Support Center or use your electronic link with IBM service.

0936**Explanation**

This abend is issued by module APSLRBS— the data control block (DCB) points to the data extent block (DEB), but the DEB does not point back to the DCB.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0937**Explanation**

This abend is issued by module APSLRBS— the data control block (DCB) does not point to a data extent block (DEB). The DEB ID must be X'F' in the low-order 4 bits of the DEBEBID.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0938**Explanation**

This abend is issued by module APSLRBS— the FIND macro returned a nonzero return code in Register 15. This return code must always be zero.

System action

PSF processing ends abnormally.

System programmer response

If Data Management messages preceded by IEC are received, follow the procedures for your operating system before you contact the IBM Support Center or use your electronic link with IBM service.

0939**Explanation**

This abend is issued by module APSLRPNM— GETDSAB system macro is not installed on the system.

System action

PSF processing ends abnormally.

System programmer response

Verify that the GETDSAB system macro is installed. If the GETDSAB system macro is installed, this is a logic error. If the GETDSAB system macro is not installed, the system programmer must install it.

0940**Explanation**

This abend is issued by module APSLCLOS— the function that is requested is not known by APSLCLOS.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0942**Explanation**

This abend is issued by module APSLCLOS— the record resource block (RRB) does not point to an interface data block (APSLIDB). The IDB does not have IDB, followed by a space, as the first 4 characters of the block.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0944**Explanation**

This abend is issued by module APSLCUSS— function request input parameter is not valid.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0945**Explanation**

This abend is issued by module APSLCUSS— no file descriptor in the RRB.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0946**Explanation**

This abend is issued by module APSLCUSS— tried to close the file, but the file is being used.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0947**Explanation**

This abend is issued by module APSLCUSS— the file descriptor is not valid.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0948**Explanation**

This abend is issued by module APSLMSG— a request was made to issue a message that is not supported by this module.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0949**Explanation**

This abend is issued by module APSLUSSO— RRB is not valid.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

094A**Explanation**

This abend is issued by module APSLUSSO— function request input parameter is not valid.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

094B**Explanation**

This abend is issued by module APSLUSSO— tried to access the USERPATH library, but the USERPATH library is not available.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

094C**Explanation**

This abend is issued by module APSLUSSO— the resource library requested was not found.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

094D**Explanation**

This abend is issued by module APSLUSSO— the initialization of the RAU was not successful.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

094E**Explanation**

This abend is issued by module APSLUSSO— IDB for USERPATH initialization is not valid.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM

Support Center or use your electronic link with IBM service for assistance with this error code.

094F**Explanation**

This abend is issued by module APSLUSSO— CEEPIPI was unsuccessful in calling a C module.

System action

PSF processing ends abnormally.

System programmer response

Look in the accompanying message for the CEEPIPI return codes to determine whether this is a logic error.

0950**Explanation**

This abend is issued by module APSLUSSO— the RAU was not successful in adding a path name to the PSF search order.

System action

PSF processing ends abnormally.

System programmer response

Look in the accompanying message for the RAU return codes to determine whether this is a logic error or a user error.

0951**Explanation**

This abend is issued by module APSLUSSO— not enough storage exists for the RAUB.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode,

increase the REGION parameter used in the PSF startup procedure.

0952**Explanation**

This abend is issued by module APSLUSSO— not enough storage exists for the path name work area.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0953**Explanation**

This abend is issued by module APSLUSSO— not enough storage exists for the tracking area.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0954**Explanation**

This abend is issued by module APSLINIT— not enough storage was available for the record resource block (RRB).

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0955**Explanation**

This abend is issued by module APSLINIT— not enough storage was available for the system object control block, APSLSOCB.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0956

Explanation

This abend is issued by module APSLINIT— the APSLINIT message data set stack is empty. A dummy message data set must be stacked.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0957**Explanation**

This abend is issued by module APSLINIT— an error occurred while the APSLINIT dummy message data set was being created. Not enough storage was available for a record resource block (RRB).

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0958**Explanation**

This abend is issued by module APSLINIT— an APSLINIT error occurred while PSF was using the APSIPUT macro to write message APS516I or APS517I to the library access system interface (LASI) message data sets. These are the message data sets used in later processing if not enough space is available to write an error or informational message to the current message data set.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0959**Explanation**

This abend is issued by module APSLINIT— the module was unable to GETMAIN storage for the Library Link List. PSF cannot proceed without sufficient storage space to build its basic control blocks.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0963**Explanation**

This abend is issued by module APSLUSSO— a CRL match cannot be found.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0964

Explanation

This abend is issued by module APSLOPEN— the record resource block (RRB) is not valid. The control block ID must be RRB.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0965**Explanation**

This abend is issued by module APSLOPEN— not enough storage for STAT.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

The REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0968**Explanation**

This abend is issued by module APSLOPEN— the function that is requested is not known to this module.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0969**Explanation**

This abend is issued by module APSLOPEN— an entry for a requested object was found in the system object control block, APSLSOCB, but the entry interface data block (APSLIDB) was not free. The entry was in use and must be disconnected before it is reused.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0973**Explanation**

This abend is issued by module APSLOPEN— not enough storage exists for a linked list element.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

The REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0974**Explanation**

This abend is issued by module APSLOPEN— the data control block (DCB) points to the data extent block (DEB), but the DEB does not point back to the DCB.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0975

Explanation

This abend is issued by module APSLOPEN— the data control block (DCB) does not point to a data extent block (DEB). The DEB ID must be X'F' in the low-order 4 bits of DEBEBID.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0976

Explanation

This abend is issued by module APSLOPEN— because the library had either an extent error or a nonzero BLDL return code, PSF tried to close it, but did not succeed.

System action

PSF processing ends abnormally.

System programmer response

If Data Management messages preceded by IEC are received, follow the procedures for your operating system before you contact the IBM Support Center or use your electronic link with IBM service.

0977

Explanation

This abend is issued by module APSLOPEN— PSF tried to reopen the library but was unable to do so because the library had either an extent error or a nonzero BLDL return code.

System action

PSF processing ends abnormally.

System programmer response

If Data Management messages preceded by IEC are received, follow the procedures for your operating system before you contact the IBM Support Center or use your electronic link with IBM service.

0978

Explanation

This abend is issued by module APSLOPEN— a request to connect to a library was received but cannot be done because of one of these:

- The combination of the encoded ID and library type was not valid. The combination of the encoded ID and library type is used to indicate that the library wanted. LASI did not recognize the combination specified. The encoded ID is found in the RRBEID field of the RRB. The library type is found in the RRB_LIBTYPE field of the RRB.
- Not enough storage exists for control blocks or buffers.

System action

PSF processing ends abnormally.

System programmer response

- If PSF issues messages to the operator console that identify the cause of the error, use these messages to correct the error.
- If no messages are issued, this abend reason code might indicate a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0979

Explanation

This abend is issued by module APSLOPEN— an IGET was issued for a member from a USERLIB before the invocation of APSLDYNA for the USERLIB.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0980

Explanation

This abend is issued by module APSLUSSO— not enough storage was available for a work area.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

The REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0981**Explanation**

This abend is issued by module APSLDYND— the system function for CLOSE of a user library did not succeed.

System action

PSF processing ends abnormally.

System programmer response

If Data Management messages preceded by IEC are received, follow the procedures for your operating system before you contact the IBM Support Center or use your electronic link with IBM service.

0982**Explanation**

This abend is issued by module APSLDYND— the system function for the deconcatenation of a user library did not succeed.

System action

PSF processing ends abnormally.

System programmer response

If Data Management messages preceded by IEC are received, follow the procedures for your operating system before you contact the IBM Support Center or use your electronic link with IBM service.

0983**Explanation**

This abend is issued by module APSLDYND— the system function for the deallocation of a user library did not succeed.

System action

PSF processing ends abnormally.

System programmer response

If Data Management messages preceded by IEC are received, follow the procedures for your operating system before you contact the IBM Support Center or use your electronic link with IBM service.

0987**Explanation**

This abend is issued by module APSLDYNA— an internal request was received to allocate and open a user library. The user libraries are already allocated and open.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0988**Explanation**

This abend is issued by module APSLDYNA— the JCL keyword required for user library processing (USERLIB) was not specified. APSLDYNA should not be called.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0990

Explanation

This abend is issued by module APSLIREP— the record resource block (RRB) is not valid. The control block ID is not RRB followed by a space.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0992**Explanation**

This abend is issued by module APSLIREP— the record resource block (RRB) is not a message type (MSG). A message-type RRB is required for a repositioning request.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0993**Explanation**

This abend is issued by module APSLIREP— the record resource block (RRB) is a message type (MSG). However, the RRB was not defined with a FIRSTCALL(PUT) macro, which is required for a repositioning request.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0994**Explanation**

This abend is issued by module APSLIREP— the interface data block (APSLIDB) is not valid. The control block ID is not IDB. The address of the IDB is in register 2.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0996**Explanation**

This abend is issued by module APSLIREP— the record resource block (RRB) does not point to an interface data block (IDB). The pointer is zero.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0998**Explanation**

This abend is issued by module APSLIREP— a request was made to reposition the message data set. The repositioning information passed was not valid. The block of data requested was less than the minimum of zero.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

099A

Explanation

This abend is issued by module APSLIREP— a request was made to reposition the message data set, but the repositioning information passed was not valid. The requested block number was greater than the number of blocks of data in the message data set.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

099C**Explanation**

This abend is issued by module APSLIREP— a request was made to reposition the message data set. However, the repositioning information passed was not valid. The requested number was less than 0, the lowest record number that can be requested.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

099E**Explanation**

This abend is issued by module APSLIREP— a request was made to reposition the message data set. However, an incorrect buffer block was encountered when searching the chain. The buffer block ID must be BUFB, but was not. Register 2 contains the address of the incorrect buffer block.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

09A1**Explanation**

This abend is issued by module APSLIREP— a request was made to reposition the message data set. However, an incorrect buffer descriptor word (BDW) was encountered in the buffer block. Register 2 contains the address of the incorrect BDW.

The incorrect BDW might be caused by one of these:

- The BDW contains a negative length.
- The BDW flags are not all zero.
- The BDW contains a length of zero.
- The BDW contains a length less than 9, the minimum valid length.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

09A3**Explanation**

This abend is issued by module APSLIREP— a request was made to reposition the message data set, but an incorrect record descriptor word (RDW) was encountered in the buffer block. Register 2 contains the address of the incorrect RDW.

- The RDW contains a negative length.
- The RDW flags are not all zero.
- The RDW contains a length of zero.
- The RDW contains a length less than 9, the minimum valid length.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

09A4

Explanation

This abend is issued by module APSLIREP— a request was made to reposition the message data set, but the record requested was not in the data set. The correct buffer block was found, but the record was not there. Register 2 contains the address of the buffer block.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

09A5**Explanation**

This abend is issued by module APSLIREP— the APSIBLD macro issued a nonzero return code when the message data set was being reinitialized.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

09A6**Explanation**

This abend is issued by module APSLIREP— the APSIPUT macro issued a nonzero return code on a STOP PROCESSING request.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

09A7**Explanation**

This abend is issue by module APSLRUSS— the function that is requested is not known to this module.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

09A8**Explanation**

This abend is issued by module APSLRUSS— the file cannot be read because nonblock option was used when it was opened.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

09A9**Explanation**

This abend is issued by module APSLRUSS— the file descriptor is not valid.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

09AA**Explanation**

This abend is issued by module APSLRUSS— the read count is not valid.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

09AB**Explanation**

This abend is issued by module APSLRUSS— a process is ignoring or blocking the READ request.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error or system error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

09AC**Explanation**

This abend is issued by module APSLRUSS— a buffer is not available.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error or system error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

09AD**Explanation**

This abend is issued by module APSLRUSS— the read request was interrupted by a signal.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error or system error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

09AE**Explanation**

This abend is issued by module APSLUSSO— the RAU was unsuccessful in acquiring TrueType Collection information.

System action

AFP Download Plus processing ends abnormally. This abend might be accompanied by a system GETMAIN abend, such as 878, if AFP Download Plus does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Look in the accompanying message for the RAU return codes to determine whether this is a logic error or if the REGION size must be increased.

09AF**Explanation**

This abend is issued by module APSLUSSO— BPX10PD failed to open a UNIX file system directory.

System action

PSF or AFP Download Plus processing ends abnormally.

System programmer response

Look in the accompanying message for the RAU return codes to determine whether this is a logic error or if the REGION size must be increased.

09B1**Explanation**

This abend is issued by module APSZCMND— the error occurred during the parsing of the CIB data processing command. The CIB contains the information specified in the MODIFY command for PSF.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

09B2**Explanation**

This abend is issued by module APSZCMND— the error occurred during the parsing of the CIB data processing printer name. The CIB contains the information specified in the MODIFY command for PSF.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

09B3**Explanation**

This abend is issued by module APSZCMND— the error is in traversing the CIB data-processing keyword. The CIB contains the information specified in the MODIFY command for PSF.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

09B4**Explanation**

This abend is issued by module APSZCMND— the error is in traversing the CIB data-processing parameter. The CIB contains the information specified in the MODIFY command for PSF.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

09B8**Explanation**

This abend is issued by module APSZTRCE— the printer name, in an internal command list, had a length of zero. A printer name is required.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

09B9**Explanation**

This abend is issued by module APSZTRCE— an incorrect parameter code was found in the internal command list.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

09BB**Explanation**

This abend is issued by module APSZWTO— the control block ID for the PWTO control block is incorrect.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

09BC**Explanation**

This abend is issued by module APSZWTO— a WTO macro call failed.

System action

The PSF operator interface ends abnormally.

System programmer response

This PSF abend reason code indicates that a WTO failed. This might be caused by a PSF logic error or by the WTO. When the PSF operator interface is restarted, try the operator interface command that caused the abend again. If the problem persists, contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

09C0**Explanation**

This abend is issued by module APSZAFSA or APSZRSTR— the incorrect interface block ID is not IPB.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

09C1**Explanation**

This abend is issued by modules APSZFORC and APSZQMAN— the incorrect interface request block ID is not IRB.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

09C2**Explanation**

This abend is issued by module APSZAFSA— the incorrect queue header ID is not QH.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

09C4**Explanation**

This abend is issued by module APSZAFSA— the incorrect common control block ID is not CCB.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

09C5**Explanation**

This abend is issued by module APSZAFSA— the incorrect FSA level control block ID is not SAB.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

09C6

Explanation

This abend is issued by module APSZAFSA— the incorrect FSA queue element ID is not SAE.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

09C7**Explanation**

This abend is issued by module APSZAFSA— the incorrect FSS queue control block ID is not SAQ.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

09C9**Explanation**

This abend is issued by module APSZQMAN— an incorrect queue code was specified in the IRB.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

09CA**Explanation**

This abend is issued by module APSZQMAN— an incorrect request code was specified in the IRB.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

09D5**Explanation**

This abend is issued by module APSZRSTR— the MVS DETACH macro did not succeed in detaching APSZCMND.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system macros to determine why the macro failed or returned unexpected results.

09D6**Explanation**

This abend is issued by module APSZRSTR— the MVS FREEMAIN macro failed to release APSZCMND storage.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system determine why FREEMAIN failed or returned unexpected results. If FREEMAIN reported that the storage requested to be freed is not owned by PSF, it indicates a PSF logic error. If it is a logic error, contact your service representative in the IBM Support Center, or use your electronic link with IBM service for assistance.

09D7**Explanation**

This abend is issued by module APSZRSTR— the MVS ATTACH macro was unsuccessful for module APSZCMND.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system macros to determine why the macro failed or returned unexpected results.

09E0**Explanation**

This abend is issued by module APSZAFSA— APSZAFSA found no free queue headers available.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

09F0**Explanation**

This abend is issued by module APSZFORC— APSZFORC received an incorrect command.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

09F1**Explanation**

This abend is issue by module APSZDTCP— an incorrect keyword was used to call this module.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

09F2**Explanation**

This abend is issued by module APSZDAFP— an incorrect parameter is specified with a keyword.

System action

The PSF operator interface ends abnormally. The operator interface is restarted once.

System programmer response

This abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

09FE**Explanation**

This abend is issued by modules APSZCMND and APSZRSTR— the MVS QEDIT macro was unsuccessful.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system macros to determine why the macro failed or returned unexpected results.

09FF**Explanation**

This abend can be issued by any module— this abend is issued by the operator interface to end without a memory dump. This abend might reflect a problem, depending on the associated messages issued with it.

System action

The operator interface is ended. No system dump is generated.

System programmer response

See associated messages to determine whether this abend indicates a logic error.

0A00**Explanation**

This abend is issued by module APSUEXTI— the GETMAIN macro failed for an exit control block.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0A10**Explanation**

This abend is issued by module APSUREXT— an incorrect Exit-type parameter was received.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0A11**Explanation**

This abend is issued by module APSUREXT— an incorrect Resource-type parameter was received.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0A12**Explanation**

This abend is issued by module APSUREXT— LASI's attempt to get the PDS concatenation resulted in an unrecoverable error.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0A20**Explanation**

This abend is issued by module APSUREXT— the system has insufficient storage for the RLST entry.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0A21**Explanation**

This abend is issued by module APSUREXT— LASI's attempt to get the data set label resulted in the return of an error.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM

Support Center or use your electronic link with IBM service for assistance with this error code.

0A30**Explanation**

This abend is issued by module APSUBLKB— this error occurred when an exit called APSUBLK; ECASABP was not valid. The exit either modified ECASABP or modified the storage pointed to by ECASABP.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0A31**Explanation**

This abend is issued by module APSUBLKB— this error occurred when an exit called APSUBLK; a valid APSGCCB cannot be found. The exit modified PSF storage.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0A40**Explanation**

This abend is issued by module APSUPUTB— this error occurred when an exit called APSUPUT; ECASABP was not valid. The exit either modified ECASABP or modified the storage pointed to by ECASABP.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM

Support Center or use your electronic link with IBM service for assistance with this error code.

0A41**Explanation**

This abend is issued by module APSUPUTB— this error occurred when an exit called APSUPUT; a valid APSGCCB cannot be found. The exit modified PSF storage.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0A50**Explanation**

This abend is issued by module APSUFSSI— the call to BPX1SDD to dub processes failed.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates that the call to BPX1SDD failed. See the return code and reason code in the accompanying message for more details.

0A51**Explanation**

This abend is issued by module APSUFSSI— the DELETE of an installation exit routine failed.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0A52

Explanation

This abend is issued by module APSUFSSI— the GETMAIN macro failed.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0A53**Explanation**

This abend is issued by module APSUEXTI— the DELETE macro failed when it was attempting to delete an installation exit routine.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0A54**Explanation**

This abend is issued by module APSUEXIT or APSUFEXT— the input parameter to the module is not valid.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM

Support Center or use your electronic link with IBM service for assistance with this error code.

0A55**Explanation**

This abend is issued by module APSUNEXT— the input parameter to APSUNEXT is not valid.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0A58**Explanation**

This abend is issued by module APSUEXTI— APSUEXTI received a nonzero return code from the invocation of the CEEPIPI to add an entry. For further information, see message APS097I, which is issued before this abend.

System action

PSF processing ends abnormally. No system dump is generated.

System programmer response

Make sure that any assembler installation exits are named correctly and are link-edited as assembler exits. If the exits are correct, this PSF abend code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0A59**Explanation**

This abend is issued by module APSUEXIT or APSUFEXT— the module received a nonzero return code from the invocation of the CEEPIPI to call as a subroutine. For further information, see message APS7000I, which is issued before this abend.

System action

PSF processing ends abnormally. No system dump is generated.

System programmer response

This PSF abend code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0A5A**Explanation**

This abend is issued by module APSUNEXT— APSUNEXT received a nonzero return code from the invocation of the CEEPIPI to call as a subroutine. For further information, see message APS7000I, which is issued before this abend.

System action

PSF processing ends abnormally. No system dump is generated.

System programmer response

This PSF abend code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0A5B**Explanation**

This abend is issued by module APSUREXT— APSUREXT received a nonzero return code from the invocation of the CEEPIPI to call as a subroutine. For further information, see message APS7000I, which is issued before this abend.

System action

PSF processing ends abnormally. No system dump is generated.

System programmer response

This PSF abend code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0A5C**Explanation**

This abend is issued by module APSPPNST— the load of the CEEPIPI routine failed.

System action

PSF processing ends abnormally.

System programmer response

Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0A5D**Explanation**

This abend is issued by module APSPPNST— APSPPNST received a nonzero return code from the invocation of the CEEPIPI to initialize for subroutines. For further information, see message APS096I, which is issued before this abend.

System action

PSF processing ends abnormally. No system dump is generated.

System programmer response

This PSF abend code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0A5E**Explanation**

This abend is issued by module APSPPNST— APSPPNST received a nonzero return code from the invocation of the CEEPIPI to add an entry. For further information, see message APS097I, which is issued before this abend.

System action

PSF processing ends abnormally. No system dump is generated.

System programmer response

Make sure that any assembler installation exits are named correctly and are link-edited as assembler exits. If the exits are correct, this PSF abend code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0A5F**Explanation**

This abend is issued by module APSUEXIT— APSUEXIT determined that both 3800 Line-Mode Conversion and Line Mode Migration processing were activated for the

same data set. For further information, see message APS7002I, which is issued before this abend.

System action

PSF processing ends abnormally. No system dump is generated.

System programmer response

This PSF abend indicates an installation exit error. Change your exits so both 3800 Line-Mode Conversion and Line Mode Migration processing are not active for the same data set.

0A60**Explanation**

This abend is issued by module APSUEXIT— APSUEXIT determined that both Line Mode Migration processing for a 4245 FCB and Line Mode Migration processing for a 4248 FCB were activated for the same data set. For further information, see message APS7003I, which is issued before this abend.

System action

PSF processing ends abnormally. No system dump is generated.

System programmer response

This PSF abend indicates an installation exit error. Change your exits so Line Mode Migration processing for a 4245 FCB or Line Mode Migration processing for a 4248 FCB are active for a data set, but not both.

0B00**Explanation**

This abend is issued by module APSIBLD— a request was received to create an input data set from an output data set, but the data set passed is not an output internal data set.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0B01**Explanation**

This abend is issued by module APSIBLD— the push-down stack does not point to a valid record resource block (RRB). The first 4 bytes of the area pointed to by the stack are not RRB followed by a space.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0B02**Explanation**

This abend is issued by module APSIBLD— the RRBAD parameter on the APSIBLD macro does not point to a record resource block (RRB). The first 4 bytes must be RRB followed by a space.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0B04**Explanation**

This abend is issued by module APSIDEQ— the push-down stack does not point to a valid record resource block (RRB). The first 4 bytes of the area pointed to by the stack must be RRB followed by a space.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0B05

Explanation

This abend is issued by module APSIGET— the area pointed to by GRITAD is not a RIT. The first 8 bytes must be APSGRIT followed by a space.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OB10**Explanation**

This abend is issued by module APSIGET— the record resource block (RRB) does not point to an RRB. The first 4 bytes must be RRB followed by a space.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OB11**Explanation**

This abend is issued by module APSIPUT— the record resource block (RRB) does not point to an RRB. The first 4 bytes must be RRB followed by a space.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OB12**Explanation**

This abend is issued by module APSIGET— the RRB used for an APSIGET QUERY was previously used for

an APSIGET or APSIPUT without reinvocation of APSIBLD.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OB13**Explanation**

This abend is issued by module APSIGET— an APSIGET that uses an RRB that is not TYPE(LIB) is issued.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OC00**Explanation**

This abend is issued by module APSMMSG— the return reason code that is specified in the DUMP JCL is encountered.

System action

PSF processing ends abnormally.

System programmer response

This abend occurred because it was requested by the user. To cancel this abend, correct the Printer Inventory or PRINTDEV parameter.

OC01**Explanation**

This abend is issued by module APSMMSG— no conversion flag was set for the variable insert currently being processed by this routine.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0C02**Explanation**

This abend is issued by module APSMMSG— a message ID (MSGID) was not valid. The MSGID either was equal to zero or was not in the range of the message index in the message text module.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0C03**Explanation**

This abend is issued by module APSMMSG— the TRACE keyword of the invocation of APSXMSG has an incorrect value that is taken from a routine variable.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0C04**Explanation**

This abend is issued by module APSMMSG— the WTOID parameter was not valid. The WTOID parameter in the delete operator message (DOM) macro was zero.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0C20**Explanation**

This abend is issued by module APSMMSG— the message count that is specified in the Dump parameter is matched.

System action

PSF processing ends abnormally.

System programmer response

This abend occurred because it was requested by the user. To cancel this abend, correct the Dump parameter in the Printer Inventory or in the PRINTDEV.

0C22**Explanation**

This abend is issued by module APSMMSG— a SEND FSA Initiated Termination (FIT) requested by the PSF message exit failed.

System action

PSF processing ends abnormally.

System programmer response

To bypass this abend, do not request a FIT in the message exit.

0C30**Explanation**

This abend is issued by module APSHMPMF— APSHMPMF cannot get storage to create a message string object.

System action

AFP Download Plus processing ends abnormally. This abend might be accompanied by a system GETMAIN abend, such as 878, if AFP Download Plus does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Increase the REGION parameter in the AFP Download Plus startup procedure.

OC31**Explanation**

This abend is issued by module APSHDWPF or APSHMPMF— APSHDWPF or APSHMPMF cannot get storage to create a string buffer object.

System action

AFP Download Plus processing ends abnormally. This abend might be accompanied by a system GETMAIN abend, such as 878, if AFP Download Plus does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Increase the REGION parameter in the AFP Download Plus startup procedure.

OD00**Explanation**

This abend is issued by module APSGGGETM— APSGGGETM received an incorrect parameter list.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OD01**Explanation**

This abend is issued by module APSGGGETM— a logic error occurred because an element was not available in a new storage block.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support

Center or use your electronic link with IBM service for assistance with this error code.

OD03**Explanation**

This abend is issued by module APSGGGETM— a logic error occurred because an element was not available in an initial storage block.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OD04**Explanation**

This abend is issued by module APSGGGETM— a logic error occurred because an element was not available in a new chain of storage blocks.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OD05**Explanation**

This abend is issued by module APSGGGETM— APSGGGETM received a nonzero return code from the system GETMAIN macro.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

OD06**Explanation**

This abend is issued by module APSGGETM— a logic error occurred because no storage was available in a new pseudo-subpool storage block.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OD07**Explanation**

This abend is issued by module APSGGETM— a request for page-fixed storage crosses a 4 KB boundary.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OD08**Explanation**

This abend is issued by module APSGGETM— a PSF logic error occurred because a pseudo-subpool storage block did not exist.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OD09**Explanation**

This abend is issued by module APSGGETM— a PSF logic error occurred because a pseudo-subpool chain did not exist.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OD0A**Explanation**

This abend is issued by module APSGGETM— a request for page-fixed storage failed; nonzero return was received from the system page-fixing routine.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system macros to determine why the macro failed or returned unexpected results.

OD0B**Explanation**

This abend is issued by module APSGGETM— the GETMAIN macro for the storage management control block failed.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

OD0C**Explanation**

This abend is issued by module APSOAT— not enough storage exists for an AttributeTriplet object.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Increase the REGION parameter in the PSF startup procedure.

OD0E**Explanation**

This abend is issued by module APSOCOLL— not enough storage exists for a Collection object.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Increase the REGION parameter in the PSF startup procedure.

OD0F**Explanation**

This abend is issued by module APSOVEC— not enough memory exists for a vector array.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Increase the REGION parameter in the PSF startup procedure.

OD10**Explanation**

This abend is issued by module APSGFREE— an incorrect type of FREEMAIN request was received.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OD11**Explanation**

This abend is issued by module APSGFREE— a logic error occurred because an element to be freed was not in use.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OD12**Explanation**

This abend is issued by module APSGFREE— a logic error occurred because no pseudo-subpool storage blocks existed.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OD13**Explanation**

This abend is issued by module APSGFREE— a logic error occurred because no element storage blocks existed.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OD14**Explanation**

This abend is issued by module APSGFREE— a logic error occurred because the correct element storage-block chain cannot be found.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OD15**Explanation**

This abend is issued by module APSGFREE— a logic error occurred because the element address was not within the bounds of any of the storage blocks.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OD16**Explanation**

This abend is issued by module APSGFREE— a page free of specified storage failed; a nonzero return was received from the PGSER macro.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system macros to determine why the macro failed or returned unexpected results.

OD17**Explanation**

This abend is issued by module APSGFREE— a logic error occurred because the storage-block chain for the specified pseudo subpool cannot be found.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OD18**Explanation**

This abend is issued by module APSGFREE— APSGFREE received a nonzero return from the system FREEMAIN macro.

System action

PSF processing ends abnormally.

System programmer response

See your operating system publication that explains system determine why FREEMAIN failed or returned unexpected results. If FREEMAIN reported that the storage requested to be freed is not owned by PSF, it

indicates a PSF logic error. If it is a logic error, contact your service representative in the IBM Support Center, or use your electronic link with IBM service for assistance.

OD19**Explanation**

This abend is issued by module APSGFREE— the free element counter for the storage management control block structure indicates how many free elements are available. A logic error occurred when a free element was expected, but not found, in the storage management control block structure.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OD1A**Explanation**

This abend is issued by module APSHODDS— AFP Download Plus cannot append the auxiliary resource group file or the auxiliary MO:DCA file to the output auxiliary file. See the return code and reason code in the accompanying message for more details.

System action

AFP Download Plus processing ends abnormally.

System programmer response

If Data Management messages preceded by IEC are received, follow the procedures for your operating system before you contact the IBM Support Center or use your electronic link with IBM service.

OD20**Explanation**

This abend is issued by APSDECH and all APSXRETN users— Any module that calls APSXRETN and APSDECH abends with this reason code whenever the return reason code that is specified on the Dump parameter is encountered.

System action

PSF processing ends abnormally.

System programmer response

This abend occurred because it was requested by the user. To cancel this abend, correct the Dump parameter in the Printer Inventory or on the PRINTDEV statement.

OD21**Explanation**

This abend is issued by module APSGGETM— the element size that is specified in the invocation of APSXGETM is too large.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OD31**Explanation**

This abend is issued by module APSGFSAI— a GETMAIN for storage below the 16 MB line failed. The storage was needed to contain save/autodata areas.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

OD32**Explanation**

This abend is issued by module APSGFSAI— a GETMAIN for storage above the 16 MB line failed. The storage was needed to contain save/autodata areas.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0D33**Explanation**

This abend is issued by module APSGFSAI— a GETMAIN for the data encapsulation area failed. The storage was requested from a key zero subpool to support encapsulation.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0D41**Explanation**

This abend is issued by module APSGFSSI— a GETMAIN for storage below the 16 MB line failed. The storage was needed to contain a copy of the module address table.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

Note: Reason codes 0E00 through 0E7F are used to end PSF without a memory dump and without message APS050I. These codes do not represent logic errors.

0D54**Explanation**

This abend is issued by module APSGMBR— the input parameters to APSGMBR were not a valid combination.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a probable PSF logic error. Contact your service representative in the IBM support center or use your electronic link with IBM service for assistance with this error code.

0D56**Explanation**

This abend is issued by module APSGCINT— CEEPIPI failed to load.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0D57

Explanation

This abend is issued by module APSGCINT— CEEPIPI failed to be initialized for subroutines.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OD58**Explanation**

This abend is issued by module APSGCINT— not enough storage for APSGCPCB.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

OD60**Explanation**

This abend is issued by module APSGCET— the z/OS Conversion Facility called by APSGCET indicated an abend.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OD70**Explanation**

This ABEND is issued by module APSGGETM on behalf of a PSF module that is using the ULCRCreat method — not enough memory was available to build an instance of the APSOULCR (UniversalLinker) class for list management.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

OD71**Explanation**

This ABEND is issued by module APSGGETM on behalf of a PSF module that is using the ULCRAdd2Head, ULCRAdd2Tail, ULCRInsertBefore, or ULCRInsertAfter methods— not enough memory was available to build an instance of the APSOUCLR (LinkListElement) class for list management.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode,

increase the REGION parameter used in the PSF startup procedure.

OD77**Explanation**

This abend is issued by module APSHDWPF— the system has insufficient storage for the RGF object.

System action

AFP Download Plus processing ends abnormally. This abend might be accompanied by a system GETMAIN abend, such as 878, if AFP Download Plus does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This AFP Download Plus abend reason code indicates that the REGION size must be increased. Increase the REGION size in the AFP Download Plus startup procedure.

OD78**Explanation**

This abend is issued by module APSHFJOF— BPX1WRT failed to write to the UNIX file system file.

System action

AFP Download Plus processing ends abnormally.

System programmer response

See the accompanying message to determine the cause of the BPX1WRT error and how to correct it. Correct the error and run the job again. If the error cannot be corrected with the information in the accompanying message, this AFP Download Plus abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OD79**Explanation**

This abend is issued by module APSHFJOF— BPX1OPN failed to open a UNIX file system file.

System action

AFP Download Plus processing ends abnormally.

System programmer response

See the accompanying message to determine the cause of the BPX1OPN error and how to correct it. Correct the error and run the job again. If the error cannot be corrected with the information in the accompanying message, this AFP Download Plus abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OD80**Explanation**

This abend can be issued by any module— the system has insufficient memory for the UFO object.

System action

PSF or AFP Download Plus processing ends abnormally. This abend might be accompanied by a system GETMAIN abend, such as 878, if PSF or AFP Download Plus does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This abend reason code indicates that the REGION size must be increased. For PSF, if the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request; if the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure. For AFP Download Plus, increase the REGION size in the AFP Download Plus startup procedure.

OD81**Explanation**

This abend is issued by APSHFJOF— the JOF object cannot be created.

System action

AFP Download Plus processing ends abnormally.

System programmer response

This AFP Download Plus abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OD82

Explanation

This abend is issued by module APSPDSC—BPX1OPN failed to open a UNIX file system file.

System action

AFP Download Plus processing ends abnormally.

System programmer response

See the accompanying message to determine the cause of the BPX1OPN error and how to correct it. Correct the error and run the job again. If the error cannot be corrected with the information in the accompanying message, this AFP Download Plus abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OD83**Explanation**

This abend is issued by APSPDSC— the MDF object cannot be created.

System action

AFP Download Plus processing ends abnormally.

System programmer response

This AFP Download Plus abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OD84**Explanation**

This abend is issued by module APSPDSC—BPX1OPN failed to open a UNIX file system file.

System action

AFP Download Plus processing ends abnormally.

System programmer response

See the accompanying message to determine the cause of the BPX1OPN error and how to correct it. Correct the error and run the job again. If the error cannot be corrected with the information in the accompanying message, this AFP Download Plus abend reason code indicates a possible logic error. Contact your service representative in the IBM Support

Center or use your electronic link with IBM service for assistance with this error code.

OD85**Explanation**

This abend is issued by module APSPDSC— the system has insufficient storage for a 32 KB write buffer.

System action

AFP Download Plus processing ends abnormally. This abend might be accompanied by a system GETMAIN abend, such as 878, if AFP Download Plus does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This AFP Download Plus abend reason code indicates that the REGION size must be increased. Increase the REGION size in the AFP Download Plus startup procedure.

OD86**Explanation**

This abend can be issued by any module— the system has insufficient memory for the UNIX file system file status control block.

System action

AFP Download Plus processing ends abnormally. This abend might be accompanied by a system GETMAIN abend, such as 878, if AFP Download Plus does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This AFP Download Plus abend reason code indicates that the REGION size must be increased. Increase the REGION size in the AFP Download Plus startup procedure.

OD87**Explanation**

This abend is issued by APSPDSC— the RGF object cannot be created.

System action

AFP Download Plus processing ends abnormally.

System programmer response

This AFP Download Plus abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OD88**Explanation**

This abend is issued by module APSHPDSC—BPX1OPN failed to open a UNIX file system file.

System action

AFP Download Plus processing ends abnormally.

System programmer response

See the accompanying message to determine the cause of the BPX1OPN error and how to correct it. Correct the error and run the job again. If the error cannot be corrected with the information in the accompanying message, this AFP Download Plus abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OD89**Explanation**

This abend is issued by APSHPDSC— the RVF object cannot be created.

System action

AFP Download Plus processing ends abnormally.

System programmer response

This AFP Download Plus abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OD90**Explanation**

This abend can be issued by any module— the system has insufficient memory for the UDO object.

System action

PSF or AFP Download Plus processing ends abnormally. This abend might be accompanied by a system GETMAIN abend, such as 878, if PSF or AFP Download Plus does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This abend reason code indicates that the REGION size must be increased. For PSF, if the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request; if the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure. For AFP Download Plus, increase the REGION size in the AFP Download Plus startup procedure.

OD91**Explanation**

This abend can be issued by any module— the system has insufficient memory for the PFN object.

System action

AFP Download Plus processing ends abnormally. This abend might be accompanied by a system GETMAIN abend, such as 878, if AFP Download Plus does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This AFP Download Plus abend reason code indicates that the REGION size must be increased. Increase the REGION size in the AFP Download Plus startup procedure.

OD92**Explanation**

This abend can be issued by any module— the system has insufficient memory for the PPN object.

System action

AFP Download Plus processing ends abnormally. This abend might be accompanied by a system GETMAIN abend, such as 878, if AFP Download Plus does not have enough storage to do its termination functions. Because of the lack of available storage, the System

Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This AFP Download Plus abend reason code indicates that the REGION size must be increased. Increase the REGION size in the AFP Download Plus startup procedure.

OD93

Explanation

This abend can be issued by any module— creation of a UDO object failed with an incorrect path name or size.

System action

PSF or AFP Download Plus processing ends abnormally.

System programmer response

This abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OD95

Explanation

This abend can be issued by any module— the system has insufficient storage for the AFPDPStatus object.

System action

AFP Download Plus processing ends abnormally. This abend might be accompanied by a system GETMAIN abend, such as 878, if AFP Download Plus does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This AFP Download Plus abend reason code indicates that the REGION size must be increased. Increase the REGION parameter in the AFP Download Plus startup procedure.

OD96

Explanation

This abend can be issued by any module— a Download Data Set object that was passed to the AFPDPStatus object is not valid.

System action

AFP Download Plus processing ends abnormally.

System programmer response

This AFP Download Plus abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OD98

Explanation

This abend can be issued by any module— the system has insufficient memory for the ENC object.

System action

AFP Download Plus processing ends abnormally. This abend might be accompanied by a system GETMAIN abend, such as 878, if AFP Download Plus does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This AFP Download Plus abend reason code indicates that the REGION size must be increased. Increase the REGION size in the AFP Download Plus startup procedure.

ODA0

Explanation

This abend is issued by multiple modules— PSF or AFP Download Plus cannot get storage for an STR object.

System action

PSF or AFP Download Plus processing ends abnormally. This abend might be accompanied by a system GETMAIN abend, such as 878, if PSF or AFP Download Plus does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This abend reason code indicates that the REGION size must be increased. For PSF, if the print request is processing in direct-printing mode, this REGION size is for the JOB or EXEC JCL statement that contains the request; if the print request is processing in deferred-printing mode, increase the REGION parameter used

in the PSF startup procedure. For AFP Download Plus, increase the REGION size in the AFP Download Plus startup procedure.

ODA1**Explanation**

This abend can be issued by any module— incorrect parameters were passed to the ENC method.

System action

AFP Download Plus processing ends abnormally.

System programmer response

This AFP Download Plus abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

ODA2**Explanation**

This abend can be issued by any module— the TIME macro failed.

System action

AFP Download Plus processing ends abnormally.

System programmer response

This AFP Download Plus abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

ODA3**Explanation**

This abend is issued by module APSJCK— the system has insufficient storage for the SDS object.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

ODA4**Explanation**

This abend is issued by module APSJCK— the system has insufficient storage for the CPR object.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

ODA5**Explanation**

This abend is issued by module APSJCK— the system has insufficient storage for the tokenization buffer for the CPR object.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is

for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

ODA6**Explanation**

This abend is issued by module APSGSTR— APSGSTR cannot interpret an input parameter.

System action

PSF or AFP Download Plus processing ends abnormally.

System programmer response

This abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

ODA7**Explanation**

This abend can be issued by any module— the system has insufficient memory for the UFO 64 KB write buffer.

System action

PSF or AFP Download Plus processing ends abnormally. This abend might be accompanied by a system GETMAIN abend, such as 878, if PSF or AFP Download Plus does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This abend reason code indicates that the REGION size must be increased. For PSF, if the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request; if the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure. For AFP Download Plus, increase the REGION parameter in the AFP Download Plus startup procedure.

ODA8**Explanation**

This abend can be issued by any module— BPX1WRT failed to write to the UNIX file system file.

System action

AFP Download Plus processing ends abnormally.

System programmer response

See the accompanying message to determine the cause of the BPX1WRT error and how to correct it. Correct the error and run the job again. If the error cannot be corrected with the information in the accompanying message, this AFP Download Plus abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

ODA9**Explanation**

This abend can be issued by any module— an error exists in calculating the write value.

System action

AFP Download Plus processing ends abnormally.

System programmer response

This AFP Download Plus abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

ODAA**Explanation**

This abend is issued by module APSHPDSC— Not enough storage exists for the MDF compression output buffer.

System action

AFP Download Plus processing ends abnormally. This abend might be accompanied by a system GETMAIN abend, such as 878, if AFP Download Plus does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This AFP Download Plus abend reason code indicates that the REGION size must be increased. Increase the REGION size in the AFP Download Plus startup procedure.

ODAB

Explanation

This abend is issued by modules APSHDWPF and APSPDSC— Not enough storage exists for the RGF compression output buffer.

System action

AFP Download Plus processing ends abnormally. This abend might be accompanied by a system GETMAIN abend, such as 878, if AFP Download Plus does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This AFP Download Plus abend reason code indicates that the REGION size must be increased. Increase the REGION size in the AFP Download Plus startup procedure.

ODAC**Explanation**

This abend is issued by APSPDSC — the system has insufficient memory to create the MDD object.

System action

AFP Download Plus processing ends abnormally. This abend might be accompanied by a system GETMAIN abend, such as 878, if AFP Download Plus does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This AFP Download Plus abend reason code indicates that the REGION size must be increased. Increase the REGION size in the AFP Download Plus startup procedure.

ODAD**Explanation**

This abend is issued by APSPDSC — the system has insufficient memory to create the MDD object work buffer.

System action

AFP Download Plus processing ends abnormally. This abend might be accompanied by a system GETMAIN abend, such as 878, if AFP Download Plus does not have enough storage to do its termination functions.

Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This AFP Download Plus abend reason code indicates that the REGION size must be increased. Increase the REGION size in the AFP Download Plus startup procedure.

ODAE**Explanation**

This abend is issued by module APSOTRCE— no storage for trace entry buffer.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Increase the REGION parameter in the PSF startup procedure.

ODBO**Explanation**

This abend can be issued by any module— A compression object that is not valid is passed to a method.

System action

AFP Download Plus processing ends abnormally.

System programmer response

This AFP Download Plus abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

ODB1**Explanation**

This abend can be issued by any module— A compression call sequence error occurred.

System action

AFP Download Plus processing ends abnormally.

System programmer response

This AFP Download Plus abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

ODB2**Explanation**

This abend can be issued by any module— Not enough storage exists for the compression object.

System action

AFP Download Plus processing ends abnormally. This abend might be accompanied by a system GETMAIN abend, such as 878, if AFP Download Plus does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This AFP Download Plus abend reason code indicates that the REGION size must be increased. Increase the REGION size in the AFP Download Plus startup procedure.

ODB3**Explanation**

This abend can be issued by any module— Not enough storage exists for the compression hash table.

System action

AFP Download Plus processing ends abnormally. This abend might be accompanied by a system GETMAIN abend, such as 878, if AFP Download Plus does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This AFP Download Plus abend reason code indicates that the REGION size must be increased. Increase the REGION size in the AFP Download Plus startup procedure.

ODB4**Explanation**

This abend can be issued by any module— A hash table pointer that is not valid is passed to a method.

System action

AFP Download Plus processing ends abnormally.

System programmer response

This AFP Download Plus abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

ODB7**Explanation**

This abend can be issued by any module— A compression method is called after a compression error.

System action

AFP Download Plus processing ends abnormally.

System programmer response

This AFP Download Plus abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

ODB8**Explanation**

This abend is issued by modules APSHDCLS and APSHDWPF— An input buffer pointer or size that is not valid is passed to a method.

System action

AFP Download Plus processing ends abnormally.

System programmer response

This AFP Download Plus abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

ODB9

Explanation

This abend is issued by modules APREPGEX and APSPDSC— An output buffer pointer or size that is not valid is passed to a method.

System action

AFP Download Plus processing ends abnormally.

System programmer response

This AFP Download Plus abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0E00**Explanation**

This abend is issued by module APSCSNA— PSF was ended because of a return code from the Page Printer Communications Component (PPCC) APPC_INITIALIZE macro. Message APS922I describes the condition that caused this abend. Depending on the return code (described in message APS922I), this might be a problem.

System action

PSF processing ends abnormally. No system dump is generated.

System programmer response

Use the information that is contained in the associated APS922I message to correct this error.

0E01**Explanation**

This abend is issued by module APSCSNA— PSF was ended because of a return code from the Page Printer Communications Component (PPCC) APPC_ACTIVATE macro. Message APS922I describes the condition that caused this abend.

System action

PSF processing ends abnormally. No system dump is generated.

System programmer response

Use the information that is contained in the associated APS922I message to correct this error.

0E02**Explanation**

This abend is issued by module APSCSNA— PSF ended because the attempt limit was reached while PSF was attempting to activate a session with a Systems Network Architecture-attached printer. Message APS922I describes the condition that caused this abend.

System action

PSF processing ends abnormally. No system dump is generated.

System programmer response

Use the information that is contained in the associated APS922I message to correct this error.

0E03**Explanation**

This abend is issued by module APSCSNA— PSF ends because of a return code from the Page Printer Communications Component (PPCC) APPC_DEALLOCATE macro. Message APS922I describes the condition that caused this abend.

System action

PSF processing ends abnormally.

System programmer response

Use the information that is contained in the associated APS922I message to correct this error.

0E04**Explanation**

This abend is issued by module APSCSNA— PSF ends because of a return code from the Page Printer Communications Component (PPCC) APPC_ALLOCATE macro. Message APS922I describes the condition that caused this abend.

System action

PSF processing ends abnormally. No system dump is generated.

System programmer response

Use the information that is contained in the associated APS922I message to correct this error.

0E05

Explanation

This abend is issued by module APSCSNA— PSF ends because the attempt limit was reached while PSF was attempting to allocate an SNA-attached printer. Message APS922I describes the condition that caused this abend.

System action

PSF processing ends abnormally. No system dump is generated.

System programmer response

Use the information that is contained in the associated APS922I message to correct this error.

OE08**Explanation**

This abend is issued by module APSCSNA— PSF ends either because of a return code from a Page Printer Communications Component (PPCC) verb or because of a Failure action = Stop in the Printer Inventory or Failure = Stop on the PRINTDEV statement. Message APS922I describes the condition that caused this abend.

System action

PSF processing ends abnormally. No system dump is generated.

System programmer response

Use the information that is contained in the associated APS922I message to correct this error.

OE09**Explanation**

This abend is issued by module APSCCLR— PSF ends because a FAILURE=STOP (a PRINTDEV JCL parameter) was specified and the printer is inoperative.

System action

PSF processing ends abnormally. No system dump is generated.

OE0A**Explanation**

This abend is issued by module APSCCLR— PSF ends because Disconnect action = Stop was specified in the Printer Inventory or TIMEOUT = STOP was specified on

the PRINTDEV statement and the disconnect interval expired.

System action

PSF processing ends abnormally. No system dump is generated.

System programmer response

This abend occurred because it was requested by the user. To cancel this abend, correct the Printer Inventory or PRINTDEV parameter.

OE0C**Explanation**

This abend is issued by module APSCINIT— APSCINIT detected an error when PSF attempted to load the Page Printer Communications Component (PPCC). The PPCC load module is probably not in an authorized library.

System action

PSF processing ends abnormally. No system dump is generated.

System programmer response

Ensure that PPCC is in an authorized library.

OE0E**Explanation**

This abend is issued by module APSCSNA— a return code of OK(DATA) or HALTREQD(DATA) was returned from the RECEIVE and WAIT verb, but OK(SEND) or HALTREQD(SEND) was expected.

System action

PSF processing ends abnormally. No system dump is generated.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OE10**Explanation**

This abend is issued by module APSTCP— PSF ends because a TCP/IP end return code was received and Failure action = stop was specified in the Printer

Inventory or FAILURE = STOP was specified on the PRINTDEV statement.

System action

PSF processing ends abnormally. No system dump is generated.

System programmer response

Use the information that is contained in message APS934I to correct this error.

0E11

Explanation

This abend is issued by module APSTCP— PSF ends because a TCP/IP end return code with no attempt to resend was received.

System action

PSF processing ends abnormally. No system dump is generated.

System programmer response

Use the information that is contained in message APS934I to correct this error.

0E12

Explanation

This abend is issued by module APSTCP— PSF ends because an end return code was received from APSNLINK

System action

PSF processing ends abnormally. No system dump is generated.

System programmer response

Use the information that is contained in message APS934I to correct this error.

0E13

Explanation

This abend is issued by module APSTCP— PSF ends because FAILURE=STOP was specified on the PRINTDEV parameter on the JCL, and an end return code was received from APSNLINK.

System action

PSF processing ends abnormally. No system dump is generated.

System programmer response

Use the information that is contained in message APS934I to correct this error.

0E14

Explanation

This abend is issued by module APSTCP— PSF ends because TCPLINK reached its attempt limit for calling APSNLINK.

System action

PSF processing ends abnormally. No system dump is generated.

System programmer response

Use the information that is contained in message APS934I to correct this error.

0E19

Explanation

This abend is issued by module APSCIPRT— APSCIPRT determined that no input-media bins from which to print pages are available. Therefore, the printer is unusable.

System action

PSF processing ends abnormally. No system dump is generated.

0E20

Explanation

This abend is issued by module APSTCP, APSCCTME, APSNRM, APSNSSND— the connect interval timer expired before connection with the printer was successful.

System action

PSF issues message APS939I. PSF processing ends abnormally.

System programmer response

See message APS939I.

0E21

Explanation

This abend is issued by module APSDDS— a default or separator page definition or form definition cannot be loaded.

System action

PSF processing ends abnormally. No system dump is generated.

OE22**Explanation**

This abend is issued by module APRBPGEX— a default object container resource for the printer (for example, COMSETUP) was not specified in the PRINTDEV but was required.

System action

PSF processing ends abnormally. No system dump is generated.

System programmer response

Specify the name of the object container resource on the OUTPUT statements for the job header, the data set header, the message data set, and the job trailer. Also, ensure that all print jobs identify the object container resource to be used.

OE23**Explanation**

This abend is issued by module APRBPGEX— a default or separator object container resource for the printer (for example, COMSETUP) cannot be loaded.

System action

PSF processing ends abnormally. No system dump is generated.

System programmer response

PSF issues more messages to the operator console, identifying the cause of the error. Correct the error identified by those messages.

OE24**Explanation**

This abend is issued by module APSDDGB— PSF was stopped because the group level medium finishing request fell outside of the allowed range.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OE30**Explanation**

This abend is issued by module APSEATCD— PSF was ended because the printer became inoperative.

System action

PSF processing ends abnormally. No system dump is generated.

System programmer response

This PSF abend reason code indicates a possible hardware error. Contact your systems engineer for assistance with this error code.

OE31**Explanation**

This abend is issued by module APSE3820— PSF was ended because the printer became inoperative.

System action

PSF processing ends abnormally. No system dump is generated.

System programmer response

This PSF abend reason code indicates a possible hardware error. Contact your systems engineer for assistance with this error code.

OE32**Explanation**

This abend is issued by module APSERRM— PSF was ended because the printer became inoperative.

System action

PSF processing ends abnormally. No system dump is generated.

System programmer response

This PSF abend reason code indicates a possible hardware error. Contact your systems engineer for assistance with this error code.

OE33

Explanation

This abend is issued by module APSERRM— PSF attempted to do I/O to a printer that was assigned (reserved) to another system.

System action

PSF processing ends abnormally. No system dump is generated.

System programmer response

This PSF abend reason code indicates a probable incorrect operational procedure. See the associated APS445I message to correct the error.

OE34

Explanation

This abend is issued by module APSERRM— PSF attempted to do I/O to a printer that was not assigned (reserved) to the system.

System action

PSF processing ends abnormally. No system dump is generated.

System programmer response

The PSF abend reason code indicates a probable incorrect operational procedure. See the associated APS479I message to correct this error.

OE35

Explanation

This abend is issued by module APSEATCD— PSF attempted to do I/O to a printer that was not assigned (reserved) to the system.

System action

PSF processing ends abnormally. No system dump is generated.

System programmer response

This PSF abend reason code indicates a probable incorrect operational procedure. See the associated APS445I message to correct this error.

OE36

Explanation

This abend is issued by module APSEATCD— PSF attempted to do I/O to a printer that was assigned (reserved) to another system.

System action

PSF processing ends abnormally. No system dump is generated.

System programmer response

This PSF abend reason code indicates a probable incorrect operational procedure. See the associated APS479I message to correct this error.

OE50

Explanation

This abend is issued by module APSXWAIT— the operator issued an MVS MODIFY FORCE command to force shutdown of a printer.

System action

PSF issues message APS627I and then ends the Functional Subsystem Application (FSA) for the printer by issuing this abend.

System programmer response

No response required.

OE51

Explanation

This ABEND is issued by module APSGGTM on behalf of a PSF module that is using the APISOESTR (EncodingString) class methods— an unexpected return occurred from the system Unicode conversion routines. Message APS4401I was produced before PSF issued the ABEND and contains the reason code that describes the error.

System action

PSF processing ends abnormally. No system dump is generated.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OE60**Explanation**

AFP Download Plus encountered an error while it was transforming a separator page. The error might be caused by one of these conditions:

- A default or a separator page definition or form definition cannot be loaded.
- A raster font was specified for the MO:DCA IS/3 separator page when the AFPPARMS or Printer Inventory parameter was specified for setting the MO:DCA level to IS/3 for auxiliary files.

System action

AFP Download Plus processing ends abnormally. No system dump is generated.

System programmer response

Use information in the preceding messages that are sent to the console log to correct this error. See *PSF for z/OS: AFP Download Plus* for information about generating IS3-compliant auxiliary files.

OE61**Explanation**

This abend is issued by module APSPMSG— AFP Download Plus encountered an error while it was transforming the message data set from line data to AFP when the AFPPARMS or Printer Inventory parameters are specified for saving IS/3-compliant auxiliary files and setting the MO:DCA level to IS/3 for auxiliary files. The error might be caused by one of these conditions:

- A default or a message data set page definition or form definition cannot be loaded.
- A raster font was specified for the MO:DCA IS3 message data set.

System action

AFP Download Plus processing ends abnormally. No system dump is generated.

System programmer response

Use information in the preceding messages that are sent to the console log to correct this error. See *PSF for z/OS: AFP Download Plus* for information about generating IS3-compliant auxiliary files.

OE80**Explanation**

This abend is issued by module APS4MLMC— a GETMAIN for virtual storage for the 3800 line mode conversion subcomponent failed. The storage was needed for control blocks that are used to support the 3800 line mode conversion function.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

OE82**Explanation**

This abend is issued by module APS4MCLS— an incorrect option was specified in the invocation of APS4MCLS. Valid options are CLOSEDCB, CLOSE, and ABNORMAL.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OE83**Explanation**

This abend is issued by module APS4POSE— an incorrect value was detected for the `paper-length` AFPPARMS control statement parameter or the `Paper Length` Printer Inventory parameter.

System action

AFP Download Plus processing ends abnormally.

System programmer response

Correct the error that is specified by the preceding message and then restart AFP Download Plus.

OE84

Explanation

This abend is issued by module APS4POSE— an incorrect value was detected for the `paper-width` AFPPARMS control statement parameter or the `Paper width Printer Inventory` parameter.

System action

AFP Download Plus processing ends abnormally.

System programmer response

Correct the error that is specified by the preceding message and then restart AFP Download Plus.

OE85

Explanation

This abend is issued by module APS8LMM— a GETMAIN for virtual storage that is used for Line Mode Migration processing failed. The storage was needed for control blocks.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size that is specified in the PSF startup procedure must be increased.

OE90

Explanation

This abend is issued by module APSNINIT— a GETMAIN for virtual storage for the Sockets Extended interface task work area failed.

System action

PSF processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to

do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

Increase the size of the REGION parameter used in the startup procedure for PSF.

OE91

Explanation

This abend is issued by module APSNLINK— the INITAPI for the Sockets Extended interface failed.

System action

PSF processing ends abnormally.

System programmer response

This abend code might indicate that TCP/IP is not started. Ensure that TCP/IP is started. TCP/IP job name that is used by PSF must match the TCP/IP job name that is running on the system. See *PSF for z/OS: Customization* for information about configuring the TCP/IP JOBNAME parameter of PSF. If this reason does not apply, consult your service representative in the IBM Support Center, or use your electronic link with IBM service for assistance related to this error code.

OE92

Explanation

This abend is issued by module APSNLINK or APSHNLNK— the IP address that is specified in the Printer Inventory or on the PRINTDEV statement of the startup procedure for PSF is not valid. It is not a valid dotted decimal address or a valid host name.

System action

PSF processing ends abnormally. No system dump is generated.

System programmer response

Ensure that the IP address is correct, and restart the PSF FSA.

OE93

Explanation

This abend is issued by module APSNLINK— an incorrect character was detected by the verification routine for the IP address.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OE94**Explanation**

This abend is issued by module APSNSEND—APSNSEND detected an incorrect message type.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OE96**Explanation**

This abend is issued by module APSNLINK— the printer issued an incorrect response after an attempt to assign the printer to the PSF FSA.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code results from a possible logic error in the microcode of the printer. Contact your hardware service provider for assistance with this error code.

OE97**Explanation**

This abend is issued by module APSNSSEL—APSNSEL detected an incorrect priority operation.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OE98**Explanation**

This abend is issued by module APSNINIT— the INITAPI cannot be completed. For further information, see message APS948I, which is issued before this abend.

System action

PSF processing ends abnormally.

System programmer response

For the appropriate response, see message APS948I, issued before this abend.

OE9A**Explanation**

This abend is issued by module APSNSEND— the length of data to send is greater than the maximum data length the printer application layer can accept.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OE9C**Explanation**

This abend is issued by module APSNLINK, APSHNLNK, or APSKDVP— both NTCB_IPV4_PTON and NTCB_IPV6_PTON are set ON.

System action

PSF processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OEA0**Explanation**

The abend is issued by module APSKDVP— following a socket INITAPI call failure, the end call to JES failed.

System action

Download for z/OS processing ends abnormally.

System programmer response

Download for z/OS detected this abend. See *PSF for z/OS: Download for z/OS* for more information about this feature. If this error persists, consult your service representative in the IBM Support Center, or use your electronic link with IBM service for assistance related to this error code.

OEA1**Explanation**

This abend is issued by module APSKROUT— Download for z/OS is unable to open the routing-control data set.

System action

Download for z/OS processing ends abnormally.

System programmer response

In the Download for z/OS startup procedure, ensure that the DD name for the routing-control data set is ROUTFILE. Download for z/OS detected this abend. See *PSF for z/OS: Download for z/OS* for more information about this feature.

OEA2**Explanation**

This abend is issued by module APSKROUT— the RECFM of the routing-control data set is not FB.

System action

Download for z/OS processing ends abnormally.

System programmer response

Reallocate the routing-control data set with fixed blocked record format. Download for z/OS detected this abend. See *PSF for z/OS: Download for z/OS* for more information about this feature.

OEA3**Explanation**

This abend is issued by module APSKROUT— the LRECL of the routing-control data set is not 80.

System action

Download for z/OS processing ends abnormally.

System programmer response

Reallocate the routing-control data set with a record length of 80 bytes. Download for z/OS detected this abend. See *PSF for z/OS: Download for z/OS* for more information about this feature.

OEA4**Explanation**

This abend is issued by module APSKROUT— Download for z/OS cannot get storage for the data control block (DCB) for the Download for z/OS routing-control data set.

System action

Processing ends abnormally.

Download for z/OS processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This code indicates that the region size must be increased. Increase the REGION parameter specified in the Download for z/OS startup procedure. Download for z/OS detected this abend. See *PSF for z/OS: Download for z/OS* for more information about this feature.

OEA5**Explanation**

This abend is issued by module APSKLNK— Download for z/OS cannot get storage to store the routing statements from the routing-control data set.

System action

Download for z/OS processing ends abnormally. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System

Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This code indicates that the region size must be increased. Increase the REGION parameter specified in the Download for z/OS startup procedure. Download for z/OS detected this abend. See [PSF for z/OS: Download for z/OS](#) for more information about this feature.

OEA7

Explanation

This abend is issued by module APSKAFPD— the socket INITAPI call failed.

System action

Download for z/OS processing ends abnormally.

System programmer response

Do the recommended action for the error that is indicated in message APS995I. Download for z/OS detected this abend. See [PSF for z/OS: Download for z/OS](#) for more information about this feature.

OEA8

Explanation

This abend is issued by module APSKDVP— an error was reported by APSIPUT in freeing the message data set buffers.

System action

Download for z/OS processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OEA9

Explanation

This abend is issued by module APSKDVP— an error was reported by APSIDEQ in de-queuing and freeing the message data set record resource block (RRB).

System action

Download for z/OS processing ends abnormally.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OF00

Explanation

This abend is issued by modules DCKCHCBE, DCKCPADE, DCKCRABE— PPCC cannot continue because it cannot acquire temporary storage.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

OF01

Explanation

This abend is issued by module DCKCRABE— a password is specified in the APPL entry, but the Access Control Block (ACB) does not contain a password. Because the password parameter is not supported by PPCC, it must not appear in the VTAM network definition statements.

System action

PSF processing ends abnormally.

System programmer response

Correct the APPL statement in the VTAM network definition for PSF.

OF02

Explanation

This abend is issued by module DCKCRABE— either this is an ACF/VTAM logic error, or incorrect information was supplied in the Access Control Block (ACB). The latter case has three possible explanations:

- The APPLID field or the PASSWD field is incorrect, or
- The address of the APPLID field or the PASSWD field is out of range for the application program, or
- The network definition of AUTH for the APPLID is incorrect.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

Correct the APL statement in the VTAM network definition for PSF.

OF03

Explanation

This abend is issued by module DCKCRABE— an attempt was made to initialize PPCC at the time the host APPLID was being closed by VTAM. This can happen if the host program is restarted too quickly or the operator varies the host APPLID inactive.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code. The failing component is VTAM.

OF04

Explanation

This abend is issued by module DCKCRABE— the Systems Network Architecture network inactivity timer of the remote logical unit (LU) expired. This can be caused either by an inappropriate setting of the Systems Network Architecture network inactivity timer at the remote LU (set to a value smaller than the PSF disconnect interval), or by a PSF problem that caused

Systems Network Architecture network activity to cease.

System action

PSF processing ends abnormally.

System programmer response

Reconfigure the printer to have a longer SNA network inactivity timer.

OF05

Explanation

This abend is issued by module DCKCRABE— ACF/VTAM detected an internal logic error in ACF/VTAM.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code. The failing component is VTAM.

OF06

Explanation

This abend is issued by module DCKCRABE— ACF/VTAM canceled a request because an error was detected either during the processing of the request, or in the associated session, task, or address space (such as an abend).

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OF07

Explanation

This abend is issued by module DCKCRINE— PPCC abended and was unable to store the correct reason code because it did not have addressability to its internal control blocks. This default reason code, which is stored in this area at initialization time, indicates a logic error. If register 15 contains the 0Fxx reason code that is wanted for this abend, see that particular code for more details.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0F09**Explanation**

This abend is issued by module DCKCRABE— as the result of an internal logic error, PPCC Resource Management incorrectly specified one of its requests to VTAM.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0F0A**Explanation**

This abend is issued by module DCKCRABE— some of the received data (request or response units) for this session is discarded by VTAM because of a lack of buffer space.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not

have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code indicates that the REGION size must be increased. If the print request is processing in direct-printing mode, this REGION size is for the job or step that contains the request. If the print request is processing in deferred-printing mode, increase the REGION parameter used in the PSF startup procedure.

0F0B**Explanation**

This abend is issued by module DCKCRABE— ACF/VTAM cannot continue because it cannot acquire temporary storage.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts. This PSF abend might be accompanied by a system GETMAIN abend, such as 878, if PSF does not have enough storage to do its termination functions. Because of the lack of available storage, the System Management Facilities (SMF) type 6 accounting record for this data set is not created.

System programmer response

This PSF abend reason code might indicate that the REGION size must be increased. Increase the REGION parameter used in the startup procedure for PSF. This abend reason code might also indicate that the VTAM buffer pools, especially CRPL or LPBUF, are too small. Change the VTAM definition to increase these. If an SNA sense code is present, it might indicate the cause of the VTAM storage shortage. For example, X'08120005' might indicate that the number of independent LUs allowed at the NCP is exceeded. In that case, the NUMILU parameter in the NCP gen must be increased.

0F0C**Explanation**

This abend is issued by module DCKCPLEE— PPCC Presentation Services was given an incorrect or incomplete logical record to send.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0F0D**Explanation**

This abend is issued by modules DCKCPLEE and DCKCRABE— PPCC Resource Management or PPCC Presentation Services detected a protocol violation for a host transaction program. Either an incorrect parameter is submitted or one of the APPC verbs is issued in the wrong sequence.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a possible logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0F0E**Explanation**

This abend is issued by module DCKCRABE— PPCC Resource Management detected an internal logic error. One of its Finite State Machines encountered a state check.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0F0F**Explanation**

This abend is issued by modules DCKCHBBF, DCKCHCRF, DCKCHCSF, DCKCHHDF, DCKCHMAE, DCKCHMBE, DCKCHQRF, DCKCHRTF, DCKCHSSF— PPCC Half-Session Management detected an internal logic error. One of its Finite State Machines encountered a state check.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0F10**Explanation**

This abend is issued by module DCKCPLEE— PPCC Presentation Services detected an internal logic error. One of its Finite State Machines encountered a state check.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

0F11**Explanation**

This abend is issued by modules DCKCHBBF, DCKCHCAE, DCKCHCBE, DCKCHCCE, DCKCHCRF, DCKCHCSF, DCKCHHDF, DCKCHMAE, DCKCHMBE, DCKCHQRF, DCKCHRTF, DCKCHSLE, DCKCHSSF, DCKCPLEE, DCKCRABE— PPCC detected an internal logic error. An internal incoming parameter contains an error.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OF12

Explanation

This abend is issued by modules DCKCHBBF, DCKCHCRF, DCKCHCSF, DCKCHHDF, DCKCHMAE, DCKCHMBE, DCKCHQRF, DCKCHRKE, DCKCHRTF, DCKCHRXE, DCKCHRYE, DCKCHRZE, DCKCPPEE, DCKCRABE— PPCC detected a protocol violation by the remote LU. An UNBIND (FE) was sent unless an incorrect type of UNBIND was received from the remote LU. If the UNBIND is sent, 4 bytes of sense data that follows the UNBIND type code indicate the specific violation. For a description of the sense data, see *SNA Formats*, GA27-3136.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

To determine the cause, see *SNA Formats* for the SNA sense code. The problem might be in the VTAM network definition or in the printer or controller configuration. Otherwise, this PSF reason code might indicate a logic error in PSF, the printer, or the controller. A VTAM buffer trace is needed to determine the failing component.

OF14

Explanation

This abend is issued by module DCKCPLEE— the remote LU indicated that the host LU was sent incorrect data. An FMH7 record is received. For a description of the sense data, see *SNA Formats*, GA27-3136.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

To determine the cause, see *SNA Formats* for the SNA sense code. The problem might be with the VTAM network definition or with the configuration of the

printer or the controller. Otherwise, this PSF reason code might indicate a logic error in PSF, the printer, or the controller. A VTAM buffer trace is needed to determine the failing component.

OF15

Explanation

This abend is issued by modules DCKCHBBF, DCKCHCAE, DCKCHCBE, DCKCHCRF, DCKCHCSF, DCKCHHDF, DCKCHRBE, DCKCHRKE, DCKCHRXE, DCKCHRYE, DCKCHRZE, DCKCHSIE, DCKCHSJE, DCKCPLEE, DCKCRABE— PPCC detected an unexpected condition, which indicates an internal logic error.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

This PSF abend reason code indicates a logic error. Contact your service representative in the IBM Support Center or use your electronic link with IBM service for assistance with this error code.

OF16

Explanation

This abend is issued by module DCKCRABE— the remote LU indicated that the host LU was sent incorrect data. An UNBIND (FE) is received. Four bytes of sense data that follows the UNBIND type code indicate the specific violation. For a description of the sense data, see *SNA Formats*, GA27-3136.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

To determine the cause, see *SNA Formats* for the SNA sense code. The problem might be a VTAM network definition problem or a problem with the configuration of the printer or the controller. Otherwise, this PSF reason code might indicate a logic error in PSF, the printer, or the controller. A VTAM buffer trace is needed to determine the failing component.

OF17

Explanation

This abend is issued by modules DCKCHRXE, DCKCHRYE— the remote LU indicated that the host LU was sent incorrect data. The situation might be any of these:

- An exception request is received.
- A negative response is received with an unexpected sense code.
- An RU (request/response unit) from the remote LU was larger than the maximum RU size.

For a description of any sense data that is sent or received, see *SNA Formats*, GA27-3136.

System action

PSF tries to recover from this abend by restarting. Message APS057I is issued if PSF successfully restarts.

System programmer response

To determine the cause, see *SNA Formats* for the SNA sense code. The problem might be with the VTAM

network definition or with the configuration of the printer or the controller. Otherwise, this PSF reason code might indicate a logic error in PSF, the printer, or the controller. A VTAM buffer trace is needed to determine the failing component.

OF18**Explanation**

This abend is issued by module DCKCRABE— VTAM did not complete the requested operations, either because the operator entered a Halt Net or a Cancel, or because an VTAMabend is occurring. In either case, VTAM is ending, and PSF cannot continue without VTAM.

System action

PSF processing ends abnormally.

System programmer response

After VTAM is restarted, start PSF again.

Appendix A. Valid scope values for the CMR Descriptor triplet

Table 2 on page 775 lists the scope values that are valid on the Color Management Resource (CMR) Descriptor triplet, X'91', for different structured fields:

Table 2: Valid scope values for the CMR Descriptor triplet.

Structured Fields	Scope Values				
	Print File	Document	Page/Sheet Group	Page/Overlay	Data Object
Map Data Resource (MDR) Document Environment Group (DEG) in form definition	X	X			
MDR medium map in form definition			X		
MDR resource Environment Group (REG) in data set or page definition	X	X	X	X	X
MDR Active Environment Group (AEG) in page or overlay				X	X
MDR Object Environment Group (OEG) in embedded object or soft page segment					X
Preprocess Presentation Object (PPO) for overlay				X	
PPO for IOCA object or object container					X
Include Object (IOB) in page/overlay or page definition					X
Line descriptor (LND), Record Descriptor (RCD), or XML Descriptor (XMD) in page definition					X

Appendix B. Accessibility

Accessible publications for this product are offered through [IBM Knowledge Center \(www.ibm.com/support/knowledgecenter/SSLTBW/welcome\)](http://www.ibm.com/support/knowledgecenter/SSLTBW/welcome).

If you experience difficulty with the accessibility of any z/OS information, send a detailed email message to mhvrcfs@us.ibm.com.

Accessibility features

Accessibility features help users who have physical disabilities such as restricted mobility or limited vision use software products successfully. The accessibility features in z/OS can help users do the following tasks:

- Run assistive technology such as screen readers and screen magnifier software.
- Operate specific or equivalent features by using the keyboard.
- Customize display attributes such as color, contrast, and font size.

Consult assistive technologies

Assistive technology products such as screen readers function with the user interfaces found in z/OS. Consult the product information for the specific assistive technology product that is used to access z/OS interfaces.

Keyboard navigation of the user interface

You can access z/OS user interfaces with TSO/E or ISPF. The following information describes how to use TSO/E and ISPF, including the use of keyboard shortcuts and function keys (PF keys). Each guide includes the default settings for the PF keys.

- [*z/OS TSO/E Primer*](#)
- [*z/OS TSO/E User's Guide*](#)
- [*z/OS ISPF User's Guide Vol I*](#)

Dotted decimal syntax diagrams

Syntax diagrams are provided in dotted decimal format for users who access IBM Knowledge Center with a screen reader. In dotted decimal format, each syntax element is written on a separate line. If two or more syntax elements are always present together (or always absent together), they can appear on the same line because they are considered a single compound syntax element.

Each line starts with a dotted decimal number; for example, 3 or 3.1 or 3.1.1. To hear these numbers correctly, make sure that the screen reader is set to read out punctuation. All the syntax elements that have the same dotted decimal number (for example, all the syntax elements that have the number 3.1) are mutually exclusive alternatives. If you hear the lines 3.1 USERID and 3.1 SYSTEMID, your syntax can include either USERID or SYSTEMID, but not both.

The dotted decimal numbering level denotes the level of nesting. For example, if a syntax element with dotted decimal number 3 is followed by a series of syntax elements with dotted decimal number 3.1, all the syntax elements numbered 3.1 are subordinate to the syntax element numbered 3.

Certain words and symbols are used next to the dotted decimal numbers to add information about the syntax elements. Occasionally, these words and symbols might occur at the beginning of the element itself. For ease of identification, if the word or symbol is a part of the syntax element, it is preceded by the backslash (\) character. The * symbol is placed next to a dotted decimal number to indicate that the syntax element repeats. For example, syntax element *FILE with dotted decimal number 3 is given the format 3 * FILE. Format 3* FILE indicates that syntax element FILE repeats. Format 3* * FILE indicates that syntax element * FILE repeats.

Characters such as commas, which are used to separate a string of syntax elements, are shown in the syntax just before the items they separate. These characters can appear on the same line as each item, or on a separate line with the same dotted decimal number as the relevant items. The line can also show another symbol to provide information about the syntax elements. For example, the lines 5.1*, 5.1 LASTRUN, and 5.1 DELETE mean that if you use more than one of the LASTRUN and DELETE syntax elements, the elements must be separated by a comma. If no separator is given, assume that you use a blank to separate each syntax element.

If a syntax element is preceded by the % symbol, it indicates a reference that is defined elsewhere. The string that follows the % symbol is the name of a syntax fragment rather than a literal. For example, the line 2.1 %OP1 means that you must refer to separate syntax fragment OP1.

The following symbols are used next to the dotted decimal numbers.

? indicates an optional syntax element

The question mark (?) symbol indicates an optional syntax element. A dotted decimal number followed by the question mark symbol (?) indicates that all the syntax elements with a corresponding dotted decimal number, and any subordinate syntax elements, are optional. If there is only one syntax element with a dotted decimal number, the ? symbol is displayed on the same line as the syntax element, (for example 5? NOTIFY). If there is more than one syntax element with a dotted decimal number, the ? symbol is displayed on a line by itself, followed by the syntax elements that are optional. For example, if you hear the lines 5 ?, 5 NOTIFY, and 5 UPDATE, you know that the syntax elements NOTIFY and UPDATE are optional. That is, you can choose one or none of them. The ? symbol is equivalent to a bypass line in a railroad diagram.

! indicates a default syntax element

The exclamation mark (!) symbol indicates a default syntax element. A dotted decimal number followed by the ! symbol and a syntax element indicate that the syntax element is the default option for all syntax elements that share the same dotted decimal number. Only one of the syntax elements that share the dotted decimal number can specify the ! symbol. For example, if you hear the lines 2? FILE, 2.1! (KEEP), and 2.1 (DELETE), you know that (KEEP) is the default option for the FILE keyword. In the example, if you include the FILE keyword, but do not specify an option, the default option KEEP is applied. A default option also applies to the next higher dotted decimal number. In this example, if the FILE keyword is omitted, the default FILE(KEEP) is used. However, if you hear the lines 2? FILE, 2.1, 2.1.1! (KEEP), and 2.1.1 (DELETE), the default option KEEP applies only to the next higher dotted decimal number, 2.1 (which does not have an associated keyword), and does not apply to 2? FILE. Nothing is used if the keyword FILE is omitted.

*** indicates an optional syntax element that is repeatable**

The asterisk or glyph (*) symbol indicates a syntax element that can be repeated zero or more times. A dotted decimal number followed by the * symbol indicates that this syntax element can be used zero or more times; that is, it is optional and can be repeated. For example, if you hear the line 5.1* data area, you know that you can include one data area, more than one data area, or no data area. If you hear the lines 3* , 3 HOST, 3 STATE, you know that you can include HOST, STATE, both together, or nothing.

Notes:

1. If a dotted decimal number has an asterisk (*) next to it and there is only one item with that dotted decimal number, you can repeat that same item more than once.
2. If a dotted decimal number has an asterisk next to it and several items have that dotted decimal number, you can use more than one item from the list, but you cannot use the items more than once each. In the previous example, you can write HOST STATE, but you cannot write HOST HOST.

3. The * symbol is equivalent to a loopback line in a railroad syntax diagram.

+ indicates a syntax element that must be included

The plus (+) symbol indicates a syntax element that must be included at least once. A dotted decimal number followed by the + symbol indicates that the syntax element must be included one or more times. That is, it must be included at least once and can be repeated. For example, if you hear the line 6.1+ data area, you must include at least one data area. If you hear the lines 2+, 2 HOST, and 2 STATE, you know that you must include HOST, STATE, or both. Similar to the * symbol, the + symbol can repeat a particular item if it is the only item with that dotted decimal number. The + symbol, like the * symbol, is equivalent to a loopback line in a railroad syntax diagram.

Notices

This information was developed for products and services that are offered in the USA or elsewhere.

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not grant you any license to these patents. You can send license inquiries, in writing, to:

*IBM Director of Licensing
IBM Corporation
North Castle Drive, MD-NC119
Armonk, NY 10504-1785
United States of America*

For license inquiries regarding double-byte character set (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

*Intellectual Property Licensing
Legal and Intellectual Property Law
IBM Japan Ltd.
19-21, Nihonbashi-Hakozakicho, Chuo-ku
Tokyo 103-8510, Japan*

The following paragraph does not apply to the United Kingdom or any other country where such provisions are inconsistent with local law: INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

This information could include missing, incorrect, or broken hyperlinks. Hyperlinks are maintained in only the HTML plug-in output for the Knowledge Centers. Use of hyperlinks in other output formats of this information is at your own risk.

Any references in this information to non-IBM websites are provided for convenience only and do not in any manner serve as an endorsement of those websites. The materials at those websites are not part of the materials for this IBM product and use of those websites is at your own risk.

IBM may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

*IBM Corporation
Site Counsel
2455 South Road*

Poughkeepsie, NY 12601-5400
USA

Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement or any equivalent agreement between us.

Any performance data contained herein was determined in a controlled environment. Therefore, the results obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

All statements regarding IBM's future direction or intent are subject to change or withdrawal without notice, and represent goals and objectives only.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to the names and addresses used by an actual business enterprise is entirely coincidental.

COPYRIGHT LICENSE:

This information contains sample application programs in source language, which illustrate programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to IBM, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating platform for which the sample programs are written. These examples have not been thoroughly tested under all conditions. IBM, therefore, cannot guarantee or imply reliability, serviceability, or function of these programs. The sample programs are provided "AS IS", without warranty of any kind. IBM shall not be liable for any damages arising out of your use of the sample programs.

Terms and conditions for product documentation

Permissions for the use of these publications are granted subject to the following terms and conditions.

Applicability

These terms and conditions are in addition to any terms of use for the IBM website.

Personal use

You may reproduce these publications for your personal, noncommercial use provided that all proprietary notices are preserved. You may not distribute, display or make derivative work of these publications, or any portion thereof, without the express consent of IBM.

Commercial use

You may reproduce, distribute and display these publications solely within your enterprise provided that all proprietary notices are preserved. You may not make derivative works of these publications, or

reproduce, distribute or display these publications or any portion thereof outside your enterprise, without the express consent of IBM.

Rights

Except as expressly granted in this permission, no other permissions, licenses or rights are granted, either express or implied, to the publications or any information, data, software or other intellectual property contained therein.

IBM reserves the right to withdraw the permissions granted herein whenever, in its discretion, the use of the publications is detrimental to its interest or, as determined by IBM, the above instructions are not being properly followed.

You may not download, export or re-export this information except in full compliance with all applicable laws and regulations, including all United States export laws and regulations.

IBM MAKES NO GUARANTEE ABOUT THE CONTENT OF THESE PUBLICATIONS. THE PUBLICATIONS ARE PROVIDED "AS-IS" AND WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY, NON-INFRINGEMENT, AND FITNESS FOR A PARTICULAR PURPOSE.

IBM Online Privacy Statement

IBM Software products, including software as a service solutions, ("Software Offerings") may use cookies or other technologies to collect product usage information, to help improve the end user experience, to tailor interactions with the end user, or for other purposes. In many cases no personally identifiable information is collected by the Software Offerings. Some of our Software Offerings can help enable you to collect personally identifiable information. If this Software Offering uses cookies to collect personally identifiable information, specific information about this offering's use of cookies is set forth below.

Depending upon the configurations deployed, this Software Offering may use session cookies that collect each user's name, email address, phone number, or other personally identifiable information for purposes of enhanced user usability and single sign-on configuration. These cookies can be disabled, but disabling them will also eliminate the functionality they enable.

If the configurations deployed for this Software Offering provide you as customer the ability to collect personally identifiable information from end users via cookies and other technologies, you should seek your own legal advice about any laws applicable to such data collection, including any requirements for notice and consent.

For more information about the use of various technologies, including cookies, for these purposes, see IBM's Privacy Policy at ibm.com/privacy and IBM's Online Privacy Statement at ibm.com/privacy/details in the section entitled "Cookies, Web Beacons and Other Technologies," and the "IBM Software Products and Software-as-a-Service Privacy Statement" at ibm.com/software/info/product-privacy.

Policy for unsupported hardware

Various z/OS elements, such as DFSMS, JES2, JES3, and MVS, contain code that supports specific hardware servers or devices. In some cases, this device-related element support remains in the product even after the hardware devices pass their announced End of Service date. z/OS may continue to service element code; however, it will not provide service related to unsupported hardware devices. Software problems related to these devices will not be accepted for service, and current service activity will cease if a problem is determined to be associated with out-of-support devices. In such cases, fixes will not be issued.

Minimum supported hardware

The minimum supported hardware for z/OS releases identified in z/OS announcements can subsequently change when service for particular servers or devices is withdrawn. Likewise, the levels of other software products supported on a particular release of z/OS are subject to the service support lifecycle of those products. Therefore, z/OS and its product publications (for example, panels, samples, messages, and product documentation) can include references to hardware and software that is no longer supported.

- For information about software support lifecycle, see: [IBM Lifecycle Support for z/OS \(www.ibm.com/software/support/systemsz/lifecycle\)](http://www.ibm.com/software/support/systemsz/lifecycle)
- For information about currently-supported IBM hardware, contact your IBM representative.

Trademarks

IBM, the IBM logo, and ibm.com are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available at [Copyright and Trademark information \(www.ibm.com/legal/copytrade.shtml\)](http://www.ibm.com/legal/copytrade.shtml).

Linux is a registered trademark of Linus Torvalds in the United States, other countries, or both.

Microsoft and Windows are trademarks of Microsoft Corporation in the United States, other countries, or both.

UNIX is a registered trademark of The Open Group in the United States and other countries.

Bibliography

This bibliography lists the titles of publications containing additional information about PSF, AFP, the z/OS operating system, and related products.

The titles and order numbers might change from time to time. To verify the current title or order number, consult your IBM marketing representative.

You can obtain many of the publications listed in this bibliography from the [AFP Consortium Publications \(afpcinc.org/publications\)](http://afpcinc.org/publications) and the [z/OS Internet Library \(www.ibm.com/servers/resourcelink/svc00100.nsf/pages/zosInternetLibrary\)](http://www.ibm.com/servers/resourcelink/svc00100.nsf/pages/zosInternetLibrary).

Advanced Function Presentation (AFP)

Publication	Order Number
<i>Advanced Function Presentation: Programming Guide and Line Data Reference</i>	S544-3884
<i>AFP Consortium: AFP Color Management Architecture (ACMA)</i>	AFPC
<i>AFP Toolbox User's Guide</i>	S544-5292
<i>Bar Code Object Content Architecture Reference</i>	AFPC-0005
<i>Color Management Object Content Architecture Reference</i>	AFPC-0006
<i>Font Object Content Architecture Reference</i>	AFPC-0007
<i>Graphics Object Content Architecture for AFP Reference</i>	AFPC-0008
<i>Guide to Advanced Function Presentation</i>	G544-3876
<i>Image Object Content Architecture Reference</i>	AFPC-0003
<i>Intelligent Printer Data Stream Reference</i>	AFPC-0001
<i>Mixed Object Document Content Architecture Reference</i>	AFPC-0004
<i>Overlay Generation Language/370 User's Guide and Reference</i>	S544-3702
<i>Presentation Text Object Content Architecture Reference</i>	AFPC-0009



G550-0432-05

