



Program Directory for IBM Engineering Test Management

V07.00.01

Program Number 5724-V10

for Use with
z/OS

Document Date: June 2020

GI13-2891-09

Note

Before using this information and the product it supports, be sure to read the general information under 7.0, "Notices" on page 43.

Contents

1.0 Introduction	1
1.1 Engineering Test Management Description	1
1.2 Engineering Test Management FMIDs	2
2.0 Program Materials	3
2.1 Basic Machine-Readable Material	3
2.2 Optional Machine-Readable Material	8
2.3 Program Publications	8
2.3.1 Optional Program Publications	8
2.4 Program Source Materials	8
2.5 Publications Useful During Installation	8
3.0 Program Support	9
3.1 Program Services	9
3.2 Preventive Service Planning	9
3.3 Statement of Support Procedures	10
4.0 Program and Service Level Information	12
4.1 Program Level Information	12
4.2 Service Level Information	12
5.0 Installation Requirements and Considerations	13
5.1 Driving System Requirements	13
5.1.1 Machine Requirements	13
5.1.2 Programming Requirements	13
5.2 Target System Requirements	14
5.2.1 Machine Requirements	14
5.2.2 Programming Requirements	14
5.2.2.1 Installation Requisites	14
5.2.2.2 Operational Requisites	15
5.2.2.3 Toleration/Coexistence Requisites	15
5.2.2.4 Incompatibility (Negative) Requisites	15
5.2.3 DASD Storage Requirements	15
5.3 FMIDs Deleted	21
5.4 Special Considerations	22
6.0 Installation Instructions	23
6.1 Installing Engineering Test Management	23
6.1.1 SMP/E Considerations for Installing Engineering Test Management	23
6.1.2 SMP/E Options Subentry Values	23
6.1.3 Overview of the installation steps	24
6.1.4 Upload Sample JCL from the client	24

6.1.5	Expand the sample jcl file by using the TSO Receive command:	26
6.1.6	Sample Jobs	26
6.1.7	Run the job to allocate sequential data sets that the FTP step will use	28
6.1.8	Upload the compressed RELFILES and SMPMCS from the client	28
6.1.9	Expand the RELFILES by running the sample job, BLZEXPND:	35
6.1.10	Delete previous release of Engineering Test Management (Optional)	35
6.1.11	Allocate SMP/E CSI (Optional)	36
6.1.12	Perform SMP/E RECEIVE	36
6.1.13	Allocate SMP/E Target and Distribution Libraries	37
6.1.14	Allocate, create and mount ZFS File System (Optional)	38
6.1.15	Allocate File System Paths	38
6.1.16	Create DDDEF Entries	39
6.1.17	Perform SMP/E APPLY	39
6.1.18	Perform SMP/E ACCEPT	41
6.1.19	Run REPORT CROSSZONE	41
6.2	Activating Engineering Test Management	42
6.2.1	Product Customization	42
7.0	Notices	43
7.1	Trademarks	43
Reader's Comments		44

Figures

1.	Program File Content for HRJS701 - Jazz Team Server	3
2.	Program File Content for HRBT701 - Build System Toolkit	4
3.	Program File Content for HRDV701 - IBM Developer for z/OS Subset	4
4.	Program File Content for HRBA701 - Build Agent	4
5.	Program File Content for HRCM701 - Change and Configuration Management	5
6.	Program File Content for HRQM701 - Quality Management	5
7.	Program File Content for HRRM701 - Requirements Management	5
8.	Program File Content for HRCC701 - Common Components	6
9.	Program File Content for HRWL701 - Websphere Liberty Profile	6
10.	Program File Content for HRRS701 - Jazz Reporting Services	7
11.	Program File Content for HRGC701 - Global Configuration Management	7
12.	Program File Content for HRRE701 - Engineering Lifecycle Optimization - Engineering Insights	7
13.	Program File Content for HRLI701 - Link Index Provider	7
14.	Publications Useful During Installation	8
15.	PSP Upgrade and Subset ID	9
16.	Component IDs	10
17.	Driving System Software Requirements	14

- 18. Total DASD Space Required by Engineering Test Management 15
- 19. Storage Requirements for Engineering Test Management Target Libraries 17
- 20. Engineering Test Management File System Paths 18
- 21. Storage Requirements for Engineering Test Management Distribution Libraries 19
- 22. Storage Requirements for Engineering Test Management - Additional Installation Data Sets 20
- 23. SMP/E Options Subentry Values 23
- 24. User Entered Values 25
- 25. Sample Installation Jobs 26

1.0 Introduction

This program directory is intended for system programmers who are responsible for program installation and maintenance. It contains information about the material and procedures associated with the installation of IBM Engineering Test Management. This publication refers to IBM Engineering Test Management as Engineering Test Management.

The Program Directory contains the following sections:

- 2.0, “Program Materials” on page 3 identifies the basic program materials and documentation for Engineering Test Management.
- 3.0, “Program Support” on page 9 describes the IBM support available for Engineering Test Management.
- 4.0, “Program and Service Level Information” on page 12 lists the APARs (program level) and PTFs (service level) that have been incorporated into Engineering Test Management.
- 5.0, “Installation Requirements and Considerations” on page 13 identifies the resources and considerations that are required for installing and using Engineering Test Management.
- 6.0, “Installation Instructions” on page 23 provides detailed installation instructions for Engineering Test Management. It also describes the procedures for activating the functions of Engineering Test Management, or refers to appropriate publications.

1.1 Engineering Test Management Description

With this release, IBM Rational Quality Manager is renamed IBM Engineering Test Management.

IBM Engineering Test Management is a collaborative, web-based tool for planning, constructing, managing, and executing tests throughout the development lifecycle.

Engineering Test Management is for test teams of all sizes and supports various user roles, such as test manager, test architect, test lead, tester, and lab manager. The application also supports roles outside the test organization.

Engineering Test Management is the Quality Management (QM) application in the Engineering Lifecycle Management solution.

For further details refer to this web site:

https://www.ibm.com/support/knowledgecenter/en/SSYMRC_7.0.1/com.ibm.rational.test.qm.doc/topics/c_qm_overview.html

1.2 Engineering Test Management FMIDs

Engineering Test Management consists of the following FMIDs:

- HRJS701 - Jazz Team Server
- HRBT701 - Engineering Workflow Management - Build System Toolkit
- HRDV701 - IBM Developer for z/OS Subset
- HRBA701 - Engineering Workflow Management - Build Agent
- HRCM701 - Engineering Workflow Management - Change and Configuration Management
- HRQM701 - Engineering Test Management - Quality Management
- HRRM701 - Engineering Requirements Management DOORS Next - Requirements Management
- HRCC701 - Common Components
- HRWL701 - Websphere Liberty Profile
- HRRS701 - Jazz Reporting Services
- HRGC701 - Global Configuration Management
- HRRE701 - Engineering Lifecycle Optimization - Engineering Insights
- HRLI701 - Link Index Provider

Note!

1. FMID HRCC701 (Common Components) is required by the other FMIDS. If you are installing IBM Engineering Test Management for the first time, you must install FMID HRCC701. If you have previously installed FMID HRCC701, there is no need to re-install it.

2.0 Program Materials

An IBM program is identified by a program number. The program number for Engineering Test Management is 5724-V10.

Basic Machine-Readable Materials are materials that are supplied under the base license and are required for the use of the product.

The program announcement material describes the features supported by Engineering Test Management. Ask your IBM representative for this information if you have not already received a copy.

2.1 Basic Machine-Readable Material

The distribution medium for this program is DVD. It is installed using SMP/E, and is in SMP/E RELFILE format. See 6.0, "Installation Instructions" on page 23 for more information about how to install the program.

Figure 1 describes the program file content for Engineering Test Management.

Notes:

1. The data set attributes in this table must be used in the JCL of jobs that read the data sets. However, because the data sets are in IEBCOPY unloaded format, their actual attributes might be different.
2. If any RELFILEs are identified as PDSEs, ensure that SMPTLIB data sets are allocated as PDSEs.

Figure 1. Program File Content for HRJS701 - Jazz Team Server

Name	O R G	R E C F M	L R E C L	BLK SIZE
SMPMCS	SEQ	FB	80	6400
IBM.HRJS701.F1	PDS	FB	80	8800
IBM.HRJS701.F2	PDS	VB	255	27998

Figure 2. Program File Content for HRBT701 - Build System Toolkit

Name	O R G	R E C F M	L R E C L	BLK SIZE
SMPMCS	SEQ	FB	80	6400
IBM.HRBT701.F1	PDS	FB	80	8800
IBM.HRBT701.F2	PDS	VB	255	27998
IBM.HRBT701.F3	PDS	FB	80	8800
IBM.HRBT701.F4	PDS	FB	80	8800
IBM.HRBT701.F5	PDS	FB	80	8800
IBM.HRBT701.F6	PDS	FB	80	8800
IBM.HRBT701.F7	PDS	FB	80	8800
IBM.HRBT701.F8	PDS	FB	80	8800
IBM.HRBT701.F9	PDS	FB	80	8800
IBM.HRBT701.F10	PDS	U	0	6144

Figure 3. Program File Content for HRDV701 - IBM Developer for z/OS Subset

Name	O R G	R E C F M	L R E C L	BLK SIZE
SMPMCS	SEQ	FB	80	6400
IBM.HRDV701.F1	PDSE	U	0	6144
IBM.HRDV701.F2	PDS	FB	80	8800
IBM.HRDV701.F3	PDS	U	0	6144

Figure 4. Program File Content for HRBA701 - Build Agent

Name	O R G	R E C F M	L R E C L	BLK SIZE
SMPMCS	SEQ	FB	80	6400
IBM.HRBA701.F1	PDS	FB	80	8800
IBM.HRBA701.F2	PDS	VB	255	27998

<i>Figure 5. Program File Content for HRCM701 - Change and Configuration Management</i>				
Name	O R G	R E C F M	L R E C L	BLK SIZE
SMPMCS	SEQ	FB	80	6400
IBM.HRCM701.F1	PDS	FB	80	8800
IBM.HRCM701.F2	PDS	VB	255	27998

<i>Figure 6. Program File Content for HRQM701 - Quality Management</i>				
Name	O R G	R E C F M	L R E C L	BLK SIZE
SMPMCS	SEQ	FB	80	6400
IBM.HRQM701.F1	PDS	FB	80	8800
IBM.HRQM701.F2	PDS	VB	255	27998

<i>Figure 7. Program File Content for HRRM701 - Requirements Management</i>				
Name	O R G	R E C F M	L R E C L	BLK SIZE
SMPMCS	SEQ	FB	80	6400
IBM.HRRM701.F1	PDS	FB	80	8800
IBM.HRRM701.F2	PDS	VB	255	27998

Figure 8. Program File Content for HRCC701 - Common Components

Name	O R G	R E C F M	L R E C L	BLK SIZE
SMPMCS	SEQ	FB	80	6400
IBM.HRCC701.F1	PDS	FB	80	8800
IBM.HRCC701.F2	PDS	FB	80	8800
IBM.HRCC701.F3	PDS	VB	255	27998
IBM.HRCC701.F4	PDS	U	0	6144
IBM.HRCC701.F5	PDS	FB	80	8800
IBM.HRCC701.F6	PDS	FB	80	8800
IBM.HRCC701.F7	PDS	FB	80	8800
IBM.HRCC701.F8	PDS	FB	80	8800
IBM.HRCC701.F9	PDS	FB	80	8800
IBM.HRCC701.F10	PDS	FB	80	8800
IBM.HRCC701.F11	PDS	FB	80	8800
IBM.HRCC701.F12	PDS	FB	80	8800
IBM.HRCC701.F13	PDS	FB	80	8800
IBM.HRCC701.F14	PDS	FB	80	8800

Figure 9. Program File Content for HRWL701 - Websphere Liberty Profile

Name	O R G	R E C F M	L R E C L	BLK SIZE
SMPMCS	SEQ	FB	80	6400
IBM.HRWL701.F1	PDS	FB	80	8800
IBM.HRWL701.F2	PDS	VB	255	27998

Figure 10. Program File Content for HRRS701 - Jazz Reporting Services

Name	O R G	R E C F M	L R E C L	BLK SIZE
SMPMCS	SEQ	FB	80	6400
IBM.HRRS701.F1	PDS	FB	80	8800
IBM.HRRS701.F2	PDS	VB	255	27998

Figure 11. Program File Content for HRGC701 - Global Configuration Management

Name	O R G	R E C F M	L R E C L	BLK SIZE
SMPMCS	SEQ	FB	80	6400
IBM.HRGC701.F1	PDS	FB	80	8800
IBM.HRGC701.F2	PDS	VB	255	27998

Figure 12. Program File Content for HRRE701 - Engineering Lifecycle Optimization - Engineering Insights

Name	O R G	R E C F M	L R E C L	BLK SIZE
SMPMCS	SEQ	FB	80	6400
IBM.HRRE701.F1	PDS	FB	80	8800
IBM.HRRE701.F2	PDS	VB	255	27998

Figure 13. Program File Content for HRLI701 - Link Index Provider

Name	O R G	R E C F M	L R E C L	BLK SIZE
SMPMCS	SEQ	FB	80	6400
IBM.HRLI701.F1	PDS	FB	80	8800
IBM.HRLI701.F2	PDS	VB	255	27998

2.2 Optional Machine-Readable Material

No optional machine-readable materials are provided for Engineering Test Management.

2.3 Program Publications

The following sections identify the basic publications for Engineering Test Management.

2.3.1 Optional Program Publications

No optional publications are provided for Engineering Test Management.

2.4 Program Source Materials

No program source materials or viewable program listings are provided for Engineering Test Management.

2.5 Publications Useful During Installation

You might want to use the publications listed in Figure 14 during the installation of Engineering Test Management.

Figure 14. Publications Useful During Installation

Publication Title	Form Number	Media Format
<i>IBM SMP/E for z/OS User's Guide</i>	SA23-2277	http://www.ibm.com/shop/publications/order/
<i>IBM SMP/E for z/OS Commands</i>	SA23-2275	http://www.ibm.com/shop/publications/order/
<i>IBM SMP/E for z/OS Reference</i>	SA23-2276	http://www.ibm.com/shop/publications/order/
<i>IBM SMP/E for z/OS Messages, Codes, and Diagnosis</i>	GA32-0883	http://www.ibm.com/shop/publications/order/

3.0 Program Support

This section describes the IBM support available for Engineering Test Management.

3.1 Program Services

Contact your IBM representative for specific information about available program services.

3.2 Preventive Service Planning

Before you install Engineering Test Management, make sure that you have reviewed the current Preventive Service Planning (PSP) information. Review the PSP Bucket for General Information, Installation Documentation, and the Cross Product Dependencies sections. For the Recommended Service section, instead of reviewing the PSP Bucket, it is recommended you use the IBM.ProductInstall-RequiredService fix category in SMP/E to ensure you have all the recommended service installed. Use the **FIXCAT(IBM.ProductInstall-RequiredService)** operand on the **APPLY CHECK command**. See 6.1.17, “Perform SMP/E APPLY” on page 39 for a sample APPLY command.

Once you have received your installation DVD, you should contact the IBM Support Center or use S/390 SoftwareXcel to obtain the latest PSP Bucket information. You can also obtain the latest PSP Bucket information by going to the following Web site:

<http://www14.software.ibm.com/webapp/set2/psearch/search?domain=psp>

You can also use S/390 SoftwareXcel or contact the IBM Support Center to obtain the latest PSP Bucket information.

For program support, access the Software Support Website at <http://www-01.ibm.com/software/support/>.

PSP Buckets are identified by UPGRADEs, which specify product levels; and SUBSETs, which specify the FMIDs for a product level. The UPGRADE and SUBSET values for Engineering Test Management are included in Figure 15.

UPGRADE	SUBSET	Description
5724V82	HRJS701	Jazz Team Server for z/OS
	HRBT701	Engineering Workflow Management - Build System Toolkit
	HRDV701	IBM Developer for z/OS Subset
	HRBA701	Engineering Workflow Management - Build Agent

Figure 15 (Page 2 of 2). PSP Upgrade and Subset ID

UPGRADE	SUBSET	Description
	HRCM701	Engineering Workflow Management - Change and Configuration Management
	HRQM701	Engineering Test Management - Quality Management
	HRRM701	Engineering Requirements Management DOORS Next - Requirements Management
	HRCC701	Common Components for z/OS
	HRWL701	Websphere Liberty Profile for z/OS
	HRRS701	Jazz Reporting Services for z/OS
	HRGC701	Global Configuration Management for z/OS
	HRRE701	Engineering Lifecycle Optimization - Engineering Insights for z/OS
	HRLI701	Link Index Provider for z/OS

3.3 Statement of Support Procedures

Report any problems which you feel might be an error in the product materials to your IBM Support Center. You may be asked to gather and submit additional diagnostics to assist the IBM Support Center in their analysis.

Figure 16 identifies the component IDs (COMPID) for Engineering Test Management.

Figure 16 (Page 1 of 2). Component IDs

FMID	COMPID	Component Name	RETAIN Release
HRJS701	5724V8210	Jazz Team Server for z/OS	701
HRBT701	5724V8220	Engineering Workflow Management - Build System Toolkit	701
HRDV701	5724V8230	IBM Developer for z/OS Subset	701
HRBA701	5724V8240	Engineering Workflow Management - Build Agent	701
HRCM701	5724V8260	Engineering Workflow Management - Change and Configuration Management	701
HRQM701	5724V8270	Engineering Test Management - Quality Management	701
HRRM701	5724V8280	Engineering Requirements Management DOORS Next - Requirements Management	701
HRCC701	5724V82CC	Common Components for z/OS	701
HRWL701	5724V82WL	Websphere Liberty Profile for z/OS	701

Figure 16 (Page 2 of 2). Component IDs

F MID	COMPID	Component Name	RETAIN Release
HRRS701	5724V82JR	Jazz Reporting Services for z/OS	701
HRGC701	5724V82GC	Global Configuration Management for z/OS	701
HRRE701	5724V82LM	Engineering Lifecycle Optimization - Engineering Insights for z/OS	701
HRLI701	5724V82LI	Link Index Provider for z/OS	701

4.0 Program and Service Level Information

This section identifies the program and relevant service levels of Engineering Test Management. The program level refers to the APAR fixes that have been incorporated into the program. The service level refers to the PTFs that have been incorporated into the program.

4.1 Program Level Information

No APARs have been incorporated into Engineering Test Management.

4.2 Service Level Information

No PTFs against this release of Engineering Test Management have been incorporated into the product package.

Frequently check the Engineering Test Management PSP Bucket for HIPER and SPECIAL attention PTFs against all FMIDs that you must install. You can also receive the latest HOLDDATA, then add the **FIXCAT(IBM.PRODUCTINSTALL-REQUIRESERVICE)** operand on your APPLY CHECK command. This will allow you to review the recommended and critical service that should be installed with your FMIDs.

5.0 Installation Requirements and Considerations

The following sections identify the system requirements for installing and activating Engineering Test Management. The following terminology is used:

- *Driving system*: the system on which SMP/E is executed to install the program.
The program might have specific operating system or product level requirements for using processes, such as binder or assembly utilities during the installation.
- *Target system*: the system on which the program is configured and run.
The program might have specific product level requirements, such as needing access to the library of another product for link-edits. These requirements, either mandatory or optional, might directly affect the element during the installation or in its basic or enhanced operation.

In many cases, you can use a system as both a driving system and a target system. However, you can make a separate IPL-able clone of the running system to use as a target system. The clone must include copies of all system libraries that SMP/E updates, copies of the SMP/E CSI data sets that describe the system libraries, and your PARMLIB and PROCLIB.

Use separate driving and target systems in the following situations:

- When you install a new level of a product that is already installed, the new level of the product will replace the old one. By installing the new level onto a separate target system, you can test the new level and keep the old one in production at the same time.
- When you install a product that shares libraries or load modules with other products, the installation can disrupt the other products. By installing the product onto a separate target system, you can assess these impacts without disrupting your production system.

5.1 Driving System Requirements

This section describes the environment of the driving system required to install Engineering Test Management.

5.1.1 Machine Requirements

The driving system can run in any hardware environment that supports the required software.

5.1.2 Programming Requirements

Figure 17. Driving System Software Requirements

Program Number	Product Name	Minimum VRM	Minimum Service Level will satisfy these APARs	Included in the shipped product?
5650-ZOS	z/OS	V02.02.00 or higher	N/A	No

Note: SMP/E is a requirement for Installation and is an element of z/OS but can also be ordered as a separate product, 5655-G44, minimally V03.06.00.

Note: Installation might require migration to new z/OS releases to be service supported. See http://www-03.ibm.com/systems/z/os/zos/support/zos_eos_dates.html.

5.2 Target System Requirements

This section describes the environment of the target system required to install and use Engineering Test Management.

Engineering Test Management installs in the z/OS (Z038) SREL.

5.2.1 Machine Requirements

The target system can run in any hardware environment that supports the required software.

5.2.2 Programming Requirements

5.2.2.1 Installation Requisites: Installation requisites identify products that are required and *must* be present on the system or products that are not required but *should* be present on the system for the successful installation of this product.

Mandatory installation requisites identify products that are required on the system for the successful installation of this product.

Engineering Test Management has no mandatory installation requisites.

Conditional installation requisites identify products that are *not* required for successful installation of this product but can resolve such things as certain warning messages at installation time.

Engineering Test Management has no conditional installation requisites.

5.2.2.2 Operational Requisites: Operational requisites are products that are required and *must* be present on the system or products that are not required but *should* be present on the system for this product to operate all or part of its functions.

Mandatory operational requisites identify products that are required for this product to operate its basic functions.

Engineering Test Management has no mandatory operational requisites.

Conditional operational requisites identify products that are *not* required for this product to operate its basic functions but are required at run time for this product to operate specific functions.

Engineering Test Management has no conditional operational requisites.

5.2.2.3 Toleration/Coexistence Requisites: Toleration/coexistence requisites identify products that must be present on sharing systems. These systems can be other systems in a multisystem environment (not necessarily sysplex), a shared DASD environment (such as test and production), or systems that reuse the same DASD environment at different time intervals.

Engineering Test Management has no toleration/coexistence requisites.

5.2.2.4 Incompatibility (Negative) Requisites: Negative requisites identify products that must *not* be installed on the same system as this product.

Engineering Test Management has no negative requisites.

5.2.3 DASD Storage Requirements

Engineering Test Management libraries can reside on all supported DASD types.

Figure 18 lists the total space that is required for each type of library.

<i>Figure 18. Total DASD Space Required by Engineering Test Management</i>	
Library Type	Total Space Required in 3390 Trks
Compressed Binaries	99811 Tracks
Expanded Installation Files	105129 Tracks
Target	469 Tracks
Distribution	123469 Tracks
File System(s)	
HFS or zFS *	178800 Tracks

*** Note regarding HFS/zFS space allocation**

For the HFS/zFS allocation the total number of tracks of 178800 is specified. However, if only certain FMIDs are going to be applied your HFS/zFS space allocation can be reduced. The following lists the HFS/zFS allocation per FMID to enable you to size your HFS/zFS accordingly.

- HRJS701 - 16000 Tracks
- HRBT701 - 23900 Tracks
- HRBA701 - 100 Tracks
- HRCM701 - 22050 Tracks
- HRQM701 - 25500 Tracks
- HRRM701 - 23500 Tracks
- HRCC701 - 2750 Tracks
- HRWL701 - 14200 Tracks
- HRRS701 - 20000 Tracks
- HRGC701 - 14100 Tracks
- HRRE701 - 14000 Tracks
- HRLI701 - 2700 Tracks

Notes:

1. For non-RECFM U data sets, IBM recommends using system-determined block sizes for efficient DASD utilization. For RECFM U data sets, IBM recommends using a block size of 32760, which is most efficient from the performance and DASD utilization perspective.
2. Abbreviations used for data set types are shown as follows.

- U** Unique data set, allocated by this product and used by only this product. This table provides all the required information to determine the correct storage for this data set. You do not need to refer to other tables or program directories for the data set size.
- S** Shared data set, allocated by this product and used by this product and other products. To determine the correct storage needed for this data set, add the storage size given in this table to those given in other tables (perhaps in other program directories). If the data set already exists, it must have enough free space to accommodate the storage size given in this table.
- E** Existing shared data set, used by this product and other products. This data set is *not* allocated by this product. To determine the correct storage for this data set, add the storage size given in this table to those given in other tables (perhaps in other program directories). If the data set already exists, it must have enough free space to accommodate the storage size given in this table.

If you currently have a previous release of this product installed in these libraries, the installation of this release will delete the old release and reclaim the space that was used by the old release and any service that had been installed. You can determine whether these libraries have enough space by deleting the old release with a dummy function, compressing the libraries, and comparing the space requirements with the free space in the libraries.

For more information about the names and sizes of the required data sets, see 6.1.13, "Allocate SMP/E Target and Distribution Libraries" on page 37.

3. Abbreviations used for the file system path type are as follows.

- N** New path, created by this product.
- X** Path created by this product, but might already exist from a previous release.
- P** Previously existing path, created by another product.

4. All target and distribution libraries listed have the following attributes:

- The default name of the data set can be changed.
- The default block size of the data set can be changed.
- The data set can be merged with another data set that has equivalent characteristics.
- The data set can be either a PDS or a PDSE, except SBLZAUTH, ABLZAUTH and ABLZHFS which must be PDSEs.

5. All target libraries listed have the following attributes:

- These data sets can be SMS-managed, but they are not required to be SMS-managed.
- These data sets are not required to reside on the IPL volume.
- The values in the "Member Type" column are not necessarily the actual SMP/E element types that are identified in the SMPMCS.

6. All target libraries that are listed and contain load modules have the following attributes:

- These data sets can be in the LPA, but they are not required to be in the LPA.
- These data sets can be in the LNKLST.
- These data sets are not required to be APF-authorized, except for SBLZAUTH.
- Engineering Test Management requires that the SMPLTS data set must be a PDSE. If your existing SMPLTS is a PDS, you will need to allocate a new PDSE and copy your existing SMPLTS into it and then change the SMPLTS DDDEF entry to indicate the new PDSE data set.

The following figures describe the target and distribution libraries and file system paths required to install Engineering Test Management. The storage requirements of Engineering Test Management must be added to the storage required by other programs that have data in the same library or path.

Note: Use the data in these tables to determine which libraries can be merged into common data sets. In addition, since some ALIAS names may not be unique, ensure that no naming conflicts will be introduced before merging libraries.

<i>Figure 19 (Page 1 of 2). Storage Requirements for Engineering Test Management Target Libraries</i>									
Library DDNAME	Member Type	Target Volume	T Y P E	O R G	R E C O M	L E C T R E	No. of 3390 Trks	No. of DIR Blks	
SBLZAUTH	APF Modules	ANY	U	PDSE	U	0	35	n/a	
SBLZDBRM	DBRM	ANY	U	PDS	FB	80	2	2	
SBLZEXEC	EXEC	ANY	U	PDS	FB	80	25	5	
SBLZJCL	Install JCL	ANY	U	PDS	FB	80	10	5	

Figure 19 (Page 2 of 2). Storage Requirements for Engineering Test Management Target Libraries

Library DDNAME	Member Type	Target Volume	T Y P E	O R G	R E C F M	L R E C L	No. of 3390 Trks	No. of DIR Blks
SBLZLOAD	Modules	ANY	U	PDS	U	0	80	20
SBLZMENP	Messages	ANY	U	PDS	FB	80	10	10
SBLZMENU	Messages	ANY	U	PDS	FB	80	10	10
SBLZMJPN	Messages	ANY	U	PDS	FB	80	10	10
SBLZPENP	Panels	ANY	U	PDS	FB	80	65	30
SBLZPENU	Panels	ANY	U	PDS	FB	80	65	30
SBLZPJPN	Panels	ANY	U	PDS	FB	80	65	30
SBLZSAMP	Samples	ANY	U	PDS	FB	80	60	15
SBLZSLIB	Skeletons	ANY	U	PDS	FB	80	30	15
SBLZTLIB	Table	ANY	U	PDS	FB	80	2	5

Figure 20 (Page 1 of 2). Engineering Test Management File System Paths

DDNAME	T Y P E	Path Name
SBLZA001	N	/usr/lpp/jazz/v7.0.1/IBM/
SBLZA002	N	/usr/lpp/jazz/v7.0.1/server/conf/jts/provision_profiles/IBM/
SBLZA003	N	/usr/lpp/jazz/v7.0.1/server/conf/ccm/provision_profiles/IBM/
SBLZA004	N	/usr/lpp/jazz/v7.0.1/server/conf/qm/provision_profiles/IBM/
SBLZA005	N	/usr/lpp/jazz/v7.0.1/server/conf/rm/provision_profiles/IBM/
SBLZA006	N	/usr/lpp/jazz/v7.0.1/server/conf/dcc/provision_profiles/IBM/
SBLZA007	N	/usr/lpp/jazz/v7.0.1/server/conf/gc/provision_profiles/IBM/
SBLZA008	N	/usr/lpp/jazz/v7.0.1/server/conf/relm/provision_profiles/IBM/
SBLZAD02	N	/usr/lpp/jazz/v7.0.1/server/conf/jts/provision_profiles/IBM/
SBLZAD03	N	/usr/lpp/jazz/v7.0.1/server/conf/ccm/provision_profiles/IBM/
SBLZAD04	N	/usr/lpp/jazz/v7.0.1/server/conf/qm/provision_profiles/IBM/
SBLZAD05	N	/usr/lpp/jazz/v7.0.1/server/conf/rm/provision_profiles/IBM/
SBLZAD06	N	/usr/lpp/jazz/v7.0.1/server/conf/dcc/provision_profiles/IBM/
SBLZAD07	N	/usr/lpp/jazz/v7.0.1/server/conf/gc/provision_profiles/IBM/

Figure 20 (Page 2 of 2). Engineering Test Management File System Paths

DDNAME	T Y P E	Path Name
SBLZAD08	N	/usr/lpp/jazz/v7.0.1/server/conf/reln/provision_profiles/IBM/
SBLZE001	N	/usr/lpp/jazz/v7.0.1/buildagent/IBM/

Figure 21. Storage Requirements for Engineering Test Management Distribution Libraries

Library DDNAME	T Y P E	O R G	R E C F M	L R E C L	No. of 3390 Trks	No. of DIR Blks
ABLZAUTH	U	PDSE	U	0	35	n/a
ABLZDBRM	U	PDS	FB	80	2	2
ABLZEXEC	U	PDS	FB	80	25	5
ABLZHFS *	U	PDSE	VB	8796	123000	n/a
ABLZJCL	U	PDS	FB	80	10	5
ABLZLOAD	U	PDS	U	0	80	20
ABLZMENP	U	PDS	FB	80	10	10
ABLZMENU	U	PDS	FB	80	10	10
ABLZMJPN	U	PDS	FB	80	10	10
ABLZPENP	U	PDS	FB	80	65	30
ABLZPENU	U	PDS	FB	80	65	30
ABLZPJPN	U	PDS	FB	80	65	30
ABLZSAMP	U	PDS	FB	80	60	15
ABLZSLIB	U	PDS	FB	80	30	15
ABLZTLIB	U	PDS	FB	80	2	5

Note: * See 6.1.13, "Allocate SMP/E Target and Distribution Libraries" for more information of the size allocation of the ABLZHFS data set.

The following figures list additional data sets that are required for the installation of Engineering Test Management.

Figure 22 (Page 1 of 2). Storage Requirements for Engineering Test Management - Additional Installation Data Sets

Data Set Name	T Y P E	O R G	R E C F M	L R E C L	No. of 3390 Trks	No. of DIR Blks
hlq.HRJS701.F1.BIN	U	PS	FB	80	10	n/a
hlq.HRJS701.F2.BIN	U	PS	FB	80	12000	n/a
hlq.HRBT701.F1.BIN	U	PS	FB	80	15	n/a
hlq.HRBT701.F2.BIN	U	PS	FB	80	13000	n/a
hlq.HRBT701.F3.BIN	U	PS	FB	80	5	n/a
hlq.HRBT701.F4.BIN	U	PS	FB	80	5	n/a
hlq.HRBT701.F5.BIN	U	PS	FB	80	30	n/a
hlq.HRBT701.F6.BIN	U	PS	FB	80	5	n/a
hlq.HRBT701.F7.BIN	U	PS	FB	80	30	n/a
hlq.HRBT701.F8.BIN	U	PS	FB	80	5	n/a
hlq.HRBT701.F9.BIN	U	PS	FB	80	30	n/a
hlq.HRBT701.F10.BIN	U	PS	FB	80	30	n/a
hlq.HRDV701.F1.BIN	U	PS	FB	80	35	n/a
hlq.HRDV701.F2.BIN	U	PS	FB	80	2	n/a
hlq.HRDV701.F3.BIN	U	PS	FB	80	45	n/a
hlq.HRBA701.F1.BIN	U	PS	FB	80	2	n/a
hlq.HRBA701.F2.BIN	U	PS	FB	80	170	n/a
hlq.HRCM701.F1.BIN	U	PS	FB	80	5	n/a
hlq.HRCM701.F2.BIN	U	PS	FB	80	16000	n/a
hlq.HRQM701.F1.BIN	U	PS	FB	80	5	n/a
hlq.HRQM701.F2.BIN	U	PS	FB	80	16000	n/a
hlq.HRRM701.F1.BIN	U	PS	FB	80	5	n/a
hlq.HRRM701.F2.BIN	U	PS	FB	80	16000	n/a
hlq.HRCC701.F1.BIN	U	PS	FB	80	10	n/a
hlq.HRCC701.F2.BIN	U	PS	FB	80	10	n/a
hlq.HRCC701.F3.BIN	U	PS	FB	80	650	n/a
hlq.HRCC701.F4.BIN	U	PS	FB	80	13	n/a
hlq.HRCC701.F5.BIN	U	PS	FB	80	4	n/a
hlq.HRCC701.F6.BIN	U	PS	FB	80	20	n/a

Figure 22 (Page 2 of 2). Storage Requirements for Engineering Test Management - Additional Installation Data Sets

Data Set Name	T Y P E	O R G	R E C F M	L R E C L	No. of 3390 Trks	No. of DIR Blks
hlq.HRCC701.F7.BIN	U	PS	FB	80	4	n/a
hlq.HRCC701.F8.BIN	U	PS	FB	80	10	n/a
hlq.HRCC701.F9.BIN	U	PS	FB	80	4	n/a
hlq.HRCC701.F10.BIN	U	PS	FB	80	10	n/a
hlq.HRCC701.F11.BIN	U	PS	FB	80	4	n/a
hlq.HRCC701.F12.BIN	U	PS	FB	80	15	n/a
hlq.HRCC701.F13.BIN	U	PS	FB	80	20	n/a
hlq.HRCC701.F14.BIN	U	PS	FB	80	2	n/a
hlq.HRWL701.F1.BIN	U	PS	FB	80	3	n/a
hlq.HRWL701.F2.BIN	U	PS	FB	80	6200	n/a
hlq.HRRS701.F1.BIN	U	PS	FB	80	5	n/a
hlq.HRRS701.F2.BIN	U	PS	FB	80	14500	n/a
hlq.HRGC701.F1.BIN	U	PS	FB	80	5	n/a
hlq.HRGC701.F2.BIN	U	PS	FB	80	9500	n/a
hlq.HRRE701.F1.BIN	U	PS	FB	80	5	n/a
hlq.HRRE701.F2.BIN	U	PS	FB	80	9500	n/a
hlq.HRLI701.F1.BIN	U	PS	FB	80	5	n/a
hlq.HRLI701.F2.BIN	U	PS	FB	80	2000	n/a

5.3 FMIDs Deleted

Installing Engineering Test Management into same SMP/E target and distribution libraries that contain a previous version of Engineering Test Management might result in the deletion of other FMIDs. To see which FMIDs will be deleted, examine the ++VER statement in the SMPMCS of the product.

If you do not want to delete these FMIDs at this time, install Engineering Test Management into separate SMP/E target and distribution zones.

If you want to delete these FMIDS it is recommended that you use a dummy function SYSMOD to delete the previous releases of Engineering Test Management product from the existing target and distribution libraries, before proceeding with the installation of the new release.

Note: These FMIDs are not automatically deleted from the Global Zone. If you want to delete these FMIDs from the Global Zone, use the SMP/E REJECT NOFMID DELETEFMID command. See the SMP/E Commands book for details.

5.4 Special Considerations

Security Considerations:

In Engineering Test Management V07.00.01, there are changes to the PassTicket support for the ISPF client. The necessary changes remove a redundant RACF profile and add a new RACF profile to increase the security in generating PassTickets. If you installed the ISPF client with a previous release, the following tasks should be performed:

1. Remove the IRRPTAUTH.BLZAPPL.* profile, where BLZAPPL is the application ID used for the ISPF client. If you used a different application ID, the profile is named with the application ID you included in the profile name.
2. Add the new profile BLZ.CONNECT.BLZAPPL. If you are using a different application ID, change BLZAPPL to your application ID. ISPF client users must have READ access to this profile to generate PassTickets and login to the RTC repository. Follow the instructions in the sample member BLZRACFT in SBLZSAMP, or if you are using the configuration utility, in the generated PassTicket command. Optionally, you can set the profile to BLZ.CONNECT.*, which enables all ISPF client application IDs to use the profile.

PDSE Considerations:

Engineering Test Management uses the "partitioned data set extended" or PDSE format for the SBLZAUTH target library. There are some operational differences between PDS and PDSE data sets. The PDS format may be shared by more than one z/OS system and no special precautions are necessary. However the PDSE format may only be shared by z/OS systems which are part of a sysplex or which are connected using Global Resource Serialization (are in a GRS complex). If z/OS systems share use of a PDSE data set outside of a sysplex or GRS environment, you may experience severe problems when the data set is updated. This is due to the fact that PDSE directory information is cached in storage, and when the data set is updated from one system the other system(s) have no knowledge of the update, and their cached directory information will be incorrect.

You must take care not to share the SBLZAUTH data set between z/OS systems unless they are in a sysplex or are connected in a GRS complex. If you need to share the content of the SBLZAUTH data set, a separate copy must be created for each z/OS system.

6.0 Installation Instructions

This chapter describes the installation method and the step-by-step procedures to install and to activate the functions of Engineering Test Management.

Please note the following points:

- If you want to install Engineering Test Management into its own SMP/E environment, consult the SMP/E manuals for instructions on creating and initializing the SMPCSI and the SMP/E control data sets.
- You can use the sample jobs that are provided to perform part or all of the installation tasks. The SMP/E jobs assume that all DDDEF entries that are required for SMP/E execution have been defined in appropriate zones.
- You can use the SMP/E dialogs instead of the sample jobs to accomplish the SMP/E installation steps.

6.1 Installing Engineering Test Management

6.1.1 SMP/E Considerations for Installing Engineering Test Management

Use the SMP/E RECEIVE, APPLY, and ACCEPT commands to install this release of Engineering Test Management.

6.1.2 SMP/E Options Subentry Values

The recommended values for certain SMP/E CSI subentries are shown in Figure 23. Using values lower than the recommended values can result in failures in the installation. DSSPACE is a subentry in the GLOBAL options entry. PEMAX is a subentry of the GENERAL entry in the GLOBAL options entry. See the SMP/E manuals for instructions on updating the global zone.

Subentry	Value	Comment
DSSPACE	(1500,1500,1500)	3390 DASD tracks
PEMAX	SMP/E Default	IBM recommends using the SMP/E default for PEMAX.

6.1.3 Overview of the installation steps

Overview of steps required to install IBM Engineering Test Management.

1. Upload sample JCL from the client
2. Expand the sample jcl file by using the TSO Receive command
3. Sample Jobs
4. Run the job to allocate sequential data sets that the FTP step will use
5. Upload the compressed RELFILES and SMPMCS from the client
6. Expand the RELFILES by running the sample job, BLZEXPND
7. Delete previous release of IBM Engineering Test Management (optional)
8. Create SMP/E Environment (optional)
9. Perform SMP/E RECEIVE
10. Allocate SMP/E target and distribution libraries
11. Create ZFS file system (optional)
12. Allocate file system paths
13. Create DDDEF entries
14. Perform SMP/E APPLY
15. Perform SMP/E ACCEPT

6.1.4 Upload Sample JCL from the client

On the client, there is a file containing sample installation JCL. This sample JCL contains a member (BLZSEQAL) that will allocate the sequential data sets on z/OS for the compressed RELFILES and SMPMCS contained on the client and other members to perform the SMP/E processing. Perform the following steps to upload it from the client to z/OS:

1. Allocate a data set on z/OS to use as the target of the upload. You can do this by creating a data set with the characteristics from the job below or by submitting the job below. If you choose to submit the following job you need to make the following updates:
 - a. Add a job card and modify the parameters to meet your site's requirements before submitting.
 - b. **hlq** will be the high level qualifier you choose to use for this data set.
 - c. (Optionally) Replace vvvvvv with the volser you choose to use for this data set.

```
//ALLOC EXEC PGM=IEFBR14
//*
//JCLBIN DD DSN=hlq.IBM.HRCC701.SMPEJOBS.BIN,
// DISP=(NEW,CATLG,DELETE),
// DSORG=PS,
// RECFM=FB,
// LRECL=80,
// BLKSIZE=6160,
//* VOL=SER=vvvvvv,
// UNIT=SYSALLDA,
// SPACE=(TRK,(15,1))
```

2. Upload the sample jcl file in binary format from the client to this z/OS data set. If the client is attached to a Windows system, you can use FTP from a command prompt to upload the file. In the sample dialog shown below, commands or other information entered by the user are in bold, and the following values are assumed:

<i>Figure 24. User Entered Values</i>	
User enters:	Values
mvsaddr	TCP/IP address or hostname of the z/OS system
tsouid	Your TSO user ID
tsopw	Your TSO password
d:	Your client drive
hlq	High-level qualifier you used for the data set you allocated in the job above

```
C:\>ftp mvsaddr
Connected to mvsaddr.
220-FTP Server (user 'email_address')
220
User (mvsaddr:(none)): tsouid

331-Password:
331
Password: tsopw

230-220-FTPD1 IBM FTP CS V2R1 at mvsaddr, 01:18:20 on 2020-06-09.
230-tsouid is logged on. Working directory is "tsouid.".
230

ftp> cd ..
250 ""is the working directory name prefix.

ftp> cd hlq
250 "hlq." is the working directory name prefix.
```

```

ftp> binary
200 Representation type is Image

ftp> put d:\HRCC701\IBM.HRCC701.F1.BIN 'hlq.IBM.HRCC701.SMPEJOBS.BIN'
200 Port request OK.
125 Storing data set hlq.IBM.HRCC701.SMPEJOBS.BIN
250 Transfer completed successfully.
ftp: 266720 bytes sent in 0.07 Seconds 4112.50 Kbytes/sec.

ftp> quit
221 Quit command received. Goodbye.

```

6.1.5 Expand the sample jcl file by using the TSO Receive command:

```
RECEIVE INDA('hlq.IBM.HRCC701.SMPEJOBS.BIN')
```

When prompted on the TSO receive command, use the appropriate DSNAME as listed below:

```
DS('hlq.IBM.HRCC701.SMPEJOBS')
```

6.1.6 Sample Jobs

The following sample installation jobs are provided as part of the product to help you install Engineering Test Management. The RELFILEs will be prefixed with the high level qualifier ("hlq" in table below) used when the files are "received". The jobs are contained in the sample JCL data set **hlq.IBM.HRCC701.SMPEJOBS** that was uploaded.

Figure 25 (Page 1 of 2). Sample Installation Jobs

Job Name	Job Type	Description	RELFILE
BLZSEQAL	SMP/E	Sample job to allocate sequential data sets for FTPing the product data sets into	hlq.IBM.HRCC701.F1
BLZEXPND	SMP/E	Sample job to expand the RELFILEs	hlq.IBM.HRCC701.F1
BLZDEL	SMP/E	Sample job to remove previous version(s) of IBM Engineering Test Management from an existing SMP/E target and distribution libraries (optional)	hlq.IBM.HRCC701.F1
BLZSMPE	SMP/E	Sample job to create an SMP/E environment (optional)	hlq.IBM.HRCC701.F1
BLZRECV1	RECEIVE	Sample SMP/E RECEIVE job for Common Components	hlq.IBM.HRCC701.F1
BLZRECV2	RECEIVE	Sample SMP/E RECEIVE job for Jazz Team Server	hlq.IBM.HRCC701.F1
BLZRECV3	RECEIVE	Sample SMP/E RECEIVE job for Change and Configuration Management	hlq.IBM.HRCC701.F1

Figure 25 (Page 2 of 2). Sample Installation Jobs

Job Name	Job Type	Description	RELFIL
BLZRECV4	RECEIVE	Sample SMP/E RECEIVE job for Quality Management	hlq.IBM.HRCC701.F1
BLZRECV5	RECEIVE	Sample SMP/E RECEIVE job for Requirements Management	hlq.IBM.HRCC701.F1
BLZRECV7	RECEIVE	Sample SMP/E RECEIVE job for Build System Toolkit	hlq.IBM.HRCC701.F1
BLZRECV8	RECEIVE	Sample SMP/E RECEIVE job for IBM Developer for z/OS Subset	hlq.IBM.HRCC701.F1
BLZRECV9	RECEIVE	Sample SMP/E RECEIVE job for Build Agent	hlq.IBM.HRCC701.F1
BLZRECVA	RECEIVE	Sample SMP/E RECEIVE job for Websphere Liberty Profile	hlq.IBM.HRCC701.F1
BLZRECVB	RECEIVE	Sample SMP/E RECEIVE job for Jazz Reporting Services	hlq.IBM.HRCC701.F1
BLZRECV C	RECEIVE	Sample SMP/E RECEIVE job for Global Configuration Management	hlq.IBM.HRCC701.F1
BLZRECV D	RECEIVE	Sample SMP/E RECEIVE job for Engineering Lifecycle Optimization - Engineering Insights	hlq.IBM.HRCC701.F1
BLZRECVE	RECEIVE	Sample SMP/E RECEIVE job for Link Index Provider	hlq.IBM.HRCC701.F1
BLZALLOC	ALLOCATE	Sample job to allocate target and distribution libraries	hlq.IBM.HRCC701.F1
BLZZFS	ALLOMZF	Sample job to create, format, and mount the data set for the ZFS file system (optional)	hlq.IBM.HRCC701.F1
BLZISMKD	MKDIR	Sample job to invoke the supplied BLZMKDIR EXEC to allocate file system paths	hlq.IBM.HRCC701.F1
BLZDDDEF	DDDEF	Sample job to define SMP/E DDDEFS	hlq.IBM.HRCC701.F1
BLZAPPLY	APPLY	Sample SMP/E APPLY job	hlq.IBM.HRCC701.F1
BLZACCP T	ACCEPT	Sample SMP/E ACCEPT job	hlq.IBM.HRCC701.F1

6.1.7 Run the job to allocate sequential data sets that the FTP step will use

Edit and submit sample job **BLZSEQAL** in the **hlq.IBM.HRCC701.SMPEJOBS** data set to allocate data sets on z/OS to be used during the upload process. Use the instructions in the sample job for information on changes required.

Expected Return Codes and Messages: RC=0

6.1.8 Upload the compressed RELFILES and SMPMCS from the client

Upload the files in binary format from the client to the z/OS data set. If the client is a Windows system, you can use FTP from a command prompt to upload the files:

```
C:\>ftp mvsaddr
Connected to mvsaddr.
220-FTP Server (user 'email_address')
220
User (mvsaddr:(none)): tsouid

331-Password:
331
Password: tsopw

230-220-FTPD1 IBM FTP CS V2R3 at mvsaddr, 05:36:25 on 2020-06-09.
230-tsouid is logged on. Working directory is "tsouid.".
230

ftp> cd ..
250 ""is the working directory name prefix.

ftp> cd hlq
250 "hlq." is the working directory name prefix.

ftp> binary
200 Representation type is Image

ftp> prompt
Interactive mode Off .
```

If you are installing Jazz Team Server - HRJS701:

```
ftp> mput d:\HRJS701\IBM.HRJS701.F*
200 Port request OK.
125 Storing data set IBM.HRJS701.F1.BIN
250 Transfer completed successfully.
ftp: 104720 bytes sent in 0.03 Seconds 4227.20 Kbytes/sec.
200 Port request OK.
```

125 Storing data set IBM.HRJS701.F2.BIN
250 Transfer completed successfully.
ftp: 453157680 bytes sent in 30.73 Seconds 11419.05 Kbytes/sec.

ftp> **put d:\HRJS701\IBM.HRJS701.SMPMCS**
200 Port request OK.
125 Storing data set IBM.HRJS701.SMPMCS
250 Transfer completed successfully.
ftp: 4560 bytes sent in 0.01 Seconds 733.33 Kbytes/sec.

If you are installing Build System Toolkit - HRBT701:

ftp> **mput d:\HRBT701\IBM.HRBT701.F***
200 Port request OK.
125 Storing data set IBM.HRBT701.F1.BIN
250 Transfer completed successfully.
ftp: 697600 bytes sent in 0.07 Seconds 8808.89 Kbytes/sec.
200 Port request OK.
125 Storing data set IBM.HRBT701.F10.BIN
250 Transfer completed successfully.
ftp: 768320 bytes sent in 0.32 Seconds 3737.28 Kbytes/sec.
200 Port request OK.
125 Storing data set IBM.HRBT701.F2.BIN
250 Transfer completed successfully.
ftp: 560387840 bytes sent in 36.78 Seconds 11329.86 Kbytes/sec.
200 Port request OK.
125 Storing data set IBM.HRBT701.F3.BIN
250 Transfer completed successfully.
ftp: 59520 bytes sent in 0.01 Seconds 1651.43 Kbytes/sec.
200 Port request OK.
125 Storing data set IBM.HRBT701.F4.BIN
250 Transfer completed successfully.
ftp: 95600 bytes sent in 0.03 Seconds 3897.93 Kbytes/sec.
200 Port request OK.
125 Storing data set IBM.HRBT701.F5.BIN
250 Transfer completed successfully.
ftp: 884640 bytes sent in 0.10 Seconds 9599.18 Kbytes/sec.
200 Port request OK.
125 Storing data set IBM.HRBT701.F6.BIN
250 Transfer completed successfully.
ftp: 95600 bytes sent in 0.03 Seconds 4186.67 Kbytes/sec.
200 Port request OK.
125 Storing data set IBM.HRBT701.F7.BIN
250 Transfer completed successfully.
ftp: 884640 bytes sent in 0.10 Seconds 9698.14 Kbytes/sec.
200 Port request OK.
125 Storing data set IBM.HRBT701.F8.BIN
250 Transfer completed successfully.
ftp: 97760 bytes sent in 0.03 Seconds 4266.67 Kbytes/sec.

200 Port request OK.
125 Storing data set IBM.HRBT701.F9.BIN
250 Transfer completed successfully.
ftp: 904880 bytes sent in 0.10 Seconds 9703.43 Kbytes/sec.

ftp> **put d:\HRBT701\IBM.HRBT701.SMPMCS**
200 Port request OK.
125 Storing data set IBM.HRBT701.SMPMCS
250 Transfer completed successfully.
ftp: 74880 bytes sent in 0.02 Seconds 3374.55 Kbytes/sec.

**If you are installing
IBM Developer for z/OS Subset - HRDV701:**

ftp> **mput d:\HRDV701\IBM.HRDV701.F***
200 Port request OK.
125 Storing data set IBM.HRDV701.F1.BIN
250 Transfer completed successfully.
ftp: 1211520 bytes sent in 0.12 Seconds 9815.93 Kbytes/sec.
200 Port request OK.
125 Storing data set IBM.HRDV701.F2.BIN
250 Transfer completed successfully.
ftp: 22640 bytes sent in 0.01 Seconds 2160.00 Kbytes/sec.
200 Port request OK.
125 Storing data set IBM.HRDV701.F3.BIN
250 Transfer completed successfully.
ftp: 303760 bytes sent in 0.07 Seconds 8268.24 Kbytes/sec.

ftp> **put d:\HRDV701\IBM.HRDV701.SMPMCS**
200 Port request OK.
125 Storing data set IBM.HRDV701.SMPMCS
250 Transfer completed successfully.
ftp: 3040 bytes sent in 0.2 Seconds 511.66 Kbytes/sec.

If you are installing Build Agent - HRBA701:

ftp> **mput d:\HRBA701\IBM.HRBA701.F***
200 Port request OK.
125 Storing data set IBM.HRBA701.F1.BIN
250 Transfer completed successfully.
ftp: 31920 bytes sent in 0.01 Seconds 2308.57 Kbytes/sec.
200 Port request OK.
125 Storing data set IBM.HRBA701.F2.BIN
250 Transfer completed successfully.
ftp: 1439600 bytes sent in 0.15 Seconds 9420.53 Kbytes/sec.

ftp> **put d:\HRBA701\IBM.HRBA701.SMPMCS**
200 Port request OK.

125 Storing data set IBM.HRBA701.SMPMCS
250 Transfer completed successfully.
ftp: 2240 bytes sent in 0.00 Seconds 1080.00 Kbytes/sec.

If you are installing Change and Configuration Management - HRCM701

ftp> **mput d:\HRCM701\IBM.HRCM701.F***
200 Port request OK.
125 Storing data set IBM.HRCM701.F1.BIN
250 Transfer completed successfully.
ftp: 73920 bytes sent in 0.02 Seconds 3381.82 Kbytes/sec.
200 Port request OK.
125 Storing data set IBM.HRCM701.F2.BIN
250 Transfer completed successfully.
ftp: 582206000 bytes sent in 39.28 Seconds 11266.47 Kbytes/sec.

ftp> **put d:\HRCM701\IBM.HRCM701.SMPMCS**
200 Port request OK.
125 Storing data set IBM.HRCM701.SMPMCS
250 Transfer completed successfully.
ftp: 5840 bytes sent in 0.01 Seconds 822.86 Kbytes/sec.

If you are installing Quality Management - HRQM701

ftp> **mput d:\HRQM701\IBM.HRQM701.F***
200 Port request OK.
125 Storing data set IBM.HRQM701.F1.BIN
250 Transfer completed successfully.
ftp: 70240 bytes sent in 0.02 Seconds 3295.24 Kbytes/sec.
200 Port request OK.
125 Storing data set IBM.HRQM701.F2.BIN
250 Transfer completed successfully.
ftp: 655971280 bytes sent in 51.40 Seconds 11157.74 Kbytes/sec.

ftp> **put d:\HRQM701\IBM.HRQM701.SMPMCS**
200 Port request OK.
125 Storing data set IBM.HRQM701.SMPMCS
250 Transfer completed successfully.
ftp: 5920 bytes sent in 0.01 Seconds 1152.00 Kbytes/sec.

If you are installing Requirements Management - HRRM701

ftp> **mput d:\HRRM701\IBM.HRRM701.F***
200 Port request OK.
125 Storing data set IBM.HRRM701.F1.BIN
250 Transfer completed successfully.
ftp: 74320 bytes sent in 0.02 Seconds 3345.45 Kbytes/sec.
200 Port request OK.
125 Storing data set IBM.HRRM701.F2.BIN
250 Transfer completed successfully.
ftp: 664305200 bytes sent in 42.57 Seconds 11363.55 Kbytes/sec.

```
ftp> put d:\HRRM701\IBM.HRRM701.SMPMCS
200 Port request OK.
125 Storing data set IBM.HRRM701.SMPMCS
250 Transfer completed successfully.
ftp: 7200 bytes sent in 0.01 Seconds 1017.14 Kbytes/sec.
```

If you are installing Common Components - HRCC701

```
ftp> mput d:\HRCC701\IBM.HRCC701.F*
200 Port request OK.
125 Storing data set IBM.HRCC701.F1.BIN
250 Transfer completed successfully.
ftp: 266720 bytes sent in 0.04 Seconds 6561.90 Kbytes/sec.
200 Port request OK.
125 Storing data set IBM.HRCC701.F10.BIN
250 Transfer completed successfully.
ftp: 455520 bytes sent in 0.07 Seconds 7546.67 Kbytes/sec.
200 Port request OK.
125 Storing data set IBM.HRCC701.F11.BIN
250 Transfer completed successfully.
ftp: 29360 bytes sent in 0.12 Seconds 440.00 Kbytes/sec.
200 Port request OK.
125 Storing data set IBM.HRCC701.F12.BIN
250 Transfer completed successfully.
ftp: 457920 bytes sent in 0.05 Seconds 7981.75 Kbytes/sec.
200 Port request OK.
125 Storing data set IBM.HRCC701.F13.BIN
250 Transfer completed successfully.
ftp: 871200 bytes sent in 0.38 Seconds 2164.04 Kbytes/sec.
200 Port request OK.
125 Storing data set IBM.HRCC701.F14.BIN
250 Transfer completed successfully.
ftp: 4320 bytes sent in 0.38 Seconds 1017.14 Kbytes/sec.
200 Port request OK.
125 Storing data set IBM.HRCC701.F2.BIN
250 Transfer completed successfully.
ftp: 412880 bytes sent in 0.05 Seconds 7425.31 Kbytes/sec.
200 Port request OK.
125 Storing data set IBM.HRCC701.F3.BIN
250 Transfer completed successfully.
ftp: 29470160 bytes sent in 2.54 Seconds 11588.90 Kbytes/sec.
200 Port request OK.
125 Storing data set IBM.HRCC701.F4.BIN
250 Transfer completed successfully.
ftp: 379120 bytes sent in 0.07 Seconds 8444.44 Kbytes/sec.
200 Port request OK.
125 Storing data set IBM.HRCC701.F5.BIN
250 Transfer completed successfully.
```

ftp: 7760 bytes sent in 0.01 Seconds 1240.00 Kbytes/sec.
125 Storing data set IBM.HRCC701.F6.BIN
250 Transfer completed successfully.
ftp: 925360 bytes sent in 0.03 Seconds 7007.65 Kbytes/sec.
200 Port request OK.
125 Storing data set IBM.HRCC701.F7.BIN
250 Transfer completed successfully.
ftp: 28800 bytes sent in 0.01 Seconds 2245.33 Kbytes/sec.
200 Port request OK.
125 Storing data set IBM.HRCC701.F8.BIN
250 Transfer completed successfully.
ftp: 455520 bytes sent in 0.05 Seconds 8385.19 Kbytes/sec.
200 Port request OK.
125 Storing data set IBM.HRCC701.F9.BIN
250 Transfer completed successfully.
ftp: 28800 bytes sent in 0.01 Seconds 2245.33 Kbytes/sec.

ftp> put d:\HRCC701\IBM.HRCC701.SMPMCS
200 Port request OK.
125 Storing data set IBM.HRCC701.SMPMCS
250 Transfer completed successfully.
ftp: 39520 bytes sent in 0.01 Seconds 2416.00 Kbytes/sec.

If you are installing Websphere Liberty Profile - HRWL701

ftp> mput d:\HRWL701\IBM.HRWL701.F*
200 Port request OK.
125 Storing data set IBM.HRWL701.F1.BIN
250 Transfer completed successfully.
ftp: 74960 bytes sent in 0.02Seconds 3607.62 Kbytes/sec.
200 Port request OK.
125 Storing data set IBM.HRWL701.F2.BIN
250 Transfer completed successfully.
ftp: 297582800 bytes sent in 21.78 Seconds 11649.77 Kbytes/sec.

ftp> put d:\HRWL701\IBM.HRWL701.SMPMCS
200 Port request OK.
125 Storing data set IBM.HRWL701.SMPMCS
250 Transfer completed successfully.
ftp: 2640 bytes sent in 0.00 Seconds 1160.00 Kbytes/sec.

If you are installing Jazz Reporting Services - HRRS701

ftp> mput d:\HRRS701\IBM.HRRS701.F*
200 Port request OK.
125 Storing data set IBM.HRRS701.F1.BIN
250 Transfer completed successfully.
ftp: 170880 bytes sent in 0.03 Seconds 5183.03 Kbytes/sec.
200 Port request OK.

125 Storing data set IBM.HRRS701.F2.BIN
250 Transfer completed successfully.
ftp: 581776400 bytes sent in 33.34 Seconds 11679.21 Kbytes/sec.

ftp> **put d:\HRRS701\IBM.HRRS701.SMPMCS**
200 Port request OK.
125 Storing data set IBM.HRRS701.SMPMCS
250 Transfer completed successfully.
ftp: 5600 bytes sent in 0.01 Seconds 880.00 Kbytes/sec.

If you are installing Global Configuration Management - HRGC701

ftp> **mput d:\HRGC701\IBM.HRGC701.F***
200 Port request OK.
125 Storing data set IBM.HRGC701.F1.BIN
250 Transfer completed successfully.
ftp: 73550 bytes sent in 0.02 Seconds 3073.33 Kbytes/sec.
200 Port request OK.
125 Storing data set IBM.HRGC701.F2.BIN
250 Transfer completed successfully.
ftp: 378664000 bytes sent in 26.04 Seconds 11468.70 Kbytes/sec.

ftp> **put d:\HRGC701\IBM.HRGC701.SMPMCS**
200 Port request OK.
125 Storing data set IBM.HRGC701.SMPMCS
250 Transfer completed successfully.
ftp: 4480 bytes sent in 0.01 Seconds 832.00 Kbytes/sec.

If you are installing Engineering Lifecycle Optimization - Engineering Insights - HRRE701

ftp> **mput d:\HRRE701\IBM.HRRE701.F***
200 Port request OK.
125 Storing data set IBM.HRRE701.F1.BIN
250 Transfer completed successfully.
ftp: 77040 bytes sent in 0.03 Seconds 3078.40 Kbytes/sec.
200 Port request OK.
125 Storing data set IBM.HRRE701.F2.BIN
250 Transfer completed successfully.
ftp: 386864080 bytes sent in 26.19 Seconds 11635.27 Kbytes/sec.

ftp> **put d:\HRRE701\IBM.HRRE701.SMPMCS**
200 Port request OK.
125 Storing data set IBM.HRRE701.SMPMCS
250 Transfer completed successfully.
ftp: 4800 bytes sent in 0.01 Seconds 896.00 Kbytes/sec.

If you are installing Link Index Provider - HRLI701

```

ftp> mput d:\HRLI701\IBM.HRLI701.F*
200 Port request OK.
125 Storing data set IBM.HRLI701.F1.BIN
250 Transfer completed successfully.
ftp: 48800 bytes sent in 0.02 Seconds 2684.44 Kbytes/sec.
200 Port request OK.
125 Storing data set IBM.HRLI701.F2.BIN
250 Transfer completed successfully.
ftp: 89414400 bytes sent in 4.00 Seconds 11241.59 Kbytes/sec.

ftp> put d:\HRLI701\IBM.HRLI701.SMPMCS
200 Port request OK.
125 Storing data set IBM.HRLI701.SMPMCS
250 Transfer completed successfully.
ftp: 2240 bytes sent in 0.00 Seconds 640.00 Kbytes/sec.

ftp> quit
221 Quit command received. Goodbye.

```

6.1.9 Expand the RELFILEs by running the sample job, BLZEXPND:

Edit and submit sample job BLZEXPND to expand the RELFILEs. Consult the instructions in the sample job for more information.

Expected Return Codes and Messages: RC=0

6.1.10 Delete previous release of Engineering Test Management (Optional)

If you wish to install Engineering Test Management into an existing set of SMP/E target and distribution libraries that contain a previous release of IBM Engineering Test Management then you should run this job to delete the previous release. If you are installing Engineering Test Management into a new set of SMP/E target and distribution libraries then you do not need to run this job.

Before running this job you will need to create a dummy function SYSMOD, that can be used to delete the previous release. Edit the sample function sysmod supplied in BLZDELF and specify all the FMIDS that are to be deleted from existing SMP/E target and distribution libraries in the DELETE operand of the ++VER MCS statement.

Edit and submit sample job BLZDEL to delete the previous release of the Engineering Test Management. Consult the instructions in the sample job for more information.

Expected Return Codes and Messages: You will receive a return code of 0 if this job runs correctly.

6.1.11 Allocate SMP/E CSI (Optional)

If you are using an existing CSI, do not execute this job.

If you are allocating a new SMP/E data set for this install, edit and submit sample job BLZSMPE to allocate the SMP/E data sets for

Engineering Test Management. Consult the instructions in the sample job for more information.

Expected Return Codes and Messages: You will receive a return code of 0 if this job runs correctly.

6.1.12 Perform SMP/E RECEIVE

If you are installing HRCC701, Common Components, edit and submit sample job BLZRECV1 to perform the SMP/E RECEIVE. Consult the instructions in the sample job for more information.

Expected Return Codes and Messages: You will receive a return code of 0 if this job runs correctly.

If you are installing HRJS701, Jazz Team Server, edit and submit sample job BLZRECV2 to perform the SMP/E RECEIVE. Consult the instructions in the sample job for more information.

Expected Return Codes and Messages: You will receive a return code of 0 if this job runs correctly.

If you are installing HRCM701, Change and Configuration Management, edit and submit sample job BLZRECV3 to perform the SMP/E RECEIVE. Consult the instructions in the sample job for more information.

Expected Return Codes and Messages: You will receive a return code of 0 if this job runs correctly.

If you are installing HRQM701, Quality Management, edit and submit sample job BLZRECV4 to perform the SMP/E RECEIVE. Consult the instructions in the sample job for more information.

Expected Return Codes and Messages: You will receive a return code of 0 if this job runs correctly.

If you are installing HRRM701, Requirements Management, edit and submit sample job BLZRECV5 to perform the SMP/E RECEIVE. Consult the instructions in the sample job for more information.

Expected Return Codes and Messages: You will receive a return code of 0 if this job runs correctly.

If you are installing HRBT701, Build System Toolkit, edit and submit sample job BLZRECV7 to perform the SMP/E RECEIVE. Consult the instructions in the sample job for more information.

Expected Return Codes and Messages: You will receive a return code of 0 if this job runs correctly.

If you are installing HRDV701, IBM Developer for z/OS Subset, edit and submit sample job BLZRECV8 to perform the SMP/E RECEIVE. Consult the instructions in the sample job for more information.

Expected Return Codes and Messages: You will receive a return code of 0 if this job runs correctly.

If you are installing HRBA701, Build Agent, edit and submit sample job BLZRECV9 to perform the SMP/E RECEIVE. Consult the instructions in the sample job for more information.

Expected Return Codes and Messages: You will receive a return code of 0 if this job runs correctly.

If you are installing HRWL701, Websphere Liberty Profile, edit and submit sample job BLZRECVA to perform the SMP/E RECEIVE. Consult the instructions in the sample job for more information.

Expected Return Codes and Messages: You will receive a return code of 0 if this job runs correctly.

If you are installing HRRS701, Jazz Reporting Services, edit and submit sample job BLZRECVB to perform the SMP/E RECEIVE. Consult the instructions in the sample job for more information.

Expected Return Codes and Messages: You will receive a return code of 0 if this job runs correctly.

If you are installing HRGC701, Global Configuration Management, edit and submit sample job BLZRECVC to perform the SMP/E RECEIVE. Consult the instructions in the sample job for more information.

Expected Return Codes and Messages: You will receive a return code of 0 if this job runs correctly.

If you are installing HRRE701, Engineering Lifecycle Optimization - Engineering Insights, edit and submit sample job BLZRECVD to perform the SMP/E RECEIVE. Consult the instructions in the sample job for more information.

Expected Return Codes and Messages: You will receive a return code of 0 if this job runs correctly.

If you are installing HRLI701, Link Index Provider, edit and submit sample job BLZRECVE to perform the SMP/E RECEIVE. Consult the instructions in the sample job for more information.

Expected Return Codes and Messages: You will receive a return code of 0 if this job runs correctly.

6.1.13 Allocate SMP/E Target and Distribution Libraries

Edit and submit sample job BLZALLOC to allocate the SMP/E target and distribution libraries for Engineering Test Management. Consult the instructions in the sample job for more information.

Expected Return Codes and Messages: You will receive a return code of 0 if this job runs correctly.

Note: Regarding ABLZHFS space allocation

The ABLZHFS data set, allocated in the BLZALLOC job specifies a primary space allocation of 7200 Cylinders (178800 Tracks). This figure is based on the assumption that all FMIDs for IBM Engineering Workflow Management will be applied and accepted. If you are only applying and accepting certain FMIDs then this space allocation can be adjusted to the amount of space required for those FMIDs. The following list specifies the space allocation utilized by each FMID in the ABLZHFS data set during the ACCEPT phase of the SMP/E installation.

- HRJS701 - 15500 Tracks
- HRBT701 - 21900 Tracks
- HRBA701 - 100 Tracks
- HRCM701 - 20700 Tracks
- HRQM701 - 25000 Tracks
- HRRM701 - 21400 Tracks
- HRCC701 - 2300 Tracks
- HRWL701 - 11300 Tracks
- HRRS701 - 13500 Tracks
- HRGC701 - 12700 Tracks
- HRRE701 - 13000 Tracks
- HRLI701 - 1950 Tracks

6.1.14 Allocate, create and mount ZFS File System (Optional)

Edit and submit sample job BLZZFS to allocate, create a mountpoint, and mount a ZFS data set.

Expected Return Codes and Messages: You will receive a return code of 0 if these jobs run correctly.

6.1.15 Allocate File System Paths

The target system HFS or zFS data set must be mounted on the driving system when running the sample BLZISMKD job since the job will create paths in the HFS or zFS.

Before running the sample job to create the paths in the file system, you must ensure that OMVS is active on the driving system and that the target system's HFS or zFS file system is mounted to the driving system. zFS must be active on the driving system if you are installing Engineering Test Management into a file system that is zFS.

If you plan to install Engineering Test Management into a new HFS or zFS file system, you must create the mountpoint and mount the new file system to the driving system for Engineering Test Management.

The recommended mountpoint is `/usr/lpp/jazz/v7.0.1`.

Edit and submit sample job BLZISMKD to allocate the HFS or zFS paths for Engineering Test Management. Consult the instructions in the sample job for more information.

If you create a new file system for this product, consider updating the BPXPRMxx PARMLIB member to mount the new file system at IPL time. This action can be helpful if an IPL occurs before the installation is completed.

Expected Return Codes and Messages: You will receive a return code of 0 if this job runs correctly.

6.1.16 Create DDDEF Entries

Edit and submit sample job BLZDDDEF to create DDDEF entries for the SMP/E target and distribution libraries for Engineering Test Management. Consult the instructions in the sample job for more information.

Expected Return Codes and Messages: You will receive a return code of 0 if this job runs correctly.

Note: If you have previously installed any of the FMIDs, HRJS701, HRBT701, HRDV701, HRBA701, HRCM701, HRQM701, HRRM701, HRCC701, HRWL701, HRRS701, HRGC701, HRRE701, or HRLI701, it is not necessary to rerun the BLZDDDEF job. It should only be run once!

6.1.17 Perform SMP/E APPLY

1. Ensure that you have the latest HOLDDATA; then edit and submit sample job BLZAPPLY to perform an SMP/E APPLY CHECK for Engineering Test Management. Consult the instructions in the sample job for more information.

The latest HOLDDATA is available through several different portals, including <http://service.software.ibm.com/holddata/390holddata.html>. The latest HOLDDATA may identify HIPER and FIXCAT APARs for the FMIDs you will be installing. An APPLY CHECK will help you determine if any HIPER or FIXCAT APARs are applicable to the FMIDs you are installing. If there are any applicable HIPER or FIXCAT APARs, the APPLY CHECK will also identify fixing PTFs that will resolve the APARs, if a fixing PTF is available.

You should install the FMIDs regardless of the status of unresolved HIPER or FIXCAT APARs. However, do not deploy the software until the unresolved HIPER and FIXCAT APARs have been analyzed to determine their applicability. That is, before deploying the software either ensure fixing PTFs are applied to resolve all HIPER or FIXCAT APARs, or ensure the problems reported by all HIPER or FIXCAT APARs are not applicable to your environment.

To receive the full benefit of the SMP/E Causer SYSMOD Summary Report, do *not* bypass the PRE, ID, REQ, and IFREQ on the APPLY CHECK. The SMP/E root cause analysis identifies the cause only of *errors* and not of *warnings* (SMP/E treats bypassed PRE, ID, REQ, and IFREQ conditions as warnings, instead of errors).

Here are sample APPLY commands:

- a. To ensure that all recommended and critical service is installed with the FMIDs, receive the latest HOLDDATA and use the APPLY CHECK command as follows

```

APPLY S(fmid,fmid,...) CHECK
FORFMID(fmid,fmid,...)
SOURCEID(RSU*)
FIXCAT(IBM.ProductInstall-RequiredService)
GROUPEXTEND .

```

Some HIPER APARs might not have fixing PTFs available yet. You should analyze the symptom flags for the unresolved HIPER APARs to determine if the reported problem is applicable to your environment and if you should bypass the specific ERROR HOLDS in order to continue the installation of the FMIDs.

This method requires more initial research, but can provide resolution for all HIPERs that have fixing PTFs available and are not in a PE chain. Unresolved PEs or HIPERs might still exist and require the use of BYPASS.

- b. To install the FMIDs without regard for unresolved HIPER APARs, you can add the BYPASS(HOLDCLASS(HIPER)) operand to the APPLY CHECK command. This will allow you to install FMIDs even though one or more unresolved HIPER APARs exist. After the FMIDs are installed, use the SMP/E REPORT ERRSYSMODS command to identify unresolved HIPER APARs and any fixing PTFs.

```

APPLY S(fmid,fmid,...) CHECK
FORFMID(fmid,fmid,...)
SOURCEID(RSU*)
FIXCAT(IBM.ProductInstall-RequiredService)
GROUPEXTEND
BYPASS(HOLDCLASS(HIPER),HOLDFIXCAT) .
..any other parameters documented in the program directory

```

This method is the quicker, but requires subsequent review of the Exception SYSMOD report produced by the REPORT ERRSYSMODS command to investigate any unresolved HIPERs. If you have received the latest HOLDDATA, you can also choose to use the REPORT MISSINGFIX command and specify Fix Category IBM.ProductInstall-RequiredService to investigate missing recommended service.

If you bypass HOLDS during the installation of the FMIDs because fixing PTFs are not yet available, you can be notified when the fixing PTFs are available by using the APAR Status Tracking (AST) function of ServiceLink or the APAR Tracking function of ResourceLink.

2. After you take actions that are indicated by the APPLY CHECK, remove the CHECK operand and run the job again to perform the APPLY.

Note: The GROUPEXTEND operand indicates that SMP/E applies all requisite SYSMODs. The requisite SYSMODs might be applicable to other functions.

Expected Return Codes and Messages from APPLY CHECK: You will receive a return code of 0 if this job runs correctly.

Expected Return Codes and Messages from APPLY: You will receive a return code of 0 if this job runs correctly.

6.1.18 Perform SMP/E ACCEPT

Edit and submit sample job BLZACCPT to perform an SMP/E ACCEPT CHECK for Engineering Test Management. Consult the instructions in the sample job for more information.

To receive the full benefit of the SMP/E Causer SYSMOD Summary Report, do *not* bypass the PRE, ID, REQ, and IFREQ on the ACCEPT CHECK. The SMP/E root cause analysis identifies the cause of only *errors* but not *warnings* (SMP/E treats bypassed PRE, ID, REQ, and IFREQ conditions as warnings rather than errors).

Before you use SMP/E to load new distribution libraries, it is recommended that you set the ACCJCLIN indicator in the distribution zone. In this way, you can save the entries that are produced from JCLIN in the distribution zone whenever a SYSMOD that contains inline JCLIN is accepted. For more information about the ACCJCLIN indicator, see the description of inline JCLIN in the SMP/E Commands book for details.

After you take actions that are indicated by the ACCEPT CHECK, remove the CHECK operand and run the job again to perform the ACCEPT.

Note: The GROUPEXTEND operand indicates that SMP/E accepts all requisite SYSMODs. The requisite SYSMODS might be applicable to other functions.

Expected Return Codes and Messages from ACCEPT CHECK: You will receive a return code of 0 if this job runs correctly.

If PTFs that contain replacement modules are accepted, SMP/E ACCEPT processing will link-edit or bind the modules into the distribution libraries. During this processing, the Linkage Editor or Binder might issue messages that indicate unresolved external references, which will result in a return code of 4 during the ACCEPT phase. You can ignore these messages, because the distribution libraries are not executable and the unresolved external references do not affect the executable system libraries.

Expected Return Codes and Messages from ACCEPT: You will receive a return code of 0 if this job runs correctly.

6.1.19 Run REPORT CROSSZONE

The SMP/E REPORT CROSSZONE command identifies requisites for products that are installed in separate zones. This command also creates APPLY and ACCEPT commands in the SMPPUNCH data set. You can use the APPLY and ACCEPT commands to install those cross-zone requisites that the SMP/E REPORT CROSSZONE command identifies.

After you install Engineering Test Management, it is recommended that you run REPORT CROSSZONE against the new or updated target and distribution zones. REPORT CROSSZONE requires a global zone with ZONEINDEX entries that describe all the target and distribution libraries to be reported on.

For more information about REPORT CROSSZONE, see the SMP/E manuals.

6.2 Activating Engineering Test Management

6.2.1 Product Customization

Refer to Engineering Test Management Knowledge Center to complete the configuration tasks.

http://www.ibm.com/support/knowledgecenter/SSR27Q_7.0.1

7.0 Notices

This information was developed for products and services offered in the U.S.A. IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

APAR numbers are provided in this document to assist in locating PTFs that may be required. Ongoing problem reporting may result in additional APARs being created. Therefore, the APAR lists in this document may not be complete. To obtain current service recommendations and to identify current product service requirements, always contact the IBM Customer Support Center or use S/390 SoftwareXcel to obtain the current "PSP Bucket".

IBM may have patents or pending patent applications covering subject matter in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to the

IBM Director of Licensing
IBM Corporation
North Castle Drive
Armonk, New York 10504-1785
USA

For license inquiries regarding double-byte (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

Intellectual Property Licensing
Legal and Intellectual Property Law
IBM Japan, Ltd.
19-21, Nihonbashi-Hakozakicho, Chuo-ku
Tokyo 103-8510, Japan

7.1 Trademarks

IBM, the IBM logo, and ibm.com are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the Web at "Copyright and trademark information" at www.ibm.com/legal/copytrade.shtml.

Reader's Comments

Program Directory for IBM Engineering Test Management, June 2020

We appreciate your input on this publication. Feel free to comment on the clarity, accuracy, and completeness of the information or give us any other feedback that you might have.

Use one of the following methods to send us your comments:

1. Send an email to comments@us.ibm.com
2. Use the form on the Web at:

www.ibm.com/software/ad/rcf

When you send information to IBM, you grant IBM a nonexclusive right to use or distribute the information in any way it believes appropriate without incurring any obligation to you.

IBM or any other organizations will only use the personal information that you supply to contact you about the issues that you submit.

Thank you for your participation.



Printed in USA

G113-2891-09

