


IBM OpenPages with Watson
Version 8.1.0.2 Interim Fix 2

Interim Fix ReadMe



NOTE

Before using this information and the product it supports, read the information in the “Notices” section of this document.

Product Information

This document applies to IBM OpenPages with Watson 8.1.0.2 and may also apply to subsequent releases.

Licensed Materials – Property of IBM

© Copyright IBM Corporation 2003, 2022. All rights reserved.

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Documentation Release Information

Last Modified: January 21, 2022

Table of Contents

About this Interim Fix	4
Defect Fixes, Enhancements, and Known Issues	4
Defect Fixes	4
Before You Begin	4
Prerequisite Software	4
General Information	4
Backup the current databases.....	4
Oracle database.....	4
Db2 database.....	4
Folder Substitutions	5
Installation Tasks.....	6
Task 1: Decide whether to update the OpenPages database manually	6
Task 2: Ensure that all OpenPages servers and services are running except the Global Search server	6
Task 3: Apply the OpenPages 8.1.0.2 IF2	7
Task 4: Stop and Restart all the OpenPages servers and services including the Global Search server	7
Uninstalling This Patch	8
Task 1: Stop all OpenPages servers and services.....	8
Task 2: Manually restore the previous patch version from the backups.....	8
Task 3: Restore Databases	14
Oracle database.....	14
Db2 database.....	14
Task 4: Start all OpenPages servers and services	14
Documentation Updates	15
Notices.....	16
Copyright.....	18

About this Interim Fix

This Interim Fix updates the IBM® OpenPages® with Watson™ environment from version 8.1.0.2 to 8.1.0.2 IF2 for IBM WebSphere Application Server on AIX or Linux or Windows.

Defect Fixes, Enhancements, and Known Issues

Defect Fixes

The following defect fixes are included in this release. The Authorized Problem Analysis Report (APAR) ID, if available, is shown in parentheses after a description. For example: (PM12345).

OpenPages 8.1.0.2 IF2

- Security updates

OpenPages 8.1.0.2 IF1

- In the Task Focused UI, security rule for restricting association causes object creation to fail (PH37718)
- Access to system files in the /Reports folder has changed. Now only super administrators and members of the OPAdministrators group can create or modify JSP report system files. Previously, all users with the Report object type in their profile had access.

Before You Begin

Prerequisite Software

Prior to installing IBM® OpenPages® with Watson™ 8.1.0.2 IF2, OpenPages 8.1.0.2 must be installed. To install IBM® OpenPages® with Watson™ 8.1.0.2 IF2, use the OpenPages 8.1.0.2 Installer.

General Information

For information regarding the installation and setup of the OpenPages installer server and installer agents, please see “*OpenPages installation server and app*” topic in the IBM OpenPages with Watson 8.1.0 Installation and Deployment Guide at https://www.ibm.com/support/knowledgecenter/en/SSFUEU_8.1.0/op_grc_installation/c_op_ig_instprg_ov.html

Backup the current databases

Oracle database

For details, see the “Using IBM OpenPages with Watson utilities with Oracle databases” chapter in the IBM® OpenPages® with Watson™ Administrator’s Guide.

Db2 database

For details, see the “Using IBM OpenPages with Watson utilities with Db2 databases” chapter in the IBM® OpenPages® with Watson™ Administrator’s Guide.

Folder Substitutions

The following table contains the folder substitutions used in this document:

Substitution	Platform	Default folder or value
<InstallerHome>	AIX/Linux	/opt/IBM/OP-Installer
	Windows	C:\IBM\OP-Installer
<InstallerMaintenance>	AIX/Linux	<InstallerHome>/src/assets/maintenance
	Windows	<InstallerHome>\src\assets\maintenance
<OP_Home>	AIX/Linux	/opt/IBM/OpenPages
	Windows	C:\IBM\OpenPages
<OPBackup8102>	AIX/Linux	<OP_Home>/installer/maintenance/interim-fix-8.1.0.2.2/backups_from_8.1.0.2[.X] where X is the most recently installed interim fix version, if any
	Windows	<OP_Home>\installer\maintenance\interim-fix-8.1.0.2.2\backups_from_8.1.0.2[.X] where X is the most recently installed interim fix version, if any
<OP-Node>	All	The application server's OpenPages Node Name, default is <i>OpenPagesNode</i>
<OP-Dmgr>	All	The deployment manager name, default is <i>OpenPagesDmgr</i>
<OP-Cell>	All	OpenPages Cell Name; default is <i>OpenPagesCell</i>
<OP_Dmgr_HostName>	All	The deployment manager server host name
<OP_Dmgr_Port>	All	The deployment manager server port, default is 8879
<cognos_home>/	AIX/Linux	/opt/IBM/cognos/analytics
	Windows	C:\IBM\cognos\analytics
<CC_Home>	AIX/Linux	/opt/IBM/CommandCenter
	Windows	C:\IBM\CommandCenter
<CCBackup8102>	AIX/Linux	<CC_Home>/installer/maintenance/interim-fix-8.1.0.2.2/backups_from_8.1.0.2[.X] where X is the most recently installed interim fix version, if any
	Windows	<CC_Home>\installer\maintenance\interim-fix-8.1.0.2.2\backups_from_8.1.0.2[.X] where X is the most recently installed interim fix version, if any
<OPSearch_Home>	AIX/Linux	/opt/IBM/OpenPages/Search
	Windows	C:\IBM\OpenPages\Search
<OPSearchBackup8102>	AIX/Linux	<OPSearch_Home>/installer/maintenance/interim-fix-8.1.0.2.2/backups_from_8.1.0.2[.X] where X is the most recently installed interim fix version, if any
	Windows	<OPSearch_Home>\installer\maintenance\interim-fix-8.1.0.2.2\backups_from_8.1.0.2[.X] where X is the most recently installed interim fix version, if any
<BPM_Home>	AIX/Linux	/opt/IBM/WebSphere/BPMServer
	Windows	C:\IBM\WebSphere\BPMServer
<OPBPMInt_Home>	AIX/Linux	/opt/IBM/BPMIntegration
	Windows	C:\IBM\BPMIntegration
<OPBPMIntBackup8102>	AIX/Linux	<OPBPMInt_Home>/installer/maintenance/interim-fix-8.1.0.2.2/backups_from_8.1.0.2[.X] where X is the most recently installed interim fix version, if any
	Windows	<OPBPMInt_Home>\installer\maintenance\interim-fix-8.1.0.2.2\backups_from_8.1.0.2[.X] where X is the most recently installed interim fix version, if any

Installation Tasks

To install IBM® OpenPages® with Watson™ 8.1.0.2 IF2, perform the following tasks.

Task 1: Decide whether to update the OpenPages database manually

When installing this interim fix, you can choose to update the database by running scripts. Use this option if you do not want to enter DBA credentials in the installation app.

It is not mandatory to update the database server manually. You can use the OpenPages® installation app to update the database automatically, if you prefer.

If you decide to update the database manually, please see the following topic in the IBM OpenPages GRC Platform 8.1.0 Installation and Deployment Guide at

Db2: Update the OpenPages database manually (DB2®)

https://www.ibm.com/support/knowledgecenter/SSFUEU_8.1.0/op_grc_installation/c_op_ig_fp_db2_update_db_manually.html

Oracle: Update the OpenPages database manually (Oracle)

http://www.ibm.com/support/knowledgecenter/SSFUEU_8.1.0/op_grc_installation/c_op_fixpacks_update_database_server_manually.html

Note: The steps to be performed for this interim fix are the same as those performed for the OpenPages 8.1.0.x fix packs, but the

`<fix_pack_kit>/OP_<version>_Non_Embedded/OP_<version>_Configuration/Database/<database_type>/PATCH_SCRIPTS` directory mentioned in the steps should be replaced with the IBM OpenPages with Watson 8.1.0.2.x media location of:
`<interim_fix_kit>/Database/<database_type>/PATCH_SCRIPTS`

Task 2: Ensure that all OpenPages servers and services are running except the Global Search server

Note: For details, see the “Starting and stopping servers” chapter in the *IBM® OpenPages® with Watson™ Administrator’s Guide*.

Task 3: Apply the OpenPages 8.1.0.2 IF2

Use the 8.1.0.2 OpenPages installer to apply the 8.1.0.2.2 Interim fix. Perform the following steps as the user that setup the Installation Server.

Using the installation app, do the following:

- 2.1 Ensure that the OpenPages 8.1.0.2 installation server is running and that the OpenPages 8.1.0.2 installer agents on the remote servers in the deployment (if applicable) are also running.
- 2.2 Copy the **openpages_interimFix_8-1-0-2-2.zip** file from the interim fix media into the *<InstallerMaintenance>* directory on the installation server.
- 2.3 Open the existing 8.1.0.2 deployment and press the browser's **Refresh** button to refresh the installation app.
- 2.4 Click the *Deployment Task* drop-down and select *Interim Fix* and select *8.1.0.2.2* in the *Version* drop-down.

Perform the **Validate**, **Install**, and **Configure** actions to apply the interim fix updates to the OpenPages 8.1.0.2.x deployment.

Note: Each file in the OpenPages deployment that is replaced by the interim fix content is automatically backed up into the *<OPBackup8102>*, *<CCBackup8102>*, or *<OPSearchBackup8102>* folder, as applicable.

Task 4: Stop and Restart all the OpenPages servers and services including the Global Search server

Note: For details, see the "Starting and stopping servers" chapter in the *IBM® OpenPages® with Watson™ Administrator's Guide*.

- When restarting the IBMOpenPagesFrameworkModelGenerator service, use the --clean option.

For example

```
./server start IBMOpenPagesFrameworkModelGenerator --clean
```

Uninstalling This Patch

Uninstalling 8.1.0.2 IF2 will revert the system to the previous patch level.

To uninstall IBM® OpenPages® with Watson™ 8.1.0.2 IF2, perform the following tasks as the user that setup the Installation server.

Task 1: Stop all OpenPages servers and services

Note: For details, see the "Starting and stopping servers" chapter in the *IBM® OpenPages® with Watson™ Administrator's Guide*.

Task 2: Manually restore the previous patch version from the backups

Manually restore the previous OpenPages patch level from the `<OPBackup8102>`, `<CCBackup8102>`, or `<OPSearchBackup8102>` directories created during the 8.1.0.2.2 interim fix installation, as applicable.

Note: Make sure to use the backup directory that reflects the previously installed OpenPages patch level. Restoring to a patch level that is not the previously installed patch level is not supported.

On Deployment Manager Server, do the following

1. Navigate to the `<OP_Home>/applications` directory.
2. Copy the following file from the `<OPBackup8102>/applications` backup directory:
 - `op-apps.ear`
 - `opappstools.ear`
3. Navigate to the `<OP_Home>/aurora/bin/compare_environments` directory
4. Delete the following file
 - `log4j-1.2.17.op.1.jar`
5. Copy the `log4j` file and the following file from the `<OPBackup8102>/aurora/bin/compare_environments` backup directory:
 - `com.ibm.openpages.env.comparsion.jar`
6. Navigate to the `<OP_Home>/aurora/ws-ext-lib` directory.
7. Copy the following file from the `<OPBackup8102>/aurora/ws-ext-lib` directory:
 - `aurora-tools.jar`
8. Navigate to the `<OP_Home>/aurora/conf` directory.
9. Copy the following file from the `<OPBackup8102>/aurora/conf` backup directory:
 - `versioninfo.txt`
10. Navigate to the `<OP_Home>/profiles/<OP-Dmgr>/config/cell/<OP-Cell>/applications/op-apps.ear/deployments/op-apps/META-INF` directory
11. Copy the following file from the `<OPBackup8102>/profiles/<OP-Dmgr>/config/cell/<OP-Cell>/applications/op-apps.ear/deployments/op-apps/META-INF` directory
 - `MANIFEST.MF`

12. Navigate to the <OP_Home>/profiles/<OP-Dmgr>/config/cell/<OP-Cell>/applications/op-apps.ear/deployments/op-apps/openpages.war/WEB-INF directory
13. Copy the following file from the <OPBackup8102>/profiles/<OP-Dmgr>/config/cell/<OP-Cell>/applications/op-apps.ear/deployments/op-apps/openpages.war/WEB-INF directory.
 - jobTileDefinitions.xml
14. Navigate to the <OP_Home>/profiles/<OP-Dmgr>/config/cell/<OP-Cell>/applications/op-apps.ear/deployments/op-apps/openpages.war/META-INF directory
15. Copy the following file from the <OPBackup8102>/profiles/<OP-Dmgr>/config/cell/<OP-Cell>/applications/op-apps.ear/deployments/op-apps/openpages.war/META-INF directory
 - MANIFEST.MF
16. Navigate to the <OP_Home>/profiles/<OP-Dmgr>/config/cell/<OP-Cell>/applications/op-apps.ear/deployments/op-apps/sosa.war/META-INF directory
17. Copy the following file from the <OPBackup8102>/profiles/<OP-Dmgr>/config/cell/<OP-Cell>/applications/op-apps.ear/deployments/op-apps/sosa.war/META-INF directory.
 - MANIFEST.MF
18. Navigate to the <OP_Home>/profiles/<OP-Dmgr>/config/cell/<OP-Cell>/applications/op-apps.ear/deployments/op-apps/publishweb.war/META-INF directory
19. Copy the following file from the <OPBackup8102>/profiles/<OP-Dmgr>/config/cell/<OP-Cell>/applications/op-apps.ear/deployments/op-apps/publishweb.war/META-INF directory.
 - MANIFEST.MF
20. Navigate to the <OP_Home>/profiles/<OP-Dmgr>/config/cell/<OP-Cell>/applications/op-apps.ear/deployments/op-apps/opstartup.war/META-INF directory
21. Copy the following file from the <OPBackup8102>/profiles/<OP-Dmgr>/config/cell/<OP-Cell>/applications/op-apps.ear/deployments/op-apps/opstartup.war/META-INF directory.
 - MANIFEST.MF
22. Navigate to the <OP_Home>/profiles/<OP-Dmgr>/config/cell/<OP-Cell>/applications/op-apps.ear/deployments/op-apps/cachesynchronizermdb.jar/META-INF directory
23. Copy the following file from the <OPBackup8102>/profiles/<OP-Dmgr>/config/cell/<OP-Cell>/applications/op-apps.ear/deployments/op-apps/cachesynchronizermdb.jar/META-INF directory.
 - MANIFEST.MF
24. Navigate to the <OP_Home>/profiles/<OP-Dmgr>/config/cell/<OP-Cell>/applications/op-apps.ear/deployments/op-apps/service-ejbs.jar/META-INF directory

25. Copy the following file from the <OPBackup8102>/profiles/<OP-Dmgr>/config/cell/<OP-Cell>/applications/op-apps.ear/deployments/op-apps/service-ejbs.jar/META-INF directory.
 - MANIFEST.MF

On each Application Server, do the following:

1. Navigate to the <OP_Home>/applications directory.
2. Copy the following files from the <OPBackup8102>/applications directory:
 - op-apps.ear
 - opappstools.ear
3. Navigate to the <OP_Home>/aurora/bin/compare_environments directory
4. Delete the following file
 - log4j-1.2.17.op.1.jar
5. Copy the log4j file and the following file from the <OPBackup8102>/aurora/bin/compare_environments backup directory:
 - com.ibm.openpages.env.comparsion.jar
6. Navigate to the <OP_Home>/aurora/ws-ext-lib directory.
7. Copy the following file from the <OPBackup8102>/aurora/ws-ext-lib directory:
 - aurora-tools.jar
8. Navigate to the <OP_Home>/aurora/conf directory.
9. Copy the following file from the <OPBackup8102>/aurora/conf directory:
 - versioninfo.txt
10. Navigate to the <OP_Home> directory.
11. Copy the following file from the <OPBackup8102> directory:
 - openpagesregistry.xml
12. Navigate to the <OP_Home>/profiles/<OP-Node>/installedApps/<OP-Cell>/op-apps.ear directory.
13. Delete the following file
 - log4j-1.2.17.op.1.jar
14. Copy the log4j file and the following files from the <OPBackup8102>/profiles/<OP-Node>/installedApps/<OP-Cell>/op-apps.ear directory:
 - aurora.jar
 - aurora-tools.jar
 - com.ibm.openpages.env.comparison.jar
 - cachesynchronizermdb.jar
 - opappsosauupdate.jar
 - opappcommon.jar
 - service-ejbs.jar
15. Navigate to the <OP_Home>/profiles/<OP-Node>/installedApps/<OP-Cell>/op-apps.ear/META-INF directory
16. Copy the following file from the <OPBackup8102>/profiles/<OP-Node>/installedApps/<OP-Cell>/op-apps.ear/META-INF directory.

- MANIFEST.MF
17. Navigate to the `<OP_Home>/profiles/<OP-Node>/installedApps/<OP-Cell>/op-apps.ear/opstartup.war/META-INF` directory
 18. Copy the following file from the `<OPBackup8102>/profiles/<OP-Node>/installedApps/<OP-Cell>/op-apps.ear/opstartup.war/META-INF` directory
 - MANIFEST.MF
 19. Navigate to the `<OP_Home>/profiles/<OP-Node>/installedApps/<OP-Cell>/op-apps.ear/publishweb.war/META-INF` directory
 20. Copy the following file from the `<OPBackup8102>/profiles/<OP-Node>/installedApps/<OP-Cell>/op-apps.ear/publishweb.war/META-INF` directory.
 - MANIFEST.MF
 21. Navigate to the `<OP_Home>/profiles/<OP-Node>/installedApps/<OP-Cell>/op-apps.ear/openpages.war/META-INF` directory
 22. Copy the following file from the `<OPBackup8102>/profiles/<OP-Node>/installedApps/<OP-Cell>/op-apps.ear/openpages.war/META-INF` directory.
 - MANIFEST.MF
 23. Navigate to the `<OP_Home>/profiles/<OP-Node>/installedApps/<OP-Cell>/op-apps.ear/openpages.war/WEB-INF` directory
 24. Copy the following file from the `<OPBackup8102>/profiles/<OP-Node>/installedApps/<OP-Cell>/op-apps.ear/openpages.war/WEB-INF` directory.
 - jobTileDefinitions.xml
 25. Navigate to the `<OP_Home>/profiles/<OP-Node>/installedApps/<OP-Cell>/op-apps.ear/openpages.war/applets` directory
 26. Delete the following file
 - log4j-1.2.17.op.1.jar
 27. Copy the log4j file and the following files from the `<OPBackup8102>/profiles/<OP-Node>/installedApps/<OP-Cell>/op-apps.ear/openpages.war/applets` directory.
 - aurora-tools.jar
 - aurora.jar
 28. Navigate to the `<OP_Home>/profiles/<OP-Node>/installedApps/<OP-Cell>/op-apps.ear/sosa.war/META-INF` directory
 29. Copy the following file from the `<OPBackup8102>/profiles/<OP-Node>/installedApps/<OP-Cell>/op-apps.ear/sosa.war/META-INF` directory.
 - MANIFEST.MF
 30. Navigate to the `<OP_Home>/profiles/<OP-Node>/installedApps/<OP-Cell>/op-apps.ear/sosa.war` directory and delete the react subdirectory.
 31. Copy the directory and its contents from the `<OPBackup8102>/profiles/<OP-Node>/installedApps/<OP-Cell>/op-apps.ear/sosa.war/react` directory.
 32. Navigate to the `<OP_Home>/profiles/<OP-Node>/config/cell/<OP-Cell>/applications/op-apps.ear/deployments/op-apps/META-INF` directory

33. Copy the following file from the <OPBackup8102>/profiles/<OP-Node>/config/cell/<OP-Cell>/applications/op-apps.ear/deployments/op-apps/META-INF directory
 - MANIFEST.MF
34. Navigate to the <OP_Home>/profiles/<OP-Node>/config/cell/<OP-Cell>/applications/op-apps.ear/deployments/op-apps/openpages.war/WEB-INF directory
35. Copy the following file from the <OPBackup8102>/profiles/<OP-Node>/config/cell/<OP-Cell>/applications/op-apps.ear/deployments/op-apps/openpages.war/WEB-INF directory.
 - jobTileDefinitions.xml
36. Navigate to the <OP_Home>/profiles/<OP-Node>/config/cell/<OP-Cell>/applications/op-apps.ear/deployments/op-apps/openpages.war/META-INF directory
37. Copy the following file from the <OPBackup8102>/profiles/<OP-Node>/config/cell/<OP-Cell>/applications/op-apps.ear/deployments/op-apps/openpages.war/META-INF directory
 - MANIFEST.MF
38. Navigate to the <OP_Home>/profiles/<OP-Node>/config/cell/<OP-Cell>/applications/op-apps.ear/deployments/op-apps/sosa.war/META-INF directory
39. Copy the following file from the <OPBackup8102>/profiles/<OP-Node>/config/cell/<OP-Cell>/applications/op-apps.ear/deployments/op-apps/sosa.war/META-INF directory.
 - MANIFEST.MF
40. Navigate to the <OP_Home>/profiles/<OP-Node>/config/cell/<OP-Cell>/applications/op-apps.ear/deployments/op-apps/publishweb.war/META-INF directory
41. Copy the following file from the <OPBackup8102>/profiles/<OP-Node>/config/cell/<OP-Cell>/applications/op-apps.ear/deployments/op-apps/publishweb.war/META-INF directory.
 - MANIFEST.MF
42. Navigate to the <OP_Home>/profiles/<OP-Node>/config/cell/<OP-Cell>/applications/op-apps.ear/deployments/op-apps/opstartup.war/META-INF directory
43. Copy the following file from the <OPBackup8102>/profiles/<OP-Node>/config/cell/<OP-Cell>/applications/op-apps.ear/deployments/op-apps/opstartup.war/META-INF directory.
 - MANIFEST.MF
44. Navigate to the <OP_Home>/profiles/<OP-Node>/config/cell/<OP-Cell>/applications/op-apps.ear/deployments/op-apps/cachesynchronizermdb.jar/META-INF directory
45. Copy the following file from the <OPBackup8102>/profiles/<OP-Node>/config/cell/<OP-Cell>/applications/op-apps.ear/deployments/op-apps/cachesynchronizermdb.jar/META-INF directory.
 - MANIFEST.MF

46. Navigate to the `<OP_Home>/profiles/<OP-Node>/config/cell/<OP-Cell>/applications/op-apps.ear/deployments/op-apps/service-ejbs.jar/META-INF` directory
47. Copy the following file from the `<OPBackup8102>/profiles/<OP-Node>/config/cell/<OP-Cell>/applications/op-apps.ear/deployments/op-apps/service-ejbs.jar/META-INF` directory.
 - MANIFEST.MF
48. Navigate to the `<OP_Home>` directory.
49. Copy the following file from the `<OPBackup8102>` directory:
 - openpagesregistry.xml

On each Reporting Server, do the following

1. Navigate to the `<CC_Home>/wlp/usr/servers/IBMOpenPagesFrameworkModelGenerator/apps/crf-refresher.war/WEB-INF/lib/` directory.
2. Delete the following file
 - log4j-1.2.17.op.1.jar
3. Copy the log4j file and the following files from the `<CCBackup8102>/wlp/usr/servers/IBMOpenPagesFrameworkModelGenerator/apps/crf-refresher.war/WEB-INF/lib/` directory.
 - aurora-tools.jar
 - reporting.jar
4. Navigate to the `<CC_Home>/temp/p2pd` directory
5. Copy the following file from the `<CCBackup8102>/temp/p2pd` directory
 - aurora-tools.jar
6. Navigate to the `<cognos_home>/webapps/p2pd/WEB-INF/lib` directory
7. Copy the following file from the `<CCBackup8102>/COGNOS/webapps/p2pd/WEB-INF/lib` directory
 - aurora-tools.jar
8. Navigate to the `<CC_Home>` directory.
9. Copy the following file from the `<CCBackup8102>` directory:
 - openpagesregistry.xml

On the Global Search Server, do the following

1. Navigate to the `<OPSearch_Home>/solr/server/lib/ext` directory.
2. Copy the following file from the `<OPSearchBackup8102>/solr/server/lib/ext` directory:
 - log4j-1.2.17.jar

3. Navigate to the <OPSearch_Home> /opsearchtools directory.
4. Copy the following file from the <OPSearchBackup8102>/opsearchtools directory:
 - opsearchtool.jar
5. Navigate to the <OPSearch_Home> directory.
6. Copy the following file from the <OPSearchBackup8102> directory:
 - openpagesregistry.xml

On the IBM BPM service, do the following (if applicable)

1. Navigate to the <OPBPMInt_Home> directory.
2. Copy the following file from the <OPBPMIntBackup8102> directory:
 - aurora-tools.jar
3. Navigate to the <BPM_Home>/lib/ext directory.
4. Copy the following file from the <OPBPMIntBackup8102> directory:
 - aurora-tools.jar

Task 3: Restore Databases

Oracle database

For details, see the “Using IBM OpenPages with Watson utilities with Oracle databases” chapter in the IBM® OpenPages® with Watson™ Administrator’s Guide.

Db2 database

For details, see the “Using IBM OpenPages with Watson utilities with Db2 databases” chapter in the IBM® OpenPages® with Watson™ Administrator’s Guide

Task 4: Start all OpenPages servers and services

Note: For details, see the “Starting and stopping servers” chapter in the IBM® OpenPages® with Watson™ Administrator’s Guide.

- When restarting the IBMOpenPagesFrameworkModelGenerator service, use the --clean option.

For example

```
./server start IBMOpenPagesFrameworkModelGenerator --clean
```

Documentation Updates

You can download the latest revision to the IBM® OpenPages® with Watson™ 8.1 documentation set from the IBM information server at:

<https://www.ibm.com/support/pages/openpages-watson-documentation-version-81>

Or you can use the IBM® OpenPages® with Watson™ 8.1 Knowledge Center at

https://www.ibm.com/support/knowledgecenter/SSFUEU_8.1.0/main/welcome.html

Notices

This information was developed for products and services offered worldwide.

This material may be available from IBM® in other languages. However, you may be required to own a copy of the product or product version in that language in order to access it.

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service. This document may describe products, services, or features that are not included in the Program or license entitlement that you have purchased.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not grant you any license to these patents. You can send license inquiries, in writing, to:

IBM Director of Licensing
IBM Corporation
North Castle Drive
Armonk, NY 10504-1785
U.S.A.

For license inquiries regarding double-byte (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

Intellectual Property Licensing
Legal and Intellectual Property Law
IBM Japan Ltd.
19-21, Nihonbashi-Hakozakicho, Chuo-ku
Tokyo 103-8510, Japan

The following paragraph does not apply to the United Kingdom or any other country where such provisions are inconsistent with local law: INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION “AS IS” WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials

at those Web sites are not part of the materials for this IBM product and use of those Web sites is at your own risk.

IBM may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

IBM Corporation
Location Code FT0
550 King Street
Littleton, MA
01460-1250
U.S.A.

Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement or any equivalent agreement between us.

Any performance data contained herein was determined in a controlled environment. Therefore, the results obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

All statements regarding IBM's future direction or intent are subject to change or withdrawal without notice, and represent goals and objectives only.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to the names and addresses used by an actual business enterprise is entirely coincidental.

If you are viewing this information softcopy, the photographs and color illustrations may not appear.

This Software Offering does not use cookies or other technologies to collect personally identifiable information.

Copyright

Licensed Materials - Property of IBM Corporation.

© Copyright IBM Corporation, 2003, 2022.

This information contains sample application programs in source language, which illustrate programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to IBM, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating platform for which the sample programs are written.

These examples have not been thoroughly tested under all conditions. IBM, therefore, cannot guarantee or imply reliability, serviceability, or function of these programs. You may copy, modify, and distribute these sample programs in any form without payment to IBM for the purposes of developing, using, marketing, or distributing application programs conforming to IBM's application programming interfaces.

IBM, the IBM logo and ibm.com are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide.

The following terms are trademarks or registered trademarks of other companies:

Adobe, the Adobe logo, PostScript, and the PostScript logo are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States, and/or other countries.

Microsoft, Windows, and the Windows logo are trademarks of Microsoft Corporation in the United States, other countries, or both.

Linux is a registered trademark of Linus Torvalds in the United States, other countries, or both.

UNIX is a registered trademark of The Open Group in the United States and other countries.

Java and all Java-based trademarks and logos are trademarks or registered trademarks of Oracle and/or its affiliates.

Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the Web at "[Copyright and trademark information](http://www.ibm.com/legal/copytrade.shtml)" at www.ibm.com/legal/copytrade.shtml.

