

Line commands that can be used in the zSecure user interface

User profile displays

A	Permits and connects
AC	Access check
C	Copy
CO	Add connect
D, DD	Delete
E	Events, SMF reports
L	Generates LISTUSER command
M	Move
MI	Manage IDs in segments
ML	Manage logon
MR	Manage CKGRACF authorization requirements
MS	Manage CKGRACF resume schedules
MT	Manage TSO information
MU	Manage user data
P	Change password and resume
PE	Add or delete permit
R, RR	Recreate
S	Show
SE	Show application segments
SR	Show relevant profiles
TR	Trust bestowed on user
X, XX	Exclude from FORALL processing
Z, ZZ	Select for FORALL processing
34	Data set list utility

Group profile displays

A	Group authorization
AC	Access check
C	Copy
CO	Add connect
D, DD	Delete
E	Events, SMF reports
L	Generates LISTGRP command
MI	Manage INSTDATA or APPLDATA
MR	Manage CKGRACF authority requirements
MU	Manage user data
P	Show profile (on segment displays)
PE	Add or delete permit
R, RR	Recreate
S	Select
SE	Show application segments
SR	Show relevant profiles
X, XX	Exclude from FORALL processing
Z, ZZ	Select for FORALL processing
34	Data set list utility

DATASET profile displays

AC	Access check
C	Copy
D, DD	Delete
E	Events, SMF reports
L	Generates LISTDSD command
LD	Generates LISTDSD DSNS command
LR	Lists data sets covered via Report
MI	Manage INSTDATA or APPLDATA
MR	CKGRACF multiple authority requirements
MU	Manage USRDATA
P	Show profile (on segment displays)
PE	Add or delete PERMIT
R, RR	Recreate
S	Select
SE	Show application segments
X, XX	Exclude from FORALL processing
Z, ZZ	Select for FORALL processing
34	Data set list utility

RESOURCE profile (GENERAL) displays

AC	Access check
C	Copy
CC	Copy to different class
D, DD	Delete
E	Events, SMF reports
K	Manage APPCLU and PTKDATA keys
L	Generates RLIST command
MI	Manage INSTDATA or APPLDATA
MR	CKGRACF multiple authority requirements
MU	Manager user data
P	Show profile (on segment displays)
PE	Add or delete permit
R, RR	Recreate
S	Select
SE	Show application segments
X, XX	Exclude from FORALL processing
Z, ZZ	Select for FORALL processing

Class settings displays

C	Copy
E	Events, SMF reports
P	Display profiles
R	Refresh
S	Show information
X, XX	Exclude
Z, ZZ	Select

USER BASE / DIGTRING CERTDATA segment

D	Delete or remove
L	List

Standard line commands

/	View available line commands
C	Copy profile or entry
D	Delete profile or entry
L	Generates a LIST command
S	Show details

ACL

C	Copy
D	Delete
I	Insert
L	List group
R	Recreate
S	Select or modify

CONNECT

C	Copy
D	Delete or remove
L	List

USR fields

C	Copy USERDATA field
D	Delete USERDATA field
I	Add USERDATA field
R	Request changes to USERDATA field
S	Set USERDATA field

CKGRACF USR fields

A	Approve queued command
C	Copy queued command or set schedule
D	Deny queued command or clear schedule
H	Hold queued command
I	Add another command and queue for approval or schedule action
R	Edit current command and queue for approval or schedule action
S	Show details

RACLINK fields

A	Approve pending association
C	Copy current RACLINK association
D	Generates RACLINK <i>id (userid)</i> undefine (<i>linked.node.user</i>) command
H	Copy or insert RACLINK association for current user

Primary (ISPF) commands that can be used in the zSecure user interface

ACCESS - Shows access for an ID on a resource.

ACL EFFECTIVE - Shows an effective access list.

ACL EXPLODE - Shows exploded access list.

ACL NORMAL, ASIS - Shows actual access list.

ACL NOSCOPE - Deactivates display of administrative authorities as part of the access list display.

ACL NOUNIVERSAL - Deactivates the UNIVERSAL option.

ACL RESOLVE - Shows resolved access list.

ACL SCOPE - Activates display of administrative authorities as part of the access list display.

ACL SORT ACCESS - Sorts access list from OWNER to NONE.

ACL SORT ID - Sorts access list by ID.

ACL SORT USER - Sorts access list by user (with resolve/explode).

ACL TRUST - Shows trust relations of the profile.

ACL UNIVERSAL - Takes system-wide operations and users with a default connection to a universal group into consideration when building the access list.

C2RIMENU - Displays the results of the authority checks for the menu options to be shown and the actions to be shown on the menus.

CANCEL - in profile displays, resets changes.

CARLA, COMM - Types CARLa commands.

CKNSERVE - Displays information about the zSecure Servers that are known to the zSecure Server address space identified by the ServerToken parameter on the CARLa OPTION command.

CKXDEBUG - Displays CKX diagnostic information.

COLS - Shows a ruler in the top of your screen.

FIELDS - Shows all fields that can be used in CARLa queries.

FIND - Performs a character string search for text in a display panel.

FORALL - Issues a command for all or selected profiles on a record-level display.

HELP - Equivalent to the PF1 key.

MESSAGES, MSG, MSGS - Shows the message library or look up a message.

MODIFY - Enables or disables the ability to change values of modifiable fields.

PRT, PRTLST - Creates a hardcopy of a display, written to the standard ISPF LIST data set.

RACF - Opens the RACF ISPF panels.

REFRESH - Resets changes in modified fields.

RESET - Removes all pending updates from display panels and cancel pending commands.

RESULTS - Shows resulting files from last query.

RFIND - Repeats the previous FIND command from the current cursor position.

SET - An alternative way to change some options on the Setup - View and Setup - Confirm display panels.

SETUP - Invokes the SETUP application.

SORT - SORT *field* [A,D] *field* [A,D]....

STARTPAN - Specifies the panel that opens when zSecure starts.

SYSPREV - Browses the SYSPRINT message file of a recursive query.

SYSPRINT - Browses the message output file of the report generated from the last query.

TEMPLATE - Shows the contents of the RACF database templates.

IBM Security zSecure Admin and Audit for RACF Line Commands and Primary Commands Summary

November 2015

This edition applies to version 2, release 2, modification 0 of IBM Security zSecure™ Admin and Audit for RACF™ (product numbers 5655-N16 and 5655-N17) and to all subsequent releases and modifications until otherwise indicated in new editions.

© Copyright IBM Corporation 2015.

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.